Guy Even¹, Moti Medina², and Boaz Patt-Shamir³

- 1 School of Electrical Engineering Tel Aviv University, Tel Aviv 6997801, Israel guy@eng.tau.ac.il 2
- **MPI** for Informatics 66123 Saarbrücken, Germany mmedina@mpi-inf.mpg.de
- 3 School of Electrical Engineering Tel Aviv University, Tel Aviv 6997801, Israel boaz@tau.ac.il

– Abstract

We consider a task of serving requests that arrive in an online fashion in Software-Defined Networks (SDNs) with network function virtualization (NFV). Each request specifies an abstract routing and processing "plan" for a flow (e.g., the flow source is at node s and it needs to reach destination node t after undergoing a few processing stages, such as firewall or encryption). Each processing function can be performed by a specified subset of servers in the system. The algorithm needs to either reject the request or admit it and return detailed routing (a.k.a. "path computation") and processing assignment ("function placement"). Each request also specifies the communication bandwidth and the processing load it requires. Components in the system (links and processors) have bounded capacity; a feasible solution may not violate the capacity constraints. Requests have benefits and the goal is to maximize the total benefit of accepted requests.

In this paper we first formalize the problem, and propose a new service model that allows us to cope with requests with unknown duration. The new service model augments the traditional accept/reject schemes with a new possible response of "stand by." Our main result is an online algorithm for path computation and function placement that guarantees, in each time step, throughput of at least $\Omega\left(\frac{\text{OPT}^*}{\log n}\right)$, where *n* is the system size and OPT^* is an upper bound on the maximal possible throughput. The guarantee holds assuming that requests ask for at most an $O(1/\log n)$ -fraction of the capacity of any component in the system. Furthermore, the guarantee holds even though our algorithm serves requests in an all-or-nothing fashion using a single path and never preempts accepted flows, while OPT* may serve fractional requests, may split the allocation over multiple paths, and may arbitrarily preempt and resume service of requests.

1 Introduction

Conventional wisdom has it that in networking, models are reinvented every twenty years or so. A deeper look into the evolution of networks shows that there is always a tension between ease of computation, which favors collecting all data and performing processing centrally, and ease of communication, which favors distributing the computation over nodes along communication paths. It seems that recently the pendulum has moved toward the centralized computation once again, with the emergence of software-defined networks (SDNs), in which the underlying abstraction is of a centrally managed network.

^{*} This work was supported in part by the Neptune Consortium, Israel.



© G. Even, M. Medina and B. Patt-Shamir; licensed under Creative Commons License CC-BY

Leibniz International Proceedings in Informatics

LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

Among the key components of SDNs are *path computation* and *function placement* [10], in which potentially complex requests need to be routed over the network. Each request specifies a "processing plan" that includes a source-destination pair as well as a description of a few processing stages that the stream needs to go through. The task is to find a route in the network from the source to the destination that includes the requested processing. The main difficulty, of course, is the bounded processing capacity of servers and links, so not all requests can be served.

Our Contributions. Path computation is often solved after function placement. Even if both tasks are solved (approximately) optimally, the quality of the composed solution may not be good. In this paper we solve these tasks together by a competitive on-line algorithm. Our contribution is both conceptual and technical. From the conceptual viewpoint, we introduce a new service model that facilitates competitive non-preemptive algorithms for requests whose duration is unknown upon arrival. In the new service model, a request which is not admitted is placed in a "standby" queue until there is room to accept it (due to other requests leaving the system). Once a request is accepted, it is guaranteed to receive service until it ends (i.e., until the user issues a "leave" signal).

Our algorithmic contribution consists of a deterministic algorithm that receives requests in an on-line fashion, and determines when each request starts receiving service (if at all), and how is this service provided (i.e., how to route the request and where to process it). Each request has a benefit per time unit it receives service, and the algorithm is guaranteed to obtain $\Omega(1/\log(nk))$ of the best possible benefit, where n is the system size and k is the maximum number of processing stages of a request.¹ More precisely, in every time step t, the benefit collected by the algorithm is at least an $\Omega(1/\log(nk))$ -fraction of the largest possible total benefit that can be obtained at time t, i.e., from from all requests that are active at time t while respecting the capacity constraints. The competitive ratio of the algorithm holds under the conditions that no processing stage of a request requires more than an $O(1/(k \log(nk)))$ fraction of the capacity of any component (node or link) in the system, and assuming that the ratio of the highest-to-lowest benefits of requests is bounded by a polynomial in n. (We provide precise statements below.) We also prove a lower bound on the competitive ratio of $\Omega(\log n)$ for every online algorithm in our new model. Hence, for $k \in n^{O(1)}$, our algorithm is asymptotically optimal.

1.1 Previous Work

SDN Abstractions via High Level SDN Programming Languages. Merlin [13, 12] is an SDN language for provisioning network resources. In Merlin, requests are specified as a regular expression with additional annotation. The system works in an off-line fashion: given a set of requests and the system description, an integer linear program (ILP) is generated. Then an external ILP solver is used to decide which requests are accepted and how are they routed. Strictly speaking, due to the use of an ILP solver, this solution is not polynomial time. For more information on SDN languages (and SDN in general) we refer the reader to [10].

Online Routing Algorithms. Our work leverages the seminal algorithm of Awerbuch et. al [2], which is an on-line algorithm for routing requests with given benefits and known durations. The algorithm of [2] decides whether to admit or reject each request when it

¹ Typically, k is constant because the number of processing stages does not grow as a function of the size n of the network.

arrives; the algorithm also computes routes for the admitted requests. The goal of the algorithm in [2] is to maximize the sum of benefits of accepted requests. The benefit-maximization algorithm of [2] resembles the cost-minimization algorithm presented in [1] for a different model: in [1], all requests must be accepted, and the goal is to minimize the maximal ratio, over all links, between the total link load and link capacity (the load of a link is the total bandwidth of all requests routed through it).

Buchbinder and Naor [4, 5] analyze the algorithm of [2] using the primal-dual method. This allows them to bound the benefit of the computed solution as a function of the benefit of an optimal fractional solution (see also [9]).

As mentioned, the above algorithms assume that each request specifies the duration of the service it needs when it arrives. The only on-line algorithm for unknown durations we know of in this context is for the problem of minimizing the maximal load [3]. The algorithm in [3] is $O(\log n)$ -competitive, but it requires rerouting of admitted requests (each request may be rerouted $O(\log n)$ times). Our algorithm, which is for benefit maximization, deals with unknown durations without rerouting by allowing the "standby" mode.

1.2 Advocacy of the Service Model

In the classical non-preemptive model with guaranteed bandwidth, requests must specify in advance what is the exact duration of the connection (which may be infinite), and the system must give an immediate response, which may be either "reject" or "admit." While immediate responses are preferable in general, the requirement that duration is specified in advance is unrealistic in many cases (say, because the length of the connection may depend on yet-unavailable inputs). However, requests with unknown durations seem to thwart the possibility for a competitive algorithm due to the following reasoning. Consider any system, and suppose that there are infinitely many requests available at time 0, all with unit benefit per time step. Clearly there exists a request, say r^* , that is rejected due to the finite capacity of the system. Now, the following adversarial scenario may unfold: all admitted requests leave the system at time 1, and request r^* persists forever. Clearly, this means that no deterministic algorithm can guarantee a non-trivial competitive ratio in the worst case.

We therefore argue that if unknown durations are to be tolerated, then the requirement for an immediate reject/admit response must be relaxed. One relaxation is to allow preemption, but with preemption the connection is never certain until it terminates. Our service model suggests to commit upon accept, but not to commit to rejection. This type of service is quite common in many daily activities (e.g., waiting in line for a restaurant seat), and is actually implicitly present in some admit/reject situations: in many cases, if a request is rejected, the user will try to re-submit it. Moreover, from a more philosophical point of view, the "standby" service model seems fair for unknown durations: on one hand, a request does not commit ahead of time to when it will leave the system, and on the other hand, the algorithm does not commit ahead of time to when the request will *enter* the system.

2 Request Model and Service Model

In this section we formalize the problem of path computation and function mapping in SDNs. The main new concept in the way the input is specified is called PR-graphs. The nodes of a PR-graph represent servers and the edges represent communication paths, so that

a PR-graph is an abstract representation of a request.² The main novelty of our output model is in allowing the system to put arriving requests in a "standby" mode instead of immediately rejecting them. Details are provided in the remainder of this section.

2.1 The Physical Network

The network is a fixed network of servers and communication links. The network is represented by a graph N = (V, E), where V is the set of *nodes* and E is the set of *edges*. Nodes and edges have *capacities*. The capacity of an edge e is denoted by c_e , and the capacity of a node $v \in V$ is denoted by c_v . All capacities are positive integers. We note that the network is static and undirected (namely each edge represents a bidirectional communication link), but may contain parallel edges.

2.2 Request Model and the Concept of PR-Graphs

Each request is a tuple $r_j = (G_j, d_j, b_j, U_j)$ with the following interpretation.

- $G_j = (X_j, Y_j)$ is a directed graph called the PR-graph, where X_j is the set of PR-vertices, and Y_j is the set of PR-edges. We elaborate on the PR-graph below.
- $d_j : X_j \cup Y_j \to \mathbb{N}$ is the *demand* of the request from each PR-graph component (i.e., bandwidth for links, processing for nodes).
- $b_j \in \mathbb{N}$ is the *benefit* paid by the request for each time step it is served.
- $U_j: X_j \cup Y_j \to 2^V \cup 2^E$ maps each node in the PR-graph to a set of nodes of N, and each edge in the PR-graph is mapped to a set of edges of N. We elaborate below.

The Processing and Routing Graph (PR-graph). We refer to edges and vertices in G_j as PR-edges and PR-vertices, respectively. There are three types of vertices in the PR-graph G_j :

- A single source vertex $s_j \in X_j$ (i.e., vertex with in-degree zero) that represents the location from which the packets arrive.
- A single sink vertex $t_j \in X_j$ (i.e., vertex with out-degree zero) that represents the location to which the packets are destined.
- Action vertices, which represent transformations to be applied to the flow (such as encryption/decryption, deep packet inspection, trans-coding etc.)

Realization of PR-**paths and the** U function. The semantics of a PR-graph is that the request can be served by any source-sink path in the PR-graph. However, these paths are abstract. To interpret them in the network, we map PR-nodes to physical network nodes and PR-edges to physical network paths. To facilitate this mapping, each request r_j also includes the U_j function, which, intuitively, says which physical nodes (in V) can implement each PR-node, and which physical links (in E) can implement each PR-edge. Formally, we define the following concepts.

▶ Definition 1 (valid realization of PR-edge). A simple path $p = (v_0, \ldots, v_k)$ in the network N is a valid realization of a PR-edge e if for all $0 < i \le k$ we have that $(v_{i-1}, v_i) \in U_j(e)$.

Note that the empty path in N is a valid realization of any PR-edge.

▶ Definition 2 (valid realizations of PR-path). A path $p = (v_0, \ldots, v_k)$ in N is a valid realization of a path $\tilde{p} = (x_0, \ldots, x_\ell)$ in G_j under segmentation $f : \{0, \ldots, \ell\} \rightarrow \{0, \ldots, k\}$ if

² Our PR-graphs are similar to Merlin's regular expressions [13], but are more expressive and, in our humble opinion, are more natural to design.

for all $0 \le i \le \ell$, $v_{f(i)} \in U_j(x_i)$, and for all $0 < i \le \ell$, the sub-path $(v_{f(i-1)}, \ldots, v_{f(i)})$ of p is a valid realization of (x_{j-1}, x_j) .

The interpretation of mapping a PR-node x to a network node v is that the service represented by x is implemented by v. $U_j(x)$ in this case represents all physical nodes in which that service can be performed. Given a PR-edge e, $U_j(e)$ is the set of links that may be used to realize e. By default, $U_j(e) = E$, but $U_j(e)$ allows the request designer to specify a set of edges to be avoided due to any consideration (e.g., security). Regarding processing, consider the segmentation of the path in N induced by a valid realization. The endpoint of each subpath is a network node in which the corresponding action takes place. Moreover, the same network node may be used for serving multiple actions for the same request.

We are now ready to define the set of valid routings and processing for request r_i .

▶ **Definition 3** (valid realizations of request). A path p in N is a valid realization of a request r_j if there exists a simple path \tilde{p} in the PR-graph G_j from s_j to t_j such that p is a realization of \tilde{p} .

Examples. Let us illustrate the utility of PR-graphs with a few examples.

Simple Routing. A request r_j to route a connection from node v to node v' is modeled by a single-edge PR-graph $s \xrightarrow{e} t$ with mappings $U_j(s) = \{v\}, U_j(t) = \{v'\}$, and $U_j(e) = E$. The demand from e is the requested connection bandwidth.

Serial Processing. A stream that needs to pass k transformations a_1, \ldots, a_k in series is modeled by a path of k + 1 edges $s_j \to a_1 \to \cdots \to a_k \to t_j$, where $U_j(a_i)$ is the set of network nodes that can perform transformation a_i , for $i = 1, \ldots, k$. Note that we can model bandwidth changes (e.g., if one of the transformations is compression) by setting different demands to different PR-edges.

Regular Expressions. Given any regular expression of processing we can construct a PR-graph by constructing the NFA corresponding to the given expression [8].

We note that our request model is more expressive than the regular-expression model proposed by Merlin [13]. For example, we can model changing loads.³

Capacity constraints and feasible realizations. Let $\tilde{p} = (s_j \stackrel{e_1}{\rightarrow} a_1, \ldots, a_k \stackrel{e_{k+1}}{\rightarrow} t_j)$ denote a path in the PR-graph G_j . Let $p = p_1 \circ \cdots \circ p_{k+1}$ denote a valid realization of \tilde{p} , where p_i is a valid realization of e_i . Let v_i denote the endpoint of subpath p_i for $1 \le i \le k$ (v_i is where action a_i takes place). The load incurred by serving request r_j with demand d_j by p on each node and edge in p is defined as follows (the load incurred on edges and nodes not in p is zero):

$$load(v,p) \triangleq \sum_{i:v=v_i} \frac{d_j(a_i)}{c_v} \text{ for all } v \in \{v_1, \dots, v_k\}$$
$$load(e,p) \triangleq \sum_{i:e \in p_i} \frac{d_j(e_i)}{c_e} \text{ for all } e \in p .$$

Informally, load(v, p) is the relative capacity of v consumed by p, and similarly load(v, e).

³ In Merlin, the input may also contain a "policing" function of capping the maximal bandwidth of a connection. We focus on resource allocation only. Policing may be enforced by an orthogonal entity.

▶ Definition 4 (capacity constraints). Given a sequence of requests $\{r_j\}_{j \in I}$, a sequence of realizations $\{p^j\}_{j \in I}$ satisfies the capacity constraints if

$$\begin{aligned} \forall v \in V : \ \sum_{j \in I} load(v, p^j) &\leq 1 \\ \forall e \in E : \ \sum_{j \in I} load(e, p^j) &\leq 1 \end{aligned}$$

Given loads for nodes and edges, we say that a path p from s_j to t_j is a *feasible realization* of request r_j if p is a valid realization of an *s*-*t* path of r, and if p satisfies the capacity constraints.

2.3 The Acc/Stdby Service Model

We now describe the service model, i.e., the user-system interface and guarantees.

Input. The input to the algorithm is the fixed network N = (V, E) and a sequence of events $\sigma = {\sigma_t}_{t \in \mathbb{N}}$ which arrive one at a time. An event is either an arrival of a new request, or the departure of a request that arrived earlier. The attributes of an arriving request r_j are as described in Sec. 2.2, along with the *arrival time* of the request $\alpha_j \in \mathbb{N}$. We use s_j and t_j to denote the source and the destination of the j^{th} request. A departure event specifies which request is departing and the current time.

Output. The algorithm must generate a response to each arrival event, and may generate any number of responses after a departure event. There are two types of responses.

• Accept: A request that has already arrived is accepted to the system; the response also includes a feasible realization of the request. The request will be served continuously from the time it is accepted until its departure event (i.e., no preemption). An "accept" response may follow any event; moreover, multiple accepts (of multiple requests) are possible after a single event (typically after a departure).

• *Standby:* In this case an arriving request is not accepted immediately, but may be accepted later. When a request arrives, the system must respond immediately by either accept or standby.

Performance Measure. We evaluate algorithms by their competitive ratio [11]. Formally, given an algorithm ALG and a finite input sequence σ , let $ALG(\sigma)$ denote the total benefit ALG receives on input σ , where the system receives the benefit b_j of request r_j for each time unit in which r_j is served. The competitive ratio of an online algorithm ALG for σ is $\rho(ALG(\sigma)) \triangleq ALG(\sigma)/OPT(\sigma)$, where $OPT(\sigma)$ denotes the maximal possible benefit from σ by any allocation that respects the capacity constraints. The competitive ratio of ALG is $\rho(ALG) \triangleq \inf_{\sigma} \rho(ALG(\sigma))$.

3 Computation of Light Valid Realizations

The algorithm presented in Section 4 uses an "oracle" (subroutine) that finds a feasible realization of requests. In this section we explain how to implement this oracle.

3.1 Construction of Product Network and Product Request

Input. We are given a weighted (physical) network N = (V, E, w) with weights $w : V \cup E \rightarrow \mathbb{R}^{\geq 0}$ over nodes and edges, and a request $r_j = (G_j, d_j, b_j, U_j)$, where $G_j = (X_j, Y_j)$ is the PR-graph with PR-nodes X_j and PR-edges Y_j (cf. Section 2.2). We are also given, for every

PR-node x and PR-edge e, the set of allowed nodes $U_j(x) \subseteq V$ and edges $U_j(e) \subseteq E$, respectively.

Output: The product network. We construct the *product network*, denoted $pn(N, r_j)$, which is a weighted directed graph, with weights over nodes only. The nodes of $pn(N, r_j)$, denoted V', are $V' = V \times Y_j$. The edges of $pn(N, r_j)$, denoted $E' = E_1 \cup E_2$, are of two categories, E_1 and E_2 , defined as follows (we use w to denote the weight function in the product network too).

- $E_1 = \{((v, y), (v', y)) \mid y \in Y_j, (v, v') \in U_j(y)\}$ (routing edges). The weight of a routing edge is defined by $w((v, y), (v', y)) \triangleq w(v, v')$, i.e., the weight of the corresponding edge in N.
- $E_2 = \left\{ \left((v, y), (v, y') \right) \mid y, y' \in Y_j \text{ s.t. } y, y' \text{ share a node } x \text{ and } v \in U_j(x) \right\} (processing edges).$

The weight of a processing edge is defined by w((v, y), (v, y')) = w(v), i.e., the weight of the corresponding node in N.

Output: The product request. The product request $pr(N, r_j)$ is a pair of sets (S_j, T_j) , called the *source* and *sink* sets, respectively. The source set S_j is the set of all (v, e) pairs such that $v \in U(s_j)$ (i.e., v is a physical node that can be a source of the request r_j) and e is incident to v in G_j (i.e., e is a PR-edge that can be the first edge in a source-sink path in the PR-graph). Similarly, the sink set T_j is defined by $T_j \triangleq \{(v, e) \mid v \in U(t_j), e \text{ is incident to } t_j \text{ in } G_j\}.$

Recall that a realization of a request is a path in N. Given a realization and weights w over nodes and edges of N, we define the weight of a realization p of r_j is defined to be $w(p) \triangleq \sum_{x \in p} d_j \cdot m_p(x)$, where $m_p(x)$ denotes the number of times node or edge x appears in p. The weight of a path q in $p(N, r_j)$ is simply the sum of the edge weights in q.

The following lemma states the main property of the construction of pn(N, r). The proof contains definitions of the functions *fold* and *expand* that convert between paths in N and $pr(N, r_j)$.

▶ Lemma 5. Let N = (V, E, w) be a physical weighted network and let r_j be a request. There is a one-to-one weight preserving correspondence between valid realizations of r_j in N and simple paths in $pn(N, r_j)$ that start in a vertex of S_j and end in a vertex of T_j .

Proof sketch: Define a function fold to map a path p'_j in the product graph to a realization $p = fold(p'_j)$ by the following local transformation: a processing edge ((v, y), (v, y')) is contracted to the node $v \in V$; each routing edge ((v, e), (v', e)) of p'_j is replaced by the edge $(v, v') \in E$. Clearly, p_j is a valid realization of r_j under the segmentation that segments p_j at the nodes representing both ends of a contracted processing edge.

Conversely, assume that a valid realization is given, where $p_j = (v_0, \ldots, v_k)$ is the path with segmentation $p_j = p_j^1 \circ p_j^2 \circ \cdots \circ p_j^\ell$. We define $p'_j = expand(p_j)$ as follows. By assumption, each subpath p_j^i is a valid realization of some PR-edge $e_j^i = (x_{i-1}, x_i)$, and such that the endpoint of subpath p_j^i is in $U_j(x_i)$. To obtain $p'_j = expand(p_j)$, apply the following mapping. Map each edge (v, v'), say in the i^{th} subpath of p_j , to the routing edge $((v, e_j^i), (v', e_j^i)) \in E'$, and map each endpoint v of subpath $i < \ell$ to the processing edge $((v, e_j^i), (v, e_j^{i+1})) \in E'$. Clearly, p'_j is a path in N', and it connects a node in S_j with a node in T_j because p'_j starts with a node (s'_j, e) for some $s'_j \in U_j(s_j), e \in Y_j$ and ends with a node (t'_i, e') for some $t'_i \in U_j(t_j), e' \in Y_j$.

It is straightforward to verify that *fold* and *expand* preserve weights. We note that an edge or a node of N might be mapped to at most k times by *fold*, where k is the length of the longest simple s-t path in the PR-graph G_j .

3.2 The Oracle

We refer to the algorithm which computes the realization as an *oracle*. The oracle's description is as follows.

We are given a request $r_j = (G_j, d_j, b_j, U_j)$ and a weighted physical network N. We then apply the following procedure to find a valid realization of r_j in N.

- 1. $N' \leftarrow \operatorname{pn}(N, r_j)$.
- 2. Let P_j denote the set of simple paths in N' that (1) start in a node in $\{(v, e) \mid v \in U_j(s_j)\}$, (2) end in a node in $\{(v, e) \mid v \in U_j(t_j)\}$, and (3) have weight at most b_j .
- **3.** Let $\Gamma_j \leftarrow \{fold(p') \mid p' \in P_j\}.$
- **4.** Return an arbitrary path $p_j \in \Gamma_j$, or "FAIL" if $\Gamma_j = \emptyset$.

Step 2 can be implemented by any shortest-paths algorithm, e.g., Dijkstra's. Note that the oracle ignores the demand d_j (and thus does not verify that the returned path p_j satisfies the capacity constraints; feasibility will follow from the weight assignment and the assumption on the maximal demand).

4 The Algorithm

In this section we first describe our algorithm in Section 4.1, then analyze it in Section 4.2, and finally present a lower bound to the problem in Section 4.2.2.

To solve the problem described in Section 2.3, we employ the resource allocation algorithm of [7, 6] (which extends [2, 4]). The general idea is as follows. We assign weights to nodes and edges according to their current load. For each incoming request, a realization in the network is found as described in Sec. 3.2, and submitted to the resource allocation algorithm. If that algorithm decides to accept the request, our algorithm algorithm accepts; otherwise the request is put in the standby mode, and it will be tried again when any accepted request leaves.

We assume for now that (1) the allocations of resources to requests are simple paths, and that (2) the demand function is defined only over edges and that all demands in a given request are equal. We lift these restrictions in Sec. 4.2.1.

Terminology. Let k denote an upper bound on the length of a longest simple path in the PR-graphs. Let p_{max} denote an upper bound on the length of valid realizations (clearly, $p_{\text{max}} < |V|k$). Let b_{max} denote an upper bound on the benefit per time unit offered by any request. Define

$$\Phi \triangleq \log(3p_{\max}b_{\max}+1) \tag{1}$$

Note that $\Phi = O(\log n + \log b_{\max} + \log k)$.

A feasible path p for request r_j is a path which is a valid realization of r_j with minimum edge capacity at least $d_j \cdot (3k\Phi)$. We denote the set of feasible paths for request r_j by Γ_j .

We say that a request r is *active* at time t is t has arrived before time t and has not departed by time t. Given time t in the run of the algorithm and an edge e of N, f(e) denotes the sum of demands of accepted active requests that are routed over e. Recall that the *load* of an edge e is defined by $load(e) \triangleq \frac{f(e)}{c_e}$. The *exp-load* of e is defined by

$$x_e \triangleq \frac{1}{p_{\max}} \cdot \left(2^{load(e) \cdot \Phi} - 1\right). \tag{2}$$

Algorithm 1 ALG - an online algorithm for the SDN problem.

State: *L*: a set, contains all unserved active requests (in standby mode) = A: a set, contains all served active requests. Each request $r_i \in A$ is routed over a path p_i . Actions: Upon arrival of request r_k : 1: Begin $\operatorname{ROUTE}(r_k)$ if $r_k \notin A$ then \triangleright request not accepted now $L \leftarrow L \cup \{r_k\}$; output " r_k : standby" end if 6: End Upon departure of request r_k : 7: Begin $UNROUTE(r_k)$ for all $r_j \in L$ do ROUTE (r_j) . \triangleright all orders allowed 10: **End** 11: procedure $ROUTE(r_i)$ Invoke ALLOCATE (r_i) if ALLOCATE returned a path $p_j \neq \perp$ then $A \leftarrow A \cup \{r_j\}; L \leftarrow L \setminus \{r_j\}$ output " r_j accepted, path p_j " end if 17: end procedure 18: procedure $UNROUTE(r_k)$ if $r_k \in A$ then $A \leftarrow A \setminus \{r_k\}$ for all $e \in p_k$ do let m(e) be the multiplicity of e in p_k $f(e) \leftarrow f(e) - m(e) \cdot d_k$ \triangleright Free the path p_k end for else $L \leftarrow L \setminus \{r_k\}$ end if 28: end procedure 29: procedure ALLOCATE (r_k) where $r_k = (G_k, d_k, b_k)$ $\triangleright x_e$ defined in Eq. 2 Assign to each edge e in N weight x_e Let C_k be a subset of Γ_k whose weight is at most b_k Pick an arbitrary path $p_k \in C_k$ \triangleright Invocation of the oracle. See Sec. 3.2 for all $e \in p_k$ do let m(e) be the multiplicity of e in p_k $f(e) \leftarrow f(e) + m(e) \cdot d_k$ \triangleright update loads end for **return** $p \in C_k$, or \perp if $C_k = \emptyset$

38: end procedure

2:

3:

4: 5:

8: 9:

12:

13:

14:

15:

16:

19:

20:

21:

22:

23:

24:

25:

26:

27:

30:

31:

32:

33:

34:35:

36:

37:

4.1 Algorithm Operation

Pseudo-code for the algorithm, called ALG, is provided in Algorithm 1. The algorithm maintains a set L of the requests in standby mode: these are all active requests currently not served. The set A contains all active requests currently served. The path allocated for an active request r_j is denoted by p_j . When a request arrives, the algorithm tries to route it by calling ROUTE. If it fails, r_i is inserted into L (line 4). A departure of an active request is handled by invoking the UNROUTE procedure (line 8), and then the algorithm tries to serve every request in L by invoking ROUTE (line 9). Any order can be used to try the standby requests, thus allowing for using arbitrary dynamic priority policies. The ROUTE procedure calls ALLOCATE, which is an online procedure for a generalization of the pathpacking problem (see below). If ALLOCATE allocates a path p_j in N, then r_j is accepted. Otherwise r_i is inserted to the standby list L. Procedure ALLOCATE first searches for a path in N which is a realization of the request. The weight of a path is defined as the sum of the exp-loads of the edges along it. If a path whose weight is less than the benefit b_i is found, then the request is allocated. The task of finding such a path is done via the oracle described in Section 3. The UNROUTE procedure removes a request from A or L; if the request was receiving service, the load of its edges is adjusted (line 23).

4.2 Analysis

We compare the performance of ALG with an offline fractional optimal solution, denoted by OPT_f . More precisely, we compare the benefit produced by ALG with the benefit and load of *any* allocation that respects the capacity constraints. Such allocations may serve a request partially and obtain the prorated benefit, and may also split the flow of one request over multiple paths. Among these allocations, OPT_f denotes the allocation that achieves the maximal benefit. Moreover, in each time step, OPT_f induces a new multicommodity flow (independent of the flow of OPT_f at any other time step). Implicitly, this means that OPT_f may also arbitrarily preempt and resume requests, partially or wholly.

Given time step t, let $benefit_t(ALG)$ denote the benefit to ALG due to step t, and analogously, let $benefit_t(OPT_f)$ denote the benefit gained by OPT_f in time step t. The competitiveness of ALG is stated in the following theorem.

▶ **Theorem 6.** Let z range over nodes and edges of N. If $\max_j d_j \leq \min_z c_z/(3k\Phi)$ for each request r_j , then $benefit_t(ALG) \geq \frac{1}{3\Phi} \cdot benefit_t(OPT_f)$ in each time step t.

The proof of Theorem 6 is based on an analysis of Procedure RA-PERSIST in each time step (which is analogous to an analysis with respect to persistent requests). This analysis appears in Sec. 4.2.1. The proof of Theorem 6 appears in Sec. 4.2.2.

4.2.1 Online Resource Allocation with Persistent Requests

We now present another key ingredient in our solution, namely the *online resource allocation* problem with respect to persistent requests (and the classical accept/reject service model). The algorithm to solve it is a generalization of [2].

By online resource allocation we mean the following setting. Consider a set E of m resources, where each resource $e \in E$ has a capacity c_e . Requests $\{r_j\}_j$ arrive in an online fashion. Each request r_j specifies a set of possible allocations denoted $\Gamma_j \subseteq 2^E$. Let p_{\max} be an upper bound on the number of resources in every feasible allocation. i.e., $|p| \leq p_{\max}$ for all $p \in \bigcup_j \Gamma_j$. We allow a general setting in which the demand requirement depends on the request, the allocation, and the resource. Formally, the demand of the *j*th request with

respect to allocation p is a function $d_{j,p} : p \to \mathbb{N}$. Each request r_j has a benefit b_j that it pays if served. Let b_{\max} denote an upper bound on $\max_j b_j$, and $\Phi \triangleq \log(1 + 3p_{\max}b_{\max})$. Small demands mean that $d_{j,p}(e)/c_e \leq 1/(3\Phi)$ for every $e \in p$.

Resource allocation generalizes allocations in circuit switching networks and SDNs:

- In the virtual circuits problem, Γ_j is simply the set of feasible paths from the source to the destination.
- For an SDN request $r_j = (G_j, d_j, b_j, U_j)$, the set of allocations Γ_j is simply the set of valid realizations, each of which is a subset of network edges and nodes. Since a realization p may contain cycle, resources may be used more than once by p. Therefore, the load on a resource $e \in p$ incurred by a realization p of request r_j is $d_j \cdot m_p(e)$, where $m_p(e)$ denotes the number of times e appears in p.

In the general resource allocation problem, Γ_j does not need to have any particular structure, but an algorithm to solve it must have an *oracle*. The task of the oracle is as follows. Assume that every resource e has a *weight* x_e . The weight of an allocation $p \subseteq E$ is simply $x_p \triangleq \sum_{e \in p} x_e$. Given a request r_j with benefit b_j , the oracle returns either an allocation $p \in \Gamma_j$ such that $x_p < b_j$, or returns "FAIL" if no such allocation exists.

The online algorithm RA-PERSIST for the resource allocation problem with persistent requests uses a modified variant of Procedure ALLOCATE for each request. The modifications of ALLOCATE are as follows. First, the term "path" is interpreted as a feasible allocation. Second, lines 31-32 are replaced by an invocation of the oracle. If a feasible allocation of weight at most b_i is found, then the flow is updated accordingly (as in Line 35).

An online resource allocation algorithm for persistent requests appears in [7, 6] (this algorithm is extends the path packing algorithm for persistent requests of [2] using the analysis in [4]). Since Algorithm RA-PERSIST is a special case of this extension, we obtain the following theorem.

▶ **Theorem 7** ([7, 6] based on [2, 4]). Let N be a given network and let $\sigma = \{r_j\}$ be a sequence of persistent requests. If $d_{j,p}(e) \leq c_e/(3 \cdot \Phi)$, for every request r_j , every allocation $p \in \Gamma_j$, and every resource e, then RA-PERSIST(σ) $\geq \operatorname{OPT}^f(\sigma)/(3 \cdot \Phi)$.

Application to SDN requests. The oracle for finding light-weight feasible realizations for SDN requests finds a lightest path in the weighted product network (see Sec. 3.2). Folding such a path may result in a realization with cycles in the SDN network. Multiple occurrences of an edge or node z in a realization p means that the load on z is multiplied by the number $m_p(z)$ of occurrences of z in p. Hence the demand from $z \in E \cup V$ induced by a realization p for request r_j satisfies $d_{j,p}(z) = d_j \cdot m_p(z)$. Let k denote an upper bound on the number of processing stages in realizations (i.e., k equals the length of a longest simple source-sink path in the PR-graphs). Then $m_p(z) \leq k$. Since Procedure ALLOCATE considers unfolded paths for its decisions, the requirement that $\max_j d_j \leq \min_z c_z/(3k\Phi)$ allows us to apply Theorem 7 to procedure ALLOCATE in the context of SDN persistent requests.

Regarding persistence, observe that the benefit in a single time step where each request pays b_j per served time step is identical to the benefit with respect to persistent requests (where each request pays b_j if served).

4.2.2 Proof of Theorem 6

Proof of Theorem 6. The proof proceeds by a simulation argument. Specifically, we interpret the execution of ALG as a repeated execution of the ALLOCATE algorithm in each time step with respect to the active requests. For the purpose of the simulation, assume that in

the ALLOCATE algorithm, each request r_k may be accompanied by a preferred feasible path p'_k . If the weight of p'_k is less than b_k (i.e., $p'_k \in C_k$), then the ALLOCATE algorithm allocates the preferred path p'_k to r_k .

We prove the theorem by induction on t. The base case t = 1 follows from Theorem 7. For the induction step, let A_t and L_t denote the sets A (served requests) and L (pending requests) at time t, respectively. The event σ_{t+1} that occurs in step t+1 is either an arrival of a new request or the departure of an active request.

Suppose first that σ_t is an arrival of a new request r_k . In this case, we simulate the ALLOCATE algorithm by feeding it first with the requests in A_t according to the order in which they were served (this order may be different than the order in which they arrived). Each request $r_j \in A_t$ is accompanied by a preferred path p'_j , where p'_j is the path that was allocated to r_j in time step t. The flow along each edge when a request is introduced to the ALLOCATE algorithm is not greater than the flow along the edge just before ALG first served the same request. Hence, the weight of p'_j during this simulation of step t + 1 does not exceed its weight when it was first allocated to r_j , and hence $p'_j \in C_j$ also in time step t + 1. This implies that the ALLOCATE algorithm accepts all the requests in A_t and routes each one along the same path allocated to it in the previous time step. Next we feed r_k to the ALLOCATE algorithm (without a preferred path). The result of this simulation is identical to the execution of ALG in time step t + 1. By Theorem 7, the theorem holds for step t + 1 in this case.

We now consider the case that σ_t is a departure of an active request r_k . In this case we may simulate the ALLOCATE algorithm by feeding it first with the served requests in $A_t \setminus \{r_k\}$ according to the order in which they were served, each request accompanied with its preferred path. Again, all these requests will be served by their preferred paths. After that, the pending requests in L_t are input to the ALLOCATE algorithm in the same order that they are processed by ALG in step t + 1; each pending request that is served by ALG in step t + 1 is accompanied by a preferred path that equals the path that is allocated to it by ALG. As the states of ALG and the simulated ALLOCATE algorithm are identical, the ALLOCATE algorithm accepts the same pending requests and serves them along their preferred paths. By Theorem 7, the theorem holds for step t + 1 in this case as well.

Note that the proof easily extends to the case that multiple events occur in each time step.

5 Lower Bound

In this section we state a lower bound which implies that the competitive ratio of ALG is asymptotically optimal, up to an additive $O(\log k)$, where k is the maximal length of a source-sink path in any PR-graph. We note that with current technology, k is typically a small constant.

▶ Theorem 8. Every online algorithm in the Acc/Stdby service model is $\Omega(\log(n \cdot b_{\max}))$ competitive.

The idea of the proof is to reduce the bad scenarios for the persistent request model [2] to bad scenarios in the Acc/Stdby model. To do that, consider requests arriving one per time unit, followed by some T time units in which no event occurs, after which all the requests leave. Observe that since all requests leave together, there is no advantage in placing a request at standby: we might as well reject it immediately. Hence, the $\Omega(\log n)$ lower bound of [2, Lemma 4.1] applies in this case. Using similar techniques as in [2] it can be showed that every online algorithm is also $\Omega(\log b_{\max})$ competitive.

— References

- 1 J. Aspnes, Y. Azar, A. Fiat, S. Plotkin, and O. Waarts. On-line routing of virtual circuits with applications to load balancing and machine scheduling. J. ACM), 44(3):486–504, 1997.
- 2 B. Awerbuch, Y. Azar, and S. Plotkin. Throughput-competitive on-line routing. In Proc. 34th IEEE Annual Symp. on Foundations of Computer Science, pages 32–40, 1993.
- 3 B. Awerbuch, Y. Azar, S. Plotkin, and O. Waarts. Competitive routing of virtual circuits with unknown duration. J. Computer and System Sciences, 62(3):385–397, 2001.
- 4 N. Buchbinder and J. S. Naor. Improved bounds for online routing and packing via a primaldual approach. 47th Ann. IEEE Symp. on Foundations of Computer Science, 0:293–304, 2006.
- 5 N. Buchbinder and J. S. Naor. Online primal-dual algorithms for covering and packing. Math. Oper. Res., 34(2):270–286, 2009.
- 6 G. Even and M. Medina. Online multi-commodity flow with high demands. In Proc. 10th Int. Workshop on Approximation and Online Algorithms (WAOA), pages 16–29, 2012.
- 7 G. Even, M. Medina, G. Schaffrath, and S. Schmid. Competitive and deterministic embeddings of virtual networks. *Theoretical Computer Science*, 496(0):184 – 194, 2013. Distributed Computing and Networking (ICDCN 2012).
- 8 J. E. Hopcroft, R. Motwani, and J. D. Ullman. *Introduction to Automata Theory, Lan*guages, and Computation). Pearson, Boston, MA, USA, 3rd edition, 2006.
- **9** J. M. Kleinberg. Approximation algorithms for disjoint paths problems. PhD thesis, Massachusetts Institute of Technology, 1996.
- 10 D. Kreutz, F. Ramos, P. Esteves Verissimo, C. Esteve Rothenberg, S. Azodolmolky, and S. Uhlig. Software-defined networking: A comprehensive survey. *Proceedings of the IEEE*, 103(1):14–76, Jan 2015.
- 11 D. D. Sleator and R. E. Tarjan. Amortized efficiency of list update and paging rules. Commun. ACM, 28(2):202–208, 1985.
- 12 R. Soulé, S. Basu, R. Kleinberg, E. G. Sirer, and N. Foster. Managing the network with merlin. In Proc. 12th ACM Workshop on Hot Topics in Networks, page 24. ACM, 2013.
- 13 R. Soulé, S. Basu, P. J. Marandi, F. Pedone, R. Kleinberg, E. G. Sirer, and N. Foster. Merlin: A language for provisioning network resources. In Proc. 10th ACM Int. Conf. on emerging Networking Experiments and Technologies, pages 213–226. ACM, 2014.