# Fixpoint Semantics and Optimization of Recursive Datalog Programs with Aggregates

Carlo Zaniolo<sup>1</sup>, Mohan Yang<sup>1</sup>, Matteo Interlandi<sup>2</sup>\*, Ariyam Das<sup>1</sup>, Alex Shkapsky<sup>1</sup>, Tyson Condie<sup>1</sup>

<sup>1</sup>University of California, Los Angeles (e-mail: {zaniolo,yang,ariyam,shkapsky,tcondie}@cs.ucla.edu)

<sup>2</sup>Microsoft

-Microsoft (e-mail: matteo.interlandi@microsoft.com)

submitted 1 January 2003; revised 1 January 2003; accepted 1 January 2003

#### Abstract

A very desirable Datalog extension investigated by many researchers in the last thirty years consists in allowing the use of the basic SQL aggregates **min**, **max**, **count** and **sum** in recursive rules. In this paper, we propose a simple comprehensive solution that extends the declarative least-fixpoint semantics of Horn Clauses, along with the optimization techniques used in the bottom-up implementation approach adopted by many Datalog systems. We start by identifying a large class of programs of great practical interest in which the use of **min** or **max** in recursive rules does not compromise the declarative fixpoint semantics of the programs using those rules. Then, we revisit the monotonic versions of **count** and **sum** aggregates proposed in (Mazuran et al. 2013b) and named, respectively, **mcount** and **msum**. Since mcount, and also msum on positive numbers, are monotonic in the lattice of set-containment, they preserve the fixpoint semantics of Horn Clauses. However, in many applications of practical interest, their use can lead to inefficiencies, that can be eliminated by combining them with max, whereby mcount and msum become the standard count and sum. Therefore, the semantics and optimization techniques of Datalog are extended to recursive programs with min, max, count and sum, making possible the advanced applications of superior performance and scalability demonstrated by BigDatalog (Shkapsky et al. 2016) and Datalog-MC (Yang et al. 2017). This paper is under consideration for acceptance in TPLP.

KEYWORDS: Datalog, Constraints, Recursion, Aggregates.

## 1 Introduction

A growing body of research on scalable data analytics has brought a renaissance of interest in Datalog because of its ability to specify, declaratively, advanced data-intensive applications that execute efficiently over different systems and architectures, including massively parallel ones (Seo et al. 2013; Shkapsky et al. 2013; Yang and Zaniolo 2014; Aref et al. 2015; Wang et al. 2015; Yang et al. 2015; Shkapsky et al. 2016; Yang et al. 2017). A common thread in this new generation of Datalog systems is the use of aggregates in recursion, since aggregates enable the concise expression and efficient support of much more powerful algorithms than those expressible by programs that are stratified w.r.t. negation and aggregates. However, the non-monotonic nature of common aggregates creates major issues, and extending the declarative semantics of Datalog to allow aggregates in recursion represents a difficult problem since the

early days of Datalog (Kemp and Stuckey 1991; Greco et al. 1992; Ross and Sagiv 1992). These approaches were seeking to achieve both (i) a formal declarative semantics for deterministic queries using the basic SQL aggregates, min, max, count and sum, in recursion and (ii) their efficient implementation by extending techniques of the early Datalog systems (Morris et al. 1986; Chimenti et al. 1987; Ramakrishnan et al. 1992; Vaghani et al. 1994; Arni et al. 2003). As discussed in the related work section, while many of these approaches only dealt with some of the four basic aggregates, the proposal presented in (Ross and Sagiv 1992) covered all four. However it used different lattices for different aggregates and thus incurred in the problems described in (Van Gelder 1993). Therefore, the search for general solutions has motivated several approaches that have addressed the problem using powerful semantics, such as answer-set semantics, that however require higher levels of computational complexity (Pelov et al. 2007; Son and Pontelli 2007; Swift and Warren 2010; Faber et al. 2011; Gelfond and Zhang 2014).

Recently, the explosion of activity on Big Data has produced a revival of interest in Datalog as a parallelizable language for expressing and supporting efficiently Big Data Analytics (Seo et al. 2013; Shkapsky et al. 2013; Wang et al. 2015). The algorithms discussed in those papers are graph algorithms or other algorithms that use aggregates in recursion for Big Data applications where performance is of the essence. Thus, a convergence of declarative semantics and efficient implementation is critically needed and has motivated the research presented in this paper, where we propose a novel approach based on the concept of *pre-mappability of constraints*. Indeed, pre-mappability of constraints provides a simple criterion that (i) the system optimizer can utilize to push constraints into recursion, and (ii) the user can utilize to write programs that use aggregates in recursion, with the guarantee that they have indeed a formal fixpoint semantics.

The rest of this paper is organized as follows. In the next section, we introduce the problem of pushing constraints into recursion, then, in Section 3, we present the rather surprising result that in many programs of practical interest constraints applied to recursive rules do not invalidate the formal fixpoint semantics of those rules. We thus introduce general sufficient conditions under which we can push comparison constraints, extrema constraints, and combinations of the two. With the treatment of min and max in recursive rules completed, we move to the problem of supporting count and sum. In Section 5, we present an in-depth treatment of this important subject by combining the monotonic versions of these aggregates proposed in (Mazuran et al. 2013a) with the treatment of extrema proposed in the previous sections. Seminaive evaluation in the presence of constraint pushing is discussed in Section 6. Related work and conclusions presented in Sections 7 and 8 bring the paper to a closing.

#### 2 Comparison and Extrema Constraints

We will now propose motivating examples that also illustrate the Datalog syntax and terminology we use, which are widely used in the literature (Zaniolo et al. 1997; Shkapsky et al. 2015).

Example 1 (Limited length paths from node a in a directed graph)

```
 \begin{array}{lll} (\textbf{r}_1) & \texttt{path}(\textbf{Y}, \texttt{Dy}) \leftarrow & \texttt{arc}(\textbf{a}, \textbf{Y}, \texttt{Dy}), \texttt{Dy} \geq \textbf{0}. \\ (\textbf{r}_2) & \texttt{path}(\textbf{Y}, \texttt{Dy}) \leftarrow & \texttt{path}(\textbf{X}, \texttt{Dx}), \texttt{arc}(\textbf{X}, \textbf{Y}, \texttt{Dxy}), \texttt{Dxy} \geq \textbf{0}, \texttt{Dy} = \texttt{Dx} + \texttt{Dxy}. \\ (\textbf{r}_3) & \texttt{1lpath}(\textbf{Y}, \texttt{Dy}) \leftarrow & \texttt{path}(\textbf{Y}, \texttt{Dy}), \texttt{Dy} < \textbf{143}. \end{array}
```

In the program of Example 1, path(Y,Dy) is the *head* of  $r_1$ , while arc(a,Y,Dy) and  $Dy \ge 0$  are the rule's *goals*, where  $Dy \ge 0$  specifies a *lower-bound constraint* (symmetrically, Dy < 143 in  $r_3$  is an *upper-bound constraint*). In rule  $r_2$ , the two-argument path is both the head and

a goal: thus  $\mathbf{r}_2$  is a *recursive rule* and path is a recursive predicate. On the other hand, non-recursive rule  $\mathbf{r}_1$  with path as its head will be called an *exit* rule. The arithmetic predicates used in  $\mathbf{r}_2$  can be defined using Horn Clauses on Datalog<sub>1s</sub> (Zaniolo et al. 1997), and therefore our program has formal semantics based on the equivalence of its model-theoretic, proof-theoretic, and least-fixpoint semantics (van Emden and Kowalski 1976). The least-fixpoint of a monotonic program can be computed by iterating over the *Immediate Consequence Operator* (ICO) defined by the rules of the program, and Datalog researchers have introduced techniques such as seminaive-fixpoint and magic-set to optimize this botton-up iterative computation into efficient implementations (Zaniolo et al. 1997). Even more significant optimization opportunities occur in the presence of constraints. For instance, an unoptimized Datalog computation for this program would apply the upper-bound constraint  $\mathbf{D}\mathbf{y} < 143$  specified by the final rule  $\mathbf{r}_3$  to all the path atoms generated by iterating over rules  $\mathbf{r}_1$  and  $\mathbf{r}_2$ . Thus this constraint is applied as a postcondition after all pairs have been generated, and does not improve the efficiency of the computation; in fact this might never terminate when our graph contains cycles.

A very simple solution for this problem is to push the upper-bound constraint Dy < 143 into the recursive computation. We can hence rewrite the above program into the following, where the constraint has been transferred to the rules defining path.

Example 2 (Rewritten version of Example 1 where the constraint is transferred)

```
 \begin{array}{lll} (\textbf{r}_1') & \mathtt{path}(\textbf{Y}, \texttt{Dy}) \leftarrow & \mathtt{arc}(\textbf{a}, \textbf{Y}, \texttt{Dy}), \texttt{Dy} \geq \textbf{0}, \texttt{Dy} < \textbf{143}. \\ (\textbf{r}_2') & \mathtt{path}(\textbf{Y}, \texttt{Dy}) \leftarrow & \mathtt{path}(\textbf{X}, \texttt{Dx}), \mathtt{arc}(\textbf{X}, \textbf{Y}, \texttt{Dxy}), \texttt{Dxy} \geq \textbf{0}, \texttt{Dy} = \texttt{Dx} + \texttt{Dxy}, \texttt{Dy} < \textbf{143}. \\ (\textbf{r}_3') & \mathtt{llpath}(\textbf{Y}, \texttt{Dy}) \leftarrow & \mathtt{path}(\textbf{Y}, \texttt{Dy}). \end{array}
```

Thus we obtain a program where the constraint Dy < 143 has been transferred from the final rule  $r_3$  into the recursive program and applied to rules  $r_2$  and  $r_1$ , i.e., pre-mapped to those rules. Observe that the rules produced by this transformation have been renamed  $r_3'$ ,  $r_2'$  and  $r_1'$ . The program so obtained provides an optimized version of the original program that is equivalent to it inasmuch as the two programs deliver the same llpath results. This equivalence follows from the fact that lengths of arc are  $\geq 0$ , whereby Dy < 143 in the body of  $r_2'$  implies that Dy < 143 for Dy in the head of the same rule—i.e., pruned values are those that would be eliminated by the final "< 143" constraint in the original  $r_3$  rule.

An even more significant optimization is possible when *extrema constraints* (i.e., max and min aggregates) are applied to the results produced by recursive rules. For instance, say that we substitute rule  $r_3$  in Example 1 with the following rule that uses the extrema constraint is\_min.

$$(r_4)$$
 spath $(Y, Dy) \leftarrow path(Y, Dy), is_min((Y), (Dy)).$ 

The construct  $is\_min$  identifies Dy as the *cost argument* and Y as the *group-by variable(s)*, using SQL terminology. Thus,  $is\_min((Y),(Dy))$  denotes that we want the min values of Dy for each unique value of Y. The special notation used for min warns the compiler that its specialized internal implementation should be used in its evaluation, along with the query transformation and optimization techniques discussed next. However the semantics of rules with our  $is\_min$  construct can be reduced to that of rules with standard (closed-world) negation, whereby the semantics of  $r_4$  is defined by the following two rules where  $is\_min$  is replaced by the negation that a lesser value exists: <sup>1</sup>

<sup>&</sup>lt;sup>1</sup> This rewriting assumes that there is only one is\_min in our program. In the presence of multiple occurrences, we will need to add a subscript to keep them distinct.

```
\begin{split} \mathtt{spath}(\mathtt{Y},\mathtt{Dy}) &\leftarrow &\mathtt{path}(\mathtt{Y},\mathtt{Dy}), \neg\mathtt{lesser}(\mathtt{Y},\mathtt{Dy}). \\ \mathtt{lesser}(\mathtt{Y},\mathtt{Dy}) &\leftarrow &\mathtt{path}(\mathtt{Y},\mathtt{Dy}),\mathtt{path}(\mathtt{Y},\mathtt{Dy1}),\mathtt{Dy1} < \mathtt{Dy}. \end{split}
```

Expressing is\_min via negation reveals the non-monotonic nature of extrema constraints, whereby their usage in the definition of recursive predicates can compromise the declarative fixpoint semantics of the program. *Stratification*, where each predicate in the programs must belong to strata that are above those of their negated goals, can be used to avoid the semantic problems caused by using aggregates in recursion. For instance, in our example spath belongs to a stratum that is above that of path, whereby our program is assured to have a *perfect-model semantics* (Przymusinski 1988). The perfect model of a stratified program is a minimal model which is computed using an *iterated fixpoint computation*, starting at the bottom stratum and moving up to higher strata. In our example, therefore, all the possible paths will be computed using rules  $r_1$  and  $r_2$ , before selecting values that are minimal using  $r_4$ . This approach, used by current Datalog compilers, can be very inefficient or even non-terminating when the original graph of Example 1 contains cycles. The naive re-writing similar to the one used to transfer the comparison constraint into our recursive rules yields:

Example 3 (Shortest path from node a)

```
 \begin{array}{lll} (\textbf{r}_1'') & \texttt{path}(\textbf{Y}, \texttt{Dy}) \leftarrow & \texttt{arc}(\textbf{a}, \textbf{Y}, \texttt{Dy}), \texttt{Dy} \geq \textbf{0}, \texttt{is\_min}((\textbf{Y}), (\texttt{Dy})). \\ (\textbf{r}_2'') & \texttt{path}(\textbf{Y}, \texttt{Dy}) \leftarrow & \texttt{path}(\textbf{X}, \texttt{Dx}), \texttt{arc}(\textbf{X}, \textbf{Y}, \texttt{Dxy}), \texttt{Dxy} \geq \textbf{0}, \texttt{Dy} = \texttt{Dx} + \texttt{Dxy}, \texttt{is\_min}((\textbf{Y}), (\texttt{Dy})). \\ (\textbf{r}_4'') & \texttt{spath}(\textbf{Y}, \texttt{Dy}) \leftarrow & \texttt{path}(\textbf{Y}, \texttt{Dy}). \end{array}
```

However, while in Example 1 the transferring of comparisons into the recursive program produces the positive program of Example 2 which has a well-defined formal semantics, the program in Example 3 above uses non-monotonic aggregates (alias negation if we replace them with their definitions) in recursive rules. Thus, there is no guarantee that a formal semantics exists for the rewritten program, and the question of whether this is a correct optimization becomes meaningless. Thus in this paper, we provide a formal minimal-fixpoint semantics that holds for Example 3, and for large classes of programs of major practical interest (Condie et al. 2017).

#### 3 Fixpoint and Constraints

The declarative and constructive semantics of a Datalog program P is defined in terms of the Immediate Consequences Operator (ICO) for P, denoted by  $T_P(I)$ , where I is any Herbrand interpretation of P. For positive Datalog programs, i.e., those without negation or aggregates,  $T_P(I)$  is a monotonic continuous mapping in the lattice of set-containment to which the interpretation I belongs, whereby we have the following well-known properties:

- 1. A unique minimal (w.r.t. set-containment) solution of the equation  $I=T_P(I)$  always exists and it is known as the *least-fixpoint* of  $T_P$ , denoted  $lfp(T_P)$ ;  $lfp(T_P)$  defines the formal declarative semantics of P.
- 2. For an immediate consequence operator T, with  $\omega$  being the first infinite ordinal,  $T^{\uparrow \omega}(\emptyset)$  is defined by letting  $T^{\uparrow 0}(\emptyset) = \emptyset$ , and  $T^{\uparrow n+1}(\emptyset) = T(T^{\uparrow n}(\emptyset))$ . Then  $T^{\uparrow \omega}(\emptyset)$  denotes the union of  $T^{\uparrow n}(\emptyset)$  for every n. The *fixpoint iteration*  $T_P^{\uparrow \omega}(\emptyset)$  defines the *operational semantics* of our program. In most applications of practical interest, the iteration converges to the final value in a finite number of steps, and it can be stopped at the first integer n+1 where,  $T_P^{\uparrow n+1}(\emptyset) = T_P^{\uparrow n}(\emptyset)$ .

For positive Datalog programs we have that the operational and declarative semantics coincide. In the previous section, we have discussed extrema and lower/upper-bound constraints which can be expressed and enforced upon rules by the addition of goals to the rules. We will now define conditions under which post-constraints on the results of recursive-rule computation can be pre-mapped and applied to those rules. Thus we introduce the notion of a constraint  $\gamma$  being *pre-mappable* to one or more rules, in which case we will simply write that  $\gamma$  is PREM to those rules. The PREM property will allow us to extend the fixpoint semantics to programs obtained by transferring a *constraint*  $\gamma$  from the final rule to the rules defining a recursive predicate<sup>2</sup>. Notions related to PREM are already used widely in optimizing distributed computations. For instance when a set of tuples is partitioned into K subsets  $S_1, \ldots, S_k$  we have that:

$$\mathtt{OP}(\bigcup_{1 \leq j \leq K} S_j) = \mathtt{OP}(\bigcup_{1 \leq j \leq K} \mathtt{OP}(S_j))$$

Since this equality holds for OP denoting the aggregates sum, min and max, we will say that these aggregates are PREM to union. This property is frequently called preaggregation and exploited by the parallel execution of K OP aggregates on different nodes followed by a final execution of OP on the results returned by those K nodes. The above property also holds when OP denotes an upper-bound or a lower-bound constraint; however in that case, the final application of OP can be omitted given that upper/lower bound constraints distribute over union.

### Definition 1 (The PREM Property)

In a given Datalog program let P be the set of its rules defining either a recursive predicate or a set of mutually recursive predicates. Also let T be the ICO defined by P. Then, the constraint  $\gamma$  will be said to be PREM to T (and to P) when, for every interpretation I of P, we have that:  $\gamma(T(I)) = \gamma(T(\gamma(I)))$ .

The importance of this property follows from the fact that if I = T(I) is a fixpoint for T, then we also have that  $\gamma(I) = \gamma(T(I))$ , and when  $\gamma$  is PREM to the rules defining T we also have that:

$$\gamma(I) = \gamma(T(I)) = \gamma(T(\gamma(I)))$$

Now, let  $T_{\gamma}$  denote the application of T followed by  $\gamma$ , i.e.,  $T_{\gamma}(I) = \gamma(T(I))$ , where  $T_{\gamma}$  will be called the  $\gamma$ -constrained ICO for the P rules. Now, if I is a fixpoint for T and  $I' = \gamma(I)$ , then the above equality can be rewritten as:

$$I' = \gamma(I) = \gamma(T(\gamma(I))) = T_{\gamma}(I')$$

Thus, when  $\gamma$  is PREM, the fact that I is a fixpoint for T implies that  $I' = \gamma(I)$  is a fixpoint for  $T_{\gamma}(I)$ . We will next focus on cases of practical interest where the transfer of constraints under PREM produces optimized programs that are safe and terminating even when the original programs were not, and prove that the transformation is indeed equivalence-preserving. Thus we focus on situations where  $T_{\gamma}^{\uparrow n}(\emptyset) = T_{\gamma}^{\uparrow n+1}(\emptyset)$ , i.e., the fixpoint iteration converges after a finite number of steps n. The rules defining a recursive predicate p are those having as head p or predicates that are mutually recursive with p.

#### Theorem 1

In a Datalog program, let T be the ICO for the positive rules defining a recursive predicate. If the constraint  $\gamma$  is PREM to T, and a fixpoint exists such that  $T^{\uparrow n+1}(\emptyset) = T^{\uparrow n}(\emptyset)$ , for some integer n then:  $\gamma(T^{\uparrow \omega}(\emptyset)) = T_{\nu}^{\uparrow n}(\emptyset)$ 

<sup>&</sup>lt;sup>2</sup> Note that here and in the following definition the  $\gamma$  symbol is overloaded because it is used to express a constraint both as a literal in a final rule, and a pruning condition over instances.

Proof Let us assume that  $T_{\gamma}^{\uparrow n+1}(\emptyset) = T_{\gamma}^{\uparrow n}(\emptyset)$  and prove by induction that  $\gamma(T^{\uparrow k}(\emptyset)) = T_{\gamma}^{\uparrow k}(\emptyset)$  holds for every non-negative integer k. Indeed, the property holds for k=0 since  $\gamma(T^{\uparrow 0}(\emptyset)) = T_{\gamma}^{\uparrow 0}(\emptyset) = \emptyset$ . Moreover, since  $\gamma$  is PREM to T, we have that the following equalities hold:  $\gamma(T^{\uparrow k+1}(\emptyset)) = \gamma(T(T^{\uparrow k}(\emptyset))) = \gamma(T(\gamma(T^{\uparrow k}(\emptyset)))) = \gamma(T(T^{\uparrow k}(\emptyset))) = T_{\gamma}^{\uparrow k+1}(\emptyset).$  Now we have that  $\gamma(T^{\uparrow \omega}(\emptyset)) = \gamma(\bigcup_{k\geq 0} T^{\uparrow k}(\emptyset))$ . But  $\bigcup_{k\geq 0} T^{\uparrow k}(\emptyset) = \bigcup_{m\geq n} (T^{\uparrow m}(\emptyset))$ . In fact,

Now we have that  $\gamma(T^{\uparrow\omega}(\emptyset)) = \gamma(\bigcup_{k \geq 0} T^{\uparrow k}(\emptyset))$ . But  $\bigcup_{k \geq 0} T^{\uparrow k}(\emptyset) = \bigcup_{m \geq n} (T^{\uparrow m}(\emptyset))$ . In fact, the monotonicity of T implies that for each  $T^{\uparrow m}(\emptyset)$  with  $m \leq k$  there is a  $T^{\uparrow m'}(\emptyset)$  with m' > k containing it. Now, our  $\gamma$  constraints are also PREM to union, and thus we have that  $\gamma(\bigcup_{m \geq n} T^{\uparrow m}(\emptyset)) = \gamma(\bigcup_{m \geq n} \gamma(T^{\uparrow m}(\emptyset))) = \gamma(\bigcup_{m \geq n} T^{\uparrow m}(\emptyset)) = \gamma(T^{\uparrow m}(\emptyset))$ 

We can next prove that the fixpoint  $T_{\gamma}^{\uparrow n}(\emptyset)$  so obtained is in fact a minimal fixpoint for  $T_{\gamma}$ .

Theorem 2

If  $\gamma$  is PREM to T and  $T_{\gamma}^{\uparrow n}(\emptyset) = T_{\gamma}^{\uparrow n+1}(\emptyset) = I$ , then I is a minimal fixpoint for  $T_{\gamma}$ .

*Proof* If  $I' \subseteq T_{\gamma}^{\uparrow n}(\emptyset)$  is a fixpoint, then  $I' = T_{\gamma}^{\uparrow k}(I')$  for every integer k. Now, starting with  $T_{\gamma}^{\uparrow 0}(I') = I' = \gamma(T^{\uparrow 0}(I'))$  we can apply the inductive reasoning process used in Theorem 1 to conclude that the equality  $T_{\gamma}^{\uparrow k}(I') = \gamma(T^{\uparrow k}(I'))$  holds for each k. Therefore the union, for all k, of the sets on the left side of the equation is equal to the union of all the sets on the right side. But the unioned sets on the left are equal to I', whereas all those on the right side define  $\gamma(T^{\uparrow \omega}(\emptyset))$ , since  $\emptyset \subseteq I'$ . But Theorem 1 has shown that  $\gamma(T^{\uparrow \omega}(\emptyset)) = T_{\gamma}^{\uparrow n}(\emptyset) = I$ . Thus no proper subset of  $\gamma(T^{\uparrow \omega}(\emptyset))$  can be a fixpoint for  $T_{\gamma}$ .  $\square$ 

Therefore, constraints which are PREM can be transferred into recursive rules and this represents a significant optimization which, in many cases, also produces programs where the fixpoint iteration terminates even when the iterated fixpoint computation on the original program did not. Moreover, the termination of the fixpoint iteration for the rewritten program ensures that we obtain a minimal fixpoint that is equivalent to the original program with respect to the predicates that were constrained by the PREM constraint  $\gamma$ . Thus the well-known compilation techniques of positive programs, including magic set and seminaive computation, can be applied to programs optimized by the transfer of PREM constraints.

While the problem of determining general classes of PREM constraints leaves much room for further research, we have already determined classes of PREM constraints that hold for programs of great practical interest, such as those discussed next.

## **4 Transferring PREM Constraints**

We will next establish basic sufficient conditions under which transferability of extrema and comparison constraints hold for programs such as those in Examples 1 and 2. In those examples we have a final rule (in the next stratum) applying a constraint to some recursive predicate, which we call the *cost predicate*, defined by a set of rules which will be called the *cost rules*. The key intuition behind PREM constraints is that some form of monotonicity must be preserved while constraints are applied in recursion. A form of monotonicity preserved under extrema is one where the  $\geq$  or  $\leq$  relationships holding for cost variables in the bodies of two instances of a rule implies that the same relationship holds for the cost variables in their heads. A stricter condition is the one in which the cost argument in the head is required to be  $\geq$  (resp.  $\leq$ ) than the related

cost argument in the body. When this condition is satisfied, upper (lower) bound constraints are PREM (Proposition 2), because once the constraint is not satisfied for a certain tuple combination and a cost argument, it cannot be satisfied for increased (decreased) costs. Next, we will make the above intuitive explanation more formal. For simplicity, we assume that there is no predicate that is mutually recursive with our cost predicate. The cost rules have two types of goals. The goals of the first type use *interpreted* predicates, such as arithmetic comparisons and other builtins whose semantics and implementation are pre-defined in the system. The remaining goals will be called *regular goals* which refer to regular predicates, i.e. predicates whose meaning is being defined by the program at hand. The cost predicates appearing in the head of our rule are also regular predicates. We will use the notation rg(r) to denote the conjunction of the regular goals in the body of a rule r. Thus in our Example 1,  $rg(r_2) = \text{"path}(X, Dx), \text{arc}(X, Y, Dxy)$ ".

Each constraint in the final rule defines a cost argument for a particular regular predicate: e.g., in our previous examples both the constraints >143 and is\_min established the second argument of path to be the cost argument. For simplicity of discussion, we will only consider cases where for each regular predicate p there is only one cost argument denoted ca(p). Finally, we assume that rules (and predicates) are *instantiated* as usual by assigning to their variables values taken from a suitable universe (e.g., a Herbrand universe that also includes numbers). Now, we will define *valid instances of a rule* to be those where variables are instantiated to values that make all the interpreted goals true. Thus for our rule  $r_2$  in Example 1, arbitrary values can be assigned to the variables X and Y. However the values assigned to Dx, Dxy and Dy must satisfy the conditions  $Dxy \ge 0 \land Dy = Dx + Dxy$ . In order to determine if extrema are PREM, we have to provide a sufficient condition whereby the validity of the  $\ge$  or  $\le$  relationship for cost variables in the bodies of two instances of the given rule implies that the same relationship holds for the cost variables in their heads. Therefore we will introduce the notion that *inflated* cost-predicates in the body of the rule also *inflate* the and cost-predicates of the heads of the rules.

Definition 2 (Inflating / Deflating cost predicates)

Let  $\mathbf{p}'$  and  $\mathbf{p}''$  be two instances of a cost predicate p where non-cost arguments of  $\mathbf{p}'$  are identical to those of  $\mathbf{p}''$ . Then when  $ca(\mathbf{p}') \ge ca(\mathbf{p}'')$  we say that  $\mathbf{p}'$  inflates  $\mathbf{p}''$ . Conversely, when  $ca(\mathbf{p}') \le ca(\mathbf{p}'')$  we say that  $\mathbf{p}'$  deflates  $\mathbf{p}''$ .

Definition 3 (Inflating / Deflating conjuncts of regular goals)

Let r be a rule and  $\mathbf{r}'$  and  $\mathbf{r}''$  be two of its instantiations where all the regular non-cost goals are identical and each regular cost goal of  $\mathbf{r}'$  in rg(r) inflates (resp. deflates) the corresponding goal in  $\mathbf{r}''$ . Then we say that the regular goals of  $\mathbf{r}'$  inflate (resp. deflate) the regular goals of  $\mathbf{r}''$ .

For example, consider the following two instances of a rule r which are identical everywhere but in their cost arguments; the interpreted goals use the square-root function sqrt:

```
\begin{aligned} \mathbf{r}': \mathtt{path}(\mathtt{y},\mathtt{dy}') \leftarrow & \mathtt{path}(\mathtt{x},\mathtt{dx}'), \mathtt{arc}(\mathtt{x},\mathtt{y},\mathtt{dxy}), \mathtt{dxy} \geq \mathtt{0}, \mathtt{dy}' = \mathtt{dx}' + \mathtt{sqrt}(\mathtt{dxy}). \\ \mathbf{r}'': \mathtt{path}(\mathtt{y},\mathtt{dy}'') \leftarrow & \mathtt{path}(\mathtt{x},\mathtt{dx}''), \mathtt{arc}(\mathtt{x},\mathtt{y},\mathtt{dxy}), \mathtt{dxy} \geq \mathtt{0}, \mathtt{dy}'' = \mathtt{dx}'' + \mathtt{sqrt}(\mathtt{dxy}). \end{aligned}
```

If we assume that dx'' > dx', then path(x, dx'') represents an arbitrary inflation of path(x, dx'). Likewise, the regular goal conjunction of the second rule, i.e., path(x, dx''), arc(x, y, dxy), represents an arbitrary inflation of regular goal conjunction of the first rule. We now have the following condition under which extrema constraints become PREM.

Definition 4 (Inflation / Deflation preserving rules)

A rule r will be said to be *inflation-preserving* (resp. deflation-preserving), when for every valid instance  $\mathbf{r}'$  of r, and for every V that is an inflation-preserving (resp. deflation-preserving)

instance of the regular goals of  $\mathbf{r}'$ , there exists a valid instance  $\mathbf{r}''$  of r which (i) has V as its regular goals, and (ii) its head that inflates (resp. deflates) the head of  $\mathbf{r}'$ .

To apply this definition to our example we must check that for each path(x, dx''), arc(x, y, dxy) that inflates path(x, dx'), arc(x, y, dxy) there exists a valid instance of the interpreted goals of  $\mathbf{r}''$  that delivers a head that inflates that of  $\mathbf{r}'$ . Now, sqrt has two valid interpretations, one that returns a positive square-root value and the other that returns its opposite negative value. Now, if we only allow the negative interpretation of sqrt, we see that for  $dy'' \ge dy'$ , r'' does not inflate r', and thus r is not inflation-preserving; however, if we only allow the positive interpretation or we allow both, then our rule becomes inflation preserving.

Next, let us call *procedure* the set of rules in a program defining the same predicate, while those defining a cost predicate will be called a cost procedure. A cost procedure will be called inflation-preserving (resp. deflation-preserving) when all its rules are inflation-preserving (resp. deflation-preserving). Moreover, by applying a PREM constraint  $\gamma$  to a cost procedure we mean that the constraint is applied to each rule in the procedure. Then, we have:

#### Proposition 1

Min constraints are PREM to deflation-preserving cost procedures, and max constraints are PREM to inflation-preserving cost procedures.

**Proof** To prove that  $\gamma$  is PREM we need to prove that for each rule r of our cost procedure  $\gamma(T(I)) = \gamma(T(\gamma(I)))$ . If r is non-recursive (i.e., an exit rule) the result is immediate since  $\gamma(T(\emptyset)) = \gamma(T(\gamma(\emptyset)))$ . If r is a recursive rule and  $\mathbf{r}'$  is an instance of r, then the application of  $\gamma = \max$  to I invalidates  $\mathbf{r}'$  iff there is another instance of r say  $\mathbf{r}''$  which inflates the regular goal conjunct of  $\mathbf{r}'$ . But since this rule is inflation-preserving the head of  $\mathbf{r}''$  inflates that of  $\mathbf{r}'$  and it will thus be eliminated by the application of the  $\gamma = \max$  outside the parentheses. Therefore we conclude that  $\max$  is PREM to inflation-preserving cost procedures, and symmetrically  $\min$  is PREM to deflation-preserving cost procedures.

For instance, returning to rules  $r_1$  and  $r_2$  in Example 1, we see that they are both inflation-preserving and deflation-preserving. Thus, we can safely transfer either the is\_min or is\_max constraint from  $r_4$ , as shown by Example 3 that was produced by transferring is\_min.

We next provide transferability conditions for upper/lower-bound constraints.

Definition 5 (Ascending / Descending mappings from rule bodies to their heads) A rule r defines an ascending (resp. descending) mapping when in each of its valid instances  $\mathbf{r}$ , the cost argument in the head is  $\geq$  (resp.  $\leq$ ) the cost argument in each of the cost goals of  $\mathbf{r}$ .

Thus, for our previous rule using sqrt, if we only use the positive interpretation of sqrt, then our rule defines an ascending mapping, but under negative interpretation of sqrt we have a descending mapping since dy' < dy. Thus if we allow both interpretations the rule neither defines an ascending mapping nor a descending one. Likewise, rules  $r_1$  and  $r_2$  in Example 1 define an ascending mapping, whereas they define a descending mapping if we assume that the arc lengths in our graphs are  $\leq 0$ . Note that inflation-/deflation-preserving differ from ascending/descending mappings in that the former does not require the cost in the head to be  $\geq$  (resp.  $\leq$ ) each cost argument in the body. For example, if in  $r_2$  we replace the goal Dy = Dx + Dxy with Dy = (Dx + Dxy) - 99, the rule remains inflation-preserving, while it no longer defines an ascending mapping.

Now, with conditions such as < 143 and  $\le 143$  defining *upper-bound constraints* (and dually for *lower-bound constraints*), we have that:

#### Proposition 2

Upper-bound constraints are PREM to cost procedures defining ascending mappings, whereas lower-bound constraints are PREM to cost procedures defining descending mappings.

*Proof* Say that an upper-bound constraint  $\gamma$  has been applied to a rule r in our cost procedure defining an ascending mapping. The proof that  $\gamma(T(I)) = \gamma(T(\gamma(I)))$  is trivial for each exit rule since they are applied upon  $I = \emptyset$ . Say now that T is the ICO of a recursive rule r. Then the application of our PREM upper-bound constraint eliminates each instance  $\mathbf{r}'$  which fails the constraint; but since r defines an ascending mapping, the head of  $\mathbf{r}'$  will then fail the same upper-bound constraint. Thus the upper-bound constraints are PREM to all rules of a cost procedure defining an ascending mapping. Symmetrically for lower-bounds and descending mappings.

We see that the cost procedure in Example 1 defines an ascending mapping and thus the transfer of upper-bound Dy < 143 done in Example 2 is correct. The rules composing the procedure also define descending mappings and would also support the transfer of lower-bound constraints. However, it is also very important to observe how upper-bound and lower-bound constraints interact and often interfere with extrema. For instance, say that rule  $r_4$  applied to our Example 2 specified both the constraints Dy < 143 and  $is_min((Y),(Dy))$ . Then we see that each of the two and their conjunct PREM and can be pushed into the procedure. But in general, the fact that each constraint is PREM does not assure that its conjunct is too. For instance, after the transfer of Dy < 143 rule  $r_2'$  is still deflation-preserving but no longer inflation-preserving. Thus, while  $is_min((Y),(Dy))$  is still transferable after we transfer Dy < 143, the constraint  $is_max((Y),(Dy))$  is not. Symmetrically if we transfer the constraint Dy  $\geq$  143 instead of Dy < 143, our rules become inflation-preserving, whereby max constraints can be transferred, but min constraints cannot since the rules are no longer deflation-preserving.

#### 5 Monotonic Aggregates

At the core of the approach proposed in (Mazuran et al. 2013b) there is the observation that the cumulative version of standard count is monotonic in the lattice of set containment. Thus (Mazuran et al. 2013b) introduce mount as the aggregate function that returns all natural numbers up to the cardinality of the set. The use of mount in actual applications is illustrated by the following example that is similar to one proposed by (Ross and Sagiv 1992).

Example 4 (Join the party once you see that three of your friends have joined) The organizer of the party will attend, while other people will attend if the number of their friends attending is greater or equal to 3, i.e.,  $Nfx \ge 3$ .

```
\begin{split} & \mathtt{attend}(\mathtt{X}) \leftarrow \mathtt{organizer}(\mathtt{X}). \\ & \mathtt{attend}(\mathtt{X}) \leftarrow \mathtt{cntfriends}(\mathtt{X},\mathtt{Nfx}),\mathtt{Nfx} \geq 3. \\ & \mathtt{cntfriends}(\mathtt{Y},\mathtt{N}) \leftarrow \mathtt{attend}(\mathtt{X}),\mathtt{friend}(\mathtt{Y},\mathtt{X}),\mathtt{mcount}((\mathtt{Y}),(\mathtt{X}),\mathtt{N}). \end{split}
```

Here too we use the body notation for our monotonic count-distinct aggregate, mcount((Y), (X), N), where its first argument (Y) is the group-by argument; its second (X), is the count argument, and the third is the result of the count aggregate. The count argument consists of one or more sub-arguments, whereas the group-by can consists of zero or more sub-arguments. As proven in (Mazuran et al. 2013b), the semantics of mcount((Y), (X), N) can be reduced to that of Horn Clauses. The use of mcount in recursion allows us to express programs, such as counting paths between two nodes, that are not expressible using the standard aggregates in

stratified programs (Mumick and Shmueli 1995). Moreover, since mount is monotonic, the fixpoint semantics and optimization techniques of Datalog remain valid. In particular, we can optimize our program by pushing max into the recursion.

By the query goal attend(N) the program in Example 4 returns the names of the people who attend the party. To find out the number of friends each attendee will have at the party, we can use the query goal cntfriends(Y,X), which however is likely to return many answers, since for an attendee with k friends it will return his/her name k times. A solution to this problem is to use the following rule to return the final results  $^3$ :

```
fcount(Y,N) \leftarrow cntfriends(Y,N), is_max((Y),(N)).
```

The obvious question now is whether  $is_{max}$  can be transferred into the recursive rules defining cntfriends(Y,N), which is true if these rules are inflation-preserving. We have previously examined the case where there is only one recursive rule, and here we can reduce our problem to that situation by taking the composition of the two recursive rules in Example 4, obtaining the following rule:

```
cntfriends(Y, N) \leftarrow cntfriends(X, Nfx), Nfx \ge 3, friend(Y, X), mcount((Y), (X), N).
```

Now, we must determine if the condition of inflation preservation is satisfied so that we can transfer the max into our recursive rules. Since there is no valid instance of this rule for Nfx < 3, we only need to consider instantiations in which Nfx  $\geq$  3. Note that the goal mcount((Y),(X),N) is independent from Nfx, and the count can not decrease: thus, the rule is inflation-preserving.

Example 5 (Join the party once three of your friends have joined using standard count)

```
\begin{array}{lll} \mathtt{attend}(\mathtt{X}) \leftarrow & \mathtt{organizer}(\mathtt{X}). \\ \mathtt{attend}(\mathtt{X}) \leftarrow & \mathtt{cntfriends}(\mathtt{X},\mathtt{Nfx}),\mathtt{Nfx} \geq 3. \\ \mathtt{cntfriends}(\mathtt{Y},\mathtt{N}) \leftarrow & \mathtt{attend}(\mathtt{X}),\mathtt{friend}(\mathtt{Y},\mathtt{X}),\mathtt{count}((\mathtt{Y}),(\mathtt{X}),\mathtt{N}). \\ \mathtt{fcount}(\mathtt{Y},\mathtt{N}) \leftarrow & \mathtt{cntfriends}(\mathtt{Y},\mathtt{N}). \end{array}
```

This formulation using count is more efficient than the one using mcount since it implies that condition  $Nfx \ge 3$  is no longer checked for each +1 increment: it is instead checked for each new count value delivered by the previous step in the iteration. At each iteration, the old count value is incremented to include all the newly-found friends. Once the fixpoint is reached, fcount(Y,N) returns, for each person Y attending the party, the actual count N of Y's friends at the party.

We might also allow users to write programs such as that in Example 5 where count is used instead of mount in recursion. The compiler will process these programs by interpreting count as a max mount and transferring max out of recursion before checking that the resulting program is indeed inflation preserving. If this check succeeds then the original program is executed, otherwise an error message, or a stern warning, is returned to the user.

## 5.1 From Monotonic SUM to Regular SUM

The notion of monotonic sum msum for positive numbers was also introduced in (Mazuran et al. 2013b) as an extension of mcount. For instance, say that we have a set of facts following the template part(Pno, Cost), where for each part number we have its cost expressed as a positive

<sup>&</sup>lt;sup>3</sup> Along with the people who count three friends at the party, this will also return those who count only one or two friends among those, who can be removed by an additional final condition  $N \ge 3$ .

integer. To compute the total value of the parts on store, we can add up their costs using the sum aggregate, as follows:

```
total(T) \leftarrow part(Pno, C), sum((), (Pno, C), T).
```

Here (Pno,C) states that the sum is taken over every C appearing under a distinct Pno. As such, the semantics of sum is easy to reduce to that of count, by first expand each cost C into C pairs (C, J), with  $1 \le J \le C$  and then compute the sum by counting these pairs. For instance, the pair (bolt,4) is represented by the four tuples: (bolt,4,1),(bolt,4,2),(bolt,4,3),(bolt,4,4). The meaning of sum((),(Pno,C),T) can now be defined by the pair of goals int up2(C,Int), count((),(Pno,C,Int),T), where int\_up2(C, Int) produces all the integers up to C. Thus our previous rule can be rewritten as:

```
total(T) \leftarrow
                       part(Pno, C), int upt2(C, Int), count((), (Pno, C, Int), T).
int up2(C,1) \leftarrow
                      C > 0.
int_up2(C, J1) \leftarrow int_up2(C, J), J1 = J+1, J1 \leq C.
```

In a totally analogous way we can define msum via int\_up2 and mcount, whereby, e.g., msum((),(C,Int),T) is defined as equivalent to int\_upt2(C,Int),mcount((),(C,Int),T). Furthermore, the regular sum is simply the result of applying the max aggregate to msum, and this leads to many useful applications where sum is used directly in inflation-preserving recursive rules. For instance say that we have the classical part-explosion problem where we have a set of basic parts with their cost basic(Part, Cost), and then we have information about assembled parts, describing for each assembled parts their subparts and quantities in the assemblage assb(Part, SubPart, Qty). To compute the cost of all parts we can write the following program:

Example 6 (Part explosion problem: the cost of parts as sum of the cost of its subparts)

```
cost(Part,Cost) \leftarrow
                                 basic(Part,Cost).
\texttt{cost}(\texttt{Part}, \texttt{Ncost}) \gets
                                  assb(Part, SP, Qty), cost(SP, Cost),
                                  CQ = Cost * Qty, sum((Part), (SP, CQ), Ncost).
finalcost(Part,Cost) \leftarrow cost(Part,Cost).
```

Presented with this program, the compiler must make sure it can be viewed as the result of transferring the max to the program obtained by replacing sum with msum in the second rule. To achieve this, the compiler will check that (i) the arguments CQ of msum are all positive, and (ii) that the rules are inflation-preserving.

To enable compile-time checking of (i) the user must add the goal CQ > 0 to the recursive rule in our example. In the absence of this, or equivalent conditions, the compiler returns a stern warning message, but the user will still be able to proceed with execution under the optional trust-but-verify policy that reports this violation as a run-time error. This trust-but-verify option represents a very useful debugging tool, and is also available if, for any reason, the compiler cannot verify (ii).

This example illustrates the great benefits that should be expected from allowing sum in recursion, for those situations where its formal semantics can be reduced to the transfer of a final max into msum. However, there seems to be no obvious application that requires the use of msum instead of sum. Moreover, say that the regular sum of costs of our parts amounts to 50,000: the msum will return the first 50,000 integers, thus causing serious inefficiencies. Thus while the compiler might use the notion of msum to verify that the given program using sum in its recursive rules has a fixpoint semantics, msum should not be part of the actual language. Since it is implemented directly without calling upon its equivalent count representation, sum can also be applied to arbitrary positive numbers represented in scientific (mantissa and exponent) notation, given that they can be viewed as large integers (Mazuran et al. 2013b).

## 6 Seminaive Optimization

So far, we have focused on optimizing the naive fixpoint computation, which basically generates a new set of tuples from the whole set obtained in the last step. We can now perform the seminaive improvement which can be used to improve the computation of the program obtained from the transferring of constraints. For standard Datalog, the seminaive computation operates as follows:

- A. Keep track of the step at which each new atom was created,
- B. Modify the rules into their differential version, which exploits the fact that rule instances whose bodies only contain atoms produced in older steps cannot produce new atoms, and
- C. Use the modified rules to produce atoms, enforcing the no-duplicate constraints as the atoms are produced.

For programs obtained by the pushing of constraints, A and B above remain the same, but C is significantly extended beyond deduplication to enforce constraints, whereby new atoms produced in B might not be kept and existing atoms might instead be eliminated. For constraints involving extrema, for instance, besides the removal of duplicate atoms, step C will also make sure no atom that violates the extremum constraint is added to the working set. For instance, if a program with max constraints produces a new (b,D), then this new pair is added to the working set only if this does not already contain a pair (b,D1) with  $D1 \ge D$ , and if this new pair is inserted then each pair (b,D2) with D2 < D is deleted from the working set. Symmetric properties hold for min aggregates. The basic A, B, and C steps are also used to compute mcount with the proviso that every non-duplicate atom produced in C will increment the running count by one, and the new count value is added to the output. For count and sum, the running counts and sum are incremented at step C, but atoms are only produced at the end of the fixpoint computation. Further refinements of this strategies support the optimizations of (Shkapsky et al. 2016).

#### 7 Related Work

Several solutions, including (Kemp et al. 1989; Srivastava and Ramakrishnan 1992) addressed the problem of pushing comparison constraints into recursive rules, without exploring relationships with the problems of supporting extrema and other aggregates into recursion. Supporting aggregates in recursion is a difficult problem which has been the topic of much previous research work. Several previous approaches focused primarily on providing a formal semantics that could accommodate the non-monotonic nature of the aggregates. In particular (Mumick et al. 1990) discussed programs that are stratified w.r.t. aggregate operators and proved that a perfect model exists for these programs. Then, (Kemp and Stuckey 1991) defined extensions of the well-founded semantics to programs with aggregates, and later showed that these might have multiple and counter-intuitive stable models. The notion of cost-monotonic extrema aggregates was introduced by (Ganguly et al. 1995), using perfect models and well-founded semantics, whereas (Greco et al. 1992) showed that to express greedy algorithms they require the don't-care non-determinism of the stable-model semantics provided by the choice construct.

The problem of optimizing programs with extrema by early pruning of non-relevant facts

was studied in (Sudarshan and Ramakrishnan 1991). A more recent work (Furfaro et al. 2002) devises an algorithm for pushing max and min constraints into recursion while preserving query equivalence under certain specific monotonicity assumptions. Those approaches provided effective optimization techniques for min and max aggregates in recursion, but did not consider count and sum aggregates. The idea of relating comparison with extrema constraints is also used in (Liu et al. 2012) to optimize logical quantification.

A general approach to deal with all four aggregates, was proposed by (Ross and Sagiv 1992) who advocated the use of semantics based on specialized lattices, different from setcontainment, whereby each aggregate will then define a monotonic mapping in its specialized lattice. However, (Van Gelder 1993) pointed out that automatically determining the correct lattices would be difficult in practice, and this was one of the causes that prevented the deployment of the monotonic-aggregate idea in query languages for the following twenty years. Interestingly, a similar idea (with similar limitations) was more recently proposed in (Swift and Warren 2010) and in several other works e.g., (Zhou et al. 2010; Zhou et al. 2015) in the context of tabling in Prolog. Also here is programmer's duty to make sure that a proper partial order / lattice type is used for the program at hand.

A renewed interest in Big Data analytics brought a revival of Datalog as a parallelizable language for expressing more powerful graph and data-intensive algorithms—including many that require aggregates in recursion (Seo et al. 2013; Shkapsky et al. 2013; Wang et al. 2015). The solution proposed here (and previously sketched in (Zaniolo et al. 2016)) builds on the monotonic count and sum proposed in (Mazuran et al. 2013a) and provides the foundation of the efficient and scalable systems discussed in (Shkapsky et al. 2015; Yang et al. 2015; Shkapsky et al. 2016; Yang et al. 2017).

#### 8 Conclusion

In this paper, we have presented a unifying solution to the problem of allowing the use of aggregates in recursive Datalog programs. The widely recognized practical importance of solving this problem has motivated in-depth formal investigations by many excellent researchers who during the last 25 years studied and proposed specialized solutions for parts of this multi-faceted problem. The main advantage of the unified treatment for the four basic aggregates, min, max, count, and sum, proposed in this paper is that it allows a simple specification of algorithms of great practical interest with the guarantee that they have a minimal model semantics that is computed via the standard fixpoint iteration, which can be further refined by the standard optimization techniques of bottom-up Datalog implementations, such as seminaive fixpoint computation, magic-set, left-linear and right-linear recursive rules. The practical significance of these results are demonstrated by the fact that, using these techniques, our BigDatalog system for Apache Spark was able to outperform graph applications written in GraphX and running on the same system (Shkapsky et al. 2016), suggesting that Datalog, as a general-purpose highlevel language, might be able to outperform high-level languages in the specialized application domains they were designed for.

Practical experience with real-world applications (Condie et al. 2017) also taught us important lessons on the dual role of fixpoint semantics and optimization that inspired the title and the research of this paper. Initially, we followed the query optimization approach since it appeals to intuition and was used by many researchers in the past. This led to the equivalent minimalfixpoint semantics for programs that, via PREM, can exploit extrema and other constraints in recursive rules. However, after developing applications in several domains (Condie et al. 2017),

we realized that specifying PREM constraints in recursive rules represents a natural way to write those applications (perhaps because of the similarity with their iterative procedural counterparts we are familiar with). Moreover, this allowed us to overcome major obstacles that proved insurmountable for the optimization approach. For instance, we have seen examples where goals stating that edge lengths or basic part costs are all positive must be added before the constraints are PREM. But most users knowing that those edges or costs are always positive, (e.g., because of constraints in the database or other rules in the program), prefer to submit their programs for execution without having to add idle conditions to make PREM manifest. In these situations, the system should produce a stern warning message, but the user should still be allowed to proceed with execution. This policy results in greater convenience and the power of handling situations that cannot be handled by optimizers. The user can also call upon the system assistance by initially executing in "debugging mode" under the trust-but-verify policy outlined at the end of Section 5. This will either produce counter-examples that show that  $\gamma$  is not PREM, or after enough testing, the user can reliably assume that the property holds, and the debugging mode can be turned off.

#### Acknowledgements

We would like to thank the reviewers for the comments and suggested improvements. This work was supported in part by NSF grants IIS-1218471, IIS-1302698 and CNS-1351047, and U54EB020404 awarded by NIH Big Data to Knowledge (BD2K).

## References

- AREF, M., TEN CATE, B., GREEN, T. J., KIMELFELD, B., ET AL. 2015. Design and implementation of the LogicBlox system. In *SIGMOD*. ACM, 1371–1382.
- ARNI, F., ONG, K., TSUR, S., WANG, H., AND ZANIOLO, C. 2003. The deductive database system LDL++. *TPLP 3*, 1, 61–94.
- CHIMENTI, D., O'HARE, A. B., KRISHNAMURTHY, R., TSUR, S., WEST, C., AND ZANIOLO, C. 1987. An overview of the LDL system. *IEEE Data Eng. Bull.* 10, 4, 52–62.
- CONDIE, T., DAS, A., INTERLANDI, M., YANG, M., ET AL. 2017. Advanced applications by least-fixpoint algorithms specified using aggregates in Datalog. Tech. Rep. 170012, UCLA CSD.
- FABER, W., PFEIFER, G., AND LEONE, N. 2011. Semantics and complexity of recursive aggregates in answer set programming. *Artif. Intell.* 175, 1, 278–298.
- FURFARO, F., GRECO, S., GANGULY, S., AND ZANIOLO, C. 2002. Pushing extrema aggregates to optimize logic queries. *Inf. Syst.* 27, 5 (July), 321–343.
- GANGULY, S., GRECO, S., AND ZANIOLO, C. 1995. Extrema predicates in deductive databases. *Journal of Computer and System Sciences* 51, 2, 244–259.
- GELFOND, M. AND ZHANG, Y. 2014. Vicious circle principle and logic programs with aggregates. *TPLP 14*, 4-5, 587–601.
- GRECO, S., ZANIOLO, C., AND GANGULY, S. 1992. Greedy by choice. In PODS. ACM, 105-113.
- KEMP, D., MEENAKSHI, K., BALBIN, I., AND RAMAMOHANARAO, K. 1989. Propagating constraints in recursive deductive databases. In *North American Conference on Logic Programming*. 981–998.
- KEMP, D. B. AND STUCKEY, P. J. 1991. Semantics of logic programs with aggregates. In ISLP. 387-401.
- LIU, Y. A., STOLLER, S. D., LIN, B., AND GORBOVITSKI, M. 2012. From clarity to efficiency for distributed algorithms. SIGPLAN Not. 47, 10 (Oct.), 395–410.
- MAZURAN, M., SERRA, E., AND ZANIOLO, C. 2013a. A declarative extension of Horn clauses, and its significance for Datalog and its applications. *TPLP 13*, 4-5, 609–623.
- MAZURAN, M., SERRA, E., AND ZANIOLO, C. 2013b. Extending the power of Datalog recursion. *The VLDB Journal* 22, 4, 471–493.

- MORRIS, K. A., ULLMAN, J. D., AND GELDER, A. V. 1986. Design overview of the NAIL! system. In ICLP. 554-568.
- MUMICK, I. S., PIRAHESH, H., AND RAMAKRISHNAN, R. 1990. The magic of duplicates and aggregates. In *VLDB*. Morgan Kaufmann Publishers Inc., 264–277.
- MUMICK, I. S. AND SHMUELI, O. 1995. How expressive is stratified aggregation? Annals of Mathematics and Artificial Intelligence 15, 3-4, 407–435.
- PELOV, N., DENECKER, M., AND BRUYNOOGHE, M. 2007. Well-founded and stable semantics of logic programs with aggregates. TPLP 7, 3, 301–353.
- PRZYMUSINSKI, T. C. 1988. Perfect model semantics. In ICLP/SLP. 1081–1096.
- RAMAKRISHNAN, R., SRIVASTAVA, D., AND SUDARSHAN, S. 1992. CORAL control, relations and logic. In PVLDB. 238-250.
- ROSS, K. A. AND SAGIV, Y. 1992. Monotonic aggregation in deductive databases. In PODS. 114-126.
- SEO, J., PARK, J., SHIN, J., AND LAM, M. S. 2013. Distributed socialite: a Datalog-based language for large-scale graph analysis. PVLDB 6, 14, 1906–1917.
- SHKAPSKY, A., YANG, M., INTERLANDI, M., CHIU, H., CONDIE, T., AND ZANIOLO, C. 2016. Big data analytics with Datalog queries on Spark. In SIGMOD. ACM, 1135–1149.
- SHKAPSKY, A., YANG, M., AND ZANIOLO, C. 2015. Optimizing recursive queries with monotonic aggregates in DeALS. In ICDE. IEEE, 867-878.
- SHKAPSKY, A., ZENG, K., AND ZANIOLO, C. 2013. Graph queries in a next-generation Datalog system. *PVLDB 6*, 12, 1258–1261.
- SON, T. C. AND PONTELLI, E. 2007. A constructive semantic characterization of aggregates in answer set programming. TPLP 7, 3, 355–375.
- SRIVASTAVA, D. AND RAMAKRISHNAN, R. 1992. Pushing constraint selections. In Journal of Logic Programming. 301–315.
- SUDARSHAN, S. AND RAMAKRISHNAN, R. 1991. Aggregation and relevance in deductive databases. In VLDB. 501-511.
- SWIFT, T. AND WARREN, D. S. 2010. Tabling with answer subsumption: Implementation, applications and performance. In JELIA. 300-312.
- VAGHANI, J., RAMAMOHANARAO, K., KEMP, D. B., SOMOGYI, Z., STUCKEY, P. J., LEASK, T. S., AND HARLAND, J. 1994. The Aditi deductive database system. VLDB J. 3, 2, 245–288.
- VAN EMDEN, M. H. AND KOWALSKI, R. A. 1976. The semantics of predicate logic as a programming language. J. ACM 23, 4, 733-742.
- VAN GELDER, A. 1993. Foundations of aggregation in deductive databases. In Deductive and Object-Oriented Databases. Springer, 13-34.
- WANG, J., BALAZINSKA, M., AND HALPERIN, D. 2015. Asynchronous and fault-tolerant recursive Datalog evaluation in shared-nothing engines. PVLDB 8, 12, 1542–1553.
- YANG, M., SHKAPSKY, A., AND ZANIOLO, C. 2015. Parallel bottom-up evaluation of logic programs: DeALS on shared-memory multicore machines. In Technical Communications of ICLP.
- YANG, M., SHKAPSKY, A., AND ZANIOLO, C. 2017. Scaling up the performance of more powerful Datalog systems on multicore machines. The VLDB Journal 26, 2, 229–248.
- YANG, M. AND ZANIOLO, C. 2014. Main memory evaluation of recursive queries on multicore machines. In IEEE Big Data. 251–260.
- ZANIOLO, C., CERI, S., FALOUTSOS, C., SNODGRASS, R. T., SUBRAHMANIAN, V. S., AND ZICARI, R. 1997. Advanced Database Systems. Morgan Kaufmann.
- ZANIOLO, C., YANG, M., DAS, A., AND INTERLANDI, M. 2016. The magic of pushing extrema into recursion: Simple, powerful Datalog programs. In AMW.
- ZHOU, N.-F., BARTÁK, R., AND DOVIER, A. 2015. Planning as tabled logic programming. TPLP 15, 4-5, 543-558.
- ZHOU, N.-F., KAMEYA, Y., AND SATO, T. 2010. Mode-directed tabling for dynamic programming, machine learning, and constraint solving. In ICTAI '10. Washington, DC, USA, 213–218.

#### **Appendix A Experiments**

Our experiments seek to quantify the performance improvements delivered by the constraint transfer optimization described in the previous sections, compared with (i) the basic iterated fixpoint of stratified programs, (ii) the monotonic aggregate approach of (Mazuran et al. 2013b), and (iii) an XY-stratification based approach (Arni et al. 2003). In fact, XY-stratification is of particular interest since it is known to be quite effective at expressing and implementing efficiently in Datalog complex algorithms that use aggregates in recursion. This is because XY-stratified programs use a restricted form of local stratification made explicit by the +1 form of the first argument in the recursive predicate, whereby the iterated fixpoint computation for basic programs becomes a basic iterative loop. In fact, the iterative loop expressed by Example 9 is akin to the one of the seminaive computation of Example 8.

For our experiments we used the sequential version of DeALS (Shkapsky et al. 2015) that along with the methods (i)–(iii), now supports the constraint transfer optimization implemented as follows: for a given program, the system (a) parses the rules and identifies the constraints to which the optimization is applicable; (b) generates a new set of rules through rewriting; (c) parses the rules again and produces an instantiated AND/OR tree (Arni et al. 2003) representing the execution plan for the rewritten rules; (d) evaluates the program using a tuple-at-a-time pipelined execution.

**Experimental Setup.** The experiments were performed on a machine with four AMD Opteron 6376 CPUs (16 cores per CPU) and 256 GB memory (configured into eight NUMA regions). The operating system is Ubuntu Linux 12.04 LTS, and the version of the JVM is Java 1.8.0\_11 from the Oracle Corporation. The DeALS runtime uses only one core, but we allow the JVM to use all the available cores for background tasks like garbage collection.

**Test Programs.** We report the experimental results on using DeALS to solve the single-source shortest path problem. The compared programs are listed in Appendix B. A user can write the program in Example 7, while DeALS will optimize it by transferring the min aggregate into the recursive rules, and evaluate the program in Example 8. The non-trivial XY-stratified Datalog program (Arni et al. 2003) shown in Example 9 mimics the seminaive evaluation of the program in Example 8. Finally, the formulation that uses monotonic min mmin is shown in Example 10. We denote these four different solutions to the same problem by spath, spath\_prem, spath\_xy and spath\_mmin, respectively.

**Datasets.** We compare the performance of these four programs on synthetic graphs and real world graphs. Each n-node synthetic graph used in the experiments has integer node ids ranging from 0 to n-1, and the length of each arc is a random integer between 1 and 100. These synthetic graphs are directed acyclic graphs (DAGs) generated by connecting each pair of vertices i and j (i < j) with probability 0.1. The real world graphs listed in Table A 1 are selected from the Stanford Large Network Dataset Collection (Leskovec and Krevel 2014). These graphs do not have arc lengths, therefore we generated integers from a uniform random distribution between 1 and 100 as the values of arc lengths. For each graph, we (i) randomly select five nodes; (ii) use each node as the source node, and take the average of five runs for each program; (iii) report the min/average/max time among all five nodes in the form of error bars, while the average time is displayed above each error bar.

**Results on Synthetic Graphs.** The evaluation time for all four programs on DAGs is shown in Figure A1. spath produces many more non-minimal tuples w.r.t. the min constraint than the

Table A 1. Parameters of real world graphs

Name	Nodes	Arcs
web-Stanford	282K	2,312K
web-Google	876K	5,105K
soc-Pokec	1,633K	30,623K
soc-LiveJournal1	4,848K	68,994K




Fig. A 1. Performance comparison on synthetic DAGs. The Y-axis is in logarithmic scale.




Fig. A 2. Performance comparison on real world graphs. The Y-axis is in logarithmic scale.

other three programs. Thus, it is the slowest on all four DAGs: from  $7\times$  to  $177\times$  slower than the second slowest program. The remaining three programs produce about the same number of intermediate tuples. The performances of spath\_prem and spath\_mmin are very close since they rely on very similar implementations. However spath\_xy is about 2× slower than spath prem due to the overhead of its evaluation plan. We also compared the performance of these programs on other types of synthetic graphs that contain cycles, including random graphs and scale-free graphs. spath does not terminate on these graphs (more details are discussed in Appendix B), while the results for the other three programs are similar to that of Figure A 1, and are omitted here due to space constraints.

Results on Real World Graphs. We only report the results for spath\_xy, spath\_mmin and spath\_prem in Figure A 2, as spath does not terminate due to the presence of cycles in these graphs. We observe a similar trend as in the results on synthetic graphs—the time of spath\_prem is very close to that of spath mmin, with spath xy always being the slowest, about 3× slower than the other two programs. This is again due to the more complex plan used by the XY-stratified program that besides usability also impacts performance on a single-processor machine. In fact we have reasons to suspect that the performance benefits of PREM aggregates in recursion over aggregates in XY-stratified programs might become substantial on parallel implementations, and this proposes an important topic deserving further investigation. Indeed, while scalable performance through parallelism of programs with PREM aggregates was amply demonstrated in (Shkapsky et al. 2015; Yang et al. 2015), the parallelization of XY-stratified program largely remains a topic for future research.

Overall, the optimized program obtained by transferring the aggregate into the recursive rules achieves basically the same performance as the program that uses monotonic aggregates, and much better performance than the original stratified program, and also speed-ups that are twice or better than those of XY-stratified program running on DeALS<sup>4</sup>.

## **Appendix B Programs Used in Experiments**

Example 7 (Shortest path from node a with stratified aggregates.)

```
\begin{array}{ll} \mathtt{path}(\mathtt{Y},\mathtt{Dy}) \leftarrow & \mathtt{arc}(\mathtt{a},\mathtt{Y},\mathtt{Dy}). \\ \mathtt{path}(\mathtt{Y},\mathtt{Dy}) \leftarrow & \mathtt{path}(\mathtt{X},\mathtt{Dx}),\mathtt{arc}(\mathtt{X},\mathtt{Y},\mathtt{Dxy}),\mathtt{Dy} = \mathtt{Dx} + \mathtt{Dxy},\mathtt{Dy} > \mathtt{Dx}. \\ \mathtt{spath}(\mathtt{Y},\mathtt{min}\langle\mathtt{Dy}\rangle) \leftarrow & \mathtt{path}(\mathtt{Y},\mathtt{Dy}). \end{array}
```

This program is the same as the program in Example 3, except that we added Dy > Dx to the recursive rule to avoid integer overflow problems in evaluating Dy = Dx + Dxy. The computation of spath does not terminate on graphs that contain cycles, unless we enforce an upper bound constraint for values that represent the path length. In our experiments, we used 32-bit signed integers and this establishes an implicit upper bound constraint. But in our experiments we never reached that upper bound since we ran out of memory on our test machine that comes with a 256 GB of memory.

Example 8 (Shortest path from node a after the transfer of the min constraint)

```
\begin{split} & \operatorname{\texttt{path}}(Y, \operatorname{\texttt{min}}\langle Dy \rangle) \leftarrow & \operatorname{\texttt{arc}}(a, Y, Dy). \\ & \operatorname{\texttt{path}}(Y, \operatorname{\texttt{min}}\langle Dy \rangle) \leftarrow & \operatorname{\texttt{path}}(X, Dx), \operatorname{\texttt{arc}}(X, Y, Dxy), Dy = Dx + Dxy, Dy > Dx. \\ & \operatorname{\texttt{spath\_prem}}(Y, Dy) \leftarrow & \operatorname{\texttt{path}}(Y, Dy). \end{split}
```

Example 9 (Shortest path from node a with XY-stratification)

```
\begin{split} \text{delta\_path}(0,Y,Dy) \leftarrow & \text{arc}(\texttt{a},Y,Dy). \\ \text{delta\_path}(\texttt{J}+1,Y,\texttt{min}\langle \texttt{Dy}\rangle) \leftarrow & \text{delta\_path}(\texttt{J},X,\texttt{Dx}), \texttt{arc}(\texttt{X},Y,\texttt{Dxy}), \\ & \text{Dy} = \texttt{Dx} + \texttt{Dxy}, \texttt{Dy} > \texttt{Dx}, \\ & \text{if}(\texttt{all\_path}(\texttt{J},Y,\texttt{D}) \text{ then } \texttt{D} > \texttt{Dy}). \\ \text{all\_path}(\texttt{J}+1,Y,\texttt{Dy}) \leftarrow & \text{all\_path}(\texttt{J},Y,\texttt{Dy}), \neg \text{delta\_path}(\texttt{J}+1,Y,\_). \\ \text{all\_path}(\texttt{J},Y,\texttt{Dy}) \leftarrow & \text{delta\_path}(\texttt{J},Y,\texttt{Dy}). \\ \text{last\_step}(\texttt{J}) \leftarrow & \text{delta\_path}(\texttt{J},\_,\_), \neg \text{delta\_path}(\texttt{J}+1,\_,\_). \\ \text{spath\_xy}(Y,\texttt{Dy}) \leftarrow & \text{last\_step}(\texttt{J}), \text{all\_path}(\texttt{J},Y,\texttt{Dy}). \end{split}
```

The evaluation plan of this program is very complex—there are 120 nodes in the corresponding AND/OR tree, while both AND/OR trees of spath and spath\_prem have only 15 nodes.

<sup>&</sup>lt;sup>4</sup> While DeALS has been shown to deliver better than competitive performance when compared with state-of-the-art systems such as DLV (Leone et al. 2006), Clingo (Gebser et al. 2014), and LogicBlox (Aref et al. 2015), such comparisons would take us beyond the scope of this paper, since the goal of our experimental evaluation was to determine the performance of different techniques on the same problem, same system and same runtime.

Example 10 (Shortest path from node a with monotonic aggregates)

```
\mathtt{arc}(\mathtt{a},\mathtt{Y},\mathtt{Dy}).
path(Y,mmin\langle Dy\rangle) \leftarrow
path(Y,mmin\langle Dy \rangle) \leftarrow
                                               path(X, Dx), arc(X, Y, Dxy), Dy = Dx + Dxy, Dy > Dx.
\operatorname{spath}_{\min}(Y,\min(Dy)) \leftarrow \operatorname{path}(Y,Dy).
```

This program is evaluated using Monotonic Aggregate Seminaive Evaluation (MASN) (Shkapsky et al. 2015), with an evaluation plan akin to that of Example 8.

## Appendix C Discussion

In this paper we have proposed a new fixpoint approach to the semantics of recursive programs with aggregates, which is conducive to efficient implementation and to a concise logic-based formulation for many basic algorithms. However the solution proposed here also has some important limitations, and does not eliminate the desirability of other past proposals including the many discussed in (Gelfond and Zhang 2014). It is also important that these limitations be understood by the Datalog programmers and compiler writers, since the enthusiasm for Datalog in BigData applications has recently lead some researchers to develop parallel systems that support recursive programs with aggregates, without providing a formal declarative semantics for program. In the absence of a formal declarative semantics, it becomes difficult to prove the correctness of a given implementation, and the risk that the same program might return different results on different platforms becomes a serious concern. A simple example of a program that cannot be optimized by pushing extrema constraints is given below:

Example 11 (Max constraint that cannot be pushed into recursion)

```
p(2).
p(5).
p(J1) \leftarrow p(J), J \le 10, J \ne 5, J1 = J + 2.
topp(J1) \leftarrow p(J1), is\_max(()(J1)).
```

In the iterated fixpoint computation of this program we obtain the following values for the argument of p: 2 and 5 at the first step; then 2, 5, 4, at the second step; then 2, 4, 5, 6, at the third step, then 2, 4, 5, 6, 8, and 2, 4, 5, 6, 8, 10 at the final step, whereby the topp result is 10.

However if we pre-apply the max to the facts and rules defining p, we obtain 5 at the first step and 5 again the second step, since the rule produces no result. Thus the fixpoint iteration over the constrained rules terminates by producing an incorrect result: i.e. the value 5 instead of 10.

While most programmers faced with the previous example will figure out that the max cannot be transferred into recursion, the question on whether the program in Example 4 and the following program are equivalent might not be easy for users to resolve without the notion of pre-applicability.

Example 12 (A simple variation of the program in Example 5)

```
attend(X) \leftarrow organizer(X).
attend(Y) \leftarrow cntfriends(Y, N).
cntfriends(Y,N) \leftarrow attend(X), friend(Y,X), mcount((Y),(X),N).
\texttt{f\_attend}(\texttt{X}) \leftarrow \texttt{cntfriends}(\texttt{X}, \texttt{Nfx}), \texttt{Nfx} \geq \texttt{3}.
```

Now, while the original Example 4 can indeed be obtained from the program in Example 12 above, by transferring  $Nfx \ge this$  does not assure that the names of friends returned by  $f_{attend}$  above are the same as those of attend in Example 5. However the fact that the max constraint is PREM. suggests that equivalence does not hold either, and simple counter-examples are in fact easy to construct  $^5$ .

The next example uses a variation from the example proposed by Ross and Sagiv (Ross and Sagiv 1992) to illustrate problems and alternative solutions for programs with aggregates.

Example 13 (A program with multiple minimal models)

```
\begin{split} &p(b).\\ &q(b).\\ &cq(C) \leftarrow &q(X), \texttt{mcount}((),(X),C).\\ &p(a) \leftarrow &cq(C), C=1\\ &cp(C) \leftarrow &p(X), \texttt{mcount}((),(X),C).\\ &q(a) \leftarrow &cp(C), C=1. \end{split}
```

This is a monotonic program, which has as least-fixpoint: p(a), p(b), cp(1), cp(2), q(a), q(b), cq(1), cq(2). However we cannot replace the monotonic counts with the standard counts since the transfer of max is incompatible with the "= 1" condition. If we remove the two "= 1" conditions, then the program obtained by replacing mount with count has a least fixpoint semantics and will return p(a), p(b), cp(2), q(a), q(b), cq(2). Finally, if we remove C=1 from the last rule, we can replace mount with count in the previous, and we obtain the following model: p(a), p(b), cp(2), q(a), q(b), cq(1), cq(2).

## Appendix D Additional References

GEBSER, M., KAMINSKI, R., KAUFMANN, B., AND SCHAUB, T. 2014. Clingo= asp+ control: Preliminary report. *arXiv preprint arXiv:1405.3694*.

LEONE, N., PFEIFER, G., FABER, W., EITER, T., , ET AL. 2006. The DLV system for knowledge representation and reasoning. *TOCL* 7, 3, 499–562.

<sup>&</sup>lt;sup>5</sup> E.g., a clique of three friends where one views an organizer as a friend satisfies Example 12 but not Example 5.