

CallE: An Effect System for Method Calls

Isaac Oscar Gariano
Victoria University of Wellington
Wellington, New Zealand
isaac@ecs.vuw.ac.nz

James Noble
Victoria University of Wellington
Wellington, New Zealand
kjx@ecs.vuw.ac.nz

Marco Servetto
Victoria University of Wellington
Wellington, New Zealand
Marco.Servetto@ecs.vuw.ac.nz

Abstract

Effect systems are used to statically reason about the *effects* an expression may have when evaluated. In the literature, such effects include various behaviours as diverse as memory accesses and exception throwing. Here we present CallE, an object-oriented language that takes a flexible approach where effects are just *method calls*: this works well because ordinary methods often model things like I/O operations, access to global state, or primitive language operations such as thread creation. CallE supports both flexible and fine-grained control over such behaviour, in a way designed to minimise the complexity of annotations.

CallE's effect system can be used to prevent OO code from performing privileged operations, such as querying a database, modifying GUI widgets, exiting the program, or performing network communication. It can also be used to ensure determinism, by preventing methods from (indirectly) calling non-deterministic primitives like random number generation or file reading.

CCS Concepts • Software and its engineering → Object oriented languages; Language features; Imperative languages; • Theory of computation → Type structures.

Keywords object oriented languages, type and effect systems, side effects, static type systems

ACM Reference Format:

Isaac Oscar Gariano, James Noble, and Marco Servetto. 2019. CallE: An Effect System for Method Calls. In *Proceedings of the 2019 ACM SIGPLAN International Symposium on New Ideas, New Paradigms, and Reflections on Programming and Software (Onward! '19)*, October 23–24, 2019, Athens, Greece. ACM, New York, NY, USA, 14 pages. <https://doi.org/10.1145/3359591.3359731>

Onward! '19, October 23–24, 2019, Athens, Greece

© 2019 Copyright held by the owner/author(s). Publication rights licensed to ACM.

This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in *Proceedings of the 2019 ACM SIGPLAN International Symposium on New Ideas, New Paradigms, and Reflections on Programming and Software (Onward! '19)*, October 23–24, 2019, Athens, Greece, <https://doi.org/10.1145/3359591.3359731>.

1 Introduction

Type and effect systems (or just *effect systems*) were originally introduced to reason about the purity of code in functional programming languages [5]; since then they have been applied to reason about many other properties of code such as memory accesses [20, 26] and exception throwing [7]. Such pre-existing effect systems typically only have a small pre-defined set of effects, such as `init(ρ)/read(ρ)/write(ρ)` (where ρ is a memory region variable), or `throws \bar{T}` (where \bar{T} is a list of exception types) [7]. Other limitations that have been identified are that they require complex and verbose source code annotations in order for library code to be useful [24].

Here we focus on the general problem of restricting the use of library defined *effectful* operations: such as I/O or (indirect) access to private global state. We present an OO language, CallE¹, which uses an effect system that works neatly with the OO concepts of sub-typing and generics, without requiring separate features like effect polymorphism [15].

Like other effect systems, CallE works by typing each expression with a list of *effects*: here effects are *method names*, indicating *behaviour* that may occur at runtime; the effects of an *expression* are simply the names of all the methods it *directly* calls in any sub-expression. Thus performing an *effect* simply corresponds to calling a method: what this means is up to the individual method in question.

Methods must be declared with an `effect[\bar{e}]`² annotation, where the list of effects \bar{e} represents an *upper-bound* on the method's behaviour: its body can only have the behaviour of an expression with effects \bar{e} . This *doesn't* mean that the list of methods it calls is exactly \bar{e} , rather we allow the body to have any *sub-effect* of \bar{e} . In particular, a method declared with (a sub-effect of) the empty list is *uneffectful*: it can be called by any method (including other uneffectful ones). Other methods are however *effectful*, and can only be called by methods with a sufficiently strong `effect` annotation.

CallE is designed to minimise the complexity of such annotations, whilst still allowing useful reasoning as to when effectful methods can be called; the core mechanism by which we do this is the following novel rule:

The Indirect-CallE Rule: *If a method $T.m$ is annotated with `effect[\bar{e}]`, then $T.m$ is a sub-effect of \bar{e} . In particular,*

¹CallE is pronounced like 'callee'; the E stands for 'effect'.

²We use the notation \bar{e} to represent a list e_1, \dots, e_n , for some $n \geq 0$.

$T.m$ can be called by any method annotated with (super-effects of) $\bar{\epsilon}$.

This rule makes sense because $T.m$ can only have the behaviour allowed by $\bar{\epsilon}$. Note that the inverse does not hold: it is unlikely that one can perform the equivalent of arbitrary calls to methods in $\bar{\epsilon}$ by simply calling $T.m$.

The following example library for interacting with the console illustrates the core parts of CallE³:

```
class Console {
  // Trusted I/O method that prints to the console,
  // defined in a possibly different language.
  foreign static Void print(Char c) effect[print];

  // Utility method to print a whole string at a time
  static Void print-str(String s) effect[print] =
    for (Char c in s) print(c);

  // Prints a line
  static Void print-line(String s) effect[print] =
    print-str(s + "\n");

  // Reads a single character from the console
  foreign static Char read() effect[read];
  ... }

```

Here `print` is declared with `effect[print]`; this ensures that the Indirect-CallE rule only applies to effects already containing `print`: only a method that lists `print` in its `effect` annotation can directly call it.⁴ Now we have `print-str` which is declared with `effect[print]`: meaning the only effectful behaviour it can perform is that of the `print` method (the only effectful method called).⁵ Now consider `print-line`, instead of implementing it with a loop like `print-str`'s, the Indirect-CallE allows it to simply call the `print-str` method. This demonstrates the main justification behind the Indirect-CallE: one can obtain the same behaviour as `print-str` by only calling `print` (together with uneffectful methods). Note that none of these `print-` methods can (indirectly) call `read`, as `read` is not in their `effect` annotations, neither is any method that (transitively) has the `read` effect.

Now consider the following example:

```
static Void hello() effect[Console.print] = (
  restrict[] Untrusted.untrusted();
  Console.print-line("Hello World"));

```

A `restrict[$\bar{\epsilon}$]` e expression ensures that the effects of e are sub-effects of $\bar{\epsilon}$. In the case above, since $\bar{\epsilon} = \epsilon$, the type checker will check that the `untrusted` effect is a sub-effect

³CallE is an expression based language, which uses semicolons as the conventional sequencing operator.

⁴As `foreign` methods do not have a body which we can type-check, we do not restrict their effect annotation. An implementation however may wish to restrict this, such as by fixing the effect annotations for `foreign` methods declared by untrusted source code.

⁵We assume that pure operations (such as iteration and addition) on standard types (like `String` and `Int`) are all declared with `effect[]`: i.e. they are uneffectful.

of the empty-effect, i.e. it is declared to not (transitively) call any effectful methods. Assuming that all other I/O methods provided by the standard library are effectful, we can be sure that the only I/O `hello` will perform is to print 'Hello World!'. Note that the Indirect-CallE rule allows `hello` to call `print-line`, just as it allowed `print-line` to call `print`.

The Indirect-CallE rule is particularly flexible as it allows for abstraction: the implementation details of the `hello` method are not exposed by its effect annotation (we know that it *may* eventually call `print`, but not that it does so by calling `print-line`). This is particularly important if `print-line` were to be a private method, then mentioning it in the effect annotation of `hello` would expose its existence to the public. Providing a more specific effect annotation than the Indirect-CallE rule requires can however allow for stronger reasoning: if `hello` were to be annotated with `effect[print-line]`, we can be sure that everything it outputs will be terminated by a newline. In order to perform such reasoning, *callers* of `hello` only need to look at the body of `print-line`, they need not look at the body of `hello` itself. This however shows a disadvantage of our system: to modify `hello` to enable such reasoning we have to look at its body and expose more implementation details in its effect annotation.⁶

This same line of reasoning we did on `Console.read` works with any other effectful operations one can define as methods, such as `File-System.append`, `Thread.spawn`, `Socket.write`, `Program.exit`, or `Random.generate` methods.

1.1 Contents

The rest of the paper is structured as follows:

- In Section 2 we explain how CallE's effect system works in the context of OO, in particular dynamic dispatch and generics.
- In Section 3 we demonstrate how CallE's effects can be used to reason about library defined behaviour, including operations on global state, creation of new instances of a class, and restricted forms of I/O.
- In Section 4 we present a minimal grammar for CallE and the typing rules for the novel parts of CallE's type system, in particular the sub-effect relation. The remaining non-novel parts of our type system are presented in Appendix A. We do not present a formalism of the runtime semantics, since they are merely a sub-set of Featherweight Generic Java's [9].
- In Section 5 we outline how we might add three additional features to CallE. In particular, we show how effects can be combined with generic type parameter

⁶Effect annotations are similar to return type specifications: one can expose more implementation details by declaring more specific return types. For example, consider `List foo() = new Linked-List()`; `foo` could expose more implementation details by specifying `Linked-List` as its return type, or it could expose less useful information by specifying `Object`.

variance, dynamic code loading/invoke, and method redirection.

- In Section 6 we present two larger use cases for CallE’s effect system: preventing security vulnerabilities caused by database accesses, and preventing untrusted advertisement code from modifying parts of a GUI.
- In Section 7 we informally make two statements of soundness, and provide sketches for their proofs.
- In Section 8 we discuss related work, and show how CallE compares.
- Finally, in Section 9 we summarise our results and conclude.

2 Object-Orientation with Effects

2.1 Dynamic Dispatch

Like many other effect systems, a method’s `effect` annotation represents an *upper* bound. In particular, they can list more methods than are actually called. This works well together with sub-typing and dynamic dispatch:

```
interface UI-Element {
  Void paint() effect[UI.set-pixel];
  List<UI-Element> children() effect[];
  ... }

static Void paint-all(UI-Element e) effect[UI.set-pixel] = (
  e.paint(); // well typed, by the Indirect-CallE rule
  for (UI-Element c in e.children()) paint-all(c);
  ... )
```

As in the above `paint-all` method, the Indirect-CallE rule always allow recursive calls, since they cannot be used to perform additional effectful behaviour. From the above code, we know that the only effectful behaviour `paint-all` can do is that of `UI.set-pixel`; however what `UI.set-pixel` calls will actually occur is up to the implementation of `paint` for the specific `UI-Elements` given. For example, consider the following:

```
class Empty-Element: UI-Element {
  Void paint() effect[] = skip; // Don't do anything
  List<UI-Element> children() effect[] = {}; // Empty list
  ... }
```

As with many other OO languages, we allow method types to be refined: the effects in a method’s `effect` annotation must be sub-effects of those in the methods it is overriding. Thus the above code is valid since `Empty-Element.paint` is declared to have no effects, which are vacuously sub-effects of `UI.set-pixel`.

2.2 F-Bounded Polymorphism

Many object-oriented languages support F-bounded polymorphism for generic code, such as in the following typical use case:

```
interface Hashable<T> {
  Bool equals(T other);
  Int hash(); }
class Hash-Map<Key: Hashable<Key>, Value> {
```

```
// Needs to call Key.hash and Key.equals
Value get(Key k) = ...;
... }
```

But what `effect` annotation should the above methods have? The `Hash-Map` and `Hashable` classes are likely to be used by lots of very different code with different desires. For example, some users of `Hash-Map` might want to ensure that accessing elements won’t perform any I/O, which some implementations of `Hashable.hash` will perform. However, some users may not mind if I/O is performed, and one may wish to implement `Hashable.hash` using a hardware random number generator. It may seem that one cannot provide a single `Hash-Map` class that is simultaneously usable in these cases. However, note how the `Hash-Map` class is already generic on the `Key` type, different `Key` types can cause `get` to perform different behaviour at runtime. This means we need not restrict the effects of the methods in `Hashable`: rather we can look at the effects for a given `Key`. As such, we will annotate the methods of `Hashable` with the special wildcard effect `*`, which is a super effect of all other effects (i.e. CallE does not restrict the behaviour/method calls of a method declared with the `*` effect):

```
interface Hashable<T> {
  Bool equals(T other) effect[*];
  Int hash() effect[*]; }
class Hash-Map<Key: Hashable<Key>, Value> {
  Value get(Key k) effect[Key.equals, Key.hash] = ...;
  ... }
```

This is particularly neat as we do not require separate generic parameters for effects, as is usual in effect system [13], rather we can just use a normal type-parameter to abstract over effects. In particular, note how the effect of `get` depends on a generic type parameter: if we have more information about the `Key` type, we know more about `get`:

```
interface Random-Hashable<T>: Hashable<T> {
  Bool equals(T other) effect[];
  Int hash() effect[Random.generate]; }

static Void f<K: Random-Hashable<K>, V>(Hash-Map<K, V> m, K k)
  effect[Random.generate] = m.get(k);
```

The Indirect-CallE rule allows the last line to type check: we know that any subtype of `Random-Hashable` must respect its interface, in particular its `hash` and `equals` methods must be declared with sub-effects of `Random.generate`. Note how even though we used the all-powerful `*` effect when declaring `Hashable`, we have not lost the ability to reason since the effect can be arbitrarily refined by implementing classes/interfaces (such as `Random-Hashable` above).

3 Reasoning Power

Here we present examples showing the kind of reasoning CallE allows. In particular, we show how libraries can define new effectful methods in order to reason about the behaviour of untrusted code, provided that such code is type-checked.

3.1 Indirect Effects

Consider a library for operating on the file system and a `log` function that uses this library:

```
class File-System {
  // Appends text to filename
  foreign static Void append(String filename, String text)
    effect[append];
  ... }

static Void log(String text) effect[File-System.append] =
  File-System.append("log.txt", text);

static Void do-something() effect[log] = ...;
```

Assuming that all methods that operate on the file system (such as `append`) are effectful, we can be sure that the only such operation that `do-something` can perform is to append to `log.txt`. This only requires inspecting the code of `log` itself; the body of `do-something` is irrelevant, since our effect system will ensure that it can't call effectful operations (such as `File-System.append`) unless their only possible effects are calls to `log`. Note how the effects of an expression are not the same as its *indirect effects*: `do-something` does *not* have the `File-System.append` effect, but it does indirectly, through the `log` effect.

In particular, the above example shows why it can be useful to declare more specific effects: if the programmer doesn't mind if the log file is appended, they can safely call `do-something`, even if they wouldn't trust `do-something` to append to *arbitrary* files. If a programmer is however unfamiliar with `log`, if it is dynamically dispatched, or if it has no source code to inspect, then the programmer can look at its `effect` annotation to see that `do-something` might indirectly call `File-System.append`, but not `Console.read`. A tool (such as an IDE) could help with such an investigation by providing a graph of all (indirect) effect annotations; doing so only requires that method signatures be available, not their bodies.

Alternatively, thanks to the Indirect-CallE rule, if there is a specific set of effects that the programmer trusts, they can use our `restrict` expression (see Section 1) without looking at any other effect annotations.

3.2 Object Creation

Consider granting an untrusted component read access to files, but only those in a runtime-determined list of files/folders. One way to do this would be to give the component a list of paths to each file/folder it can read; then by preventing the component from creating new file paths, we can be sure that only those files are read:

```
class Path {
  // Converts 's' to a Path object
  static Path parse(String s) effect[parse] = ...;
  // Appends the given file/directory name to the path
  Void append-path(String suffix) effect[] = ...;
```

```
// Reads the contents of the identified file
String read() effect[read] = ...;

// Assuming a private constructor
... }

static Void untrusted(List<Path> allowed-paths)
  effect[Path.read] = ...;
static Void trusted() effect[Path.parse, Path.read] =
  untrusted({Path.parse("~/"), Path.parse("/tmp/")});
```

Since `untrusted` is not declared with the `Path.parse` effect, we can be sure that it can't create new `Path` objects out of thin air; rather it can only read from folders it obtains from elsewhere. In the above call to it in `trusted`, we can be sure that it can only read from the user's home directory, or the system wide `tmp` directory (this however does require the absence of any other pre-existing `Paths` accessible through global variables).

3.3 Global State

As an `effect` annotation represents an upper bound, we can provide effects which are stronger than necessary to type check the methods body. This has two important advantages: method signatures can be more resilient to implementation changes, and one can make 'privileged' methods harder to call. The second part is very useful: it allows one to declare new *effectful* operations, even if their bodies are not otherwise effectful. Recall the UI example from Section 2.1, we mentioned a `set-pixel` function, but what is it? It could be an externally defined method like our `print` function from Section 1. Alternatively, we could implement it with a global variable, and delay updating the actual display till later:

```
class UI {
  // 'global' variable
  private static Array2D<Pixel> pixels = ...;
  Void set-pixel(Pixel p, Int x, Int y) effect[set-pixel] =
    // Assuming that set is not an effectful method
    pixels.set(x, y, p);

  // The window will only update when this is called
  static Void update-display() effect[update-display] =
    set-window(pixels);

  // Defined externally, probably by the OS/Window Manager
  private foreign static Void set-window(Array2D<Pixel> p)
    effect[];
  ... }
```

Notice that we haven't marked the `set-window` function as effectful: since it is `private`, one merely needs to inspect the code for the `UI` class to know that the only way for it to be called is through the effectful `update-display` method. Since we do not restrict the effect annotations of `foreign` methods, we allow this, even though one may semantically consider `update-display` to be 'effectful'. In fact, marking `set-window` as effectful could break encapsulation, by requiring the signature of the public `update-display` method to modify its `effect` annotation.

$$\begin{array}{c}
\boxed{\Delta \vdash \bar{\varepsilon} \leq \varepsilon'} \\
(\leq_{\text{REF}}) \frac{\{\bar{\varepsilon}\} = \{\varepsilon'\}}{\Delta \vdash \bar{\varepsilon} \leq \varepsilon'} \\
(\leq_T) \frac{\Delta \vdash T \leq T'}{\Delta \vdash T.m \leq T'.m} \\
(\leq_{\text{TRANS}}) \frac{\Delta \vdash \bar{\varepsilon} \leq \varepsilon' \quad \Delta \vdash \varepsilon' \leq \varepsilon''}{\Delta \vdash \bar{\varepsilon} \leq \varepsilon''} \\
(\leq_{C.m}) \frac{\Sigma(C.m) = _ \mu \langle _ \rangle (_) \text{effect}[\bar{\varepsilon}] _ ;}{\Delta \vdash C.m \leq \bar{\varepsilon}} \\
(\leq_{\text{COMP}}) \frac{\Delta \vdash \bar{\varepsilon}_1 \leq \varepsilon'_1 \quad \Delta \vdash \bar{\varepsilon}_2 \leq \varepsilon'_2}{\Delta \vdash \bar{\varepsilon}_1, \bar{\varepsilon}_2 \leq \Delta \vdash \varepsilon'_1, \varepsilon'_2} \\
(\leq_*) \frac{}{\Delta \vdash \bar{\varepsilon} \leq *} \quad (\leq_\varepsilon) \frac{}{\Delta \vdash \varepsilon \leq \bar{\varepsilon}}
\end{array}$$

Figure 1. Sub-effect Rules

Since `set-pixel` does not contain any calls to effectful methods,⁷ we could have annotated it with `effect[]`. By annotating it with `effect[set-pixel]`, we can now reason as to what methods can call it. As in our `print` example from Section 1, a method $T.m$ can only *directly* call `set-pixel` if $T.m$ is annotated with `effect[... , set-pixel, ...]`. Similarly, $T.m$ can *indirectly* call `set-pixel` only if $T.m$ is annotated with `effect[... , T'.m' , ...]` and $T'.m'$ can directly or indirectly call `set-pixel`. In particular, after checking that no other code in `UI` modifies `pixels`, we can be sure that a method call to $T.m$ could modify `pixels` only if the effect annotation of $T.m$ allows it to indirectly call `set-pixel`.

4 Formalism

We will now present a formalism of CallE, focusing on the novel parts of our effect system. Our language is based on Featherweight Generic Java (FGJ) [9], but in order to keep our formalism simple and our discussion focused on our effect system, we have minimised the number of language features we have formalised. In particular, we do not formalise generic classes (only generic methods) or *user defined* constructors. In addition, we support interfaces and only a limited form of inheritance: classes can inherit from multiple super interfaces, interfaces can not inherit from other interfaces, and classes cannot be inherited. Though our examples used such features, as well as additional ones such as accessibility control, static methods, mutable state, and global variables, we do not include them in our formalism as they do not make the novel parts of our language more interesting.

In addition, we do not present reduction rules, as CallE's only novel runtime expression (`restrict[$\bar{\varepsilon}$] e`) has a trivial reduction (namely `restrict[$\bar{\varepsilon}$] e \rightarrow e`), rather we refer to FGJ for our runtime semantics. Note that as is conventional with statically typed-languages, we assume that the expression that is being reduced (i.e. the 'main expression') is initially well-typed; however we do not impose any restriction on what such an expressions types or effects are.

⁷For simplicity, CallE only treats method calls as effectful; if we wished to restrict when `static` variables can be read/written, we could type such expression with effects such as `static-read/static-write`, where for the purposes of the effect system, `static-read/static-write` are the names of some predefined effectful methods.

4.1 Grammar

We will use the meta-variables x , f , and μ as identifiers for variables, fields, and methods (respectively). Similarly, C and X identify classes/interfaces and generic type parameters, respectively. The abstract syntax of CallE has the following grammar:⁸

$$\begin{array}{l}
T ::= C \mid X \\
m ::= \mu \langle \bar{T} \rangle \\
S ::= T \mu \langle \bar{X} : \bar{C} \rangle (\bar{T} \bar{x}) \text{effect}[\bar{\varepsilon}] \\
D ::= \text{class } C(\bar{C} f) : \bar{C}'' \{ \bar{S} = e ; \} \mid \text{interface } C \{ \bar{S} ; \} \\
e ::= x \mid \text{new } C(\bar{e}) \mid e.f \mid e.m(\bar{e}') \mid \text{restrict}[\bar{\varepsilon}] e \\
\varepsilon ::= * \mid T.m
\end{array}$$

A *type*, T , is either the name of a class or a generic type parameter. A *method selector*, m , is a method name μ , provided with \bar{T} for its type parameters. A *method signature*, S , specifies a return type T , a method name μ , generic parameters \bar{X} (with upper bounds \bar{C}), parameter names \bar{x} (with types \bar{T}'), and a list of effects $\bar{\varepsilon}$. A (top-level) declaration, D , either declares a *class* C with fields \bar{f} (of types \bar{C}'), implemented interfaces \bar{C}'' , and method implementations with signatures \bar{S} and bodies \bar{e} ; or declares an *interface* with name C requiring the method signatures \bar{S} . An expression e is either a variable name, a `new` expression, a field access, a method call, or an effect restriction. Finally, an *effect*, ε , either names the wildcard effect or a method.

Additionally, we will use $\Gamma : x \rightarrow T$ as a variable environment. We will use $\Delta : X \rightarrow C$ as a mapping of generic parameters to their upper bounds; to simplify our typing rules we will overload notation and define $\Delta(C) := C$, for any C . We will assume a global, and constant class table Σ , where $\Sigma(C)$ is the class or interface declaration for C . We assume the obvious definition for $\Sigma(C.\mu)$ to extract the method implementation/specification with name μ from the class/interface C (i.e. $\Sigma(C.\mu)$ will be of form $S = e$ or S). We also use $\Sigma(C.\mu \langle \bar{T} \rangle)$ to mean $\Sigma(C.\mu)[\bar{X} := \bar{T}]$, where \bar{X} are the generic parameters declared by $\Sigma(C.\mu)$, except that this substitution

⁸We use that notation $\bar{X} : \bar{C}$ to mean $X_1 : C_1, \dots, X_n : C_n$, for some $n \geq 0$; similarly for the other overbars. Overbars can also nest, for example $\mu \langle \bar{T} \rangle$ is shorthand form $\mu_1 \langle \bar{T}_1 \rangle, \dots, \mu_n \langle \bar{T}_n \rangle$, which is itself shorthand for $\mu_1 \langle T_{1,1}, \dots, T_{1,k_1} \rangle, \dots, \mu_n \langle T_{n,1}, \dots, T_{n,k_n} \rangle$. We use this interpretation since it is less ambiguous than the more common $\bar{X} : \bar{C}$, which we would interpret as meaning $X_1, \dots, X_n : C_1, \dots, C_n$.

does not apply to the occurrences of X on the LHS of a $' : '$ (i.e. when X is in a binding position).

4.2 The Sub-Effect Relation

The core novelty of our type system is our sub-effect judgement, $\Delta \vdash \bar{e} \leq \bar{e}'$, indicating that under the generic-parameter environment Δ , the effects \bar{e} are at most as effectful as \bar{e}' . Sections 1 & 2 informally describe when and why we allow this to hold; however here in Figure 1⁹ we formalise exactly when it holds. Our (\leq_{REF}) rule establishes \leq as reflexive, and that the order, and any duplication of effects is irrelevant. Our (\leq_{TRANS}) rule simply establishes transitivity, and (\leq_{COMP}) establishes that composing two sequences of effects preserves sub-effecting. The (\leq_T) rule says that our sub-effect relation is covariant with respect to sub-typing. Our ($\leq_{C.m}$) rule formalises our novel Indirect-CallE rule: the effects in the annotation of $T.m$ are super-effects of $T.m$. Finally our trivial (\leq_*) and (\leq_ϵ) rules simply establish $*$ and ϵ as the greatest and least effects, respectively. Note in particular that by applying (\leq_{REF}), (\leq_{COMP}), (\leq_ϵ), and (\leq_{TRANS}) rules together, we have that if \bar{e} is a subset of \bar{e}' , then \bar{e} is a sub-effect of \bar{e}' .

4.3 Expression Typing

We use typing judgements of the form $\Delta | \Gamma \vdash e : T | \bar{e}$ to check that the expression e , using variables/type-parameters in Γ/Δ has type T and effects \bar{e} . Most of the typing rules are pretty standard, and simply return the effects of each sub-expression (if an expression has no sub-expressions, this will be the empty list). However we have two non-standard rules: the rule for method calls, and the rule for our novel restrict expression:

$$\begin{aligned} & \Sigma(\Delta(T).m) = T'' \mu(_) (\overline{T'x}) _ ; \\ (\vdash e.m) \frac{\Delta \vdash T.m \quad \Delta | \Gamma \vdash e : T | \bar{e} \quad \Delta | \Gamma \vdash e' : T' | \bar{e}'}{\Delta | \Gamma \vdash e.m(e') : T'' | \bar{e}, \bar{e}', T.m} \\ (\vdash \text{restrict}) \frac{\Delta | \Gamma \vdash e : T | \bar{e}' \quad \Delta \vdash \bar{e}' \leq \bar{e}}{\Delta | \Gamma \vdash \text{restrict}[\bar{e}] e : T | \bar{e}} \end{aligned}$$

The ($\vdash e.m$) rule¹⁰ works in the usual way, but reports the called method as one of the expressions effects, along with the effects of the receiver and argument expressions. The ($\vdash \text{restrict}$) rule simply reports the types and effects of e , but checks that they are sub-effects of \bar{e} .

⁹We use underscores to match against an arbitrary sequence of syntax trees.

¹⁰As an abuse of notation, if a metavariable M appears somewhere in a formula under n overbars, then $M_{i_1, \dots, i_n, i_{n+1}, \dots, i_{n+k}} = M_{i_1, \dots, i_n}$, for all $n, k \geq 0$. This means that in the ($\vdash e.m : T$) rule, as Γ and Δ have occurrences with zero overbars above them, $\Delta_i = \Delta$ and $\Gamma_i = \Gamma$, for all i ; thus $\Delta | \Gamma \vdash e' : T' | \bar{e}'$ is equivalent to $\Delta | \Gamma \vdash e'_1 : T'_1 | \bar{e}'_1, \dots, \Delta | \Gamma \vdash e'_n : T'_n | \bar{e}'_n$.

4.4 Other Rules

Finally, we show CallE's two other typing rules that use our novel sub-effect relation:

$$\begin{aligned} & \boxed{C \vdash S = e} \\ (\vdash S = e) \frac{\vdash T \mu(\overline{X} : C') (\overline{T'x}) \text{effect}[\bar{e}]}{C \vdash T \mu(\overline{X} : C') (\overline{T'x}) \text{effect}[\bar{e}] = e} \frac{X \mapsto C' | \text{this} \mapsto C, x \mapsto T' \vdash e : T | \bar{e}'}{\bar{e}' \leq \bar{e}} \\ \hline & \boxed{\vdash \overline{S = e} \triangleleft S'} \\ (\overline{S = e} \triangleleft S') \frac{(T_1 \mu(\overline{X}_2 : C_1) (\overline{T'_1 x_1}) \text{effect}[\bar{e}_1]) (\overline{X}_2 := X_1) \in \overline{S = e} \quad \Delta = \overline{X}_2 \mapsto C_2 \quad \Delta \vdash \bar{e}_1 \leq \bar{e}_2}{\Delta \vdash T_1 \leq T_2 \quad \Delta \vdash T'_2 \leq T'_1 \quad \Delta \vdash C_2 \leq C_1} \frac{\Delta \vdash T_1 \leq T_2 \quad \Delta \vdash T'_2 \leq T'_1 \quad \Delta \vdash C_2 \leq C_1}{\vdash \overline{S = e} \triangleleft T_2 \mu(\overline{X}_2 : C_2) (\overline{T'_2 x_2}) \text{effect}[\bar{e}_2]} \end{aligned}$$

We use judgements of the form $C \vdash S = e$ to check that each method, $S = e$, of every class, C , is well typed. The ($\vdash S = e$) rule checks that S is well-typed, and that the expression e is well-typed under the appropriate variable and type-parameter contexts. The rule also checks that the effects of e are sub-effects of those in the `effect` annotation of S .

To check that a class with methods $\overline{S = e}$ correctly implements interfaces, we use judgements of the form $\vdash \overline{S = e} \triangleleft S'$, for each method signature S' in each implemented interface. Our ($\overline{S = e} \triangleleft S'$) rule allows the usual refinements: more specific return types, more general argument types and type-parameter bounds, as well as different (type) parameter names. In addition, we allow refining the `effect` annotation: a method's declared effects must be sub-effects of those declared by the signature that is being implemented.

The rest of our type system is otherwise standard, and is presented in Appendix A. We also assume the usual rules that classes, methods, fields, type-parameters and method-parameters are not declared with duplicate names.

5 Extensions

The discussion and formalism presented above for CallE is missing many potentially useful features; here we present an outline for three such extensions that would be worth exploring further in future work. In particular, we discuss allowing useful and sound dynamic code loading and reflective method invocation; adding support for both sub-type and sub-effect variance, with respect to generic type parameters; and the ability to alter the effects of a method based on the context it is called in. As these extensions are still works in progress, we do not formally define their semantics, but rather given an informal explanation for their semantics and use case.

5.1 Reflection and Dynamic Class Loading

One common feature in many OO languages is reflection, which can be used to *dynamically* invoke a method, without statically knowing whether it exists or has an appropriate signature. For example, consider:

```
reflect-invoke(Console.read(), 1)
```

Here `reflect-invoke` will, at runtime, find a method with whatever name the user typed into the console, check that it accepts an argument/receiver of type `Int`, and then invoke it with `1`. But what should the *effects* of `reflect-invoke` be? As we statically don't know anything about what method it may try and invoke, the only safe option would be for `reflect-invoke` to be declared with `effect[*]`. Alternatively, instead of `reflect-invoke` being a library function, we could make it a primitive form of expression, which takes an effect as an argument: `invoke[\bar{e}](e, \bar{e}')`. This expression will have the effects \bar{e} , as well as the effects of e and \bar{e}' . This will behave like `reflect-invoke(e, \bar{e}')`, except that it will dynamically check that the called method is a sub-effect of \bar{e} .

But what about dynamic class loading? This is one common use case for reflection, where a method won't actually exist until the program is run. Consider for example the following class:

```
class C { static Void foo() effect[C.foo()] = ...; }
```

Suppose we want to dynamically load and invoke `C.foo`:

```
static Void bar() effect[*] = (
  load-class(/* code for C above */);
  invoke[]("C.foo");
```

Will `bar()` produce a runtime error? `C.foo` is declared as effectful, so the dynamic invocation of it (with the empty effect) will not work. However, the reason it fails is because `C.foo` has `C.foo` in its `effect` annotation; since `C.foo` did not exist when the `invoke` expression was typed/compiled, the only way to call such dynamically loaded methods would be with the `*` effect. Instead, we propose ignoring the presence of any methods that did not exist when the `invoke` expression was type checked; formally this means that `invoke[\bar{e}]("T.m", ...)` will check that $T.m \leq_{\Sigma_0} \bar{e}$ where Σ_0 is the class table when the expression was type checked, and \leq_{Σ_0} is like \leq , but also with the following variation of the Indirect-CallE rule:

$$(\leq_{\Sigma_0}) \frac{\Sigma(\Delta(T).m) = _ \mu \langle _ \rangle \langle _ \rangle \text{effect}[\bar{e}'] _}{\bar{e}' \leq_{\Sigma_0} T'.m', \bar{e} \quad T'.m' \notin \text{dom}(\Sigma_0)}{\Delta \vdash T'.m' \leq_{\Sigma_0} \bar{e}}$$

A similar rule could also be added to allow calling methods with private methods in their effect annotation: in which Σ_0 will only contain declarations for *accessible* methods.

Though it is clear to us how `invoke` should work, formalising it would require non-trivial modifications to the FGJ runtime semantics.

5.2 Generic Type Parameter Variance

One likely useful addition is support for declaration-site¹¹ generic type parameter variance, as is supported by OO languages such as Scala, C#, and Kotlin. For example, consider the following interface for iterators:

```
interface Iterator<out T> { T next(); }
```

Here, as in C# and Kotlin, we use `out T` to declare that `T` is a *covariant* parameter: for any types `T` and `T'`, if `T` is a subtype of `T'` then `Iterator<T>` is also a subtype of `Iterator<T'>`. This makes sense since one can use an `Iterator<String>` as if it were an `Iterator<Object>`, since calling `next` on the former produces a `String`, which is a sub-type of `Object` (the type returned by calling `next` on the later). The usual rule for when an `out T` declaration is valid is that within the method signatures of the class, `T` only appears in a covariant position: in particular, the return type of a method is a covariant position.

It would make sense to use this feature together with effect annotations as well, for example consider the following contrived interface for logging objects:

```
interface Logger<in T> {
  Void log(T x) effect[File-System.append];
  Void log-all(Iterator<T> x) effect[Logger<T>.log]; }
```

Here we use `in T` to declare that `T` is a *contravariant* parameter: for any types `T` and `T'`, if `T` is a subtype of `T'` then `Logger<T>` is a *supertype* of `Logger<T'>`. This should be allowed when `T` only appears in contravariant positions. In particular, an argument type of a method is a contravariant position. We suggest also making the `effect` annotation a *covariant* position: if `T` is a subtype of `T'`, then our typing rules enforce that `T.m` is a sub-effect of `T'.m`. When types are used as generic parameters however, co and contra-variance gets more complicated. In general if `C<T>` is in a covariant position, and `C` is declared as taking a covariant type parameter, then `T` is also in a covariant position, otherwise if it is a contravariant parameter, then `T` is in a contra-variant position. On the other hand, if `C<T>` is in a contravariant position, then `T` is in a covariant (or contravariant) position if `C` takes a contravariant (or, respectively, covariant) type parameter. The above code is sound since `T` only appears in contra-variant positions: the argument type of `log`, as a covariant parameter to `Iterator` in the argument type of `log-all`, and as a contravariant parameter to `Logger`, which appears in the `effect` annotation (a covariant position) of `log-all`.

Now consider generic method parameters:

```
static Void secure-hash<out X: Hashable>(X x)
  effect[secure-hash, X.hash] = ...;
```

¹¹This is different to the more expressive, complex, and verbose *use-site* variance offered by Java's wildcards; although we could also extend CallE to support such a feature.

Since the only use of X in the effect annotation is in a covariant position, this example should type-check and mean that the *effect* of `secure-hash` is covariant with respect to X : if T is a sub-type of T' then `secure-hash<T>` is a sub-effect of `secure-hash<T'>`. This relation makes intuitive sense: if T is a subtype of T' then $T.hash$ is no more effectful than $T'.hash$, and so `secure-hash<T>` cannot be more effectful than the effect declaration of `secure-hash<T'>`. Note that at runtime however, calling `secure-hash<T>` could perform more effectful behaviour than calling `secure-hash<T'>`, but no more than the effect declaration of $T'.hash$ allows.

We have not formalised this kind of variance since this would be merely a simple straightforward extension over non-trivial prior work [4, 10].

5.3 Effect Redirection

One potentially useful feature would be to add something similar to effect *handlers* to CallE, as it could be particularly useful to redirect an effectful method to a less effectful one:

```
static Void untrusted() effect[Console.print] = ...;
static Void fake-print(String s) effect[] = skip;
static Void sandbox() effect[] =
  redirect[Console.print = fake-print] untrusted();
```

The idea is that `redirect[T.m = T'.m'] e` would execute e , but at runtime, whenever it tries to call $T.m(\bar{e})$, it actually calls $T'.m'(\bar{e})$.¹² Thus in the above example, we can be sure that `sandbox` prints nothing to the console. However formalising this with our effect system is non-trivial, for example suppose `untrusted` was instead declared with:

```
effect[Console.print, Console.read]
```

What should the effects of the `redirect` expression be? We could choose an upper bound such as `Console.read`, but that throws away the information that it was called through `untrusted`. Instead we are thinking of adding ‘substitution effects’ of the form $\varepsilon[T.m = \bar{e}']$, meaning the effect ε , except that any calls to $T.m$ will actually have sub-effects of \bar{e}' . In particular, we would have that $T.m[T.m = \bar{e}] \leq \bar{e}$. With this, the effects of `redirect[T.m = T'.m'] e` would be $\bar{\varepsilon}[T.m = T'.m']$ (where e has effects $\bar{\varepsilon}$). There are other sub-effect rules we could include: if $\varepsilon \leq \bar{\varepsilon}'$, then $\varepsilon[T.m = \bar{e}'] \leq \bar{\varepsilon}'[T.m = \bar{e}']$; if $\bar{\varepsilon}' \leq \bar{\varepsilon}''$, then $\varepsilon[T.m = \bar{e}'] \leq \bar{\varepsilon}''[T.m = \bar{e}']$; and $*$ \leq $*[T.m = \bar{e}]$. However we are not sure if there are more rules that would be useful, and if there is a smaller but equivalent set. Though our example shows that the type system using such substitution effects internally could be useful, we are not sure if exposing such additional complexity would be worthwhile. For example, would a programmer file the following annotation on `sandbox` useful or unnecessarily complex:

¹²We leave it to future work to determine how this should behave when either $T.m$ or $T'.m'$ are instance methods. For example, if $T.m$ is an instance method, it could redirect calls of the form $e.m(\bar{e}')$ to $T'.m'(e, \bar{e}')$. We could also allow $T.m = e.m'$ to redirect calls of the form $T.m(\bar{e}')$ to $e.m'(\bar{e}')$; this would be particularly useful if e were a lambda expression.

```
static Void sandbox()
  effect[untrusted[Console.print = fake-print]]
```

6 Larger Examples

In this section we show two larger examples demonstrating the practical benefits of CallE’s effect system. First we show how CallE can help prevent security vulnerabilities by restricting how code interacts with a database. Then we show how a graphical program can contain code for untrusted advertisements, whilst being sure they will not interfere with the rest of the program’s GUI.

6.1 Controlling Access to a Database

Consider an interactive program that wishes to communicate with an SQL database. There are several security vulnerabilities that could arise here: user input could be mistakenly processed as an SQL query (i.e. SQL injection), arbitrary SQL queries could be executed by untrusted components of the program, and sensitive data resulting from queries could be handled by such untrusted components. Here we show how our effect system can help prevent such potential vulnerabilities.

Consider the following sketch of a class for prepared statements:

```
class SQL-Statement {
  // Make a new prepared statement, with "?" as placeholders
  // for arguments (here Socket.read-write is a foreign
  // method that communicates with the database)
  static SQL-Statement prepare(String s)
    effect[prepare, Socket.read-write] = ...;

  // Execute the query replacing any "?"s with arguments
  SQL-Result execute(List<String> arguments)
    effect[execute, Socket.read-write] = ...;

  // Assuming a private constructor
  ... }
}
```

The idea is that a `Statement` is first made by calling `prepare`, using place-holders (“?”) wherever values from user-input might be inserted, and then providing the values for such place-holders by calling `execute`. For example, we could safely obtain the age of a given user:

```
SQL-Statement.prepare("SELECT age FROM Users WHERE name = ?")
  .execute({Console.read-line()})
```

This code is resilient to SQL injection because the arguments parsed to `execute` will not be treated as SQL syntax, but rather as plain text with no special meaning for any characters. This means that no matter what input the user writes, `execute` will return the `age` of all `Users` with the given `name` (if any). SQL injection can still occur if this API is misused:

```
SQL-Statement.prepare("SELECT age FROM Users WHERE name = '"
  + Console.read-line() + "'").execute({})
```


Now if the user types in ‘`! ; DROP TABLE Users --`’, the `Users` table will be deleted!

Because `prepare` is declared as effectful, and is not a sub-effect of `execute`, we only need to consider the code of any methods declared with super-effects of `prepare`, and check that no such code incorrectly passes user input to `prepare`. Any other code, even if it calls the `execute` method, cannot possibly cause SQL injection:

```
// Might cause SQL injection (perhaps param contains user
// input)
List<SQL-Statement> setup-queries(Object param)
  effect[SQL-Statement.prepare] = ...;

// Can't cause SQL injection, but can execute queries
SQL-Result run-queries(List<SQL-Statement> queries)
  effect[SQL-Statement.execute, Console.read] = ...;
```

We would also like to prevent untrusted code from looking at the potentially sensitive information retrieved by such queries. We can restrict this by making the results of such queries be wrappers over strings:

```
class SQL-Result(private String result) {
  String value() effect[value] = result; }
```

Because `value` is effectful, code without such an effect will see an `SQL-Result` as a black box: such code can pass around `SQL-Results`, but cannot inspect their internal state. Thus in order to understand how results from database queries are used, we do not need to reason about how `SQL-Results` are passed around, we only need to look at methods declared with (super effects of) the `value` effect and check that they do not inappropriately process or pass the result of `value`:

```
Bool is-adult(SQL-Result age) effect[SQL-Result.value] =
  Int.parse(age.value) ≥ 18;

// Can't know the exact age of users, but can check if they
// are adults
Void do-stuff(SQL-Statement age-query)
  effect[SQL-Statement.execute, is-adult] = ...;
```

6.2 Controlling Access to GUI Widgets

Suppose we have an app that contains untrusted advertisements which need to maintain their own GUI widgets, but must not modify other parts of the app’s GUI. One way of doing this is by ensuring that advertisement code is only given references to widgets it is allowed to modify [2]. This approach works best when there is a common ancestor widget all of whose descendants should be modifiable by the ad. Suppose we instead have a complicated GUI with many nested widgets, where some nodes should be modifiable by the advertisement, but not their parents or children.

We can use our effect system to statically ensure that advertisements do not attempt to modify properties of widgets they are not allowed to, and we can give the advertisement a

reference to the top-level widget, even if it is not itself modifiable by the advertisement. We can encode such a permission using an abstract method of an interface:

```
interface Permission { Void modify() effect[modify]; }
```

This interface is not designed to be instantiated by any concrete classes (although doing so will not cause problems), rather its method will be used in effect annotations. The idea is that a method marked with `effect[Permission.modify]` may modify properties of a widget, and can only be (directly) called by methods mentioning it or `Permission.modify` in their effect annotation.

We can create a proper sub-effect of `Permission.modify` by creating a sub-interface of `Permission`:

```
interface Ad-Permission: Permission { }
```

The `Ad-Permission` interface will inherit the method of `Permission` along with its effect annotation: `Ad-Permission` contains a `modify` method with ‘`Permission.modify`’ as its effect annotation. Since effects are covariant with respect to their receiver, we will have that `Ad-Permission.modify` is a sub-effect of `Permission.modify`; however the converse does not hold. Thus the `Permission.modify` effect is sufficient to call methods with `Ad-Permission.modify` in their effect annotation, but not vice versa.

At first glance it may seem like widget *classes* will need to be specifically written for the use of ads by mentioning the `Ad-Permission` interface. We can make such classes generic, thus encoding permission-generacity [23], and let *object* creation determine what permission to require:

```
interface Widget { ... }
// A sidebar with a stack of widgets on top of eachother
class Sidebar<P: Permission>(List<Widget> c): Widget {
  // Gets the indexth widget
  Widget get(Nat index) effect[] = c.get(index);

  // Sets the indexth widget
  Void set(Nat index, Widget widget) effect[P.modify] =
    c.set(index, widget); ...}
```

The idea is that the `P.modify` effect is sufficient to modify the children of a `Sidebar<P>`.¹³ We can now safely give an arbitrary widget to an advertisement, and be sure that it won’t modify any sidebars that were not created with `Ad-Permission`:

```
interface Ad {
  Void update(Sidebar<Permission> sb)
    effect[Ad-Permission.modify]; }

class Example-Ad(): Ad {
  Void update(Sidebar<Permission> sb)
    effect[Ad-Permission.modify] = (
    // Cast sb.get(0) to a type we can modify
    ((Sidebar<Ad-Permission>)(sb.get(0))).set(...));}
```

¹³Since the `Sidebar` class only uses `P` in effect annotations, we could have declared it with `out`, thus marking it as covariant (see Section 5.2). With this, one could use a `Sidebar<Ad-Permission>` as if it were a `Sidebar<Permission>`.

```

// Some nested sidebars, those created with <Ad-Permission>
// are modifiable by Ad, but those with <Permission> are not.
var sidebar1 = new Sidebar<Permission>(…);
var sidebar2 = new Sidebar<Ad-Permission>({sidebar1, …});
var sidebar3 = new Sidebar<Permission>({sidebar2, …});

Ad ad = …;
// Regardless of what the dynamic type of ad is, this won't
// modify sidebar1 or sidebar3, but could modify sidebar2.
ad.update(sidebar3);

```

For the above dynamic casts in [Example-Ad](#) to be sound we need generic reification (as in C^\sharp) instead of type erasure (as in Java). Though this does not require reification of any *effect* information (such as the `effect` annotations of methods or the sub-effect relation).

7 Soundness

In order to ensure that the reasoning we showed in Sections 3 & 6 is correct, we need to be sure that our type system enforces our interpretation of effects. In particular, we need to know what the *direct* effects of a method call could be, and what the *indirect* effects could be. To do this we will informally sketch the proofs of the two soundness statements.

First we define *direct soundness*: the effect annotations of method declarations are respected, even in the presence of dynamic dispatch and sub-typing:

Direct Soundness: *If a method $C.\mu\langle\bar{T}\rangle$ is annotated with $\text{effect}[\bar{e}]$, then a well-typed call to $\mu\langle\bar{T}\rangle$ on a receiver of (static) type C will directly reduce to an expression whose effects are (sub-effects of) \bar{e} .*

Proof Sketch: Our typing rule for method bodies, $(\vdash S = e)$, ensures that the effects of the method body (before any substitutions have occurred) are sub-effects of its `effect` annotation, which our refinement rule, $(\overline{S = e} \triangleleft S')$, ensures is a sub-effect of that of $C.\mu$.

Because our $(\leq T)$ rule ensures that method effects are covariant with respect to their receiver, and type preservation (which we inherit from FGJ) ensures that evaluation can only refine types, we can be sure that any (type) parameter substitutions that are performed by the method call can only refine the effects of the method body. Thus, after substitution has been performed, the effects of the method body will be sub-effects of those before substitution, and hence will also be sub-effects of the `effect` annotation of the (substituted) method declaration for $C.\mu\langle\bar{T}\rangle$. ■

Secondly, we define *indirect soundness*: the *only* effectful behaviour an expression with (sub-effects of) \bar{e} can perform is that allowed by the methods listed in \bar{e} :

Indirect Soundness: *If a well-typed expression has sub-effects of \bar{e} , and after reducing it any number of times, it contains a call to $C.m$, then either: (a) $C.m$ (or a method it overrides) is in \bar{e} , (b) the `effect` annotation of $C.m$ is (a sub-effect of) \bar{e} , or*

(c) the call to $C.m$ was (indirectly) introduced by the reduction of a call to a method (overriding one) in \bar{e} .¹⁴

Proof Sketch: This can be proved by induction on the depth of the call stack. In the base case the call was present in the initial expression. Because the receiver of the call may have been (partially) reduced, the call to $C.m$ was originally a call to $C'.m$, for some $C' \geq C$. Thus, by transitivity and covariance of our sub-effect relation (the $(\leq \text{TRANS})$ and $(\leq T)$ rules), we have $C.m \leq C'.m \leq \bar{e}$. By analysing our sub-effect rules, it can be seen that either $C.m$ (or a method it overrides) must be in \bar{e} (because the $(\leq T)$, $(\leq \text{REF})$, $(\leq \text{COMP})$, and $(\leq \epsilon)$ rules apply), or the Indirect-CallE rule applies (this trivially holds if $*$ is in \bar{e} or $C.m$ is uneffectful). Either way, case (a) or (b) holds.

In the inductive case, we will have that the call to $C.m$ was directly introduced by a call to a method $C'.m'$ satisfying case (a), (b), or (c). If $C'.m'$ satisfied case (a) or (c), then clearly $C.m$ now satisfies case (c). If $C.m$ does not satisfy case (c), then we must have that $C'.m'$ satisfied case (b). Let \bar{e}' be the effect annotation of $C'.m'$, then by direct soundness, case (b), and our sub-effect transitivity rule, $(\leq \text{TRANS})$, we have that $C.m \leq \bar{e}' \leq \bar{e}$. By the same logic we used above for the base case, we can conclude that case (a) or (b) holds for $C.m$. ■

Note that case (c) only says the call to $C.m$ was introduced by a call to one in \bar{e} . To further reason about $C.m$, one can either analyse the source code of the methods in \bar{e} , or use direct and indirect soundness on their effect annotations.

Together *direct soundness* and *indirect soundness* ensure our key property: the only *effectful* behaviour a method $T.m$ declared with $\text{effect}[\bar{e}]$ can perform is that of each \bar{e} . Our soundness statements also allow us to reason as to what methods can never be called: if another method $T'.m'$ is not a sub-effect of \bar{e} , nor is it a sub-effect of the effects of any methods in \bar{e} , and so on transitively, we can be sure that calling $T.m$ will not (indirectly) call $T'.m'$. We can also perform such reasoning on `restrict` expressions, since their typing rule, $(\vdash \text{restrict})$, enforces a bound on the effect of their bodies.

8 Related Work

There are three main techniques in the literature for reasoning over effectful operations: type and effect systems, monads, and object-capabilities. The former two are most common in functional programming languages, whereas the latter is naturally used in OO languages.

8.1 Type and Effect Systems

Most effect type systems in the literature feature a specific set of effects designed for a particular purpose [20]. The application of Hindley–Milner style polymorphism and type

¹⁴Case (c) can be thought of as saying the call to $C.m$ is below the stack frame of a method (overriding one) one in \bar{e} .

inference [13, 24, 29] to such effect systems has been studied heavily. Though most effect systems have focused on functional programming languages, research has also investigated object-oriented languages, such as for traditional region based effects [8], and controlling access to UI objects [6].

An effect system for control flow analysis [20, 27, 28] annotates lambda expressions with ‘labels’ and then uses such labels as effects. This system is not intended to be used by programmers directly, rather it would be used internally by automated analyses, as it requires lambdas to list the label of every other lambda they may (indirectly) call. Its sub-effect relation is much simpler than ours, allowing this system to be presented with a sound and complete algorithm that will take an expression with no effect annotations, and produce a minimally annotated version.

A ‘generic’ framework for effect systems has also been presented with a language definition parametrised by ‘effect disciplines’ [16]. An ‘effect discipline’ defines what constitutes an effect, how the effects of each expression form are computed, and when an expression is valid for a given set of effects. This system is more general than ours, as effect disciplines may allow an uneffectful expression to contain effectful sub-expressions, e.g. a `throw` expression inside a `try-catch` expression, where the `throw` itself has a ‘throw’ effect but the enclosing `try-catch` does not.

A distinct, but related concept is that of effect *handler* systems [14, 22], which were originally presented for pure functional languages, but have also been extend to object-oriented languages [11]. These are essentially a system for checked and resumable exceptions; however the main motivation for their use is also to reason over side-effects. For example, a method `foo` could be declared as raising an effect/exception ‘`read`’, the caller of this method can then provide a handler for `read`, so that when `foo` raises the `read` ‘exception’, a value is returned like an ordinary method call; alternatively the handler could behave like a normal exception and terminate execution of `foo`. The main advantages of this approach is that one can determine the effectful operations a method may perform by simply looking at its signature, as well as allowing these operations to be arbitrarily redefined. An effect handler system that allows effects to declare default handlers (in case the effect were leaked from the main function) could be seen as an alternative to our system; however they require that every effect a method leaks to be explicitly listed in their signature, as well as requiring explicit effect handling to allow reasoning like that in our `log` example from Section 3.1.

8.2 Monads

In functional programming (such as Haskell) the most common tool for side effect reasoning is that of monads; however one usually has to write code in a specific ‘monadic’ style

that is very alien compared to typical imperative code, for example instead of writing `print(readLn())`, in Haskell, one would write `readLn >>= print`. Or using the less flexible `do` syntax sugar, `do {line <- readLn; print line}`. However, some monads can even be ‘unwrapped’, for example Haskell’s `runST` function allows stateful computations of type $\forall s. ST\ s\ a$ (which cannot access externally accessible memory) to be executed and return a pure value (of type `a`).

Prior work has also shown how effect systems can be represented as monads [12, 30], for example the `effect-monad` package [21] uses advanced Haskell type system extensions provided by GHC to allow easily encoding user-defined effects as monads. In particular, it supports sub-effecting in ways similar to CallE. This library is more general than CallE, but is more verbose: both in the use and definition of effects.

8.3 Object-Capabilities

Object-capabilities appear to be the most active research area in OO languages for side-effect reasoning [2, 3, 19]. The object-capability model relies on two language guarantees: references cannot be forged and calling a method on an object is the only way to perform restricted operations. For example, in this model one could have a `File` class, where calling a `write` method on an instance of this class is the only way to (directly) `write` to a file (compare this with CallE, in which the `write` method can be a static method). A `File` object is a ‘capability’ object, and can only be obtained by making a new one (from another pre-existing capability object, such as a `Directory` one), by receiving it as an argument to a method, or through a field of a reachable object. Typically, the main function of the program will be initially given an, all-powerful capability from which other capability objects can be made (compare this with CallE’s `*` effect). Compared to effect systems, these simple requirements do not require type system features or annotations, allowing for example Joe-E [18], a subset of Java, to be created by simply disallowing problematic features. In particular it heavily restricts global variables and static methods in order to prevent ‘ambient authority’, i.e., the ability to perform restricted operations without being explicitly passed a capability object. CallE does not enforce the object-capability style, so it does not need such heavy restrictions.

A key advantage of object-capability based systems is that new capability objects can be *dynamically* created. For example one can create a `File` object and pass it to a method, granting that method the capability to read only a single (dynamically chosen) file. In contrast, our effect system only allows *statically* creating new effects (i.e. methods), such as our `log` method from Section 3.1, which can only write to the statically chosen file. However, CallE allows a less restrictive form of the object-capability style as in the `Path` example from Section 3.2; in that example `Path` is like a capability object, as it grants the ability to read files. They are not true capability objects, as other code can create them ‘out of thin

air' (provided they are allowed to call the static `Path.parse` method). This however does require reasoning over aliasing: we will need to reason what pre-existing `Path` instances a method might have access to, such as those accessible in global variables, or in the reachable object graph of a methods parameter.

A key disadvantage of object-capability systems is that they require complicated reasoning on object aliasing. For example if a method has access to an instance of the `Hashable` interface, how can we be sure that such instance is not also a `File`? In contrast, in CallE, a method that is not declared with a sufficiently powerful effect would not be able to call I/O methods on such an object, but it might be able to call a `hash` function on it. This works because our effect system restricts what methods can be *called*, not what objects can be accessed or passed around.

The atypical object-capability language of 'pop' [25] follows an approach similar to conventional accessibility: the `File` class would declare what code can call its methods. Thus their approach inherits the problems of accessibility control, the `File` class would need to be modified if new code wishes to directly call its methods, even worse, it allows 'rights amplification' by code that has permission to call a certain method on an object. For example, such code can create a trivial wrapper around a method that can then be passed to and used by arbitrary code. In contrast, CallE is designed to not have such problems by being the *inverse* of accessibility control: code declares (in its `effect` annotation) what methods it has access to call.

Finally, object capabilities usually require explicitly passing objects to code that needs their capabilities. In particular, to create restricted effects (such as a `ConsolePrint` object over a `Console` one), a wrapper object needs to be explicitly created, whereas CallE's type system does not require any such input from the programmer. However, such problems with object-capabilities can be alleviated by using implicit parameters and/or variables which are kept in scope for entire modules [17], this is a simpler alternative to effect systems [1], but is weaker and less flexible.

To summarise: when reasoning over *statically* known behaviour, CallE is less verbose and easier to reason with than object-capabilities; however CallE allows code similar to the object-capability systems (as in the `Path` example) enabling *dynamic* behaviour.

9 Conclusion

In conclusion, CallE presents a new and interesting way of statically reasoning over effectful operation in object-oriented programs. We have illustrated how it can provide useful guarantees without being either too strict, or requiring heavy annotation. We have also shown how our concept of method call effects combine nicely with object-oriented polymorphism. Though we have presented a formalised version of CallE, we have only informally stated and proved its soundness.

We believe that the concept of method call effects is a promising addition to an OO and imperative language, offering an alternative to the more common concepts of object-capabilities and monads. In particular our Indirect-CallE rule aims to allow the system to be both flexible and easy to use.

Though we have shown three potential extension to CallE, there are more that could be added to CallE, in particular, allowing constructors, field operations, and other language primitives to be used as an effect could be quite useful; however the resulting language formalism would not be more interesting than the one presented here. Adding some kind of effect alias or other similar mechanism to enable reusing effect annotations would also be useful, as would inference of effect annotations. However with generics and mutually recursive methods, it is not clear what effects an inference system should choose, or even whether this is decidable.

Acknowledgments

The authors would also like to thank the anonymous reviewers for their valuable comments and helpful suggestions. This work is supported in part by the Royal Society of New Zealand (Te Apārangi) Marsden Fund (Te Pūtea Rangahau a Marsden) under grant VUW1815.

A Additional Typing Judgements

Section 4 describes CallE's abstract syntax, our notational conventions, and the typing rules for the judgements of form $\Delta \vdash \bar{e} \leq \bar{e}'$, $C \vdash S = e$, and $\vdash \overline{S=e} \triangleleft S'$. Figure 2 presents the complete set of typing rules, including the remaining judgements, of forms $\vdash D$, $\vdash S$, $\Delta \vdash T$, $\Delta \vdash \epsilon$, that check that declarations, method signatures, type names, and effects are well typed; as well as judgements of form $\Delta | \Gamma \vdash e : T | \bar{e}$ and $\Delta \vdash T \leq T'$, which check that an expression has type T and effects \bar{e} , and that T is a subtype of T' . Note that the occurrence of $\vdash \overline{S=e} \triangleleft S'$ in the (\vdash class) rule is equivalent to $\vdash \overline{S=e} \triangleleft S'_{1,1}, \dots, \vdash \overline{S=e} \triangleleft S'_{n,m}$, this is because S and e also occur under one overbar (in the conclusion of the rule), so our notation rule described in Section 4.3 applies.

<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\vdash D$</div> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> $\text{(\vdash class)} \frac{\overline{\Sigma(C'') = \text{interface } C'' \{S';\}} \quad \overline{\{C'\} \subseteq \text{dom}(\Sigma)} \quad \overline{C \vdash S=e} \quad \overline{\vdash \overline{S=e} \triangleleft S'}}$ $\vdash \text{class } C(C'f) : \overline{C'} \{S=e;\}$ </div> <div style="width: 45%;"> $\text{(\vdash interface)} \frac{\overline{\vdash S}}{\vdash \text{interface } C \{S;\}}$ </div> </div>	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\vdash S$</div> $\text{(\vdash S)} \frac{\overline{\{C\} \subseteq \text{dom}(\Sigma)} \quad \overline{\Delta \vdash T} \quad \overline{\Delta \vdash T'} \quad \overline{\Delta \vdash \epsilon}}{\vdash T \mu \langle \overline{X} : \overline{C} \rangle (\overline{T'} x) \text{ effect}[\overline{\epsilon}]} \quad \overline{\Delta = \overline{X} \mapsto \overline{C}}$	
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$C \vdash S=e$</div> $\text{(\vdash S=e)} \frac{\overline{\vdash T \mu \langle \overline{X} : \overline{C}' \rangle (\overline{T'} x) \text{ effect}[\overline{\epsilon}]}}{\overline{X \mapsto \overline{C}' \text{this} \mapsto C, x \mapsto \overline{T'} \vdash e : T \overline{\epsilon}'}} \quad \overline{\epsilon}' \leq \overline{\epsilon}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\vdash \overline{S=e} \triangleleft S'$</div> $\text{(\overline{S=e} \triangleleft S')} \frac{(T_1 \mu \langle \overline{X}_2 : \overline{C}_1 \rangle (\overline{T}'_1 x_1) \text{ effect}[\overline{\epsilon}_1]) [\overline{X}_2 := \overline{X}_1] \in \overline{S=e} \quad \overline{\Delta = \overline{X}_2 \mapsto \overline{C}_2} \quad \overline{\Delta \vdash \overline{\epsilon}_1} \leq \overline{\epsilon}_2}{\overline{\Delta \vdash T_1} \leq \overline{\Delta \vdash T_2} \quad \overline{\Delta \vdash T'_2} \leq \overline{\Delta \vdash T'_1} \quad \overline{\Delta \vdash C_2} \leq \overline{\Delta \vdash C_1}} \quad \overline{\vdash \overline{S=e} \triangleleft T_2 \mu \langle \overline{X}_2 : \overline{C}_2 \rangle (\overline{T}'_2 x_2) \text{ effect}[\overline{\epsilon}_2]}$	
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash T$</div> $\text{(\vdash T)} \frac{\overline{\Delta(T) \in \text{dom}(\Sigma)}}{\overline{\Delta \vdash T}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash \epsilon$</div> $\text{(\vdash T.m)} \frac{\overline{\Delta \vdash T' \leq C'}}{\overline{\Delta \vdash T.m \langle \overline{T}' \rangle}} \quad \overline{\Sigma(\Delta(T). \mu) = _ \mu \langle \overline{X} : \overline{C}' \rangle (_) _};$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \Gamma \vdash e : T \bar{e}$</div> $\text{(\vdash*)} \frac{}{\overline{\Delta \vdash *}} \quad \text{(\vdash x:T)} \frac{\overline{\Gamma(x) = T}}{\overline{\Delta \Gamma \vdash x : T \bar{e}}}$
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \Gamma \vdash e : T \bar{e}$</div> $\text{(\vdash new)} \frac{\overline{\Sigma(C) = \text{class } C(\overline{T}f) _ \{ _ \}} \quad \overline{\Delta \Gamma \vdash e : T \bar{e}}}{\overline{\Delta \Gamma \vdash \text{new } C(\overline{e}) : C \bar{e}}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \Gamma \vdash e : C \bar{e}$</div> $\text{(\vdash e.f)} \frac{\overline{\Sigma(C) = \text{class } C(\overline{T}f) _ \{ _ \}} \quad \overline{\Delta \Gamma \vdash e : C \bar{e}}}{\overline{\Delta \Gamma \vdash e.f : T \bar{e}}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \Gamma \vdash e.m : T' \bar{e}'$</div> $\text{(\vdash e.m)} \frac{\overline{\Sigma(\Delta(T).m) = T' \mu \langle _ \rangle (\overline{T'} x) _}}{\overline{\Delta \Gamma \vdash e : T \bar{e}} \quad \overline{\Delta \Gamma \vdash e' : T' \bar{e}'}} \quad \overline{\Delta \Gamma \vdash e.m(\overline{e}') : T' \bar{e}', \overline{\epsilon}', T.m}$
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \Gamma \vdash e : T \bar{e}$</div> $\text{(\vdash restrict)} \frac{\overline{\Delta \Gamma \vdash e : T \bar{e}'}}{\overline{\Delta \Gamma \vdash \text{restrict}[\overline{\epsilon}] e : T \bar{e}'}} \quad \overline{\Delta \vdash \bar{e}' \leq \bar{e}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \Gamma \vdash e : T' \bar{e}$</div> $\text{(\vdash SUB)} \frac{\overline{\Delta \Gamma \vdash e : T \bar{e}} \quad \overline{\Delta \vdash T \leq T'}}{\overline{\Delta \Gamma \vdash e : T' \bar{e}}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash T \leq T'$</div> $\text{(\le REFL)} \frac{}{\overline{\Delta \vdash T \leq T}} \quad \text{(\le T)} \frac{\overline{\Sigma(\Delta(T)) = \text{class } C(_) : \overline{C}' _ \{ _ \}} \quad \overline{C' \in \overline{C}'}, \overline{\Delta(T)}}{\overline{\Delta \vdash T \leq C'}}$
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash \bar{e} \leq \bar{e}'$</div> $\text{(\le REF)} \frac{\overline{\{ \bar{e}' \} = \{ \bar{e} \}}}{\overline{\Delta \vdash \bar{e} \leq \bar{e}'}} \quad \text{(\le TRANS)} \frac{\overline{\Delta \vdash \bar{e} \leq \bar{e}'} \quad \overline{\Delta \vdash \bar{e}' \leq \bar{e}''}}{\overline{\Delta \vdash \bar{e} \leq \bar{e}''}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash T \leq T'$</div> $\text{(\le COMP)} \frac{\overline{\Delta \vdash \bar{e}_1 \leq \bar{e}'_1} \quad \overline{\Delta \vdash \bar{e}_2 \leq \bar{e}'_2}}{\overline{\Delta \vdash \bar{e}_1, \bar{e}_2 \leq \Delta \vdash \bar{e}'_1, \bar{e}'_2}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash T \leq T'$</div> $\text{(\le*)} \frac{}{\overline{\Delta \vdash \bar{e} \leq *}} \quad \text{(\le \epsilon)} \frac{}{\overline{\Delta \vdash \epsilon \leq \bar{e}}}$
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash T \leq T'$</div> $\text{(\le T)} \frac{\overline{\Delta \vdash T \leq T'}}{\overline{\Delta \vdash T.m \leq T'.m}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash C.m \leq \bar{e}$</div> $\text{(\le C.m)} \frac{\overline{\Sigma(C.m) = _ \mu \langle _ \rangle (_) \text{ effect}[\overline{\epsilon}] _};}{\overline{\Delta \vdash C.m \leq \bar{e}}}$	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">$\Delta \vdash \bar{e} \leq \bar{e}'$</div> $\text{(\le*)} \frac{}{\overline{\Delta \vdash \bar{e} \leq *}} \quad \text{(\le \epsilon)} \frac{}{\overline{\Delta \vdash \epsilon \leq \bar{e}}}$

Figure 2. Complete Set of Typing Judgements

References

- [1] Aaron Craig, Alex Potanin, Lindsay Groves, and Jonathan Aldrich. 2018. Capabilities: Effects for Free. In *Formal Methods and Software Engineering*, Jing Sun and Meng Sun (Eds.). Springer International Publishing, Cham, 231–247.
- [2] D. Devriese, L. Birkedal, and F. Piessens. 2016. Reasoning about Object Capabilities with Logical Relations and Effect Parametricity. In *2016 IEEE European Symposium on Security and Privacy (EuroSP)*. 147–162. <https://doi.org/10.1109/EuroSP.2016.22>
- [3] C. Dimoulas, S. Moore, A. Askarov, and S. Chong. 2014. Declarative Policies for Capability Control. In *2014 IEEE 27th Computer Security Foundations Symposium*. 3–17. <https://doi.org/10.1109/CSF.2014.9>
- [4] Burak Emir, Andrew Kennedy, Claudio Russo, and Dachuan Yu. 2006. Variance and Generalized Constraints for C[#] Generics. In *ECOOP 2006 – Object-Oriented Programming*, Dave Thomas (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 279–303.
- [5] David K. Gifford and John M. Lucassen. 1986. Integrating Functional and Imperative Programming. In *Proceedings of the 1986 ACM Conference on LISP and Functional Programming (LFP '86)*. ACM, New York, NY, USA, 28–38. <https://doi.org/10.1145/319838.319848>
- [6] Colin S. Gordon, Werner Dietl, Michael D. Ernst, and Dan Grossman. 2013. JavaUI: Effects for Controlling UI Object Access. In *ECOOP 2013 – Object-Oriented Programming*, Giuseppe Castagna (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 179–204.
- [7] James Gosling, Bill Joy, Guy Steele, and Bracha. Gilad. 2005. *The Java Language Specification* (3rd ed.). Addison-Wesley Longman Publishing Co., Boston, MA, USA.
- [8] Aaron Greenhouse and John Boyland. 1999. An Object-Oriented Effects System. In *Proceedings of the 13th European Conference on Object-Oriented Programming (ECOOP '99)*. Springer-Verlag, London, UK, UK, 205–229. <http://dl.acm.org/citation.cfm?id=646156.679836>
- [9] Atsushi Igarashi, Benjamin C. Pierce, and Philip Wadler. 2001. Featherweight Java: A Minimal Core Calculus for Java and GJ. *ACM Trans. Program. Lang. Syst.* 23, 3 (May 2001), 396–450. <https://doi.org/10.1145/503502.503505>
- [10] Atsushi Igarashi and Mirko Viroli. 2006. Variant Parametric Types: A Flexible Subtyping Scheme for Generics. *ACM Trans. Program. Lang. Syst.* 28, 5 (Sept. 2006), 795–847. <https://doi.org/10.1145/1152649.1152650>
- [11] Pablo Inostroza and Tijs van der Storm. 2018. JEff: Objects for Effect. In *Proceedings of the 2018 ACM SIGPLAN International Symposium on New Ideas, New Paradigms, and Reflections on Programming and Software (Onward! 2018)*. ACM, New York, NY, USA, 111–124. <https://doi.org/10.1145/3276954.3276955>
- [12] Shin-ya Katsumata. 2014. Parametric Effect Monads and Semantics of Effect Systems. In *Proceedings of the 41st ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '14)*. ACM, New York, NY, USA, 633–645. <https://doi.org/10.1145/2535838.2535846>
- [13] Daan Leijen. 2014. Koka: Programming with Row Polymorphic Effect Types. In *Proceedings 5th Workshop on Mathematically Structured Functional Programming, MSFP@ETAPS 2014, Grenoble, France, 12 April 2014*. 100–126. <https://doi.org/10.4204/EPTCS.153.8>
- [14] Sam Lindley, Conor McBride, and Craig McLaughlin. 2017. Do Be Do Be Do. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages (POPL 2017)*. ACM, New York, NY, USA, 500–514. <https://doi.org/10.1145/3009837.3009897>
- [15] J. M. Lucassen and D. K. Gifford. 1988. Polymorphic Effect Systems. In *Proceedings of the 15th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '88)*. ACM, New York, NY, USA, 47–57. <https://doi.org/10.1145/73560.73564>
- [16] Daniel Marino and Todd Millstein. 2009. A Generic Type-and-effect System. In *Proceedings of the 4th International Workshop on Types in Language Design and Implementation (TLDI '09)*. ACM, New York, NY, USA, 39–50. <https://doi.org/10.1145/1481861.1481868>
- [17] Darya Melicher, Yangqingwei Shi, Alex Potanin, and Jonathan Aldrich. 2017. A Capability-Based Module System for Authority Control. In *31st European Conference on Object-Oriented Programming (ECOOP 2017) (Leibniz International Proceedings in Informatics (LIPIcs))*, Peter Müller (Ed.), Vol. 74. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, Dagstuhl, Germany, 20:1–20:27. <https://doi.org/10.4230/LIPIcs.ECOOP.2017.20>
- [18] Adrian Mettler, David A. Wagner, and Tyler Close. 2010. Joe-E: A Security-Oriented Subset of Java. In *Proceedings of the Network and Distributed System Security Symposium, NDSS 2010, San Diego, California, USA, 28th February - 3rd March 2010*. <http://www.isoc.org/isoc/conferences/ndss/10/pdf/20.pdf>
- [19] Mark Miller, Ka-Ping Yee, Jonathan Shapiro, and Combex Inc. 2003. *Capability Myths Demolished*. Technical Report.
- [20] Flemming Nielson and Hanne Riis Nielson. 1999. Type and Effect Systems. In *Correct System Design, Recent Insight and Advances, (to Hans Langmaack on the Occasion of His Retirement from His Professorship at the University of Kiel)*. Springer-Verlag, Berlin, Heidelberg, 114–136. <http://dl.acm.org/citation.cfm?id=646005.673740>
- [21] Dominic Orchard and Tomas Petricek. 2014. Embedding Effect Systems in Haskell. In *Proceedings of the 2014 ACM SIGPLAN Symposium on Haskell (Haskell '14)*. ACM, New York, NY, USA, 13–24. <https://doi.org/10.1145/2633357.2633368>
- [22] Gordon Plotkin and Matija Pretnar. 2009. Handlers of Algebraic Effects. In *Proceedings of the 18th European Symposium on Programming Languages and Systems: Held As Part of the Joint European Conferences on Theory and Practice of Software, ETAPS 2009 (ESOP '09)*. Springer-Verlag, Berlin, Heidelberg, 80–94. http://dx.doi.org/10.1007/978-3-642-00590-9_7
- [23] Alex Potanin, James Noble, Dave Clarke, and Robert Biddle. 2006. Generic Ownership for Generic Java. In *Proceedings of the 21st Annual ACM SIGPLAN Conference on Object-oriented Programming Systems, Languages, and Applications (OOPSLA '06)*. ACM, New York, NY, USA, 311–324. <https://doi.org/10.1145/1167473.1167500>
- [24] Lukas Rytz, Martin Odersky, and Philipp Haller. 2012. Lightweight Polymorphic Effects. In *Proceedings of the 26th European Conference on Object-Oriented Programming (ECOOP'12)*. Springer-Verlag, Berlin, Heidelberg, 258–282. https://doi.org/10.1007/978-3-642-31057-7_13
- [25] Christian Skalka and Scott Smith. 2005. Static Use-based Object Confinement. *Int. J. Inf. Secur.* 4, 1-2 (Feb. 2005), 87–104. <https://doi.org/10.1007/s10207-004-0049-5>
- [26] Jean-Pierre Talpin and Pierre Jouvelot. 1992. Polymorphic Type, Region and Effect Inference. *Journal of Functional Programming* 2 (1992), 245–271.
- [27] Yan Mei Tang and Pierre Jouvelot. 1994. Separate Abstract Interpretation for Control-Flow Analysis. In *Proceedings of the International Conference on Theoretical Aspects of Computer Software (TACS '94)*. Springer-Verlag, London, UK, UK, 224–243. <http://dl.acm.org/citation.cfm?id=645868.668505>
- [28] Yan Mei Tang and Pierre Jouvelot. 1995. Effect Systems with Subtyping. In *Proceedings of the 1995 ACM SIGPLAN Symposium on Partial Evaluation and Semantics-based Program Manipulation (PEPM '95)*. ACM, New York, NY, USA, 45–53. <https://doi.org/10.1145/215465.215552>
- [29] Ross Tate and Daan Leijen. 2010. *Convenient explicit effects using type inference with subeffects*. Technical Report.
- [30] Philip Wadler and Peter Thiemann. 2003. The Marriage of Effects and Monads. *ACM Trans. Comput. Logic* 4, 1 (Jan. 2003), 1–32. <https://doi.org/10.1145/601775.601776>