A Privacy-Preserving Longevity Study of Tor's Hidden Services

Amirali Sanatinia[∗] , Jeman Park† , Erik-Oliver Blass‡ , Aziz Mohaisen† , Guevara Noubir[∗]

[∗]Northeastern University {amirali, noubir}@ccs.neu.edu †University of Central Florida

{parkjeman, mohaisen}@cs.ucf.edu

‡Airbus

{erik-oliver.blass@}@airbus.com

Abstract—Tor and hidden services have emerged as a practical solution to protect user privacy against tracking and censorship. At the same time, little is known about the lifetime and nature of hidden services. Data collection and study of Tor hidden services is challenging due to its nature of providing privacy. Studying the lifetime of hidden services provides several benefits. For example, it allows investigation of the maliciousness of domains based on their lifetime. Short-lived hidden services are more likely not to be legitimate domains, e.g., used by ransomware, as compared to long-lived domains.

In this work, we investigate the lifetime of hidden services by collecting data from a small (2%) subset of all Tor HSDir relays in a privacy-preserving manner. Based on the data collected, we devise protocols and extrapolation techniques to infer the lifetime of hidden services. Moreover we show that, due to Tor's specifics, our small subset of HSDir relays is sufficient to extrapolate lifetime with high accuracy, while respecting Tor user and service privacy and following Tor's research safety guidelines. Our results indicate that a large majority of the hidden services have a very short lifetime. In particular, 50% of all current Tor hidden services have an estimate lifetime of only 10 days or less, and 80% have a lifetime of less than a month.

I. INTRODUCTION

Only little is known about Tor's hidden services, their nature, and their lifetime. Yet, studying the lifetime ("longevity") of hidden services can provide several benefits: for example knowledge about service lifetime provides insights into the performance and resource allocation requirements of Tor's infrastructures, knowledge about the typical lifetime might be an indicator of maliciousness of individual onion domains. Short-lived hidden services are considered more likely not to be legitimate domains, as compared to long-lived domains.

The distributed, anonymity-providing nature of Tor renders any study about hidden services non-trivial and technically challenging. To enable users to connect to hidden services with anonymity, Tor employs a complex rendezvous protocol. Hidden services announce themselves on a special subset of all Tor relays, the so called Hidden Service Directory (HSDir) relays. These relays, currently around 3, 000, store service descriptors uploaded by each hidden service and reply to user connection requests in a distributed fashion. Specifically, each hidden service registers itself every day to a (pseudo-)randomly chosen set of 6 HSDir relays. Only these 6 relays

know about the hidden service and user connection requests. If the party conducting the study would have access to all HSDir relays, a lifetime study of hidden services would become trivial. The party would simply count the number of days a hidden service descriptor is uploaded to any HSDir relay. However, given the decentralized, volunteer-run nature of Tor relays, such a straightforward approach is obviously impossible. There will always be HSDir relays outside the measuring party's access, resulting in an incomplete view of hidden services.

Besides such a purely technical challenge, there exist also ethical challenges when conducting a study on Tor. Any study collecting real-world data from Tor's relays must consider implications of data collection, storage, and analysis. Publishing (statistical) information about real-world data and performing the study itself must not de-anonymize individual parties. Therefore, the recently established Tor Research Safety Board reviews new research proposals and approves only projects with minimal privacy risks and an expected benefit for the Tor community.

This paper: We measure and analyze Tor's hidden services lifetime in a privacy-preserving fashion. First, we investigate the effect of having access to only a fraction of HSDir relays on the precision of hidden service lifetime estimation. Surprisingly, we are able to show that access to even a small fraction ($\approx 2\%$) already allows lifetime prediction with high precision, independent of the real distribution of lifetimes.

We then institute several changes to the Tor relay software. First, with our software, a relay counts the number of observations of each individual hidden service descriptor and user connection requests to this hidden service. To protect anonymity of individuals and hidden services, we also design and implement new techniques for multiple different parties running multiple relays. At the end of a measuring epoch, a lifetime histogram is computed in a privacy-preserving manner. Following the standard rationale of secure multi-party computation, each (potentially malicious) party running a set of relays only learns the information from their set of relays and the histograms, but nothing else. We store observation and request counts with forward security. That is, if a relay is compromised by an adversary at some point, the adversary will not learn count and request values from before the time of compromise.

We have deployed a total of 80 modified relays on cloud VMs, i.e., 2% of all HSDir relays. Our set of relays has been separated into different entities, based on the affiliation running the relay, different cloud providers, and different geolocations. Our modified relays were monitoring hidden service and connection requests over a period of 180 days.

This paper makes the following major contributions:

- We design and implement new analysis, simulation, and extrapolation techniques for Tor hidden service lifetime estimation. These techniques allows us to infer lifetimes with high accuracy using data collected from a small number of HSDir relays.
- We design and implement a new protocol for multi-party, privacy-preserving computation of lifetime histograms. Therewith, curious HSDir relays do not learn anything about hidden services besides what can be deduced from histograms. Our protocol is significantly more efficient than related approaches.
- We deployed 80 relays over a period of 180 days. Our relays span over 3 different cloud platforms across USA and Europe (9 cities from 5 countries).
- As an outlook, we discuss several new techniques to cope with malicious adversaries which are dishonest regarding their input and thus violate correctness of a measurement. Our techniques are general and also apply to previous work on measuring Tor properties.

Remark: We stress that technical details of our approach were reviewed and approved by the Tor research safety board before deployment.

II. BACKGROUND: HIDDEN SERVICES & HIDDEN SERVICE DIRECTORIES

Tor does not only anonymize client origin, but also network services by introducing the concept of hidden services (also called onion services). Roughly speaking, by connecting to a hidden service, neither the client nor an eavesdropping adversary learn the service's IP address and therewith location. Hidden services have been used to protect both legitimate, legal services for privacy conscious users (e.g., Associated Press, CBC, or the Center for Public Integrity all using SecureDrop through hidden services), but also for illicit purposes such as drug and contraband markets and extortion. We briefly summarize key properties of Tor's hidden services. In particular, we focus on the architecture of hidden services, how hidden services are offered such that clients and service providers can communicate. The Tor hidden services architecture is composed of the following components:

- *Server*: computer running a service (e.g., a web server).
- *Client*: computer wishing to access the server.
- *Introduction Points (IP)*: a set of Tor relays, chosen by the hidden service server. They forward initial messages between the server and the client's Rendezvous Point.
- *Rendezvous Point (RP)*: a Tor relay randomly chosen by the client that will forward data between the client and the server.
- *Hidden Service Directories (HSDir)*: a set of Tor relays chosen pseudo-randomly to store certain service information.

Server. The first step for the server is to make its service accessible. Once for each service, the server generates an RSA key pair. The (truncated) SHA-1 digest of the resulting public key is the Identifier of the hidden service, and the .onion hostname is the Base-32 encoding of this identifier. Typically, it is sufficient for clients to know the .onion hostname to be able to connect to the server over Tor. However before, the server registers its hidden service inside Tor. As shown in Figure [1,](#page-2-0) the server randomly chooses a set of Introduction Points and establishes Tor circuits with them (step 1). After setting up circuits, the hidden service then calculates two service *descriptor-id*s and determines several HSDir relays, details below. The server uploads their list of Introduction Points to those HSDir relays (step 2). The following simple relations hold for the descriptor-ids:

Here, H denotes the SHA-1 hash function, Identifier is the 80 bit truncated SHA-1 digest of the public key of the hidden service. Descriptor-cookie is an optional 128 bit field which could be used for additional authorization such that knowledge of the .onion is not sufficient to connect to a hidden service.

Hidden services, i.e., their servers, change their HSDir relays periodically. The time-period determines when each descriptor-id expires, and the hidden service needs to calculate Introduction Points and uploads them to the new corresponding HSDir relays. To prevent descriptor-ids from changing all at the same time, a permanent-id-byte is also included in the calculations. The Replica index takes values 0 or 1, and thus there exist two descriptor-ids.

The range of all possible descriptor-ids forms a ring, see Figure [2.](#page-2-0) Additionally, each HSDir relay features a fingerprint, the SHA-1 hash of their own public key. These fingerprints allowing placing HSDir relays on the ring of descriptorids, essentially dividing the ring into segments. Each hidden service stores their Introduction Points with their descriptorid on three consecutive HSDir relays in the ring, so to a total of six relays. Specifically, if a descriptor-id of a hidden service falls between fingerprints of HSDir relays HSDir $_{k-1}$ and $HSDir_k$, then the Introduction Points will be stored on relays HSDir_k, HSDir_{k+1}, and HSDir_{k+2}.

Client. When a client wishes to connect to a hidden service, they first need to compute the descriptor-id as above. The client then contacts the corresponding HSDir relays (step

3) by establishing a circuit to receive the list of the hidden service's Introduction Points. Then, the client first randomly selects a Tor relay as its Rendezvous Point and establishes a Tor circuit with it (step 4). The client connects to one of the hidden service's Introduction Points and asks to contact the hidden service, announcing their Rendezvous Point (step 5). Then, the Introduction Point forwards the Rendezvous Point to the hidden services (step 6). Finally, the hidden service establishes a circuit to the Rendezvous Point, and hidden service server and client start communicating.

III. MEASUREMENT CONFIGURATION

Our key idea is to deploy several modified HSDir relays within the Tor network to collect partial statistics. These HSDir relays follow the standard Tor protocol specification with only one difference: the relays maintain counters for all descriptor-ids observed. Whenever descriptor-id is uploaded to one of our HSDir relays, this relay will increase its local counter for descriptor-id by one. After some time, which we divide into *epochs*, all of our HSDir relays jointly produce a histogram of the hidden service lifetime during that epoch. The histogram will capture how many hidden services were observed on how many days. Computing the histograms should be both precise and privacy-preserving. In this section, we discuss our approach on how to measure with precision. We will present the privacy-preserving computation aspects in the following section.

Deploying a large number of modified Tor relays such that nearly all relays in the Tor network are our modified relays would obviously result in high precision for the estimated lifetime and popularity. However, deploying large numbers of relays clearly incurs high (monetary) costs. As described later in Section [VI,](#page-8-0) we use several different cloud providers and deploy Tor relays on cloud VMs. The costs of running the measurement is thus proportional to the number of relays we deploy.

Therefore, a first question is how many relays result in what level of precision for our estimation. In the following, we present our approach to calculate the trade-off between the number of relays (costs) on the one hand and the precision of lifetime and popularity estimation on the other via simulation.

A. Simulation Methodology

We simulate the behavior of hidden services uploading their descriptors to the HSDirs. As such, every hidden service chooses six HSDir based on their fingerprint ring, following

Fig. 1: Hidden service connection setup Fig. 2: Ring of descriptor-ids and HSDir relay fingerprints

Tor's specification. Given that we have the ground truth for the lifespan of each hidden service, we are able to analyze the effect of the number of controlled HSDirs on the statistical error, for each lifespan d. Thus, the estimated lifespan $l_e(i)$ for $HS_i(i = 1, 2, \ldots n)$ using the counts from all controlled HSDirs can be written as.

$$
l_e(i) = \frac{\left(\sum_{k=1,2..N_c} C_{k,i}\right) \times N_t}{N_c \times 6},
$$

where $C_{k,i}$ is the counter value for the hidden service HS_i (measured at $HSDir_k$), N_c is the number of controlled HSDirs (e.g., 80), and N_t is the total number of HSDirs (e.g., 3,000) on Tor. By dividing the sum of counters by N_c , we can estimate what would have been obtained if we measured the results using all HSDirs. During an epoch of 24 hours, six HSDirs store descriptors at the same time, so we divide the results by six to estimate lifespan, accounting for the overcount at those HSDirs.

Error Estimation. The error for each hidden service, $E(i)$, is calculated as the difference between the estimated and actual lifespan. The total average error rate, E_{avg} is calculated by integrating these errors. Let $l_a(i)$ be the actual lifespan for HS_i from the initial phase. The error and total average error are calculated as follows:

$$
E(i) = |l_e(i) - l_a(i)|/l_a(i),
$$
\n(1)

$$
E_{avg}(N_c) = \left[\sum_{i=1,2..N_t} E(i)\right] / N_t.
$$
 (2)

Using a simulator we experiment with various variables to compute the above error rates and decide an acceptable measurement setting.

Simulation Setting. During the simulation, we maintain the total number of HSDirs in the network at 3,000 and the number of hidden services at 60,000, which is the number of unique hidden services per day [\(16\)](#page-10-0). In addition, since the main purpose of this simulation is to discover the correlation between the number of controlled HSDirs and the error of the statistical results, we do not consider users' behavior in the simulation. The number of HSDirs controlled between 30 to 300, in steps of 30 (i.e., $N_c = 30, 60, 90, \ldots, 300$).

Lifespan estimation using HSDirs. Figure [3](#page-3-0) shows the distribution of the actual and the estimated lifespan in our simulations with 30 and 300 controlled HSDirs. The actual lifespan (blue bars) is densely set following a given normal random distribution, and the estimated lifespan (red bars) looks rough as it is estimated from the counts collected from the controlled HSDirs. Comparing the left and right graphs, the actual lifespan of both graphs are observed to be similar, but the estimated lifespan varies (per the variance or frequency of the estimated values). This difference occurs because the range of counter values to be collected can be widened when the number of the controlled HSDirs is large and the range of the estimated lifespan also widens together. In the right graph, the difference between the estimated and actual lifespan is small, which means that the accuracy of lifespan estimation is high.

Figure [4](#page-3-1) shows numerically a comparison between the estimated and the actual lifespans. The X-axis represents the calculated error of the hidden service using the above equation, while the Y-axis is the number of hidden services that have the corresponding error. In this graph, we can see that when N_C is 300, more than 90% of HSs have an error of less than 0.2, while when N_C is 30 only about 50% have error of less than 0.2. This shows that the accuracy of the accumulated results can vary depending on how many HSDirs are used to collect information among all HSDirs.

B. Determining the number of controlled HSDirs

The previous experiments have empirically demonstrated that the number of controlled HSDirs can directly impact the measurement error. Based on these observations, we measure how E_{avg} varies according to the number of HSDirs. It is clear that a large number of HSDirs ensures high accuracy in the statistics, but it is necessary to find an optimal value for realistic, safe, and practical measurements.

As shown in Figure [5,](#page-4-0) the average error rate E_{avg} changes as we we change the value of N_c . As the number of the controlled HSDirs is increased, the estimated lifespan becomes more accurate and the error rate decreases. Through this experiment, we calculate the optimal number of controlled HSDirs to be between 60 and 90, as it is an appropriate compromise between cost and accuracy.

C. Determining the number of contolled HSDirs for various distributions

In the previous section, we investigated the optimal value of the number of controlled HSDirs, assuming that the hidden services have a lifespan following a normal distribution. However, assuming that it follows a normal distribution in the absence of a baseline for the true distribution of the lifespan of the hidden service introduces additional errors. Therefore, we have also experimented with a case where the lifespan of the hidden service is distributed along a uniform and exponential distribution.

Figure [6](#page-4-1) shows the average of errors of the lifespan estimation with various random distributions. We note a difference in the individual error rate, although the overall trend is similar to our previous results. Through these extended experiments, we also find that using the number of controlled HSDirs between 60 and 90 is an acceptable setting, regardless of the distribution of hidden services' lifespan.

Fig. 3: The distributions of actual and estimated lifespan. Note that the distributions of actual lifespan in both cases are almost similar, but the distributions of estimated lifespan are quite different.

Fig. 4: CDF for hidden service errors. Note that when using 300 HSDirs for the lifespan estimation only less than 10% of HSs have an error over 0.2, while when using 30 HSDirs about half of HSs have error larger than 0.2

Fig. 5: The average expected error for various number of controlled HSDirs.

In the next section, we describe a privacy-preserving protocol that we use to encrypt the lifespan counts for each hidden services, while also hiding the raw hidden services addresses.

Fig. 6: The average of errors with the uniform, normal, and exponential distribution, respectively.

IV. PRIVACY-PRESERVING HISTOGRAMS

We now turn to protecting privacy during our measurement study and begin by discussing this paper's threat model. Essentially, our work should not allow an adversary to learn more sensitive information than if they would run several HSDir relays themselves.

A. Threat Model

As of today, a malicious party (an *adversary*) running any HSDir relay in Tor is able to get limited information about descriptor-ids and client requests and therewith hidden services' lifetimes and popularities.

Our experiment on the Tor network produces a histogram of hidden service lifetimes. Informally, our privacy intuituion is that our experiment must not enable the adversary to learn more than the histograms and all data recorded by the adversary controlled HSDir relays.

This should also hold for our own HSDir relays which we deploy inside the Tor network using several cloud providers. Some relays could be compromised by an adversary. One could even argue that some members of our team behaves adversarial (and thus we have separated control over all relays to 3 different parties, see Section [V\)](#page-7-0).

More formally, we assume that an adversary has compromised a subset S of our HSDir relays. Still, the adversary should not learn anything besides

- what each compromised HSDir relay in S observes. Specifically, this comprises service descriptors and client requests.
- the histogram of lifetimes produced in the end.

An adversary either compromising some of our relays our simply running relays themselves can obviously combine the *view* of their relays and possibly infer additional information. As the Tor network is based on volunteering, an adversary can participate at any time, and there is no way to prevent such kind of data leakage. The goal of our security mechanisms is to not introduce additional issues.

As a side note we remark that an adversary compromising a relay might have full system access to the computer running the relay. This might include the power to dump the computer's memory, read swap data etc. Against such an adversary it is difficult to protect sensitive data, e.g., service descriptors, from before the time of compromise. To offer at least some security, we will use techniques to hide previously stored information.

B. A New Protocol for Privacy-Preserving Histograms

We now describe technical details of our protocol which computes histograms in a privacy-preserving way. The main setup of data collection and aggregation is based on and extends the second variant of the PrivEx [\(9\)](#page-10-1) protocol. PrivEx introduces intuitive distributed encryption and multi-party computation for a single count and has already served as the basis for other work, too [\(14\)](#page-10-2). In the following, we present the main protocol steps. To avoid confusion, we use the same notation and terminology (TKS and DC) as PrivEx.

1) Overview: We separate trust into multiple different, mutually distrusting *parties*. Each party runs one Tally Key Server (TKS) and several Data Collection (DC) node. Each DC node in our setting is an HSDir relay. During data collection, each DC node stores a count, the number of times a hidden service has registered its service descriptor at this DC node. To realize that, each DC manages a set of (key, value) pairs, where the key is the hash of a .onion hostname, and the value is the count for that .onion hostname. We store counts using additively homomorphic encryption, see below.

After some time interval (an epoch), all DCs send their (key,value) pairs to their corresponding TKS. A TKS homomorphically adds values (counts) reported for the same key (hostname). This is done only for safety reasons, such that not all measurements of a DC are in case that DC crashes within our multiple-month study.

At the end of the whole data collection phase, i.e., after several epochs, all TKS interactively compute a lifetime histogram with privacy. In our setup with multiple distrustful parties, computation resembles standard cryptographic multiparty computation.

Cryptography Overview. During initialization, our protocol uses a standard distributed key generation technique to generate a (private, public) key pair for an additively homomorphic encryption scheme. Here, the public key will be known to everybody, but not the private key. The private key is split into shares, and each TKS knows one share of the private key. To decrypt a ciphertext, all TKS need to cooperate and contribute to the decryption.

The DCs use this public key to encrypt the counts during the data collection phase. We employ the additively homomorphic variant of Elgamal encryption with plaintexts "in the exponent". Thanks to the additively homomorphic property, each TKS homomorphically adds counts until the end of the data collection phase. During an aggregation phase, all TKSs homomorphically add their individual sums to compute encrypted aggregated sums. To separate sums for the corresponding .onion service, each TKS shuffles the list of aggregated sums.

Finally, each individual sum is decrypted by each TKS contributing with to each decryption with its share of the private key.

We use a public bulletin board (PBB) for storage of all the intermediary and final results of the computations that are accessible to all DC and TKS nodes, to read from and write to. To mitigate against misbehavior and data manipulation by the PBB, all data can be either signed by the publishers, or the PBB can act as an append only database or ledger. We use a private git data repository where each DC and TKS have their own private key to publish their data.

After this overview, we now turn to technical details.

2) Technical Details:

Initial Setup. Initially, all parties agree on an asymmetric key. We use Elgamal's additively homomorphic variant, as distributed key generation for Elgamal is straightforward. All operations below take place in a group where the Decisional DiffieHellman assumption is believed to hold, e.g., the group of quadratic residues QR_p of \mathbb{Z}_p , where $p = 2 \cdot q + 1$ is a large safe prime. For any $a \stackrel{\$}{\leftarrow} QR_p$, $g = a^2$ is a generator of QR_n .

During an initial setup stage, parties jointly agree on a public key using the following standard distributed key generation technique. Each party i picks a random value $a_i \stackrel{\$}{\leftarrow} \mathbb{Z}_q$ to be used as its share of a joint private key. The share of the joint public key is calculated, $A_i = g^{a_i}$. To mitigate against an adversarial party, each party first publishes a hashbased commitment to A_i . After all parties have published their commitments, they open them to reveal A_i . An alternative would be to commit to A_i and publish the commitment together with a zero-knowledge proof of knowledge of a_i .

Next, the joint public key A is calculated as $A = \prod_i A_i$.

Encryption of a message $m \in \mathbb{Z}_q$ is $E_A(r, m) = (g^r, A^r \cdot$ h^m)

for a random value $r \in \mathbb{Z}_q$ and two generators g and h. Note the encryption's additively homomorphism, as we have

$$
E_A(r_1, m_1) = (g^{r_1}, A^{r_1} \cdot h^{m_1})
$$

$$
E_A(r_2, m_2) = (g^{r_2}, A^{r_2} \cdot h^{m_2})
$$

$$
D_a(E_A(r_1, m_1)) \cdot D_a(E_A(r_2, m_2)) = D_a(E_A(r_1 + r_2, m_1 + m_2))
$$

Our additive variant of Elgamal encryption supports reencryption. That is, for a ciphertext $C = (C_1, C_2) = (g^r,$ $A^r \cdot h^m$), we can re-encrypt to $C' = (C_1^{r'}, C_2 \cdot A^{r'})$ for a randomly chosen $r' \in \mathbb{Z}_q$.

Decryption of ciphertext tuple (C_1, C_2) is,

$$
D_a(C_1, C_2) = DLog_h(C_2/C_1^a).
$$

So to decrypt, you have to calculate a discrete logarithm. Given that the size of message space is small in our experiments, it can be calculated using "brute-force". A count value cannot be larger than the duration of the data collection phase d. Even if we control all HSDirs in the Tor network, the total count cannot be larger than $6 \cdot d$. For further optimization and more efficient calculation of discrete logarithm, other general approaches such as baby-step giant-step [\(23\)](#page-11-0), Pollard's kangaroo algorithm [\(22\)](#page-11-1) or Pollard's rho algorithm [\(21\)](#page-11-2) can be employed.

Note that secret key a is not known to anybody. Yet, to enable joint decryption, we make use of the property that each party *i* knows share a_i , and $a = \prod_i a_i$. So, during decryption of ciphertext (C_1, C_2) , party *i* computes intermediate value $v_i = C_2/C_1^{a_i}$ and sends the result to party $i + 1$. Party $i + 1$ takes v_i and computes $v_{i+1} = v_i / C_1^{a_{i+1}}$ and so on. Eventually, the last party publishes the recovered plaintext.

Data Collection. Each DC stores a simple database of (key, value) pairs. When receiving the descriptor of a hidden service, the DC verifies whether the hash of the .onion address already exist in the database. If it exists, the DC increments its counter value by calculating $E_A(r,1) = (g^r, A^r \cdot h)$ and homomorphically adding $E_A(r, 1)$ to the current encrypted count in its database. If the hash of the .onion address does not exist in the database, the DC creates a new entry and stores $E_A(r, 1)$ for this hash. We use an epoch of 24 hours to consider a new hidden service. After a hidden service is observed by a DC c times, the value for the counter will consequently be $(g^r, A^r \cdot h^c).$

Aggregation. At the end of an epoch, each DC publishes a commitment of their encrypted counts to the PBB. After all DCs have committed, they open their commitment by publishing their encrypted counts to the PBB, i.e., for each onion address they publish the encrypted count $(H(onion))$, $(g^r, A^r · h^c)$). After opening commitments, the TKSs verify counts against commitments and if successful continue operation.

At the end of the data collection phase, one TKS, e.g., TKS_1 sums up all encrypted counts by componentwise multiplication of ciphertexts belonging to the same $H(onion)$. TKS₁ publishes result R which is a list of ciphertexts $C = E_A(r,$ (c)). All other TKS re-do this computation and check TKS₁'s R. If it matches their computation, they continue.

Shuffling. The last step is that all TKS engage in a privacypreserving shuffle of R . Therewith, they will break the connection between $H(onion)$ and the encrypted count corresponding to $H($ *onion* $).$

Specifically, TKS_1 starts by computing and publishing a random permutation R' of R where all ciphertexts in R are re-encrypted. TKS₂ computes another random permutation R'' of R' and publishes R'' , and so on.

To protect against malicious TKSs, we use standard zeroknowledge proofs of knowledge of correctness of shuffles (permutation and re-encryption). That is, each TKS does not only publish their shuffle, but publishes their shuffle together with a zero-knowledge proof of knowledge. There are several (very efficient) variants of such zero-knowledge proofs [\(19;](#page-11-3) [3;](#page-10-3) [11\)](#page-10-4). However, we use a simple cut-and-choose implementation of a zero-knowledge proof of knowledge of correctness of a shuffle working as follows. For a given sequence R of ciphertexts,

- 1) TKS_i computes and publishes two permutations R_0 and R_1 with re-encrypted ciphertexts of R .
- 2) TKS_i also computes the hash $H(R_0, R_1)$, where "," is an unambiguous pairing of inputs.
- 3) If the first bit of $H(R_0, R_1)$ is 0, then TKS_i publishes details of how to permute R to R_0 together with all random coins r used during re-encryption.
- 4) If the first bit of $H(R_0, R_1)$ is 1, then TKS_i publishes permutation from R to R_1 together with the random coins.

The above four steps are repeated ℓ times, resulting in a zeroknowledge proof of knowledge of correctness of a shuffle in the random oracle model, and with a (statistical) soundness error of $2^{-\ell}$. A reasonable value of ℓ is, e.g., $\ell = 40$.

Decryption. After the last shuffle has been published and its proof verified, this last shuffle is then decrypted ciphertext by ciphertext. As described above, each TKS partially decrypts each ciphertext. The last TKS publishes the list of h^c values. Given that each count cannot be larger than the duration of the study, we use brute-force to calculate the discrete logarithm, but any of the faster, general algorithms mentioned above are possible, too.

3) Security Analysis and Discussion: The distributed key generation mechanism guarantees establishing a public-private key pair against malicious adversaries. Committing and opening the public part of a key share, or using a zero-knowledge proof of knowledge as PrivEx, is a standard technique to compute an unbiased key pair.

For simplicity, we use a k -out-of-n approach for our distributed key generation where $k = n$. While it is easy to implement, it has several drawbacks. For example, if any of the parties aborts the protocol, no encrypted data can be decrypted. As an alternative for more robustness, one could use $k < n$ approaches. Note, however, that any multi-party computation protocol requires a honest majority.

To comply with Tor's standard ethics we do not store the raw hidden services at any point. Each DC calculates the hash of an onion service, $H(onion)$. This mitigates against leaking the hidden services address to an adversary without prior knowledge of the onion address. However, it does not protect against an adversary with prior knowledge of a hidden service.

Along the same lines as distributed key generation, aggregation also uses a commit-and-prove approach [\(5\)](#page-10-5) to securely compute sums in the presence of malicious adversaries.

There is, however, still one constraint. A malicious adversary can lie about their input, i.e., their encrypted counts. That is, a malicious adversary can publish and prove encryptions of counts that are not reflecting the really observed counts. In the specific context of our computations, it is important to point out consequences. For example, if 2 out of 3 parties are malicious, they could both commit to and publish only encryptions of 0. As a result, the adversary would learn a random permutation of the benign party's counts.

In general, it is difficult to protect against adversaries lying about their input. Yet, in contrast to related work, we discuss several strategies for mitigation. Besides using differential privacy, we dedicate Section [IV-C](#page-6-0) to more details.

If we assume adversaries with the only constrain that they do not cheat about their input, than the above protocol is secure in that an adversary only learns the histogram (and everything they can derive from their own view), but nothing else about the other parties' input.

C. Protection Against Dishonest Adversary

In this section, we describe and discuss several first ideas to detect and mitigate against dishonest parties (DC and TKS) who lie and report fake counts. Dishonest DCs and TKSs can skew the histograms and final counts by reporting fake values.

Approach 1. The rationale behind our first approach is that parties control each other and verify their output. Due to the random distribution of descriptor-ids on HSDir relays, there is a non-zero probability that the same descriptor-id is placed on HSDir relays of multiple parties. Increasing the number of HSDir relays increases this probability.

Now let P_1, \ldots, P_n be parties, with at most one being malicious. Each party controls their own subset of HSDir relays of size x . Parameter x must be chosen carefully in advance such that it gives certain properties on the precision of the mapping between counts and hidden service lifetime later. The protocol goes as follows.

- 1) Parties P_1, \ldots, P_n enter the data collection phase at the same time. During measurement, each party individually and independently of other parties counts occurrences of hidden services as before.
- 2) At a predetermined deadline, all parties cease measurement. Each party P_i computes a histogram histogram of counts.
- 3) Parties engage in an interactive protocol.
	- a) Each party P_i publishes a commitment to its histogram histogram $_i$.
- b) After all parties have committed, they open commitments and publish their histogram histogram $_i$.
- c) For any pair of histograms histogram_i and histogram_j, parties locally compute histogram $distances$ D(histogram_i, histogram_j). There are several distances for histograms, e.g., Kullback-Leibler, χ^2 distance, Earth Moving Distance, quadratic form distance, and combinations of that. In any case, the output of this step are numbers $d_1 = D(\text{histogram}_1, \text{histogram}_2),$ d_2 = D(histogram₁, histogram₃), . . . , d_{n-1} = $\mathsf{D}(\mathsf{histogram}_{n-1}, \mathsf{histogram}_n)$. For simplicity, assume $d_1 < \ldots < d_{n-1}$.

Now, the "true" histogram is histogram₁. The rationale is that histograms of honest, non-malicious parties will be closer than the histograms of a honest party and a malicious.

Obviously, for this mitigation strategy to work in a straightforward manner, the number of HSDir relays for each party must be as high as the number of relays for the set of all parties in the previous section. However future work could investigate trade-offs between the choice of x and a compromise between security, cost, and precision of results.

Approach 2. In this approach, each party creates a set of "private" hidden services, i.e., without announcing them to other parties. By running these hidden services, each party knows exactly which HSDir relays should have hosted their own descriptors-ids at any time. To verify if another party is honest, each party can ask for the decryption of the count of their hidden service after proving that they own the hidden service's corresponding private key.

More formally, each party P_i owns k RSA (private, public) key pairs (d, e) and runs k private hidden services onion_i . During initialization, each party commits to their k onion services. After data collection, each party then open commitments and proves the ownership of each of their onion_i using the private key.

After the ownership of a hidden service is verified, each DC_i reveals their count for *onion_i*. If *onion_i* was online all the time, everybody knows the exact count of any hidden service for each DC using the DC's fingerprint. If count reported from a DC diverges from its expectation, the DC has cheated. In some sense, this technique is like a spot checking technique for onion services.

This approach requires that parties actually run their onion services and not falsely blame other parties. To prove that their services were really online, one party could reveal an onion service to a subset of the other parties which would then regularly check availability of the onion service and serve as witnesses later on.

Approach 3. Considering that an adversary can detect the honeypots, another approach is to verify the counts of a set of all hidden services. This is a variant of the second approach. We sample a random set of all online hidden services, and query each entity for their corresponding counts. In this method, the adversary is not able to report fake values on

Country	City	Cloud Provider	Count
USA	City 11	Private	20
USA	Chicago	Vultr	2
USA	Dallas	Vultr	2
USA	Atlanta	Vultr	\overline{c}
USA	Miami	Vultr	\overline{c}
Germany	Frankfurt	Vultr	6
UK	London	Vultr	6
France	Paris	Online SAS	32
Netherlands	Amsterdam	Online SAS	8

TABLE I: The distribution of our relays per country, city, and cloud provider. We chose diverse location for the relays, both for security reasons and also to help the Tor network by contributing relays and bandwidth.

the known hidden services that do not belong to the verifiers. Each verifier checks the lifespan of any hidden service that is uploaded to his HSDir, by performing a non-intrusive probing. Such probing is carried out by establishing a connection to the hidden service, without making an HTTP request. Imagine that in a dynamic HSDir circle formation, the probability that an honest HSDir reports a count outside the threshold is p_1 . Therefore, after *i* iterations of sampling hidden services lifespan, each TKS can establish a level of confidence on the correctness of the counts. In this model, each TKS entity can set their own threshold δ and only consider the counts that meet their security requirements.

V. IMPLEMENTATION AND DEPLOYMENT

To ensure that we are not compromising the security and privacy of Tor, we took the following procedures. We setup a website detailing our project, methodology, fingerprints of our relays, and the identities of the research team. We limit the bandwidth of our relays to 250KB/s, to prevent acquiring the *Guard* flag. Additionally, we disable the egress traffic to the Internet from our relays, to avoid acquiring the *Exit* flag. The *Exit* nodes are specially important component of the Tor network, because they have access to the traffic (if not encrypted). They are also a target of abuse complaints, since their IP is listed as the source of connection to any Internet domain. Furthermore, if the same entity is chosen as both the *Guard* node and *Exit* node, he can perform network correlation attack and de-anonymize Tor users. Therefore, we listed all of our relays as one *Effective Family*, to prohibit two of our relays to be chosen in any one circuit. This ensures that our relays only serve as *Middle* relays and HSDirs inside the Tor network.

In the following section, we describe our implementation and deployment of the privacy preserving data collection and analytics. We took the procedures necessary to ensure the security and privacy of the data collected.

We deployed 80 relays that were managed by three different teams, two from the USA and another one from Europe. We divided our relays between the teams at different geolocations for security and privacy reasons. 40 relays (20 VM) were managed by Entity 1, 20 relays (10 VM) managed by Entity

Fig. 7: The geolocation map of our relays.

2, and 20 relays (10 VM) by Entity 3. We hosted two relays per VM instance. We used a combination of private and public cloud to host our relays. 20 relays (10 VM) were hosted on private cloud, 20 relays (10 VM) on Vultr cloud provider, and 40 relays (20 VM) on Online SAS. We chose these two cloud providers because of low cost, and that both are in the top 5 cloud providers used by the Tor relays. These providers have data centers in multiple geolocations, allowing us to distribute our relays, both for security reasons and also to help the Tor network. The 20 private cloud relays, were hosted in City 1, USA; 32 Online SAS relays in Paris, France; 8 Online SAS relays in Amsterdam, Netherlands, 6 Vultr relays in Frankfurt, Germany; 6 Vultr relays in London, UK; 2 Vulr relays in Miami, USA; 2 Vultr relays in Atlanta, USA; 2 Vultr relays in Chicago, USA; and 2 Vultr relays in Dallas, USA. Table [I](#page-7-1) summarizes the distribution of our relays per country, city, and cloud provider. Please note that the count is the number of the relays, not the number of VM instances. There are two relays per VM instance, since only two relays can run on a single IP address, per Tor policies.

We made modifications to the Tor software to log the hash of the hidden services and the time they were uploaded to the HSDirs into an in-memory database. For privacy and security reasons, we used the Redis in-memory database, with the persistence storage disabled. As a result, as soon as the machine is restarted, all unencrypted data that resides in the memory will be deleted. We implemented the privacy preserving counting and aggregation in Python. At the end of each 24 hour epoch, the Python program reads the data from the Redis database, writes the encrypted data to disk, and flushes the databases. At the end of each cycle, we publish the data to the PBB. We used a private git server as our PBB, to collect data from all DCs. When the data collection phase is over, all TKS aggregate the counts, calculate their contributions and publish it to the PBB as well.

Note that the encrypted data on the DCs, cannot be decrypted until all parties participate. The reason behind using a k out of n (where $k = n$) encryption technique is to ensure the security of the collected data. Even if parties are coerced in disclosing their private keys, as long as one party deletes his private key, the encrypted data cannot be decrypted. Moreover, both our DCs and the TKSs reside in different geolocations with different jurisdictions, which makes the coercion of the private keys less practical.

Fig. 8: Expected counts at HSDirs as a function of lifespan. As we can see, 95% of the expected values are within two standard deviation of the mean expected value.

Figure [7](#page-8-1) depicts the geolocation distribution of our HSDir relays. As evident, we distributed our servers to different geolocations for security and privacy reasons. Furthermore, we helped the Tor network by contributing relays and bandwidth at different data servers.

VI. RESULTS

In this section, we discuss the results and findings of our study. As mentioned previously, we deployed 80 HSDirs over a range of public and private cloud providers. Our experiments lasted for 180 days, from September 15, 2017 to March 15, 2018. During this period, we collected the lifespan counts for 317090 hidden services from our relays.

We use simulations to find the expected observation counts as a function of the lifespan of a hidden service for the duration of the our study. Figure [8](#page-8-2) shows the expected values for lifespan of hidden services. We calculate the mean, one standard deviation, two standard deviations and 95% of the values from the mean value. The distribution of expected counts follows the bell curve distribution. As we can see, 95% of the expected values are within two standard deviations of the mean expected value.

Figure [9](#page-9-0) plots the distribution of the extrapolated lifespan and the raw lifespan counts from the HSDirs. As we can see around 50% of the collected hidden services have count of 1. However, in the extrapolated lifespan graph, the majority of the hidden services have an estimated lifespan of 2 days. This is because if a hidden service has a count of 1, it can be, with a high probability, a hidden service with lifespan of 1, 2, 3, or higher. However, if a hidden service is counted 2 times, it can only have a minimum lifespan of 2 days. This imbalance between the estimated lifespan and the observed counts for values less than 10, explains the different distribution shape between the raw lifespan counts and the estimated lifespan of hidden services.

Figure [10](#page-9-1) depicts the CDF of the observed counts and the estimated lifespan. More than 60% of hidden services are

Fig. 9: Distribution of the estimated lifespan and raw lifespan counts from the HSDirs.

Fig. 10: CDF of distribution of the estimated lifespan and raw lifespan counts from the HSDirs.

observed 2 times or less on the HSDirs. At the same time, more than 50% of the hidden services, have an estimated lifespan of less than 10 days, where 40% of them are online for only less than a week. Our results show that a large majority of hidden services, have short lifespan, less than a few weeks. Our findings confirms the results of previous work [\(20\)](#page-11-4), regarding the number of hidden services with short life span. However, the previous work did not consider any safeguards, and their results were based on the probing of the collected onion address from their HSDirs, which is against Tor user agreement. In contrast, our work does not store any information about the onion services. Furthermore, we do not perform any probing of the hidden services. Our results rely on the extrapolation of lifespan based on the privacy-preserving aggregated counts from a small number of hidden service (2% of the hidden services).

Without a holistic view of all the hidden services (i.e., controlling all HSDirs), it is difficult and non-trivial to draw conclusions on the churn of the hidden services. However, by using the hidden services statistics that the Tor project collects from all relays and the lifespan of hidden services, it can be inferred that the hidden services have a high churn. A possible explanation for such short-lived hidden services with high churn can be the dynamics and behavior of the applications that use hidden services. For example, OnionShare, a secure and private file sharing that uses Tor hidden services, creates a new random hidden service address for each file transfer. As soon as the file is downloaded by the recipients, the hidden service is discarded.

VII. RELATED WORK

Previous work looking at hidden services [\(20\)](#page-11-4), did not consider any safeguards, and their results were based on the probing of the collected onion address from their HSDirs, which is clearly against Tor user agreement. In contrast, our work does not store any information about the onion services. Furthermore, we do not perform any probing of the hidden services.

In this section, we review the related work on study of Tor hidden services, and advancements in the privacy preserving data collection and analytics.

One of the first studies on the Tor network by McCoy et al. [\(18\)](#page-11-5), collected data from the network by participating and contributing relays to the Tor network. The authors were studying three main questions: "How is Tor being used?", "How is Tor being mis-used?", and "Who is using Tor?". Although such research questions and their answers are important, unfortunately, the authors did not use the required safeguards to protect the privacy of users, and mitigate against its compromise. Another example of studies looking at Tor and hidden services that does not implement security and privacy safeguards is [\(20\)](#page-11-4), where authors collect information about hidden services by setting up HSDirs. Additionally, the authors actively probe the collected hidden services for content. Such work, have been widely criticized by other researchers [\(24\)](#page-11-6) and the Tor Project. As a result tools such as ExperimenTor [\(2\)](#page-10-6) and Shadow [\(13\)](#page-10-7) were introduced, for researchers to experiment with simulated Tor network. As a measure to prevent future unethical work, the Tor Research Safety Board [\(1\)](#page-10-8) was established to review the research projects studying the Tor network, to ensure such works do not harm users' privacy. In the next section we will further discuss the Tor Research Safety Board.

One of the early works on privacy preserving data collection and study of the Tor network, specially hidden services, is a work by the Tor team [\(12\)](#page-10-9) to collect and count the number of unique hidden services. The authors use differential privacy, controlled noise addition to the statistics, and limiting accuracy to a certain granularity via binning. However, this work does not study the lifespan, or the nature of hidden services and how they are used. This is mainly because reporting such statistics, might harm the privacy of individual Tor users.

The closest study to our work is PrivEx [\(9\)](#page-10-1), which our privacy preserving counting protocol is based upon. In this work, the authors introduce two variants for secure counting. One with a shared secret key and another one that relies on multi-party computation. Our work uses the second variant. The authors implement and deploy their protocol to collect and study egress traffic from Tor, and case study the popularity of certain Internet website in different locations. Such work can be used to investigate the censorship of content in different locations, in a privacy preserving manner. PrivCount [\(14\)](#page-10-2) is another work that relies on PrivEx, for measuring the Tor network designed with user privacy as a primary goal. It aggregates the collected data from different Tor relays to produce differentially private outputs. Another work that uses shuffling of the data to hide relations between the elements and counts is PSC [\(10\)](#page-10-10), which is a work on private set union cardinality [\(8\)](#page-10-11).

Another work [\(15\)](#page-10-12) uses Tor circuit and website fingerprinting techniques from the middle relays to detect the hidden services popularity and usage. Furthermore, the authors use their fingerprinting technique to study the popularity of a social networking hidden service, by setting up middle relays in the Tor network. The authors demonstrate the possibility of such passive study in a privacy preserving manner from the middle relays. In another work [\(17\)](#page-11-7), the authors introduce Histor, which relies on differential privacy to collect and analyze information about Tor statistics.

Privacy preserving techniques are also being used in machine learning and deep learning algorithms for secure aggregation of high-dimensional data. For example, [\(4\)](#page-10-13) allows the computation of sum of large values at the honest-butcurious and active adversary server, using the data from different clients. Dolev et al. [\(7\)](#page-10-14) introduce privacy preserving algorithms for computation and performing search, fetch, and range queries with the map-reduce framework. Related to our work is also Prio [\(6\)](#page-10-15), a privacy-preserving system for the collection of aggregate statistics.

VIII. CONCLUSION

Tor and hidden services attracted a large user base in the past few years. Investigating the hidden services dynamics and pro-actively protecting them against abuse and subversion is crucial in their success. Given the strict privacy requirement and security assumption of Tor, it is important to consider the implication of data collection and analysis in such infrastructure. In this paper, we demonstrate that it is possible to carryout a privacy-preserving study of hidden services longevity, satisfying the Tor safety board requirements, yet obtaining fairly accurate estimations.

REFERENCES

- [1] Tor research safety board. ["h](")ttps://research.torproject.org/safetyboard.html".
- [2] K. Bauer, M. Sherr, D. McCoy, and D. Grunwald. Experimentor: a testbed for safe and realistic tor experimentation. In *Proceedings of the 4th conference on Cyber security experimentation and test*. USENIX Association, 2011.
- [3] S. Bayer and J. Groth. Efficient zero-knowledge argument for correctness of a shuffle. In *Advances in Cryptology - EUROCRYPT 2012 - 31st Annual International Conference on the Theory and Applications of*

Cryptographic Techniques, Cambridge, UK, April 15-19, 2012. Proceedings, pages 263–280, 2012.

- [4] K. Bonawitz, V. Ivanov, B. Kreuter, A. Marcedone, H. B. McMahan, S. Patel, D. Ramage, A. Segal, and K. Seth. Practical secure aggregation for privacy-preserving machine learning. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, CCS '17, 2017.
- [5] R. Canetti, Y. Lindell, R. Ostrovsky, and A. Sahai. Universally composable two-party and multi-party secure computation. In *Proceedings on 34th Annual ACM Symposium on Theory of Computing, May 19-21, 2002, Montreal, Qu ´ ebec, Canada ´* , pages 494–503, 2002.
- [6] H. Corrigan-Gibbs and D. Boneh. Prio: Private, robust, and scalable computation of aggregate statistics. In *Proceedings of the 14th USENIX Conference on Networked Systems Design and Implementation*, NSDI'17, 2017.
- [7] S. Dolev, Y. Li, and S. Sharma. Private and secure secret shared mapreduce. In *IFIP Annual Conference on Data and Applications Security and Privacy*, 2016.
- [8] C. Dong and G. Loukides. Approximating private set union/intersection cardinality with logarithmic complexity. *IEEE Transactions on Information Forensics and Security*, 2017.
- [9] T. Elahi, G. Danezis, and I. Goldberg. Privex: Private collection of traffic statistics for anonymous communication networks. In *Proceedings of the 2014 ACM SIGSAC Conference on Computer and Communications Security*, CCS '14, 2014.
- [10] E. Fenske, A. Mani, A. Johnson, and M. Sherr. Distributed measurement with private set-union cardinality. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*. ACM, 2017.
- [11] J. Furukawa and K. Sako. An efficient scheme for proving a shuffle. In *Advances in Cryptology - CRYPTO 2001, 21st Annual International Cryptology Conference, Santa Barbara, California, USA, August 19-23, 2001, Proceedings*, pages 368–387, 2001.
- [12] D. Goulet, A. Johnson, G. Kadianakis, and K. Loesing. Hidden-service statistics reported by relays. Technical report, NAVAL RESEARCH LAB WASHINGTON DC, 2015.
- [13] R. Jansen and N. Hooper. Shadow: Running tor in a box for accurate and efficient experimentation. Technical report, MINNESOTA UNIV MINNEAPOLIS DEPT OF COMPUTER SCIENCE AND ENGINEERING, 2011.
- [14] R. Jansen and A. Johnson. Safely measuring tor. In *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security*, CCS '16, 2016.
- [15] R. Jansen, M. Juarez, R. Galvez, T. Elahi, and C. Diaz. Inside job: Applying traffic analysis to measure tor from within. In *Network and Distributed System Security Symposium (NDSS)*, 2017.
- [16] G. Kadianakis and K. Loesing. Extrapolating network totals from hidden-service statistics. Technical report, Tor Tech Repor, 2015.
- [17] A. Mani and M. Sherr. Histore: Differentially Private and Robust Statistics Collection for Tor. In *Network and Distributed System Security Symposium (NDSS)*, February 2017.
- [18] D. McCoy, K. Bauer, D. Grunwald, T. Kohno, and D. Sicker. Shining light in dark places: Understanding the tor network. In *International Symposium on Privacy Enhancing Technologies Symposium*, pages 63–76. Springer, 2008.
- [19] C. A. Neff. A verifiable secret shuffle and its application to e-voting. In *Proceedings of the 8th ACM Conference on Computer and Communications Security*, CCS '01, 2001.
- [20] G. Owen and N. Savage. The tor dark net. 2015.
- [21] J. Pollard. Monte Carlo methods for index computation (mod p). *Mathematics of Computation*, 32, 1978.
- [22] J. M. Pollard. Kangaroos, monopoly and discrete logarithms. *Journal of Cryptology*, 13, 2000.
- [23] D. Shanks. Class number, a theory of factorization and genera. *Proceedings of Symposium of Pure Mathematics*, 20, 1969.
- [24] C. Soghoian. Enforced community standards for research on users of the tor anonymity network. In *International Conference on Financial Cryptography and Data Security*, 2011.