IEEE Transactions on Geoscience and Remote Sensing December 2011, Vol. 49 (12), pp. 4856-4864

http://dx.doi.org/ [10.1109/TGRS.2011.2152848](http://dx.doi.org/%2010.1109/TGRS.2011.2152848) © 2012 IEEE – All Rights Reserved

Analytical Techniques for the Doppler Signature of Sea Surfaces in the Microwave Regime-I: Linear Surfaces

Frédéric Nouguier^{1,*}, Charles-Antoine Guérin², Gabriel Soriano³

¹ IFREMER, Lab Oceanog Spatiale, F-29280 Plouzane, France

² Univ Sud Toulon Var, Unite Mixte Rech 6017, Lab Sondages Electromagnet Environm Terr, Ctr Natl Resch Sci,Geosci & Remote Sensing Dept, F-83957 La Garde, France

³ Univ Aix Marseille 3, Ctr Natl Rech Sci, Unite Mixte Rech 6133, Inst Fresnel, F-13397 Marseille, France

*: Corresponding author : Frédéric Nouguier, email address : frederic.nouguier@gmail.com

Abstract :

This paper is the first in a series of two papers on the use of combined improved hydrodynamic and electromagnetic analytical models for the simulation of the ocean Doppler spectrum at microwave frequencies. Under a linear assumption for the sea surface, we derive statistical expression for the main Doppler characteristics according to asymptotic scattering models. We consider classical models such as the Kirchhoff approximation and the two-scale model, as well as the more recent weighted curvature approximation (WCA). We recover two salient features of Doppler signature in the microwave regime. First, the Doppler characteristics are very sensitive to polarization, with higher mean Doppler shift in horizontal polarization. This is correctly rendered by the WCA but not the classical models. Second, the first two moments of the Doppler spectrum exhibit a nontrivial dependence on incidence angle. Results compare favorably with rigorous numerical computations for 1-D surfaces published in the literature. The simplicity and accuracy of the analytical models provide a valuable tool for the Doppler analysis of 2-D sea surfaces.

Keywords : Doppler spectrum; gravity waves; microwave; remote sensing; rough surfaces; scattering; sea surface

1. Introduction

The Doppler analysis associated to the backscattered radar return from the sea surface is a very valuable tool in ocean remote sensing. The Doppler spectrum indeed carries much more information than a mere radar backscattering cross section under a given incidence and is easily interpretable in terms of wind and current conditions for HF radiowaves (e.g. [1] and references therein). In that case the dominant mechanism is resonant Bragg scattering and the mean Doppler shift is imposed by the so-called free Bragg frequency, namely the frequency associated to the wave with half the electromagnetic wavelength at grazing incidence. The experimental Doppler spectra are accurately modelled by the perturbative theory of Barrick and Weber [2], [3], which describes second-order interactions of both the electromagnetical and hydrodynamical processes.

In the microwave regime, Doppler characteristics turn out to be more complex. A large number of field experiments have been conducted in the last thirty years, most of them at grazing incidence because of practical constraints (e.g. [4] for the Ku-band, [5], [6] for the Xband and [7] for the L-band). The observed Doppler spectra are usually broader than in the HF regime, with a mean frequency sometimes much higher than the free Bragg frequency, depending of wind speed and radar incidence. This effect is more pronounced in horizontal polarization and at large incidences. Today, however, no asymptotic theory is capable of fully explaining and reproducing these experimental observations. The reason is twofold. First, the analytical scattering models [8] have limited range of validity, especially at larger incidences and, second, the hydrodynamical description of nonlinear short gravity waves is still an open issue. The aim of the present work is to go further in this direction by combining recent and efficient scattering and hydrodynamic analytical models. This task will be decomposed in a set of two companion papers. This first paper will put the emphasis on analytical scattering models, whose potential for the Doppler analysis has in our opinion not be fully exploited. To separate electromagnetical and hydrodynamical issues, the sea surface will be assumed linear in this first stage. In a second companion paper, weakly nonlinear analytical models will becombined with the scattering models to reach a complete realistic description of the Doppler spectrum.

The classical approach to tackle the problem relies on the Two-Scale Model (TSM) [9]. More recent results [10], [11], [12], [13] have shown that modern analytical scattering models can account for some characteristic features of microwave Doppler spectra such as the non-trivial dependence of the central frequency upon the incidence angle and its sensitivity to polarization. However, in using such asymptotic techniques a trade-off must be found between the accuracy and robustness of the model and its numerical efficiency. The latter is intimately related to the existence of a statistical formulation for the main Doppler characteristics (central frequency and width) which prevents from time-consuming Monte-Carlo simulations. With this idea in mind we will revisit the classical models starting with the Kirchhoff approximation and its Two-Scale formulation. We will show that extremely simple, yet non trivial formula can be obtained for the central frequency and width of the Doppler spectrum. These models, however, apply to a limited incidence range and are polarization insensitive. We will show that a more accurate electromagnetic description can be reached with the Weighted Curvature Approximation [14], [15], whose recently improved formulation [16] is adapted to a fully analytical derivations of the Doppler spectrum.

The theory will be developped for fully two-dimensional (2D) surfaces and, in most cases, analytical formulas will be given for the central frequency and width of the Doppler spectrum, which can be easily implemented. At this stage, however, our goal is not to produce realistic simulations to be compared with experiments but rather to validate the technique. The numerical validation of this and the subsequent studies will therefore be performed for one-dimensional surfaces. This makes the illustration easier and renders a comparison possible with the reference work by Brown and Toporkov [17], who realized a set of extensive simulations according to a rigorous electromagnetical model for one-dimensional (1D) surfaces. Therefore, our numerical tests have been designed identical to those presented in [17], [18], namely 1D surfaces with PM spectrum at L- and X-band for 5 and 7 m.s⁻¹ wind speed (at 19.5 m above the sea level). We are aware that more realistic spectra as PM could have been chosen and certainly will be implemented in future steps. However, this choice is imposed for the moment by the necessity of a fair comparison with the previously cited works.

II. The ocean Doppler spectrum

As usual the sea surface is described by its Cartesian coordinates $z = \eta(\mathbf{r}, t)$, with mean horizontal plane $\mathbf{r} = (x, y)$ and upwards directed vertical axis. From an electromagnetic point of view, the interface separates the upper medium (air), assimilated to vacuum, from the lower medium (water), assumed to be homogeneous and described by its complex permittivity. A fixed coherent radar illuminates the surface at some given frequency and incidence. We assimilate the radar beam to a monochromatic plane wave with wave vector \mathbf{K}_0 , so that $\hat{\mathbf{K}}_0$ will also denote the radar look direction (here and everywhere we use the notation $\hat{\mathbf{u}} = \mathbf{u}/||\mathbf{u}||$ for the direction of a vector). Denoting $S(t)$ the backscattered amplitude from the frozen surface at time t (we refer to $[8]$ for the exact definition), the time covariance function of the

backscattered field is the limit of the statistical average:

$$
\mathcal{C}(t) = \frac{4\pi}{|A|} \left(\langle \mathbb{S}(t) \mathbb{S}^*(0) \rangle - |\langle \mathbb{S}(0) \rangle|^2 \right) \tag{II.1}
$$

for an infinite illumination area |A|. Note that $\mathcal{C}(0)$ is the classical definition of the Normalized Radar Cross Section (NRCS). The Doppler spectrum is the corresponding Fourier transform:

$$
D(\omega) = \int_{\mathbb{R}} e^{-i\omega t} C(t) dt
$$
 (II.2)

and $f = \omega/(2\pi)$ is the Doppler frequency shift. Waves travelling away from the radar mainly contribute to negative Doppler shifts while waves travelling towards the radar mainly create positive shifts. Thus Doppler spectra usually contains two peaks with different amplitudes depending on the radar look direction. This is illustrated on Figure 1(a). For 1D surfaces, it is customary to consider one-sided sea spectra corresponding to waves travelling to the left (or right) direction. In that case the Doppler spectrum is centered around some positive (or negative) peak frequency and the Doppler centroïd f_c and width γ can be defined through the first two moments of the spectrum:

$$
f_c = \frac{\omega_c}{2\pi} = \frac{1}{2\pi} \frac{\int_{\mathbb{R}} \omega D(\omega) d\omega}{\int_{\mathbb{R}} D(\omega) d\omega} \quad \text{and} \quad \gamma^2 = \frac{1}{(2\pi)^2} \frac{\int_{\mathbb{R}} \omega^2 D(\omega) d\omega}{\int_{\mathbb{R}} D(\omega) d\omega} - f_c^2 \quad (II.3)
$$

The notion of one-sided spectrum can be extended to the case of 2D surfaces by artificially restricting the sea spectrum to waves travelling towards (or away from) the radar. This amounts to keep waves directions in the same (or opposite) half-plane as the radar look direction $\hat{\mathbf{K}}_0$ as shown on Figure 1(b). Positive shift is arbitrary chosen and imply that the propagation half-plane is defined by sgn $(\widehat{K}_0 \cdot \widehat{k}) < 0$ where k is the considered wave direction and sgn is the sign function (sgn(x) = ± 1 if $x \ge 0$). Note that we thereby ignore the contribution of waves travelling away from the radar to positive frequencies and vice versa. In reality, the spectral density varies continuously as a function of the azimuth angle with respect to the wind direction and the notion of half-sided spectrum is purely artificial. In the practical case of a two-sided spectrum, there are two Doppler centroids along and against the wind direction. Under theses circumstances the definition of a central peak through the first moment is irrelevant as sign cancellations in the integral will produce some meaningless intermediate value. The solution is to calculate the center of each peak for the two half-spectra separately. One should keep this in mind when using the main results of this paper.

III. The time-evolving linear sea surface

Without loss of generality (waves propagate in all directions), we can represent a linear time-dependent surfaces in the form:

$$
\eta(\mathbf{r},t) = \int_{\mathbb{R}^2} d\mathbf{k} \left[a(\mathbf{k}) e^{-i\omega_{\mathbf{k}}t} + a^*(-\mathbf{k}) e^{i\omega_{\mathbf{k}}t} \right] e^{i\mathbf{k}\cdot\mathbf{r}}
$$
(III.4)

where $a(\mathbf{k})$ is the complex amplitude of the wave, **k** the associated wave number and $\omega_{\mathbf{k}} = \sqrt{g|\mathbf{k}|(1+|\mathbf{k}|^2/k_M^2)}$ is the gravity-capillarity dispersion relationship $(k_M = 363.2 \text{ rad.m}^{-1})$ is the wave number with minimum

phase speed). In the linear assumption, the phases of the different complex amplitudes are supposed to be uncorrelated. Denoting $\rho(\mathbf{r}, t) = \langle \eta(\mathbf{r}, t) \eta(\mathbf{0}, 0) \rangle$ the spatio-temporal covariance function of the surface, it follows that:

$$
\rho(\mathbf{r},t) = \int_{\mathbb{R}^2} d\mathbf{k} \left[\Gamma_a(\mathbf{k}) e^{-i\omega_{\mathbf{k}}t} + \Gamma_a(-\mathbf{k}) e^{i\omega_{\mathbf{k}}t} \right] e^{i\mathbf{k}\cdot\mathbf{r}}
$$
(III.5)

where $\Gamma_a(\mathbf{k})$ defined by $\langle a(\mathbf{k})a^*(\mathbf{k}')\rangle = \Gamma_a(\mathbf{k})\delta(\mathbf{k}-\mathbf{k}')$ is the square amplitude of waves travelling in different azimutal directions. Assuming the waves to travel only towards (or away from) the radar is equivalent to supposing that $\Gamma_a(\mathbf{k})$ vanishes in the half-space of waves number pointing in the radar look direction $(\hat{\mathbf{k}} \cdot \hat{\mathbf{K}}_0 > 0)$, i.e. Γ_a is half-sided. Using this assumption, equation (III.5) can be rewritten as:

$$
\rho(\mathbf{r},t) = \int_{\mathbb{R}^2} d\mathbf{k} \, \Gamma(\mathbf{k}) e^{i(\mathbf{k}\cdot\mathbf{r} + \text{sgn}(\hat{\mathbf{k}}\cdot\hat{\mathbf{k}}_0)\omega_{\mathbf{k}}t)} \tag{III.6}
$$

where $\Gamma(\mathbf{k}) = \Gamma_a(\mathbf{k}) + \Gamma_a(-\mathbf{k})$ is the usual centro-symetric wave vector spectrum.

Figure 2 displays an example of the spatio-temporal covariance function $\rho(x, t)$ for 1D surfaces whith wind speed $U_{19.5} = 7 \text{ m.s}^{-1}$. Along this paper we use the omnidirectional PM spectrum, $\Gamma(k)$ $\frac{1}{2}\Gamma_{\text{PM}}(|k|),$ where

$$
\Gamma_{\rm PM}(k) = \frac{\alpha}{2|k|^3} \exp\left\{-\frac{\beta g^2}{k^2 U_{19.5}^4}\right\}
$$
\n(III.7)

with $\alpha = 8.1 \text{ } 10^{-3}$ and $\beta = 0.74$. The extra factor $\frac{1}{2}$ accounts for the fact that energy is equally spread over both positive and negative axis. Note that this is different from [17]) who chosed the half-sided PM spectrum (i.e. expression (III.7) for positive k only, zero otherwise). However in our basic assumption that the negative wave numbers do not contribute to positive Doppler shifts this amounts to the same. Again, we insist on the fact that the choice of the PM spectrum along this work is imposed by a first stage of validation after the results of [17], even if it is less realistic than some more recent spectra.

In both cases, waves are travelling in the positive x direction only $(K_0 < 0)$. We note in passing that the covariance function oscillates both in time and space and is localized around the diagonal $k_p x - \omega_{k_p} t = 0$, where k_p is the peak frequency. As a consequence, its spatial range varies with time. This makes the computation of the field covariance function (see eq. (IV.9) further) more difficult than an ordinary NRCS.

IV. The Kirchhoff Approximation

The back-scattered amplitude in the Kirchhoff Approximation (KA, [19]) is given by:

$$
\mathbb{S}_{KA}(t) = \frac{\mathbb{K}}{Q_z} \int_{\mathbb{R}^2} \frac{d\mathbf{r}}{(2\pi)^2} e^{i\mathbf{Q_H} \cdot \mathbf{r}} e^{iQ_z \eta(\mathbf{r}, t)}
$$
(IV.8)

where we have introduced the so-called Ewald vector $\mathbf{Q} = -2\mathbf{K}_0$, together with its horizontal and vertical projections \mathbf{Q}_H and Q_z , respectively. Here K is the Kirchhoff kernel whose expression can be found in e.g. [8]. If the surface is assumed to be a Gaussian random process, a classical calculation leads to the following expression for the field time covariance function:

$$
C_{KA}(t) = \frac{1}{Q_z^2} \frac{|\mathbb{K}|^2}{\pi} \int_{\mathbb{R}^2} d\mathbf{r} \, e^{i\mathbf{Q_H} \cdot \mathbf{r}} \, \left[e^{-Q_z^2(\rho(\mathbf{0},0) - \rho(\mathbf{r},t))} - e^{-Q_z^2\rho(\mathbf{0},0)} \right]. \tag{IV.9}
$$

J

The Doppler spectrum at every incidence angle can be computed in a three-step procedure through successive evaluation of the spatio-temporal covariance function, the field covariance function $\mathcal{C}_{KA}(t)$ and its Fourier transform. The Doppler central frequency (f_c) and width (γ) can then be obtained through the moments (II.3). Numerical details are given in Appendix B. However, in the KA framework, a more direct derivation of these quantities can be made by noting that:

$$
\int_{\mathbb{R}} \omega D(\omega) d\omega = -i \left. \frac{\partial \mathcal{C}}{\partial t} \right|_{t=0} \tag{IV.10}
$$

$$
\int_{\mathbb{R}} \omega^2 D(\omega) d\omega = -\frac{\partial^2 C}{\partial t^2}\Big|_{t=0},
$$
\n(IV.11)

which leads to:

$$
2\pi f_c = -iQ_z^2 N^{-1} \int_{\mathbb{R}^2} d\mathbf{r} e^{i\mathbf{Q_H} \cdot \mathbf{r}} \partial_t \rho(\mathbf{r}, 0) e^{-Q_z^2(\rho(\mathbf{0}, 0) - \rho(\mathbf{r}, 0))}
$$
(IV.12)

$$
(2\pi\gamma)^2 + \omega_c = -Q_z^2 N^{-1} \int_{\mathbb{R}^2} d\mathbf{r} e^{i\mathbf{Q_H}\cdot\mathbf{r}} \left[\partial_{t^2} \rho(\mathbf{r}, 0) + Q_z^2 (\partial_t \rho(\mathbf{r}, 0))^2 \right] e^{-Q_z^2(\rho(\mathbf{0}, 0) - \rho(\mathbf{r}, 0))} (IV.13)
$$

where

$$
N = \int_{\mathbb{R}^2} d\mathbf{r} \ e^{i\mathbf{Q_H} \cdot \mathbf{r}} \left[e^{-Q_z^2(\rho(\mathbf{0},0) - \rho(\mathbf{r},0))} - e^{-Q_z^2 \rho(\mathbf{0},0)} \right]
$$
(IV.14)

$$
\partial_t \rho(\mathbf{r}, 0) = i \int_{\mathbb{R}^2} d\mathbf{k} \, \text{sgn}(\hat{\mathbf{K}}_0 \cdot \hat{\mathbf{k}}) \omega_\mathbf{k} \, \Gamma(\mathbf{k}) e^{i\mathbf{k} \cdot \mathbf{r}} \tag{IV.15}
$$

$$
\partial_{t^2} \rho(\mathbf{r}, 0) = - \int_{\mathbb{R}^2} d\mathbf{k} \,\,\omega_{\mathbf{k}}^2 \Gamma(\mathbf{k}) e^{i\mathbf{k} \cdot \mathbf{r}}
$$
 (IV.16)

Equations (IV.15) and (IV.16) are derived from equation (III.6) but their general forms can be derived from the expression of ρ at equation (III.5). Hence, under the KA and the linear assumption for the sea surface, the central Doppler frequency and its width can be calculated at the same cost as a classical NRCS.

V. Doppler spectrum in the TSM approximation

In order to derive fully analytical expressions for the Doppler centroïd and width in the framework of the KA, we use a Two-Scale argument in a way very similar to [9]. We decompose the spectrum into small and large scales components, $\Gamma_a = \Gamma_{aL} + \Gamma_{as}$. We call the ρ_L and ρ_s , respectively, the corresponding covariance functions:

$$
\rho_{s/L}(\mathbf{r},t) = \int_{\mathbb{R}^2} d\mathbf{k} \left[\Gamma_{as/aL}(\mathbf{k}) e^{-i\omega_{\mathbf{k}}t} + \Gamma_{as/aL}(-\mathbf{k}) e^{i\omega_{\mathbf{k}}t} \right] e^{i\mathbf{k}\cdot\mathbf{r}}
$$
(V.17)

For sea spectra, a separation frequency around Bragg wavenumber ensures that $Q_z^2 \rho_s(\mathbf{0},0) \ll 1$, so we may treat the small scales perturbatively in the exponential:

$$
\mathcal{C}(t) \simeq \frac{|\mathbb{K}|^2}{\pi Q_z^2} \left(\int_{\mathbb{R}^2} d\mathbf{r} \, \mathrm{e}^{\mathrm{i}\mathbf{Q_H} \cdot \mathbf{r}} \left[\mathrm{e}^{-Q_z^2(\rho_L(0,0) - \rho_L(\mathbf{r},t))} - \mathrm{e}^{-Q_z^2 \rho_L(0,0)} \right] + Q_z^2 \int_{\mathbb{R}^2} d\mathbf{r} \rho_s(\mathbf{r},t) \mathrm{e}^{\mathrm{i}\mathbf{Q_H} \cdot \mathbf{r}} \mathrm{e}^{-Q_z^2(\rho_L(0,0) - \rho_L(\mathbf{r},t))} \right)
$$
\n
$$
(V.18)
$$

The first integral is the field covariance function of a smooth surface (large scale only) and thus has negligible effect in backscattering direction away from nadir. The second integral is mainly controlled by the behavior of the large-scale correlation function ρ_L at small space and time lags. Therefore we may operate a "geometrical-optics like" expansion about the origin:

$$
\rho_L(0,0) - \rho_L(\mathbf{r},t) \simeq \frac{1}{2} [x, y, t] \cdot \Sigma_L \cdot [x, y, t]^\mathrm{T},\tag{V.19}
$$

where the subscript T indicates the transposed vector and

$$
\Sigma_L = \begin{bmatrix} \sigma_{200}^2 & \sigma_{110}^2 & \sigma_{101}^2 \\ \sigma_{110}^2 & \sigma_{020}^2 & \sigma_{011}^2 \\ \sigma_{101}^2 & \sigma_{011}^2 & \sigma_{002}^2 \end{bmatrix}
$$
 (V.20)

is the spatio-temporal covariance matrix of large-scale slopes. Its elements,

$$
\sigma_{\alpha\beta\nu}^2 = -\left. \frac{\partial^2 \rho_L}{\partial x^\alpha \partial y^\beta \partial t^\nu} \right|_{\mathbf{r} = 0, t = 0} \tag{V.21}
$$

are the cross mean square slopes with respect to the space and time variables. After Fourier transform we obtain the Doppler spectrum:

$$
D(\omega) \propto \int_{\mathbb{R}^3} dt \, d\mathbf{r} \, e^{i\mathbf{Q_H} \cdot \mathbf{r}} e^{-i\omega t} \rho_s(\mathbf{r}, t) \exp\left(-\frac{1}{2} Q_z^2[\mathbf{r}, t]^{\mathrm{T}} \cdot \Sigma_L \cdot [\mathbf{r}, t]\right) \tag{V.22}
$$

which can conveniently be rewritten as a convolution integral:

$$
D(\omega) \propto \int_{\mathbb{R}^3} d\mathbf{k}' d\omega' \ \hat{\rho}_s(\mathbf{k}', \omega') P_{Q_z^2 \Sigma_L}(\mathbf{Q}_H - \mathbf{k}', \omega - \omega'). \tag{V.23}
$$

Here we have introduced $P_{Q_z^2 \Sigma_L}$ the three-dimensional Gaussian centered probability density with subscripted covariance matrix:

$$
P_{Q_z^2 \Sigma_L}(\mathbf{u}, v) = \frac{1}{(2\pi |Q_z^2 \Sigma_L|)^{3/2}} \exp\left(-\frac{1}{2Q_z^2}[\mathbf{u}, v]^\mathrm{T} \cdot \Sigma_L^{-1} \cdot [\mathbf{u}, v]\right)
$$
(V.24)

and $\hat{\rho}_s$ the three-dimensional Fourier transform of the surface covariance function:

$$
\widehat{\rho}_s(\mathbf{k}, \omega) = \frac{1}{(2\pi)^3} \int_{\mathbb{R}^3} dt \, d\mathbf{r} \, e^{-i\mathbf{k} \cdot \mathbf{r}} e^{-i\omega t} \rho_s(\mathbf{r}, t). \tag{V.25}
$$

This leads to a reduction of the Doppler spectrum :

$$
D(\omega) \propto \int_{\mathbb{R}^2} d\mathbf{k}' \ \Gamma_{as}(\mathbf{k}') P_{Q_z^2 \Sigma_L} \left(\mathbf{Q}_H - \mathbf{k}', \omega - \omega_{\mathbf{k}'} \right) + \int_{\mathbb{R}^2} d\mathbf{k}' \ \Gamma_{as}(-\mathbf{k}') P_{Q_z^2 \Sigma_L} \left(\mathbf{Q}_H - \mathbf{k}', \omega + \omega_{\mathbf{k}'} \right) \tag{V.26}
$$

where $\omega_{\mathbf{k'}} = \sqrt{g|\mathbf{k'}|(1+|\mathbf{k'}|^2/k_M^2)}$. In the case of half-sided spectra we may restrict the waves numbers **k** to the half-plane $\mathbf{k} \cdot \hat{\mathbf{K}}_0 < 0$, that is we may assume that Γ_{as} vanishes over the half-space $\mathbf{k} \cdot \hat{\mathbf{K}}_0 > 0$. Hence we can rewrite the Doppler spectrum in terms of centro-symmetric spectrum $\Gamma_s(\mathbf{k}) = \Gamma_{as}(\mathbf{k}) + \Gamma_{as}(-\mathbf{k})$:

$$
D(\omega) \propto \int_{\mathbb{R}^2} d\mathbf{k} \, \Gamma_s(\mathbf{k}) P_{Q_z^2 \Sigma_L} \left(\mathbf{Q}_H - \mathbf{k}, \omega + \text{sgn} \left(\hat{\mathbf{k}} \cdot \hat{\mathbf{K}}_0 \right) \omega_\mathbf{k} \right) \tag{V.27}
$$

and same for the elements of the covariance matrix:

$$
\sigma_{\alpha\beta\nu}^{2} = \int_{\mathbb{R}^{2}} \left(\text{sgn} \left(\hat{\mathbf{k}} \cdot \hat{\mathbf{K}}_{0} \right) \omega_{\mathbf{k}} \right)^{\nu} k_{x}^{\alpha} k_{y}^{\beta} \Gamma_{L}(\mathbf{k}) dk_{x} dk_{y}. \tag{V.28}
$$

After some algebraic manipulations, the first two moments of the Doppler spectrum can be easily extracted. Altogether we obtain (we have dropped the \mathbf{K}_0 variable using the replacement $\hat{\mathbf{Q}}_H = -\hat{\mathbf{K}}_0$):

$$
\omega_c = A^{-1} \int_{\mathbb{R}^2} d\mathbf{k} \, \Gamma_s(\mathbf{k}) P(\mathbf{Q}_H - \mathbf{k}) \left(\text{sgn} \left(\hat{\mathbf{k}} \cdot \hat{\mathbf{Q}}_H \right) \omega_\mathbf{k} + (\mathbb{M} \mathbf{T}) \cdot (\mathbf{Q}_H - \mathbf{k}) \right) \tag{V.29}
$$

$$
(2\pi\gamma)^2 + \omega_c^2 = A^{-1} \int_{\mathbb{R}^2} d\mathbf{k} \Gamma_s(\mathbf{k}) P(\mathbf{Q}_H - \mathbf{k}) \left(\chi Q_z^2 + \left[\text{sgn}\left(\hat{\mathbf{k}} \cdot \hat{\mathbf{Q}}_H \right) \omega_{\mathbf{k}} + (\mathbb{M}\mathbf{T}) \cdot (\mathbf{Q}_H - \mathbf{k}) \right]^2 \right) \mathbf{y}.30
$$

with

$$
A = \int d\mathbf{k} \Gamma_s(\mathbf{k}) P(\mathbf{Q}_H - \mathbf{k}).
$$
 (V.31)

Here we have written P for the two-dimensional Gaussian with covariance symetric matrix $Q_z^{-2}M$, where

$$
\mathbb{M} = \begin{bmatrix} \sigma_{200}^2 & \sigma_{110}^2 \\ \sigma_{110}^2 & \sigma_{020}^2 \end{bmatrix}^{-1} , \quad \chi = |\Sigma_L||\mathbb{M}| = \sigma_{002}^2 - \mathbf{T}^T \mathbb{M} \mathbf{T} \quad \text{and} \quad \mathbf{T} = [\sigma_{101}^2 & \sigma_{011}^2]^T. \tag{V.32}
$$

These expressions for the position and width of the Doppler spectrum are much simpler to evaluated numerically than the formulas (IV.12) and (IV.13) derived in the framework of KA, as they do not require the computation of the spatiotemporal covariance function. They merely involve the small-scale spectrum (Γ_s) and some moments of the large-scale spectrum (Γ_L) . For 1D surfaces the quantities M, T and χ reduce to $1/\sigma_{20}^2$, σ_{11}^2 and $(\sigma_{20}^2 \sigma_{02}^2 - \sigma_{11}^4)/\sigma_{20}^2$, respectively, with the notation:

$$
\sigma_{\alpha\nu}^2 = \int_{\mathbb{R}} k^{\alpha} \left(\text{sgn}(k)\omega_k \right)^{\nu} \Gamma_L(k) \, dk \tag{V.33}
$$

for the signed moments of the spectrum. The expressions $(V.29)$ and $(V.30)$ can be further simplified whenever the components of \mathbb{M}^{-1} are very small compared to unity, which is usually the case since they have the order of magnitude of mean square slopes. In that case the Gaussian term P is a sharp peak about the Bragg frequency, over which the spectrum can be supposed to be slowly varying. Mathematically, this mean that the Gaussian integrand and its polynomial factor can be replaced by a combination of delta functions and their derivative about the Bragg wave number \mathbf{Q}_H . Tedious but straightforward calculations lead to:

$$
\omega_c = \omega_{\mathbf{Q}_H} - Q_z^2 \frac{[\nabla_{\mathbf{k}} \Gamma_s](\mathbf{Q}_H)}{\Gamma_s(\mathbf{Q}_H)} \cdot \mathbf{T}
$$
\n(V.34)

$$
(2\pi\gamma)^2 = Q_z^2 \left(\sigma_{002}^2 - \widehat{\mathbf{Q}}_H \cdot \mathbf{T} \left(\frac{g(1+3|\mathbf{Q}_H|^2/k_M^2)}{\omega_{\mathbf{Q}_H}} \right) + Q_z^2 \mathbf{T}^{\mathrm{T}} \cdot \nabla_{\mathbf{k}} \left[\frac{\nabla_{\mathbf{k}} \Gamma_s}{\Gamma_s} \right]_{\mathbf{k} = \mathbf{Q}_H} \cdot \mathbf{T} \right) (V.35)
$$

where $\omega_{\mathbf{Q}_H} = \sqrt{g|\mathbf{Q}_H|(1 + |\mathbf{Q}_H|^2/k_M^2)}$ is the free Bragg wave pulsation and $\nabla_{\mathbf{k}}$ the gradient operator relative to the wavenumber variable. These simple formulas show that under the TSM starting from the KA the main Doppler characteristics only depend on the level and shape of the wave number spectrum

at the Bragg vector. To distinguish them from the previous TSM approximation (V.29) and (V.30), we will refer to this new set of equations as the D-TSM approximation, as a further Dirac approximation is employed to reduce the integral.

To ease the interpretation, let us focus again on 1D surfaces, and suppose that the sea surface wave number spectrum can be locally approximated by a power-law in the region of Bragg's wavenumber:

$$
\Gamma(k) \sim k^{-\mu} \tag{V.36}
$$

Then the approximate Doppler central frequency and width reduce to:

$$
f_c = \frac{1}{2\pi} \left(\omega_{Q_H} + \mu \frac{Q_z^2 \sigma_{11}^2}{Q_H} \right) \tag{V.37}
$$

$$
\gamma = \frac{1}{2\pi} \sqrt{Q_z^2 \left(\sigma_{02}^2 - g\sigma_{11}^2 \left(\frac{1 + 3Q_H^2/k_M^2}{\omega_{Q_H}}\right) + \mu \sigma_{11}^4 \frac{Q_z^2}{Q_H^2}\right)}.
$$
 (V.38)

Formula (V.37) means that the free Bragg frequency is increased by the contribution of large scales through the moment σ_{11}^2 . To understand the occurence of the latter, it is illuminating to consider the case of a single sinusoidal large wave, say $\Gamma_L(k) = H^2 \delta(k - k_p)$. Then $\sigma_{11}^2 = H^2 k_p \omega_p = H^2 k_p^2 c_p$, where c_p is the phase speed of the large wave. Thus the Doppler shift with respect to the free Bragg frequency is proportional to the phase speed of the large wave, weighted by an angular factor $\cos^2(\theta)/\sin\theta$. Note that this factor blows up at normal incidence. This is, however, not problematic as the formula is not applicable at small incidence where the conditions of reduction of the integrals (V.29) and (V.30) are not met.

Figures 3 and 4 show the Doppler centroïd and width for the three levels of approximation: 1D versions of equations $(IV.12)$ and $(IV.13)$ for the KA, the simplified formulas $(V.29)$ and $(V.30)$ arising from the TSM and the ultimate approximations (V.37) and (V.38) obtained in assimilating the Gaussian integrand to a Dirac function in the TSM (D-TSM) with $\mu = 3$. The wave number cut-off between short and long wave is taken to be $k_c = Q_H/5$ for both TSM and D-TSM, a value which we have numerically checked to validate the TSM (V.18).

The KA and TSM approximation are in good agreement and reveal a non-monotonic behaviour for both the central frequency and width of the Doppler spectrum. At 5 m.s^{-1} wind speed, these quantities reach a maximum about 25 degrees, as already noticed by [17] and [11] and recover the free Bragg frequency position $(f_B = (2\pi)^{-1}\sqrt{gQ_H(1+Q_H^2/k_M^2)}\right)$ and width $(\gamma_B = 0)$ at higher incidence angles. The D-TSM approximation is found to be accurate for incidence angles greater than 45 deg in X band as in L Band (not shown here). This makes the latter approximation valuable in view of its simplicity. Note that TSM shows a correct behavior even at small incidence angles. This is to be expected as the TSM is expected to be a good approximation to the KA from which it is derived. In this respect, an angle-dependent value of the separation frequency between large and small scales is crucial (namely $k_c = Q_H/5$), as it allows to take into account larger scales for the KA term in the nadiral region.

We note that the Kirchhoff kernel K does not appear in the expressions of either f_c or γ . Consequently any approximate scattering model with the same roughness dependence as the KA NRCS (IV.8) will yield identical expressions. This is the case in particular for the first-order Small-Slope Approximation (SSA1, [20])

$$
\mathbb{S}_{SSA}(t) = \frac{\mathbb{B}}{Q_z} \int_{\mathbb{R}^2} \frac{d\mathbf{r}}{(2\pi)^2} e^{i\mathbf{Q_H} \cdot \mathbf{r}} e^{iQ_z \eta(\mathbf{r}, t)}, \qquad (V.39)
$$

which is identical to KA with the Kirchhoff kernel (K) replaced by the Bragg's kernel (B, see [8]). Moreover, KA and thus SSA1 are unsensitive to polarization, which means that they predict the same Normalized Doppler spectrum for both vertical (VV) and horizontal (HH) polarization, an important limitation of the methods.

VI. The Weighted Curvature Approximation

The KA is known to be accurate at small angles and to be unsensitive to polarization effects. In order to extend our methodology to larger angles and to estimate the polarization dependence of the Doppler spectrum we use the so-called Weighted Curvature Approximation (WCA). Recently revisited by [16] this approximation introduced in [14] was shown capable to predict reasonably the NRCS from rough surfaces for both polarizations to about 80 degrees incidence angle. The scattering amplitude in the WCA [16] writes as a correction to the tangent plane approximation in the form of a Kirchhoff integral involving second-order spatial derivatives of the surface (that is essentially its curvatures):

$$
\mathbb{S}_{WCA}(t) = \mathbb{S}_{KA}(t) + \mathbf{i} \frac{\mathbb{T}}{Q_H^2} \int_{\mathbb{R}^2} \frac{d\mathbf{r}}{(2\pi)^2} \Delta \eta(\mathbf{r}, t) e^{i\mathbf{Q_H} \cdot \mathbf{r}} e^{iQ_z \eta(\mathbf{r}, t)}, \qquad (VI.40)
$$

where the kernel $\mathbb{T} = \mathbb{B} - \mathbb{K}$ is the difference between the Bragg and Kirchhoff kernel and $\Delta \eta$ is the spatial Laplacian of the surface. For 2D surfaces, the second-order differential operator involved in the Kirchhoff integral can actually take a more general form than a mere Laplacian. However, for sea surfaces, all admissible operators have been shown in [16] to yield equivalent values for the NRCS (the so-called universal WCA), so that we will adopt the Laplacian kernel for simplicity. For 1D surfaces, there is no such ambiguity as all admissible second-order differential operators reduce to a second-order spatial derivative (η'') of the surface:

$$
\mathbb{S}_{WCA}(t) = \mathbb{S}_{KA}(t) + \mathbf{i}\frac{\mathbb{T}}{Q_H^2} \int_{\mathbb{R}} \frac{dx}{2\pi} \eta''(x, t) e^{\mathbf{i}Q_H x} e^{\mathbf{i}Q_z \eta(x, t)}.
$$
\n(VI.41)

An alternative equivalent expression of the WCA scattering amplitude can be obtained through an integration by part, which transforms the second derivative into a square slope $(\eta')^2$.

$$
\mathbb{S}_{WCA}(t) = \mathbb{S}_{SSA}(t) - \frac{Q_z \mathbb{T}}{Q_H^2} \int_{\mathbb{R}} \frac{dx}{2\pi} (\eta'(x,t))^2 e^{iQ_H x} e^{iQ_z \eta(x,t)}.
$$
 (VI.42)

This formulation was found advantageous for the statistical calculation of NRCS and for the numerical evaluation of the scattering amplitude on deterministic surfaces (because it is difficult to compute accurately the second-order derivative, especially in the case of sharp crests). For simplicity we will present the statistical calculations pertaining to the WCA approximation for 1D linear surfaces. We actually could derive a general analytical formulation for 2D surfaces, but its technical complexity makes it too heavy to present in the context of this paper and is left for specific subsequent applications.

Starting from the alternative representation (VI.42) and using standard properties of Gaussian processes recalled in Appendix A, we obtain the following expression for the field covariance function:

$$
C_{WCA}(t) = C_{SSA}(t) + \frac{2\Re e(\mathbb{B}^{T})}{Q_H^2} \int_{\mathbb{R}} dx e^{iQ_H x} \left[\left(Q_z^2 \rho'^2 - \sigma_{20}^2 \right) e^{-Q_z^2 S_0/2} + \sigma_{20}^2 e^{-Q_z^2 \rho(0,0)} \right] \quad \text{(V1.43)}
$$

+
$$
\frac{Q_z^2 |\mathbb{T}|^2}{Q_H^4} \int_{\mathbb{R}} dx e^{iQ_H x} \left\{ \left[2\rho''(\rho'' + 2Q_z^2 \rho'^2) + \left(Q_z^2 \rho'^2 - \sigma_{20}^2 \right)^2 \right] e^{-Q_z^2 S_0/2} - \sigma_{20}^4 e^{-Q_z^2 \rho(0,0)} \right\}
$$

The first term on the right-hand side is the field covariance function arising from SSA1 (that is (IV.9) with K replaced by B). The functions ρ' and ρ'' are the first two space derivatives of the covariance function, respectively, $\sigma_{20}^2 = -\rho''(0,0)$ is the mean square slope and $S_0 = 2(\rho(0,0) - \rho(x,t))$ is the structure function of elevations. We did not derive direct analytical solutions of f_c and γ as in the KA framework (equations (IV.12) and (IV.13)) as this was found too complicate. Instead, we computed the time-dependent functions arising under the integral (VI.43) and evaluated the associated Doppler spectrum through a Fourier transform, as well as its first two moments (equations II.3). See Appendix B for numerical details. When evaluating the Doppler spectrum through a numerical time-integration it is crucial to ensure that the time interval is large enough, in order to avoid artificial broadening of the central peak. This might be an issue in working in experimental datasets since the coherence time is limited. However, we ignore this effect in this theoretical study, which does not claim to simulate a realistic field experiment. Figure 5 and 6 show the central frequency and width obtained with a Pierson-Moskowitz (PM) sea spectrum at $U_{19.5} = 7 \text{ m.s}^{-1}$ wind speed in L band (electromagnetic wavelength $\lambda_e = 0.23$ m). Superimposed are Toporkov and Brown [17] results obtained in the same conditions, with the exact electromagnetic Method of Order Multiple Interactions (MOMI) and Monte-Carlo average on deterministic time-evolving surfaces. (The datasets from [17] have been kindly provided to us by J. Toporkov, with an increased number of incidence angles and statisticaly more robust computations. We can observe an excellent agreement for both polarizations on the whole range of incidence. Again, the central Doppler frequency is well above the free Bragg frequency, the latter being recovered at grazing incidences. A marked polarization sensibility is apparent, with higher mean Doppler shifts in horizontal polarization, as it is classically observed. The shift in horizontal polarization can be understood by some qualitative arguments. The mean Doppler speed can be seen as an average of the phase speed of the different rough facets on the sea surface, weighted by their scattering cross-section. The WCA recovers a Bragg mechanism at large incidence, where the horizontal polarization is much lower than the vertical one. The relative contribution of the ripples (small speed) is therefore weaker in horizontal polarization, so that more weight is given to larger (and faster) waves in the mean Doppler speed, thus increasing the

latter.

VII. CONCLUSION

This paper has investigated the characteristics of the microwave sea Doppler spectrum in the framework of analytical electromagnetic and hydrodynamic models. Processing these models in increasing order of complexity, we have derived the first two moments of the Doppler spectrum in the framework of the KA, its TSM formulation and finally the WCA for linear surfaces. The most accurate model is the WCA which is sensitive to polarization and still enjoys a statistical, numerically efficient, formulation. It is robust to incidence and remains reasonably accurate until about 80 degrees. Doppler spectra in the microwave regime are quite different from those observed with HF radio waves. Their central frequency is higher than the free Bragg frequency, is polarization-dependent and has a non-monotonic behavior with incidence. The assumption of linear seas, however, misses an important well-known characteristic of the observed Doppler spectra, namely their broadening at large incidence angles. This will be corrected in a companion paper, where nonlinear hydrodynamic effects will be included.

Acknowledgments. This work was supported by the ANR Project No. ANR-09-BLAN-0232-01 SIMODE. Many thanks go to D.R. Thompson for helpful discussions, to J.V. Toporkov for providing us supplementary data and to Bertrand Chapron for his warm support during the revision process.

REFERENCES

- [1] M. B. Kanevskii. Radar imaging of the ocean waves. Elsevier, Oxford, 2009.
- [2] B.L. Weber and D.E. Barrick. On the nonlinear theory for gravity waves on the ocean's surface. J. Phys. Oceanogr., 7(1), 1977.
- [3] DE Barrick and BL Weber. On the nonlinear theory for gravity waves on the ocean's surface. Part II: Interpretation and Applications. Journal of Physical Oceanography, 7(1):11–21, 1977.
- [4] DR Thompson, BL Gotwols, and WC Keller. A comparison of Ku-band Doppler measurements at 20 incidence with predictions from a time-dependent scattering model. Journal of Geophysical Research, 96(C3):4947–4955, 1991.
- [5] PHY Lee, JD Barter, KL Beach, CL Hindman, BM Lake, H. Rungaldier, JC Shelton, AB Williams, R. Yee, and HC Yuen. X band microwave backscattering from ocean waves. Journal of Geophysical Research-Oceans, 100(C2), 1995.
- [6] PHY Lee, JD Barter, E. Caponi, M. Caponi, CL Hindman, BM Lake, and H. Rungaldier. Wind-speed dependence of small-grazing-angle microwave backscatterfrom sea surfaces. IEEE Transactions on Antennas and Propagation, 44(3):333–340, 1996.
- [7] P. Forget, M. Saillard, and P. Broche. Observations of the sea surface by coherent L band radar at low grazing angles in a nearshore environment. Journal of Geophysical Research, 111(C9):C09015, 2006.
- [8] T. Elfouhaily and C.A. Guérin. A critical survey of approximate scattering wave theories from random rough surfaces. Waves in Random and Complex Media, 14(4):1–40, 2004.
- [9] DR Thompson. Calculation of microwave Doppler spectra from the ocean surface with a time-dependent composite model. Kluwer Academic Publishers, 1989.
- [10] J.V. Toporkov and G.S. Brown. Numerical study of the extended Kirchhoff approach and the lowest order small slope

approximation for scattering from ocean-like surfaces: Doppler analysis. Antennas and Propagation, IEEE Transactions on, 50(4):417–425, 2002.

- [11] AA Mouche, B. Chapron, N. Reul, and F. Collard. Predicted Doppler shifts induced by ocean surface wave displacements using asymptotic electromagnetic wave scattering theories. Waves in Random and Complex Media, 18(1):185-196, 2008.
- [12] W. Yun-Hua, Z. Yan-Min, and G. Li-Xin. Investigation on the Doppler shifts induced by 1-D ocean surface wave displacements by the first order small slope approximation theory: comparison of hydrodynamic models. Chinese Physics B, 19:074103, 2010.
- [13] X. Li and X. Xu. Scattering and Doppler Spectral Analysis for Two-Dimensional Linear and Nonlinear Sea Surfaces. Geoscience and Remote Sensing, IEEE Transactions on, 49(2):603–611, 2011.
- [14] T. Elfouhaily, S. Guignard, R. Awadallah, and D.R. Thompson. Local and non-local curvature approximation: a new asymptotic theory for wave scattering. Waves in Random and Complex Media, 13(4):321–337, 2003.
- [15] C.A. Guérin, G. Soriano, and T. Elfouhaily. Weighted curvature approximation: numerical tests for 2D dielectric surfaces. Waves in Random and Complex Media, 14(3):349–363, 2004.
- [16] C.A. Guérin, G. Soriano, and B. Chapron. The Weighted Curvature Approximation in scattering from sea surfaces. Waves in Random and Complex Media, 20(3):364–384, 2010.
- [17] J. V. Toporkov and G. S. Brown. Numerical simulations of scattering from time-varying, randomly rough surfaces. IEEE Trans. Geophys. Remote Sensing, 38:1616–1624, July 2000.
- [18] J.V. Toporkov, M.A. Sletten, and G.S. Brown. Numerical scattering simulations from time-evolving ocean-like surfaces at L-and X-band: Doppler analysis and comparisons with a composite surface analytical model. Proc. of XXVII General Assembly of URSI, 2002.
- [19] P. Beckmann and A. Spizzichino. The scattering of electromagnetic waves from rough surfaces. Artech House, Norwood, 1987.
- [20] A. G. Voronovich. Small-Slope Approximation for electromagnetic wave scattering at a rough interface of two dielectric half-spaces. Waves in Random Media, 4:337–367, 1994.

APPENDIX

I. Characteristic functions and related correlators

In order to calculate statistical expressions of the Weighted Curvature Approximation and his equivalent nonlinear one we need to evaluate complex functions of Gaussian processes. The following intermediate results are given to help the reader who would like additional calculation steps. The braket symbols $\langle . \rangle$ means the statistical average over realisations. We suppose the surface elevation η defined by:

$$
\eta(x,t) = \int_{\mathbb{R}} \sqrt{\Gamma(k)} e^{i\phi_k} e^{ikx - i \operatorname{sgn}(k)\omega_k t} dk \tag{A.44}
$$

where Γ is the well known wave number sea spectrum and where the ϕ_k are random phases. The prime superscript means the space derivation and the "0" subscript means that quatities are taken at space and time origins. As example, D'_0 means the space derivative of the displacement D taken at $t = 0$ and $x = 0$. η , η' , D and D' are thus centered Gaussian processes and tedious but straightforward calculations lead to

$$
\left\langle e^{iQ_z(\eta-\eta_0)} \right\rangle = e^{-Q_z^2 S_0/2}, \tag{A.45}
$$

$$
\left\langle \eta^{'2} e^{iQ_z(\eta - \eta_0)} \right\rangle = (Q_z^2 \rho'^2 - \sigma_z^2) e^{-Q_z^2 S_0 / 2}, \qquad (A.46)
$$

$$
\left\langle \eta^{'2} \eta_0^{'2} e^{i Q_z(\eta - \eta_0)} \right\rangle = \left[2 \rho''(\rho'' + 2Q_z^2 \rho'^2) + (Q_z^2 \rho'^2 - \sigma_2^2)^2 \right] e^{-Q_z^2 S_0/2}
$$
 (A.47)

useful for WCA statistic calculations

II. Numerical recipees

In order to help the reader for numerical purposes, we report here some recipees that could help the calculations of the integrals in the paper. Here, we call "functions" all covariance functions that are Fourier Transforms of the sea spectrum coupled with a kernel. (eg : ρ (III.6), $\partial_t \rho$ (IV.15), ρ' , ρ'' , ...).

The sea surface spectrum (in wavenumber) used for these calculations is sampled over a logarithmic grid with 2^8 points between 0 and five times the electromagnetic wavenumber. All spatio-temporal functions are evaluated over a logarithmic spatial grid depending on the electromagnetic wavelength. In most of the calculations we used 2^{13} points between 0 and 600 times the electromagnetic wavelength (for which the integrand of the Kirchhoff integral is vanished).

The temporal sampling of the functions is linear since we then use a Fast Fourier Transform to evaluate the Doppler spectrum. Spatio-temporal symetries of the functions are also used in order to minimize time calculations. The spatial integration of spatio-temporal Kirchhof integral (equations (IV.9), (VI.43), ...) is done without any tricks while the time integration is realized through the Fast Fourier Transform. For Doppler evaluation at close nadir angles, only functions' values at close zero lags are needed and the processing time is very short (a time zero padding completion of $C(t)$ in equation (II.2) is used for numerical purpose). For higher incidence angles, larger lag values of the functions are needed for accurate calculations. All calculations done in this paper (except MOMI results which were provided by Dr. Toporkov) takes less than few minutes on a ordinary laptop.

LIST OF FIGURES

(a) Full spectrum

(b) Half-sided spectrum

Fig. 1. Norm of the waves complex amplitude : Γ_a in wavenumber space (k_x, k_y) . Three radar looking directions and their corresponding Doppler spectra are shown.

Fig. 2. 1D spatio-temporal covariance function of elevation: $\rho(x,t)$ at $U_{19.5} = 7 \text{ m.s}^{-1}$ wind speed.

Fig. 3. Comparison of KA, TSM and D-TSM Doppler central frequency in X band with $U_{19.5} = 5$ m.s⁻¹.

Fig. 4. Comparison of KA, TSM and D-TSM Doppler width in X band with $U_{19.5} = 5$ m.s⁻¹.

Fig. 5. Comparison of WCA vertical (VV) and horizontal (HH) polarization and KA Doppler central frequencies in L band with $U_{19.5} = 7 \text{ m.s}^{-1}$. T&B : Toporkov & Brown results obtained with the exact electromagnetic Method of Order Multiple Interactions.

Fig. 6. Comparison of WCA vertical (VV) and horizontal (HH) polarization and KA Doppler widths in L band with $U_{19.5} = 7 \text{ m.s}^{-1}$. T&B: Toporkov & Brown results obtained with the exact electromagnetic Method of Order Multiple Interactions.