Seeking the best Internet Model

F. A. Rodrigues P. R. Villas Boas, G. Travieso and L. da F. Costa

Instituto de Física de São Carlos. Universidade de São Paulo, São Carlos, SP, PO Box 369,

13560-970, phone +55 16 3373 9858, FAX +55 16 3371 3616, Brazil,

luciano@if.sc.usp.br

The models of the Internet reported in the literature are mainly aimed at reproducing the scalefree structure, the high clustering coefficient and the small world effects found in the real Internet, while other important properties (e.g. related to centrality and hierarchical measurements) are not considered. For a better characterization and modeling of such network, a larger number of topological properties must be considered. In this work, we present a sound multivariate statistical approach, including feature spaces and multivariate statistical analysis (especially canonical projections), in order to characterize several Internet models while considering a larger set of relevant measurements. We apply such a methodology to determine, among nine complex networks models, which are those most compatible with the real Internet data (on the autonomous systems level) considering a set of 21 network measurements. We conclude that none of the considered models can reproduce the Internet topology with high accuracy.

I. INTRODUCTION

In the Internet, an autonomous system (AS) is a large domain of IP addresses that usually belongs to one organization such as a university, a private company, or an Internet Service Provider. Since AS are connected through border routers, the Internet can be considered as consisting of interconnected AS. The understanding of the fundamental mechanisms that govern the Internet evolution and emergence are fundamental for modeling and simulating of dynamical process, such as attacks [1] and cascade failures [2], as well as for trying to improve protocols and routing.

Large data sets about the Internet connections have been available since the 90s. In 1999, Faloutsos et al. [3] showed that the distribution of connections is follow a power law, despite the fact that new vertices and edges appear and disappear all the time. This finding boosted the modeling and characterization of the Internet. Among the obtained results, it has been shown that the scale-free structure is important for providing network tolerance to random failures [1] and traffic congestion [4, 5]. However, such a topology makes the network vulnerable to intentional attacks [6]. At the same time, the Internet protocol efficiency is highly influenced by the network connectivity, while the power law degree distribution results in an absence of an epidemic threshold, which favors the spreading of computer viruses [7].

The models proposed to generate the Internet topology vary from completely random to those including preferential attachments [8]. Accurate models for the Internet are particularly important for growth forecast, architecture planning and design, and to provide topologies for dynamical process simulation. Although the characterization of the Internet structure is becoming more and more precise, just a few models can statically reproduce, and even so in approximate fashion, the Internet evolution [9]. While the current models are mainly aimed at the degree distribution, other important features — such as those quantified by central and hierarchical measurements — have not teen considered in these models. This approach can result in inaccurate and incomplete models. For instance, Alderson et al. [10] showed that networks with the same number of vertices and edges, but distinct structure, can present the same degree distribution (see also [11]). In this way, the fact that a model reproduces the same degree distribution as the real network is not enough to validation. This suggests that most current Internet models can be biased, undermining endeavors such as the prediction of Internet evolution and dynamical simulations. In this paper, we apply an alternative approach to determine the accuracy of network models, by considering multivariate statistical analysis and Bayesian decision theory [12, 13, 14, 15].

Multivariate statistical methods have not been considered by complex networks researchers until recently. The application of such methods in classification of network has been suggested recently (e.g. [15, 16, 17]). Multivariate statistical methods allow the consideration of a large set of variables and can be of great help for network modeling. Indeed, a model can be considered as being accurate if it can generate networks whose structural properties — quantified by a large set of network measurements — are statistically similar to those found for the real network being considered.

In this work we present the application of multivariate statistical methods, namely canonical projections and Bayesian decision theory, in order to determine which among a set of Internet models is the most appropriated to generate AS topologies. We considered nine different complex networks models and a set of 21 measurement in our analysis.

II. CONCEPTS AND METHODS

The considered Internet database, defined at the level of autonomous systems (AS), is available at the web site of the National Laboratory of Applied Network Research (http://www.nlanr.net). The data was collected in February 1998, with the network containing 3522 vertices and 6324 edges. For the network characterization, we took into account a set of 21 network measurements: (i) $\langle k \rangle$, average vertex degree; (ii) k_{max} , maximum degree, (iii) $\langle cc \rangle$, average clustering coefficient; (iv) k_{nn} , average neighbor connectivity; (v) ℓ , average shortest path length; (vi) r, assortative coefficient; (vii) $\langle B \rangle$, average betweenness, (viii) c_D , central point dominance; (ix) st, straightness coefficient of the degree distribution; (x) $\langle k_2 \rangle$, hierarchical degree of level two; (xi) $\langle cc_2 \rangle$, hierarchical clustering coefficient of level two; (xii) cv_2 , convergence ratio of level two; (xiii) dv_2 , divergence ratio of level two; (xiv) E_2 , average inter-ring degree of level two; (xv) A_2 , average intra-ring degree of level two; (xi) $\langle k_3 \rangle$, hierarchical degree of level three; (xvii) $\langle cc_3 \rangle$, hierarchical clustering coefficient of level three; (xviii) cv_3 , convergence ratio of level three; (xix) dv_3 , divergence ratio of level three; (xx) E_3 , average inter-ring degree of level three; and (xxi) A_3 , average intra-ring degree of level three. The classification was obtained by considered canonical variable analysis and Bayesian decision theory [12, 13, 16].

A. Network measurements

The AS network can be represented in terms of its adjacency matrix A, whose elements a_{ij} are equal to one whenever there is a connection between the vertices i and j, or equal to 0, otherwise. The average vertex degree is given as

$$\langle k \rangle = \frac{1}{N} \sum_{ij} a_{ij}.$$
 (1)

The clustering coefficient of a node i (cc_i) is defined by the proportion of links between the vertices within its neighborhood, l_i , divided by the number of links that could possibly exist between them ($k_i(k_i - 1)/2$). The average clustering coefficient is computed as

$$\langle cc \rangle = \frac{1}{N} \sum_{i=1}^{N} cc_i = \frac{1}{N} \sum_{i=1}^{N} \frac{\sum_{j=1}^{N} \sum_{m=1}^{N} a_{ij} a_{jm} a_{mi}}{k_i (k_i - 1)}.$$
 (2)

The average neighbor connectivity (k_{nn}) measures the average degree of vertices neighbor of the each vertex in the network [18]. The average shortest path length (ℓ) is calculated by taking into account the shortest distance between each pair of vertices in the network. The assortative coefficient measures the correlation between vertex degrees, i.e.,

$$r = \frac{\frac{1}{M} \sum_{j>i} k_i k_j a_{ij} - \left[\frac{1}{M} \sum_{j>i} \frac{1}{2} (k_i + k_j) a_{ij}\right]^2}{\frac{1}{M} \sum_{j>i} \frac{1}{2} (k_i^2 + k_j^2) a_{ij} - \left[\frac{1}{M} \sum_{j>i} \frac{1}{2} (k_i + k_j) a_{ij}\right]^2}.$$
(3)

The straightness coefficient (st) quantifies the level to which a log-log distribution of points approaches a power law, which is computed in terms of the Pearson correlation coefficient of the loglog degree distribution [16].

The considered centrality measurements are based on the betweenness centrality, which is defined as

$$B_u = \sum_{ij} \frac{\sigma(i, u, j)}{\sigma(i, j)},\tag{4}$$

where $\sigma(i, u, j)$ is the number of shortest paths between vertices *i* and *j* that pass through vertex u, $\sigma(i, j)$ is the total number of shortest paths between *i* and *j*, and the sum is over all pairs *i*, *j* of distinct vertices. The average betweenness centrality ($\langle B \rangle$) is computed considering the whole set of vertices in the network. The central point dominance is defined in terms of the betweenness by the following equation,

$$c_D = \frac{1}{N-1} \sum_{i} (B_{\max} - B_i).$$
 (5)

where B_{max} represents the maximum betweenness found in the network.

Complex networks measurements can also be defined in a hierarchical (or concentric) way [14, 19, 20, 21], i.e. by considering the successive neighborhoods around each node. Therefore, it is interesting to define the ring of vertices $R_d(i)$, which is formed by those vertices distant dedges from the reference vertex i. The hierarchical degree at distance d ($k_d(i)$) is defined as the number of edges connecting the rings $R_d(i)$ and $R_{d+1}(i)$. The hierarchical clustering coefficient is given by the number of edges in the respective d-ring ($m_d(i)$), divided by the total number of possible edges between the vertices in that ring, i.e.,

$$cc_d(i) = \frac{2m_d(i)}{n_d(i)(n_d(i) - 1)},$$
 (6)

where $n_d(i)$ represents the number of vertices in the ring $R_d(i)$. The convergence ratio at distance d of i corresponds to the ratio between the hierarchical degree at distance d-1 and the number of vertices in the ring $R_d(i)$,

$$cv_d(i) = \frac{k_{d-1}(i)}{n_d(i)}.$$
 (7)

The divergence ratio corresponds to the reciprocal of the convergence ratio, i.e.,

$$dv_d(i) = \frac{n_d(i)}{k_{d-1}(i)}.$$
(8)

Finally, the average inter ring degree is given by the average of the number of connections between each vertex in the ring $R_d(i)$ and those in $R_{d+1}(i)$,

$$E_d(i) = \frac{k_d(i)}{n_d(i)};\tag{9}$$

and the average intra ring degree is defined as the average among the degrees of the vertices in the ring $R_d(i)$,

$$A_d(i) = \frac{2m_d(i)}{n_d(i)},$$
 (10)

The average of each hierarchical measurements is obtained by taking into account the local hierarchical measurement of each vertex in the network.

B. Network models

The following nine complex network types are considered for modeling the Internet:

- 1. Erdős-Rényi random graph (ER): The network is constructed connecting each pair of vertices in the network with a fixed probability p [22], where each pair of vertices (i, j) is selected at random only once. This model generates a Poisson degree distribution.
- 2. Small-world model of Watts and Strogatz (WS): To construct this small-word network, one starts with a regular lattice of N vertices in which each vertex is connected to κ nearest neighbors in each direction. Each edge is then randomly rewired with probability p [23].
- 3. Waxman geographical Internet model (WGM): Geographical networks can be constructed by distributing N vertices at random in a 2D space and connecting them according to the distance. The model suggested by Waxman to model the Internet topology [24] considers the probability to connect two vertices i and j, distant D_{ij} , as $P(i \rightarrow j) \sim \theta e^{-\lambda D_{ij}}$.
- 4. Barabási-Albert scale-free model (BA): The network is generated by starting with a set of m_0 vertices and, at each time step, the network grows with the addition of a new vertice with m links. The vertices which receive the new edges are chosen following a linear preferential attachment rule, i.e. the probability of the new vertex i to connect with an existing vertex j is proportional to the degree of j, $\mathcal{P}(i \to j) = k_j / \sum_u k_u$ [25].
- 5. Limited scale-free model (LSF): The network is generated as in the BA model but the maximum degree is limited in order to be equal to the degree of the real network [26].

- 6. Scale-free model of Dorogovtsev, Mendes and Samukhin (DMS): This network is constructed as in the BA model, but the preferential attachment rule is defined as $\mathcal{P}(i \rightarrow j) = (k_j + k_0) / \sum_u (k_u + k_0)$ [27]. The constant k_0 controls the initial attractiveness and provides variation of connectivity from $-m < k_0 < \infty$, allowing a larger variation in the exponent of the power law, $\gamma = 3 + k_0/m$ (for the BA model, $\gamma = 3$).
- 7. Nonlinear scale-free network model (NLSF): The network is constructed as in the BA model, but instead of a linear preferential attachment rule, the vertices are connected following a nonlinear preferential attachment rule, i.e., $P_{i\rightarrow j} = k_j^{\alpha} / \sum_u k_u^{\alpha}$. In this case, while for $\alpha < 1$, the network has a stretched exponential degree distribution, for $\alpha > 1$ a single site connects to nearly all other sites [28].
- 8. The geographic directed preferential Internet topology model (GdTang): This internet generator constructs direct AS networks by considering some rules of the BA model. At each time step, a new vertex i and m edges are added to the network. The new vertex i connects with a vertex j according to the the rule $P_{i \to j} = k_j^{out} / \sum_u k_u^{out}$. The remaining m - 1 edges connect any vertex in the network according to the rule: the outgoing endpoint of each edge (node i) is chosen with probability $P_i = k_j^{in} / \sum_u k_u^{in}$ and the incoming endpoint (node j) with $P_j = k_j^{out} / \sum_u k_u^{out}$. With probability β , the added edge is local and the endpoints are restricted to the same region. The nodes are spatially distributed considering a pre-defined distribution. On the other hand, with probability $1-\beta$, the edge is global and can connect any endpoints. With probability p, each added edge may become a undirected edge [29].
- 9. The Inet internet topology generator: The Inet 3.0 has been based on the AS growth analysis since November 1997. Basically, this model assumes an exponential growth rate of the number of AS and it is computed the number of months t necessary to obtain a network with N vertices. Next, the out-degree frequency and the rank out-degree distribution are calculated. A fraction of n vertices are assigned to degree one and the remaining vertices are assigned out-degrees according to the out-degrees frequency. More details about this model can be found in [8, 30].

The models (iv)-(ix) produce networks with power law degree distributions as observed in the Internet. The models (i)-(iii) are considered in the current network classification because of their ability to reproduce network topological properties such as the small world effect and the high average clustering coefficient values. The NLSF model is simulated considering the exponents of the preferential attachment equal to $\alpha = 0.5$ and $\alpha = 1.5$. The

models WGM, GdTang and Inet were developed specifically to generate Internet topologies. Despite GdTang generates directed networks, we symmetrize the connections — directed connections were transformed in undirected. This transformation does not alters the network structure. All considered networks were formed by N = 3522 vertex and the average vertex degree adjusted to that of the original network ($\langle k_{AS} \rangle = 3.59$).

C. Classification methodology

A multivariate statistical method was adopted in order to associate (through classification) the Internet to the most likely among the considered models [16]. The classification was obtained by associating the real network to the model which best reproduces its topology, as quantified by the measurements. The features space was defined for 10 classes (the nonlinear model is defined considering two different exponents for the preferential attachment). For each model, 50 networks were generated and 21 measurements were computed. In this way, each network model realization was represented by a feature vector composed by 21 elements in the space of attributes. Such a space was projected into 2D by using canonical variable analysis [16, 31] and the region of classification was obtained by Bayesian decision theory [12, 13].

Canonical analysis has been used to reduce the dimensionality of the measurement feature space. It provides a powerful extension of principal component analysis [31], performing projections which optimize the separation between known categories of objects. To perform the canonical analysis it is necessary to construct a matrix which quantifies the variation inside the groups previously defined, and a second matrix which quantifies the variation among these groups. If we consider C classes (network models), each one identified as $C_i, i = 1, \ldots, C$, and that each network realization n is represented by its respective feature vector $\vec{x}_n = (x_1, x_2, \ldots, x_p)^T$, the intraclass scatter matrix is defined as

$$S_{\text{intra}} = \sum_{i=1}^{C} \sum_{n \in C_i} \left(\vec{x_n} - \langle \vec{x} \rangle_i \right) \left(\vec{x_n} - \langle \vec{x} \rangle_i \right)^T, \quad (11)$$

and the interclass scatter matrix is given as,

$$S_{\text{inter}} = \sum_{i=1}^{C} N_i \left(\langle \vec{x} \rangle_i - \langle \vec{x} \rangle \right) \left(\langle \vec{x} \rangle_i - \langle \vec{x} \rangle \right)^T, \quad (12)$$

where $\langle \vec{x} \rangle_i$ corresponds to the average of a given variable for the class *i* and $\langle \vec{x} \rangle$ is the general average of a given variable for all classes.

By computing the eigenvectors of the matrix $S_{\text{inter}}^{-1} S_{\text{inter}}$ and selecting those corresponding to highest absolute eigenvalues, $\lambda_1, \ldots, \lambda_p$, it is possible to project the set of variables into less dimension —usually 2 or 3

dimensions, depending on the number of highest eigenvalues considered [13].

The Bayesian decision is performed in order to obtain the regions of classification by considering nonparametric estimation [12]. In this, case the mass probabilities P_i , which corresponds to the probability that an network belongs to class C_i , as well as the conditional probability densities, $p(\vec{x_n}|C_i)$, are estimated by using non-parametric methods (see [12, 13]). The Bayes rule can then be expressed as:

if
$$f(\vec{x}_n|C_a)P(C_m) = \max_{b=1,m} \{ f(\vec{x}_n|C_b)P(C_b) \}$$

then select C_a ,

where \vec{x}_n is the vector that stores the network set of measurements and C_a is the class of networks associated to the model a. Further details about such an approach are discussed in [16].

III. RESULTS AND DISCUSSION

The network models were generated while considering parameters that best approximate the average vertex degree and/or the average clustering coefficient of the real network. In this way, we considered fpr each model: (i) ER, $p = \langle k_{AS} \rangle / (N-1)$; (ii) SW, $\kappa \simeq \langle k_{AS} \rangle / 2 = 2$ and $p = 1 - [\langle cc_{AS} \rangle (4\kappa - 2)/(3\kappa - 3)]^{1/3}$; (iii) BA, $m \simeq \langle k_{AS} \rangle / 2 = 2$; (iv) WGM, the parameters $\lambda = 1.35$ and $\theta = 1$ were adjusted in order to obtain a degree similar to the real network; (iv) LSF, $m \simeq \langle k_{AS} \rangle / 2 = 2$ and the maximum degree was taken equal to that observed in the real network; (v) DMS, $m \simeq \langle k_{AS} \rangle / 2 = 2$ and $k_0 = m(\gamma_{AS} - 3)$, where $\gamma_{AS} = 2.2$ is the exponent of the degree distribution of Internet [18]; (vi) KP, $m \simeq \langle k_{AS} \rangle / 2 = 2$ and the coefficient of the nonlinearity was taken $\alpha = 0.5$ and $\alpha = 1.5$; (vii) GdTang, p = 0.5and $\beta = 0.07$; and (viii) Inet 2.0, the fraction of vertices with degree equal to one was defined as observed in the Internet. The measurements $\langle k_{AS} \rangle$ and $\langle cc_{AS} \rangle$ are the average degree and the average clustering coefficient found in the Internet, respectively. For each model, 50 networks were generated and a set of 21 different measurements were computed for each one (nine non-hierarchical and 6 hierarchical, where the hierarchical measurements consider the second and third hierarchies).

Table I presents the five most commonly used measurements for network characterization. According to their values, we may conclude that the Inet 3.0 is the most accurate model, in spite of $\langle cc \rangle = 0$. However, such a set of measurements does not quantify the majority of network properties and a larger set of measurements must be considered in order to enhance the precision of the analysis.

In order to obtain the classification of the Internet by using canonical variable analysis and Bayesian decision theory, according to the set of models and measurements, we took into account the following eight measurements configurations: 1. $\{k_{max}, \ell, r\}$.

- 2. $\{\langle k \rangle, k_{max}, \langle cc \rangle, \ell, r, c_D\}$
- 3. $\{\langle cc \rangle, k_{nn}, \ell, c_D, st\}$
- 4. $\{k_{max}, \langle cc \rangle, k_{nn}, \ell, r, \langle B \rangle, st\}$
- 5. $\{k_{nn}, \ell, r, \langle B \rangle, \langle k_2 \rangle, \langle cc_2 \rangle, \langle k_3 \rangle, \langle cc_3 \rangle\}$
- 6. $\{\langle k \rangle, k_{max}, \langle cc \rangle, \ell, r, c_D, \langle k_2 \rangle, \langle cc_2 \rangle\}$
- 7. $\{\langle k_2 \rangle, \langle cc_2 \rangle, \langle cv_2 \rangle, \langle E_2 \rangle, \langle A_2 \rangle, \langle k_3 \rangle, \langle cc_3, \rangle \langle cv_3 \rangle, \langle E_3 \rangle, \langle A_3 \rangle\}$
- 8. $\{\langle k \rangle, k_{max}, \langle cc \rangle, k_{nn}, \ell, r, \langle B \rangle, c_D, st, \langle k_2 \rangle, \langle cc_2 \rangle, cv_2, E_2, A_2, \langle k_3 \rangle, \langle cc_3 \rangle, cv_3, E_3, A_3 \}.$

Figures 1 and 2 present the obtained partitions and classifications. As we can see, different classifications were obtained depending on the set of measurements considered. For the set (i) and (ii) (Figure 2(a) and 2(b)), the Internet was best represented by the model Inet 3.0. Indeed, this result is observed in Table I and reflects the biased classification when a reduced set of measurements is considered. The Inet reproduces well some topological measurements $(\langle k \rangle, k_{max}, \ell, r)$, while other measurements $\langle c \rangle$ and c_D tend to diverge. When the sets (vi) and (vii) are taken into account, the Internet is best modeled by the ER network model (Figures 2(b) and 2(c)). This classification was not expected, since ER model produces networks with topology different from the Internet (see Table I). In case the measurements (iii), (iv) and (viii) are considered, the Internet was classified as $KP(\alpha = 1.5)$ (Figures 1(c), 1(d) and 2(d)). Indeed, this model considers the non-linear preferential attachment, which has been considered in other Internet models, such as that developed by Zhou and Mondragon [32] — which was not considered here because it is suitable to reproduce only CAIDA networks [33]. For the set of measurements (v), the Internet was classified as BA model, even if the BA model did not produce assortative networks with high average clustering coefficient and degree distribution with the same exponent as observed in Internet $(\gamma_{Ba} = 3 \text{ and } \gamma_{AS} = 2.2)$. In none of the classifications, the real network was placed among the points that defined each class. All these results suggest that none of the models can reproduce the Internet topology with high accuracy. The ER, BA, NLSF ($\alpha = 1.5$) and Inet 3.0 can reproduce just some topological properties of the real network. Therefore, such models can be considered as roughly approximated. For a given model to reproduce the Internet structure with precision, whatever the set of measurements considered, the network would have to be classified as corresponding to this model. Our results suggest that a revision of Internet modeling must be considered in order to obtaining improved prototypes. A possibility to obtain a better model of Internet is to observe which of the properties of the ER, BA, NLSF and Inet 3.0 are important for Internet evolution. In this case, a hybrid model may be constructed.

IV. CONCLUSIONS

In this work we presented an application of multivariate statistical analysis to determine, among a set of predefined complex networks models, which of them is potentially most suitable to represent the Internet topology. Our results suggest that none of the considered models reproduce all considered features of the Internet. Even models developed specifically to reproduce the Internet structure — such as the Inet, WGM and GdTang — do not seem to be very accurate. In order to obtain more precise modeling, hybrid models can be constructed, considering properties of the ER, BA, NLSF and Inet 3.0 that are important for Internet evolution, as these models were the only that reproduced, partially, some Internet topological properties.

The present work suggests that a revision in Internet modeling, which can be assisted by the methods considered in this work. Also, it is possible to extend our approach by considering the contribution of each measurement for the separation in the phase space as a systematic methodology for identifying the incompleteness of the models. This approach can result in incremental improvements, allowing to quantify the importance of each measurement in discrimination. The extension of the modeling methods for other types of complex networks, such as social and biological, is straightforward.

V. ACKNOWLEDGMENTS

Luciano da F. Costa is grateful to FAPESP (proc. 05/00587-5), CNPq (proc. 301303/06-1) for financial support. Francisco A. Rodrigues acknowledges FAPESP sponsorship (proc. 07/50633-9) and Paulino R. Villas Boas is grateful to CNPq (141390/2004-2).

References

- R. Albert, H. Jeong, and A.L. Barabasi. Error and attack tolerance of complex networks. *Nature*, 406(6794):378– 382, 2000.
- [2] A.E. Motter. Cascade control and defense in complex

networks. Physical Review Letters, 93(9):98701, 2004.

[3] M. Faloutsos, P. Faloutsos, and C. Faloutsos. On powerlaw relationships of the Internet topology. *Proceedings* of the conference on Applications, technologies, architec-

TABLE I: Average and standard deviation of the average degree $(\langle k \rangle)$, maximum degree (k_{max}) , average clustering coefficient $(\langle cc \rangle)$, average shortest path length (ℓ) , assortative coefficient (r) and the central point dominance (c_D) . Each measurements was computed taking into account 50 realizations of each model.

-						
Network	$\langle k \rangle$	k_{max}	$\langle cc \rangle$	l	r	c_D
$\operatorname{Internet}$	3.59	742	0.19	3.46	-0.21	0.33
\mathbf{ER}	$3,59{\pm}0,04$	12 ± 2	$0.0010 {\pm} 0.0005$	$6.5 {\pm} 0.1$	-0.004 ± 0.0140	$0.010 {\pm} 0.02$
SW	4 ± 0	7 ± 21	$0.37{\pm}0.05$	10 ± 1	-0.023 ± 0.01	0.020 ± 0.05
BA	4 ± 0	$158{\pm}33$	$0.010{\pm}0.002$	$4.4 {\pm} 0.1$	-0.06 ± 0.01	$0.20 {\pm} 0.05$
WGM	$3.35{\pm}0.05$	11 ± 2	$0.12 {\pm} 0.01$	18 ± 1	$0.15 {\pm} 0.1$	$0.15 {\pm} 0.05$
LSF	4 ± 0	$160{\pm}33$	$0.010{\pm}0.002$	$4.3 {\pm} 0.1$	-0.06 ± 0.01	$0.20 {\pm} 0.05$
DMS	4 ± 0	$352 {\pm} 63$	$0.04{\pm}0.01$	$3.7 {\pm} 0.1$	$-0.13 {\pm} 0.01$	$0.30 {\pm} 0.05$
$\text{LNSF}(\alpha = 0.5)$	4 ± 0	40 ± 5	$0.002{\pm}0.001$	$5.1 {\pm} 0.1$	$0.08 {\pm} 0.01$	$0.08 {\pm} 0.02$
$\text{NLSF}(\alpha = 1.5)$	4 ± 0	$1500{\pm}300$	$0.3 {\pm} 0.1$	$2.7 {\pm} 0.2$	$-0.25 {\pm} 0.05$	$0.6 {\pm} 0.1$
GdTang	$4.7 {\pm} 0.1$	$380{\pm}50$	$0.03{\pm}0.01$	$5.0 {\pm} 0.1$	$-0.18 {\pm} 0.01$	$0.10 {\pm} 0.01$
Inet 3.0	$_{3,23\pm0}$	771 ± 0	0 ± 0	$3,\!38{\pm}0.01$	-018 ± 0.01	$0.52 {\pm} 0.02$

tures, and protocols for computer communication, pages 251-262, 1999.

- [4] Y. Moreno, R. Pastor-Satorras, A. Vazquez, and A. Vespignani. Critical load and congestion instabilities in scale-free networks. *Europhysics Letters*, 62(2):292– 298, 2003.
- [5] R.V. Solé and S. Valverde. Information transfer and phase transitions in a model of internet traffic. *Phys*ica A: Statistical Mechanics and its Applications, 289(3-4):595-605, 2001.
- [6] R. Cohen, K. Erez, D. ben Avraham, and S. Havlin. Breakdown of the Internet under Intentional Attack. *Physical Review Letters*, 86(16):3682-3685, 2001.
- [7] R. Pastor-Satorras and A. Vespignani. Epidemic spreading in scale-free networks. *Physical Review Letters*, 86(14):3200-3203, 2001.
- [8] C. Jin, Q. Chen, and S. Jamin. Inet: Internet topology generator. University of Michigan Technical Report CSE-TR-433-00, 2000.
- [9] S.H. Yook, H. Jeong, and A.L. Barabasi. Modeling the Internet's large-scale topology. *Proceedings of the Na*tional Academy of Sciences, 99(21):13382-13386, 2002.
- [10] D. Alderson, J.C. Doyle, L. Li, and W. Willinger. Towards a theory of scale-free graphs: Definition, properties, and implications. *Internet Math*, 2(4):431-523, 2005.
- [11] L. da F. Costa. Seeking for simplicity in complex networks. arXiv:physics/0702102v1, 2007.
- [12] R.O. Duda, P.E. Hart, and D.G. Stork. Pattern Classification. Wiley-Interscience, 2000.
- [13] L.D.F. Costa. Shape Analysis and Classification: Theory and Practice. CRC Press, 2001.
- [14] L. da F. Costa and R. F. S. Andrade. What are the best hierarchical descriptors for complex networks? arXiv:0705.4251v1, 2007.
- [15] A. Clauset, C. Moore, and M. E. J. Newman. Structural inference of hierarchies in networks. In Proc. 23rd International Conference on Machine Learning (ICML), New York, 2006. Association of Computing Machinery.
- [16] L. da F. Costa, F. A. Rodrigues, G. Travieso, and P. R. Villas Boas. Characterization of complex networks: A survey of measurements. *Advances in Physics*, 56(1):167 – 242, 2007.
- [17] M. E. J. Newman and E. A. Leicht. Mixture models and exploratory data analysis in networks. *Proc. Natl. Acad. Sci. USA*, 104:9564–9569, 2007.

- [18] R. Pastor-Satorras, A. Vázquez, and A. Vespignani. Dynamical and correlation properties of the internet. *Physical Review Letters*, 87(25):258701, 2001.
- [19] L.F. Costa. The hierarchical backbone of complex networks. *Physical Review Letters*, 93(9):98702, 2004.
- [20] L. da F. Costa and F. N. Silva. Hierarchical characterization of complex networks. *Journal of Statistical Physics*, 125(4):841-872, 2006.
- [21] L. da F. Costa and L. E. C. da Rocha. A generalized approach to complex networks. *The European Physical Journal B-Condensed Matter*, 50(1):237-242, 2006.
- [22] B. Bollobás. Modern Graph Theory. Graduate Texts in Mathematics, Springer-Verlag, New York, 1998.
- [23] D. J. Watts and S. H. Strogatz. Collective dynamics of small-world networks. *Nature*, 393(6684):440-442, 1998.
- [24] BM Waxman. Routing of multipoint connections. Selected Areas in Communications, IEEE Journal on, 6(9):1617-1622, 1988.
- [25] A.L. Barabási and R. Albert. Emergence of scaling in random networks. *Science*, 286:509, 1999.
- [26] L.A.N. Amaral, A. Scala, M. Barthelemy, and HE Stanley. Classes of Small-World Networks. Proceedings of the National Academy of Sciences of the United States of America, 97(21):11149-11152, 2000.
- [27] SN Dorogovtsev, JFF Mendes, and AN Samukhin. Structure of Growing Networks with Preferential Linking. *Physical Review Letters*, 85(21):4633-4636, 2000.
- [28] PL Krapivsky and S. Redner. Organization of growing random networks. *Physical Review E*, 63(6):66123, 2001.
- [29] S. Bar, M. Gonen, A. Wool, and S. Bar. A geographic directed preferential internet topology model. Modeling, Analysis, and Simulation of Computer and Telecommunication Systems, 2005. 13th IEEE International Symposium on, pages 325-328, 2005.
- [30] J. Winick and S. Jamin. Inet-3.0: Internet topology generator. University of Michigan Technical Report CSE-TR-456-02, 2002.
- [31] R. A. Johnson and D. W. Wichern. Applied Multivariate Statistical Analysis. Prentice Hall, fourth edition, 1998.
- [32] S. Zhou and R.J. Mondragón. Accurately modeling the internet topology. *Physical Review E*, 70(6):66108, 2004.
- [33] S. Zhou, G. Zhang, and G. Zhang. The chinese internet as-level topology. arXiv:cs/0511101v4, 2005.



FIG. 1: Classification obtained considering different set of measurements. The network realizations are represented by dots, corresponding to the following models: + ER, $\times \text{ WS}$, $\oplus \text{ BA}$, $\blacklozenge \text{ WGM}$, $\Diamond \text{ LSF}$, $\triangle \text{ DMS}$, $\triangledown \text{ NLSF}$ ($\alpha = 0.5$), $\Box \text{ NLSF}$ ($\alpha = 1.5$), $\circ \text{ GdTang}$ and * Inet 3.0. The real network is represented by \triangleleft . The set of measurements in each case are (a) { k_{max} , ℓ, r }, (b) { $\langle k \rangle$, k_{max} , $\langle cc \rangle$, ℓ, r, c_D }, (c) { $\langle cc \rangle$, k_{nn} , ℓ, c_D , st} and (d) { k_{max} , $\langle cc \rangle$, k_{nn} , ℓ, r , $\langle B \rangle$, st}



FIG. 2: Classification obtained considering different sets of measurements. The network realizations are represented by dots, corresponding to the following models: + ER, × WS, \oplus BA, \blacklozenge WGM, \Diamond LSF, \triangle DMS, \bigtriangledown NLSF ($\alpha = 0.5$), \Box NLSF ($\alpha = 1.5$), \circ GdTang and * Inet 3.0. The real network is represented by \triangleleft . The set of measurements in each case are (a) $\{k_{nn}, \ell, r, \langle B \rangle, \langle k_2 \rangle, \langle cc_2 \rangle, \langle k_3 \rangle, \langle cc_3 \rangle\}$, (b) $\{\langle k \rangle, k_{max}, \langle cc \rangle, \ell, r, c_D, \langle k_2 \rangle, \langle cc_2 \rangle\}$, (c) $\{\langle k_2 \rangle, \langle cc_2 \rangle, \langle cv_2 \rangle, \langle k_3 \rangle, \langle cc_3 \rangle, \langle cv_3 \rangle, \langle cv_3 \rangle, \langle cc_3 \rangle\}$ and (d) $\{\langle k \rangle, k_{max}, \langle cc \rangle, k_{nn}, \ell, r, \langle B \rangle, c_D, st, \langle k_2 \rangle, \langle cc_2 \rangle, cv_2, E_2, A_2, \langle k_3 \rangle, \langle cc_3, A_3 \rangle\}$.