Giant strain-sensitivity of acoustic energy dissipation in solids containing dry and saturated cracks with wavy interfaces

V. Yu. Zaitsev^{a)} and L. A. Matveev

Division of Hydrophysics and Hydroacoustics, Institute of Applied Physics, Russian Academy of Sciences, Uljanova St. 46, Nizhny Novgorod, 603950, Russia

(Dated: July 20, 2018)

Mechanisms of acoustic energy dissipation in heterogeneous solids attract much attention in view of their importance for material characterization, nondestructive testing, and geophysics. Due to the progress in measurement techniques in recent years it has been revealed that rocks can demonstrate extremely high strain sensitivity of seismo-acoustic loss. In particular, it has been found that strains of order 10^{-8} produced by lunar and solar tides are capable to cause variations in the seismoacoustic decrement on the order of several percents. Some laboratory data (although obtained for higher frequencies) also indicate the presence of very high dissipative nonlinearity. Conventionally discussed dissipation mechanisms (thermoelastic loss in dry solids, Biot and squirt-type loss in fluid-saturated ones) do not suffice to interpret such data. Here, the dissipation at individual cracks is revised taking into account the influence of wavy asperities of their surfaces quite typical of real cracks, which can drastically change the values of the relaxation frequencies and can result in giant strain sensitivity of the dissipation without the necessity to assume the presence of unrealistically thin (and, therefore, unrealistically soft) cracks. In particular, these mechanisms suggest interpretation for observations of pronounced amplitude modulation of seismo-acoustic waves by tidal strains.

PACS numbers: 43.25.Ba, 43.25.Dc, 43.25.Ed

I. INTRODUCTION

In recent years, much attention is paid to the so-called mesoscopic nonlinear elasticity of solids containing such structural features as cracks, contacts, intergrain aggregates of dislocations etc. that are small in the scale of the elastic wave length. Quite often the quadratic nonlinearelastic parameter β for such materials can be $10^3 - 10^4$ in contrast to $\beta \sim 10^0$ typical of ideal crystals of homogeneous amorphous solids. The common feature of the above-mentioned structural features-defects is their very high relative softness compared with that of the surrounding homogeneous material. Thus the local strains at the defects are strongly (often by several orders of magnitude) enhanced. This fact results in strongly increased macroscopic elastic nonlinearity, which can be be instructively elucidated using rheological-level models^{2,3} that are in principle distributed and heterogeneous even if the properties of regions small in the wavelength scale are described.

In many cases, adhesion or frictional effects are also localized at those soft defects, which makes the resultant nonlinearity hysteretic¹. In recent years increasing attention is also paid to nonlinear-dissipative properties of mesoscopic solids, which manifest themselves in rather pronounced variations in the dissipation of one elastic wave in the presence of another wave^{4,5} or an applied (quasi)static stress (although the very fact of pressuredependence of dissipation or its dependence on the acoustic wave amplitude in rocks has been known for years^{6,7}). The most striking feature is that quite moderate strains

 $\varepsilon \sim 10^{-6} - 10^{-5}$ are able to cause variations in the decrement up to tens of percents or even several times^{5,8,9,10}. whereas the accompanying variations in the elastic moduli are on the order $\beta \varepsilon$ and do not exceed $10^{-2} - 10^{-3}$.

In addition to laboratory measurements, even more giant strain sensitivity of the dissipation is indicated by some field data. For example, in experiments¹¹ on longrange (357 km and 430 km) propagation of monochromatic elastic wave produced by high-stability vibration sources operating at frequencies of 5-7 Hz, the accuracy of the measurements was sufficient to single out periodic variations in the received-signal parameters which were well-correlated with the periodicity of the lunar-solar tides. For tidal strains in the Earth-crust, the characteristic amplitude¹² is $\sim 10^{-8}$, whereas in observations¹¹ the variations of the received-signal amplitude amounted to 2-4 percents and 1-2 degrees for the signal phase. These values correspond to the path-averaged relative variations in the elastic modulus $\Delta E/E \sim 10^{-5}$ and absolute variations in the decrement $\Delta \theta \sim 3 \cdot 10^{-5}$ which are of the same order of magnitude. Assuming for the average value of the decrement $\theta \sim (0.3-1) \cdot 10^{-2}$ (i.e., $Q = \pi/\theta \sim 100 - 300$), we estimate that the relative variation in the decrement is $\Delta\theta/\theta \sim 0.3 \cdot 10^{-2}$ and is over two orders of magnitude greater than $\Delta E/E \sim 10^{-5}$.

Taking into account that the tidal strain $\varepsilon_0 \sim 10^{-8}$, we obtain the path-averaged estimate for the quadratic nonlinear parameter $\beta = (\Delta E/E)/\varepsilon_0 \sim 500 - 700$, which is not so high as $\beta \sim 10^5$ reported, for example, in the pioneering observations 13,14 of the tidal variations in the elastic-wave velocities. The above estimated smaller value of β is not surprising since in the long-range experiments¹¹ the wave path reached depths of several tens of kilometers where the high pressure of the overburden rock layers closed soft cracks and significantly

a) Electronic address: vyuzai@hydro.appl.sci-nnov.ru

reduced the path-averaged nonlinearity of the rocks.

Much higher (comparable with the data^{13,14}) values of β were observed in cross-well experiments¹⁵ with a high-stability downhole seismo-acoustic source operating at a frequency of 167 Hz, the propagation distance 360 m with the estimated wave velocity along the path about 3000 m/s. In work¹⁵ the tide-induced variations for the wave phase were about 0.05 rad. and elastic-modulus variations $\Delta E/E \sim 10^{-3}$ that indicated the nonlinearity parameter $\beta = (\Delta E/E)/\varepsilon_0 \sim (1-2) \cdot 10^5$ like in works^{13,14}. For the wave amplitude, its tide-induced variations were about 10% and corresponded to the absolute variations in the decrement $\Delta\theta \sim (2-5) \cdot 10^{-3}$, which means that the strain-sensitivity of the rocks was so giant that the tidal strains 10^{-8} were able to produce the relative variations in the decrement $\Delta\theta/\theta \sim 10^{-2} - 10^{-1}$.

Similar estimates for $\Delta\theta/\theta$, although less directly, are confirmed by the field observations of the tidal modulation of the intensity of received endogenous seismic noises at several observation sites at the Kamchatka peninsula and in Japan^{16,17}. Normally, the weak-amplitude noise with strains $10^{-10} - 10^{-12}$ was recorded by a sensitive narrow-band receiver around a frequency of 30 Hz. Coherent averaging (from several weeks to several months) of the noise envelope made it possible to reliably single out periods of individual solar and lunar-tide components in the noise-intensity modulation with a typical depth ranged from 2-3 to 6-8%. Taking into account that for rather weak tidal strains $\varepsilon_0 \sim 10^{-8}$, their direct influence on the rock fracturing and the accompanying seismo-acoustic emission does not look very probable, the observed modulation can readily be explained¹⁸ by the tidal modulation of the effective size of the region from which the signal at the receiver is collected. This size is determined by the characteristic damping length for the noise. Thus, the relative variations in the intensity of the received noise should be proportional to $\Delta\theta/\theta$. The above obtained estimate $\Delta\theta/\theta \sim 10^{-2}-10^{-1}$ based on the independent direct measurements well agrees with the depth of the tidal modulation of the noise 16,17.

Thus various experimental data require an explanation of the giant value of strain-sensitivity of dissipation in mesoscopic solids. Since those strain-induced variations in the dissipation are observed for very small amplitudes of probing acoustic waves, for which absolute displacements at the microstructural defects (cracks and contacts) fall into essentially sub-atomic range, the responsible mechanism(s) should not involve an activation threshold (unlike hysteretic mechanisms of frictional^{6,19} or adhesion origin 20).

As discussed in works^{4,21}, pronounced straindependent dissipation in mesoscopic solids should arise due to combined action of purely elastic nonlinearity of the soft defects and conventional linear (i.e., viscous-like) dissipation that is also localized at the same defects because of the locally strongly enhanced strain rate. This mechanism does not require a finite threshold (unlike essentially super-atomic displacements required for activation of adhesion/frictional phenomena), although it can act in parallel with hysteretic mechanisms.

In what follows, we consider physical realizations of




FIG. 1. Schematically shown crack with wavy roughness at the interface which results in the creation of elongated (striplike) contacts or waists inside the crack that may act as a kind of valve for the fluid flow is the crack is liquid-saturated.

this mechanism that are relevant to solids containing dry and fluid saturated cracks. In both cases, the dissipation is threshold-less in amplitude: of thermoelastic origin in dry and viscous in fluid-filled cracks. In both cases the key role is played by the same geometrical features of real cracks for which corrugated surfaces (having wavy asperities) are typical rather than smooth nearly plane-parallel form often used in the dissipation models. The analysis will be performed in the style of physical argumentation used by Landau and Lifshitz 22 in the discussion of thermoelastic loss in polycrystalline solids and in work²³. Such an asymptotic approach gives clear representation of the physics of the discussed phenomena and ensures quantitative estimates with a reasonable accuracy comparable with that for formally exact solutions obtained for idealized (and thus approximate) models like elliptical cracks, etc.

II. GENERAL CONSEQUENCES OF WAVY ROUGHNESS OF SURFACES IN REAL CRACKS FOR STRAIN SENSITIVITY OF DISSIPATION

We emphasize the fact that unlike often assumed nearparallel geometry, for interfaces of real cracks, wavy forms are quite typical, which is confirmed by crack images obtained by various methods and is in agreement with known models of crack initiation. Such initially coinciding surfaces often are not simply separated in the normal direction but also exhibit certain tangential displacement and create inside the crack elongated "waists" (either nearly contacting or already contacting) as shown in Fig. 1. Inside liquid-saturated cracks, the so-created narrow waist can act for fluid flows as a kind of valve near which pressure gradients, flow velocities and the corresponding viscous dissipation in the crack should be localized. For dry cracks, the thermo-elastic dissipation should also be strongly localized and enhanced at the inner contacts. In the vicinity of such wavy asperities, the local separation (or interpenetration) h of the crack surfaces is significantly smaller than the average opening hof the crack. In contrast, the absolute variation in the average opening h and in the local separation h of the crack surfaces are practically the same, $\Delta h \approx \Delta \tilde{h}$. Due to this fact, the variations of the contact pre-strain (or the narrow waist opening) can be $h/h \gg 1$ stronger perturbed than the average opening which determines the loss at the whole crack.

After finding the acoustic loss at one crack the macroscopic logarithmic decrement θ can be found as the ratio

$$\theta(\omega) = \frac{W_0}{2W_{-1}},\tag{1}$$

where the energy W_0 is dissipated during one period in a unit volume and $W_{ac}=K\varepsilon^2/2$ is the acoustic energy density stored in the material with the modulus K. In the order-of-magnitude estimates, it is not critical to specify which particular modulus is taken. Besides, we also can approximately consider that the presence of cracks does not drastically change the material's elastic modulus K.

III. THERMOELASTIC LOSS AT INNER CONTACTS IN **DRY CRACKS**

Unlike homogeneous materials for which thermoelastic dissipation of elastic waves is often negligible, in solids with microstructure (e.g., polycrystalline²²) thermoelastic dissipation significantly increases due to the presence of small (compared with the elastic-wave length) heterogeneities that strongly increase temperature gradients. For crack-containing solids, there is another factor which additionally strongly enhances the thermo-elastic coupling: the stress- and strain concentration at the crack perimeter as considered in work²⁴. For the thermoelastic loss at the entire crack with characteristic diameter L, the thermoelastic dissipation exhibits maximum in the vicinity of the relaxation frequency $f_L \approx \kappa/(2\pi\rho CL^2)$, where ρ is the material density, C the specific heat per unit mass, and κ the thermal diffusivity. For millimetersize cracks in rocks, this maximum corresponds to frequencies in the range $10^{-3}...10^{-1}$ Hz. The analysis²⁴ was based on exact solutions for the stress-field distribution near two-dimensional cracks represented as narrow elliptical cavities. However, even without specifying details of a particular crack model and estimating temperature gradients determined by the crack size in the low-frequency limit and by the temperature-wave length in the highfrequency limit, it is possible to evaluate the elastic energy loss using the approach similar to that used by Landau and Lifshitz²² for polycrystalline solids.

We start from the thermal diffusivity equation for temperature variations T with respect to the mean value T_0

$$\frac{\partial \widetilde{T}}{\partial t} + \frac{\kappa}{C\rho} \Delta \widetilde{T} = \gamma T_0 \frac{\partial \varepsilon}{\partial t}, \tag{2}$$

where $\gamma = \mu_T K/(\rho C)$ is the Gruneisen parameter of the thermoelastic coupling, μ_T is the thermal expansion coefficient, K is the bulk modulus, ε is the material dilatation which for the present approximate consideration can be identified with strain in the field of a compressional wave. The acoustic energy loss due to irreversible heat flows can be found from the $integral^{22}$

$$\frac{\partial W}{\partial t} = -\frac{\kappa}{T_0} \int \left(\nabla \widetilde{T}\right)^2 dV. \tag{3}$$

Estimating the gradients in the crack from Eq. (2) and evaluating integral (3) we obtain the following approximate expressions for the elastic energy dissipated by the crack during one oscillation period, which well agree with the asymptotic forms of the results presented in 24 :

$$W_{crack}^{LF} \approx 2\pi\omega T_0(\mu_T^2 K^2/\kappa) L^5 \varepsilon^2$$
, for $\omega \ll \omega_L \approx \frac{\kappa}{\rho C L^2}$, (4)

$$W_{crack}^{HF} \approx 2\pi T_0 \frac{\mu_T^2 K^2}{\rho C} \left[\frac{\kappa}{\rho C \omega}\right]^{1/2} L^2 \varepsilon^2, \text{ for } \omega \gg \omega_L, \quad (5)$$

$$W_{crack}^{max} \approx 2\pi T_0(\mu_T^2 K^2/\rho C) L^3 \varepsilon^2$$
, for $\omega \approx \omega_L$, (6)

where ω is the circular frequency and ω_L is the characteristic circular frequency of thermal relaxation determined by the characteristic diameter L of the crack.

Since we need Eqs. (4)-(6) only for comparison with similar equations for thermoelastic loss at inner contacts in cracks, here, we only briefly outline their derivation. First, note that for sufficiently low frequencies, the crack size L is much smaller than both the elastic wave length and the thermal wave length $\lambda_{th} = [\kappa/(C\rho\omega)]^{1/2}$. Therefore, it is the scale L which determines the gradients of the temperature variations in the elastic-wave field, $\nabla \tilde{T} \sim \tilde{T}/L$. Thus in Eq. (2), we can estimate that $\Delta \widetilde{T} \sim \widetilde{T}/L^2$ and $\partial \widetilde{T}/\partial t \sim \omega \widetilde{T}$. The condition $L \ll \lambda_{th}$ is equivalent to $\omega \ll \omega_L = \kappa/(\rho C L^2)$ and thus $\partial \widetilde{T}/\partial t \ll \Delta \widetilde{T}$, so that the first term in Eq. (2) can be omitted. Since $\partial \varepsilon / \partial t \sim \omega \varepsilon$, Eq.(2) yields the estimate for the temeprature variation $\widetilde{T} \sim \omega \gamma T_0 C \rho L^2 / \kappa$. Then we estimate integral (3) taking into account that the temperature gradient \tilde{T}/L is localized in the crack vicinity within the characteristic volume L^3 . Then one obtains $\partial W/\partial t \sim \omega^2 T_0 \gamma^2 C^2 \rho^2 L^5 \varepsilon^2$. Finally, for the energy dissipated over one oscillation period $2\pi/\omega$ we recover Eq.(4).

In the high-frequency limit when $\omega \gg \omega_L = \kappa/(\rho C L^2)$, in contrast, the first term $\partial T/\partial t$ becomes dominant in Eq. (2), so that the the temperature variations are adiabatic: $T \approx \gamma T_0 \varepsilon$ and $\lambda_{th} \ll L$. In this case, the dissipation is mainly localized in the near vicinity of the crack edge, in which fairly universal asymptotic behavior of strain²⁵ has the form $\varepsilon_{cr} \sim \varepsilon(r/L)^{-1/2}$. Here, radius r is counted from the crack edge (and the angular factor in this order-of-magnitude estimate is neglected). When estimating integral (3) we have to consider two regions $r \geq \lambda_{th}$ and $r < \lambda_{th}$. It the latter region, the formally infinite strain $\varepsilon_{cr} \sim \varepsilon(r/L)^{-1/2}$ and strain gradient at $r \to 0$ does not cause divergence of the integral, since the amount of the generated heat is finite and is smeared within the region $r < \lambda_{th}$. As a result, both subregions $r \geq \lambda_{th}$ and $r < \lambda_{th}$ give functionally identical and approximately equal contributions, so that $\partial W/\partial t \sim \kappa T_0 \gamma^2 L^2/\lambda_{th}$ and for the loss over one period we recover Eq. (5). Finally, Eq. (6) can be found as the crossover between Eq. (4) and Eq. (5) at $\omega = \omega_L$.

To estimate the expected relaxation frequency, we can take parameters $\kappa \sim 0.015 \text{ W/cm/K}$ and $\rho \sim 2.6$ g/cm^3 typical of quartz-like rocks and consider cracks with $L \sim 1$ mm, which yields $f_L = \omega/(2\pi) \sim 10^{-1}$ Hz. It has been estimated is works^{23,24} that thermoelastic losses described by Eqs. (4)-(6) can account for the observed values of Q-factor in dry rocks, especially for low seismic frequencies. On the other hand, it is seen from Eq. (6) that the height of the relaxation maximum is proportional to the cube of the characteristic crack size L. Therefore, to explain the typically observed in dry rocks values $Q \sim 300-1000$ for ultrasonic frequencies and even for frequencies of the order of $10^2 - 10^3$ Hz, it is necessary to assume very high densities of very small cracks (of micro-meter scale), which does not look realistic.

In this context, the above mentioned narrow inner contacts have much higher relaxation frequencies. However, the question arises whether such contacts (whose volume is much smaller than that for the entire crack) can dissipate an appreciable amount of the elastic-wave energy? The expressions for thermoelastic energy loss at the inner contacts in cracks can be obtained much like Eqs. (4)-(6) taking additionally into account the local concentration of strain at the contacts ($\sec^{26,27}$):

$$W_{cont}^{LF} \approx 2\pi\omega T_0(\mu_T^2 K^2/\kappa) l^2 L_c L^2 \varepsilon^2$$
, for $\omega \ll \omega_l \approx \frac{\kappa}{\rho C l^2}$, (7)

$$W_{cont}^{HF} \approx (2\pi/\omega)\kappa T_0(\mu_T K/C\rho)^2 L_c(L/l)^2 \varepsilon^2$$
, for $\omega \gg \omega_l$, (8)

$$W_{cont}^{\rm max} \approx 2\pi T_0(\mu_T^2 K^2/\rho C) L_c L^2 \varepsilon^2$$
, for $\omega \approx \omega_l$, (9)

Here, L_c in the length of the strip-like contact, l is its width and the other notations are the same as for Eqs. (4)–(6), but the relaxation frequency ω_l is determined by the width $l \ll L$ of the strip-like contact. It is seen from Eqs. (7)–(9) that for frequencies much lower that the relaxation frequency ω_l , the loss is growing as a linear function of ω , and for frequencies much greater than ω_l , the loss is inversely proportional to ω . The asymptotic law ω^{-1} is similar to the high-frequency asymptotic for spheroidal voids²⁴ rather than flat cracks.

The most striking conclusion, which is seen from Eqs. (7)-(9), is that for a strip-like contact with a length $L_c \sim L$, the magnitude of loss in the vicinity of the maximum located at $\omega_l \gg \omega$ is determined by the size of the whole crack (since $L_cL \sim L^3$). Consequently the maximum loss at such contact is of the same order as for the conventionally considered maximum for the entire crack (compare Eqs. (6) and (9)). In contrast, the positions of the maxima $\omega_l \approx \kappa/(\rho C l^2)$ and $\omega_L \approx \kappa/(\rho C L^2)$ on the frequency axis can differ orders of magnitude. Thus one crack of size L with a strip-like contact $L_c \sim L$ of width $l \ll L$ can produce near the relaxation peak ω_l the thermoelastic dissipation comparable with the contribution




FIG. 2. Schematically shown relative positions and heights of the thermoelastic relaxation peaks for the crack of size Las a whole (curve 1), for the inner strip-like contact of width $l \ll L$ and length $L_c \sim L$ (curve 2), and a peak similar to curve 1, but for a small crack of size l (curve 1'). It is assumed that L = 1 mm and $l/L \sim 10^{-2}$.

of $(L/l)^3 \gg 1$ small cracks with the diameter l. Taking again an example of quartz-like rock, this difference is illustrated in Fig. 2 for $L/l = 10^2$, which means that one such inner contact produces the same dissipation as 10^6 small cracks of size l.

Noting that asymptotic Eqs. (7)-(9) agree with the frequency dependence of loss for a classical relaxator and assuming that the density of such cracks with inner contacts equals n_0 we obtain from Eq.(1) the expression for the decrement in the entire frequency range:

$$\theta^{cont} = \frac{2\pi T_0 \mu_T^2 K L_c L^2}{\rho C} \frac{\omega/\omega_l}{1 + (\omega/\omega_l)^2} n_0 \qquad (10)$$

To find the overall decrement determined by the contributions of contacts with different parameters L, L_c , and l we have to integrate Eq. (10) over the distribution $n(L, L_c, l)$, for which it is reasonable to assume that the distribution over the width l should be essentially independent of the distribution over L and L_c , so that $n(L, L_c, l) = n(L, L_c)n(l)$ and the averaging takes the

$$\theta^{cont} = \frac{2\pi T_0 \mu_T^2 K}{\rho C} \int \frac{L_c L^2 \omega / \omega_l}{1 + (\omega / \omega_l)^2} n(L, L_c) n(l) dL dL_c dl$$
(11)

We note that a wide distribution n(l) can strongly smoothen the frequency dependence of the dissipation resulting in nearly-constant Q-factor even without assuming very high densities of tiny cracks.

It is seen from the structure of integral (11) that the height of the relaxation peak and its location on the frequency axis are quite independent since they are determined by essentially different parameters (L and L_c for the peak height and l for the position). Evidently, for sufficiently small variation in the average strains and stresses, the width of the contacts can already be significantly perturbed, whereas the length of the contact




FIG. 3. Variation in the shape $\theta(\omega)$ of the normalized relaxation peak for an inner contact (curves 1 and 2) due to 15% variation in the contact width. The variation $\Delta\theta$ in the decrement has opposite signs at the opposite sides from the maximum and peak-to-peak excursion about 15% (curve 3).

and the average opening of the crack can be only slightly affected. This can result in the displacement of the relaxation maximum on the frequency axis almost without affecting its height as illustrated in Fig. 3 for the case of identical contacts. To estimate how strongly the frequency $\omega_l \approx \kappa/(\rho C l^2)$ of the maximum of the thermoelastic loss at such a contact can be perturbed by variation in the mean strain in the material, let us use the presented in Landau and Lifshitz 22 solution for the width of the contact between two compressed aligned cylinders:

$$l \approx 2 \left(\frac{16DF}{3\pi} \frac{RR'}{R+R'} \right)^{1/2}, \tag{12}$$

where $D = (3/4)[(1 - \sigma^2)/E + (1 - {\sigma'}^2)/E]$, σ and σ' are Poisson's coefficients of the materials of the cylinders, Eand E' are the Young moduli of the cylinders, and F is the specific force per unit length of the contacts. In the case of identical materials with the same accuracy which corresponds to Eqs. (7)-(10), we can consider that $D \approx$ 3/(2E) and the force F per unit length can be expressed as $F = F_c/L_c$, where F_c is the total force applied to the contact. Then from Eq. (12) we obtain

$$l^2 \approx (16F_c R)/(\pi E L_c). \tag{13}$$

For the force F_c applied to the inner contact in a crack, an approximate expression $F_c/L_c \approx \varepsilon E L^2/(L+L_c)$ can be obtained²⁷, where ε is the mean strain in the material. Then taking into account that $1/2 \le L/(L+L_c) \le 1$ one obtains from Eq. (12) the following approximate expres-

$$l^2 \approx \frac{16}{\pi} \frac{L}{L + L_c} \varepsilon RL \approx \frac{8}{\pi} \varepsilon RL, \quad \left| \frac{\Delta \omega_l}{\omega_l} \right| = \frac{\Delta(l^2)}{l^2} \approx \Delta \varepsilon \frac{RL}{l^2}.$$
(14)

This expression clearly elucidates the reason of the extremely high sensitivity of l^2 (and, consequently, variations in ω_l) with respect to the variation $\Delta \varepsilon$ in the mean strain. Indeed, the wavy asperities at the crack interfaces often have radius comparable with the characteristic diameter of the entire crack $(R \sim L)$, whereas the width of the inner strip-like contact often does not exceed the average opening h of the crack. Therefore, taking into account the above discussed characteristic values of the crack aspect ratios, we conclude that the factor RL/l^2 in Eq. (14) can easily be as great as 10^6-10^8 . This means that even variations in the mean deformation $\sim 10^{-8}$ (which are conventionally considered unable to appreciably influence acoustical parameters of solids) actually can be able to significantly change the width of inner contacts and affect the near-contact acoustic loss (see Fig. 3).

Estimating the overall sensitivity of the thermoelastic dissipation to the mean strain it is necessary to take into account that conventionally considered thermoelastic losses at the crack as a whole²⁴ also contribute to the total decrement. We have, however, to recollect that the characteristic relaxation frequencies $\omega_l \approx \kappa/\rho C l^2$ and $\omega_L \approx \kappa/\rho CL^2$ are related as $(L/l)^2$ and the highfrequency thermoelastic loss at the whole crack decreases as $(\omega/\omega_L)^{-1/2}$ (see Eq.(5)) as illustraed in Fig. 2. Then near the relaxation maximum ω_l we found that the ratio of the contributions of the loss θ_{loc} ($\omega = \omega_l$) at the inner contacts to the conventionally considered "global" loss $\theta_{alob} (\omega = \omega_l)$ at the cracks as a whole has the form

$$\frac{\theta_{loc}(\omega = \omega_l)}{\theta_{glob}(\omega = \omega_L)} \approx \frac{\widetilde{n}_{cr}}{n_{cr}} \left(\frac{\omega_l}{\omega_L}\right)^{1/2} \approx \frac{\widetilde{n}_{cr}}{n_{cr}} \frac{L}{l}, \tag{15}$$

where \widetilde{n}_{cr} and n_{cr} are the densities of cracks with and without inner contacts, respectively. Since $L/l \gg 1$, it is clear that even a small portion (e.g., a few percents) of cracks with narrow strip-like inner contacts can ensure near $\omega = \omega_l$ the same contribution to the decrement as the conventional "global" mechanism of thermoelastic dissipation at whole cracks. Therefore, even quite a small portion of cracks with contacts can provide the above discussed extremely high sensitivity of the dissipation to small variations in the mean strain in the material.

Even putting aside somewhat exotic manifestations of the giant stress-sensitivity of the dissipation and considering only its mean value, it can be emphasized that in the audible and ultrasonic ranges typical of laboratory studies, inner contacts can ensure a fairly strong contribution to dissipation comparable with the estimates obtained in works^{23,24} for the "global" thermoelastic loss at a crack as a whole for lower frequencies, which showed a reasonable agreement with the experimental data.

IV. VISCOUS LOSS AT FLUID-SATURATED CRACKS WITH INNER STRIP-LIKE "WAISTS"

Now let us consider viscous dissipation in cracks containing liquids. There is general agreement that along with the dissipation due to "global" fluid flows in pore channels (Biot's mechanism), an important role in the elastic-wave energy dissipation in rocks belongs to the local (or "squirt") flows inside cracks^{28,29}. Since the geometry of pore channels for the Biot flows rather weakly

depends on the average strain and stress, it is the squirttype dissipation in relatively soft narrow cracks which demonstrates much higher sensitivity to the variation in the mean strain in the material. In this section we focus on very important new features of the squirt mechanism in the case of cracks with wavy asperities of the interface.

To estimate the viscous loss in narrow cracks with nearly parallel surfaces we will use the integral $expression^{30}$ for the rate of kinetic energy dissipation in a flow of a viscous fluid between parallel solid planes:

$$\frac{\partial W_{kin}}{\partial t} = -\frac{\eta}{2} \int \left(\frac{\partial v_x}{\partial y}\right)^2 dV \tag{16}$$

In integral (16) over the volume of the flow, Y axis is orthogonal to the interface, v_x is the projection of the liquid-flow velocity on the X axis, and η is the fluid viscosity. The integration should be made over the volume of the flow. Using Eq.(16) we first estimate the amount of energy W_0 dissipated in a unit volume over one period. The form of $W_0(\omega)$ can again be understood by using asymptotic estimates very similar to those in the previous section considering now the linearized Navier-Stokes equation for the flow velocity v_x

$$\rho \frac{\partial v_x}{\partial t} = -\frac{\partial p}{\partial x} + \eta \frac{\partial^2 v_x}{\partial u^2},\tag{17}$$

where p is pressure. In view of similar structures of Eq. (17) and Eq.(2), the roles of the diffusive term and the term with the time derivative can be estimated in a very similar way.

In order to better delineate the place of our mechanism in the context of conventionally discussed ones we first recall how the well-known properties of the "global" Biot loss in fluid-filled channels can be derived from very simple arguments. For low acoustic frequencies, the role of the first inertial term in Eq. (17) is negligible, so that $|\partial p/\partial x| \approx |\eta \partial^2 v_x/\partial y^2|$, which corresponds to a fluid motion as a parabolic Poiseuille flow in the channel. Thus the velocity gradient is determined by the entire channel thickness H, $\partial^2 v_x/\partial y^2 \sim v_x/H^2$, and is frequency independent. The fluid velocity v_x in the Poiseuille flow is induced by the gradient of the acoustic pressure p_{ac} , which is determined by the acoustic wave length $\lambda_{\omega} \propto \omega^{-1}$, so that $v_x \propto \partial p/\partial x \sim p_{ac}/\lambda_\omega \propto \omega$. Taking into account that integral (16) is evaluated over a frequency-independent volume of the flow, the corresponding loss over one period $2\pi/\omega$ is $W_0 \propto (2\pi/\omega) \cdot \omega^2$, so that $\theta(\omega)_{LF} \propto \omega$.

With increasing frequency ω the first inertial term in Eq. (17) increases and becomes comparable with (and even greater than) the viscous term. This happens when $|\omega \rho v_x| \approx |\eta v_x/H^2|$, i.e., for the characteristic frequency

$$\omega_c \sim \eta/(\rho H^2),$$
 (18)

which is often expressed in a more indirect way via the ratio of porosity to permeability instead of the use of the characteristic width of the channels. The representation of ω_c in form (18) is especially physically clear and means that the viscous wave length $\lambda_{visc} = (2\eta/\rho\omega)^{1/2}$ becomes comparable with H. For $\omega \gg \omega_c$ the velocity gradient becomes localized near the walls within the viscous layer $\lambda_{visc} \ll H$, which determines the flowvelocity gradient, and we have $(\partial v_x/\partial y)^2 \propto (\omega^{1/2})^2 \propto \omega$. Next, since the last viscous term in Eq. (17) now can be neglected, we see that the velocity v_x becomes proportional to the acoustical pressure amplitude p_{ac} without any frequency-dependent factor, since $\partial v_x/\partial t \propto \omega v_x$ and $\partial p/\partial x \sim p_{ac}/\lambda_{\omega} \propto \omega$ both are proportional to ω . Besides, in integral Eq. (16) the intergration should be made only within the viscous layer with the thickness $\sim \lambda_{visc} \propto \omega^{-1/2}$ (where the gradient is localized) rather than over the entire volume of the fluid flow. The resultant frequency dependence of integral (16) has the form $\omega^{-1/2}(\omega^{1/2})^2=\omega^{1/2}$. The latter estimate should be multiplied by the factor $2\pi/\omega$ to find the energy loss W_0^{HF} during one period, so that for $\omega \gg \omega_c$, we obtain the asymptotic frequency dependence for the decrement: $\theta(\omega)^{HF} \propto (2\pi/\omega)\omega^{1/2} \propto \omega^{-1/2}$. Thus we recovered the well-known asymptotic dependences of the decrement $\theta(\omega)$ due to the Biot flows in the pore channels.

Let us now turn to narrow cracks which are much softer objects and can exhibit stronger stress-dependence. The above considered arguments based on the Poiseuille-flow approximation in the low-frequency limit remain very similar for flows in cracks and predict the same asymptotic behavior of the decrement $\theta(\omega)^{LF} \propto \omega$. As was mentioned in work²⁹, the localization of the shear-flow gradients within a narrow viscous layer $\sim \lambda_{visc}$ for sufficiently high frequencies may also be applied to cracks, but the characteristic frequency is much higher, since the crack opening h is much smaller than the diameter H of the pore channels. However, in contrast to rigid pore channels, cracks are much softer objects¹⁴, with a characteristic own modulus $\alpha K \ll K$. For cracks, the aspect ratio $\alpha \sim h/L$ plays the role of their softness parameter: due to their planar geometry cracks are roughly α^{-1} times more compliant than the surrounding matrix with respect to both compression and shear. Thus for crack-like compliant pores, another characteristic frequency of viscous relaxation appears, which physically corresponds to the condition that under sufficiently high-frequency oscillation, the viscous resistance to crack shearing becomes comparable with the elastic response of the crack to shearing. Namely, under tangential displacement Δx of the center of the crack, its shear elastic reaction $\alpha \mu \Delta x/h$ should be compared with the tangential viscous stress $\eta \omega \Delta x/h$. This yields a characteristic frequency

$$\omega_d \sim \alpha \mu / \eta,$$
 (19)

which was pointed out, for example, in work³¹. Now we note that for geophysical materials, typically the values of the shear modulus μ and compression modulus K are of the same order and the corresponding ω_d is relatively high. For example, for viscosity $\eta = 10^{-3} \text{ Pa} \cdot \text{s}$ typical of water and modulus $\mu \sim 10^{10} \ \mathrm{N/m^2}$ typical of rocks and quite narrow cracks with $\alpha \sim 10^{-3}-10^{-4}$ we obtain $\omega_d \sim$ $10^9 - 10^{10}$ rad./s, which evidently can be relevant only to utrasonic laboratory studies, but not to the seismoacoustic data discussed in the introduction.

One more characteristic frequency can be obtained in a similar way, but considering the viscous resistance of a crack-like defect to the compression in the direction normal to its plane. This viscous resistance should be compared with the elastic reaction also in the normal direction. To estimate the normal viscous resistance we have to supplement Eq. (17) with the continuity equation

$$\frac{\partial v_x}{\partial x} + \frac{\partial v_y}{\partial y} = 0 \tag{20}$$

since in the first approximation the liquid can be considered incompressible. For the discussed nearly Poiseuille flow, $\partial v_x/\partial x \sim v_x/L$ and $\partial v_y/\partial y \sim v_y/L$, so that from Eq. (20) we obtain $v_x \sim (L/h)v_y$. Since the variation Δh of the crack opening in the acoustic field corresponds to $v_y \sim \omega \Delta h$, we find that $v_x \sim (L/h)\omega \Delta h$. Next, in Eq. (17), we can similarly estimate that $\partial p/\partial x \sim p/L$ and $\eta \partial^2 v_x/\partial y^2 \sim \eta v_x/h^2$. Neglecting the first inertial term in Eq. (17) for the Poiseuille flow and equalling the above estimated terms in the right-hand side of Eq. (17) we obtain the estimate for the pressure p^{visc} induced by the viscous flow of the liquid in the narrow gap:

$$p^{visc} \sim \eta \upsilon_x(L/h^2) \sim \eta \omega(L/h)^2(\Delta h/h),$$
 (21)

For the application to real cracks it is important to understand how critical is the parallelism of the crack surfaces (which for real cracks is rather a rule than an exception). Assuming that the crack opening has the values h_1 and h_2 at the opposite sides we conclude that, in the extreme case when at one side the $h_1 = 0$, the maximal nonpapallelism angle is of the order $h/L \sim \alpha$, where h is the average crack opening. It is clear that for estimate (21), this small non-parallelism is not important. On the other hand, one may argue that if the planes are not exactly parallel then the tangential viscous force acting along the inclined wall has a component normal to the crack plane. The viscous stress τ^{visc} acting along the inclined plane is readily estimated as $\tau^{visc} \sim \eta v_x/h \sim \eta(L/h)\omega\Delta h/h$, so that its normal component is $\tau_n^{visc} \sim \tau^{visc}\alpha \sim \eta\omega\Delta h/h$. Comparing the latter contribution and Eq.(21) for the pressure due to the viscous flow, we see that p^{visc} is $1/\alpha^2 >> 1$ times greater than τ_n^{visc} , so that actually the contribution of the eventual non-parallelism is not significant. Thus we can use Eq. (21) for the normal viscous reaction even for cracks with not perfectly parallel surfaces.

Now we have another question: what is the elastic reaction that should be taken for comparison with the above found value (21) for the viscous normal resistance. In literature different variants can be found. One variant is by analogy with obtaining Eq. (19) to compare Eq. (21) with the normal elastic reaction of the crack related to its effective modulus, that is, the quantity $\sim \alpha K$. The latter value corresponds to the well known rule of thumb³² that the effective softness relatively to the matrix material for a crack approximately equals its aspect ratio. This comparison gives us some characteristic frequency often discussed in literature³³

$$\omega_K \sim \alpha^3 K/\eta.$$
 (22)

Less formally, it can be said that the viscous flow pressure p^{visc} arisen due to approaching of the crack surfaces by Δh (see Eq.(21)) becomes so high that the nearcrack region of the size L (where the elastic stress was initially nearly released) experiences compression by the value $\Delta h^* \sim p^{visc}/(KL)$. For $\omega \sim \omega_K$, the value of Δh^* becomes comparable with the initial approaching Δh and strongly compensates the latter. If the crack is "instantaneously" compressed, initially the liquid remains almost "frozen" and then is redistributed during the characteristic time $1/\omega_K$ when the elastic compression Δh^* of the near-crack region gradually releases. For sufficiently high frequency $\omega \gg \omega_K$, the actually displaced volume of the liquid is equal to a small fraction ω_K/ω of the volume that would be quasistatically displaced, so that if the flow structure remains of the Poiseuille type, the amount of the dissipated energy during one period decreases as $(\omega/\omega_K)^{-1}$. This observation will be used below to estimate the absorption in the relaxation maximum.

It can also be pointed out that besides the relaxation frequency (22) another relaxation frequency for cracks filled by compressible fluids is also discussed²⁸. Namely, in view of the fact that modulus K_f of the filling fluid typically is at least an order of magnitude smaller than modulus K, it can be argued that the surrounding rock in the first approximation compresses the fluid as "absolutely rigid" body. Thus comparing the pressure of the compressed fluid $K_f \Delta h/h$ with the above found normal viscous reaction (21) of the fluid flow, we obtain another characteristic frequency $\omega_r \sim K_f \alpha^2/\eta$ which is determined by the compressibility of the fluid and in contrast to Eq.(22) does not depend on the modulus of the rock.^a This new relaxation frequency differs from ω_K given by Eq.(22) by a factor of $K_f/(K\alpha)$. For narrow cracks with $\alpha \ll 1$ and typical liquids like water or oil, for which $K_f/K \sim 10^{-1}$, the factor $K_f/(K\alpha)$ is quite large, so that $\omega_r \gg \omega_K$. In such a case, long before the frequency ω_r would be attained, the fluid flow should already be strongly damped for $\omega > \omega_K$ because of the finite rigidity of the near-crack region as discussed above. Therefore, the initial low-frequency asymptotic $\propto \omega$ cannot be extrapolated till the frequency $\omega_r \gg \omega_K$. Consequently, the new (and potentially stronger) relaxation maximum near ω_r simply will not be formed for typical liquids (like water and oil), for which $K_f/(K\alpha) \gg 1$. Only for sufficiently high-compressible (gaseous) fluids with $K_f/(K\alpha) < 1$ this mechanism should form the relaxation maximum near ω_r . But in this case the relaxation frequency ω_r should necessarily lie lower than ω_K .

Less formally, the physical meaning of this type of relaxation is that a finite time is required for a compressible fluid squeezed inside a crack to form the flow which redistributes the fluid end equalizes the internal pressure.

In any case, the character of such flows can noticeably be perturbed only if the mean opening of the entire crack is perturbed. This means that the mean perturbing strain should already be comparable with α like for the above-considered "global" thermoelastic loss.

^a Finally, another type of the characteristic frequency related to the fluid compressibility was considered in paper²⁹. For this

In what follows, we consider a modified form of the viscous loss in cracks with wavy roughness of the surface. This mechanism relates to the conventionally considered viscous loss at cracks much like the thermoelastic loss at the inner contacts relate to the thermoelastic loss at a crack as a whole. Even for "normal" liquids, the new strongly shifted to lower frequencies and very intense relaxation maximum is related to the fluid compressibility rather than to compressibility of rock in the crack vicinity. Besides, which is especially interesting, the stress sensitivity of such a mechanism can be additionally enhanced orders of magnitude and can readily explain the experimental data discussed in the introduction.

Consider a crack with a "waist" created by wavy asperities as shown in Fig. 4. The notations used are clear from the figure. Here, quantities P_i characterize the pressure in the respective cross sections of the crack. Assuming again the Poiseuille character of the flow for sufficiently low frequencies, the nearly plane fluid flow $q = L_z \int v_x(y) dy$ in the main part of the crack and in the narrower region of the waist should be equal:

$$q = \frac{h^3 L_z}{12\eta} \frac{P_2 - P_1}{L} = \frac{\tilde{h}^3 L_z}{12\eta} \frac{P_3 - P_2}{\tilde{l}}, \tag{23}$$

where the meaning of the pressure gradients $(P_2 - P_1)/L$ and $(P_3 - P_2)/\tilde{l}$ is clear from Fig. 4. Then Eq. (23) yields

$$\frac{P_2 - P_1}{P_3 - P_2} \sim \frac{\tilde{h}^3 L}{h^3 \tilde{l}},\tag{24}$$

so that for sufficiently narrow waist in the crack, $(h^3/h^3)(L/l) \ll 1$, we conclude that $(P_2 - P_1) \ll (P_3 - P_1) \ll (P_3 - P_2)$ P_2) $\approx \Delta P_{tot}$, that is, the total drop ΔP_{tot} of pressure is mainly localized in the region of the narrow waist. Now imagine an instantaneous slight compression of the crack under an external action after which the fluid compressed inside the crack flows through the narrowing into the outer region to equalize the pressure. This flow will exponentially decrease with a characteristic relaxation time τ . Consequently the total volume q_{τ} of the leaked fluid during this relaxation process is given by the integral

$$q_{\tau} = q \int_{0}^{\infty} exp(-t/\tau)dt = q\tau, \tag{25}$$

where q is the flow value corresponding to the initial excess of pressure inside the crack over the pressure in the outer space. Since the rigidity of the outer pore space is much greater than that of the thin crack, the change in the volume of this rigid pore fraction is negligibly small compared with the strain of the crack. Consequently, the outer pore pressure remains close to its equilibrium value

characteristic frequency, the elastic wave length becomes comparable with the length of the liquid drop inside the crack, so that the liquid drop cannot be already considered as a lumped object in the scale of the elastic wave length. If the liquid occupies almost all crack of diameter L, this frequency is given by the condition $\omega \sim (K_f/\rho)^{1/2}/L$, which corresponds to fairly high ultrasonic frequencies and will not be further discussed.




FIG. 4. Schematically shown crack with a narrow strip-like waist created by wavy asperities. The dominant part of the total difference in the pressure $|P_1 - P_4|$ in the fluid flow is localized near the narrow waist, so that $|P_1-P_4|/|P_3-P_2|\approx 1$. P_4 is close to the equilibrium pressure P_0 in the outer pore channel.

 P_0 and we can consider that $P_3 - P_2 \approx P_1 - P_4 \approx P_1 - P_0$. Thus the initial value of the flow

$$q = \frac{h^3 L_z}{12\eta} \frac{P_3 - P_2}{\tilde{l}} \approx \frac{\tilde{h}^3 L_z}{12\eta} \frac{P_1 - P_0}{\tilde{l}}, \tag{26}$$

Since the variation χ in the volume of the liquid and the pressure P are related via the bulk modulus K_f of the liquid, $P = \chi K_f$, then the total liquid volume $q_\tau = q\tau$ displaced in order to equalize the pressure can be written via the initial volume C_0 of the fluid-filled crack as

$$q_{\tau} = C_0(\chi_1 - \chi_0) = C_0 K_f(P_1 - P_0), \tag{27}$$

Equations (26) and (27) yield

$$q_{\tau} = \frac{h^3 L_z}{12\eta} \frac{K_f(\chi_1 - \chi_0)}{\tilde{l}} \tau \approx C_0(\chi_1 - \chi_0).$$
 (28)

Assuming that the sizes of cracks along X and Z directions are of the same order $L_z \sim L$, the crack volume can be estimated as $C_0 \approx hL^2$, so that from Eq. (28) we readily obtain the relaxation time $\tilde{\tau}$ and its inverse value, i.e., the relaxation frequency $\widetilde{\omega}_r$ (tilde denotes that we consider the crack with a narrowing):

$$\widetilde{\omega}_r = \frac{\alpha^2 K_f}{12\eta} \left(\frac{\widetilde{h}}{h}\right)^3 \frac{L}{\widetilde{l}}, \text{ and } \widetilde{\tau} = \frac{12\eta}{\alpha^2 K_f} \left(\frac{h}{\widetilde{h}}\right)^3 \frac{\widetilde{l}}{L}.$$
 (29)

Here, we intentionally singled out the squared aspect ratio α^2 for convenience of comparison with the crack without waists²⁸. The absence of the narrow waist can be interpreted as $l \sim L$ and $h \sim h$, i.e., $(h/h)^3 l/L \sim 1$ so that Eq. (29) reduces to

$$\omega_r = \frac{\alpha^2 K_f}{12\eta}$$
, and $\tau \approx \frac{12\eta}{\alpha^2 K_f}$. (30)

Within the accuracy of its derivation Eq. (30) coincides with the result $\tau \approx 8\eta/\alpha^2 K_f$ obtained in work²⁸ for narrow cracks without the waist.

The relaxation times in Eqs. (29) and (30) do not depend on the elastic modulus of the solid matrix. However, we have already mentioned that for cracks with uniform opening, the relaxation peak (30) can actually be formed

only for very highly compressible fluids (i.e., gases rather than liquids), for which $K_f/K \leq \alpha$, otherwise the compressibility of rock in the crack vicinity should dominate and form the relaxation peak near ω_K given by Eq.(22).

In contrast to this, the presence of the narrow waist creates a strong obstacle for the fluid leaking. Therefore, for a given frequency, this increases the role of the liquid compression, whereas the pressure p^{visc} and the deformation of the rock in the crack vicinity is strongly reduced. All this results in a very strong reduction of the relaxation frequency $\widetilde{\omega}_r$ related to the compressibility of the fluid (compare Eq. (30) and Eq. (29) containing the additional small factor $(\tilde{h}/h)^3\tilde{l}/L \ll 1$). Thus even for "normal" liquids like water and oil, the frequency $\widetilde{\omega}_r$ of the new relaxation maximum becomes comparable and even lower than ω_K , that is, shifts from ultrasonic frequencies to the seismoacoustic range directly relevant to the experiments^{11,13,14,15,16} discussed in the Introduction.

Compared with the mean crack opening h, the local opening h of the waist is much more sensitive to variations in the mean strain in the medium. Therefore it is not necessary to assume the existence of unrealistically thin cracks to ensure the same sensitivity for the mean opening of the crack. The conditions ensuring the Poiseuille type of the flow are even better fulfilled in the vicinity of the waist, so that we can apply the considered in the beginning of this section aguments concerning the low- and high-frequency asymptotic behavior of the decrement (proportional to ω and $1/\omega$, respectively). This means that the dissipation due to the discussed mechanism can be well approximated by the frequency dependence for a standard relaxator:

$$\theta \approx \theta_0 \frac{\omega/\widetilde{\omega}_r}{1 + (\omega/\widetilde{\omega}_r)^2},$$
 (31)

where the relaxation frequency $\widetilde{\omega}_r$ is given by Eq. (29) for a crack with a narrow waist.

Now, using Eq. (16) we will determine the prefactor θ_0 in two cases: for a crack with the narrow waist and for a similar in size crack with uniform opening, although in the latter case the formation of the relaxation peak ω_r can be possible only if $K_f/K \leq \alpha$, that is, for gaseous fluids (or for unrealistically rigid solid matrix in the case of "normal" liquids). Nevertheless, such an expression will be useful for comparison.

The velocity profile for the Poiseuille's flow in the crack with uniform opening h has a parabolic form

$$v_x = -\frac{1}{2\eta} \frac{\partial P}{\partial x} y(h - y) = -4v_{\text{max}} \frac{y(h - y)}{h^2}, \quad (32)$$

where $v_{max} = -\frac{1}{8\eta} \left| \frac{\partial P}{\partial x} \right| h^2$ is the maximal velocity of the fluid in the flow. Similarly, for the narrow waist, where the losses and gradients are localized, we have

$$\tilde{v}_x = -\frac{1}{2\eta} \frac{\partial P}{\partial x} y (\tilde{h} - y) = -4 \tilde{v}_{\text{max}} \frac{y (\tilde{h} - y)}{\tilde{h}^2}, \quad (33)$$

where $\widetilde{v}_{max} = -\frac{1}{8\eta} |\frac{\partial P}{\partial x}| h^2$. Equations (16), (32), (33) yield for $\partial W_{kin}/\partial t$ the following expressions in the discussed two cases of the crack without and with the waist:

$$\frac{\partial W_{kin}}{\partial t} = -\frac{8}{3}\eta v_{\text{max}}^2 \frac{L_x L_z}{h} \tag{34}$$

$$\frac{\partial \widetilde{W}_{kin}}{\partial t} = -\frac{8}{3} \eta \widetilde{v}_{\max}^2 \frac{\widetilde{l}L_z}{\widetilde{h}}$$
 (35)

In the estimates below we will assume that $L_x \sim L_z \sim L$. Let us now relate the characteristics of the flow with the mean strain in the crack-containing solid. When the mean macroscopic strain ε is created in the material, the crack volume correspondingly changes, which creates the flow of the liquid inside the crack. We recall³² that the crack is a soft object whose relative (compared with the surrounding matrix) compliance ζ is approximately equal to the crack aspect ratio, $\zeta \sim \alpha \sim h/L$. Therefore, the own strain ε_{cr} of the crack (i.e., the relative variation in its volume) can be estimated as $\varepsilon_{cr} \approx \varepsilon/\alpha \approx \varepsilon L/h$, where L is the characteristic size of the crack, so that its volume can be estimated as $V_{cr} \sim L^2 h$. Then for the variation in the crack volume ΔV_{cr} one obtains $\Delta V_{cr} \approx \varepsilon_{cr} V_{cr} \sim \varepsilon L^2 h \cdot (L/h) = \varepsilon L^3$. Under sinusoidal oscillatory variation of the crack volume with frequency ω and amplitude ΔV_{cr} , we can readily relate the rate $\omega \Delta V_{cr}$ of the crack-volume variation with the maximum velocity of the Poiseuille's flow of the fluid inside the cracks without and with the waist:

$$v_{max} = \frac{3}{2} \frac{\omega \varepsilon L^2}{h} \tag{36}$$

$$\widetilde{v}_{max} = \frac{3}{2} \frac{\omega \varepsilon L^2}{\widetilde{h}} \tag{37}$$

Substituting these expressions into Eqs. (34) and (35) for cracks without and with the waist we obtain for the period-averaged amounts of the dissipated energy expressions via the amplitude of the mean strain ε :

$$\left(\frac{\partial W_{kin}}{\partial t}\right)_{aver} = -3\eta\omega^2\varepsilon^2 \frac{L^6}{h^3} \tag{38}$$

$$\left(\frac{\partial \widetilde{W}_{kin}}{\partial t}\right)_{aver} = -3\eta\omega^2\varepsilon^2 \frac{L^5\widetilde{l}}{\widetilde{h}^3}$$
(39)

In Eqs. (38) and (39) we took into account that for sinusoidal strain with amplitude ε , the period-averaged value of its square equals $\varepsilon^2/2$. We also take into account that the energy loss during one period $T=2\pi/\omega$ is $W_0 = (2\pi/\omega)(\partial W_{kin}/\partial t)_{aver}$ and the density of the accumulated elastic energy is $W_{el} \approx K \varepsilon^2/2$ (since in the used approximation we assume that the elastic modulus does not significantly change due to the presence of the cracks). Then from Eq.(1) we obtain the following asymptotic low-frequency expression for the decrement in the case of cracks without the waists:

$$\theta_{LF} = 6\pi \eta \frac{L^6}{h^3 K} n_{cr} \omega, \tag{40}$$

The low-frequency Eq. (40) is obtained neglecting the liquid compressibility and agrees with the low-frequency results earlier obtained for cracks without waists²⁹.

To obtain high-frequency expressions (for $\omega \gg \omega_r$) we take into account that because of the finite relaxation time, the volume of the replaced liquid is ω/ω_r smaller than in the low-frequency limit. Thus the high-frequency expression for the cracks without the waists is

$$\theta_{HF} = 6\pi \eta \frac{L^6}{h^3 K} n_{cr} \omega \frac{\omega_r^2}{\omega^2} = \frac{\pi}{2} n_{cr} L^3 \frac{K_f}{\alpha K} \frac{\omega_r}{\omega}. \tag{41}$$

For cracks with the waists in a similar way we obtain:

$$\widetilde{\theta}_{LF} = 6\pi \eta \frac{L^6}{\widetilde{h}^3 K} \left(\frac{\widetilde{l}}{L}\right) \widetilde{n}_{cr} \omega, \tag{42}$$

$$\widetilde{\theta}_{HF} = 6\pi \eta \frac{L^6}{\widetilde{h}^3 K} \left(\frac{\widetilde{l}}{L} \right) \widetilde{n}_{cr} \omega \frac{\widetilde{\omega}_r^2}{\omega^2} = \frac{\pi}{2} \widetilde{n}_{cr} \frac{L^3 K_f}{\alpha K} \frac{\widetilde{\omega}_r}{\omega}.$$
(43)

Comparing Eqs. (40), (41) and (42), (43) with the lowand high-frequency asymptotics of Eqs. (31) we obtain the following relaxator-like expressions for the viscous loss at cracks without and with the waists, respectively:

$$\theta = \frac{\pi}{2} \frac{K_f L^3}{K\alpha} n_{cr} \frac{\omega/\omega_r}{1 + (\omega/\omega_r)^2},\tag{44}$$

$$\widetilde{\theta} = \frac{\pi}{2} \frac{K_f L^3}{K\alpha} \widetilde{n}_{cr} \frac{\omega/\widetilde{\omega}_r}{1 + (\omega/\widetilde{\omega}_r)^2},\tag{45}$$

where ω_r and $\widetilde{\omega}_r$ are given by Eqs. (29).

A striking feature of Eqs. (44) and (45) is that they have the same maximum values determined by the characteristic size L of the whole crack. However, the relaxation frequency in Eq. (45) is strongly shifted from ultrasonic to seismoacoustic frequencies down to $10^0 - 10^2$ Hz which were used in field experiments 11,15,16 .

The next point is that much smaller mean strains (such as the above discussed tidal strains) can already noticeably affect the opening of the waist. This means that due to the variation in the relaxation frequency $\widetilde{\omega}_r$ for the crack with the waist, the position of the relaxation maximum can noticeably be changed, whereas the height of the relaxation maximum should remain yet practically unperturbed. Taking into account the equality of the absolute variations $\Delta h \approx \Delta h$ and the relationship $\varepsilon_{cr} = \varepsilon/\alpha = \varepsilon L/h$ (which we have already used above) we find that the relative variation in the relaxation frequency $\widetilde{\omega}_r$ caused by the variation $\Delta \varepsilon$ in the mean strain:

$$\Delta\widetilde{\omega}_r/\widetilde{\omega}_r = \Delta\varepsilon \frac{d\widetilde{\omega}_r}{d\varepsilon} \frac{1}{\widetilde{\omega}_r} \approx \Delta\varepsilon \frac{3h}{\widetilde{h}} (L/h) = \Delta\varepsilon \frac{3h}{\widetilde{h}} \frac{1}{\alpha}. \quad (46)$$

The parameter $(3h/h)/\alpha$ can be very large, for example, $(3h/\tilde{h})/\alpha \sim 10^6$ for quite realistic $\alpha \sim 10^{-4}$ and $(h/\tilde{h}) \sim$ 20..30. Thus the tidal strains with amplitude $\varepsilon_0 \sim 10^{-8}$ can cause the peak-to-peak variation in the relaxation frequency $2\Delta \widetilde{\omega}_r/\widetilde{\omega}_r$ of several percents and, consequently,

comparable variation $2\Delta\theta/\theta$ of the decrement should be observed at the wings of the relaxation curve.

Besides, there are known indications that for flows in very narrow gaps (down to nanometer scale), the effective viscosity of the liquid can significantly exceed the viscosity for macroscopic gaps^{34,35}. This effect can additionally enhance the variations in the dissipation due to variations in the waist opening. Since small variations in the average strain practically do not yet affect the average aspect ratio for the crack, the prefactor in Eq. (45) remains practically unchanged. Thus the shift of the relaxation maximum can cause the variation in $\Delta\theta$ of opposite signs depending on the position of the observation frequency ω relative to the frequency $\widetilde{\omega}_r$ of the relaxation-curve maximum similar to the situation for the thermoelastic loss illustrated in Fig. 3.

Since not all cracks can have the strip-like waists, it is a key question how many such cracks are required to ensure near the characteristic frequency $\widetilde{\omega}_r$ the dissipation $\theta \sim$ $10^{-2}-10^{-1}$. Since the maximum of the frequency factor in Eq. (45) is 1/2 we have to estimate the factor

$$\widetilde{\theta}_{max} = \frac{\pi}{4} \frac{K_f L^3}{K\alpha} \widetilde{n}_{cr} = \frac{\pi}{4} \frac{K_f}{K\alpha} \widetilde{\epsilon}, \tag{47}$$

where we singled out the quantity $\tilde{\epsilon} = L^3 \tilde{n}_{cr}$. The latter is close to the effective volume of cracks³⁶ (i.e., the volume of the circumscribed spheres independent of the cracks' aspect ratios). For the further estimates we will use the well known fact that the presence of cracks with the effective volume $\tilde{\epsilon}$ results is the reduction of the elastic moduli of the material by a fraction of $a\tilde{\epsilon}$ (where factor $a \sim 1$ slightly differ for particular moduli³⁶). Then taking for filling water $K_f = 2.25 \cdot 10^9$ Pa, modulus $K = 3.8 \cdot 10^{10}$ Pa typical of quartz, and $\alpha = 10^{-3} - 10^{-4}$ we obtain $\widetilde{\theta}_{max} \approx (50-500)\widetilde{\epsilon}$. This means that for the effective crack density $\widetilde{\epsilon} = 10^{-2} - 10^{-3}$, which reduces the elastic moduli also by a fraction of order $10^{-2} - 10^{-3}$, we can already obtain $\widetilde{\theta} \sim 10^{-2} - 10^{-1}$ in the vicinity of the relaxation frequency $\widetilde{\omega}_r$. On the other hand, it is well known that in real sandstones the modulus reduction due to high-compliant crack-type porosity typically is on the order of tens of percents³⁷. This means that even if only a small portion of all cracks (a few percents or even less) has wavy surfaces creating the narrow waists, this portion can already be sufficient to explain both the background value of dissipation observed in the seismo-acoustic frequency range $10^0 - 10^3$ Hz and its extremely high strain sensitivity indicated by the experimental data^{11,15,16}.

Therefore, the considered modified mechanism of the squirt-type dissipation in cracks suggests a plausible alternative explanation to the experimentally observed rather high dissipation in the seismoacoustic frequency range. In terms of paper³⁸, our mechanism is of purely "microscopic" type and does not require the presence of larger-scale ("mesoscale") heterogeneities assumed in the "double porosity" and "patchy saturation" models to shift the frequencies of viscous relaxation towards the seismoacoustic frequency range. Certainly such mechanisms can operate simultaneously. However, among those possibilities, only the above considered modified squirt




FIG. 5. Schematically shown relative positions and heights of the viscous relaxation peaks at ω_r and ω_K for the crack as a whole (curves 1 and 1') and the low-frequency peak for a crack of the same size L having an inner narrow waist with the local opening \widetilde{h} and length \widetilde{l} (curve 2). The examples correspond to $(h/\tilde{h})^3(\tilde{l}/L) = 10^4$ and $\alpha = 10^3$.

mechanism is evidently able to ensure sufficiently high strain sensitivity to explain the observations^{11,15,16}.

To better understand the ratio of contributions of the conventional and the proposed modified squirt mechanisms, let us compare the corresponding decrements given by Eqs. (44) and (45) in the vicinity of the characteristic relaxation frequency $\omega \sim \widetilde{\omega}_r$ of the cracks with the narrow waists. Since $\omega_r \ll \widetilde{\omega}_r$ for this comparison we take the low-frequency asymptotic form of Eq. (44), such that in the vicinity of $\widetilde{\omega}_r$ we obtain

$$\theta(\omega \sim \widetilde{\omega}_r) \approx 2 \frac{n_{cr}}{\widetilde{n}_{cr}} \frac{\widetilde{\omega}_r}{\omega_r} \widetilde{\theta}_{max},$$
 (48)

where the difference in the relaxation frequencies $\omega/\widetilde{\omega}_r =$ $(h/\tilde{h})^3(\tilde{l}/L) \gg 1$ as follows from Eqs. (29) and (30). The factor $(h/\tilde{h})^3(\tilde{l}/L)$ which can easily reach $10^2 - 10^4$, so that guite a small portion of cracks with narrow waists can ensure in the low-frequency range a contribution comparable with or even strongly exceeding the contribution of the majority of other cracks of the same size, but without the waists. For example, a portion $\widetilde{n}_{cr}/n_{cr} \sim 10^{-2}-10^{-4}$ of cracks with narrow waists is able to ensure extremely high sensitivity of the overall decrement to weak variations in the mean strain.

Figure 5 illustrates the relative positions and heights of the relaxation peaks corresponding to the relaxation frequencies $\widetilde{\omega}_r$ (Eq. (29)) for a crack with a narrow waist, and the peaks at frequencies ω_K (Eq. (22)) and ω_r (Eq. (30)) for cracks with the same aspect ratio α and size L, but without waists. We emphasize that for $\omega_K < \omega_r$, the relaxation peak at ω_r actually does not exist and is shown by the dashed line. However, it is shown for convenience of comparison with the low-frequency peak $\widetilde{\omega}_r$, for which the height is the same as for the would-be peak at ω_r . The figure demonstrates that the viscous relaxation in cracks with the waists can form extremely

strong peaks in the seismo-acoustic frequency range, so that even for small density of such cracks, their contribution can easily account for the typically observed levels of the dissipation in this frequency range.

Concerning the question of averaging over the distribution of real cracks over their parameters, we can put forward very similar arguments as for Eq. (11) in the above considered case of thermoelastic loss. Namely, it is reasonable to assume that the distributions over the sizes Land h of the crack as a whole and the distribution over the local parameters h and l of the waist (which determine the characteristic relaxation frequency $\widetilde{\omega}_r$) are essentially independent and can be factorized. Therefore, the averaging over the characteristic size L of the crack gives only a numerical factor like in integral Eq. (11), whereas the averaging over the relaxation frequencies (of, equivalently, the relaxation times) can also be performed independently. Such averaging should not radically change the conclusions obtained for the simplest case of cracks with identical parameters of the inner contacts or waists.

V. CONCLUSION

The performed analysis of the role of elongated inner contacts and waists in cracks significantly changes the conclusions based on conventionally discussed models of thermoelastic dissipation at cracks (like^{23,24}) and viscous squirt loss (like works^{28,29,31,33,38}). Thus a single larger crack with a strip-like contact can ensure the same thermoelastic dissipation as $10^5 - 10^6$ small cracks of the size equal to the contact width.

For fluid saturated cracks, a rather intense maximum formed by a crack with a narrow waist can ensure the same dissipation in the seismo-acoustic frequency range of $10^2 - 10^3$ Hz as a similar crack without the waist would produce in the ultrasonic range according to conventional squirt-dissipation models (see Fig. 5). This can significantly affect some conclusions³⁸ on insignificant role of local viscous loss at cracks in the seismo-acoustic range.

Probably the most striking feature of the considered modified dissipation mechanisms is their giant strain sensitivity. In this context, it should be clearly understood that each group of cracks with the wavy asperities can exhibit this giant strain sensitivity only in a rather narrow strain range. When the waist becomes either completely closed or widely open, the loss at such cracks does not much differ from that at cracks without the asperities. Nevertheless, since the parameters of real cracks should have rather wide distribution, for a current mean strain, another portion of cracks with such narrow waists or contacts can be "activated". This resolves the problem¹⁴ how apparently very soft defects exhibiting giant strain sensitivity can exist under very different mean pressures (in a wide range of depths in field conditions). Their giant effective compliance should be understood as differential. It cannot be directly extrapolated for significantly higher strains $10^{-6}-10^{-4}$ often used in laboratory experiments or typical of tectonic strains, for which the level of the dissipation does not change many times, although for 10^{-8} the variations may reach several percents.

We acknowledge the support of the RFBR grants Nos 09-02-91071-CNRS and 11-05-01003.

- ¹ R. A. Guyer and P. A. Johnson, "Nonlinear mesoscopic elasticity", Physics Today **52**, 30–36 (1999).
- ² V. Y. Zaitsev, "A model of anomalous elastic nonlinearity of microinhomogeneous media", Acoustics Lett. 19, 171-174 (1996).
- $^{3}\,$ I. Y. Belyaeva and V. Y. Zaitsev, "Nonlinear elastic properties of microinhomogeneous hierarchically structured media", Acoustical Physics 43, 594-599 (1997).
- ⁴ V. Y. Zaitsev and P. Sas, Dissipation in microinhomoeneous solids: inherent amplitude-dependent loss of a nonhysteretic and non-frictional type, Acustica-Acta Acustica **86**, 429–445 (2000).
- V. E. Nazarov, A. V. Radostin, and I. A. Soustova, Effect of an intense sound wave on the acoustic properties of a sandstone bar resonator. Experiment, Acoustical Physics **48**, 76–80 (2002).
- ⁶ R. B. Gordon and L. A. Davis, Velocity and attenuation of seismic waves in imperfectly elastic rock, J. Geophys. Res. **73**, 3917–3935 (1968).
- M. N. Toksöz, D. H. Johnston, and A. Timur, Attenuation of seismic waves in dry and saturated rocks: I. Laboratory measurements, Geophysics 44, 681-690 (1979).
- V. Y. Zaitsev, V. E. Gusev, and B. Castagnède, Thermoelastic mechanism for logarithmic slow dynamics and memory in elastic wave interactions with individual cracks, Phys. Rev. Lett. **90**, 075501(1-4) (2003).
- L. Fillinger, V. Y. Zaitsev, V. Gusev, and B. Castagnède, Wave self-modulation in an acoustic resonator due to self-induced transparency, Europhysics Lett. 76, 229–235
- E. I. Mashinskii, Experimental study of the amplitude effect on wave velocity and attenuation in consolidated rocks under confining pressure, J. Geophys. Eng. 2, 199–212
- B. M. Glinskii, V. V. Kovalevskii, and M. S. Khairetdinov, Vibroseismic monitoring of earthquake-prone areas, Volcanol. and Seismol. 21, 723–730 (2000).
- $^{\rm 12}$ P. Melchior, $\it The\ tides\ of\ the\ planet\ Earth\ (Pergamon$ Press, Oxford, 1983), 653 p.
- ¹³ T. L. de Fazio, K. Aki, and J. Alba, Solid earth tide and observed change in the in situ seismic velocity, J. Geophys. Res. 78, 1319–1322 (1973).
- ¹⁴ P. Reasenberg and K. Aki, A precise, continuous measurement of seismic velocity for monitoring in situ stress, J. Geophys. Res. 79, 399–406 (1974).
- ¹⁵ B. N. Bogolyubov, V. N. Lobanov, V. E. Nazarov, V. I. Rylov, A. A. Stromkov, and V. I. Talanov, Phaseamplitude modulation of a seismoacoustic wave under diurnal tides, Russ. Geol. and Geophys. 45, 996–1000 (2004).
- $^{16}\,$ V. Saltykov, V. Chebrov, Y. Kugaenko, and V. Sinitsyn, High-frequency seismic noise: Results of investigation in Kamchatka, Phys. Chem. Earth 31, 132-137 (2006).
- $^{\rm 17}\,$ V. A. Saltykov, M. Kasahara, E. I. Gordeev, M. Okayama, V. I. Sinitsyn, M. Takada, and V. N. Chebrov, Highfrequency seismic noise components observed on cape Erimo, Hokkaido Island, Japan, Izvestia Phys. Solid Earth **38**, 165–172 (2002).
- V. Y. Zaitsev, V. A. Saltykov, and L. A. Matveev, Relation between the tidal modulation of seismic noise and the amplitude-dependent loss in rock, Acoustical Physics 54,

- 538-544 (2008).
- G. M. Mavko, Frictional attenuation: an inherent amplitude dependence, J. Geophys. Res. 84, 4769-4775 (1979).
- M. M. Sharma and A. N. Tutuncu, Grain contact adhesion hysteresis: A mechanism for attenuation of seismic waves, Geophys. Res. Lett. 21, 2323-2326 (1994).
- V. Y. Zaitsev and L. A. Matveev, Strain-amplitude dependent dissipation in linearly dissipative and nonlinear elastic microinhomogeneous media, Russ. Geol. and Geophys. 47, 694-709 (2006).
- ²² L. D. Landau and E. M. Lifshitz, Theory of elasticity, (Butterworth-Heinemann, Oxford, 1986), Chap. 5.
- ²³ B. H. Armstrong, Frequency-independent background internal friction in heterogeneous solids, Geophysics 45, 1042–1054 (1980).
- ²⁴ J. C. Savage, Thermoelastic attenuation of elastic waves by cracks, J. Geophys. Res. 71, 3929-3938 (1966).
- $^{25}\,$ M. F. Kanninen and C. H. Popelar, Advanced fracture mechanics (Oxford Univ. Press, NY, 1985), 584 p.
- ²⁶ V. Y. Zaitsev, V. E. Gusev, and B. Castagnède, Luxemburg-gorky effect retooled for elastic waves: A mechanism and experimental evidence, Phys. Rev. Lett. **89**, 105502(1–4) (2002).
- ²⁷ L. Fillinger, V. Y. Zaitsev, and V. Gusev, Nonlinear relaxational absorption/transparency for acoustic waves due to thermoelastic effect, Acustica-Acta Acustica 92, 24-34
- ²⁸ D. H. Johnston, M. N. Toksöz, and A. Timur, Attenuation of seismic waves in dry and saturated rocks: II. Mechanisms, Geophysics 44, 691-711 (1979).
- G. M. Mavko and A. Nur, Wave attenuation in partially saturated rocks, Geophysics 44, 161–178 (1979).
- L. D. Landau and E. M. Lifshits, Fluid mechanics, Chap. 2, (Butterworth-Heinemann, Oxford, 1987), Chap. 2.
- J. B. Walsh, New analysis of attenuation in partially melted rock, J. Geophys. Res. 74, 4333–4337 (1969).
- G. M. Mayko and A. Nur. The effect of nonelliptical cracks on the compressibility of rocks, J. Geophys. Res. 83, 4459-
- ³³ W. F. Murphy, K. W. Winkler, and R. L. Kleinberg, Acoustic relaxation in sedimentary rocks: Dependence on grain contacts and fluid saturation, Geophysics 51, 757-
- $^{34}\,$ N. V. Churaev, V. D. Sobolev, and Z. M. Zorin, Thin liquid films and boundary layers, Spec. Disc. Faraday Soc. 213-220 (1971).
- N. R. Tas, J. Haneveld, H. V. Jansen, M. Elwenspoek, and A. Van Den Berg, Capillary filling speed of water in nanochannels, Appl. Phys. Lett. 85, 3274–3276 (2009).
- R. J. O'Connell and B. Budiansky, Seismic velocities in dry and saturated rocks, J. Geophys. Res. 79, 5412-5426 (1974).
- G. Mavko and D. Jizba, The relation between seismic Pand S-wave velocity dispersion in saturated rocks, Geophysics 59, 87-92 (1994).
- S. R. Pride, J. G. Berryman, and J. M. Harris, Seismic attenuation due to wave-induced flow, J. Geophys. Res. 109, B01201 (2004).