Noisy-Interference Sum-Rate Capacity for Vector Gaussian Interference Channels

Xiaohu Shang, and H. Vincent Poor

Abstract

New sufficient conditions for a vector Gaussian interference channel to achieve the sum-rate capacity by treating interference as noise are derived, which generalize the existing results. More concise conditions for multiple-input-single-output, and single-input-multiple-output scenarios are obtained.

I. INTRODUCTION

The interference channel (IC) was first introduce by Shannon [1], and was later studied by Ahlswede [2] who gave a limiting expression for the capacity region. Determination of the single-letter expression of the capacity region of an IC has been a long standing open problem ever since.

The first capacity region of the IC was obtained by Carleial in [3] for the very strong interference case, in which the capacity is achieved by decoding and subtracting the interference before decoding the useful signals. The Gaussian IC model with power constraint was also introduced in [3]. The result of [3] was later extended to discrete memoryless ICs in [4]. In [5], Carleial showed that any Gaussian IC can be written in the standard form, i.e., both direct links have unit channel gain and the Gaussian noise has unit variance. An inner bound on the capacity region was obtained in [5] using superposition coding and sequential decoding. The best inner bound was obtained in [6] using superposition coding and joint decoding. This inner bound was later simplified in [7] and [8]. Early outer bounds on the capacity region of the IC can be found in [9], [10] and [11]. The capacity region of Gaussian IC with strong interference was obtained in [6] and [12], in which jointly decoding both the interference and the useful signal achieves the capacity. This result was extended to discrete memoryless ICs in [13]. The

X. Shang is with Bell-Labs, Alcatel-Lucent, 791 Holmdel Rd., R-127, Holmdel, NJ, 07733. Email:xiaohu.shang@alcatellucent.com. H. V. Poor is with Princeton University, Department of Electrical Engineering, Princeton, NJ, 08544. Email: poor@princeton.edu. H. V. Poor was supported in part by the National Science Foundation under Grant CNS-09-05398.

degraded memoryless IC was studied in [14] and later in [15]. The degraded Gaussian IC was studied in [12] and the sum-rate capacity was obtained. It was shown in [16] that the capacity region of a Gaussian Z interference channel (ZIC) is equivalent to that of a degraded Gaussian IC. Therefore, the sum-rate capacity of a Gaussian ZIC is automatically obtained. The corner points of the capacity region of a Gaussian IC were also studied in [16] and this still remains an open problem [17]. In [18], it has been shown that Gaussian inputs do not achieve the capacity region of the Gaussian IC in the limiting expression of [2].

In [19], two outer bounds on the capacity region were derived. The first bound is based on a genieaided approach in which additional information is provided to the receivers. The second bound of [19] is obtained by allowing cooperation between transmitters. It was speculated in [19] that there might be other genies which give tighter outer bound than [19, Theorem 1]. In [20] another outer bound was derived using different genies. Using this bound, the Han and Kobayashi inner bound [6] is shown to be within 1 bit of the capacity region. Motivated by [20], new outer bounds were derived in [21]–[23] and it was shown that the sum-rate capacity is achieved by treating interference as noise if the IC satisfies a simple condition. This kind of Gaussian IC is said to have noisy interference. This noisy-interference sum-rate capacity is extended to multi-user Gaussian ICs in [23]–[25]. Meanwhile, the sum-rate capacity for Gaussian ICs with mix-interference was determined in [22] and [26] using [19, Theorem 1].

In this paper, we study the capacity of the two-user multiple-input multiple-output (MIMO) IC. As shown in Fig. 1, the received signals are defined as

$$
\mathbf{y}_1 = \mathbf{H}_1 \mathbf{x}_1 + \mathbf{F}_2 \mathbf{x}_2 + \mathbf{z}_1
$$

$$
\mathbf{y}_2 = \mathbf{H}_2 \mathbf{x}_2 + \mathbf{F}_1 \mathbf{x}_1 + \mathbf{z}_2
$$
 (1)

where x_i , $i = 1, 2$, is the transmitted (column) vector signal of user i which is subject to the average power constraint

$$
\sum_{j=1}^{n} \text{tr}\left(E\left[\boldsymbol{x}_{ij}\boldsymbol{x}_{ij}^T\right]\right) \leq n_i
$$
\n(2)

where $x_{i1}, x_{i2}, \ldots, x_{in}$, is the transmitted vector sequence of user i, and P_i is the power constraint. The noise z_i is a Gaussian random vector with zero mean and identity covariance matrix; and H_i and F_i , $i = 1, 2$, are the channel matrices known at both the transmitters and receivers. Transmitter i has t_i antennas and receiver i has r_i antennas. Without loss of generality, we assume $H_i \neq 0$ and $P_i > 0$.

The capacity of a MIMO IC was first studied in [27] which derived an outer bound on the capacity region and determined the capacity region for the single-input-multiple-output (SIMO) IC with strong

Fig. 1. The two-user MIMO IC.

interference. A lower bound for the sum-rate capacity based on Han and Kobayashi's region were discussed in [28]. Telatar and Tse [29] showed that Han and Kobayashi's region is within one bit per receive antenna of the capacity region. Recent work in [30] and [31] extended the existing capacity results from scalar ICs to MIMO ICs under average power constraints. Specifically, [30] and [31] derived the capacity region for aligned-strong interference, and the sum-rate capacity for aligned-strong Z interference, aligned-weak Z interference, noisy interference and mixed interference under average power constraints. In [31], we say that a MIMO IC has

- aligned-strong interference if $H_i = F_i A_i$, $i = 1, 2$; or aligned strong Z interference: if $F_1 = 0$ and $H_2 = F_2A_2;$
- aligned-weak Z interference: if $\mathbf{F}_1 = \mathbf{0}$ and $\mathbf{F}_2 = \mathbf{H}_2 \mathbf{A}_2$;
- noisy interference if [31, (36)-(39)] are satisfied for all $\mathbf{S}_i \succeq \mathbf{0}$ with $tr(\mathbf{S}_i) \leq P_i$; and
- mixed interference if $H_1 = F_1A_1$ and $F_2 = H_2A_2$;

where A_i is a matrix satisfying $A_i A_i^T \preceq I$, and I is an identity matrix. It can be shown that the capacity region of the SIMO IC with strong interference [27] is a special case of that of the aligned-strong interference. Moreover, the capacity results for aligned-strong interference, aligned-strong or alignedweak Z interference and mixed-interference apply to other power constraints, e.g., a covariance matrix constraint, a peak power constraint and a per-antenna power constraint.

The noisy-interference condition for MIMO ICs was later studied in [32] which requires only the optimal covariance matrices of x_1 and x_2 to satisfy the conditions [31, (36)-(39)], as long as these optimal covariance matrices are of full rank. An application of this result is the noisy-interference sumrate capacity for symmetric SIMO ICs, i.e., H_i and F_i are column vectors with $H_1 = H_2$ and $F_1 = F_2$ and the power constraints are identical $P_1 = P_2$.

The results of [31] and [32] on the MIMO IC with noisy interference obtain different power regions.

Intuitively, [31] obtains the low power region of the noisy interference and [32] obtains the comparatively high power region of the noisy interference. The reason is that, [31] requires the power to be low enough such that any power allocation satisfies conditions [31, (36)-(39)]; while [32] requires the power to be high enough such that each eigen-mode is allocated non-zero power, and [31, (36)-(39)] are satisfied.

There exist MIMO ICs with noisy interference but which are not in the categories of [31] or [32]. These MIMO ICs include the parallel Gaussian IC [33] in which H_i and F_i are diagonal matrices, and the symmetric multiple-input-single-output (MISO) IC [32] in which H_i and F_i are row vectors with $H_1 = H_2$ and $F_1 = F_2$ and the power constraints are identical $P_1 = P_2$. For the noisy-interference conditions of both the parallel Gaussian IC and the symmetric MISO IC, there may exist some power allocations that violate [31, (36)-(39)]. Furthermore, the optimal input covariance matrices for the parallel Gaussian IC can be singular, and the optimal input covariance matrices for the symmetric MISO IC is always rank-1. Therefore, neither [31] nor [32] applies to these two special cases.

The major difficulty in the determination of the noisy-interference sum-rate capacity of a MIMO IC is that the characterization of the optimal input covariance matrices by treating interference as noise is needed in the derivation. However, these optimal input covariance matrices are unknown due to the non-convex nature of the optimization problem for maximizing the sum rate of single-user detection. In [31] all the possible input covariance matrices are required to satisfy some conditions. The results in [32] and [33], although not requiring all the input covariance matrices to satisfy the conditions, they do have some assumptions, or have some knowledge on the optimal input covariance matrices:

- Special MIMO ICs in [32]: the optimal input covariance matrices are assumed to be of full rank.
- Parallel Gaussian IC in [33]: the optimal input covariance matrices are diagonal. More importantly, the optimal power allocated at each antenna satisfies the parallel supporting hyperplane condition, or in another words, the sum-rate function for each sub-channel has the same subgradient at the optimal power allocation.
- Symmetric MISO IC in [32]: beamforming achieves the largest sum-rate for treating interference as noise. Thus the optimal input covariance matrices are both rank-1. The optimality of beamforming was proved in [34] and [35]. The same result was reproduced using different methods in [36] and [37]. By restricting to rank-1 matrices and using the assumption that the MISO IC is symmetric, the closed-form optimal input covariance matrices are obtained, which is crucial in deriving the noisy interference condition.

In this paper, we revisit the sum-rate capacity of the MIMO IC and derive a new noisy-interference

condition, i.e., treating interference as noise achieves the sum-rate capacity. This new condition requires only the optimal input covariance matrices to satisfy [31, (36)-(39)] and an additional condition, but does not require the optimal input covariance matrices to be of full rank (when they are of full rank, this additional condition is automatically satisfied). Thus, this new noisy-interference condition includes those in [31] and [32] as special cases. In addition, this noisy-interference condition includes those of the parallel Gaussian IC [33] and the symmetric MISO IC [32] as special cases. More concise condition for the general asymmetric MISO or SIMO ICs are also obtained.

The rest of the paper is organized as follows: the noisy-interference sum-rate capacity for the MIMO IC is obtained in Section II; the MISO and SIMO ICs are discussed in Sections III and IV, respectively; numerical examples are given in Section V; and we conclude in Section VI.

Before proceeding, we introduce some notation that will be used in the paper.

- Italic letters (e.g. X) denote scalars; and bold letters x and X denote column vectors and matrices, respectively.
- I denotes the identity matrix and 0 denotes the all-zero vector or matrix. The dimensions of I and 0 are determined by the context.
- |X|, X^T , X^{-1} and rank (X) denote respectively the determinant, transpose, inverse, and rank of the matrix **X**, and $||x||$ denotes the Euclidean vector norm of **x**, i.e., $||x||^2 = x^T x$.
- radius(X) is the numerical radius [38, p. 321] of the square real matrix X , and is defined as

radius(
$$
\mathbf{X}
$$
) = $\underset{\mathbf{C}^T \mathbf{C} \leq 1}{\max} \text{ abs} (\mathbf{\alpha}^T \mathbf{X} \mathbf{\alpha}),$

where α is a vector, and abs(\cdot) denotes the absolute value.

- $\mathbf{x}^n = \begin{bmatrix} \mathbf{x}_1^T, \mathbf{x}_2^T, \dots, \mathbf{x}_n^T \end{bmatrix}^T$ is a long vector that consists of a sequence of vectors $\mathbf{x}_i, i = 1, \dots, n$. $diag[X_1, \dots, X_n]$ is a diagonal matrix with diagonal entries X_i .
- Vec (A) denote the vectorization operator, i.e., let $A = [a_1, a_2, \dots, a_n]$, and $a_i, i = 1, \dots, n$ be the column vectors, then Vec $(\mathbf{A}) = [\mathbf{a}_1^T, \mathbf{a}_2^T, \cdots, \mathbf{a}_n^T]^T$.
- $x \sim \mathcal{N}(0, \Sigma)$ means that the random vector x has Gaussian distribution with zero mean and covariance matrix Σ.
- E[·] denotes expectation; Cov(·) denotes covariance matrix; $I(\cdot;\cdot)$ denotes mutual information; $h(\cdot)$ denotes differential entropy with the logarithm base e , and $\log(\cdot) = \log_e(\cdot)$.

II. MIMO ICS

We first derive a lower bound and an upper bound on the sum-rate capacity. The lower bound is simply the single-user detection sum rate. The upper bound is obtained by providing the receivers with

6

appropriate side information. Both the lower and upper bounds are formulated as optimization problems in which the lower bound is a non-convex problem and the upper bound is a convex problem. The sumrate capacity is obtained by determining conditions under which these two optimization problems have the same solution.

A. Lower bound on the sum-rate capacity

By treating interference as noise, the maximum of the following optimization problem is a lower bound on the sum-rate capacity:

$$
\max \quad \frac{1}{2} \log \left| \mathbf{I} + \mathbf{H}_1 \mathbf{S}_1 \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \right| + \frac{1}{2} \log \left| \mathbf{I} + \mathbf{H}_2 \mathbf{S}_2 \mathbf{H}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1 \mathbf{F}_1^T \right)^{-1} \right|
$$
\nsubject to
$$
\text{tr}(\mathbf{S}_1) \le P_1, \quad \text{tr}(\mathbf{S}_2) \le P_2
$$
\n
$$
\mathbf{S}_1 \succeq \mathbf{0}, \quad \mathbf{S}_2 \succeq \mathbf{0}.
$$
\n(3)

The following lemma gives the necessary Karush-Kuhn-Tucker (KKT) conditions for the optimal input covariance matrices S_i^* , $i = 1, 2$.

Lemma 1: Let S_1^* and S_2^* be optimal for problem (3), if $P_1, P_2 > 0$, then there exist scalars λ_i and matrices W_i , $i = 1, 2$, such that

$$
\mathbf{G}_1 + \lambda_1 \mathbf{I} - \mathbf{W}_1 = \mathbf{0} \tag{4}
$$

$$
\mathbf{G}_2 + \lambda_2 \mathbf{I} - \mathbf{W}_2 = \mathbf{0} \tag{5}
$$

$$
\lambda_i \begin{cases}\n> 0 & \text{if } \operatorname{tr}(\mathbf{S}_i^*) = P_i \\
= 0 & \text{if } \operatorname{tr}(\mathbf{S}_i^*) < P_i\n\end{cases} \quad i = 1, 2
$$
\n
$$
(6)
$$

$$
\operatorname{tr}(\mathbf{S}_i^* \mathbf{W}_i) = 0, \quad \mathbf{W}_i \succeq \mathbf{0} \quad i = 1, 2 \tag{7}
$$

where

$$
\mathbf{G}_1 = -\left. \frac{\partial R_{1l}}{\partial \mathbf{S}_1} \right|_{\mathbf{S}_i = \mathbf{S}_i^*} - \left. \frac{\partial R_{2l}}{\partial \mathbf{S}_1} \right|_{\mathbf{S}_i = \mathbf{S}_i^*}
$$
(8)

$$
\mathbf{G}_2 = -\left. \frac{\partial R_{1l}}{\partial \mathbf{S}_2} \right|_{\mathbf{S}_i = \mathbf{S}_i^*} - \left. \frac{\partial R_{2l}}{\partial \mathbf{S}_2} \right|_{\mathbf{S}_i = \mathbf{S}_i^*}
$$
(9)

$$
\frac{\partial R_{1l}}{\partial \mathbf{S}_1}\bigg|_{\mathbf{S}_i=\mathbf{S}_i^*} = \frac{1}{2}\mathbf{H}_1^T \left(\mathbf{I} + \mathbf{H}_1 \mathbf{S}_1^* \mathbf{H}_1^T + \mathbf{F}_2 \mathbf{S}_2^* \mathbf{F}_2^T\right)^{-1} \mathbf{H}_1
$$
\n(10)

$$
\frac{\partial R_{1l}}{\partial \mathbf{S}_2}\bigg|_{\mathbf{S}_i=\mathbf{S}_i^*} = -\frac{1}{2}\mathbf{F}_2^T \left[\left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2^* \mathbf{F}_2^T \right)^{-1} - \left(\mathbf{I} + \mathbf{H}_1 \mathbf{S}_1^* \mathbf{H}_1^T + \mathbf{F}_2 \mathbf{S}_2^* \mathbf{F}_2^T \right)^{-1} \right] \mathbf{F}_2 \tag{11}
$$

$$
\frac{\partial R_{2l}}{\partial \mathbf{S}}\bigg|_{\mathbf{S}_1=\mathbf{S}_i^*} = -\frac{1}{2}\mathbf{F}_1^T \left[\left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} - \left(\mathbf{I} + \mathbf{H}_2 \mathbf{S}_2^* \mathbf{H}_2^T + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} \right] \mathbf{F}_1 \tag{12}
$$

$$
\frac{\partial R_{2l}}{\partial \mathbf{S}_2}\bigg|_{\mathbf{S}_i=\mathbf{S}_i^*} = \frac{1}{2}\mathbf{H}_2^T \left(\mathbf{I} + \mathbf{H}_2 \mathbf{S}_2^* \mathbf{H}_2^T + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T\right)^{-1} \mathbf{H}_2
$$
\n(13)

and

$$
R_{1l}(\mathbf{S}_1, \mathbf{S}_2) = \frac{1}{2} \log \left| \mathbf{I} + \mathbf{H}_1 \mathbf{S}_1 \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \right|
$$
(14)

$$
R_{2l}(\mathbf{S}_1, \mathbf{S}_2) = \frac{1}{2} \log \left| \mathbf{I} + \mathbf{H}_2 \mathbf{S}_2 \mathbf{H}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1 \mathbf{F}_1^T \right)^{-1} \right|.
$$
 (15)

Proof: Conditions (4)-(7) are the KKT conditions for problem (3). Here, we only need to prove that problem (3) satisfies some constraint qualifications denoted by CQ5 in [39, p. 306] such that λ_i and \mathbf{W}_i do exist. The rest of the proof is included in Appendix A. \blacksquare

B. Upper bound on the sum-rate capacity

The following is an upper bound on the sum-rate capacity of a MIMO IC.

Theorem 1: The sum-rate capacity of the MIMO IC is upper bounded by the maximum achieved in the following optimization problem:

$$
\max \quad \frac{1}{2} \log \left| \mathbf{I} + \begin{bmatrix} \mathbf{H}_1 \\ \mathbf{F}_1 \end{bmatrix} \mathbf{S}_1 \begin{bmatrix} \mathbf{H}_1 \\ \mathbf{F}_1 \end{bmatrix}^T \left(\mathbf{E}_1 + \begin{bmatrix} \mathbf{F}_2 \\ \mathbf{0} \end{bmatrix} \mathbf{S}_2 \begin{bmatrix} \mathbf{F}_2 \\ \mathbf{0} \end{bmatrix}^T \right)^{-1} \right|
$$
\n
$$
+ \frac{1}{2} \log \left| \mathbf{I} + \begin{bmatrix} \mathbf{H}_2 \\ \mathbf{F}_2 \end{bmatrix} \mathbf{S}_2 \begin{bmatrix} \mathbf{H}_2 \\ \mathbf{F}_2 \end{bmatrix}^T \left(\mathbf{E}_2 + \begin{bmatrix} \mathbf{F}_1 \\ \mathbf{0} \end{bmatrix} \mathbf{S}_1 \begin{bmatrix} \mathbf{F}_1 \\ \mathbf{0} \end{bmatrix}^T \right)^{-1} \right|
$$
\nsubject to $\text{tr}(\mathbf{S}_1) \le P_1$, $\text{tr}(\mathbf{S}_2) \le P_2$
\n $\mathbf{S}_1 \ge \mathbf{0}$, $\mathbf{S}_2 \ge \mathbf{0}$ \n(16)

where \mathbf{E}_i , $i = 1, 2$, can be any symmetric positive definite matrix satisfying

$$
\mathbf{E}_{i} = \begin{bmatrix} \mathbf{I} & \mathbf{A}_{i} \\ \mathbf{A}_{i}^{T} & \mathbf{\Sigma}_{i} \end{bmatrix} \succ \mathbf{0}
$$
 (17)

$$
\Sigma_1 \preceq \mathbf{I} - \mathbf{A}_2 \Sigma_2^{-1} \mathbf{A}_2^T \tag{18}
$$

$$
\Sigma_2 \preceq \mathbf{I} - \mathbf{A}_1 \Sigma_1^{-1} \mathbf{A}_1^T. \tag{19}
$$

Proof: Let \mathbf{n}_i^n , $i = 1, 2$, be a length-n sequence of independent and identically distributed (i.i.d.) Gaussian vectors, each having joint distribution with z_i given by

$$
\begin{bmatrix} \mathbf{z}_i \\ \mathbf{n}_i \end{bmatrix} \sim \mathcal{N}(\mathbf{0}, \mathbf{E}_i) = \mathcal{N} \left(\mathbf{0}, \begin{bmatrix} \mathbf{I} & \mathbf{A}_i \\ \mathbf{A}_i^T & \mathbf{\Sigma}_i \end{bmatrix} \right).
$$
 (20)

Let x_i^n be the input sequence of user i, and

$$
\sum_{j=1}^{n} \text{Cov}(\boldsymbol{x}_{ij}) = n\mathbf{S}_{i}
$$
\n(21)

$$
\text{tr}\left(\mathbf{S}_{i}\right) \leq P_{i} \tag{22}
$$

Let $\epsilon > 0$ and $\epsilon \to 0$ when $n \to \infty$. Then for any achievable rate R_1 and R_2 , we have

$$
n(R_1 + R_2) - n\epsilon
$$
\n
$$
\leq I(\mathbf{x}_1^n; \mathbf{H}_1 \mathbf{x}_1^n + \mathbf{F}_2 \mathbf{x}_2^n + \mathbf{z}_1^n) + I(\mathbf{x}_2^n; \mathbf{H}_2 \mathbf{x}_2^n + \mathbf{F}_1 \mathbf{x}_1^n + \mathbf{z}_2^n)
$$
\n
$$
\leq I(\mathbf{x}_1^n; \mathbf{H}_1 \mathbf{x}_1^n + \mathbf{F}_2 \mathbf{x}_2^n + \mathbf{z}_1^n, \mathbf{F}_1 \mathbf{x}_1^n + \mathbf{n}_1^n) + I(\mathbf{x}_2^n; \mathbf{H}_2 \mathbf{x}_2^n + \mathbf{F}_1 \mathbf{x}_1^n + \mathbf{z}_2^n, \mathbf{F}_2 \mathbf{x}_2^n + \mathbf{n}_2^n)
$$
\n
$$
= h(\mathbf{F}_1 \mathbf{x}_1^n + \mathbf{n}_1^n) - h(n_1^n) + h(\mathbf{H}_1 \mathbf{x}_1^n + \mathbf{F}_2 \mathbf{x}_2^n + \mathbf{z}_1^n | \mathbf{F}_1 \mathbf{x}_1^n + \mathbf{n}_1^n) - h(\mathbf{F}_2 \mathbf{x}_2^n + \mathbf{z}_1^n | \mathbf{n}_1^n)
$$
\n
$$
+ h(\mathbf{F}_2 \mathbf{x}_2^n + \mathbf{n}_2^n) - h(n_2^n) + h(\mathbf{H}_2 \mathbf{x}_2^n + \mathbf{F}_1 \mathbf{x}_1^n + \mathbf{z}_2^n | \mathbf{F}_2 \mathbf{x}_2^n + \mathbf{n}_2^n) - h(\mathbf{F}_1 \mathbf{x}_1^n + \mathbf{z}_2^n | \mathbf{n}_2^n)
$$
\n
$$
\leq h(\mathbf{F}_1 \mathbf{x}_1^n + \mathbf{n}_1^n) - nh(n_1) + nh(\mathbf{H}_1 \mathbf{x}_{1G} + \mathbf{F}_2 \mathbf{x}_{2G} + \mathbf{z}_1 | \mathbf{F}_1 \mathbf{x}_{1G} + \mathbf{n}_1) - h(\mathbf{F}_2 \mathbf{x}_2^n + \mathbf{z}_1^n | \mathbf{n}_1^n)
$$
\n
$$
+ h(\mathbf{F}_2 \mathbf{x}_2^n + \mathbf{n}_2^n) - nh(n_2) + nh(\mathbf{H}_2 \mathbf{x}_{2G} + \mathbf{F}_1
$$

where in (a) we define $x_{iG} \sim N(0, S_i)$ and the inequality is by [31, Lemma 2], and (b) is by (18), (19) and [31, Lemma 3].

The following lemma establishes the convexity of the optimization problem (16) and the proof is included in Appendix B.

Lemma 2: The optimization problem (16) is a convex optimization problem.

Theorem 1 is derived using the same method that has been used in [31]. The maximum achieved in problem (16) for any choice of A_i and Σ_i that satisfy (17)-(19) is an upper bound on the sum-rate capacity of this MIMO IC regardless of whether it has noisy interference or not.

C. Sum-rate capacity

When the MIMO IC has noisy interference, we can choose appropriate A_i and Σ_i such that the lower and upper bounds converge. Before proceeding, we first introduce the following matrix identity which will be used repeatedly in the proof of our main result.

Г

9

Lemma 3: Assuming all the matrices have feasible dimension and the relevant matrices are invertible, we have

$$
\begin{bmatrix} A_{11} & A_{12} \ A_{21} & A_{22} \end{bmatrix}^{-1} = \begin{bmatrix} A_{11}^{-1} & 0 \ 0 & 0 \end{bmatrix} + \begin{bmatrix} A_{11}^{-1}A_{12} \ -I \end{bmatrix} (A_{22} - A_{21}A_{11}^{-1}A_{12})^{-1} [A_{21}A_{11}^{-1} - I]. \quad (25)
$$

Proof:

$$
\begin{bmatrix}\n\mathbf{A}_{11} & \mathbf{A}_{12} \\
\mathbf{A}_{21} & \mathbf{A}_{22}\n\end{bmatrix}^{-1} \\
\underline{\begin{bmatrix}\n(\mathbf{A}_{11} - \mathbf{A}_{12}\mathbf{A}_{22}^{-1}\mathbf{A}_{21})^{-1} & -\mathbf{A}_{11}^{-1}\mathbf{A}_{12}(\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1} \\
-(\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1}\mathbf{A}_{21}\mathbf{A}_{11}^{-1} & (\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1}\n\end{bmatrix}}_{\underline{\begin{bmatrix}\n\underline{\mathbf{b}} \\
\underline{\mathbf{b}} \\
-\begin{bmatrix}\n\mathbf{A}_{11}^{-1} + \mathbf{A}_{11}^{-1}\mathbf{A}_{12}(\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1} & \mathbf{A}_{21}\mathbf{A}_{11}^{-1} & -\mathbf{A}_{11}^{-1}\mathbf{A}_{12}(\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1} \\
-(\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1}\mathbf{A}_{21}\mathbf{A}_{11}^{-1} & (\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1}\n\end{bmatrix}}_{\underline{\begin{bmatrix}\n\mathbf{a}_{11}^{-1} & \mathbf{0} \\
\mathbf{0} & \mathbf{0}\n\end{bmatrix}} + \begin{bmatrix}\n\mathbf{A}_{11}^{-1}\mathbf{A}_{12} \\
-\mathbf{I}\n\end{bmatrix}\n(\mathbf{A}_{22} - \mathbf{A}_{21}\mathbf{A}_{11}^{-1}\mathbf{A}_{12})^{-1}\n[\mathbf{A}_{21}\mathbf{A}_{11}^{-1} - \mathbf{I}].
$$

where (a) is by the block matrix inversion lemma [38, p. 18], and (b) is by the Woodbury matrix identity [38, p. 19]:

$$
(\mathbf{C} + \mathbf{U}\mathbf{B}\mathbf{V})^{-1} = \mathbf{C}^{-1} - \mathbf{C}^{-1}\mathbf{U} (\mathbf{B}^{-1} + \mathbf{V}\mathbf{C}^{-1}\mathbf{U})^{-1} \mathbf{V}\mathbf{C}^{-1}.
$$
 (26)

The noisy-interference sum-rate capacity of a MIMO IC is obtained in the following theorem:

Theorem 2: For the MIMO IC defined in (1) and $P_i > 0, i = 1, 2$, if the optimal solution of problem (3) has tr(S_i^*) > 0, and there exist matrices A_i and Σ_i that satisfy (17)-(19) and

$$
\mathbf{S}_1^* \mathbf{F}_1^T = \mathbf{S}_1^* \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2^* \mathbf{F}_2^T \right)^{-1} \mathbf{A}_1 \tag{27}
$$

$$
\mathbf{S}_2^* \mathbf{F}_2^T = \mathbf{S}_2^* \mathbf{H}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} \mathbf{A}_2 \tag{28}
$$

$$
\mathbf{W}_1 \succeq \mathbf{O}_1 \tag{29}
$$

$$
\mathbf{W}_2 \succeq \mathbf{O}_2 \tag{30}
$$

where

$$
\mathbf{W}_1 = \mathbf{G}_1 - \frac{\text{tr}(\mathbf{S}_1^* \mathbf{G}_1)}{P_1} \mathbf{I}
$$
 (31)

$$
\mathbf{W}_2 = \mathbf{G}_2 - \frac{\text{tr}\left(\mathbf{S}_2^* \mathbf{G}_2\right)}{P_2} \mathbf{I}
$$
\n(32)

September 27, 2018 DRAFT

 \blacksquare

$$
\mathbf{O}_{1} = \frac{1}{2} \left[\mathbf{A}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} - \mathbf{F}_{1} \right]^{T} \left[\mathbf{\Sigma}_{1} - \mathbf{A}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{A}_{1} \right]^{-1}
$$

.
$$
\left[\mathbf{A}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} - \mathbf{F}_{1} \right]
$$
(33)

$$
\mathbf{O}_2 = \frac{1}{2} \left[\mathbf{A}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} \mathbf{H}_2 - \mathbf{F}_2 \right]^T \left[\mathbf{\Sigma}_2 - \mathbf{A}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} \mathbf{A}_2 \right]^{-1} \cdot \left[\mathbf{A}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} \mathbf{H}_2 - \mathbf{F}_2 \right]
$$
\n(34)

and G_1 and G_2 are defined in (8) and (9), respectively, then the sum-rate capacity is the maximum in problem (3) and is achieved by Gaussian input $x_i^* \sim \mathcal{N}(0, S_i^*)$ and treating interference as noise.

Proof: It suffices to show that under conditions (17)-(19) and (27)-(30), the upper bound on the sumrate capacity, i.e., the maximum in problem (16) for the given A_i and Σ_i , is the same as the maximum in problem (3); and the maximum in (16) is also achieved by S_i^* .

The proof has two stages. In stage one, we rewrite the objective function of problem (16) and show that this objective function, by choosing $S_i = S_i^*$, equals the maximum achieved in problem (3). In stage two, we compare the KKT conditions of problems (3) and (16), and show that if the conditions in this theorem are all satisfied, then problem (16) is solved by the same S_i^* that maximizes (3).

Define

$$
R_{1u}(\mathbf{S}_1, \mathbf{S}_2) = \frac{1}{2} \log \left| \mathbf{I} + \begin{bmatrix} \mathbf{H}_1 \\ \mathbf{F}_1 \end{bmatrix} \mathbf{S}_1 \begin{bmatrix} \mathbf{H}_1 \\ \mathbf{F}_1 \end{bmatrix}^T \left(\mathbf{E}_1 + \begin{bmatrix} \mathbf{F}_2 \\ \mathbf{0} \end{bmatrix} \mathbf{S}_2 \begin{bmatrix} \mathbf{F}_2 \\ \mathbf{0} \end{bmatrix}^T \right)^{-1} \right|
$$
(35)

$$
R_{2u}(\mathbf{S}_1, \mathbf{S}_2) = \frac{1}{2} \log \left| \mathbf{I} + \begin{bmatrix} \mathbf{H}_2 \\ \mathbf{F}_2 \end{bmatrix} \mathbf{S}_2 \begin{bmatrix} \mathbf{H}_2 \\ \mathbf{F}_2 \end{bmatrix}^T \left(\mathbf{E}_2 + \begin{bmatrix} \mathbf{F}_1 \\ \mathbf{0} \end{bmatrix} \mathbf{S}_1 \begin{bmatrix} \mathbf{F}_1 \\ \mathbf{0} \end{bmatrix}^T \right)^{-1} \right|.
$$
 (36)

Before proceeding, we first show the following equality since it will be used repeatedly in the sequel:

$$
\begin{aligned}\n\begin{bmatrix}\n\mathbf{H}_{i} \\
\mathbf{F}_{i}\n\end{bmatrix}^{T}\n\begin{bmatrix}\n\mathbf{E}_{i} + \begin{bmatrix}\n\mathbf{F}_{j} \\
\mathbf{0}\n\end{bmatrix}\n\mathbf{S}_{j}\n\begin{bmatrix}\n\mathbf{F}_{j} \\
\mathbf{0}\n\end{bmatrix}^{T}\n\end{aligned}\n\begin{bmatrix}\n\mathbf{H}_{i} \\
\mathbf{F}_{i}\n\end{bmatrix} \\
= \begin{bmatrix}\n\mathbf{H}_{i} \\
\mathbf{F}_{i}\n\end{bmatrix}^{T}\n\begin{bmatrix}\n\mathbf{I} + \mathbf{F}_{j}\mathbf{S}_{j}\mathbf{F}_{j}^{T} & \mathbf{A}_{i} \\
\mathbf{A}_{i}^{T} & \mathbf{\Sigma}_{i}\n\end{bmatrix}^{-1}\n\begin{bmatrix}\n\mathbf{H}_{i} \\
\mathbf{F}_{i}\n\end{bmatrix} \\
\stackrel{(a)}{=} \begin{bmatrix}\n\mathbf{H}_{i} \\
\mathbf{F}_{i}\n\end{bmatrix}^{T}\n\begin{bmatrix}\n\left(\begin{bmatrix}\n(\mathbf{I} + \mathbf{F}_{j}\mathbf{S}_{j}\mathbf{F}_{j}^{T})^{-1} & \mathbf{0} \\
\mathbf{0} & \mathbf{0}\n\end{bmatrix} + \begin{bmatrix}\n(\mathbf{I} + \mathbf{F}_{j}\mathbf{S}_{j}\mathbf{F}_{j}^{T})^{-1}\mathbf{A}_{1} \\
-\mathbf{I}\n\end{bmatrix} \\
\cdot \begin{bmatrix}\n\mathbf{\Sigma}_{i} - \mathbf{A}_{i}^{T}(\mathbf{I} + \mathbf{F}_{j}\mathbf{S}_{j}\mathbf{F}_{j}^{T})^{-1}\mathbf{A}_{i}\n\end{bmatrix}^{-1}\n\begin{bmatrix}\n\mathbf{A}_{1}^{T}(\mathbf{I} + \mathbf{F}_{j}\mathbf{S}_{j}\mathbf{F}_{j}^{T})^{-1} & -\mathbf{I}\n\end{bmatrix}\n\end{aligned}
$$

$$
= \mathbf{H}_{i}^{T} \left(\mathbf{I} + \mathbf{F}_{j} \mathbf{S}_{j} \mathbf{F}_{j}^{T} \right)^{-1} \mathbf{H}_{i} + \left[\mathbf{A}_{i}^{T} \left(\mathbf{I} + \mathbf{F}_{j} \mathbf{S}_{j} \mathbf{F}_{j}^{T} \right)^{-1} \mathbf{H}_{i} - \mathbf{F}_{i} \right]^{T}
$$

$$
\cdot \left[\mathbf{\Sigma}_{i} - \mathbf{A}_{i}^{T} \left(\mathbf{I} + \mathbf{F}_{j} \mathbf{S}_{j} \mathbf{F}_{j}^{T} \right)^{-1} \mathbf{A}_{i} \right]^{-1} \left[\mathbf{A}_{i}^{T} \left(\mathbf{I} + \mathbf{F}_{j} \mathbf{S}_{j} \mathbf{F}_{j}^{T} \right)^{-1} \mathbf{H}_{i} - \mathbf{F}_{i} \right]
$$

$$
= \mathbf{H}_{i}^{T} \left(\mathbf{I} + \mathbf{F}_{j} \mathbf{S}_{j} \mathbf{F}_{j}^{T} \right)^{-1} \mathbf{H}_{i} + 2 \overline{\mathbf{O}}_{i}
$$
(37)

where (a) is by Lemma 3, $i, j \in \{1, 2\}$, and $i \neq j$, and we define \overline{O}_i in the same way as in (33) and (34) by replacing S_i^* with S_i .

We first show $R_{il}(\mathbf{S}_1^*, \mathbf{S}_2^*) = R_{iu}(\mathbf{S}_1^*, \mathbf{S}_2^*)$:

$$
R_{1u}(\mathbf{S}_1, \mathbf{S}_2)
$$
\n
$$
\stackrel{(a)}{=} \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_1 \left[\mathbf{H}_1 \right]^T \left(\mathbf{E}_1 + \left[\mathbf{F}_2 \right] \mathbf{S}_2 \left[\mathbf{F}_2 \right]^T \right)^{-1} \left[\mathbf{H}_1 \right]
$$
\n
$$
\stackrel{(b)}{=} \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_1 \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \mathbf{H}_1 + 2 \mathbf{S}_1 \overline{\mathbf{O}}_1 \right|
$$
\n(38)

where (a) is by the matrix identity

$$
|\mathbf{I} + \mathbf{CD}| = |\mathbf{I} + \mathbf{DC}| \tag{39}
$$

and (b) is from (37). Similarly, we have

$$
R_{2u}(\mathbf{S}_1, \mathbf{S}_2) = \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_2 \mathbf{H}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1 \mathbf{F}_1^T \right)^{-1} \mathbf{H}_2 + 2 \mathbf{S}_2 \overline{\mathbf{O}}_2 \right|.
$$
 (40)

Since (27) and (28) imply

$$
\mathbf{S}_i^* \mathbf{O}_i = \mathbf{0} \tag{41}
$$

then we immediately have

$$
R_{1u}(\mathbf{S}_{1}^{*}, \mathbf{S}_{2}^{*}) = \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} \right|
$$

\n
$$
= \frac{1}{2} \log \left| \mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \right|
$$

\n
$$
= R_{1l}(\mathbf{S}_{1}^{*}, \mathbf{S}_{2}^{*})
$$
(42)

where the second equality is by (39). Similarly, we have

$$
R_{2u}(\mathbf{S}_1^*, \mathbf{S}_2^*) = R_{2l}(\mathbf{S}_1^*, \mathbf{S}_2^*)\,. \tag{43}
$$

Next, we prove that the maximum in problem (16) is achieved when $S_i = S_i^*$. Since by Lemma 2, problem (16) is a convex optimization problem, it suffices to prove that there exist Lagrangian multipliers $\overline{\lambda}_i$ and $\overline{\mathbf{W}}_i$ such that the following KKT conditions are satisfied:

$$
-\left.\frac{\partial R_{1u}}{\partial \mathbf{S}_1}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} - \left.\frac{\partial R_{2u}}{\partial \mathbf{S}_1}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} + \overline{\lambda}_1 \mathbf{I} - \overline{\mathbf{W}}_1 = 0\tag{44}
$$

$$
-\left.\frac{\partial R_{1u}}{\partial \mathbf{S}_2}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} - \left.\frac{\partial R_{2u}}{\partial \mathbf{S}_2}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} + \overline{\lambda}_2 \mathbf{I} - \overline{\mathbf{W}}_2 = 0\tag{45}
$$

$$
\overline{\lambda}_i \begin{cases}\n>0 & \text{if } \operatorname{tr}(\mathbf{S}_i^*) = P_i \\
=0 & \text{if } \operatorname{tr}(\mathbf{S}_i^*) < P_i\n\end{cases}\n\tag{46}
$$

$$
\operatorname{tr}\left(\mathbf{S}_i^*\overline{\mathbf{W}}_i\right) = 0, \quad \overline{\mathbf{W}}_i \succeq \mathbf{0}.\tag{47}
$$

We first compute

$$
\begin{split} &-\frac{\partial R_{1u}}{\partial s_{1}}\bigg|_{s_{1}=s_{1}^{*}}\\ &\stackrel{(a)}{=} -\frac{1}{2}\frac{\partial}{\partial s_{1}}\left(\log\left|{\bf I}+s_{1}\left[\frac{{\bf H}_{1}}{\bf F}_{1}\right]^{T}\left({\bf E}_{1}+\left[\frac{{\bf F}_{2}}{\bf 0}\right]{\bf S}_{2}\left[\frac{{\bf F}_{2}}{\bf 0}\right]^{T}\right)^{-1}\left[{\bf H}_{1}\right]\right]\bigg|_{s_{1}=s_{1}^{*}}\\ &=-\frac{1}{2}\left[\frac{{\bf H}_{1}}{\bf F}_{1}\right]^{T}\left({\bf E}_{1}+\left[\frac{{\bf F}_{2}}{\bf 0}\right]{\bf S}_{2}^{*}\left[\frac{{\bf F}_{2}}{\bf 0}\right]^{T}\right)^{-1}\left[{\bf H}_{1}\right]\\ &\qquad\cdot\left({\bf I}+{\bf S}_{1}^{*}\left[\frac{{\bf H}_{1}}{\bf F}_{1}\right]^{T}\left({\bf E}_{1}+\left[\frac{{\bf F}_{2}}{\bf 0}\right]{\bf S}_{2}^{*}\left[\frac{{\bf F}_{2}}{\bf 0}\right]^{T}\right)^{-1}\left[{\bf H}_{1}\right]\right)^{-1}\\ &\stackrel{(b)}{=} -\frac{1}{2}\left[\frac{{\bf H}_{1}}{\bf F}_{1}\right]^{T}\left[{\bf I}+{\bf F}_{2}{\bf S}_{2}^{*}{\bf F}_{2}^{T}\left.\begin{array}{c} {\bf A}_{1}\right]^{-1}\left[{\bf H}_{1}\right] \left({\bf I}+{\bf S}_{1}^{*}\left({\bf H}_{1}^{T}\left({\bf I}+{\bf F}_{2}{\bf S}_{2}^{*}{\bf F}_{2}^{T}\right)^{-1}{\bf H}_{1}+2{\bf O}_{1}\right)\right)\\ &\stackrel{(c)}{=} -\frac{1}{2}\left[\frac{{\bf H}_{1}}{\bf F}_{1}\right]^{T}\left[{\bf I}+{\bf F}_{2}{\bf S}_{2}^{*}{\bf F}_{2}^{T}\left.\begin{array}{c} {\bf A}_{1}\right]^{-1}\left[{\bf H}_{1}\right] \left({\bf I}+{\bf S}_{1}^{*}{\bf H}_{1}^{T}\left({\bf I}+{\bf F}_{2}{\bf S}_{2}^{*}{\bf F}_{2}^{T}\right)^{-1}{\bf H}_{1}\right)^{-1}\\ &\
$$

September 27, 2018 DRAFT

12

$$
= -\frac{1}{2} \frac{\partial}{\partial \mathbf{S}_1} \left[\log \left(\mathbf{I} + \mathbf{H}_1 \mathbf{S}_1 \mathbf{H}_1^T + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right) - \log \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right) \right] \Big|_{\mathbf{S}_i = \mathbf{S}_i^*} - \mathbf{O}_1
$$

=
$$
-\frac{\partial R_{1l}}{\partial \mathbf{S}_1} \Big|_{\mathbf{S}_i = \mathbf{S}_i^*} - \mathbf{O}_1
$$
(48)

where (a) is by the matrix identity (39), (b) and (d) are both by (37), (c) and (f) are both by (41), (e) is by the Woodbury matrix identity (26), and (g) is by the matrix identity [40, p. 151]:

$$
\mathbf{C} \left(\mathbf{I} + \mathbf{D} \mathbf{C} \right)^{-1} = \left(\mathbf{I} + \mathbf{C} \mathbf{D} \right)^{-1} \mathbf{C}.
$$
 (49)

Then we compute

$$
\begin{split} &-\frac{\partial R_{1u}}{\partial \mathbf{S}_{2}}\Bigg|_{\mathbf{S}_{1}=\mathbf{S}_{1}^{*}}\\ &=-\frac{1}{2}\frac{\partial}{\partial \mathbf{S}_{2}}\left(\log\left|\mathbf{E}_{1}+\left[\frac{\mathbf{H}_{1}}{\mathbf{F}_{1}}\right]\mathbf{S}_{1}\left[\frac{\mathbf{H}_{1}}{\mathbf{F}_{1}}\right]^{T}+\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]\mathbf{S}_{2}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\right|-\log\left|\mathbf{E}_{1}+\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]\mathbf{S}_{2}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\right)\Bigg|_{\mathbf{S}_{1}=\mathbf{S}_{1}^{*}}\\ &=-\frac{1}{2}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\left(\mathbf{E}_{1}+\left[\frac{\mathbf{H}_{1}}{\mathbf{F}_{1}}\right]\mathbf{S}_{1}^{*}\left[\frac{\mathbf{H}_{1}}{\mathbf{F}_{1}}\right]^{T}+\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]\mathbf{S}_{2}^{*}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\right)^{-1}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]\\ &+\frac{1}{2}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\left(\mathbf{E}_{1}+\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]\mathbf{S}_{2}^{*}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\right)^{-1}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]\\ &\overset{(a)}{=} \frac{1}{2}\left[\frac{\mathbf{F}_{2}}{\mathbf{0}}\right]^{T}\left[\mathbf{I}+\mathbf{H}_{1}\mathbf{S}_{1}^{*}\mathbf{H}_{1}^{T}+\mathbf{F}_{2}\mathbf{S}_{2}^{*}\mathbf{F}_{2}^{T}-\mathbf{H}_{1}\mathbf{S}_{1}^{*}\mathbf{F}_{1}^{T}+\mathbf{A}_{1}\right]^{-1}\left[\frac{\mathbf{H}_{1}}{\mathbf{F}_{1}}\right]\mathbf{S}_{1}^{*}\left[\frac{\mathbf
$$

$$
\begin{split}\n&\stackrel{(d)}{=} \frac{1}{2} \left[\mathbf{F}_{2} \right]^{T} \left(\left[(\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T})^{-1} \mathbf{0} \right] + \left[(\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T})^{-1} (\mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{F}_{1}^{T} + \mathbf{A}_{1}) \right] \\
&\quad (\mathbf{F}_{1} \mathbf{S}_{1}^{*} \mathbf{F}_{1}^{T} + \Sigma_{1} - (\mathbf{F}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{A}_{1}^{T}) (\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T})^{-1} (\mathbf{F}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{A}_{1}^{T})^{T})^{-1} \\
&\quad \left[(\mathbf{F}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{A}_{1}^{T}) (\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T})^{-1} - \mathbf{I} \right] \right) \left[\begin{bmatrix} \mathbf{H}_{1} \\ \mathbf{F}_{1} \end{bmatrix} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} (\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T})^{-1} - \mathbf{I} \right] \\
&\quad \left[\mathbf{F}_{2} \right] \left[(\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \
$$

where both (a) and (f) are from the matrix identity

$$
C^{-1} - D^{-1} = C^{-1} (D - C) D^{-1},
$$
\n(51)

equality (b) and (d) are both from Lemma 3, (c) is directly from (27), and (e) is also from (27) which implies

$$
\begin{split}\n&\left(\left(\mathbf{F}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{A}_{1}^{T} \right) \left(\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} - \mathbf{F}_{1} \right) \mathbf{S}_{1}^{*} \\
&= \left(\mathbf{A}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} \mathbf{S}_{1} \mathbf{H}_{1}^{T} + \mathbf{A}_{1}^{T} \right) \left(\mathbf{I} + \mathbf{H}_{1} \mathbf{S}_{1}^{*} \mathbf{H}_{1}^{T} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} \mathbf{S}_{1}^{*} - \mathbf{F}_{1} \mathbf{S}_{1}^{*} \\
&= \mathbf{A}_{1}^{T} \left(\mathbf{I} + \mathbf{F}_{2} \mathbf{S}_{2}^{*} \mathbf{F}_{2}^{T} \right)^{-1} \mathbf{H}_{1} \mathbf{S}_{1}^{*} - \mathbf{F}_{1} \mathbf{S}_{1}^{*} \\
&= 0.\n\end{split} \tag{52}
$$

Similarly, we have

$$
-\left.\frac{\partial R_{2u}}{\partial \mathbf{S}_1}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} = -\left.\frac{\partial R_{2l}}{\partial \mathbf{S}_1}\right|_{\mathbf{S}_i=\mathbf{S}_i^*}
$$
(53)

15

$$
-\left.\frac{\partial R_{2u}}{\partial \mathbf{S}_2}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} = -\left.\frac{\partial R_{2l}}{\partial \mathbf{S}_2}\right|_{\mathbf{S}_i=\mathbf{S}_i^*} - \mathbf{O}_2. \tag{54}
$$

By (4) and (7) , we have

$$
\mathbf{S}_i^* \mathbf{G}_i + \lambda_i \mathbf{S}_i^* = 0. \tag{55}
$$

Thus, by (6) we have

$$
\lambda_i = -\frac{\text{tr}\left(\mathbf{S}_i^*\mathbf{G}_i\right)}{P_i},\tag{56}
$$

and hence from (4) and (5) we have

$$
\mathbf{W}_{i} = \mathbf{G}_{i} - \frac{\text{tr}\left(\mathbf{S}_{i}^{*}\mathbf{G}_{i}\right)}{P_{i}}\mathbf{I}
$$
\n
$$
(57)
$$

i.e., the W_i 's defined in (31) and (32) are the Lagrangian multipliers in (4) and (5).

Then, we choose

$$
\overline{\lambda}_i = \lambda_i \tag{58}
$$

$$
\overline{\mathbf{W}}_i = \mathbf{W}_i - \mathbf{O}_i \tag{59}
$$

such that

$$
-\frac{\partial R_{1u}}{\partial \mathbf{S}_{1}}\Big|_{\mathbf{S}_{i}=\mathbf{S}_{i}^{*}} - \frac{\partial R_{2u}}{\partial \mathbf{S}_{1}}\Big|_{\mathbf{S}_{i}=\mathbf{S}_{i}^{*}} + \overline{\lambda}_{1}\mathbf{I} - \overline{\mathbf{W}}_{1}
$$

= $-\frac{\partial R_{1l}}{\partial \mathbf{S}_{1}}\Big|_{\mathbf{S}_{i}=\mathbf{S}_{i}^{*}} - \mathbf{O}_{1} - \frac{\partial R_{2l}}{\partial \mathbf{S}_{1}}\Big|_{\mathbf{S}_{i}=\mathbf{S}_{i}^{*}} + \lambda_{1}\mathbf{I} - (\mathbf{W}_{1} - \mathbf{O}_{1})$
= $\mathbf{0}$ (60)

where the last equality is from (4). Therefore, condition (44) is satisfied. Similarly, condition (45) is also satisfied. Condition (46) is satisfied because of (6), and condition (47) is satisfied by the assumptions (29) and (30) and conditions (27) and (28) which imply

$$
\mathbf{S}_i^* \overline{\mathbf{W}}_i = \mathbf{S}_i^* (\mathbf{W}_i - \mathbf{O}_i) = -\mathbf{S}_i^* \mathbf{O}_i = \mathbf{0}
$$
 (61)

where in the second equality, we use the fact that $S_i^*W_i = 0$ when $tr(S_i^*W_i) = 0$ and $S_i^* \succeq 0$ and $W_i \succeq 0$. Therefore, there exist Lagrangian multipliers such that S_i^* satisfies the KKT conditions for problem (16). Since problem (16) is a convex optimization problem, S_i^* achieves the maximum in problem (16). By (42) and (43), we conclude that the maximum in (3) is the sum-rate capacity of the MIMO IC. \blacksquare

Remark 1: On comparing the upper bound function R_{ui} in (38) and (40) with the lower bound function in (14) and (15), respectively, we note that there is an extra term $2S_iO_i$ in the logarithm function. It

is obvious that $\overline{O}_i \succeq 0$ under conditions (18) and (19). Although $2S_i\overline{O}_i$ may not necessary be a semipositive definite matrix, this extra term still increases the rate upon R_{il} , e.g.,

$$
R_{1u} = \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_1 \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \mathbf{H}_1 + 2 \mathbf{S}_1 \overline{\mathbf{O}}_1 \right|
$$

\n
$$
= \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_1^{\frac{1}{2}} \left(\mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \mathbf{H}_1 + 2 \overline{\mathbf{O}}_1 \right) \mathbf{S}_1^{\frac{1}{2}} \right|
$$

\n
$$
\geq \frac{1}{2} \log \left| \mathbf{I} + \mathbf{S}_1^{\frac{1}{2}} \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \mathbf{H}_1 \mathbf{S}_1^{\frac{1}{2}} \right|
$$

\n
$$
= \frac{1}{2} \log \left| \mathbf{I} + \mathbf{H}_1 \mathbf{S}_1 \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2 \mathbf{F}_2^T \right)^{-1} \right|
$$

\n
$$
= R_{1l}.
$$

Conditions (27) and (28) are sufficient conditions for (41) to hold, which makes the lower and upper bounds converge. This extra term $2S_i\overline{O}_i$ is also considered in the scaler Gaussian IC [21, p. 696] and the parallel Gaussian IC [33, eq. (64)], in which we have $O_i = 0$ for both cases. Furthermore, conditions (27) and (28) also mean that [31, Lemma 5]

$$
\boldsymbol{x}_{iG}^* \rightarrow \mathbf{H}_i \boldsymbol{x}_{iG}^* + \mathbf{F}_j \boldsymbol{x}_{jG}^* + \boldsymbol{z}_i \rightarrow \mathbf{F}_i \boldsymbol{x}_{iG}^* + \boldsymbol{n}_i \quad i,j \in \{1,2\}, i \neq j
$$

form a Markov chain, where $\mathbf{x}_{iG}^* \sim \mathcal{N}(\mathbf{0}, \mathbf{S}_i^*)$.

Remark 2: When all the conditions in Theorem 2 are satisfied, the optimal input covariance matrix \mathbf{S}_i^* and the corresponding auxiliary matrix \mathbf{E}_i^* in (17) (obtained by replacing Σ_i and \mathbf{A}_i with Σ_i^* and A_i^* associated with S_i^*), form a saddle point of the upper bound function defined as

$$
R_{su}(\mathbf{S}_i, \mathbf{E}_i) = R_{1u}(\mathbf{S}_i, \mathbf{E}_i) + R_{2u}(\mathbf{S}_i, \mathbf{E}_i)
$$

where $R_{iu}(\mathbf{S}_i, \mathbf{E}_i)$ is defined in (38) and (40). We use this expression in this remark to emphasize that \mathbf{E}_i is also a parameter.

To show that this optimal solution is the saddle point, we first have

$$
\min_{\mathbf{E}_i} \max_{\text{tr}(\mathbf{S}_i) \leq P_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) \leq \max_{\text{tr}(\mathbf{S}_i) \leq P_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i^*) = R_{su}(\mathbf{S}_i^*, \mathbf{E}_i^*)
$$

where the second equality is by the existence of the Lagrangian multiplier satisfying the KKT conditions, and the convexity of $R_{su}(S_i, E_i^*)$ over S_i , which imply that $R_{su}(S_i, E_i^*)$ is maximized by S_i^* . On the other hand, we have

$$
\max_{\text{tr}(\mathbf{S}_i) \leq P_i} \min_{\mathbf{E}_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) \geq \min_{\mathbf{E}_i} R_{su}(\mathbf{S}_i^*, \mathbf{E}_i) = R_{su}(\mathbf{S}_i^*, \mathbf{E}_i^*)
$$

where the second inequality is by (41). Since the following is always true

$$
\min_{\mathbf{E}_i} \max_{\text{tr}(\mathbf{S}_i) \leq P_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) \geq \max_{\text{tr}(\mathbf{S}_i) \leq P_i} \min_{\mathbf{E}_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i)
$$

September 27, 2018 DRAFT

we have

$$
\min_{\mathbf{E}_i} \max_{\mathbf{tr}(\mathbf{S}_i) \leq P_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) = \max_{\mathbf{tr}(\mathbf{S}_i) \leq P_i} \min_{\mathbf{E}_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) = R_{su}(\mathbf{S}_i^*, \mathbf{E}_i^*).
$$

By [39, Proposition 2.6.1 p. 132], $(\mathbf{S}_i^*, \mathbf{E}_i^*)$ is the saddle point of $R_{su}(\mathbf{S}_i, \mathbf{E}_i)$.

Remark 3: Denote by \bar{S}_i the covariance matrix constraint in [31, Theorem 6] and denote by \bar{E}_i the corresponding auxiliary matrix consisting of \bar{A}_i and $\bar{\Sigma}_i$ for this \bar{S}_i that satisfy condition (17)-(19), (27) and (28). If all the conditions in [31, Theorem 6] are satisfied, i.e., for any $0 \leq S_i \leq \overline{S}_i$ there exist corresponding A_i and Σ_i such that (17)-(19), (27) and (28) are satisfied, then (\bar{S}_i, \bar{E}_i) is also a saddle point of the upper bound function according to the covariance matrix constraint. This can be shown in a similar way as the result in Remark 2. First, we have

$$
\max_{\substack{\mathbf{0} \preceq \mathbf{S}_i \preceq \bar{\mathbf{S}}_i}} \min_{\substack{\mathbf{E}_i}} R_{su}(\mathbf{S}_i, \mathbf{E}_i) = \max_{\substack{\mathbf{0} \preceq \mathbf{S}_i \preceq \bar{\mathbf{S}}_i}} R_{su}(\mathbf{S}_i, \mathbf{E}_i(\mathbf{S}_i)) = R_{su}(\bar{\mathbf{S}}_i, \bar{\mathbf{A}}_i)
$$

where the first equality is by the assumption of existence of A_i and Σ_i that satisfy condition (17)-(19), (27) and (28) for each feasible S_i , and we denote such auxiliary matrix E_i as $E_i(S_i)$. The second equality is by the fact that R_{su} is an increasing function of S_i . On the other hand, we have

$$
\min_{\mathbf{E}_i} \max_{\mathbf{S}_i \preceq \bar{\mathbf{S}}_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) = \min_{\mathbf{E}_i} R_{su}(\bar{\mathbf{S}}_i, \mathbf{E}_i) = R_{su}(\bar{\mathbf{S}}_i, \bar{\mathbf{E}}_i).
$$

Therefore, we also have

$$
\max_{\mathbf{S}_i \preceq \bar{\mathbf{S}}_i} \min_{\mathbf{E}_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i) = \min_{\mathbf{E}_i} \max_{\mathbf{S}_i \preceq \bar{\mathbf{S}}_i} R_{su}(\mathbf{S}_i, \mathbf{E}_i).
$$

By [39, Proposition 2.6.1 p. 132], (\bar{S}_i, \bar{E}_i) is also a saddle point for $R_{su}(S_i, E_i)$ according to the covariance matrix constraint. Therefore, [31, Theorem 6] parallels Theorem 2 in the covariance matrix constraint.

Remark 4: Theorem 2 includes [32, Theorem 1] as a special case. In [32, Theorem 1], it was shown that if the S_i^* is full rank and there exist A_i and Σ_i satisfying (17)-(18), (27) and (28), then this MIMO IC has noisy interference. In this case, (27) and (28) imply

$$
\mathbf{F}_i^T = \mathbf{H}_i^T \left(\mathbf{I} + \mathbf{F}_j \mathbf{S}_j^* \mathbf{F}_j^T \right)^{-1} \mathbf{A}_i, \quad i, j \in \{1, 2\}, i \neq j
$$

and thus

$$
\mathbf{O}_i=\mathbf{0}.
$$

Therefore, (29) and (30) are both satisfied since $W_i \succeq 0$ has been shown in Lemma 1.

Remark 5: Theorem 2 includes the noisy-interference sum-rate capacity result for the parallel IC in [33] as a special case. The parallel IC is a special MIMO IC with diagonal channel matrices H_i = diag $[h_{i1}, \dots, h_{it}]$ and $\mathbf{F}_i = \text{diag}[f_{i1}, \dots, f_{it}]$. We define the *i*th subchannel as that consisting of only the ith transmit and receive antennas. The lower bound in (3) for this channel, by choosing the diagonal input covariance matrix S_i can be written as

$$
\max \quad R_{sl}(\mathbf{S}_i) = \sum_{j=1}^t r_j \, (s_{1j}, s_{2j})
$$
\n
$$
\text{subject to} \quad \sum_{j=1}^t s_{ij} \le P_i, \quad s_{ij} \ge 0, \quad i = 1, 2. \tag{62}
$$

where

$$
r_j(s_{1j}, s_{2j}) = \frac{1}{2} \log \left(1 + \frac{h_{1j}^2 s_{1j}}{1 + f_{2j}^2 s_{2j}} \right) + \frac{1}{2} \log \left(1 + \frac{h_{2j}^2 s_{2j}}{1 + f_{1j}^2 s_{1j}} \right).
$$
 (63)

However, in [33] the lower bound on the sum-rate capacity is not formulated as above, but as

$$
\max \sum_{j=1}^{t} C_j (s_{1j}, s_{2j})
$$
\n
$$
\text{subject to } \sum_{j=1}^{t} s_{ij} \le P_i, \quad s_{ij} \ge 0, \quad i = 1, 2 \tag{64}
$$

where s_{ij} denotes the power allocated to the jth subchannel for user i, and C_j (s_{1j} , s_{2j}) denotes the sum-rate capacity of the jth subchannel under power constraint s_{ij} , i.e., power s_{ij} is allocated to the jth transmit antenna of user i. The upper bound on the sum-rate capacity is also formulated via optimization problem (16). However, if we choose the auxiliary matrices A_i and Σ_i as in [33, eqs.(41) and (42)], then the upper bound can be written as

$$
\max \quad R_{su}(\mathbf{S}_i) = \sum_{j=1}^t f_j \left(s_{1j}, s_{2j} \right)
$$
\n
$$
\text{subject to} \quad \text{tr}(\mathbf{S}_i) = \sum_{j=1}^t s_{ij} \le P_i, \quad s_{ij} \ge 0, \quad i = 1, 2. \tag{65}
$$

where $S_i = diag[s_{i1}, \dots, s_{i,t_i}]$ and $f_j(\cdot)$ is defined in [33, eq.(64)]. The auxiliary matrix E_i is the same in both upper bounds. Therefore, [33] uses exactly the same side information as that in Theorem 2. Moreover, [33] shows that the matrices A_i^* and Σ_i^* are both diagonal matrices (see E_i in [33, eqs. (41) and (42)]). Thus, the upper bound $R_{su}(\mathbf{S}_i)$ is the sum of the upper bound for each subchannel f_i .

It has been shown in [33] that if the power constraint P_i is in the set [33, eq. (18)], then by [33, Theorem 3] this parallel IC has noisy interference and the optimal input covariance matrix $S_i^* = diag[s_{i1}^*, \dots, s_{i,t_i}^*]$ has the properties [33, eqs.(18), (74) and (75)]

$$
\begin{bmatrix} \lambda_1 \\ \lambda_2 \end{bmatrix} \in \bigcap_{j=1}^t \partial C_j \left(s_{1j}^*, s_{2j}^* \right) \neq \text{empty}
$$
 (66)

$$
\frac{\partial f_j}{\partial s_{ij}}\left|_{s_{1j}=s_{1j}^*} = \frac{\partial C_j}{\partial s_{ij}}\right|_{s_{1j}=s_{1j}^*} = \frac{\partial r_j}{\partial s_{ij}}\left|_{s_{1j}=s_{1j}^*} = \frac{\partial r_j}{\partial s_{ij}}\right|_{s_{1j}=s_{1j}^*} \text{ for all } i=1,2, \quad j=1,\cdots,t \tag{67}
$$

where ∂C_j (s_{1j}^*, s_{2j}^*) is the subdifferential of C_j (s_{1j}, s_{2j}) at (s_{1j}^*, s_{2j}^*) , and $[\lambda_1, \lambda_2]^T$ is the common subgradient shared by all the subdifferentials. From the expression of ∂C_j (s_{1j}^*, s_{2j}^*) in [33, eq. (100)], we have

$$
\begin{bmatrix} \lambda_1 \\ \lambda_2 \end{bmatrix} = \begin{bmatrix} \left. \frac{\partial r_j}{\partial s_{1j}} \right|_{s_{ij} = s_{ij}^*} \\ \left. \frac{\partial r_j}{\partial s_{2j}} \right|_{s_{ij} = s_{ij}^*} \end{bmatrix} + \begin{bmatrix} w_{1j} \\ w_{2j} \end{bmatrix}, \quad i = 1, 2, \quad j = 1, \cdots, t
$$
 (68)

where w_{1j} and w_{2j} are nonnegative constants. Hence, we have

$$
\left. \frac{\partial R_{sl}}{\partial \mathbf{S}_i} \right|_{\mathbf{S}_1 = \mathbf{S}_1^*, \mathbf{S}_2 = \mathbf{S}_2^*} = \lambda_i \mathbf{I} + \mathbf{W}_i \tag{69}
$$

where $\mathbf{W}_i = \text{diag}[w_{i1}, \dots, w_{it}] \succeq 0$. By (67), we have

$$
\left. \frac{\partial R_{su}}{\partial \mathbf{S}_i} \right|_{\mathbf{S}_1 = \mathbf{S}_1^*, \mathbf{S}_2 = \mathbf{S}_2^*} = \left. \frac{\partial R_{sl}}{\partial \mathbf{S}_i} \right|_{\mathbf{S}_1 = \mathbf{S}_1^*, \mathbf{S}_2 = \mathbf{S}_2^*} = \lambda_i \mathbf{I} + \mathbf{W}_i \tag{70}
$$

which implies $O_i = 0$. Therefore, if a parallel IC satisfies the noisy-interference condition in [33], it also satisfies Theorem 2. The lower bound $\max R_{sl}$ and the upper bound $\max R_{su}$ are optimized at the same S_i^* with the same Lagrangian multipliers. The Lagrangian multipliers λ_i associated with the power constraint tr(S_i) $\leq P_i$ form the common subgradient of all the individual subchannel capacities C_j (as well as the individual lower bounds r_j) and upper bounds f_j , i.e., C_j (or r_j) and f_j have parallel supporting hyperplanes with the subgradient $[\lambda_1, \lambda_2]^T$ at the optimal power allocation point.

We note that to formulate the lower bound as in (64) is important for [33] since the problem is then a convex optimization problem. Furthermore, condition (67) directly guarantees the optimality of s_{ij}^* for (64), and only through which we show the optimality of s_{ij}^* for (62) [33].

Remark 6: Theorem 2 determines the noisy-interference sum-rate capacity for general MIMO ICs. When the MIMO IC reduces to a MISO or SIMO IC, the conditions in Theorem 2 can be simplified. We defer these results in Sections III and IV, respectively. In [32], noisy-interference sum-rate capacities of symmetric MISO and SIMO ICs are obtained, i.e., ICs with $H_1 = H_2$, $F_1 = F_2$, $P_1 = P_2$, and where all the H_i and F_i are column or row vectors. These two results are both included as special cases of Theorem 2. In Sections III and IV, the MISO and SIMO ICs can be symmetric and asymmetric.

Remark 7: Equations (27) and (28) are special cases of the Sylvester equation [41]. Once S_i^* is obtained, the matrix A_i can be obtained by solving the following linear equations:

$$
\mathbf{I} \otimes \left(\mathbf{S}_1^* \mathbf{H}_1^T \left(\mathbf{I} + \mathbf{F}_2 \mathbf{S}_2^* \mathbf{F}_2^T\right)^{-1}\right) \text{Vec}(\mathbf{A}_1) = \text{Vec}\left(\mathbf{S}_1^* \mathbf{F}_1^T\right)
$$

$$
\mathbf{I} \otimes \left(\mathbf{S}_2^* \mathbf{H}_2^T \left(\mathbf{I} + \mathbf{F}_1 \mathbf{S}_1^* \mathbf{F}_1^T \right)^{-1} \right) \text{Vec}(\mathbf{A}_2) = \text{Vec} \left(\mathbf{S}_2^* \mathbf{F}_2^T \right)
$$

where \otimes denotes the Kronecker product of matrices. Therefore, the existence of A_i can be determined by the theory of linear equations.

Remark 8: In Theorem 2 and its proof, we need to determine the existence of a positive definite Σ_i . Sometimes the expression for Σ_i is not important (e.g., the parallel Gaussian IC discussed in Remark 5, and the symmetric SIMO IC discussed later in Remark 14). If we choose equality in both (18) and (19), we obtain two matrix equations which are special cases of a discrete algebraic Ricatti equation [42]. The existence of a positive definite solution is determined by [31, Lemma 9] using [42], which requires, for both $i = 1$ and 2:

radius
$$
(\Phi_i) \le \frac{1}{2}
$$
 (71)

where

$$
\Phi_1 = \left(\mathbf{I} - \mathbf{A}_1^T \mathbf{A}_1 - \mathbf{A}_2 \mathbf{A}_2^T\right)^{-\frac{1}{2}} \mathbf{A}_1^T \mathbf{A}_2^T \left(\mathbf{I} - \mathbf{A}_1^T \mathbf{A}_1 - \mathbf{A}_2 \mathbf{A}_2^T\right)^{-\frac{1}{2}}
$$
(72)

$$
\Phi_2 = \left(\mathbf{I} - \mathbf{A}_1 \mathbf{A}_1^T - \mathbf{A}_2^T \mathbf{A}_2\right)^{-\frac{1}{2}} \mathbf{A}_2^T \mathbf{A}_1^T \left(\mathbf{I} - \mathbf{A}_1 \mathbf{A}_1^T - \mathbf{A}_2^T \mathbf{A}_2\right)^{-\frac{1}{2}}.
$$
\n(73)

Here we present a strengthened result of [31, Lemma 9] which requires (71) to be satisfied for only $i = 1$ or $i = 2$.

Lemma 4: For the following matrix equations for Σ_1 and Σ_2 :

$$
\Sigma_1 = \mathbf{I} - \mathbf{A}_2 \Sigma_2^{-1} \mathbf{A}_2^T
$$
 (74)

$$
\Sigma_2 = \mathbf{I} - \mathbf{A}_1 \Sigma_1^{-1} \mathbf{A}_1^T
$$
 (75)

if radius $(\mathbf{\Phi}_1) \leq \frac{1}{2}$ $\frac{1}{2}$ or radius(Φ_2) $\leq \frac{1}{2}$ where Φ_i is defined in (72) and (73), then there exist symmetric positive definite solutions for Σ_1 and Σ_2 . Moreover, the solutions for both $i = 1$ and 2 satisfy

$$
\Sigma_i \succ \mathbf{A}_i^T \mathbf{A}_i \tag{76}
$$

or equivalently

$$
\mathbf{E}_{i} = \begin{bmatrix} \mathbf{I} & \mathbf{A}_{i} \\ \mathbf{A}_{i}^{T} & \mathbf{\Sigma}_{i} \end{bmatrix} \succ \mathbf{0}.
$$
 (77)

The proof is included in Appendix C.

For completeness, we give the noisy-interference condition of MIMO ZIC in the following proposition.

Proposition 1: For the MIMO IC defined in (1) with $\mathbf{F}_1 = \mathbf{0}$ and $P_i > 0, i = 1, 2$, if the optimal solution of problem (3) has tr $(S_i^*) > 0$, and there exist matrices A_2 and Σ_2 that satisfy

$$
\mathbf{I} \succeq \mathbf{A}_2 \mathbf{A}_2^T
$$

$$
\mathbf{S}_2^* \mathbf{F}_2^T = \mathbf{S}_2^* \mathbf{H}_2^T \mathbf{A}_2
$$

$$
\mathbf{W}_2 \succeq \mathbf{O}_2
$$

where

$$
\mathbf{W}_2 = \mathbf{G}_2 - \frac{\text{tr}(\mathbf{S}_2^* \mathbf{G}_2)}{P_2} \mathbf{I}
$$

$$
\mathbf{O}_2 = \frac{1}{2} \left(\mathbf{A}_2^T \mathbf{H}_2 - \mathbf{F}_2 \right)^T \left(\mathbf{I} - \mathbf{A}_2^T \mathbf{A}_2 \right)^{-1} \left(\mathbf{A}_2^T \mathbf{H}_2 - \mathbf{F}_2 \right)
$$

and G_2 are defined in (9), then the sum-rate capacity is the maximum in problem (3) and is achieved by Gaussian input $\mathbf{x}_{i}^{*} \sim \mathcal{N}(0, \mathbf{S}_{i}^{*})$ and treating interference as noise.

Proof: The proof is straightforward from Theorem 2 by choosing $A_1 = 0$, $\Sigma_1 = I - A_2 A_2^T$ and $\Sigma_2 = I$. Condition (29) is automatically satisfied by $W_1 \succeq 0 = O_1$.

Remark 9: The aligned-weak interference condition in [31, Proposition 5] for the average power constraint is a special case of Proposition 1. The alignment weak interference means that if there exists a matrix A_2 with $A_2A_2^T \preceq I$ and $F_2 = A_2^T H_2$, then treating interference as noise achieves the sum-rate capacity. Obviously, in such a case, all the conditions in Proposition 1 are satisfied.

In Sections III and IV, we apply Theorem 2 to MISO and SIMO channels and simplify the noisyinterference conditions.

III. MISO ICS

In [32], it has been shown that the capacity of a two-user MISO IC is the same as that of a MISO IC with each transmitter having only two antennas. The main idea is to write the direct link channel vector as the sum of the interference channel vector and its orthogonal vector. The antenna reduction is also studied in [35] which shows that the single-user detection rate region of an m −user MISO IC with transmitter $i, 1 \le i \le m$, having t_i antennas, is the same as that of a MISO IC with transmitter i, having only $\min\{t_i, m\}$ antennas. The antenna reduction is performed systematically using [35, eqs.(45)-(47)] which can also be used to show the equivalence of the capacity regions between the original m -user MISO IC and the new m -user MISO IC after antenna reduction. In the following, we apply the method in [35] to the two-user MISO IC to show the reduction process. On letting $H_i = \hat{h}_i^T$ \sum_{i}^{T} and $\mathbf{F}_{i} = \hat{\boldsymbol{f}}_{i}^{T}$ i ,

 $i = 1, 2$, in (1), the received signals of a MISO IC are

$$
Y_1 = \hat{\boldsymbol{h}}_1^T \hat{\boldsymbol{x}}_1 + \hat{\boldsymbol{f}}_2^T \hat{\boldsymbol{x}}_2 + Z_1
$$

$$
Y_2 = \hat{\boldsymbol{h}}_2^T \hat{\boldsymbol{x}}_2 + \hat{\boldsymbol{f}}_1^T \hat{\boldsymbol{x}}_1 + Z_2
$$
 (78)

where h_i and f_i are $t_i \times 1$ column vectors and we write the transmitted signal as \hat{x}_i with power constraint \hat{P}_i . Define the singular value decomposition of f_i as

$$
\hat{\boldsymbol{f}}_{i} = \mathbf{U}_{i} \left[\left\| \hat{\boldsymbol{f}} \right\|, \mathbf{0} \right]^{T} \tag{79}
$$

where $U_i U_i^T = I$ and the dimension of the zero vector is $t_i - 1$. Then we have

$$
\mathbf{U}_{i}^{T}\hat{\boldsymbol{h}}_{i} \stackrel{(a)}{=} \begin{bmatrix} \left\| \hat{\boldsymbol{h}}_{i} \right\| \cos \theta_{i} \\ \mathbf{g}_{i} \end{bmatrix}
$$

$$
\stackrel{(b)}{=} \begin{bmatrix} 1 & \mathbf{0} \\ \mathbf{0} & \mathbf{V}_{i} \end{bmatrix} \begin{bmatrix} \left\| \hat{\boldsymbol{h}}_{i} \right\| \cos \theta_{i} \\ \left\| \hat{\boldsymbol{h}}_{i} \right\| \sin \theta_{i} \\ \mathbf{0} \end{bmatrix}
$$
(80)

where we define $\theta_i \triangleq \angle(\hat{\bm{h}}_i, \hat{\bm{f}}_i)$, and \bm{g}_i is a $(t_i - 1) \times 1$ vector. Equality (a) follows from the fact that the first row of \mathbf{U}_i^T is $\hat{\boldsymbol{f}}_i^T / ||\hat{\boldsymbol{f}}_i||$. Equality (b) is by the fact $||\boldsymbol{g}_i|| = ||\hat{\boldsymbol{h}}_i|| \sin \theta_i$ and the singular value decomposition

$$
\boldsymbol{g}_{i}=\mathbf{V}_{i}\left[\left\Vert \hat{\boldsymbol{h}}_{i}\right\Vert \sin\theta_{i},\mathbf{0}\right]^{T}
$$

where $V_i^T V_i = I$, and the dimension of the zero vector is $t_i - 2$.

Define

$$
\bar{x} \triangleq \mathbf{Q}_i \hat{x}_i \tag{81}
$$

where

$$
\mathbf{Q}_i = \begin{bmatrix} 1 & \mathbf{0} \\ \mathbf{0} & \mathbf{V}_i \end{bmatrix}^T \mathbf{U}_i^T.
$$
 (82)

It is obvious that $\mathbf{Q}^T \mathbf{Q} = \mathbf{I}$. Then the received signals of the MISO IC can be written as

$$
Y_1 = \begin{bmatrix} \|\hat{\boldsymbol{h}}_1 \| \cos \theta_1 \\ \|\hat{\boldsymbol{h}}_1 \| \sin \theta_1 \\ 0 \end{bmatrix}^T \bar{\boldsymbol{x}}_1 + \begin{bmatrix} \|\hat{\boldsymbol{f}}_2 \| \\ 0 \\ 0 \end{bmatrix}^T \bar{\boldsymbol{x}}_2 + \boldsymbol{z}_1
$$

$$
Y_2 = \begin{bmatrix} \|\hat{\boldsymbol{h}}_2\| \cos \theta_2 \\ \|\hat{\boldsymbol{h}}_2\| \sin \theta_2 \\ 0 \end{bmatrix}^T \bar{\boldsymbol{x}}_2 + \begin{bmatrix} \|\hat{\boldsymbol{f}}_1\| \\ 0 \\ 0 \end{bmatrix}^T \bar{\boldsymbol{x}}_1 + \boldsymbol{z}_2.
$$

By removing irrelevant dimensions, we write the MISO IC in the following standard form:

$$
Y_1 = \boldsymbol{h}_1^T \boldsymbol{x}_1 + \boldsymbol{f}_2^T \boldsymbol{x}_2 + Z_1
$$

$$
Y_2 = \boldsymbol{h}_2^T \boldsymbol{x}_2 + \boldsymbol{f}_1^T \boldsymbol{x}_1 + Z_2
$$
 (83)

where the dimension of all the vectors is 2, and the power constraint for user i is now P_i , and

$$
P_i = \hat{P}_i ||\hat{\boldsymbol{h}}_i||^2 \tag{84}
$$

$$
a_i = \frac{\|\hat{f}_i\|^2}{\|\hat{h}_i\|^2}
$$
 (85)

$$
\boldsymbol{f}_i = \begin{bmatrix} \sqrt{a_i} \\ 0 \end{bmatrix} \tag{86}
$$

$$
\boldsymbol{h}_i = \begin{bmatrix} \cos \theta_i \\ \sin \theta_i \end{bmatrix} . \tag{87}
$$

Consequently, if S_i is the input covariance matrix of user i for equivalent channel (83), the corresponding input covariance for the original channel is

$$
\hat{\mathbf{S}}_i = \frac{1}{\left\| \hat{\boldsymbol{h}}_i \right\|^2} \mathbf{Q}_i^T \begin{bmatrix} \mathbf{S}_i & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix} \mathbf{Q}_i.
$$
 (88)

With the antenna reduction, we have the following result.

Theorem 3: For the MISO IC defined in (78) and its equivalent channel (83) with $\cos \angle (\mathbf{h}_i, \mathbf{f}_i) \neq 0$, $f_i \neq 0$, $h_i \neq 0$, $i = 1, 2$, denote S_i^* as the optimal solution of problem (3) for the equivalent channel (83), if $S_i^* \neq 0$ and

$$
\sigma_i^2 \ge \bar{\sigma}_i^2, \quad i = 1, 2 \tag{89}
$$

$$
abs(A_1) + abs(A_2) \le 1
$$
\n(90)

where

$$
\sigma_1^2 = \frac{1}{2} \left[\left(1 + A_1^2 - A_2^2 \right) + \sqrt{\left(1 + A_1^2 - A_2^2 \right)^2 - 4A_1^2} \right] \tag{91}
$$

$$
\sigma_2^2 = \frac{1}{2} \left[\left(1 + A_2^2 - A_1^2 \right) + \sqrt{\left(1 + A_2^2 - A_1^2 \right)^2 - 4A_2^2} \right] \tag{92}
$$

$$
24 \\
$$

$$
\bar{\sigma}_1^2 = -\bm{f}_2^T \mathbf{S}_2^* \bm{f}_2 + \frac{\sqrt{a_2}}{\cos \theta_2} \left(1 + \bm{h}_2^T \mathbf{S}_2^* \bm{h}_2 + \bm{f}_1^T \mathbf{S}_1^* \bm{f}_1 \right) \frac{\bm{f}_2^T \mathbf{S}_2^* \bm{h}_2}{\bm{h}_2^T \mathbf{S}_2^* \bm{h}_2}
$$
(93)

$$
\bar{\sigma}_2^2 = -f_1^T \mathbf{S}_1^* f_1 + \frac{\sqrt{a_1}}{\cos \theta_1} \left(1 + \mathbf{h}_1^T \mathbf{S}_1^* \mathbf{h}_1 + f_2^T \mathbf{S}_2^* f_2 \right) \frac{f_1^T \mathbf{S}_1^* \mathbf{h}_1}{\mathbf{h}_1^T \mathbf{S}_1^* \mathbf{h}_1}
$$
(94)

$$
A_1 = \frac{f_1^T \mathbf{S}_1^* \mathbf{h}_1}{\mathbf{h}_1^T \mathbf{S}_1^* \mathbf{h}_1} \left(1 + f_2^T \mathbf{S}_2^* \mathbf{f}_2 \right)
$$
(95)

$$
A_2 = \frac{\boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{h}_2}{\boldsymbol{h}_2^T \mathbf{S}_2^* \boldsymbol{h}_2} \left(1 + \boldsymbol{f}_1^T \mathbf{S}_1^* \boldsymbol{f}_1 \right)
$$
(96)

then the sum-rate capacity is the maximum of problem (3) and is achieved by treating interference as noise.

Proof: We use Theorem 2 to prove the converse. We first consider the existence of A_i (i.e., $A_i = A_i$) in the MISO case) in (27) and (28) which require

$$
\mathbf{S}_1^* \boldsymbol{f}_1 = \mathbf{S}_1^* \boldsymbol{h}_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2 \right)^{-1} A_1 \tag{97}
$$

$$
\mathbf{S}_2^* \mathbf{f}_2 = \mathbf{S}_2^* \mathbf{h}_2 \left(1 + \mathbf{f}_1^T \mathbf{S}_1^* \mathbf{f}_1 \right)^{-1} A_2.
$$
 (98)

It has been shown in [35] that rank $(S_i^*) \leq 1$. With the assumption $tr(S_i^*) > 0$, we have

$$
rank\left(\mathbf{S}_{i}^{*}\right)=1.\tag{99}
$$

Then we can write

$$
\mathbf{S}_{i}^{*} = \gamma_{i} \gamma_{i}^{T} \tag{100}
$$

where γ is a 2 × 1 vector. We have

$$
\boldsymbol{\gamma}_1 \boldsymbol{\gamma}_1^T \boldsymbol{f}_1 = \boldsymbol{\gamma}_1 \boldsymbol{\gamma}_1^T \boldsymbol{h}_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2 \right)^{-1} A_1. \tag{101}
$$

Obviously, if $\gamma^T h_1 = 0$, then $\gamma^T f_1 = 0$ because otherwise transmitter 1 does not transmit anything to receiver 1 while still generating interference to receiver 2. In this case A_1 can choose any value. If $\boldsymbol{\gamma}^T \boldsymbol{h}_1 \neq 0$, we have

$$
A_1 = \frac{\gamma_1^T \boldsymbol{f}_1}{\gamma_1^T \boldsymbol{h}_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2\right)^{-1}}.
$$
\n(102)

Therefore, A_1 always exists. Similarly, we can show the existence of A_2 . Another expression of A_i in (95) and (96) is obtained by left-multiply (97) and (98) with h_1^T and h_2^T , respectively.

We then consider the existence of Σ_i (i.e., $\Sigma_i = \sigma_i^2$ in the MISO case) in (18) and (19). By choosing equality in both (18) and (19), we obtain σ_i^2 in (91) and (92). It can be shown that the existence of σ_i^2 , or equivalently, that (91) and (92) are feasible, is guaranteed by (90) (details can be found in [21, p. 696]).

It remains to consider whether conditions (29) and (30) are satisfied. In the following, we do not verify these two conditions directly from (31) or (32) . Instead, we use the equivalent conditions $(4)-(7)$ since we have additional information (99) for S_i^* .

From (7), the columns of W_i are all in the eigenvector space of S_i^* associated with its zero eigenvalue. Since rank $(\mathbf{S}_{i}^{*}) = 1$ and \mathbf{S}_{i}^{*} is a 2×2 matrix, the dimension of this eigenvector space is 1. By (97), the eigenvector is $A_1\left(1+\bm{f}_2^T\mathbf{S}_2^*\bm{f}_2\right)^{-1}\bm{h}_1-\bm{f}_1$. Therefore, there exist a constant $k\geq 0$ such that

$$
\mathbf{W}_1 = k \left(A_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2 \right)^{-1} \boldsymbol{h}_1 - \boldsymbol{f}_1 \right) \left(A_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2 \right)^{-1} \boldsymbol{h}_1 - \boldsymbol{f}_1 \right)^T.
$$
 (103)

On the other hand, from (4) we have

$$
\mathbf{W}_{1} = -\frac{\mathbf{h}_{1}\mathbf{h}_{1}^{T}}{2\left(1 + \mathbf{h}_{1}^{T}\mathbf{S}_{1}^{*}\mathbf{h}_{1} + \mathbf{f}_{2}^{T}\mathbf{S}_{2}^{*}\mathbf{f}_{2}\right)} + \frac{\mathbf{h}_{2}^{T}\mathbf{S}_{2}^{*}\mathbf{h}_{2} \cdot \mathbf{f}_{1}\mathbf{f}_{1}^{T}}{2\left(1 + \mathbf{f}_{1}^{T}\mathbf{S}_{1}^{*}\mathbf{f}_{1}\right)\left(1 + \mathbf{h}_{2}^{T}\mathbf{S}_{2}^{*}\mathbf{h}_{2} + \mathbf{f}_{1}^{T}\mathbf{S}_{1}^{*}\mathbf{f}_{1}\right)} + \lambda_{1}\mathbf{I}.
$$
 (104)

On comparing the element of W_1 on the first row and the second column in expression (103) and (104), we have

$$
k = \frac{-\cos\theta_1}{2\left(1 + \mathbf{h}_1^T \mathbf{S}_1^* \mathbf{h}_1 + \mathbf{f}_2^T \mathbf{S}_2^* \mathbf{f}_2\right)} \frac{\mathbf{f}_1^T \mathbf{S}_1^* \mathbf{h}_1}{\mathbf{h}_1^T \mathbf{S}_1^* \mathbf{h}_1} \left(\frac{\mathbf{f}_1^T \mathbf{S}_1^* \mathbf{h}_1}{\mathbf{h}_1^T \mathbf{S}_1^* \mathbf{h}_1} \cos\theta_1 - \sqrt{a_1}\right)}.
$$
(105)

From (33), we have

$$
O_1 = \frac{1}{2} \frac{\left(A_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2\right)^{-1} \boldsymbol{h}_1 - \boldsymbol{f}_1\right) \left(A_1 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2\right)^{-1} \boldsymbol{h}_1 - \boldsymbol{f}_1\right)^T}{\sigma_1^2 - \frac{A_1^2}{1 + \boldsymbol{f}_2 \mathbf{S}_2^* \boldsymbol{f}_2}}.
$$
(106)

Therefore, condition (29) requires

$$
k \ge \frac{1}{\sigma_1^2 - \frac{A_1^2}{1 + \bm{f}_2 \mathbf{S}_2^* \bm{f}_2}}
$$
(107)

which is equivalent to (89). Similarly, (89) guarantees that (30) is satisfied. Therefore, under conditions (89) and (90), all the requirements of Theorem 2 are satisfied, and the MISO IC has noisy interference.

Remark 10: Consider the computation of the noisy-interference sum-rate capacity of a MISO IC. Using [35, Theorem 1], the maximum of problem (3) is

$$
\max_{\phi_i \in [0, \text{abs}\left(\frac{\pi}{2} - \theta_i\right)]} \frac{1}{2} \log \left(1 + \frac{P_1 \sin^2 \left(\theta_1 + \rho_1 \phi_1\right)}{1 + a_2 P_2 \sin^2 \phi_2} \right) + \frac{1}{2} \log \left(1 + \frac{P_2 \sin^2 \left(\theta_2 + \rho_2 \phi_2\right)}{1 + a_1 P_1 \sin^2 \phi_1} \right) \tag{108}
$$

 \blacksquare

where $\rho_i = 1$ if $\theta_i \in [0, \frac{\pi}{2}]$ $\left[\frac{\pi}{2}\right]$ and $\rho_i = -1$ otherwise. If ϕ_i^* is optimal, then the corresponding input covariance matrix is

$$
\mathbf{S}_{i}^{*} = P_{i} \begin{bmatrix} \sin^{2} \phi_{i}^{*} & \rho_{i} \sin \phi_{i}^{*} \cos \phi_{i}^{*} \\ \rho_{i} \sin \phi_{i}^{*} \cos \phi_{i}^{*} & \cos^{2} \phi_{i}^{*} \end{bmatrix} . \tag{109}
$$

A closed-form expression for ϕ_i^* is difficult to obtain for the general MISO ICs, or even MISO ZICs. However, if the MISO IC is symmetric with $\theta_1 = \theta_2 = \theta$, $a_1 = a_2 = a$ and $P_1 = P_2 = P$, then we have:

$$
\tan \phi^* = \text{abs}\left(\frac{1}{(1+aP)\tan\theta}\right). \tag{110}
$$

Remark 11: If the MISO IC is symmetric as defined above, the noisy-interference condition is given in [32, Theorem 2], which can also be obtained from Theorem 3. In this case, the optimal S_i^* is given in (109) and (110). Conditions in Theorem 3 reduce to

$$
A = \frac{f\mathbf{S}^* \mathbf{h}}{\mathbf{h}^T \mathbf{S}^* \mathbf{h}} \left(1 + \mathbf{f}^T \mathbf{S}^* \mathbf{f} \right) \le \frac{1}{2}
$$
\n(111)

$$
\sigma^2 = \frac{1}{2} + \frac{1}{2}\sqrt{1 - 4A^2} \le \bar{\sigma}^2 = -\boldsymbol{f}^T \mathbf{S}^* \boldsymbol{f} + \frac{\sqrt{a}}{\cos \theta} \left(\boldsymbol{f}^T \mathbf{S}^* \boldsymbol{f} + A \right).
$$
 (112)

The above conditions are exactly [32, eq.(53)] which are satisfied under the conditions in [32, Theorem 2].

Theorem 3 applies to the case in which $\cos \theta_i \neq 0$ and $\|\mathbf{f}_i\| \neq 0$. If any of these two conditions are satisfied, the MISO IC reduces to a MISO ZIC. The noisy-interference sum-rate capacity is obtain in the following proposition.

Proposition 2: For the MISO IC defined in (78) and its equivalent channel (83) with $\cos \angle (\mathbf{h}_1, \mathbf{f}_1)$ = π $\frac{\pi}{2}$, or $f_1 = 0$, denote by S_i^* , $i = 1, 2$, the optimal solution of problem (3) for the equivalent channel (83). If $S_i^* \neq 0$ and

$$
\boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2 \leq \boldsymbol{h}_2^T \mathbf{S}_2^* \boldsymbol{h}_2 \tag{113}
$$

$$
a_2 \left[\frac{\boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{h}_2 \left(1 + \boldsymbol{h}_2^T \mathbf{S}_2^* \boldsymbol{h}_2 \right)}{\boldsymbol{h}_2^T \mathbf{S}_2^* \boldsymbol{h}_2 \left(1 + \boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2 \right)} \right]^2 \leq \cos^2 \theta_2 \tag{114}
$$

then the sum-rate capacity is the maximum in problem (3) and is achieved by treating interference as noise.

Proof: We first consider the case when $f_1 = 0$. From (91)-(96), we have

 $\frac{2}{2}$

$$
\sigma_1^2 = 1 - A
$$

$$
\sigma_2^2 = 1
$$

$$
\bar{\sigma}_1^2 = -f_2 S_2^* f_2 + \frac{\sqrt{a_2}}{\cos \theta_2} \left(1 + h_2^T S_2^* h_2 \right) \frac{f_2^T S_2^* h_2}{h_2^T S_2^* h_2} \n\bar{\sigma}_2^2 = 0 \nA_1 = 0 \nA_2 = \frac{f_2^T S_2^* h_2}{h_2^T S_2^* h_2}.
$$

Condition (113) guarantees that (90) is satisfied since

$$
A_2^2 = \left(\frac{\boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{h}_2}{\boldsymbol{h}_2^T \mathbf{S}_2^* \boldsymbol{h}_2}\right)^2 = \frac{\boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{f}_2}{\boldsymbol{h}_2^T \mathbf{S}_2^* \boldsymbol{h}_2}
$$
(115)

due to the fact that rank $(S_2^*) = 1$. Then it remains to consider (89) for $i = 1$, which is satisfied by (114) on the condition

$$
\frac{\boldsymbol{f}_2^T\mathbf{S}_2^*\boldsymbol{h}_2}{\cos\theta_2} \geq 0
$$

which is true by (109):

$$
\frac{\boldsymbol{f}_2^T \mathbf{S}_2^* \boldsymbol{h}_2}{\cos \theta_2} = \sqrt{a_2} P_2 \frac{\sin^2 \phi_2^* \cos \theta_2 + \rho_2 \sin \phi_2^* \cos \phi_2^* \sin \theta_2}{\cos \theta_2} \ge 0.
$$

In the case $f_1 \neq 0$ but $\theta_1 = \frac{\pi}{2}$ $\frac{\pi}{2}$, the capacity region is outer bound by that of the same channel but with $f_1 = 0$. If (113) and (114) are satisfied, then the sum-rate capacity of the channel with $f_1 = 0$ is an outer bound on that of the channel with $f_1 \neq 0$ but $\theta_1 = \frac{\pi}{2}$ $\frac{\pi}{2}$. The achievability is due to the fact that

$$
\boldsymbol{f}_1^T\mathbf{S}_1^*\boldsymbol{f}_1=0
$$

since

$$
\mathbf{S}_1^* = P_1 \mathbf{h}_1 \mathbf{h}_1^T.
$$

We note that Proposition 2 can also be proved by Proposition 1.

IV. SIMO ICS

On letting $H_i = \hat{h}_i$ and $F_i = \hat{f}_i$, $i = 1, 2$, in (1), the received signals of a MISO IC are

$$
\hat{\mathbf{y}}_1 = \hat{\mathbf{h}}_1 X_1 + \hat{\mathbf{f}}_2 X_2 + \hat{\mathbf{z}}_1
$$

$$
\hat{\mathbf{y}}_2 = \hat{\mathbf{h}}_2 X_2 + \hat{\mathbf{f}}_1 X_1 + \hat{\mathbf{z}}_2
$$
 (116)

where h_i and f_i are $t_i \times 1$ vectors and we write the transmitted signal as \hat{x}_i with power constraint \hat{P}_i .

T

We can follow the same process (79)-(81) in Section III to find the equivalent channel for (116) with reduced number of antennas. The difference is that we need to replace the h_i in (80) with h_j where $j \neq i$. Then we left-multiply y_i with Q_i and obtain the equivalent channel

$$
\mathbf{y}_1 = \mathbf{h}_1 X_1 + \mathbf{f}_2 X_2 + \mathbf{z}_1
$$

$$
\mathbf{y}_2 = \mathbf{h}_2 X_2 + \mathbf{f}_1 X_1 + \mathbf{z}_2
$$
 (117)

where the dimension of all the vectors is 2, the power constraint for user i is now P_i , and

$$
P_i = \hat{P}_i \tag{118}
$$

$$
a_i = \frac{\|\hat{\boldsymbol{f}}_i\|^2}{\|\hat{\boldsymbol{h}}_i\|^2}
$$
\n(119)

$$
\boldsymbol{f}_i = \begin{bmatrix} \sqrt{a_i} \\ \mathbf{0} \end{bmatrix} \tag{120}
$$

$$
\boldsymbol{h}_i = \begin{bmatrix} \cos \varphi_i \\ \sin \varphi_i \end{bmatrix} \tag{121}
$$

$$
\varphi_i = \angle (\boldsymbol{h}_i, \boldsymbol{f}_j) \qquad i, j \in \{1, 2\}, j \neq i. \tag{122}
$$

We first present the noisy-interference sum-rate capacity of the SIMO ZIC as this is a special case of [31, Proposition 5].

Proposition 3: [31, Proposition 5] For the SIMO IC defined in (116) and its equivalent channel (117) with $\varphi_2 = \frac{\pi}{2}$ or $\boldsymbol{f}_1 = 0$, if $\|\boldsymbol{f}_2\| \le \|\boldsymbol{h}_2\|$, then the sum-rate capacity is

$$
\frac{1}{2}\log\left|\mathbf{I}+P_1\boldsymbol{h}_1\boldsymbol{h}_1^T\left(\mathbf{I}+P_2\boldsymbol{f}_2\boldsymbol{f}_2^T\right)^{-1}\right|+\frac{1}{2}\log\left|\mathbf{I}+P_2\boldsymbol{h}_2\boldsymbol{h}_2^T\right|.
$$
\n(123)

Proof: We first consider the case when $f_1 = 0$. Then from [31, Proposition 5], if there exists a matrix A_2 such that

$$
\boldsymbol{f}_2 = \mathbf{A}_2^T \boldsymbol{h}_2 \tag{124}
$$

$$
\mathbf{I} \succeq \mathbf{A}_2^T \mathbf{A}_2 \tag{125}
$$

then the sum-rate capacity is

$$
\max_{0 \leq S_i \leq P_i, i=1,2} \frac{1}{2} \log \left| \mathbf{I} + S_1 \mathbf{h}_1 \mathbf{h}_1^T \left(\mathbf{I} + S_2 \mathbf{f}_2 \mathbf{f}_2^T \right)^{-1} \right| + \frac{1}{2} \log \left| \mathbf{I} + S_2 \mathbf{h}_2 \mathbf{h}_2^T \right|.
$$
 (126)

Then we can choose

$$
\mathbf{A}_2^T = \frac{\bm{f}_2 \bm{h}_2^T}{\|\bm{h}_2\|^2} = \bm{f}_2 \bm{h}_2^T
$$
 (127)

and (124) is satisfied. For (125), we observe

$$
\mathbf{A}_2^T \mathbf{A}_2 = \boldsymbol{f}_2 \left(\boldsymbol{h}_2^T \boldsymbol{h}_2 \right) \boldsymbol{f}_2^T = \begin{bmatrix} a_2 & 0 \\ 0 & 0 \end{bmatrix} \preceq \mathbf{I} \tag{128}
$$

where the last equality is by the assumption $||f_2|| \le ||h_2||$.

Then we need to show that $S_i^* = P_i$ maximizes (126). On denoting the objective function of (126) by R_s , we have

$$
\frac{\partial R_s}{\partial S_1} = \frac{1}{2} \boldsymbol{h}_1^T \left(\mathbf{I} + S_1 \boldsymbol{h}_1 \boldsymbol{h}_1^T + S_2 \boldsymbol{f}_2 \boldsymbol{f}_2^T \right)^{-1} \boldsymbol{h}_1 \ge 0 \tag{129}
$$

and

$$
\frac{\partial R_s}{\partial S_2} \n= \frac{1}{2} f_2^T \left(\mathbf{I} + S_1 \mathbf{h}_1 \mathbf{h}_1^T + S_2 \mathbf{f}_2 \mathbf{f}_2^T \right)^{-1} \mathbf{f}_2 - \frac{1}{2} \mathbf{f}_2^T \left(\mathbf{I} + S_2 \mathbf{f}_2 \mathbf{f}_2^T \right)^{-1} \mathbf{f}_2 + \frac{1}{2} \mathbf{h}_2^T \left(\mathbf{I} + S_2 \mathbf{h}_2 \mathbf{h}_2^T \right)^{-1} \mathbf{h}_2 \n\geq -\frac{1}{2} f_2^T \left(\mathbf{I} + S_2 \mathbf{f}_2 \mathbf{f}_2^T \right)^{-1} \mathbf{f}_2 + \frac{1}{2} \mathbf{h}_2^T \left(\mathbf{I} + S_2 \mathbf{h}_2 \mathbf{h}_2^T \right)^{-1} \mathbf{h}_2 \n= -\frac{1}{2} \left(1 + S_2 \mathbf{f}_2^T \mathbf{f}_2 \right)^{-1} \mathbf{f}_2^T \mathbf{f}_2 + \frac{1}{2} \left(1 + S_2 \mathbf{h}_2^T \mathbf{h}_2 \right)^{-1} \mathbf{h}_2^T \mathbf{h}_2 \n= \frac{\|\mathbf{h}_2\|^2 - \|\mathbf{f}_2\|^2}{2 \left(1 + S_2 \|\mathbf{f}_2\|^2 \right) \left(1 + S_2 \|\mathbf{h}_2\|^2 \right)} \n\geq 0
$$
\n(130)

where (a) is by the matrix identity (49). Therefore R_s is maximized by $S_i^* = P_i$.

In the case when $f_1 \neq 0$ and $\varphi_2 = \frac{\pi}{2}$ $\frac{\pi}{2}$, the converse can be proved by assuming $f_1 = 0$ to eliminate the interference, and the achievability is proved by left-multiplying y_2 with h_2 to null out the interference.

We note that Proposition 3 can also be proved by Proposition 1.

Theorem 4: For the SIMO IC defined in (116) and its equivalent channel (117), if for $i = 1$ or 2

radius
$$
(\Phi_i) \le \frac{1}{2}
$$
 (131)

where

$$
\mathbf{\Phi}_1 = \left(\mathbf{I} - \mathbf{A}_1^T \mathbf{A}_1 - \mathbf{A}_2 \mathbf{A}_2^T\right)^{-\frac{1}{2}} \mathbf{A}_1^T \mathbf{A}_2^T \left(\mathbf{I} - \mathbf{A}_1^T \mathbf{A}_1 - \mathbf{A}_2 \mathbf{A}_2^T\right)^{-\frac{1}{2}}
$$
(132)

$$
\Phi_2 = \left(\mathbf{I} - \mathbf{A}_1 \mathbf{A}_1^T - \mathbf{A}_2^T \mathbf{A}_2\right)^{-\frac{1}{2}} \mathbf{A}_2^T \mathbf{A}_1^T \left(\mathbf{I} - \mathbf{A}_1 \mathbf{A}_1^T - \mathbf{A}_2^T \mathbf{A}_2\right)^{-\frac{1}{2}}
$$
(133)

$$
\mathbf{A}_1 \left(\mathbf{I} + P_2 \mathbf{f}_2 \mathbf{f}_2^T \right) \mathbf{h}_1 = \mathbf{f}_1 \tag{134}
$$

$$
\mathbf{A}_2 \left(\mathbf{I} + P_1 \mathbf{f}_1 \mathbf{f}_1^T \right) \mathbf{h}_2 = \mathbf{f}_2 \tag{135}
$$

 \blacksquare

then the sum-rate capacity is

$$
\frac{1}{2}\log\left|\mathbf{I}+P_1\mathbf{h}_1\mathbf{h}_1^T\left(\mathbf{I}+P_2\mathbf{f}_2\mathbf{f}_2^T\right)^{-1}\right|+\frac{1}{2}\log\left|\mathbf{I}+P_2\mathbf{h}_2\mathbf{h}_2^T\left(\mathbf{I}+P_1\mathbf{f}_1\mathbf{f}_1^T\right)^{-1}\right|.\tag{136}
$$

Proof: We prove Theorem 4 from Theorem 1 instead of Theorem 2 since the optimal solution is known for problem (16). If we choose A_i in (134) and (135), then by Lemma 3, given (131) there exists Σ_i such that

$$
\mathbf{A}_1^T \mathbf{A}_1 \prec \mathbf{\Sigma}_1 = \mathbf{I} - \mathbf{A}_2 \mathbf{\Sigma}_2^{-1} \mathbf{A}_2^T
$$
 (137)

$$
\mathbf{A}_2^T \mathbf{A}_2 \prec \Sigma_2 = \mathbf{I} - \mathbf{A}_1 \Sigma_1^{-1} \mathbf{A}_1^T.
$$
 (138)

Therefore, conditions (17)-(19) are satisfied. In the following, we show that the upper bound $R_{1u}(S_1, S_2)$ + $R_{2u}(S_1, S_2)$ is maximized at $S_i^* = P_i$ and $R_{1u}(P_1, P_2) + R_{2u}(P_1, P_2) = R_{1l}(P_1, P_2) + R_{2l}(P_1, P_2)$.

From (24) we have

$$
R_{1u} + R_{2u}
$$

\n
$$
= I\left(X_{1G}; \begin{bmatrix} h_1 \\ f_1 \end{bmatrix} X_{1G} + \begin{bmatrix} f_2 \\ 0 \end{bmatrix} X_{2G} + \begin{bmatrix} z_1 \\ n_1 \end{bmatrix} \right) + I\left(X_{1G}; \begin{bmatrix} h_2 \\ f_2 \end{bmatrix} X_{2G} + \begin{bmatrix} f_1 \\ 0 \end{bmatrix} X_{1G} + \begin{bmatrix} z_2 \\ n_2 \end{bmatrix} \right)
$$

\n
$$
= h(f_1 X_{1G} + n_1) - h(n_1) + h(h_1 X_{1G} + f_2 X_{2G} + z_1 | f_1 X_{1G} + n_1) - h(f_2 X_{2G} + z_1 | n_1)
$$

\n
$$
+ h(f_2 X_{2G} + n_2) - h(n_2) + h(h_2 X_{2G} + f_1 X_{1G} + z_2 | f_2 X_{2G} + n_2) - h(f_1 X_{1G} + z_2 | n_2)
$$

\n
$$
= -h(n_1) + h(h_1 X_{1G} + f_2 X_{2G} + z_1 | f_1 X_{1G} + n_1) - h(n_2) + h(h_2 X_{2G} + f_1 X_{1G} + z_2 | f_2 X_{2G} + n_2)
$$
\n(139)

where the last equality is by (137) and (138) which mean

$$
Cov(\boldsymbol{n}_i) = Cov(\boldsymbol{z}_j|\boldsymbol{n}_j) \qquad i, j \in \{1, 2\}, i \neq j. \tag{140}
$$

Then it suffices to show that $h(h_1X_{1G} + \mathbf{f}_2X_{2G} + \mathbf{z}_1|\mathbf{f}_1X_{1G} + \mathbf{n}_1)$ is an increasing function of Cov(X_{iG}). We write $X_{iG} = \bar{X}_{iG} + \hat{X}_{iG}$ where X_{iG} and \hat{X}_{iG} are independent Gaussian variables. Obviously, we have $\text{Cov}(X_{iG}) \geq \text{Cov}(\bar{X}_{iG})$ and

$$
h(\mathbf{h}_1 X_{1G} + \mathbf{f}_2 X_{2G} + \mathbf{z}_1 | \mathbf{f}_1 X_{1G} + \mathbf{n}_1)
$$

\n
$$
\geq h\left(\mathbf{h}_1 X_{1G} + \mathbf{f}_2 X_{2G} + \mathbf{z}_1 | \mathbf{f}_1 X_{1G} + \mathbf{n}_1, \hat{X}_{1G}, \hat{X}_{2G}\right)
$$

\n
$$
= h\left(\mathbf{h}_1 \bar{X}_{1G} + \mathbf{f}_2 \bar{X}_{2G} + \mathbf{z}_1 | \mathbf{f}_1 \bar{X}_{1G} + \mathbf{n}_1\right).
$$
 (141)

Therefore, the upper bound $R_{1u}(S_1, S_2) + R_{2u}(S_1, S_2)$ is maximized at $S_i^* = P_i$. From (38), (40), (134) and (135), we have

$$
R_{iu}(P_1, P_2) = R_{il}(P_1, P_2). \tag{142}
$$

Therefore, the upper bound is achievable and hence is the sum-rate capacity.

Remark 12: A simple way to choose matrix A_i that satisfies (134) and (135) is to let

$$
\mathbf{A}_1 = \left(\mathbf{I} + P_2 \mathbf{f}_2 \mathbf{f}_2^T\right) \mathbf{h}_1 \mathbf{f}_1^T
$$
 (143)

$$
\mathbf{A}_2 = \left(\mathbf{I} + P_1 \mathbf{f}_1 \mathbf{f}_1^T\right) \mathbf{h}_2 \mathbf{f}_2^T. \tag{144}
$$

However, this may not always be the best choice for (131). An alternative way is to let [32, eq. (39)]

$$
\mathbf{A}_{i} = \frac{\boldsymbol{v}_{i} \boldsymbol{f}_{i}^{T}}{\boldsymbol{h}_{i}^{T} \left(1 + P_{j} \boldsymbol{f}_{j} \boldsymbol{f}_{j}^{T}\right) \boldsymbol{v}_{i}}
$$
(145)

where v_i is a vector. Then, to satisfy (131), we need only

$$
\min_{\mathbf{v}_1, \mathbf{v}_2} \text{radius}(\mathbf{\Phi}_i) \le \frac{1}{2}.\tag{146}
$$

Remark 13: Proposition 3 can also be obtained from Theorem 4. Let $f_1 = 0$, then we have $A_1 = 0$, $A_2 = h_2 f_2^T$ and $\Phi_i = 0$. Therefore, condition (131) is always satisfied. Notice that $(I - A_2 A_2^T)^{-\frac{1}{2}}$ and $(I - A_2^T A_2)^{-\frac{1}{2}}$ must exist such that Φ_i exists. By [31, Lemma 7] this requires $A_2^T A_2 \preceq I$ which is (128).

Remark 14: If the SIMO IC is symmetric, i.e., $h_1 = h_2 = h$, $f_1 = f_2 = f$ and $P_1 = P_2 = P$, the noisy-interference condition is given in [32, Theorem 3]. We will show that the same result can be obtained from Theorem 4. Without loss of generality, we assume $\theta \in \left[0, \frac{\pi}{2}\right]$ $\frac{\pi}{2}$. The matrix **A** that satisfies (134) and (135) can be chosen as

$$
\mathbf{A} = \frac{\sqrt{a}}{\frac{\cos \omega \cos \theta}{1 + aP} + \sin \omega \sin \theta} \begin{bmatrix} \cos \omega & \sin \omega \\ 0 & 0 \end{bmatrix}
$$
(147)

where ω is a real number. Since $A_1 = A_2$, condition (131) reduces to radius($A \leq \frac{1}{2}$, i.e.,

$$
\frac{1}{2} \ge \min_{\omega} \max_{\phi} \text{ abs}\left(\left[\frac{\cos \phi}{\sin \phi}\right]^T \mathbf{A} \left[\frac{\cos \phi}{\sin \phi}\right]\right)
$$

$$
= \min_{\omega} \max_{\phi} \text{ abs}\left[\frac{\sqrt{a} \left(\cos^2 \phi \cos \omega + \cos \phi \sin \phi \sin \omega\right)}{\frac{\cos \omega \cos \theta}{1 + aP} + \sin \omega \sin \theta}\right]
$$

$$
= \min_{\omega} \frac{\sqrt{a} (1 + \mathrm{abs}(\cos \omega)) / 2}{\mathrm{abs} \left[\frac{\cos \omega \cos \theta}{1 + aP} + \sin \omega \sin \theta \right]}
$$

$$
= \min_{\omega \in [0, \frac{\pi}{2}]} \frac{\sqrt{a} (1 + \cos \omega) / 2}{\sqrt{r} \sin(\omega + \beta)}
$$
(148)

where

$$
r = \frac{\cos^2 \theta}{(1 + aP)^2} + \sin^2 \theta
$$

$$
\beta = \operatorname{atan} \frac{\cos \theta}{(1 + aP)\sin \theta} \in \left[0, \frac{\pi}{2}\right].
$$
 (149)

It can be shown that the optimal ω for (148) is

$$
\omega = \begin{cases} \frac{\pi}{2}, & \text{if } \beta \in [0, \frac{\pi}{4}] \\ \pi - 2\beta, & \text{if } \beta \in [\frac{\pi}{4}, \frac{\pi}{2}]. \end{cases}
$$
(150)

Then (148) becomes

$$
a \le \sin^2 \theta \qquad \qquad \text{if } \frac{\cos \theta}{(1 + aP)} \le \sin \theta \qquad (151)
$$

$$
\frac{\cos^2 \theta}{(1+aP)^2} - \frac{2\sqrt{a}\cos\theta}{1+aP} + \sin^2 \theta \ge 0 \qquad \text{otherwise} \tag{152}
$$

which are exactly the conditions in [32, Theorem 3].

V. NUMERICAL EXAMPLES

Example 1: Consider a MIMO IC with channel matrices:

$$
\mathbf{H}_1 = \begin{bmatrix} -1.4510 & -1.0078 \\ -1.8953 & 0.2184 \\ 1.9125 & -1.6068 \end{bmatrix}, \quad \mathbf{F}_2 = \begin{bmatrix} 0.4255 & -0.1702 & 0.6865 \\ 0.5133 & 0.1574 & 0.1805 \\ -0.4795 & -0.5019 & 0.4648 \end{bmatrix},
$$

$$
\mathbf{H}_2 = \begin{bmatrix} 0.7739 & 1.4112 & -1.8231 \\ 1.4817 & -0.4647 & 2.1620 \end{bmatrix} \quad \text{and} \quad \mathbf{F}_1 = \begin{bmatrix} -0.2636 & 0.2981 \\ -0.3483 & -0.1426 \end{bmatrix}
$$

and power constraints:

$$
P_1 = 1
$$
 and $P_2 = 4$.

The optimal input covariance matrices for problem (3) are

$$
\mathbf{S}_{1}^{*} = \begin{bmatrix} 0.9079 & -0.2892 \\ -0.2892 & 0.0921 \end{bmatrix} \text{ and } \mathbf{S}_{2}^{*} = \begin{bmatrix} 0.9458 & 0.1788 & 0.5314 \\ 0.1788 & 0.6839 & -1.0601 \\ 0.5314 & -1.0601 & 2.3703 \end{bmatrix}
$$

and both S_1^* and S_2^* are singular:

$$
\text{rank}(\mathbf{S}_1^*)=1 \quad \text{and} \quad \text{rank}(\mathbf{S}_2^*)=2.
$$

The G_1 and G_2 in (4) and (5) and the Lagrangian multipliers are

$$
\mathbf{G}_{1} = \begin{bmatrix} -0.3624 & 0.0005 \\ 0.0005 & -0.3608 \end{bmatrix}, \quad \mathbf{G}_{2} = \begin{bmatrix} -0.1368 & -0.0525 & -0.0294 \\ -0.0525 & -0.0591 & 0.0583 \\ -0.0294 & 0.0583 & -0.1305 \end{bmatrix}
$$

$$
\mathbf{W}_{1} = \begin{bmatrix} 0.1740 & 0.5463 \\ 0.5463 & 1.7150 \end{bmatrix} * 10^{-3}, \quad \mathbf{W}_{2} = \begin{bmatrix} 2.6419 & -5.2450 & -2.9381 \\ -5.2450 & 10.4117 & 5.8325 \\ -2.9381 & 5.8325 & 3.2674 \end{bmatrix} * 10^{-2}
$$

$$
\lambda_{1} = 0.3626 \quad \text{and} \quad \lambda_{2} = 0.1632.
$$

It is easy to verify that the KKT conditions in (4)-(7) are satisfied.

The A_1 and A_2 that satisfy (27) and (28) are

$$
\mathbf{A}_1 = \begin{bmatrix} -0.2821 & 0.4705 \\ 0.0254 & 0.2073 \\ -0.3814 & 0.1588 \end{bmatrix} \text{ and } \mathbf{A}_2 = \begin{bmatrix} 0.0047 & 0.2392 & -0.4520 \\ 0.3215 & 0.2853 & -0.1663 \end{bmatrix}.
$$

The O_1 and O_2 in (33) and (34) are

$$
O_1 = 0
$$
 and $O_2 = 0$.

Therefore, (29) and (30) are satisfied. Hence the expressions for Σ_1 and Σ_2 are not relevant. As in Remark 8, we only need to show the existence of Σ_1 and Σ_2 that satisfy (17)-(19). We have that (71) is also satisfied:

radius (
$$
\Phi_1
$$
) = 0.4350 and radius (Φ_2) = 0.3130.

Then, all the conditions in Theorem 2 are satisfied. Therefore, the sum-rate capacity is achieved by treating interference as noise and the optimal input covariances are S_1^* and S_2^* .

Example 2: Consider a MISO IC in the form (78) with channel vectors: \overline{a}

$$
\hat{\mathbf{h}}_1 = \begin{bmatrix} -0.1481 \\ -1.7969 \\ 0.1331 \\ 0.6644 \end{bmatrix}, \quad \hat{\mathbf{f}}_1 = \begin{bmatrix} 0.0201 \\ -0.0197 \\ -0.0729 \\ 0.7636 \end{bmatrix}, \quad \hat{\mathbf{h}}_2 = \begin{bmatrix} 0.1050 \\ -0.0523 \\ 1.8070 \end{bmatrix}, \quad \hat{\mathbf{f}}_2 = \begin{bmatrix} -0.4748 \\ -0.7711 \\ 0.3813 \end{bmatrix}
$$

and power constraint

$$
\hat{P}_1 = \hat{P}_2 = 1.
$$

The equivalent MISO IC in the form (83) has channel vectors

$$
\boldsymbol{h}_1 = \begin{bmatrix} 0.3586 \\ 0.9335 \end{bmatrix}, \quad \boldsymbol{f}_1 = \begin{bmatrix} 0.3985 \\ 0 \end{bmatrix}, \quad \boldsymbol{h}_2 = \begin{bmatrix} 0.3818 \\ 0.9242 \end{bmatrix}, \quad \boldsymbol{f}_2 = \begin{bmatrix} 0.5426 \\ 0 \end{bmatrix}
$$

and power constraints

$$
P_1 = 3.7100
$$
 and $P_2 = 3.2789$.

The corresponding channel parameters are

$$
\theta_1 = 0.3833\pi
$$
, $\theta_2 = 0.3753\pi$, $a_1 = 0.1588$, $a_2 = 0.2944$.

The optimal input covariance matrices for the equivalent channel are

$$
\mathbf{S}_1^* = \begin{bmatrix} 0.2093 & 0.8561 \\ 0.8561 & 3.5007 \end{bmatrix} \text{ and } \mathbf{S}_2^* = \begin{bmatrix} 0.1345 & 0.6503 \\ 0.6503 & 3.1445 \end{bmatrix}.
$$

The corresponding optimal covariance matrices for the original channel are

$$
\hat{\mathbf{S}}_{1}^{*} = \begin{bmatrix} 0.0070 & 0.0808 & -0.0071 & -0.0187 \\ 0.0808 & 0.9356 & -0.0820 & -0.2168 \\ -0.0071 & -0.0820 & 0.0072 & 0.0190 \\ -0.0187 & -0.2168 & 0.0190 & 0.0502 \end{bmatrix} \text{ and } \hat{\mathbf{S}}_{2}^{*} = \begin{bmatrix} 0.0253 & 0.0204 & 0.1558 \\ 0.0204 & 0.0164 & 0.1253 \\ 0.1558 & 0.1253 & 0.9583 \end{bmatrix}.
$$

The G_1 , G_2 in (4) and (5) and the Lagrangian multipliers are

$$
\mathbf{G}_1 = \begin{bmatrix} 0.0442 & -0.0357 \\ -0.0357 & -0.0929 \end{bmatrix}, \quad \mathbf{G}_2 = \begin{bmatrix} 0.0929 & -0.0420 \\ -0.0420 & -0.1017 \end{bmatrix}
$$

$$
\mathbf{W}_1 = \begin{bmatrix} 0.1459 & -0.0357 \\ -0.0357 & 0.0087 \end{bmatrix}, \quad \mathbf{W}_2 = \begin{bmatrix} 0.2033 & -0.0420 \\ -0.0420 & 0.0087 \end{bmatrix}
$$

$$
\lambda_1 = 0.1016, \quad \lambda_2 = 0.1104.
$$

It can be easily verified that the KKT conditions in (4)-(7) are satisfied.

The A_1 and A_2 that satisfy (97) and (98) (or (27) and (28)) are

$$
A_1 = 0.0992
$$
 and $A_2 = 0.1156$,

and the σ_i^2 and $\bar{\sigma}_i^2$ in (91)-(94) are

$$
\sigma_1^2 = 0.9874 > \bar{\sigma}_1^2 = 0.6277
$$

$$
\sigma_2^2 = 0.9891 > \bar{\sigma}_2^2 = 0.4643.
$$

Therefore, by Theorem 3, the sum-rate capacity of this MISO channel is achieved by treating interference as noise.

We can also verify condition (103) with

$$
k_1 = 1.0994
$$
 and $k_2 = 0.8133$.

The O_1 and O_2 matrices in (33) and (34) are

$$
\mathbf{O}_1 = \begin{bmatrix} 0.0679 & -0.0166 \\ -0.0166 & 0.0041 \end{bmatrix} \text{ and } \mathbf{O}_2 = \begin{bmatrix} 0.1280 & -0.0265 \\ -0.0265 & 0.0055 \end{bmatrix}.
$$

Since $W_i \succeq O_i$, by Theorem 2, the sum-rate capacity of this MISO channel is achieved by treating interference as noise.

The sum-rate capacity is

$$
R_1 + R_2 = 0.7533 + 0.7009 = 1.4543.
$$

Example 3: Consider a SIMO IC with channel vectors:

$$
\hat{\boldsymbol{h}}_1 = \begin{bmatrix} -1.8356 \\ 0.0668 \\ 0.0355 \end{bmatrix}, \quad \hat{\boldsymbol{f}}_1 = \begin{bmatrix} 1.1136 \\ -0.0346 \\ -0.2537 \\ 0.1179 \end{bmatrix}, \quad \hat{\boldsymbol{h}}_2 = \begin{bmatrix} 0.2458 \\ 0.0700 \\ -0.6086 \\ -1.2226 \end{bmatrix}, \quad \hat{\boldsymbol{f}}_2 = \begin{bmatrix} 0.1583 \\ -0.6714 \\ -0.5161 \end{bmatrix}
$$

and power constraint

$$
P_1 = P_2 = 1.
$$

The equivalent SIMO IC is

$$
\boldsymbol{h}_1 = \begin{bmatrix} -0.2234 \\ 0.9747 \end{bmatrix}, \quad \boldsymbol{f}_1 = \begin{bmatrix} 0.6252 \\ 0 \end{bmatrix}, \quad \boldsymbol{h}_2 = \begin{bmatrix} 0.1764 \\ 0.9843 \end{bmatrix}, \quad \boldsymbol{f}_2 = \begin{bmatrix} 0.6201 \\ 0 \end{bmatrix}
$$

with power constraint

$$
P_1 = 3.3753
$$
 and $P_2 = 1.9304$.

The corresponding channel parameters are

$$
\varphi_1 = 0.5717\pi
$$
, $\varphi_2 = 0.4436\pi$, $a_1 = 0.3909$, $a_2 = 0.3845$.

We simply choose matrices A_1 and A_2 as in (143) and (144):

$$
\mathbf{A}_1 = \begin{bmatrix} -0.2434 & 0 \\ 0.6094 & 0 \end{bmatrix} \text{ and } \mathbf{A}_2 = \begin{bmatrix} 0.2537 & 0 \\ 0.6103 & 0 \end{bmatrix}.
$$

We have $I - A_1^T A_1 - A_2 A_2^T \succeq 0$, $I - A_1 A_1^T - A_2^T A_2 \succeq 0$ and

radius (
$$
\Phi_1
$$
) = 0.2784 and radius (Φ_1) = 0.2815.

Therefore, by Theorem 4 treating interference as noise achieves the sum-rate capacity and

$$
R_1 + R_2 = 0.7297 + 0.5317 = 1.2614.
$$

We can also use Theorem 2 to verify the result. The A_1 and A_2 satisfy (27) and (28). The numerical radius condition guarantees the existence of Σ_1 and Σ_2 to satisfy (17)-(19). Furthermore, we have $W_1 = W_2 = O_1 = O_2 = 0$. Therefore, all the conditions in Theorem 2 are satisfied.

Example 4: In this example, we consider the maximum value of a_i for MISO and SIMO ICs to have noisy interference with various choices of P_i and θ_i or φ_i . For the symmetric MISO or SIMO IC, one can use Theorem 3 and 4 to generate the same result as [32, Fig. 2]. For the SIMO ZICs, the maximum a_2 is 1 regardless of P_i and φ_2 by Proposition 3. For the MISO ZIC, the maximum a_2 is shown in Fig. 2 by Proposition 2.

Example 5: In this example, we show that a MISO ZIC in which the noisy-interference conditions in Proposition 2 are violated and treating interference as noise does not achieve the sum-rate capacity.

Consider a MISO ZIC with $P_1 = 1, P_2 = 10, a_1 = 0, a_2 = 0.4, \theta_1 = \frac{\pi}{2}$ $\frac{\pi}{2}$ and $\theta_2 = \frac{\pi}{4}$ $\frac{\pi}{4}$. As is shown in Fig. 2, this MISO IC does not satisfy the noisy-interference condition. The maximum sum-rate by treating interference as noisy is

$$
R_1 + R_2 = 1.3725
$$

and is achieved by (108) and (109):

$$
\mathbf{S}_{1}^{*} = \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \text{ and } \mathbf{S}_{2}^{*} = \begin{bmatrix} 1.7566 & 3.8053 \\ 3.8053 & 8.2434 \end{bmatrix}.
$$

However, we consider a Han and Kobayashi achievable rate region [6], [7] for the MISO ZIC:

$$
R_1 \leq \frac{1}{2} \log \left(1 + \frac{P_1}{1 + \boldsymbol{f}_2^T \mathbf{S}_p \boldsymbol{f}_2} \right)
$$

$$
R_2 \leq \frac{1}{2} \log \left(1 + \boldsymbol{h}_2^T \left(\mathbf{S}_p + \mathbf{S}_c \right) \boldsymbol{h}_2 \right)
$$

$$
R_1+R_2 \leq \frac{1}{2}\log\left(1+\pmb{h}^T_2\mathbf{S}_p\pmb{h}_2\right)+\frac{1}{2}\log\left(1+\frac{P_1+\pmb{f}^T_2\mathbf{S}_c\pmb{f}_2}{1+\pmb{f}^T_2\mathbf{S}_p\pmb{f}_2}\right)
$$

where S_p and S_c are respectively the covariance matrices for the input vectors that carry the private and common messages. Then we can achieve a sum-rate of

$$
R_1 + R_2 = 1.4093
$$

by the same S_1^* and a different $S_2^* = S_p^* + S_c^*$ with

$$
\mathbf{S}_{p}^{*} = \begin{bmatrix} 1.1542 & 2.2652 \\ 2.2652 & 4.4458 \end{bmatrix} \text{ and } \mathbf{S}_{c}^{*} = \begin{bmatrix} 4.1906 & 0.9367 \\ 0.9367 & 0.2094 \end{bmatrix}.
$$

VI. CONCLUSION

We have studied the noisy-interference sum-rate capacity of MIMO ICs. Sufficient conditions for a MIMO IC to achieve the sum-rate capacity by treating interference as noise have been obtained. For the special cases of MISO and SIMO ICs, simplified conditions have been derived. These conditions largely extend all the existing sufficient conditions.

APPENDIX

A. Proof of Lemma 1

If we write the optimization problem in the standard form:

$$
\begin{aligned}\n\min \quad & f(\mathbf{x}) \\
\text{subject to} \quad & g_i(\mathbf{x}) \le 0, \quad i = 1, \cdots, m \\
& \mathbf{x} \in \mathcal{X}\n\end{aligned}\n\tag{153}
$$

then CQ5 in [39, p. 306] requires that there exist a vector $y \in N_{\mathcal{X}}(x^*)^*$ such that

$$
\nabla g_j(\boldsymbol{x}^*)^T \boldsymbol{y} < 0 \quad \forall j \in A(\boldsymbol{x}^*) \tag{154}
$$

where x^* is optimal for problem (153), $\bigtriangledown g_j(x^*)$ is the gradient of $g_j(x)$ at x^* , $N_{\mathcal{X}}(x^*)$ is the normal cone of X at x^* , $N_{\mathcal{X}}(x^*)^*$ is the polar cone of $N_{\mathcal{X}}(x^*)$, and $A(x^*)$ is index set of all the active inequality constraints. Applying this theorem to our case, we need to find matrices K_i , $i = 1, 2$, such that

$$
\mathbf{K}_{i} \in N_{\mathcal{S}_{i}}\left(\mathbf{S}_{i}^{*}\right)^{*} = T_{\mathcal{S}_{i}}\left(\mathbf{S}_{i}^{*}\right) \tag{155}
$$

$$
\operatorname{tr}\left(\mathbf{K}_{i}\right) < 0 \quad \text{if } \operatorname{tr}\left(\mathbf{S}_{i}^{*}\right) = P_{i} \tag{156}
$$

Fig. 2. The maximum value of a for a MISO ZIC with $P_1 = 1$ to have noisy interference.

where S_i is the set of symmetric positive semi-definite matrices with the same dimension as that of S_i^* , and $T_{\mathcal{S}_i}$ (\mathbf{S}_i^*) is the tangent cone of \mathcal{S}_i at \mathbf{S}_i^* . The equality of (155) is due to the convexity of \mathcal{S}_i and [39, Proposition 4.6.3, p. 254].

Define a sequence of matrices ${Y_k}$:

$$
\mathbf{Y}_k = \mathbf{S}_1^* - \frac{1}{k} \mathbf{U} \cdot \text{diag}[\eta_1, 0, \cdots, 0] \cdot \mathbf{U}^T, \quad k = 1, 2 \cdots \cdots \tag{157}
$$

where U is a unitary matrix associated with the eigenvalue decomposition of S_1^* , and η_1 is the largest eigenvalue of S_i^* :

$$
\mathbf{S}_{i}^{*} = \mathbf{U} \cdot \text{diag}[\eta_{1}, \eta_{2}, \cdots, \eta_{t_{i}}] \cdot \mathbf{U}^{T}.
$$
 (158)

Obviously, we have

$$
\{Y_k\} \subseteq \mathcal{S}_1, \quad Y_k \neq S_1^*
$$
\n⁽¹⁵⁹⁾

39

$$
\lim_{k \to \infty} \mathbf{Y}_k = \mathbf{S}_1^* \tag{160}
$$

$$
\lim_{k \to \infty} \frac{\mathbf{Y}_k - \mathbf{S}_1^*}{\|\text{Vec}\left(\mathbf{Y}_k - \mathbf{S}_1^*\right)\|} = \frac{-\mathbf{U} \cdot \text{diag}[\eta_1, 0, \cdots, 0] \cdot \mathbf{U}^T}{\|\text{Vec}\left(\mathbf{U} \cdot \text{diag}[\eta_1, 0, \cdots, 0] \cdot \mathbf{U}^T\right)\|}.
$$
\n(161)

Therefore, by [39, Definition 4.6.2, p. 248]

$$
\mathbf{K}_1 \triangleq -\mathbf{U} \cdot \text{diag}[\eta_1, 0, \cdots, 0] \cdot \mathbf{U}^T \in T_{\mathcal{S}_i} \left(\mathbf{S}_i^* \right). \tag{162}
$$

Since η_1 is the largest eigenvalue of S_1^* , we have

$$
tr(K_1) = -\eta_1 < 0 \quad \text{if } tr(S_1^*) = P_1 > 0. \tag{163}
$$

We can similarly find K_2 satisfying (155) and (156) for S_2^* . Therefore, the constraint qualifications are satisfied and there exist Lagrangian multipliers λ_i and \mathbf{W}_i satisfying (4)-(7).

B. Proof of Lemma 2

To prove that the objective function of problem (16) is concave over S_1 and S_2 , it is equivalent to prove that (23) is concave. By [31, Lemma 1], both the conditional entropies $h(\mathbf{H}_1 \mathbf{x}_{1G} + \mathbf{F}_2 \mathbf{x}_{2G} + \mathbf{z}_1 | \mathbf{F}_1 \mathbf{x}_{1G} + \mathbf{n}_1)$ and $h(\mathbf{H}_2\boldsymbol{x}_{2G} + \mathbf{F}_1\boldsymbol{x}_{1G} + \boldsymbol{z}_2 | \mathbf{F}_2\boldsymbol{x}_{2G} + \boldsymbol{n}_2)$ are concave. Therefore, by symmetry, it suffices to prove that $h(\mathbf{F}_1\boldsymbol{x}_{1G} + \boldsymbol{n}_1) - h(\mathbf{F}_1\boldsymbol{x}_{1G} + \boldsymbol{z}_2|\boldsymbol{n}_2)$ is concave over \mathbf{S}_1 and \mathbf{S}_2 .

From (20) we have Cov $(z_2|\mathbf{n}_2) = \mathbf{I} - \mathbf{A}_2 \mathbf{\Sigma}_2^{-1} \mathbf{A}_2^T$. From (18), there exists a Gaussian vector $\mathbf{v} \sim$ $\mathcal{N}\left(\mathbf{0}, \tilde{\boldsymbol{\Sigma}}\right)$ where

$$
\tilde{\mathbf{\Sigma}} = \left(\mathbf{I} - \mathbf{A}_2 \mathbf{\Sigma}_2^{-1} \mathbf{A}_2^T\right) - \mathbf{\Sigma}_1.
$$

We further let \tilde{z} be independent of all other random vectors of interest, and then we have

$$
h\left(\mathbf{F}_{1}\boldsymbol{x}_{1G}+\boldsymbol{n}_{1}\right)-h\left(\mathbf{F}_{1}\boldsymbol{x}_{1G}+\boldsymbol{z}_{2}|\boldsymbol{n}_{2}\right)=h\left(\mathbf{F}_{1}\boldsymbol{x}_{1G}+\boldsymbol{n}_{1}\right)-h\left(\mathbf{F}_{1}\boldsymbol{x}_{1G}+\boldsymbol{n}_{1}+\boldsymbol{v}\right)
$$

$$
=-I\left(\boldsymbol{v};\mathbf{F}_{1}\boldsymbol{x}_{1G}+\boldsymbol{n}_{1}+\boldsymbol{v}\right).
$$
 (164)

Define a binary random variable Q with probability mass function $Pr(Q = 0) = q$ and $Pr(Q = 1) = 1-q$ where $0 \le q \le 1$. Let \bar{x}_1 have mixed Gaussian distribution with conditional distribution

$$
p\left(\bar{\boldsymbol{x}}_1 | Q\right) = \begin{cases} p\left(\bar{\boldsymbol{x}}_1 | Q = 0\right) = p\left(\bar{\boldsymbol{x}}_1^{(1)}\right) \sim \mathcal{N}\left(\mathbf{0}, \mathbf{S}_1^{(1)}\right) \\ p\left(\bar{\boldsymbol{x}}_1 | Q = 1\right) = p\left(\bar{\boldsymbol{x}}_1^{(2)}\right) \sim \mathcal{N}\left(\mathbf{0}, \mathbf{S}_1^{(2)}\right) \end{cases}
$$
(165)

where

$$
\mathbf{S}_1 = q\mathbf{S}_1^{(1)} + (1-q)\mathbf{S}_1^{(2)}.
$$
 (166)

Then we have

$$
-qI\left(\mathbf{v};\mathbf{F}_{1}\mathbf{x}_{1}^{(1)}+\mathbf{n}_{1}+\mathbf{v}\right)-\left(1-q\right)I\left(\mathbf{v};\mathbf{F}_{1}\mathbf{x}_{2}^{(2)}+\mathbf{n}_{1}+\mathbf{v}\right)
$$
\n
$$
=-I\left(\mathbf{v};\mathbf{F}_{1}\bar{\mathbf{x}}_{1}+\mathbf{n}_{1}+\mathbf{v}|Q\right)
$$
\n
$$
=-h\left(\mathbf{v}|Q\right)+h\left(\mathbf{v}|\mathbf{F}_{1}\bar{\mathbf{x}}_{1}+\mathbf{n}_{1}+\mathbf{v},Q\right)
$$
\n
$$
\stackrel{(a)}{\leq}-I\left(\mathbf{v};\mathbf{F}_{1}\bar{\mathbf{x}}_{1}+\mathbf{n}_{1}+\mathbf{v}\right)
$$
\n
$$
\stackrel{(b)}{\leq}-I\left(\mathbf{v};\mathbf{F}_{1}\mathbf{x}_{1G}+\mathbf{n}_{1}+\mathbf{v}\right)
$$
\n(167)

where (a) is by the assumption that Q is independent of \boldsymbol{v} and the fact that conditioning does not increase entropy. In (b), we let $x_{1G} \sim \mathcal{N}(0, S_1)$. The inequality is by (166) and the fact that Gaussian noise is the worst additive noise [43]. Therefore, $h(\mathbf{F}_1 \mathbf{x}_{1G} + \mathbf{n}_1) - h(\mathbf{F}_1 \mathbf{x}_{1G} + \mathbf{z}_2 | \mathbf{n}_2)$ is concave over \mathbf{S}_1 and S₂. Similarly, we can prove that $h(\mathbf{F}_2\mathbf{x}_{2G} + \mathbf{n}_2) - h(\mathbf{F}_2\mathbf{x}_{2G} + \mathbf{z}_1|\mathbf{n}_1)$ is also a concave function of \mathbf{S}_1 and S_2 .

C. Proof of Lemma 3

In the proof of [31, Lemma 9], if radius $(\Phi_1) \leq \frac{1}{2}$ $\frac{1}{2}$, then there exist Σ_1 that satisfy

$$
\Sigma_1 = \mathbf{I} - \mathbf{A}_1 \left(\mathbf{I} - \mathbf{A}_1 \Sigma_1^{-1} \mathbf{A}_1^T \right)^{-1} \mathbf{A}_2 \tag{168}
$$

and $\Sigma_1 - A_1^T A_1$ is positive definite. Then it suffice to prove that $I - A_1 \Sigma_1^{-1} A_1^T$ is positive definite since we can substitute Σ_1 defined in (168) into (75) and obtain a positive definite Σ_2 .

Let $\Sigma_1 = \mathbf{A}_1^T \mathbf{A}_1 + \mathbf{X}$ where $\mathbf{X} \succ 0$; then we have

$$
\Sigma_2 = \mathbf{I} - \mathbf{A}_1 \Sigma_1^{-1} \mathbf{A}_1^T
$$

= $\mathbf{I} - \mathbf{A}_1 (\mathbf{X} + \mathbf{A}_1^T \mathbf{A}_1)^{-1} \mathbf{A}_1^T$

$$
\stackrel{(a)}{=} \mathbf{I} - \mathbf{A}_1 (\mathbf{X} + \mathbf{T} \mathbf{\Lambda} \mathbf{T}^T)^{-1} \mathbf{A}_1^T
$$

$$
\stackrel{(b)}{\succeq} \mathbf{I} - \mathbf{A}_1 (\eta \mathbf{I} + \mathbf{T} \mathbf{\Lambda} \mathbf{T}^T)^{-1} \mathbf{A}_1^T
$$

= $\mathbf{I} - \mathbf{A}_1 \mathbf{T} (\eta \mathbf{I} + \mathbf{\Lambda})^{-1} \mathbf{T}^T \mathbf{A}_1^T$ (169)

where in (a) we let $A_1^T A_1 = T\Lambda T^T$ be the eigenvalue decomposition of $A_1^T A_1$ and $TT^T = I$ and Λ is a diagonal matrix with non-negative diagonal elements. In (b), we let η be the smallest eigenvalue of **X**. Since **X** is symmetric positive definite, we have $\eta > 0$. The inequality of (b) is by the fact $X \succeq \eta I$.

Since $I - B^TB$ is positive definite if and only if $I - BB^T$ is positive definite, we only need to prove that $I - (\eta I + \Lambda)^{-\frac{1}{2}} T^T A_1^T A_1 T (\eta I + \Lambda)^{-\frac{1}{2}}$ is positive definite, which is obviously true since $\mathbf{T}^T \mathbf{A}_1^T \mathbf{A}_1 \mathbf{T} = \mathbf{\Lambda}$ and $\eta > 0$.

We have proved that if radius $(\Phi_1) \leq \frac{1}{2}$ $\frac{1}{2}$, then there exist $\Sigma_1 \succ A_1^T A_1$ and $\Sigma_2 \succ 0$ that satisfy (74) and (75). Now we need to prove that $\Sigma_2 \succ A_2^T A_2$, which is true by the fact $I - A_2 \Sigma_2^{-1} A_2^T = \Sigma_1 \succ 0$ and [31, Lemma 6].

By symmetry, if radius(Φ_2) $\leq \frac{1}{2}$, we also have positive definite solutions. The equivalence between (76) and (77) is by [31, Lemma 6].

REFERENCES

- [1] C. E. Shannon, "Two-way communication channels," in *Proc. 4th Berkeley Symp. Math. Stat. and Prob.*, Berkeley, CA, 1961, vol. 1, pp. 611–644, Also available in *Claude E. Shannon: Collected Papers*, IEEE Press, New York, 1993.
- [2] R. Ahlswede, "The capacity region of a channel with two senders and two receivers," *Ann. Prob.*, vol. 2, no. 5, pp. 805–814, 1974.
- [3] A. B. Carleial, "A case where interference does not reduce capacity," *IEEE Trans. Inf. Theory*, vol. 21, pp. 569–570, Sep. 1975.
- [4] H. Sato and M. Tanabe, "A discrete two-user channel with strong interferene," *Trans. IECE Japan*, vol. 61, pp. 880–884, 1978.
- [5] A. B. Carleial, "Interference channels," *IEEE Trans. Inf. Theory*, vol. 24, pp. 60–70, Jan. 1978.
- [6] T. S. Han and K. Kobayashi, "A new achievable rate region for the interference channel," *IEEE Trans. Inf. Theory*, vol. 27, pp. 49–60, Jan. 1981.
- [7] H. F. Chong, M. Motani, H. K. Garg, and H. El Gamal, "On the Han-Kobayashi region for the interference channel," *IEEE Trans. Inf. Theory*, vol. 54, pp. 3188–3195, Jul. 2008.
- [8] G. Kramer, "Review of rate regions for interference channels," in *Proc. International Zurich Seminar*, Zurich, Switzerland, Feb. 2006, pp. 162–165.
- [9] H. Sato, "Two-user communication channels," *IEEE Trans. Inf. Theory*, vol. 23, pp. 295–304, May 1977.
- [10] H. Sato, "On degraded Gaussian two-user channels," *IEEE Trans. Inf. Theory*, vol. 24, pp. 634–640, Sep. 1978.
- [11] A. B. Carleial, "Outer bounds on the capacity of interference channels," *IEEE Trans. Inf. Theory*, vol. 29, pp. 602–606, July 1983.
- [12] H. Sato, "The capacity of the Gaussian interference channel under strong interference," *IEEE Trans. Inf. Theory*, vol. 27, pp. 786–788, Nov. 1981.
- [13] M. H. M. Costa and A. A. El Gamal, "The capacity region of the discrete memoryless interference channel with strong interference," *IEEE Trans. Inf. Theory*, vol. 33, pp. 710–711, Sep. 1987.
- [14] R. Benzel, "The capacity region of a class of discrete additive degraded interference channels," *IEEE Trans. Inf. Theory*, vol. 25, pp. 228–231, Mar. 1979.
- [15] N. Liu and S. Ulukus, "The capacity region of a class of discrete degraded interference channels," *IEEE Trans. Inf. Theory*, vol. 54, pp. 4372–4378, Sep. 2008.
- [16] M. H. M. Costa, "On the Gaussian interference channel," *IEEE Trans. Inf. Theory*, vol. 31, pp. 607–615, Sept. 1985.

41

- [17] I. Sason, "On achievable rate regions for the Gaussian interference channels," *IEEE Trans. Inf. Theory*, vol. 50, pp. 1345–1356, June 2004.
- [18] R. S. Cheng and S. Verd´u, "On limiting characterizations of memoryless multiuser capacity regions," *Trans. Inf. Theory*, vol. 39, pp. 609–612, 1993.
- [19] G. Kramer, "Outer bounds on the capacity of Gaussian interference channels," *IEEE Trans. Inf. Theory*, vol. 50, pp. 581–586, Mar. 2004.
- [20] R. H. Etkin, D. Tse, and H. Wang, "Gaussian interference channel capacity to within one bit," *IEEE Trans. Inf. Theory*, vol. 54, no. 12, pp. 5534–5562, Dec. 2008.
- [21] X. Shang, G. Kramer, and B. Chen, "A new outer bound and the noisy-interference sum-rate capacity for Gaussian interference channels," *IEEE Trans. Inf. Theory*, vol. 55, no. 2, pp. 689–699, Feb. 2009.
- [22] A. S. Motahari and A. K. Khandani, "Capacity bounds for the Gaussian interference channel," *IEEE Trans. Inf. Theory*, vol. 55, no. 2, pp. 620–643, Feb. 2009.
- [23] V. S. Annapureddy and V. V. Veeravalli, "Gaussian interference networks: Sum capacity in the low interference regime and new outer bounds on the capacity region," *IEEE Trans. Inf. Theory*, vol. 55, no. 7, pp. 3032–3050, Jul. 2009.
- [24] X. Shang, G. Kramer, and B. Chen, "New outer bounds on the capacity region of Gaussian interference channels," in *Proc. IEEE International Symposium on Information Theory*, Toronto, Canada, Jul. 2008, pp. 245 – 249.
- [25] X. Shang, G. Kramer, and B. Chen, "Throughput optimization for multi-user interference channels," in *Proc. IEEE Military Communications Conference*, San Diego, CA, Nov. 2008, pp. 1–7.
- [26] Y. Weng and D. Tuninetti, "On Gaussian interference channels with mixed interference," in *Proc. Information Theory and Applications Workshop*, San Diego, CA, Jan. 2008, [Online]. Available: http://ita.ucsa/workshop/08/files/paper/paper 264.pdf.
- [27] S. Vishwanath and S. A. Jafar, "On the capacity of vector Gaussian interference channels," in *Proc. IEEE Information Theory Workshop*, San Antonio, TX, Oct. 2004, pp. 365–369.
- [28] X. Shang, B. Chen, and M. J. Gans, "On achievable sum rate for MIMO interference channels," *IEEE Trans. Inf. Theory*, vol. 52, no. 9, pp. 4313–4320, Sep. 2006.
- [29] E. Telatar and D. Tse, "Bounds on the capacity region of a class of interference channels," in *Proc. IEEE International Symposium on Information Theory*, Nice, France, Jun. 2007, pp. 2871–2874.
- [30] X. Shang, B. Chen, G. Kramer, and H. V. Poor, "On the capacity of MIMO interference channels," in *Proc.* 46*th Annual Allerton Conference on Communication, Control, and Computing*, Monticello, IL, Sep. 2008, pp. 700–707.
- [31] X. Shang, B. Chen, G. Kramer, and H. V. Poor, "Capacity regions and sum-rate capacities of vector Gaussian interference channels," *IEEE Trans. Inf. Theory*, vol. 56, no. 10, pp. 5030–5044, Oct. 2010.
- [32] V. S. Annapureddy and V. V. Veeravalli, "Sum capacity of MIMO interference channels in the low interference regime," submitted to *IEEE Trans. Inf. Theory. http://arxiv.org/abs/0909.2074*, Sep. 2009.
- [33] X. Shang, B. Chen, G. Kramer, and H. V. Poor, "Noisy-interference sum-rate capacity of parallel Gaussian interference channels," *IEEE Trans. Inf. Theory*, vol. 57, no. 1, pp. 210–226, Jan. 2011.
- [34] X. Shang and B. Chen, "Achievable rate region for downlink beamforming in the presence of interference," in *Proc. 41st Asilomar Conference on Signals, Systems, and Computers*, Pacific Grove, CA, Nov. 2007, pp. 1684–1688.
- [35] X. Shang, B. Chen, and H. V. Poor, "Multi-user MISO interference channels with single-user detection: optimality of beamforming and the achievable rate region," *IEEE Trans. Inf. Theory,* to appear *, http://arxiv.org/abs/0907.0505*, Apr. 2009.
- [36] R. Zhang and S. Cui, "Cooperative interference management with MISO beamforming," *IEEE Trans. Signal Processing*, vol. 58, pp. 5450–5458, Oct. 2010.
- [37] R. Mochaourab and E. Jorswieck, "Optimal beamforming in interference networks with perfect local channel information," submitted to *IEEE Trans. Signal Processing, http://arxiv.org/abs/1004.4492*, Oct. 2010.
- [38] R. A. Horn and C. R. Johnson, *Matrix Analysis*, Cambridge University Press, New York, 1985.
- [39] D. P. Bertsekas, A. Nedic, and A. E. Ozdaglar, *Convex Analysis and Optimization*, Athena Scientific, Belmont, MA, 2003.
- [40] S. R. Searle, *Matrix Algebra Useful for Statistics*, John Wiley & Sons, Inc., New York, 1982.
- [41] R. H. Bartels and G. W. Stewart, "Solution of the matrix equation AX + XB = C," *Communications of the ACM*, vol. 15, pp. 820–826, Sep. 1972.
- [42] J. C. Engwerda, A. C. M. Ran, and A. L. Rijkeboer, "Necessary and sufficient conditions for the existence of a positive definite solution of the matrix equation $X + A^*X^{-1}A = Q$," *Linear Algebra and Its Applications*, vol. 186, pp. 255–275, 1993.
- [43] S. N. Diggavi and T. M. Cover, "The worst additive noise under a covariance constraint," *IEEE Trans. Inf. Theory*, vol. 47, no. 7, pp. 3072–3081, Nov. 2001.