

Evangelism in Social Networks: Algorithms and Complexity*

Gennaro Cordasco

Seconda Università degli studi di Napoli, Caserta, Italy
 gennaro.cordasco@unina2.it

Luisa Gargano, Adele Anna Rescigno and Ugo Vaccaro
 Università degli Studi di Salerno, Fisciano, Italy
 {lgargano,arescigno,uvaccaro}@unisa.it

April 18, 2022

Abstract

We consider a population of interconnected individuals that, with respect to a piece of information, at each time instant can be subdivided into three (time-dependent) categories: *agnostics*, *influenced*, and *evangelists*. A dynamical process of information diffusion evolves among the individuals of the population according to the following rules. Initially, all individuals are agnostic. Then, a set of people is chosen from the outside and convinced to start evangelizing, i.e., to start spreading the information. When a number of evangelists, greater than a given threshold, communicate with a node v , the node v becomes influenced, whereas, as soon as the individual v is contacted by a sufficiently *much larger* number of evangelists, it is itself converted into an evangelist and consequently it starts spreading the information. The question is: How to choose a bounded cardinality initial set of evangelists so as to maximize the final number of *influenced* individuals? We prove that the problem is hard to solve, even in an approximate sense. On the positive side, we present exact polynomial time algorithms for trees and complete graphs. For general graphs, we derive exact parameterized algorithms. We also investigate the problem when the objective is to select a minimum number of evangelists capable of influencing the whole network. Our motivations to study these problems come from the areas of Viral Marketing and the analysis of quantitative models of spreading of influence in social networks.

1 The Context

Customer Evangelism [32] occurs when a customer *actively* tries to convince other customers to buy or use a particular brand. Fathered by Apple marketing *guru* Guy Kawasaki in the 90's [27], the idea of consumer evangelism has found a new and more powerful incarnation in modern communications media. Social networks like Twitter, Facebook and Pinterest have indeed immensely

*An extended abstract of this paper was presented at the 27th International Workshop on Combinatorial Algorithms (IWOCA 2016), Helsinki, Finland, August 17–19, 2016 [14]

empowered properly motivated individuals towards brand advocacy and proselytism. We plan to abstract a few algorithmic problems out of this scenario, and provide efficient solutions for some of them.

2 The Problem

Our model posits an interconnected population consisting of individuals that, with respect to a piece of information and/or an opinion, at each time instant can be subdivided into three time-dependent categories: *agnostics*, *influenced*, and *evangelists*. Initially, all individuals are agnostic. Then, a set of people is chosen and converted into evangelists, that is, convinced to start spreading the information. When a sufficiently large number of evangelists communicate with an node v , the node v becomes influenced; as soon as the individual v has in his neighborhood a *much larger* number of evangelists, it is converted to an evangelist and *only then* it starts spreading the information itself. Our model can be seen also as an idealization of diffusion processes studied in the area of memetics. A *meme* [18] is a conviction, behavior, or fashion that spreads from person to person within a culture. It is apparent that not every meme learned by a person spreads among the individuals of a population. We are making here the reasonable hypothesis that individuals indeed acquire a meme when it has been heard of from a few friends, but people start spreading the same meme only when they believe it is popular, fashionable, or important, i.e., when it has been communicated to them by a *large* number of friends. This is not too far from what has been experimentally observed about how memes evolve and spread within Facebook [2].

A bit more concretely, we are given a graph $G = (V, E)$, abstracting a social network, where the node set V corresponds to people and the edge set to relationships among them. We denote by $N_G(v)$ the neighborhood of node $v \in V$ and by $d_G(v) = |N_G(v)|$ the degree of v in G , we avoid the subscript G whenever the graph is clear from the context. Moreover, let $t_I : V \rightarrow \{0, 1, 2, \dots\}$ and $t_E : V \rightarrow \{0, 1, 2, \dots\}$ be two functions assigning integer thresholds to the nodes in G such that $0 \leq t_I(v) \leq t_E(v) \leq d(v) + 1$, for each $v \in V$.

An evangelization process in G , starting at a subset of nodes $S \subseteq V$, is characterized by two sequences of node subsets

$$\text{Evg}[S, 0] \subseteq \text{Evg}[S, 1] \subseteq \dots \subseteq \text{Evg}[S, \tau] \subseteq \dots \subseteq V,$$

and

$$\text{Inf}[S, 0] \subseteq \text{Inf}[S, 1] \subseteq \dots \subseteq \text{Inf}[S, \tau] \subseteq \dots \subseteq V,$$

where for each $\tau = 0, 1, \dots$, it holds that $\text{Evg}[S, \tau] \subseteq \text{Inf}[S, \tau]$. The process is formally described by the following dynamics:

$$\begin{aligned} \text{Evg}[S, 0] &= \text{Inf}[S, 0] = S, \text{ and for each } \tau \geq 1 \\ \text{Evg}[S, \tau] &= \text{Evg}[S, \tau-1] \cup \left\{ u : |N(u) \cap \text{Evg}[S, \tau-1]| \geq t_E(u) \right\}, \\ \text{Inf}[S, \tau] &= \text{Inf}[S, \tau-1] \cup \left\{ u : |N(u) \cap \text{Evg}[S, \tau-1]| \geq t_I(u) \right\}. \end{aligned}$$

In words, a node v becomes influenced if the number of its evangelist neighbors is greater than or equal to its influence threshold $t_I(v)$, and v becomes an evangelist if the number of evangelists among its neighbors reaches its evangelization threshold $t_E(v) \geq t_I(v)$. The process terminates when $\text{Evg}[S, \rho] = \text{Evg}[S, \rho - 1]$ for some $\rho \geq 0$. We denote by $\text{Evg}[S] = \text{Evg}[S, \rho]$ and $\text{Inf}[S] = \text{Inf}[S, \rho]$ the final sets when the process terminates. The initial set S is also denoted as a *seed set* of the evangelization process. Due to foreseeable difficulties in hiring evangelists, it seems reasonable trying to limit their initial number, and see how the dynamics of the spreading process evolves. Therefore, we state our problems as follows:

MAXIMALLY EVANGELIZING SET (MES).

Instance: A graph $G = (V, E)$, thresholds $t_I, t_E : V \rightarrow \{0, 1, 2, \dots\}$, and a budget β .

Question: Find a seed set $S \subseteq V$, with $|S| \leq \beta$, such that $|\text{Inf}[S]|$ is *maximum*.

PERFECT EVANGELIZING SET (PES).

Instance: A graph $G = (V, E)$, thresholds $t_I, t_E : V \rightarrow \{0, 1, 2, \dots\}$.

Question: Find a seed set $S \subseteq V$ of *minimum size* such that $\text{Inf}[S] = V$.

It is worth to mention that the PES problem is, in a sense, easier than the MES problem. Indeed, any algorithm that solves the MES problem can be easily adapted to the PES problem by means of a standard binary search argument, while the opposite it is not true.

3 What is already known and what we prove

The above algorithmic problems have roots in the broad area of the *spread of influence* in Social Networks (see [6, 21] and references quoted therein). In the introduction of this paper we have already highlighted the connections of our model to the general area of viral marketing. There, companies wanting to promote products or behaviors might try initially to target and

convince a few individuals which, by word-of-mouth effects, can trigger a cascade of influence in the network, leading to an adoption of the products by a much larger number of individuals. Not unexpectedly, viral marketing has also become an important tool in the communication strategies of politicians [31, 35]. Less secular applications of our evangelization process can also be envisioned. Here, we shall limit ourselves to discuss the work that is most directly related to ours, and refer the reader to the authoritative texts [6, 21] for a synopsis of the area. The first authors to study spread of influence in networks from an algorithmic point of view were Kempe *et al.*, see [28]. However, they were mostly interested in networks with randomly chosen thresholds. Chen [5] studied the following minimization problem: given an unweighted graph G and fixed thresholds $t(v)$, for each vertex v in G , find a set of minimum size that eventually influences all (or a fixed fraction of) the nodes of G . He proved a strong inapproximability result that makes unlikely the existence of an algorithm with approximation factor better than $O(2^{\log^{1-\epsilon} |V|})$. Chen's result stimulated a series of papers, e.g., [1, 3, 4, 7, 8, 9, 10, 11, 12, 13, 26, 29, 33, 34] that isolated interesting cases in which the problem (and variants thereof) become tractable.

All of the above quoted papers considered the basic model in which *any* node, as soon as it is influenced by its neighbors, immediately starts spreading influence. The more refined model put forward in this paper, that differentiate among active spreaders (evangelists) and plain informed (influenced) nodes, appears to be new, to the best of our knowledge. We would like to point out that we obtain an interesting information diffusion model already in the particular case in which $t_I(v) = 1$, for each node v . In fact, in this case nodes in the sets $\text{Inf}[S, \tau]$ would correspond to people that have simply *heard* about a piece of information, while people in the sets $\text{Evg}[S, \tau]$ would correspond to people who are *actively* spreading that same piece of information.

In Section 4, we first prove that the MES problem is hard to solve, even in the approximate sense. Subsequently, we design exact algorithms, for the MES problem, parameterized with respect to neighborhood diversity (and, as a byproduct, by vertex cover) and for the PES problem parameterized with respect to the treewidth. In Section 6, we present exact polynomial time algorithms for the MES problem on complete graphs and trees. Finally, in Section 7 we study the PES problem in dense graphs.

4 MES is hard, also to approximate

The MES problem includes the INFLUENCE MAXIMIZATION (IM) problem [28], that is known to be NP-hard to approximate within a ratio of $n^{1-\epsilon}$, for any $\epsilon > 0$. In our terminology, the IM

problem takes in input a graph G with a threshold function $t : V \rightarrow \{0, 1, 2, \dots\}$ and a budget β , and asks for a subset S of β nodes of G such that $|\text{Evg}[S]|$ is maximum. An instance of the IM problem corresponds to the MES instance consisting of G , β , and threshold functions t_E, t_I , with $t_I(v) = t_E(v) = t(v)$, for each $v \in V$. Here we show that the MES problem remains hard even if the influence threshold t_I is equal to 1, for each node $v \in V$.

Theorem 1. *It is NP-hard to approximate the MES problem within a ratio of $n^{1-\epsilon}$ for any $\epsilon > 0$ even when $t_I(v) = 1$, for each node $v \in V$.*

Proof. We construct a gap-preserving reduction from the INFLUENCE MAXIMIZATION (IM) problem. The theorem follows from the inapproximability of influence maximization problem proved in [28]. Consider an instance of the IM problem consisting in a graph $G = (V, E)$ with threshold function $t(\cdot)$ and bound β . Let $V = \{v_1, \dots, v_n\}$, we build a graph $G' = (V', E')$ having $n(n+1)$ nodes, as follows:

- Replace each $v_i \in V$ by a gadget G'_i consisting in a star in which the node set is $V'_i = \{v_{i,0}, v_{i,1}, \dots, v_{i,n}\}$ and the center $v_{i,0}$ is connected with each of the other nodes $v_{i,1}, \dots, v_{i,n}$. Formally,

$$-V' = \bigcup_{i=1}^n V'_i = \{v_{i,j} \mid 1 \leq i \leq n, 0 \leq j \leq n\}$$

$$-E' = \{(v_{i,0}, v_{\ell,0}) \mid 1 \leq i < \ell \leq n, (v_i, v_\ell) \in E\} \cup \{(v_{i,0}, v_{i,j}), \text{ for } i, j = 1, \dots, n\}.$$

- the node $v_{i,0}$ has threshold $t_E(v_{i,0}) = t(v_i)$, while each other node $v_{i,j} \in V'_i$ with $j \geq 1$ has $t_E(v_{i,j}) = 1$, for $i = 1, \dots, n$.

Notice that G corresponds to the subgraph of G' induced by the set $\{v_{i,0} \mid 1 \leq i \leq n\}$. Hence, for each star G'_i in G' , the center $v_{i,0}$ plays the role of v_i in G . Moreover, it is worth mentioning that during an evangelization process in G' if the node $v_{i,0}$ in the gadget G'_i is an evangelist, then all the nodes in V'_i will be influenced within the next round.

We prove that: *There exists a seed set $S \subseteq V$ for G of size $|S| = \beta$ s.t. $|\text{Evg}_G[S]| \geq k$ iff there exists a seed set $S' \subseteq V'$ for G' of cardinality $|S'| = \beta$ such that $|\text{Inf}_{G'}[S']| \geq k(n+1)$.*

Assume that $S \subseteq V$ is a seed set for G such that $|S| = \beta$ and $|\text{Evg}_G[S]| \geq k$, we can easily build a seed set for G' as $S' = \{v_{i,0} \in V' \mid v_i \in S\}$. Clearly, $|S'| = |S|$. To see that $|\text{Inf}_{G'}[S']| \geq k(n+1)$ we notice that since G is isomorphic to the subgraph of G' induced by $\{v_{i,0} \in V' \mid v_i \in S\}$, all the nodes $v_{i,0} \in V'_i$ such that $v_i \in \text{Evg}_G[S]$ will become evangelists. Then

once a node $v_{i,0}$ becomes an evangelist, the nodes $\{v_{i,1}, v_{i,2}, \dots, v_{i,n}\}$ will be influenced in the next round. Hence $|\text{Inf}_{G'}[S']| \geq (n+1) \times |\text{Evg}_G[S]| \geq k(n+1)$.

On the other hand, assume that $S' \subseteq V'$ is a seed set for G' such that $|S'| = \beta$ and $|\text{Inf}_{G'}[S']| \geq k(n+1)$, we can easily build a seed set for G as $S = \{v_i \in V \mid S' \cap V'_i \neq \emptyset\}$. By construction $|S| \leq |S'|$. Let $S'' = \{v_{i,0} \in V' \mid S' \cap V'_i \neq \emptyset\}$. It is easy to observe that $|\text{Inf}_{G'}[S'']| = |\text{Inf}_{G'}[S']| \geq k(n+1)$. Let $V'_0 = \{v_{i,0} \mid 1 \leq i \leq n\}$; to see that $|\text{Evg}_G[S]| \geq k$ we will show that $|\text{Evg}_{G'}[S''] \cap V'_0| \geq k$. The result will follow since G is isomorphic to the subgraph of G' induced by V'_0 . In order to show that $|\text{Evg}_{G'}[S''] \cap V'_0| \geq k$, we first observe that $|\text{Inf}_{G'}[S''] \cap (V' - V'_0)| \geq |\text{Inf}_{G'}[S'']| - |V'_0| \geq k(n+1) - n$. Nodes in $V' - V'_0$ can be influenced only by nodes in V'_0 . Moreover, a node in V'_0 can influence at most n nodes in $V' - V'_0$ —the leaves of the star of which it is the center. Hence in order to influence $k(n+1) - n$ nodes in $V' - V'_0$ at least $\left\lceil \frac{k(n+1)-n}{n} \right\rceil \geq k$ nodes must be evangelist among those in V'_0 and consequently $|\text{Evg}_{G'}[S''] \cap V'_0| \geq k$.

□

5 Parameterized complexity

A parameterized computational problem with input size n and parameter t is called *fixed parameter tractable (FPT)* if it can be solved in time $f(t) \cdot n^c$, where f is a function depending on t only, and c is a constant [19]. In this section we study the effect of some parameters on the computational complexity of the MES and PES problems.

5.1 Parameterization of MES with Neighborhood Diversity.

We consider the decision version (α, β) -MES of the problem. It takes in input a graph $G = (V, E)$, node thresholds $t_I : V \rightarrow \{0, 1, 2, \dots\}$ and $t_E : V \rightarrow \{0, 1, 2, \dots\}$, and integer bounds $\alpha, \beta \in \mathbb{N}$, and asks if there exists a seed set $S \subseteq V$ such that $|S| \leq \beta$ and $|\text{Inf}[S]| \geq \alpha$.

We notice that by conveniently choosing the thresholds t_E and t_I , the MES problem specializes in problems whose parameterized complexity is well known. When $t_I(v) = t_E(v)$ for each $v \in V$ and $\alpha = |V|$, the problem becomes the *target set selection* [5]. This problem is $W[2]$ -hard¹ with respect to the solution size β [33], it is XP when parameterized with respect to the treewidth [4], and is $W[1]$ -hard with respect to the parameters treewidth, cluster vertex deletion number and pathwidth [4, 8]. Moreover, the target set selection problem becomes

¹See [19] for definitions of $W[2]$ -hardness, $W[1]$ -hardness and the class XP.

fixed-parameter tractable with respect to the single parameters: Vertex cover number, feedback edge set size, bandwidth [8, 33]. In general when $t_I(v) = t_E(v)$ for each $v \in V$, the (α, β) -MES problem has no parameterized approximation algorithm with respect to the parameter β and it is $W[1]$ -hard with respect to the combined parameters α and β [3]. Moreover, the target set selection problem is $W[1]$ -hard parameterized by the neighborhood diversity of the input graph [20].

In the following, we study the parameterized complexity of the (α, β) -MES problem for the general case $t_I(v) \neq t_E(v)$. We concentrate our attention on two parameters: the neighborhood diversity and the vertex cover size.

The *neighborhood diversity* was first introduced in [30]. It has recently received particular attention [20, 22, 24, 25] also due to its property of being computable in polynomial time [30]—unlike other parameters, including treewidth, rankwidth, and vertex cover.

Definition 1. *Given a graph $G = (V, E)$, two nodes $u, v \in V$ have the same type iff $N(v) \setminus \{u\} = N(u) \setminus \{v\}$. The graph G has neighborhood diversity t , if there exists a partition of V into at most t sets, V_1, V_2, \dots, V_t , s.t. all the nodes in V_i have the same type, for $i = 1, \dots, t$. The family $\mathcal{V} = \{V_1, V_2, \dots, V_t\}$ is called the type partition of G .*

Let $G = (V, E)$ be a graph with type partition $\mathcal{V} = \{V_1, V_2, \dots, V_t\}$. By Definition 1, each V_i induces either a clique or an independent set in G . For each $V_i, V_j \in \mathcal{V}$, we get that either each node in V_i is a neighbor of each node in V_j or no node in V_i has a neighbor in V_j . Hence, all the nodes in the same V_i have the same neighborhood $N(V_i)$ —excluding the nodes in V_i itself.

We present a FPT-algorithm for the MES problem with parameters t and β . At the end of the evangelization process in G starting at S , we identify the number of evangelists that are neighbors of (all) the nodes in V_i and define for each $i = 1, 2, \dots, t$,

$$N_i(S) = \begin{cases} |\text{Evg}[S] \cap N(V_i)| & \text{if } V_i \text{ is an independent set,} \\ |\text{Evg}[S] \cap (V_i \cup N(V_i))| & \text{if } V_i \text{ is a clique.} \end{cases}$$

It is easy to see that a node $u \in V_i - \text{Evg}[S]$ is influenced if $t_I(u) \leq N_i(S)$.

The proposed algorithm will be based on the following Lemma.

Lemma 1. *Let S' be a seed set for G . Let $u, v \in V_i$ be s.t. $u \in S'$ and $v \notin S'$, and consider the set $S'' = (S' - \{u\}) \cup \{v\}$. If $t_I(v) > N_i(S')$ then $\text{Inf}[S'] \subseteq \text{Inf}[S'']$.*

Proof. Consider a seed set S' for G . For $u, v \in V_i$ such that $u \in S'$ and $v \notin S'$ consider $S'' = (S' - \{u\}) \cup \{v\}$.

It is trivial to see that after the first round of the evangelization process with seed set S'' , the number of influenced nodes (resp. of evangelists) in each $V_i \in \mathcal{V}$ is the same as with seed set S' . Namely,

$$|N(v) \cap S'| = |N(u) \cap S''| \text{ and } |N(w) \cap S'| = |N(w) \cap S''| \text{ for each } w \in V - \{u, v\}. \quad (1)$$

Let $t_I(v) > N_i(S')$. Note that since $t_E(v) \geq t_I(v) > N_i(S')$, node v does not take part to make any node an evangelist in the evangelization process starting at S' . To prove the lemma we distinguish two cases according to the value of $t_E(u)$.

- If $t_E(u) \leq N_i(S')$ then there exists a round i of the process starting at S' in which u becomes an evangelist, that is, $|N(u) \cap \text{Evg}[S', i - 1]| \geq t_E(u)$. Consider now the evangelization process starting at S'' . By (1), the effect on any node of the process starting at S'' at the end of the first round is the same of the process starting at S' at the end of the first round. Furthermore, till round $i - 1$ of the process starting at S'' , the evangelists and the influenced nodes are exactly the same of the corresponding ones of the process starting at S' . Hence at round i of the process starting at S'' , node u becomes an evangelist and $\text{Evg}[S', i] \subseteq \text{Evg}[S'', i]$. In the following rounds $j > i$ the relation $\text{Evg}[S', j] \subseteq \text{Evg}[S'', j]$ is retained, and at the end of the process we have $\text{Evg}[S'] \subseteq \text{Evg}[S'']$. Since $\text{Evg}[S'] \subseteq \text{Evg}[S'']$ implies $\text{Inf}[S'] \subseteq \text{Inf}[S'']$, the lemma is proved in this case.

- Let $t_E(u) < N_i(S')$. By (1) and considering that during the process starting at S'' , the set of evangelists grows exactly as the set of evangelists in the process starting at S' we have that the evangelization process starting at S'' proceeds exactly as the process starting at S' and at the end of the process it holds $\text{Evg}[S'] = \text{Evg}[S'']$ and $\text{Inf}[S'] = \text{Inf}[S'']$. \square

We now present our algorithm. We assume that the nodes of G are sorted in order of non-increasing evangelization thresholds and consider all the possible t -ples (s_1, s_2, \dots, s_t) such that $\sum_{i=1}^t s_i = \beta$. For each $\mathbf{s} = (s_1, s_2, \dots, s_t)$ we construct the set $S_{\mathbf{s}}$ in two steps. In the first step we set $S_{\mathbf{s}} = \cup_{i=1}^t S_i$ where S_i is obtained by choosing s_i nodes with the largest evangelization threshold in V_i . In the second step we first consider the evangelization process in G starting at $S_{\mathbf{s}}$ and then we update each S_i by using the nodes that have not been influenced in the process. In particular, S_i is updated by replacing as many nodes as possible among those that could be influenced (if outside S_i) by nodes that cannot be influenced. The construction of $S_{\mathbf{s}}$ is detailed in algorithm ME-ND(\mathbf{s}, \mathcal{V}). We then consider the evangelization process in G starting at $S_{\mathbf{s}}$ and get the number $\alpha_{\mathbf{s}} = |\text{Inf}[S_{\mathbf{s}}]|$ of influenced nodes at the end of the process. Finally, we

determine $\mathbf{s}' = \arg \max_{\mathbf{s}} \alpha_{\mathbf{s}}$ and compare α with $\alpha_{\mathbf{s}'}$. If $\alpha_{\mathbf{s}'} \geq \alpha$ then we answer YES to the MES question for G with parameters α and β and $S_{\mathbf{s}'}$ is the desired seed set; otherwise we answer NO.

Algorithm 1: ME-ND(\mathbf{s}, G)

Input: A graph $G = (V, E)$, threshold functions t_I and t_E and $\mathbf{s} = (s_1, s_2, \dots, s_t)$; a type partition of G .

Output: $S_{\mathbf{s}} = \cup_{i=1}^t S_i$, a seed set for G such that for each $i = 1, 2, \dots, t$, $s_i = |S_i|$

- 1 **foreach** $i = 1, \dots, t$ **do**
- 2 $\left[\begin{array}{l} \text{Let } S_i \text{ be a set of } s_i \text{ nodes of } V_i \text{ with the largest evangelization thresholds (e.g., for} \\ \text{any } u \in S_i \text{ and } v \in V_i - S_i \text{ it holds } t_E(u) \geq t_E(v). \end{array} \right.$
- 3 Set $S_{\mathbf{s}} = \cup_{i=1}^t S_i$ and consider the process in G starting at $S_{\mathbf{s}}$.
- 4 **foreach** $i = 1, \dots, t$ **do** // Update set S_i ;
- 5 $\left[\begin{array}{l} \text{while } (\exists u \in S_i, t_I(u) \leq N_i(S_{\mathbf{s}}) \text{ AND } \exists v \in V_i - S_i, t_I(v) > N_i(S_{\mathbf{s}})) \text{ do} \\ \quad \left[\begin{array}{l} S_i = S_i - \{u\} \cup \{v\} \end{array} \right. \end{array} \right.$
- 7 **return** $S_{\mathbf{s}} = \cup_{i=1}^t S_i$

The Lemma 2 shows that the algorithm ME-ND provides an optimal seed set according to a fixed t -ple $\mathbf{s} = (s_1, s_2, \dots, s_t)$.

Lemma 2. *Let t be the neighborhood diversity of G . For any fixed t -ple $\mathbf{s} = (s_1, s_2, \dots, s_t)$, the algorithm ME-ND(\mathbf{s}, G) computes a seed set $S_{\mathbf{s}}$, such that $|\text{Inf}[S_{\mathbf{s}}]|$ is maximum among all the seed set S such that each $|S \cap V_i| = s_i$, for $i = 1, \dots, t$.*

Proof. Let $S_{\mathbf{s}} = \cup_{i=1}^t S_i$ be the seed set returned by the algorithm ME-ND(\mathbf{s}, G). Let now S' be any optimal seed set satisfying the decomposition \mathbf{s} , i.e., $|\text{Inf}[S']|$ is maximum among all the seed set S such that each $|S \cap V_i| = s_i$, for $i = 1, \dots, t$. We show that $|\text{Inf}[S_{\mathbf{s}}]| \geq |\text{Inf}[S']|$. To this aim, we iteratively transform each S'_i into S_i by trading a node $u \in S'_i - S_i$ for a node $v \in S_i - S'_i$ without decreasing the number of informed nodes.

- If we can choose v such that $t_I(v) > N_i(S')$ then by Lemma 1 we get that $S'' = (S' - \{u\}) \cup \{v\}$ has $|\text{Inf}[S'']| \geq |\text{Inf}[S']|$.
- Suppose now that for any choice of v it holds $t_I(v) \leq N_i(S')$. It is possible to see that the sets S_i (both as initially chosen at line 2 of the algorithm as well as after each update) maximize the number of evangelized nodes in each V_i and $N_i(S_{\mathbf{s}}) \geq N_i(\overline{S})$, for any seed set \overline{S} such $|\overline{S} \cap V_i| = s_i$, for $i = 1, \dots, t$. Hence,

$$N_i(S_{\mathbf{s}}) \geq N_i(S'), \quad \text{for } i = 1, \dots, t.$$

Furthermore, the construction of the sets S_i excludes the possibility that $t_I(u) > N_i(S_{\mathbf{s}})$ and $t_I(v) \leq N_i(S_{\mathbf{s}})$ (cfr. lines 5-6 of the algorithm). Therefore, we can assume that $t_I(u) < N_i(S_{\mathbf{s}})$ and $t_I(v) \leq N_i(S') \leq N_i(S_{\mathbf{s}})$ for each $u \in S'_i - S_i$ and $v \in S_i - S'_i$. In such a case, we have

$$\text{Inf}[S'] \cap V_i \subseteq S'_i \cup \{w \in V_i \mid t_I(w) \leq N_i(S_{\mathbf{s}})\} \subseteq V_i \cap \text{Inf}[S_{\mathbf{s}}].$$

Hence, $\text{Inf}[S'] \subseteq \text{Inf}[S_{\mathbf{s}}]$ and we can straight conclude that $|\text{Inf}[S_{\mathbf{s}}]| \geq |\text{Inf}[S']|$. \square

Theorem 2. *Let t be the neighborhood diversity of G . It is possible to decide the (α, β) -MES question in time $O(nt \cdot 2^{t \log(\beta+1)})$.*

Proof. For any possible $\mathbf{s} = (s_1, s_2, \dots, s_t)$, denote by $S_{\mathbf{s}}$ the output of Algorithm ME-ND(\mathbf{s}, G). We then consider the evangelization process in G starting at $S_{\mathbf{s}}$ and get the number $\alpha_{\mathbf{s}} = |\text{Inf}[S_{\mathbf{s}}]|$ of influenced nodes at the end of the process, which, thanks to Lemma 2, is optimal for the partitioning \mathbf{s} . Finally, we determine $\mathbf{s}' = \arg \max_{\mathbf{s}} \alpha_{\mathbf{s}}$ and comparing α with $\alpha_{\mathbf{s}'}$ we are able to answer the (α, β) -MES question.

Now we evaluate the running time of the algorithm. The number of all the possible t -ples $\mathbf{s} = (s_1, s_2, \dots, s_t)$ such that $\sum_{i=1}^t s_i = \beta$ is $\binom{\beta+t-1}{t-1} < 2^{t \log(\beta+1)}$. Moreover, one needs $O(nt)$ time to construct $S_{\mathbf{s}}$ and $O(nt)$ time to determine $|\text{Inf}[S_{\mathbf{s}}]|$. Hence, the time for deciding if a (α, β) -MES for G exists is $O(nt \cdot 2^{t \log(\beta+1)})$. \square

Noticing that the type partition \mathcal{V} can be obtained in polynomial time, one has that the (α, β) -MES problem is in the class FPT when parameterized by the neighborhood diversity t and the solution size β .

Theorem 2 can be used to also have FPT linear time algorithms with vertex cover size as parameter for (α, β) -MES. Indeed, graphs of bounded vertex cover have bounded neighborhood diversity—while the opposite is not true since large cliques have neighborhood diversity 1 [25].

Theorem 3. *Given a vertex cover of G of size ℓ , it is possible to decide the (α, β) -MES question in time $O(n(2^{\ell} + \ell)2^{(2^{\ell} + \ell) \log \ell})$.*

Proof. Let $\text{VC}(G)$ be a vertex cover of G with $|\text{VC}(G)| = \ell$. If $\beta \geq \ell$ then we can use $\text{VC}(G)$ as seed set. Indeed, since the nodes in $V - \text{VC}(G)$ are independent, after one round of the evangelization process in G starting at $\text{VC}(G)$ all the nodes in V are evangelist. Hence, since $|V| \geq \alpha$, we have proved the theorem for $\beta \geq \ell$.

Let $\beta < \ell$. Since G has vertex cover size ℓ , it cannot have a type partition with more than $2^\ell + \ell$ sets [25]. Hence, we use Theorem 2 with $t \leq 2^\ell + \ell$ and get the result. \square

5.2 Parameterization of PES with Treewidth.

Roughly speaking, the treewidth measures the “tree-likeness” of a given graph, in particular any tree has treewidth 1. We generalize the results given in [4] for the target set selection problem. We design an algorithm for the PERFECT EVANGELIC SET (PES) problem that runs in $n^{O(w)}$, where w is the treewidth of the input graph. If all the nodes have the same influence threshold we obtain that the problem is FPT.

Definition 2. A tree decomposition of a graph G is a pair $(\mathcal{T}, \mathcal{X})$, where \mathcal{X} is a family of subsets of $V(G)$, and \mathcal{T} is a tree over \mathcal{X} , satisfying the following conditions:

1. $\cup_{X \in \mathcal{X}} G[X] = G$, and
2. $\forall v \in V(G)$, $\{X \in \mathcal{X} \mid v \in X\}$ is connected in \mathcal{T} .

A tree decomposition $(\mathcal{T}, \mathcal{X})$ of a graph G is nice if \mathcal{T} is rooted, binary, each node $X \in \mathcal{X}$ has exactly w vertices, and is of one of the following three types:

- Leaf node. X is a leaf in \mathcal{T} and consists of w pairwise non-adjacent vertices of G .
- Replace node. X has one child Y in \mathcal{T} , s.t. $X - Y = \{u\}$ and $Y - X = \{v\}$ for $u \neq v$.
- Join node. X has two children Y and Z in \mathcal{T} with $X = Y = Z$.

The width of \mathcal{T} is $\max_{X \in \mathcal{X}} |X| - 1$. The treewidth of G is the minimum width over all tree (nice) decompositions of G .

The algorithm follows a dynamic programming approach computing a table, for each node X of a nice tree decomposition of G , that depends on the pair of thresholds of the vertices in X . Each entry in the table stores the smallest seed set for the subgraph $G[X]$ of G induced by the vertices of the subtree rooted at X . The desired seed set for G is the one corresponding to the root node of the tree decomposition of G . The proof follows the lines of the one in [4] for the target set selection problem (e.g. in the special case $t_E = t_I$), except for the role played by vertices that need to be influenced but not evangelized and by the influence thresholds in computing the entries of the table for each node X . We can prove the following result whose proof is omitted since, as said before, it is essentially patterned after the arguments of Section 3 of [4].

Theorem 4. In graphs of treewidth w the PES problem can be solved in $n^{O(w)}$ time.

6 Exact Polynomial Time Algorithms for MES

In this section we show that the MES problem is exactly solvable in polynomial time on complete graphs and trees.

6.1 Complete Graphs

Since the neighborhood diversity of a complete graph is 1 we already know that the MES problem is solvable in polynomial time on complete graphs. However, by observing that when $t = 1$, then $\mathbf{s} = (s_1)$ is a singleton and there a single 1-tuple available (i.e., $s_1 = \beta$), we can design an algorithm to solve the MES problem that is much simpler than the one described in Section 5. We show below the MES-K algorithm that represents a specialized, and more efficient, version of the ME-ND algorithm to complete graphs. By Lemma 2, that gives the correctness of the algorithm, we can prove the following Theorem.

Theorem 5. *In a complete graph with n nodes, the MES problem can be solved in $O(n)$ time.*

Algorithm 2: Algorithm MES -K(K, β)

Input: A clique $K = (V, E)$, threshold functions t_I and t_E , budget $\beta \leq |V|$.

Output: S a seed set for K such that $|S| \leq \beta$.

- 1 Let $X = \{v_1, v_2, \dots, v_\beta\}$ be a set of β nodes of V with the largest evangelization thresholds (i.e., for any $u \in X$ and $v \in V - X$ it holds $t_E(u) \geq t_I(v)$) and $\eta^* = |\text{Evg}[X]|$
 - 2 Set $S = X$
 - 3 **while** ($\exists u \in S, t_I(u) \leq \eta^*$ **AND** $\exists v \in V - S, t_I(v) > \eta^*$) **do**
 - 4 $S = S - \{u\} \cup \{v\}$
 - 5 **return** S
-

6.2 Trees

Thanks to Theorem 4, we know that the PES problem is solvable in polynomial time on graphs having constant treewidth. In the special case of trees, we are able to solve in polynomial time also the MES problem. In the following we give a dynamic programming algorithm that proves Theorem 6.

Theorem 6. *The MES problem with bound β can be solved in time $O(\min\{n\Delta^2\beta^3, n^2\beta^3\})$ on any tree with n nodes and maximum degree Δ .*

The rest of this section is devoted to the description and analysis of the algorithm proving Theorem 6. Let $T = (V, E)$ be a tree rooted at any node r and denote by $T(v)$ the subtree rooted at v , for $v \in V$. The algorithm makes a postorder traversal of the input tree T . For each node v , the algorithm solves all possible instances of the MES problem on the subtree $T(v)$, with bound $b \in \{0, 1, \dots, \beta\}$. Moreover, in order to compute these values one has to consider—for the root node v of $T(v)$ —not only the original thresholds $t_I(v)$ and $t_E(v)$ of v , but also the decremented values $t_I(v) - 1$ and $t_E(v) - 1$ which we call the *residual thresholds*. For each node $v \in V$ and integer $b \geq 0$ we define the following quantities:

$$\begin{aligned} NO_v[b] & \text{ is the maximum number of nodes that can be influenced in } T(v), & (2) \\ & \text{ assuming that at most } b \text{ of the nodes in } T(v) \text{ belong to the seed set,} \\ & \text{ if } v \text{ is still agnostic at the end of the evangelization process;} \end{aligned}$$

$$\begin{aligned} Inf_v[b] & \text{ is the maximum number of nodes that can be influenced in } T(v) & (3) \\ & \text{ assuming that at most } b \text{ of the nodes in } T(v) \text{ belong to the seed set,} \\ & \text{ if, at the end of the process, } v \text{ is influenced but it is not an evangelist;} \end{aligned}$$

$$\begin{aligned} Evg_v[b] & \text{ is the maximum number of nodes that can be influenced in } T(v) & (4) \\ & \text{ assuming that at most } b \text{ of the nodes in } T(v) \text{ belong to the seed set,} \\ & \text{ if } v \text{ is an evangelist at the end of the evangelization process.} \end{aligned}$$

Similarly the quantities $\widehat{NO}_v[b]$, $\widehat{Inf}_v[b]$ and $\widehat{Evg}_v[b]$ represent the same quantities as above but considering the decreased thresholds for v (which may reflect the fact that the parent node of v becomes an evangelist before v itself).

We define the above quantities be $-\infty$ if any of the constraints is not satisfiable. For instance, if v is a single node, $b = 0$ and $t_E(v) > 0$ we set² $Evg_v[0] = -\infty$.

Remark 1. *We mention that all the above quantities are monotonically non-decreasing in b and that $NO_v[b] \leq \widehat{NO}_v[b]$, $Inf_v[b] \leq \widehat{Inf}_v[b]$ and $Evg_v[b] \leq \widehat{Evg}_v[b]$.*

The maximum number of nodes in T that can be influenced with any seed set of size β can be then obtained by computing

$$\max\{NO_r[\beta], Inf_r[\beta], Evg_r[\beta]\}. \quad (5)$$

²Indeed v should be an evangelist, however the budget is 0 while the threshold is > 0 .

In order to obtain the value in (5), we compute the quantities³ $NO_v[b]$, $Inf_v[b]$, $Evg_v[b]$, $\widehat{NO}_v[b]$, $\widehat{Inf}_v[b]$ and $\widehat{Evg}_v[b]$ for each $v \in V$ and for each $b = 0, 1, \dots, \beta$.

We proceed postorder fashion on the tree, so that the computation of the various values for a node v is done after all the values for v 's children are known.

For each leaf node ℓ we have the values below. Recall that they refer to the tree $T(\ell)$ consisting of the single node ℓ .

The node ℓ will be not even influenced only if the budget is not sufficient to have ℓ in the seed set (e.g. $b = 0$) while the influence threshold is $t_I(\ell) > 0$. Hence,

$$NO_\ell[b] = \begin{cases} 0 & \text{if } (b = 0 \text{ AND } t_I(\ell) > 0) \\ -\infty & \text{otherwise,} \end{cases} \quad (6)$$

The node ℓ gets influenced but does not become an evangelist in case the budget is not sufficient to have ℓ in the seed set (e.g. $b = 0$) and the evangelization threshold is $t_E(\ell) > 0$, but the influence threshold is $t_I(\ell) = 0$. Hence,

$$Inf_\ell[b] = \begin{cases} 1 & \text{if } (b = 0 \text{ AND } t_I(\ell) = 0 \text{ AND } t_E(\ell) > 0) \\ -\infty & \text{otherwise.} \end{cases} \quad (7)$$

The node ℓ becomes evangelist in $T(\ell)$ when either the budget is sufficiently large to have ℓ in the seed set ($b \geq 1$) or its evangelization threshold is $t_E(\ell) = 0$. Hence,

$$Evg_\ell[b] = \begin{cases} 1 & \text{if } (b \geq 1 \text{ OR } t_E(\ell) = 0) \\ -\infty & \text{otherwise.} \end{cases} \quad (8)$$

The values for $\widehat{NO}_\ell[b]$, $\widehat{Inf}_\ell[b]$ and $\widehat{Evg}_\ell[b]$ are computed similarly by using on ℓ the residual thresholds ($t_I(\ell) - 1$ and $t_E(\ell) - 1$) instead of $t_I(\ell)$ and $t_E(\ell)$.

We show now that for any internal node v and for any integer $b \in \{0, \dots, \beta\}$, each of the values $NO_v[b]$, $Inf_v[b]$, $Evg_v[b]$, $\widehat{NO}_v[b]$, $\widehat{Inf}_v[b]$, and $\widehat{Evg}_v[b]$ can be computed in time $O(d^2b^2)$, where d is the number of children of v in T .

We recall that when computing one of the values $NO_v[b]$, $Inf_v[b]$, $Evg_v[b]$, $\widehat{NO}_v[b]$, $\widehat{Inf}_v[b]$ or $\widehat{Evg}_v[b]$, we already have computed all the values for each child v_i of v . We distinguish two cases: The computation of the values $NO_v[b]$ and $Inf_v[b]$ and the computation of the values $Evg_v[b]$.

1. Computation of $NO_v[b]$ and $Inf_v[b]$. In this case we know that v will not become evangelist. Hence, we do not use the budget for the node v itself and the computation of $NO_v[b]$

³For the root node r , the quantities $\widehat{NO}_r[b]$, $\widehat{Inf}_r[b]$ and $\widehat{Evg}_r[b]$ are not required.

and $Inf_v[b]$ must consider all the possible ways in which the whole budget b can be partitioned among v 's children.

Fact 1. *It is possible to compute $NO_v[b]$, $Inf_v[b]$, $\widehat{NO}_v[b]$ and $\widehat{Inf}_v[b]$, in time $O(d^2b^2)$, where d is the number of children of v .*

Proof. We focus our attention on $NO_v[b]$ and $Inf_v[b]$, the remaining values can be computed in the same way but for using the residual threshold $t_E(v) - 1$ and $t_I(v) - 1$ on v instead of original ones.

Fix an ordering v_1, v_2, \dots, v_d of the children of node v . For $i = 1, \dots, d$, $j = 0, \dots, b$ and $k = 0, \dots, d$, let $A_v[i, j, k]$ be the maximum number of nodes that can be influenced in the forest consisting of the (sub)trees $T(v_1), T(v_2), \dots, T(v_i)$, assuming that these trees contain at most j seeds altogether and that k among their roots v_1, v_2, \dots, v_i will become evangelist—in the respective tree. By (2) and (3) we have

$$NO_v[b] = \max_{k \in \{0, 1, \dots, t_I(v) - 1\}} A_v[d, b, k] \quad (9)$$

$$Inf_v[b] = \max_{k \in \{t_I(v), t_I(v) + 1, \dots, t_E(v) - 1\}} A_v[d, b, k] + 1. \quad (10)$$

We now show how to compute $A_v[d, b, k]$ for $k \in \{0, 1, \dots, t_E(v) - 1\}$ by recursively computing the values $A_v[i, j, k]$, for each $i = 1, 2, \dots, d$, $j = 0, 1, \dots, b$ and $k = 0, \dots, t_E(v) - 1$.

For $i = 1$, we assign all of the budget to $T(v_1)$ and

$$A_v[1, j, k] = \begin{cases} \max\{NO_{v_1}[j], Inf_{v_1}[j]\} & \text{if } k = 0 \\ Evg_{v_1}[j] & \text{if } k = 1 \\ -\infty & \text{if } k > 1. \end{cases}$$

For $i > 1$, we consider each $0 \leq a \leq j$: Budget a is assigned to the first $i - 1$ trees, while the remaining budget $j - a$ is assigned to $T(v_i)$. Hence,

$$A_v[i, j, k] = \max \begin{cases} \max_{0 \leq a \leq j} \{A_v[i-1, a, k] + \max\{NO_{v_i}[j-a], Inf_{v_i}[j-a]\}\} \\ \max_{0 \leq a \leq j} \{A_v[i-1, a, k-1] + Evg_{v_i}[j-a]\} \end{cases}$$

The computation of $A_v[\cdot, \cdot, \cdot]$ involves $O(d^2b)$ values, each recursively computed in time $O(b)$. Hence we are able to compute it—and by (9) and (10), also $NO_v[b]$ and $Inf_v[b]$ —in time $O(d^2b^2)$. \square

2. Computation of $Evg_v[b]$. We focus our attention on $Evg_v[b]$, the same reasoning applies to $\widehat{Evg}_v[b]$ by using the residual threshold on v instead of the original one. In this case we know that v will be an evangelist and we have two cases to consider depending whether v belongs to the seed set or not. In the following we will analyze the two cases separately. The desired value will be

$$Evg_v[b] = \max\{M_1, M_2\}, \quad (11)$$

where M_1 denotes the value one obtains assuming $v \in S$ and by M_2 denotes the value one obtains assuming $v \notin S$.

- $v \in S$. In this case we assume that $t_E(v) > 0$ (otherwise v would become an evangelist anyhow and it makes no sense to spend part of the budget to evangelize it). We consider $b \geq 1$ (otherwise $M_1 = -\infty$). Since $v \in S$ the computation of M_1 must consider all the possible ways in which the remaining budget $b - 1$ can be partitioned among v 's children.

Fact 2. M_1 is computable in time $O(db^2)$, where d is the number of children of v .

Proof. Fix an ordering v_1, v_2, \dots, v_d of the children of node v . For $i = 1, \dots, d$ and $j = 0, \dots, b$ let $B_v[i, j]$ be the maximum number of nodes that can be influenced in the first i subtrees $T(v_1), T(v_2), \dots, T(v_i)$ assuming that the seed set contains v and at most j among the nodes in such subtrees. By (4) we have

$$M_1 = B_v[d, b - 1] + 1. \quad (12)$$

We now show how to compute $B_v[d, b - 1]$ by recursively computing the values $B_v[i, j]$, for each $i = 1, 2, \dots, d$ and $j = 0, 1, \dots, b - 1$.

For $i = 1$, we assign all of the budget to $T(v_1)$ and

$$B_v[1, j] = \max \left\{ \widehat{NO}_{v_1}[j], \widehat{Inf}_{v_1}[j], \widehat{Evg}_{v_1}[j] \right\}.$$

For $i > 1$, we consider each $a \in \{0, \dots, j\}$ and assign budget a to the first $i - 1$ subtrees, while the remaining budget $j - a$ is assigned to $T(v_i)$. Hence,

$$B_v[i, j] = \max_{0 \leq a \leq j} \left\{ B_v[i-1, a] + \max \left\{ \widehat{NO}_{v_i}[j - a], \widehat{Inf}_{v_i}[j - a], \widehat{Evg}_{v_i}[j - a] \right\} \right\}.$$

The computation of B_v uses $O(db)$ values and each one is computed recursively in time $O(b)$. Hence, we are able to compute it and, by (12), M_1 , in time $O(db^2)$. \square

- $v \notin S$. In this case we know that v will be made an evangelist by the evangelic action of (some of) its children. Hence the computation of M_2 must consider all the possible ways in which the (whole) budget b can be partitioned among v 's children in such a way that at least $t_E(v)$ of v 's children become evangelists.

Fact 3. M_2 can be computed in time $O(d^2b^2)$, where d is the number of children of v .

Proof. Fix an ordering v_1, v_2, \dots, v_d of the children of the node v . For $i = 1, \dots, d$, $j = 0, \dots, b$, and $k = 0, \dots, d$, let $C_v[i, j, k]$ be the maximum number of nodes that can be influenced, in $T(v_1), T(v_2), \dots, T(v_i)$ assuming that: v will be an evangelist, at most j among the nodes in $T(v_1), \dots, T(v_i)$ belong to the seed set, and k among v_1, v_2, \dots, v_i will be evangelists (in the respective subtrees). By (4) we have

$$M_2 = \max_{k \geq t_E(v)} C_v[d, b, k] + 1. \quad (13)$$

We now show how to compute $C_v[d, b, k]$ for $k \in \{t_E(v), t_E(v) + 1, \dots, d\}$ by recursively computing the values $C_v[i, j, k]$, for each $i = 1, 2, \dots, d$, $j = 0, 1, \dots, b$ and $k = 0, \dots, d$.

For $i = 1$, we assign all of the budget to $T(v_1)$ and

$$C_v[1, j, k] = \begin{cases} \max \{ \widehat{NO}_{v_1}[j], \widehat{Inf}_{v_1}[j], \widehat{Evg}_{v_1}[j] \} & \text{if } k = 0 \\ \widehat{Evg}_{v_1}[j] & \text{if } k = 1 \\ -\infty & \text{if } k > 1. \end{cases}$$

Consider now $i > 1$. For each $a \in \{0, \dots, j\}$ we assign budget a to the first $i - 1$ subtrees, while the remaining budget $j - a$ is assigned to $T(v_i)$. Hence,

$$C_v[i, j, k] = \max \begin{cases} \max_{0 \leq a \leq j} \left\{ C_v[i-1, a, k] + \right. \\ \quad \left. \max \{ \widehat{NO}_{v_i}[j-a], \widehat{Inf}_{v_i}[j-a], \widehat{Evg}_{v_i}[j-a] \} \right\} \\ \max_{0 \leq a \leq j} \{ C_v[i-1, a, k-1] + \widehat{Evg}_{v_i}[j-a] \} \end{cases}$$

The computation of C_v comprises $O(d^2b)$ values and each one is computed recursively in time $O(b)$. Hence we are able to compute it, and by (13), also M_2 , in time $O(d^2b^2)$. \square

As a consequence of Facts 2 and 3 and equation 11, we are able to compute $\widehat{Evg}_v[b]$ and $\widehat{Evg}_v[b]$, in time $O(d^2b^2)$.

The above Facts 1-3, imply that the value $\max\{NO_r[\beta], Inf_r[\beta], Evgr[\beta]\}$ in (5) can be computed in time

$$\sum_{v \in V} O(d(v)^2 \beta^2) \times O(\beta) = O(\beta^3) \times \sum_{v \in V} O(d(v)^2) = O(\min\{n\Delta^2 \beta^3, n^2 \beta^3\}),$$

where Δ is the maximum node degree. Standard backtracking techniques can be used to compute a seed set of size at most β that influences this maximum number of nodes in the same $O(\min\{n\Delta^2 \beta^3, n^2 \beta^3\})$ time. This concludes the proof of Theorem 6. \square

7 The PES problem on Dense graphs

In this section we concentrate on the PES problem in graphs characterized by large minimum degree. In particular, we relate the graph minimum degree to the size of the smallest perfect seed set, e.g., a set $S \subseteq V$ such that $\text{Inf}[S] = V$.

Assuming that $t_I(v) \leq t_I$ and $t_E(v) \leq t_E$, for each $v \in V$, and $t_E + t_I \leq |V| + 2$, the algorithm $\text{PES}(G, t_E, t_I)$ selects and returns a set $S \subseteq V$, of size at most $2(t_E - 1)$, that we will prove to be a PES for G whenever the minimum degree of G is $\frac{|V| + t_E + t_I}{2} - 2$.

Algorithm 3: Algorithm $\text{PES}(G, t_E, t_I)$

Input: A graph $G = (V, E)$ having thresholds $t_I(v) \leq t_I$ and $t_E(v) \leq t_E$ for $v \in V$.

Output: S , a perfect seed set for G .

- 1 Set S as any subset of V such that
 - 2 - $|S| = t_I$ and
 - 3 - at least two nodes in S are independent, if possible [e.g., if G is not a clique],
 - 4 **while** ($|S| < 2(t_E - 1)$) **AND** ($\exists v \in V - S$ s.t. $|N(v) \cap S| \leq t_I - 1$) **do** $S = S \cup \{v\}$
 - 5 **return** S
-

The construction of the set S returned by the algorithm $\text{PES}(G, t_E, t_I)$, immediately implies the fact below.

Fact 4. 1) If $|S| < 2(t_E - 1)$ then each $v \in V - S$ has at least t_I neighbors in S .

2) If $|S| = 2(t_E - 1)$ then the sum of the degrees of the nodes in the subgraph induced by S in G is upper bounded by

$$[t_I(t_I - 1) - 2] + 2(t_I - 1)[2(t_E - 1) - t_I] = (t_I - 1)(4t_E - t_I - 4) - 2$$

if $t_I \geq 2$; it is 0 if $t_I = 1$.

Theorem 7. Let $G = (V, E)$ be a graph on n nodes with $t_I(v) \leq t_I$, $t_E(v) \leq t_E$, for each $v \in V$, where $t_E + t_I \leq n + 2$, and $d(v) \geq \frac{n+t_E+t_I}{2} - 2$, for each $v \in V$. The algorithm $\text{PES}(G, t_E, t_I)$ returns a PES for G of size at most $2t_E - 2$.

Proof. Consider the evangelization process in G starting at the set S returned by the algorithm $\text{PES}(G, t_E, t_I)$. Let $i \in \{0, 1, \dots\}$ be a round of the process and $a(i) = |\text{Evg}[S, i] - S|$ be the number of evangelists at round i that not belong to the seed set S . If $V - \text{Inf}[S, i] = \emptyset$ then each node in $V - \text{Evg}[S, i]$ has at least t_I neighbors in $\text{Evg}[S, i]$ and the theorem is proved. Assume then $V - \text{Inf}[S, i] \neq \emptyset$. By 1) of Fact 4, we know that $|S| = 2(t_E - 1)$. Let $\sigma(\text{Evg}[S, i])$ denote the number of edges in the subgraph of G induced by $\text{Evg}[S, i]$. In the following we assume that $t_I \geq 2$. The proof for $t_I = 1$ can be obtained similarly recalling that the value in 2) of Fact 4 is 0 in this case. By 2) of Fact 4 and since each node in $\text{Evg}[S, i] - S$ is connected at most to each other node in $\text{Evg}[S, i] \cup S$, we have that sum of the degrees of the nodes in the subgraph of G induced by $\text{Evg}[S, i]$ is

$$\begin{aligned} 2\sigma(\text{Evg}[S, i]) &\leq (t_I - 1)(4t_E - t_I - 4) - 2 + a(i)(a(i) - 1) + 2a(i)[2(t_E - 1)] \\ &= (t_I - 1)(4t_E - 4 - t_I) - 2 + a(i)^2 + a(i)(4t_E - 5) \end{aligned} \quad (14)$$

Recalling that $d(v) \geq \frac{n+t_E+t_I}{2} - 2$ for each $v \in V$, we get that the number $\sigma(\text{Evg}[S, i], V - \text{Evg}[S, i])$ of edges connecting one node in $\text{Evg}[S, i]$ and one in $V - \text{Evg}[S, i]$ is

$$\begin{aligned} \sigma(\text{Evg}[S, i], V - \text{Evg}[S, i]) &\geq \\ &\geq \frac{n+t_E+t_I-4}{2}[2(t_E-1)+a(i)] - [(t_I-1)(4t_E-4-t_I)-2 + a(i)^2 + a(i)(4t_E-5)] \\ &= (n+t_E+t_I-4)(t_E-1) - (t_I-1)(4t_E-4-t_I) + 2 - a(i)^2 + \\ &\quad + a(i)\left(\frac{n+t_E+t_I}{2} - 4t_E + 3\right) \\ &= (n+t_E-3t_I)(t_E-1) + (t_I-1)t_I + 2 - a(i)^2 + a(i)\left(\frac{n+t_E+t_I}{2} - 4t_E + 3\right) \end{aligned} \quad (15)$$

We first determine the minimum value of $a(i)$ that guaranties that at least one node $v \in V - \text{Evg}[S, i]$ becomes an evangelist at round $i + 1$. By contradiction assume that each node in $V -$

$\text{Evg}[S, i]$ has at most $t_E - 1$ neighbors in $\text{Evg}[S, i]$. This assumption implies that $\sigma(\text{Evg}[S, i], V - \text{Evg}[S, i]) \leq (n - 2(t_E - 1) - a(i))(t_E - 1)$

It is not hard to see that the lower bound in (15) is larger than the above upper bound when $0 \leq a(i) \leq \frac{n+t_E+t_I}{2} - 3t_E + 2$. This leads to a contradiction for such a range of values of $a(i)$. Hence, for each round i for which $0 \leq a(i) \leq \frac{n+t_E+t_I}{2} - 3t_E + 2$ at least one node $v \in V - \text{Evg}[S, i]$ moves from $V - \text{Evg}[S, i]$ to $\text{Evg}[S, i + 1]$ at round $i + 1$.

We show now that if $a(i) = \frac{n+t_E+t_I}{2} - 3t_E + 2$ (i.e., $|\text{Evg}[S, i + 1]| \geq 2(t_E - 1) + \frac{n+t_E+t_I}{2} - 3t_E + 3$) then $|V - \text{Inf}[S, i + 1]| = 0$, thus completing the proof.

Indeed, we have $|V - \text{Evg}[S, i + 1]| \leq n - [2(t_E - 1) + \frac{n+t_E+t_I}{2} - 3t_E + 3] = \frac{n - (t_E + t_I)}{2} + t_E - 1$. This implies that the number of evangelists among the neighbors of any node $v \in V - \text{Evg}[S, i + 1]$ is at least

$$\frac{n + t_E + t_I}{2} - 2 - \frac{n - (t_E + t_I)}{2} - t_E + 2 = t_I.$$

Hence, at round $i + 1$ each node in $V - \text{Evg}[S, i]$ is influenced. Therefore, $|V - \text{Inf}[S, i + 1]| = 0$. \square

We notice that in case $t_E = t_I = 2$, we reobtain the result for Dirac graphs given in [23].

Corollary 1. *Let G be a graph with $d(v) \geq \frac{n}{2}$, for each $v \in V$. The algorithm $\text{PES}(G, 2, 2)$ returns an optimal PES for G of size 2.*

References

- [1] E. Ackerman, O. Ben-Zwi and G. Wolfowitz. Combinatorial Model and Bounds for Target Set Selection. *Theoretical Computer Science*, Vol. 411, (2010), 4017–4022.
- [2] L.A. Adamic, T.M. Lento, E. Adar, P.C. Ng. Information Evolution in Social Networks, *Proc. of the 9th ACM Inter. Conference on Web Search and Data Mining*, (2016) 473–482
- [3] C. Bazgan, M. Chopin, A. Nichterlein and F. Sikora. Parametrized Approximability of Maximizing the Spread of Influence in Networks. *J. Discrete Algorithms*, Vol. 27, (2014), 54–65.
- [4] O. Ben-Zwi, D. Hermelin, D. Lokshтанov and I. Newman. Treewidth governs the complexity of target set selection. *Discrete Optimization*, 8, (2011), 87–96.
- [5] N. Chen. On the approximability of influence in social networks. *SIAM J. Discrete Math.*, 23, (2009), 1400–1415.
- [6] W. Chen, L. V.S. Lakshmanan, and C. Castillo. *Information and Influence Propagation in Social Networks*. Morgan & Claypool, (2013).
- [7] C.C. Centeno M.C. Dourado, L. Draque Penso, D. Rautenbach and J.L. Szwarcfiter. Irreversible conversion of graphs. *Theoretical Computer Science*, 412 (29), (2011), 3693–3700.

- [8] M. Chopin, A. Nichterlein, R. Niedermeier and M. Weller. Constant Thresholds Can Make Target Set Selection Tractable. *Theory of Computing Systems* vol. 55, (2014), 61–83.
- [9] C.-Y. Chiang, L.-H. Huang, B.-J. Li, J. Wu and H.-G. Yeh. Some results on the target set selection problem. *Journal of Combinatorial Optimization*, Vol. 25 (2013), 702–715.
- [10] F. Cicalese, G. Cordasco, L. Gargano, M. Milanič and U. Vaccaro. Latency-Bounded Target Set Selection in Social Networks. *Theoretical Computer Science*, Vol. 535, (2014), 1–15.
- [11] F. Cicalese, G. Cordasco, L. Gargano, M. Milanič, J. G. Peters and U. Vaccaro. Spread of Influence in Weighted Networks under Time and Budget Constraints. *Theoretical Computer Science*, Vol. 586, (2015), 40–58.
- [12] A. Coja-Oghlan, U. Feige, M. Krivelevich and D. Reichman. Contagious Sets in Expanders. In: *Proc. of the Twenty-Sixth Ann. ACM-SIAM Symp. on Discrete Algorithms*, (2015), 1953–1987.
- [13] G. Cordasco, L. Gargano, M. Mecchia, A. A. Rescigno, and U. Vaccaro. A Fast and Effective Heuristic for Discovering Small Target Sets in Social Networks, *Proc. of Combinatorial Optimization and Applications*, LNCS vol. 9486, (2015), pp. 193–208.
- [14] G. Cordasco, L. Gargano, A. A. Rescigno, and U. Vaccaro. Evangelism in Social Networks, *27th International Workshop on Combinatorial Algorithms (IWOCA2016)* Helsinki, Finland, August 17–19, 2016.
- [15] G. Cordasco, L. Gargano, A. A. Rescigno, and U. Vaccaro. Optimizing Spread of Influence in Social Networks via Partial Incentives. In *Structural Information and Communication Complexity: 22nd International Colloquium, SIROCCO 2015*, pages 119–134. Springer International Publishing, 2015.
- [16] G. Cordasco, L. Gargano, A. A. Rescigno, and U. Vaccaro. Brief announcement: Active information spread in networks. In *Proceedings of the 2016 ACM Symposium on Principles of Distributed Computing, PODC 16*, pages 435–437, New York, NY, USA, 2016. ACM.
- [17] G. Cordasco, L. Gargano, and A. A. Rescigno. On Finding Small Sets that Influence Large Networks. In *Social Network Analysis and Mining (SNAM)*, 2016. (To Appear).
- [18] R. Dawkins. *The Selfish Gene*, Oxford University Press, (1989).
- [19] R. G. Downey and M. R. Fellows. *Parameterized Complexity*, Springer, (2012).
- [20] P. Dvorák, D. Knop, and T. Toufar. Target Set Selection in Dense Graph Classes. arXiv:1610.07530, 2016.
- [21] D. Easley and J. Kleinberg. *Networks, Crowds, and Markets: Reasoning About a Highly Connected World*. Cambridge University Press, (2010).
- [22] J. Fiala, T. Gavenciak, D. Knop, M. Koutecky, J. Kratochvíl, Fixed parameter complexity of distance constrained labeling and uniform channel assignment problems, arXiv: arXiv:1507.00640, (2015).
- [23] D. Freund, M. Poloczek, and D. Reichman. Contagious Sets in Dense Graphs. *Proc. 26th International Workshop on Combinatorial Algorithms (IWOCA 2015)*, LNCS 9538, (2016).
- [24] R. Ganian, Using neighborhood diversity to solve hard problems, arXiv:1201.3091,(2012).
- [25] L. Gargano and A.A. Rescigno. Complexity of conflict-free colorings of graphs, *Theoretical Computer Science*, 566 (2015), 39–49.
- [26] L. Gargano, P. Hell, J. G. Peters, and U. Vaccaro. Influence Diffusion in Social Networks under Time Window Constraints. *Theoretical Computer Science*, vol. 584, (2015), 53–66.

- [27] G. Kawasaki. *Selling the Dream: How to Promote Your Product, Company, or Ideas and Make a Difference Using Everyday Evangelism*. New York: HarperCollins, (1991).
- [28] D. Kempe, J.M. Kleinberg, and E. Tardos. Maximizing the Spread of Influence through a Social Network. *Theory of Computing* 11: 105-147 (2015).
- [29] M. Lafond, L. Narayanan, and Kangkang Wu. Whom to befriend to influence people. *Proceedings of Sirocco '16*, to appear.
- [30] M. Lampis. Algorithmic Meta-theorems for Restrictions of Treewidth, *Algorithmica*, 64 (2011), 19–37.
- [31] M. Leppaniemi *et al.* Targeting Young Voters in a Political Campaign: Empirical Insights into an Interactive Digital Marketing Campaign in the 2007 Finnish General Election. *J. of Nonprofit & Public Sector Marketing*, vol. 22 (2010), 14–37.
- [32] B. McConnell and J. Huba. *Creating Customer Evangelists: How Loyal Customers Become a Volunteer Sales Force*, Lewis Lane Press, (2012).
- [33] A. Nichterlein, R. Niedermeier, J. Uhlmann, M. Weller. Tractable Cases of Target Set Selection. *Social Network Analysis and Mining*, (2012) 1–24.
- [34] T. V. T. Reddy and C. P. Rangan. Variants of spreading messages, *J. Graph Algorithms & Appl.*, 15(5), (2011), 683–699.
- [35] K. Tumulty. Obama’s Viral Marketing Campaign. *TIME Magazine*, July 5, (2007).