Monolingual and Cross-lingual Zero-shot Style Transfer

Elizaveta Korotkova Maksym Del Mark Fishel

Institute of Computer Science Universitu of Tartu, Estonia

{elizaveta.korotkova, maksym.del, fishel}@ut.ee

Abstract

We introduce the task of zero-shot style transfer between different languages. Our training data includes multilingual parallel corpora, but does not contain any parallel sentences between styles, similarly to the recent previous work. We propose a unified multilingual multi-style machine translation system design, that allows to perform zero-shot style conversions during inference; moreover, it does so both monolingually and cross-lingually. Our model allows to increase the presence of dissimilar styles in corpus by up to 3 times, easily learns to operate with various contractions, and provides reasonable lexicon swaps as we see from manual evaluation.

1 Introduction

It is crucial for intelligent natural language generation systems to produce text which is appropriate for the task at hand in terms of semantic content as well as style.

Due to the shortage of parallel corpora which could be used for learning to transfer style in a supervised fashion, much of recent work has been focusing on style transfer using non-parallel data (Prabhumoye et al., 2018; Mueller et al., 2017; Shen et al., 2017). The proposed approaches mostly involve learning style representations disentangled from semantic content. Other work has been based on paraphrase data (Carlson et al., 2017) or explicit attribute substitution (Li et al., 2018).

We do not rely on explicit separation between content and style representations nor on explicit attributes. Instead, we approach the problem from a different angle.

In this paper we propose a multilingual multistyle machine translation system that allows to modify stylistic traits of a sentence while also translating it into a different language. It uses

ideas from multilingual NMT (Johnson et al., 2016; Firat et al., 2016), while extending them to styles, and relies on source word factors as a key design choice (Sennrich and Haddow, 2016). We use no parallel data between styles, but still can perform cross-style conversions during inference; moreover, we do so cross-lingually.

In our experiments, we evaluate the proposed model incorporating three languages and three styles. The system shows strong results as a pure machine translation model as well, which provides for good meaning preservation and fluency in output texts. The system can be easily expanded to incorporate more languages and styles (though scaling up to more languages and styles is to be tested).

The paper contains the following contributions:

- Extends the task of style transfer to multiple languages resulting in cross-lingual style transfer
- Tackles the task of cross-lingual style transfer without parallel data between styles
- Proposes a unified multilingual multi-style system design that enables cross-lingual zero-shot style transfer

This paper is organized as follows. In Section 2, we formally state the problem we attempt to solve, that is, cross-lingual zero-shot style transfer. We then describe our general approach in Section 3 and specific details of the experiments, their results, and evaluation in Section 4. Some discussion points are put forward in Section 5. Related work in the field is summarized in Section 6. Finally, in Sections 7 and 8 we present our conclusions and plans for future work.



Figure 1: Machine Translation and Style Transfer tasks. Blue (dotted) line describes the usual Machine Translation task which is generally done inside a single domain. Yellow (dashed) line corresponds to Monolingual Style Transfer task. Red (solid) line represents Cross-lingual Style Transfer Task. If parallel data is available only between multiple languages inside one style (highlighted columns), and not between styles, then the red (solid) and yellow (dashed) lines correspond to Zero-shot Transfer Tasks.

2 Problem Statement

Let $L = \{l_1, l_2, ..., l_m\}$ be a set of languages and $S = \{s_1, s_2, ..., s_n\}$ a set of text styles¹.

Let $e(l_x, s_y)$ and $e(l_q, s_p)$ be sentences representing the same semantic content, but in different languages $(l_{x/q})$ and styles $(s_{y/p})$: $x, q \in \{1..m\}$, and $y, p \in \{1..n\}$, while $x \neq q$ and $y \neq p$.

Our task then is to learn the mapping between sentences like $e(l_x,s_y)$ and $e(l_q,s_p)$, which we call Cross-lingual Style Transfer. Refer to Figure 1 for more details and comparison to tasks of Monolingual Style Transfer and Machine Translation.

A key point is that we do not use any parallel data between styles neither monolingually inside a single language nor cross-lingually. Since the only data available is the data between different languages inside individual styles, the task becomes harder and result predictions can be called "Zero-shot".

3 Approach

For our attempt at cross-lingual style transfer, we train a factored multilingual neural machine translation system, passing the desired target language and style as factors (word features), token-parallel to source texts.

The source side of one training example e, where we translate source words $e_1, e_2, ..., e_n$ into language l_{tgt} and style s_{tgt} , looks like following:

$$|e_1|l_{tat}|s_{tat}| |e_2|l_{tat}|s_{tat}| ... |e_N|l_{tat}|s_{tat}|,$$




Figure 2: Proposed Multilingual Multistyle Machine Translation System. In this experiment, we consider 3 languages: English (en), Franch (fr), German (de), and 3 styles: Open-Subtitles (OS), Europarl (EP), and JRC-Acquis (JRC). The image shows the data flow between language-style pairs. Arrows of the same color correspond to the parallel data. During training, source sentences in a particular language and belonging to a particular style are encoded with Factored (Sennrich and Haddow, 2016) Transformer (Vaswani et al., 2017) model and decoded into a different language, but the same style. At inference time, we are able to convert source sentences into different languages, and, importantly, into different styles (despite not having cross-style parallel data for training). Information about languages and styles is communicated to the model in form of the word factors.

where vertical lines highlight input words factors. The target sentence remains unchanged.

See Figure 2 for a concrete example of the training architecture and data flow. In this way, during training the model encounters examples of translation in different language directions, but texts belonging to a certain style are only translated into the same style, since we do not use any style-parallel data. Our assumption is that given enough data for different languages and styles the model should learn to match the translations not just to the output language but also to the desired style, even without having seen style-wise parallel data during training.

To perform cross-lingual style transfer, we translate texts using the trained model, passing the desired target language and style, which now may be different from the style of the source text, as factors.

4 Experiments

4.1 Datasets

The translation model was trained using three parallel corpora: OpenSubtitles2018 ² , a new release

¹We treat the term "text style" loosely as covering concepts like text domain, genre, formality and other text characteristics.

²http://www.opensubtitles.org/

	OS	EP	JRC
$de \leftrightarrow en$	3M	1.95M	0.71M
$en \leftrightarrow fr$	3M	2.04M	0.71M
$de \leftrightarrow fr$	3M	1.93M	1.47M

Table 1: Training set sizes (number of sentence pairs).

of the corpus presented by Lison and Tiedemann (2016), Europarl (Koehn, 2005) and JRC-Acquis (Steinberger et al., 2006). OpenSubtitles2018 is a corpus made up of movie and TV subtitles, Europarl consists of texts of European Parliament proceedings, and JRC-Acquis comprises legislative texts of the European Union.

We assume that there should be sufficient stylistic difference between these three corpora, especially between the more informal OpenSubtitles2018 and the other two, while acknowledging the fact that most text corpora and OpenSubtitles in particular constitute a heterogeneous mix of genres and text characteristics; however, many stylistic traits are also similar across the whole corpus, which means that these common traits can be learned as a single style.

We used three language pairs: English-German, English-French and German-French, each taken in both directions. Refer to the Figure 2 for the system architecture and data flow.

Prior to model training, we discarded all sentence pairs where at least one sentence was an empty string, consisted of more than 100 tokens, or did not contain any alphabetic characters, and pairs where token-wise length ratio exceeded 9. Table 1 shows the sizes of the training sets.

4.2 Experiment Details

All corpora were preprocessed in a standard way: they were tokenized using Moses tokenizer (Koehn et al., 2007), true-cased and, finally, segmented using the SentencePiece³ (Wu et al., 2016) implementation of sub-word units with a joint vocabulary of size 32000.

We trained an NMT model using the Sockeye framework (Hieber et al., 2017). We used transformer encoder and decoder with 6 layers, transformer model size of 512, 8 attention heads and ReLU activation for both encoder and decoder. Adam optimizer was used. Source and target token embeddings were both of size 512, and factors

S_{src}	S_{tgt}		
ν_{src}	OS	EP	JRC
OS	462 (350)	14	25
EP	320	0 (0)	0
JRC	31	0	0 (0)

Table 2: Number of contractions in 1000-sentence test sets when translated from German into English in all 9 style directions. The numbers in parentheses indicate the number of contracted forms in the human-translated test sets.

determining target language and style had embeddings of size 4. Batch size was set to 2048 words, initial learning rate to 0.0002, reducing by a factor of 0.7 every time when validation perplexity has not improved for 8 checkpoints, which happened every 4000 updates.

The model finished training during the 11th epoch, when validation perplexity has not improved for 32 consecutive checkpoints.

The parameters of a single best checkpoint were used for all translations, with beam size set to 5.

For evaluation we use the BLEU (Papineni et al., 2002) and METEOR (Banerjee and Lavie, 2005) metrics in cases where parallel test data is available. For evaluating style transfer without parallel data we perform a qualitative comparison using a style classifier, described in the following section.

4.3 Evaluation Results

When prompted to translate sentences into different styles, the model shows the ability to capture some key characteristics of those styles. One such characteristic in the English language is the presence of contracted forms, such as *I'll*, *she's* and so on. Contracted forms are typically abundant in informal texts, such as those making up the Open-Subtitles corpus, and are typically absent in formal and official texts, such as parliament proceedings in Europarl and legal documents in JRC-Acquis. Tables 2 and 3 show the number of contractions in test sets translated, respectively, from German and French into English in all possible style directions.

One other aspect that the model captures is the different lexical and grammatical choices appropriate for different styles. Some examples of different wording that the system uses when translating the same source sentences into different domains can be found in Table 4 for German-English and in Table 5 for French-English. For more and longer examples refer to Supplemental Material A.

³https://github.com/google/ sentencepiece

S_{src}	S_{tgt}		
$ _{Src} $	OS	EP	JRC
OS	469 (352)	10	11
EP	327	0 (1)	0
JRC	35	0	0 (0)

Table 3: Number of contractions in 1000-sentence test sets when translated from French into English in all 9 style directions. The numbers in parentheses indicate the number of contracted forms in the human-translated test sets.

Source	OS	EP	JRC
(de)			
möchte ich	i want	i would like	i would like
aber	but	however	however
ich wechsle	i'm turning	i am turn-	i shall refer
		ing	
tatsächlich	actually	indeed	indeed
wir gehen	we're leav-	we are	we shall
	ing	leaving	leave
noch viel	more that	much more	even more
mehr	than		so
lindern	ease	alleviate	alleviate
ja	yeah	yes	yes
chance	chance	opportunity	opportunity
bleibt	stay	remain	remain
wie schon	like i said	as i have al-	as already
gesagt		ready said	stated
außerdem	besides	moreover	moreover
ach ja?	oh, yeah?	is that so?	is that so?
wir gehen	we're leav-	we are	we shall
	ing	leaving	leave
wie geht's	so, what's	what hap-	how are we
dann	next?	pens then?	to proceed
weiter?			then?

Table 4: Examples of different wording in German-English style transfer. The German phrase *möchte ich* will be translated into OpenSubtitles as *I want*, and into Europarl and JRC-Acquis as *I would like. lindern* and *bleiben* become *ease* and *stay*, respectively, in OpenSubtitles, but *alleviate* and *remain* in Europarl and JRC-Acquis. In some other cases there is also difference between the formal styles: *wie geht's dann weiter?* becomes *so, what's next?* in OpenSubtitles, *what happens then?* in Europarl and *how are we to proceed then?* in JRC-Acquis.

Source (fr)	OS	EP	JRC
salut	hey	hi	hi
on se lance?	let 's go.	are we getting started?	are we go-ing?
un délai de deux heures	two hours	two hours	a two-hour period
c'est ça	that 's right	that is it	that is the case
vrai	real	genuine	genuine
il parle de vous	he 's talk- ing about you	he talks about you	he speaks of you
evanouis - toi	get out of here	get away from it	evacuate yourself
merdique	crappy	a mess	merchandical
halte	stop	stop	halt
rester pru- dent	be careful	be careful	remain cau- tious
intérieur	inside	inside	within
je vous rembours- erai	i 'll pay you back	i will pay you back	i shall reim- burse you

Table 5: Examples of different wording in French-English style transfer. The French *salut* translates to *hey* in OpenSubtitles and to *hi* in both Europarl and JRC-Acquis. *evanouistoi* can become *get out of here*, *get away from it* or *evacuate yourself* when formality increases.

S_{src}	S_{tgt}		
O_{src}	OS	EP	JRC
OS	33.1/30.5	26.2/27.4	24.6/26.8
EP	35.4/35.9	38.6/37.4	37.7/37.0
JRC	52.6/42.9	55.4/44.2	58.9/45.9

Table 6: BLEU / METEOR scores of test sets translated from German into English in all style directions. METEOR typically sees a smaller decrease that BLEU, presumably due to use of style-appropriate synonyms.

To support our assumption that the model at least somewhat consistently uses synonyms to discriminate between styles, we show in Tables 6 and 7 the BLEU and METEOR scores for test sets translated, respectively, from German and French into English in all style directions.

To qualitatively assess the performance of our system, we train convolutional neural network (CNN) classifiers to predict the styles of sentences presented to it, as described by Kim (2014). We use an implementation of convolutional neural networks for text classification⁴. We train three separate two-class classifiers for English sentences, each of which aims to distinguish between one of the styles and the other two. The

⁴https://github.com/dennybritz/ cnn-text-classification-tf

S_{src}	S_{tgt}		
$ \mathcal{D}_{src} $	OS	EP	JRC
OS	33.3/31.0	25.3/27.1	24.9/27.0
EP	39.6/38.2	42.4/39.6	41.1/39.1
JRC	56.6/45.3	59.1/46.5	62.6/48.1

Table 7: BLEU / METEOR scores of test sets translated from French into English in all style directions. METEOR typically sees a smaller decrease that BLEU, presumably due to use of style-appropriate synonyms.

S_{src}	S_{tgt}		
S_{src}	OS	EP	JRC
OS	96.4 / 97.4	8.1 / 24.3	3.4 / 5.5
EP	4.4 / 14.0	96.4 / 96.1	5.4 / 8.5
JRC	1.9 / 2.8	6.9 / 12.8	96.5 / 96.8

Table 8: Percentage of sentences recognized as the target style in human-translated German-English test sets / test sets translated from German into English and into the target style by the NMT model.

CNN classifiers are trained on a portion of the data used for training the NMT model, with filter sizes 3, 4 and 5, and 128 filters per size, with max-pooling, and dropout probability of 0.5. The classifiers for OpenSubtitles, Europarl and JRC-Acquis achieve validation accuracy of 96%, 95% and 96% respectively.

Tables 8 and 9 demonstrate, for German-English and French-English translations respectively, the percentage of sentences classified as the target class in the human-translated test sets (that is, belonging effectively to the source class) and in the test sets translated automatically into the target class.

4.4 Interpretation

It is clear that the system chooses shortened forms when translating into OpenSubtitles, even being over-eager and incorporating more of those than in the human translations. When translating into the more formal domains, it gets rid of most con-

S_{src}	S_{tgt}		
$ \mathcal{D}_{src} $	OS	EP	JRC
OS	96.0 / 96.5	8.7 / 25.4	3.2 / 6.7
EP	3.9 / 14.1	95.3 / 96.2	4.5 / 6.4
JRC	1.9 / 3.7	7.0 / 12.4	96.8 / 96.7

Table 9: Percentage of sentences recognized as the target style in human-translated French-English test sets / test sets translated from French into English and into the target style by the NMT model.

S_{src}	S_{tgt}		
Ssrc	OS	EP	JRC
OS	1%	200%	62%
EP	218%	-0.3%	57%
JRC	47%	86%	0.3%

Table 10: Relative change in style. Percentages show how much the amount of the target style in corpus increased after cross-lingual zero-shot style transfer. Language direction: German into English

S_{src}	S_{tgt}		
ν_{src}	OS	EP	JRC
OS	0.5%	192%	109%
EP	262%	0.9%	42%
JRC	95%	77%	0.1%

Table 11: Relative change in style. Percentages show how much the amount of the target style in corpus increased after cross-lingual zero-shot style transfer. Language direction: French into English.

tractions (see Tables 2, 3) for both language pairs.

We also expect the model to use lexical variations while translating into different styles. It is clear that both BLEU and METEOR scores should fall when the sentences are translated into a different style, because human-translated references are in the style of source sentences. However, since METEOR relies on synonymy when determining matches and BLEU does not, METEOR generally decreases about twice as less as BLEU does (see Tables 12 and 13).

Regarding the classification results, there is a consistent increase in the percentage of sentences recognized as the desired style when they are translated into that style using the Transformer NMT model. The highest rise occurs when we translate between most dissimilar styles (OS and EP) and sits in range of 200-300%. The lowest rise accordingly occurs in case of similar styles (EP, JRC). This trend is consistent across language pairs. Refer to the Tables 10, 11 for more details.

4.5 Monolingual Zero-shot Style Transfer

While the main focus of our paper has been so far on cross-lingual style transfer, as a side effect, translating from English to English while passing different target styles to the model potentially leads to a monolingual (zero-shot) style transfer. Tables 14 and 15 demonstrate that this is indeed the case and trends observed in cross-lingual transfer reappear.

S_{src}	S_{tgt}		
Osrc	OS	EP	JRC
OS	-	20.9/10.2%	25.7/12.1%
EP	8.3/4.0%	-	2.3/1.1%
JRC	10.7/6.5%	5.9/3.7%	-

Table 12: Relative decrease in BLEU / METEOR scores of test sets translated from German into English in all style directions. METEOR typically drops about twice as less comparing to the BLEU, presumably due to use of style-appropriate synonyms.

S_{src}	S_{tgt}		
$ D_{src} $	OS	EP	JRC
OS	-	24.0/12.6%	25.3/12.9%
EP	6.6/3.5%	-	3.1/1.3%
JRC	9.6/5.8%	5.6/3.3%	-

Table 13: Relative decrease in BLEU / METEOR scores of test sets translated from French into English in all style directions. METEOR typically drops about twice as less comparing to the BLEU, presumably due to use of style-appropriate synonyms.

S_{src}	S_{tgt}		
	OS	EP	JRC
OS	85.4/60.9	70.0/50.3	75.0/53.7
EP	85.5/61.3	83.6/60.4	82.1/59.4
JRC	90.9/64.7	87.9/62.1	87.9/61.9

Table 14: BLEU / METEOR scores of test sets translated from English into English in all style directions.

S_{src}	S_{tgt}		
$ $ \cup_{src}	OS	EP	JRC
OS	390 (363)	23	70
EP	167	0 (0)	0
JRC	4	0	0 (0)

Table 15: Number of contractions in 1000-sentence test sets when translated from English into English in all 9 style directions. The numbers in parentheses indicate the number of contracted forms in the human-translated test sets.

5 Discussion

The proportion of sentences recognized as members of the desired target classes by the CNN domain classifiers remains quite low. However, we believe that such evaluation may be less suitable for our task than it is for the more typical tasks in style transfer, such as sentiment or gender transfer.

Our CNN network is, in fact, a domain classifier, trained, unavoidably in our case, to classify relying not only on style, but on semantic content as well. Thus, the topic of a sentence might significantly influence the classifier decision. For example, it is highly unlikely to have words typical for such genres as fantasy or rock'n'roll in Europarl (European Parliament speech transcripts) corpus, while it is natural to expect such topics from Open-Subtitles texts. The style transfer itself can influence some lexical choices and the general feeling of the sentence, but not dramatically enough to fool our domain classification model on vast majority of cases. The topics differ significantly between the corpora we use, and semantic content should greatly influence classifier output.

From this perspective, our style transfer model is strong enough to make the domain classification model increase its predictions of the target domain by up to three times (Tables 10, 11). We interpret it as a solid result.

It should be also noted that while we only provide results for English as the target language for now, the system is, by design, multilingual, and there is nothing English-specific to it. All assumptions should hold true for other target languages as well. We chose English as a target language to simplify evaluation and understanding.

6 Related Work

The task of cross-lingual zero-shot style transfer is novel and is not discussed in the literature at the best of our knowledge. However, many recent models for style transfer that do not rely on direct parallel signal contain innate structure that is aimed to separate content and style representations (Hu et al., 2017; Mueller et al., 2017; Shen et al., 2017). This is often done using VAE's (Kingma and Welling, 2013) and GAN's (Goodfellow et al., 2014), while sometimes explicit attribute substitutions are involved (Li et al., 2018).

We in turn employ ideas from multilingual NMT systems (Firat et al., 2016; Johnson et al., 2016), which are proven to have a high perfor-

mance while also enabling translation between language pairs that we not have direct parallel corpora. We use a similar multilingual architecture while also extending its benefits to styles.

Several authors also employed machine translation ideas to support style transfer task. Approaches include back-translating languages (Prabhumoye et al., 2018) and using seq2seq architectures (Han et al., 2018) as a part of the pipeline.

Most similar work to ours conceptually is done by Carlson et al. (2017). They aim to do monolingual zero-shot style transfer, and use 32 different English versions of Bible as their source of paraphrase training data. We use multiple languages, multiple styles, and do not rely on any explicit lexicons.

Finally, Niu et al. (2017) inspect generating NMT output with different degrees of formality. Methods include vector space models that require large mixed-topic corpora to be trained. While being similar in a way that it also modifies NMT output, the main focus of our work is cross-lingual zero-shot style transfer. Moreover, our work is not limited to generating hypotheses with different degrees formality, but arbitrary styles can be used.

7 Conclusion

We propose a method for cross-lingual zero-shot style transfer. While our model does not achieve high scores based on classifier output, we believe that such evaluation may be less suitable for our tasks than it is for the more typical tasks in style transfer, such as sentiment or gender transfer, because the topics differ significantly between the corpora we use, and semantic content should greatly influence classifier output.

However, the model does show promising qualitative results, demonstrating the ability to capture some important aspects of stylistic difference between domains.

8 Future work

In the future, we plan to assess other aspects of style differences that the model may capture, and to use help of human evaluators in assessing our results. We intend to perform a meaningful qualitative and quantitative comparison to a previously existing strong style transfer system. We also intend to train and evaluate two-language NMT systems with the same approach to learning style to

see how multilinguality interferes with style transfer.

In addition, we plan to improve quantitative evaluation of the model by making the CNN classifiers more appropriate for the task, for instance, by training them as multi-class and yielding class probabilities rather than labels, and by making them more content-agnostic and style-sensitive.

Acknowledgments

The authors would like to thank the University for providing GPU computing resources.

References

Satanjeev Banerjee and Alon Lavie. 2005. METEOR: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pages 65–72.

Keith Carlson, Allen Riddell, and Daniel N. Rockmore. 2017. Zero-shot style transfer in text using recurrent neural networks. *CoRR*, abs/1711.04731.

Orhan Firat, KyungHyun Cho, and Yoshua Bengio. 2016. Multi-way, multilingual neural machine translation with a shared attention mechanism. *CoRR*, abs/1601.01073.

I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. 2014. Generative Adversarial Networks. *ArXiv* e-prints.

Mengqiao Han, Ou Wu, and Zhendong Niu. 2018. Unsupervised automatic text style transfer using lstm. pages 281–292.

Felix Hieber, Tobias Domhan, Michael Denkowski, David Vilar, Artem Sokolov, Ann Clifton, and Matt Post. 2017. Sockeye: A toolkit for neural machine translation. *CoRR*, abs/1712.05690.

Zhiting Hu, Zichao Yang, Xiaodan Liang, Ruslan Salakhutdinov, and Eric P. Xing. 2017. Controllable text generation. *CoRR*, abs/1703.00955.

Melvin Johnson, Mike Schuster, Quoc V. Le, Maxim Krikun, Yonghui Wu, Zhifeng Chen, Nikhil Thorat, Fernanda B. Viégas, Martin Wattenberg, Greg Corrado, Macduff Hughes, and Jeffrey Dean. 2016. Google's multilingual neural machine translation system: Enabling zero-shot translation. *CoRR*, abs/1611.04558.

Yoon Kim. 2014. Convolutional neural networks for sentence classification. *CoRR*, abs/1408.5882.

- D. P Kingma and M. Welling. 2013. Auto-Encoding Variational Bayes. *ArXiv e-prints*.
- Philipp Koehn. 2005. Europarl: A parallel corpus for statistical machine translation. In *MT summit*, volume 5, pages 79–86.
- Philipp Koehn, Hieu Hoang, Alexandra Birch, Chris Callison-burch, Richard Zens, Marcello Federico, Nicola Bertoldi, Chris Dyer, Brooke Cowan, Wade Shen, Christine Moran, Ondrej Bojar, Alexandra Constantin, and Evan Herbst. 2007. Moses: Open source toolkit for statistical machine translation.
- Juncen Li, Robin Jia, He He, and Percy Liang. 2018. Delete, retrieve, generate: A simple approach to sentiment and style transfer. *CoRR*, abs/1804.06437.
- Pierre Lison and Jörg Tiedemann. 2016. Opensubtitles 2016: Extracting large parallel corpora from movie and tv subtitles. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC 2016)*, Paris, France. European Language Resources Association (ELRA).
- Jonas Mueller, David Gifford, and Tommi Jaakkola. 2017. Sequence to better sequence: Continuous revision of combinatorial structures. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2536–2544, International Convention Centre, Sydney, Australia. PMLR.
- Xing Niu, Marianna J. Martindale, and Marine Carpuat. 2017. A study of style in machine translation: Controlling the formality of machine translation output.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318, Philadelphia, Pennsylvania, USA. Association for Computational Linguistics.
- Shrimai Prabhumoye, Yulia Tsvetkov, Ruslan Salakhutdinov, and Alan W Black. 2018. Style transfer through back-translation.
- Rico Sennrich and Barry Haddow. 2016. Linguistic input features improve neural machine translation. *CoRR*, abs/1606.02892.
- Tianxiao Shen, Tao Lei, Regina Barzilay, and Tommi S. Jaakkola. 2017. Style transfer from non-parallel text by cross-alignment. *CoRR*, abs/1705.09655.
- Ralf Steinberger, Bruno Pouliquen, Anna Widiger, Camelia Ignat, Tomaž Erjavec, Dan Tufiş, and Dániel Varga. 2006. The jrc-acquis: A multilingual aligned parallel corpus with 20+ languages. In *Proceedings of the Fifth International Conference on Language Resources and Evaluation (LREC'06)*.

- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *CoRR*, abs/1706.03762.
- Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V. Le, Mohammad Norouzi, Wolfgang Macherey, Maxim Krikun, Yuan Cao, Qin Gao, Klaus Macherey, Jeff Klingner, Apurva Shah, Melvin Johnson, Xiaobing Liu, Lukasz Kaiser, Stephan Gouws, Yoshikiyo Kato, Taku Kudo, Hideto Kazawa, Keith Stevens, George Kurian, Nishant Patil, Wei Wang, Cliff Young, Jason Smith, Jason Riesa, Alex Rudnick, Oriol Vinyals, Greg Corrado, Macduff Hughes, and Jeffrey Dean. 2016. Google's neural machine translation system: Bridging the gap between human and machine translation. *CoRR*, abs/1609.08144.

A Supplemental Material

Source (de)	OS	EP	JRC
möchte ich	i want	i would like	i would like
erst	first	first of all	first of all
damit du dich hinlegen	so you can lie down	so that you can lie	and lie down
kannst	-	down	
er jetzt verrückt wird	he's going crazy now	he gets mad now	he becomes crazy now
schnell	fast	quickly	quickly
ich reise nach london	i'm going to london	i will continue to travel	i shall continue to
weiter		to london	travel to london
aber	but	however	however
ich wechsle	i'm turning	i am turning	i shall refer
mach das nicht	don't do that	don't do that	do not do so
tatsächlich	actually	indeed	indeed
wir gehen	we're leaving	we are leaving	we shall leave
wer	whoever	those who	those who
ich halte es auf	i'll stop it	i will stop it	i shall stop it
nichts derartiges	anything like that	anything like this	anything of this kind
ich hätte gedacht	i thought	i would have thought	i would have thought
sonst	or	otherwise	otherwise
um den schmerz zu	to ease the pain	in order to alleviate the	in order to alleviate the
lindern		pain	pain
noch viel mehr	more that than	much more	even more so
ja	yeah	yes	yes
größer	bigger	greater	greater
eine chance	a chance	an opportunity	an opportunity
auch der Mörder	the killer, too	also the murderer	also the murderer
heutzutage ist es schw-	nowadays, it's harder	today, it is more diffi-	it is now more difficult
erer		cult	
wie geht's dann weiter?	so, what's next?	what happens then?	how are we to proceed then?
ein rätsel, das es zu	a mystery to solve	a mystery that needs to	a mystery to be re-
lösen gilt		be resolved	solved
bleibt	stay	remain	remain
wie schon gesagt	like i said	as i have already said	as already stated
ich mache eine anfrage	i'll ask you a question	i have a question	i shall make a request
ich wollte sie nicht	i didn't mean to hurt	i did not want to offend	i did not wish to offend
kränken	you	you	you
damit ich das richtig	let me get this straight	let me get this straight	in order to understand
verstehe			this correctly
sie haben die fotos	they've got the photos	they have the pho-	they shall have the
		tographs	photographs
shauen sie genau hin	look carefully	look carefully	take a close look
du für kommunikation	you're in charge of	you are responsible for	you are responsible for
zuständig bist	communication	communication	communication
ich wagte mich schon	i've gone too far	i have dared to go too	i have dared to go too
zu weit vor		far	far
ohne auch nur kurz	without even thinking	without even thinking	without even consider-
darüber nachzudenken	about it	a little bit about it	ing it briefly
außerdem	besides	moreover	moreover
ach ja?	oh, yeah?	is that so?	is that so?

Table 16: Additional examples of difference in lexical and grammatical choices when translating from German to English into different styles.

Source (fr)	OS	EP	JRC
il paraît que vous êtes	i hear you 're special .	i understand that you	it appears that you are
spéciale.		are special.	special.
c'est ça	that 's right	that is it	that is the case
très vilaine	very bad	very bad	very vile
vrai	real	genuine	genuine
on a un autre concert	we 've got another	we have another con-	a further concert will
demain	concert tomorrow.	cert tomorrow.	be held tomorrow
on se tire une balle	we shoot each other	you get a bullet	a bullet is fired
donc	so	so	therefore
bien, on a fini.	all right, we 're done.	well, we have finished.	well, we have finished.
qu'est - ce que vous mijotez?	what are you up to?	what are you doing?	what are you doing?
manquent de respect	have no respect	do not respect	are disrespectful to
vous m'aviez indiqué	you told me	you indicated to me	you indicated to me
enlève l'argent	take the money away	take the money away	remove the money
rester prudent	be careful	be careful	remain cautious
une réunion est orga-	there 's a meeting at	a meeting is being held	a meeting shall be held
nisée à la mairie de-	the city hall tomorrow	in the city hall tomor-	at the council meeting
main soir, - si vous	night, if you'd like	row evening - if you	tomorrow evening, - if
souhaitez		wish	you wish
on l'a détectée	we detected it	it was detected	it was detected
deux heures	two hours	two hours	a two-hour period
précieuse	precious	valuable	valuable
vous ne voyez pas	can 't you see he re-	do you not see that he	do you not see that he
qu'il a répondu à une	sponded to a provoca-	responded to a provo-	responded to a provo-
provocation ?	tion ?	cation?	cation ?
c'est incroyable!	it 's amazing!	that is unbelievable!	this is unbelievable!
halte	stop	stop	halt
ca risque d'être une	it 's gonna be a hard	there is a risk that this	this is likely to be a
piste difficile	run	will be a difficult path	difficult path
ça m'a fait plaisir de le	it made me happy to	i was pleased to see	i was pleased to see
voir heureux	see him happy	him happy	him happy
le petit a disparu	the kid 's gone	the child has disap-	the child has disap-
		peared	peared
film	movie	film	film
journaux	papers	newspapers	newspapers
merdique	crappy	a mess	merchandical
je vous rembourserai.	i 'll pay you back.	i will pay you back.	i shall reimburse you.
procureur	d.a.	prosecutor	public prosecutor
personne	no one	nobody	no person
honte	shame	disgrace	disgrace
evanouis - toi .	get out of here.	get away from it.	evacuate yourself.
il parle de vous	he 's talking about you	he talks about you	he speaks of you
on se lance?	let 's go .	are we getting started?	are we going?
salut	hey	hi	hi
on me prendrait pour	they 'd think i 'm an	i would be thought to	i would be regarded as
un idiot	idiot	be an idiot	an idiot

Table 17: Additional examples of difference in lexical and grammatical choices when translating from French to English into different styles.