A Generalization of the Łoś-Tarski Preservation Theorem

(Summary of dissertation including extensions of dissertation results)

Abhisekh Sankaran*

Advisors: Supratik Chakraborty and Bharat Adsul

Indian Institute of Technology Bombay, Maharashtra, India.

Abstract

This article gives a summary of the author's Ph.D. dissertation [30]. In addition to an overview of notions and results, it also provides sketches of various proofs and simplified presentations of certain abstract results of the dissertation, that concern tree representations of structures. Further, some extensions of the dissertation results are presented. These include the connections of the model-theoretic notions introduced in the thesis with fixed parameter tractability and notions in the structure theory of sparse graph classes. The constructive aspects of the proofs of the model-theoretic results of the dissertation are used to obtain (algorithmic) meta-kernels for various dense graphs such as graphs of bounded clique-width and subclasses of these like *m*-partite cographs and graph classes of bounded shrub-depth. Finally, the article presents updated definitions and results concerning logical fractals introduced in [31] as a generalization of the Equivalent Bounded Substructure Property from the dissertation. In particular, our results show that (natural finitary adaptations of) both the upward and downward versions of the Löwenheim-Skolem theorem from classical model theory can be recovered in a variety of algorithmically interesting settings, and further in most cases, in effective form and even for logics beyond first order logic.

1 Introduction

Classical model theory is a subject within mathematical logic that studies the relationship between a formal language and its interpretations also called structures or models [3]. Amongst the earliest areas of study in classical model theory, is a class of results called *preservation theorems*. A preservation theorem syntactically characterizes classes of arbitrary structures (structures that could be finite or infinite) that are closed under a given model-theoretic operation. For instance, the class of all cliques is preserved under substructures (induced subgraphs in this context). This class is also defined by the first order (FO) sentence that says "for all (vertices) x and for all (vertices) y, (there is an) edge between x and y". The latter is a "universal" sentence, i.e. an FO description that contains only universal quantifications. One of the earliest preservation theorems of classical

^{*}Current affiliation: Department of Computer Science and Technology, University of Cambridge, UK.

model theory, the Łoś-Tarski theorem, proven by Jerzy Łoś and Alfred Tarski in 1954-55, says that universal sentences are indeed *expressively complete* for preservation under substructures.

Technically, the Loś-Tarski theorem states that a class of arbitrary structures defined by an FO sentence is preserved under substructures if, and only if, it is definable by a universal sentence [3]. The theorem in "dual" form characterizes extension closed FO definable classes of arbitrary structures in terms of "existential" sentences. Both forms of the theorem extend to theories (sets of sentences) as well. The Loś-Tarski theorem is historically important for classical model theory since its proof constituted the earliest applications of the FO Compactness theorem which is now regarded as one of the pillars of model theory. Further, the proof triggered off an extensive study of preservation theorems in which various other model-theoretic operations like homomorphisms, unions of chains, direct products, etc. were taken up and preservation theorems for these operations were proven not just for FO but even extensions of it, like infinitary logics [18]. These investigations contributed significantly to the development of the (then young) subject of classical model theory.

In 1973, Fagin proved a landmark result characterizing the complexity class NP in terms of existential second order logic. This result began the area of finite model theory, whose aims are similar to classical model theory, namely the study of the expressive power of formal languages, but now the structures under consideration are only finite. Finite model theory [20] is closely connected with computer science since many disciplines within the latter use formal languages, such as programming languages, database query languages or specification languages, and further the structures arising in these disciplines are often finite. It is natural to ask if the results and techniques of classical model theory can be carried over to the finite too. It turns out that the class of all finite structures is very poorly behaved from the model-theoretic perspective. The Loś-Tarski theorem fails, the Löwenheim-Skolem theorem (a central result in model theory) becomes meaningless, and important concepts like saturation and homogeneity that provide elegant results in the infinite, trivialize in the finite [26]. A few theorems survive, such as the homomorphism preservation theorem [28] and van Benthem's modal characterization theorem [25], but these are rare. This inspired the research programme of identifying classes of finite structures over which results of classical model theory could be recovered. The pioneering steps were taken in [1, 2] where it was shown that algorithmically interesting classes, in particular sparse structures, such as those that are acyclic, of bounded degree or of bounded tree-width, under reasonable closure assumptions satisfy the (relativized versions of the) Łoś-Tarski and homomorphism preservation theorems. (Note that the truth of a preservation theorem over a class does not imply its truth over a subclass; going to the subclass weakens both sides of the equivalence given by the theorem). The homomorphism preservation theorem was later shown to be true over hereditary quasi-wide classes too (under mild assumptions) [6]. Quasi-wide structures are exactly nowhere dense structures under hereditariness [23], and the latter are regarded as the natural limit of algorithmic techniques for sparse classes [17].

While a preservation theorem provides a syntactic characterization of a preservation property, the same theorem flipped around, can also be seen as providing a semantic characterization (via a preservation property) of a syntactic class of sentences. Thus the Łoś-Tarski theorem characterizes universal and existential sentences in terms of preservation under substructures and extensions, respectively. It is well known that if the vocabulary contains only relation symbols, then the sizes of the minimal models of a sentence preserved under extensions, are no larger than the number of quantifiers in any equivalent existential sentence [1]. Thus the Łoś-Tarski theorem, besides giving a syntax-semantics correspondence, also yields a relation between a quantitative model-theoretic property (size of minimal models) of a sentence in a semantic class and the count of quantifiers in an equivalent sentence in the corresponding syntactic class. Two subclasses of FO that are semantically richer than the universal and existential classes of sentences, are the Σ_2^0 and Π_2^0 classes of prenex FO sentences having two blocks of quantifiers, with the leading block being existential and universal respectively. These subclasses of FO arise in a wide variety of areas in computer science: decision procedures for SAT, program verification, SMT solvers and program synthesis (where Σ_2^0 is called the *Bernays-Schönfinkel-Ramsey* class or effectively propositional logic), and databases, particularly data exchange, data integration and query answering over RDF and OWL knowledge (where Π_2^0 is called the forall-existential fragment) [8, 9, 19, 24]. Further, a number of fixed parameter tractable (FPT) problems, as well as important notions from finite model theory and the structure theory of sparse graphs, turn out to be naturally described in the Σ_2^0 and Π_2^0 fragments (see Appendix A). The classical model theory literature contains several semantic characterizations, over arbitrary structures, for these syntactic fragments, in terms of notions such as ascending chains, descending chains, and Keisler's 1-sandwiches [3].

However, there are two major drawbacks of the mentioned notions from the perspective of computer science. First, none of these notions enables relating quantifier counts in the syntactic classes to any model-theoretic properties. Second, all of these notions, being infinitary, trivialize in the finite. With the result that there are no preservation theorems in the finite, that semantically characterize the Σ_2^0 and Π_2^0 classes, or their subclasses with given (non-zero) quantifier counts. Next, we observe that within the programme of recovering classical model theory in the finite, the investigations so far have been only over *sparse* structures. After the momentous recent result characterizing nowhere dense classes as the largest subgraph-closed classes of sparse graphs admitting FO algorithmic meta-theorems [17], the focus has shifted to *dense* structures, such as posets, subclasses of bounded clique-width graphs, and structures that are first-order interpretable in sparse classes, for algorithmic meta-theorems and structural studies [10, 11, 12, 13]. However, there has been no research on the model-theoretic properties of these classes, akin to that done for sparse structures. We observe also that the studies for sparse structures have considered only the Loś-Tarski and homomorphism preservation theorems from model theory. This thesis is motivated by all of the above issues, and takes the first steps towards addressing them.

2 Overview of the Thesis

New parameterized preservation properties: The starting point of the thesis [30] is the introduction of two dual parameterized preservation properties that generalize the properties of preservation under substructures and preservation under extensions (Chapter 3). We call these respectively preservation under substructures modulo k-cruxes, denoted PSC(k), and preservation under k-ary covered extensions, denoted PCE(k), where k is a

natural number.

Definition 2.1 (Defn. 3.1.1, Chp. 3). A sentence φ is said to be PSC(k) if for every model \mathfrak{A} of φ , there is a subset C of the universe of \mathfrak{A} , of size $\leq k$, such that if \mathfrak{B} is a substructure of \mathfrak{A} and \mathfrak{B} contains C, then \mathfrak{B} is also a model of φ . We call C a k-crux of \mathfrak{A} with respect to φ .

Definition 2.2 (Defn. 3.2.1 & Defn. 3.2.4, Chp. 3). Given a structure \mathfrak{A} , a non-empty collection \mathcal{R} of substructures of \mathfrak{A} is said to be a *k*-ary cover of \mathfrak{A} if for every subset C of the universe of \mathfrak{A} , of size $\leq k$, there is a structure in \mathcal{R} that contains C. We call \mathfrak{A} a *k*-ary covered extension of \mathcal{R} . We now say a sentence φ is PCE(k) if for every collection \mathcal{R} of models of φ , if \mathfrak{A} is a *k*-ary covered extension of \mathcal{R} , then \mathfrak{A} is also a model of φ .

As an example, consider the sentence φ over graphs that asserts "there is a dominating set of size $\leq k$ ". In any model of φ , any dominating set witnessing φ is a k-crux of the model with respect to φ ; then φ is PSC(k). One observes that $\neg \varphi$ is PCE(k); indeed this an instance of the more general observation that a sentence is PSC(k) if, and only if, its negation is PCE(k). We see that $PSC(\cdot)$ and $PCE(\cdot)$ form semantic hierarchies under inclusion, that strictly increase with k (the sentence that asserts "there are $\geq k$ vertices in the graph" is PSC(k) but not PSC(k-1)), and whose k = 0 levels correspond exactly to preservation under substructures and extensions respectively.

The introduced properties turn out to be widely realized in computer science (see Appendix A). The reason as it turns out, is connected with the definability of these properties using syntactical structure that entails the properties. Specifically, any $\exists^k \forall^*$ sentence, i.e. a Σ_2^0 sentence having k quantifiers in its leading block, is PSC(k): the witnesses to the existential quantifiers in any model form a k-crux in the model. For instance, the dominating set example above is definable using the $\exists^k \forall^*$ sentence $\varphi = \exists x_1 \ldots \exists x_k \forall y \bigvee_{i=1}^{i=k} (y = x_i \lor E(y, x_i))$. Dually any $\forall^k \exists^*$ sentence is PCE(k). The natural question that arises is whether the mentioned syntactic fragments characterize their corresponding preservation properties. This question is the central thrust of this thesis, and indeed we show that in a number of scenarios, infinitary and finitary, the question has an affirmative answer via the following preservation theorem, that we call the generalized Loś-Tarski theorem, or $\mathsf{GLT}(k)$ in short: an FO sentence is PSC(k), respectively PCE(k), if, and only if, it is equivalent to an $\exists^k \forall^*$ sentence, respectively a $\forall^k \exists^*$ sentence. The case of k = 0 is verily the Loś-Tarski theorem.

Classical model theory results: In Part I of the thesis, we investigate GLT(k), its variants and extensions, over arbitrary structures. Specifically, we first show (in Chapter 4.1) that GLT(k) holds over any elementary class of arbitrary structures (i.e. a class definable using an FO theory). To the best of our knowledge, GLT(k) is the first in the classical model theory literature to relate natural quantitative properties of models of sentences in a semantic class, to counts of leading quantifiers in equivalent Σ_2^0 or Π_2^0 sentences. It thereby provides new and finer characterizations of these syntactic classes than those in the literature, and moreover, via notions that are combinatorial in nature. Precisely due to the latter, the notions remain non-trivial in the finite too, making it meaningful to ask which classes of finite structures satisfy GLT(k).

We continue our investigations over arbitrary structures, generalizing GLT(k) by extending the definitions of PSC(k) and PCE(k) in two different directions: one, by considering cruxes of sizes, and covers of arities, less than an infinite cardinal λ (Chapter 4.2), and the other, by considering theories instead of sentences (Chapter 5). For the former, we show that our "infinitary" properties $PSC(\lambda)$ and $PCE(\lambda)$ characterize all of Σ_2^0 and Π_2^0 respectively for sentences, and thus coincide with their finitary counterparts taken together over all k. This is indeed a Compactness-like phenomenon which we employ as a new technique to (re)prove well-known inexpressibility results of FO, such as acyclicity, bipartiteness, etc. [34] The other aforementioned direction, namely the extension of GLT(k) to theories, yields us results that differ from the "sentential" results for GLT(k)in many important ways. Specifically, while PCE(k) theories do characterize theories of $\forall^k \exists^*$ sentences, PSC(k) theories fall way short of doing analogously for theories of $\exists^k \forall^*$ sentences. Indeed the $\exists \forall^*$ theory (just one existential quantifier) defining the class of (arbitrary) graphs not containing for any n, a vertex cycle cover consisting of cycles of length $\leq n$, is not even $PSC(\aleph_0)$ (and hence not PSC(k) for any k). The infinitary properties are more well-behaved in contrast: for $\lambda \geq \aleph_0$, $PCE(\lambda)$ characterizes Π_2^0 theories, while for $\lambda \geq \aleph_1$, $PSC(\lambda)$ characterizes Σ_2^0 theories, so instead of an "infinite to finite collapse" of the PSC and PCE hierarchies as in the case of sentences, for theories there is a such collapse in the infinite realm down to the first or second level.

The above investigations leave open the characterization of PSC(k) theories. While this question has still evaded our best efforts to answer it, we do give partial results which constitute the most technically involved parts of Part I of the thesis. Specifically, we first show that a PSC(k) theory is always equivalent to a Σ_2^0 theory, and then using key insights gained from its proof, we refine this result by showing that under a wellmotivated model-theoretic hypothesis, a PSC(k) theory is always equivalent to an $\exists^k \forall^*$ theory. The proof of the latter introduces a novel technique of characterizing semantically defined FO theories by *qoing outside FO*. In particular, we show under the mentioned hypothesis, a characterization of PSC(k) theories in terms of sentences of an *infinitary* logic, and then "compile" the infinitary sentences down to their equivalent syntactically defined FO theories, by using suitable "finite approximations" of the former. We believe that this technique of characterizing FO theories might be of independent interest. We conclude Part I of the thesis on this note (Chapter 6), raising various natural questions for future work (over arbitrary structures), notable amongst them being a characterization of PSC(k) theories, and a lifting of our results to characterize prefix subclasses of FO having more quantifier alternations than just one.

Finite model theory results: In Part II of the thesis, we turn our attention to finite structures to investigate for GLT(k). The failure of the Loś-Tarski theorem over the class of all finite structures shows that GLT(0) fails over this class. We show a stronger failure: GLT(k) fails for each k (Chapter 8). Indeed for each k, we construct a sentence φ_k that is hereditary (preserved under substructures) over the class of all finite structures (so φ_k is also PSC(k) over this class), but that is not equivalent over this class to any $\exists^k \forall^*$ sentence. This strengthens the known failure of the Loś-Tarski theorem in the finite, by showing that not just universal sentences, but even $\exists^k \forall^*$ sentences for each k, fail to capture hereditary FO properties over all finite structures. Investigating further, we also show that the classes of sparse graphs mentioned earlier that admit the Loś-Tarski theorem (graphs that are acyclic, of bounded degree or of bounded tree-width), do not admit GLT(k) for any $k \geq 2$. This is because for $k \geq 2$, (the satisfaction of) GLT(k) forces a (hereditary) class to have bounded induced path lengths. (It is interesting to note here

that a preservation theorem enforces a structural condition.) We therefore consider classes of dense structures, in particular those of significant current interest from the perspectives of algorithmic meta-theorems and structural graph theory. Remarkably, these turn out to not just satisfy GLT(k), but various other classical model theory results as well, none of which were earlier known to hold over them.

We do all our investigations within an abstract framework that incorporates crucial observations about the structural and logical properties of the dense classes referred to. Specifically, the framework considers classes of structures that admit, what we call, \mathcal{L} -good tree representations, where \mathcal{L} is either FO, or monadic second order logic (MSO). An \mathcal{L} -good tree representation is a tree whose leaf nodes are labeled with simple structures (typically singletons) and whose internal nodes are labeled with operations on structures, that satisfy a few natural monotonicity properties with respect to isomorphic embedding, along with the *Feferman-Vaught composition (FVC)* property. An operation has the \mathcal{L} -FVC property if for each m, the $\mathcal{L}[m]$ theory of the operation's output is determined by the $\mathcal{L}[m]$ theories of the operation's inputs. Here, the $\mathcal{L}[m]$ theory of a structure is the set of \mathcal{L} sentences of quantifier nesting depth m that are true in the structure. As examples, disjoint union has the MSO-FVC property, while Cartesian product has the FO-FVC property.

Towards our model-theoretic results, we first show for each k, that if the class \mathcal{S}_k of k-labeled (i.e. labeled with $\{1, \ldots, k\}$, partially) versions of the structures of a given class S admits \mathcal{L} -good tree representations, then S_k satisfies a natural finitary analogue of the downward Löwenheim-Skolem (DLS) property from classical model theory, and \mathcal{S} satisfies a "k-rooted" version of this analogue. We call the latter version the \mathcal{L} -Equivalent Bounded Substructure Property, denoted \mathcal{L} -EBSP(\mathcal{S}, k). Intuitively, \mathcal{L} -EBSP(\mathcal{S}, k) asserts that any structure \mathfrak{A} in \mathcal{S} contains a small substructure \mathfrak{B} in \mathcal{S} , that is " $\mathcal{L}[m]$ -similar" to \mathfrak{A} , in the sense that \mathfrak{A} and \mathfrak{B} have the same $\mathcal{L}[m]$ theory. The bound on the size of \mathfrak{B} is a function of m alone (if \mathcal{S} and k are fixed); we call the latter a "witness function". Further, such a substructure \mathfrak{B} can always be found "around" any given set of at most k elements of \mathfrak{A} . Comparing this with the DLS property that states that every infinite structure has a countable FO-similar substructure "around" any countable subset of the former, we see (right away) that \mathcal{L} -EBSP(\mathcal{S}, k) can be regarded as a finitary analogue of the DLS. While \mathcal{L} -EBSP(\mathcal{S}, k) puts no constraints on the witness function, we show that a class \mathcal{S} that admits \mathcal{L} -good tree representations for \mathcal{S}_k , actually satisfies \mathcal{L} -EBSP (\mathcal{S}, k) with a *computable* witness function.

We now go on to show that \mathcal{L} -EBSP(\mathcal{S}, k) in turn always entails (irrespective of the abstract framework), an " \mathcal{L} -version" of $\mathsf{GLT}(k)$, denoted \mathcal{L} - $\mathsf{GLT}(k)$, which characterizes \mathcal{L} sentences that are PSC(k) in terms of $\exists^k \forall^*$ FO sentences (thus \mathcal{L} - $\mathsf{GLT}(k)$) is stronger than $\mathsf{GLT}(k)$ which is only for FO). Furthermore, if \mathcal{L} -EBSP(\mathcal{S}, k) holds with a computable witness function, then \mathcal{L} - $\mathsf{GLT}(k)$ holds in effective form, i.e. the translation from an \mathcal{L} sentence that is PSC(k) to its equivalent $\exists^k \forall^*$ sentence, is effective. It turns out that \mathcal{L} -EBSP(\mathcal{S}, k) (with computable witness functions) also entails (an effective version of) the homomorphism preservation theorem (HPT) and a parameterized generalization of it along the lines of \mathcal{L} - $\mathsf{GLT}(k)$. This we prove by showing \mathcal{L} -EBSP(\mathcal{S}, k) to entail a "homomorphic" variant of itself, which in turn entails the said generalization of the HPT. Summing up our analysis above then, we get that any class of structures falling within our abstract framework is model-theoretically very well behaved: it admits (i) the \mathcal{L} -FVC property for

operations that construct its structures, (ii) two variants of a finitary and "computable" analogue of the DLS, a "substructure" variant and a "homomorphic" variant, and finally, effective \mathcal{L} -versions of (iii) the Loś-Tarski theorem and its parameterized generalization $\mathsf{GLT}(k)$, and (iv) the HPT and its parameterized generalization akin to $\mathsf{GLT}(k)$. (Chapters 9, 10.1 and 11.3 contain the above results.)

We now show that various interesting dense classes of structures come within the fold of our abstract framework, by proving the relevant FVC theorems for these classes (Chapters 10.2, 10.3 and 10.4.). The dense classes we investigate are broadly of two kinds: special types of labeled posets and special classes of graphs. For the former, we show our results for words, trees (unordered, ordered, ranked, partially ranked) and nested words over a finite alphabet, and further regular subclasses of these. For the latter, we consider hereditary subclasses of graphs of bounded clique-width whose k-expressions exclude relabeling, such as threshold graphs, cographs, graph classes of bounded shrubdepth (which include graphs of bounded tree-depth), *m*-partite threshold graphs, and *m*-partite cographs [14]. These classes have attracted significant current interest due to their excellent algorithmic and logical properties: for instance, bounded shrub-depth classes admit algorithmic meta-theorems for CMSO (a counting extension of MSO) with elementary parameter dependence; also MSO and FO have equal expressive powers over these classes [11]. We go further to show a number of closure properties of \mathcal{L} -EBSP(\cdot, \cdot), such as closure under various set-theoretic operations and logical interpretations, enabling us to construct several model-theoretically well-behaved classes from ones that are already so (preserving the computational aspects of the model-theoretic results).

In addition to the classes described above, we identify another important collection of classes that admit our model-theoretic results: classes well-quasi-ordered (w.q.o.) under isomorphic embedding. Well-quasi-ordering is a concept that has time and again proved to be of importance for computer science [15]. We first observe that for any given class, w.q.o. under isomorphic embedding is equivalent to the class satisfying the following "unconditional version" of the Łoś-Tarski theorem: any isomorphism-closed hereditary subclass (not necessarily apriori known to be definable in a logic) is always defined by a universal FO sentence that asserts the exclusion under isomorphic embedding, of a finite set of structures from the class (the so called "forbidden" set). We now show (Chapter 11.2) that if a class \mathcal{S} is such that \mathcal{S}_k (its k-labeled version) is w.q.o. under isomorphic embedding, then S satisfies \mathcal{L} -EBSP(\mathcal{S}, k), and hence all other model-theoretic results the latter entails. The witness functions need not be computable though, so that the preservation theorems entailed by \mathcal{L} -EBSP(\mathcal{S}, k) need not hold in effective form. In recent years, the study of graph classes w.q.o./"labeled-w.q.o." under induced subgraphs has become an active research theme, particularly in the context of analyzing their cliquewidth. Cographs, k-letter graphs and k-uniform graphs are examples of (dense) graph classes that are w.q.o. under induced subgraphs (in fact, labeled-w.q.o. as well) [21]. While all these graph classes have bounded clique-width, it was shown in [21] that there are hereditary graph classes, so called "power graphs", of bounded induced path lengths and of unbounded clique-width (and hence dense) that are w.q.o. under induced subgraphs. This then adds to our list of model-theoretically well-behaved classes, various dense graph classes, including those of unbounded clique-width as well.

Extensions of thesis results: While preparing for his Ph.D. defence, the author re-

alized that the proof establishing \mathcal{L} -EBSP(\cdot, \cdot) within the abstract framework, is really constructive in nature. In fact, the small $\mathcal{L}[m]$ -similar substructure for any structure as given by \mathcal{L} -EBSP(\cdot, \cdot), is actually computable in time *linear* in the size of an \mathcal{L} -good tree representation of the structure. Observing that the mentioned substructure is indeed a "meta-kernel", we get linear time algorithmic meta-theorems for FO/MSO model checking, for any class that falls within the framework. (These results were subsequently published in [31].) Going further, it also dawned that the scope of the abstract framework could be widened by not insisting on isomorphic embedding in the monotonicity conditions, but rather allowing for other wider relations as well. This relaxation brings many more interesting classes into the ambit of the framework, including sparse graphs: for instance, the class of all trees is admitted by considering the homomorphic image relation, and more generally, bounded tree-width graphs are admitted by considering the minor relation.

Going still further, it was perceived that \mathcal{L} -EBSP (\cdot, \cdot) really asserts "logical self-similarity" "under substructure" at "small scales". This suggested a strengthening of \mathcal{L} -EBSP (\cdot, \cdot) that asserts logical self-similarity under any given relation "at all scales" for a suitable notion of scale, as a logical adaptation of the extensively studied *fractal* property from mathematics. We call this the *logical fractal* property "under" the given relation. As shown in Section 8, this property turns out to be ubiquitous in computer science. Further, for any class falling inside the abstract framework relaxed to a relation \preceq , there is an FPT algorithm parameterized by the quantifier nesting depth m of the logic \mathcal{L} that, given a structure from the class, produces an $\mathcal{L}[m]$ -similar \preceq -related structure at any given scale, in linear time. This yields the aforementioned meta-kernelization as a special case. Observing that the logical fractal property is a finitary adaptation of the "full" Löwenheim-Skolem theorem proven by Mal'tsev in 1936 [3], our generalizations above post the thesis submission, based on the abstract framework and the proof ideas for it as contained in the thesis, demonstrate that suitably adapted versions of classical model theoretic results can be widespread in the finite.

Organization of the report. In the forthcoming sections, we give more technical details for the overview presented above. In Sections 3 and 4 we discuss GLT(k) and its variants for sentences and theories, over arbitrary structures. Turning to the finite, we present in Section 5 the abstract framework within which various model-theoretic results are established. Applications of the framework are discussed in Section 6 and connections with well-quasi-ordering in Section 7. Logical fractals and algorithmic results are presented in Section 8, before concluding the report in Section 9. Finally, Appendix A shows the relevance of our notions to computer science.

PART I: CLASSICAL MODEL THEORY

3 The Generalized Łoś-Tarski Theorem for Sentences

We syntactically characterize our preservation properties via the following generalized Loś-Tarski theorem, abbreviated GLT(k). The Łoś-Tarski theorem is exactly GLT(k) when k equals 0. **Theorem 3.1** (GLT(k); Thm. 4.1.1, Chp. 4). The following are true for each $k \in \mathbb{N}$.

- 1. A sentence φ is PSC(k) if, and only if, φ is equivalent to a Σ_2^0 sentence that has k existential quantifiers.
- 2. A sentence φ is PCE(k) if, and only if, φ is equivalent to a Π_2^0 sentence that has k universal quantifiers.

Corollary 3.2 (Cor. 4.1.2, Chp. 4). Let $PSC \Leftrightarrow \bigvee_{k>0} PSC(k)$ and $PCE \Leftrightarrow \bigvee_{k>0} PCE(k)$.

- 1. A sentence φ is PSC if, and only if, φ is equivalent to a Σ_2^0 sentence. 2. A sentence φ is PCE if, and only if, φ is equivalent to a Π_2^0 sentence.

We give two proofs of Theorem 3.1, one based on saturated structures and the other based on ascending chains of structures. Both proofs first show the characterization for PCE(k), and then "dualize" it to obtain the characterization for PSC(k). The nontrivial direction is the semantics-implies-syntax direction, and in both proofs, we show that a PCE(k) sentence φ is equivalent to the set Γ of $\forall^k \exists^*$ sentences that are entailed by it; then one application of Compactness yields a finite subset of Γ , and hence a single $\forall^k \exists^*$ sentence, that is equivalent to φ . We sketch below the saturation based method of showing the equivalence of the mentioned φ and Γ .

We first show for any fixed infinite cardinal λ , that $\varphi \leftrightarrow \Gamma$ holds over the class of λ -saturated structures. These structures possess several nice model-theoretic features; of relevance to us is the feature by which such a structure contains (as substructure) an isomorphic copy of every structure of size $\leq \lambda$, that realizes the universal type (i.e. the set of universal formulae that are true) of a finite tuple of elements of the λ -saturated structure. We now show that the universal type of any k-tuple \bar{a} of a λ -saturated model \mathfrak{A} of Γ , is realized in a model $\mathfrak{B}_{\bar{a}}$ of φ , of size $\leq \lambda$; the latter then embeds into \mathfrak{A} , further "around" \bar{a} , due to the λ -saturatedness of \mathfrak{A} . The collection of all such $\mathfrak{B}_{\bar{a}}$'s forms a k-ary cover of \mathfrak{A} , making \mathfrak{A} a model of φ as the latter is PCE(k). We complete the proof by transferring the truth of $\varphi \leftrightarrow \Gamma$ over λ -saturated structures, to over all structures, using the fact that any (arbitrary) structure has an elementary extension that is λ -saturated for some λ .

"Infinitary" variants of PSC(k) and PCE(k): The notions of PSC(k) and PCE(k)can be naturally generalized to their infinitary counterparts obtained by respectively allowing cruxes to be of sizes $\langle \lambda \rangle$ and covers to be of arities $\langle \lambda \rangle$, for an infinite cardinal λ ; we call these variants $PSC(\lambda)$ and $PCE(\lambda)$ respectively. These properties are dual in the same sense as PSC(k) and PCE(k) are. The following characterizations can be shown analogously to Theorem 3.1.

Theorem 3.3 (Thm. 4.2.6, Chp. 4). The following are true for each infinite cardinal λ .

- 1. A sentence φ is $PSC(\lambda)$ if, and only if, φ is equivalent to a Σ_2^0 sentence. 2. A sentence φ is $PCE(\lambda)$ if, and only if, φ is equivalent to a Π_2^0 sentence.

Corollary 3.4 (Cor. 4.2.7, Chp. 4). For each infinite cardinal λ , a sentence is $PSC(\lambda)$ (resp. $PCE(\lambda)$) if, and only if, it is PSC(k) (resp. PCE(k)) for some $k \in \mathbb{N}$.

As mentioned in Section 2, the "Compactness flavour" of the above corollary enables us to give a new technique, via *preservation properties*, to analyse the expressive power of FO. Corollary 3.4 also gives rise to the question whether k for a given $PSC(\lambda)/PCE(\lambda)$ sentence φ , is a computable function of some (computable) parameter of φ . We answer this in the negative by showing that for every recursive function $\nu : \mathbb{N} \to \mathbb{N}$, there is a Π_2^0 (resp. Σ_2^0) sentence that is $PSC(\aleph_0)$ (resp. $PCE(\aleph_0)$) but that is not PSC(k)(resp. PCE(k)) for any $k \leq \nu(|\varphi|)$, where $|\varphi|$ denotes the length of φ . Our proof uses an unpublished result of Rossman [27] that gives a non-recursive lower bound on the length of Π_1^0 sentences equivalent to sentences defining hereditary classes (this strengthens a previous non-elementary lower bound in the same context [7]). Our result thus shows that if a sentence φ is PSC(k)/PCE(k), then the smallest such k can be non-recursively larger than $|\varphi|$.

4 GLT(k) for Theories

The case of theories (sets of sentences) for GLT(k) turns out to be much different than the case of sentences, both in terms of the results in general and the methods to prove them.

Theorem 4.1 ("Extensional" results; Thm. 5.1.1, Prop. 5.1.4, Chp. 5). Let $k \in \mathbb{N}$ and $\lambda \geq \aleph_0$.

- 1. A theory T is PCE(k) if, and only if, T is equivalent to a theory of Π_2^0 sentences, all of which have k universal quantifiers.
- 2. A theory T is $PCE(\lambda)$ if, and only if, T is equivalent to a theory of Π_2^0 sentences.
- 3. The universal theory T defining the class of undirected acyclic graphs is such that T is $PCE(\aleph_0)$ but not PCE(l) for any $l \in \mathbb{N}$.

Theorem 4.2 ("Substructural" results; Thm. 5.2.1, Chp. 5). Let $k \in \mathbb{N}$ and $\lambda \geq \aleph_1$.

- 1. A theory T is $PSC(\lambda)$ if, and only if, T is equivalent to a theory of Σ_2^0 sentences.
- 2. If a theory T is $PSC(\aleph_0)$, then T is equivalent to a theory of Σ_2^0 sentences. The same therefore holds if T is PSC(k).
- 3. The theory T defining the class of graphs not containing for any n, a vertex cycle cover comprising cycles of length $\leq n$, is such that (i) T is theory of Σ_2^0 sentences each of which has one existential quantifier, and (ii) T is not $PSC(\aleph_0)$, and thus not PSC(l) for any $l \in \mathbb{N}$.

In contrast to Corollary 3.4, we see that the "infinite to finite collapse" does not happen in the case of theories. However a collapse does happen in the infinite realm: the *PSC* heirarchy collapses to the level \aleph_1 , while the *PCE* hierarchy collapses to the level \aleph_0 . We do not know yet however, whether $PSC(\aleph_0)$ collapses to the union of PSC(k) over all k.

The proofs of the extensional characterizations above are similar to the proof of the extensional part of Theorem 3.1. The substructural results require an altogether different approach, and we establish them by using a characterization of Σ_2^0 theories in terms of *1-sandwiches*, the notion and the result both due to Keisler [3]. Given structures \mathfrak{A} and \mathfrak{B} , we say \mathfrak{B} is 1-sandwiched by \mathfrak{A} if there exist elementary extensions \mathfrak{A}' and \mathfrak{B}' resp. of \mathfrak{A} and \mathfrak{B} , such that $\mathfrak{A} \subseteq \mathfrak{B}' \subseteq \mathfrak{A}'$. A theory *T* is preserved under 1-sandwiches if for every model \mathfrak{A} of *T*, if \mathfrak{B} is 1-sandwiched by \mathfrak{A} , then \mathfrak{B} models *T*. We show Theorem 4.2 by showing that for any λ and *k*, a $PSC(\lambda)/PSC(k)$ theory is always preserved under 1-sandwiches. The idea, just as in the sketched proof of Theorem 3.1(2), is to first prove the result for μ -saturated structures, and then "transfer it out" to all structures.

Lemma 4.3 (Lem. 5.2.5, Lem. 5.2.6, Chp. 5). The following are true.

- 1. If \mathfrak{B}_1 is 1-sandwiched by \mathfrak{A}_1 , and \mathfrak{A} is a μ -saturated elementary extension of \mathfrak{A}_1 for $\mu \geq \omega$, then there is an isomorphic copy \mathfrak{B} of \mathfrak{B}_1 such that \mathfrak{B} is sandwiched by \mathfrak{A} .
- 2. If \mathfrak{B} is 1-sandwiched by a μ -saturated model \mathfrak{A} of a $PSC(\lambda)$ theory T, then \mathfrak{B} is a model of T.

Enroute proving Lemma 4.3, we show a crucial result that we call the "crux-determination" lemma; we describe this for PSC(k) theories. Firstly we extend the notion of a k-crux from sets to k-tuples in the natural way. The crux-determination lemma characterizes the conditions under which the FO-type of a k-tuple \bar{a} of a structure \mathfrak{A} determines a k-crux in a model of a PSC(k) theory T. That is, if a k-tuple \bar{b} of a structure \mathfrak{B} has the same FO-type as \bar{a} in \mathfrak{A} , then \mathfrak{B} is a model of T and \bar{b} is a k-crux of \mathfrak{B} (w.r.t. T). Towards the lemma, we introduce a key notion. For a model \mathfrak{A} of a PSC(k) theory T and a k-tuple \bar{a} of \mathfrak{A} , we say \bar{a} is a distinguished k-crux of \mathfrak{A} if there is a μ -saturated elementary extension \mathfrak{B} of \mathfrak{A} (whereby \mathfrak{B} models T) for some $\mu \geq \omega$, such that \bar{a} is a k-crux of \mathfrak{B} (and hence a k-crux of \mathfrak{A}). We now have the following characterization.

Lemma 4.4 (Crux-determination; Lem. 5.2.17, Chp. 5). Let T be a theory that is PSC(k). Then the universal type (and hence the FO-type) of a k-tuple \bar{a} of a structure \mathfrak{A} determines a k-crux in a model of T if, and only if, \mathfrak{A} is a model of T and \bar{a} is a distinguished k-crux of \mathfrak{A} .

The notion of a distinguished k-crux and its characterization by Lemma 4.4 above, turn out to play an important role in obtaining a (conditional) refinement of Theorem 4.2(2). The latter, while showing that a PSC(k) theory is always equivalent to a Σ_2^0 theory, does not tell us anything about the number of existential quantifiers appearing in the Σ_2^0 sentences of the latter theory. Given that a PSC(k) sentence is always equivalent to an $\exists^k \forall^*$ sentence, it is natural to ask if the same holds for theories too. We answer this in the affirmative, conditioned on a well-motivated hypothesis about PSC(k) theories and distinguished k-cruxes, that we state below. Observe that PSC(k) sentences (singleton theories) for instance, satisfy this hypothesis.

Hypothesis 4.5. Every model of a PSC(k) theory contains a distinguished k-crux.

Theorem 4.6 (Thm. 5.2.3, Chp. 5). Assume Hypothesis 4.5 holds. If a theory T is PSC(k), then T is equivalent to a theory of Σ_2^0 sentences, all of which have k existential quantifiers.

The proof is amongst the most technically involved of the thesis, and introduces a novel technique of getting a syntactically defined FO theory equivalent to a given FO theory satisfying a semantic property, by going outside of FO (first presented in [33]). The proof is in two parts:

- 1. "Going up": We give a characterization of PSC(k) theories in terms of sentences of the infinitary logic $\mathsf{L} = [\bigvee] [\exists^k \bigwedge] \Pi_1^0$, that consists of infinitary disjunctions of sentences obtained by taking the existential closure of infinitary conjunctions of Π_1^0 formulae, all of whose free variables are among a given set of k variables.
- 2. "Coming down": We show that a sentence Φ of L defines an elementary (i.e. FO definable) class if, and only if, Φ is equivalent to a countable subset of the set $\mathcal{A}(\Phi)$ of suitably defined *finite approximations* of Φ . Each of these finite approximations would turn out to be an $\exists^k \forall^*$ FO sentence, proving Theorem 4.6.

We explain briefly the ideas involved in proving these parts. For the "Going up" part, the non-trivial direction is showing that a PSC(k) theory T is equivalent to an L-sentence. Consider the L-sentence Φ obtained by taking the disjunction over all models \mathfrak{A} of T and all distinguished k-cruxes \bar{a} of \mathfrak{A} (which exist by Hypothesis 4.5), of the existential closure of the universal type of \bar{a} in \mathfrak{A} . That T is equivalent to Φ now follows from Lemma 4.4. For the "Coming down" part, consider the logic $\mathsf{L}_1 = [\exists^k \Lambda]$ FO defined just as $[\exists^k \Lambda] \Pi_1^0$ above, by considering all of FO instead of just Π_1^0 . For $\Psi \in \mathsf{L}_1$, define the set $\mathcal{A}(\Psi)$ of finite approximations of Ψ as follows: if $\Psi = \exists^k \bar{x} \bigwedge_{j \in J} \psi_j(\bar{x})$, then $\mathcal{A}(\Psi) = \{\exists^k \bar{x} \bigwedge_{j \in J_1} \psi_j(\bar{x}) \mid J_1 \subseteq_f J\}$ where \subseteq_f denotes "finite subset of". And now for $\Phi \in \mathsf{L}$, if $\Phi = \bigvee_{i \in I} \Psi_i$ where $\Psi_i \in [\exists^k \bigwedge] \Pi_1^0 \subseteq \mathsf{L}_1$, then define $\mathcal{A}(\Phi) = \{\bigvee_{i \in I_1} \psi_i \mid I_1 \subseteq_f I, \psi_i \in \mathcal{A}(\Psi_i)\}$. Observe that each sentence in $\mathcal{A}(\Phi)$ is equivalent to an $\exists^k \forall^*$ sentence. The heart of the proof of the "Coming down" part is now equivalence (1) below for $\Phi = \bigvee_{i \in I} \Psi_i$ as above. Once (1) is shown, the proof is completed by rewriting the RHS of (1) as a conjunction of disjuncts, and then using (FO) Compactness to reduce each (infinite) disjunct down to a finite subset of it.

$$\Phi \leftrightarrow \bigvee_{i \in I} \bigwedge_{\psi \in \mathcal{A}(\Psi_i)} \psi \tag{1}$$

We conclude Part I by presenting our key result that enables us to prove (1) – a Compactness theorem for L₁. The standard FO Compactness is a special case of this theorem.

Theorem 4.7 (Compactness for L₁; Lem. 5.2.18, Lem. 5.2.21, Chp. 5). Let $\Psi \in L_1$ be given.

- 1. Any model of Ψ is also a model of $\mathcal{A}(\Psi)$.
- 2. If every sentence of $\mathcal{A}(\Psi)$ is satisfiable, then Ψ is satisfiable.

PART II: FINITE MODEL THEORY

We now turn our attention to finite structures. As the following results show, GLT(k) fails over the class of all finite structures, and also over the classes of sparse graphs shown in [1] to satisfy the Loś-Tarski theorem. Below S-equivalent means "equivalent over S".

Proposition 4.8 (Prop. 8.1.1, Chp. 8). Let S be the class of all finite structures over a vocabulary consisting of two binary predicates, one unary predicate and two constants. For each $k \ge 0$, there is an FO sentence φ_k that is hereditary over S (hence PSC(k) over S), but that is not S-equivalent to any $\exists^k \forall^*$ sentence.

Proposition 4.9 (Thm. 8.2.2, Chp. 8). Let S be a hereditary graph class having unbounded induced path lengths. Then for each $k \geq 2$, there is an FO sentence φ_k that is PSC(k) over S, but that is not S-equivalent to any $\exists^k \forall^*$ sentence.

For both results above, the proof idea is akin to the Ehrenfeucht-Fräissé method for showing inexpressibility results in FO: the sentence φ_k is such that for each n, it has a model and a non-model such that every $\exists^k \forall^n$ sentence true in the model is also true in the non-model; then φ_k cannot be equivalent to any $\exists^k \forall^*$ sentence. Interestingly, φ_k itself turns out to be an $\exists^l \forall^*$ sentence for l > k. Proposition 4.9 naturally leads us to consider *dense structures*. We investigate various classes of posets and dense graphs, all of active ongoing interest. As mentioned in Section 2, our investigations are done within an abstract framework that incorporates the favourable structural and logical properties of the mentioned classes. Our presentation of the framework follows [31] which simplifies the more technical presentation of the framework in Chapter 10.1.

5 An Abstract Framework

A. \mathcal{L} -good tree representations: We consider classes of structures that admit tree representations in which the leaf nodes represent simple structures and the internal nodes represent operations on structures. Formally, our tree representations are ordered trees over the finite alphabet $\Sigma_{int} \cup \Sigma_{leaf}$ where Σ_{leaf} denotes the structures labeling the leaves and Σ_{int} denotes the operations. The operations can have fixed arity or unbounded arity. The latter case is used to represent an arbitrary number of iterations of a fixed arity operation; for instance, the binary disjoint union operator has a natural extension to an arbitrary arity version of it that iterates the binary disjoint union over the inputs. We formalize these ideas by equipping our trees with a ranking function $\rho : \Sigma_{int} \to \mathbb{N}$ and a subset Σ_{rank} of Σ_{int} such that an operator $\mathsf{O} \in \Sigma_{rank}$ has arity $\rho(\mathsf{O})$, and so does the fixed arity operator corresponding to an operator $\mathsf{O} \in \Sigma_{int} \setminus \Sigma_{rank}$; then the allowed arities for $\mathsf{O} \in \Sigma_{int} \setminus \Sigma_{rank}$ belong to the set $\{\rho(\mathsf{O}) + i \cdot (\rho(\mathsf{O}) - 1) \mid i \in \mathbb{N}\}$.

Let \mathcal{L} be one of the logics FO or MSO over a vocabulary τ and $\mathcal{L}[m]$ denote the sentences of \mathcal{L} of quantifier rank m. Let $\equiv_{m,\mathcal{L}}$ denote the equivalence relation on τ -structures such that for τ -structures \mathfrak{A} and \mathfrak{B} , we have $\mathfrak{A} \equiv_{m,\mathcal{L}} \mathfrak{B}$ if and only if \mathfrak{A} and \mathfrak{B} agree on all sentences of $\mathcal{L}[m]$. Let $\Delta_{m,\mathcal{L}}$ be the set of equivalence classes of the $\equiv_{m,\mathcal{L}}$ relation. For the purposes of our results, we consider \mathcal{L} -good operations that satisfy the properties stated below:

- 1. Monotonicity: Let $O \in \Sigma_{int}$ and let *n* be the/an allowed arity of O. Let $O(\mathfrak{A}_1, \ldots, \mathfrak{A}_n)$ denote the output of O when fed with $\mathfrak{A}_1, \ldots, \mathfrak{A}_n$ as inputs. Let \hookrightarrow denote "isomorphically embeddable".
 - (a) $\mathfrak{A}_i \hookrightarrow \mathsf{O}(\mathfrak{A}_1, \ldots, \mathfrak{A}_n)$ for $i \in \{1, \ldots, n\}$.
 - (b) If $\mathfrak{B}_i \hookrightarrow \mathfrak{A}_i$ for $i \in \{1, \ldots, n\}$, then $\mathsf{O}(\mathfrak{B}_1, \ldots, \mathfrak{B}_n) \hookrightarrow \mathsf{O}(\mathfrak{A}_1, \ldots, \mathfrak{A}_n)$.
 - (c) Suppose $\mathsf{O} \in \Sigma_{\text{int}} \setminus \Sigma_{\text{rank}}, r = \rho(\mathsf{O}), n = r + q \cdot (r 1) \text{ and } i = r + j \cdot (r 1) \text{ for some } j \in \{0, \dots, q 1\}$. Then $\mathsf{O}(\mathfrak{A}_1, \dots, \mathfrak{A}_i, \mathfrak{A}_{i+r}, \dots, \mathfrak{A}_n) \hookrightarrow \mathsf{O}(\mathfrak{A}_1, \dots, \mathfrak{A}_n)$.
- 2. Feferman-Vaught composition (FVC): The \mathcal{L} -FVC property of an operation $\mathsf{O} \in \Sigma_{\text{int}}$ intuitively states that the $\equiv_{m,\mathcal{L}}$ -equivalence classes of the inputs to O determine the $\equiv_{m,\mathcal{L}}$ -equivalence class of its output. Formally, there is a composition function $f_{m,\mathsf{O}}$: $(\Delta_{m,\mathcal{L}})^{\rho(\mathsf{O})} \to \Delta_{m,\mathcal{L}}$ such that the following hold. Let $\delta(\mathfrak{A})$ denote the $\equiv_{m,\mathcal{L}}$ -equivalence class of \mathfrak{A} .
 - If $O \in \Sigma_{\text{rank}}$, then $\delta(O(\mathfrak{A}_1, \ldots, \mathfrak{A}_n)) = f_{m,O}(\delta(\mathfrak{A}_1), \ldots, \delta(\mathfrak{A}_n)))$ where $n = \rho(O)$.
 - If $O \in \Sigma_{int} \setminus \Sigma_{rank}$ and r, n, i, j are as in point (1c) above, then $\delta_m(O(\mathfrak{A}_1, \ldots, \mathfrak{A}_n)) = \chi_q$ where $\chi_0 = f_{m,O}(\delta(\mathfrak{A}_1), \ldots, \delta(\mathfrak{A}_r))$ and $\chi_{j+1} = f_{m,O}(\chi_j, \delta(\mathfrak{A}_{i+1}), \ldots, \delta(\mathfrak{A}_{i+r-1}))$.

The above properties are satisfied by a variety of operations as we will see later. As quick examples, disjoint union satisfies the above properties for MSO, as does Cartesian product for FO. For a set Σ_{int} of \mathcal{L} -good operations and a tree t over $\Sigma_{int} \cup \Sigma_{leaf}$, let $\mathfrak{A} =$ $\mathsf{Str}(t)$ be the natural structure associated with t, obtained by a "bottom-up evaluation" in the latter. We then say t is an \mathcal{L} -good tree representation of \mathfrak{A} over $\Sigma_{int} \cup \Sigma_{leaf}$ and that Str is an \mathcal{L} -good representation map. We say a class \mathcal{S} of structures admits an \mathcal{L} -good tree representation if there exist Σ_{int} and Σ_{leaf} such that for each $\mathfrak{A} \in \mathcal{S}$, there is an \mathcal{L} -good tree representation of \mathfrak{A} over $\Sigma_{int} \cup \Sigma_{leaf}$. The following theorem is at the heart of most of the results in the remainder of this report. It shows shows why \mathcal{L} -good tree representations are called so. The theorem is a joint presentation of Theorems 10.1.1 and 10.4.11 from Chapter 10. (The latter theorems together are actually slighty more general.)

Theorem 5.1. Let S be a class of structures that admits an \mathcal{L} -good tree representation. Let \mathcal{T} be a class of \mathcal{L} -good tree representations of the structures of S over some alphabet $\Sigma_{leaf} \cup \Sigma_{int}$ and let $Str : \mathcal{T} \to S$ be the associated \mathcal{L} -good representation map. Suppose \mathcal{T} is a regular language of trees. Then there exist computable functions $\eta_1, \eta_2 : \mathbb{N} \to \mathbb{N}$ such that for each $t \in \mathcal{T}$ and $m \in \mathbb{N}$, we have the following:

- 1. (Height reduction) There exists a subtree s_1 of t, of height $\leq \eta_1(m)$, such that (i) $s_1 \in \mathcal{T}$, (ii) $\mathsf{Str}(s_1) \hookrightarrow \mathsf{Str}(t)$, and (iii) $\mathsf{Str}(s_1) \equiv_{m,\mathcal{L}} \mathsf{Str}(t)$.
- 2. (Degree reduction) There exists a subtree s_2 of t, of degree $\leq \eta_2(m)$, such that (i) $s_2 \in \mathcal{T}$, (ii) $\mathsf{Str}(s_2) \hookrightarrow \mathsf{Str}(t)$, and (iii) $\mathsf{Str}(s_2) \equiv_{m,\mathcal{L}} \mathsf{Str}(t)$.

Indeed Theorem 5.1 shows that for S as in the theorem, for any structure \mathfrak{A} in S, a degree and height reduction of a tree representation t of \mathfrak{A} given by Str yields a computably small subtree of t that represents a small $\mathcal{L}[m]$ -similar substructure of \mathfrak{A} in S. We use this crucially in our model-theoretic results. Theorem 5.1 turns out to also have important algorithmic and "conceptual" consequences (Section 8) due to the constructive nature of its proof that we sketch now. We make an important use of a composition lemma for ordered trees given by Lemma 6.1. Let $t \in \mathcal{T}$ be given. Since \mathcal{T} is regular, it is definable in MSO [4] by a sentence of rank say n.

- 1. Height reduction: Suppose there is a long root-to-leaf path in t. We label each node a of this path with the pair (δ_1, δ_2) where δ_1 is the $\equiv_{m,\mathcal{L}}$ class of the structure \mathfrak{A}_a represented by $\mathsf{t}_{\geq a}$ which is the subtree of t rooted at a ($\mathsf{t}_{\geq a}$ need not be in \mathcal{T}), and δ_2 is the $\equiv_{n,\text{MSO}}$ class of $\mathsf{t}_{\geq a}$ itself. Given that the indices of the $\equiv_{m,\mathcal{L}}$ and $\equiv_{n,\text{MSO}}$ relations over all finite structures are finite (and bounded by computable functions of m and n resp. [20]), the number of pairs (δ_1, δ_2) is finite (and bounded by a computable function of m and n). Then some such pair repeats at a node a and a descendent b of it along the path. We then replace $\mathsf{t}_{\geq a}$ with $\mathsf{t}_{\geq b}$ to get a proper subtree t_1 of t . Since $\mathsf{t}_{\geq b} \equiv_{n,\text{MSO}} \mathsf{t}_{\geq a}$ it follows by Lemma 6.1 that $\mathsf{t}_1 \equiv_{n,\text{MSO}} \mathsf{t}$; then $\mathsf{t}_1 \in \mathcal{T}$ since $\mathsf{t} \in \mathcal{T}$. Again since $\mathfrak{A}_b \equiv_{m,\mathcal{L}} \mathfrak{A}_a$ and since the operations of Σ_{int} are \mathcal{L} -good, we have $\mathsf{Str}(\mathsf{t}_1) \hookrightarrow \mathsf{Str}(\mathsf{t})$ and $\mathsf{Str}(\mathsf{t}_1) \equiv_{m,\mathcal{L}} \mathsf{Str}(\mathsf{t})$. Iterating, we eventually get the desired subtree s_1 .
- 2. Degree reduction: We illustrate our reasoning for the case when for each $O \in \Sigma_{int} \setminus \Sigma_{rank}$, we have $\rho(O) = 2$. Let *a* be a node of t of large degree, say *r*; then the operation labeling it is in $\Sigma_{int} \setminus \Sigma_{rank}$. Let $z = t_{\geq a}$. For $i \in \{1, \ldots, r-1\}$, let x_i , resp. y_i , be the subtree of z obtained by retaining the first *i*, resp. the last r - i, child subtrees of the root of z and deleting the rest; then z is the tree $x_i \odot y_i$ obtained by merging x_i and y_i at their

roots (and in that order). Label each x_i with the pair (δ_1, δ_2) as described above; so δ_1 is the $\equiv_{m,\mathcal{L}}$ class of the structure represented by x_i and δ_2 the $\equiv_{n,\text{MSO}}$ class of x_i itself. Since r is large, such a pair repeats for some $l, k \in \{1, \ldots, r-1\}, l < k$. Then consider the tree $z_2 = x_l \odot y_k$ and let t_2 be the proper subtree of t obtained by replacing z with z_2 in t. By Lemma 6.1, $z_2 \equiv_{n,\text{MSO}} z$, whereby $t_2 \equiv_{n,\text{MSO}} t$; then $t_2 \in \mathcal{T}$. Since the operations of Σ_{int} are \mathcal{L} -good, we have $\text{Str}(z_2) \hookrightarrow \text{Str}(z)$ and $\text{Str}(z_2) \equiv_{m,\mathcal{L}} \text{Str}(z)$; then $\text{Str}(t_2) \hookrightarrow \text{Str}(t)$ and $\text{Str}(t_2) \equiv_{m,\mathcal{L}} \text{Str}(t)$. Iterating, we eventually get the desired subtree s_2 .

B. The \mathcal{L} -Equivalent Bounded Substructure Property: The following abstract property of finite structures formalizes the implication of Theorem 5.1, discussed above. (This property was first introduced in [32] for FO.)

Definition 5.2 (\mathcal{L} -EBSP(\mathcal{S}, k); Def. 9.1, Chp. 9). Let \mathcal{S} be a class of structures and $k \in \mathbb{N}$. We say that \mathcal{S} satisfies the \mathcal{L} -Equivalent Bounded Substructure Property for parameter k, abbreviated \mathcal{L} -EBSP(\mathcal{S}, k), if there exists a function $\vartheta : \mathbb{N} \to \mathbb{N}$ such that for each $m \in \mathbb{N}$, for each structure \mathfrak{A} of \mathcal{S} and for each subset W of at most k elements from \mathfrak{A} , there exists a structure \mathfrak{B} such that (i) $\mathfrak{B} \in \mathcal{S}$, (ii) $\mathfrak{B} \subseteq \mathfrak{A}$, (iii) the elements of W are contained in \mathfrak{B} , (iv) $|\mathfrak{B}| \leq \vartheta(m)$, and (v) $\mathcal{B} \equiv_{m,\mathcal{L}} \mathfrak{A}$. We call ϑ a witness function for \mathcal{L} -EBSP(\mathcal{S}, k).

The above definition does not insist on the computability of the witness function; we present scenarios later (Section 7) where the witness functions are necessarily uncomputable. However, for the classes we consider in this section, we have the following result that Theorem 5.1 entails.

Proposition 5.3 (Lem. 10.1.2, Chp. 10). For $k \in \mathbb{N}$ and a class S of structures, let S_k be the class of structures obtained by labeling (possibly partially) the elements of the structures of S with labels from $\{1, \ldots, k\}$. Suppose S_k admits an \mathcal{L} -good tree representation with a computable \mathcal{L} -good representation map. Then \mathcal{L} -EBSP(S, k) holds with a computable witness function.

Section 6 discusses a number of concrete instances where the premises of Proposition 5.3 are satisfied, wherby these instances satisfy \mathcal{L} -EBSP(\cdot, k). As mentioned in Section 2, \mathcal{L} -EBSP(\cdot, k) can be seen as a finitary analogue of the DLS property; then a class satisfying \mathcal{L} -EBSP(\cdot, k) satisfies (a finitary adaptation of) the DLS theorem. We remark that there has been no study of the DLS (or adaptations of it) over finite structures, except for [16] which proves a number of negative results concerning this theorem over the class of all finite structures.

C. \mathcal{L} -EBSP(\mathcal{S}, k) entails GLT(k) and HPT: We say an \mathcal{L} sentence φ is PSC(k) over a class \mathcal{S} if the class of models of φ in \mathcal{S} is PSC(k) relativized to \mathcal{S} . We say \mathcal{L} -GLT(k) holds over \mathcal{S} if for all \mathcal{L} sentences φ , we have φ is PSC(k) over \mathcal{S} if, and only if, φ is \mathcal{S} -equivalent to an $\exists^k \forall^*$ FO sentence.

Theorem 5.4 (Thm. 9.1.2, Chp. 9). Let S be a class of finite structures and $k \in \mathbb{N}$ be such that \mathcal{L} -EBSP(S, k) holds. Then \mathcal{L} -GLT(k), and hence GLT(k) and the Loś-Tarski theorem, hold over S. Further, if there is a computable witness function for \mathcal{L} -EBSP(S, k), then the translation from an \mathcal{L} sentence that is PSC(k) over S, to an S-equivalent $\exists^k \forall^*$ sentence, is effective. The key idea of the proof is to construct for a given PSC(k) sentence φ , an $\exists^k \forall^*$ sentence that checks in any given structure \mathfrak{A} , the existence of a set W of $\leq k$ elements such that the truth of φ in the substructures of \mathfrak{A} in \mathcal{S} , that contain W, and that are of *bounded size*, itself suffices to ascertain the truth of φ in \mathfrak{A} . Given that \mathcal{L} -EBSP(\mathcal{S}, k) is true, if ϑ is a witness function and m is the rank of φ , then one sees that the mentioned bound can indeed be taken to be $\vartheta(m)$.

Using similar ideas as above in "dual" form, we show that \mathcal{L} -EBSP(\mathcal{S}, k) entails a generalization of the HPT. The HPT characterizes preservation under homomorphisms in terms of existential-positive sentences which are FO sentences built up from positive atomic formulae using conjunctions, disjunctions and existential quantifications. Towards our result, we define *k*-ary homomorphic covers and preservation under *k*-ary homomorphic c

Definition 5.5 (Defn. 11.3.2, Defn. 11.3.4, Chp. 11). Given a τ -structure \mathfrak{A} , a nonempty collection \mathcal{R} of τ_k -structures (expansions of τ -structures with k constants) is called a k-ary homomorphic cover of \mathfrak{A} if for every k-tuple \bar{a} of \mathfrak{A} , there is a homomorphism $h_{\bar{a}} : (\mathfrak{B}, \bar{b}) \to (\mathfrak{A}, \bar{a})$ for some $(\mathfrak{B}, \bar{b}) \in \mathcal{R}$. The set $\{h_{\bar{a}} \mid \bar{a} \text{ is a } k$ -tuple of $\mathfrak{A}\}$ is called a k-ary homomorphic covering from \mathcal{R} to \mathfrak{A} . For an \mathcal{L} sentence φ , if \mathcal{M} is the class of expansions of the models of φ with k constants, then we say φ is preserved under k-ary homomorphic coverings, in short φ is h-PC(k), if for every collection \mathcal{R} of structures of \mathcal{M} , if there is a k-ary homomorphic covering from \mathcal{R} to \mathfrak{A} , then \mathfrak{A} models φ .

We say that a class S satisfies the generalized HPT for \mathcal{L} and k, denoted \mathcal{L} -GHPT(k), if the following is true: an \mathcal{L} sentence φ is h-PC(k) over S if, and only if, φ is S-equivalent to a $(\forall^k \exists^*)$ -positive (FO) sentence which is sentence having the form $\forall x_1 \ldots \forall x_k \psi(x_1, \ldots, x_k)$ where $\psi(x_1, \ldots, x_k)$ is an existential positive formula. We now show \mathcal{L} -EBSP (\mathcal{S}, k) entails \mathcal{L} -GHPT(k) for all k, by showing that a homomorphic version of \mathcal{L} -EBSP (\mathcal{S}, k) "interpolates" the said implication.

Definition 5.6 $(h-\mathcal{L}\text{-}\mathsf{EBSP}(\mathcal{S},k);$ Def. 11.3.5, Chp. 11). A class \mathcal{S} satisfies the *homomorphic* $\mathcal{L}\text{-}\mathsf{EBSP}$ for parameter k, abbreviated $h-\mathcal{L}\text{-}\mathsf{EBSP}(\mathcal{S},k)$, if there is a function $\vartheta : \mathbb{N} \to \mathbb{N}$ such that for each $m \in \mathbb{N}$, for each structure \mathfrak{A} of \mathcal{S} and for every k-tuple \bar{a} from \mathfrak{A} , there exists $\mathfrak{B} \in \mathcal{S}$ and a k-tuple \bar{b} of \mathfrak{B} such that (i) there is a homomorphism $h : (\mathfrak{B}, \bar{b}) \to (\mathfrak{A}, \bar{a}),$ (ii) $|\mathfrak{B}| \leq \vartheta(m)$, and (iii) $\mathfrak{B} \equiv_{m,\mathcal{L}} \mathfrak{A}$. We call ϑ a witness function of $h-\mathcal{L}\text{-}\mathsf{EBSP}(\mathcal{S},k)$.

Theorem 5.7 (Thm. 11.3.7, Chp. 11). Let S be a class of finite structures and $k \in \mathbb{N}$ be such that h- \mathcal{L} -EBSP(S, k) holds. Then \mathcal{L} -GHPT(k), and hence HPT, hold over S. Further, if there is a computable witness function for h- \mathcal{L} -EBSP(S, k), then the translation from an \mathcal{L} sentence that is h-PC(k) over S to an S-equivalent ($\forall^k \exists^*$)-positive sentence, is effective. The above results also hold with \mathcal{L} -EBSP(S, k) in place of h- \mathcal{L} -EBSP(S, k) (as the former entails the latter).

6 Applications

In this section, we show that various classes of dense structures, specifically posets and recently defined subclasses of bounded clique-width graphs, fall within the abstract framework described above and are hence model-theoretically very well-behaved: they admit the FVC property for the operations that construct their structures, and effective versions of the DLS, \mathcal{L} -GLT(k) and \mathcal{L} -GHPT(k) theorems for all k and for \mathcal{L} as FO and MSO.

A. Words, trees (unordered, ordered, ranked or partially ranked) and nested words: A tree (of any of the above kinds) over a finite alphabet Σ has a natural \mathcal{L} -good tree representation; we describe this for an ordered partially ranked Σ -tree whose ranking function is $\nu : X \to \mathbb{N}$ where $X \subseteq \Sigma$. The tree representation has the following parameters: $\Sigma_{\text{leaf}} = \Sigma$, $\Sigma_{\text{int}} = \{\mathsf{O}_a \mid a \in \Sigma\}$, $\Sigma_{\text{rank}} = \{\mathsf{O}_a \mid a \in X\}$, and $\rho : \Sigma_{\text{int}} \to \mathbb{N}$ is such that $\rho(\mathsf{O}_a) = \nu(a)$ if $a \in X$, else $\rho(\mathsf{O}_a) = 2$. Here O_a takes in a sequence of n trees as input, makes them the child subtrees in that order, of a new root node labeled a and outputs the resulting tree. The monotonicity properties (Section 5.A) of O_a are easy to see. The FVC property follows from Lemma 6.1. We first introduce some terminology. For an alphabet Ω , given ordered Ω -trees t, s and a non-root node a of t, the join of s to t to the right of a, denoted t \cdot_a^{\rightarrow} s, is defined (upto isomorphism) as the tree obtained by making s as a new child subtree of the parent of a in t, at the successor position of the position of a among the siblings of a in t. Similarly define t \cdot_a^{\leftarrow} s (joining to the left of a) and t \cdot_a^{\uparrow} s (joining below a).

Lemma 6.1 (Composition lemma for ordered trees; Lem. 10.2.3, Chp. 10). Given a finite alphabet Ω , let $\mathbf{t}_i, \mathbf{s}_i$ be non-empty ordered Ω -trees, and let a_i be a non-root node of \mathbf{t}_i , for each $i \in \{1, 2\}$. Let $m \geq 2$ and suppose that $(\mathbf{t}_1, a_1) \equiv_{m, \mathcal{L}} (\mathbf{t}_2, a_2)$ and $\mathbf{s}_1 \equiv_{m, \mathcal{L}} \mathbf{s}_2$. Then $((\mathbf{t}_1 \cdot \overrightarrow{a_1} \mathbf{s}_1), a_1) \equiv_{m, \mathcal{L}} ((\mathbf{t}_2 \cdot \overrightarrow{a_2} \mathbf{s}_2), a_2)$. The result also holds if we replace $\cdot \rightarrow$ with $\cdot \leftarrow$ or \cdot^\uparrow .

Nested words have natural representations using trees of our kind. The non-trivial part here is showing the FVC property and this follows from Lemma 6.2. For given nested words u and v, let $u \uparrow_e v$ denote the nested word obtained by inserting v in u at a position e of the latter.

Lemma 6.2 (Composition lemma for nested words; Lem. 10.2.6, Chp. 10). For a finite alphabet Σ , let u_i, v_i be nested Σ -words and let e_i be a position in u_i for $i \in \{1, 2\}$. Then given $m \in \mathbb{N}$, if $(u_1, e_1) \equiv_{m,\mathcal{L}} (u_2, e_2)$ and $v_1 \equiv_{m,\mathcal{L}} v_2$, then $(u_1 \uparrow_{e_1} v_1) \equiv_{m,\mathcal{L}} (u_2 \uparrow_{e_2} v_2)$.

B. *n*-partite cographs: These recently defined graphs [14] are subclasses of bounded clique-width graphs, that generalize a number of graph classes: threshold graphs, cographs, graph classes of bounded tree-depth and those of bounded shrub-depth. An *n*-partite cograph G = (V, E) is a graph that is built up from the point graphs corresponding to the vertices of V, labeled with labels from $[n] = \{1, \ldots, n\}$, using operations O_f defined as follows for functions $f : [n]^2 \to \{0, 1\}$: the operation O_f takes in $p \ge 2$ graphs G_1, \ldots, G_p that are vertex-labeled with labels from [n], and produces a graph that is their disjoint union alongwith the addition of all edges between vertices of G_i with label l and vertices of G_j with label k where $1 \le i < j \le p, 1 \le l, k \le n$, and f(l, k) = 1. One sees that *n*-partite cographs are exactly the subclass of graphs of NLC-width $\le n$ (and hence clique-width $\le n$) that are defined without relabelings. Further, these graphs fall within our abstract framework with $\Sigma_{\text{leaf}} = [n], \Sigma_{\text{int}} = \{O_f \mid f : [n]^2 \to \{0,1\}\}, \Sigma_{\text{rank}} = \emptyset$ and ρ as the constant 2. The monotonicity properties are easy to see; the FVC property follows by Lemma 6.3 below and the fact that $O_f(G_1, \ldots, G_n) = O_f(H_{n-2}, G_n)$ where $H_1 = O_f(G_1, G_2)$ and $H_i = O_f(H_{i-1}, G_{i+1})$ for $1 \le i \le n - 2$.

Lemma 6.3 (Composition lemma for O_f ; Lem. 10.3.2, Chp. 10). For $n \in \mathbb{N}$, let G_i and H_i be graphs whose vertices are labeled with labels from [n], for $i \in \{1, 2\}$. If $G_1 \equiv_{m,\mathcal{L}} G_2$ and $H_1 \equiv_{m,\mathcal{L}} H_2$, then $O_f(G_1, H_1) \equiv_{m,\mathcal{L}} O_f(G_2, H_2)$ for each function $f : [n]^2 \to \{0, 1\}$ and $m \in \mathbb{N}$.

C. Classes generated using set theoretic and logical operations: We now present a number of methods of generating classes that satisfy \mathcal{L} -EBSP(\cdot, k) from those known to satisfy the latter, thereby preserving the model-theoretic properties of the latter entailed by \mathcal{L} -EBSP(\cdot, k) (Chapter 10.4). For $i \in \{1, 2\}$, suppose \mathcal{L} -EBSP(\mathcal{S}_i, k_i) is true with witness function ϑ_i . Then each of the following classes satisfy \mathcal{L} -EBSP(\cdot, k) for the k and witness function ϑ mentioned.

- 1. Any hereditary subclass of S_i , with $k = k_i$ and $\vartheta = \vartheta_i$
- 2. The union $S_1 \cup S_2$, with $k = \min(k_1, k_2)$ and $\vartheta = \max(\vartheta_1, \vartheta_2)$
- 3. The intersection $S_1 \cap S_2$, with $k = k_2$ and $\vartheta = \vartheta_2$ if S_1 is hereditary, and $k = \max(k_1, k_2)$ and $\vartheta = \max(\vartheta_1, \vartheta_2)$ if both S_1, S_2 are hereditary
- 4. Any $\mathcal{L}[r]$ definable subclass of \mathcal{S}_i , with $k = k_i$ and $\vartheta(m) = \vartheta_i(r)$ if $m \leq r$ else $\vartheta(m) = \vartheta_i(m)$.

We now look at classes generated using operations that are "implementable" using quantifier-free translation schemes [22]. Specifically, we consider such translation schemes that "act on" the *n*-disjoint sum of input structures $\mathfrak{A}_1, \ldots, \mathfrak{A}_n$ or the *n*-copy of an input structure \mathfrak{A} . The former is the structure obtained by expanding the disjoint union of $\mathfrak{A}_1, \ldots, \mathfrak{A}_n$ with fresh unary predicates P_1, \ldots, P_n where P_i is interpreted as the universe of \mathfrak{A}_i for $i \in \{1, \ldots, n\}$. The latter is the structure obtained by equipping the *n*-disjoint sum of *n* isomorphic copies of \mathfrak{A} with a binary relation that relates corresponding elements in these isomorphic copies. Let O be an *n*-ary operation implemented by the above mentioned kinds of translation schemes. Define the dimension of O to be the minimum dimension of its implementing translation schemes (the dimension of the latter is the number of free variables in its universe-defining formula). Call O as "sum-like" if its dimension is one, else call it "product-like". For example, disjoint union and the operator O_f of Lemma 6.3 are sum-like, whereas Cartesian and tensor products are product-like. We now have the following.

Proposition 6.4 (Cor. 10.4.7, Chp. 10). Let S_1, \ldots, S_n and S be classes of structures and let $O: S_1 \times \cdots \times S_n \to S$ be a surjective n-ary operation that is implementable using a quantifier-free translation scheme of the kind mentioned above. Let the dimension of Obe t.

- 1. If \mathcal{L} -EBSP (\mathcal{S}_i, k_i) is true for $k_i \in \mathbb{N}$ for each $i \in \{1, ..., n\}$, then so is \mathcal{L} -EBSP (\mathcal{S}, l) , for $l = min\{k_i \mid i \in \{1, ..., n\}\}$, whenever O is sum-like.
- 2. If FO-EBSP($S_i, k_i \cdot t$) is true for $k_i \in \mathbb{N}$ for each $i \in \{1, ..., n\}$, then so is FO-EBSP(S, l), for $l = min\{k_i \mid i \in \{1, ..., n\}\}$, whenever O is product-like.

In the implications above, if there are computable witness functions for each of the conjuncts in the antecedent, then there is a computable witness function for the consequent as well.

We now observe that Proposition 6.4 in conjunction with the set theoretic closure properties above, shows that finite unions of classes obtained by applying finite compositions of the operations of above kind, to a given class S of structures, preserve the \mathcal{L} -EBSP(\cdot, \cdot) property of S. However, given that taking (even binary) unions can in general increase the value of the witness function, it is unclear if infinite unions of the kind mentioned would preserve \mathcal{L} -EBSP(\cdot, \cdot). We show that if the infinite unions are "regular", then \mathcal{L} -EBSP($\cdot, 0$) indeed remains preserved. More precisely, consider a set Op of \mathcal{L} -good operations and let \mathcal{T} be a class of trees over Op in which the leaf nodes are labeled with a symbol \diamond that acts a "place holder" for an input structure. Each tree $t \in \mathcal{T}$ can be seen as an operation itself, with inputs fed at the leaves and output obtained at the root. Given a class S, let t(S) denote the class obtained by "applying" t to the structures of S. By extension, let $\mathcal{T}(S) = \bigcup_{t \in \mathcal{T}} t(S)$. We now show the following result using similar ideas as for Theorem 5.1.

Theorem 6.5. Let \mathcal{T} as described above be a regular language of trees. If \mathcal{L} -EBSP($\mathcal{S}, 0$) is true (with a computable witness function), then so is \mathcal{L} -EBSP($\mathcal{T}(\mathcal{S}), 0$).

Using the methods above, we get a wide array of classes satisfying \mathcal{L} -EBSP (\cdot, k) . Classes 1-11 in Table 1 of Section 8 are examples (these in fact satisfy a strengthened version of \mathcal{L} -EBSP (\cdot, k)).

7 Well-quasi-ordering and \mathcal{L} -EBSP

A class S is *well-quasi-ordered* (w.q.o.) under a pre-order \leq on S, if for every infinite sequence $\mathfrak{A}_1, \mathfrak{A}_2, \ldots$ of structures of S, there exists i < j such that $\mathfrak{A}_i \leq \mathfrak{A}_j$. A priori, there is no reason to expect any relation between well-quasi-ordering and \mathcal{L} -EBSP. Surprisingly, the following holds.

Theorem 7.1 (Thm. 11.2.2, Prop. 11.2.4, Chp. 11). Let S be a class of structures and S_k be as in Proposition 5.3. If S_k is w.q.o. under isomorphic embedding, then \mathcal{L} -EBSP(S, k) holds. The witness function is not computable in general. Also, the converse is not true in general.

While Theorem 7.1 channelizes the ongoing research in w.q.o. theory [21] to our modeltheoretic studies (see Section 2), it also gives a technique to show \mathcal{L} -EBSP(\cdot, \cdot) for a class of structures. For instance, while the fact that for n > 1, the class \mathcal{S} of *n*-dimensional grid posets satisfies FO-EBSP(\cdot, k) follows from the FO-FVC property of Cartesian product and Theorem 6.5, nothing can be inferred about MSO-EBSP(\cdot, k) since Cartesian product does not have the MSO-FVC property. But by Theorem 7.1, MSO-EBSP(\mathcal{S}, k) is true since linear orders are w.q.o. under embedding and hence so is their *n*-fold Cartesian product (which gives \mathcal{S}). However, as MSO-SAT is undecidable over even 2-dimensional grid posets, any witness function for MSO-EBSP(\mathcal{S}, k) is necessarily uncomputable.

8 Extensions of Dissertation Results

In this section, we let \mathbb{N} denote positive integers. A function $f: \mathbb{N} \to \mathbb{N}$ is called a *scale* function if it is strictly increasing. The i^{th} scale, denoted $\langle i \rangle_f$, is defined as the interval $[1, f(1)] = \{j \mid 1 \leq j \leq f(1)\}$ if i = 1, and $[f(i-1)+1, f(i)] = \{j \mid f(i-1)+1 \leq j \leq f(i)\}$ if i > 1. As mentioned in Section 2, various observations about the proof of Theorem 5.1 inspire the following definition.

Definition 8.1 (Logical fractal¹). Given a class S of structures, $k \in \mathbb{N} \cup \{0\}$, and a pre-order \leq on S_k (where S_k is as in Proposition 5.3), we say S is an (\mathcal{L}, k) -fractal under \leq , if there exists a function $\vartheta_k : \mathbb{N}^2 \to \mathbb{N}$ such that (i) $\vartheta_k(n, \cdot)$ is a scale function for all $n \in \mathbb{N}$, and (ii) for each $m \in \mathbb{N}$ and each structure \mathfrak{A} of S_k , if f is the function $\vartheta_k(m, \cdot)$ and $|\mathfrak{A}| \in \langle i \rangle_f$ for $i \geq 2$, then for all $j \neq i$, there exists a structure \mathfrak{B} in S_k such that (i) $\mathfrak{B} \leq \mathfrak{A}$ if $j \leq i$, else $\mathfrak{A} \leq \mathfrak{B}$, (ii) $|\mathfrak{B}| \in \langle j \rangle_f$, and (iii) $\mathfrak{B} \equiv_{m,\mathcal{L}} \mathfrak{A}$. We say ϑ_k is a witness to the (\mathcal{L}, k) -fractal property of S.

Observe that if S is an (\mathcal{L}, k) -fractal under isomorphic embedding, then \mathcal{L} -EBSP (\mathcal{S}, k) is true. Table 1 lists a wide spectrum of classes of computer science interest, that satisfy Definition 8.1. The listing in Table 1 is according to the complexity of the relation \preceq appearing in column 4. We put the function $\nu(m) = \vartheta(m, 1)$ in column 5; we call this a supporting function. In all the cases listed where this function is computable, the witness function $\vartheta(m,n)$ turns out to be $O(\nu(m) \cdot n)$. The results of Table 1 follow from the generalizations of Proposition 5.3 and Theorem 7.1 presented below, that are established exactly like the latter. Towards these results, we first relax the conditions of the abstract framework in part A of Section 5 to consider \prec instead of \hookrightarrow . Define an (\mathcal{L}, \preceq) -good tree representation as an \mathcal{L} -good tree representation whose operations satisfy the monotonicity properties of Section 5 where \hookrightarrow is replaced with \prec . Call the associated representation map as (\mathcal{L}, \preceq) -good. We now consider special kinds of (\mathcal{L}, \preceq) -good representation maps Str, those we call (\mathcal{L}, \prec) -great, that satisfy the following conditions: (i) Str is computable, and (ii) there is a strictly increasing function $\beta : \mathbb{N} \to \mathbb{N}$ such that for every t, s in the domain of Str, if $abs(|\mathbf{t}| - |\mathbf{s}|) \le n$, then $abs(|\mathsf{Str}(\mathbf{t})| - |\mathsf{Str}(\mathbf{s})|) \le \beta(n)$, where $abs(\cdot)$ denotes "absolute value". We now present our results which include an algorithmic metatheorem obtained by the simple observation that the labelings, "graftings" and "prunings" of tree representations t as described in the proof sketch of Theorem 5.1, which enable getting "downward self-similarity", are doable in time linear in |t|. (This is demonstrated in detail in the proof of Proposition 3.2 in [31].) Further, the same ideas in a "reverse direction" give us "upward self-similarity" again in linear time. All the classes in Table 1 that have computable supporting functions admit (\mathcal{L}, \preceq) -great representations, whereby they are (\mathcal{L}, k) -fractals under \leq , for the k and \leq mentioned against them.

Theorem 8.2. Given a class S of structures, let S_k be as before, the class of structures obtained by labeling (possibly partially) the elements of the structures of S with labels from $\{1, \ldots, k\}$. For a pre-order \preceq on S_k , suppose S_k admits (\mathcal{L}, \preceq) -great tree representations. Then the following hold:

- 1. S is an (\mathcal{L}, k) -fractal under \leq having a computable witness function $\vartheta_k : \mathbb{N}^2 \to \mathbb{N}$.
- There exists an FPT algorithm Fractal-generator, parameterized by m (the "degree of logical self-similarity") that, given a structure 𝔅 ∈ 𝔅_k, an (𝔅, ≤)-great tree representation t of 𝔅, and a number j ≥ 1, outputs in time g(m) · (|t|+j) for some computable function g : 𝔅 → 𝔅, a structure 𝔅 ∈ 𝔅_k, such that if f = ϑ_k(m, ·) and |𝔅| ∈ ⟨i⟩_f, then (i) |𝔅| ∈ ⟨j⟩_f, (ii) 𝔅 ≤ 𝔅 if j ≤ i, else 𝔅 ≤ 𝔅, and (iii) 𝔅 ≡_{m,𝔅} 𝔅. In short, Fractal-generator produces a logically self-similar structure at any given scale in FPT linear time.

¹A research proposal on this notion, written jointly with Anuj Dawar, has been granted a 3 year funding by the Leverhulme Trust, UK. The author has joined the University of Cambridge, UK as a post-doctoral research associate to pursue this research.

No.	Class	(\mathcal{L}, k) -fractal	Fractal under \preceq for	Supporting		
		for $(\mathcal{L}, k) =$	$\preceq =$	function		
Posets						
1.	Regular languages of words/nested	MSO, all k	subword/sub-	non-elem.		
	words		nested-word			
2.	Regular languages of trees (ordered, un-	MSO, all k	subtree	non-elem.		
	ordered, ranked, partially ranked)					
3.	Regular languages of traces	MSO, all k	subtrace	non-elem.		
4a.	<i>r</i> -dimensional grid posets	FO, all k	subgrid	non-elem.		
4b.	"	CMSO, all k	"	uncomp.		
5.	All grid posets	FO, $k = 0, 1$	subgrid	non-elem.		
	(Graphs				
6.	Hamming graphs of the n -clique	FO, $k = 0$	ind. subgraph	non-elem.		
7a.	Disjoint unions of paths	FO, $k = 0, 1$	ind. subgraph	exp.		
7b.	"	CMSO, $k = 0, 1$	"	non-elem.		
8.	<i>d</i> -regular trees	CMSO, $k = 0$	ind. subgraph	non-elem.		
9.	Graphs of tree-depth $\leq d$	CMSO, all k	ind. subgraph	d-fold exp.		
10.	Hereditary graph classes of shrub-depth	CMSO, all k	ind. subgraph	d-fold exp.		
	$\leq d$					
11.	m-partite cographs (includes threshold	CMSO, all k	ind. subgraph	non-elem.		
	graphs, Turan graphs, cographs, m -					
	partite threshold graphs)					
12.	Power graphs $[21]^1$	CMSO, $k = 0$	ind. subgraph	uncomp.		
13.	Colored forests of height $\leq d$	CMSO, all k	surj. hom. img.;	d-fold exp.		
			vertex-minor; minor			
14.	Colored forests	CMSO, all k	hom. img.; minor;	non-elem.		
			vertex-minor			
15.	Graphs excluding a top. minor isomor-	CMSO, $k = 0$	topological minor	uncomp.		
	phic to P_k with each edge duplicated					
16.	Series-parallel graphs ²	CMSO, $k = 0$	minor	$\operatorname{comp.}(?)$		
17.	Graphs of tree-width ² $\leq n$	CMSO, $k = 0$	minor	$\operatorname{comp.}(?)$		
18.	Graphs of clique-width/NLC-width $\leq n$	CMSO, all k	a comp. reln.	non-elem.		
19a.	Graphs of rank-width ³ $\leq n$	CMSO, all k	vertex-minor	$\operatorname{comp.}(?)$		
19b.		"	a comp. reln.	non-elem.		
20.	All finite graphs	CMSO, $k = 0$	minor; weak imm.	uncomp.		

Table 1: A list of 20 logical fractals

†: ind.= induced; surj.= surjective; hom.= homomorphic; img.= image; reln.= relation; imm.= immersion

: comp.= computable; elem.= elementary; non-elem.= computable & not elem.; exp.= exponential

1: Anuj Dawar and the author have recently shown these graphs to admit MSO interpretability of grids.

2: It is quite possible that these graphs have computable (but non-elementary) supporting functions.

3: It is open whether these graphs have computably bounded $\equiv_{m,\mathcal{L}}$ -equivalent vertex-minors.

Remark 8.3. Given that the ideas used in proving the "existential" Theorem 5.1 are used to show the "algorithmic" Theorem 8.2, an important question that arises is: how does one algorithmically construct the composition functions $f_{m,0}$ for the (\mathcal{L}, \preceq) -great operations O that build the structures of \mathcal{S}_k ? This is necessary to get the function g in Theorem 8.2 to be computable. Here is how we do it. We first observe that simply the existence of an (\mathcal{L}, \preceq) -great tree representation for \mathcal{S}_k entails the computable small model property for \mathcal{L} , and hence the decidability of \mathcal{L} -SAT, over \mathcal{S}_k . We use this fact to construct the set \mathcal{E} of $\mathcal{L}[m]$ sentences corresponding to those equivalence classes of the $\equiv_{m,\mathcal{L}}$ relation, that have a non-empty intersection with \mathcal{S}_k . For $\delta_1, \ldots, \delta_r \in \mathcal{E}$, we find a model $\mathfrak{A}_i \in \mathcal{S}_k$ for each δ_i – this is possible due to the small model property of \mathcal{L} over \mathcal{S}_k . Then $f_{m,O}(\delta_1, \ldots, \delta_n)$ is the $\equiv_{m,\mathcal{L}}$ class of $O(\mathfrak{A}_1, \ldots, \mathfrak{A}_n)$. This argument shows that simply the *existence* of the FVC property for a (computable) operation, entails an *effective version* of this property. Finally, the generalization below of Theorem 7.1, along with Theorem 8.2, explains all of Table 1.

Theorem 8.4. Let S be a class of structures and S_k be as in Theorem 8.2. For a pre-order \preceq on S_k , if S_k is w.q.o. under \preceq , then S is an (\mathcal{L}, k) -fractal under \preceq . The supporting function is not computable in general. Also, the converse is not true in general.

9 Conclusion

The dissertation [30] introduces new dual parameterized preservation properties that generalize the well-studied notions of preservation under substructures (hereditariness) and preservation under extensions; we call these preservation under substructures modulo kcruxes and preservation under k-ary covered extensions respectively. These properties are syntactically characterized in terms of Σ_2^0 and Π_2^0 sentences that have k quantifiers in their leading block. This gives a parameterized generalization of the classical Łoś-Tarski preservation theorem, abbreviated $\mathsf{GLT}(k)$, and also finer characterizations of the Σ_2^0 and Π_2^0 classes than those in the literature. We establish $\mathsf{GLT}(k)$ and its variants first over arbitrary (finite or infinite) structures and then over various classes of finite structures, particularly those that are *dense*; these include several kinds of posets and subclasses of graphs of bounded clique-width of active current interest. We show that all of these classes are model-theoretically very well behaved: they not only satisfy GLT(k), but also the homomorphism preservation theorem and a generalization of it akin to GLT(k), and a finitary analogue of the downward Löwenheim-Skolem theorem, all of these in effective form and for MSO. These results come about by making the key observation that the mentioned classes can be constructed using operations that satisfy the Feferman-Vaught composition (FVC) property. Extending these results (post thesis submission), we show that the FVC property entails an effective finitary adaptation of the full Löwenheim-Skolem property (upward and downward), that we call the *logical fractal* property, and also entails linear time algorithmic meta-theorems for CMSO. The above results collectively seem to suggest that the FVC property might be playing a similar role over the mentioned dense structures, as FO locality does over sparse structures. We also show in the dissertation, a new connection between well-quasi-ordering and model theory, that yields us another important collection of dense classes that are model-theoretically well-behaved. In summary, the thesis contributes new results to the classical model theory literature, and also contributes to the research programme of recovering classical model theory results over finite structures. (A number of future directions, including a conjecture, are presented in Chapter 12. Finally, a summary of the thesis contributions appears in Chapter 13.)

References

- Albert Atserias, Anuj Dawar, and Martin Grohe. Preservation under extensions on well-behaved finite structures. SIAM J. Comput., 38(4):1364–1381, 2008.
- [2] Albert Atserias, Anuj Dawar, and Phokion G. Kolaitis. On preservation under homomorphisms and unions of conjunctive queries. J. ACM, 53(2):208–237, 2006.
- [3] Chen C. Chang and Howard J. Keisler. Model Theory. Elsevier Science Publishers, 3rd edition, 1990.
- [4] Hubert Comon, Max Dauchet, Remi Gilleron, Christof Löding, Florent Jacquemard, Denis Lugiez, Sophie Tison, and Marc Tommasi. Tree automata techniques and applications. Available at: http://www.grappa.univ-lille3.fr/tata, 2007. release October 12, 2007.
- [5] Marek Cygan, Fedor V Fomin, Łukasz Kowalik, Daniel Lokshtanov, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Saket Saurabh. *Parameterized algorithms*, volume 3. Springer, 2015.
- [6] Anuj Dawar. Homomorphism preservation on quasi-wide classes. J. Comput. Sys. Sci., 76(5):324–332, 2010.
- [7] Anuj Dawar, Martin Grohe, Stephan Kreutzer, and Nicole Schweikardt. Model theory makes formulas large. In Proceedings of the International Colloquium on Automata, Languages and Programming, ICALP 2007, Wroclaw, Poland, July 9 – 13, 2007, pages 913–924, 2007.
- [8] Ronald Fagin, Phokion G. Kolaitis, Renée J. Miller, and Lucian Popa. Data exchange: semantics and query answering. *Theor. Comput. Sci.*, 336(1):89–124, 2005.
- [9] Pascal Fontaine. Combinations of theories and the Bernays-Schönfinkel-Ramsey class. In 4th International Verification Workshop - VERIFY'07, volume 259, pages 37–54, 2007.
- [10] J. Gajarskỳ, P. Hliněnỳ, J. Obdržálek, D. Lokshtanov, and M. S. Ramanujan. A new perspective on FO model checking of dense graph classes. In *Proceedings of the* 31st Annual ACM/IEEE Symposium on Logic in Computer Science, pages 176–184. ACM, 2016.
- [11] Jakub Gajarsky and Petr Hlinený. Kernelizing MSO properties of trees of fixed height, and some consequences. Log. Meth. Comp. Sci., 11(19):1–26, 2015.
- [12] Jakub Gajarskỳ, Petr Hlinenỳ, Daniel Lokshtanov, Jan Obdralek, Sebastian Ordyniak, MS Ramanujan, and Saket Saurabh. FO model checking on posets of bounded width. In Foundations of Computer Science (FOCS), 2015 IEEE 56th Annual Symposium on, pages 963–974. IEEE, 2015.
- [13] Jakub Gajarský, Stephan Kreutzer, Jaroslav Nesetril, Patrice Ossona de Mendez, Michal Pilipczuk, Sebastian Siebertz, and Szymon Torunczyk. First-Order Interpretations of Bounded Expansion Classes. In Proc. of the 45th International Colloquium on Automata, Languages, and Programming (ICALP 2018), volume 107, pages 126:1– 126:14. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2018.
- [14] Robert Ganian, Petr Hlinený, Jaroslav Nešetřil, Jan Obdrzálek, Patrice Ossona de Mendez, and Reshma Ramadurai. When trees grow low: Shrubs and fast MSO1.

In MFCS 2012, Bratislava, Slovakia, August 27-31, 2012, pages 419-430, 2012.

- [15] Jean Goubault-Larrecq, Monika Seisenberger, Victor Selivanov, and Andreas Weiermann. Well Quasi-Orders in Computer Science (Dagstuhl Seminar 16031). Dagstuhl Reports, 6(1):69–98, 2016.
- [16] Martin Grohe. Some remarks on finite Löwenheim-Skolem theorems. Math. Log. Q., 42:569–571, 1996.
- [17] Martin Grohe, Stephan Kreutzer, and Sebastian Siebertz. Deciding first-order properties of nowhere dense graphs. J. ACM, 64(3):17:1–17:32, 2017.
- [18] Wilfrid Hodges. Model Theory (Draft 20 Jul 00), 2000.
- [19] Mathew Joseph, Gabriel M. Kuper, Till Mossakowski, and Luciano Serafini. Query answering over contextualized RDF/OWL knowledge with forall-existential bridge rules: Decidable finite extension classes. *Semantic Web*, 7(1):25–61, 2016.
- [20] Leonid Libkin. *Elements of Finite Model Theory*. Springer-Verlag, 2004.
- [21] Vadim Lozin, Igor Razgon, and Viktor Zamaraev. Well-quasi-ordering versus cliquewidth. Journal of Combinatorial Theory, Series B, 130:1 – 18, 2018.
- [22] Johann A. Makowsky. Algorithmic uses of the Feferman-Vaught theorem. Ann. Pure Appl. Logic, 126(1-3):159–213, 2004.
- [23] Jaroslav Nesetril and Patrice Ossona de Mendez. Sparsity: Graphs, Structures, and Algorithms. Springer Publishing Company, Incorporated, 2014.
- [24] Ruzica Piskac, Leonardo Mendonça de Moura, and Nikolaj Bjørner. Deciding effectively propositional logic using DPLL and substitution sets. J. Autom. Reasoning, 44(4):401–424, 2010.
- [25] Eric Rosen. Modal logic over finite structures. Journal of Logic, Language and Information, 6:427–439, 1997.
- [26] Eric Rosen. Some aspects of model theory and finite structures. *Bull. Symbolic Logic*, 8(3):380–403, 2002.
- [27] Benjamin Rossman. Personal Communication. 2012.
- [28] Benjamin Rossman. Homomorphism preservation theorems. J. ACM, 55(3):15:1– 15:53, 2008.
- [29] Abhisekh Sankaran. Reachability analysis in graph transformation svstems. Master's thesis, Dept. of Computer Science and Engineer-Institute of Technology Bombay, 2007.Available ing, Indian at: https://www.cse.iitb.ac.in/~abhisekh/reachability-GTS.pdf.
- [30] Abhisekh Sankaran. A Generalization of the Loś-Tarski Preservation Theorem. PhD thesis, Dept. of Computer Science and Engineering, Indian Institute of Technology Bombay, 2016. Available at: http://arxiv.org/abs/1609.06297.
- [31] Abhisekh Sankaran. A finitary analogue of the downward Löwenheim-Skolem property. In 26th EACSL Annual Conference on Computer Science Logic, CSL 2017, August 20-24, 2017, Stockholm, Sweden, pages 37:1–37:21, 2017.
- [32] Abhisekh Sankaran, Bharat Adsul, and Supratik Chakraborty. A generalization of the Loś-Tarski preservation theorem over classes of finite structures. In MFCS 2014, Budapest, Hungary, August 25-29, 2014, Part I, pages 474–485, 2014.

- [33] Abhisekh Sankaran, Bharat Adsul, and Supratik Chakraborty. A generalization of the Loś-Tarski preservation theorem. Ann. Pure Appl. Logic, 167(3):189–210, 2016.
- [34] Abhisekh Sankaran, Nutan Limaye, Akshay Sundararaman, and Supratik Chakraborty. Using preservation theorems for inexpressibility results in first order logic. Technical report, IIT Bombay, 2012. Available at: http://www.cfdvs.iitb.ac.in/reports/index.php.

A Relevance of Introduced Notions to Computer Science

1. Fixed parameter tractability: Table 2 lists 22 well-studied parameterized problems [5] that are PSC(k) for some k, for k related to the parameter of the problem². For each problem below, if it is PSC(k), then it is not PSC(k-1); also, the problem is expressible using an $\exists^k \forall^*$ sentence.

Sr. No.	Problem parameterized by k	is
1.	BIPARTITE MATCHING	PSC(2k)
2.	Multicolored Clique/Ind. Set	PSC(k)
3.	Colorful Graph Motif	PSC(k)
4.	Perfect Code	PSC(k)
5.	Dominating Set	PSC(k)
6.	Pseudo Achromatic Number	$PSC(2\binom{k}{2})$
7.	HITTING SET/ d -HITTING SET	PSC(k)
8.	RAMSEY	PSC(k)
9.	Independent Set/Clique	PSC(k)
10.	Set Cover	PSC(k)
11.	Longest Cycle/Directed Cycle	PSC(k)
12.	Set Packing/ d -Set Packing	PSC(k)
13.	Longest Path/Induced Path	PSC(k)
14.	Subgraph Isomorphism	PSC(k)
15.	MaxCut	PSC(2k)
16.	Subset Sum	PSC(k)
17.	Maximum Matching	PSC(2k)
18.	TRIANGLE PACKING	PSC(k)
19.	Max-SAT/Max-r-SAT	PSC(k)
20.	Vertex Multiway Cut	PSC(k)
21.	Multicolored Biclique	PSC(2k)
22.	Unique Hitting Set	PSC(k)

Table 2: A list of 22 parameterized problems that are PSC(k) for some k

There are other FPT problems that can be readily seen to be PSC(k) (and definable using $\exists^k \forall^*$ sentences) for some k > 0, such as CHORDAL COMPLETION, FEEDBACK VER-

 $^{^{2}}$ The author acknowledges Rian Neogi, a Ph.D. student at the Institute of Mathematical Sciences Chennai, in helping him prepare Table 2.

TEX SET, ODD CYCLE TRANSVERSAL and VERTEX COVER, but actually turn out to be hereditary. The reason is that they talk of graphs that are $\leq k$ vertex deletions/edge modifications away from a hereditary property (that is related to the example). We leave out these examples in Table 2 to demonstrate that PSC(k) strictly extends the scope and usefulness of hereditariness, and in an interesting way.³

2. Finite model theory: A set X of vertices in a graph G is said to be *d*-scattered in G if for any two distinct vertices $u, v \in X$, their d-neighborhoods in G are disjoint. This notion is central to the locality of FO: any FO sentence is equivalent to a Boolean combination of "local sentences", where a local sentence asserts, for some $d, m \in \mathbb{N}$, the existence of a dscattered set of size m satisfying some FO condition on the d-neighborhoods of the points in the scattered set [20]. The notion of a scattered set appears again in the definition of quasiwide classes that were first introduced in the context of the homomorphism preservation theorem in the finite [6]. If $\mathcal{P}(d, m, r, N)$ is a property of graphs asserting "If the graph is of size $\geq N$, then there exists a d-scattered set of size m upon removal of $\leq r$ vertices", then a graph class is quasi-wide if there exists $f : \mathbb{N} \to \mathbb{N}$ such that for every d, m, there exists N such that $\mathcal{P}(d, m, f(d), N)$ is true. We now observe that $\mathcal{P}(d, m, 0, N)$ is indeed PSC(m) (and not PSC(m-1)) for every $d, m, N \in \mathbb{N}$. And since $\mathcal{P}(d, m, r, N)$ is < r vertex deletions "away from" $\mathcal{P}(d, m, 0, N)$, we get (by a similar reasoning as in the previous point) that $\mathcal{P}(d, m, r, N)$ is also PSC(m) (and not PSC(m-1)) for every $d, m, r, N \in \mathbb{N}$. We also observe that $\mathcal{P}(d, m, r, N)$ is (readily) expressible using an $\exists^{m+r} \forall^*$ sentence.

3. Structural graph theory of sparse graph classes: On the dual front, k-ary covers play a central role in graphs of bounded expansion and nowhere dense graphs [23], as seen from the characterizations of these graphs, stated below:

A class \mathcal{C} of graphs has bounded expansion (is nowhere dense) if, and only if, there exists $f : \mathbb{N} \to \mathbb{N}$ such that for every integer k (for every integer k and every $\epsilon > 0$), every graph $G \in \mathcal{C}$ (every graph $G \in \mathcal{C}$ of order $n \ge f(k, \epsilon)$) has a k-ary cover R consisting of graphs of tree-depth at most k, where every vertex of G is in $\le f(k)$ (in $\le n^{\epsilon}$) structures of R.

Very recently [13], graph classes that have structurally bounded expansion have been introduced in the context of investigating dense structures for algorithmic metatheorems. These are graph classes that are obtained from bounded expansion classes by means of first-order interpretations. It turns out that these classes also have a characterization in terms of k-ary covers, as stated below:

A class C of graphs has structurally bounded expansion if, and only if, there exist functions $f, g: \mathbb{N} \to \mathbb{N}$ such that for every integer k, every graph $G \in C$ has a k-ary cover R consisting of graphs from a graph class of shrub-depth at most g(k), where every vertex of G is in $\leq f(k)$ structures of R.

³The notion of PSC(k) was first formulated in the author's Master's thesis at IIT Bombay [29]. The motivation was to develop methods for TRDDC (Tata Research Development and Design Center) to formally verify a software being developed for an insurance company in Pune, India.