Convex Set Disjointness, Distributed Learning of Halfspaces, and LP Feasibility

Mark Braverman * Gillat Kol[†] Shay Moran [‡] Raghuvansh R. Saxena [§]

Abstract

We study the *Convex Set Disjointness* (CSD) problem, where two players have input sets taken from an arbitrary fixed domain $U \subseteq \mathbb{R}^d$ of size |U| = n. Their mutual goal is to decide using minimum communication whether the convex hulls of their sets intersect (equivalently, whether their sets can be separated by a hyperplane).

Different forms of this problem naturally arise in distributed learning and optimization: it is equivalent to *Distributed Linear Program (LP) Feasibility* – a basic task in distributed optimization, and it is tightly linked to *Distributed Learning of Halfdpaces in* \mathbb{R}^d . In communication complexity theory, CSD can be viewed as a geometric interpolation between the classical problems of Set Disjointness (when $d \ge n-1$) and Greater-Than (when d = 1).

We establish a nearly tight bound of $\hat{\Theta}(d \log n)$ on the communication complexity of learning halfspaces in \mathbb{R}^d . For Convex Set Disjointness (and the equivalent task of distributed LP feasibility) we derive upper and lower bounds of $\tilde{O}(d^2 \log n)$ and $\Omega(d \log n)$. These results improve upon several previous works in distributed learning and optimization.

Unlike typical works in communication complexity, the main technical contribution of this work lies in the upper bounds. In particular, our protocols are based on a *Container Lemma for Halfspaces* and on two variants of *Carathéodory's Theorem*, which may be of independent interest. These geometric statements are used by our protocols to provide a compressed summary of the players' input.

1 Introduction

Let $U \subseteq \mathbb{R}^d$ be an arbitrary set of n >> d points and consider the *Convex Set Disjointness* communication problem CSD_U in which two parties, called Alice and Bob, hold input

^{*}Princeton University

[†]Princeton University

[‡]Google AI Princeton

[§]Princeton University

sets $X, Y \subseteq U$ and their goal is to decide whether $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$, where $\operatorname{conv}(\cdot)$ denotes the convex hull operator. As we briefly discuss next, this problem has roots in *distributed learning, distributed optimization,* and in *communication complexity.*

Distributed Learning

Some modern applications of machine learning involve collecting data from several sources. For example, in healthcare related applications, data is often collected from hospitals and labs in remote locations. Another host of examples involves algorithms that are trained on personal data (e.g. a music recommendation app which is trained on preferences made by numerous users).

Such applications raise the need for algorithms that are able to train on distributed data without gathering it all on single a centralized machine. Moreover, distributed training is also beneficial from a privacy perspective in contexts where the data contains sensitive information (e.g. personal data on smartphones). Consequently, tech companies invest significant efforts in developing suitable technologies; one notable example is Google's *Federated Learning* project [Konečný et al., 2016].

The Convex Set Disjointness communication problem was introduced in this context by Kane et al. [2019] to analyze the communication complexity of learning linear classifiers. Linear classifiers (a.k.a. halfspaces) form the backbone of many popular learning algorithms: they date back to the seminal *Perceptron algorithm* from the 50's [Rosenblatt, 1958], and also play a key role in more modern algorithms such as kernel machines and neural nets.

In the distributed setting, Learning Halfspaces refers to the following task: a set of *examples* is distributed between several parties. Each example consists of a pair (x, y), where $x \in U$ is a feature vector, y = sign(L(x)) is the label, and $L : \mathbb{R}^d \to \mathbb{R}$ is the (unknown) target linear function. The parties' goal is to agree on a classifier $h : U \to \{\pm 1\}$ such that h(x) = y for every input example (x, y), while minimizing the amount of communication. In this context, it may be natural to think of the domain U as a grid, or as a discretized manifold, or any other domain that arises naturally from euclidean representations of data.

Our Contribution. We provide a nearly tight bound of $\Theta(d \log n)$ on the communication complexity of this problem in the two-party setting. Our upper bound improves upon a previous bounds of $O(d \log^2 n)$ by Daumé III et al. [2012] and Balcan et al. [2012] which rely on distributed implementations of boosting algorithms. Our protocol exploits a tool we call halfspace containers which may be of independent interest (Theorem 2.6 below). Roughly speaking, halfspace containers provide a way to summarize important information about the players' input in a compressed manner.

We also give a nearly matching lower bound of $\Omega(d \log n)$, which improves upon a previous lower bound of $\Omega(d + \log n)$ by Kane et al. [2019].

Our upper bound is achieved by a deterministic protocol whereas our lower bound applies even when the protocol is randomized and may err with constant probability.

Distributed Optimization

Linear Programming (LP) is one of the most basic primitives in optimization. In the associated decision problem, called LP feasibility, the goal is to determine whether a system of linear inequalities (also called constraints) is satisfiable. In distributed LP feasibility the constraints are divided between several parties.

This problem is essentially equivalent to Convex Set Disjointness, albeit in a dual formulation where constraints and points are interchanged: indeed, disjointness of the convex hulls amounts to the existence of a separating hyperplane which, from a dual perspective, corresponds to point that satisfies all of the constraints.

Our Contribution. This work yields a protocol for LP feasibility in the two-party setting which communicates $\tilde{O}(d^2 \log n)$ bits. Similarly to our learning protocol, also this protocol is based on halfspace containers (Theorem 2.6). This improves upon two incomparable previous upper bounds by Vempala et al. [2019] which rely on classical sequential LP algorithms: (i) a distributed implementation of Clarkson [1995]'s algorithm with communication complexity of $O(d^3 \log^2 n)$ bits (see their Theorem 10.1), and (ii) a protocol based on the Center of Gravity algorithm (see their Theorem 11.3). The communication complexity of the latter protocol matches our $\tilde{O}(d^2 \log n)$ bound when the domain U is a grid (e.g. $U = [n^{1/d}]^d$), but can¹ be significantly larger when U is arbitrary.

We also give a lower bound of $\Omega(d \log n)$ which is off by a factor of d from our upper bound. Our lower bound applies also to randomized protocols that may err with a small probability. This improves upon Vempala et al. [2019] who derive a similar lower bound of $\Omega(d \log n)$ in the deterministic setting (see their Theorem 3.6) and a lower bound of $\Omega(\log n)$ in the randomized setting (their Theorem 9.2).

Communication Complexity

Convex Set Disjointness can be seen as a geometric interpolation between Set Disjointness (when $d \ge n-1$), and Greater-Than (when d = 1). Indeed, if $d \ge n-1$ then one can pick the *n* points in $U \subseteq \mathbb{R}^d$ to be affinely independent, which implies that

$$X \cap Y = \emptyset \iff \operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$$

Therefore, in this case the communication complexity of CSD_U is the same like Set Disjointness which is $\Theta(n)$ [Kalyanasundaram and Schintger, 1992]. In the other extreme, if d = 1 then U is a set of n points on the real line and CSD_U boils down to comparing the two extreme points in Alice's input with the two extreme points in Bob's input (see Figure 1). Thus, the case of d = 1 is equivalent to the Greater-Than problem on $\log n$ bits,

¹In fact, already in the one-dimensional case, if the domain $U \subseteq \mathbb{R}$ consists of n points which form a geometric progression (say $U = \{1, 2, 4, ..., 2^n\}$), then the Center of Gravity protocol can transmit up to $\Omega(n)$ bits, which is exponentially larger than the $O(\log n)$ optimal deterministic protocol, and double exponentially larger than the $O(\log \log n)$ optimal randomized protocol.



Figure 1: Convex Set Disjointness in 1D: the convex hull of Alice's input (blue points) is disjoint from the convex hull of Bob's input (red points) if and only if $\mathbf{x_{right}} < \mathbf{y_{left}}$ or $\mathbf{y_{right}} < \mathbf{x_{left}}$. Thus, this case amounts to deciding (2 instances of) the *Greater-Than* problem on log *n* bits.

Dimension	Upper bound	Lower bound
d = 1; deterministic	$O(\log n)$ [trivial]	$\Omega(\log n)$ [folklore]
d = 1; randomized	$O(\log \log n)$ [Feige et al. [1994]]	$\Omega(\log \log n)$ [Viola [2013]]
d > 1; deterministic	$\tilde{O}(d^2 \log n)$ [this work]	$\tilde{\Omega}(d\log n)$ [Vempala et al. [2019]]
d > 1; randomized	н	$\tilde{\Omega}(d\log n)$ [this work]

Table 1: Deterministic and randomized communication complexity of CSD_U for arbitrary $U \subseteq \mathbb{R}^d$ with |U| = n. The case of d = 1 is equivalent to the *Greater-Than* problem on $\log n$ bits.

whose deterministic communication complexity is $\Theta(\log n)$ in the deterministic setting and $\Theta(\log \log n)$ in the randomized setting (with constant error) [Feige et al., 1994, Viola, 2013].

Organization

We begin by formally stating the main results in Section 2. Then, in Section 3 we survey some of the related work. Section 4 contains an overview of some of the proofs, and Sections 5 and 6 contain the complete proofs.

2 Results

We begin with formally stating our results for Learning Halfspaces and for Convex Set Disjointness. Later, in Section 2.3, we present the halfspace container lemma along with some geometric statements that arise in our analysis which may be of independent interest.

We use standard notation and terminology from communication complexity [Kushilevitz and Nisan, 1997]. Specifically, for a boolean function f, let D(f) and R(f) denote its deterministic and randomized² communication complexity.

2.1 Learning Halfspaces

We first define the Halfspace Learning Problem. Let $U \subseteq \mathbb{R}^d$ be a domain with n points. An *example* is a pair of the form $(u, b) \in U \times \{\pm 1\}$. An example (u, b) is called *positive*

²With error probability $\varepsilon = 1/3$.

if b = +1 and negative if b = -1. A set of examples $S \subseteq U \times \{\pm 1\}$ is called a sample. Learning Halfpaces over U refers to the following search problem. Alice's and Bob's inputs are samples $S_a, S_b \subseteq U \times \{\pm 1\}$ such that there exists a hyperplane that separates the positive examples in $S_a \cup S_b$ from the negative examples in $S_a \cup S_b$. Their goal is to output a function $f : U \to \{\pm 1\}$ such that f(x) = y for every example $(x, y) \in S_a \cup S_b$. If the protocol always outputs f such that f is an indicator of a halfspace then the protocol is called a proper learning protocol. Otherwise it is called an improper learning protocol.

The following theorems establish a bound of $\Theta(d \log n)$ on the communication complexity of Learning Halfspaces.

Theorem 2.1 (Upper bound). Let $d, n \in \mathbb{N}$, and let $U \subseteq \mathbb{R}^d$ be a domain with n points. Then, there exists a deterministic protocol for Learning Halfspaces over U with communication complexity $O(d \log d \log n)$.

We note that our protocol is improper. It remains open whether the above bound can be achieved by a proper protocol.

Theorem 2.2 (Lower bound). Let $d, n \in \mathbb{N}$. Then, there exists a domain $U \subseteq \mathbb{R}^d$ with n points such that every (possibly improper and randomized) protocol that learns halfspaces over U must transmit at least $\Omega(d \log(n/d))$ bits of communication.

Theorems 2.1 and 2.2 are proved in Section 6. A proof overview is given in Section 4.3

2.2 Convex Set Disjointness and LP Feasibility

Recall that CSD_U denotes the Convex Set Disjointness problem on a domain $U \subseteq \mathbb{R}^d$.

Theorem 2.3 (Upper bound). Let $d, n \in \mathbb{N}$, and let $U \subseteq \mathbb{R}^d$ be a domain with n points. Then,

$$D(\mathsf{CSD}_U) = O(d^2 \log d \log n).$$

Theorem 2.4 (Lower bound). Let $d, n \in \mathbb{N}$. Then, there exists a domain $U \subseteq \mathbb{R}^d$ with n points such that

$$R(\mathsf{CSD}_U) = \Omega(d\log(n/d)).$$

As noted in the introduction, Convex Set Disjointness is equivalent to distributed LP feasibility, and therefore the above bounds apply in both contexts. Theorems 2.3 and 2.4 are proved in Section 6. A short overview of the proofs is given in Section 4.2

2.3 Geometric Results

Our analysis utilizes some geometric tools which, to the best of our knowledge, are novel. As some of them may be of independent interest, we next present them in a self contained manner.

2.3.1 Halfspace Containers

Our protocols hinge on ε -containers³ (defined below). This is a variant of the notion of ε -covers, which we recall next: an ε -cover for a family $\mathcal{F} \subseteq 2^X$ is a family $\mathcal{C} \subseteq 2^X$ such that for every $F \in \mathcal{F}$ there is $C \in \mathcal{C}$ such that the symmetric difference⁴ between C and F is of size at most $\varepsilon |X|$. In other words, the hamming balls of radius $\varepsilon |X|$ around \mathcal{C} cover \mathcal{F} . Note that this is a special instance of the notion of ε -cover in metric spaces. In the case of containers, we also require that $F \subseteq C$:

Definition 2.5 (Containers). Let X be a finite set and let $\mathcal{F} \subseteq 2^X$ be a family of subsets. A family $\mathcal{C} \subseteq 2^X$ is a family of ε -containers for \mathcal{F} if

$$(\forall F \in \mathcal{F})(\exists C \in \mathcal{C}) : F \subseteq C \text{ and } |C \setminus F| \leq \varepsilon |X|.$$

Note that every set of ε -containers is in particular an ε -cover (but not vice versa).

A Container Lemma for Halfspaces. Let HS_d denote the family of all halfspaces in \mathbb{R}^d , and for $U \subseteq \mathbb{R}^d$ let $\mathsf{HS}(U) = \{H \cap U : H \in \mathsf{HS}_d\}$ denote the family of all halfspaces restricted to U. A classical result by Haussler implies that $\mathsf{HS}(U)$ has an ε -cover of size roughly $(1/\varepsilon)^d$ [Haussler, 1995]. A remarkable property of this ε -cover is that its size depends only on ε and d; in particular, it does not depend on |U|.

The following result, which is our main technical contribution, establishes a similar statement for ε -containers.

Theorem 2.6 (Container Lemma for Halfspaces). Let $U \subseteq \mathbb{R}^d$. Then, for every $\varepsilon > 0$ there is a set of ε -containers for HS(U) of size $(d/\varepsilon)^{O(d)}$.

We mention that, in contrast with Haussler's result which applies to any family with VC dimension d, Theorem 2.6 does not extend to arbitrary VC classes (e.g. it fails for projective planes; see Section 5). This is also reflected in our proof which exploits geometric properties of halfspaces, and in particular a dual version of Carathéodory's Theorem (see Proposition 2.7 below). We discuss it in more detail in Section 5, where we also prove Theorem 2.6.

2.3.2 Variants of Carathéodory's Theorem

Carathéodory's Theorem is a fundamental statement in convex geometry [Carathéodory, 1907]: it asserts that if $x \in \mathbb{R}^d$, $Y \subseteq \mathbb{R}^d$ are such that $x \in \operatorname{conv}(Y)$ then there are $y_1, \ldots, y_{d+1} \in Y$ such that $x \in \operatorname{conv}(\{y_1, \ldots, y_{d+1}\})$. Our proof of Theorem 2.3 exploits two variants of Carathéodory's Theorem.

³This notation is inspired by a similar notion that arises in Graph Theory (see, *e.g.*, Balogh et al. [2018] and references within).

 $^{^4\}mathrm{Equivalently},$ the hamming distance between the indicator vectors.

A Dual Variant. Let $\mathcal{Q} \subseteq \mathbb{R}^d$ be a polytope. There are two natural ways of representing \mathcal{Q} : (i) as the convex hull of its vertices, (ii) as an intersection of halfspaces.

Carathéodory's Theorem implies that if \mathcal{Q} is the convex hull of a few vertices then it can be covered by a few simplices: indeed, if \mathcal{Q} has *n* vertices then, by Carathéodory's Theorem, it can be covered by at most n^{d+1} sets of the form $\operatorname{conv}(\{x_1, \ldots, x_{d+1}\})$, where the x_i 's are vertices of \mathcal{Q} .

Assume now that Q is an intersection of few halfspaces (say n). How many subsimplices are needed in order to cover Q in this case? A bound of $n^{d(d+1)}$ follows by the previous bound, since the number of vertices in Q is at most n^d (every vertex is defined by d hyperplanes). The next proposition achieves a quadratic improvement in the exponent.

Proposition 2.7 (A dual variant of Carathéodory's Theorem). Let $\mathcal{Q} \subseteq \mathbb{R}^d$ be a polytope that can be represented as an intersection of n halfspaces. Then, \mathcal{Q} can be covered using at most n^d subsimplices of the form $\operatorname{conv}(\{x_0, \ldots, x_d\})$, where the x_i 's are vertices of \mathcal{Q} .

Proposition 2.7 is proven in Section 5.

A Symmetric Variant. Carathéodory's Theorem concerns a relation between a point x and a set Y such that $x \in \operatorname{conv}(Y)$. The following simple generalization provides a symmetric relation between two set X, Y such that $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$.

Proposition 2.8 (A symmetric variant of Carathéodory's Theorem). Let $X, Y \subseteq \mathbb{R}^d$ such that $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$. Then $\operatorname{conv}(S_1) \cap \operatorname{conv}(S_2) \neq \emptyset$ for some $S_1 \subseteq X, S_2 \subseteq Y$ such that $|S_1| + |S_2| \leq d + 2$.

Note that Carathéodory's Theorem boils down to the case where $X = \{x\}$ (and hence $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset \implies x \in \operatorname{conv}(Y)$).

Since the proof of Proposition 2.8 is short, we present it here.

Proof of Proposition 2.8. The proof follows an argument similar to the linear algebraic proof of Carathéodory's Theorem. Assume $z \in \operatorname{conv}(X) \cap \operatorname{conv}(Y)$ can be represented as a convex combination of d_1 points $x_1 \dots x_{d_1} \in X$ and as a convex combination of d_2 points $y_1 \dots y_{d_2} \in Y$ such that $d_1 + d_2 > d + 2$. Consider the system of linear equalities in $d_1 + d_2$ variables $\alpha_1 \dots \alpha_{d_1}, \beta_1 \dots \beta_{d_2}$ defined by the constraints (i) $\sum \alpha_i x_i = \sum \beta_j y_j$, and (ii) $\sum \alpha_i = \sum \beta_j = 0$. This system has $d_1 + d_2 > d + 2$ variables and only d + 2 constraints (d constraints from (i) and 2 more constraints from (ii)). Thus, it has a solution such that not all α_i 's and β_j 's are 0. Consequently, one can shift z by a sufficiently small scaling of the vector $v = \sum \alpha_i x_i = \sum \beta_i y_i$, so that one of the coefficients of the x_i 's or the y_j 's vanishes. This process can be repeated until $d_1 + d_2 \leq d + 2$, which yields the desired sets $S_1 \subseteq X, S_2 \subseteq Y$.

Remark. Proposition 2.8 establishes a tight bound of d+2 on the coVC number of halfspaces in \mathbb{R}^d . The coVC number is a combinatorial parameter which characterizes the concept classes that can be properly learned using polylogarithmic communication complexity (see Kane et al. [2019]). It is defined as follows: let $H \subseteq \{\pm 1\}^X$ be an hypothesis class over a domain X. Its coVC number is the smallest number k such that every sample $S \subseteq X \times \{\pm 1\}$ which is not realizable⁵ by H has a subsample $S' \subseteq S$ of size $|S'| \leq k$ which is not realizable by H. A weaker upper bound of 2d + 2 on the coVC number of halfspaces was given by Kane et al. [2019] (see Example 1 in their paper).

3 Related Work

Lovăsz and Saks [1993] studied a variant of convex set disjointness where the goal is to decide whether the convex hulls intersect in a point from U. This variant exhibits a very different behaviour, even in dimension d = 2: indeed, if U is in convex position⁶ (say n points on the unit circle) then this becomes equivalent to the classical set disjointness problem whose communication complexity is $\Theta(n)$, whereas in the formulation considered in this paper, any planar instance $U \subseteq \mathbb{R}^2$ can be decided using $O(\log n)$ bits.

Variants of the convex set disjointness problem were considered by several works in distributed machine learning and distributed optimization (see, *e.g.*, Balcan et al. [2012], Daumé III et al. [2012], Chen et al. [2016], Kane et al. [2019], Vempala et al. [2019]. Other variants in which the number of rounds is bounded arise in space lower bounds for learning linear classifiers in streaming models [Dagan et al., 2019].

Kane et al. [2019] studied convex set disjointess in a more general communication model in which the input domain U may be infinite, and the players are allowed to transmit points from their input sets for a unit cost of communication. They established an upper bound of $\tilde{O}(d^3 \log n)$ and a lower bound of $\tilde{\Omega}(d + \log n)$ on the number of transmitted points/bits when the input subsets are of size n and the dimension is d. These bounds translate⁷ to upper and lower bounds of $\tilde{O}(d^3 \log^2 n)$ and $\tilde{\Omega}(d + \log n)$ in the setting considered in this paper.

Recently, Vempala et al. [2019] published a thorough study of communication complexity of various optimization problems. One of the problems they consider is Linear Program feasibility, which, as explained in the introduction, is equivalent to Convex Set Disjointness. The main difference is that Vempala et al. [2019] do not consider arbitrary domains U, and focus on the case when U is a grid (say $[n^{1/d}]^d$). On the other hand, in our setting U can be arbitrary. They derive a lower bound of $\Omega(\log n)$ in the randomized setting (Theorem 9.2) and of $\Omega(d \log n)$ in the deterministic setting (Theorem 3.6), as well as several upper bounds. Their best upper bound of $O(d^2 \log^2 d \log n)$ (Theorem 11.3) is based on an implementation

⁵A sample S is realizable with respect to H if there is $h \in H$ such that h(x) = y for every $(x, y) \in S$.

⁶A set U is in convex position if $u \notin \operatorname{conv}(U \setminus \{u\})$ for all $u \in U$.

⁷The extra log *n* factor in the upper bound is because transmitting $u \in U$ requires $\log |U| = \log n$ bits.

of the Center of Gravity algorithm. This matches (up to an extra "log d" factor) the upper bound given in this work. However, their upper bound does not apply⁸ to arbitrary domains U. In fact, already in the one-dimensional case, if the domain $U \subseteq \mathbb{R}$ consists of npoints which form a geometric progression (say $U = \{1, 2, 4, \ldots, 2^n\}$), then the Center of Gravity protocol can transmit up to $\Omega(n)$ bits, which is exponentially larger than the $O(\log n)$ optimal deterministic protocol, and double exponentially larger than the $O(\log \log n)$ optimal randomized protocol. It is worth noting that Vempala et al. [2019] provide another upper bound (Theorem 10.1), which is based on Clarkson [1995]'s algorithm whose analysis extends arbitrary domains U. This protocol has communication complexity of $O(d^3 \log^2 n)$ bits (matching the bound of Kane et al. [2019]).

4 **Proofs Overview**

In this section we overview the proofs and highlight some of the more technical arguments. We begin with overviewing the proof of the Halfspace Container Lemma (Theorem 2.6), which is the most involved derivation in this work and forms the crux of our communication protocols. Then, we outline the proofs for Convex Set Disjointness in Section 4.2 and for Distributed Halfspace Learning in Section 4.3.

4.1 Halfspace Containers

Let $U \subseteq \mathbb{R}^d$ be a domain with *n* points. We want to show that for every $\varepsilon > 0$ there is a collection of (roughly) $(d/\varepsilon)^d$ sets called *containers* such that for every halfspace *H* there is a container *C* such that $H \subseteq C$ and $C \setminus H$ contains at most $\varepsilon \cdot n$ points from *U*. It will be more convenient to prove the following equivalent statement in which *H* and *C* switch roles:

There is a collection \mathcal{C} of (roughly) $(d/\varepsilon)^d$ sets such that for every halfspace H there is $C \in \mathcal{C}$ such that $C \subseteq H$ and $H \setminus C$ contains at most $\varepsilon \cdot n$ points from U.

Indeed, these statements are equivalent, because a complement of a halfspace is a halfspace, and so taking the complements of all sets in a family C with the above property yields the desired family of ε -containers.

Constructing an ε -net. Each of the sets in the constructed family \mathcal{C} will be an intersection of d + 1 halfspaces. The first step in the construction is to pick a "small" $V \subseteq U$ which forms an ε -net to sets of the form $H_0 \setminus (\bigcap_{i \leq d+1} H_i)$, where the H_i 's are halfspaces:

That is, V satisfies that for every set B of the form $B = H_0 \setminus (\bigcap_{i \leq d+1} H_i)$, if B contains at least $\varepsilon \cdot n$ points from U then $B \cap V \neq \emptyset$.

⁸Specifically, their analysis exploits the assumed grid structure of U: their bound on the number of iterations of the protocol uses bounds on determinants of matrices with entries from $[n^{1/d}]$.

By standard arguments from VC theory, a random subset $V \subseteq U$ of size roughly d^2/ε will satisfy this property. Once we have such an ε -net V, the idea is to associate with any given half-space H a set of d + 1 halfspaces H_1, \ldots, H_{d+1} which are induced by V such that

- (i) $\cap_{i \leq d+1} H_i \subseteq H$, and
- (ii) $H \setminus (\bigcap_{i < d+1} H_i)$ does not contain any point from V.

Since V is an ε -net, property (ii) implies that $H \setminus (\bigcap_{i \leq d+1} H_i)$ contains at most $\varepsilon \cdot n$ points from U, as needed.

Dual Polytope. To derive the halfspaces H_1, \ldots, H_{d+1} which satisfy the above properties (i) and (ii) we consider the *dual space* in which each halfspace is associated by a d + 1 dimensional vector of the form (\vec{a}, b) , where $\vec{a} \in \mathbb{R}^d$ is the normal to the supporting hyperplane and b is the bias; that is, the halfspace is given by $\{x \in \mathbb{R}^d : \vec{a} \cdot x \leq b\}$.

Consider the set $\mathcal{P} = \mathcal{P}(H)$ of all halfspaces that are *equivalent* to H with respect to the ε -net V. That is, $\mathcal{P} \subseteq \mathbb{R}^{d+1}$ contains representations of all halfspaces H' such that $H' \cap V = H \cap V$ (we stress that there can be several such halfspaces which have a different intersection with the domain U). Note that \mathcal{P} is a convex set which is defined⁹ by |V| linear inequalities (each $v \in V$ corresponds to a linear inequality posing that $v \in H \iff v \in H'$). For an illustration, see Figure 2.

Now, by Carathéodory Theorem there are d + 2 vertices of \mathcal{P} such that H is in their convex hull. By the definition of \mathcal{P} , these d + 2 vertices correspond to halfspaces $H_i \subseteq \mathbb{R}^d$ such that $H_i \cap V = H \cap V$. We claim that these H_i 's satisfy the above properties (i) and (ii). Indeed, since H is in their convex hull it follows that $\bigcap_i H_i \subseteq H$ which amounts to (i), and since the H_i 's are in \mathcal{P} , we have that $H_i \cap V = H_i$ for every i which implies (ii).

An Inferior Bound. Let us now see how to get an inferior bound of $|V|^{O(d^2)} = (d/\varepsilon)^{O(d^2)}$ on the size of \mathcal{C} . How many polytopes $\mathcal{P}(H)$ are there? (counting over all possible halfspaces H.) The constraints defining each polytope \mathcal{P} are determined by the intersection $V \cap H$, where H is a halfspace. Therefore, since there are $O(|V|^d)$ distinct intersections of V with halfspaces, we get that there are $O(|V|^d)$ such polytopes $\mathcal{P}(H)$. Now, given a fixed $\mathcal{P}(H)$, how many vertices does it have? \mathcal{P} is defined by |V| constraints and therefore has at most $|V|^{d+1}$ vertices (each vertex is determined by d + 1 constraints). Therefore the number of d + 2 tuples of vertices is at most $|V|^{(d+1)(d+2)}$. To conclude, the number of possibilities for obtaining the halfspaces $H_1 \dots H_{d+2}$ is bounded by

$$|V|^{O(d)} \cdot |V|^{O(d^2)} = (d/\varepsilon)^{O(d^2)}$$

To remove the extra factor of d from the exponent we exploit the Dual Carathéodory Theorem (Proposition 2.7), which enables us to find a collection of just $|V|^{O(d)}$ tuples of (d+2) vertices such that every point in P(H) is in the convex hull of one of these tuples.

⁹In the complete proof we will define $\overline{\mathcal{P}}$ with O(d) more constraints in order to ensure boundedness.



Figure 2: The auxiliary dual polytope: halfspaces in the top-left of the figure (the primal space) are represented by points in the bottom right of the figure (the dual space), and points in the top-left correspond to half-spaces in the bottom right. The circled points in the top-left denote the points in the ε -net V; these points define the facets of the auxiliary polytope \mathcal{P} , which is (a dual representation of) the set of halfspaces that induce the same partition on V like H.

Dual Carathéodory Theorem. The $|V|^{O(d^2)}$ dependence in the above calculation arises because for every H, we count a tuple of d+2 vertices of $\mathcal{P}(H)$ whose convex hull contains H. As the number of vertices can be as large as roughly $|V|^d$, a naive counting such as the one sketched above yields a bound of $|V|^{O(d^2)}$. In order to improve this, it suffices to show that $\mathcal{P}(H)$ can be covered by $|V|^{O(d)}$ subsimplices (i.e. sets of the form $\operatorname{conv}(H_1, \ldots, H_{d+2})$ where $H_1 \ldots H_{d+2}$ are vertices of $\mathcal{P}(H)$).

To this end we prove Proposition 2.7 which asserts more generally, that if a polytope $\mathcal{Q} \subseteq \mathbb{R}^d$ is defined by *n* linear inequalities then it can be covered by n^d subsimplices (in our context the number of constraints *n* is $|V| \approx d^2/\varepsilon$ and the dimension *d* is d + 1). We prove this in a constructive manner using a process from computational geometry called Bottom Vertex Triangulation [Clarkson, 1988, Goodman and O'Rourke, 2004].

In a nutshell, given a point $a \in \mathcal{Q}$ we use the Bottom Vertex Triangulation process to encode in a sequence of d out of the n linear inequalities that define \mathcal{Q} , the names of d + 1vertices of \mathcal{Q} whose convex hull contains a. This implies that the polytope can be covered using at most n^d subsimplices, corresponding to the number of sequences of length d out of a set of size n.

In more detail, the sequence is defined as follows (see Figure 4 for an illustration). Given the input point a, let p_0 be the bottom-most¹⁰ vertex of Q, and shoot a ray starting in p_0 which passes through a until it hits a facet Q_1 of Q in a point $a_1 \in Q_1$. Append to the constructed sequence the name of the linear inequality which became tight as a result of hitting Q_1 . Next, continue recursively the same process on Q_1 (i.e. again shoot a ray from its bottom vertex p_1 which passes through a_1 until it hits a facet Q_2 , etcetera). We refer the reader to Figure 3 to an illustration of this encoding procedure as well as to Figure 4 for an illustration of the bottom vertex triangulation process.

4.2 Convex Set Disjointness

Upper Bound

Imagine for simplicity that d = O(1). Already in this regime, deriving an o(n) upper bound is non-trivial.¹¹ Kane et al. [2019] present a natural protocol based on *boosting/multiplicativeweights update rule* with $\Theta(\log^2 n)$ communication complexity. Such quadratic dependence is also exhibited by other approaches (*e.g.*, the protocol by Vempala et al. [2019] which is based on Clarkson's algorithm). Roughly speaking, this is because these protocols take $\Theta(\log n)$ rounds¹² with $\Theta(\log n)$ bits per round. Improving upon this quadratic dependence is already non-trivial. Our approach is based on two steps.

 $^{^{10}\}mathrm{Or}$ any other canonical vertex.

¹¹The case of d = 1 is easy, d = 2 is more sophisticated, and d = 3 seems to require a general approach.

¹²Kane et al. prove that any optimal protocol must have $\tilde{\Omega}(\log n)$ rounds.

A Dual Carathéodory's Theorem

Encoding:

Input: a polytope $\mathcal{Q} \in \mathbb{R}^d$ which is defined by n constraints (linear inequalities) and a point $\mathbf{a} \in \mathcal{Q}$.

Output: a sequence S of d constraints which encodes vertices $x_0, \ldots, x_d \in Q$ such that $a \in \text{conv}(\{x_0, \ldots, p_d\}).$

- (1) Initialize $Q_0 = Q$, $a_0 = a$, $x_0 = p(Q_0)$, and $S = \varepsilon$ (the empty sequence). (p(Q') denotes the bottom vertex of a polytope Q'.)
- (2) For i = 1, ..., d:
 - (2.1) Extend the ray that starts at x_{i-1} and passes through a_{i-1} until it hits the boundary of Q_{i-1} .
 - (2.2) Set \boldsymbol{a}_i to be the point on the boundary of \mathcal{Q}_{i-1} that the ray hits. Set \mathcal{Q}_i to be the^{*a*} facet of \mathcal{Q}_{i-1} that contains \boldsymbol{a}_i and Set $\boldsymbol{x}_i = \boldsymbol{p}(\mathcal{Q}_{i+1})$.
 - (2.3) Append to S the linear inequality which is tightened by Q_i .
- (3) Output \boldsymbol{S} .

Decoding:

Input: a polytope $\mathcal{Q} \in \mathbb{R}^d$ which is defined by *n* constraints (linear inequalities) and a sequence S of *d* constraints.

Output: a sequence of vertices $\boldsymbol{x}_0, \ldots, \boldsymbol{x}_d \in \mathcal{Q}$.

- (1) Initialize $\mathcal{Q}_0 = \mathcal{Q}, \, \boldsymbol{x}_0 = \boldsymbol{p}(\mathcal{Q}_0).$
- (2) For $i = 1, \ldots, d$:
 - (2.1) Set Q_i to be the facet of Q_{i-1} which is defined by tightening the *i*'th constraint in S.
 - 2.2 Set $\boldsymbol{x}_i = \boldsymbol{p}(\mathcal{Q}_i)$.
- (3) Output $\boldsymbol{x}_0, \ldots \boldsymbol{x}_d$.

^aIf a_{i+1} belongs to several facets (i.e. it sits on a face whose dimension is (d-1) then pick Q_{i+1} to be any facet that contains it.

Figure 3: The encoding procedure receives \mathcal{Q} and $a \in \mathcal{Q}$ as inputs and outputs a sequence S of d out of the n linear inequalities used to define \mathcal{Q} . The decoding procedure receives \mathcal{Q} and S as inputs and output a sequence $\mathbf{x}_0, \ldots, \mathbf{x}_d$ of vertices of \mathcal{Q} such that $a \in \operatorname{conv}(\{\mathbf{x}_0, \ldots, \mathbf{x}_d\})$. Since there are at most n^d sequences S and since every point $a \in \mathcal{Q}$ is contained in one of the decoded subpolytopes $\operatorname{conv}(\{\mathbf{x}_0, \ldots, \mathbf{x}_d\})$, it follows that \mathcal{Q} can be covered by n^d such subpolytopes as required.



Figure 4: An illustration of bottom vertex triangulation for the polytope \mathcal{P} and a point $x \in \mathcal{P}$. The process starts by shooting a ray from the bottom vertex, (i.e. v_1) to x. The ray is extended untill it hits one of the faces to the polytope at a point which is denoted by x_1 . The process is then repeated with the face as a polytope with one fewer dimension.



Figure 5: The algorithm for the promise variant does not extend to the general case: the figure depicts a case where the convex hull of the red points intersects the convex hull of the blue points. Since the halfspace on the right of the dashed hyperplane contains all the blue points and less than half of the total, the parties will decide to remove all the points to the left of the hyperplane. However, once these points are removed from consideration, the convex hulls of the remaining red and blue points are disjoint.

Step (i): Reducing to a Promise Variant (Lemma 6.12). Let $PromiseCSD_U$ denote the variant of Convex Set Disjointness in which it is *promised* that the inputs X, Y satisfy:

- (i) $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$, or
- (ii) $X \cap Y \neq \emptyset$.

(In particular, the output of the protocol is not restricted in the remaining case when $X \cap Y = \emptyset$ and $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$).

Clearly, PromiseCSD_U can only be easier to decide than CSD_U . In the opposite direction, it turns out that it is not much harder. Specifically, one can reduce to the promise variant by adding at most $(2n)^{d+2}$ carefully chosen points to the domain. The idea is to use Proposition 2.8 which asserts that if $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$ then there are $X' \subseteq X$ and $Y' \subseteq Y$ such that $|X'| + |Y'| \leq d + 2$ and $\operatorname{conv}(X') \cap \operatorname{conv}(Y') \neq \emptyset$. Therefore, for every pair of sets $X', Y' \subseteq U$ such that $|X'| + |Y'| \leq d + 2$, we add to U an auxiliary point in $\operatorname{conv}(X') \cap \operatorname{conv}(Y')$. Then, whenever $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$, their intersection must contain one of the auxiliary points.

We then devise a protocol for $\mathsf{PromiseCSD}_U$ with communication complexity

$$O(d\log d\log n).$$

This implies the stated upper bound of $O(d^2 \log d \log n)$ on CSD_U , since the reduction to the promise variant enlarges the domain by at most $(2n)^{d+2}$ points.

Step (ii): Solving the Promise Variant (Lemma 6.9). It remains to explain how PromiseCSD_U can be solved with $\tilde{O}(d \log n)$ bits of communication. As a warmup, note that devising a non-trivial protocol for PromiseCSD_U is considerably easier than for CSD_U: indeed, if conv $(X) \cap$ conv $(Y) = \emptyset$, then X and Y can be separated by a hyperplane and one of the two halfspaces it defines contains at most n/2 points from U. This suggests the following approach: Alice and Bob each privately checks if their input lies in a halfspace which contains at most n/2 points from U. If there is no such halfspace then by the above reasoning it must be the case that conv $(X) \cap \text{conv}(Y) \neq \emptyset$ and the protocol terminates. Else, they can agree on such a halfspace using $O(d \log n)$ bits and remove all domain points outside this halfspace

(the bound on the number of bits is because there are $n^{O(d)}$ halfspaces up to equivalences¹³). Alice and Bob can iteratively proceed in this manner and in every step remove at least half of the (remaining) points while maintaining that all points in $X \cap Y \subseteq U$ are never being removed. The implied protocol has a total of $O(\log n)$ rounds, and in each round $O(d \log n)$ bits are communicated. Thus, the total number of bits is $O(d \log^2 n)$ (which is $\log n$ factor away from the stated bound).

Our final protocol uses a similar recursive approach, but transmits only $O(d \log d)$ bits in each round. This is achieved by using Halfspace Containers (Theorem 2.6). Specifically, instead of finding a halfspace which contains the entire input of one of the players, they find an ε -container for this halfspace with $\varepsilon = 1/4$. This allows to reduce the domain size by a factor of 1/2 + 1/4 = 3/4 in each round and, by Theorem 2.6, requires only $d \log d$ bits per round. The proof of Theorem 2.6 is sketched in Section 4.1.

One may be tempted to try a similar approach for the non-promise variant. However, note that points in $\operatorname{conv}(X) \cap \operatorname{conv}(Y)$ that are not in $X \cap Y$ may be removed by the protocol. Indeed, Figure 5 depicts a situation where the protocol starts with sets X, Y with $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$ and removes some of the points in U to obtain a domain U' in which $\operatorname{conv}(X \cap U') \cap \operatorname{conv}(Y \cap U') = \emptyset$. This shows that without the promise, this approach may fail.

Lower Bound

We prove a stronger lower bound then the one stated in Theorem 2.4. In particular, in Section 6.3 we derive an $\Omega(d \log(n/d))$ lower bound which applies even to the promise variant.

The first part in the lower bound is a reduction from Set Disjointness on log m bits to planar convex set disjointness with m points. This achieved by fixing m points in a convex position, say on the unit circle, and identifying each log m bit-string z with one of the mpoints. Thus, for a bit-string z, let v_z denote the corresponding point on the unit circle. Next, given inputs $x, y \in \{0, 1\}^{\log m}$, Alice transform her input to the singleton set $\{v_x\}$, whereas Bob transform his input to the set $\{v_z | (\exists i) : y(i) = z(i) = 1\}$. Note that Alice's point is in Bob's set if and only if $x \cap y \neq \emptyset$. Moreover, since the m points are in convex position, Alice's point is in Bob's set if and only if it can not be separated from it by a hyperplane; i.e. if and only if their convex hulls intersect. This establishes a reduction from Set Disjointness on log m bits to (promise) Convex Set Disjointness on m points in \mathbb{R}^2 . See Figure 6 for an illustration of this construction.

The second part of the lower bound is to lift the planar construction to higher dimensions in a way that preserves the logic of the reduction: we take d orthogonal copies U_1, \ldots, U_d of the planar construction, each of size n/d and place them such that the following holds. Let $X, Y \subseteq \bigcup_i U_i$ be possible inputs for Alice and Bob and let $X_i = X \cap U_i, Y_i = Y \cap U_i$. Then,

$$((\forall i) : \operatorname{conv}(X_i) \cap \operatorname{conv}(Y_i) = \emptyset) \implies \operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset.$$

¹³Two halfspaces are equivalent if they have the same intersection with U.



Figure 6: A depiction of the reduction from Set Disjointness on 4 bits to Convex Set Disjointness on 16 points. Alice's input in Set Disjointness is 0010 while Bob's input is 0101. The domain U of Convex Set Disjointness has 16 equally spaced points on the unit circle (not the case in the figure above, to emphasize the dashed separating hyperplane). Alice's input is mapped to a single point, in this case, the point 0010. As every point in this construction can be separated by a line (in this figure, *e.g.*, the blue point), it follows that the convex hulls of Alice's and Bob's points are disjoint if and only if Alice's input is mapped to a point which is not in the set of points Bob's input is mapped to, which, in turn, happens if and only if the inputs of Alice and Bob for Set Disjointness were disjoint.

Specifically, the U_i 's are placed such that if \vec{n}_i is the normal of a hyperplane separating X_i and Y_i , then the vector $\vec{n} = \sum_i \vec{n}_i$ is the normal to a hyperplane that separates X and Y.

4.3 Learning Halfspaces

The bounds for Learning Halfspaces follow from the corresponding bounds for CSD.

The lower bound utilizes the lower bound for the promise variant of CSD. The promise plays a key role in enabling the lower bound to apply also to improper protocols. Indeed, it is not hard to see that an improper learning protocol can be used to decide the promise variant. The argument is straightforward, and we refer the reader to Section 6.3.2 for the complete short proof.

The upper bound is based on the $O(d \log n)$ protocol for the promise variant. Specifically, it exploits its following property: in the case when the convex hulls of X, Y are disjoint, the protocol returns a certificate in the form of a function $f : U \to {\pm 1}$ such f(u) = +1for every $u \in Y$ and f(u) = -1 for every $u \in X$ (see Lemma 6.10). This immediately yields a learning protocol in the case when Alice only has negative examples and Bob only has positive examples. The case where both Alice and Bob may have mixed examples is more subtle, but the protocol and analysis remain rather simple. We refer the reader to Section 6.2.2 for the complete proof.

5 A Container Lemma for Halfspaces

We establish here the existence of a small set of containers for halfspaces in \mathbb{R}^d .

Theorem (Theorem 2.6 restated). Let $U \subseteq \mathbb{R}^d$. Then, for every $\varepsilon > 0$ there is a set of ε -containers for $\mathsf{HS}(U)$ of size $(d/\varepsilon)^{O(d)}$.

This section is organized as follows: Section 5.1 contains some basic facts from VC theory. In Section 5.2 we discuss how this result relates with a classical result by Haussler which has a similar flavour Haussler [1995]. Finally, a complete proof of Theorem 2.6 is given in Section 5.3.

5.1 Preliminaries from VC theory.

We will use two basic results from VC theory. Recall that the VC dimension of a family $\mathcal{F} \subseteq 2^X$ is the size of the largest $Y \subseteq X$ such that $\{F \cap Y : F \in \mathcal{F}\} = 2^Y$. An ε -net for \mathcal{F} is a set $N \subseteq X$ such that $N \cap F \neq \emptyset$ for all $F \in \mathcal{F}$ with $|F| \ge \epsilon |X|$. A useful property of families with small VC-dimension is that they have small ε -nets.

Theorem 5.1 (ε -net Theorem). [Haussler and Welzl, 1986, Vapnik and Chervonenkis, 2015] Let $\mathcal{F} \subseteq 2^X$ be a family with VC dimension d and let $\varepsilon > 0$. Then, there exists an ε -net for \mathcal{F} of size $O\left(\frac{d\log(1/\varepsilon)}{\varepsilon}\right)$. We will also use the following lemma which bounds the growth in the VC dimension under set operations:

Lemma 5.2 (VC of k-fold compositions). [Blumer et al., 1989] Let $\mathcal{F}_1 \ldots \mathcal{F}_k$ be a sequence of families with VC dimension at most d, and let $\star_1 \ldots \star_{k-1}$ be a sequence of binary operations on sets (e.g. $\star_1 = \cap, \star_2 = \cup, \star_3 = \Delta$, and so forth). Set

$$\mathcal{F}^{\star k} = \Big\{ F_1 \star_1 (F_2 \star_2 \dots (F_{k-1} \star_{k-1} F_k)) : F_i \in \mathcal{F}_i \Big\}.$$

Then, the VC dimension of $\mathcal{F}^{\star k}$ is at most $O(kd \log d)$.

This Lemma allows to use the VC dimension of \mathcal{F} to bound the VC dimension of more complex families, *e.g.*,

$$\left\{ \left(F_1 \setminus \left(\cap_{i=2}^{100} F_i \right) \right) \cup F_{101} : F_i \in \mathcal{F} \right\}$$

5.2 Comparison with Haussler's Packing Lemma

Theorem 2.6 is closely related to a result by Haussler [1995], which asserts that every family $\mathcal{F} \subseteq 2^X$ with VC dimension d (e.g. d-1 dimensional halfspaces) has an ε -cover of size roughly $(1/\varepsilon)^d$, where an ε -cover is a family \mathcal{C} such that for every $F \in \mathcal{F}$ there is $C \in \mathcal{C}$ such that $|F\Delta C| \leq \varepsilon |X|$ (see Section 2.3.1).

We note that unlike Haussler's result, Theorem 2.6 does not extend to arbitrary VC classes (below is a counterexample with VC dimension 2). This is also reflected in our proof of Theorem 2.6 which exploits the dual variant of Carathéodory's Theorem (Proposition 2.7), which does not extend to arbitrary VC classes.

Example. Consider a projective plane P of order n with $N = n^2 + n + 1$ points and N lines. In particular the following holds: (i) for every pair of points there is a unique line containing them, (ii) every pair of lines intersects in one point, (iii) every line contains exactly n points, (iv) and every point is contained in exactly n lines.

Let \mathcal{F} be the family

$$\{L: L \text{ is a line in } P\}.$$

One can verify that \mathcal{F} has VC dimension 2. Set $\varepsilon = 1/4$. Since each line contains $n = O(\sqrt{N})$ points, then for a sufficiently large N, the existence of a set of ε -containers for \mathcal{F} of size t amounts to the following statement:

There exist t sets of size at most N/3 each, such that every line in P is contained in at least one of them.

Therefore, by averaging, one of these t sets contains at least N/t lines $L_1, L_2, \ldots L_{N/t}$. Denote such a set by C. Assume towards contradiction that t depends only on $\varepsilon = 1/4$ and d = 2, and in particular that $t \leq N/n = \theta(n)$. Now, since every two lines intersect in one point it follows that

$$|\cup_{i=1}^{N/t} L_i| \ge n + (n-1) + \dots + 1 \qquad (\text{because } |L_i \setminus \bigcup_{j < i} L_j| \ge n - (i-1)) \\ \ge n^2/2,$$

where in the first inequality we used that $N/t \ge n$. Thus, since C contains this union:

$$n^2/2 \le |C| \le N/3 = (n^2 + n + 1)/3,$$

which is a contradiction when n is sufficiently large.

5.3 Proof of Container Lemma (Theorem 2.6)

The superset \mathcal{C}' . Let $\mathcal{C}' = \{U \setminus (\bigcap_{i=1}^{d} H_i) : H_i \in \mathsf{HS}_d\}$. It is easy to see that $\mathcal{C}' \supseteq \mathsf{HS}(U)$, and therefore it is an ε -cover for $\mathsf{HS}(U)$, for every ε . However \mathcal{C}' is a much larger set than we can afford. The final cover \mathcal{C} will be a carefully selected subfamily of \mathcal{C}' .

To select the subset $\mathcal{C} \subseteq \mathcal{C}'$, we use the following observation that provides a criteria to certify that \mathcal{C} is a set of ε -containers for HS_d : it suffices to show that for every $H \in \mathsf{HS}_d$ there is $C \in \mathcal{C}$ such that C is an ε -container for F. Here, for any $C, F \subseteq 2^X$, we say that Cis an ε -container for F if $F \subseteq C$, and $|C \setminus F| \leq \varepsilon |X|$.

Observation 5.3. Let $\mathcal{F}, \mathcal{C} \subseteq 2^X$. Let V be an ε -net for $\{C' \setminus F' : C' \in \mathcal{C}, F' \in \mathcal{F}\}$. Let $C \in \mathcal{C}$ and $F \in \mathcal{F}$ such that

- 1. $F \subseteq C$ and
- 2. $C \cap V = F \cap V$.

Then, C is an ε -container for F. (Namely, $F \subseteq C$, and $|C \setminus F| \leq \varepsilon |X|$).

Proof. Given items 1 in the observation, it remains to show that $|C \setminus F| \leq \varepsilon |X|$. This follows by the second item, which implies that $\emptyset = (C \cap V) \setminus (F \cap V) = (C \setminus F) \cap V$, and since V is an ε -net for $\{C' \setminus F' : C' \in \mathcal{C}, F' \in \mathcal{F}\}$. We get that $|C \setminus F| \leq \varepsilon |X|$, as required.

The ε -net V. Our selection of $\mathcal{C} \subseteq \mathcal{C}'$ hinges on Observation 5.3, and therefore we use an ε -net V for the family $\mathcal{C}'' = \{C' \setminus H' : C' \in \mathcal{C}', H' \in \mathsf{HS}_d\}$ of size

$$|V| = O\left(\frac{d^2 \log d \log(1/\varepsilon)}{\varepsilon}\right).$$

(Note, in particular, that V is an ϵ -net for every subfamily of \mathcal{C}''). The bound on |V| follows from Theorem 5.1 because the VC dimension of \mathcal{C}'' is $O(d^2 \log d)$. This bound on the VC dimension of \mathcal{C}'' follows because the VC dimension of HS_d is d+1, thus, due to Lemma 5.2, the VC dimension of \mathcal{C}' and \mathcal{C}'' is $O(d^2 \log d)$. The family of containers C. Next we construct C. The construction is based on an encoding-decoding scheme: given a halfspace $H \in \mathsf{HS}(U)$, the scheme encodes H into a bit-string $\mathbf{b} = \mathbf{b}(H)$ of length $t = O(d \log |V|)$. The bit-string \mathbf{b} is then decoded to a set $C = C(\mathbf{b}) \in C'$ satisfying the two items in Observation 5.3 with respect to V – and therefore C is an ε -container of H. The upper bound on the length t of \mathbf{b} implies that the collection $\{C(\mathbf{b}) : \mathbf{b} \in \{0,1\}^t\} \subseteq C'$ is a set of ε -containers for $\mathsf{HS}(U)$ of size $2^t = O(d \log |V|) = |V|^{O(d)} = (d/\varepsilon)^{O(d)}$.

Let $H \in \mathsf{HS}(U)$. Let $a \in \mathbb{R}^d$, $||a||_{\infty} \leq 1$ and $b \in \mathbb{R}$, $|b| \leq 1$ be such that

$$H = \{ u \in U : \langle a, u \rangle < b \}.$$

Moreover, since U is finite, we may assume without loss of generality that there exists a universal¹⁴ small constant $\varepsilon > 0$ such that $\langle a, u \rangle < b - \varepsilon$ for every $u \in H$ and $\langle a, u \rangle > b + \varepsilon$ for every $u \in U \setminus H$.

The rest of the proof is devoted to constructing an ε -container C for H by first constructing $\mathbf{b} = \mathbf{b}(H)$ and then $C = C(\mathbf{b})$.

The auxiliary polytope \mathcal{P} . The definition of $\boldsymbol{b}(H)$ uses a polytope \mathcal{P} that we define next. Recall that $V \subseteq U$ is an ε -net for $\mathcal{C}'' = \{C' \setminus H' : C' \in \mathcal{C}', H' \in \mathsf{HS}_d\}$. Let $V^- = V \cap H = \{v \in V : \langle a, v \rangle < b\}, V^+ = V \setminus H = \{v \in V : \langle a, v \rangle \ge b\}$. Define $\mathcal{P} \subseteq \mathbb{R}^{d+1}$:

$$\mathcal{P} = \left\{ (\alpha, \beta) \in \mathbb{R}^d \times \mathbb{R} \mid (\|(\alpha, \beta)\|_{\infty} \le 1) \land (\forall v \in V^+ : \langle \alpha, v \rangle \ge \beta + \varepsilon) \land (\forall v \in V^- : \langle \alpha, v \rangle \le \beta - \varepsilon) \right\}$$

Observe that \mathcal{P} contains a representation (α, β) for each halfspace $H' = \{u \in U : \langle \alpha, u \rangle < \beta\}$ such that $H' \cap V = H \cap V = V^-$, and only such representations. The constraint $\|(\alpha, \beta)\|_{\infty} \leq 1$ ensures that $\mathcal{P} \subseteq \mathbb{R}^{d+1}$ is bounded, a property which will be enable us to apply Proposition 2.7 to \mathcal{P} . Note that \mathcal{P} is a closed polytope which is defined by |V| + 2(d+1)linear inequalities (the constraint $\|(\alpha, \beta)\|_{\infty} \leq 1$ amounts to 2(d+1) linear inequalities). Moreover, note that \mathcal{P} is non-empty, since $(a, b) \in \mathcal{P}$ (see Figure 2).

The encoding b(H). The bit-string b = b(H) encodes the polytope \mathcal{P} , as well as the names of d + 2 vertices x_0, \ldots, x_{d+1} of \mathcal{P} such that $(a, b) \in \operatorname{conv}(\{x_0, \ldots, x_{d+1}\})$ is in their convex hull (the existence of such vertices is promised by the Carathéodory's Theorem).

The polytope \mathcal{P} can be encoded using $O(d \log d)$ bits, as \mathcal{P} is determined by $V^- = H \cap V \in \mathsf{HS}(V)$, and V^- can be described using $\log|\mathsf{HS}(V)| \leq d \log|V| + 1 = O(d \log d)$ bits, where the first inequality is because $|\mathsf{HS}(V)| \leq 2|V|^d$ (see, e.g., [Gärtner and Welzl, 1994]).

The points $\boldsymbol{x}_0, \ldots, \boldsymbol{x}_{d+1}$ can be naively conveyed using $d^2 \log d$ bits¹⁵. To obtain a more compressed representation of these points, we use the dual version of Carathéodory

¹⁴I.e. that depends only on U.

¹⁵To see that, observe that the number of vertices in \mathcal{P} is $O(\binom{|V|+2(d+1)}{d+1}) = \exp(d\log d)$, because \mathcal{P} is defined by |V| + 2(d+1) constraints, and each vertex is determined by d+1 constraints. Therefore, each vertex can be described using $O(d\log d)$ bits, and d+2 vertices can be represented by $O(d^2\log d)$ bits.

Theorem (Proposition 2.7). Since $\mathcal{P} \subseteq \mathbb{R}^{d+1}$ is defined as the intersection of |V| + 2(d+1) halfspaces, Proposition 2.7 shows such vertices $\boldsymbol{x}_0, \ldots, \boldsymbol{x}_{d+1}$ can be represented using $\log(|V| + 2(d+1))^{d+2} = O(d \log d)$ bits.

The decoding $C(\mathbf{b})$. The next lemma shows how an ε -container $C = C(\mathbf{b})$ for H can be derived from \mathbf{b} , thus concluding the proof of Theorem 2.6.

Lemma 5.4. Let $H = \{u \in U : \langle a, u \rangle < b\}$ as above. Let $(\alpha_0, \beta_0), \ldots, (\alpha_{d+1}, \beta_{d+1})$ be vertices of \mathcal{P} such that $(a, b) \in \operatorname{conv}(\{(\alpha_i, \beta_i)\})$. Then, the set $C = U \setminus (\bigcap_{i=1}^{d+2} H_i)$, where $H_i = \{x : \langle \alpha_i, x \rangle \geq \beta_i\}$, satisfies the two items in Observation 5.3 with respect to H.

Proof. (i) $H \subseteq C$: let $u \in H$. Therefore, $u \in U$ and $\langle a, u \rangle < b$. Now, since (a, b) is a convex combination of the (α_i, β_i) 's, it must be the case that $\langle \alpha_i, u \rangle < \beta_i$ for some $i \in \{0, \ldots, d+1\}$, *i.e.*, that $u \notin H_i$. The reason is that we can write $a = \sum_{i=0}^{d+1} \gamma_i \alpha_i$ and $b = \sum_{i=0}^{d+1} \gamma_i \beta_i$ where $\gamma_i \in [0, 1]$. Thus, if $\langle \alpha_i, u \rangle \geq \beta_i$ for all $i \in \{0, \ldots, d+1\}$, then $\langle a, u \rangle = \langle \sum_{i=0}^{d+1} \gamma_i \alpha_i, u \rangle = \sum_{i=0}^{d+1} \gamma_i \langle \alpha_i, u \rangle \geq \sum_{i=0}^{d+1} \gamma_i \beta_i = b$, contradicting the fact that $\langle a, u \rangle < b$. Since there exists $i \in \{0, \ldots, d+1\}$ such that $u \notin H_i$, we get $u \notin \bigcap_i H_i$. This implies $u \in C$, as required.

(ii) $C \cap V = H \cap V$: For every $i \in \{0, \ldots, d+1\}$, since $(\alpha_i, \beta_i) \in \mathcal{P}$, it follows that $V \setminus H_i = \overline{H}_i \cap V = H \cap V = V^-$. This implies $H \cap V = V^- = V \setminus (\bigcap_{i=1}^m H_i) = C \cap V$, as required.

5.4 Proof of Dual Carathéodory Theorem (Proposition 2.7)

The Encoding-Decoding Procedure. Let $\mathcal{Q} \subseteq \mathbb{R}^d$ be a polytope which is defined by n linear inequalities and let $a \in \mathcal{Q}$. The proof boils down to an encoding and encoding procedures which are based on bottom vertex triangulation [Clarkson, 1988, Goodman and O'Rourke, 2004] and are described in Figure 3.

The encoding procedure receives \mathcal{Q} and $a \in \mathcal{Q}$ as inputs and outputs a sequence S of d out of the n linear inequalities used to define \mathcal{Q} . The decoding procedure receives \mathcal{Q} and S as inputs and output a sequence $\mathbf{x}_0, \ldots, \mathbf{x}_d$ of vertices of \mathcal{Q} such that $a \in \operatorname{conv}(\{\mathbf{x}_0, \ldots, \mathbf{x}_d\})$. That is, S encodes a subpolytope defined by d + 1 vertices that contains a. Since there are at most n^d such sequences S and since every point $a \in \mathcal{Q}$ is contained in one of the encoded subpolytopes, this will imply that \mathcal{Q} can be covered by n^d such subpolytopes as required.

We use the following convention: for every polytope \mathcal{Q}' , fix a pivot vertex $p(\mathcal{Q}') \in \mathcal{Q}'$ (for example, $p(\mathcal{Q}')$ can be the bottom vertex in \mathcal{Q} , or the smallest vertex with respect to the lexicographical order, etcetera). Also, let dim (\mathcal{Q}') denote the dimension of \mathcal{Q}' (*i.e.*, the dimension of the affine span¹⁶ of \mathcal{Q}).

¹⁶Recall that the affine span of a set A is the minimal affine subspace that contains A.

Analysis. The description of the encoding and decoding procedures appears in Figure 3. We finish the proof by showing that $\boldsymbol{a} \in \operatorname{conv}(\{\boldsymbol{x}_0, \ldots, \boldsymbol{x}_d\})$. This follows by induction on $\dim(\mathcal{Q})$: the base case of $\dim(\mathcal{Q}) = 0$ is trivial. For the induction step, assume that the claim holds for every polytope of dimension strictly less than k, and prove the claim for $\dim(\mathcal{Q}) = k$: by construction, \boldsymbol{a} is a convex combination of \boldsymbol{x}_0 and \boldsymbol{a}_1 . Since $\dim(\mathcal{Q}_1) = k - 1$, by the induction hypothesis, \boldsymbol{a}_1 is in the convex hull of $\boldsymbol{x}_1 \ldots \boldsymbol{x}_d$. This implies that \boldsymbol{a} is in the convex hull of $\boldsymbol{x}_0 \ldots \boldsymbol{x}_d$, as required.

6 Communication Complexity Proofs

This section is organized as follows. In Section 6.1 we formally define the communication problems discussed in this paper and survey some elementary tools from communication complexity. In Sections 6.2 and 6.3 we prove Theorems 2.3 and 2.4.

6.1 Preliminaries

We use capital letters to denotes sets (e.g., X, Y, U). We denote by calligraphic capital letters families of sets (e.g., C, \mathcal{F}). We use bold small letters to denote vectors (e.g., $\boldsymbol{x}, \boldsymbol{y}$). We sometimes write $\boldsymbol{x}^{(k)}$ to stress that the vector \boldsymbol{x} consists of k coordinates, numbered 1 to k. If \boldsymbol{x} is a vector, we denote by x_i the i^{th} coordinate in \boldsymbol{x} .

Communication complexity

We use standard notation and terminology from Yao's communication complexity model [Yao, 1979], and refer the reader to [Kushilevitz and Nisan, 1997] for a textbook introduction. For a (possibly partial) function f, we denote by D(f) the deterministic communication complexity of f, and by $R_{\epsilon}(f)$ the randomized communication complexity of f with error probability $\epsilon \geq 0$. We set $R(f) = R_{1/3}(f)$.

Definition 6.1 (DISJ_n). The disjointness function $DISJ_n : \{0,1\}^n \times \{0,1\}^n \rightarrow \{0,1\}$ is defined as:

$$\mathsf{DISJ}_n(\boldsymbol{x}, \boldsymbol{y}) = \begin{cases} 0 & , \exists i \colon x_i = y_i = 1 \\ 1 & , otherwise. \end{cases}$$

Definition 6.2 (AND_k). For a function $f : \mathcal{X} \times \mathcal{Y} \to \{0,1\}$, the function AND_k $\circ f : \mathcal{X}^k \times \mathcal{Y}^k \to \{0,1\}$ is defined as:

$$\mathsf{AND}_k \circ f(\boldsymbol{x}^{(k)}, \boldsymbol{y}^{(k)}) = \bigwedge_{i=1}^k f(x_i, y_i).$$

Convex set disjointness

Definition 6.3 (CSD_U). Let $U \subseteq \mathbb{R}^d$ be a finite set. The convex set disjointness function $CSD_U(X,Y): 2^U \times 2^U \to \{0,1\}$ is defined as:

$$\mathsf{CSD}_U(X,Y) = \begin{cases} 0 & ,\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \phi \\ 1 & , otherwise. \end{cases}$$

Definition 6.4 (PromiseCSD_U). Let $U \subseteq \mathbb{R}^d$ be a finite set. The partial function $\mathsf{PromiseCSD}_U(X,Y): 2^U \times 2^U \to \{0,1\}$ is defined as:

$$\mathsf{PromiseCSD}_U(X,Y) = \begin{cases} 0 & , X \cap Y \neq \phi \\ 1 & , \operatorname{conv}(X) \cap \operatorname{conv}(Y) = \phi. \end{cases}$$

Learning halfspaces

Fix a finite domain $U \subseteq \mathbb{R}^n$. An example is a pair $(\boldsymbol{x}, y) \in U \times \{\pm 1\}$. An example (\boldsymbol{x}, y) is called a positive (negative) example if y = +1 (y = -1). A set of examples $S \subseteq U \times \{\pm 1\}$ is called a sample. Recall that for a set $U \subseteq \mathbb{R}^d$ we denote by $\mathsf{HS}(U) = \{H \cap U : H \in \mathsf{HS}_d\}$ family of all halfspaces restricted to U.

<u>Learning halfpaces over U</u> refers to the following search problem. Alice's and Bob's inputs are samples $S_a, S_b \subseteq U \times \{\pm 1\}$ such that there exists a halfspace which contains all the positive examples in $S_a \cup S_b$ and does not contain any negative examples in $S_a \cup S_b$, and their goal is to output a function $f : U \to \{\pm 1\}$ such that $f(\boldsymbol{x}) = y$ for every example $(\boldsymbol{x}, y) \in S_a \cup S_b$. If the protocol is randomized then we require it will outputs such a function with probability at least 2/3.

Reductions

All functions in this section may be partial. We denote by dom(f) the domain of the (possibly partial) function f.

Definition 6.5 (Reduction). We say a function $f_1 : \mathcal{X}_1 \times \mathcal{Y}_1 \to \{0,1\}$ reduces to a function $f_2 : \mathcal{X}_2 \times \mathcal{Y}_2 \to \{0,1\}$ (denoted $f_1 \leq f_2$) if there exists functions $\alpha : \mathcal{X}_1 \to \mathcal{X}_2$ and $\beta : \mathcal{Y}_1 \to \mathcal{Y}_2$ such that for all $(x, y) \in \text{dom}(f_1)$:

$$f_1(x, y) = f_2(\alpha(x), \beta(y)).$$

We use the phrase "reduction functions" to refer to the functions α, β . If f_2 is a partial function, we further require that $(\alpha(x), \beta(y)) \in \text{dom}(f_2)$.

The following results are straightforward:

Observation 6.6. For functions f_1 , f_2 , and f_3 , we have $(f_1 \leq f_2) \land (f_2 \leq f_3) \implies f_1 \leq f_3$. **Observation 6.7.** For functions f_1 , f_2 , we have $f_1 \leq f_2 \implies R_{\epsilon}(f_1) \leq R_{\epsilon}(f_2)$ for all $\epsilon \geq 0$. We will also use the following basic lemma whose proof appears in in Section A.

Lemma 6.8. For functions f_1, f_2 , if $f_1 \leq f_2$, then for any k > 0, we have $AND_k \circ f_1 \leq AND_k \circ f_2$.

6.2 Upper Bounds

6.2.1 Convex Set Disjointness

In this section, we prove the following upper bound on the communication complexity of the *Convex Set Disjointness* problem and its promise variant:

Lemma 6.9. Let $U \subseteq \mathbb{R}^d$ with |U| = n. Then,

- 1. $D(\mathsf{PromiseCSD}_U) = O(d \log d \log n), and$
- 2. $D(\mathsf{CSD}_U) = O(d^2 \log d \log n).$

Lemma 6.9 clearly implies Theorem 2.3. We prove Lemma 6.9 in two steps: (i) we prove the first item by demonstrating a protocol for $\mathsf{PromiseCSD}_U$, and (ii) we derive the second item by a general reduction that shows that any protocol for $\mathsf{PromiseCSD}_U$ with communication complexity C(n,d) implies a protocol with communication complexity $C'(n,d) = C((2n)^{d+2},d)$ for CSD_U . Plugging $C(n,d) = O(d \log d \log n)$ then yields the second item.

An Upper Bound for PromiseCSD

We next prove the following lemma, which amounts to the first item in Lemma 6.9:

Lemma 6.10. Let $U \subseteq \mathbb{R}^d$ with |U| = n. Then, the protocol in Figure 7 witnesses that $D(\mathsf{PromiseCSD}_U) = O(d \log d \log n)$. Furthermore, for inputs $X, Y \subseteq U$ such that $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$, the protocol outputs a function $h : U \to \{\pm 1\}$ such that $X \subseteq h^{-1}(-1)$ and $Y \subseteq h^{-1}(+1)$.

This function h promised by the above lemma will later be used for learning halfspaces.

Proof. A complete description of the protocol is presented in Figure 7. The correctness is based on the following simple observation:

Observation 6.11. Consider the sets U_i, X_i, Y_i in the "While" loop in item (2) of the protocol in Figure 7.

- 1. If $\operatorname{conv}(X_i) \cap \operatorname{conv}(Y_i) = \emptyset$ then there is a halfspace $H \in \mathsf{HS}(U_i)$ such that $|H| \leq |U_i|/2$, and either $X_i \subseteq H$ or $Y_i \subseteq H$.
- 2. $X_i \cap Y_i = X_{i+1} \cap Y_{i+1}$.

The first item follows since $\operatorname{conv}(X_i) \cap \operatorname{conv}(Y_i) = \emptyset$ implies that there is a hyperplane that separates X_i from Y_i , and therefore one of the two halfspaces defined by this hyperplane contains at most half of the points in U_i .

The second item follows since $C \in C_i$ either contains X_i or Y_i . If $C \supseteq X_i$ then $X_{i+1} = X_i$ and $Y_{i+1} = Y_i \cap C \supseteq Y_i \cap X_i$. Otherwise, $C \supseteq Y_i$ and $X_{i+1} = X_i \cap C \supseteq X_i \cap Y_i$ and $Y_{i+1} = Y_i$. In both cases, $X_i \cap Y_i = X_{i+1} \cap Y_{i+1}$.

Correctness. We first assume that $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$. Consider iteration *i* of the "While" loop. Since $X_i \subseteq X$ and $Y_i \subseteq Y$, it holds that $\operatorname{conv}(X_i) \cap \operatorname{conv}(Y_i) \subseteq \operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$. By the first item of Observation 6.11, either Alice or Bob always find a container $C \in \mathcal{C}_i$ in item (2.2), and therefore the protocol will reach items (2.4) and (2.5). Since the protocol will never reach item (2.3), the "While" loop will eventually terminate with $|U_i| = 0$ and item (3) will be reached, outputting "1" as required. To see that the output function h satisfies $X \subseteq h^{-1}(-1), Y \subseteq h^{-1}(1)$, note that at the *i*'th step, h is defined over all points in $U \setminus U_i$ and satisfies $X \setminus X_i \in h^{-1}(-1), Y \setminus Y_i \in h^{-1}(1)$. Thus, the requirement is met since at the last iteration i^* we have $U_{i^*} = X_{i^*} = \emptyset$.

Next, assume that $X \cap Y \neq \emptyset$. In this case, the protocol must terminate in item (2.3) within the "While" loop. This is because, by the second item of Observation 6.11, $|X_i \cap Y_i|$ is a positive constant for all *i* while $|U_i|$ decreases, thus eventually $X_i \cap Y_i$ becomes larger than $\frac{3}{4}|U_i|$. When this happens, no party can find a set *C* satisfying the requirements of (2.2) and the protocol outputs "0".

Communication Complexity. The "While" loop in item (2) proceeds for at most $O(\log n)$ iterations; this is because in each iteration U_i shrinks by a multiplicative factor of at most 3/4. In each of the iterations the parties exchange $\log |\mathcal{C}_i| + O(1)$ bits, which is bounded by $O(d \log d)$ bits. Thus, the total number of bits communicated is $O(d \log d \log n)$.

From Protocols for PromiseCSD to Protocols for CSD

The next lemma implies that a bound of C = C(n, d) on the communication complexity of the promise variant implies a bound of $C'(n, d) = C((2n)^{d+2}, d)$ on the communication complexity of the non-promise variant.

Lemma 6.12. For any $U \subseteq \mathbb{R}^d$ of size n there is $V \subseteq \mathbb{R}^d$ of size at most $(2n)^{d+2}$ such that $\mathsf{CSD}_U \prec \mathsf{PromiseCSD}_V.$

(Recall that " \leq " denotes a reduction with zero communication, see Definition 6.5).

Lemma 6.12 implies the second item in Lemma 6.9 by plugging $(2n)^{d+2}$ instead of n in Lemma 6.10. Thus, Lemma 6.10 and Lemma 6.12 imply Lemma 6.9. It therefore remains to prove Lemma 6.12.

An $O(d \log d \log n)$ -bits deterministic protocol for PromiseCSD_U

Let U ⊆ ℝ^d and let n = |U|.
Alice's input: X ⊆ U,
Bob's input: Y ⊆ U.
Output: if X ∩ Y ≠ Ø output "0",
if conv(X) ∩ conv(Y) = Ø output "1" as well as a function h : U → {±1} such that X ⊆ h⁻¹(-1) and Y ⊆ h⁻¹(+1) (h will be used in our learning protocol).
(1) Set i = 1, U₁ = U, X₁ = X, Y₁ = Y, ε = 1/4, and f as the empty function.
(2) While |U_i| > 0:
(2.1) Without communication, the parties agree on a set C_i of ε-containers HS(U_i), such that |C_i| = (d/ε)^{O(d)} (as in Theorem 2.6).
(2.2) Each of Alice and Bob checks whether there is C ∈ C_i such that |C| ≤ ³/₄|U_i| and C contains their current set; namely, Alice looks for such a C ∈ C_i that contains Y_i.
(2.3) If both Alice and Bob cannot find such a C then the protocol terminates with output "0".

- (2.4) Else, if Alice found C then she communicates it to Bob (using $O(d \log d)$ bits), and the parties do:
 - (2.4.1) set $X_{i+1} = X_i \cap C, Y_{i+1} = Y_i \cap C, U_{i+1} = U_i \cap C,$
 - (2.4.2) extend h to $U_i \setminus C$ by setting h(u) = 0 for all $u \in U_i \setminus C$,
 - (2.4.3) increment $i \leftarrow i + 1$ and go to (2)
- (2.5) Similarly, if Bob found C then he communicates it to Alice (using $O(d \log d)$ bits), and the parties do:
 - (2.4.1) set $X_{i+1} = X_i \cap C, Y_{i+1} = Y_i \cap C, U_{i+1} = U_i \cap C,$
 - (2.4.2) extend h to $U_i \setminus C$ by setting $\underline{h(u)} = 1$ for all $u \in U_i \setminus C$,
 - (2.4.3) increment $i \leftarrow i + 1$ and go to (2)
- (3) Output "1" and the function h.

Figure 7: A protocol for Promise Convex Set Disjointness

Proof of Lemma 6.12. The set V is defined as follows: for any $S_1, S_2 \subseteq U$ such that $\operatorname{conv}(S_1) \cap \operatorname{conv}(S_2) \neq \emptyset$ and $|S_1| + |S_2| \leq d + 2$ add to V (any) point $x = x(S_1, S_2) \in \operatorname{conv}(S_1) \cap \operatorname{conv}(S_2)$. Note that indeed $|V| \leq \sum_{d_1+d_2=d+2} {|U| \choose d_1} {|U| \choose d_2} \leq (2n)^{d+2}$. Next, given inputs $X, Y \subseteq U$ for CSD_U , Alice and Bob transform them to

$$\alpha(X) = \operatorname{conv}(X) \cap V \text{ and } \beta(Y) = \operatorname{conv}(Y) \cap V.$$

Validity. To establish the validity of this reduction we need to show that

 $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset \implies \operatorname{conv}(\alpha(X)) \cap \operatorname{conv}(\beta(Y)) = \emptyset$, and $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset \implies \alpha(X) \cap \beta(Y) \neq \emptyset$.

Indeed, if $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$ then also $\operatorname{conv}(\alpha(X)) \cap \operatorname{conv}(\alpha(Y)) = \emptyset$ (because $\alpha(X) \subseteq \operatorname{conv}(X)$ and $\beta(Y) \subseteq \operatorname{conv}(Y)$).

The second assertion follows from Proposition 2.8 which we next recall:

Proposition (Proposition 2.8 restatement). Let $X, Y \subseteq \mathbb{R}^d$ such that $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$. \emptyset . Then $\operatorname{conv}(S_1) \cap \operatorname{conv}(S_2) \neq \emptyset$ for some $S_1 \subseteq X, S_2 \subseteq Y$ such that $|S_1| + |S_2| \leq d + 2$.

To see how this implies the second assertion, assume that $\operatorname{conv}(X) \cap \operatorname{conv}(Y) \neq \emptyset$. By Proposition 2.8, there exists $S_1 \subseteq X, S_2 \subseteq Y$ with $|S_1| + |S_2| \leq d + 2$ and $\operatorname{conv}(S_1) \cap \operatorname{conv}(S_2) \neq \emptyset$. By construction, V contains a point $x = x(S_1, S_2)$ in $\operatorname{conv}(S_1) \cap \operatorname{conv}(S_2)$. It holds that $x \in \operatorname{conv}(S_1) \cap V \subseteq \operatorname{conv}(X) \cap V = \alpha(X)$ and $x \in \operatorname{conv}(S_2) \cap V \subseteq \operatorname{conv}(Y) \cap V = \beta(Y)$. Hence, $\alpha(X) \cap \beta(Y) \neq \emptyset$, as claimed.

6.2.2 Learning Halfspaces

We next prove the following upper bound for learning halfspaces.

Theorem (Theorem 2.1 restatement). Let $d, n \in \mathbb{N}$, and let $U \subseteq \mathbb{R}^d$ be a domain with n points. Then, there exists a deterministic protocol for learning HS(U) with communication complexity $O(d \log d \log n)$.

Proof. We present a learning protocol which relies on Lemma 6.9 and uses the protocol in Figure 7 as a black-box. The learning protocol is presented in Figure 8.

Analysis. First, note that the communication complexity is at most $O(d \log d \log n)$ bits: indeed, there is no communication in steps (3) and (6), each of steps (1) and (2) involves an application of the protocol from Figure 7 which costs $O(d \log d \log n)$ bits, and each of steps (4) and (5) involves transmitting a separator from $\mathsf{HS}(U)$ which costs $O(d \log n)$ bits (since $|\mathsf{HS}(U)| \leq O(n^d)$, see *e.g.* [Gärtner and Welzl, 1994]).

As for correctness, note that since it is assumed that the negative and positive examples in $S_a \cup S_b$ are separated by a hyperplane, Lemma 6.9 implies that the functions f, g which are outputted in steps (1) and (2) satisfy: An $O(d \log d \log n)$ -bits deterministic learning protocol for halfspaces

Let $U \subseteq \mathbb{R}^d$ and let n = |U|.

Alice's input: a sample $S_a \subseteq U \times \{\pm 1\}$,

Bob's input: a sample $S_b \subseteq U \times \{\pm 1\}$.

(It is assumed that there exists a separating hyperplane between the positive and negative examples in $S_a \cup S_b$).

Output: a function $h: U \to \{\pm 1\}$ such that $h(\boldsymbol{x}) = y$ for every $(\boldsymbol{x}, y) \in S_a \cup S_b$.

- (1) Apply the protocol from Figure 7 on inputs X^-, Y^+ , where $X^- = \{ \boldsymbol{u} : (\boldsymbol{u}, -1) \in S_a \}$ and $Y^+ = \{ \boldsymbol{u} : (\boldsymbol{u}, +1) \in S_b \}$.
 - (1.1) If the protocol outputted "0" then output "Error".
 - (1.2) Else, let $g: U \to \{\pm 1\}$ denote the function outputted by the protocol, such that $g(\boldsymbol{u}) = +1$ for every $\boldsymbol{u} \in Y^+$ and $g(\boldsymbol{u}) = -1$ for every $\boldsymbol{u} \in X^-$.
- (2) Apply the protocol from Figure 7 on inputs X^+, Y^- , where $X^+ = \{ \boldsymbol{u} : (\boldsymbol{u}, +1) \in S_a \}$ and $Y^+ = \{ \boldsymbol{u} : (\boldsymbol{u}, -1) \in S_b \}$.
 - (2.1) If the protocol outputted "0" then output "Error".
 - (2.2) Else, let $f: U \to \{\pm 1\}$ denote the function outputted by the protocol, such that $f(\boldsymbol{u}) = +1$ for every $\boldsymbol{u} \in X^+$ and $f(\boldsymbol{u}) = -1$ for every $\boldsymbol{u} \in Y^-$. (note that f is actually the negation of the output function.)
- (3) Let $F^+ = f^{-1}(+1), F^- = f^{-1}(-1)$ and $G^+ = g^{-1}(+1), G^- = g^{-1}(-1)$. (Note that these 4 sets are known to both Alice and Bob.)
- (4) Alice transmits to Bob using $O(d \log n)$ bits an indicator $I_{+-} : U \to \{\pm 1\}$ of a halfspace in $\mathsf{HS}(U)$ which separates <u>her</u> positive and negative examples in $F^+ \cap G^-$; namely, $I_{+-}(u) = b$ for every $u \in F^+ \cap G^-$ such that $(u, b) \in S_a$.
- (5) Bob transmits to Alice using $O(d \log n)$ bits an indicator $I_{-+} : U \to \{\pm 1\}$ of a halfspace in $\mathsf{HS}(U)$ which separates <u>his</u> positive and negative examples in $F^- \cap G^+$; namely, $I_{-+}(u) = b$ for every $u \in F^- \cap G^+$ such that $(u, b) \in S_b$.
- (6) Alice and Bob output the function h defined by

$$h(u) = \begin{cases} +1 & \boldsymbol{u} \in F^+ \cap G^+, \\ -1 & \boldsymbol{u} \in F^- \cap G^-, \\ I_{+-}(u) & \boldsymbol{u} \in F^+ \cap G^-, \\ I_{-+}(u) & \boldsymbol{u} \in F^- \cap G^+. \end{cases}$$

Figure 8: A protocol for Promise Convex Set Disjointness

- $f(\boldsymbol{u}) = +1$ for every $(\boldsymbol{u}, +1) \in S_a$ and $f(\boldsymbol{u}) = -1$ for every $(\boldsymbol{u}, -1) \in S_b$, and similarly
- $g(\boldsymbol{u}) = -1$ for every $(\boldsymbol{u}, -1) \in S_a$ and $g(\boldsymbol{u}) = +1$ for every $(\boldsymbol{u}, +1) \in S_b$.

We will show that the h (the function outputted by the protocol) classifies correctly each of the regions $F^+ \cap G^+$, $F^- \cap G^-$, $F^+ \cap G^-$, and $F^- \cap G^+$ (the definition of these regions appears in the protocol). Since these 4 regions cover U, it will follow that h classifies correctly all examples. Indeed $F^+ \cap G^+$ contains only positive examples and $F^- \cap G^-$ contains only negative examples, therefore h classifies correctly these regions. As for $F^+ \cap G^-$ and $F^- \cap G^+$, note that $F^+ \cap G^-$ contains only examples in S_a and $F^- \cap G^+$ contains only examples in S_b . Thus, I_{+-} classifies correctly every example in $F^+ \cap G^-$ and I_{-+} classifies correctly every example in $F^- \cap G^+$. It therefore follows that h classifies correctly also these regions.

Remark. Note that the above protocol actually learns a more general problem than halfspaces: indeed, let S_a^+, S_a^- denote Alice's positive and negative examples respectively, and let S_b^+, S_b^- denote Bob's positive and negative examples respectively. The protocol will output a consistent function h for as long as each of the pairs S_a^+ and S_a^-, S_b^+ and S_b^-, S_a^+ and S_b^- and S_b^- and S_b^- and superplane (possibly a different hyperplane for every pair). However it is not necessary that there will be a single hyperplane separating all positive examples from all negative examples.

6.3 Lower Bounds

6.3.1 Convex Set Disjointness

In this section we prove a lower bound on the randomized communication complexity of **PromiseCSD**. This implies the same lower bound for **CSD**, and therefore yields Theorem 2.4. More precisely, we prove that

Theorem 6.13. Let n, d > 0 be integers. There is a set $U \subseteq \mathbb{R}^d$ such that |U| = nand $R(\mathsf{PromiseCSD}_U) \ge \Omega(d \log(n/d))$.

The key ingredient in the proof of Theorem 6.13 is the following reduction:

Lemma 6.14. For any integers c, k > 0, there is a set $U \subseteq \mathbb{R}^{3c}$ such that $|U| = 2^k c$ and

$$\mathsf{DISJ}_{ck} \preceq \mathsf{PromiseCSD}_U$$
.

We prove Lemma 6.14 below. Assuming Lemma 6.14, the following argument proves Theorem 6.13.

Proof of Theorem 6.13. Fix d and n. Set c = d/3 and set k such that $n = 2^k c$. We assume without loss of generality that k, c are positive integers. By Lemma 6.14, there is set $U \subseteq \mathbb{R}^d$, |U| = n such that

$$\mathsf{DISJ}_{ck} \preceq \mathsf{PromiseCSD}_U$$
.

Using the well known fact that $R(\text{DISJ}_m) \ge \Omega(m)$ (see, e.g., Kalyanasundaram and Schintger [1992]), and Observation 6.7, it follows that

$$R(\mathsf{PromiseCSD}_U) \ge \Omega(ck) = \Omega(d \log(n/d)).$$

Proof of Lemma 6.14

Let c, k > 0 be arbitrary. To prove Lemma 6.14, we show that there exist sets $U \subseteq \mathbb{R}^{3c}, V \subseteq \mathbb{R}^2$ such that $|U| = 2^k c$ and $|V| = 2^k$ such that the following sequence of reductions holds

$$\mathsf{DISJ}_{ck} \preceq \mathsf{AND}_c \circ \mathsf{DISJ}_k \preceq \mathsf{AND}_c \circ \mathsf{PromiseCSD}_V \preceq \mathsf{PromiseCSD}_U.$$

Each of these reductions is proved separately below. Lemma 6.14 then follows using Observation 6.6.

Proving $DISJ_{ck} \preceq AND_c \circ DISJ_k$. The first reduction in our sequence is essentially using the fact that $DISJ_m$ can be viewed as an AND of m simpler functions.

Lemma 6.15. $DISJ_{ck} \preceq AND_c \circ DISJ_k$

Proof. Let $\boldsymbol{x}^*, \boldsymbol{y}^* \in \{0, 1\}^{ck}$ be an input for DISJ_{ck} . We can view \boldsymbol{x}^* as a vector $\boldsymbol{x}^{(c)}$ with entries in \mathbb{R}^k . Precisely, \boldsymbol{x}_i (respectively \boldsymbol{y}_i) is the $((i-1)k+1)^{\text{st}}$ to $(ik)^{\text{th}}$ coordinates of \boldsymbol{x}^* (resp. \boldsymbol{y}^*). Let the reduction function α (resp. β) be the function that takes \boldsymbol{x}^* to \boldsymbol{x} (resp. \boldsymbol{y}^* to \boldsymbol{y}). Note that:

$$\mathsf{DISJ}_{ck}(\boldsymbol{x}^*, \boldsymbol{y}^*) = 0 \iff \exists i \in [ck] \colon x_i^* = y_i^* = 1$$
$$\iff \exists i \in [c], j \in [k] \colon x_{ij} = y_{ij} = 1$$
$$\iff \exists i \in [c] \colon \mathsf{DISJ}_k(\boldsymbol{x}_i, \boldsymbol{y}_i) = 0$$
$$\iff \left(\bigwedge_{i=1}^c \mathsf{DISJ}_k(\boldsymbol{x}_i, \boldsymbol{y}_i) \right) = 0$$
$$\iff \mathsf{AND}_c \circ \mathsf{DISJ}_k(\boldsymbol{x}, \boldsymbol{y}) = 0$$
$$\iff \mathsf{AND}_c \circ \mathsf{DISJ}_k(\boldsymbol{\alpha}(\boldsymbol{x}^*), \beta(\boldsymbol{y}^*)) = 0.$$

Proving $AND_c \circ DISJ_k \preceq AND_c \circ PromiseCSD_V$. By Lemma 6.8, the following result is sufficient:

Lemma 6.16. For all k > 0, there exists $V \subseteq \mathbb{R}^2$, $|V| = 2^k$ such that $\mathsf{DISJ}_k \preceq \mathsf{PromiseCSD}_V$.

Proof. We define the set V to consist of 2^k points on the unit circle in \mathbb{R}^2 . The crucial property satisfied by these set of points is that every $\boldsymbol{v} \in V$ can be separated by a line

from $V \setminus \{v\}$ (*i.e.*, these points are in *convex position*). Let us index the points in V by the vectors in $\{0, 1\}^k$, *i.e.*, $V = \{v_x \mid x \in \{0, 1\}^k\}$ (see Figure 6).

We next define the functions α, β which witness the desired reduction. Define α : $\{0, 1\}^k \to 2^V$ by

$$\alpha(\boldsymbol{x}) = \{\boldsymbol{v}_{\boldsymbol{x}}\}.$$

Next, define $\beta : \{0,1\}^k \to 2^V$ as

$$\beta(\boldsymbol{y}) = \{ \boldsymbol{v}_{\boldsymbol{z}} \text{ for } \boldsymbol{z} \in \{0,1\}^k \text{ such that } \exists i \in [k] : z_i = y_i = 1 \}.$$

Observe that for every input $\boldsymbol{x} \in \{0,1\}^k$, the set $\alpha(\boldsymbol{x}) = \{\boldsymbol{v}_{\boldsymbol{x}}\}$ is a singleton. Thus, for every possible $\boldsymbol{y} \in \{0,1\}^k$, it is either the case that $\boldsymbol{v}_{\boldsymbol{x}} \in \beta(\boldsymbol{y})$, or else, since $\boldsymbol{x} \in V$ and $\beta(\boldsymbol{y}) \subseteq V$, and due to the crucial property described above, it is the case that $\boldsymbol{v}_{\boldsymbol{x}} \notin \operatorname{conv}(\beta(\boldsymbol{y}))$. Equivalently, it is either the case that $\alpha(\boldsymbol{x}) \cap \beta(\boldsymbol{y}) \neq \emptyset$ or that $\operatorname{conv}(\alpha(\boldsymbol{x})) \cap \operatorname{conv}(\beta(\boldsymbol{y})) = \emptyset$, thus the sets $\alpha(\boldsymbol{x})$ and $\beta(\boldsymbol{y})$ are in the domain of $\operatorname{PromiseCSD}_V$.

We have

$$\mathsf{DISJ}_k(\boldsymbol{x}, \boldsymbol{y}) = 0 \iff \exists i \in [k] \colon x_i = y_i = 1$$
$$\iff \alpha(\boldsymbol{x}) \cap \beta(\boldsymbol{y}) \neq \emptyset$$
$$\iff \mathsf{PromiseCSD}_V(\alpha(\boldsymbol{x}), \beta(\boldsymbol{y})) = 0.$$

Proving $AND_c \circ PromiseCSD_V \preceq PromiseCSD_U$.

Lemma 6.17. Let $V \subseteq \mathbb{R}^2$, |V| = m. For all integers c > 0, there is a set $U \subseteq \mathbb{R}^{3c}$ of size $c \cdot m$ such that

$$\mathsf{AND}_c \circ \mathsf{PromiseCSD}_V \preceq \mathsf{PromiseCSD}_U.$$

Proof. We embed each of the c copies of $\mathsf{PromiseCSD}_V$ in a disjoint triplet of coordinates of \mathbb{R}^{3c} . Formally, for $j \in [c]$, define the j^{th} 'lift' function $g_j : \mathbb{R}^2 \to \mathbb{R}^{3c}$ as:

$$g_j((x_1, x_2)) = (\underbrace{0, 0, \cdots, 0}_{3(j-1) \text{ times}}, x_1, x_2, 1, \underbrace{0, 0, \cdots, 0}_{3(c-j) \text{ times}}).$$

Define the set $U = \{g_j(v) \mid j \in [c], v \in V\}.$

Let $X^{(c)}, Y^{(c)}$ be an input for $AND_c \circ PromiseCSD_V$. Define:

$$\alpha(\boldsymbol{X}) = \bigcup_{j=1}^{c} g_j(X_j) \qquad \qquad \beta(\boldsymbol{Y}) = \bigcup_{j=1}^{c} g_j(Y_j).$$

(Recall that X_j, Y_j denote the j'th copies of $\mathbf{X}^{(c)}, \mathbf{Y}^{(c)}$ respectively.) We prove that α, β define the desired reduction. First, assume that $\mathsf{AND}_c \circ \mathsf{PromiseCSD}_V(\mathbf{X}, \mathbf{Y}) = 1$, that is, $\forall j \in [c], \operatorname{conv}(X_j) \cap \operatorname{conv}(Y_j) = \emptyset$. By the hyperplane separation theorem, for every $j \in [c]$

there exists an affine function $l_j : \mathbb{R}^2 \to \mathbb{R}$ of the form $l_j((x_1, x_2)) = l_j + l'_j x_1 + l''_j x_2$ such that $l_j(x) > 0$ for all $x \in X_j$, while $l_j(y) < 0$ for all $y \in Y_j$.

Define the affine function $l : \mathbb{R}^{3c} \to \mathbb{R}$ by $l((x_1, x_2, \cdots, x_{3c})) = \sum_{i \in [c]} l_j x_{3j} + l'_j x_{3j-2} + l''_j x_{3j-1}$. Observe that for all $j \in [c]$, we have $\forall (x_1, x_2) \in \mathbb{R}^2 : l(g_j((x_1, x_2))) = l_j((x_1, x_2))$. This implies that l(x) > 0 for all $x \in \alpha(\mathbf{X})$, while l(y) < 0 for all $y \in \beta(\mathbf{Y})$. Thus, $\alpha(\mathbf{X}) \cap \beta(\mathbf{Y}) = \emptyset$, implying $\mathsf{PromiseCSD}_U(\alpha(\mathbf{X}), \beta(\mathbf{Y})) = 1$.

For the other direction, assume that $\mathsf{AND}_c \circ \mathsf{PromiseCSD}_V(\mathbf{X}, \mathbf{Y}) = 0$, that is, $\exists j \in [c], z \in V: z \in X_j \cap Y_j$. Then, $g_j(z) \in \alpha(\mathbf{X}) \cap \beta(\mathbf{Y})$, implying $\alpha(\mathbf{X}) \cap \beta(\mathbf{Y}) \neq \emptyset$ and therefore also $\mathsf{PromiseCSD}_U(\alpha(\mathbf{X}), \beta(\mathbf{Y})) = 0$.

6.3.2 Learning Halfspaces

Theorem (Theorem 2.2 restatement). Let $d, n \in \mathbb{N}$. Then, there exists a domain $U \subseteq \mathbb{R}^d$ with n points such that every (possibly improper and randomized) protocol that learns $\mathsf{HS}(U)$ must transmit at least $\Omega(d \log(n/d))$ bits of communication.

Proof. This is a corollary of Theorem 6.13: let $U \subseteq \mathbb{R}^d$ be as in the conclusion of Theorem 6.13. We claim that every protocol that learns $\mathsf{HS}(U)$ can be used to decide $\mathsf{PromiseCSD}_U$. Indeed, let X, Y be inputs to $\mathsf{PromiseCSD}_U$. Alice and Bob apply the learning protocol on the samples $X \times \{+1\}$ and $Y \times \{-1\}$. (i) If $\operatorname{conv}(X) \cap \operatorname{conv}(Y) = \emptyset$ then X, Y can be separated by a hyperplane and the protocol will output a function $h: U \to \{\pm 1\}$ such that $h(\boldsymbol{u}) = +1$ for every $\boldsymbol{u} \in X$ and $h(\boldsymbol{u}) = -1$ for every $\boldsymbol{u} \in Y$. (ii) In the other case, if $X \cap Y = \emptyset$ then there exists no such function and therefore the learning protocol must output "Error". Therefore, by Theorem 6.13, every such learning protocol must transmit at least $\Omega(d \log(n/d))$ bits.

7 Summary and Future Research

We established bounds on the communication complexity of convex set disjointness (equivalently, LP feasibility) and learning halfspaces over a domain of n points in \mathbb{R}^d .

For learning halfspaces we establish a bound of $\Theta(d \log n)$, which is tight up to a $\log d$ factor. Our upper bound is achieved by an improper protocol (i.e. it returns a classifier which is not necessarily a halfspace). It would be interesting to determine whether a similar bound can be achieved by a proper learning protocol.

For Convex Set Disjointness, the gap between our lower and upper bounds is more significant: $\tilde{O}(d^2 \log n)$ versus $\Omega(d \log n)$, and it would be interesting to tighten it.

Another interesting direction is to further explore the halfspace container lemma which we used (e.g. improve the bound, find other natural VC classes which satisfy a similar statement, etcetera.)

Acknowledgements

We thank Noga Alon, Sepehr Assadi, and Shachar Lovett for insightful discussions and comments.

References

- Maria-Florina Balcan, Avrim Blum, Shai Fine, and Yishay Mansour. Distributed learning, communication complexity and privacy. In COLT 2012 - The 25th Annual Conference on Learning Theory, June 25-27, 2012, Edinburgh, Scotland, pages 26.1-26.22, 2012. URL http://www.jmlr.org/proceedings/papers/v23/balcan12a/balcan12a.pdf. 2, 8
- Jozsef Balogh, Robert Morris, and Wojciech Samotij. The method of hypergraph containers, 2018.6
- A. Blumer, A. Ehrenfeucht, D. Haussler, and M. K. Warmuth. Learnability and the Vapnik-Chervonenkis dimension. J. Assoc. Comput. Mach., 36(4):929–965, 1989. ISSN 0004-5411. doi: 10.1145/76359.76371. 19
- C. Carathéodory. Über den Variabilitätsbereich der Koeffizienten von Potenzreihen, die gegebene Werte nicht annehmen. Math. Ann., 64(1):95–115, 1907. ISSN 0025-5831. doi: 10.1007/BF01449883. URL https://doi.org/10.1007/BF01449883. 6
- Shang-Tse Chen, Maria-Florina Balcan, and Duen Horng Chau. Communication efficient distributed agnostic boosting. In Proceedings of the 19th International Conference on Artificial Intelligence and Statistics, AISTATS 2016, Cadiz, Spain, May 9-11, 2016, pages 1299–1307, 2016. URL http://jmlr.org/proceedings/papers/v51/chen16e.html. 8
- Kenneth L. Clarkson. A randomized algorithm for closest-point queries. *SIAM J. Comput.*, 17(4):830-847, August 1988. ISSN 0097-5397. doi: 10.1137/0217052. URL http://dx.doi.org/10.1137/0217052. 12, 22
- Kenneth L. Clarkson. Las vegas algorithms for linear and integer programming when the dimension is small. J. ACM, 42(2):488-499, March 1995. ISSN 0004-5411. doi: 10.1145/201019.201036. URL http://doi.acm.org/10.1145/201019.201036. 3, 9
- Yuval Dagan, Gil Kur, and Ohad Shamir. Space lower bounds for linear prediction. In *COLT, to appear*, volume abs/1902.03498, 2019. 8
- Hal Daumé III, Jeff M. Phillips, Avishek Saha, and Suresh Venkatasubramanian. Efficient protocols for distributed classification and optimization. In Algorithmic Learning Theory 23rd International Conference, ALT 2012, Lyon, France, October 29-31, 2012. Proceedings, pages 154–168, 2012. doi: 10.1007/978-3-642-34106-9_15. URL https://doi.org/10.1007/978-3-642-34106-9_15. 2, 8

- Uriel Feige, David Peleg, Prabhakar Raghavan, and Eli Upfal. Computing with noisy information. SIAM Journal on Computing, 23(5):1001–1018, 1994. 4
- Bernd Gärtner and Emo Welzl. Vapnik-chervonenkis dimension and (pseudo-)hyperplane arrangements. Discrete & Computational Geometry, 12:399–432, 1994. doi: 10.1007/ BF02574389. URL https://doi.org/10.1007/BF02574389. 21, 28
- Jacob E. Goodman and Joseph O'Rourke, editors. Handbook of Discrete and Computational Geometry, Second Edition. Chapman and Hall/CRC, 2004. ISBN 978-1-58488-301-2. doi: 10.1201/9781420035315. URL https://doi.org/10.1201/9781420035315. 12, 22
- David Haussler. Sphere packing numbers for subsets of the boolean n-cube with bounded vapnik-chervonenkis dimension. Journal of Combinatorial Theory, Series A, 69(2):217– 232, 1995. 6, 18, 19
- David Haussler and Emo Welzl. Epsilon-nets and simplex range queries. In CG, pages 61–71, 1986. 18
- Bala Kalyanasundaram and Georg Schintger. The probabilistic communication complexity of set intersection. SIAM Journal on Discrete Mathematics, 5(4):545–557, 1992. 3, 31
- Daniel M. Kane, Roi Livni, Shay Moran, and Amir Yehudayoff. On communication complexity of classification problems. In COLT, to appear, volume abs/1711.05893, 2019. 2, 8, 9, 12
- Jakub Konečný, H. Brendan McMahan, Felix X. Yu, Peter Richtarik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. In NIPS Workshop on Private Multi-Party Machine Learning, 2016. URL https://arxiv.org/abs/1610.05492. 2
- Eyal Kushilevitz and Noam Nisan. Communication complexity. Cambridge University Press, 1997. ISBN 978-0-521-56067-2. 4, 23
- László Loväsz and Michael Saks. Communication complexity and combinatorial lattice theory. Journal of Computer and System Sciences, 47(2):322 – 349, 1993. ISSN 0022-0000. doi: https://doi.org/10.1016/0022-0000(93)90035-U. URL http://www.sciencedirect. com/science/article/pii/002200009390035U. 8
- F. Rosenblatt. The perceptron: A probabilistic model for information storage and organization in the brain. *Psychological Review*, pages 65–386, 1958. 2
- Vladimir N Vapnik and A Ya Chervonenkis. On the uniform convergence of relative frequencies of events to their probabilities. In *Measures of Complexity*, pages 11–30. Springer, 2015. 18

- Santosh S. Vempala, Ruosong Wang, and David P. Woodruff. The communication complexity of optimization, 2019. 3, 4, 8, 9, 12
- Emanuele Viola. The communication complexity of addition. In SODA, pages 632–651, 2013. 4
- Andrew Chi-Chih Yao. Some complexity questions related to distributive computing (preliminary report). In *STOC*, pages 209–213, 1979. 23

Appendix A Missing proofs

Proof of Lemma 6.8. Since $f_1 \leq f_2$, we know that there exists reduction functions α, β such that for all $(x, y) \in \text{dom}(f_1)$:

$$f_1(x,y) = f_2(\alpha(x),\beta(y)).$$

Define:

$$\alpha^*(\boldsymbol{x}^{(k)}) = (\alpha(x_1), \alpha(x_2), \cdots, \alpha(x_k)),$$

$$\beta^*(\boldsymbol{y}^{(k)}) = (\beta(y_1), \beta(y_2), \cdots, \beta(y_k)).$$

Note that

$$\mathsf{AND}_k \circ f_1(\boldsymbol{x}, \boldsymbol{y}) = \bigwedge_{i \in [k]} f_1(x_i, y_i)$$
$$= \bigwedge_{i \in [k]} f_2(\alpha(x_i), \beta(y_i)) = \mathsf{AND}_k \circ f_2(\alpha^*(\boldsymbol{x}), \beta^*(\boldsymbol{y})).$$

. 6		т