

Secure Distributed Storage: Rate-Privacy Trade-Off and XOR-Based Coding Scheme

Rémi A. Chou

Department of Electrical Engineering & Computer Science
Wichita State University
Wichita, KS 67260
remi.chou@wichita.edu

Jörg Kliewer

Department of Electrical & Computer Engineering
New Jersey Institute of Technology
Newark, NJ 07102
jkliwer@njit.edu

Abstract—We consider the problem of storing data in a distributed manner over T servers. We require the data (i) to be recoverable from the T servers, and (ii) to remain private from any $T - 1$ colluding servers, where privacy is quantified in terms of mutual information between the data and all the information available at the $T - 1$ colluding servers. For this model, we determine (i) the fundamental trade-off between storage size and the level of desired privacy, (ii) the optimal amount of local randomness necessary at the encoder, and (iii) an explicit low-complexity coding scheme that solely relies on XOR operations and that asymptotically (with the data size) matches the fundamental limits found.

I. INTRODUCTION

Secure distributed storage schemes, e.g., [1]–[5], often rely on the idea of secret sharing as introduced in [6], [7]. Hence, there is a fundamental lower bound on the required storage space necessary to securely store information in a distributed manner. Specifically, in any secret sharing scheme, the total amount of information that needs to be stored must at least be equal to the entropy of the secret times the number of participants, see e.g., [8], and it is thus impossible to reduce the storage space without any changes to the model assumptions.

To this end, we propose to determine the optimal cost reduction, in terms of storage space, that can be obtained in exchange of tolerating a *controlled amount* of reduced privacy. This idea is closely related to non-perfect secret sharing [9], [10] with a non-linear access function that generalize traditional ramp secret sharing [11]–[13]. Unfortunately, for large secrets, as required for data storage, no low-complexity coding scheme is known to implement non-perfect secret sharing. Note that in the absence of a privacy constraint, for the related problems of perfect secret sharing and secure distributed storage, XOR-based coding schemes have been proposed in [14] and [15], [16], respectively.

We aim to fill this void in this paper and focus on a setting where a file F needs to be stored at T servers. The data is intended to be recoverable from these T servers, and needs to remain private from any $T - 1$ colluding servers. Here, privacy is quantified in terms of mutual information between the data and all the information available at the $T - 1$ colluding servers.

To be concrete, consider the example of three servers, i.e., $T = 3$, where the mutual information between the data of any two servers and the file F must not exceed $L \triangleq \frac{1}{4}H(F)$. Assuming that F is a sequence of uniformly distributed bits, we split F in four parts (F_1, F_2, F_3, F_4) of equal length (for simplicity we assume here that $|F|$ is a multiple of four), and we store in the three servers the shares

$$\begin{aligned} M_1 &\triangleq (F_1 \| K_1 \| F_2 \oplus K_2 \oplus K_4), \\ M_2 &\triangleq (K_2 \| K_3 \| F_3 \oplus K_1 \oplus K_5), \\ M_3 &\triangleq (K_4 \| K_5 \| F_4 \oplus K_3), \end{aligned}$$

where $(K_1, K_2, K_3, K_4, K_5)$ are five sequences of uniformly distributed bits with size $|F|/4$, \oplus denotes the XOR operation, and $\|$ denotes concatenation. We remark that all the four parts (F_1, F_2, F_3, F_4) are either stored in clear or encrypted through a one-time pad. By inspection, one easily sees in this example that F can be recovered from (M_1, M_2, M_3) and any two shares leak at most $\frac{1}{4}H(F)$ bits about F . As it will be shown in the following, the size of the shares is optimal as well as the amount of local randomness, i.e., the length of $(K_1, K_2, K_3, K_4, K_5)$.

Our main contribution is the design of a low-complexity coding scheme for this problem with arbitrary parameters L and T that solely relies on XOR operations and that is asymptotically (with file size) optimal in terms of data storage and the required amount of local randomness at the encoder.

The remainder of the paper is organized as follows. We formalize the problem in Section II and state our main results in Section III. Our coding scheme is presented in Section IV. We present the proofs of our results in the appendix. Finally, we provide concluding remarks in Section V.

II. PROBLEM STATEMENT

Notation: For $a, b \in \mathbb{R}$, define $\llbracket a, b \rrbracket \triangleq \llbracket a \rrbracket, \llbracket b \rrbracket \cap \mathbb{N}$ and $[a]^+ \triangleq \max(0, a)$. Let \oplus denote the XOR operator. Consider $T \geq 2$ servers and define $\mathcal{T} \triangleq \llbracket 1, T \rrbracket$. Consider a file F which is a sequence of $|F|$ bits uniformly distributed over $\{0, 1\}^{|F|}$.

Definition 1. A (λ, ρ) coding scheme consists of

- A stochastic encoder $e : \{0, 1\}^{|F|} \times \{0, 1\}^\rho \rightarrow \{0, 1\}^{\lambda T}, (F, R) \mapsto (M_t)_{t \in \mathcal{T}}$, which takes as input the

file F to store and a sequence R of $\rho \in \mathbb{N}$ bits uniformly distributed over $\{0, 1\}^\rho$ and independent of F , and outputs T sequences (referred to as shares in the following) $(M_t)_{t \in \mathcal{T}}$ of length $\lambda \in \mathbb{N}$, where M_t is stored in Server $t \in \mathcal{T}$.

- A decoder $d : \{0, 1\}^{\lambda T} \rightarrow \{0, 1\}^{|F|}$, $(M_t)_{t \in \mathcal{T}} \mapsto \hat{F}$, which takes as input all the T sequences stored at the servers, and outputs an estimate \hat{F} of the file F .

Definition 2. For $\alpha \in [0, 1]$, a (λ, ρ) coding scheme is said to be α -private if

$$H(F|M_{\mathcal{T}}) = 0, \text{ (Decodability)} \quad (1)$$

$$\lim_{|F| \rightarrow \infty} \frac{I(F; M_{\mathcal{S}})}{H(F)} \leq \alpha, \forall \mathcal{S} \subsetneq \mathcal{T}, \text{ (Privacy)} \quad (2)$$

where we have used the notation $M_{\mathcal{S}} \triangleq (M_t)_{t \in \mathcal{S}}$, $\forall \mathcal{S} \subsetneq \mathcal{T}$.

The objective is to design α -private (λ, ρ) coding schemes with minimal storage size requirement, i.e., minimal λ , and minimal amount of local randomness requirement at the encoder, i.e., minimal ρ .

In the following, one can assume

$$\alpha < 1 - 1/T. \quad (3)$$

Indeed, if $\alpha \geq 1 - 1/T$, i.e., $\alpha \geq \frac{T-1}{T}$, then the privacy constraint is trivially satisfied if one splits the file in T parts of size $H(F)/T$ and store one part in each server.

III. MAIN RESULTS

Theorem 1 (Minimal storage size requirement). For any α -private (λ, ρ) coding scheme, we have

$$\lim_{|F| \rightarrow \infty} \frac{\lambda}{H(F)} \geq (1 - \alpha).$$

Theorem 2 (Minimal local randomness requirement). For any α -private (λ, ρ) coding scheme, we have

$$\lim_{|F| \rightarrow \infty} \frac{\rho}{H(F)} \geq [T(1 - \alpha) - 1]^+.$$

Theorem 3 (Achievability). Assume that $\alpha = 0$ or $\alpha = \frac{l}{k}$, for some $k, l \in \mathbb{N}^*$ with k and l coprime, and $\alpha \in [0, 1 - 1/T[$. By density of \mathbb{Q} in \mathbb{R} , such an α can be chosen arbitrarily close to any point in $[0, 1]$. The coding scheme in Section IV is an α -private (λ, ρ) coding scheme with

$$\lim_{|F| \rightarrow \infty} \frac{\lambda}{H(F)} = (1 - \alpha), \quad (4)$$

$$\lim_{|F| \rightarrow \infty} \frac{\rho}{H(F)} = [T(1 - \alpha) - 1]^+. \quad (5)$$

IV. CODING SCHEME

Consider $\alpha \in [0, 1 - 1/T[$ such that $\alpha = 0$ or $\alpha = \frac{l}{k}$, for some $k, l \in \mathbb{N}^*$ with k and l coprime.

A. Preliminaries

- There exists $q \in \mathbb{N}$, $r \in [0, T - 2]$ such that

$$l = q(T - 1) + r, \quad (6)$$

and one can assume

$$qT + r < k. \quad (7)$$

Otherwise, if $qT + r = k$ (one has a similar argument if $qT + r > k$), then one can split the file F in k parts of equal size and store $q + 1$ parts of F in the first r servers and q parts of F in the remaining servers. The privacy constraint is satisfied by (6) because any $T - 1$ servers have at most $q(T - 1) + r = l$ parts of F , and (2) holds.

- Note that $T(k - l) - k = (T - 1)k - lT > 0$ by (3), and there exists $u \in \mathbb{N}$, $v \in [0, T - 1]$ such that

$$T(k - l) - k = uT + v. \quad (8)$$

We emphasize that l , k , and T are the only parameters of the coding scheme; q , r , u , and v are obtained as sole functions of l , k , and T .

B. Coding Scheme

Step 1. Divide the file in k parts $(F_i)_{i \in [1, k]}$ (if necessary, add β zeros to F , where β is the smallest integer in $[1, k - 1]$ such that $(H(F) + \beta)/k \in \mathbb{N}$. For convenience, we write $F_{i:j} \triangleq (F_{i'})_{i' \in [i, j]}$ for $i, j \in [1, k]$.

Step 2. Generate $N_{\text{keys}} \triangleq T(k - l) - k (> 0$ by (8)) keys $(K_i)_{i \in [1, N_{\text{keys}}]}$ each uniformly distributed over $\{0, 1\}^{(H(F) + \beta)/k}$ and independent of all other random variables. For convenience, we write $K_{i:j} \triangleq (K_{i'})_{i' \in [i, j]}$ for $i, j \in [1, N_{\text{keys}}]$.

Step 3. We now describe how to design the shares $M_{\mathcal{T}}$. Each share M_t , stored in Server $t \in \mathcal{T}$, is a vector of $(k - l)$ sequences (labeled from 1 to $k - l$) of size $(H(F) + \beta)/k$. For convenience, for $t \in \mathcal{T}$, and $i, j \in [1, k - l]$ such that $i \leq j$, we write $M_t[i : j]$ to designate the sequences of M_t labeled from i to j , and $M_t[i]$ to designate the sequence of M_t labeled by i . For $t \in \mathcal{T}$, the $k - l$ components of the vector M_t are of one of the following types.

- An unencrypted part of F , i.e., an element of $\{F_i : i \in [1, k]\}$.
- A key, i.e., an element of $\{K_i : i \in [1, N_{\text{keys}}]\}$;
- An encrypted part of F , obtained by XORing a part of F with one or several keys.

To precisely describe how the shares $M_{\mathcal{T}}$ are chosen we distinguish two cases.

Case 1. Assume that $r + v < T$. The unencrypted parts of F and keys are assigned according to Algorithms 1, 2, respectively. The encrypted parts of F are defined and assigned according to Algorithm 4. Note that we have the following.

- For $t \in [1, r]$, M_t consists of $k - l$ sequences: $q + 1$ unencrypted parts of F , u keys, and

$$x \triangleq k - l - q - 1 - u \quad (9)$$

encrypted parts of F .

- For $t \in [r + 1, T - v]$, M_t consists of $k - l$ sequences: q unencrypted parts of F , u keys, and $x + 1$ encrypted parts of F .

- For $t \in \llbracket T - v + 1, T \rrbracket$, M_t consists of $k - l$ sequences: q unencrypted parts of F , $u + 1$ keys, and x encrypted parts of F .

Case 2. Assume that $r + v \geq T$. The unencrypted parts of F and keys are assigned according to Algorithms 1, 3, respectively. The encrypted parts of F are defined and assigned according to Algorithm 5. Note that we have the following.

- For $t \in \llbracket 1, T - v \rrbracket$, M_t consists of $k - l$ sequences: $q + 1$ unencrypted parts of F , u keys, and x encrypted parts of F .
- For $t \in \llbracket T - v + 1, r \rrbracket$, M_t consists of $k - l$ sequences: $q + 1$ unencrypted parts of F , $u + 1$ keys, and $x - 1$ encrypted parts of F .
- For $t \in \llbracket r + 1, T \rrbracket$, M_t consists of $k - l$ sequences: q unencrypted parts of F , $u + 1$ keys, and x encrypted parts of F .

Remark 1. In both cases, the first $N_{\text{Plain}} \triangleq qT + r$ parts $(F_i)_{i \in \llbracket 1, qT + r \rrbracket}$ are stored unencrypted in the servers, and the $N_{\text{Encrypted}} \triangleq k - r - Tq$ (> 0 by (7)) remaining parts $(F_i)_{i \in \llbracket qT + r + 1, k \rrbracket}$ are first encrypted using the keys $(K_i)_{i \in \llbracket 1, T(k-l) - k \rrbracket}$ before being stored in the servers.

Remark 2. In Case 1, we have $x \geq 0$, otherwise $k - r - Tq = N_{\text{Encrypted}} = (r + v)x + (T - r - v)(x + 1) < 0$, which contradicts (7). In Case 2, we also have $x \geq 0$, otherwise $k - r - Tq = N_{\text{Encrypted}} = (T - v + T - r)x + (r - T + v)(x - 1) < 0$, which again contradicts (7).

Algorithm 1 Assignment of unencrypted parts

Input: File F

```

1: for  $t \in \mathcal{T}$  do
2:    $M_t[1 : q] \triangleq F_{(t-1)q+1:tq}$ 
3:   if  $t \leq r$  then
4:      $M_t[q + 1] \triangleq F_{Tq+t}$ 
5:   end if
6: end for

```

Algorithm 2 Assignment of keys when $r + v < T$

Inputs: Keys $(K_i)_{i \in \llbracket 1, N_{\text{keys}} \rrbracket}$

```

1: for  $t \in \mathcal{T}$  do
2:   if  $t \leq r$  then
3:      $M_t[q + 2 : q + 1 + u] \triangleq K_{u(t-1)+1:ut}$ 
4:   else if  $r < t \leq T - v$  then
5:      $M_t[q + 1 : q + u] \triangleq K_{u(t-1)+1:ut}$ 
6:   else if  $t > T - v$  then
7:      $M_t[q + 1 : q + u] \triangleq K_{u(t-1)+1:ut}$ 
8:      $M_t[q + u + 1] \triangleq K_{Tu+t-(T-v)}$ 
9:   end if
10:  Define
11:   $\mathcal{I}_t \triangleq \{j \in \llbracket 1, N_{\text{keys}} \rrbracket : \exists i \in \llbracket 1, l - k \rrbracket, M_t[i] = K_j\}$ 
12: end for

```

Algorithm 3 Assignment of keys when $r + v \geq T$

Inputs: Keys $(K_i)_{i \in \llbracket 1, N_{\text{keys}} \rrbracket}$

```

1: for  $t \in \mathcal{T}$  do
2:   if  $t \leq T - v$  then
3:      $M_t[q + 2 : q + 1 + u] \triangleq K_{u(t-1)+1:ut}$ 
4:   else if  $T - v < t \leq r$  then
5:      $M_t[q + 2 : q + u + 2] \triangleq K_{u(T-v)+(u+1)(t-T+v-1)+1:u(T-v)+(u+1)(t-T+v)}$ 
6:   else if  $t > r$  then
7:      $M_t[q + 1 : q + u + 1] \triangleq K_{u(T-v)+(u+1)(t-T+v-1)+1:u(T-v)+(u+1)(t-T+v)}$ 
8:   end if
9:   Define
10:   $\mathcal{I}_t \triangleq \{j \in \llbracket 1, N_{\text{keys}} \rrbracket : \exists i \in \llbracket 1, l - k \rrbracket, M_t[i] = K_j\}$ 
11: end for

```

Algorithm 4 Creation and assignment of encrypted parts when $r + v < T$

Inputs: File F and keys $(K_i)_{i \in \llbracket 1, N_{\text{keys}} \rrbracket}$

```

1: for  $i \in \llbracket 1, x + 1 \rrbracket$  do
2:   for  $t \in \mathcal{T}$  do
3:     if  $t \leq r$  then
4:        $j \triangleq N_{\text{Plain}} + (t - 1)x + i$ 
5:        $z \triangleq \begin{cases} q + u + 1 + i & \text{if } i \neq x + 1 \\ \emptyset & \text{if } i = x + 1 \end{cases}$ 
6:     else if  $r < t \leq T - v$  then
7:        $j \triangleq N_{\text{Plain}} + rx + (t - r - 1)(x + 1) + i$ 
8:        $z \triangleq q + u + i$ 
9:     else if  $t > T - v$  then
10:       $j \triangleq N_{\text{Plain}} + rx + (x + 1)(T - v - r) + (t - T + v - 1)x + i$ 
11:       $z \triangleq \begin{cases} q + u + 1 + i & \text{if } i \neq x + 1 \\ \emptyset & \text{if } i = x + 1 \end{cases}$ 
12:     end if
13:     For  $t' \in \mathcal{T} \setminus \{t\}$ , choose the key  $K_a$  with the smallest  $a \in \mathcal{I}_{t'}$ , which has not previously been chosen in this algorithm, among the keys stored in Server  $t'$ , and define  $\kappa_{t'} \triangleq K_a$ . If this is not possible, then define  $\kappa_{t'} = \mathbf{0}$ .
14:     If  $z \neq \emptyset$ , then define  $M_t[z] \triangleq F_j \oplus \bigoplus_{t' \in \mathcal{T} \setminus \{t\}} \kappa_{t'}$ 
15:   end for
16: end for

```

C. Examples

Example 1 ($T = 3$, $\alpha = \frac{3}{10}$). Write $F = (F_i)_{i \in \llbracket 1, 10 \rrbracket}$. We have $(l, k) \triangleq (3, 10)$. By (6), we have $(q, r) = (1, 1)$ and by (8), we have $(u, v) = (3, 2)$. We have $r + v = T$, so we are in Case 2. Moreover, $N_{\text{Keys}} = 11$, $N_{\text{Plain}} = 4$, $N_{\text{Encrypted}} = 6$, $x = 2$. After running Algorithms 1 and 3, we have

$$M_1 \triangleq (F_1 \| F_4 \| K_1 \| K_2 \| K_3 \| M_1[6] \| M_1[7]),$$

$$M_2 \triangleq (F_2 \| K_4 \| K_5 \| K_6 \| K_7 \| M_2[6] \| M_2[7]),$$

$$M_3 \triangleq (F_3 \| K_8 \| K_9 \| K_{10} \| K_{11} \| M_3[6] \| M_3[7]).$$

Algorithm 5 Creation and assignment of encrypted parts when $r + v \geq T$

Input: File F

```

1: for  $i \in \llbracket 1, x \rrbracket$  do
2:   for  $t \in \mathcal{T}$  do
3:     if  $t \leq T - v$  then
4:        $j \triangleq N_{\text{Plain}} + (t - 1)x + i$ 
5:        $z \triangleq q + u + 1 + i$ 
6:     else if  $T - v < t \leq r$  then
7:        $j \triangleq N_{\text{Plain}} + (T - v)x + (t - T + v - 1)(x - 1) + i$ 
8:        $z \triangleq \begin{cases} q + u + 2 + i & \text{if } i \neq x \\ \emptyset & \text{if } i = x \end{cases}$ 
9:     else if  $t > r$  then
10:       $j \triangleq N_{\text{Plain}} + (T - v)x + (r - T - v)(x - 1) + (t - r - 1)x + i$ 
11:       $z \triangleq q + u + 1 + i$ 
12:     end if
13:     if  $z \neq \emptyset$  then
14:       For  $t' \in \mathcal{T} \setminus \{t\}$ , choose the key  $K_a$  with the
       smallest  $a \in \mathcal{I}_{t'}$ , which has not previously been
       chosen in this algorithm, and define  $\kappa_{t'} \triangleq K_a$ . If
       this is not possible, then define  $\kappa_{t'} = \mathbf{0}$ .
15:       Define  $M_t[z] \triangleq F_j \oplus \bigoplus_{t' \in \mathcal{T} \setminus \{t\}} \kappa_{t'}$ 
16:     end if
17:   end for
18: end for

```

After running Algorithm 5, we obtain the encrypted parts of the file F as

$$\begin{aligned}
M_1[6] &\triangleq F_5 \oplus K_4 \oplus K_8, \\
M_1[7] &\triangleq F_6 \oplus K_6 \oplus K_{10}, \\
M_2[6] &\triangleq F_7 \oplus K_1 \oplus K_9, \\
M_2[7] &\triangleq F_8 \oplus K_3 \oplus K_{11}, \\
M_3[6] &\triangleq F_9 \oplus K_2 \oplus K_5, \\
M_3[7] &\triangleq F_{10} \oplus K_7.
\end{aligned}$$

Example 2 ($T = 5, \alpha = \frac{7}{11}$). We have $(l, k) \triangleq (7, 11)$. By (6), we have $(q, r) = (1, 3)$ and by (8), we have $(u, v) = (1, 4)$. We have $r + v > T$, so we are in Case 2. Moreover, $N_{\text{Keys}} = 9$, $N_{\text{Plain}} = 8$, $N_{\text{Encrypted}} = 3$, $x = 1$. After running Algorithms 1 and 3 we have

$$\begin{aligned}
M_1 &\triangleq (F_1 \| F_6 \| K_1 \| M_1[4]), \\
M_2 &\triangleq (F_2 \| F_7 \| K_2 \| K_3), \\
M_3 &\triangleq (F_3 \| F_8 \| K_4 \| K_5), \\
M_4 &\triangleq (F_4 \| K_6 \| K_7 \| M_4[4]), \\
M_5 &\triangleq (F_5 \| K_8 \| K_9 \| M_5[4]).
\end{aligned}$$

After running Algorithm 5 the encrypted parts of F are

$$\begin{aligned}
M_1[4] &\triangleq F_9 \oplus K_2 \oplus K_4 \oplus K_6 \oplus K_8, \\
M_4[4] &\triangleq F_{10} \oplus K_1 \oplus K_3 \oplus K_5 \oplus K_9,
\end{aligned}$$

$$M_5[4] \triangleq F_{11} \oplus K_7.$$

Example 3 ($T = 3, \alpha = \frac{5}{17}$). We have $(l, k) \triangleq (5, 17)$. By (6), we have $(q, r) = (2, 1)$ and by (8), we have $(u, v) = (6, 1)$. We have $r + v < T$, so we are in Case 1. Moreover, $N_{\text{Keys}} = 19$, $N_{\text{Plain}} = 7$, $N_{\text{Encrypted}} = 10$, $x = 3$. After running Algorithms 1 and 2, we have

$$\begin{aligned}
M_1 &\triangleq (F_1 \| F_2 \| F_7 \| K_1 \| K_2 \| K_3 \| K_4 \| K_5 \| K_6 \\
&\quad \| M_1[10] \| M_1[11] \| M_1[12]), \\
M_2 &\triangleq (F_3 \| F_4 \| K_7 \| K_8 \| K_9 \| K_{10} \| K_{11} \| K_{12} \\
&\quad \| M_2[9] \| M_2[10] \| M_2[11] \| M_2[12]), \\
M_3 &\triangleq (F_5 \| F_6 \| K_{13} \| K_{14} \| K_{15} \| K_{16} \| K_{17} \| K_{18} \| K_{19} \\
&\quad \| M_3[10] \| M_3[11] \| M_3[12]).
\end{aligned}$$

After running Algorithm 4, the encrypted parts of F are obtained as follows:

$$\begin{aligned}
M_1[10] &\triangleq F_8 \oplus K_7 \oplus K_{13}, \\
M_1[11] &\triangleq F_9 \oplus K_9 \oplus K_{15}, \\
M_1[12] &\triangleq F_{10} \oplus K_{11} \oplus K_{17}, \\
M_2[9] &\triangleq F_{11} \oplus K_1 \oplus K_{14}, \\
M_2[10] &\triangleq F_{12} \oplus K_3 \oplus K_{16}, \\
M_2[11] &\triangleq F_{13} \oplus K_5 \oplus K_{18}, \\
M_2[12] &\triangleq F_{14} \oplus K_{19}, \\
M_3[10] &\triangleq F_{15} \oplus K_2 \oplus K_8, \\
M_3[11] &\triangleq F_{16} \oplus K_4 \oplus K_{10}, \\
M_3[12] &\triangleq F_{17} \oplus K_6 \oplus K_{12}.
\end{aligned}$$

V. CONCLUDING REMARKS

We have studied the problem of storing a file in T servers such that the privacy leakage generated by $T - 1$ colluding servers with respect to the content of the file is bounded. The main contribution of this paper is a coding scheme for this problem that (i) achieves the asymptotically (with the file size) optimal storage space at the servers, (ii) uses the optimal amount of local randomness at the encoder, (iii) solely relies on XOR operations and is thus suited to handle large amount of data with low-complexity. Generalization of our XOR-based coding scheme to a threshold access structure, i.e., when decodability in (1) and the privacy constraint in (2) are replaced by

$$\begin{aligned}
H(F | M_{\mathcal{A}}) &= 0, \forall \mathcal{A} \subset \mathcal{T} \text{ s.t. } |\mathcal{A}| \geq t, \\
\lim_{|F| \rightarrow \infty} \frac{I(F; M_{\mathcal{U}})}{H(F)} &\leq \alpha, \forall \mathcal{U} \subset \mathcal{T} \text{ s.t. } |\mathcal{U}| \leq t - 1
\end{aligned}$$

for some $t \in \llbracket 1, T - 1 \rrbracket$, is under investigation.

APPENDIX A

PROOF OF THEOREM 1

Let $\mathcal{S} \subsetneq \mathcal{T}$. For any α -private (λ, ρ) coding scheme, we have

$$\lambda \geq H(M_t)$$

$$\begin{aligned}
&\geq I(F; M_t | M_{\mathcal{T} \setminus \{t\}}) \\
&= H(F | M_{\mathcal{T} \setminus \{t\}}) - H(F | M_{\mathcal{T}}) \\
&\stackrel{(a)}{=} H(F | M_{\mathcal{T} \setminus \{t\}}) \\
&= H(F) - I(F; M_{\mathcal{T} \setminus \{t\}}) \\
&\stackrel{(b)}{\geq} H(F) - H(F)(\alpha + o(1)) \\
&= (1 - \alpha)H(F) + o(H(F)),
\end{aligned}$$

where (a) holds by (1), (b) holds by (2).

APPENDIX B PROOF OF THEOREM 2

For any α -private (λ, ρ) coding scheme, we have

$$\begin{aligned}
\rho + H(F) &\stackrel{(a)}{=} H(R) + H(F) \\
&\stackrel{(b)}{=} H(RF) \\
&\stackrel{(c)}{\geq} H(M_{\mathcal{T}}) \\
&\stackrel{(d)}{=} \sum_{t \in \mathcal{T}} H(M_t | M_{1:t-1}) \\
&\stackrel{(e)}{\geq} \sum_{t \in \mathcal{T}} H(M_t | M_{\mathcal{T} \setminus \{t\}}) \\
&\geq \sum_{t \in \mathcal{T}} I(M_t; F | M_{\mathcal{T} \setminus \{t\}}) \\
&\stackrel{(f)}{\geq} \sum_{t \in \mathcal{T}} [(1 - \alpha)H(F) + o(H(F))] \\
&= T(1 - \alpha)H(F) + o(H(F)),
\end{aligned}$$

where (a) holds by uniformity of R , (b) holds by independence between F and R , (c) holds because $M_{\mathcal{T}}$ is a deterministic function of (R, F) , (d) holds by the chain rule, (e) holds because conditioning reduces entropy, (f) holds by the proof of Theorem 1.

APPENDIX C PROOF OF THEOREM 3

We will use the following definition in our analysis of the coding scheme of Section IV.

Definition 3. Consider an encrypted part E_t of F stored in Server $t \in \mathcal{T}$ as in Line 14 of Algorithm 4, or Line 15 of Algorithm 5. One can write E_t as $E_t = F_j \oplus \bigoplus_{t' \in \mathcal{T} \setminus \{t\}} \kappa_{t'}$, where $j \in \llbracket 1, k \rrbracket$ and for $t' \in \mathcal{T} \setminus \{t\}$, $\kappa_{t'} \in \{K_i : i \in \mathcal{I}_{t'}\} \cup \{0\}$. The encrypted part E_t is said to be protected by a key of Server $t' \in \mathcal{T}$, if there exists $i \in \mathcal{I}_{t'}$ such that $\kappa_{t'} = K_i$, i.e., if $\kappa_{t'} \neq 0$.

By construction, it is straightforward to verify that the storage size in (4) and the required amount of local randomness at the encoder in (5) are satisfied. Next, we prove decodability (1) and privacy (2).

Decodability: (1) holds because all the parts $(F_i)_{i \in \llbracket 1, k \rrbracket}$ of F are stored in $M_{\mathcal{T}}$: N_{Plain} parts are unencrypted and the

$N_{\text{Encrypted}}$ encrypted parts can be decrypted from modulo-2 addition with keys that are all stored in $M_{\mathcal{T}}$.

Privacy: It is sufficient to prove that the privacy constraint in (2) holds for all the subsets of \mathcal{T} with size $T - 1$, since $I(F; M_{\mathcal{S}'}) \leq I(F; M_{\mathcal{S}})$ if $\mathcal{S}' \subseteq \mathcal{S} \subseteq \mathcal{T}$. We will thus prove that (2) holds for the sets $\mathcal{S}_t \triangleq \mathcal{T} \setminus \{t\}$, $t \in \mathcal{T}$. We first define $K_{\mathcal{S}_t}$, $F_{\mathcal{S}_t}$, and $E_{\mathcal{S}_t}$ as all the keys, unencrypted parts of F , and encrypted parts of F , respectively, stored in the servers whose indices are in \mathcal{S}_t . We next consider two cases.

A. Case 1. $r + v < T$

Remark that

$$\begin{aligned}
&(r - 1)x + (T - v - r)(x + 1) + vx \\
&= (T - 1)x + T - v - r \\
&\stackrel{(a)}{=} (T - 1)(k - l - q - 1 - u) + T - v - r \\
&\stackrel{(b)}{=} 1 + u,
\end{aligned} \tag{10}$$

where (a) holds by (9), (b) holds by (6) and (8). We next consider three cases depending on the value of $t \in \mathcal{T}$.

- Assume $t \leq r$. We have

$$\begin{aligned}
&I(M_{\mathcal{S}_t}; F) \\
&= I(K_{\mathcal{S}_t} F_{\mathcal{S}_t} E_{\mathcal{S}_t}; F) \\
&\stackrel{(a)}{=} I(K_{\mathcal{S}_t} F_{\mathcal{S}_t} F_j (F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F) \\
&= I(K_{\mathcal{S}_t} F_{\mathcal{S}_t} F_j; F) + I((F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F | K_{\mathcal{S}_t} F_{\mathcal{S}_t} F_j) \\
&\stackrel{(b)}{=} I(F_{\mathcal{S}_t} F_j; F) + I((F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F | K_{\mathcal{S}_t} F_{\mathcal{S}_t} F_j) \\
&\stackrel{(c)}{\leq} I(F_{\mathcal{S}_t} F_j; F) + I((F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; (F_{s(i)})_{i \in \mathcal{I}_t}) \\
&\stackrel{(d)}{\leq} l(H(F) + \beta)/k + \sum_{i \in \mathcal{I}_t} I(F_{s(i)} \oplus K_i; F_{s(i)}) \\
&\stackrel{(e)}{=} \alpha(H(F) + \beta),
\end{aligned} \tag{11}$$

where (a) holds for some $j \in \llbracket N_{\text{Plain}} + 1, k \rrbracket$ and $(s(i))_{i \in \mathcal{I}_t} \in \llbracket N_{\text{Plain}} + 1, k \rrbracket^{|\mathcal{I}_t|}$ as follows. Note indeed that Server t stores $|\mathcal{I}_t| = u$ keys and all the other servers store $(r - 1)x + (T - v - r)(x + 1) + vx = u + 1$ (by (10)) encrypted parts of F , hence, considering the encrypted parts $E_{\mathcal{S}_t}$ of all the servers in \mathcal{S}_t , all but one are protected by a key of Server t by Line 14 of Algorithm 4. (b) holds because $K_{\mathcal{S}_t}$ is independent of F , (c) holds by the chain rule and because $(K_{\mathcal{S}_t}, (F_i)_{i \in \llbracket 1, k \rrbracket \setminus \{s(i) : i \in \mathcal{I}_t\}})$ is independent from $(F_{s(i)}, F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}$, (d) holds because $F_{\mathcal{S}_t}$ contains $(r - 1)(q + 1) + (T - r)q = l - 1$ (by (6)) parts of F , (e) holds by the one-time pad [17].

- Assume $r + 1 \leq t \leq T - v$. We have

$$\begin{aligned}
&I(M_{\mathcal{S}_t}; F) \\
&= I(K_{\mathcal{S}_t} F_{\mathcal{S}_t} E_{\mathcal{S}_t}; F) \\
&\stackrel{(a)}{=} I(K_{\mathcal{S}_t} F_{\mathcal{S}_t} (F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F) \\
&\stackrel{(b)}{\leq} \alpha(H(F) + \beta),
\end{aligned}$$

where (a) holds for some $(s(i))_{i \in \mathcal{I}_t} \in \llbracket N_{\text{Plain}} + 1, k \rrbracket^{|\mathcal{I}_t|}$ as follows. Note indeed that Server t stores $|\mathcal{I}_t| = u$ keys, and all the other servers store $rx + (T - v - r - 1)(x + 1) + vx = u$ (by (10)) encrypted parts of F . Hence, all the encrypted parts E_{S_t} of all the servers in \mathcal{S}_t are protected by a key of Server t by Line 14 of Algorithm 4. (b) holds similar to (11) because F_{S_t} contains $r(q + 1) + (T - r - 1)q = l$ (by (6)) parts of F .

- Assume $t \geq T - v + 1$. The proof of (11) is identical to Subcase ii by remarking that (i) Server t stores $|\mathcal{I}_t| = u + 1$ keys, and all the other servers store $rx + (T - v - r)(x + 1) + (v - 1)x = u + 1$ (by (10)) encrypted parts of F , and (ii) F_{S_t} contains $r(q + 1) + (T - r - 1)q = l$ (by (6)) parts of F .

B. Case 2. $r + v \geq T$

Remark that

$$\begin{aligned} & (T - v - 1)x + (r - T + v)(x - 1) + (T - r)x \\ &= (r - 1)x + (T - v - r)(x + 1) + vx \\ &= 1 + u, \end{aligned} \quad (12)$$

where the last equality holds by (10). We next consider three cases depending on the value of $t \in \mathcal{T}$.

- Assume $t \leq T - v$. We have

$$\begin{aligned} & I(M_{S_t}; F) \\ &= I(K_{S_t} F_{S_t} E_{S_t}; F) \\ &\stackrel{(a)}{=} I(K_{S_t} F_{S_t} F_j(F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F) \\ &\stackrel{(b)}{\leq} \alpha(H(F) + \beta), \end{aligned} \quad (13)$$

where (a) holds for some $j \in \llbracket N_{\text{Plain}} + 1, k \rrbracket$ and $(s(i))_{i \in \mathcal{I}_t} \in \llbracket N_{\text{Plain}} + 1, k \rrbracket^{|\mathcal{I}_t|}$ as follows. Note indeed that Server t stores $|\mathcal{I}_t| = u$ keys and all the other servers store $(T - v - 1)x + (r - T + v)(x - 1) + (T - r)x = u + 1$ (by (12)) encrypted parts of F , hence, considering the encrypted parts E_{S_t} of all the servers in \mathcal{S}_t , all *but one* are protected by a key of Server t by Line 15 of Algorithm 5. (b) holds similar to (11) because F_{S_t} contains $(r - 1)(q + 1) + (T - r)q = l - 1$ (by (6)) parts of F .

- Assume $r < t \leq T - v$. We have

$$\begin{aligned} & I(M_{S_t}; F) \\ &= I(K_{S_t} F_{S_t} E_{S_t}; F) \\ &\stackrel{(a)}{=} I(K_{S_t} F_{S_t} F_j(F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F) \\ &\stackrel{(b)}{\leq} \alpha(H(F) + \beta), \end{aligned}$$

where (a) holds for some $j \in \llbracket N_{\text{Plain}} + 1, k \rrbracket$ and $(s(i))_{i \in \mathcal{I}_t} \in \llbracket N_{\text{Plain}} + 1, k \rrbracket^{|\mathcal{I}_t|}$ as follows. Note indeed that Server t stores $|\mathcal{I}_t| = u + 1$ keys, and all the other servers store $(T - v)x + (r - T + v - 1)(x - 1) + (T - r)x = u + 2$ (by (12)) encrypted parts of F , hence, considering the encrypted parts E_{S_t} of all the servers in \mathcal{S}_t , all

but one are protected by a key of Server t by Line 15 of Algorithm 5. (b) holds similar to (11) because F_{S_t} contains $(r - 1)(q + 1) + (T - r)q = l - 1$ (by (6)) parts of F .

- Assume $t \geq T - v + 1$. We have

$$\begin{aligned} & I(M_{S_t}; F) \\ &= I(K_{S_t} F_{S_t} E_{S_t}; F) \\ &\stackrel{(a)}{=} I(K_{S_t} F_{S_t} (F_{s(i)} \oplus K_i)_{i \in \mathcal{I}_t}; F) \\ &\stackrel{(b)}{\leq} \alpha(H(F) + \beta), \end{aligned}$$

where (a) holds for some $(s(i))_{i \in \mathcal{I}_t} \in \llbracket N_{\text{Plain}} + 1, k \rrbracket^{|\mathcal{I}_t|}$ as follows. Note indeed that Server t stores $|\mathcal{I}_t| = u + 1$ keys, and all the other servers store $(T - v)x + (r - T + v)(x - 1) + (T - r - 1)x = 1 + u$ (by (12)) encrypted parts of F . Hence, all the encrypted parts E_{S_t} of all the servers in \mathcal{S}_t are protected by a key of Server t by Line 15 of Algorithm 5. (b) holds similar to (11) because F_{S_t} contains $r(q + 1) + (T - r - 1)q = l$ (by (6)) parts of F .

REFERENCES

- [1] J. A. Garay, R. Gennaro, C. Jutla, and T. Rabin, "Secure distributed storage and retrieval," *Theoretical Computer Science*, vol. 243, no. 1-2, pp. 363–389, 2000.
- [2] A. S. Rawat, O. O. Koyluoglu, and S. Vishwanath, "Centralized repair of multiple node failures with applications to communication efficient secret sharing," *IEEE Transactions on Information Theory*, vol. 64, no. 12, pp. 7529–7550, 2018.
- [3] R. Bitar and S. El Rouayheb, "Staircase codes for secret sharing with optimal communication and read overheads," *IEEE Transactions on Information Theory*, vol. 64, no. 2, pp. 933–943, 2018.
- [4] Q. Yu, S. Li, N. Raviv, S. M. M. Kalan, M. Soltanolkotabi, and S. Avestimehr, "Lagrange coded computing: Optimal design for resiliency, security and privacy," *arXiv preprint arXiv:1806.00939*, 2018.
- [5] W. Huang, M. Langberg, J. Klierer, and J. Bruck, "Communication efficient secret sharing," *IEEE Transactions on Information Theory*, vol. 62, no. 12, pp. 7195–7206, 2016.
- [6] A. Shamir, "How to share a secret," *Communications of the ACM*, vol. 22, no. 11, pp. 612–613, 1979.
- [7] G. R. Blakley, "Safeguarding cryptographic keys," in *Proceedings of the national computer conference*, vol. 48, 1979, pp. 313–317.
- [8] A. Beimel, "Secret-sharing schemes: A survey," in *International Conference on Coding and Cryptology*. Springer, 2011, pp. 11–46.
- [9] O. Farràs, "Recent advances in non-perfect secret sharing schemes," in *Conference on Computability in Europe*. Springer, 2016, pp. 89–98.
- [10] M. Yoshida, T. Fujiwara, and M. P. Fossorier, "Optimal uniform secret sharing," *IEEE Transactions on Information Theory*, vol. 65, no. 1, pp. 436–443, 2018.
- [11] H. Yamamoto, "Secret sharing system using (k, l, n) threshold scheme," *Electronics and Communications in Japan (Part I: Communications)*, vol. 69, no. 9, pp. 46–54, 1986.
- [12] M. Yoshida and T. Fujiwara, "Secure construction for nonlinear function threshold ramp secret sharing," in *Proc. of IEEE Int. Symp. Inf. Theory*, 2007, pp. 1041–1045.
- [13] G. R. Blakley and C. Meadows, "Security of ramp schemes," in *Workshop on the Theory and Application of Cryptographic Techniques*. Springer, 1984, pp. 242–268.
- [14] Y. Wang and Y. Desmedt, "Efficient secret sharing schemes achieving optimal information rate," in *IEEE Information Theory Workshop*, 2014, pp. 516–520.
- [15] W. Huang and J. Bruck, "Secure raid schemes for distributed storage," in *Proc. of IEEE Int. Symp. Inf. Theory*, 2016, pp. 1401–1405.
- [16] —, "Secure raid schemes from EVENODD and STAR codes," in *Proc. of IEEE Int. Symp. Inf. Theory*, 2017, pp. 609–613.
- [17] D. R. Stinson, *Cryptography: Theory and practice*. Chapman and Hall/CRC, 2005.