Business Process Full Compliance with Respect to a Set of Conditional Obligation in Polynomial Time

Silvano Colombo Tosatto, Guido Governatori, and Nick Van Beest

Data61, CSIRO, Dutton Park, Australia {silvano.colombotosatto;guido.governatori;nick.vanbeest}@data61.csiro.au

Abstract. In this paper, we present a new methodology to evaluate whether a business process model is fully compliant with a regulatory framework composed of a set of conditional obligations. The methodology is based failure Δ -constraints that are evaluated on bottom-up aggregations of a tree-like representation of business process models. While the generic problem of proving full compliance is in coNP-complete, we show that verifying full compliance can be done in polynomial time using our methodology, for an acyclic structured process model given a regulatory framework composed by a set of conditional obligations, whose elements are restricted to be represented by propositional literals.

Keywords: Regulatory Compliance, Business Process Models, Computational Complexity

1 Introduction

Business process models are often used by companies and organisations to compactly represent how their business goals and objectives are achieved. It is, therefore, vital for the stakeholders to show that such business process models comply with the relevant regulations in place.

Various approaches have been proposed in the past, proving whether business process model are compliant with a regulatory framework [11,6,9,7]. However, as shown by Colombo Tosatto et al. [3], the generic problem of proving regulatory compliance is complex enough to be in **NP**-complete. Colombo Tosatto et al. [4] also show that when considering the problem of proving *partial compliance* of business process models (i.e. checking whether the model contains at least one compliant execution), the majority of the variants of the problem are indeed in **NP**-complete.

In this paper, we consider the problem of proving *full compliance* of a business process, to ensure that every execution of the model is compliant with the given regulatory framework. While the generic problem of proving full compliance is in coNP-complete [3], we show that verifying full compliance can be done in polynomial time for an acyclic structured process model given a regulatory framework composed by a set of conditional obligations, whose elements are restricted to be represented by propositional literals.

The proposed approach is based on verifying an alternative representation of the constraints defined by the regulatory frameworks, referred to as failure Δ -constraints by Colombo Tosatto et al. [5]. These constraints are evaluated on a tree-like structure representing the business process model, adopting a *divide* & *conquer* strategy by independently evaluating the leaves and cumulatively aggregating the results towards the root of the process tree.

The remainder of the paper is structured as follows: Section 2 introduces the studied variant of the compliance problem. Section 3 introduces the failure Δ -constraints. Subsequently, the basic principles of the evaluation procedure is described in Section 4. Next, the aggregation of the results towards the root of the process tree is presented in Section 5, followed by a conclusion of the work in Section 6.

2 Proving Regulatory Compliance

In this preliminary section, we introduce the problem of proving regulatory compliance of business process models. As the goal of this paper is to provide a solution, which is in polynomial time with respect to the size of the problem, we focus on a simplified variant rather than the general problem. Similar to every regulatory compliance problem, this variant is composed by two distinct components, which we introduce separately. First, we introduce the business process model, describing the possible executions capable of achieving an objective. Second, we introduce the regulatory framework, describing the compliance requirements that the executions of a process model must follow.

2.1 Acyclic Structured Business Processes

We focus our approach on solving a variant of the problem involving acyclic structured process models. We limit our approach to structured process models, as the soundness¹ of such models can be verified in polynomial time with respect to their size. These processes are similar to structured workflows defined by Kiepuszewski et al. [10]. An additional advantage of limiting ourselves to deal with these kind of process models is that their structure is composed by properly nested components², can be exploited to navigate the structure using an alternative *tree-like* representation.

Finally, the advantage of considering acyclic process models, is that the number of possible executions of a model is always finite. When considering process models including cycles, on the other hand, unless an upper limit of iteration is enforced on a cycle, a cycle can be run any number of times and to each number of possible iterations corresponds a potential execution of the model. While an infinite execution does not make sense, as to be considered a possible execution of the model, it must be allowed to terminate. It is still easy to see how such cycles can lead to models containing an infinite amount of executions. In this paper, we focus on models foregoing such structures.

Definition 1 (**Process Block**). A process block *B* is a directed graph: the nodes are called elements and the directed edges are called arcs. The set of elements of a process block are identified by the function V(B) and the set of arcs by the function E(B). The set of elements is composed of tasks and coordinators. There are 4 types of coordinators: and_split, and_join, xor_split and xor_join. Each process block *B* has two distinguished nodes called the initial and final element. The initial element has no incoming arc from other elements in *B* and is denoted by b(B). Similarly the final element has no outgoing arcs to other elements in *B* and is denoted by f(B).

A directed graph composing a process block is defined inductively as follows:

¹ A process is sound, as defined by van der Aalst [1,12], if it avoids livelocks and deadlocks.

² Considering a structured process model as a set of nested components, by properly nested we mean that every component, except the outer process model itself, always has exactly one parent compoent.

- A single task constitutes a process block. The task is both initial and final element of the block.
- Let B_1, \ldots, B_n be distinct process blocks with n > 1:
 - SEQ (B_1, \ldots, B_n) denotes the process block with node set $\bigcup_{i=0}^n V(B_i)$ and edge set $\bigcup_{i=0}^{n} (E(B_i) \cup \{ (f(B_i), b(B_{i+1})) : 1 \le i < n \}).$
 - The initial element of $SEQ(B_1,...,B_n)$ is $b(B_1)$ and its final element is $f(B_n)$. • XOR (B_1,\ldots,B_n) denotes the block with vertex set $\bigcup_{i=0}^n V(B_i) \cup \{\text{xsplit},\text{xjoin}\}$
 - and edge set $\bigcup_{i=0}^{n} (E(B_i) \cup \{(xsplit, b(B_i)), (f(B_i), xjoin) : 1 \le i \le n\})$ where xsplit and xjoin respectively denote an xor_split coordinator and an xor_join *coordinator, respectively. The initial element of* $XOR(B_1, \ldots, B_n)$ *is* xsplit *and* its final element is xjoin.
 - AND (B_1,\ldots,B_n) denotes the block with vertex set $\bigcup_{i=0}^n V(B_i) \cup \{\text{asplit},\text{ajoin}\}$ and edge set $\bigcup_{i=0}^{n} (E(B_i) \cup \{(asplit, b(B_i)), (f(B_i), ajoin) : 1 \le i \le n\})$ where asplit and ajoin denote an and_split and an and_join coordinator, respectively. The initial element of $AND(B_1, \ldots, B_n)$ is asplit and its final element is ajoin.

By enclosing a process block as defined in Definition 1 along with a start and end task in a sequence block, we obtain a structured process model. The effects of executing the tasks contained in a business process model are described using annotations as shown in Definition 2.

Definition 2 (Annotated process). Let P be a structured process and let T be the set of tasks contained in P. An annotated process is a pair (P. ann), where ann is a function associating a consistent set of literals to each task in T: ann : $T \mapsto 2^{\mathscr{L}}$. The function ann is constrained to the consistent literals sets in $2^{\mathscr{L}}$.

The update between the states of a process during its execution is inspired by the AGM belief revision operator [2] and is used in the context of business processes to define the transitions between states, which in turn are used to define the traces.

Definition 3 (State update). Given two consistent sets of literals L_1 and L_2 , representing the process state and the annotation of a task being executed, the update of L_1 with L_2 , denoted by $L_1 \oplus L_2$ is a set of literals defined as follows:

$$L_1 \oplus L_2 = L_1 \setminus \{\overline{l} \mid l \in L_2\} \cup L_2$$

Definition 4 (Executions and Traces). Let $\mathbb{P}_1 = (\mathscr{S}_1, \prec_{s_1})$ and $\mathbb{P}_2 = (\mathscr{S}_2, \prec_{s_2})$ be partial ordered sets, we define the following four operations:

- Union: $\mathbb{P}_1 \cup_{\mathbb{P}} \mathbb{P}_2 = (\mathscr{S}_1 \cup \mathscr{S}_2, \prec_{s_1} \cup \prec_{s_2})$, where \cup is the disjoint union. Intersection: $\mathbb{P}_1 \cap_{\mathbb{P}} \mathbb{P}_2 = (\mathscr{S}_1 \cap \mathscr{S}_2, \prec_{s_1} \cap \prec_{s_2})$ Concatenation: $\mathbb{P}_1 +_{\mathbb{P}} \mathbb{P}_2 = (\mathscr{S}_1 \cup \mathscr{S}_2, \prec_{s_1} \cup \prec_{s_2} \cup \{s_1 \prec s_2 | s_1 \in \mathscr{S}_1 \text{ and } s_2 \in \mathscr{S}_2\})$. Linear Extensions: $\mathscr{E}(\mathbb{P}_1) = \{(\mathscr{S}, \prec_s) | \mathscr{S} = \mathscr{S}_1, (\mathscr{S}, \prec_s) \text{ is a sequence and } \prec_{s_1} \subseteq \mathscr{S}_1 \in \mathscr{S}_2\}$ \prec_s .

The associative property holds for Union, Intersection and Concatenation.

Given a structured process model identified by a process block B, the set of its executions, written $\Sigma(B) = \{ \varepsilon | \varepsilon \text{ is a sequence and is an execution of } B \}$. The function $\Sigma(B)$ is defined as follows:

- 1. If B is a task t, then $\Sigma(B) = \{(\{t\}, \emptyset)\}$
- 2. if B is a composite block with subblocks B_1, \ldots, B_n let ε_i be the projection of ε on block B_i (obtained by ignoring all tasks which do not belong to B_i)

(a) If $B = SEQ(B_1, ..., B_n)$, then $\Sigma(B) = \{\varepsilon_1 + \mathbb{P} \cdots + \mathbb{P} \varepsilon_n | \varepsilon_i \in \Sigma(B_i)\}$ (b) If $B = XOR(B_1, ..., B_n)$, then $\Sigma(B) = \Sigma(B_1) \cup \cdots \cup \Sigma(B_n)$ (c) If $B = AND(B_1, ..., B_n)$, then $\bigcup_{\varepsilon_1, ..., \varepsilon_n} \mathscr{E}(\varepsilon_1 \cup \mathbb{P} \cdots \cup \mathbb{P} \varepsilon_n | \forall \varepsilon_i \in \Sigma(B_i))$

Given an annotated process (B, ann) and an execution $\varepsilon = (t_1, \ldots, t_n)$ such that $\varepsilon \in \Sigma(B)$. A trace θ is a finite sequence of states: $(\sigma_1, \ldots, \sigma_n)$. Each state of $\sigma_i \in \theta$ contains a set of literals L_i capturing what holds after the execution of a task t_i . Each L_i is a set of literals such that:

1. $L_0 = \emptyset$ 2. $L_{i+1} = L_i \oplus \operatorname{ann}(t_{i+1})$, for $1 \le i < n$.

To denote the set of possible traces resulting from an process model (B,ann), we use $\Theta(B,ann)$.

Example 1. Annotated Process Model. Fig. 1 shows a structured process containing four tasks labelled t_1, t_2, t_3 and t_4 and their annotations. The process contains an AND block followed by a task and an XOR block nested within the AND block. The annotations indicate what has to hold after a task is executed. If t_1 is executed, then the literal *a* has to hold in that state of the process.



Fig. 1: An annotated process

$\Sigma(B)$	$oldsymbol{\Theta}(B, ext{ann})$
$(start, t_1, t_3, t_4, end)$	$((start, \emptyset), (t_1, \{a\}), (t_3, \{a, c, d\}), (t_4, \{\neg a, c, d\}), (end, \{\neg a, c, d\}))$
$(start, t_2, t_3, t_4 end)$	$((start, \emptyset), (t_2, \{b, c\}), (t_3, \{b, c, d\}), (t_4, \{\neg a, b, c, d\}), (end, \{\neg a, b, c, d\}))$
$(start, t_3, t_1, t_4 end)$	$((start, \emptyset), (t_3, \{c, d\}), (t_1, \{a, c, d\}), (t_4, \{\neg a, c, d\}), (end, \{\neg a, c, d\}))$
$(start, t_3, t_2, t_4 end)$	$((start, \emptyset), (t_3, \{c, d\}), (t_2, \{b, c, d\}), (t_4, \{\neg a, b, c, d\}), (end, \{\neg a, b, c, d\}))$

Table 1: Executions and Traces of the annotated process in Fig. 1.

2.2 Regulatory Framework

We now introduce now the regulatory framework, the requirements that a business process model needs to follow to be considered compliant. We aim to solve a variant of the problem, hence we introduce in this section conditional obligations. Considering that a regulatory framework is composed by a set of them, then an execution is required to comply with every obligation belonging to the set. One of the limitations we are applying to the regulatory framework is that the components defining the obligations are limited to propositional literals. We use a subset of Process Compliance Logic, introduced by Governatori and Rotolo [8], to describe the conditional obligations composing the regulatory framework.

Definition 5 (Conditional Obligation). A local obligation \odot is a tuple $\langle o, r, t, d \rangle$, where $o \in \{a, m\}$ and represents the type of the obligation. The elements c, t and d are propositional literals in \mathcal{L} . r is the requirement of the obligation, t is the trigger of the obligation and d is the deadline of the obligation.

We use the notation $\odot = \mathcal{O}^o(r, t, d)$ to represent a conditional obligation.

Recalling one of the limitations of the variant of the problem being solved in this paper, the elements of a conditional obligation are limited to be represented by propositional literals. Thus, the *requirement*, *trigger*, and *deadline* of a conditional obligation are represented using propositional literals. These elements are evaluated against the states of a trace, as illustrated for instance in Table 1, as the elements are propositional literals, they are considered to be positively satisfied if they are contained in a state.

Given a trace of a business process model and a conditional obligation, if a state of the trace satisfies the the obligation's triggering element, then the obligation is set in force. Additionally, when an obligation is in force over a trace, and the deadline element is satisfied by a state of a trace, then conditional obligation ceases to be in force. Figure 2 graphically illustrates the in force interval of a conditional obligation over a trace of a business process model.



Fig. 2: Obligation in force

Notice that when a conditional obligation is in force, then the requirement element of the obligation is evaluated within the in force interval to determine whether the obligation is satisfied or violated in that particular in force interval. How the requirement element is evaluated depends on the type of the obligation. We consider two types of obligations, *achievement* and *maintenance*:

- Achievement When this type of obligation is in force, the requirement specified by the regulation must be satisfied by at least one state within the in force interval, in other words, before the deadline is satisfied. When this is the case, the obligation in force is considered to be satisfied, otherwise it is violated.
- **Maintenance** When this type of obligation is in force, the requirement must be satisfied *continuously* in every state of the in force interval, until the deadline is satisfied. Again, if this is the case, the obligation in force is then satisfied, otherwise it is violated.

Before proceeding with the formal introduction of the different types of obligations, we introduce two syntactical shorthands to keep the subsequent definitions more compact.

Definition 6 (Syntax Shorthands). *To avoid cluttering, we adopt the following shorthands:*

- $\sigma \in \theta$ such that $\sigma \models l$ is abbreviated as: σ_l
- A task-state pair appearing in a trace: (t, σ) such that $l \in ann(t)$, is abbreviated as: $contain(l, \sigma)$

Notice that an *in force* interval instance of an obligation, having l as its trigger, is always started from a state σ , where contain (l, σ) is true. Therefore, potentially

multiple in force intervals of an obligation can co-exist at the same time. However, multiple in force intervals can be fulfilled by a single event happening in a trace, as shown in the following definitions.

An achievement obligation is fulfilled by a trace if the requirement holds at least in one of the trace states when the obligation is in force.

Definition 7 (Comply with Achievement). *Given an achievement obligation* $\mathcal{O}^a \langle r, t, d \rangle$ *and a trace* θ , θ *is compliant with* $\mathcal{O}^a \langle r, t, d \rangle$ *if and only if:* $\forall \sigma_t, \exists \sigma_r | \text{contain}(t, \sigma_t)$ *and* $\sigma_t \preceq \sigma_r$ *and* $\neg \exists \sigma_d | \sigma_t \preceq \sigma_d \prec \sigma_r$.

A trace not complying with an achievement obligations is considered to violate it.

A maintenance obligation, on the other hand, is fulfilled if the requirement holds in each of the states where the obligation is in force.

Definition 8 (Comply with Maintenance). Given a maintenance obligation $\mathcal{O}^m \langle r, t, d \rangle$ and a trace θ , θ is compliant with $\mathcal{O}^m \langle r, t, d \rangle$ if and only if: $\forall \sigma_t, \exists \sigma_d | \text{contain}(t, \sigma_t)$ and $\sigma_t \preceq \sigma_d$ and $\forall \sigma | \sigma_t \preceq \sigma \preceq \sigma_d, r \in \sigma$.

A trace not complying with a maintenance obligations is considered to violate it.

Notice that according to Definition 7 and Definition 8, an obligation can be still in force when the end of a trace is reached, in other words, none of the tasks before and including the last one in a trace contained the *deadline condition* of the obligation being evaluated. While this can be a viable scenario in the real world, in this paper we are interested on verifying whether a trace is compliant with an obligation, hence we force the semantics of the tasks belonging to a trace to always allow that. More precisely, we assume that the last task of a trace always satisfies the *deadline* of an obligation in force, in this way we can always decide at the end of a trace whether an obligation is fulfilled or violated. Finally, notice that according to how we defined *structured process models*, the last task in a trace is always the *end task*.

Assumption 1 (Final Deadline) Given a structured process model (*P*, ann) and an obligation \mathcal{O}^o $\langle r, t, d \rangle$. For every $\theta \in \Theta(P, \operatorname{ann})$:

- *if e is the last task in* θ *, then d* \in ann(*e*).

Process Compliance Considering a trace to be compliant with a regulatory framework, if it complies with every obligation belonging to the set composing the framework. A business process model can be compliant with a regulatory framework to various degrees, depending on how many of the traces of the model comply with the regulatory framework. A process model is said to be fully compliant if every trace of the process is compliant with the regulatory framework. A process model is compliant with the regulatory framework, and not compliant if there exists at least one trace compliant with the regulatory framework, and not compliant if there is no trace complying with the framework.

Definition 9 (Process Compliance). Given a process (P, ann) and a regulatory framework composed by a set of obligations \odot , the compliance of (P, ann) with respect to \odot is determined as follows:

- *Full compliance* $(P, \operatorname{ann}) \vdash^{\mathbb{F}} \odot$ *if and only if* $\forall \theta \in \Theta[(P, \operatorname{ann})], \theta \vdash \odot$. - *Partial compliance* $(P, \operatorname{ann}) \vdash^{\mathbb{P}} \odot$ *if and only if* $\exists \theta \in \Theta[(P, \operatorname{ann})], \theta \vdash \odot$. - *Not compliant* (*P*,ann) $\forall \odot$ *if and only if* $\neg \exists \theta \in \Theta[(P, \operatorname{ann})], \theta \vdash \odot$.

Notice that in this paper we focus on verifying whether a given business process model is *fully* compliant with a regulatory framework. In particular, the approach relies on verifying whether the complementary condition of full compliance is true: in other words, whether a business process model contains a trace not compliant with the regulatory framework. This is equivalent to finding a trace in the process model violating at least an obligation composing the regulatory framework.

3 Failure Δ -constraints

As full compliance of a business process model can be verified by checking whether it contains a trace violating at least one of the obligations composing the regulatory framework, we formally introduce the definitions for violating the different types of obligations. For each of the two types of obligations, achievement and maintenance, we define a set of *Failure \Delta-constraints*, an alternative representation of the requirements required to be satisfied by a trace to violate a given obligation. These sets of constraints are the ones going to be verified by the approach proposed in the paper.

Before introducing the *Failure* Δ -constraints we need to consider an assumption, as such constraints are verifying the complement of the fulfilment condition of the obligation being checked. In order for the complementary condition of an obligation to be correctly verified, it is necessary that the complement of the requirement condition belongs to the state in order to satisfy the *Failure* Δ -constraints. As it is not always the case that the complementary condition is introduced by the tasks executed in a trace, we assume that the initial task contain the complementary required condition. While we are aware that introducing a syntactical representation for missing literals in a state would have provided the same result, we opted for this solution as it does not introduce additional notation.

Assumption 2 (Complementary Start) Given a structured process model (P, ann) and an obligation \mathcal{O}^o $\langle r, t, d \rangle$. For every $\theta \in \Theta(P, \operatorname{ann})$:

- *if s is the first task in* θ *, then* $\{\neg r\} \in ann(s)$ *.*

3.1 Achievement

We describe in the following, Definition 10, the complement of Definition 7, the failure condition for an achievement conditional obligation.

Definition 10 (Achievement Failure). *Given an achievement obligation* $\mathcal{O}^a\langle r, t, d \rangle$ *and a trace* θ , θ *is not compliant with* $\mathcal{O}^a\langle r, t, d \rangle$ *if and only if:* $\exists \sigma_t, \sigma_d | \text{contain}(t, \sigma_t)$ *and* $\sigma_t \leq \sigma_d$ and $\neg \exists \sigma_r | \sigma_t \leq \sigma_r \leq \sigma_d$.

In the following definition we translate the requirements described in Definition 10 into its Failure Δ -constraints representation.

Definition 11 (Achievement Failure Δ -constraints).

Given a conditional achievement obligation $\mathcal{O}^a\langle r,t,d\rangle$ and an execution \mathcal{E} , \mathcal{E} is compliant with $\mathcal{O}^a\langle r,t,d\rangle$, if and only if one of the following conditions is satisfied:

 $\overline{A}\Delta 1 \exists t_t \text{ such that:} \\ \exists t_{\neg r}, t_d | t_{\neg r} \leq t_t \leq t_d \text{ and} \\ \neg \exists t_r | t_{\neg r} \leq t_r \leq t_d \text{ and} \\ \exists t_{\neg d}, \neg \exists t_d | t_{\neg d} \leq t_d \leq t_t \end{cases}$

 $\overline{A}\Delta 2 \exists t_t \text{ such that:} \\ \exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \leq t_r \leq t_t \text{ and} \\ \exists t_d, \neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_t \end{cases}$



Fig. 3: Achievement constraints

Figure 3 illustrates a graphical representation of the Failure Δ -constraints for achievement obligations. The nodes represent annotations in the tasks and the arrows represent the ordering relations between the tasks that must be fulfilled by an execution of the process model to fulfil the Failure Δ -constraint. A slashed arrow denotes the required absence of the respective element in the interval identified by the surrounding elements.

Theorem 1. Given an execution ε , represented as a sequence of tasks, if ε satisfies either of the Achievement Failure Δ -Constraints (Definition 11), then ε satisfies the obligation related to the Achievement Failure Δ -Constraints.

3.2 Maintenance

The translation to Failure Δ -constraints is also applied to local maintenance obligations, in a similar was as for local achievement obligations.

Again, we first introduce the complement of local maintenance obligation fulfilment, Definition 8, in Definition 12.

Definition 12 (Maintenance Failure). Given a conditional maintenance obligation $\mathcal{O}^m\langle r,t,d\rangle$ and a trace θ , θ is not compliant with $\mathcal{O}^m\langle r,t,d\rangle$ if and only if:

 $\exists \sigma_t \forall \sigma_d | \text{contain}(t, \sigma_t) \text{ and } \sigma_t \preceq \sigma_d \text{ and } \exists \sigma_{\neg r} | \sigma_t \preceq \sigma_{\neg r} \preceq \sigma_d$

Definition 13 illustrates how the conditions of Definition 12 can be represented as a set of Failure Δ -constraints.

Definition 13 (Maintenance Failure Δ **-constraints).** *Given a maintenance obligation* $\mathcal{O}^m\langle r,t,d\rangle$ and an execution ε , ε is not compliant with $\mathcal{O}^m\langle r,t,d\rangle$ if and only if one of the following conditions is satisfied:

 $\overline{M}\Delta 1 \exists t_t \text{ such that:} \\ \exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \preceq t_r \preceq t_t$

 $\overline{M}\Delta 2 \exists t_t \text{ such that:} \\ \exists t_r, \neg \exists t_{\neg r} | t_r \leq t_{\neg r} \leq t_t \text{ and} \\ \forall t_d (\exists t_{\neg r} | t_t \leq t_{\neg r} \prec t_d)$



Fig. 4: Maintenance constraints

Theorem 2. Given an execution ε , represented as a sequence of tasks, if ε satisfies either of the Maintenance Failure Δ -constraints (Definition 13), then ε violates the obligation related to the Maintenance Failure Δ -constraints.

Translation Complexity Translating a given conditional obligation in the corresponding set of failure Δ -constraints can be done in constant time, since depending on the type of obligations, the associated failure Δ -constraints just need to be instantiated with the parameters of the respective obligation.

4 Approach: Stem Evaluation

In this section, we introduce the approach verifying whether a business process model is fully compliant with a regulatory framework. The proposed approach evaluates the *tree-like* representation according to the failure Δ -constraints associated to each obligation of the framework.

4.1 Process Tree Model

We refer to the tree-like representation of a structured business process model as the *Process Tree Model*, and it is defined as follows.

Definition 14 (**Process Tree Model**). *Let P be a structured process model. A* Process Tree *PT is an abstract hierarchical representation of P, where:*

- Each process block B in P corresponds to a node N in PT.
- Given a process block $B(B_1,...,B_n)$, where $B_1,...,B_n$ are the process blocks directly nested in B, the nodes $N_1,...,N_n$ in PT, corresponding to $B_1,...,B_n$ in P, are children of N, corresponding to B in P. Mind that the order between the sub-blocks of a process block is preserved between the children of the same node.

In accordance to Definition 14, the *main block* of a structured process model always represents the root of its corresponding *process tree* model, as it is not contained as a sub-process block in any other process blocks. Similarly, as the tasks in a process model are also process blocks, they also represent nodes in the tree. However, since a block



Fig. 5: Process Tree Example

representing a task does not have any sub-process block, such type of process block always corresponds to the leaves of a process tree. Figure 5 illustrates the process tree model of the structured process model used in Example 1.

Notice that a process block can only be the sub-block of a single other processblock, hence Definition 14 is sufficient, as the process blocks nesting ensures that a process tree is a proper tree. Moreover, notice that, as the only process blocks that do not contain nested blocks are tasks, then each leaf in a process tree corresponds to one of the tasks³ of the original business process model.

Intuitively, the tasks having the same parent in a process tree representation are related by an ordering relationship, or by a mutual exclusion relationship, depending on the sub-process block type associated to the parent node. By navigating the structure bottom-up, it is possible to recursively infer the relations between the tasks, and we exploit this in our approach evaluating the compliance state of a process model.

Process Tree Stem The proposed approach uses the sufficient conditions, described in Definition 11 and Definition 13, expressed as failure Δ -constraints, to identify whether a process model contains an execution violating an obligation being evaluated. By checking whether a business process model contains an execution violating one or more obligations, it is possible to verify whether such model is fully compliant with a regulatory framework.

Recalling some details from Definition 11 and Definition 13, every sufficient condition is in relation to the existence of a *trigger task*, a task having annotated the trigger of the conditional obligation being evaluated. With this in mind, given a *process tree model* and a *trigger task*, we refer to the path between the root and the *trigger task* as the *Stem*, as illustrated in Figure 6.

Given a process tree and a conditional obligation, notice that the tree can contain multiple trigger tasks, hence its tree representation can contain multiple stems. The proposed approach investigates each stem in a process tree model independently.

Additionally, the nodes in a process tree can be considered to represent sets of subexecutions of the related business process model⁴, and that these partial executions involve the tasks belonging to the sub-tree of the node. Moreover, the nodes on the

³ A minor exception to this, is that the start and end elements of the process models are also represented as leaves in the process tree. Despite these two elements not being proper tasks, they can be treated as such for the sake of the evaluation procedure.

⁴ As each node in a process tree is associated to a process block, even simple tasks, every execution obtainable by applying Definition 4 to the process block is always a sub execution of a possible execution of the associated business process model.



Fig. 6: Process Tree and Stem

Stem represent sub-executions involving the *trigger task*, which we can use to verify the conditions expressed in the failure Δ -constraints. Finally, verifying a failure Δ -constraint condition in a set of partial executions of a model corresponds to verifying it in the set of executions of the model itself, as it is stated by Lemma 2.

4.2 Stem Evaluation Procedure

The inputs of the *Stem Evaluation* procedure are a business process model *P* and a Δ -constraint δ . The procedure is detailed in the pseudo-code shown in Algorithm 1.

```
input : A business process model: P, and a failure \Delta-constraint: \delta
   output: Whether P satisfies \delta
1 Let \mathscr{T} be the set of tasks in P containing t of \delta in their annotation;
<sup>2</sup> Let \mathscr{P} be the tree representation of P;
3 for \tau \in \mathscr{T} do
         if !checkLeafFail(\tau, \delta) then
4
              Let the path between the root in \mathscr{P} to \tau be the stem;
              Let \mathscr{P}' be the tree where each XOR node on the stem is replaced with its child on the
6
                 stem;
              if Evaluate(\mathscr{P}', \tau, \delta) then
7
                    return true:
8
              end
        end
   end
9 return false;
```

Algorithm 1: Stem Evaluation

Algorithm 1 identifies the *trigger leaves* (\mathscr{T}) of the tree representation of the business process in line 1. Notice that in line 4 checkLeafFail(τ , δ) verifies whether the trigger leaf contains certain annotations that would immediately falsify the Δ -constraint being evaluated. checkLeafFail is defined as follows depending on the value of δ :

 $\overline{A}\Delta 1$ if $c \in \operatorname{ann}(\tau)$ then return true, false otherwise $\overline{A}\Delta 2$ if $c \in \operatorname{ann}(\tau)$ then return true, false otherwise $\overline{M}\Delta 1$ if $c \in \operatorname{ann}(\tau)$ then return true, false otherwise $\overline{M}\Delta 2$ if $d \in \operatorname{ann}(\tau)$ then return true, false otherwise

For each of the trigger leaves, the procedure prunes the tree in line 5, removing each XOR branch on the stem that would not lead to the considered trigger leaf, this is graphically illustrated in Figure 7. Intuitively, as the tree is a representation of a business process model, the pruning procedure XOR branches on the stem, removes



Fig. 7: Stem Pruning

from the pool of the possible executions all the execution not containing the trigger leaf (τ) .

As shown later in this section, the Evaluation procedure verifies whether a tree representation of a model satisfies a failure Δ -constraint given a specific task having the trigger of the constraint annotated, the trigger leaf τ . Thus, Lemma 3 formally states that the pruning procedure removes exactly every execution in the process not containing τ .

Theorem 3 (Algorithm 1 Correctness). Given a business process model P and a failure Δ -constrain δ , if there exists an execution of P such that the execution satisfies δ , then Algorithm 1 returns true, otherwise it returns false.

4.3 Function Evaluate

Before proceeding with describing Evaluate, notice that we use the term *overnodes* to refer to the nodes on the stem, and the term *undernodes* to refer to the others. The *trigger leaf* is always an *overnode*.

As reported in Lemma 2, if the evaluation of an overnode satisfies a failure Δ -constraint, then it is the case that the root overnode satisfies the same failure Δ -constraint, and the same for the corresponding process model. The consequence of this property is that the evaluation of whether a model satisfies a failure Δ -constraint, can be sometimes assessed by evaluating only some of the associated overnodes.

To determine the extent to which a node in a process tree satisfies a failure Δ -constraint being evaluated, we adopt a set of classifications. While we introduce the classes used to evaluate the failure Δ -constraints and their sub-patterns in Section 5 in detail, for the sake of simplicity we introduce now an abstract function, classification as described in Definition 15, which assigns a set of classifications to a node of a process tree according to the failure Δ -constraint being evaluated.

Definition 15 (Classification). Let B be a process block. The following classification function (cl) returns a set of classifications C, where the requirements of each classification in C are satisfied by B.

 $\mathsf{cl}(B) = \mathscr{C}$

The result of classifying a node in a process tree is generally a set of classes instead of a single class. This is the result of the properties of a node to match the requirements of multiple classes. Note, however, that even if the cartesian product suggests an explosion of the number of aggregations required to be performed, such number is limited by the number of classifications kept in the resulting set, which is again is going to be limited by preference orders defined for each type of classes, allowing to discard classifications from the result if another strictly better classification exists in the set.

The classification of the leaves in a process tree depends uniquely on which failure Δ -constraint is being evaluated, and on the properties of the leaf. Differently, the classification of a non-leaf node in a process tree can be derived from the classifications of its children as shown in Definition 16.

Definition 16 (Aggregation).

Let B be a process block and let $B_1, B_2, ..., B_n$ be the sub-blocks composing B. Let aggregate (agg) be a binary function taking two sets of classifications and returning the set of resulting aggregated classifications.

The classification of B is equivalent to the cumulative aggregations of the classifications of its sub-blocks as follows:

 $cl(B) \equiv agg(agg(agg(cl(B_1), cl(B_2)), ...), cl(B_n))$

Notice that the result of agg also depends on the type of the process block whose sub-blocks classifications are being aggregated. Moreover, the aggregation order follows the left to right order of appearance of the sub-blocks in the process tree, which maintains the order in the process description using the prefix representation, shown in Definition 1. While the aggregation order is important only when the node being classified is of type SEQ, for the sake of simplicity we force a strict left-to-right aggregation for every type of node.

Example 2 (Classifications and Aggregations).

Considering the process tree representation in Figure 21, where $\overline{A}\Delta 1$ is evaluated through the classification \circ of the nodes of the tree.

The nodes in the process tree are classified to evaluate the constraint. For instance,

it can be noticed that $cl(t_1) = \frac{\mathbf{w}_2}{\mathbf{w}_2}$, and that $cl(t_2) = \mathbf{w}_2$. Considering now the process block composed by t_1 and t_2 , labelled \times in Figure 21, its classification is the following: $cl(\times) = \overset{00}{xz}$.

The classification of \times can also represented as the aggregations⁶ of the classifications of the process blocks composing it as follows: $agg(\underline{xz}, \underline{xz}) = \underline{xz}$

Aggregations for SEQ and AND Undernodes When evaluating a failure Δ -constraint over a process-tree representation of a model, we are interested in the classifications of the overnodes. Keeping this in mind, and despite using a comparable left-to-right cumulative aggregation for both nodes of type SEQ and AND, the following difference must be adopted when such nodes are overnodes.

SEQ Classifying an overnode of type SEQ requires to evaluate and aggregate its left and right children independently with respect to the stem. This is graphically illustrated in Figure 8. As the properties to verify a Δ -constraints are always relative to a given trigger task, which identifies the stem, and because of the execution semantics of a SEQ process block, classifications on the left side of the stem can only be used to verify the part of the Δ -constraint on the left of the *trigger task*. The same holds for classifications on the right side of the stem.

⁵ Some of the classes to evaluate $\overline{A}\Delta 1$ are first introduced in Table 3.

⁶ Notice that in this particular case, as the node being evaluated is of type XOR, the aggregation consists of the union of the classifications of the blocks composing the XOR, and by removing the classes which are strictly worst than the ones included in the resulting set. This is further explained in a following subsection.

AND When classifying an overnode of type AND, the left and right of the stem division is not required, and the classification of the overnode is obtained by aggregating together the evaluations of its direct undernode children and then aggregating the result with its overnode child. This is graphically illustrated in Figure 9.



Fig. 8: SEQ Overnode Evaluation



Fig. 9: AND Overnode Evaluation

Aggregations for XOR **Undernodes** The aggregation of undernodes of type XOR is performed by considering the union of the sets of classifications of the children of the XOR undernode. The resulting set of classification is then simplified in accordance to the preference orders of the classification being evaluated.

When the preference order of the classifications is linear, after simplifying the resulting set of an XOR aggregation, it always consists of a single classification. Differently, when the preference order of the classifications is not linear (i.e., the preference orders between the possible classifications is a lattice), then it is possible that the simplification of an aggregation contains more than a single classification.

Removing possible classifications from a result set does not interfere with verifying whether the failure Δ -constraint being evaluated can be satisfied, as only the classifications being strictly worse than existing ones in the result set are eliminated. Hence, the remaining classifications allow to verify the fulfilment of the failure Δ -constraint. Intuitively, when a classification is strictly better than another, the former is capable

of achieving at least the same classification through aggregations than the latter, and possibly a better one.

Example 3 (XOR *Aggregation*). Let B_1 and B_2 be process blocks composing an XOR block, and let their classifications be the following:

-
$$\operatorname{cl}(B_1) = \mathscr{C}_1$$

- $\operatorname{cl}(B_2) = \mathscr{C}_2$

The result of the aggregation (and, as such, the classification of the XOR block) is the following:

$$\mathsf{cl}(\mathsf{XOR}(B_1, B_2)) \equiv \mathscr{C}_1 \cup \mathscr{C}_2$$

Aggregations for the Overnode The evaluation of the overnode on the stem is performed in a similar way as for the undernodes of type SEQ and AND. The aggregation is defined in some aggregation tables, depending on the failure Δ -constraint being evaluated, and the type of the overnode. This aggregation is performed over the classification of the overnode's child of type overnode, with the classifications of its children of type undernode. Again, the classification is always performed from left to right in accordance to where the children appear in the process tree.

When an overnode is of type XOR, then its evaluation simply corresponds to the classification of its child of type overnode, as its children of type undernode can be safely discarded by the *Stem Pruning* procedure described in Lemma 3.

Evaluate **Termination** Finally, the evaluation of the stem (i.e. the overnodes of a process-tree) can be terminated either when Evaluate reaches the root of the process-tree and fails to verify the satisfaction of the failure Δ -constraint, or when the failure Δ -constraint is satisfied by any of the overnodes.

While the latter case ensures that there exists an execution in the model violating the obligation associated to the failure Δ -constraint, the former only ensures that there is no execution in the process model violating, given that particular trigger leaf, if and only if the sister failure Δ -constraint⁷ associated to the same obligation is also not satisfied for the same trigger leaf.

4.4 Computational Complexity of the Evaluation

The number of times the Evaluate function needs to be applied is in the worst case scenario equal to the number of overnodes times the number of trigger leaf for both failure Δ -constraints representing a given obligation that is required to be checked. Thus this procedure must be considered for each obligation in the regulatory framework. However, this evaluation procedure is *polynomial* with respect to the size of the process model and the size of the regulatory framework.

Furthermore, we need to look into the Evaluate function to actually show that the whole evaluation procedure is actually in time polynomial with respect to the size of the problem. From the provided description, we know that in order to classify the overnode being evaluated, Evaluate needs to aggregate the classification of each of its children

⁷ Remember that each obligation produces a pair of failure Δ -constraints, as shown in Definition 11 and Definition 13.

classifications. Resulting in n-1 aggregations, where n is the number of children of the overnode.

While the classification of the child of type overnode is provided by the previous application of Evaluate, the evaluations of the other children must be constructed by exploring the sub trees, hence classifying the leaves and aggregating their results up to the desired level where the children of the overnode reside. Notice that the number of aggregations required is polynomial with respect to the size of the process model, as it is at most equal to the number of sub-blocks of the block corresponding to the overnode.

Finally, we have to consider the complexity of each aggregation, which potentially involves aggregating sets of classifications together. As mentioned previously, the combinatorial explosion of aggregation is taken care of by providing a preference partial order between the possible classifications, hence allowing to discards classifications for which a strictly better one exists. As a consequence, for each aggregation between nodes in the process-tree, the amount of required aggregations between the classifications is reduced to a constant number of aggregations in the worst case scenario, depending on the preferences between the classifications.

The whole procedure, from aggregating classifications to the recursive application of Evaluate from the trigger leaf towards the root of the process-tree, involves steps that are polynomial or constant with respect to the size of the problem. Therefore, we can conclude that the computational complexity of the whole procedure is in time polynomial with respect to the size of the problem.

5 An Overview of the Aggregations

In this section, we introduce the classifications used to classify the tasks while evaluating the stem of a process tree against a failure Δ -constraints. It is not surprising that different classifications are required depending on the failure Δ -constraint being evaluated. However, we also introduce sub-patterns that can be reused through the classification and aggregation procedures, limiting in this way the number of possible combinations required to be analysed.

Note that, for the sake of readability, we do not explicitly show the aggregation tables for the classifications introduced. The aggregation tables, along with the correctness proof for the classifications considered, and the aggregations can be found in Appendix C.

5.1 $\overline{A}\Delta 1$

We hereby show the classifications used by $\text{Evaluate}(\mathscr{P}', \tau, \delta)$ when δ is $\overline{A}\Delta 1$. Before proceeding with the classifications, we introduce a simplified version of $\overline{A}\Delta 1$, which is used during the evaluation procedure, and is equivalent to evaluating $\overline{A}\Delta 1$.

The simplified failure Δ -constraint is introduced in Definition 17 and Figure 10 illustrates side by side the two versions of the failure Δ -constraint.

Definition 17 ($\overline{A}\Delta 1$ **Simplified**). *The Achievement Failure* Δ *-constraint from Definition 11, recalled below:*

 $\overline{A}\Delta 1 \exists t_t \text{ such that:} \\ \exists t_r, t_d | t_r \leq t_t \leq t_d \text{ and} \\ \neg \exists t_{\neg r} | t_r \leq t_{\neg r} \leq t_d \text{ and} \\ \exists t_{\neg d}, \neg \exists t_d | t_{\neg d} \leq t_d \leq t_t \end{cases}$

is simplified as follows:

 $\overline{A}\Delta 1S \exists t_t \text{ such that:} \\ \exists t_{\neg r}, t_d | t_{\neg r} \leq t_t \leq t_d \text{ and} \\ \neg \exists t_r | t_{\neg r} \leq t_r \leq t_d \end{cases}$



Fig. 10: $\overline{A}\Delta 1S$

The idea behind using simplified versions of the failure Δ -constraints is to have simpler patterns to evaluate in the nodes of the process tree. While the original formulation of some failure Δ -constraints is easier to understand, it contains some superfluous sub-patterns that can be omitted, hence easing their overall evaluation.

Moreover, Theorem 4 states that the simplification does not hinder the relation between the constraint and the model not being fully compliant. In detail, the difference in the simplified constraint consists of removing the sub-pattern regarding the presence in a possible execution of a task having $\neg d$ annotated on the left of the trigger leaf, while not having a task with d annotated between. The remainder of the pattern is sufficient to recognise executions violating the associated achievement obligation to $\overline{A}\Delta 1$, as the removed sub-pattern purpose is mainly to differentiate it from $\overline{A}\Delta 2$. The proof of Theorem 4 shows in details how the simplified version of $\overline{A}\Delta 1$ is sufficient to recognise the same as the original version.

Theorem 4. If a violation in a business process model is identified by satisfying either $\overline{A}\Delta 1$ or $\overline{A}\Delta 2$, then the same violation is identified by satisfying either $\overline{A}\Delta 1S$ or $\overline{A}\Delta 2$.

Interval Overnode Pattern We now introduce the Interval Overnode Pattern, a generalisation of $\overline{A}\Delta 1S$.

Definition 18 (Interval Overnode Pattern).

Let an Interval Overnode Pattern be the following:

iop(x, y, z)

Where x represents the desired task on the left side of the aggregation, and z the one desired on the right side. Moreover, y represents the task that is required not to appear between the interval identified by x and y, as shown in Figure 11.

The $\overline{A}\Delta 1S$ pattern can be parametrised as an Interval Overnode Pattern as follows:

 $iop(t_{\neg r}, t_r, t_d)$



Fig. 11: Interval Overnode Pattern

The associated process block contains an execution fulfilling the Interval Overxtz node Pattern. + 0 xtz The associated process block contains an execution fulfilling the left sub-pattern of the Interval Overnode Pattern. $\frac{0}{xtz}$ The associated process block contains an execution fulfilling the right subpattern of the Interval Overnode Pattern. The associated process block contains an execution fulfilling the left sub-pattern $\mathbf{x}\mathbf{t}\mathbf{z}$ of the Interval Overnode Pattern, and fails the right sub-pattern. 0 0 xtz The associated process block contains an execution not failing or fulfilling either sub-pattern of the Interval Overnode Pattern. The associated process block contains an execution fulfilling the right subxtz pattern of the Interval Overnode Pattern, and fails the left sub-pattern. $\frac{0}{xtz}$ The associated process block contains an execution failing the right sub-pattern of the Interval Overnode Pattern. - 0xtz The associated process block contains an execution failing the left sub-pattern of the Interval Overnode Pattern. The associated process block contains only executions failing the Interval Overxtz node Pattern.

Table 2: Overnode classification classes.

As such, fulfilling an Interval Overnode Pattern with the above instantiation corresponds to fulfilling the corresponding $\overline{A}\Delta 1S$. An overview of the possible classifications of an overnode is provided in Table 2.

Even though an overnode can potentially belong to multiple classes, only the classes for which no strictly better class is available, are considered as the classes of a node. The preference relations between the classes is shown in Figure 12.

When classifying overnodes along the stem of a process tree, if one of the nodes is classified as $\mathbf{x}\mathbf{t}\mathbf{z}^+$ then the evaluation procedure can be terminated, as this is sufficient proof to conclude that $\overline{A}\Delta 1S$ is satisfied. Consequently, the process model associated to the process tree being analysed violates the obligation associated to the failure Δ -constraint.

Interval Overnode Pattern: Trigger Leaf Classification The trigger leaf can be assigned to the following classes: xtz, xtz, xtz, xtz, xtz, depending on the literals annotated on the task associated to the trigger leaf.

Note that if the associated task has *y* in its annotations, then the evaluation can safely be terminated, as the process-tree given this particular trigger leaf will never satisfy the Interval Overnode Pattern.



Fig. 12: Interval Overnode Pattern Classes' Preference Lattice

Interval Overnode Pattern: Undernodes Classification for SEQ **Overnode** Considering the Interval Overnode Pattern, it can be divided into its left and right sides as illustrated in Figure 13. The undernodes can be then classified and aggregated using the simpler *Left Sub-Pattern*, and *Right Sub-Pattern*.



Fig. 13: Interval Overnode Pattern Left and Right Sub-Patterns

Left Sub-Pattern Definition 19 (Left Sub-Pattern). Let a Left Sub-Pattern be the following:

lsp(x,y)

Where x represents the desired task on the right side of the aggregation, and y the undesired task on the right side of x, as shown in Figure 14.

Fig. 14: Left Sub-Pattern

Notice that for $\overline{A}\Delta 1S$, the corresponding parametrisation of the left sub-pattern check is the following:

$$lsp(t_{\neg r}, t_r)$$

Considering the left sub-pattern, an undernode in the process tree can belong to the following classes. The association to a class depends on the properties of the associated process block.

- \mathbf{x}^+ The associated process block contains an execution capable of fulfilling the left sub-pattern.
- ${}^{0}_{X}$ The associated process block contains an execution that does not influence the left sub-pattern.
- $\bar{\mathbf{x}}$ The associated process block contains only executions hindering the capability of fulfilling the left sub-pattern.

Even though a process block can potentially belong to multiple classes, a process block belongs to the classes for which no better class is available, in accordance to the following linear preference order of the classes: $\mathbf{x} < \mathbf{x} < \mathbf{x} < \mathbf{x}$.

Right Sub-Pattern We discuss now the *Right Sub-Pattern*, used to evaluate the right side of the stem parting from an overnode of type SEQ.

Definition 20 (Right Sub-Pattern). Let a Right Sub-Pattern be the following:

rsp(y,z)

Where z represents the desired task on the left side of the aggregation, and y the undesired task on the left side of z, as shown in Figure 15.

(y) ← / - (z)

Fig. 15: Right Sub-Pattern

Notice that for $\overline{A}\Delta 1S$, the corresponding parametrisation of the right sub-pattern check is the following:

$rsp(t_r, t_d)$

Considering the right sub-pattern, an undernode in the process tree can belong to the following classes. The association to a class depends on the properties of the associated process block.

- ${}^+_z$ The associated process block contains an execution capable of fulfilling the right sub-pattern of the right sub-pattern.
- ${}^{0}_{z}$ The associated process block contains an execution that does not influence the right sub-pattern of the right sub-pattern.
- \bar{z} The associated process block contains only executions hindering the capability of the right sub-pattern.

Even though a process block can potentially belong to multiple classes, a process block belongs to the classes for which no better class is available, in accordance to the following linear preference order of the classes: $\mathbf{\bar{z}} < \mathbf{\bar{z}} < \mathbf{\bar{z}} < \mathbf{\bar{z}} + \mathbf{\bar{z}}$

Interval Overnode Pattern: Undernodes Classification for AND **Overnode** We introduce a generalised sub-pattern to evaluate the undernodes: *Interval Sub-Pattern*.

Definition 21 (Interval Sub-Pattern).

Let an Interval Sub-Pattern be the following:

isp(x, y, z)

Where x represents the desired task on the right side of the interval, and z the left side within an aggregation. Additionally, y represent a task that is undesired when appearing within the interval formed by x and z, as shown in Figure 16.



Fig. 16: Interval Sub-Pattern

For $\overline{A}\Delta 1S$, the parametrisation of the interval sub-pattern is as follows:

 $isp(t_{\neg r}, t_r, t_d)$

- $\frac{ZZ}{ZZ}$ The associated process block contains an execution containing an interval fulfilling the complete interval sub-pattern.
- $\frac{+0}{XZ}$ The associated process block contains an execution fulfilling the left side of the interval sub-pattern, and with no failure conditions for the right side.
- $\frac{0+}{XZ}$ The associated process block contains an execution fulfilling the right side of the interval sub-pattern, and with no failure conditions for the left side.
- $\frac{+-}{XZ}$ The associated process block contains an execution fulfilling the left side of the interval sub-pattern, while failing its right side.
- $\frac{00}{XZ}$ The associated process block contains an execution not fulfilling the interval subpattern, and not containing any undesired element.
- $\frac{\bar{x}z}{\bar{x}z}$ The associated process block contains an execution fulfilling the right side of the interval sub-pattern, while failing its left side.
- $\frac{\mathbf{x}}{\mathbf{x}}$ The associated process block contains only executions failing either side of the interval sub-pattern without partially achieving any of them.

Table 3: Interval sub-pattern classification classes.

Note that in Table 3 the classes \underline{xz}^{0} and \underline{xz}^{0} are missing. It is not necessary to explicitly include these classes, as the class \underline{xz} covers them. The intuitive reason is the following: as the omitted classes represent scenarios where either the left side or the right side of the pattern contain elements leading to the failure of $\overline{A}\Delta 1$, and no additional helpful element towards the satisfaction of the constraint are present. Such classifications can be reduced to the worst classification type, because as these sub-patterns are

used to evaluate AND nodes, their semantics allows to disregard such sub-blocks when evaluating the failure Δ -constraint. This means that we are not required to keep track of these cases, as they can all be aggregated to the worst class \overline{xz} .

Even though a process block can potentially belong to multiple classes, a process block belongs to the classes for which no better class is available, in accordance to the preference lattice shown in Figure 17. Despite the fact that the evaluation of an overnode can increase due to a single evaluation aggregated with a classification producing multiple ones, the number of evaluations required to be kept is limited to at most 3 in the worst case scenario due to the preference order expressed in Figure 17.



Fig. 17: Interval Sub-Pattern Classes Preference Lattice

 $\overline{A}\Delta 1S$: **Computational Complexity of the Aggregations** The evaluation of an overnode of type SEQ is linear with respect to the size of the undernode children sub-trees. When evaluating an overnode of type AND, we must consider the number of possible simultaneous classifications that can appear while evaluating an overnode sub-pattern and an interval sub-pattern. In both cases, the number is limited to 3, as it can be seen in the preference lattices shown in Figure 12 and Figure 17. Therefore, we can conclude that the overall complexity of verifying whether a process model satisfies $\overline{A}\Delta 1S$ is determined by the complexity of aggregating the evaluations of the overnodes belonging to its process tree. As evaluating an overnode of type AND is more complex than evaluating one of type SEQ, we can generalise the complexity of checking the satisfaction of $\overline{A}\Delta 1S$ as: is **O**(9*n*) evaluations/aggregations, where *n* is the number of nodes in the tree, representing the number of blocks in a business process. Therefore the complexity of evaluating is polynomial with respect to the size of the process model.

Example: Evaluating $\overline{A}\Delta 1S$ **along a Process Tree** In this sub-section, we illustrate an example of how the evaluation is performed on a process tree while checking whether the related process model contains an execution satisfying $\overline{A}\Delta 1S$.

In Figure 18b, the process tree is shown derived from the process introduced in Figure 1. Notice that the start task contains the negation of the sought annotated requirement of the obligation, in accordance to Assumption 2, and the deadline is contained in the end task, in accordance to Assumption 1.

Given the obligation $\mathcal{O}^a \langle b, c, \neg a \rangle$, there are two trigger leaves candidates: t_2 and t_3 , as they both contain the annotation c. Let us first consider the process tree using t_2 as trigger leaf and proceed with the classification of the leaves in the tree. However, since t_2



(b) Process tree representation

Fig. 18: Process tree representation.

satisfies the termination condition while evaluating the trigger leaf, we can safely state that for this particular stem the process does not satisfy $\overline{A}\Delta 1S$. Let us now consider t_3 as the trigger leaf. We can classify the leaves of the tree as shown in Figure 19, where:

- t_3 , being the trigger leaf on the stem (and, therefore, an overnode) is classified according to the overnode sub-pattern.
- t_1 and t_2 are classified according to the interval sub pattern, as their parent node on the stem (their parent overnode) is an AND.
- start is classified according to the left sub-pattern as its parent overnode is a SEQ and it sits on the left of the stem.
- t_4 and end are classified according to the righ sub-pattern as their parent overnode is a SEQ and it sits on the right of the stem.



Fig. 19: Evaluating $\overline{A}\Delta 1S$ on a process tree (1).

In Figure 20, we show the aggregations towards the classifications of the overnode AND on the stem. Note that the XOR undernode classification is the union of the classifications of the children, and then pruned according to the priority lattice.



Fig. 20: Evaluating $\overline{A}\Delta 1S$ on a process tree (2).

Figure 21 depicts the aggregation towards the classification of the overnode SEQ, the root. Notice that the resulting classification is $\overset{+}{\mathbf{x}} \overset{+}{\mathbf{z}} \overset{*}{\mathbf{z}}$, hence the process tree, using this stem, does satisfy $\overline{A}\Delta 1S$.



Fig. 21: Evaluating $\overline{A}\Delta 1S$ on a process tree (3).

⁸ The aggregation is performed in two steps, the first step involves the overnode class with either one of the left or right classifications. Then the result is aggregated with the remainder, producing the final result.

5.2 $\overline{A}\Delta 2$

We hereby show the classifications used by $\text{Evaluate}(\mathscr{P}', \tau, \delta)$ when δ is $\overline{A}\Delta 2$. Notice that the procedure is actually evaluated over two simplified constraints of $\overline{A}\Delta 2$ obtained from its decomposition, which we first introduce.

Decomposing $\overline{A}\Delta 2$ We now introduce the decomposed counterparts of $\overline{A}\Delta 2$, which we refer to as $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.2$. The two decomposed Δ -constraints are derived from $\overline{A}\Delta 2$ as illustrated in Figure 22.



Fig. 22: $\overline{A}\Delta 2$ Pattern Reductions

Definition 22 ($\overline{A}\Delta 2$ **Decomposed**). *The Achievement Failure* Δ *-constraint from Definition 11, recalled below:*

 $\overline{A}\Delta 2 \exists t_t \text{ such that:} \\ \exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \leq t_r \leq t_t \text{ and} \\ \exists t_d, \neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_t \end{cases}$

is simplified as follows:

 $\overline{A}\Delta 2.1 \exists t_t \text{ such that:} \\ \exists t_{\neg r}, t_d | t_{\neg r} \leq t_d \leq t_t \text{ and} \\ \neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_t \text{ and} \\ \neg \exists t_r | t_{\neg r} \leq t_r \leq t_d \\ \overline{A}\Delta 2.2 \exists t_t \text{ such that:} \\ \exists t_{\neg r}, t_d | t_d \leq t_{\neg r} \leq t_t \text{ and} \\ \neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_{\neg r} \text{ and} \\ \neg \exists t_r | t_{\neg r} \leq t_r \leq t_t \\ \end{cases}$

 $\overline{A}\Delta 2$ contains two sub-patterns, and both of these sub-patterns sit on the left of the trigger leaf. The idea behind the simplification is to serialise the two possible interleavings of the sub-patterns to ease their verification. While the simplification introduces an additional constraint to verify, it allows to get rid of the complexity of verifying interleaved sub-patterns. Finally, Theorem 5 shows how verifying the two decomposed constraints is equivalent to verifying the original.

Theorem 5. If a violation in business process model is identified by satisfying $\overline{A}\Delta 2$, then the same violation is identified by satisfying either $\overline{A}\Delta 2.1$ or $\overline{A}\Delta 2.2$.

Generalised Sequence Pattern

Definition 23 (Generalised Sequence Pattern).

Let a Generalised Sequence Pattern be the following:

gsp(x, y, z, k)

Where z represents the desired task on the right side of the aggregation, and k the undesired task on the right side of z. Moreover x represents a desired task on the left of z, and with no y between x and z, as shown in Figure 23.



Fig. 23: Generalised Sequence Constraint

Despite the generalised sequence pattern looking different than $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.2$, it captures the key properties that neither the unwanted elements k and y should appear on the right of the required element z, and maintaining the additional condition that there should be another required element x on the left of z, and y should also not be between them.

Notice that, given an obligation $\mathcal{O}^o \langle r, t, d \rangle$, the parametrisations of its Δ -constrains $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.2$, in generalised sequence patterns, is the following:

 $\overline{\underline{A}}\Delta 2.1 \quad gsp(t_{\neg r}, t_r, t_d, t_{\neg d}) \\ \overline{\underline{A}}\Delta 2.2 \quad gsp(t_d, t_{\neg d}, t_{\neg r}, t_r)$

Generalised Sequence Pattern Undernode's Classes The following classifications can be used to classify the undernodes while checking for a decomposed $\overline{A}\Delta 2$ and evaluating an overnode of type SEQ. Notice also that due to the shape of the pattern, only the undernodes on the left of the stem are considered. An overview of the classifications of the generalised sequence pattern is provided in Table 4.

Even though a process block can potentially belong to multiple classes, a process block belongs to the classes for which no better class is available, in accordance to the preference lattice shown in Figure 24.

Generalised Sequence Pattern Overnode's Classes The overnodes on the stem being evaluated while checking for $\overline{A}\Delta 2.1$ or $\overline{A}\Delta 2.2$, use a variant of the *Generalised Sequence Pattern* classification.

In particular, the labels of the classes are the same, but with appended on the right \mathbf{t} , signifying that the classification constraints of the definitions for the generalised sequence patterns are supposed to have always on the right the *trigger leaf* task.⁹ For

⁹ Notice that, since these classifications are always on the stem, and we are classifying the children nodes of the tree on the left of the stem, then this is always the case.

XZ	Exists an execution such that: both x and z sub-patterns are fulfilled and in the correct order
+0 XZ	Exists an execution such that: x sub-pattern is satisfied, but z sub-pattern is not-satisfied on the right of the former, neither invalidated.
0+ XZ	Exists an execution such that: z sub-pattern is satisfied and x is neither satisfied or invalidated on the left of the former.
00 XZ	Exists an execution such that: neither sub-pattern invalidated or satisfied.
-+ XZ	Exists an execution such that: z sub-pattern is satisfied and x is invalidated on the left of the former.
+- X Z	Exists an execution such that: x sub-pattern is satisfied, but z sub-pattern is invalidated on the right of the former.
$0 - x^{-7}$	Exists an execution: z is falsified and x is neither satisfied or falsified on the left of

- \mathbf{x} **z** Exists an execution: z is falsified and x is neither satisfied or falsified on the left of z.
- $\bar{\mathbf{x}}_{\mathbf{z}}$ For every execution: *z* is falsified or *x* is falsified without having a satisfied *z* on its right. (Represents the remainder possibilities: $\bar{\mathbf{x}}_{\mathbf{z}}$ and $\bar{\mathbf{x}}_{\mathbf{z}}$).

Table 4: Classification classes of the generalised sequence pattern.



Fig. 24: Generalised Sequence Pattern Undernode Classes

instance, considering the class $\overset{++}{\mathbf{x}}$ used to classify undernodes, its corresponding class used for overnodes would be $\overset{++}{\mathbf{x}}$, and it would have the same properties as $\overset{++}{\mathbf{x}}$, with the addition of having a t_t on the right of each considered element. The graphical representation of the pattern used to classify the overnodes is shown in Figure 25.



Fig. 25: $\overline{A}\Delta 2$ SEQ Generalised Sub Patterns

When classifying overnodes along the stem of a process tree, if one of the nodes is classified as $\overset{++}{\mathbf{x}zt}$, then the evaluation procedure can be terminated, as this is sufficient proof to conclude that one of the decomposed version of $\overline{A}\Delta 2$ is satisfied. That is, the process model associated to the process tree being analysed violates the obligation associated to the Δ -constraint.

Noticing the similarity between the classes used to classify undernodes and overnodes while verifying a generalised sequence pattern, the aggregation tables describing how undernode classes are aggregated to classify their undernode parent can be used to classify an overnode on the stem. More precisely, the column SEQ(A, B) can be used as the aggregation result to classify an overnode of type SEQ on the stem when using the column A as the left-to-right classification aggregation of its undernode children on the left of the stem, and using the column B as the equivalent classification of the overnode's overnode child.

AND **Overnode** When evaluating an overnode of type AND, its undernodes can be classified using the *Interval Sub-Pattern*. Note that in this case every undernode, either on the left or the right of the stem, must be evaluated.

As illustrated in Figure 26, the same pattern used to evaluate $\overline{A}\Delta 1S$ can be used to evaluate both $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.2$. In Figure 26, the $\overline{A}\Delta 2$ decomposed patterns are obtained by adding the trigger task on the right of the interval sub-pattern.



Fig. 26: $\overline{A}\Delta 2$ decomposed Patterns AND Overnode Aggregation Comparison With $\overline{A}\Delta 1S$

While evaluating a generalised sequence pattern: gsp(x, y, z, k), the interval subpattern used to classify its undernodes is the following: isp(x, y, z).

 $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.1$:Computational Complexity of the Aggregations In general, for both SEQ and AND overnode evaluations, in the worst case scenario at most 3 classifications are used at the same time to classify a single node of the process-tree. Therefore, the overall complexity of evaluating whether a process tree (and, as such, the associated business process model) satisfies one of the decomposed pattern representations of $\overline{A}\Delta 2$ (namely $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.2$) is $O(3^2n)$, where *n* is the number of nodes in the process tree. Note that independently from the type of overnode on the stem, the complexity of its evaluation is $O(3^2n)$.

Finally, considering that to actually evaluate $\overline{A}\Delta 2$ on a process tree, both its decomposed patterns need to be evaluated. As such, the actual complexity of evaluating $\overline{A}\Delta 2$ is $\mathbf{O}(2 \times 3^2 n)$.

5.3 $\overline{M}\Delta 1$

We hereby show the classifications used by $\text{Evaluate}(\mathscr{P}', \tau, \delta)$ when δ is $\overline{M}\Delta 1$. The illustration of the Δ -constraint is recalled in Figure 27.



Fig. 27: $\overline{M}\Delta 1$

Evaluate Using LSP To evaluate $\overline{M}\Delta 1$ we use the left sub-pattern with the following parametrisation:

$$lsp(\neg r, r)$$

The possible classifications of an overnode, derived from the existing classifications of the left sub-pattern, are listed as follows:

- $\mathbf{\dot{x}t}$ The associated process block contains an execution capable of fulfilling $\overline{M}\Delta 1$.
- ⁰ xt The associated process block contains an execution that does not contain elements influencing whether $\overline{M}\Delta 1$ is satisfied or violated.
- $\mathbf{\bar{x}t}$ The associated process block contains only executions hindering the capability of fulfilling $\overline{M}\Delta 1$.

The classes follow the following linear preference order of the classes:

$$\overline{\mathbf{x}}\mathbf{t} < \mathbf{x}\mathbf{t} < \mathbf{x}\mathbf{t}$$

The undernodes of an overnode of type SEQ are classified using left sub-pattern classes, and only the undernodes on the left of the stem are used to evaluate the overnode. The aggregation to evaluate the overnode follows exactly the left sub-pattern aggregations.

AND **Overnode Evaluation: Interleaved Generic Pattern** Let the Interleaved Generic Pattern be the following:

igp(k, y)

The undernodes of an overnode of type AND are evaluated using to the following Interleaved Generic Pattern classes:

- \mathbf{k}^{+} The associated process block contains a task having a k annotated and no y.
- $^{0}_{\mathbf{k}}$ Otherwise.

The classification of the undernodes of an AND overnode while evaluating $\overline{M}\Delta 1$ is done using the following parametrisation: $igp(\neg r, r)$. The evaluations of the undernodes can be aggregated with the Left Sub-Pattern classification of the overnode using the AND column of the aggregations while considering one of the columns A of B as the equivalent Interleaved Generic Pattern classification and the other as the classification of the overnode child.

 $\overline{M}\Delta 1$: Computational Complexity of the Aggregations As the preferences between the classes is a total order independent from the type of overnode, the overall computational complexity of $\overline{M}\Delta 1$ is linear: O(n), where *n* is the number of nodes in the process tree.

5.4 $\overline{M}\Delta 2$

We hereby show the classifications used by $\text{Evaluate}(\mathscr{P}', \tau, \delta)$ when δ is $\overline{M}\Delta 2$. The evaluation is done using a simplified version of the failure Δ -constraint, defined as follows.

Definition 24 ($\overline{M}\Delta 2$ **Simplified**). $\overline{M}\Delta 2$ from Definition 13 can be simplified as follows:

 $\overline{M}\Delta 2S \exists t_t \text{ such that:} \\ \exists t_{\neg r}, \neg \exists t_d | t_t \leq t_d \leq t_{\neg r}$



Fig. 28: $\overline{M}\Delta 2$ Simplified

Theorem 6. If a violation in business process model is identified by satisfying either $\overline{M}\Delta 1$ or $\overline{M}\Delta 2$, then the same violation is identified by satisfying either $\overline{M}\Delta 1$ or $\overline{M}\Delta 2S$.

Evaluate Using RSP To evaluate $\overline{M}\Delta 2S$, we use the right sub-pattern with the following parametrisation:

rsp(r,d)

When an overnode is of type SEQ, then the undernodes on the right of the stem can be classified using right sub-pattern classes and used to evaluate the overnode using the same aggregations.

AND **Overnode Evaluation using IGP** In a similar way for $\overline{M}\Delta 1$, the classification of the undernodes of an AND overnode while evaluating $\overline{M}\Delta 2S$ is done using the following parametrisation: $igp(\neg r, d)$.

The evaluations of the undernodes can be aggregated with the Right Sub-Pattern classification of the overnode using the AND column of the aggregations while considering one of the columns A of B as the equivalent Interleaved Generic Pattern classification and the other as the classification of the overnode's overnode child.

 $\overline{M}\Delta 2S$ **Overall Complexity** As the preferences between the classes is a total order, the overall complexity of verifying whether a process model satisfies $\overline{M}\Delta 2S$ is determined by the complexity of aggregating the evaluations of the overnodes belonging to its process tree. As evaluating an overnode of type AND or of type SEQ is linear: O(n), where *n* is the number of nodes in the process tree.

6 Conclusion

We have shown that verifying a failure Δ -constraint over a process-tree for one of its trigger leaves is achievable in polynomial time with respect to the size of the tree. Given an obligation, independent of whether such obligation is of type achievement or maintenance, its corresponding failure Δ -constraints can be verified over the process tree for each of its trigger leaves and determine whether the process model corresponding to the tree is *fully compliant* with the obligation as follows:

- Not Fully Compliant If one of the failure Δ -constraints is positively verified for the process tree and one of its trigger leaves, then it means that there exists an execution of the process violating the obligation associated to the failure Δ -constraint, hence the process model cannot be fully compliant.
- **Fully Compliant** Otherwise, when no failure Δ -constraint is positively verified for each of the trigger leaves of the process tree, then every execution satisfies the obligation, and the process is fully compliant.

Notice that the number of failure Δ -constraints being verified is 3 when the obligation is of type achievement, and 2 when the obligation is of type maintenance. Moreover, the number of trigger leaves in a process model can in the worst case be the same as the amount of tasks in the process. Although this can be significant, the procedure iterating through each of them for each failure Δ -constraint and aggregating through the nodes of the tree is still polynomial with respect to the size of the process model.

Finally, even considering a set of obligations, the same procedure can be reused by simply reiterating the verification for each obligation in the set composing the regulatory framework, which would increase the number of steps for the procedure to achieve an answer by up to a factor of the cardinality of the set of obligations being checked. However, the verification would be still in polynomial time with respect to the size of the process model and the cardinality of the set of obligations.

Therefore, we have shown that evaluating whether a structured business process is fully compliant with a set of conditional obligations, whose elements are restricted to be propositional literals, belongs to the computational complexity class **P**.

Acknowledgments

This research is supported by the Science and Industry Endowment Fund.

References

- Wil M. P. van der Aalst. Verification of workflow nets. In *Proceedings of the 18th International Conference on Application and Theory of Petri Nets*, ICATPN '97, pages 407–426, London, UK, UK, 1997. Springer-Verlag.
- Carlos E. Alchourrón, Peter Gärdenfors, and David Makinson. On the logic of theory change: Partial meet contraction and revision functions. J. of Symbolic Logic, 50(2):510–530, 1985.
- 3. Silvano Colombo Tosatto, Guido Governatori, and Pierre Kelsen. Business process regulatory compliance is hard. *IEEE Transactions on Services Computing*, 8(6):958–970, 2015.
- Silvano Colombo Tosatto, Guido Governatori, and Nick van Beest. Checking regulatory compliance: Will we live to see it? In Thomas Hildebrandt, Boudewijn F. van Dongen, Maximilian Röglinger, and Jan Mendling, editors, *Business Process Management*, pages 119–138, Cham, 2019. Springer International Publishing.
- Silvano Colombo Tosatto, Guido Governatori, Nick R.T.P. van Beest, and Francesco Olivieri. Efficient full compliance checking of concurrent components for business process models. *IfCoLog Journal of Logics and their Applications - Special Issue: Reasoning for Legal AI*, 6(5):963–998, 08 2019.
- Amal Elgammal, Oktay Turetken, Willem-Jan van den Heuvel, and Mike Papazoglou. Formalizing and applying compliance patterns for business process compliance. *Software & Systems Modeling*, 15(1):119–146, 2016.
- Guido Governatori. The Regorous approach to process compliance. In 2015 IEEE 19th International EDOC Workshop, pages 33–40. IEEE Press, 2015.
- Guido Governatori and Antonino Rotolo. Norm compliance in business process modeling. In Proceedings of the 4th International Web Rule Symposium: Research Based and Industry Focused (RuleML 2010), volume 6403 of LNCS, pages 194–209. Springer, 2010.
- J org Hoffmann, Ingo Weber, and Guido Governatori. On compliance checking for clausal constraints in annotated process models. *Information Systems Frontiers*, 14(2):155–177, 2012.
- Bartek Kiepuszewski, Arthur H. M. ter Hofstede, and Christoph Bussler. On structured workflow modelling. In *Proceedings of the 12th International Conference on Advanced Information Systems Engineering*, pages 431–445, London, UK, UK, 2000. Springer-Verlag.
- David Knuplesch, Linh Thao Ly, Stefanie Rinderle-Ma, Holger Pfeifer, and Peter Dadam. On enabling data-aware compliance checking of business process models. In *International Conference on Conceptual Modeling*, pages 332–346. Springer, 2010.
- 12. Wil M. P. van der Aalst. The application of petri nets to workflow management. *Journal of Circuits, Systems, and Computers*, 8(1):21–66, 1998.

A Failure Δ -constraints

A.1 Achievement Obligations to Failure Δ-constraints

Lemma 1. Given a conditional obligation, executing a task having its trigger annotated always results in its following state having the obligation in force, where it can be potentially fulfilled or violated.

Proof. Either the execution changes the previous state where t was not holding to one where it is, or t had been holding already.

In the first case, the execution brings a new in force period for the obligation.

In the second case, either the obligation is in force and not fulfilled in the previous state, or it becomes fulfilled in the previous state. In both cases, the execution of the task brings the obligation in force again and requires to be fulfilled.

Theorem 1. Given an execution ε , represented as a sequence of tasks, if ε satisfies either of the Achievement Failure Δ -Constraints (Definition 11), then ε satisfies the obligation related to the Achievement Failure Δ -Constraints.

Proof. Soundness:

First case: $\overline{A}\Delta 1$

- 1. From the hypothesis, and Definition 11, it follows that ε satisfies the following conditions: (a) $\exists t_t | \exists t_{\neg r}, t_d | t_{\neg r} \leq t_t \leq t_d$
 - (b) $\exists t_t | \neg \exists t_r | t_{\neg r} \preceq t_r \preceq t_d$

(c)
$$\exists t_t | \exists t_{\neg d}, \neg \exists t_d | t_{\neg d} \preceq t_d \preceq$$

- 2. From 1.(a), and Lemma 1, it follows that: t holds and r does not, in the state holding after the execution of the task t_t .
- 3. From 2., and 1.(b), it follows that: there is no state included between the state after executing the task t_t and one where *d* starts holding, where *r* holds.
- 4. From 3. and Definition 10, it follows that ε would violate the obligation related to the Achievement Failure Δ -constraints.

Second case: $\overline{A}\Delta 2$

- From the hypothesis, and Definition 11, it follows that ε satisfies the following conditions:

 (a) ∃t_t]∃t_{¬r}, ¬∃t_r|t_{¬r} ≤ t_r ≤ t_t
 (b) ∃t_t]∃t_d, ¬∃t_{¬d}|t_d ≤ t_{¬d} ≤ t_t
- 2. From I.(a), and Lemma 1, it follows that t holds and r does not, in the state holding after the execution of the task t_t .
- 3. From 1.(b), it follows that t holds and d holds, in the state holding after the execution of the task t_t .
- 4. From 2. and 3., it follows that after executing the task t_t , t and d hold and r does not hold.
- 5. From 4. and Definition 10, it follows that ε would violate the obligation related to the Achievement Failure Δ -constraints.

Completeness:

- 1. Given a trace violating a given achievement obligation.
- 2. From 1. and Definition 10 it follows that $\exists \sigma_t, \sigma_d | \text{contain}(t, \sigma_t)$ and $\sigma_t \leq \sigma_d$ and $\neg \exists \sigma_r | \sigma_t \leq \sigma_t \leq \sigma_t$.
- 3. From 2., it follows that a task with *t* annotated is executed.
- 4. From 2., it follows that a task with d annotated is executed.
- 5. From 2., it follows that $\neg r$ holds and no task with *r* annotated is executed between the one with *t* and the one with *d*.
- 6. Following from 3., 4., and 5. two <u>cases are possible</u>:
 - $t_d \leq t_t$ this case is covered by the $\overline{A}\Delta 2$ conditions in Definition 11.
 - $t_t \leq t_d$ this case covered by the $\overline{A}\Delta 1$ conditions in Definition 11.
- 7. Thus, all cases are covered and a violating trace is always identified by the Achievement Failure Δ -constraints.

$\overline{A}\Delta 1$ Simplified

Theorem 4. If a violation in business process model is identified by satisfying either $\overline{A}\Delta 1$ or $\overline{A}\Delta 2$, then the same violation is identified by satisfying either $\overline{A}\Delta 1S$ or $\overline{A}\Delta 2$.

Proof. As both procedures identifying whether a regulation violates a business process model contain the constraint $\overline{A}\Delta 2$, we focus on proving soundness and completeness when the violation is identified by fulfilling the other constraint, respectively $\overline{A}\Delta 1$ and $\overline{A}\Delta 1S$.

Soundness:

- 1. Given a violated regulation and satisfying $\overline{A}\Delta 1$.
- 2. From 1. and Definition 11 for $\overline{A}\Delta 1$, if follows that:

(a)
$$\exists t_{\neg r}, t_d | t_{\neg r} \leq t_t \leq t_d$$

(b)
$$\neg \exists t_r | t_{\neg r} \preceq t_r \preceq t_d$$

3. From 2.(a), 2.(b), and Definition 17 if follows that the violation is identified by $\overline{A}\Delta 1S$.

Completeness:

- 1. Given a violated regulation and satisfying $\overline{A}\Delta 1S$.
- 2. From 1. and Definition 17 for $\overline{A}\Delta 1S$, if follows that:
 - (a) $\exists t_t$ such that: $\exists t_{\neg r}, t_d | t_{\neg r} \leq t_t \leq t_d$
 - (b) $\exists t_t$ such that: $\neg \exists t_r | t_{\neg r} \leq t_r \leq t_d$
- 3. We consider the two following mutually exclusive cases:
 - **case 1** : $\exists t_t$ such that: $\exists t_{\neg d}, \neg \exists t_d | t_{\neg d} \leq t_d \leq t_t$
 - 3.1.1 From 2.(a), 2.(b), case 1, and Definition 11 for $\overline{A}\Delta 1$ if follows that the violation is identified by $\overline{A}\Delta 1$.
 - **case 2** : $\exists t_t$ such that: $\exists t_d, \neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_t$
 - 3.2.1 From 2.(a), and 2.(b), it follows that $\exists t_t$ such that: $\exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \leq t_r \leq t_t$.
 - 3.2.2 From 3.2.1, case 2, and Definition 11 for $\overline{A}\Delta 2$ if follows that the violation is identified by $\overline{A}\Delta 2$.
- 4. Therefore in each case, it follows that a violation identified by $\overline{A}\Delta 1S$ would be identified by either $\overline{A}\Delta 1$ or $\overline{A}\Delta 2$.

$\overline{A}\Delta 2$ Decomposed

Theorem 5. If a violation in business process model is identified by satisfying $\overline{A}\Delta 2$, then the same violation is identified by satisfying either $\overline{A}\Delta 2.1$ or $\overline{A}\Delta 2.2$.

Proof. Soundness:

- 1. Given a violated regulation and satisfying $\overline{A}\Delta 2$.
- 2. From 1. and Definition 11 for $\overline{A}\Delta 2$, if follows that: $\exists t_t$ such that:
 - $\exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \leq t_r \leq t_t$ and
 - $\exists t_d, \neg \exists t_{\neg d} | t_d \preceq t_{\neg d} \preceq t_t$
- 3. We distinguish 3 cases:
 - $t_{\neg r} \leq t_d$ (a) From the constraint introduced by the case, from 2., and from Definition 22 it follows that $\overline{A}\Delta 2.1$ is satisfied.
 - $t_d \leq t_{\neg r}$ (a) From the constraint introduced by the case, from 2., and from Definition 22 it follows that $\overline{A}\Delta 2.2$ is satisfied.
 - $t_{\neg r}$ and t_d are the same task (a) From the constraint introduced by the case, from 2., and from Definition 22 it follows that both $\overline{A}\Delta 2.1$ and $\overline{A}\Delta 2.2$ are satisfied.
- 4. From the cases analysed in 3., it follows that the violation is captured by either $\overline{A}\Delta 2.1$ or $\overline{A}\Delta 2.2$.

Completeness: We analyse the two cases separately.

- 1. Given a violated regulation and satisfying $\overline{A}\Delta 2.1$.
- 2. From 1. and Definition 22 for $\overline{A}\Delta 2.1$, if follows that: $\exists t_t$ such that:
 - $\exists t_{\neg r}, t_d | t_{\neg r} \preceq t_d \preceq t_t$ and

$$\neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_t \text{ an} \neg \exists t_r | t_{\neg r} \leq t_r \leq t_d$$

- 3. From 2., and Definition 11 for $\overline{A}\Delta 2$, it follows that the violation is captured by $\overline{A}\Delta 2$.
- 1. Given a violated regulation and satisfying $\overline{A}\Delta 2.2$.
- 2. From 1. and Definition 22 for $\overline{A}\Delta 2.2$, if follows that: $\exists t_t$ such that:
 - $\exists t_{\neg r}, t_d | t_d \leq t_{\neg r} \leq t_t \text{ and} \\ \neg \exists t_{\neg d} | t_d \leq t_{\neg d} \leq t_{\neg r} \text{ and} \end{cases}$
- $\neg \exists t_r | t_{\neg r} \leq t_r \leq t_t$ 3. From 2., and Definition 11 for $\overline{A}\Delta 2$, it follows that the violation is captured by $\overline{A}\Delta 2$.

We have shown that in both cases the violations identified by the decomposed by the decomposed Δ -constraints are violations identified by $\overline{A}\Delta 2$.

A.2 Maintenance Obligations to Failure Δ -constraints

Theorem 2. Given an execution ε , represented as a sequence of tasks, if ε satisfies either of the Maintenance Failure Δ -constraints (Definition 13), then ε violates the obligation related to the Maintenance Failure Δ -constraints.

Proof. Soundness:

First case: $\overline{M}\Delta 1$

- 1. From the hypothesis, and Definition 13, it follows that ε satisfies the following condition: (a) $\exists t_t | \exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \preceq t_r \preceq t_t$
- 2. From 1.(a), and Lemma 1, it follows that: t holds and r does not, after the execution of the task t_t annotated.
- 3. From 2. and Definition 12, it follows that ε would violate the obligation related to the Maintenance Failure Δ -constraints.

Second case: $\overline{M}\Delta 2$

- 1. From the hypothesis, and Definition 13, it follows that ε satisfies the following condition: (a) $\exists t_t | \exists t_r, \neg \exists t_{\neg r} | t_r \leq t_{\neg r} \leq t_t$ and
 - (b) $\exists t_t | \forall t_d (\exists t_{\neg r} | t_t \leq t_{\neg r} \prec t_d)$
- 2. From 1.(a), and Lemma 1, it follows that t holds and r holds, in the state holding after executing t_t .
- 3. From 1.(b), and Lemma 1, it follows that after executing the t_t , t it is always the case that in the following states r stops holding before d starts holding.
- 4. From 2. it follows that after the execution of the task t_t , r holds due to the constraint preventing a task having $\neg r$ annotated to be executed and cancelling r from the process state, which is already holding due to the execution of a task with r annotated.
- 5. From 3. it follows before the execution of any task having *d* in its annotation, a task having $\neg r$ annotated is executed, leading to the removal of *r* from the process state.
- From 4. and 5. and Definition 12, it follows that ε would violate the obligation related to the Maintenance Failure Δ-constraints.

Completeness:

- 1. Given a trace violating a given maintenance obligation.
- 2. From 1. and Definition 12 it follows that $\exists \sigma_t \forall \sigma_d \mid \text{contain}(t, \sigma)$ and $\sigma_t \preceq \sigma_d$ and $\exists \sigma_{\neg r} \mid \sigma_t \preceq \sigma_{\neg r} \preceq \sigma_d$.
- 3. From 2., it follows that a task with *t* annotated is executed.
- 4. From 2., it follows that a task with $\neg r$ annotated is executed.
- 5. Following from 3., and 4. two cases are possible:
 - $t_{\neg r} \leq t_t$ case covered by the $\overline{M}\Delta 1$ conditions in Definition 13.
 - $t_t \leq t_{\neg r}$ case covered by the $\overline{M}\Delta 2$ conditions in Definition 13.
- 6. Thus, all cases are covered and a violating trace is always identified by the Maintenance Failure Δ -constraints.

$\overline{M}\Delta 2$ Simplified

Theorem 7. If a violation in business process model is identified by satisfying either $\overline{M}\Delta 1$ or $\overline{M}\Delta 2$, then the same violation is identified by satisfying either $\overline{M}\Delta 1$ or $\overline{M}\Delta 2S$.

Proof. As both procedures identifying whether a regulation violates a business process model contain the constraint $\overline{M}\Delta 1$, we focus on proving soundness and completeness when the violation is identified by fulfilling the other constraint, respectively $\overline{M}\Delta 2$ and $\overline{M}\Delta 2S$.

- Soundness:
- 1. Given a violated obligation and satisfying $\overline{M}\Delta 2$.
- 2. From 1. and Definition 13 for $\overline{M}\Delta 2$, if follows that $\exists t_t$ such that: $\forall t_d (\exists t_{\neg r} | t_t \leq t_{\neg r} \prec t_d)$
- 3. Logically, $\exists t_t$ such that: $\forall t_d (\exists t_{\neg r} | t_t \leq t_{\neg r} \prec t_d) \equiv \exists t_t$ such that: $\exists t_{\neg r}, \neg \exists t_d | t_t \leq t_d \leq t_{\neg r}$
- 4. From 3., and Definition 24, it follows that the violation is identified by $\overline{M}\Delta 2S$.

Completeness:

- 1. Given a violated obligation and satisfying $\overline{M}\Delta 2S$.
- 2. From 1., and Definition 24, it follows that $\exists t_t$ such that: $\exists t_{\neg r}, \neg \exists t_d | t_t \leq t_d \leq t_{\neg r}$
- 3. We consider the two following mutually exclusive cases:
 - **case 1** : $\exists t_t$ such that: $\exists t_r, \neg \exists t_{\neg r} | t_r \leq t_{\neg r} \leq t_t$
 - 3.1.1 Logically, $\exists t_t$ such that: $\forall t_d (\exists t_{\neg r} | t_t \leq t_{\neg r} \prec t_d) \equiv \exists t_t$ such that: $\exists t_{\neg r}, \neg \exists t_d | t_t \leq t_d \leq t_{\neg r}$
 - 3.1.2 From **case 1**, 3.1.1, and Definition 13 for $\overline{M}\Delta 2$, it follows that the violation is identified by $\overline{M}\Delta 2$.
 - **case 2** : $\exists t_t$ such that: $\exists t_{\neg r}, \neg \exists t_r | t_{\neg r} \leq t_r \leq t_t$
 - 3.2.1 From case 2, and Definition 13 for $\overline{M}\Delta 1$, it follows that the violation is identified by $\overline{M}\Delta 1$.
- 4. Therefore in each case, it follows that a violation identified by $\overline{M}\Delta 2S$ would be identified by either $\overline{M}\Delta 1$ or $\overline{M}\Delta 2$.
B Stem Evaluation

Lemma 2. Given a process model P and a process block B contained in P. If B satisfies a failure Δ -constraint, then P satisfies the same Δ -constraint.

- *Proof.* 1. Assume that an execution ε in a process block *B* satisfies the constraints specified by a Δ -constraint.
- 2. Considering a process block B' containing B, we analyse three different cases depending on the type of B':
 - XOR The super block B' contains the execution ε , which directly follows from Definition 4.
 - SEQ Following from Definition 4, the super block B' contains an execution ε' which contains ε as part of its execution. Thus, as ε is part of ε' , ε' would also satisfy the same Δ -constraint as ε .
 - AND The fact that an execution belonging to the super block of this type, satisfies the same property satisfied by an execution of one of its sub blocks, follows from Lemma 6 and the case SEQ.
- 3. Independently on the case shown in 2., the Δ -constraint satisfied in an execution of *B* is also satisfied by an execution of *B'*.
- 4. Each case shown in 2. allows us to recursively apply them to each super blocks, which would lead to having the process model block, P, still satisfying the same Δ -constraint as one of its sub blocks B.

Lemma 3 (Stem Pruning). Given a tree representation \mathscr{P} of a business process P, and a task τ in P. Let \mathscr{P}' be \mathscr{P} where each XOR block on the path from the root to τ is substituted with its child leading to τ . The business process model P', corresponding to \mathscr{P}' , contains τ in each of its executions, and there are no executions in P that contain τ that are not appear in P'.

Proof. We first prove that each execution in P' contains τ . We prove it by contradiction.

- 1. Assume there exists an execution in P' that does not contain τ .
- 2. From construction, P' contains τ .
- 3. From 2. and Definition 4, it follows that exists an execution of P' containing τ .
- 4. From 1. and 3., it follows that P' contains at least an execution containing τ , and contains at least an execution not containing τ .
- 5. From 4., and Definition 4, it follows that P' contains a XOR block, X, having a sub-block containing τ , and a different sub-block not containing τ .
- 6. From 5., and Definition 14, it follows that *X* is on the path from the root to τ in \mathscr{P}' .
- 7. However, 6. contradicts the premises, as X would have been removed by construction.
- 8. Therefore, there cannot be an execution in P' not containing τ .

We prove now that every execution containing τ in *P*, is also an execution of *P'*. We prove it by contradiction.

- 1. Assume there is an execution in *P* containing τ , and such execution does not belong to the executions of *P'*.
- 2. We consider two possible cases:
 - There is at least an XOR on the path from the root to τ in ${\mathscr P}\,$:
 - (a) By construction, the difference between \mathscr{P} and \mathscr{P}' is only on the missing children of XOR nodes on the path from the root to τ .
 - (b) From the assumption 1., (a), and Definition 4, it follows that a children of one of the XOR on the path from the root to τ , has been removed and it leads to τ .
 - (c) In this case, (b) is in contradiction with both the construction, and both the uniqueness of a task τ .
 - There is not an XOR on the path from the root to τ in \mathscr{P} :
 - (a) By construction, then $\mathscr{P} \equiv \mathscr{P}'$.

- (b) From (a), and Definition 14, it follows that $P \equiv P'$.
- (c) From (b), and Definition 4, it follows that $\Sigma(P) \equiv \Sigma(P')$.
- (d) In this case, (c) is in contradiction with the assumption in 1.
- 3. We have shown in both cases a contradiction, hence every execution containing τ in *P*, is also an execution of *P'*.

Theorem 3 (Algorithm 1 Correctness). Given a business process model P and a failure Δ -constrain δ , if there exists an execution of P such that the execution satisfies δ , then Algorithm 1 returns true, otherwise it returns false.

Proof. Soundness

- 1. From line 1 and line 3, each task containing the obligation's trigger is considered.
- 2. From 1. lines 4 and 5, and Lemma 3, it follows that the pruning procedure does not remove executions containing the task considered as the *trigger leaf*.
- 3. Let the Evaluate function be true when the tree representation contains an execution satisfying δ , and false otherwise.¹⁰
- 4. From 2., and line 6, the function Evaluate is given a tree representation of a process containing each execution having the *trigger leaf*.
- 5. From 1., and 4., it follows that the Evaluate function considers every executions in *P* having a task with the obligation's trigger annotated.
- 6. From 3., and 5., it follows that if *P* contains an execution fulfilling δ , then Evaluate is evaluated true.
- 7. From 6., and lines 6 and 7, it follows that Algorithm 1 returns true when *P* contains an execution fulfilling δ .
- 8. From 6., and line 8, it follows that if *P* does not contain an execution fulfilling δ , then Algorithm 1 returns false.
- 9. From 7., and 8., it follows that Algorithm 1 returns the correct value depending whether *P* contains an execution satisfying δ .

Completeness

- 1. Depending on the output of Algorithm 1, we distinguish two cases:
 - **true** (a) Line 7 of Algorithm 1 is executed.
 - (b) From (a), it follows that Evaluate at line 6 is true at least once.
 - (c) From (b), and lines 1 and 2, it follows that \mathscr{P} contains an execution satisfying δ .
 - (d) From (c), and Definition 14, it follows that *P* contains an execution satisfying δ .
 - false (a) Line 8 of Algorithm 1 is executed.
 - (b) From (a), it follows that Evaluate at line 6 is always false.
 - (c) From line 1 and line 3, each task containing the obligation's trigger is considered.
 - (d) From (c), lines 4 and 5, and Lemma 3, it follows that the pruning procedure does not remove executions containing the task considered as the *trigger leaf*.
 - (e) From (d), and line 6, the function Evaluate is given a tree representation of a process containing each execution having the *trigger leaf*.
 - (f) From (c), and (e), it follows that the Evaluate function considers every executions in *P* having a task with the obligation's trigger annotated.
 - (g) From (b), and (f), it follows that non of the executions of *P* satisfy δ .
- 2. We have proven that in both cases, Algorithm 1 correctly recognises whether a business process *P* contains an execution satisfying δ .

¹⁰ Let Evaluate be a function calculating the bottom up aggregation of a node in a tree according to the classification of its children as shown by the aggregations shown in the tables in Appendix C.

C Aggregating the Evaluations

C.1 Left Sub-Pattern

Definition 25 (Left Sub-Pattern \mathbf{x}). Left side pattern fulfilling state: there exists an execution belonging to the process block containing *x*, and no *y* on its right.

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that: • $\exists x \in \varepsilon$ such that: * $\exists y \in \varepsilon$ such that $x \preceq y$.

Definition 26 (Left Sub-Pattern $\overset{0}{x}$). *neutral state: there exists an execution belonging to the process block, such that it does not contain x or y.*

Formally:

Given a process block B, it belongs to this class if and only if:

-
$$\exists \varepsilon \in \Sigma(B)$$
 such that:
• $\exists x, \in \varepsilon, and$

• $\exists y \in \varepsilon.$

Definition 27 (Left Sub-Pattern \mathbf{x}). blocking state: every execution belonging to the process block contains at least a y, and no x on its right.

Formally:

Given a process block B, it belongs to this class if and only if:

 $\begin{array}{l} - \forall \varepsilon \in \Sigma(B) \ such \ that: \\ \bullet \ \exists y \in \varepsilon \ such \ that: \\ & * \ \not\exists x \in \varepsilon \ such \ that \ y \preceq x. \end{array}$

Theorem 8 (Classification Completeness for Left Sub-Pattern). The set of possible evaluations of Left Sub-Pattern is completely covered by the provided set of classifications.

- *Proof.* 1. The pattern (*x*) in Left Sub-Pattern allows 3 possible evaluations: whether the partial requirement is satisfied, failing, or in a neutral state.
- 2. The 3 possible evaluations are completely covered by the 3 possible classifications.

Lemmas

Lemma 4 (Aggregation Neutral Class). Given a process block A, assigned to the evaluation class $\hat{\mathbf{x}}$, and another process block B, assigned to any of the available evaluation classes. Let C

be a process block having A and B as its sub-blocks, then the evaluation class of C is the same class as the process block B.

Proof. We prove Lemma 4 by contradiction.

- 1. Let A be a process block classified as \mathbf{x} .
- 2. Let *B* be a process block classified as one of the possible classifications.
- 3. Let *C* be a process block having *A* and *B* as its sub-blocks.
- 4. Assume that *C* is classified as a different class than the one that classifies *B*.
- 5. From 4., and Definition 26, it follows that the executions in *C* do not have the same properties as the executions in *B*.
- 6. From 5., it follows that *A* contains at least a serialisation capable of changing the properties of the serialisations in *B* when considered in the super-block *C*.

- 7. From 6., it follows that *A* must contain some tasks with some relevant literals in their annotation, in other words *x* or *y* must appear in at least one annotation of at least one of the tasks.
- 8. From 7. and the preference order: $\mathbf{\bar{x}} < \mathbf{\bar{x}} < \mathbf{\bar{x}}$, it follows that either exists an execution in *A* such that *A* belongs to one of the most preferred classes than 0, or each execution of *A* contains a *x* annotated in one of the appearing tasks, and it was not possible to assign it to any of the more preferred classes, hence it is assigned to $\mathbf{\bar{x}}$.
- 9. 1. and 8. are in contradiction, as the former assigns A to $\hat{\mathbf{x}}$, while the latter to any other class but not $\hat{\mathbf{x}}$.
- 10. From 9., it follows that a process classified as $\hat{\mathbf{x}}$ is a neutral element in any aggregation.

Lemma 5 (Aggregation Compositionality). Given a process block B having a list of sub-blocks: A_0, \ldots, A_n . The classification of B is the same as ordered pair aggregation of the classifications of its sub-blocks: $agg(\ldots (agg(agg(A_0, A_1), A_2) \ldots), A_n)$.

Proof. We prove Lemma 5 by cases:

For SEQ the order of the aggregation follows the execution order so is natural that compositionally aggregating does not affect the result.

For AND the order is irrelevant. The aggregation tables take care of keeping track of the best possible outcomes of the aggregations, allowing again compositionality.

Lemma 6 (Executions Inclusivity). Given two process blocks A and B, and two super-blocks SEQ(A,B) and AND(A,B), then $\Sigma(SEQ(A,B)) \subseteq \Sigma(AND(A,B))$.

Proof. Lemma 6 directly follows from Definition 4.

Aggregations

Finally, for the Left Sub-Pattern, the aggregation of the classifications of the children while evaluating an undernode, is described in Table 5. Notice that the aggregation is performed pair-wise left to right, with the result being aggregated with next brother on the right. The result depends on the classifications of the two children, or the result of a partial aggregation and a child, and the type of the parent undernode.

А	В	SEQ(A, B)	AND(A, B)
0	0	0	0
X	X	X	X
0	+	+	+
X	X	X	x
0 X	x	x	- x
\mathbf{x}^+	0	+	+
	X	X	X
+	+	+	+
X	X	X	X
\mathbf{x}^+	x	x	+ X
$\overline{\mathbf{x}}$	0 X	x	x
$\bar{\mathbf{x}}$	+	+	+
	X	X	X
x	x	x	x

Table 5: Aggregation Table Left Sub-Pattern

Proof (Table 5).

Considering the row in the table where A is $\overset{0}{\mathbf{x}}$ and B is $\overset{0}{\mathbf{x}}$

- **SEQ** 1. SEQ(A, B) is correctly classified $\hat{\mathbf{x}}$ according to Lemma 4.
- **AND** 1. AND(A, B) is correctly classified $\frac{9}{x}$ according to Lemma 4.

Considering the row in the table where A is $\overset{0}{\mathbf{x}}$ and B is $\overset{+}{\mathbf{x}}$

- **SEQ** 1. SEQ(A, B) is correctly classified $\overset{+}{\mathbf{x}}$ according to Lemma 4.
- **AND** 1. AND(A, B) is correctly classified $\overset{+}{\mathbf{x}}$ according to Lemma 4.

Considering the row in the table where A is $\hat{\mathbf{x}}$ and B is $\bar{\mathbf{x}}$

- **SEQ** 1. SEQ(A, B) is correctly classified $\overline{\mathbf{x}}$ according to Lemma 4.
- **AND** 1. AND(A, B) is correctly classified $\overline{\mathbf{x}}$ according to Lemma 4.

Considering the row in the table where A is $\overset{+}{\mathbf{x}}$ and B is $\overset{0}{\mathbf{x}}$

- **SEQ** 1. SEQ(A, B) is correctly classified \mathbf{x}^+ according to Lemma 4.
- **AND** 1. AND(A, B) is correctly classified $\overset{+}{\mathbf{x}}$ according to Lemma 4.

Considering the row in the table where A is $\overset{+}{\mathbf{x}}$ and B is $\overset{+}{\mathbf{x}}$

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(*A*,*B*) contains at least an *x* and no *y* on its right.
 - 3. From 2. and Definition 25, it follows that SEQ(*A*,*B*) is correctly classified as $\stackrel{+}{\mathbf{x}}$.
- **AND** 1. From Lemma 6 and the result for SEQ(*A*,*B*), we can conclude that AND(*A*,*B*) is correctly classified as $\stackrel{+}{\mathbf{x}}$

Considering the row in the table where A is $\mathbf{\dot{x}}$ and B is $\mathbf{\ddot{x}}$

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least an x and a y on its right.
 - 3. From 2. and Definition 27, it follows that SEQ(A, B) is correctly classified as \mathbf{x} .
- **AND** 1. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - 2. From 1. and Definition 4, it follows that each execution resulting from SEQ(*B*,*A*) is a subset of the executions of AND(*A*,*B*).
 - 3. From the hypothesis and 2., it follows that SEQ(B,A) contains at least an x and no y on its right.
 - 4. From 1., 3. and Definition 25, it follows that AND(A, B) is correctly classified as \mathbf{x}^+ .

Considering the row in the table where A is $\bar{\mathbf{x}}$ and B is $\bar{\mathbf{x}}$

SEQ 1. SEQ(A, B) is correctly classified $\overline{\mathbf{x}}$ according to Lemma 4.

AND 1. AND(A, B) is correctly classified \mathbf{x} according to Lemma 4.

Considering the row in the table where A is \mathbf{x} and B is \mathbf{x}^+

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least an x and no y on its right.
 - 3. From 2. and Definition 25, it follows that SEQ(A, B) is correctly classified as \mathbf{x} .
- **AND** 1. From Lemma 6 and the result for SEQ(*A*, *B*), we can conclude that AND(*A*, *B*) is correctly classified as $\stackrel{+}{\mathbf{x}}$

Considering the row in the table where A is $\overline{\mathbf{x}}$ and B is $\overline{\mathbf{x}}$

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least a y and no x on its right.
 - 3. From 2. and Definition 27, it follows that SEQ(A, B) is correctly classified as \mathbf{x} .
- **AND** 1. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - 2. From 1. and the hypothesis, it follows that independently on the execution order, a *x* on the right of a not *y* is not possible, while a *y* with no *x* on its right is guaranteed.
 - 3. From 2. and Definition 27, it follows that SEQ(A,B) is correctly classified as $\overline{\mathbf{x}}$.

C.2 Right Sub-Pattern

Definition 28 (Right Sub-Pattern \pm). *left side pattern fulfilling state: there exists an execution belonging to the process block containing z, and no y on its left. Formally:*

Given a process block B, it belongs to this class if and only if:

 $\begin{array}{l} - \exists \varepsilon \in \Sigma(B) \text{ such that:} \\ \bullet \exists z \in \varepsilon \text{ such that:} \\ &* \exists y \in \varepsilon \text{ such that } z \succeq y. \end{array}$

Definition 29 (**Right Sub-Pattern z**). *neutral state: there exists an execution belonging to the process block, such that it does not contain z or y.*

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that: • $\exists z \in \varepsilon$, and • $\exists y \in \varepsilon$.

Definition 30 (Right Sub-Pattern z). blocking state: every execution belonging to the process block contains at least a y, and no z on its right.

Formally:

Given a process block B, it belongs to this class if and only if:

 $\begin{array}{l} - \forall \varepsilon \in \Sigma(B) \text{ such that:} \\ \bullet \exists y \in \varepsilon \text{ such that:} \\ * \exists z \in \varepsilon \text{ such that } y \succeq z. \end{array}$

Theorem 9 (Classification Completeness for Right Sub-Pattern). The set of possible evaluations of Right Sub-Pattern is completely covered by the provided set of classifications.

- *Proof.* 1. The pattern (*z*) in Right Sub-Pattern allows 3 possible evaluations: whether the partial requirement is satisfied, failing, or in a neutral state.
- 2. The 3 possible evaluations are completely covered by the 3 possible classifications.

Lemmas

Lemma 7 (Aggregation Neutral Class). Given a process block A, assigned to the evaluation

class $\overset{0}{\mathbf{z}}$, and another process block *B*, assigned to any of the available evaluation classes. Let *C* be a process block having *A* and *B* as its sub-blocks, then the evaluation class of *C* is the same class as the process block *B*.

Proof. This proof follows closely the proof for Lemma 4

Aggregations

Similarly for the left sub-pattern, we illustrate how an undernode is classified on the right side of the stem using the right sub-pattern in a table. The aggregation is shown in Table 6.

Proof (Table 6).

Considering the row in the table where A is $\mathbf{\ddot{z}}$ and B is $\mathbf{\ddot{z}}$

SEQ 1. SEQ(A, B) is correctly classified $\frac{0}{2}$ according to Lemma 7.

AND 1. AND(A, B) is correctly classified $\frac{9}{2}$ according to Lemma 7.

А	В	SEQ(A, B)	AND(A, B)
0 Z	0 Z	0 Z	0 Z
0 Z	^+z	+z	\mathbf{z}^+
0 Z	z	¯z	¯z
\mathbf{z}^+	0 Z	+z	+ Z
+ Z	+ Z	+ Z	+ Z
\mathbf{z}^+	z	+ Z	+ Z
$\bar{\mathbf{z}}$	0 Z	z	¯z
$\bar{\mathbf{z}}$	+ Z	z	+ Z
z	z	z	z

Table 6: Aggregation Table Right Sub-Pattern

Considering the row in the table where A is $\overset{0}{z}$ and B is $\overset{+}{z}$

- **SEQ** 1. SEQ(A, B) is correctly classified $\stackrel{+}{\mathbf{z}}$ according to Lemma 7.
- **AND** 1. AND(A, B) is correctly classified $\stackrel{+}{\mathbf{z}}$ according to Lemma 7.

Considering the row in the table where A is \hat{z}^0 and B is \bar{z}

- **SEQ** 1. SEQ(A, B) is correctly classified \overline{z} according to Lemma 7.
- **AND** 1. AND(A, B) is correctly classified \overline{z} according to Lemma 7.

Considering the row in the table where A is $\overset{+}{z}$ and B is $\overset{0}{z}$

- **SEQ** 1. SEQ(A, B) is correctly classified $\stackrel{+}{\mathbf{z}}$ according to Lemma 7.
- **AND** 1. AND(A, B) is correctly classified $\stackrel{+}{\mathbf{z}}$ according to Lemma 7.

Considering the row in the table where A is $\stackrel{+}{z}$ and B is $\stackrel{+}{z}$

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least an z and no y on its left.
 - 3. From 2. and Definition 28, it follows that SEQ(A,B) is correctly classified as $\stackrel{+}{\mathbf{z}}$.
- **AND** 1. From Lemma 6 and the result for SEQ(*A*,*B*), we can conclude that AND(*A*,*B*) is correctly classified as $\stackrel{+}{\mathbf{z}}$

Considering the row in the table where A is $\stackrel{+}{z}$ and B is $\stackrel{-}{z}$

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least an *z* and no *y* on its left.
 - 3. From 2. and Definition 28, it follows that SEQ(A, B) is correctly classified as $\stackrel{+}{\mathbf{z}}$.
- **AND** 1. From Lemma 6 and the result for SEQ(*A*,*B*), we can conclude that AND(*A*,*B*) is correctly classified as $\stackrel{+}{\mathbf{z}}$

Considering the row in the table where A is \bar{z} and B is \bar{z}

- **SEQ** 1. SEQ(A, B) is correctly classified \overline{z} according to Lemma 7.
- **AND** 1. AND(A, B) is correctly classified \overline{z} according to Lemma 7.

Considering the row in the table where A is \overline{z} and B is \overline{z}

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least an z and a y on its left.
 - 3. From 2. and Definition 30, it follows that SEQ(A,B) is correctly classified as \overline{z} .
- **AND** 1. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of *A* interleaved with an execution of *B*.
 - 2. From 1. and Definition 4, it follows that each execution resulting from SEQ(*B*,*A*) is a subset of the executions of AND(*A*,*B*).
 - 3. From the hypothesis and 2., it follows that SEQ(B,A) contains at least an z and no y on its left.
 - 4. From 1., 3. and Definition 28, it follows that AND(A,B) is correctly classified as $\stackrel{+}{\mathbf{z}}$.

Considering the row in the table where A is \overline{z} and B is \overline{z}

- **SEQ** 1. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - 2. From the hypothesis and 1., it follows that SEQ(A,B) contains at least a y and no z on its left.
 - 3. From 2. and Definition 30, it follows that SEQ(A,B) is correctly classified as \overline{z} .

AND 1. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of *A* interleaved with an execution of *B*.

- 2. From 1. and the hypothesis, it follows that independently on the execution order, a *z* on the right of a not *y* is not possible, while a *y* with no *z* on its right is guaranteed.
- 3. From 2. and Definition 30, it follows that SEQ(A,B) is correctly classified as \overline{z} .

C.3 Interval Sub-Pattern

Definition 31 $(\stackrel{++}{\underline{xz}})$. Closed interval class: there exists an execution belonging to the process block containing x and z on its right, while having no y in-between. *Formally*:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

• $\exists x, z \in \varepsilon$ such that $x \prec z$, and

• $\exists y \in \varepsilon$ such that $x \leq y \leq z$.

Definition 32 (\underline{xz}) . Left side pattern fulfilling state: there exists an execution belonging to the process block containing x, and no y on its right.

Formally:

Given a process block B, it belongs to this class if and only if:

 $\begin{array}{l} - \exists \varepsilon \in \Sigma(B) \ \text{such that:} \\ \bullet \ \exists x \in \varepsilon \ \text{such that:} \\ &* \ \nexists z \in \varepsilon \ \text{such that } x \prec z, \ \text{and} \\ &* \ \nexists y \in \varepsilon \ \text{such that } x \preceq y. \end{array}$

Definition 33 $(\underline{xz})^{0+}$. *Right side pattern fulfilling state: there exists an execution belonging to the process block containing z, and no y on its left.*

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists z \in \varepsilon$ such that:
 - * $\not\exists x \in \varepsilon$ such that $x \prec z$, and
 - * $\not\exists y \in \varepsilon$ such that $y \leq z$.

Definition 34 $(\stackrel{+}{\mathbf{x}} \overline{\mathbf{z}})$. Left side pattern right blocked state: there exists an execution belonging to the process block containing *x*, and *y* on its right.

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

• $\exists x \in \varepsilon$ such that:

* $\exists z \in \varepsilon$ such that $x \prec z$, and

*
$$\exists y \in \varepsilon$$
 such that $x \leq y$.

Definition 35 (\underline{xz}) . Neutral state: there exists an execution belonging to the process block, such that it does not contain *x*, *y*, or *z*. *Formally*:

Given a process block B, it belongs to this class if and only if:

-
$$\exists \varepsilon \in \Sigma(B)$$
 such that:
• $\not\exists y, x, z \in \varepsilon$.

Definition 36 $(\bar{x}\bar{z})$. *Right side pattern left blocked state: there exists an execution belonging to the process block containing z, and y on its left. Formally:*

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that: • $\exists z \in \varepsilon$ such that: * $\exists x \in \varepsilon$ such that $x \prec z$, and * $\exists y \in \varepsilon$ such that $y \preceq z$.

Definition 37 $(\mathbf{x}\mathbf{z})$. Blocking state: every execution belonging to the process block contains y, and no x or z.

Formally:

Given a process block B, it belongs to this class if and only if:

- $\forall \varepsilon \in \Sigma(B)$ such that: • $\exists y \in \varepsilon$.

Theorem 10 (Classification Completeness for Interval Sub-Pattern). The set of possible evaluations of Interval Sub-Pattern is completely covered by the provided set of classifications.

- *Proof.* 1. The two sides of the pattern, the left (x) and on the right (z), in Interval Sub-Pattern allow 3 possible evaluations each: whether the partial requirement is satisfied, failing, or in a neutral state.
- 2. While the sides of the pattern share the same undesired element (y), the two sides are virtually independent as their evaluation is not influenced directly by the evaluation of the other side of the pattern, but only by the presence of the undesired element and their own required element.
- 3. From 1. and the independence from 2., it follows that the amount of possible combinations in Interval Sub-Pattern is 3², hence 9 possible combinations. Moreover the case from 2. is also covered within the 9 combinations.
- 4. Therefore, every possible evaluation of Interval Sub-Pattern is captured by one of the 9 provided classifications.

Lemmas

Lemma 8 (Aggregation Neutral Class). Given a process block A, assigned to the evaluation

class $\frac{00}{XZ}$, and another process block B, assigned to any of the available evaluation classes. Let C be a process block having A and B as its sub-blocks, then the evaluation class of C is the same class as the process block B.

Proof. This proof follows closely the proof for Lemma 4

Lemma 9 (AND Commutativity). Given two process blocks A and B, the executions of AND(A, B) are the same as AND(B,A).

Proof. The correctness of Lemma 9 follows directly from Definition 4.

Lemma 10 (Class $\frac{++}{xz}$ Aggregation). Given a process block A classified as $\frac{++}{xz}$ and another process block B with any classification, aggregating A and B, independently than the order and the type of their super-block always results in being classified as \mathbf{x}^{++}

Proof. Considering the case where the aggregation is made through a super-block of type SEQ, according to Definition 4, the aggregation of the executions corresponds to the concatenation of the executions in the sub blocks. From the hypothesis we know that there is an execution satisfying the requirements to be classified as $\frac{++}{xz}$.

Independently than the order of aggregation, from Definition 31, we can see that the concatenation does not influence the properties allowing to classify the aggregation as $\frac{++}{xz}$, and as shown in Figure 17, given that $\frac{t}{xz}$ is the top ranked classification, then the aggregation can be correctly classified as $\mathbf{x}\mathbf{z}$.

The correctness of the case concerning a super block of type AND follows directly from the previous case and Lemma 6.

Aggregations

The aggregation of the classes used to evaluate undernodes while evaluating an overnode of type AND are contained in Tables $7, \ldots, 13$.

А	В	SEQ(A, B)	AND(A, B)
00	00	00	00
XZ	XZ	<u>XZ</u>	<u>XZ</u>
00 XZ		xz	XZ
00	+0	+0	+0
XZ	XZ	xz	xz
00	+-	+-	+-
XZ	X Z	xz	xz
00	0+	0+	0+
XZ	XZ	xz	xz
00	$\frac{-+}{\mathbf{x}\mathbf{z}}$	-+	
XZ		x z	xz
00	++	++	++
XZ	X Z	x z	X Z

Table 7: Aggregation Table from Interval Sub-Pattern Evaluation Classes

Proof (Table 7). As each of the aggregations shown in Table 7 contains at least an element belonging to the aggregation class \underline{xz} , the correctness of the columns SEQ and AND follows directly from Lemma 8.

А	В	SEQ(A, B)	AND(A, B)
<u>xz</u>	00 <u>XZ</u>	<u></u>	<u></u>
	<u>xz</u>	<u></u>	<u></u>
	+0 XZ	+0 <u>xz</u>	+0 <u>XZ</u>
<u>xz</u>	+- xz	$\frac{+-}{\mathbf{x}\mathbf{z}}$	$\frac{+-}{\mathbf{X}\mathbf{Z}}$
	0+ XZ	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{0+}{XZ}$
<u>xz</u>	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$
	$\frac{++}{XZ}$	++ <u>X Z</u>	++ xz

Table 8: Aggregation Table from Interval Sub-Pattern Evaluation Classes

Proof (Table 8).

- 1. From Definition 37, and column **A** of the table, it follows that each execution of the process block *A* contains a task having *y* annotated, and no other literals beneficial towards the pattern fulfilment.
- 2. We prove the correctness by case, depending on the class assigned to the process block in column **B**, each row of the table and each of the two different types of aggregation.
 - **<u>00</u>** Independently on the type of the process block, the correctness of the row follows directly from Lemma 8.

- $\mathbf{x}\mathbf{z}$ (a) From Definition 37, and the classification of the process block in the column **B** of the table, it follows that each execution of **B** contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.
 - SEQ i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that each possible execution of SEQ(A, B)contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.
 - iii. From ii., and Definition 37, it follows that the process block resulting from SEQ(A, B) is correctly classified as \overline{xz} .
 - **AND** i. From Definition 4, it follows that each execution resulting from AND(A, A)B) consists of an execution of A interleaved with an execution of B.
 - ii. From i., 1., and (a), it follows that each possible execution of AND(A, B)contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.
 - iii. From ii., and Definition 37, it follows that the process block resulting from AND(A,B) is correctly classified as \overline{xz} .
- $\frac{+0}{xz}$ (a) From Definition 32, and the classification of the process block in the column **B** of
 - the table, it follows that there exists an execution belonging to the process block containing a task having x annotated, and no task on its right having y annotated.
 - SEQ i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to SEQ(A,B) containing a task having x annotated, and no task on its right having y annotated. This because the y appearing in each execution of A always appears on the left of each whole execution of B.
 - iii. From ii., and Definition 32, it follows that the process block resulting from SEQ(A,B) is correctly classified as $\frac{+0}{\underline{xz}}$.
 - AND i. From the SEQ case result, and Lemma 6, it follows that AND(A, B) can
 - be classified as $\frac{\dot{x}}{xz}$ or better. ii. From the preference lattice in Figure 17 and Definition 31, it follows that for AND(A, B) to achieve a better class than $\frac{+0}{xz}$, it requires a z annotated in one of its tasks.
 - iii. From (a), and Definition 32, it follows that B does not contain z in its tasks annotations, otherwise it would be assigned to a better class.
 - iv. From 1., and iii., it follows that AND(A, B) does not contain tasks having z annotated.
 - v. From i., ii., and iv., it follows that AND(A, B) is correctly classified as $\frac{+0}{xz}$.
- $\mathbf{x}\mathbf{z}$ (a) From Definition 34, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having x annotated, and a task on its right having y annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having x annotated, and a task on its right having y annotated. This because the y appearing in each execution of A always appears on the left of each whole execution of B, hence not influencing the execution order of the tasks on the right side of the task having x annotated.

- iii. From ii., and Definition 34, it follows that the process block resulting from SEQ(A,B) is correctly classified as $\frac{+}{xz}$.
- **AND** i. From the **SEQ** case result, and Lemma 6, it follows that AND(A, B) can be classified as $\frac{+-}{xz}$ or better.
 - ii. From the preference lattice in Figure 17 and Definition 31, it follows that for AND(A, B) to achieve a better class than $\frac{x}{xz}$, it requires either a *z* annotated in one of its tasks, or an execution not having a *y* annotated on the right of a task having *x* annotated.
 - iii. From (a), and Definition 34, it follows that B does not contain a z not preceded by a y after the x in its tasks' annotations, otherwise it would be assigned to a better class.
 - iv. From 1., and iii., it follows that AND(*A*,*B*) does not contain tasks having *z* annotated.
 - v. From (a), and Definition 34, it follows that *B* does not contain an execution having a task with *x* annotated and no task on its right with *y* annotated, otherwise *B* would be classified as $\frac{*0}{xz}$.
 - vi. From v., and Definition 4, it follows that AND(A, B) does not contain an execution not having a *y* annotated on the right of a task having *x* annotated.
 - vii. From i., ii., iv., and vi., it follows that AND(A,B) is correctly classified as $\frac{+-}{XZ}$.
- (a) From Definition 33, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and no tasks on its left having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and a task on its left having *y* annotated. This because the *y* appearing in each execution of *A* always appears on the left of each whole execution of *B*, hence influencing the execution on the left side of the task having *z* annotated.
 - iii. From ii., and Definition 36, it follows that the process block resulting from SEQ(A,B) is correctly classified as $\frac{x}{x}$.
 - AND i. From Definition 4, it follows that each execution resulting from AND(*A*, *B*) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From i., it follows that an execution of *B* followed by an execution of *A* is a valid execution of AND(A, B).
 - iii. From ii., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having z annotated, and no task on its left having y annotated. This because the y appearing in each execution of A can always be put on the right of an execution of A, hence not influencing the execution on the left side of the task having z annotated.
 - iv. From iii., and Definition 33, it follows that the process block resulting from AND(A,B) is correctly classified as $\frac{0+}{xz}$.
- (a) From Definition 36, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having z annotated, and having another task on its left having y annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.

- ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and a task on its left having *y* annotated. This corresponds to the original class of *B*, as the *y* from *A* does not alter the initial properties of *B*.
- iii. From ii., and Definition 36, it follows that the process block resulting from SEQ(A, B) is correctly classified as \overline{xz} .
- AND i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having z annotated, and a task on its left having y annotated. This corresponds to the original class of B, as no matter the interleaving chosen, in particular where the y from the execution of A would be positioned within the execution of B, it would not change its properties.
 - iii. From ii., and Definition 36, it follows that the process block resulting from AND(A, B) is correctly classified as $\frac{\overline{xz}}{\overline{xz}}$.
- $\frac{z}{z}$ (a) Independently on the type of the process block, the correctness of the row follows directly from Lemma 10.
- 3. We have shown that, for each row the SEQ and AND aggregation between the states correctly aggregates in the described result
- 4. The correctness of column XOR follows directly from the preference order defined in the lattice shown in Figure 17.
- 5. From 3., and 4., it follows that the Aggregations in Table 8 are correct.

А	В	SEQ(A, B)	AND(A, B)
+0	00	+0	+0
XZ	XZ	<u>xz</u>	<u>xz</u>
+0		<u>+-</u>	+0
XZ		<u>xz</u>	<u>xz</u>
+0	+0	+0	+0
XZ	XZ	<u>xz</u>	xz
+0	+-	<u>+-</u>	+0
XZ	x z	<u>xz</u>	<u>xz</u>
+0	0+	<u>++</u>	$\frac{++}{\mathbf{x}\mathbf{z}}$
XZ	XZ	<u>xz</u>	
+0 <u>XZ</u>	$\frac{-+}{\mathbf{x}\mathbf{z}}$	$\frac{\mathbf{x}}{\mathbf{x}\mathbf{z}} / \frac{\mathbf{x}}{\mathbf{x}\mathbf{z}}$	$\frac{++}{\mathbf{X}\mathbf{Z}}$
+0	++	++	++
xz	X Z	X Z	X Z

Table 9: Aggregation Table from Interval Sub-Pattern Evaluation Classes

Proof (Table 9).

- 1. From Definition 32, and column \mathbf{A} of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and no task on its right having *y* annotated.
- 2. We prove by case each row of the table and each of the two different types of aggregation.
 - $\frac{00}{xz}$ Independently on the type of the process block, the correctness of the row follows directly from Lemma 8.
 - <u>xz</u> (a) From Definition 37, and the classification of the process block in the column **B** of the table, it follows that each execution of **B** contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.

- **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and a task on its right having *y* annotated. This because the *y* appearing in each execution of *B* always appears on the right of each whole execution of *A*.
 - iii. From ii., and Definition 34, it follows that the process block resulting from SEQ(A, B) is correctly classified as $\frac{+-}{xz}$.
- **AND** i. From Lemma 9, and row $\frac{\overline{xz}}{xz} \frac{+0}{xz}$ of Table 8, it follows that the process block resulting from AND(*A*, *B*) is correctly classified as $\frac{+0}{xz}$.
- $\frac{+0}{xz}$ (a) From Definition 32, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and no task on its right having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and no task on its right having *y* annotated. This because there is an execution of *B* that without *y* that can follow each execution of *A*.
 - iii. From ii., and Definition 32, it follows that the process block resulting from SEQ(A,B) is correctly classified as ⁺⁰/<u>xz</u>.
 AND i. From the SEQ case result, and Lemma 6, it follows that AND(A,B) can
 - **ND** i. From the **SEQ** case result, and Lemma 6, it follows that AND(A,B) can be classified as $\frac{+0}{xz}$ or better.
 - ii. From the preference lattice in Figure 17, it follows that for AND(A, B) to achieve a better class than $\frac{+0}{xz}$, it requires a *z* annotated in one of its tasks.
 - iii. From (a), and Definition 32, it follows that both A and B do not contain z in its tasks annotations, otherwise they would be assigned to a better class.
 - iv. From 1., and iii., it follows that AND(*A*,*B*) does not contain tasks having *z* annotated.
 - v. From i., ii., and iv., it follows that AND(*A*,*B*) is correctly classified as $\frac{+0}{xz}$.
- (a) From Definition 34, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and a task on its right having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and a task on its right having *y* annotated. This because the executions of *B* are not influenced by the executions of *A* as they appear on their left side.
 - iii. From ii., and Definition 34, it follows that the process block resulting from SEQ(A, B) is correctly classified as $\frac{+-}{xz}$.
 - **AND** i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - ii. From i., it follows that an execution of *B* followed by an execution of *A* is a valid execution of AND(*A*, *B*).
 - iii. From ii., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and no task on its right

having y annotated. This because the executions of A are not influenced by the executions of B as they appear on their left side.

iv. From iii., and Definition 32, it follows that the process block resulting from AND(A,B) is correctly classified as $\frac{+0}{xz}$

- $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having z annotated, and no tasks on its left having y annotated.
 - SEQ i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having x annotated and another task on its right having z annotated, while having no task in-between having y annotated. As appending the execution of B to an execution of A completes the interval without including any y in-between.
 - iii. From ii., and Definition 31, it follows that the process block resulting from SEQ(A, B) is correctly classified as $\frac{++}{xz}$.
 - AND i. From the SEQ case result, and Lemma 6, it follows that AND(A, B) can be correctly classified as $\frac{++}{xz}$.
- (a) From Definition 36, and the classification of the process block in the column **B** of хż the table, it follows that there exists an execution belonging to the process block containing a task having z annotated, and having another task on its left having y annotated.
 - SEQ i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution belonging to the process block containing a task having x annotated and another task on its right having z annotated, while having at least task in-between having y annotated. As appending the execution of B to an execution of A completes the interval and including any y from the execution of B in-between.
 - iii. From ii., Definition 34 and Definition 36, it follows that the process block resulting from SEQ(A, B) is correctly classified as both $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$.
 - **AND** i. From Definition 4, it follows that each execution resulting from AND(A, A)B) consists of an execution of A interleaved with an execution of B.
 - ii. From i., 1., and (a), it follows that an execution of A can be preceded by the part of the execution of B containing y, and followed by the remainder of that execution containing z.
 - iii. From ii., it follows that there exist an execution of AND(A,B) having a task with x annotated and another task on its right having z annotated, without having a task in-between having y annotated.
 - iv. From iii., and Definition 31, it follows that the process block resulting from AND(A, B) is correctly classified as $\overset{++}{\mathbf{x}\mathbf{z}}$.
- $\frac{++}{xz}$ (a) Independently on the type of the process block, the correctness of the row follows directly from Lemma 10.
- 3. We have shown that, for each row the SEQ and AND aggregation between the states correctly aggregates in the described result
- 4. The correctness of column XOR follows directly from the preference order defined in the lattice shown in Figure 17.
- 5. From 3., and 4., it follows that the Aggregations in Table 9 are correct.

Proof (Table 10).

А	В	SEQ(A, B)	AND(A, B)
+- X Z	00 <u>XZ</u>	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	$\frac{+-}{\mathbf{x}\mathbf{z}}$
+- X Z	<u></u>	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	$\frac{+-}{\mathbf{X}\mathbf{Z}}$
+- x z	+0 xz	$\frac{+0}{XZ}$	+0 <u>xz</u>
+- X Z	+- X Z	$\frac{+-}{\mathbf{x}\mathbf{z}}$	$\frac{+-}{\mathbf{X}\mathbf{Z}}$
+- X Z	0+ XZ	$\frac{\mathbf{x}}{\mathbf{x}\mathbf{z}} / \frac{\mathbf{x}}{\mathbf{x}\mathbf{z}}$	$\frac{++}{\mathbf{X}\mathbf{Z}}$
+- X Z	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{\mathbf{x}}{\mathbf{x}\mathbf{z}} / \frac{\mathbf{x}}{\mathbf{x}\mathbf{z}}$	++ <u>xz</u>
+- × 7	++	++	++

 Table 10: Aggregation Table from Interval Sub-Pattern Evaluation Classes

- 1. From Definition 34, and column A of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and a task on its right having *y* annotated.
- 2. We prove by case each row of the table and each of the two different types of aggregation.
 - **<u>00</u>** <u>**xz**</u> Independently on the type of the process block, the correctness of the row follows directly from Lemma 8.
 - \underline{xz} (a) From Definition 37, and the classification of the process block in the column **B** of the table, it follows that each execution of **B** contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A, B) containing x and followed by at least a y.
 - iii. From ii. and Definition 34, it follows that SEQ(A, B) can be correctly classified as $\frac{+-}{xz}$.
 - **AND** i. From Lemma 9, it follows that AND(A, B) is classified as the same class as the row $\overline{xz} \times \overline{xz}$ in Table 8, which is correctly \overline{xz} .
 - $\frac{\mathbf{x}}{\mathbf{x}}$ (a) From Definition 32, and the classification of the process block in the column **B** of
 - the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and no task on its right having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From 1., (a) and i., it follows that there is an execution in SEQ(A, B) having the execution of *B*, where there is a *x* and no *y* on its right, as its tail.
 - iii. From ii. and Definition 32, it follows that SEQ(A, B) is correctly classified as $\frac{+0}{xZ}$.
 - **AND** i. From Lemma 9, it follows that AND(*A*, *B*) is classified as the same class as the row $\frac{+0}{xZ} \frac{+-1}{xZ}$ in Table 9, which is correctly $\frac{+0}{xZ}$.
 - $\mathbf{x}\mathbf{z}$ (a) From Definition 34, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and a task on its right having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.

- ii. From 1., (a) and i., it follows that there is an execution in SEQ(A, B) having the execution of *B*, where there is a *x* and a *y* on its right, as its tail.
- iii. From ii. and Definition 34, it follows that SEQ(A, B) is correctly classified as $\frac{+-}{xz}$.
- AND i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - ii. From Lemma 6 and the result for the SEQ case, it follows that the classification of AND(*A*,*B*) cannot be worse than $\frac{+-}{xz}$.
 - iii. From 1. and (a), it follows that none of the executions identified by the classifications contain a z.
 - iv. From 1. and (a), it follows that none of the executions identified by the classifications contain a *x* without a *y* on its right.
 - v. From i., iii., iv. and the preference order in Figure 17, it follows that there cannot be a better classification than $\frac{+z}{\mathbf{x}\mathbf{z}}$.
 - vi. From ii. and v., it follows that AND(A, B) is correctly classified as $\frac{+-}{xz}$.
- (a) From Definition 33, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and no tasks on its left having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From 1., (a) and i., it follows that there is an execution composed by a classified execution in *A* followed by a classification in *B* where there is a *x*, with a *y* on its right, and a *z* on the right of the *y*.
 - iii. From ii. and Definition 34, it follows that SEQ(A, B) is correctly classified as $\frac{+}{xz}$.
 - iv. From ii. and Definition 36, it follows that SEQ(A, B) is correctly classified as $\frac{-+}{\mathbf{x}\mathbf{z}}$.
 - AND i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - ii. From 1., (a) and i., it follows that the execution of *A*, having *x* and a *y* on its right, can be interleaved with the execution from *B* containing a *z*, and the *z* from *B* can be placed in the resulting execution between the *x* and *y* from *A*.
 - iii. From ii. and Definition 31, it follows that AND(A, B) is correctly classified as $\stackrel{++}{\mathbf{x}}$.
- (a) From Definition 36, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having z annotated, and having another task on its left having y annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From 1., (a) and i., it follows that there is an execution composed by a classified execution in *A* followed by a classification in *B* where there is a *x*, with a *y* on its right, and a *z* on the right of the *y*.
 - iii. From ii. and Definition 34, it follows that SEQ(A, B) is correctly classified as $\stackrel{+}{\mathbf{x}}$.
 - iv. From ii. and Definition 36, it follows that SEQ(A, B) is correctly classified as $\frac{x}{xz}$.

- AND i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - ii. From 1., (a) and i., it follows that the execution of A, having x and a y on its right, can be interleaved with the execution from B containing a z, and the z from B can be placed in the resulting execution between the x and y from A.
 - iii. From ii. and Definition 31, it follows that AND(A, B) is correctly classified as $\stackrel{++}{\mathbf{xz}}$.
- (a) Independently on the type of the process block, the correctness of the row follows directly from Lemma 10.
- We have shown that, for each row the SEQ and AND aggregation between the states correctly aggregates in the described result
- 4. The correctness of column XOR follows directly from the preference order defined in the lattice shown in Figure 17.
- 5. From 3., and 4., it follows that the Aggregations in Table 10 are correct.

Α	В	SEQ(A, B)	AND(A, B)
0+ XZ	00 XZ	$\frac{0+}{XZ}$	$\frac{0+}{XZ}$
0+ XZ	xz	$\overline{\begin{array}{c} 0+\\ \mathbf{xz} \end{array}}$	$\overline{\begin{array}{c} 0+\\ \mathbf{xz} \end{array}}$
0+	+0	$\frac{0}{xz}$ / $\frac{+0}{xz}$	++
XZ	XZ		xz
0+ XZ	$\frac{+-}{XZ}$	$\frac{0}{xz} / \frac{+}{xz}$	++ XZ
0+	0+	0+	0+
XZ	XZ	xz	xz
0+	$\frac{-+}{\mathbf{x}\mathbf{z}}$	0+	0+
XZ		xz	xz
0+	++	++	++
xz	X Z	X Z	XZ

Table 11: Aggregation Table from Interval Sub-Pattern Evaluation State

Proof (Table 11).

- 1. From Definition 33, and column \mathbf{A} of the table, it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and no task on its left having *y* annotated.
- 2. We prove by case each row of the table and each of the two different types of aggregation.
 - **<u>00</u>** Independently on the type of the process block, the correctness of the row follows directly from Lemma 8.
 - <u>xz</u> (a) From Definition 37, and the classification of the process block in the column **B** of the table, it follows that each execution of **B** contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A, B) containing z and no y on its left, as each execution from B is appended on the right.
 - iii. From ii. and Definition 33, it follows that SEQ(A, B) can be correctly classified as $\frac{\mathbf{0}_{+}}{\mathbf{x}\mathbf{z}}$.

- **AND** i. From Lemma 9, it follows that AND(A, B) is classified as the same class as the row $\frac{xz}{xz} \frac{0+}{xz}$ in Table 8, which is correctly $\frac{0+}{xz}$
- $\overset{+0}{xz}$ (a) From Definition 32, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having x annotated, and no task on its right having y annotated.
 - SEQ i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A, B)containing z and a x on its right, as each execution from B is appended on the right. While the x has no y on its right, and z has no y on its left.
 - iii. From ii. and Definition 33, it follows that SEQ(A, B) can be correctly classified as $\frac{0+}{xz}$.
 - iv. From ii. and Definition 32, it follows that SEQ(A, B) can be correctly classified as $\frac{+0}{xz}$.
 - v. From iii., iv. and the priority ordering in Figure 17, it follows that SEQ(A, B)
 - is correctly classified as both $\frac{\pm 0}{XZ}$ and $\frac{0+}{XZ}$. **AND** i. From Lemma 9, it follows that AND(*A*,*B*) is classified as the same class as the row $\frac{+0}{xz} \frac{0}{xz}$ in Table 9, which is correctly $\frac{++}{xz}$.
- $\frac{1}{xz}$ (a) From Definition 34, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having x annotated, and a task on its right having y annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A, B)containing z and a x on its right, which in turn has a y on its right, as each execution from B is appended on the right.
 - iii. From ii. and Definition 33, it follows that SEQ(A, B) can be correctly classified as $\overset{0+}{xz}$.
 - iv. From ii. and Definition 34, it follows that SEQ(A, B) can be correctly classified as $\underline{\mathbf{x}}\mathbf{z}$.
 - v. From iii., iv. and the priority ordering in Figure 17, it follows that SEQ(A, B)
 - is correctly classified as both $\frac{+}{xz}$ and $\frac{0+}{xz}$. **AND** i. From Lemma 9, it follows that AND(*A*,*B*) is classified as the same class as the row $\frac{\mathbf{x}}{\mathbf{x}} \frac{\mathbf{0}}{\mathbf{x}\mathbf{z}}$ in Table 10, which is correctly $\frac{\mathbf{x}}{\mathbf{x}}$.
- $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having z annotated, and no tasks on its left having y annotated.
 - SEQ i. From Definition 4, it follows that the possible executions of a process block SEQ(A, B) are the concatenation of an execution of A and an execution of B.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A, B)containing z and no y on its left.
 - iii. From ii. and Definition 33, it follows that SEQ(A, B) can be correctly classified as $\frac{0+}{xz}$.
 - **AND** i. From Definition 4, it follows that each execution resulting from AND(A, B)consists of an execution of A interleaved with an execution of B.
 - ii. From i., 1., and (a), it follows that the aggregated execution does not contain a *x*.

- iii. From Lemma 6 and the result from the SEQ column, it follows that AND(*A*, *B*) is at least classified as $\frac{0+}{xz}$.
- iv. From ii., Definition 33, Definition 31 and the preference ordering of the classes in Figure 17, it follows that AND(A, B) is classified as $\frac{\mathbf{0}_{+}}{\mathbf{x}\mathbf{z}}$ at best as no *x* is contained.
- v. From iii. and iv., it follows that SEQ(*A*,*B*) can be correctly classified as $\frac{\mathbf{0}_{+}}{\mathbf{x}\mathbf{z}}$.
- (a) From Definition 36, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having z annotated, and having another task on its left having y annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A,B) containing z and no y on its left, since the execution containing y is appended on the right.
 - iii. From ii. and Definition 33, it follows that SEQ(A,B) can be correctly classified as $\overset{0+}{\mathbf{xz}}$.
 - **AND** i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From i., 1., and (a), it follows that the aggregated execution does not contain a *x*.
 - iii. From Lemma 6 and the result from the SEQ column, it follows that AND(A, B) is at least classified as $\frac{0+}{XZ}$.
 - iv. From ii., Definition 33, Definition 31 and the preference ordering of the classes in Figure 17, it follows that AND(A, B) is classified as $\frac{\mathbf{0}_{+}}{\mathbf{x}\mathbf{z}}$ at best as no *x* is contained.
 - v. From iii. and iv., it follows that SEQ(A, B) can be correctly classified as $\frac{\mathbf{0}_{+}}{\mathbf{x}\mathbf{z}}$.
- $\frac{x}{x}$ (a) Independently on the type of the process block, the correctness of the row follows directly from Lemma 10.
- 3. We have shown that, for each row the SEQ and AND aggregation between the states correctly aggregates in the described result
- 4. The correctness of column XOR follows directly from the preference order defined in the lattice shown in Figure 17.
- 5. From 3., and 4., it follows that the Aggregations in Table 11 are correct.

А	В	SEQ(A, B)	AND(A, B)
$\frac{-+}{\mathbf{x}\mathbf{z}}$	00 XZ	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{-+}{\mathbf{x}\mathbf{z}}$
-+ x z		$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$
$\frac{-+}{\mathbf{x}\mathbf{z}}$	+0 XZ	$\frac{-+}{\mathbf{x}\mathbf{z}}/\frac{+0}{\mathbf{x}\mathbf{z}}$	++ x z
-+ X Z	+- X Z	$\frac{\mathbf{x}}{\mathbf{x}\mathbf{z}} / \frac{\mathbf{x}}{\mathbf{x}\mathbf{z}}$	++ <u>XZ</u>
$\frac{-+}{\mathbf{X}\mathbf{Z}}$	0+ XZ	$\frac{-+}{\mathbf{x}\mathbf{z}}$	0+ <u>xz</u>
$\frac{-+}{XZ}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{-+}{\mathbf{x}\mathbf{z}}$
$\mathbf{x}\mathbf{z}^+$	++ X Z	++ X Z	++ X Z

Table 12: Aggregation Table from Interval Sub-Pattern Evaluation State

Proof (Table 12).

- 1. From Definition 36, and column \mathbf{A} of the table, it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and a task on its left having *y* annotated.
- 2. We prove by case each row of the table and each of the two different types of aggregation.
 - $\frac{00}{\underline{xz}}$ Independently on the type of the process block, the correctness of the row follows directly from Lemma 8.
 - $\overline{\mathbf{xz}}$ (a) From Definition 37, and the classification of the process block in the column **B** of the table, it follows that each execution of **B** contains at least a task having y annotated, and no other literals beneficial towards the pattern fulfilment.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A,B) containing z and a y on its left.
 - iii. From ii. and Definition 36, it follows that SEQ(A, B) can be correctly classified as $\frac{x}{xz}$.
 - **AND** i. From Lemma 9, it follows that AND(*A*,*B*) is classified as the same class as the row $\overline{\mathbf{xz}} \, \overline{\mathbf{xz}}^+$ in Table 8, which is correctly $\overline{\mathbf{xz}}$.
 - s the low $\underline{\mathbf{x}} \underline{\mathbf{x}} \underline{\mathbf{x}} \underline{\mathbf{x}}$ in Table 6, which is confectly $\underline{\mathbf{x}} \underline{\mathbf{z}}$.
 - $\frac{+0}{xz}$ (a) From Definition 32, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and no task on its right having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A,B) containing *z* and a *x* on its right, as each execution from *B* is appended on the right. While the *x* has no *y* on its right, and *z* has a *y* on its left.
 - iii. From ii. and Definition 36, it follows that SEQ(A,B) can be correctly classified as \mathbf{x}^{-+} .
 - iv. From ii. and Definition 32, it follows that SEQ(A,B) can be correctly classified as $\frac{+0}{XZ}$.
 - v. From iii., iv. and the priority ordering in Figure 17, it follows that SEQ(A, B) is correctly classified as both $\frac{+0}{2}$ and $\frac{-+}{2}$
 - is correctly classified as both $\frac{\pm 0}{xz}$ and $\frac{\pm 2}{xz}$. **AND** i. From Lemma 9, it follows that AND(*A*,*B*) is classified as the same class
 - as the row $\frac{\mathbf{x}\mathbf{z}}{\mathbf{x}\mathbf{z}} \frac{\mathbf{z}^{-+}}{\mathbf{x}\mathbf{z}}$ in Table 9, which is correctly $\frac{\mathbf{z}^{++}}{\mathbf{x}\mathbf{z}}$.
 - $\mathbf{x}\mathbf{z}$ (a) From Definition 34, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *x* annotated, and a task on its right having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A,B) containing *z* and a *x* on its right, as each execution from *B* is appended on the right. While the *x* has a *y* on its right, and *z* has a *y* on its left.
 - iii. From ii. and Definition 36, it follows that SEQ(A, B) can be correctly classified as $\overline{\mathbf{x}}_{\mathbf{z}}^+$.
 - iv. From ii. and Definition 34, it follows that SEQ(A,B) can be correctly classified as $\frac{+-}{xz}$.

- v. From iii., iv. and the priority ordering in Figure 17, it follows that SEQ(*A*,*B*) is correctly classified as both $\mathbf{x}^{+}_{\mathbf{z}}$ and $\mathbf{x}^{+}_{\mathbf{z}}$.
- is correctly classified as both $\frac{\mathbf{x}}{\mathbf{z}}$ and $\frac{\mathbf{x}}{\mathbf{z}}$. **AND** i. From Lemma 9, it follows that AND(*A*,*B*) is classified as the same class as the row $\frac{\mathbf{x}}{\mathbf{z}} \frac{\mathbf{x}}{\mathbf{z}}$ in Table 10, which is correctly $\frac{\mathbf{x}}{\mathbf{z}}$.
- $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and no tasks on its left having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A,B) containing z and a y on its left.
 - iii. From ii. and Definition 36, it follows that SEQ(A,B) can be correctly classified as $\frac{-+}{xz}$.
 - **AND** i. From Lemma 9, it follows that AND(*A*, *B*) is classified as the same class as the row $\frac{\mathbf{0}_{+}}{\mathbf{xz}} \frac{-+}{\mathbf{xz}}$ in Table 11, which is correctly $\frac{\mathbf{0}_{+}}{\mathbf{xz}}$.
- $\mathbf{x}\mathbf{z}$ (a) From Definition 36, and the classification of the process block in the column **B** of the table, it follows that there exists an execution belonging to the process block containing a task having *z* annotated, and having another task on its left having *y* annotated.
 - **SEQ** i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of *A* and an execution of *B*.
 - ii. From i., 1., and (a), it follows that there exists an execution in SEQ(A, B) containing z and a y on its left.
 - iii. From ii. and Definition 36, it follows that SEQ(A, B) can be correctly classified as $\overline{\mathbf{xz}}$.
 - **AND** i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From i., 1., and (a), it follows that the aggregated execution does not contain a *x*.
 - iii. From i., 1., and (a), it follows that the aggregated execution always contains a *z* with a *y* on its left.
 - iv. From Lemma 6 and the result from the SEQ column, it follows that AND(*A*,*B*) is at least classified as $\frac{\overline{xz}}{\overline{z}}$.
 - v. From ii., iii., Definition 36, Definition 33, Definition 31 and the preference ordering of the classes in Figure 17, it follows that AND(A,B) is classified

as $\frac{\mathbf{0}+}{\mathbf{x}\mathbf{z}}$ at best as no *x* is contained in the aggregated execution and *y* cannot be removed from the left of *z*.

- vi. From iv. and v., it follows that SEQ(A, B) can be correctly classified as $\frac{\overline{xz}}{xz}$.
- \underline{xz} (a) Independently on the type of the process block, the correctness of the row follows directly from Lemma 10.
- 3. We have shown that, for each row the SEQ and AND aggregation between the states correctly aggregates in the described result
- 4. The correctness of column XOR follows directly from the preference order defined in the lattice shown in Figure 17.
- 5. From 3., and 4., it follows that the Aggregations in Table 12 are correct.

Proof (Table 13). As each of the aggregations shown in Table 13 contains at least an element belonging to the aggregation class $\frac{++}{XZ}$, the correctness of the columns SEQ and AND follows directly from Lemma 10.

А	В	SEQ(A, B)	AND(A, B)
++ X Z	00 XZ	++ X Z	++ X Z
++	- v7	++	++
++	+0	++	++
<u>XZ</u> ++	<u>XZ</u> +-	<u>XZ</u> ++	<u>XZ</u> ++
<u>xz</u>	XZ	<u>X Z</u>	<u>X Z</u>
++ X Z	0+ XZ	<u>++</u> <u>X Z</u>	<u>++</u> <u>X Z</u>
++ X Z	$\frac{-+}{\mathbf{x}\mathbf{z}}$	++ <u>xz</u>	++ <u>XZ</u>
++ x 7	++ x 7	++	++

 xz | xz
 xz

 Table 13: Aggregation Table from Interval Sub-Pattern Evaluation State

C.4 Interval Overnode Pattern

Definition 38 (Interval Overnode Pattern $\mathbf{x}^{\dagger}\mathbf{t}^{\dagger}$). Fulfilment class: there exists an execution belonging to the process block containing the trigger leaf, a x on its left, a z on the trigger leaf right, and no y between x and z.

Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

• $\exists x, t_t, z \in \varepsilon$ such that $x \leq t_t \leq z$, and * $\exists y \in \varepsilon$ such that $x \leq y \leq z$.

Definition 39 (Interval Overnode Pattern $\overset{+0}{\text{xtz}}$). Left class: there exists an execution belonging to the process block containing the trigger leaf, a x on its left, and no y between x and the trigger leaf. Moreover there are no z or y on the right of the trigger leaf. Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

- $\exists x, t_t \in \varepsilon$ such that $x \leq t_t$, and
 - * $\exists y \in \varepsilon$ such that $x \leq y \leq t_t$, and
 - * $\exists z \in \varepsilon$ such that $t_t \leq z$, and
 - * $\exists y \in \varepsilon$ such that $t_t \leq y$.

Definition 40 (Interval Overnode Pattern xtz). Right class: there exists an execution belonging to the process block containing the trigger leaf, *a z on its right, and no y between the* trigger leaf and *z*. Moreover there are no *x* or *y* on the left of the trigger leaf. Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists z, t_t \in \varepsilon$ such that $t_t \leq z$, and
 - * $\not\exists y \in \varepsilon$ such that $t_t \leq y \leq z$, and
 - * $\exists y \in \varepsilon$ such that $y \leq t_t$.

Definition 41 (Interval Overnode Pattern \overline{xtz}). Left right blocked class: there exists an execution belonging to the process block containing the trigger leaf, a x on its left, and no y between x and the trigger leaf. Moreover there is y on the right of the trigger leaf. Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists x, t_t \in \varepsilon$ such that $x \leq t_t$, and
 - * $\exists y \in \varepsilon$ such that $x \leq y \leq t_t$, and
 - * $\exists y \in \varepsilon$ such that $t_t \leq y$.

Definition 42 (Interval Overnode Pattern $\frac{0}{\text{stz}}$). Neutral class: there exists an execution belonging to the process block containing the trigger leaf, there is no x on the left of the trigger leaf, and there is no z on the right of the trigger leaf. Moreover there is y in the execution. Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists t_t \in \varepsilon$ such that
 - * $\exists x \in \varepsilon$ such that $x \leq t_t$,
 - * $\exists z \in \varepsilon$ such that $t_t \leq z$, and
 - * $\not\exists y \in \varepsilon$.

Definition 43 (Interval Overnode Pattern $\mathbf{x} \mathbf{t}^2$). Right left blocked class: there exists an execution belonging to the process block containing the trigger leaf, a z on its right, and no y between the trigger leaf and z. Moreover there is a y on the left of the trigger leaf. Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists z, t_t \in \varepsilon$ such that $t_t \leq z$, and
 - * $\not\exists y \in \varepsilon$ such that $t_t \leq y \leq z$, and
 - * $\exists y \in \varepsilon$ such that $y \leq t_t$.

Definition 44 (Interval Overnode Pattern $\frac{0}{\text{xtz}}$). Right blocked class: there exists an execution belonging to the process block containing the trigger leaf, and there is a y on its right. Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists y \in \varepsilon$ such that $t_t \leq y$.

Definition 45 (Interval Overnode Pattern $\mathbf{x}\mathbf{t}\mathbf{z}$). Left blocked class: there exists an execution belonging to the process block containing the trigger leaf, and there is a y on its left. *Formally*:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that: • $\exists y \in \varepsilon$ such that $y \leq t_t$.

• $\exists y \in e$ such that $y \leq i_i$.

Definition 46 (Interval Overnode Pattern \overline{xtz}). Both blocked class: for each execution belonging to the process block, it contains the trigger leaf, and there are ys on both of its right and left side.

Formally:

Given a process block B belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists y \in \varepsilon$ such that $y \leq t_t$, and
 - $\exists y \in \varepsilon$ such that $t_t \leq y$.

Theorem 11 (Classification Completeness for Interval Overnode Pattern). *The set of possible evaluations of Interval Overnode Pattern is completely covered by the provided set of classifications.*

- *Proof.* 1. The two sides on the left (x) and on the right (z) of t in Interval Overnode Pattern allow 3 possible evaluations each: whether the partial requirement is satisfied, failing, or in a neutral state.
- 2. The two sides are independent. Considering that the only shared element between the two sides is *t*, even if the undesired element *y* is ordinally at the same position as *t*, meaning that $t \le y$ and $t \ge y$, then the consequence is that both sides are falsified.
- From 1. and the independence from 2., it follows that the amount of possible combinations in Interval Overnode Pattern is 3², hence 9 possible combinations. Moreover the case from 2. is also covered within the 9 combinations.
- 4. Therefore, every possible evaluation of Interval Overnode Pattern is captured by one of the 9 provided classifications.

Lemmas

Lemma 11 (Aggregation Neutral Class). Given a process block A, assigned to the evaluation class $\overset{0}{\text{xtz}}$, and another process block B, assigned to any of the available evaluation classes. Let C be a process block having A and B as its sub-blocks, then the evaluation class of C is the same class as the process block B.

Proof. This proof follows closely the proof for Lemma 4

Lemma 12 $(\stackrel{++}{\mathbf{x}}_{\mathbf{z}}^{+}$ super class). Independently from the classification of the overnode's overnode child, when aggregated with the overnode's undernode class $\stackrel{++}{\mathbf{x}}_{\mathbf{z}}$, it always results in $\stackrel{+}{\mathbf{x}}_{\mathbf{z}}_{\mathbf{z}}$.

Proof. The correctness of Lemma 12 follows from Definition 4, where the execution of a process block classified as $\frac{\mathbf{x}z}{\mathbf{x}z}$, can be interleaved with another execution from whatever classification¹¹ and result in $\frac{\mathbf{x}t}{\mathbf{x}t}$. According to Definition 31, $\frac{\mathbf{x}z}{\mathbf{x}z}$ contains an *x* with a *z* on its right and no *y* inbetween. Thus independently than what appears around a trigger task *t* and its classification, such task can be plugged within the interval identified in the undernode classified execution, while leaving outside the interval the remainder of the elements in the overnode, making them virtually useless for the classification, as independently from them, the resulting block clearly allows an execution satisfying the criteria described in Definition 38, allowing the result to be always classified as $\frac{\mathbf{x}t}{\mathbf{x}t}$, since is the most preferred class as show in Figure 12.

Lemma 13 (Top Classification). Independently from the classification of the overnode's undernode children, when aggregated with the overnode's overnode child classification $\overset{+}{\mathbf{xt}}\overset{+}{\mathbf{z}}$, it always results in $\overset{+}{\mathbf{xt}}\overset{+}{\mathbf{z}}$.

Proof. Considering Definition 4 and that the aggregations considered refer to AND blocks as the way executions from different sub blocks are merged together, considering that one of the sub-blocks is classified as $\overset{+}{\mathbf{xt}}\overset{+}{\mathbf{z}}$, the executions relative to the other sub-block(s) can be appended before and / or after the execution in the block classified $\overset{+}{\mathbf{xt}}\overset{+}{\mathbf{z}}$, hence without disrupting the properties allowing the aggregation to be classified as $\overset{+}{\mathbf{xt}}\overset{+}{\mathbf{z}}$ in accordance to Definition 38. Finally, as the preference order shown in Figure 12 illustrates that $\overset{+}{\mathbf{xt}}\overset{+}{\mathbf{z}}$ is the best classification achievable, then we can state that Lemma 13 is correct.

Lemma 14 (Hide The Bubu). Given a overnode's overnode child not classified as $\mathbf{x}\mathbf{t}\mathbf{z}^0$ and a overnode's undernode children classified as $\mathbf{x}\mathbf{z}$, their aggregation always corresponds to the classification of the overnode's overnode child. In the case Given a overnode's overnode child is classified as $\mathbf{x}\mathbf{t}$, then the aggregation results in both: $\mathbf{x}\mathbf{t}\mathbf{z}$ and $\mathbf{x}\mathbf{t}$.

¹¹ Notice that the trigger task must not contain a *y*, otherwise such interleaving is not possible anymore (this is ensure by one of the premature exit condition in the stem algorithm).

Proof. Considering the case where the overnode's overnode child is classified as $\frac{0}{\text{xtz}}$, the y from the execution of the block classified as $\frac{\overline{xz}}{\overline{xz}}$ can be put on the left or the right of the execution allowing to classify overnode's overnode child as $\frac{0}{\text{xtz}}$, which would then allow to classify it either as $\frac{\overline{xz}}{\overline{xtz}}$ or $\frac{0}{\overline{xtz}}$. Notice that the resulting classification are strictly worse than the starting one.

In the opposite case, where the overnode's overnode child is not classified as $\frac{0}{xtz}$, considering that the *y* from the other block's executions cannot make any classification better, to avoid making the current classification worse it is sufficient to place the *y* on the left side of an *x* on the left of a *t*, on the right of a *z* on the right of a *t* or on the left / right of a *y* left / right of a *t*. In such a way, the classification of the side where the newly set *y* would be dominated by the pre-existing elements, which would not make that side of the classification to change. Which overall means that the whole classification remains the same as the overnode's overnode child.

Lemma 15 (Not Worse). Given a overnode's overnode child not classified as $\overset{0}{\text{xtz}}$ and a overnode's undernode children classified either as $\overset{+-}{\text{xz}}$ or $\overset{-+}{\text{xz}}$, their aggregation cannot be worse than the classification of the overnode's overnode child.

Proof. Considering Definition 34 and Definition 36, we know that both $\frac{+-}{xz}$ are $\frac{-+}{xz}$ contain an element y, and another element that can potentially be useful to bring either the left or right side of an overnode's overnode child classification to a +.

We can apply Lemma 14 the the *y* element, while the remainder element can be either used to improve the classification, or not if that is not possible. Leading to the conclusion that the classification of the overnode's overnode child cannot get worse.

SEQ Aggregations

The aggregations leading to the classification of the overnode of type SEQ are illustrated in Table 14 and Table 15. The two table show the aggregation between the current classification of the overnode's overnode child with the left and right undernodes classifications. As the two sub-patterns are independent, the order in which the tables are applied is irrelevant.

Proof (Table 14). Let the left part of the overnode classification be B, while the left sub-pattern be A and, as the aggregation in Table 14 refers to aggregations of a SEQ block, we can use the same aggregations from Table 5 using the result column SEQ(A, B), as it computes exactly the same aggregation required in Table 14 for the right side of the overnode classification, and the aggregation does not influence the classification on the right side of the current overnode classification, which remains unchanged in the result.

Proof (Table 15). Let the right part of the overnode classification be *A*, while the right subpattern be *B* and, as the aggregation in Table 15 refers to aggregations of a SEQ block, we can use the same aggregations from Table 6 using the result column SEQ(A, B), as it computes exactly the same aggregation required in Table 15 for the right side of the overnode classification, and the aggregation does not influence the classification on the left side of the current overnode classification, which remains unchanged in the result.

AND Aggregations

The classification of an overnode of type AND is obtained by the aggregating the aggregation result of the classification of its undernode children with the classification of its overnode child. The aggregations are illustrated in Table 16, Table 17 and Table 18.

Proof (Table 16).

Overnode's Overnode Child	Left Sub-Pattern Classification	Result
$\mathbf{x}\mathbf{t}\mathbf{z}^{+}$	+ X	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
+ xtz	0 X	*tz
*tz	- X	$\frac{+}{xtz}$
+ 0 xtz	+ X	+ 0 xtz
+ 0 xtz	0 X	+ 0 xtz
+ 0 xtz	- X	+ 0 xtz
0+ xtz	+ X	$\frac{+}{xtz}$
0 + xtz	0 X	$\frac{0}{xtz}$
	X	$\frac{-}{xtz}$
+- xtz	+ X	+ -
+ - xtz	0 X	$\frac{+}{xt7}$
+ - xt7	- - X	+ $ +$ 7
	+ V	+ 0
	0 X	0 0 xtz
	- X	-0 xtz
$-\mathbf{x}\mathbf{t}\mathbf{z}^+$	+ X	$\frac{-}{\mathbf{x}\mathbf{t}\mathbf{z}}^+$
$-\mathbf{x}\mathbf{t}\mathbf{z}^+$	0 X	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	X	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
0 – xtz	+ X	$\frac{+}{xtz}$
0 – xtz	0 X	$\frac{0}{xtz}$
0 - xtz	- X	$\overline{\mathbf{x}}\mathbf{t}\overline{\mathbf{z}}$
$-\frac{0}{xtz}$	+ X	-0 xtz
$-\frac{0}{xtz}$	0 X	0 xtz
$-\frac{0}{xtz}$	- X	-0 xtz
xtz	+ X	xtz
xtz	0 X	$\overline{\mathbf{x}}\mathbf{t}\overline{\mathbf{z}}$
xtz	x	$\bar{\mathbf{x}}\mathbf{t}\bar{\mathbf{z}}$

Table 14: Aggregation	Table SEQ	Overnode	Left
-----------------------	-----------	----------	------

- 1. As the aggregation involves AND blocks, from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of the *Overnode's Overnode Child* interleaved with an execution of the *Overnode's Undernode Children*.
- 2. We prove the correctness of the table by proving the correctness of the aggregation in each of its line. Considering by case the *Overnode's Overnode Child* classifications:
 - $\mathbf{\dot{x}tz}^+$ Independently on the *Overnode's Undernode Children* classification, the correctness of the row follows directly from Lemma 13.
 - $\overset{+}{\mathbf{x}} \overset{\mathbf{0}}{\mathbf{z}}$ (a) From Definition 39, it follows that there exists an execution of the *Overnode's Overnode Child* where there is a *x* on the left of *t* with no *y* between them, and no *y* or *z* on the right of the *t*.

Overnode's Overnode Child	Right Sub-Pattern Classification	Result
****	+ Z	*tz
*tz	0 Z	*tz
*tz	– Z	*tz
+ 0 xtz	+ Z	$\frac{+}{xtz}$
+ 0 xtz	0 Z	+ 0 xtz
+ 0 xtz	Z	$\frac{+}{xtz}$
	+ Z	$\frac{0}{xtz}$
0 + xtz	 0 Z	0 + xtz
	- 7	0 +
+ - vt7	+ 7	+ - vtz
	0	+ $-$
	7	+ -
	 + 	
	<u> </u>	
	Z —	$\frac{\mathbf{x}\mathbf{t}\mathbf{z}}{0_{1}-\mathbf{z}}$
	Z +	-+
<u>xtz</u>	Z 0	xtz
	Z	xtz
0 –	Z +	xtz
xtz	Ž	$\hat{\mathbf{x}}\mathbf{t}\mathbf{z}$
xtz	Ž	xtz
	Z	xtz
	+ Z	xtz ⁺
	0 Z	- 0 xtz
	Z	xtz
xtz	+ Z	xtz
xtz	0 Z	$\bar{\mathbf{x}}\mathbf{t}\bar{\mathbf{z}}$
xtz	Z	xtz

Table 15: Ag	ggregation	Table SEQ	Overnode	Right
--------------	------------	-----------	----------	-------

- (b) Considering by case the Overnode's Undernode Children classification:

 - $\frac{++}{xz}$ The correctness of the row follows directly from Lemma 12. $\frac{+0}{xz}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From i., it follows that it does not contain any element capable of improving the Overnode's Overnode Child classification, or making it worse.
 - iii. From 1., (a) and ii., it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}$.

Overnode's Overnode Child	Overnode's Undernode Children	Result
+ xtz	++ <u>X Z</u>	*tz
*++ xtz	+0 <u>XZ</u>	$\frac{+}{xtz}$
++ xtz	$0 + \mathbf{XZ}$	t^+_{xtz}
*++ xtz	+- <u>x z</u>	$\frac{+}{xtz}$
*++ xtz	00 XZ	$\frac{+}{xtz}$
*tz	$\frac{-+}{XZ}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
+ xtz	<u>xz</u>	*tz
+ 0 xtz	$\frac{++}{\mathbf{X}\mathbf{Z}}$	t^+_{xtz}
+ 0 xtz	+0 <u>xz</u>	+ 0 xtz
+ 0 xtz	$0 + \underline{\mathbf{x}} \mathbf{Z}$	++ xtz
+ 0 xtz	+- X Z	+ 0 xtz
+ 0 xtz	00 XZ	+ 0 xtz
+ 0 xtz		++ xtz
+ 0 xtz	 xz	+ 0 xtz
0 + xtz	++ X Z	$ t^+ t^+$
0 + xtz	+0 XZ	$ t^+ t^+$
0 + xtz	0+ XZ	0 + xtz
	+- X Z	$ t^+ t^+$
	00 XZ	0 + xtz
		$\frac{0}{xtz}$
		$\frac{0}{xtz}$

Table 16: Aggregation Table from Interval Sub-Pattern to Interval Overnode Pattern

- $\frac{\mathbf{0}_{\pm}^{+}}{\mathbf{xz}}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - ii. From 1., (a) and i., it follows that a possible interleaving would allow to place the z on the right of the t.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
- $\frac{\mathbf{x}\mathbf{z}}{\mathbf{x}\mathbf{z}}$ i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification.
 - iii. From ii., (a) and Lemma 15, it follows that the aggregation is then correctly classified as $\stackrel{+}{xtz}$.
- $\frac{00}{\underline{xz}}$ The correctness of the row follows directly from Lemma 11.
- $\vec{x}\vec{z}$ i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and a *y* on its left, while not containing *x*.

- ii. From 1., (a) and i., it follows that the z from $\frac{xz}{xz}$ can be set on the right of t, while the y, thanks to the interleaving, can be set on the left of the x from $\frac{+0}{xtz}$.
- iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.
- $\overset{\mathbf{0}}{\mathbf{xtz}} ^+$ (a) From Definition 40, it follows that there exists an execution of the *Overnode's Overnode Child* where there is a *z* on the right of *t* with no *y* between them, and no *y* or *x* on the left of the *t*.
 - (b) Considering by case the Overnode's Undernode Children classification:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{xz}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From 1., (a) and i., it follows that a possible interleaving would allow to place the *x* on the left of the *t*.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as $\overset{+}{\mathbf{xtz}}$.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{XZ}}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification, or making it worse.
 - iii. From 1., (a) and ii., it follows that the aggregation is then correctly classified as $\frac{\mathbf{0}}{\mathbf{x}\mathbf{t}\mathbf{z}}$.
 - **<u>xz</u>** i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From 1., (a) and i., it follows that the *x* from $\mathbf{1'_r}$ can be set on the left of *t*, while the *y*, thanks to the interleaving, can be set on the right of the *z* from $\mathbf{0}_{\mathbf{xtz}}^+$.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
 - $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 11.
 - **x** \vec{z} i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and a *y* on its left, while not containing *x*.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification.
 - iii. From ii., (a) and Lemma 15, it follows that the aggregation is then correctly classified as $\frac{0}{2}t^{+}$.
 - $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.

Proof (Table 17).

- 1. As the aggregation involves AND blocks, from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of the *Overnode's Overnode Child* interleaved with an execution of the *Overnode's Undernode Children*.
- 2. We prove the correctness of the table by proving the correctness of the aggregation in each of its line. Considering by case the *Overnode's Overnode Child* classifications:

Overnode's Overnode Child	Overnode's Undernode Children	Result
* tz	++ <u>xz</u>	*tz
$\mathbf{x} \mathbf{t} \mathbf{z}^+$	+0 <u>xz</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^{+}$
+ - xtz	0+ xz	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
+ xtz	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
+ xtz	00 <u>xz</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^{+}$
+ xtz	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	xz	$\frac{+}{xtz}$
0 0 xtz	++ <u>XZ</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^{+}$
0 0 xtz	+0 <u>xz</u>	+ 0 xtz
0 0 xtz	0+ <u>XZ</u>	
0 0 xtz	$\frac{+-}{\mathbf{x}\mathbf{z}}$	$\dot{x}tz / xtz^{0}$
0 0 xtz	00 <u>XZ</u>	0 0 xtz
0 0 xtz		$\frac{1}{xtz} + \frac{0}{xtz}$
0 0 xtz	<u></u>	$\frac{0}{xtz}$ / $\frac{-0}{xtz}$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	++ <u>X Z</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	+0 <u>xz</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	0+ <u>XZ</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	*tz
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	00 <u>xz</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x}\mathbf{t}\mathbf{z}^+$	<u>-+</u> <u>XZ</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
$\mathbf{x} \mathbf{t} \mathbf{z}^+$	xz	$\mathbf{x}\mathbf{t}\mathbf{z}^+$

Table 17: Aggregation Table from Interval Sub-Pattern to Interval Overnode Pattern

- $\mathbf{x}\mathbf{t}\mathbf{z}$ (a) From Definition 41, it follows that there exists an execution of the *Overnode's Overnode Child* where there is a *z* on the right of *t* with no *y* between them, and no *y* or *x* on the left of the *t*.
 - (b) Considering by case the *Overnode's Undernode Children* classification:
 - $\frac{++}{\mathbf{x}\mathbf{z}}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{XZ}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification, or making it worse.
 - iii. From 1., (a) and ii., it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
 - $\frac{0}{xz}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - ii. From 1., (a) and i., it follows that a possible interleaving would allow to place the *z* on the right of the *t*, before the existing *y*.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as $\overset{+}{\mathbf{x}}\overset{+}{\mathbf{z}}$.

- $\frac{1}{xz}$ i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification.
 - iii. From ii., (a) and Lemma 15, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 11.
- i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - ii. From 1., (a) and i., it follows that the z from $\frac{-+}{xz}$ can be set on the right of t, before the existing y in $\frac{+}{xtz}$, while the y, thanks to the interleaving, can be set on the left of the x from $\frac{+0}{xtz}$.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as ${}^{+}_{xtz}$.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.
- - (b) Considering by case the Overnode's Undernode Children classification:
 - $\mathbf{x}\mathbf{z}^{++}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{\underline{x}\underline{z}}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{+0}{xz}$ can be placed on the left of the t from $\frac{0}{xtz}$.
 - iii. From ii. and Definition 39, it follows that the aggregation is then correctly classified as $\frac{+0}{xtz}$.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{XZ}}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - ii. From 1., (a) and i., it follows that the *y* from $\frac{\mathbf{0}_{t}}{\mathbf{x}\mathbf{z}}$ can be placed on the right of the *t* from $\frac{\mathbf{0}_{t}\mathbf{0}}{\mathbf{x}\mathbf{z}}$.
 - iii. From ii. and Definition 39, it follows that the aggregation is then correctly classified as ${}^{0}_{xtz}$.
 - $\frac{z}{xz}$ i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{xz}{xz}$ can be placed on the left of the t from $\frac{0}{xtz}$, while the y can be placed on the right.
 - iii. From 1., (a) and i., it follows that the x from $\frac{xz}{xz}$ can be placed on the left of the t from $\frac{0}{xtz}$, while the y can be placed between the x and the t.
 - iv. From ii. and Definition 41, it follows that the aggregation is then correctly classified as $\mathbf{\dot{x}tz}$.
 - v. From iii. and Definition 45, it follows that the aggregation is then correctly classified as $\bar{\mathbf{x}} t \bar{\mathbf{z}}$.
 - vi. From iv. and v., it follows that the classification of the row is correct.

- $\frac{30}{xz}$ The correctness of the row follows directly from Lemma 11.
- i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - ii. From 1., (a) and i., it follows that the z from $\underline{\mathbf{x}} \mathbf{z}^{++}$ can be placed on the right of the t from $\mathbf{x} \mathbf{z}$, while the y can be placed on the left.
 - iii. From 1., (a) and i., it follows that the z from $\frac{x}{z}$ can be placed on the right of the t from $\frac{0}{xt}$, while the y can be placed between the t and the z.
 - iv. From ii. and Definition 43, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}$.
 - v. From iii. and Definition 44, it follows that the aggregation is then correctly classified as $\frac{\Phi}{xtz}$.
 - vi. From iv. and v., it follows that the classification of the row is correct.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.
- **xt**^{\mathbf{z}} (a) From Definition 43, it follows that there exists an execution of the *Overnode's Overnode Child* where there is a *z* on the right of *t* with no *y* between them, and no *y* or *x* on the left of the *t*.
 - (b) Considering by case the Overnode's Undernode Children classification:
 - $\frac{xz}{xz}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{xz}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a x and no y or z.
 - ii. From 1., (a) and i., it follows that a possible interleaving would allow to place the *x* on the left of the *t*.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
 - $\frac{0}{xz}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a z and no y or x.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification, or making it worse.
 - iii. From 1., (a) and ii., it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}$.
 - \overline{xz} i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From 1., (a) and i., it follows that the x from $\mathbf{1'_r}$ can be set on the left of t, while the y, thanks to the interleaving, can be set on the right of the z from $\mathbf{0} + \mathbf{xtz}$.
 - iii. From ii and Definition 38, it follows that the aggregation is then correctly classified as ${}^{+}xt$.
 - \underline{xz} The correctness of the row follows directly from Lemma 11.
 - i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - ii. From i., it follows that it does not contain any element capable of improving the *Overnode's Overnode Child* classification.
 - iii. From ii., (a) and Lemma 15, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}^+$.
 - $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.

Overnode's Overnode Child	Overnode's Undernode Children	Result
	++ <u>X Z</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
0 - xtz	+0 <u>XZ</u>	$\frac{+}{xtz}$
	0+ xz	0 + xtz
	+- XZ	$\frac{+}{xtz}$
0 - xtz	00 XZ	$\frac{0}{xtz}$
0 - xtz	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$ / $\mathbf{x}\mathbf{t}\mathbf{z}^-$
0 - xtz	xz	$\frac{0}{xtz}$
$-\frac{0}{xtz}$	++ X Z	*tz
$-\frac{0}{xtz}$	+0 XZ	+ 0 xtz
$-\frac{0}{xtz}$		$\frac{-}{\mathbf{x}\mathbf{t}\mathbf{z}}^+$
	+- XZ	$\frac{+}{xtz}$ / $\frac{-}{xtz}$
- 0 xtz	00 <u>XZ</u>	- 0 xtz
$-\mathbf{x}\mathbf{t}\mathbf{z}^{0}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
- 0 xtz	xz	- 0 xtz
xtz	$\frac{++}{\mathbf{X}\mathbf{Z}}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
xtz	+0 <u>xz</u>	$\frac{+}{xtz}$
xtz	0+ <u>xz</u>	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
xtz	+- <u>XZ</u>	$\dot{x}tz$
xtz	00 <u>XZ</u>	$\overline{\mathbf{x}}\mathbf{t}\overline{\mathbf{z}}$
xtz	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\mathbf{x}\mathbf{t}\mathbf{z}^+$
xtz	xz	xtz

Table 18: Aggregation Table from Interval Sub-Pattern to Interval Overnode Pattern

Proof (Table 18).

- 1. As the aggregation involves AND blocks, from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of the *Overnode's Overnode Child* interleaved with an execution of the *Overnode's Undernode Children*.
- 2. We prove the correctness of the table by proving the correctness of the aggregation in each of its line. Considering by case the *Overnode's Overnode Child* classifications:
 - $\overset{0}{\mathbf{xtz}}$ (a) From Definition 44, it follows that there exists an execution of the *Overnode's Overnode Child* where there is a *z* on the right of *t* with no *y* between them, and no *y* or *x* on the left of the *t*.
 - (b) Considering by case the *Overnode's Undernode Children* classification:
 - $\frac{++}{\mathbf{x}\mathbf{z}}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{\underline{xz}}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{+0}{xz}$ can be placed on the left of the t from $\frac{0}{xz}$, while the y remains on the right of the t.
 - iii. From ii. and Definition 41, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
- $\overset{0+}{xz}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - ii. From 1., (a) and i., it follows that the z from $\frac{\mathbf{0}^+}{\mathbf{x}\mathbf{z}}$ can be placed between the t and the y from $\mathbf{x}\mathbf{t}\mathbf{z}$.
 - iii. From ii. and Definition 40, it follows that the aggregation is then correctly classified as ${}^{0}_{xtz}$.
- $\frac{1}{xz}$ i. From Definition 34, it follows that Overnode's Undernode Children contains an execution containing a x and a y on its right, while not containing
 - ii. From 1., (a) and i., it follows that the x from $\frac{+-}{xz}$ can be placed on the left of the *t* from $\mathbf{x}\mathbf{t}\mathbf{z}$, while the *y* from $\mathbf{x}\mathbf{z}$ can be placed on the right of *t*. iii. From ii. and Definition 41, it follows that the aggregation is then correctly
 - classified as $\mathbf{x}\mathbf{t}\mathbf{z}$.
- \underline{xz} The correctness of the row follows directly from Lemma 11.
- $\mathbf{x}\mathbf{z}$ i. From Definition 36, it follows that Overnode's Undernode Children contains an execution containing a z and a y on its left, while not containing x.
 - ii. From 1., (a) and i., it follows that the z from $\frac{z}{xz}$ can be placed between the *t* and the *y* from $\frac{\mathbf{0}}{\mathbf{x}\mathbf{z}}$, while the *y* from $\frac{\mathbf{x}^+}{\mathbf{x}\mathbf{z}}$ remains on the right of *z*.
 - iii. From 1., (a) and i., it follows that the z and the y from $\frac{x}{xz}$ can be placed on the right the t and the y from $\mathbf{x}\mathbf{t}\mathbf{z}$.
 - iv. From ii. and Definition 43, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}^{+}$.
 - v. From iii. and Definition 44, it follows that the aggregation is then correctly classified as xtz.
 - vi. From iv. and v., it follows that the classification of the row is correct.
- $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 14.

 $\mathbf{x}\mathbf{z}^{\mathbf{0}}$ (a) From Definition 45, it follows that there exists an execution of the *Overnode's* Overnode Child where there is a z on the right of t with no y between them, and no y or x on the left of the t.

- (b) Considering by case the Overnode's Undernode Children classification:
 - $\frac{xz}{xz}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{\underline{xz}}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{+0}{xz}$ can be placed between the y and t from $\mathbf{x}\mathbf{t}\mathbf{z}^{0}$.
 - iii. From ii. and Definition 39, it follows that the aggregation is then correctly classified as $\overset{+}{\mathbf{x}} \overset{0}{\mathbf{z}}$.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ i. From Definition 33, it follows that Overnode's Undernode Children contains an execution containing a z and no y or x.
 - ii. From 1., (a) and i., it follows the z from $\frac{\mathbf{0}_{+}}{\mathbf{x}\mathbf{z}}$ can be placed on the right of the y and the t from $\mathbf{x}\mathbf{t}\mathbf{z}$.
 - iii. From ii. and Definition 43, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}^{+}$.

- \overline{xz} i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{t}{xz}$ can be placed between the y and t from $\overline{xt^0}$, while the y from $\frac{t}{xz}$ can be placed on the left of t.
 - iii. From 1., (a) and i., it follows that the x and the y from $\frac{t}{\mathbf{x}\mathbf{z}}$ can be placed on the left of the y and t from $\frac{1}{\mathbf{x}\mathbf{t}}\mathbf{z}$.
 - iv. From ii. and Definition 41, it follows that the aggregation is then correctly classified as $\frac{^{+}t\bar{z}}{xtz}$.
 - v. From iii. and Definition 45, it follows that the aggregation is then correctly classified as $\bar{\mathbf{x}} t \mathbf{\hat{z}}$.
 - vi. From iv. and v., it follows that the classification of the row is correct.
- $\frac{300}{xz}$ The correctness of the row follows directly from Lemma 11.
- $\frac{xz}{xz}$ i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - ii. From 1., (a) and i., it follows that the z from $\overline{\mathbf{x}} \overline{\mathbf{z}}^{+}$ can be placed on the right of the t from $\overline{\mathbf{x}} \overline{\mathbf{z}}^{0}$, and the y from $\overline{\mathbf{x}} \overline{\mathbf{z}}^{+}$ can be placed on the left of t.
 - iii. From ii. and Definition 43, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}^+$.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.
- xtz (a) From Definition 46, it follows that there exists an execution of the *Overnode's* Overnode Child where there is a z on the right of t with no y between them, and no y or x on the left of the t.
 - (b) Considering by case the Overnode's Undernode Children classification:
 - $\frac{xz}{xz}$ The correctness of the row follows directly from Lemma 12.
 - $\frac{+0}{xz}$ i. From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{+0}{xz}$ can be placed between the t and its left y from \overline{xtz} .
 - iii. From ii. and Definition 41, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ i. From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{0+}{xz}$ can be placed between the t and its right y from \overline{xtz} .
 - iii. From ii. and Definition 43, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}^+$.
 - \overline{xz} i. From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - ii. From 1., (a) and i., it follows that the x from $\frac{\mathbf{x}\mathbf{z}}{\mathbf{x}\mathbf{z}}$ can be placed between the t and its left y from $\mathbf{x}\mathbf{t}\mathbf{z}$, while the y from $\frac{\mathbf{x}\mathbf{z}}{\mathbf{x}\mathbf{z}}$ can be placed on the right of the t.
 - iii. From ii. and Definition 41, it follows that the aggregation is then correctly classified as $\frac{+}{xtz}$.

- $\frac{\underline{wz}}{\underline{xz}}$ The correctness of the row follows directly from Lemma 11. $\frac{\overline{xz}}{\underline{xz}}$ i. From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing х.
 - ii. From 1., (a) and i., it follows that the *x* from $\frac{x}{xz}$ can be placed between the t and its right y from $\mathbf{x}\mathbf{t}\mathbf{z}$, while the y from $\mathbf{x}\mathbf{z}^+$ can be placed on the left of the t.
 - iii. From ii. and Definition 43, it follows that the aggregation is then correctly classified as $\mathbf{x}\mathbf{t}\mathbf{z}^+$.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 14.

C.5 Generalised Sequence Pattern

Definition 47 (Generalised Sequence Pattern $\overset{++}{xz}$). Exists an execution such that: both x and z sub-patterns are fulfilled and in the correct order.

Formally:

Given a process block B, it belongs to this class if and only if:

 $\begin{array}{l} - \exists \varepsilon \in \Sigma(B) \ such \ that: \\ \bullet \ \exists x \in \varepsilon \ such \ that: \\ & * \ \not \exists y \in \varepsilon \ such \ that \ x \preceq y, \ and \\ & * \ \exists z \in \varepsilon \ such \ that: \\ & \cdot \ x \preceq z, \ and \\ & \cdot \ \not \exists k \in \varepsilon \ such \ that \ z \preceq k \end{array}$

Definition 48 (Generalised Sequence Pattern xz). Exists an execution such that: x sub-pattern satisfied, but z sub-pattern not-satisfied on the right of the former, neither invalidated. Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

• $\exists x \in \varepsilon$ such that:

- * $\exists y \in \varepsilon$ such that $x \leq y$, and
- * $\exists z \in \varepsilon$ such that $x \leq z$, and
- * $\exists k \in \varepsilon$ such that $x \leq k$

Definition 49 (Generalised Sequence Pattern $\mathbf{x}_{\mathbf{z}}^{9+}$). Exists an execution such that: *z* sub-pattern satisfied and *x* is neither satisfied or invalidated on the left of the former. *Formally*:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

- $\exists z \in \varepsilon$ such that:
 - * $\exists y \in \varepsilon$, and
 - * $\nexists x \in \varepsilon$ such that $x \leq z$, and
 - * $\exists k \in \varepsilon$ such that $z \leq k$

Definition 50 (Generalised Sequence Pattern $\overset{00}{xz}$). Exists an execution such that: neither subpattern invalidated or satisfied.

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

- $\exists x \in \varepsilon$,
- *∃*y∈ ε,
- $\not\exists z \in \varepsilon$, and
- $\exists k \in \varepsilon$

Definition 51 (Generalised Sequence Pattern $\mathbf{x}\mathbf{z}$). Exists an execution such that: z sub-pattern satisfied and x is invalidated on the left of the former.

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:
 - $\exists z \in \varepsilon$ such that:
 - * $\exists y \in \varepsilon$ such that $y \preceq z$,
 - * $\nexists x \in \varepsilon$ such that $x \leq z$, and

* $\not\exists k \in \varepsilon$ such that $z \leq k$

Definition 52 $(\mathbf{x} \mathbf{z})$. *Exists an execution such that: x sub-pattern satisfied and z is invalidated on the right of the former.*

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that: • $\exists x \in \varepsilon$ such that:

* $\exists k \in \varepsilon$ such that $x \leq k$,

* $\nexists y \in \varepsilon$ such that $k \leq y$, and

* $\exists z \in \varepsilon$ such that $k \leq z$

Definition 53 (Generalised Sequence Pattern $\overset{0}{xz}$). Exists an execution: z is falsified and x is neither satisfied or falsified on the left of z.

Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

- $\not\exists y \in \varepsilon$, and
- $\exists k \in \varepsilon$ such that:
 - * $\not\exists x \in \varepsilon$ such that $x \leq z$, and
 - * $\exists z \in \varepsilon$ such that $k \leq z$

Definition 54 (Generalised Sequence Pattern xz). Exists an execution: z is falsified and x is neither satisfied or falsified on the left of z. Formally:

Given a process block B, it belongs to this class if and only if:

-
$$\forall \varepsilon \in \Sigma(B)$$
 such that:

- $\exists y \in \varepsilon$, such that:
 - * $\not\exists x \in \varepsilon$, such that $y \leq x$, and
 - * $\forall z \in \varepsilon$, such that $y \leq z$:

$$\cdot \exists k \in \varepsilon$$
, such that $z \leq k$

- *OR* $\exists y \in \varepsilon$, such that:
 - * $\not\exists x \in \varepsilon$, such that $y \leq x$, and

*
$$\exists z \in \varepsilon$$
, such that $y \leq z$:

• $\not\exists k \in \varepsilon$, such that $z \leq k$

Theorem 12 (Classification Completeness for Generalised Sequence Pattern). *The set of possible evaluations of Generalised Sequence Pattern is completely covered by the provided set of classifications.*

- *Proof.* 1. The Generalised Sequence Pattern is composed of two sub patterns on the left of t, the far (x) and the near (z) one, and each allows 3 possible evaluations: whether the partial requirement is satisfied, failing, or in a neutral state.
- 2. The near and far sub patterns are independent, and the only shared element between the two sub patterns is *t*.
- 3. From 1. and 2., it follows that the amount of possible combinations in Generalised Sequence Pattern is 3², hence 9 possible combinations.
- 4. 7 of the 9 possible combinations are covered by the classifications described from Definition 47 to Definition 53.
- 5. The remainder 2 combinations are covered by the classification in Definition 54.
- 6. From 3., 4., and 5., it follows that every possible combination is covered by the classifications allowed while evaluating the Generalised Sequence Pattern.

Lemmas

Lemma 16 (Aggregation Neutral Class). Given a process block A, assigned to the evaluation

 $^{00}_{class xz}$, and another process block B, assigned to any of the available evaluation classes. Let C be a process block having A and B as its sub-blocks, then the evaluation class of C is the same class as the process block B.

Proof. This proof follows closely the proof for Lemma 4

Lemma 17 (AND **Super Element**). Given a process block A, assigned to the evaluation class $\overset{++}{\mathbf{x}\mathbf{z}}$, and another process block B, assigned to any of the available evaluation classes. Let B be a process block of type AND having A as one of its sub-blocks, then the evaluation class of B is always $\overset{++}{\mathbf{x}\mathbf{z}}$.

- *Proof.* 1. From Definition 47, it follows the classification $\mathbf{x}\mathbf{z}^{++}$ contains the required properties to satisfy the Generalised Sequence Pattern.
- 2. From the premise, we have that a process block A is classified as $\mathbf{x}\mathbf{z}^{++}$ and is one of the subblocks of a process block C of type AND.
- 3. From 1., 2., and Definition 4, it follows that as the requirements for the Generalised Sequence Pattern are satisfied already by *A*, then one of the possible executions of *B* is the result of append the partial executions of from the other sub-blocks of *B* either before of after the partial execution of *A* that allows it to be classified as $\frac{++}{xz}$.
- 4. From 3., it follows that there exists an execution in *B* that maintains the same properties as the one allowing to classify *A* as $\frac{++}{xz}$.
- 5. From 4., and Definition 47, it follows that *B* can be indeed classified as $\overset{++}{\mathbf{x}}$.

Lemma 18 (SEQ Right Dominant). Given an aggregation SEQ(A,B), where B is classified either as $\stackrel{++}{\mathbf{x}\mathbf{z}}$, $\stackrel{-+}{\mathbf{x}\mathbf{z}}$, $\stackrel{0}{\mathbf{x}\mathbf{z}}$, $\stackrel{+-}{\mathbf{x}\mathbf{z}}$ or $\mathbf{x}\mathbf{z}$, then the result of the aggregation is the same class as B independently from the classification of A.

Proof. If one of such classes is on the right, it does not matter the left part, because it becomes irrelevant for various reasons, for instance because B is a super, or because B be contains a failure invalidating whatever A can bring.

Lemma 19 (Both by Unblocking). Given an aggregation SEQ(A,B), where B is classified as $\stackrel{+0}{xz}$, the result is the same as XOR(A,B).

Proof. $\overset{+0}{\mathbf{x}\mathbf{z}}$ is non blocking as it does not contain a *y* or a *k*. In accordance, whatever is on the left can be potentially be used to improve the class through a an AND aggregation for both classifications. As well, this type of aggregation cannot improve $\overset{+0}{\mathbf{x}\mathbf{z}}$ as it is already on the right, unless the left element classification is already strictly better, but this is captured by the XOR way of aggregating plus the priority given by the lattice for pruning strictly worse classifications.

Lemma 20 (Mirror). Given an aggregation AND(A,B), where A and B have the same classification, then AND(A,B) has the same classification.

Proof. Provable by contradiction. Assuming that AND(A, B) can achieve a better classification than A or B, which entails that either A or B contain some elements capable of improving the classification of the other. This is verifiably false as A and B are constrained to have the same classification, and by going through the possible classifications and their properties.

Aggregations

The classification of the undernode children according to the Generalised Sequence Pattern is described in the following tables. Mind that the aggregation is performed pair-wise left to right, with the result being aggregated with next brother on the right. While an ordered aggregation is not necessarily required when dealing with parent nodes of type AND, however this allows to deal with both types of parent nodes in the same way.

А	В	SEQ(A, B)	AND(A, B)
++	++	++	++
X Z	X Z	X Z	X Z
++	+0	++	++
X Z	XZ	x z	X Z
++	0+	++	++
X Z	XZ	X Z	X Z
++	00	++	++
X Z	XZ	X Z	X Z
++	−+	-+	++
X Z	xz	x z	X Z
++	+-	+-	++
X Z	X Z	x z	X Z
++	0-	0-	++
X Z	XZ	xz	x z
++ X Z	xz	xz	++ X Z

Table 19: Generalised Sequence Aggregations

Proof (Table 19).

- 1. From Definition 47, it follows that *A* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
- 2. For *B*:
 - (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 - (b) For the aggregation types: SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 - $\overset{+0}{\mathbf{xz}}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 - \mathbf{x}^{0+} (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From the hypothesis and 1., it follows that SEQ(A,B) contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 - iii. From ii. and Definition 47, it follows that the aggregation is correctly classified as $\overset{++}{xz}$.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 17.

- **00 xz** (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 SEQ(A,B) i. The correctness of this row follows directly from Lemma 16.
 AND(A,B) i. The correctness of this row follows directly from Lemma 17.
- (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
- (b) For the aggregation types: SEQ(A,B) i. The correctness of this row follows directly from Lemma 18. AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 +xz (a) From Definition 52, it follows that B contains an execution containing a x, there is
 - (a) From Definition 32, it follows that B contains an execution containing a x, there no y on its right, and there is a k on the right, with no z on the right of the k.
 (b) For the aggregation types:
 - $SEQ(A, \overline{B})$ i. The correctness of this row follows directly from Lemma 18. AND(A, B) i. The correctness of this row follows directly from Lemma 17.
- $\mathbf{x}^{\mathbf{0}}_{\mathbf{z}}$ (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 AND(A,B) i. The correctness of this row follows directly from Lemma 17.
- \overline{xz} (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 17.

А	В	SEQ(A, B)	AND(A, B)
+0	++	++	++
XZ	X Z	x z	X Z
+0	+0	+0	+0
XZ	XZ	XZ	XZ
+0	0+	++	++
XZ	X Z	x z	X Z
+0	00	+0	+0
XZ	XZ	XZ	XZ
+0	$\mathbf{x}\mathbf{z}^{+}$		++
XZ		xz	X Z
+0	+-	+-	+0
XZ	x z	x z	XZ
+0	0-	0-	+0
XZ	X Z	xz	XZ
+0 XZ		xz	+0 XZ

Table 20: Generalised Sequence Aggregations

Proof (Table 20).

- 1. From Definition 48, it follows that A contains an execution where a x, and there are no y or k on its right.
- 2. For *B*:
 - (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.

(b) For the aggregation types:

SEQ(A,B) i. The correctness of this row follows directly from Lemma 18. AND(A,B) i. The correctness of this row follows directly from Lemma 17.

- $\overset{+0}{\mathbf{xz}}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.
 - AND(A,B) i. From 1. and (a), it follows that neither A or B contain elements
 - capable of improving the classification over $\overset{+0}{xz}$, following the preference order in Figure 24.
 - ii. From i., the result of column SEQ and Lemma 6, it follows that the aggregation is correctly classified.
- \mathbf{x}^{0+} (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From 1., (a), and i., it follows that SEQ(*A*,*B*) contains a *x* and a *z* on its right, with no *y* on the right of the *x*, and no *k* on the right of the *z*.
 - iii. From ii. and Definition 47, it follows that the aggregation is correctly classified as $\frac{++}{xz}$
 - AND(A,B) i. From the result of column SEQ and Lemma 6, it follows that the aggregation is correctly classified.
- (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 16. AND(A,B) i. The correctness of this row follows directly from Lemma 16.
- (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains the z from B and has the x from A on the left of z and on the right of y of B.
 - iii. From ii. and Definition 47, it follows that the aggregation is correctly classified as $\frac{++}{xz}$.
- $\mathbf{x}\mathbf{\overline{z}}$ (a) From Definition 52, it follows that *B* contains an execution containing a *x*, there is no y on its right, and there is a *k* on the right, with no *z* on the right of the *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From i. and Lemma 6, it follows that the executions of SEQ(B,A) are included in AND(A,B).
 - iii. From ii., Lemma 19 and the preference lattice in Figure 24, it follows that a classification of SEQ(A,B) is $\stackrel{+0}{xz}$.

- iv. From 1. and (a), it follows that *B* does not contain elements capable of improving the classification over $\stackrel{+0}{xz}$.
- v. From iii., iv. and Lemma 6 it follows that the aggregation is correctly classified as $\stackrel{+0}{xz}$.
- \mathbf{x}^{-} (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From i. and Lemma 6, it follows that the executions of SEQ(*B*,*A*) are included in AND(*A*,*B*).
 - iii. From ii., Lemma 19 and the preference lattice in Figure 24, it follows that a classification of SEQ(A, B) is $\stackrel{+0}{xz}$.
 - iv. From 1. and (a), it follows that *B* does not contain elements capable of improving the classification over $\frac{+0}{xz}$.
 - v. From iii., iv. and Lemma 6 it follows that the aggregation is correctly classified as $\frac{+0}{xz}$.
- \overline{xz} (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From i. and Lemma 6, it follows that the executions of SEQ(*B*,*A*) are included in AND(*A*,*B*).
 - iii. From ii., Lemma 19 and the preference lattice in Figure 24, it follows that a classification of SEQ(A, B) is $\stackrel{+0}{xz}$.
 - iv. From 1. and (a), it follows that *B* does not contain elements capable of improving the classification over xz.
 - v. From iii., iv. and Lemma 6 it follows that the aggregation is correctly classified as $\overset{+0}{xz}$.

Proof (Table 21).

- 1. From Definition 49, it follows that *A* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
- 2. For *B*:
 - $\dot{\mathbf{x}}$ (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 - (b) For the aggregation types:SEQ(*A*, *B*) i. The correctness of this row follows directly from Lemma 18.AND(*A*, *B*) i. The correctness of this row follows directly from Lemma 17.
 - $\overset{+0}{\mathbf{xz}}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.

А	В	SEQ(A, B)	AND(A, B)
0+	++	++	++
XZ	X Z	x z	xz
0+	+0	${\substack{0+ \ \mathbf{xz}}}^{+0}$ / ${\substack{+0 \ \mathbf{xz}}}$	++
XZ	XZ		x z
0+	0+	0+	0+
XZ	X Z	xz	xz
0+	00	0+	0+
XZ	XZ	xz	xz
0+	$\mathbf{x}\mathbf{z}^{+}$	-+	
XZ		x z	xz
0+	+−	+-	++
XZ	X Z	x z	X Z
0+	0-	0-	0+
XZ	XZ	xz	xz
$\frac{0}{xz}$		xz	-+ x z

Table 21: Generalised Sequence Aggregations

- AND(*A*,*B*) i. The correctness of this row follows directly from the result of row $\overset{+0}{xz}$ and $\overset{0+}{xz}$ in Table 20, and Lemma 9
- \mathbf{x}^{0+} (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From 1., (a), and i., it follows that the execution of *A* appended on the left of the execution of *B* does not contain any element capable of manipulating the value of **x** is the classification.
 - iii. From ii. it follows that the classification it correct.
 - AND(*A*,*B*) i. From 1. and (a), it follows that neither *A* or *B* contain elements capable of improving the classification over $\stackrel{+0}{xz}$, following the preference
 - capable of improving the classification over **xz**, following the preference order in Figure 24.
 - ii. From i., the result of column SEQ and Lemma 6, it follows that the aggregation is correctly classified.
- **00 xz** (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 16.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
- $\mathbf{x}\mathbf{z}^+$ (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of A interleaved with an execution of B.
 - ii. From 1., (a), and i., it follows that *A* does not contain elements capable of improving the classification of **x**.
 - iii. From i. Lemma 6 and the SEQ(*A*,*B*) result, it follows that the aggregation is correctly classified as $\overline{\mathbf{x}}_{\mathbf{z}}^+$.
- $\mathbf{x}\mathbf{z}$ (a) From Definition 52, it follows that *B* contains an execution containing a *x*, there is no *y* on its right, and there is a *k* on the right, with no *z* on the right of the *k*.

- (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of A interleaved with an execution of B.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains the *z* from *A* and has the *x* from *B* on the left of *z* and on the right of *y* of *B*.
 - iii. From ii. and Definition 47, it follows that the aggregation is correctly classified as $\overset{++}{\mathbf{x}}$.
- $\mathbf{x}^{\mathbf{0}}$ (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(*A*, *B*) contains the *z* from *A* while the *k* from *B* is attached on the left, making it irrelevant.
 - iii. From ii. and Definition 49 it follows that the aggregation is correctly classified as $\stackrel{0+}{xz}$.
- $\overline{\mathbf{xz}}$ (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains z from A while every other element from B is on the left, where the only relevant one is y.
 - iii. From ii. and Definition 51 it follows that the aggregation is correctly classified as $\mathbf{x}_{\mathbf{z}}^{-+}$.

А	В	SEQ(A, B)	AND(A, B)
00	++	++	++
XZ	X Z	X Z	X Z
00	+0	+0	+0
XZ	XZ	XZ	XZ
00	0+	0+	0+
XZ	XZ	xz	XZ
00	00	00	00
XZ	XZ	XZ	XZ
00	$\mathbf{x}\mathbf{z}^{+}$	-+	-+
XZ		x z	xz
00	+-	+-	+-
XZ	X Z	x z	xz
00	0-	0-	0-
XZ	XZ	XZ	XZ
00 XZ	xz	xz	

Table 22: Generalised Sequence Aggregations

Proof (Table 22).

- From Definition 50, it follows that A contains an execution where a there are no x, y, z and k.
 For B:
- 2. For B:
 - (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 - (b) For the aggregation types: SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 - $\overset{+0}{xz}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A, B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
 - $\overset{\mathbf{0}}{\mathbf{x}} \overset{\mathbf{0}}{\mathbf{z}}$ (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types: SEQ(A, B) i. The correctness of this row follows directly from Lemma 16.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
 - **00 xz** (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 16. AND(A,B) i. The correctness of this row follows directly from Lemma 16.
 - $\mathbf{x}\mathbf{z}^+$ (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
 - (a) From Definition 52, it follows that B contains an execution containing a x, there is no y on its right, and there is a k on the right, with no z on the right of the k.
 (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18. AND(A,B) i. The correctness of this row follows directly from Lemma 16.
 - $\mathbf{x}^{\mathbf{0}}_{\mathbf{x}}$ (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
 - $\mathbf{x}\mathbf{z}$ (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.

Proof (Table 23).

- 1. From Definition 51, it follows that A contains an execution containing a z, there is no k on its right, and there is a y on the z left.
- 2. For *B*:

А	В	SEQ(A, B)	AND(A, B)
$\mathbf{x}\mathbf{z}^{+}$	++	++	++
	X Z	X Z	X Z
$\mathbf{x}\mathbf{z}^{+}$	+0 XZ	$^{-+}_{xz}$ / $^{+0}_{xz}$	++ X Z
$\mathbf{x}\mathbf{z}^+$	0+	-+	-+
	XZ	x z	xz
$\mathbf{x}\mathbf{z}^+$	00	-+	
	XZ	x z	xz
$\mathbf{x}\mathbf{z}^+$	$\mathbf{x}\mathbf{z}^{+}$	-+ x z	xz
$\mathbf{x}\mathbf{z}^+$	+-	+-	++
	X Z	x z	X Z
$\mathbf{x}\mathbf{z}^{+}$	0-	0-	
	XZ	xz	xz
$\frac{-+}{\mathbf{x}\mathbf{z}}$	xz	xz	-+ x z

Table 23: Generalised Sequence Aggregations

- $\mathbf{x}\mathbf{z}^{++}$ (a) From Definition 47, it follows that B contains an execution where a x is followed by or on the same task as a z, and there are no y or k on their respective right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A, B) i. The correctness of this row follows directly from Lemma 17.
- $\overset{+0}{xz}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no y or k on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.
 - $AND(\overline{A}, B)$ i. The correctness of the aggregation follows directly from Lemma 9 and row $\overset{+0}{xz}$ and $\overset{-+}{xz}$ of Table 20.
- and y, contains a z, and there is no k on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From 1., (a), and i., it follows that the evaluation of x from A cannot be influenced by B appended on the left, while the evaluation of z is not influenced by the classification of B.
 - iii. From ii. it follows that the classification of the aggregation is correct.
 - AND(A,B) i. The correctness of the aggregation follows directly from Lemma 9 and row $\overset{0+}{xz}$ and $\overset{-+}{xz}$ of Table 21.
- ⁰⁰ (a) From Definition 50, it follows that *B* contains an execution where a there are no x, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - SEQ(A, B) i. The correctness of this row follows directly from Lemma 16.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
- $\mathbf{x}\mathbf{z}^+$ (a) From Definition 51, it follows that B contains an execution containing a z, there is no k on its right, and there is a y on the z left.
 - (b) For the aggregation types:
 - SEQ(A, B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A, B) i. From 1. and (a), it follows that neither A or B contain elements
 - capable of improving the classification over $\mathbf{x}^{+}\mathbf{z}$, following the preference order in Figure 24.

- From i., the result of column SEQ and Lemma 6, it follows that the aggregation is correctly classified.
- $\mathbf{x}\mathbf{z}$ (a) From Definition 52, it follows that *B* contains an execution containing a *x*, there is no *y* on its right, and there is a *k* on the right, with no *z* on the right of the *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of A interleaved with an execution of B.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains z from A, and on its left appears the x from B, while the y from A is kept on the left of x and the k from B on the left of the z from A.
 - iii. From ii. and Definition 47, it follows that the aggregation is correct.
- $\mathbf{x}\mathbf{z}^{0-}$ (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - SEQ(A, B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains the z from B and keeps the k from A on the left, making it irrelevant. The execution still contains a y on the left of z and no x on the right of y.
 - iii. From ii. and Definition 51, it follows that the aggregation is correct.
- \overline{xz} (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains the *z* from *B* and keeps the *k*, and eventual *y*, from *A* on the left, making it irrelevant. The execution still contains a *y* on the left of *z* and no *x* on the right of *y*.
 - iii. From ii. and Definition 51, it follows that the aggregation is correct.

Proof (Table 24).

- 1. From Definition 52, it follows that *A* contains an execution containing a *x*, there is no *y* on its right, and there is a *k* on the right, with no *z* on the right of the *k*.
- 2. For *B*:
 - (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 (b) For the aggregation types:
 - (b) For the aggregation types. SEQ(A,B) i. The correctness of this row follows directly from Lemma 18. AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 - $\overset{+0}{\mathbf{xz}}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.

А	В	SEQ(A, B)	AND(A, B)
+-	++	++	++
X Z	X Z	X Z	X Z
+−	+0	$+0 \\ xz$	+0
X Z	XZ		XZ
+−	0+	++	++
X Z	XZ	x z	x z
+-	00	+-	+-
X Z	XZ	x z	x z
+-	$\mathbf{x}\mathbf{z}^{+}$	-+	++
X Z		x z	X Z
+-	+-	+-	+-
X Z	x z	x z	xz
+- X Z	$\frac{0}{XZ}$	$\frac{0}{\mathbf{x}\mathbf{z}}$	+- xz
+- x z	xz	xz	+- x z

Table 24: Generalised Sequence Aggregations

- AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\overset{+0}{\mathbf{xz}}$ and $\overset{+-}{\mathbf{xz}}$ of Table 20.
- \mathbf{x}^{0+} **x** (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From 1., (a), and i., it follows that the *z* in *B* is on the right of the *k* from *A*, while the *x* from *A* is on the left of *x*, and no *y* is contained.
 - iii. From ii. and Definition 47, it follows that the classification of the aggregation is correct.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 6, the result of the column SEQ(A, B) and the preference lattice in Figure 24.
- (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - $SEQ(A, \vec{B})$ i. The correctness of this row follows directly from Lemma 16.
 - AND(A, B) i. The correctness of this row follows directly from Lemma 16.
- \vec{x} (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
 - (b) For the aggregation types:
 - SEQ(A, B) i. The correctness of this row follows directly from Lemma 18.
 - AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$ of Table 20.
- (a) From Definition 52, it follows that B contains an execution containing a x, there is no y on its right, and there is a k on the right, with no z on the right of the k.
 (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18. AND(A,B) i. The correctness of this row follows directly from Lemma 20.
- xz (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - $SEQ(A, \tilde{B})$ i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of A interleaved with an execution of B.

- ii. From 1., (a) and i., it follows that a valid execution of AND(*A*, *B*) contains the *x* and *k* from *A* in the same order, while the *k* from *B* is attached on the left, making it irrelevant.
- iii. From ii. and Definition 52 it follows that the aggregation is correctly classified as $\frac{+}{xz}$.
- $\overline{\mathbf{xz}}$ (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A, B) i. From Definition 4, it follows that each execution resulting from AND(A, B) consists of an execution of A interleaved with an execution of B.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains the *x* and *k* from *A* in the same order, while the *k*, and eventual *y*, from *B* is attached on the left, making it irrelevant.
 - iii. From ii. and Definition 52 it follows that the aggregation is correctly classified as $\frac{+}{xz}$.

А	В	SEQ(A, B)	AND(A, B)
0-	++	++	++
XZ	X Z	X Z	xz
0-	+0	+0	+0
XZ	XZ	XZ	XZ
0-	0+	0+	0+
XZ	X Z	xz	xz
0-	00	0-	0-
XZ	XZ	xz	xz
0-	$\mathbf{x}\mathbf{z}^{+}$		
XZ		x z	xz
0-	+−	+-	+-
XZ	x z	x z	x z
0-	$\frac{0}{xz}$	0-	0-
XZ		xz	xz
$\frac{0}{xz}$		xz	xz

Table 25: Generalised Sequence Aggregations

Proof (Table 25).

- 1. From Definition 53, it follows that A contains an execution containing a k with no z on its right, and not containing any x or y.
- 2. For *B*:
 - (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 (b) For the aggregation types:
 - (b) For the aggregation types. SEQ(A,B) i. The correctness of this row follows directly from Lemma 18. AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 - $\overset{+0}{\mathbf{xz}}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.

- AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\frac{+0}{\mathbf{xz}}$ and $\frac{0}{\mathbf{xz}}$ of Table 20.
- $\overset{\mathbf{0}}{\mathbf{xz}}$ (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From 1., (a), and i., it follows that the *z* in *B* is on the right of the *k* from *A*, while no *y* is contained.
 - iii. From ii. and Definition 49, it follows that the classification of the aggregation is correct.
 - AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}^{\mathbf{0}+}_{\mathbf{x}}$ and $\mathbf{x}^{\mathbf{0}-}_{\mathbf{z}}$ of Table 21.
- **00 xz** (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 16.
 - AND(A, B) i. The correctness of this row follows directly from Lemma 16.
- (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$ of Table 23.
- $\mathbf{x}\mathbf{z}^+$ (a) From Definition 52, it follows that *B* contains an execution containing a *x*, there is no *y* on its right, and there is a *k* on the right, with no *z* on the right of the *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(*A*, *B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\stackrel{+}{\mathbf{x}\mathbf{z}}$ and $\stackrel{0}{\mathbf{x}\mathbf{z}}$ of Table 24.
- $\mathbf{x}^{\mathbf{0}}_{\mathbf{z}}$ (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 20.
- $\overline{\mathbf{xz}}$ (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A,B) i. From Definition 4, it follows that each execution resulting from AND(A,B) consists of an execution of *A* interleaved with an execution of *B*.
 - ii. From 1., (a) and i., it follows that a valid execution of AND(A, B) contains the *k* from *A* and *y* from *B*. The order is not relevant.
 - iii. From ii. and Definition 54 it follows that the aggregation is correctly classified as \overline{xz} .

Proof (Table 26).

Α	В	SEQ(A, B)	AND(A, B)
	++ X Z	++ X Z	++ X Z
	+0 XZ	$+0 \\ xz$	+0 XZ
	0+ XZ	 x z	 xz
	00 XZ	xz	xz
xz	−+ xz	 xz	 xz
	+- X Z	+- X Z	+- X Z
xz	0- XZ	xz	xz
xz	xz	xz	xz

Table 26: Generalised Sequence Aggregations

- 1. From Definition 54, it follows that every execution in A contains a y and a k with no x and z on their respective rights, OR contains a y with no x on its right, and no z or k.
- 2. For *B*:
 - (a) From Definition 47, it follows that *B* contains an execution where a *x* is followed by or on the same task as a *z*, and there are no *y* or *k* on their respective right.
 - (b) For the aggregation types:
 SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 AND(A,B) i. The correctness of this row follows directly from Lemma 17.
 - $\overset{+0}{\mathbf{xz}}$ (a) From Definition 48, it follows that *B* contains an execution where a *x*, and there are no *y* or *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 19 and the preference lattice in Figure 24.

AND(A,B) i. asdf

- $\overset{\mathbf{0}}{\mathbf{xz}}$ (a) From Definition 49, it follows that *B* contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
 - (b) For the aggregation types:
 - SEQ(A,B) i. From Definition 4, it follows that the possible executions of a process block SEQ(A,B) are the concatenation of an execution of A and an execution of B.
 - ii. From 1., (a), and i., it follows that the *z* in *B* is on the right of the *y*, and eventual *k* from *A*.
 - iii. From ii. and Definition 51, it follows that the classification of the aggregation is correct.
 - AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$ of Table 21.
- **00 xz** (a) From Definition 50, it follows that *B* contains an execution where a there are no *x*, *y*, *z* and *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 16.
 - AND(A,B) i. The correctness of this row follows directly from Lemma 16.
- \vec{x} (a) From Definition 51, it follows that *B* contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.

- AND(*A*,*B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$ of Table 23.
- $\mathbf{x}\mathbf{z}^+$ (a) From Definition 52, it follows that *B* contains an execution containing a *x*, there is no *y* on its right, and there is a *k* on the right, with no *z* on the right of the *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A, B) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$ of Table 24.
- \mathbf{x}^{-} (a) From Definition 53, it follows that *B* contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(*A*, *B*) i. The correctness of the aggregation follows directly from Lemma 9 and row $\mathbf{x}\mathbf{z}$ and $\mathbf{x}\mathbf{z}$ of Table 25.
- $\overline{\mathbf{xz}}$ (a) From Definition 54, it follows that every execution in *B* contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
 - (b) For the aggregation types:
 - SEQ(A,B) i. The correctness of this row follows directly from Lemma 18.
 - AND(A, B) i. The correctness of this row follows directly from Lemma 20.

C.6 Aggregating GSP with ISP for AND Overnode Evaluation

When evaluating an overnode of type A for $\overline{A}\Delta 2.1$ or $\overline{A}\Delta 2.2$, its overnode child is classified according to the *Generalised Sequence Pattern*, while its direct undernode children are classified according to the *Interval Sub-Pattern*. The following tables illustrate the classification of an overnode of type AND where its overnode child classification is aggregated with the overall aggregation of its direct children classification according to the interval sub-pattern aggregation tables.

Lemmas

Lemma 21 (Aggregation Neutral Class). Given a process block A, assigned to the evaluation

class \underline{xz} , and another process block *B*, assigned to any of the available evaluation classes. Let *C* be a process block having *A* and *B* as its sub-blocks, then the evaluation class of *C* is the same class as the process block *B*.

Proof. This proof follows closely the proof for Lemma 4.

Lemma 22 (Super Elements). $\overset{++}{\mathbf{x}\mathbf{z}\mathbf{t}}$ and $\overset{++}{\mathbf{x}\mathbf{z}}$

Proof. As the aggregations between a GSP class and an ISP class is always done when the common parent overnode is of type AND, the proof follows closely the proof for Lemma 17.

Lemma 23 (Hide the Bubu). When evaluating an AND overnode and one of the elements being

aggregated is classified as $\overline{\mathbf{x}}$, then the resulting classification is always the overnode classification corresponding to the other element.

Proof. The worst element classification, \underline{xz} , as it cannot improve any classification the aggregation as it involves an AND block it always allows to "hide" the *problematic* segment on the right of *t*, hence not modifying (i.e. making it worse) the current classification on the stem.

Overnode Child	Undernode Children	Result
		±±
xzt	$\frac{\mathbf{X}\mathbf{Z}}{\mathbf{X}\mathbf{Z}}$	xzt
*++ xzt	+0 <u>XZ</u>	*++ xzt
x^{++}_{zt}	0+ <u>XZ</u>	*++ xzt
*++ xzt	+- <u>XZ</u>	*++ xzt
*++ xzt	00 <u>XZ</u>	*++ xzt
$\frac{+}{xzt}$	<u>-+</u> <u>X Z</u>	xzt
++ x z t	xz	xzt

Table 27: Aggregation Table AND Overnode

Aggregations

Proof (Table 27).

1. The Overnode Child is classified as $\overset{++}{\mathbf{x}}\mathbf{zt}$.

2. For Undernode Children:

- $\frac{++}{\mathbf{x}\mathbf{z}}$ The correctness of the row follows directly from Lemma 22.
- $\frac{+0}{xz}$ The correctness of the row follows directly from Lemma 22. $\frac{0}{xz}$ The correctness of the row follows directly from Lemma 22.

- $\frac{+-}{\mathbf{x}\mathbf{z}}$ The correctness of the row follows directly from Lemma 22.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- $\mathbf{x}\mathbf{z}^+$ The correctness of the row follows directly from Lemma 22.
- \underline{xz} The correctness of the row follows directly from Lemma 23.

Overnode Child	Undernode Children	Result
+0 xzt	++ <u>X Z</u>	*±t
+0 xzt	+0 <u>XZ</u>	+0 xzt
$+0 \\ xzt$	$\frac{0+}{XZ}$	*** xzt
+0 xzt	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	+0 xzt
$+0 \\ xzt$	00 <u>XZ</u>	+0 xzt
+0 xzt	<u>-+</u> <u>X Z</u>	*++ xzt
+0 xzt	<u>xz</u>	+0 xzt

Table 28: Aggregation Table AND Overnode

Proof (Table 28).

- 1. From Definition 48, it follows that Overnode Child contains an execution where a x, and there are no y or k on its right.
- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 22.
 - $\frac{+0}{xz}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a x and no y or z.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the z sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the t from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.
 - $\frac{0+}{xz}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a z and no y or x.
 - (b) From 1., 2. and (a), it follows that the z from Undernode Children can be put between the x and the t from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
 - $\mathbf{x}\mathbf{z}$ (a) From Definition 34, it follows that Overnode's Undernode Children contains an execution containing a x and a y on its right, while not containing z.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the z sub-classification of Overnode Child.

- (c) From 2., it follows that the execution of Undernode Children can be put on the right of the t from Overnode Child.
- (d) From (b) and (c), it follows that the classification is correct.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1., 2. and (a), it follows that the *z* from Undernode Children can be put between the *x* and the *t* from Overnode Child, while the *y* from Undernode Children can be put on the left of *x* from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
- \underline{xz} The correctness of the row follows directly from Lemma 23.

Overnode Child	Undernode Children	Result
⁰⁺ xzt	++ <u>X Z</u>	*±t
0+ xzt	+0 <u>xz</u>	*±t
⁰⁺ xzt	0+ <u>XZ</u>	0+ xzt
0+ xzt	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	*++ xzt
0+ xzt	00 <u>xz</u>	0+ xzt
0+ xzt	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	0+ xzt
⁰⁺ xzt	<u>xz</u>	0+ xzt
11 00 1	THE THE AND O	

Table 29: Aggregation Table AND Overnode

Proof (Table 29).

- 1. From Definition 49, it follows that Overnode Child contains an execution where a there are no *x* and *y*, contains a *z*, and there is no *k* on its right.
- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 22.
 - $\frac{+0}{xz}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - (b) From 1., 2. and (a), it follows that the x from Undernode Children can be put on the left of the z and the t from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{XZ}}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the **x** sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the *t* from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.

- (a) From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a x and a y on its right, while not containing z.
 - (b) From 1., 2. and (a), it follows that the *x* from Undernode Children can be put on the left of the *z* and the *t* from Overnode Child, while the *y* from Undernode Children can be put on the right of *t* from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- $\underline{x}\underline{z}$ (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the **x** sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the *t* from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.
- $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 23.

Overnode Child	Undernode Children	Result
00 xzt	++ <u>X Z</u>	*++ xzt
00 xzt	+0 <u>XZ</u>	+0 xzt
00 xzt	$\frac{0+}{XZ}$	xzt
00 xzt	+- <u>X Z</u>	+0 xzt
00 xzt	00 <u>XZ</u>	00 xzt
00 xzt	<u>-+</u> <u>X Z</u>	$\frac{00}{xzt}$ / $\frac{-+}{xzt}$
00 xzt	XZ	00 xzt

Table 30: Aggregation Table AND Overnode

Proof (Table 30).

- 1. From Definition 50, it follows that Overnode Child contains an execution where a there are no *x*, *y*, *z* and *k*.
- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 22.
 - $\frac{+0}{\underline{xz}}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a x and no y or z.
 - (b) From 1. and (a), it follows that the *x* from the Undernode Children can be placed on the left of the *t* from Overnode Child.
 - (c) From (b) and Definition 48, it follows that the classification of the aggregation is correct.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - (b) From 1. and (a), it follows that the *z* from the Undernode Children can be placed on the left of the *t* from Overnode Child.

- (c) From (b) and Definition 49, it follows that the classification of the aggregation is correct.
- **XZ** (a) From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a x and a y on its right, while not containing z.
 - (b) From 1. and (a), it follows that the *x* from the Undernode Children can be placed on the left of the *t* from Overnode Child, while the *y* from Undernode Children can be put on the right of the *t*.
 - (c) From (b) and Definition 48, it follows that the classification of the aggregation is correct.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1. and (a), it follows that the whole execution from Undernode Children can be put on the right of *t* from Overnode Child.
 - (c) From 1. and (a), it follows that the *y* and *z* from Undernode children can be placed on the left of *t* from Overnode Child.
 - (d) From (b) and Definition 50, it follows that $\overset{00}{\text{xzt}}$ is a valid classification.
 - (e) From (c) and Definition 51, it follows that $\mathbf{x}\mathbf{z}\mathbf{t}$ is a valid classification.
 - (f) From (d), (e) and the preference orders in Figure 24, it follows that both classifications are viable.
- xz The correctness of the row follows directly from Lemma 23.

Overnode Child	Undernode Children	Result
xzt	++ X Z	*++ xzt
xzt	+0 <u>XZ</u>	*++ xzt
xzt	$\frac{0+}{\mathbf{X}\mathbf{Z}}$	xzt
xzt	+- <u>X Z</u>	xzt
$\mathbf{x}\mathbf{z}\mathbf{t}$	00 <u>XZ</u>	$\mathbf{x}\mathbf{z}\mathbf{t}$
xzt	<u>-+</u> <u>X Z</u>	$\frac{-+}{xzt}$
$\mathbf{x}\mathbf{z}\mathbf{t}$	xz	$x^{-+}zt$

Table 31: Aggregation Table AND Overnode

Proof (Table 31).

- 1. From Definition 51, it follows that Overnode Child contains an execution containing a *z*, there is no *k* on its right, and there is a *y* on the *z* left.
- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 22.
 - $\frac{+0}{\underline{xz}}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a x and no y or z.
 - (b) From 1., 2. and (a), it follows that the *x* from Undernode Children can be put on the left of the *z* and the *t* from Overnode Child, while still being on the right of the *y* from Overnode Child.

- (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
- $\frac{\mathbf{0}_{\pm}}{\mathbf{XZ}}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the **x** sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the *t* from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.
- (a) From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a x and a y on its right, while not containing z.
 - (b) From 1., 2. and (a), it follows that the *x* from Undernode Children can be put on the left of the *z* and the *t* from Overnode Child and having the *y* from Overnode Child on its left, while the *y* from Undernode Children can be put on the right of *t* from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the x sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the *t* from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 23.

Overnode Child	Undernode Children	Result
xzt	++ <u>XZ</u>	*++ xzt
xzt	+0 XZ	*_t
*-t	0+ <u>XZ</u>	*++ xzt
$\mathbf{x} \mathbf{z} \mathbf{t}$	<u>+-</u> <u>XZ</u>	*zt
xzt	00 <u>xz</u>	*t
xzt	<u>-+</u> <u>XZ</u>	*++ xzt
$\frac{+}{xzt}$	xz	xzt

Table 32: Aggregation Table AND Overnode

Proof (Table 32).

- 1. From Definition 52, it follows that Overnode Child contains an execution containing a x, there is no y on its right, and there is a k on the right, with no z on the right of the k.
- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 22.

- $\frac{+0}{\underline{xz}}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the z sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the *t* from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.
- $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - (b) From 1., 2. and (a), it follows that the *z* from Undernode Children can be put between the *x* and the *t* from Overnode Child, while also being on the right of the *k* from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
- (a) From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a x and a y on its right, while not containing z.
 - (b) From 1. and (a), it follows that the Undernode Children do not contain elements to improve the classification for the z sub-classification of Overnode Child.
 - (c) From 2., it follows that the execution of Undernode Children can be put on the right of the *t* from Overnode Child.
 - (d) From (b) and (c), it follows that the classification is correct.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1., 2. and (a), it follows that the *z* from Undernode Children can be put between the *x* and the *t* from Overnode Child, while also being on the right of the *k* from Overnode Child. Moreover the *y* from Undernode Children can be put on the left of *x* from Overnode Child.
 - (c) From (b) and Definition 47, it follows that the classification of the aggregation is correct.
- xz The correctness of the row follows directly from Lemma 23.

Overnode Child	Undernode Children	Result
⁰⁻ xzt	++ <u>X Z</u>	*++ xzt
0- xzt	+0 <u>XZ</u>	+0 xzt
⁰⁻ xzt	$\frac{0+}{XZ}$	$x^{-+}zt$
$\frac{0}{xzt}$	+- <u>X Z</u>	+0 xzt
⁰⁻ xzt	00 <u>XZ</u>	0- xzt
$\frac{0}{xzt}$	$\frac{-+}{\mathbf{X}\mathbf{Z}}$	$\frac{0}{xzt}/\frac{-}{xzt}$
0- xzt	<u> </u>	0- xzt

Table 33: Aggregation Table AND Overnode

Proof (Table 33).

1. From Definition 53, it follows that Overnode Child contains an execution containing a *k* with no *z* on its right, and not containing any *x* or *y*.

- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}^{++}$ The correctness of the row follows directly from Lemma 22.
 - $\frac{+0}{\underline{xz}}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.
 - (b) From 1., 2. and (a), it follows that the *x* from Undernode Children can be placed immediately on the left of the *t* from the Overnode Child.
 - (c) From (b) and Definition 48, it follows that the classification of the aggregation is correct.
 - $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - (b) From 1., 2. and (a), it follows that the *z* from Undernode Children can be placed immediately on the left of the *t* from the Overnode Child.
 - (c) From (b) and Definition 51, it follows that the classification of the aggregation is correct.
 - **<u>x</u>** (a) From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and a *y* on its right, while not containing *z*.
 - (b) From 1., 2. and (a), it follows that the x from Undernode Children can be placed immediately on the left of the t from the Overnode Child, while the y from the Undernode Children is set on the right of the t.
 - (c) From (b) and Definition 48, it follows that the classification of the aggregation is correct.
 - $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
 - (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1., 2. and (a), it follows that the *z* from Undernode Children can be placed immediately on the left of the *t* from the Overnode Child.
 - (c) From 1., 2. and (a), it follows that the whole execution from Undernode Children can be placed on the right of the *t* from the Overnode Child.
 - (d) From (b) and Definition 51, it follows that \vec{xzt} is a valid classification of the aggregation.
 - (e) From (c) and Definition 53, it follows that \mathbf{xzt}^{0-} is a valid classification of the aggregation.
 - (f) From (d), (e) and the preference orders in Figure 24, it follows that both classifications are viable.
 - $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 23.

Proof (Table 34).

- 1. From Definition 50, it follows that every execution of the Overnode Child contains a *y* and a *k* with no *x* and *z* on their respective rights, OR contains a *y* with no *x* on its right, and no *z* or *k*.
- 2. The aggregation is of type AND and from Definition 4, it follows that each execution resulting from the aggregation consists of an execution of Overnode Child interleaved with an execution of Undernode Children.
- 3. For Undernode Children:
 - $\mathbf{x}\mathbf{z}$ The correctness of the row follows directly from Lemma 22.
 - $\frac{+0}{\underline{xz}}$ (a) From Definition 32, it follows that *Overnode's Undernode Children* contains an execution containing a *x* and no *y* or *z*.

Overnode Child	Undernode Children	Result
xzt	++ <u>X Z</u>	*++ xzt
xzt	+0 <u>XZ</u>	+0 xzt
xzt	0+ <u>xz</u>	xzt
xzt	$\frac{+-}{\mathbf{X}\mathbf{Z}}$	+0 xzt
xzt	00 <u>xz</u>	xzt
xzt	<u>-+</u> <u>X Z</u>	xzt
xzt	xz	xzt

Table 34: Aggregation Table AND Overnode

- (b) From 1., 2. and (a), it follows that the *x* from Undernode Children can be placed immediately on the left of the *t* from the Overnode Child.
- (c) From (b) and Definition 48, it follows that the classification of the aggregation is correct.
- $\frac{\mathbf{0}_{\pm}}{\mathbf{x}\mathbf{z}}$ (a) From Definition 33, it follows that *Overnode's Undernode Children* contains an execution containing a *z* and no *y* or *x*.
 - (b) From 1., 2. and (a), it follows that the z from Undernode Children can be placed immediately on the left of the t from the Overnode Child.
 - (c) From (b) and Definition 51, it follows that the classification of the aggregation is correct.
- (a) From Definition 34, it follows that *Overnode's Undernode Children* contains an execution containing a x and a y on its right, while not containing z.
 - (b) From 1., 2. and (a), it follows that the *x* from Undernode Children can be placed immediately on the left of the *t* from the Overnode Child, while the *y* from the Undernode Children is set on the right of the *t*.
 - (c) From (b) and Definition 48, it follows that the classification of the aggregation is correct.
- $\frac{00}{xz}$ The correctness of the row follows directly from Lemma 21.
- $\vec{x}\vec{z}$ (a) From Definition 36, it follows that *Overnode's Undernode Children* contains an execution containing a z and a y on its left, while not containing x.
 - (b) From 1., 2. and (a), it follows that the *z* from Undernode Children can be placed immediately on the left of the *t* from the Overnode Child.
 - (c) From (b) and Definition 51, it follows that the classification of the aggregation is correct.
- $\overline{\mathbf{xz}}$ The correctness of the row follows directly from Lemma 23.

C.7 Interleaved Generic Pattern

Definition 55 (k). generic pattern fulfilling state: there exists an execution belonging to the process block containing a task having d annotated, and not containing the failing annotation. Formally:

Given a process block B, it belongs to this class if and only if:

- $\exists \varepsilon \in \Sigma(B)$ such that:

• $\exists t_k \in \varepsilon$ and

• $\not\exists t_y \in \varepsilon$ such that t_y is the same task as t_k .

Definition 56 (k). *neutral state: the block cannot be classified as* \mathbf{k} . Formally:

Given a process block B, it belongs to this class if and only if:

- $\forall \varepsilon \in \Sigma(B)$ such that either:

 - $\not\exists t_k \in \varepsilon$ or, $\forall t_k \in \varepsilon, \exists t_y \text{ such that } t_k \text{ and } t_y \text{ are the same task.}$

Theorem 13 (Classification Completeness for Interleaved Generic Pattern). The set of possible evaluations of Interleaved Generic Pattern is completely covered by the provided set of classifications.

Proof. As the classification for the Interleaved Generic Pattern is binary, we can see that the completeness is given by the two mutually exclusive and complementary classes in Definition 55 and Definition 56.

А	В	SEQ(A, B)	AND(A, B)
0	0	0	0
k	k	k	k
0	+	+	+
k	k	k	k
+	0	+	+
k	k	k	k
+	+	+	+
k	12	k	k

 K K
 K

 Table 35: Interleaved Generic Pattern Aggregation

Aggregations

Proof (Table 35). The table checks whether exists a task with a given property in a possible execution of the block being evaluated. Therefore either the task exists (\mathbf{k}) and it therefore keeps existing in every further aggregation, or it does not (\mathbf{k}) but the classification can still be overwritten when it is aggregated with a positive classification.

Proof (Table 36). Table 36 shows how the Interleaved Generic Pattern classification of the undernodes is aggregated with the Left/Right Sub-Pattern classification of an overnode. The correctness of these aggregations follows directly from the correctness of the AND columns of Table 5 and Table 6 when considering one of the columns A or B containing the equivalent classification for the Interleaved Generic Pattern, and the other the respective version of the overnode class for the Left or Right Sub-Pattern respectively.

Overnode's Overnode Child	Overnode's Undernode Children	Result
x/zt	- X	0 xt
x/zt	x	x^+
0 x/zt	0 k	0 xt
0 x/zt	+ k	+ xt
×/zt	0 k	+ xt
x/zt	+ k	x^+

Table 36: Aggregating Interleaved Generic Pattern with Left/Right Sub-Pattern Classes for Overnodes