Fast Flexible Paxos: Relaxing Quorum Intersection for Fast Paxos

Heidi Howard University of Cambridge heidi.howard@cl.cam.ac.uk Aleksey Charapko
University of New Hampshire
aleksey.charapko@unh.edu

Richard Mortier University of Cambridge richard.mortier@cl.cam.ac.uk

ABSTRACT

Paxos, the de facto standard approach to solving distributed consensus, operates in two phases, each of which requires an intersecting quorum of nodes. Multi-Paxos reduces this to one phase by electing a leader but this leader is also a performance bottleneck. Fast Paxos bypasses the leader but has stronger quorum intersection requirements.

In this paper we observe that Fast Paxos' intersection requirements can be safely relaxed, reducing to just one additional intersection requirement between phase-1 quorums and any pair of fast round phase-2 quorums. We thus find that the quorums used with Fast Paxos are larger than necessary, allowing alternative quorum systems to obtain new tradeoffs between performance and fault-tolerance.

ACM Reference Format:

Heidi Howard, Aleksey Charapko, and Richard Mortier. 2021. Fast Flexible Paxos: Relaxing Quorum Intersection for Fast Paxos. In *International Conference on Distributed Computing and Networking 2021 (ICDCN '21), January 5–8, 2021, Nara, Japan.* ACM, New York, NY, USA, 15 pages. https://doi.org/10.1145/3427796.3427815

1 INTRODUCTION

Paxos [18, 19] and its variants [7, 23, 25, 26, 29, 32] provide reliable solutions to the problem of distributed consensus [10]. Thanks to their excellent fault-tolerance properties and proven consistency guarantees, these algorithms often underpin the replicated state machines [31] at the heart of many industrial distributed systems, e.g., Chubby [6], CockroachDB [33], and PaxosStore [36].

Traditionally, the Paxos family of algorithms uses majority quorums, guaranteeing that any two sets containing the majority of nodes intersect, ensuring that previously decided values are not lost. Flexible Paxos [14] relaxes the requirement for intersecting quorums in Paxos, proving that quorum intersection is only required between phases, permitting disjoint quorums to be used within each phase. This result enabled subsequent algorithms to improve performance by adjusting quorums depending on the phase of the algorithm [1, 4, 8, 9, 28, 35].

Paxos is usually implemented using Multi-Paxos [18, 19], an optimization that elects one node to be a *leader*. This single leader can then achieve distributed consensus in just one phase, but unfortunately also becomes a performance bottleneck.

Seeking to improve performance, a new family of *leaderless* consensus algorithms emerged, starting with Fast Paxos [23], which forms the basis for subsequent algorithms including Generalized




Figure 1: Relationships between distributed consensus algorithms. The arrows denote where one algorithm generalizes over another.

Paxos [22] and Egalitarian Paxos [26]. Paxos uses the idea of *rounds* in which at most one value can be *proposed*. Fast Paxos introduced the notion of *fast rounds* where multiple values can be safely proposed in the same round. However, such fast rounds require stronger quorum intersection than classical rounds. Specifically, Paxos only requires that any two quorums intersect whereas Fast Paxos also requires that any quorum intersects with any two fast round quorums. Fast Paxos' quorum intersection requirements can be satisfied by requiring fast round quorums to contain at least three-quarters of nodes. Due to this additional quorum intersection requirement, Fast Paxos and its variants cannot directly benefit from Flexible Paxos.

In this paper, we show that the approach of Flexible Paxos can be safely applied to consensus algorithms that rely on stronger quorum intersection by extending Flexible Paxos to Fast Paxos. The resulting algorithm, which we refer to as *Fast Flexible Paxos*, relaxes the quorum intersection requirements of Fast Paxos. Specifically, Fast Flexible Paxos proves that the only additional quorum intersection requirement is between phase-1 quorums and any pair of fast round phase-2 quorums.

Relaxed quorum intersection in Fast Flexible Paxos permits new performance tradeoffs by manipulation of the quorum systems. For example, reducing the size of fast round quorums reduces the contention in the algorithm. This may further improve overall performance on top of an improvement attained by a smaller quorum alone. For instance, we illustrate that the Fast Flexible Paxos with smaller fast quorums achieves up to 10% better latency than Fast Paxos in low conflict scenarios.

2 BACKGROUND

We begin by recapping how distributed consensus is currently solved by Paxos, Flexible Paxos, and Fast Paxos. The relation between these algorithms is shown in Figure 1.

2.1 Paxos

The Paxos algorithm distinguishes between two roles a node can take: a *proposer* and an *acceptor*. A proposer initiates a decision by executing Paxos using a *round*. Rounds are integers allocated to proposers, and each proposer must propose only one value in each

1

ICDCN '21, January 5-8, 2021, Nara, Japan

^{© 2021} Copyright held by the owner/author(s). Publication rights licensed to ACM. This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in *International Conference on Distributed Computing and Networking 2021 (ICDCN '21), January 5–8, 2021, Nara, Japan, https://doi.org/10.1145/3427796.3427815.*

round. A proposal is a pair of a round and a value. The algorithm runs in two phases per round, each requiring a quorum of acceptors to proceed.

In phase-1, the proposer learns if a value was decided in any previous round by asking the acceptors to send the last proposal they voted for. Acceptors promise not to vote in any smaller round.

In phase-2, the proposer asks acceptors to vote for a value v. If during phase-1 the proposer learned that a value might become decided, then it must use that value for v. Provided that an acceptor has not promised otherwise, it updates its last proposal voted for and acknowledges that to the proposer. Once the proposer has completed phase-2, it will learn that v is decided.

Paxos requires intersection between any two quorums. If Q denotes the set of quorums then this intersection requirement can be expressed as:

$$\forall Q, Q' \in Q : Q \cap Q' \neq \{\} \tag{1}$$

Consider a simple quorum system based solely on the cardinality of quorums. If q denotes the cardinality of quorums in Q and n denotes the number of acceptors, then we can express Paxos' quorum intersection requirement (Eq. 1) as:

$$2q > n \tag{2}$$

Paxos is often used to decide a sequence of values, where the $i^{\rm th}$ instance of Paxos decides the $i^{\rm th}$ value. Multi-Paxos improves the algorithm's performance by pre-executing the phase-1 of every instance by the same stable proposer, known as a leader. The leader can then decide each value in just two communication steps, compared to the four communication steps needed by Paxos.

2.2 Flexible Paxos

Flexible Paxos differentiates between the quorums for phase-1, Q_1 and phase-2, Q_2 . This approach allows the weakening of Paxos' quorum intersection requirement (Eq. 1) to the following:

$$\forall Q \in Q_1, \forall Q' \in Q_2 : Q \cap Q' \neq \{\} \tag{3}$$

That is, quorum intersection is not required within each of the two phases. As previously, if q_i denotes the cardinality of quorums in Q_i , then we can express Flexible Paxos' quorum intersection requirement (Eq. 3) as:

$$q_1 + q_2 > n \tag{4}$$

In Multi-Paxos, phase-1 is executed rarely compared to phase-2 so applications can decrease the phase-2 quorum to improve performance at the cost of decreased fault-tolerance.

2.3 Fast Paxos

In Multi-Paxos, the leader is a bottleneck and other proposers must first send values to the leader, adding a communication step. Fast Paxos addresses these issues by allowing all proposers to propose values directly to the acceptors. Fast Paxos can thus decide a value in one phase, an optimal solution to distributed consensus [21].

Fast Paxos achieves this by introducing *fast* rounds, where it is safe for multiple values to be proposed in the same round. In a fast round, if the leader is free to propose any value in phase-2 then instead of proposing a specific value it proposes a special *any* value to the acceptors. Proposers can then send proposals directly

to the acceptors and each acceptor will vote for the first proposal it receives as if it had been sent by the leader.

Fast Paxos needs stronger quorum intersection for fast rounds to ensure safety and progress in the case of conflicts. If Q_f denotes fast round quorums and Q_c denotes classic round quorums then Fast Paxos requires:¹

$$\forall Q, Q' \in Q_c : Q \cap Q' \neq \{\} \tag{5}$$

$$\forall Q, Q' \in Q_f, \forall Q'' \in Q_c : Q \cap Q' \cap Q'' \neq \{\}$$
 (6)

$$\forall Q, Q', Q'' \in Q_f : Q \cap Q' \cap Q'' \neq \{\} \tag{7}$$

In other words, Fast Paxos requires that any pair of classic round quorums intersect (Eq. 5), that any pair of fast round quorums intersect with any classic round quorum (Eq. 6) and that any three fast round quorums intersect (Eq. 7).

As before, let q_f and q_c denote the cardinality of quorums in Q_f and Q_c respectively. We can now express Fast Paxos' quorum intersection requirements (Eq. 5, Eq. 6 & Eq. 7) as:

$$2q_c > n \tag{8}$$

$$q_c + 2q_f > 2n \tag{9}$$

$$3q_f > 2n \tag{10}$$

Fast Paxos suggests using $q_c = q_f = \lfloor \frac{2n}{3} \rfloor + 1$ or $q_c = \lfloor \frac{n}{2} \rfloor + 1$ and $q_f = \lceil \frac{3n}{4} \rceil$ to satisfy these requirements.² The larger quorums required by Fast Paxos have been shown to significantly decrease performance compared to Paxos [15].

3 FAST FLEXIBLE PAXOS

Following the approach of Flexible Paxos, we will differentiate between the quorums used for each phase of Fast Paxos.

Recall that quorum intersection is required between the two phases to ensure that a proposer learns in phase-1 any value which may be decided in phase-2. In phase-2, the proposer needs to pick a value from the highest round it learned during phase-1. In Fast Paxos, there may be multiple such values as acceptors may vote for different values during the phase-2 of fast rounds, requiring a proposer to determine which single value (if any) could be decided in previous rounds. Fast Flexible Paxos achieves this by ensuring that each phase-1 quorum intersects with any pair of fast round phase-2 quorums.

The quorum intersection requirements are the same regardless of whether phase-1 is for a fast or classic round. Therefore Q_1 denotes the phase-1 quorums (fast or classic) whereas Q_{2c} and Q_{2f} denote the phase-2 quorums for classic and fast rounds respectively. The weakened intersection requirements for Fast Paxos are as follows:

$$\forall Q \in Q_1, \forall Q' \in Q_{2c} : Q \cap Q' \neq \{\}$$

$$\tag{11}$$

$$\forall Q \in Q_1, \forall Q', Q'' \in Q_{2f} : Q \cap Q' \cap Q'' \neq \{\}$$

$$\tag{12}$$

In other words, we find that quorum intersection is only required between phase-1 quorums and phase-2 classic round quorums (Eq. 11) and between phase-1 quorums and any pair of phase-2 fast round quorums (Eq. 12). Note that quorum intersection is not

¹The original paper asserts that (a) any two quorums intersect and (b) any two fast quorums and any classic or fast quorum intersect. Since (b) already covers the intersection between two fast quorums as well as a fast and classic quorum, we have reduced (a) to any two classic quorums intersect.

²The former is sometimes written as n = 3f + 1 and $q_f = q_c = 2f + 1$ where f is the number of faults which can be tolerated [15].

required between phase-1 quorums, between phase-2 classic round quorums, or between phase-2 classic round quorums and phase-2 fast round quorums.

If q_1 , q_{2f} and q_{2c} denote the cardinality of quorums in Q_1 , Q_{2f} and Q_{2c} respectively then we can express Fast Flexible Paxos' intersection requirements (Eq. 11 & Eq. 12) as:

$$q_1 + q_{2c} > n \tag{13}$$

$$q_1 + 2q_{2f} > 2n \tag{14}$$

4 CORRECTNESS

Fast Flexible Paxos must ensure that at most one value is decided. We can show this by proving the following two properties:

PROPERTY 1. At most one value is decided per round.

PROOF. If the round is classic, then at most one proposer can propose (and therefore decide) a value. If the round is fast, then at most one value will be decided as any two fast phase-2 quorums will intersect (Eq. 12).

PROPERTY 2. A proposer will only propose a value in a given round if no smaller round can decide a different value.

PROOF. Assume that a value v is decided in round r. Consider the next round r' (r' > r) where a value is proposed. In phase-1, the proposer of round r' will ask the acceptors to promise not to vote in any smaller rounds and to reply with the last proposal they voted for

Due to quorum intersection between the phase-1 and phase-2 (Eq. 11 & Eq. 12), at least one acceptor will reply to the proposer in round r' with value v and round r. This is because the acceptor must have voted for value v in round r before participating in round r' as it promises not to vote in any smaller rounds. The acceptor also cannot have voted in any round since r as round r' is the first round after r where a value is proposed. The proposer in round r' will propose the value v as it will not receive any proposals from rounds greater than r. If the round r is fast then the proposer in round r' may receive multiple values from round r, however, the proposer will choose value v since v is decided.

Consider the next round r''(r'' > r') where a value is proposed. The value proposed in round r'' must be value v as only the value v has been proposed since value v was decided in round v. By induction, we can see that for all rounds larger than v, if a value is proposed then that value will be v.

Fast Flexible Paxos must also ensure liveness to solve distributed consensus, and in particular, it must satisfy the following property:

PROPERTY 3. Upon completion of phase-1, a proposer can determine at least one value which is safe to propose in phase-2.

PROOF. Consider a proposer that has just completed phase-1 of round r'. A value is safe to propose in round r' only if the proposer knows that no smaller round has decided a different value (Property 2). If a proposer receives multiple proposals in phase-1 then it proposes the value with the greatest round r (r < r'). However, if the round r is a fast round the proposer may receive multiple values and so must determine which of the values (if any) could be decided in round r. Note that a value could be decided in

round r only if there exists a phase-2 fast round quorum of acceptors which may have voted for the value in round r.

For every pair of phase-2 fast round quorums, at least one acceptor which will reply to a proposer in phase-1 of round r' must also vote in both quorums if both quorums decide a value in round r (Eq. 12). The acceptor will only vote for one value in round r and thus will reply to the proposer with only one value. The proposer thus learns that the other value cannot have been decided in round r by any quorum containing that acceptor.

Once the proposer has heard from a phase-1 quorum of acceptors, the proposer can safely eliminate either all or all but one of the values received with round r.

In Appendix A, we adapted the Fast Paxos specification [23] to model check a formal specification of Fast Flexible Paxos using TLA+ [20]. Both our specification and model checking configurations are also available online [2].

5 IMPLICATIONS

The weakened intersection requirements show that phase-1 of a fast round can use the same quorum as phase-1 of a classic round. Since the requirement of fast round quorums is stricter than classic round quorums then fast round quorums must be at least as large as classic round quorums.

For example, Fast Paxos suggests using $q_f = \lceil \frac{3n}{4} \rceil$ and $q_c = \lfloor \frac{n}{2} \rfloor + 1$, but our relaxed intersection requirements demonstrate that a simple majority of acceptors is sufficient for phase-1 of fast rounds. Similarly, Fast Paxos also suggests using $q_c = q_f = \lfloor \frac{2n}{3} \rfloor + 1$ and again we observe that is conservative and only one third of acceptors are needed for phase-2 of classic rounds $(q_{2c} = \lceil \frac{n}{3} \rceil)$.

More generally, by weakening the intersection requirements of Fast Paxos, we provide more flexibility to choose quorum systems and tradeoffs. In a stable system, phase-1 is rarely executed compared to phase-2 so we can decrease the size of our phase-2 quorums, fast and classic, provided we increase the size of our phase-1 quorums. For example, a system of 11 acceptors could use phase-2 quorums of 7 acceptors for fast rounds and 3 acceptors for classic rounds, if it uses quorums of 9 acceptors for phase-1.


Note that the liveness of such a system does depend upon both phase-1 and phase-2 quorums. For example, we could minimize fast round phase-2 by using a simple majority for q_{2f} , but this would require all acceptors to start a new round.

6 PRELIMINARY EVALUATION


The main contribution of this paper is the observation that the quorum intersection requirements of Fast Paxos can safely be relaxed. We have also implemented Fast Flexible Paxos to illustrate the potential performance improvements this result enables, even with a simple quorum system based solely on quorum cardinality.

We evaluated Fast Flexible Paxos with the aforementioned quorum configuration ($q_1 = 9$, $q_{2f} = 7$, and $q_{2c} = 3$) using Paxi [3] on AWS EC2 m5a.large VMs. We focused on two key aspects of Fast Flexible Paxos: latency and conflict reduction due to the smaller phase-2 fast round quorums. We compared our algorithm against a Fast Paxos ($q_c = 6$ and $q_f = 9$) baseline.


In Figure 2a we illustrate the performance of two algorithms under a workload of 1400 requests/second with no conflicts. Smaller



(a) Instance latency in conflict-free workload at 1400 requests/s.



(b) Instance latency in a workload with 0.5%-1.5% conflicts at 2700 requests/s.



(c) Probability of conflict under different intervals between potentially conflicting commands.

Figure 2: Evaluation of Fast Flexible Paxos in a Paxi 11 node cluster. Fast Paxos uses quorums of the following sizes: $q_c=6$ and $q_f=9$. Fast Flexible Paxos runs with $q_1=9$, $q_{2f}=7$, and $q_{2c}=3$ quorums.

fast round quorums allowed Fast Flexible Paxos to reduce the average and median latency by 5-8% compared to Fast Paxos.

We also evaluated under conflicts by generating a workload with several clients racing to propose different commands for the same consensus instance. For this workload we generated a steady stream of operations with only small intervals between them. We also preassigned each operation to an instance to control the potential for conflicts. In about 10% of the cases, we assigned the same instances to two consecutive operations, creating a race condition between them. In this setup there are two possible outcomes for such races: one of the operations reaches the fast round quorum, causing the second to abort; or none of the operations reach the fast round quorum, causing entry into the conflict resolution phase. We then measured the conflict avoidance ratio to study the impact of the Fast Flexible Paxos on conflict handling.

We found that Fast Flexible Paxos entered the conflict recovery almost one-third as frequently as Fast Paxos due to the smaller fast quorum. However, the overall frequency of recovery phases increased substantially for both algorithms as the throughput rises and the interval between the commands shrinks, as Figure 2c shows. Considering the overall performance in the conflict workload, Figure 2b shows that our Fast Flexible Paxos continues to maintain a roughly 5% latency advantage over Fast Paxos even under high load compared to our non-conflict experiment.

We believe Fast Flexible Paxos will enable further performance improvements if quorum systems are used that are not based solely on quorum cardinality [11, 12, 16, 27, 30]. This has already proven to be the case for Flexible Paxos [1, 4, 8, 9, 28, 35]. In particular, Fast Flexible Paxos can benefit from the existing literature on Byzantine and Refined quorum systems [13, 24] as these quorum systems provide stronger quorum intersection.

7 SUMMARY

Fast Paxos allows any proposer to decide a value in two communication steps in the absence of collisions. This is the optimal number of communication steps for distributed consensus. However, to achieve this it needs a stronger quorum intersection than Paxos and thus has not benefited from recent work on relaxing quorum intersection requirements.

Fast Flexible Paxos weakens Fast Paxos' quorum intersection requirements by differentiating between the quorums used in each phase of the algorithm. We find that quorum intersection is only required between any phase-1 quorum and both (a) any phase-2 classic round quorum, and (b) any pair of phase-2 fast round quorums. This shows that the quorum systems used by Fast Paxos are conservative and that alternative quorum systems could be safely used.

More generally, we have proven that the approach of Flexible Paxos generalizes to distributed consensus algorithms beyond Paxos. We hope more consensus algorithms, particularly those which extend Fast Paxos such as Generalized Paxos [22], Egalitarian Paxos [26], MDCC [17], Alvin [34] and Caesar [5], adopt this approach to relax their quorum intersection requirements, giving applications greater flexibility to determine their performance and fault-tolerance tradeoffs.

ACKNOWLEDGMENTS

This work was funded in part by EPSRC EP/M02315X/1.

REFERENCES

- [1] 2020. LogDevice: Distributed storage for sequential data. https://logdevice.io.
- [2] 2020. TLA+ Specification of Fast Flexible Paxos. https://github.com/fpaxos/ffpaxos-tlaplus. (2020).
- [3] Ailidani Ailijiang, Aleksey Charapko, and Murat Demirbas. 2019. Dissecting the Performance of Strongly-Consistent Replication Protocols. In Proceedings of the 2019 International Conference on Management of Data (SIGMOD '19). ACM, Amsterdam, Netherlands, 1696–1710. https://doi.org/10.1145/3299869.3319893
- [4] Ailidani Ailijiang, Aleksey Charapko, Murat Demirbas, and Tevfik Kosar. 2020. WPaxos: Wide area network flexible consensus. IEEE Transactions on Parallel and Distributed Systems 31, 1 (2020), 211–223.
- [5] Balaji Arun, Sebastiano Peluso, Roberto Palmieri, Giuliano Losa, and Binoy Ravindran. 2017. Speeding up Consensus by Chasing Fast Decisions. In 47th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN). 49–60.
- [6] Mike Burrows. 2006. The Chubby lock service for loosely-coupled distributed systems. In 7th USENIX Symposium on Operating Systems Design and Implementation (OSDI).
- [7] Lásaro Jonas Camargos, Rodrigo Malta Schmidt, and Fernando Pedone. 2007. Multicoordinated Paxos. In Proceedings of the Twenty-Sixth Annual ACM Symposium on Principles of Distributed Computing (PODC '07). ACM, New York, NY, USA, 316–317. https://doi.org/10.1145/1281100.1281150
- [8] Michael Eischer, Benedikt Straßner, and Tobias Distler. 2020. Low-Latency Geo-Replicated State Machines with Guaranteed Writes. In Proceedings of the 7th Workshop on Principles and Practice of Consistency for Distributed Data (PaPoC '20). ACM, Heraklion, Greece, Article 13, 9 pages. https://doi.org/10.1145/3380787.3393686
- [9] Vitor Enes, Carlos Baquero, Tuanir França Rezende, Alexey Gotsman, Matthieu Perrin, and Pierre Sutra. 2020. State-Machine Replication for Planet-Scale Systems. In Proceedings of the Fifteenth European Conference on Computer Systems (EuroSys '20). ACM, Heraklion, Greece, Article 24, 15 pages. https://doi.org/10. 1145/3342195.3387543
- [10] Michael J. Fischer, Nancy A. Lynch, and Michael S. Paterson. 1985. Impossibility of Distributed Consensus with One Faulty Process. J. ACM 32, 2 (April 1985), 374–382. https://doi.org/10.1145/3149.214121
- [11] Hector Garcia-Molina and Daniel Barbara. 1985. How to Assign Votes in a Distributed System. J. ACM 32, 4 (Oct. 1985), 841–860. https://doi.org/10.1145/ 4221.4223
- [12] David K. Gifford. 1979. Weighted Voting for Replicated Data. In Proceedings of the Seventh ACM Symposium on Operating Systems Principles (SOSP '79). ACM, Pacific Grove. CA, USA, 150–162. https://doi.org/10.1145/800215.806583
- [13] Rachid Guerraoui and Marko Vukoliundefined. 2007. Refined Quorum Systems. In Proceedings of the Twenty-Sixth Annual ACM Symposium on Principles of Distributed Computing (PODC '07). ACM, Portland, OR, USA, 119–128. https://doi.org/10.1145/1281100.1281120
- [14] Heidi Howard, Dahlia Malkhi, and Alexander Spiegelman. 2017. Flexible Paxos: Quorum Intersection Revisited. In 20th International Conference on Principles of Distributed Systems (OPODIS 2016). 25:1–25:14. https://doi.org/10.4230/LIPIcs. OPODIS.2016.25
- [15] Flavio Junqueira, Yanhua Mao, and Keith Marzullo. 2007. Classic Paxos vs. Fast Paxos: Caveat Emptor. In Proceedings of the 3rd Workshop on on Hot Topics in System Dependability (HotDep'07). USENIX Association, Edinburgh, UK, 18–es.
- [16] Flavio P. Junqueira and Keith Marzullo. 2005. The Virtue of Dependent Failures in Multi-Site Systems. In Proceedings of the First Conference on Hot Topics in System Dependability (HotDep'05). USENIX Association, Yokohama, Japan, 1.
- [17] Tim Kraska, Gene Pang, Michael J. Franklin, Samuel Madden, and Alan Fekete. 2013. MDCC: Multi-Data Center Consistency. In Proceedings of the 8th ACM European Conference on Computer Systems (EuroSys '13). ACM, Prague, Czech Republic, 113–126. https://doi.org/10.1145/2465351.2465363
- [18] Leslie Lamport. 1998. The Part-time Parliament. ACM Trans. Comput. Syst. 16, 2 (May 1998), 133–169. https://doi.org/10.1145/279227.279229
- [19] Leslie Lamport. 2001. Paxos made simple. ACM SIGACT News (Distributed Computing Column) (2001).
- [20] Leslie Lamport. 2002. Specifying Systems: The TLA+ Language and Tools for Hardware and Software Engineers. Addison-Wesley Longman Publishing Co., Inc., Boston, MA, USA.
- [21] Leslie Lamport. 2003. Lower Bounds for Asynchronous Consensus. In Future Directions in Distributed Computing: Research and Position Papers. Springer-Verlag, 22–23.
- [22] Leslie Lamport. 2004. Generalized Consensus and Paxos. Technical Report MSR-TR-2005-33. Microsoft Research.
- [23] Leslie Lamport. 2005. Fast Paxos. Technical Report MSR-TR-2005-112. Microsoft Research.
- [24] Dahlia Malkhi and Michael Reiter. 1998. Byzantine Quorum Systems. Distrib. Comput. 11, 4 (Oct. 1998), 203–213. https://doi.org/10.1007/s004460050050

- [25] Yanhua Mao, Flavio P. Junqueira, and Keith Marzullo. 2008. Mencius: Building Efficient Replicated State Machines for WANs. In Proceedings of the 8th USENIX Conference on Operating Systems Design and Implementation (OSDI'08). USENIX Association, San Diego, CA, USA, 369–384.
- [26] Iulian Moraru, David G. Andersen, and Michael Kaminsky. 2013. There is More Consensus in Egalitarian Parliaments. In Proceedings of the Twenty-Fourth ACM Symposium on Operating Systems Principles (SOSP '13). ACM, Farminton, PA, USA, 358–372. https://doi.org/10.1145/2517349.2517350
- [27] Moni Naor and Avishai Wool. 1998. The Load, Capacity, and Availability of Quorum Systems. SIAM J. Comput. 27, 2 (April 1998), 423–447. https://doi.org/ 10.1137/S0097539795281232
- [28] Faisal Nawab, Divyakant Agrawal, and Amr El Abbadi. 2018. DPaxos: Managing Data Closer to Users for Low-Latency and Mobile Applications. In Proceedings of the 2018 International Conference on Management of Data (SIGMOD '18). ACM, Houston, TX, USA, 1221–1236. https://doi.org/10.1145/3183713.3196928
- [29] Diego Ongaro and John Ousterhout. 2014. In Search of an Understandable Consensus Algorithm. In Proceedings of the 2014 USENIX Conference on USENIX Annual Technical Conference (USENIX ATC'14). USENIX Association, Philadelphia, PA, USA, 305–320.
- [30] David Peleg and Avishai Wool. 1995. Crumbling Walls: A Class of Practical and Efficient Quorum Systems. In Proceedings of the Fourteenth Annual ACM Symposium on Principles of Distributed Computing (PODC '95). ACM, Ottowa, ON, Canada, 120–129. https://doi.org/10.1145/224964.224978
- [31] Fred B. Schneider. 1990. Implementing Fault-Tolerant Services Using the State Machine Approach: A Tutorial. ACM Comput. Surv. 22, 4 (Dec. 1990), 299–319. https://doi.org/10.1145/98163.98167
- [32] Pierre Sutra and Marc Shapiro. 2011. Fast Genuine Generalized Consensus. In Proceedings of the 2011 IEEE 30th International Symposium on Reliable Distributed Systems (SRDS '11). IEEE Computer Society, 255–264. https://doi.org/10.1109/ SRDS.2011.38
- [33] Rebecca Taft, Irfan Sharif, Andrei Matei, Nathan VanBenschoten, Jordan Lewis, Tobias Grieger, Kai Niemi, Andy Woods, Anne Birzin, Raphael Poss, Paul Bardea, Amruta Ranade, Ben Darnell, Bram Gruneir, Justin Jaffray, Lucy Zhang, and Peter Mattis. 2020. CockroachDB: The Resilient Geo-Distributed SQL Database. In Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data (SIGMOD '20). ACM, Portland, OR, USA, 1493–1509. https://doi.org/10. 1145/3318464.3386134
- [34] Alexandru Turcu, Sebastiano Peluso, Roberto Palmieri, and Binoy Ravindran. 2014. Be General and Don't Give Up Consistency in Geo-Replicated Transactional Systems. In *Principles of Distributed Systems*. Springer International Publishing, Cham, 33–48.
- [35] Muhammed Uluyol, Anthony Huang, Ayush Goel, Mosharaf Chowdhury, and Harsha V. Madhyastha. 2020. Near-Optimal Latency Versus Cost Tradeoffs in Geo-Distributed Storage. In 17th USENIX Symposium on Networked Systems Design and Implementation (NSDI 20). USENIX Association, Santa Clara, CA, 157–180. https://www.usenix.org/conference/nsdi20/presentation/uluyol
- [36] Jianjun Zheng, Qian Lin, Jiatao Xu, Cheng Wei, Chuwei Zeng, Pingan Yang, and Yunfan Zhang. 2017. PaxosStore: high-availability storage made practical in WeChat. Proceedings of the VLDB Endowment 10, 12 (2017), 1730–1741.

A FORMAL SPECIFICATION OF FAST FLEXIBLE PAXOS

This appendix presents a formal specification of Fast Flexible Paxos, written in TLA+ and model checked in TLC [20]. Both the TLA+ specification and TLC configuration are available online [2].

This specification is the result of only a minor modifications to the original Fast Paxos specification [23]. Underlined comments highlight where changes have been made to the original specification, particularly regarding the distinction between phase-1 and phase-2 quorums. Readers may wish to pay particular attention to IsPickableVal(Q, i, M, v) which implements the proposer's rule for picking a value v to send to acceptors in phase-2 of round i after receiving the messages M from the acceptor quorum Q. This specification refers to proposers as coordinators.

- Module FastFlexiblePaxos

The module imports two standard modules. Module Naturals defines the set Nat of naturals and the ordinary arithmetic operators; module FiniteSets defines IsFiniteSet(S) to be true iff S is a finite set and defines Cardinality(S) to be the number of elements in S, if S is finite.

EXTENDS Naturals, FiniteSets

Constants

Max(S) is defined to be the maximum of a nonempty finite set S of numbers.

```
Max(S) \stackrel{\Delta}{=} \text{ CHOOSE } i \in S : \forall j \in S : j \leq i
```

The next statement declares the specification's constant parameters.

CONSTANTS Val, the set of values that may be proposed.

Acceptor, the set of acceptors.

FastNum, the set of fast round numbers. QuorumP1($_$), the set of phase-1 i-quorums. QuorumP2($_$), the set of phase-2 i-quorums. Coord, the set of coordinators. CoordOf($_$) the coordinator of round i.

RNum is defined to be the set of positive integers, which is the set of round numbers.

```
RNum \triangleq Nat \setminus \{0\}
```

The following statement asserts the assumption that FastNum is a set of round numbers.

```
Assume FastNum \subseteq RNum
```

ClassicNum is defined to be the set of classic round numbers.

```
ClassicNum \triangleq RNum \setminus FastNum
```

The following assumption asserts that the set of acceptors is finite. It is needed to ensure progress. Assume IsFiniteSet(Acceptor)

The following asserts the assumptions that both QuorumP1(i) and QuorumP2(i) are set of sets of acceptors, for every round number i.

```
ASSUME \forall i \in RNum:
```

```
\land QuorumP1(i) \subseteq \text{SUBSET } Acceptor \land QuorumP2(i) \subseteq \text{SUBSET } Acceptor
```

The following asserts the quorum intersection requirement of Fast Flexible Paxos holds.

```
ASSUME \forall i \in RNum:
```

The following asserts the assumptions that CoordOf(i) is a coordinator, for every round number i, and that every coordinator is the coordinator of infinitely many classic rounds.

```
ASSUME \land \forall i \in RNum : CoordOf(i) \in Coord

\land \forall c \in Coord, i \in Nat :

\exists j \in ClassicNum : (j > i) \land (c = CoordOf(j))
```

any and none are defined to be arbitrary, distinct values that are not elements of Val.

```
any \stackrel{\triangle}{=} \text{CHOOSE } v : v \notin Val

none \stackrel{\triangle}{=} \text{CHOOSE } n : n \notin Val \cup \{any\}
```

Message is defined to be the set of all possible messages. A message is a record having a type field indicating what phase message it is, a rnd field indicating the round number. What other fields, if any, a message has depends on its type.

```
\begin{split} \mathit{Message} &\triangleq \\ & [\mathit{type}: \{ \text{``phase1a''} \}, \, \mathit{rnd}: \mathit{RNum} ] \\ & \cup \ [\mathit{type}: \{ \text{``phase1b''} \}, \, \mathit{rnd}: \mathit{RNum}, \, \mathit{vrnd}: \mathit{RNum} \cup \{0\}, \\ & \mathit{vval}: \, \mathit{Val} \cup \{\mathit{any}\}, \, \mathit{acc}: \mathit{Acceptor} ] \\ & \cup \ [\mathit{type}: \{ \text{``phase2a''} \}, \, \mathit{rnd}: \mathit{RNum}, \, \mathit{val}: \mathit{Val} \cup \{\mathit{any}\} ] \\ & \cup \ [\mathit{type}: \{ \text{``phase2b''} \}, \, \mathit{rnd}: \mathit{RNum}, \, \mathit{val}: \, \mathit{Val}, \, \mathit{acc}: \, \mathit{Acceptor} ] \end{split}
```

Variables and State Predicates

The following statement declares the specification's variables, which have all been described above—either in Fast Paxos, Section 2.2.1 on page 4 or in this appendix.

```
 \begin{array}{c} {\it VARIABLES} \ rnd, \ vrnd, \ vval, \ crnd, \ cval, \ amLeader, \ sentMsg, \ proposed, \\ learned, \ goodSet \end{array}
```

Defining the following tuples of variables makes it more convenient to state which variables are left unchanged by the actions.

```
aVars \stackrel{\triangle}{=} \langle rnd, vrnd, vval \rangle Acceptor variables.

cVars \stackrel{\triangle}{=} \langle crnd, cval \rangle Coordinator variables.

oVars \stackrel{\triangle}{=} \langle amLeader, proposed, learned, goodSet \rangle Most other variables.

vars \stackrel{\triangle}{=} \langle aVars, cVars, oVars, sentMsg \rangle All variables.
```

TypeOK is the type-correctness invariant, asserting that the value of each variable is an element of the proper set (its "type"). Type correctness of the specification means that TypeOK is an invariant—that is, it is true in every state of every behavior allowed by the specification.

```
TypeOK \triangleq \\ \land rnd \in [Acceptor \rightarrow Nat] \\ \land vrnd \in [Acceptor \rightarrow Nat] \\ \land vval \in [Acceptor \rightarrow Val \cup \{any\}] \\ \land crnd \in [Coord \rightarrow Nat] \\ \land cval \in [Coord \rightarrow Val \cup \{any, none\}] \\ \land amLeader \in [Coord \rightarrow BOOLEAN] \\ \land sentMsg \in SUBSET Message \\ \land proposed \in SUBSET Val
```

```
\land learned \in SUBSET \ Val
\land goodSet \subseteq Acceptor \cup Coord
```

Init is the initial predicate that describes the initial values of all the variables.

```
 \begin{array}{ll} Init \ \stackrel{\triangle}{=} \\ \land \ rnd \ = [a \in Acceptor \mapsto 0] \\ \land \ vrnd = [a \in Acceptor \mapsto 0] \\ \land \ vval \ = [a \in Acceptor \mapsto any] \\ \land \ crnd = [c \in Coord \mapsto 0] \\ \land \ cval \ = [c \in Coord \mapsto none] \\ \land \ amLeader \in [Coord \mapsto BOOLEAN] \\ \land \ sentMsg \ = \{\} \\ \land \ proposed \ = \{\} \\ \land \ poodSet \in SUBSET \ (Acceptor \cup Coord) \\ \end{array}
```

Action Definitions

Send(m) describes the state change that represents the sending of message m. It is used as a conjunct in defining the algorithm actions.

```
Send(m) \stackrel{\triangle}{=} sentMsg' = sentMsg \cup \{m\}
```

Coordinator Actions

Action Phase1a(c, i) specifies the execution of phase 1a of round i by coordinator c, described in Fast Paxos, Section 2.2.1 (on page 5) and refined by CA2' (Fast Paxos, Section 3.3, page 22).

MsgsFrom(Q,i,phase) is defined to be the set of messages in sentMsg of type phase (which may equal "phase1b" or "phase2b") sent in round i by the acceptors in the set Q.

```
MsgsFrom(Q, i, phase) \triangleq \{m \in sentMsg : (m.type = phase) \land (m.acc \in Q) \land (m.rnd = i)\}
```

If M is the set of round i phase 1b messages sent by the acceptors in a quorum Q, then IsPickableVal(Q,i,M,v) is true iff the rule of Fast Paxos, Figure 2 (page 20) allows the coordinator to send the value v in a phase 2a message for round i. Q4(w) has been modified to use phase-2 quorums.

```
IsPickable Val(Q, i, M, v) \triangleq \\ LET \ vr(a) \triangleq (CHOOSE \ m \in M : m.acc = a).vrnd \\ vv(a) \triangleq (CHOOSE \ m \in M : m.acc = a).vval \\ k \triangleq Max(\{vr(a) : a \in Q\}) \\ V \triangleq \{vv(a) : a \in \{b \in Q : vr(b) = k\}\} \\ O4(w) \triangleq \exists \ R \in QuorumP2(k) : \\ \forall \ a \in R \cap Q : (vr(a) = k) \land (vv(a) = w) \\ IN \quad IF \ k = 0 \ THEN \ \forall \ v \in proposed \\ \lor \land i \in FastNum \\ \land \ v = any \\ ELSE \quad IF \ Cardinality(V) = 1 \\ THEN \ v \in V \\ ELSE \quad IF \ \exists \ w \in V : O4(w) \\ THEN \ v = CHOOSE \ w \in V : O4(w) \\ ELSE \ v \in proposed
```

Action Phase2a(c, v) specifies the execution of phase 2a by coordinator c with value v, as described in Fast Paxos, Section 2.2.1 (on page 5) and Fast Paxos, Section 2.2.2 (page 6), and refined by CA2' (Fast Paxos, Section 3.3, page 22). This action has been modified to use phase-1 quorums.

```
\begin{split} Phase2a(c,\,v) &\stackrel{\triangle}{=} \\ \text{LET } i \stackrel{\triangle}{=} crnd[c] \\ \text{IN } & \land i \neq 0 \\ & \land cval[c] = none \\ & \land amLeader[c] \\ & \land \exists \, Q \in QuorumP1(i) : \\ & \land \forall \, a \in \, Q : \exists \, m \in MsgsFrom(Q,\,i,\,\text{``phase1b''}) : m.acc = a \\ & \land IsPickable\,Val(Q,\,i,\,MsgsFrom(Q,\,i,\,\text{``phase1b''}),\,v) \\ & \land cval' = [cval\,\,\text{EXCEPT }\,![c] = v] \\ & \land Send([type \mapsto \text{``phase2a''},\,rnd \mapsto i,\,val \mapsto v]) \\ & \land \text{UNCHANGED } \land crnd,\,a\,Vars,\,o\,Vars \\ \end{split}
```

P2bToP1b(Q, i) is defined to be the set of round i+1 phase 1b messages implied by the round i phase 2b messages sent by the acceptors in the set Q, as explained in Fast Paxos, Section 3.2.

```
\begin{array}{ll} P2bToP1b(Q,\ i) \stackrel{\triangle}{=} \\ \{[type \mapsto \text{``phase1b''},\ rnd \mapsto i+1,\ vrnd \mapsto i, \\ vval \mapsto m.val,\ acc \mapsto m.acc] : m \in MsgsFrom(Q,\ i,\ \text{``phase2b''})\} \end{array}
```

Action CoordinatedRecovery(c,v) specifies the coordinated recovery described in Fast Paxos, Section 3.2, page 20. With this action, coordinator c attempts to recover from a collision in round crnd[c] by sending round crnd[c]+1 phase 2a messages for the value v. Although CA2' (Fast Paxos, Section 3.3, page 22) implies that this action should be performed only if crnd[c]+1 is a classic round, that restriction is not required for correctness and is omitted from the specification. This action has been modified to use phase-1 quorums.

```
CoordinatedRecovery(c, v) \stackrel{\Delta}{=}
  LET i \triangleq crnd[c]
  IN \wedge amLeader[c]
        \wedge cval[c] = any
         \land i + 1 \in RNum
         \wedge c = CoordOf(i+1)
         \land \exists Q \in QuorumP1(i+1):
              \land \forall a \in Q : \exists m \in P2bToP1b(Q, i) : m.acc = a
              \land IsPickableVal(Q, i + 1, P2bToP1b(Q, i), v)
         \wedge cval' = [cval \text{ EXCEPT } ![c] = v]
         \wedge crnd' = [crnd \text{ EXCEPT } ! [c] = i + 1]
         \land Send([type \mapsto "phase2a", rnd \mapsto i+1, val \mapsto v])
         \land UNCHANGED \langle aVars, oVars \rangle
coordLastMsg(c) is defined to be the last message that coordinator c sent, if crnd[c] > 0.
coordLastMsg(c) \triangleq
   If cval[c] = none
       THEN [type \mapsto \text{"phase1a"}, rnd \mapsto crnd[c]]
       ELSE [type \mapsto "phase2a", rnd \mapsto crnd[c], val \mapsto cval[c]]
```

In action CoordRetransmit(c), coordinator c retransmits the last message it sent. This action is a stuttering action (meaning it does not change the value of any variable, so it is a no-op) if that message is still in sentMsg. However, this action is needed because c might have failed after first sending the message and subsequently have been repaired after the message was removed from sentMsg.

```
CoordRetransmit(c) \triangleq \\ \land amLeader[c] \\ \land crnd[c] \neq 0 \\ \land Send(coordLastMsg(c)) \\ \land \text{UNCHANGED } \langle aVars, cVars, oVars \rangle
```

CoordNext(c) is the next-state action of coordinator c—that is, the disjunct of the algorithm's complete next-state action that represents actions of that coordinator.

```
\begin{array}{l} CoordNext(c) \triangleq \\ \lor \exists i \in RNum : Phase1a(c, i) \\ \lor \exists v \in Val \cup \{any\} : Phase2a(c, v) \\ \lor \exists v \in Val : CoordinatedRecovery(c, v) \\ \lor CoordRetransmit(c) \end{array}
```

Acceptor Actions

Action Phase1b(i, a) specifies the execution of phase 1b for round i by acceptor a, described in Fast Paxos, Section 2.2.1 on page 5.

```
Phase1b(i, a) \stackrel{\Delta}{=} \\ \wedge rnd[a] < i
```

```
\land [type \mapsto "phase1a", rnd \mapsto i] \in sentMsg
\wedge rnd' = [rnd \text{ EXCEPT } ! [a] = i]
\land Send([type \mapsto "phase1b", rnd \mapsto i, vrnd \mapsto vrnd[a], vval \mapsto vval[a],
            acc \mapsto a
\land UNCHANGED \langle cVars, oVars, vrnd, vval \rangle
```

Action Phase2b(i, a, v) specifies the execution of phase 2b for round i by acceptor a, upon receipt of either a phase 2a message or a proposal (for a fast round) with value v. It is described in Fast Paxos, Section 2.2.1 on page 5 and Fast Paxos, Section 3.1 on page 17.

```
Phase2b(i, a, v) \triangleq
   \wedge rnd[a] < i
  \land vrnd[a] < i
   \wedge \exists m \in sentMsg:
         \land m.type = "phase2a"
         \wedge m.rnd = i
         \land \lor m.val = v
            \vee \wedge m.val = any
                \land v \in proposed
   \wedge rnd' = [rnd \text{ EXCEPT } ! [a] = i]
   \wedge vrnd' = [vrnd \text{ EXCEPT } ! [a] = i]
   \wedge vval' = [vval \text{ EXCEPT } ![a] = v]
   \land Send([type \mapsto "phase2b", rnd \mapsto i, val \mapsto v, acc \mapsto a])
   \land UNCHANGED \langle cVars, oVars \rangle
```

 $\label{eq:condition} Action \ \ Uncoordinated Recovery(i,a,v) \ \ \text{specifies uncoordinated recovery, described in Fast}$ Paxos, Section 3.2 on page 21. With this action, acceptor a attempts to recover from a collision in round i by sending a round i+1 phase 2b message with value v. This action has been modified to use phase-1 quorums.

```
UncoordinatedRecovery(i, a, v) \triangleq
   \land i + 1 \in FastNum
   \wedge rnd[a] \leq i
   \land \exists Q \in QuorumP1(i+1):
        \land \forall b \in Q : \exists m \in P2bToP1b(Q, i) : m.acc = b
        \wedge IsPickable Val(Q, i + 1, P2bToP1b(Q, i), v)
   \land rnd' = [rnd \text{ except } ![a] = i + 1]
   \wedge vrnd' = [vrnd \text{ EXCEPT } ![a] = i + 1]
   \wedge vval' = [vval \text{ EXCEPT } ![a] = v]
   \land Send([type \mapsto "phase2b", rnd \mapsto i+1, val \mapsto v, acc \mapsto a])
   \land UNCHANGED \langle cVars, oVars \rangle
accLastMsg(a) is defined to be the last message sent by acceptor a, if rnd[a] > 0.
```

```
accLastMsq(a) \triangleq
  IF vrnd[a] < rnd[a]
     THEN [type \mapsto \text{"phase1b"}, rnd \mapsto rnd[a], vrnd \mapsto vrnd[a],
                 vval \mapsto vval[a], acc \mapsto a
     ELSE [type \mapsto \text{"phase2b"}, rnd \mapsto rnd[a], val \mapsto vval[a],
```

```
acc \mapsto a
```

In action AcceptorRetransmit(a), acceptor a retransmits the last message it sent.

```
AcceptorRetransmit(a) \triangleq \\ \land rnd[a] \neq 0 \\ \land Send(accLastMsg(a)) \\ \land \text{UNCHANGED } \langle aVars, \ cVars, \ oVars \rangle
```

AcceptorNext(a) is the next-state action of acceptor a—that is, the disjunct of the next-state action that represents actions of that acceptor.

```
AcceptorNext(a) \triangleq \\ \lor \exists i \in RNum : \lor Phase1b(i, a) \\ \lor \exists v \in Val : Phase2b(i, a, v) \\ \lor \exists i \in FastNum, v \in Val : UncoordinatedRecovery(i, a, v) \\ \lor AcceptorRetransmit(a)
```

Other Actions

Action Propose(v) represents the proposal of a value v by some proposer.

```
Propose(v) \triangleq \land proposed' = proposed \cup \{v\} \land UNCHANGED \ \langle aVars, \ cVars, \ amLeader, \ sentMsg, \ learned, \ goodSet \rangle
```

Action Learn(v) represents the learning of a value v by some learner. This action has been modified to use phase-2 quorums.

Action LeaderSelection allows an arbitrary change to the values of amLeader[c], for all coordinators c. Since this action may be performed at any time, the specification makes no assumption about the outcome of leader selection. (However, progress is guaranteed only under an assumption about the values of amLeader[c].)

```
LeaderSelection \triangleq
 \land amLeader' \in [Coord \rightarrow BOOLEAN]
 \land UNCHANGED \langle aVars, cVars, sentMsg, proposed, learned, goodSet \rangle
```

Action FailOrRepair allows an arbitrary change to the set goodSet. Since this action may be performed at any time, the specification makes no assumption about what agents are good. (However, progress is guaranteed only under an assumption about the value of goodSet.)

```
FailOrRepair \triangleq
 \land goodSet' \in SUBSET \ (Coord \cup Acceptor)
 \land UNCHANGED \ \langle aVars, \ cVars, \ amLeader, \ sentMsq, \ proposed, \ learned \rangle
```

Action LoseMsg(m) removes message m from sentMsg. It is always enabled unless m is the last message sent by an acceptor or coordinator in goodSet. Hence, the only assumption the specification makes about message loss is that the last message sent by an agent in goodSet is not lost. Because sentMsg includes messages in an agent's output buffer, this effectively means that a non-failed process always has the last message it sent in its output buffer, ready to be retransmitted.

```
LoseMsg(m) \triangleq \\ \land \neg \lor \land m.type \in \{\text{"phase1a"}, \text{"phase2a"}\} \\ \land m = coordLastMsg(CoordOf(m.rnd)) \\ \land CoordOf(m.rnd) \in goodSet \\ \land amLeader[CoordOf(m.rnd)] \\ \lor \land m.type \in \{\text{"phase1b"}, \text{"phase2b"}\} \\ \land m = accLastMsg(m.acc) \\ \land m.acc \in goodSet \\ \land sentMsg' = sentMsg \setminus \{m\} \\ \land \text{UNCHANGED } \langle aVars, \ cVars, \ oVars \rangle
```

Action *OtherAction* is the disjunction of all actions other than ones performed by acceptors or coordinators, plus the *LeaderSelection* action (which represents leader-selection actions performed by the coordinators).

```
OtherAction \triangleq \\ \lor \exists \ v \in Val : Propose(v) \lor Learn(v) \\ \lor LeaderSelection \lor FailOrRepair \\ \lor \exists \ m \in sentMsg : LoseMsg(m)
```

Next is the algorithm's complete next-state action.

```
Next \triangleq 
\forall \exists c \in Coord : CoordNext(c)
\forall \exists a \in Acceptor : AcceptorNext(a)
\forall OtherAction
```

Temporal Formulas

Formula *Fairness* specifies the fairness requirements as the conjunction of weak fairnes formulas. Intuitively, it states approximately the following:

A coordinator c in goodSet must perform some action if it can, and it must perform a Phase1a(c,i) action for a classic round i if it can.

An acceptor in goodSet must perform some action if it can.

A value that can be learned must be learned.

It is not obvious that these fairness requirements suffice to imply the progress property, and that fairness of each individual acceptor and coordinator action is not needed. Part of the reason is that formula Fairness does not allow an agent in goodSet to do nothing but Retransmit actions if another of its actions is enabled, since all but the first retransmission would be a stuttering step, and weak fairness of an action A requires a non-stuttering A step to occur if it is enabled.

 $Fairness \triangleq$

Formula Spec is the complete specification of the Fast Paxos algorithm.

```
Spec \triangleq Init \wedge \Box [Next]_{vars} \wedge Fairness
```

Nontriviality asserts that every learned value has been proposed, and Consistency asserts that at most one value has been learned. The Nontriviality and Consistency conditions for consensus (Fast Paxos, Section 2.1) are equivalent to the invariance of these state predicates.

```
Nontriviality \triangleq learned \subseteq proposed
Consistency \triangleq Cardinality(learned) \leq 1
```

The following theorem asserts that the state predicates TypeOK, Nontriviality, and Consistency are invariants of specification Spec, which implies that Spec satisfies the safety properties of a consensus algorithm. It was checked by the TLC model checker on models that were too small to find a real bug in the algorithm but would have detected most simple errors in the specification.

```
THEOREM Spec \Rightarrow \Box (TypeOK \land Nontriviality \land Consistency)
```

Because the specification does not explicitly mention proposers and learners, condition LA(p,l,c,Q) described by Fast Paxos, page 10 of Section 2.3.1 is replaced by LA(c,Q), which depends only on c and Q. Instead of asserting that some particular proposer p has proposed a value, it asserts that some value has been proposed.

```
 LA(c, Q) \triangleq \\  \land \{c\} \cup Q \subseteq goodSet \\  \land proposed \neq \{\} \\  \land \forall ll \in Coord : amLeader[ll] \equiv (c = ll)
```

The following theorem asserts that Spec satisfies the progress property of Fast Paxos, described in Fast Paxos, Sections 2.3 and 3.3. The temporal formula <> []LA(c,Q) asserts that LA(c,Q) holds from some time on, and $<> (learned \neq \{\})$ asserts that some value is eventually learned. This theorem has been modified assume that Q includes both a phase-1 and phase-2 quorum.

```
THEOREM \land Spec
\land \exists Q \in SUBSET \ Acceptor :
```