Contextual Linear Types for Differential Privacy

MATÍAS TORO, Computer Science Department (DCC), University of Chile, Chile DAVID DARAIS^{*}, Galois, Inc., USA CHIKE ABUAH, Computer Science Department, University of Vermont, USA JOE NEAR, Computer Science Department, University of Vermont, USA FEDERICO OLMEDO, Computer Science Department (DCC), University of Chile, Chile ÉRIC TANTER, Computer Science Department (DCC), University of Chile, Chile

Language support for differentially-private programming is both crucial and delicate. While elaborate program logics can be very expressive, type-system based approaches using linear types tend to be more lightweight and amenable to automatic checking and inference, and in particular in the presence of higher-order programming. Since the seminal design of Fuzz, which is restricted to ϵ -differential privacy, a lot of effort has been made to support more advanced variants of differential privacy, like (ϵ, δ) -differential privacy. However, no existing type system supports these advanced privacy variants while also supporting higher-order programming in full generality. We present Jazz, a language and type system which uses linear types and latent contextual effects to support both advanced variants of differential privacy and higher order programming . Even when avoiding advanced variants and higher order programming, our system achieves higher precision than prior work for a large class of programming patterns. We formalize the core of the Jazz language, prove it sound for privacy via a logical relation for metric preservation, and illustrate its expressive power through a number of case studies drawn from the recent differential privacy literature.

1 INTRODUCTION

Note. This paper uses colorblind-friendly colors in notation to convey information, and is best consumed using an electronic device or color printer.

Over the past decade, differential privacy [\[24\]](#page-49-0) has become the de-facto gold standard in protecting the privacy of individuals when processing sensitive data. In contrast to traditional approaches like de-identification, differential privacy provides a formal, composable privacy guarantee. Differentially private algorithms typically protect privacy by selecting from a handful of basic mechanisms to perturb their outputs. For example, the Laplace mechanism can be used to add noise to the population count of a city to prevent an adversary from successfully guessing whether or not a particular individual lives in that city. Most programming-language-based approaches to differential privacy are applied to verifying either the implementation of a mechanism, such as the Exponential mechanism, or the composition of multiple uses of mechanisms, such as computing a histogram using the Laplace mechanism (multiple times) as a primitive.

There are two challenges when writing differentially private programs. First, noise must be added to the right values in the program in order to achieve some guarantee of privacy; this includes the final output of the program, as well as many intermediate program values. Second, the correct amount of noise must be added in those places to achieve the desired amount of privacy. In the differential privacy framework, privacy is a quantity—more noise gives more privacy. Adding too little noise is as ineffective as adding no noise at all, and adding too much noise renders the result

[∗]Work done in part while at University of Vermont

Authors' addresses: Matías Toro, Computer Science Department (DCC), University of Chile, Santiago, Chile; David Darais, Galois, Inc., Portland, USA; Chike Abuah, Computer Science Department, University of Vermont, Burlington, USA; Joe Near, Computer Science Department, University of Vermont, Burlington, USA; Federico Olmedo, Computer Science Department (DCC), University of Chile, Santiago, Chile; Éric Tanter, Computer Science Department (DCC), University of Chile, Santiago, Chile.

of the computation useless. Programmers must therefore ensure they have added enough noise, in the right places, and that the noise is minimal—a daunting task.

Since differential privacy is a probabilistic, multi-run (hyper[\[19\]](#page-49-1)) property, it is not straightforward to develop test cases for differentially private algorithms. Consequently, differentially private algorithms are usually developed by experts in the field, and these experts produce manual proofs of privacy for each new algorithm. This reliance on experts is limiting. First, there is a practical need for developing privacy-preserving applications without access to an expert in differential privacy. Even still, experts aren't perfect: for example, several incorrect versions of the Sparse Vector Technique [\[23](#page-49-2), [24](#page-49-0)] have appeared in published papers [29], despite being authored and peer-reviewed by experts in differential privacy.

Due to these challenges, verifying differential privacy in programs via type checking has received considerable attention. The first such approach, Fuzz [\[33\]](#page-50-0), uses linear types to verify pure ϵ -differential privacy. Fuzz and its successor DFuzz [\[26\]](#page-49-3) have a number of attractive properties, including support for automation and higher-order programming. Fuzz was the first to use linear types to bound function sensitivity: how much a function's output changes given a change to its input. Sensitivity is then used to determine the (minimal) amount of noise required to achieve privacy. Fuzz uses the same sensitivity type system to also track privacy, which is advantageous due to its simplicity, but as a consequence is unable to support advanced variants of differential privacy, like (ϵ , δ). Another approach, HOARE², uses relational refinement types to encode differential privacy [\[9\]](#page-49-4), and improves on Fuzz-like systems in its ability to support advanced variants, but has limited support for automation. In general, type-based approaches like Fuzz and HOAR \rm{e}^{2} are used to verify programs which compose mechanisms, and not the implementations of mechanisms.

An alternative set of approaches use program logics [\[10](#page-49-5)[–12,](#page-49-6) [34\]](#page-50-1) to verify both the implementations of mechanisms and simple forms of composing mechanisms, while also supporting advanced variants like (ϵ , δ)-differential privacy [\[24\]](#page-49-0), zero-concentrated differential privacy [\[16\]](#page-49-7), and Rényi differential privacy [\[31\]](#page-50-2). However, these benefits come at the expense of automation and support for higher-order programming.

The Duer language [\[32\]](#page-50-3) and type system strikes a new balance in this space by building on the designs of Fuzz and DFuzz. Like Fuzz, Duet supports automation and higher order programming, and like $\rm HOARE^{2}$ and recently developed program logics, $\rm D \bar u \bar \rm r$ supports advanced variants of differential privacy. Like all type-based approaches, DUET cannot be used to verify the implementation of mechanisms, however even when verifying programs which compose mechanisms there is still room to improve: DUET is not expressive enough to support higher-order programming in full generality—something Fuzz, DFuzz and $\rm HOARE^2$ are each able to achieve.

This paper presents Jazz, the successor to Duer which significantly improves upon its design. JAZZ is a linear type system with latent contextual effects for function sensitivity and differential privacy; this combination supports advanced privacy variants (like \rm{DuET} and \rm{HOARE}^2), automation (like Du \rm{E} and Fuzz/DFuzz), and higher-order programming (like Fuzz/DFuzz and HOAR \rm{E}^2). Like DUET, the JAZZ language is built from two mutually-embedded sublanguages—one for sensitivity, and one for privacy—which allows it to support advanced variants of differential privacy automatically through typechecking. Also like Duet (and Fuzz/DFuzz), Jazz is designed for verifying the composition of mechanisms, and not their direct implementation.

The key insight of Jazz is the incorporation of latent contextual effects into a linear type system. Alatent effect is one which is deferred or delayed; rather than accounting for the effect immediately, it is tracked and accounted for later. A contextual effect is one that tracks effect information for each variable in the context, including closure variables used in higher-order function bodies. In addition to supporting higher order programming in the presence of advanced privacy variants,

these latent contextual effects also enable increased precision for sensitivity analysis for sums and products when compared to all existing approaches based on linear typing.

The challenge of higher-order programming. Consider the *n*-iteration loop combinator in Fuzz, loop_n, which has type $\tau \to (\tau \to \bigcirc \tau) \to_n \bigcirc \tau$. This type describes a two argument function which takes some value of type τ as the first argument, a function as second argument (which accepts and returns values of type τ), and returns a final value of type τ . The modality \circ in the return type for the function argument and final return type indicates that the function is probabilistic (due to use of differential privacy mechanisms), and indicates that the function satisfies differential privacy.

Both function sensitivity and differential privacy are two-run (hyper)properties of a function output w.r.t. some particular input. For example, $2x + 3y$ is 2-sensitive in x and 3-sensitive in y , meaning that if input x varies by at most d , then the function output varies at most by 2 d . When a closure is created, the closure captures sensitivities as well as values, so the sensitivity of the closure λx . $2x + 3y$ would be "3 in y". The situation is analogous when tracking privacy and creating closures which capture privacy costs. Looking back to the type of loop_n in Fuzz, the second argument will be a closure whose captured environment tracks a privacy cost for each closure variable. The interpretation of the linear function type \neg _n is to *scale* the privacy effects in the closure environment of the looping function of type $\tau \to \infty$ by *n*. This scaling is *implicit* and *pervasive* in Fuzz and, most importantly, only valid for pure ϵ -differential privacy. As a consequence of this pervasive scaling, Fuzz cannot be instantiated to advanced differential privacy variants.

The Duer language prohibits this pervasive scaling in its type system in order to support advanced differential privacy variants, but as a consequence no type can be given to loop_n in $\mathrm{D}\mathrm{u}\mathrm{e}\mathrm{r}.$ The issue is that Duer prohibits all scaling of privacy quantities. However, scaling is allowable (i.e., sound) in special restricted instances when using advanced variants. The challenge is then to disallow implicit pervasive scaling while allowing explicit restricted scaling. Because no type can be written for loop_n in $\mathrm{D}\mathrm{u}\mathrm{E}$, it (and many other higher order functions) must be given explicit *typing rules*. This is restrictive for higher order programming, e.g., loop_n can't be lambda-abstracted.

Jazz directly solves the challenge of encoding the explicit, restricted scaling that is required to support both advanced privacy variants and higher order programming. In Jazz, the type of the *n*-iteration construct is: $\text{loop}_n : \tau \to (\tau \xrightarrow{\sum [\tau \in \mathcal{S}]} \tau) \xrightarrow{\sum [\tau \in \mathcal{S}]} \tau$. In this type, the privacy effect on the closure is given an explicit representation notated $\sum \lceil \epsilon, \delta \rceil$, which means " (ϵ, δ) -privacy for variables in the closure environment Σ". This effect is latent because the effect isn't "paid for" until (and each time) the function is called, and it is *contextual* because it includes a privacy effect (which may be "zero") for each free variables in the context. This effect is then explicitly scaled by n , the number of loop iterations, in the final effect of applying the function.^{[1](#page-2-0)} More powerful looping combinators such as advanced composition can also be encoded with these latent contextual effects; such combinators cannot be described in any prior linear type system—including Fuzz and DFuzz.

Contributions. Jazz supports writing higher order programs, and automatically verifying that such programs satisfy *advanced variants* of differential privacy-a significant improvement over prior work. The novel features of Jazz—linear types with latent contextual effects—are crucial for practical differentially-private programming. We illustrate this expressive power by showing how to encode numerous mechanisms and tools for differential privacy as Jazz primitives, including the Laplace, Gaussian, and Exponential mechanisms, advanced composition, and privacy amplification by subsampling. We also demonstrate the use of Jazz to verify larger algorithms in two case

¹In addition to the color red, we notate the arrow in privacy function types with a double head \rightarrow to further visually distinguish them from sensitivity function arrows \rightarrow . We describe details such as the definition of the \Box \Box notation later.

studies: the MWEM algorithm [\[28](#page-50-4)] and a recently-proposed differentially-private machine learning algorithm based on gradient descent with adaptive gradient clipping [\[36](#page-50-5)]. Note that these examples are expressible in Duer only by adding new core typing rules for each primitive used, which strictly speaking requires re-proving the metatheory of the extended language. In contrast, JAZZ subsumes DUET and supports all these examples without having to add new typing rules, and with a much smaller core language. Finally, Jazz is amenable to reasonably efficient automated typechecking; we have implemented a typechecker for the language that can verify privacy costs for our case studies in milliseconds.

We prove the type soundness of Jazz using a step-indexed logical relation over a mixed bigstep/denotational semantics with embedded discrete probability distributions as probability mass functions (PMFs). To soundly deal with latent contextual effects, our model uses semantic equivalence in the discrete probability distributions with countably infinite support.

In summary, the contributions of this paper are:

- Jazz, a practical, higher-order, general purpose programming language for writing differentially private programs, which supports advanced variants of differential privacy.
- A novel linear type system for Jazz which includes latent contextual effects, yielding tighter bounds on sensitivity and privacy than previous linear-type-based approaches.
- A formalization and proof of type soundness of λ_J , the core language of JAzz, based on a proof technique with step-indexed logical relations.
- A prototype implementation of the Jazz typechecker, together with a library of primitives for differential privacy, and case studies that demonstrate the expressive power and practicality of Jazz.

We first briefly introduce some key concepts of differential privacy $(\S 2)$ $(\S 2)$ and then give an overview of key design choices and benefits of contextual linear types in Jazz (§ [3\)](#page-5-0). Jazz is a two-language design, and what follows is a presentation of each sub-language in two multi-section arcs. First, we present the sensitivity-only language design (§ [4\)](#page-9-0) and metatheory (§ [5\)](#page-14-0). This language does not include differential privacy operations in the language, or privacy quantities in types. Next, building on this sensitivity core, we present the full privacy language design and metatheory (§ [6](#page-26-0) and [7\)](#page-29-0). Finally, we discuss implementation details including gaps between the actual implementation of Jazz and its formal model (§ [8\)](#page-42-0), present a few case studies in Jazz (§ [9\)](#page-43-0), discuss related work (§ [10\)](#page-46-0), and conclude (§ [11\)](#page-48-0).

2 A DIFFERENTIAL PRIVACY PRIMER

Differential privacy is a mathematical definition of what it means for a computation over sensitive data to preserve privacy [\[24\]](#page-49-0). It interprets privacy as a form of plausible deniability and relies on the use of randomization to achieve it. Informally, a randomized algorithm is differentially private if the probability that it outputs a particular value remains almost the same with or without a single individual's data used as part of the input. Formally, the definition is parameterized by two *privacy parameters* ϵ and δ that specify to what extent two probabilities are "almost the same", and by a distance metric over the algorithm's (sensitive) input whose role we discuss shortly.

DEFINITION 2.1 (DIFFERENTIAL PRIVACY). Given a randomized algorithm (or mechanism) $M \in$ $A \to B$ and a distance metric $\mathfrak{D}_A \in A \times A \to \mathbb{R}$, the algorithm M a satisfies (ϵ, δ)-differential privacy if for all $x, x' \in A$ such that $\mathfrak{D}_A(x, x') \leq 1$ and all possible sets $S \subseteq B$ of outcomes, $Pr[\mathcal{M}(x) \in S] \leq$ $e^{\epsilon}Pr[\mathcal{M}(x') \in S] + \delta.$

The paramenter ϵ quantifies the adversary ability to distinguish two neighbouring inputs upon observing the corresponding algorithm outputs. It represents the privacy guarantee provided by the algorithm—the smaller, the less information is leaked about its input. On the other hand, the parameter δ represents a *failure* probability: with probability at most δ , the algorithm is allowed to violate privacy altogether. In combination, ϵ and δ are typically understood as the "privacy cost" incurred by publicly releasing the algorithm output, associated to a given sensitive input. The case where $\delta = 0$ is called *pure* (or *pure* ϵ *-)* differential privacy, and the case where $\delta > 0$ is called approximate differential privacy. Several other recently-proposed variants of the definition build on the advantages of (ϵ, δ) -differential privacy while eliminating the potential for failure; these include Rényi differential privacy (RDP) [\[31](#page-50-2)], zero-concentrated differential privacy (zCDP) [\[16\]](#page-49-7), and truncated concentrated differential privacy (tCDP) [\[15\]](#page-49-8).

Two algorithm inputs are said to be neighbors if the distance between them is bounded by 1 (i.e. $\mathfrak{D}(x, x') \leq 1$). In order for the formal definition to match our informal statement, the distance metric \mathfrak{D}_A should ensure that neighboring inputs differ by at most one individual's data. Formalizing this notion depends heavily on the domain, so different definitions of $\mathfrak D$ are used in different domains. When considering a relational database table represented as a bag of tuples, one commonly-used definition for \mathfrak{D}_{DB} is symmetric difference [30]: $\mathfrak{D}_{\text{DB}}(x, x') = |(x - x') \cup (x' - x)|$. Under this definition, $\mathfrak{D}_{\mathrm{DB}}(x,x') = 1$ for tables that differ in one *row*; if the data contributed by each individual is bounded to a single row, then this is a good approximation of neighboring inputs.

The definition of differential privacy implies two key properties: post-processing and composition. Post-processing means that the output of a differentially-private mechanism stays differentially private, no matter what additional processing is applied. Composition allows bounding the privacy cost of multiple computations over the same underlaying data: running an (ϵ_1, δ_1) differentially private mechanism followed by an (ϵ_2, δ_2) -differentially private mechanism satisfies $(\epsilon_1 + \epsilon_2, \delta_1 + \delta_2)$ -differential privacy. The privacy parameters ϵ and δ are often called the *privacy* cost because of the additive nature of composition.

Basic Mechanisms, composition, and scaling. Differential privacy mechanisms typically add noise to the output of a deterministic function scaled to the function's *sensitivity* [\[24\]](#page-49-0). A function $f \in$ $A \to B$ with distance metrics \mathfrak{D}_A and \mathfrak{D}_B is called *s*-sensitive if $\mathfrak{D}_A(x, y) \leq d \implies \mathfrak{D}_B(f(x), f(y)) \leq d$ sd for every $d \in \mathbb{R}$ and every $x, y \in A$. Two commonly-used mechanisms are the *Laplace* [\[24\]](#page-49-0) and the *Gaussian* [\[24\]](#page-49-0) mechanisms. Given an *s*-sensitive function $f \in A \rightarrow \mathbb{R}$, the Laplace mechanism releases $f(x) + \text{Lap}(\frac{s}{\epsilon})$, where $\text{Lap}(b)$ denotes a random sample from the Laplace distribution centered at 0 with scale b ; it satisfies ϵ -differential privacy. The Gaussian mechanism releases $f(x) + \mathcal{N}\left(\frac{2s^2 \ln(1.25/\delta)}{\epsilon^2}\right)$ $\frac{(1.25/\delta)}{\epsilon^2}\Big)$, where $\mathcal{N}(\sigma^2)$ denotes a random sample from the Gaussian distribution centered at 0 with variance $\sigma^2;$ it satisfies (ϵ, δ)-differential privacy.

Advanced composition [\[24\]](#page-49-0) yields tighter bounds on privacy cost for many iterative algorithms, but requires (ϵ , δ)-differential privacy. For ϵ , δ , $\delta' \geq 0$, the class of (ϵ , δ)-differentially private mechanisms satisfies $(\epsilon', k\delta + \delta')$ -differential privacy under k -fold adaptive composition (e.g. a loop with k iterations) where $\epsilon' = k\epsilon(e^{\epsilon} - 1) + \epsilon \sqrt{2k \ln(1/\delta')}$. Advanced composition is especially useful for iterative algorithms that perform many differentially private steps in sequence (e.g. iterative machine learning algorithms).

Differential privacy is stated in terms of neighboring inputs, i.e. inputs x and x' such that $\mathfrak{D}_A(x, x') \leq 1$. When $\mathfrak{D}_A(x, x') > 1$, an ϵ -differentially private mechanism provides $\mathfrak{D}_A(x, x') \cdot \epsilon$ differential privacy. Distances larger than one are typically interpreted as groups of individuals, e.g., $\mathfrak{D}_A(x, x') = k$ represents a change to k individual's input data. Therefore, an ϵ -differentially private mechanism provides $k\epsilon$ -differential group privacy [\[24\]](#page-49-0) for groups of size k. A similar property holds for (ϵ, δ) -differential privacy and the more recently developed advanced variants, but the scaling of privacy cost is *nonlinear* for all of these variants, e.g., worse than $(k\epsilon, k\delta)$ for (ϵ, δ) differential privacy. This nonlinearity makes it difficult to apply techniques based on linear types

(which generally internalize linear scaling of costs [\[26](#page-49-3), [33\]](#page-50-0)) for these variants of differential privacy.

Verification Techniques for Differential Privacy. A number of techniques have been proposed for verifying that a program satisfies differential privacy, including approaches based on linear logic $[21, 26, 32, 33, 41]$ $[21, 26, 32, 33, 41]$ $[21, 26, 32, 33, 41]$ $[21, 26, 32, 33, 41]$ $[21, 26, 32, 33, 41]$ $[21, 26, 32, 33, 41]$ $[21, 26, 32, 33, 41]$, couplings and program logics $[5, 7, 8, 10-12, 34]$ $[5, 7, 8, 10-12, 34]$ $[5, 7, 8, 10-12, 34]$ $[5, 7, 8, 10-12, 34]$ $[5, 7, 8, 10-12, 34]$ $[5, 7, 8, 10-12, 34]$, and randomness alignments [\[37,](#page-50-7) [40\]](#page-50-8). Our work is most closely related to Fuzz [\[33](#page-50-0)] and its descendants DFuzz [\[26](#page-49-3)] and DUET [\[32](#page-50-3)], which are based on linear type systems. In particular, these approaches focus heavily on fully automated verification of differential privacy properties through typechecking, and are typically less expressive than program logics, which by contrast support significantly less (or no) automation. We defer a more complete discussion of related work to Section [10.](#page-46-0)

3 OVERVIEW OF JAZZ

Jazz builds on the linear type system of Fuzz [\[33\]](#page-50-0) and the two-language design of Duer [\[32](#page-50-3)] by introducing latent contextual effects. This section introduces and motivates the design of Jazz's two languages— one for sensitivity and one for privacy—using simple examples. The design of each language is described in Sections [4](#page-9-0) and [6](#page-26-0) respectively, and each metatheory is described in Sections [5](#page-14-0) and [7.](#page-29-0)

3.1 A Two-Language Design

Jazz follows Duer in being structured as two mutually-embedded sublanguages, one for sensitivity and one for privacy. The motivation for this choice is described in detail by Near et al. [\[32\]](#page-50-3); we summarize the main points here. The central challenge is that supporting scaling of both sensitivity and privacy is sound only for ϵ -differential privacy, but not for (ϵ, δ) -differential privacy—which has nonlinear group privacy, as discussed in Section [2.](#page-3-0) Therefore, a single language for both sensitivity and privacy, as in Fuzz/DFuzz, does not support (ϵ, δ) -differential privacy, and cannot be easily extended to do so.

In Fuzz/DFuzz, privacy and sensitivity are encoded by the presence (or absence) of a modality/monad, notated $\circ \tau$ for a type τ in the modality \circ . In this way, the type $\mathbb{R} \to_{\circ} \mathbb{R}$ encodes an s-sensitive function and $\mathbb{R} \rightharpoonup_{\epsilon} \rightharpoonup \mathbb{R}$ encoded an ϵ -differentially private function. However, strictly speaking, the type system only sees sensitivity. The type system is parameterized by metric spaces as induced by types, e.g., R induces an absolute difference metric space on the reals. Privacy is then encoded in this system by selecting an appropriate metric that, when interpreted as sensitivity, recovers the definition of differential privacy; the modality \bigcirc induces such a metric.

For sensitivity analysis, it is essential that sensitivities are implicitly and pervasively scaled, and this scaling is justified via the rich structure of metric spaces. Because differentially private functions in Fuzz are encoded as sensitive functions with a special metric, implicit and pervasive scaling is imposed on the tracking of privacy in types as well; this is desirable and—more importantly—sound. However, no such metric exists for embedding (ϵ, δ) -differential privacy in a sensitivity type system, and worse, the implicit and pervasive scaling that is necessary for Fuzz's sensitivity analysis is unsound for (ϵ, δ) -differential privacy (as well as other advanced variants).

Because pervasive scaling of privacy is unsound for (ϵ, δ) -differential privacy, Duer introduced a two-language design, separating a sensitivity sublanguage in which scaling remains implicit and pervasive, and a privacy sublanguage in which scaling is explicit and restricted. JAZZ builds upon this approach. Additionally, Jazz significantly improves both sublanguages thanks to latent contextual effects, as we illustrate next.

Coloring convention. As noted in the introduction, this paper uses colorblind-friendly colors in notation to convey information, and is best consumed using an electronic device or color printer. Contextual Linear Types for Differential Privacy 7

Jazz consists of two mutually embedded sublanguages, and each language is given its own color. Furthermore, these two languages share the same language of types, so we use a third color for the shared fragment. Consequently, we use three color schemes throughout the paper: (1) blue for general math notation and the type system shared between languages; (2) green for the sensitivity language; and (3) red for the privacy language. We have carefully chosen the schemes to be distinguishable (as much as possible) for persons with various forms of color blindness.^{[2](#page-6-0)}

3.2 Sensitivity

In the sensitivity sublanguage of Jazz, the identity function is written $\lambda^\text{s} x$. x . We write sensitivity lambdas as λ^{s} to more easily distinguish them from privacy lambdas, written λ^{p} (described later). The identity function is 1-sensitive in its argument x : if x changes by d , then the function's output also changes by d. Similarly to the identity function, the doubling function $\lambda^s x$. $x + x$ is 2-sensitive in x: if x changes by d then, the function's output changes by $2d$. The same principle applies for multi-argument functions. For example, the curried function $\lambda^s x$. $\lambda^s y$. $x + x + y$ is 2-sensitive in x and 1-sensitive in y . If x changes by d_x and y changes by d_y , then the function's output changes by $2d_x + d_y$.

In general, the sensitivity of a function can be written as a linear combination of the changes in its inputs. In Jazz, we express function sensitivities as linear formulas over the function's input variables, using the variable name itself as a placeholder for the change in that input. Jazz's type system gives the following types for the three examples we have seen so far:

$$
(\lambda^s x. x) : (x : \mathbb{R}) \xrightarrow{x} \mathbb{R}
$$

$$
(\lambda^s x. x + x) : (x : \mathbb{R}) \xrightarrow{2x} \mathbb{R}
$$

$$
(\lambda^s x. \lambda^s y. x + x + y) : (x : \mathbb{R}) \xrightarrow{0x} (y : \mathbb{R}) \xrightarrow{2x+y} \mathbb{R}
$$

The linear formulas written above function arrows represent the sensitivity effect of the corresponding function. The general form of sensitivity function types is $(x:\tau_1) \stackrel{\sum}{\rightarrow} \tau_2$, where Σ is the sensitivity effect of the function, expressed as a linear formula; Note that x is in scope for Σ and τ_2 . Importantly, occurrences of x in Σ and τ_2 represent the sensitivity of the variable x, rather than its value, so Jazz supports sensitivity-dependent types. Also, we usually drop "empty" effects over function arrows such as $\stackrel{0x}{\longrightarrow}$ above, and instead just write \rightarrow .

As usual, Jazz accommodates higher-order functions by scaling sensitivities. For example, applying a 2-sensitive function twice yields a 4-sensitive function:

$$
(\lambda^* f. \lambda^* y. f y + f y) (\lambda^* x. x + x) : (y : \mathbb{R}) \xrightarrow{4y} \mathbb{R}
$$

In addition to function types, other type connectives in Jazz like sums and products also carry sensitivity effects, such as $\tau_1 \xrightarrow{\Sigma_1} \bigoplus_{\mathbb{Z}_2} \tau_2$ for sums, $\tau_1 \xrightarrow{\Sigma_1} \bigotimes_{\mathbb{Z}_2} \tau_2$ for multiplicative products, and $\tau_1 \xrightarrow{\Sigma_1} \bigotimes_{\mathbb{Z}_2} \tau_2$ for additive products. These connectives are extensions of the linear type connectives $\tau_1 \oplus \tau_2$, $\tau_1 \otimes \tau_2$ and τ_1 & τ_2 from Fuzz, augmented with latent sensitivity effects.

We say that sensitivity effects in Jazz are *latent* because they only contribute to the sensitivity of an expression when the type connective is actually eliminated. For instance, in the third example above—a curried function—the sensitivity effect on the first argument is delayed until the second argument is received. If a second argument is never received, then the sensitivity effect on the first argument can be ignored. Likewise, the annotations Σ_1 and Σ_2 in the type $\tau_1 \stackrel{\Sigma_1}{\otimes} \Sigma_2$ τ_2 encode the latent sensitivity cost for each component of the connective: for τ_1 (the left) and τ_2 (the right)

 2 We chose colors following the 24-Color Palette from [http://mkweb.bcgsc.ca/colorblind.](http://mkweb.bcgsc.ca/colorblind) E.g., to persons with deuteranopia (the most common form of color blindness), colorschemes $\blacksquare/\blacksquare$ appear as $\blacksquare/\blacksquare$ respectively.

respectively. In contrast to Fuzz, creating a pair in Jazz has no immediate sensitivity cost: only projecting out of a pair has a cost in sensitivity, depending on which component is projected. Additionally, we say that sensitivity effects are *contextual* because Σ can refer to variables in scope.

As we illustrate in Section [4,](#page-9-0) latent contextual effects are the key mechanism that enable strictly more precise analyses in Jazz than in prior systems. The same technique also applies to the privacy tracking overviewed below.

3.3 Privacy

To encode differential privacy, JAZZ makes use of privacy functions (notated \rightarrow) rather than of sensitivity functions (notated \rightarrow) as in the previous examples. As such, privacy functions are annotated with *privacy*—rather than *sensitivity*—effects. The type of a function from τ_1 to τ_2 which is (ϵ, δ) -differentially private in its argument is as follows:

$$
(x:\tau_1\!\cdot\! d) \xrightarrow{(\epsilon,\,\delta)x} \tau_2
$$

Semantically, this type describes functions f, where if $\mathfrak{D}_{\tau_1}(x, x') \leq d$ then $f(x)$ and $f(x')$ yield distributions which are " (ϵ, δ) -close" according to the definition of (ϵ, δ) -differential privacy.

The annotation d is necessary to support (and unique to) advanced variants of differential privacy like (ϵ, δ) -differential privacy. In the pure ϵ -differential privacy framework, it is common to first establish the property for $d = 1$, that is, if $\mathfrak{D}_{\tau_1}(x, x') \leq 1$ then $f(x)$ and $f(x')$ are ϵ -close. Once established, this property then implies that if $\mathfrak{D}_{\tau_1}(x, x') \leq d$ then $f(x)$ and $f(x')$ are $d\epsilon$ -close, for any d. However, the analogous property is not implied when using advanced variants like (ϵ, δ) differential privacy. As a consequence, d must be specified directly as a parameter and cannot be recovered by scaling the property instantiated to $d = 1$. We refer to this distance— d —as the relational distance since it pertains to the (two-run) relational property of differential privacy, and specifically, the distance between inputs x and x' for each of the two executions $f(x)$ and $f(x')$. We also use this terminology in the context of sensitivity, e.g., an s -sensitive function is one which accepts an input with relational distance d and returns an output with relational distance sd .

As explained in Section [2,](#page-3-0) differential privacy is usually achieved by the use of mechanisms like the Laplace (for ϵ -differential privacy) or the Gaussian mechanism (for (ϵ, δ) -differential privacy). In Jazz, the primitive function implementing the Laplace mechanism has the following type:

$$
\text{laplace}: \forall (\hat{d}: \mathbb{R}) \ (\hat{\epsilon}: \mathbb{R}). \ (d: \mathbb{R}[\hat{d}]) \rightarrow (\epsilon: \mathbb{R}[\hat{\epsilon}]) \rightarrow (x: \mathbb{R} \cdot \hat{d}) \xrightarrow{\infty (d+\epsilon)+(\hat{\epsilon},0)x} \mathbb{R}
$$

There are three logical parameters to the laplace function: d is the relational distance (explained above) used in the statement of privacy satisfied by the function, ϵ is the desired privacy we want to enforce, and x is the value we are adding noise to (and we want to protect). When *executing* laplace, the amount of noise added is Lap $(\frac{d}{\epsilon})$ which depends on both d and ϵ , so they must be runtime values. However, when typechecking laplace, the amount of privacy obtained depends on ϵ , and the distance d must also be tracked to enforce that the computation produces an argument x that has output relational distance no larger than d. Because the values of d and ϵ are required for both runtime execution and type checking, we require a form of dependent types.

To support dependent types, we use a singletons approach—a technique initially developed for dependently typed programming in Haskell [\[25\]](#page-49-11), and which we borrow directly from DFuzz in the context of supporting parameterized differentially private functions [\[26](#page-49-3)]. In this approach, each dependent argument has two representations—one for the type and term level respectively. In the type of laplace, \hat{d} is the type-level representation of term-level variable d , and likewise for $\hat{\epsilon}$ and $\epsilon.$ (We further discuss singletons and their implementation in Section [8.](#page-42-0))

Contextual Linear Types for Differential Privacy 9

The final argument $x:\mathbb{R}\cdot\hat{d}$ will have Laplace noise added to it and then returned as the result of the laplace function. The annotation " $\cdot \hat{d}$ " in the type of x places a precondition on the computation used to supply the value to protect: its output must have relational distance no larger than \hat{d} . After all, the noise added is only guaranteed to give ϵ -differential privacy for values that result from computations with relational distance d .

The final privacy effect for the function is $\infty(d+\epsilon) + (\hat{\epsilon}, 0)x$, indicating that no privacy promises are made for the values d and ϵ , and that privacy is promised for input x with cost ($\hat{\epsilon}$, 0); we write $\infty(d+\epsilon)$ as shorthand for $\infty d + \infty \epsilon$.

We can give a similar type to the gauss function, which provides (ϵ, δ) -differential privacy by adding Gaussian noise drawn from $\mathcal{N}\left(\frac{2d^2\ln(1.25/\delta)}{\epsilon^2}\right)$ $rac{(1.25/\delta)}{\epsilon^2}$:

gauss :
$$
\forall (\hat{d} : \mathbb{R}) (\hat{\epsilon} : \mathbb{R}) (\hat{\delta} : \mathbb{R})
$$
. $(d : \mathbb{R}[\hat{d}]) \rightarrow (\epsilon : \mathbb{R}[\hat{\epsilon}]) \rightarrow (\delta : \mathbb{R}[\hat{\delta}]) \rightarrow (x : \mathbb{R} \cdot \hat{d}) \xrightarrow{\infty (d + \epsilon + \delta) + (\hat{\epsilon}, \hat{\delta})x}$

In Jazz, privacy primitives are used in the privacy sublanguage. For example, the following privacysublanguage expression partially applies the Gaussian mechanism to values for d , ϵ and δ , resulting in a privacy function that satisfies $(1.5, 10^{-5})$ -differential privacy for any 4-sensitive input x:

gauss 4 1.5
$$
10^{-5}
$$
 : $(x : \mathbb{R} \cdot 4) \xrightarrow{(1.5, 10^{-5})x} \mathbb{R}$

Note that we omit the instantiation of forall-quantified type variables \hat{d} , $\hat{\epsilon}$ and $\hat{\delta}$ to type-level constants 4, 1.5 and 10⁻⁵, as they can be inferred from the value-level arguments d , ϵ and δ .

The privacy sublanguage also contains monadic *bind* (notated \leftarrow) and *return* constructs for composing differentially private computations. Privacy functions $\lambda^p(x \cdot d)$. *e* are created in the sensitivity sublanguage (because function creation is "pure"), although the function body e lives in the privacy sublanguage. The annotation d is the relational distance explained previously for privacy function types. For example, the following function computes two differentially private results and adds them together:

$$
\lambda^{p}(x\cdot 1). \ r_1 \leftarrow \text{gauss 1 1.5 0.001 x};
$$
\n
$$
r_2 \leftarrow \text{gauss 2 0.5 0.001} (x + x); \qquad : \qquad (x : \mathbb{R} \cdot 1) \xrightarrow{(2.0,0.002)x} \mathbb{R}
$$
\n
$$
\text{return } (r_1 + r_2)
$$

The bind operator encodes the sequential composition property of differential privacy (Section [2\)](#page-3-0), adding up the ϵ and δ values of subcomputations. The *return* operator encodes the post-processing property of differential privacy. The relational distance parameter of 1 is in general inferrable during type checking; we include it as a visible term-level parameter for presentation purposes.

Beyond Duer. The privacy sublanguage of Jazz briefly introduced here lifts a number of important limitations of the privacy sublanguage of Duer. We sketch two of these here, and postpone further comparison to later sections.

First, to avoid scaling in the privacy sublanguage, DUET requires the arguments to privacy functions to have a maximum sensitivity of 1. This limitation makes it impossible to give general types to the gauss and laplace functions as we just shown in JAZZ. As a result, DUET includes a dedicated type rule for each basic differential privacy mechanism, where each rule is parametric in the sensitivity of the argument. Jazz's addition of the sensitivity annotation " $\cdot d$ " in the types of function arguments eliminates the need for special type rules, and mechanisms can instead be encoded as primitives with an axiomatized type. The primary benefit of this is that the metatheory need not be extended each time a new mechanism is considered.

Table 1. Datatype abstractions provided by systems based on linear types [\[33\]](#page-50-0). For defining the distance associated to the datatypes (table last column), we assume that e_{11} , e_{21} : τ_1 and e_{12} , e_{22} : τ_2 .

Second, while pervasive scaling is generally undesirable for privacy costs, some constructs such as advanced composition rely on the ability to scale privacy costs in controlled ways that are supported by an underlying property. Because DUET's privacy language disallows scaling entirely, these constructs are impossible to encode as functions and must also be given special typing rules. The latent privacy effects in Jazz allow constructs like advanced composition to be given regular function types. Overall, the Jazz design makes differential privacy by typing in the presence of higher-order programming possible for advanced differential privacy variants. The following sections dive into these benefits, by focusing first on the sensitivity sublanguage (Section [4\)](#page-9-0), and then the privacy sublanguage (Section [6\)](#page-26-0). Sections [5](#page-14-0) and [7](#page-29-0) develop the metatheory of each respective sublanguage.

4 DESIGN OF JAZZ'S SENSITIVITY TYPE SYSTEM

Jazz builds upon prior approaches to encoding differential privacy using linear types, addressing several limitations. In this section, we first overview the limitations of these approaches related to the tracking of sensitivities, and then discuss how they are addressed by Jazz. In this section we color expressions and metavariables green as they pertain to the sensitivity fragment of Jazz.

4.1 Linear Products and Sums

Existing approaches based on linear types [\[26,](#page-49-3) [32,](#page-50-3) [33\]](#page-50-0) provide elementary datatype abstractions to programmers such as pairs (products) and tagged unions (sums). However, the sensitivity analysis they implement for these datatypes can lead to overly imprecise—or even unsound—approximations in some circumstances

We now briefly overview these datatype abstractions; a summary is provided in Table [1.](#page-9-1)

Linear products. Because existing systems are based on intuitionistic linear logic, two product types emerge: multiplicative products ⊗ and additive products ⊕. Multiplicative pairs encode two resources, both of which can be used. Additive pairs encode two resources, but in contrast to multiplicative pairs, only one of them can be used at a time—a computation may use either their left or right component, but not both. This constraint is reflected in their destruction mechanisms: while a multiplicative pair is destructed via pattern matching giving access to both its components, an additive product is destructed via projection operators that give access to a single component.

When applied to sensitivity analysis, these type connectives no longer encode accessibility of a pair of resources, rather they encode an abstraction of the sensitivities of each component of the pair. The sensitivity for the whole pair is coarse and either tracks the sum of sensitivities of each component (in the case of multiplicative products) or their maximum (in the case of additive products), as reflected in the last column of Table [1.](#page-9-1)

Linear sums. Rather than a simultaneous occurrence of resources, sums encode an alternative occurrence of resources. Sums are introduced via inl and inr constructors, and destructed via a case expression with one branch for each of the constructors.

In the context of sensitivity analysis, the sensitivity of a sum inl e encodes both the sensitivities of the contained expression e , as well as the sensitivities for the *direction* of the injection (left or right). For example, inl $(x + x)$ is 2-sensitive in x, however if $y \le 10$ then inl x else inr x is ∞ -sensitive in ψ because a change in ψ could change the direction of the injection.

As usual, these systems leverage sums to encode boolean values, e.g., the boolean type is encoded as $\mathbb{B} \triangleq$ unit \oplus unit, where unit represents the unit type, inhabited by unit value tt. Under this encoding, an if − then − else expression becomes syntactic sugar for a case expression. Also note that boolean values true \triangleq inl tt and false \triangleq inr tt are at distance ∞ from each other in this encoding. This observation will be particularly relevant in some of the forthcoming examples.

4.2 Limitations of Prior Sensitivity Linear Type Systems

Fuzz [\[33\]](#page-50-0) is the first work to leverage linear (or affine) types for reasoning about program sensitivity. Since its introduction, others systems based on linear types were developed to address different limitations of Fuzz. These primarily comprises DFuzz [\[26](#page-49-3)], which allows value-dependent sensi-tivities and privacy costs, and Duer [\[32\]](#page-50-3), which allows advanced variants of differential privacy.

Being based on the same underlying sensitivity analysis, all these systems suffer from common limitations related to the sensitivity tracking for products and sums. Through a series of minimal instructive examples, we now discuss the limitations we have identified.

Limitations related to linear products. In Fuzz-like systems, each product and sum type introduces an approximation for the sensitivity analysis they underpin. When using pair types, this approximation forces the programmer to predict how each pair will be used in later parts of the program, and select the right one to achieve precision: if only one component of the pair is used, then the additive product will give perfect precision; conversely, if both components of the pair are used with the same sensitivity, then the multiplicative product will give perfect precision. This is limiting for abstraction, e.g., a library author must commit to one product type, and clients of the library may turn out to require the other.

Imprecision issues remain even if functions can be inlined: (1) the optimal product choice may be influenced by the dynamic control flow of the program, which cannot be predicted statically in general; and (2) for multiplicative products in particular, if both components of the pair are used with different sensitivities in the body of the pattern match, the sensitivity estimation may give imprecise results. To illustrate these limitations, consider the following examples as seen by Fuzz.

Example 4.1 (dynamic control). The program below contains a branch on a boolean variable, which determines the usage pattern of an additive pair: while one branch uses one component of the pair, the other branch uses both.

```
// variant using an additive pair (\cdot, \cdot)let p = (2 * x, x) in
if b then 3 * fst pelse 2 * (fst p + snd p)
```
First, observe that the program is semantically equivalent to 6 $* x$, which is 6-sensitive in x . For the sensitivity analysis a la Fuzz, the pair p is assigned 2-sensitivity in x (the max of each side). The if rule pessimistically takes the maximum between the sensitivities of each branch. This

maximum sensitivity is attained by the else-branch and gives $8 = 2 \cdot (2+2)$, where the underlined 2 corresponds to the sensitivity of pair p in variable x .

Now assume that we rewrite the program using a multiplicative—rather than additive—pair:

// variant using a multiplicative pair
$$
\langle \cdot, \cdot \rangle
$$

let $x_1, x_2 = \langle 2 * x, x \rangle$ in
if *b* then $3 * x_1$
else $2 * (x_1 + x_2)$

In this case, the pair is considered 3-sensitive (rather than 2-sensitive) in x , an estimate that is obtained by adding the sensitivities of its two components, instead of taking their maximum. To obtain the overall program sensitivity, the pair sensitivity is scaled by the maximum sensitivity of the two branches in either component of the pair; this maximum is attained by the then-branch and gives 3 (since the else-branch has sensitivity 2 in both pair components). Overall, this gives an even worse sensitivity in variable x of $9 = 3 \cdot 3$.

In summary, following Fuzz-like analysis, there is no choice of product connective that yields the precise sensitivity bound in x of 6.

Example 4.2 (imprecise scaling). This example shows how imprecision can arise when components of a pair are scaled before introduction, and then in an asymmetric way after elimination. We only show the multiplicative pair variant.

$$
\begin{aligned} \text{let } x_1, x_2 &= \langle 2 * x, y \rangle \text{ in} \\ x_1 + 2 * x_2 \end{aligned}
$$

The above program is semantically equivalent to $2*x+2*y$, which is 2-sensitive in x and 2-sensitive in ψ . However, the type-based analysis yields a sensitivity bound of 4 in x, doubling its actual value. The analysis proceeds roughly as follows. The left component of the pair is 2-sensitive in x , and the right component is 1-sensitive in y . As hinted in the previous example, for multiplicative pairs Fuzz-like systems sum the sensitivities of each component to yield the sensitivity of the whole, so the resulting pair is 2-sensitive in x and 1-sensitive in y; note that $\langle 2 * x + y, 0 \rangle$, $\langle 0, 2 * x + y \rangle$ or even $\langle x, x+y \rangle$ would also result in the exact same sensitivity analysis. The effect of eliminating the pair via pattern matching is to scale the pair sensitivity by the maximum sensitivity of the body $(x_1 + 2 * x_2)$ in the pattern variables $(x_1$ and x_2), 2 in this case. The result is a final sensitivity of $4 = 2 \cdot 2$ in x and $2 = 2 \cdot 1$ in y, which is precise for y, but imprecise for x.

If the program is converted to instead use additive pairs, the sensitivity of the pair construction is 2 in x and 1 in y (the pointwise max from of each side), and the sensitivity of the whole expression is 6 in *x* and 3 in *y*—strictly worse than the analysis when using multiplicative pairs. \Box

Limitations related to linear sums. In addition to imprecision with the product types, Fuzz-like systems also exhibit imprecision with sum types. In these systems, the sensitivity analysis for a sum introduction is straightforward: the sensitivity of $\ln l$ e is simply the sensitivity of e. The sensitivity analysis for the a sum elimination via expression case e of $\{x_1 \Rightarrow e_1\} \{x_2 \Rightarrow e_2\}$ is, however, more involved. First, it computes the sensitivity of e_i in binder x_i for $i = 1, 2$ and retains the greatest, say r . The sensitivity of the overall case expression in some variable, say x , is then computed as the sum between (1) the max sensitivity of e_i in x for $i = 1, 2$, and (2) the sensitivity of e in x , scaled by r . This brings both unsound and imprecise estimations.

Example 4.3 (discontinuous predicate). An unsound corner case of the above sensitivity analysis arises, for example, for the program:

if $(x \leq 10)$ then true else false

The program, which desugars to case $(x \leq 10)$ $\{x_1 \Rightarrow \text{true}\}\{x_2 \Rightarrow \text{false}\}\$, is semantically ∞ sensitive in x because changing x by, say 1, could change the result from true to false, which are infinitely far apart values. Intuitively, we can attribute this to the discontinuity of the program at $x = 10$. As for the Fuzz type system, it derives a sensitivity of $0+0$ · ∞ : the left summand 0 originates from the fact that both branches are 0-sensitive in x and the right summand 0∞ originates from the fact that branches are also 0-sensitive in their binders, and expression $x \leq 10$ is ∞ -sensitive in x. Since the product operation (for sensitivities) adopted by Fuzz regards $0·∞ = 0$, the analysis wrongly infers an overall sensitivity of 0 in x wrongly infers an overall sensitivity of 0 in x .

Fuzz and DFuzz (and derivative systems, like Duer's sensitivity type system) do not account for this corner case and are, therefore, unsound. A follow-up work [20] introduces rules that recover the analysis soundness by interpreting $\infty \cdot 0 = \infty$ rather than $\infty \cdot 0 = 0$, but this leads to imprecision elsewhere in the system. For example, with this fix the program let $y = 100 \times x$ in 1 reports sensitivity 100 in x despite the term being equivalent to the constant 1.

A more recent work [\[21\]](#page-49-9) defines a non-commutative multiplication operator where $0 \cdot \infty = \infty$ but $\infty \cdot 0 = 0$. In doing so, it addresses the soundness problem for case expressions while also preventing imprecisions for let-like operations. This operator is, however, awkward to manipulate and not amenable to automation due to lack of support for non-commutative ring theories in SMT solvers. Even still, imprecisions continue to arise in this design, as we will see in the forthcoming Example [4.4.](#page-12-0)

Besides the corner case described above leading to unsound estimates, imprecise estimates can also arise when eliminating sums. Imprecision arises because, loosely speaking, the analysis approximates the sensitivity of a sum elimination via a case expression as the maximum sensitivity of its branches. As illustrated by the following example, this analysis can dismiss significant information.

Example 4.4 (conflated branches). Consider the following program:

let $a =$ if b then inl $(x * x)$ else inr x in case *a* of $\{x_1 \Rightarrow 0\} \{x_2 \Rightarrow x_2\}$

A sum is created as either the left injection of an expression that is ∞ -sensitive in x (since $x * x$ is so), or the right injection of an expression 1-sensitive in x . In Fuzz-like systems, such a sum is conservatively deemed ∞ -sensitive in x. The sum is then eliminated with a constant left branch, and a right branch that is 1-sensitive in its binder. The ground truth for the program is that it is 1 sensitive in x, as the left injection ∞ -sensitive in x is eliminated to a constant. However, the usual linear typing discipline does not match the sensitivities of each injection with the case-branch that each injection would see, reporting an imprecise final sensitivity of ∞ in x.

4.3 Latent Contextual Effects for Precise Sensitivity Tracking in Jazz

Jazz improves on prior Fuzz-like systems in its ability to achieve strictly more precise sensitivity tracking for product and sum types. The key insight to improved precision is to delay the tracking of sensitivities whenever possible, and to split it into two separate analyses: one for each side of the product or sum. Technically, the main idea is to encode latent sensitivity effects at the typeconnective level. For instance, for multiplicative pairs Jazz has type $\tau_1 \xrightarrow{\Sigma_1 \otimes \Sigma_2} \tau_2$, where Σ_1 and Σ_2 denote the latent sensitivity effects of each of the pair components. This is in contrast to the Fuzz type $\tau_1 \otimes \tau_2$, which pays for all of its sensitivity effects upfront, when the pair is created.

Precise products. Consider the three related multiplicative pair constructions:

 $e_1 \triangleq (2 * x + y, 0)$ $e_2 \triangleq (0, 2 * x + y)$ $e_3 \triangleq (x, x + y)$

For the purpose of sensitivity analysis, Fuzz is unable to distinguish them, as it derives the very same type judgment for all three, namely

 $x :_2 \mathbb{R}, y :_1 \mathbb{R} \vdash e : \mathbb{R} \otimes \mathbb{R}$ for $e \in \{e_1, e_2, e_3\}$

The type judgment says that the pairs are 2-sensitive in x and 1-sensitive in y (the subscript annotations in the type environment), but does not say how this sensitivity effect is distributed between the pair components. In other words, Fuzz treats pairs as a whole. In contrast, Jazz derives three different type judgments, precisely capturing the sensitivity of each pair component:

 $\vdash e_1 : \mathbb{R}^{2x+y} \otimes \mathbb{R} \qquad \vdash e_2 : \mathbb{R} \otimes^{2x+y} \mathbb{R} \qquad \vdash e_3 : \mathbb{R}^{x} \otimes^{x+y} \mathbb{R}$

Recall from Section [3.2](#page-6-1) that in Jazz we use linear formulas to denote sensitivity effects and therefore, in e.g. the first type judgment above, $2x + y$ refers to the sensitivity effect $\Sigma \triangleq \{x \mapsto 2, y \mapsto 1\}$, meaning 2-sensitive in x , and 1-sensitive in y . Moreover, we elide empty sensitivity effects likes $0x + 0y$. This fine-grained tracking of the sensitivity of each pair component allows, in turn, deferring the payment of the pair sensitivity effect to the precise point where the pair is used, i.e. eliminated, and therefore paying only for what (and how it) is used. For example, if pair e_3 is used in a context where only its first component is referred, we pay for sensitivity effect x . Fuzz, in contrast, would always pay $2x + y$.

Let us discuss the benefits that this fine-grained tracking brings to Examples [4.1](#page-10-0) and [4.2.](#page-11-0) Consider first the program from Example [4.1,](#page-10-0) more concretely, the variant with additive pairs. The sensitivity of the then-branch is calculated as $6x$ from scaling by 3 the (latent) sensitivity effect $2x$ of the left component of pair p . Likewise, the sensitivity of the else-branch is calculated also as 6 x from scaling by 2 the sum of (latent) sensitivity effects 2 x and x of the respective left and right component of the pair. As a result, JAZZ reports the precise sensitivity of $6x$ for the whole program. An analogous fine-grained tracking for the program from Example [4.2](#page-11-0) gives also precise sensitivity $2x + 2y$.

Precise sums. The use of latent sensitivity effects yields tighter sensitivity bounds also for sums. However, the handling of sums impose an additional technical challenge related to the impossibility of delaying sensitivity effects. To illustrate this phenomenon, consider expressions:

```
e_4 \triangleq \text{inl} (x * x) e_5 \triangleq \text{inr} (x * x) e_6 \triangleq \text{if} (x \leq 10) then inl 1 else inr 1
```
All three expressions are ∞ -sensitive in x. Fuzz sensitivity analysis conflates e_4 and e_5 to the same type and derives an unsound type (w.r.t. the embodied sensitivity analysis) for e_6 :

 $x :_{\infty} \mathbb{R} \vdash e_4 : \mathbb{R} \oplus \mathbb{R}$ $x :_{\infty} \mathbb{R} \vdash e_5 : \mathbb{R} \oplus \mathbb{R}$ $x :_{0} \mathbb{R} \vdash e_6 : \mathbb{R} \oplus \mathbb{R}$

Jazz derives instead:

$$
\vdash e_4 : \mathbb{R}^{\infty} \oplus \mathbb{R} \qquad \vdash e_5 : \mathbb{R} \oplus^{\infty} \mathbb{R} \qquad \vdash e_6 : \mathbb{R} \oplus \mathbb{R}
$$

The types of e_4 and e_5 encode a latent sensitivity effect for each side of the sum. In contrast, the type of e_6 is not able to represent its ∞-sensitivity in x as a latent effect because x influences which injection is used to create the sum itself, not the value inside the injection. Instead, the effect must be paid for *eagerly* in the so-called *ambient* sensitivity effect (which was empty in previous examples). Therefore type judgments in Jazz have shape $Γ$ \vdash $e : \tau : \Sigma$, where Σ represents the ambient sensitivity effect and Γ is a "traditional" environment, mapping variables to types. Thus, expression e_6 is formally typed as:

$⊢ e_6 : \mathbb{R} \oplus \mathbb{R} : \infty x$

with ambient sensitivity effect ∞x . e_4 is typed as $\vdash e_4 : \mathbb{R}^{\infty x} \oplus \mathbb{R}$; \varnothing , i.e., with an empty ambient sensitivity effect, and analogously for e_5 .

Contextual Linear Types for Differential Privacy 15

	FUZZ		JAZZ	
Program	Reported Sensitivity	Bound Quality	Reported Sensitivity	Bound Quality
Example 4.1 (additive)	8x	loose	6x	tight
Example 4.2 (multiplicative)	$4x + 2y$	loose (in x)	$2x + 2y$	tight
Example 4.3	0x	unsound	∞x	tight
Example 4.4	$\infty x + 0b$	loose (in x) unsound in <i>b</i>	$x + b$	tight

Table 2. Comparison of sensitivity type-system: Fuzz vs Jazz.

To showcase the benefits of this design, let us re-examine Example [4.4.](#page-12-0) In Jazz, the type for t is $\mathbb{R} \infty$ $\mathbb{R} \in \mathbb{R}$ with ambient effect b .^{[3](#page-14-1)} To compute the sensitivity of the case-expression over *t*, we join—by taking the variable-wise maximum—the ambient effect of t , namely b , with the "global" sensitivity effect of the second branch, namely $[b + x/x_2]x_2$ —the first branch is dismissed because it has no ambient effect. To compute the purported sensitivity effect of the second branch, we take its ambient effect x_2 and replace every occurrence of the branch binder, also x_2 , with the effect $b + x$ of the right component of t, computed as the sum between its ambient effect b and its latent effect x. This yields an overall sensitivity of $b + x = b \sqcup [b + x/x_2]x_2$ for the case-expression.

Consider now Example [4.3.](#page-11-1) The guard $x \le 10$ of the conditional expression has type unit⊕unit with ambient effect ∞x . Since the branches are constant and have no ambient effect, they do not contribute to the sensitivity of the conditional. Jazz analysis then concludes that the sensitivity of the conditional reduces to the ambient sensitivity of the guard, namely ∞x , recovering soundness (and precision).

Jazz recovers soundness and precision for all four examples discussed in Section [4.2,](#page-11-2) as summarized in Table [2.](#page-14-2) With this observation, we conclude our motivation for the design of the Jazz sensitivity type system, based on latent contextual effects.

As a final technical remark, we highlight that even with latent contextual effects, which allow for very precise sensitivity bounds, the distinction between multiplicative and additive products is particularly important to maintain in presence of type-level polymorphism. Indeed, effects may need to be paid for "upfront" if a latent effect would otherwise be substituted into an incompatible scoping environment. When paying for these sensitivities upfront, the usual advantages of having two product type connectives apply—one pays for the maximum sensitivity of arguments while the other pays for the sum.

The following section presents the formal development of latent contextual effects for sensitivity typing, and includes a step-by-step type derivation for all four examples.

5 SAX: JAZZ'S SENSITIVITY TYPE SYSTEM, FORMALLY

In this section, we present a core sensitivity sublanguage of Jazz, called Sax, for which we develop the sensitivity metatheory. In particular, we prove the type soundness property known as sensitivity metric preservation [\[33\]](#page-50-0). The core subset of Jazz that extends Sax with privacy is presented in later sections.

³At first sight, one might think that t is ∞ -sensitive in b because a change in b may flip the direction of the returned injection. However, any change on the value of b necessarily results in an infinite variation since true and false are ∞ far apart. Therefore, the induced variation on the value of t is trivially bounded by ∞ , scaled by 1, turning t 1-sensitive in b .

```
r \in \mathbb{R}b \in \mathbb{B}x \in \text{var}e \in \text{sexpr} \equiv r \mid e + e \mid e * e \mid e \leq e real numbers
                     \vert x \vert \lambda^svariables, functions, applications<br>unit
                     | tt unit
                     | inl<sup>\tau_2</sup> e | inr<sup>\tau_1</sup> e | case e of \{x \Rightarrow e\} {x \Rightarrow e} sums
                    |(e,e)| fst e| snd e add. products and (e,e) and
                    | h𝑒, 𝑒i | let 𝑥, 𝑥 = 𝑒 in 𝑒 mult. products
                                                                                                                 ascription<br>(derived) booleans
                    | b | if e then e else e (derived) booleans (derived) booleans (derived) booleans (derived) let
                   | let x = e in es \in sens \cong \mathbb{R}^{\infty}_{\geq 0}sensitivities
\Sigma \in \text{senv} \triangleq \text{var} \rightarrow \text{sens} :: = sx + \ldots + sx sensitivity environments
 \tau \in \text{type} = \mathbb{R} \mid \mathbb{B} \mid \text{unit} \mid (x : \tau) \xrightarrow{\Sigma} \tau\int \tau^{\Sigma} \oplus \frac{\Sigma}{\tau} \mid \tau^{\Sigma} \otimes \frac{\Sigma}{\tau} \mid \tau^{\Sigma} \otimes \frac{\Sigma}{\tau}types
\Gamma \in \text{tenv} \ \triangleq \ \text{var} \rightarrow \text{type} \ \coloneqq \{x : \tau, \ldots, x : \tau\} type environments
```
Fig. 1. Sax: Syntax

5.1 Syntax and Type System

The Sax type system is technically a type-and-effect system [\[27\]](#page-50-9). It supports real numbers, functions, sums and products. As Sax only deals with ambient effects, all metavariables and keywords are typeset in green.

Syntax. Figure [9](#page-30-0) presents the syntax of SAx. Expressions e are mostly standard and include: real number *r*, addition $e + e$, multiplication $e * e$, comparison $e \le e$, variable *x*, sensitivity lambda $\lambda^s(x : \tau)$. e, application e e, unit value tt, sum constructors inl^{τ_2} e and inr^{τ_1} e, and the sum destructor case *e* of $\{x \Rightarrow e\}$ $\{x \Rightarrow e\}$.

Sax also supports two linear products types: additive and multiplicative. With additive products, the sensitivity of a pair may be approximated as the max of the sensitivities of each side; this sensitivity is paid for every projection. With multiplicative products, the sensitivity of a pair may be approximated as the sum of the sensitivities of each side; this sensitivity is paid for every tuple pattern match, scaled by the sensitivities of pattern variables in the body.We write additive product constructions (e, e) and destructions fst e and snd e, and multiplicative product constructions $\langle e, e \rangle$ and destructions let $x, x = e$ in e .

Finally, an expression e can be an ascription $e :: \tau$, or a derived expressions such as a boolean b, a conditional if e then e else e, or a let expression let $x = e$ in e. Booleans are encoded as true \triangleq inl tt and false \triangleq inr tt, conditionals as if e_1 then e_2 else $e_3 \triangleq$ case e_1 of $\{x \Rightarrow$ e_2 $\{y \Rightarrow e_3\}$, and let expressions as let $x = e_1$ in $e_2 \triangleq (\lambda^s(x : \tau_1).e_2)$ e_1 .

A sensitivity s is either a non-negative real number or the symbol ∞ , which represents an unbounded sensitivity; we notate this set $\mathbb{R}^{\infty}_{\geq 0} \triangleq \mathbb{R}_{\geq 0} \cup \{\infty\}$. A sensitivity environment Σ is a mapping from variables to their sensitivities. For convenience, we write sensitivity environments as firstorder polynomials, e.g. $\Sigma = 1x + 2y$ corresponds to an environment Σ such that $\Sigma(x) = 1$ and $\Sigma(y) = 2$. A type τ is either the real number type R, the boolean type B, the unit type unit, a

Contextual Linear Types for Differential Privacy 17

function type $(x : \tau) \xrightarrow{\Sigma} \tau$, a sum type $\tau^{\Sigma} \oplus \Sigma \tau$, an additive product type $\tau^{\Sigma} \otimes \Sigma \tau$, or a multiplicative product type $\tau \Sigma \otimes \Sigma \tau$. The sensitivity environment annotation Σ is called the *latent contextual* sensitivity effect (also called latent effect when clear from the context) and represents a delayed effect that emerges when a term of said type is eliminated. The latent effect Σ of a function of type $(x : \tau) \xrightarrow{\Sigma} \tau$ corresponds to the effects of applying the function, i.e., a static approximation of the sensitivity of each variable used in its body. The sensitivity environment Σ_1 (resp. Σ_2) in τ_1 $\Sigma_1 \oplus \Sigma_2$ τ_2 corresponds to the latent effect of the injected value using inl (resp. inr). And similarly, Σ_1 and Σ_2 in τ_1 $\Sigma_1 \otimes \Sigma_2$ τ_2 or τ_1 $\Sigma_1 \otimes \Sigma_2$ τ_2 correspond to the latent effect of accessing the first and second components of the pair, respectively. Finally, a type environment Γ is, as usual, a mapping from variables to types.

Type system. The SAX type system is presented in Figure [2.](#page-17-0) The judgment $\Gamma \vdash e : \tau : \Sigma$ says that the term e has type τ and ambient sensitivity effect Σ (or ambient effect when clear from the context) under type environment Γ. The ambient effect Σ represents an upper bound (conservative approximation) of the real sensitivity of e after executing the program.

- Rules RLIT and UNIT are standard and report no effect, as no variable is accessed.
- Rule var is mostly standard; it reports an ambient effect $1x$.
- For example,

$$
\frac{\text{var}}{(x : \mathbb{R})(x) = \mathbb{R}}{\overline{x : \mathbb{R} + x : \mathbb{R} : x}}
$$

- Rule plus computes the resulting ambient effect as the addition of the ambient effects of both subterms. To add sensitivity environments we use the + operator, which is simply defined as the addition of polynomials, e.g. $(1x + 2y) + (3x) = 4x + 2y$. For example, in the following type derivation

$$
\frac{x : \mathbb{R} \vdash x : \mathbb{R} ; x \qquad x : \mathbb{R} \vdash x : \mathbb{R} ; x}{x : \mathbb{R} \vdash x + x : \mathbb{R} ; 2x}
$$

we write $2x$ instead of $x + x$.

- Rules TIMES and LEQ are similar to plus, but the resulting sensitivity effect is scaled by infinity because (1) the sensitivity of a multiplication when neither side is a constant is unbounded, and (2) the distance between distinct boolean values is deemed infinite, as explained in Section [4.1.](#page-9-2) Scaling a sensitivity environment Σ by sensitivity s, written $s\Sigma$, produces a new sensitivity environment in which each sensitivity in Σ is multiplied by s. For multiplication we assume that $0s = s0 = 0$ for all $s \in \mathbb{R}^{\infty}_{\geq 0}$ and we deem $\infty s = s\infty = \infty$ for $s \neq 0$.

Rules L-SCALE and R-SCALE address the overapproximation yielded by rule TIMES when one of the factors is a real number. For instance, for program $0.5 * x$ rule L-scale reports a (precise) sensitivity of 0.5 x , whereas rules TIMES would report ∞x .

- Rule lam typechecks sensitivity functions. The type of the function is annotated with a latent effect Σ , computed as the ambient effect of its body. The ambient effect of function definition expression proper is empty, because creating a function value is pure.

For example, consider program $\lambda^s(x : \mathbb{R})$. $x + x$ and its type derivation:

lam $x : \mathbb{R} \vdash x + x : \mathbb{R}$; 2x $\varnothing \vdash \lambda^s(x : \mathbb{R})$. $x + x : (x : \mathbb{R}) \xrightarrow{2x} \mathbb{R}$; \varnothing

Fig. 3. Sax: Auxiliary definitions of the static semantics (selected rules)

The ambient effect of the program is empty (values are pure) but its latent effect is $2x$, the ambient effect of its body.

- Rule app deals with function application. As variable x may be free in τ_2 (e.g. τ_2 can be a function type whose latent effect includes x), the resulting type replaces x with the ambient effect Σ_2 of its argument using the sensitivity environment substitution operator defined in Figure [3.](#page-18-0) For instance, consider type $(x : \mathbb{R}) \stackrel{\emptyset}{\rightarrow} (z : \mathbb{R}) \xrightarrow{2x+y+z} \mathbb{R}$. After application, if $\Sigma_2 = 3y$, the resulting type would be $[3y/x]((z : \mathbb{R}) \xrightarrow{2x+y+z} \mathbb{R}) = ((z : \mathbb{R}) \xrightarrow{6y+y+z} \mathbb{R}) = ((z : \mathbb{R}) \xrightarrow{7y+y} \mathbb{R})$. The ambient effect of an application is computed as the ambient effect of the function Σ_1 , plus its latent effect; but as *x* is free we substitute it by Σ_2 , e.g. if $\Sigma = \Sigma' + sx$, then $[\Sigma_2/x](\Sigma_1 + \Sigma' + sx) = \Sigma_1 + (\Sigma' + s\Sigma_2)$. For instance, consider the open program $(\lambda^s(x : \mathbb{R})$. $2 * x + y)$ $(3 * y)$ and the following type derivation:

$$
\frac{y:\mathbb{R} \vdash \lambda^s(x:\mathbb{R}). 2*x+y:(x:\mathbb{R}) \xrightarrow{2x+y} \mathbb{R}; \emptyset \qquad y:\mathbb{R} \vdash 3*y:\mathbb{R}; 3y}{y:\mathbb{R} \vdash (\lambda^s(x:\mathbb{R}). 2*x+y)(3*y):\mathbb{R}; 7y}
$$

The resulting ambient effect cannot depend on x (otherwise it would be free), therefore it is computed as the substitution of x by the security effect of the argument $\frac{3y}{x}\left(\frac{2x+y}{-7y}\right) = 7y$.

- Contrary to previous work [\[26](#page-49-3), [32,](#page-50-3) [33](#page-50-0)], Rule INL reports an empty ambient effect: it is considered a pure value. The payment of effects for the subexpression is *delayed*, and eventually done only if the sum is accessed or used. The term is tagged with type τ_2 to aid type inference. The resulting type is just a sum type where the latent effect of the left type is Σ , the ambient effect of its subterm, and the latent effect of the right type is empty (as it will never be used/accessed so we choose the tighter ambient effect). Rule inr is defined similarly.

For instance, consider the type derivations of expressions $e_4 = \text{inl } (x * x)$ and $e_5 = \text{inr } (x * x)$ of Section [4.3:](#page-12-1)

Fig. 4. Sax: Join and Meet of types and sensitivity environments

For expression e_4 , the latent effect of the left type is ∞x , and of the right type is empty (it is the tighter upper bound as the right component cannot be accessed). An analogous argument is used for e_5 .

- Rule case is more involved. The resulting type of the case is just the least upper bound (join) of the branch types τ_2 and τ_3 . The join operator is defined in Figure [4.](#page-19-0) Note that similarly to rule APP, τ_2 and τ_3 may have x and y as free variables respectively, thus we replace those variables with the ambient effects of using the sum term $e_1: \Sigma_1 + \Sigma_{11}$ and $\Sigma_1 + \Sigma_{12}$ respectively. The resulting ambient effect is computed as follows: we join the cost of reducing $e_1: \Sigma_1$, with the join of the cost of taking each branch. Similarly to types τ_2 and τ_3 , ambient effects Σ_2 and Σ_3 may have x and y free, so we substitute them away from the effects. Note that we use the join between Σ_1 and the cost of the branches (instead of the addition for instance), otherwise the result would be less precise when the branches use x or y .

case

For instance, the type derivation of Example [4.4](#page-12-0) is described below:

$$
\frac{\Gamma \vdash e : \mathbb{R} \stackrel{\infty}{x} \oplus^x \mathbb{R}; b \qquad \Gamma, x_1 : \mathbb{R} \vdash 0 : \mathbb{R}; \emptyset \qquad \Gamma, x_2 : \mathbb{R} \vdash x_2 : \mathbb{R}; x_2}{\Gamma \vdash \text{case } e \text{ of } \{x_1 \Rightarrow 0\} \{x_2 \Rightarrow x_2\} : \mathbb{R}; b \sqcup (0b + 0(\infty x)) \sqcup (1b + 1(x))}
$$

where $\Gamma = b : \mathbb{B}, x : \mathbb{R}$, and $e = \text{if } b \text{ then } \{\text{inl } (x * x)\}\text{ else } \{\text{inr } x\}$. The resulting ambient effect is $b \sqcup (0b + 0(\infty x)) \sqcup (1b + 1(x)) = b \sqcup (0b + 0x) \sqcup (b + x) = b + x$, where previous work reported ∞ on x.

Notice that if we change the program to case e of $\{x_1 \Rightarrow 0\} \{x_2 \Rightarrow 1\}$, then the resulting ambient effect is $b \sqcup (0b + 0(\infty x)) \sqcup (0b + 0(x)) = b$, i.e. the payment is not zero but b, the cost of reducing expression e to a value.

Example [4.3](#page-11-1) is desugared and type checked as follows:

CASE
 $\Gamma \vdash x \leq 10 : \mathbb{B}; \infty x$ $\Gamma, x_1 : \mathbb{R} \vdash \text{true} : \mathbb{R}; \emptyset$ $\Gamma, x_2 : \mathbb{R} \vdash \text{false} : \mathbb{R}; \emptyset$ $\Gamma \vdash \text{case } x \leq 10 \text{ of } \{x_1 \Rightarrow \text{true}\}\{x_2 \Rightarrow \text{false}\} : \mathbb{B}; \infty \times \sqcup (0(\infty x) + 0(\emptyset)) \sqcup (0(\infty x) + 0(\emptyset))$

where $\mathbb{B} = \text{unit} \ \mathcal{O} \oplus \mathcal{O} \text{ unit.}$ As $\infty x \sqcup (0(\infty x) + 0(\emptyset)) \sqcup (0(\infty x) + 0(\emptyset)) = \infty x \sqcup 0x = \inftyx$, the expression is ∞ -sensitive in \hat{x} .

- Similarly to Rules inl and inr, Rules pair and tup report no ambient effects, since the payment is done when each component is accessed. The latent annotations Σ_1 and Σ_2 are computed from the first and second components respectively.

For instance, let us consider examples $e_1 = (2 * x + y, 0), e_2 = (0, 2 * x + y)$, and $e_3 = (x, x + y)$ from Section [4.3:](#page-12-1)

$$
\frac{\Gamma+2*x+y:\mathbb{R};2x+y \Gamma+0:\mathbb{R};\emptyset}{\Gamma+(2*x+y,0):\mathbb{R}^{2x+y}\&\Phi \mathbb{R};\emptyset} \qquad \frac{\Gamma+0:\mathbb{R};\emptyset \Gamma+2*x+y:\mathbb{R};2x+y}{\Gamma+(0,2*x+y):\mathbb{R}^{\emptyset}\&\mathbb{R}^{2x+y}\mathbb{R};\emptyset}
$$
\n
$$
\frac{\Gamma+x:\mathbb{R};x \Gamma+x+y:\mathbb{R};x+y}{\Gamma+(x,2*x+y):\mathbb{R}^{x}\&\mathbb{R}^{x+y}\mathbb{R};\emptyset}
$$

where $\Gamma = x : \mathbb{R}, y : \mathbb{R}$.

- Rules proj1 and proj2 type check the deconstruction of an additive product. The ambient effect is computed as the cost of reducing the product (Σ) , plus the cost of accessing either the first or the second component correspondingly (Σ_1 or Σ_2).

For instance, let us consider the first projections of last examples:

proj1 $\Gamma \vdash (2 * x + y, 0) : \mathbb{R}^{2x+y} \&^\emptyset \mathbb{R}$; \emptyset Γ + fst $(2 * x + y, 0) : \mathbb{R}$; 2x + y proj1 $\Gamma \vdash (0, 2*x+y) : \mathbb{R}^\varnothing \&^{2x+y} \mathbb{R}$; \varnothing Γ ⊦ fst $(0, 2 * x + y) : \mathbb{R}$; ∅ proj1 $\Gamma \vdash (x, 2 * x + y) : \mathbb{R}^x \&x+y$ Γ + fst $(x, 2 * x + y) : \mathbb{R}$; x

Contrary to previous work, the ambient effects of all three projections are different, as they capture precisely the variables accessed on the corresponding component.

- Rule UNTUP typechecks the deconstruction of a multiplicative product. The resulting type and ambient effect, is the type and ambient effect of subexpression e_2 , where we substitute away free

Fig. 5. Sax: Derived type rules

variables x_1 and x_2 with the cost of accessing the left and right components respectively, i.e. x_1 for $\Sigma_1 + \Sigma_{11}$ and x_2 for $\Sigma_1 + \Sigma_{12}$.

For instance, let us consider the type derivation of Example [4.2:](#page-11-0)

UNITUP

\n
$$
\frac{\Gamma \vdash (2 * x, y) : \mathbb{R}^{2x} \otimes^y \mathbb{R} ; \varnothing \qquad \Gamma, x_1 : \mathbb{R}, x_2 : \mathbb{R} \vdash x_1 + 2 * x_2 : \mathbb{R} ; x_1 + 2x_2}{\Gamma \vdash \text{let } x_1, x_2 = (2 * x, y) \text{ in } x_1 + 2 * x_2 : \mathbb{R} ; 1(2x) + 2(y)}
$$

where $\Gamma = x : \mathbb{R}, y : \mathbb{R}$. The resulting ambient effect is $1(2x) + 2(y) = 2x + 2y$.

- Rules for booleans, conditionals and let expressions are derived rules from sums, case, and application rules respectively, and can be found in Figure [5.](#page-21-0)
- Finally, Rule ascr is the only rule that supports the use of subtyping.

Subtyping for types and sensitivity environments is presented in Figure [6,](#page-22-0) and is mostly standard. We only allow subtyping for the sensitivity parts of types. A sensitivity environment is subtype of another if their sensitivities are less than or equal than the other for each variable. For instance,

 $(x : \mathbb{R}) \xrightarrow{x+y} \mathbb{R} \leq: (x : \mathbb{R}) \xrightarrow{x+2y+3z} \mathbb{R}$ because $x + y \leq: x + 2y + 3z$ $(x \leq x, y \leq 2y,$ and $0z \leq 3z$).

5.2 Type Safety

Type safety is established relative to the runtime semantics of Sax. We adopt a big-step semantics with explicit substitutions. Concretely, we use $\gamma \vdash e \Downarrow v$ to represent that *configuration* $\gamma \vdash e$ –formed by expression e and value environment γ mapping variables to values– reduces to value v after some number of steps. Reducion rules are rather standard and can be found in Appendix [B,](#page-51-0) Figure [28.](#page-59-0)

To establish SAx type safety, we employ simple unary logical relations, called the type safety logical relations, that characterize well-typed, non-stuck execution. The type safety result itself is derived as a corollary of the fundamental property of the type safety logical relations.

The type safety logical relations is defined in Figure [7.](#page-23-0) For simplicity, we only present the cases for real numbers, variables, functions, and sums. The other cases are similar and straightforward. The unary logical relations are split into mutually recursive value relations V , computation relation $\mathcal E$, and environment relation $\mathcal G$, and defined as follows:

- Any value is in $Atom[[\tau]]$ if the value type checks to some $\tau' < \tau$ under an empty type environment.
- A real number is in the value relation at type $\mathbb R$ if the number is in $Atom[\mathbb R]$.

Fig. 6. Sax: Subtyping

- Similarly, a unit value tt is always related at type unit.
- An inl(resp. inr) value is in the value relation at $\tau_1 \circ \theta \circ \tau_2$ if the value is in $Atom[\![\tau_1 \circ \theta \circ \tau_2]\!]$ and the underlying value v is in the value relation at τ_1 (resp. τ_2).
- $-$ A closure is in the value relation at type $(x : \tau_1) \xrightarrow{sx} \tau_2$ if it satisfies $Atom[[x : \tau_1) \xrightarrow{sx} \tau_2]$, and given any value \bar{v} in the value relation at argument type τ_1 , the extended configuration $\gamma[x \mapsto v] \vdash e$ is in the computation relation at type $\tau_2/(x:\tau_1)$. We use the ./Γ operator to remove variables from a type and is defined as follows:

$$
\tau/\Gamma = [\emptyset/x_1, ..., \emptyset/x_n]\tau, \forall x_i \in dom(\Gamma)
$$

- A configuration is in the computation relation at type τ , if the configuration reduces to some value v , which is itself in the value relation at type τ .
- Finally, a value environment γ is in the environment relation at Γ if the domains of γ and Γ are the same, and for each variable in the domain of γ the underlying value $\gamma(x)$ is in the value relation at type $\Gamma(x)/\Gamma$ (we use the ./Γ operator to empathize that the type is closed).

As usual, the fundamental property of the type safety logical relation states that well-typed open terms are in the relation closed by an adequate environment γ :

PROPOSITION 5.1 (FUNDAMENTAL PROPERTY OF THE TYPE SAFETY LOGICAL RELATION). Let $\Gamma \vdash e : \tau; \Sigma$, and $\gamma \in \mathcal{G}[\Gamma]$. Then $\gamma \vdash e \in \mathcal{E}[\tau/\Gamma]$.

Type safety for closed terms follows immediately as a corollary:

Corollary 5.1 (Type Safety and Normalization of Sax). Let $\vdash e : \tau; \varnothing$, then $\vdash e \Downarrow v$, and $\vdash v : \tau'; \varnothing$, where $\tau' \leq \tau$.

$$
\frac{\emptyset \vdash v : \tau'; \emptyset \qquad \tau' < : \tau}{v \in Atom[\![\tau]\!]} \qquad \frac{r \in Atom[\![\mathbb{R}]\!]}{r \in V[\![\mathbb{R}]\!]} \qquad \frac{\text{tt } \in Atom[\![\text{unit}]\!]}{\text{tt } \in V[\![\text{unit}]\!]}
$$
\n
$$
\frac{\text{in} \Gamma^2 v \in Atom[\![\tau_1 \otimes \oplus \otimes \tau_2]\!] \qquad v \in V[\![\tau_1]\!]}{\text{in} \Gamma^2 v \in V[\![\tau_1 \otimes \oplus \otimes \tau_2]\!]} \qquad \frac{\text{in} \Gamma^2 v \in Atom[\![\tau_1 \otimes \oplus \otimes \tau_2]\!] \qquad v \in V[\![\tau_2]\!]}{\text{in} \Gamma^2 v \in V[\![\tau_1 \otimes \oplus \otimes \tau_2]\!]}
$$
\n
$$
\frac{\langle v_1, v_2 \rangle \in Atom[\![\tau_1 \otimes \otimes \otimes \tau_2]\!] \qquad v_1 \in V[\![\tau_1]\!] \qquad v_2 \in V[\![\tau_2]\!]}{\langle v_1, v_2 \rangle \in V[\![\tau_1 \otimes \otimes \otimes \tau_2]\!]}
$$
\n
$$
\frac{\langle \vec{x} \cdot \tau, e, \gamma \rangle \in Atom[\![(x : \tau_1) \xrightarrow{sx} \tau_2]\!] \qquad v_1 \in V[\![\tau_1]\!] \qquad v_2 \in V[\![\tau_2]\!]}{\langle \vec{x} \cdot \tau_1, e, \gamma \rangle \in V[\![\tau_1 \otimes \otimes \tau_2]\!]}
$$
\n
$$
\frac{\langle \vec{x} \cdot \tau, e, \gamma \rangle \in Atom[\![(x : \tau_1) \xrightarrow{sx} \tau_2]\!] \qquad Vv \in V[\![\tau_1]\!] \cdot \gamma[x \mapsto v] \mapsto e \in \mathcal{E}[\![\tau_2 \mid (x : \tau_1)\!]]}{\langle \vec{x} \cdot \tau_1, e, \gamma \rangle \in V[\![\tau_1 \cdot \tau_1] \xrightarrow{sx} \tau_2]\!]}
$$
\n
$$
\frac{\gamma \vdash e \downarrow v \qquad v \in V[\![\tau]\!]}{\gamma \vdash e \in \mathcal{E}[\![
$$

Fig. 7. Sax: Type Safety Logical Relations

5.3 Type Soundness

This section establishes the type soundness of SAx, stated in terms of a *metric preservation* result. Loosely speaking, metric preservation captures the maximum variation of an open term when it is closed under two different (but related) environments.

Logical relations. To establish this soundness result, we make use of logical relations. In particular, we define (mutually recursive) logical relations for sensitivity values, computations and environments; see Figure [8.](#page-24-0) The logical relations for values ($\mathcal{V}_d[\sigma]$) and computations ($\mathcal{E}_d[\sigma]$) are indexed by a relational distance $d \in \mathbb{R}^{\infty}_{\geq 0}$ and a so called *relational distance type* σ , which is a regular type where sensitivity environments are enriched with a constant $d \in \mathbb{R}^{\infty}_{\geq 0}$ denoting the distance induced by pair of substitutions. Formally, the syntax of relational distance types is defined as follows:

$\sigma = \mathbb{R} \mid \mathbb{B} \mid \text{unit} \mid (x : \sigma) \xrightarrow{\Sigma + d} \sigma \mid \sigma^{\Sigma + d} \oplus^{\Sigma + d} \sigma \mid \sigma^{\Sigma + d} \otimes^{\Sigma + d} \sigma \mid \sigma^{\Sigma + d} \otimes^{\Sigma + d} \sigma$

For notation simplicity, in the rest of the section we name relational distance types as types when the acompanying relational distances can be inferred from the context. Also we omit the environment notations when they are empty. On the other hand, the logical relation for environments $(G_\Delta \|\Gamma\|)$ is indexed by a *relational distance environment* Δ , mapping variables to relational distances in $\mathbb{R}^\infty_{\geq 0}$ and a type environment Γ . We use $(v_1, v_2) \in \mathcal{V}_d[\![\sigma]\!]$ to denote that value v_1 is related to value v_2 at type σ and relational distance d, and likewise for expressions (i.e. computations) and environments.

Fig. 8. Sax: logical relations for metric preservation

To define logical relations we also make use of relational distance instantiations, which have shape $\Delta(\Sigma + d)$ and act by replacing free variables in sensitivity environment Σ with the distances provided by distance environment Δ. Relational distance instantiations only close variables defined in Δ and are formally defined as:

> $\Delta \cdot \varnothing = 0$ $\Delta \cdot (\Sigma + d) = \Delta \cdot \Sigma + d$ $\Delta \cdot (\Sigma + sx) = \Delta \cdot \Sigma + sd$ if $\Delta(x) = d$ $\Delta \cdot (\Sigma + sx) = \Delta \cdot \Sigma + sx$ otherwise

Furthermore, to close a type under a sensitivity environment we use the relational distance type instantiation operator $\Delta(\sigma)$ (note that a τ is also an σ assuming that the "default" relational distance d is 0) defined below.

$$
\Delta(\mathbb{R}) = \mathbb{R}
$$

\n
$$
\Delta(\mathbb{B}) = \mathbb{B}
$$

\n
$$
\Delta(\text{unit}) = \text{unit}
$$

\n
$$
\Delta((x : \sigma_1) \xrightarrow{\Sigma' \downarrow d} \sigma_2) = (x : \Delta(\sigma_1)) \xrightarrow{\Delta \cdot \Sigma' \uparrow d} \Delta(\sigma_2)
$$

\n
$$
\Delta(\sigma_1 \xrightarrow{\Sigma_1 + d_1} \bigoplus_{\Sigma_2 + d_2} \sigma_2) = \Delta(\sigma_1) \xrightarrow{\Delta \cdot \Sigma_1 + d_1} \bigoplus_{\Delta \cdot \Sigma_2 + d_2} \Delta(\sigma_2)
$$

\n
$$
\Delta(\sigma_1 \xrightarrow{\Sigma_1 + d_1} \bigotimes_{\Sigma_2 + d_2} \sigma_2) = \Delta(\sigma_1) \xrightarrow{\Delta \cdot \Sigma_1 + d_1} \bigotimes_{\Delta \cdot \Sigma_2 + d_2} \Delta(\sigma_2)
$$

\n
$$
\Delta(\sigma_1 \xrightarrow{\Sigma_1 + d_1} \bigotimes_{\Sigma_2 + d_2} \sigma_2) = \Delta(\sigma_1) \xrightarrow{\Delta \cdot \Sigma_1 + d_1} \bigotimes_{\Delta \cdot \Sigma_2 + d_2} \Delta(\sigma_2)
$$

Now that we have all the prerequisite, we briefly go through the definition of the logical relations $(in Figure 8)⁴$ $(in Figure 8)⁴$ $(in Figure 8)⁴$ $(in Figure 8)⁴$ $(in Figure 8)⁴$:

- Two real numbers are related at type $\mathbb R$ and distance d , if and only if the absolute difference between both numbers is at most d. For instance, $(1,3) \in \mathcal{V}_2[\mathbb{R}]$ and $(3,1) \in \mathcal{V}_2[\mathbb{R}]$, as the logical relations are reflexive.
- Unit value tt is always related to itself at type unit under any distance.
- Two inl (resp. inr) values are related at σ_1 $\frac{d_1 \oplus d_2}{d_1 \oplus d_2}$ σ_2 and distance d if the underlying values are related at type σ_1 (resp. σ_2) and distance $d + d_1$ (resp. $d + d_2$). The intuition is that d can be treated as the distance between two computations that reduce to the given sums, and d_1 can be treated as the distance between the underlying values; thus the total cost is the addition of both distances. For instance, for any d and σ , we have (inl 1, inl 3) $\in \mathcal{V}_0[\mathbb{R}^2 \oplus \sigma]$ because they are at immediate distance zero (both are ∞) and latent distance 2; instead of delaying the distance, one also has (inl 1, inl 3) $\in V_2[\mathbb{R} \ 0 \oplus^d \sigma]$, i.e. both values are at distance 2 with zero latent distance between their content.
- Any inl value is considered to be at infinite distance from any inr value, although they may have the same type. For instance, (inl 1, inr tt) $\in V_{\infty}[\mathbb{R}^{d_1} \oplus^{d_2} \text{unit}],$ for any d_1, d_2 .
- Similarly to sum values, two additive (resp. multiplicative) products are related at type σ_1 $^{d_1}\&^{d_2}$ σ_2 (resp. σ_1 $d_1 \otimes d_2$ σ_2) and distance d, if both first components are related at type σ_1 and distance $d + d_1$, and both second components are related at type σ_2 and distance $d + d_2$. For instance, $((\text{inl } 1, 4), (\text{inl } 3, 5)) \in \mathcal{V}_0(\mathbb{R}^2 \oplus^d \sigma) \otimes \mathcal{R}^1 \mathbb{R}^d$ are at distance 0 and $(\text{inl } 1, \text{inl } 3) \in \mathcal{V}_0(\mathbb{R}^2 \oplus^d \sigma)$ and $(4, 5) \in \mathcal{V}_1[\mathbb{R}]$.
- Two sensitivity closures are related if, given related inputs, they produce related computations. In more detail, first the environments has to be related at some Γ and distance environment Δ . Note that Δ has to be the same environment that closes the latent effect of the function $\Delta \cdot \Sigma + s'x$, and the one that closes the input type $(\sigma_1 = \Delta(\tau_1))$. Second, inputs v'_1 and v'_2 have to be related at argument type σ_1 and any distance d' . Finally, the body of the functions in environments extended with inputs v'_1 and v'_2 have to be related computations at type $d'x(\sigma_2)$ and distance $d + \Delta \cdot \Sigma + s d'$. Note that, as the variable x is out of scope after the application, we replace any instance of x with the distance of the inputs d' , using the distance type instantiation operator. The new distance at which both computations are now related is computed as the addition of the distance of the values d, and the closed latent effect $d'x(\Delta \cdot \Sigma + sx) = \Delta \cdot \Sigma + sd'$. For instance,

 $(\langle \lambda^* x : \mathbb{R}. x + y \rangle, y \mapsto 1 \rangle, \langle \lambda^* x : \mathbb{R}. x + y \rangle, y \mapsto 3 \rangle \in \mathcal{V}_0[[x : \mathbb{R}] \xrightarrow{2+1x} \mathbb{R}],$ as in this case $\Delta = 2y$, $\Sigma = 1y$, and $\Delta \cdot \Sigma = 2y \cdot 1y = 2$.

- Two sensitivity configurations are related computations at type σ and distance d , noted (γ_1 ⊢ $e_1, \gamma_2 \vdash e_2) \in \mathcal{E}_d[\sigma]$, when if both configurations reduce to two values, then these values are related at type σ and distance d.
- Finally, value environment γ_1 is related to value environment γ_2 at type environment Γ and distance environment Δ , written $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta}[\Gamma]$, if they both map each variable x in the type environment to values related at their corresponding type (closed with Δ) and at distance $\Delta(x)$.

Sensitivity Metric Preservation. Armed with these logical relations, we can establish the notion of type soundness, and prove the fundamental property—well-typed terms are related with themselves—which corresponds to metric preservation [\[33](#page-50-0)]. As usual, we state this property appealing to open terms, where free variables indicate input parameters, which are then closed by related value environments.

⁴ for simplicity we use "distance" instead of "relational distance"

Contextual Linear Types for Differential Privacy 27

THEOREM 5.2 (SENSITIVITY METRIC PRESERVATION). If $\Gamma \vdash e : \tau : \Sigma$, then for any distance environment Δ with $dom(\Gamma) \subseteq dom(\Delta)$ and any pair of value environments $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta}[\Gamma]$, it holds that $(y_1 \vdash e, y_2 \vdash e) \in \mathcal{E}_{\Delta \cdot \Sigma} [\Delta(\tau)]$.

In other words, if a sensitivity term is well-typed, then for any valid distance environment Δ (that "fits" Γ) and any two value environments γ_1, γ_2 related at Γ and Δ, configurations $\gamma_1 \vdash e, \gamma_2 \vdash e$ represent related computations at type $\Delta(τ)$ (closing all free variables) and distance $\Delta \cdot \Sigma$. Note that since $dom(\Sigma) \subseteq dom(\Gamma) \leq dom(\Delta)$, we have $\Delta \cdot \Sigma \in \mathbb{R}^{\infty}_{\geq 0}$.

From the above theorem it is easy to derive a corollary that only characterizes closed terms:

CORROLARY 5.2.1 (FP FOR CLOSED SENSITIVITY TERMS). If $\emptyset \vdash e : \tau : \emptyset$, then $(\emptyset \vdash e, \emptyset \vdash e) \in$ $\mathcal{E}_{_0}\llbracket\tau\rrbracket.$

As a direct consequence of Theorem [5.2](#page-26-1) we can also establish the sensitivity type soundness at base types:

Theorem 5.3 (Sensitivity Type Soundness at Base Types). If $\varnothing \vdash e : (x : \mathbb{R}) \xrightarrow{s_X} \mathbb{R}$; \varnothing , $|r_1 - r_2| \leq d$, $\varnothing \vdash e \ r_1 \Downarrow r_1'$, $\varnothing \vdash e \ r_2 \Downarrow r_2'$, then $|r_1' - r_2'| \leq sd$.

6 DESIGN OF JAZZ'S PRIVACY TYPE SYSTEM

In this section, we review the limitations of prior approaches related to the tracking of privacy, and then discuss how they are addressed by Jazz. In this section, we color expressions and metavariables *red* as they pertain to the privacy fragment of Jazz.

6.1 Privacy Closures

Consider a family of looping combinators parameterized by the number of loop iterations n , which in Fuzz might have type $\text{loop}_n : \tau \to (\tau \to \bigcirc \tau) \to_n \bigcirc \tau$. In this type, regular arrows \to mean no sensitivity is tracked for the argument. The linear arrow \sim_n means the result is *n*-sensitive (where n is the number of loop iterations) in the *closure variables* of the supplied function of type $(\tau \to \circ \tau)$. This allows for instantiating loop with a closure capturing a sensitive variable, like db. So loop_n 0 (λx . x + laplace_{ϵ} db) will give $n\epsilon$ differential privacy for db by scaling ϵ —the privacy cost of closure variable db —by the loop iteration n . This type of scaling is disallowed in advanced variants of differential privacy like (ϵ , δ), and this argument only holds up for pure ϵ -differential privacy.

In Duer, in order to support (ϵ , δ)-differential privacy (and disallow problematic scaling), privacy closures immediately report unbounded privacy (∞) for any captured variables in privacy lambdas. The principle of loop's type above is justified in DUET, but not via a scaling argument, and instead via a primitive type *rule*—it cannot be expressed as a *type*. This is problematic for two reasons: first, it is not possible to extend DUET's implementation with new looping primitives by adding terms with axiomatically justified types, leading to a bloated set of core typing rules, and second, it is not possible to lambda abstract looping combinators, e.g., to chain or compose them in helper functions.

To see the root cause for the limitation in DUET, we show the type rules for looping (advanced composition) and function introduction (from [\[32](#page-50-3)]):

DUET: LOOP (ADVANCED COMPOSITION)

$$
\frac{\Gamma_1 \vdash e_1 : \tau \qquad \boxed{|\Gamma_2|^{\epsilon,\delta}}, x :_{\infty} \tau \vdash e_2 : \tau \qquad \qquad \text{Duet: Privacy-Fun-I } (1-ARY)}{\left|\Gamma_1\right|^{\infty} + \boxed{|\Gamma_2\right|^{\epsilon} \sqrt{2n \ln \frac{1}{\delta'}, \delta' + n\delta}}} + \frac{\mathcal{D}uer: Privacy-Fun-I }{\left|\Gamma\right|, x :_{\epsilon,\delta} \tau_1 \vdash e : \tau_2}
$$

In the rule for advanced composition shown above, e_1 is the initial value for the looping state of type τ , and e_2 is the loop body which updates the looping state $\tau \to \tau$ and may mention closure variables in Γ₂. Parameter δ' is a meta-parameter for the advanced composition formula–this parameter is unique to looping in (ϵ, δ) -differential privacy. The notation $\Gamma_2[\epsilon, \delta]$ means there must exist some privacy cost ϵ and δ which upper-bounds any individual cost for each of these closure variables. The privacy cost of the whole loop is calculated based on this upper bound for closure variables with the formula $2\epsilon\sqrt{2n\ln(1/\delta')}$, $\delta' + n\delta$. An attempt to turn loop into a primitive (or abstract over loop, e.g., eta-expand via lambda abstraction) fails because privacy types in Duer do not track privacy effects for closure variables; instead, they are just thrown away. In the rule for function introduction, also shown above, notice the closure environment Γ above the line which is bumped to ∞ in $\lceil \Gamma \rceil^{\infty}$ below the line. This has the effect of tossing out privacy bounds for anything with non-zero privacy in Γ. Privacy is only tracked for the function parameter x (or possibly multiple parameters; privacy functions in DUET are n-ary).

A deeper limitation in Duer is that the iterated 1-ary function space does not generalize to support encoding n-ary functions (i.e., currification is not supported). For this reason, n-ary functions are primitive in Duer. Implementing n-ary from 1-ary functions is computationally possible in Duer, but results in discarding bounds on privacy effects. For example, the Duer term $\lambda^p(x:\tau_1)$. return $(\lambda^p(y:\tau_2), f(x,y))$ in a context where $f : (\tau_1 \omega(\epsilon_1, \delta_1), \tau_2 \omega(\epsilon_2, \delta_2)) \rightarrow^* \tau_3$ has type $(\tau_1 \textcircled{a} \infty) \rightarrow^* (\tau_2 \textcircled{a}(\epsilon_2, \delta_2)) \rightarrow^* \tau_3$, i.e., the privacy bounds (ϵ_1, δ_1) for the first argument τ_1 get discarded due to the DUET: PRIVACY-FUN-I rule.

Privacy Closures in Jazz. In Jazz, both privacy and sensitivity effects are delayed and attached to type-level connectives, including for privacy functions. Whereas in Duer privacy functions are written $(\tau_1 \otimes p_1, \ldots, \tau_n \otimes p_n) \to \tau$, privacy functions in Jazz are written simply $(x : \tau_1) \to \tau_2$ where Σ is a latent contextual effect that can mention x. A type can now be given to loop (a named constant, analogous to the loop *primitive* from DUET) in JAZZ, and abstracting over loop is possible due to the function introduction rule, also shown below.

$$
\text{loop}^{\delta'}_{n} : \tau \to (\tau \xrightarrow{\text{I\Sigma}^{\lceil \epsilon, \delta\rceil}} \tau) \xrightarrow{\text{I\Sigma}^{\lceil \epsilon', \delta''\rceil}} \tau \xrightarrow{\text{I\rho z: P\n R\text{IVACY-FUN-I}} \tau, x : \tau_1 \vdash e : \tau_2 : \text{Z}\text{W\n here } \epsilon', \delta'' \triangleq 2\epsilon\sqrt{2n\ln(1/\delta')}, \delta' + n\delta \xrightarrow{\text{I\rho z: P\n R\text{IVACY-FUN-I}} \tau \vdash \lambda^{\text{P}}(x : \tau_1 \cdot d) \cdot e : (x : \tau_1 \cdot d) \xrightarrow{\text{Z}} \tau_2 : \text{Z}
$$

N-ary functions are now recoverable from 1-ary ones using latent contextual effects in closures. The relational distance d defaults to 1 when omitted. The encoding of lambda-abstracted gauss then follows the usual approach of nested lambda abstractions, but with sensitivity lambdas on the outside with a single privacy lambda on the inside. A 3-ary abstraction of the Gaussian mechanism applied to the sum of three arguments is as follows: $\bar{(\lambda^{\mathrm{s}}% ,\lambda^{\mathrm{s}}_{\mathrm{c}})}$

$$
(x : \mathbb{R} \cdot 1). \lambda^s(y : \mathbb{R} \cdot 1). \lambda^p(z : \mathbb{R} \cdot 1).
$$

desired privacy
gauss $\frac{3}{4} \epsilon \delta (x + y + z) : (x : \mathbb{R} \cdot 1) \rightarrow (y : \mathbb{R} \cdot 1) \rightarrow (z : \mathbb{R} \cdot 1) \xrightarrow{(\epsilon, \delta)x \sqcup (\epsilon, \delta)y \sqcup (\epsilon, \delta)z}$
sensitivity sum of $(x + y + z)$

Notice here that the latent contextual effect is computed using a syntactic *join* operator (ϵ, δ) *x* ⊔ $(\epsilon, \delta)y \sqcup (\epsilon, \delta)z$, which computes the pointwise maximum, instead of the sum $((\epsilon, \delta)x+(\epsilon, \delta)y+(\epsilon, \delta)z)$. One of the novelties of Jazz is that we can reason about two executions where more than one input is at relational distance greater than 0. In particular, if x , y and z are at relational distance 1, i.e. the argument of gauss $3 \epsilon \delta$ is at relational distance 3, then using addition would yield an overapproximated latent privacy of (3 ϵ , 3 δ), while using the join, we obtain a latent privacy of (ϵ , δ) as desired.

Contextual Linear Types for Differential Privacy 29

Abstracting Privacy Mechanisms. Even with support for privacy closures, there are still challenges in supporting lambda abstraction around privacy mechanisms in full generality. In Fuzz, the type assigned to the family of Laplace differential privacy mechanisms parameterized by ϵ is laplace $_\epsilon:\mathbb{R}\to_\epsilon\circ\mathbb{R}$ for achieved privacy $\epsilon.$ This mechanism does not need a dedicated type rule in the core calculus—it can be axiomatized as a primitive with the right type—and lambdaabstracting this primitive is natural via eta-expansion $\lambda(x : \mathbb{R})$. Laplace_{ϵ} x resulting in the same type and guarantee for privacy. However this approach does not support (ϵ, δ) -differential privacy. In Duer, in order to support (ϵ, δ) -differential privacy, the Gaussian mechanism requires its own typing rule, shown below. Furthermore, a use of the mechanism looks like gaus $s_{\epsilon,\delta}^s$ e where the argument e is a term in the sensitivity language with sensitivity bounded by s . Using privacy closures as described above, we can write $\lambda^p(x : \mathbb{R})$. gauss $1 \in \delta x$, however note that we have lost the ability to be parametric in s —it must be fixed to 1. This assumption that gauss will be called only with a 1-sensitive argument is enforced in the function application rule in Duer, also shown below.

Duer: Gauss
\n
$$
\frac{|\Gamma|^s}{|\Gamma|^s} \vdash e : \mathbb{R}
$$
\nDuer: Privacv-Fun-E
\n
$$
\frac{|\Gamma|^s}{|\Gamma|^s} \vdash e : \mathbb{R}
$$
\n
$$
\frac{\Gamma_1 \vdash e_1 : \tau_1 \omega(\epsilon, \delta) \rightarrow^* \tau_2}{|\Gamma_1|^{\infty} + |\Gamma_2|^{\epsilon, \delta} + e_1 e_2 : \tau_2}
$$

In the rule for gauss (left) it allows an argument of any sensitivity s , however the privacy function application rule (right) restricts that arguments must have sensitivity equal to 1. Restricting gauss to only 1-distance arguments can be overly restrictive (e.g., gauss 2 $\epsilon \delta$ (x + x)), and relaxing the restriction on function application to an arbitrary $s \neq 1$ in Duer would be unsound.

In Jazz, we extend function introduction to include an explicit bound on the sensitivity of the parameter, and enforce this restriction in the application rule. Function introduction syntax introduces the bound, and allows us to eta-expand the Gaussian mechanism with relational distance d as a parameter, as shown below. The bound \bar{d} for the lambda argument is then enforced in function application as the upper bound of argument relational distance, instead of being fixed to 1 as in DUET. Now the use of a variable—like x in the body of eta-expanded gauss below—is not always considered 1-sensitive. To communicate non-zero sensitivities to variables in the type system, an environment of relational distances on lambda arguments must be threaded through the type system, which we notate Δ . After extending this Δ to remember that x has relational distance d in Jazz lambda abstraction, gauss $s \in \delta x$ will see x as d distant inside the lambda body. To do this, we allow lambda-abstracting gauss (including the distance parameter d , via singleton types), and extend the structure of typing for sensitivity and privacy terms respectively as follows:

6.2 Sensitivity Binding in Privacy Contexts

Jazz improves on prior systems by supporting let-binding intermediate sensitivity computations within the privacy language, while also supporting (ϵ, δ) -differential privacy. Fuzz and DFuzz have one rule for let-binding which scales the sensitivity of the right-hand-side of the let with the sensitivity of the let-variable in the body. So let $y = 2 * x$ in 3 * y is 6-sensitive in x because the right-hand-side is 2-sensitive, and this is scaled by 3, the sensitivity of y in the body. The analog of let for privacy in Fuzz is monadic bind. The Fuzz program $y \leftarrow 1$ aplace_{ϵ_1} $x : z \leftarrow$ laplace_{ϵ_2} x; return (*f* y z) results in $\epsilon_1 + \epsilon_2$ differential privacy for x by adding up the privacy effects from each monadic statement. Unlike let, instead of depending on the sensitivity of bound variables y and z in the body of a bind, they may instead be used without restriction because they are now differentially private, so f may do anything with y and z without any consequence. Note that in Fuzz, the encoding of let using return and monadic bind does not preserve typeability, instead it destroys the sensitivity/privacy analysis of the right-hand-side, bumping its privacy cost unnecessarily to ∞.

In Fuzz, let-binding a sensitivity computation (the pure fragment) inside a privacy computation (the monadic fragment) is supported seamlessly without the addition of extra rules. In Duer, however, the privacy/monadic fragment of Fuzz is pulled out into its own language with explicit typing rules; the primary reason to do this is to place restrictions on function application, as described in the previous subsection. This leaves the need for either an explicit typing rule for let-binding inside the privacy language, or an escape hatch so that privacy analysis is not destroyed for letbinding in privacy contexts a la Fuzz. Duer solves this issue by introducing a boxed type which delays the payment of a sensitivity term at the point it is "boxed", and pays for it later when it is "unboxed". This avoids the issue but is unfriendly to program with: every let-binding requires an explicit box, and every use of a let-bound variable requires an explicit unbox. So instead of writing the program below on the left, DUET programmers are forced to write the program on the right.

```
let y = expensive x in
loop 100 initial (\lambda^p(i:\tau). body y i)
                                                  let y = \vert \text{box} \vert (expensive x) in
                                                  loop 100 initial (\lambda^p(i:\tau)) body (unbox y) i)
```
In this program it is essential to let-bind the expensive result, since inlining it would unnecessarily duplicate the computation, and many real programs in differential privacy require support for this pattern [\[32\]](#page-50-3).

In Jazz, we eliminate the need for box types and explicit boxing/unboxing entirely. To do this, we add new information to typing judgments that has the effect of automatically boxing let-bound variables in privacy contexts, and unboxing them at their use. The added information extends typing judgments with a new component Φ that tracks the sensitivities of all let-bound variables w.r.t. the sensitivities of all lambda-bound variables. All sensitivity contexts that mention both let-bound and lambda-bound variables are then reduced using Φ as needed to contexts that only mention lambda-bound variables. Φ can be seen as a matrix, and the reduction of contexts to only lambda-bound variables is then just matrix multiplication—a beautiful coincidence for a linear type system. The final form of type judgments for the sensitivity and privacy type systems are then:

 $\Gamma : \Delta : \Phi \vdash e : \tau : \Sigma$ $\Gamma : \Delta : \Phi \vdash e : \tau : \Sigma$

Although the prototype implementation adopts the typing rules with Φ , and because the manipulation of Φ is routine, we omit it in the following technical presentation.

7 JAZZ'S DIFFERENTIAL PRIVACY TYPE SYSTEM, FORMALLY

In this section, we present a core subset of Jazz, dubbed λ_J . λ_J is an extension of Sax with support for reasoning about differential privacy. Similarly to Sax, we prove the type safety and type soundness property of $\lambda_{\rm J}$. We discuss how to bridge the gap between $\lambda_{\rm J}$ and J<code>Azz</code> in Section [8.](#page-42-0) Note that our formalism is fixed to (ϵ, δ) -differential privacy, but our design can be instantiated to other forms of advanced differential privacy disciplines as illustrated in Section [8.](#page-42-0)

7.1 Syntax and Type System

 $\lambda_{\rm J}$ is divided in two mutually embedded sublanguages: the sensitivity sublanguage —an extension of SAX— used to reason about the sensitivity of computations, and the *privacy* sublanguage used to reason about differential privacy. Thus, the type system of λ_I contains two mutually embedded type systems, one for each of the sublanguages. Expressions of the sensitivity sublanguage remain typeset in green and expressions of the privacy sublanguage are typeset in red.

```
e \in \text{sexpr} \ ::= ... \mid \lambda^s(x : \tau \cdot d). e \mid \lambda^pe \in pexpr ::= return e | x : \tau \leftarrow e; e | e e| if e then e else e | case e of \{x \Rightarrow e\} \{y \Rightarrow e\} conditionals, case | let x = e in e
                     | let x = e in e
p \in \text{priv} \quad \triangleq \quad (\mathbb{R}^{\infty}, \mathbb{R})\Sigma \in \text{pen} \geq \emptyset \mid px \mid \Sigma + \Sigma \mid \Sigma \sqcup \Sigma \mid \Sigma \sqcap \Sigma privacy environments
 \tau \in \text{type} \ \ \mathrel{\mathop:}= \ \ldots \ \mid (\mathbf{x} : \tau \cdot \mathbf{d}) \xrightarrow{\Sigma} \ \tau \mid (\mathbf{x} : \tau \cdot \mathbf{d}) \xrightarrow{\Sigma} \ \tau\Gamma \in \text{tenv} \quad \triangleq \text{ var} \rightarrow \text{type} \coloneqq \{x : \tau, \ldots, x : \tau\} type environments
```

```
sensitivity expressions<br>return, bind, applications
privacies
```
Fig. 9. λ_J: Syntax

Syntax. Figure [9](#page-30-0) presents the syntax of λ _J. Expressions of the language are divided into two mutually embedded expressions: sensitivity expressions e and privacy expressions e . Sensitivity expressions are defined the same way as in Sax, except that functions are split into sensitivity lambdas $\lambda^s(x : \tau \cdot d)$. e and privacy lambdas $\lambda^p(x : \tau \cdot d)$. e. Note that the only difference between a sensitivity lambda and a privacy lambda is that the body of a privacy lambda is a privacy expression e. Also, both sensitivity lambdas and privacy lambdas are parametrized by a relational distance d which represents an upper bound on distance between inputs pertained to the binary relational property of differential privacy: the maximum argument variation for each of two executions.

A privacy expression e can be a point distribution return e, a sequential composition $x : \tau \leftarrow$ e ; e, an application e e, a conditional if e then e else e, a case expression case e of $\{x \Rightarrow$ e} $\{y \Rightarrow e\}$, or a let let $x = e$ in e.

A privacy cost $p = (\epsilon, \delta)$ is a pair of two (possibly-infinite) real numbers, where the first component corresponds to the epsilon, and the second to the delta in (ϵ, δ) -differential privacy. We use notation *p*.*ε* and *p*. δ to extract ϵ and δ respectively. A privacy environment Σ is either an empty environment \emptyset , a pair px representing that variable x has privacy cost p, the addition $\Sigma + \Sigma$ of two privacy environment, the join $\Sigma \sqcup \Sigma$ of two privacy environment, and the meet $\Sigma \sqcap \Sigma$ of two privacy environment. Similarly to sensitivity environments, we also write privacy environments as first-order polynomials when possible. For instance $p_1x + p_2x$ can be written as $(p_1 + p_2)x$, but $p_1x + (p_2x \sqcup p_3y)$ cannot be rewritten as a polynomial without loosing precision. Function types are now divided into sensitivity function types $(x : \tau \cdot d) \xrightarrow{\Sigma} \tau$, and privacy function types $(x : \tau \cdot d) \xrightarrow{\Sigma} \tau$.

Sensitivity type system. The type system for the sensitivity sublanguage is presented in Figure [10.](#page-31-0) The judgment Γ ; $\Delta \vdash e : \tau$; Σ now includes a relational distance environment Δ . The relational distance environment Δ stores how much each variable in Γ can vary in every two executions of a program. Most of the rules are straightforward extensions of the type system of Sax to include relational distance environments. We only present interesting cases.

Some of the rules use the sensitivity environment substitution operator $[\Sigma/x]$. We extend the definition of Sax to support privacy functions as shown in Figure [11.](#page-32-0) Substitution on privacy function types depends on the definition of sensitivity environment substitution on privacy environments $[\Sigma/x]\Sigma$. $[\Sigma/x]\Sigma$ is defined inductively on the structure of Σ, where the only interesting case is when $\Sigma = px$. Substitution $[\Sigma/x]px$ is defined using the lift operator: $[\Sigma]^p$. Intuitively, if

Fig. 10. λ_j : Type system of the sensitivity sublanguage (extract)

we wiggle $5 \times$ $5 \times$ on px , then the privacy obtained is at most p (no scaling, and zero if x does not change). After substitution, as x depends on all variables on Σ , if we wiggle all variable in Σ at the same time, then the privacy obtained should still be p (scaling p would be an over approximation). Because of this, $\sum_{i} p_i$ is defined as the join $px_1 \sqcup ... \sqcup px_n$, where $x_i \in dom(\Sigma)$. If all x_i wiggle, then the privacy obtained would be at most p . But as any $\Sigma(x_i)$ can be zero (it means that variable x_i is not used), we multiply each p in px_i , by $\sum(x_i)$ ^{\sum}, to remove those variables from the resulting privacy environment. $]s[^{s'}$ along other lift operators used by Near et al. [\[32](#page-50-3)] are defined in Figure [11.](#page-32-0) For instance, suppose that x depends on $2y + 0z$, then $[(2y + 0z)/x]px$ is computed as $\bigl] 2y + 0z \bigr[P = py \sqcup 0z = py.$

We now turn to describe the main changes of each type rule with respect to Sax.

- Rule var now requires variable x to be present in the relational distance environment Δ . This way, if Γ ; $\Delta \vdash e : \tau$; Σ , we can compute how much the result of evaluating e can change if we wiggle input x, by multiplying $\Delta(x)$ by $\Sigma(x)$. For instance, consider program $x + x$ and the

⁵We show how to wiggle variables on privacy environment with the relational distance instantiation operator, later on Section [7.3.](#page-38-0)

Fig. 11. λ _J: Auxiliary definitions of the static semantics

following type derivations

$$
\mathcal{D} = \frac{(x : \mathbb{R})(x) = \mathbb{R}}{x : \mathbb{R}; 3x + x : \mathbb{R} ; x} \qquad \qquad \frac{\text{PLUS}}{x : \mathbb{R}; 3x + x + x : \mathbb{R} ; 2x}
$$

Then we know that (1) x can change at most by 3, and (2) the expression is 2-sensitive in x , therefore the result can change at most by 6.

- Rule s-LAM type checks sensitivity functions. As the body of the lambda has x as a free variable, the relational distance environment Δ is extended with distance d obtained from the type annotation on the argument. For example, consider program $\lambda^s(x : \mathbb{R} \cdot 1)$. $x + x$ and its type derivation:

S-LAM

$$
x : \mathbb{R}; 2x \vdash x + x : \mathbb{R}; 2x
$$

 $\varnothing; \varnothing \vdash \lambda^s(x : \mathbb{R} \cdot 1), x + x : (x : \mathbb{R}) \xrightarrow{2x} \mathbb{R}; \varnothing$

The program is a sensitivity lambda that takes as argument a real with an allowed variation of at most 1, and has a latent contextual effect of $2x$.

- Rule p-lam is defined analogously to s-lam, except that its body is a privacy term, therefore it is type checked using the privacy type system, explained later.
- Rule s-app deals with sensitivity applications. Note that from the type of the function we know that d is an upper bound on the allowed argument variation, therefore we require that the dot product between the relational distance environment and the sensitivity effect of the argument be less or equal than d. Intuitively, as Δ represents how much the input can change, and Σ_2 represent the sensitivity of variables used in the argument, $\Delta \cdot \Sigma_2$ represents how much the argument can change. For example, consider subprogram program $\lambda^s(y : \mathbb{R} \cdot 1)$. $(\lambda^s(x : \mathbb{R} \cdot 2)$. $x + x)(y + y)$ and its type derivation:

The outermost lambda allows a maximum variation of 1 in its argument ψ . The inner lambda allows a maximum variation of 2 on its argument, and its being applied to $2 * y$. As $2 * y$ is 2sensitive on y and x can wiggle at most by 1, then we know that the argument is going to wiggle at most by 2, which matches the maximum permitted argument variation. If the argument were $3 * y$, then the program would not type check as the argument of the application could wiggle at most by $1 * 3 = 3$.

- Rule s-case type checks subterms e_2 and e_3 by extending the relational distance environment with a sound bound for x and y respectively. For x (resp. y) we use the dot product between the relational distance on all variables in scope Δ , and the cost of using e_1 : the cost Σ_1 of reducing the expression, plus the latent cost of using its subterm Σ_{11} (resp. Σ_{12}). For example, consider the type derivation of Example [4.4](#page-12-0) given e.g. relational distance environment $x + 2b$:

CASE

$$
\Gamma; x + 2b + e : \mathbb{R}^{\infty} x \oplus^x \mathbb{R}; b
$$

$$
\Gamma, x_1 : \mathbb{R}; x + 2b + \boxed{\infty} x_1 + 0 : \mathbb{R}; \emptyset \qquad \Gamma, x_2 : \mathbb{R}; x + 2b + \boxed{3x_2} + x_2 : \mathbb{R}; x_2
$$

$$
\Gamma; x + 2b + \text{case } e \text{ of } \{x_1 \Rightarrow 0\} \{x_2 \Rightarrow x_2\} : \mathbb{R}; b + x
$$

The relational distance for x_1 on the first branch is computed as the dot product between the maximum distance of all variables in scope, $x + 2b$, and the cost of using e if it were an inl expression, i.e. $((x + 2b) \cdot (\infty x + b)) = \infty$. Analogously, the bound for x_2 on the second branch is computed as $((x+2b)\cdot(x+b)) = 3$.

- In Rule untup, as expression e_2 has in scope new variables x_1 and x_2 , the relational distance environment Δ is extended accordingly. The relational distance for x_1 is computed as the dot product between the relational distance environment Δ and the cost $\Sigma_1 + \Sigma_{11}$ of accessing the first component (we proceed similarly with x_2). For instance, consider the type derivation of

s-lam

$$
\frac{\tau \leq \tau}{\tau \leq \tau_1} \frac{d' < d \quad \Sigma < \tau_2' \quad \tau_2 < \tau_2'}{\left(\chi : \tau_1 \cdot d\right) \xrightarrow{\Sigma} \tau_2} < \frac{\tau_1' < \tau_1 \quad d' < d \quad \Sigma < \tau_2' \quad \tau_2 < \tau_2'}{\left(\chi : \tau_1 \cdot d\right) \xrightarrow{\Sigma} \tau_2} < \frac{\tau_1' < \tau_1 \quad d' < \tau_1 \quad d' < \tau_2' \quad \tau_2' \quad
$$

Fig. 12. λ_J: Subtyping

Example [4.2](#page-11-0) given some arbitrary relational distance environment $2x + 3y$

untup Γ ; 2x + 3y + $(2 * x, y) : \mathbb{R}^{2x} \otimes y \mathbb{R}$; \varnothing $\Gamma, x_1 : \mathbb{R}, x_2 : \mathbb{R}; 2x + 3y + 4x_1 + 3x_2 + x_1 + 2*x_2 : \mathbb{R}; x_1 + 2x_2$ $Γ; 2x + 3y ⊢ let x_1, x_2 = (2 * x, y) in x_1 + 2 * x_2 : ℝ; 2x + 2y$

The relational distance for x_1 is computed as the dot product between the relational distance of all variables in scope $2x + 3y$ and the effect of using the left component of the pair $2x + 0y$, i.e. $(2x + 3y) \cdot (2x + 0y) = 4$. Similarly, the bound of x_2 is computed as $(2x + 3y) \cdot (y + 0x) = 3$

Subtyping is extended accordingly and presented in Figure [12.](#page-34-0) Parameterized relational distances on function types are contra variant, and subtyping for privacy function types relies on the definition of subtyping for privacy environment also defined in Figure [12,](#page-34-0) where • is an operator to close privacy environments defined below:

$$
\Delta \cdot \Sigma = |\Delta|^{1} \cdot \Sigma
$$

\n
$$
|\Delta|^{1} \cdot \varnothing = 0
$$

\n
$$
|\Delta|^{1} \cdot (\Sigma_{1} + \Sigma_{2}) = (|\Delta|^{1} \cdot \Sigma_{1}) + (|\Delta|^{1} \cdot \Sigma_{2})
$$

\n
$$
|\Delta|^{1} \cdot (\Sigma_{1} \cup \Sigma_{2}) = (|\Delta|^{1} \cdot \Sigma_{1}) \cup (|\Delta|^{1} \cdot \Sigma_{2})
$$

\n
$$
|\Delta|^{1} \cdot (\Sigma_{1} \cap \Sigma_{2}) = (|\Delta|^{1} \cdot \Sigma_{1}) \cap (|\Delta|^{1} \cdot \Sigma_{2})
$$

\n
$$
|\Delta|^{1} \cdot px = dp
$$

\nif $|\Delta|^{1}(x) = d$
\n
$$
|\Delta|^{1} \cdot px = px
$$

\nif $x \notin \Delta$

Privacy type system. The type system of the privacy part of the language is presented in Figure [13.](#page-35-0) The judgment Γ ; Δ ⊢ e : τ ; Σ says that privacy term e has type τ and ambient privacy effect Σ under type environment Γ , and relational distance environment Δ .

- Rule RETURN uses the type system of the sensitivity language to type check its subexpression e . Operationally, return constructs a point-distribution, and any sensitive variables in the subexpression e will have their privacy violated, i.e., privacy cost ∞ . Notice that ∞ correspond to the pair $(\epsilon, \delta) = (\infty, \infty)$. The resulting ambient privacy effect is computed by lifting to infinity the sensitivity of every variable with non-zero sensitivity in e , as well as variables with non-zero sensitivity or privacy in free variables of τ , the type of e . The operator that collects and lift to ∞

RETURN Γ ; Δ + e : τ ; Σ_1 \widehat{x} = FV(FP [∞] (τ))
$\Gamma : \Delta \vdash$ return $e : [\varnothing/\widehat{x}] \tau : \Im \Sigma_1 \Gamma^\infty + \text{FP}^\infty(\tau)$
BIND Γ ; Δ + e ₁ : τ_1 ; Σ_1 Γ , x : τ_1 ; Δ + 0x + e ₂ : τ_2 ; Σ_2
$\Gamma: \Delta \vdash x : \tau_1 \leftarrow e_1 : e_2 : [\emptyset/x] \tau_2 : \Sigma_1 + [\emptyset/x] \Sigma_2$
TF Γ ; Δ + e_1 : \mathbb{B} ; Σ_1 Γ ; Δ + e_2 : τ ; Σ_2 Γ ; Δ + e_3 : τ ; Σ_3 $\Gamma : \Delta \vdash \text{if } e_1 \text{ then } e_2 \text{ else } e_3 : \tau : \exists \Sigma_1 \Gamma^\infty + (\Sigma_2 \sqcup \Sigma_3)$
P-CASE
Γ ; Δ + e_1 : τ_{11} Σ_{11} \oplus Σ_{12} τ_{12} ; Σ_1
$\Gamma, x : \tau_{11} : \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2 : \Sigma_2$ $\Gamma, y : \tau_{12} : \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{12}))y + e_3 : \tau_3 : \Sigma_3$
$\Gamma : \Delta \vdash$ case e_1 of $\{x \Rightarrow e_2\}$ $\{u \Rightarrow e_3\}$: $[\Sigma_{11}/x]\tau_2 \sqcup [\Sigma_{12}/y]\tau_3; [\Sigma_1\Gamma^\infty \sqcup ([\Sigma_{11}/x]\Sigma_2 \sqcup [\Sigma_{12}/y]\Sigma_3)]$
$P-APP$
Γ ; $\Delta \vdash e_1 : (x : \tau_1 \cdot d) \xrightarrow{\Delta} \tau_2$; $\Sigma_1 \qquad \Gamma$; $\Delta \vdash e_2 : \tau_1$; $\Sigma_2 \qquad \Delta \cdot \Sigma_2 \leq d$
Γ ; Δ + e ₁ e ₂ : $[\Sigma_2/x]\tau_2$; $[\Sigma_1\Gamma^\infty + [\Sigma_2/x]\Sigma]$
$FP^{\infty}(\mathbb{R}) = \emptyset$ FP^{∞} (unit) = \emptyset
$\text{FP}^{\infty}((x:\tau_1\cdot d)\xrightarrow{\Sigma}\tau_2)=[\emptyset/x]\big[\Sigma\big[\infty+\text{FP}^{\infty}(\tau_1)+\text{FP}^{\infty}([\emptyset/x]\tau_2)$
$FP^{\infty}((x:\tau_1 \cdot d) \xrightarrow{\Sigma} \tau_2) = [\emptyset/x] [\Sigma]^{\infty} + FP^{\infty}(\tau_1) + FP^{\infty}([\emptyset/x]\tau_2)$
$FP^{\infty}(\tau_1 \stackrel{\Sigma_1}{\rightarrow} \mathbb{P}^{\Sigma_2} \tau_2) = \left[\sum_1 \left[\infty + \left[\sum_2 \left[\infty + FP^{\infty}(\tau_1) + FP^{\infty}(\tau_2)\right]\right]\right]\right]$
$FP^{\infty}(\tau_1 \stackrel{\Sigma_1} {\alpha} \&^{\Sigma_2} \tau_2) = \frac{1}{2} \Gamma^{\infty} + \frac{1}{2} \Gamma^{\infty} + FP^{\infty}(\tau_1) + FP^{\infty}(\tau_2)$
$FP^{\infty}(\tau_1 \stackrel{\Sigma_1}{\otimes} \stackrel{\Sigma_2}{\tau_2}) = \frac{1}{2} \cdot \frac{1$

Fig. 13. λ _J: Type system of the privacy sublanguage

free variables from τ is written FP[∞] and defined in Figure [13.](#page-35-0) The free variables, sensitivities and privacies in τ represent the possible latent contextual effect of the subexpression. To lift variables we use the $\lfloor \rfloor$ - operator defined in Figure [11.](#page-32-0) As we pay infinity for every free variable in τ , we remove those variables from the reported type τ using the sensitivity environment substitution operator defined in Figure [11.](#page-32-0) For instance, consider the following type derivation,

> return $\Gamma; x+y+z \vdash e; (x : \mathbb{R}) \xrightarrow{2x+y} \mathbb{R}; \emptyset$ $\Gamma; x + y + z \vdash$ return $e : (x : \mathbb{R}) \xrightarrow{2x} \mathbb{R}; y : \infty y$

The resulting type and effect environment is computed by paying in advance for the free variables in scope: the type $\lceil \mathcal{O}/y \rceil(2x + y) = 2x$ is computed by erasing the free variables, and the effect environment ∞y is computed by lifting to infinite the free variables.
- Rule bind type checks both subexpressions using the type system for the privacy language as they are privacy expressions. To type check e_2 we extend type environment with variable x, therefore the relational distance environment Δ is also extended. We extend Δ with 0x as the value bound to x is no longer considered sensitive—it has been declassified and can be used without restriction. Finally, as x is out of scope we remove it from τ_2 and from the resulting ambient privacy effect. For instance, consider the type derivation of program $y : \mathbb{R} \leftarrow \text{laplace}_{\epsilon_1} x$; $z : \mathbb{R} \leftarrow \text{laplace}_{\epsilon_2} x; \text{return } y + z$, similar to the example presented in Section [6.2,](#page-28-0) given an arbitrary relational distance environment x .

Each laplace call has an effect environment of $(\epsilon_1, 0)x$ and $(\epsilon_2, 0)x$ respectively. The return subexpression lifts to infinite the privacy of variables y and z , but to typecheck the innermost bind expression the privacy on z is dropped: $(\epsilon_2, 0)x + (\infty, 0)y$. Then to typecheck the outermost bind expression, now the privacy on y is dropped getting a final effect environment of $({\epsilon}_1, 0)x + ({\epsilon}_2, 0)x = ({\epsilon}_1 + {\epsilon}_2, 0)x.$

- Rule p-case is similar to rule s-case. Here we lift the ambient sensitivity effect of the sum expression to infinity, i.e., we pay infinity for all non-zero-sensitive variables used in e_1 . For the additional cost of each branch, we compute the join between the cost of each branch by substituting each binder by their appropriated cost: $[\Sigma_{11}/x]\Sigma_2$ for the first branch, and $[\Sigma_{12}/y]\Sigma_3$ for the second. Note that we do not use $[\Sigma_1 + \Sigma_{11}/x]\Sigma_2$ and $[\Sigma_1 + \Sigma_{12}/x]\Sigma_3$ as we do in rule s-case, because we are already lifting to infinity (or paying for) every cost associated with Σ_1 . For example, consider the following type derivation

p-case Γ ; $x + 2y + x : \mathbb{R}^y \oplus \mathbb{R}^y$; $x = \Gamma, x_1 : \mathbb{R}^y : x + 2y + 3x_1 + e_2 : \mathbb{R}^y : x + py + p_2x_1$ $\Gamma, x_1 : \mathbb{R}$; $x + 2y + x_2 + e_3 : \mathbb{R}$; $p'_x x + p'_y y + p_3 x_2$ Γ ; $x + 2y$ + case x of $\{x_1 \Rightarrow e_2\}$ $\{x_2 \Rightarrow e_3\}$: \mathbb{R} ; $\lceil x \rceil^{\infty} \sqcup (p_x x + p_y y + \lceil y \rceil^{p_2}) \sqcup (p_x' x + p_y' y + \lceil \varnothing \lceil \frac{p_3}{p_3} \rceil)$

Note that the variation bound of x_1 is computed as $(x + 2y) \cdot (x + y) = 3$, and that of x_2 as $(x +$ $2y)(x) = 1$. As $\vert x \vert^{\infty} = \infty x$, $\vert y \vert^{p_2} = p_2 y$, and $\vert \varnothing \vert^{p_3} = \varnothing$, then the resulting effect environment is $\infty x \sqcup (p_x x + (p_y + p_2)y) \sqcup (p'_x x + p'_y y) = \infty x \sqcup ((p_y + p_2) \sqcup p'_y) y.$

- Rule p-app uses the sensitivity type system to typecheck both subterms. The first subterm has to be typed as a privacy function. Just as s-app, it checks that the sensitivity cost of the argument is bounded by d by computing the dot operation $\Delta \cdot \Sigma_2$ between relational distance environment Δ and sensitivity environment Σ_2 . The resulting ambient privacy effect is computed as the lift to infinite of the ambient sensitivity effect of e_1 , plus the latent contextual effect of the privacy function, where we substitute x by Σ_2 . Similarly to rule s-APP, rule P-APP also enforces that the relational distance of the argument is bounded by d, i.e. $\Delta \cdot \Sigma_2 \leq d$. For instance, consider the following type derivation:

Fig. 14. Non-deterministic sampling semantics for privacy expressions

p-app Γ ; $y \vdash \text{if } y \text{ then } e_2 \text{ else } e_3 : (x : \mathbb{R} \cdot 4) \xrightarrow{p_1 y \sqcup p_2 x} \mathbb{R}$; $y \qquad \Gamma$; $y \vdash 2 * y : \mathbb{R}$; $2y \qquad 2 \le 4$ $\Gamma: y \vdash (\text{if } y \text{ then } e_2 \text{ else } e_3))$ $(2 * y): \mathbb{R}: \exists 0 y \times y \mathbb{P}^{\infty} + (p_1 y \sqcup \exists 2y \mathbb{P}^2)$

The resulting effect environment is computed as $\infty y + [2y/x](p_1y \sqcup p_2x) = \infty y + p_1y \sqcup [2y \upharpoonright p_2$ $(p_1 \sqcup p_2)y$, which is equivalent to ∞y . If y does not wiggle, then the ambient privacy effect will be zero. If the relational distance environment for y were 3, then this program would be ill-typed since $3y.2y \nleq 4$.

7.2 λ_J: Type Safety

Type safety is defined in the same line of Section [5.2.](#page-21-0) To define type safety of the privacy language, we define a non-deterministic sampling big-step semantics of privacy expressions; see Figure [32.](#page-80-0) We naturally extend the type safety logical relations of Figure [8](#page-24-0) to support for both sensitivity and privacy lambdas, and privacy expressions as shown in Figure [33.](#page-81-0) The fundamental property of the type safety logical relation is defined similarly to Proposition [5.2,](#page-26-0) but now accounting for relational distance environments and expressions:

PROPOSITION 7.1 (FUNDAMENTAL PROPERTY OF THE TYPE SAFETY LOGICAL RELATION).

(a) Let $\Gamma; \Delta \vdash e : \tau; \Sigma$, and $\gamma \in \mathcal{G}[\Gamma]$. Then $\gamma \vdash e \in \mathcal{E}[\tau/\Gamma]$. (b) Let $\Gamma; \Delta \vdash e : \tau; \Sigma$, and $\gamma \in \mathcal{G}[\Gamma]$. Then $\gamma \vdash e \in \mathcal{E}[\tau/\Gamma]$.

Finally type safety for closed terms is just a corollary of the fundamental property above:

COROLLARY 7.1 (TYPE SAFETY AND NORMALIZATION OF λ_1).

(a) Let $\vdash e : \tau; \emptyset$, then $\vdash e \Downarrow v$, and $\vdash v : \tau'$; \emptyset , where $\tau' \leq \tau$. (b) Let \vdash e : τ ; \varnothing , then \vdash e \Downarrow v, and \vdash v : τ' ; \varnothing , where τ' <: τ .

$$
\frac{\langle \hat{\lambda}^s x : \tau \cdot s'.e, \gamma \rangle \in Atom[[x : \tau_1 \cdot s'] \xrightarrow{sx} \tau_2]] \qquad \forall v \in \mathcal{V}[[\tau_1]], \gamma[x \mapsto v] \vdash e \in \mathcal{E}[[\tau_2/(x : \tau_1)]]
$$

$$
\langle \hat{\lambda}^s x : \tau_1 \cdot s'.e, \gamma \rangle \in \mathcal{V}[[x : \tau_1 \cdot s'] \xrightarrow{sx} \tau_2]]
$$

$$
\frac{\langle \hat{\lambda}^p x : \tau \cdot s.e, \gamma \rangle \in Atom[[x : \tau_1 \cdot s] \xrightarrow{\Sigma} \tau_2]] \qquad \forall v \in \mathcal{V}[[\tau_1], \gamma[x \mapsto v] \vdash e \in \mathcal{E}[[\tau_2/(x : \tau_1)]]}{\langle \hat{\lambda}^p x : \tau_1 \cdot s.e, \gamma \rangle \in \mathcal{V}[[x : \tau_1 \cdot s] \xrightarrow{\Sigma} \tau_2]]}
$$

$$
\frac{\gamma \vdash e \Downarrow v \qquad v \in \mathcal{V}[[\tau]]}{\gamma \vdash e \in \mathcal{E}[[\tau]]}
$$

Fig. 15. λ _J: Type Safety Logical Relation

7.3 Soundness of λ _J: Metric Preservation

This section establishes the *soundness* of $\lambda_{\rm J}$, named *metric preservation*. Metric preservation for $\lambda_{\rm J}$ extends the notion of metric preservation of Sax. In addition to reason about sensitivity terms, given a privacy term with free variables, we can reason about what quantity of differentially privacy is achieved when closed under different (related) environments.

Contrary to SAx, we establish soundness for λ_1 using a step-indexed logical relation [\[4\]](#page-48-0). Although $\lambda_{\rm J}$ is a strongly-normalizing language, step indexing is still required to prove the bind case of the fundamental property of the logical relation.

Logical relation. The logical relations for sensitivity computations, privacy computations, values, and environments are mutually recursive and presented in Figure [16.](#page-39-0)

Note that each logical relation is also indexed by a relational distance type that now accounts for sensitivity and privacy lambdas:

$$
\sigma = \dots \mid (x : \sigma \cdot s) \xrightarrow{\Sigma + d} \sigma \mid (x : \sigma \cdot s) \xrightarrow{\Sigma} \sigma
$$

$$
\Sigma = \dots \mid p
$$

Note that similarly to sensitivity environments, privacy environment Σ are also extended to include partially instantiated data, for instance $px + p'$. Notation $(v_1, v_2) \in \mathcal{V}_d^k[\![\sigma]\!]$ indicates that value v_1 is related to v_2 at type σ and distance d for k steps.

The sensitivity parts of the logical relations are defined analogously to Figure [8](#page-24-0) with the addition of a step index k . We only present relevant changes:

- Two sensitivity closures are also related if, given related inputs, they produce related computations. Specifically, first the environments has to be related for any step $j < k$. Second, inputs v'_1 tions. Specifically, first the environments has to be related for any step $f \sim \kappa$. Second, inputs v_1 and v_2' have to be related at distance d'' not greater than d , and for j steps. Finally, the body of the functions in extended environments have to be related computations for j steps.
- Similarly to sensitivity closures, two privacy closures are related if they produce related computations when applied to related inputs. The computations are related at privacy $d\Gamma^{\infty}+(\Delta+d''x)\Sigma$. Note that we lift d to infinite because we cannot record relational distances as a privacy result. In addition to that, we also pay the latent contextual effect of the function instantiated to $d''x$, i.e. $(\Delta + d''x) \cdot \Sigma$.

$$
(r_1, r_2) \in V_R^k[\mathbb{R}] \xrightarrow{\Delta} (r_1, r_2) \in \mathbb{R}^k[\mathbb{R}]
$$
\n
$$
(r_1, r_2) \in V_R^k[\mathbb{R}] \xrightarrow{\Delta} (r_1, r_2) \in V_{R+1}^k[\sigma_1]
$$
\n
$$
(r_1, r_1, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} (r_1, r_2) \in V_{R+1}^k[\sigma_1]
$$
\n
$$
(r_1, r_1, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} (r_1, r_2) \in V_{R+1}^k[\sigma_2]
$$
\n
$$
(r_1, r_2, r_1, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} d = \infty
$$
\n
$$
(r_1, r_2, r_2, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} d = \infty
$$
\n
$$
(r_1, r_2, r_2, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} (r_1, r_2, r_2) \in V_{R+1}^k[\sigma_1] \wedge (r_2, r_2, r_2) \in V_{R+1}^k[\sigma_2]
$$
\n
$$
(r_1, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} (r_1, r_2) \in V_{R+1}^k[\sigma_1] \wedge (r_2, r_2) \in V_{R+1}^k[\sigma_2]
$$
\n
$$
(r_1, r_2) \in V_R^k[\sigma_1 d_1 \oplus d_2 \sigma_2] \xrightarrow{\Delta} (r_1, r_2, r_1, r_1, r_1, r_2) \wedge (r_2, r_2, r_2) \wedge V_{R+1}^k[\sigma_2]
$$
\n
$$
(r_1, r_2) \in V_R^k[\sigma_1] \xrightarrow{\Delta} (r_1, r_2) \in V_{R+1}^k[\sigma_1] \x
$$

Fig. 16. λ _J: logical relations for metric preservation

Two sensitivity configurations are related computations at type σ and distance d for k steps, noted $(y_1 + e_1, y_2 + e_2) \in \mathcal{E}_d^k[\![\sigma]\!]$, when for any $j < k$, if both configurations reduce in at most j steps to two values, then these values are related for the remaining $k - j$ steps at type σ and distance *d*. We write $\gamma \vdash e \Downarrow^k v$ to say that the configuration $\gamma \vdash e$ reduces to value v in at most k steps.

The definition of related privacy computations is more involved and requires a number of concepts defined next. First, we need a notion of step-indexed semantic equivalence, defined in Fig-ure [17;](#page-40-0) $v_1 \approx^k v_2$ denotes that v_1 is semantically equivalent for k steps to v_2 . Any real number, or unit value is equivalent to itself at any number of steps. Two sensitivity closures are equivalent for k steps if, when applied to any input, they either both produce equivalent values in $j < k$ steps that are themselves equivalent for the the remaining $k - j - 1$ steps. If one of the expressions

 $r \approx k$ r tt \approx k tt $\forall \vdash v : \tau$ $(0 \leq j < k - 1 \land \gamma_1, x \mapsto v + e_1 \Downarrow^j v_1 \land \gamma_2, x \mapsto v + e_2 \Downarrow^j v_2 \Rightarrow v_1 \approx^{k-j-1} v_2$ $\langle \hat{\lambda}^s x : \tau \cdot s.e_1, \gamma_1 \rangle \approx^k \langle \hat{\lambda}^s x : \tau \cdot s.e_2, \gamma_2 \rangle$ $\forall v, v'$ $(\Pr[\gamma_1, x \mapsto v \vdash e_1 \Downarrow^k v'] \wedge \Pr[\gamma_1, x \mapsto v \vdash e_2 \Downarrow^k v'])$ $\Rightarrow \Pr[\gamma_1, x \mapsto v \vdash e_1 \Downarrow^k v'] = \Pr[\gamma_2, x \mapsto v \vdash e_2 \Downarrow^k v']$ $\langle \lambda^p x : \tau \cdot s \cdot e_1, \gamma_1 \rangle \approx^k \langle \lambda^p x : \tau \cdot s \cdot e_2, \gamma_2 \rangle$ $v_1 \approx^k v_2$ inl $v_1 \approx^k$ inl v_2 $v_1 \approx^k v_2$ inr $v_1 \approx^k$ inr v_2 $v_{11} \approx^k v_{21}$ $v_{12} \approx^k v_{22}$ $(v_{11}, v_{12}) \approx^k (v_{21}, v_{22})$ $v_{11} \approx^k v_{21}$ $v_{12} \approx^k v_{22}$ $\langle v_{11}, v_{12} \rangle \approx^k \langle v_{21}, v_{22} \rangle$

Fig. 17. Step-indexed semantic equivalence

does not reduce to a value after j steps, then the result vacuously holds. Similarly, two privacy closures are equivalent for k steps if applied to any value v , then the probabilities of reducing both expressions to some value v' in at most k steps is the same (if both probabilities are defined). Two inl (resp. inr) values are equivalent for k steps, if the underlying values are equivalent for k steps. And similarly two products are equivalent for k steps if both components are also equivalent for k steps.

We use notation $Pr[y \vdash e \Downarrow^k S]$ to indicate the probability of reducing the privacy configuration γ ⊢ e to an element of the set *S* in at most *k* steps. Formally, Pr[γ ⊢ e $\Downarrow^k S$] = $\sum_{v \in S} Pr[\gamma$ ⊢ e $\Downarrow^k v$], where $Pr[y \vdash e \Downarrow^k v]$ represents the probability of reducing the configuration $y \vdash e$ to value *v*. The probability of reducing a configuration to a value is defined as $Pr[y \in \mathbb{R}^k]$ v $] = [\![e]\!]_Y^k v$, where $[\![{\bf e}]\!]_Y^k$ correspond to the probabilistic semantics of e, defined as a probability mass function (PMF), and presented in Figure [18.](#page-41-0) Index k in $[\![{\bf e}]\!]_Y^k$ correspond to the minimal number of steps such that expression e always reduces to some value \mathbf{v} . We can always find such a number as the language is strongly normalizing. The probabilistic semantics of return e is defined as a function that returns 1 if the argument is semantically equivalent to some v for $k - j$ steps, where e reduces to v in at most $j \leq k$ steps. The probabilistic semantics of a bind $x : \tau_1 \leftarrow e_1$; e_2 is defined as a function that computes for any υ of type τ/γ (τ/γ removes free variables from type τ , and is defined as $\lceil \emptyset / x_1, ..., \emptyset / x_n \rceil \tau$ for $x_i \in dom(y)$, the sum of the probabilities of reducing e_1 to v times the probability of reducing e_2 to its argument ψ , with an extended environment where x is bound to v . Note that as we want probabilities to be no greater than 1, we quantify over values drawn from the set of representatives of the equivalence classes of values wrt \approx^k , written $\mathit{val}_*^k(\tau/\gamma)$.

The probabilistic semantics of a privacy application is defined as the probabilistic semantics of The probabilistic semantics of a privacy application is defined as the probabilistic semantics of the body of the resulting privacy closure, with an environment extended with the value of the argument expression. Similarly, the probabilistic semantics of a case term is simply the probabilistic semantics of either branch, depending on the value of e_1 .

With these notions laid out, we are now ready to define related privacy computations. Notation $(y_1 + e_1, y_2 + e_2) \in \mathcal{E}_{p}^k[\![\sigma]\!]$ indicates that two privacy configurations are related computations at

Fig. 18. Probabilistic semantics (selected rules)

type σ and privacy $p=(\epsilon,\delta)$ for k steps. This means that for any subset S of val_*^k , if the probabilities s_f and p_f are ϵ of s are defined for k steps (notation (Pr[γ_1 \vdash e_1 $\Downarrow^k S$] \wedge Pr[γ_2 \vdash $e_2 \downarrow k$ S)), then the probability of reducing the first configuration to an element of set *S* is no greater than e^{ϵ} times the probability of reducing the second configuration to an element of the same set *S*, plus δ (and vice versa).

Metric Preservation. Armed with these logical relations, we can establish the notion of type soundness for $\lambda_{\rm J}$, and prove the fundamental property.

Theorem 7.2 (Metric Preservation).

(1) $\Gamma, \Delta \vdash e : \tau : \Sigma \Rightarrow \forall k \geq 0, \forall \Delta' \sqsubseteq \Delta, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\Gamma], (\gamma_1 + e, \gamma_2 + e) \in \mathcal{E}_{\Delta', \Sigma}^k[\Delta'(\tau)]$ (2) $\Gamma, \Delta \vdash e : \tau : \Sigma \Rightarrow \forall k \geq 0, \forall \Delta' \sqsubseteq \Delta, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{\overline{k}-1}[\![\Gamma]\!], (\gamma_1 + e, \gamma_2 + e) \in \mathcal{E}_{\Delta', \Sigma}^{\overline{k}}[\![\Delta'(\tau)]\!]$

where $\Delta' \subseteq \Delta \iff dom(\Delta') = dom(\Delta) \land \forall x \in dom(\Delta'), \Delta'(x) \leq \Delta(x)$. The theorem says that if a sensitivity term (resp. privacy term) is well-typed, then for any number of steps k , valid relational distance environment Δ' (not greater than Δ) and value environments (γ_1, γ_2), the two configurations are related computations at distance type $\Delta'(\tau)$ (closing all free sensitivity or privacy variables), and at relational distance $\Delta' \cdot \Sigma$ (resp. $\Delta' \cdot \Sigma$). Note that as $dom(\Sigma) \subseteq dom(\Delta') = dom(\Delta)$ and $dom(\Sigma) \subseteq dom(\Delta') = dom(\Delta)$, then $\Delta' \cdot \Sigma \in \mathbb{R}^{\infty}$ and $\Delta' \cdot \Sigma \in priv$.

To prove the fundamental property, in particular for the return case, we crucially rely on the following lemma, which states that if two values are related at zero distance and at a type where all non-free variable sensitivities and privacies are zero, then the two values are also semantically equivalent.

LEMMA 7.3. Let Σ_{\emptyset} , such that $\Sigma_{\emptyset}(x) = 0$, for all $x \in FV(\tau)$. If $(v_1, v_2) \in \mathcal{V}_0^k[\Sigma_{\emptyset}(\tau)]$ then $v_1 \approx^k v_2$.

Also, we rely on the following three lemmas which connect types, sensitivities and privacies environments from the type system, with distances and privacies from the logical relations:

LEMMA 7.4. If $\Delta \cdot \Sigma = d$ and $x \notin dom(\Sigma) \cup dom(\Delta)$, then $\Delta \cdot ([\Sigma/x]\Sigma') = (\Delta + dx) \cdot \Sigma'$

LEMMA 7.5. If $\Delta \cdot \Sigma = d$ and $x \notin dom(\Sigma) \cup dom(\Delta)$, then $\Delta \cdot ([\Sigma/x]\Sigma') = (\Delta + dx) \cdot \Sigma'$

LEMMA 7.6. Let $\Delta \cdot \Sigma = d$ and $x \notin dom(\Sigma) \cup dom(\Delta)$, then $\Delta(\Sigma/x | \tau) = dx(\Delta(\tau))$

We can also derive from the fundamental property some corollaries about closed terms.

CORROLARY 7.6.1 (FP FOR CLOSED SENSITIVITY TERMS). If \emptyset ; $\emptyset \vdash e : \tau$; \emptyset , then $(\varnothing \vdash e, \varnothing \vdash e) \in \mathcal{E}_{0}\llbracket \tau \rrbracket$

CORROLARY 7.6.2 (FP FOR CLOSED PRIVACY TERMS). If \emptyset ; $\emptyset \vdash e : \tau$; \emptyset , then $(\varnothing \vdash e, \varnothing \vdash e) \in \mathcal{E}_{(0,0)}[[\tau]]$

In addition to sensitivity type soundness at base types (Prop [5.3,](#page-26-1) from the fundamental property we can now establish privacy type soundness at base types:

THEOREM 7.7 (PRIVACY TYPE SOUNDNESS AT BASE TYPES). If $\varnothing \vdash e : (x : \mathbb{R} \cdot 1) \xrightarrow{(\epsilon, \delta)x} \mathbb{R}$; \varnothing , $|r_1 - r_2| \leq 1$, $\forall r, Pr[\emptyset \vdash e \ r_1 \Downarrow r] \leq e^{\epsilon} Pr[\emptyset \vdash e \ r_2 \Downarrow r] + \delta$

8 FROM λ _I TO JAZZ

The full prototype implementation of JAzz includes several extensions to the core language $\lambda_{\rm J}$.

Type Polymorphism. Jazz implements System F (universal quntification over well-kinded types) and parametric polymorphism over all compound types, including vector/matrix schemas, allowing all data objects and functions in the language to be fully generic. This feature requires the use of type-level quantifiers and application.

Value Dependency. Jazz supports type-level dependency on values through singleton types an approach we borrow directly from DFuzz [\[26\]](#page-49-0). This allows differentially private algorithms to be verified with respect to privacy parameters which are not fixed, and instead are function arguments.

More specifically, singleton types ?? are a technique for supporting limited forms of value dependency which builds on standard (System-F-style) polymorphic type system features and an enriched kind system. In a type system with native support for dependent types, a dependent function with a real-valued argument is written $(x : \mathbb{R}) \to \tau$ where the return type τ can use x to refer symbolically to the eventual runtime value of x . In a singleton type encoding of dependent types, the same function is written $x : \mathbb{R}[\hat{x}] \to \tau$, where the return type τ can use \hat{x} to refer symbolically to the eventual runtime value of x . In essence, there is still a syntactic split between term-level variables (x) and type-level variables (\hat{x}), and the type declaration (x : $\mathbb{R}[\hat{x}]$) links them, so \hat{x} is the type-level *proxy* for the term-level variable x .

Let-binding Sensitivity Terms in Privacy Contexts. As described in Section [6.2](#page-28-0) we implement latent sensitivity via local bindings in the privacy language. We implement this feature using an environment Φ to delay the "payments" of a value's sensitivity, which fulfills the same role as the boxed type introduced by Near et al. [\[32](#page-50-0)]. Unlike boxed types, this feature requires no additional annotations—sensitivity is inferred automatically. The complete type systems that includes Φ are presented in Appendix [A,](#page-51-0) Figures [20](#page-52-0) and [21.](#page-53-0)

Context Polymorphism. Jazz implements quantification over latent contextual effects, making it possible to afford privacy in type signatures to closed-over variables involved in the differentially private computation. This feature requires the use of type-level quantifiers, application, and annotations for context schemas (angle bracket enclosed lists of variables). Angle bracket schemas in Jazz denote the set of variables that we care about preserving privacy for, and are used in the

introductions forms for sums, pairs, and functions, as well as in type-level application For example, gauss $\langle x \rangle$ ($x + y * y$) is 1-sensitive in x , and bumps y to infinity privacy.

Variants of Differential Privacy. In addition to (ϵ, δ) -differential privacy, Jazz supports zero-concentrated differential privacy [\[16](#page-49-1)] and Rényi differential privacy [\[31\]](#page-50-1), and has built-in constructs for mixing the variants. Each variant has different privacy parameters and rules for composition, but all of them follow the same basic pattern as (ϵ, δ) -differential privacy. For example, we can give the Gaussian mechanism the following types for Rényi differential privacy (RDP; privacy parameters α and ϵ) and zero-concentrated differential privacy (zCDP; privacy parameter ρ):

```
RDP<br>gauss : \forall (\hat{d} : \mathbb{R}) (\hat{\alpha} : \mathbb{R}) (\hat{\epsilon} : \mathbb{R}). (d : \mathbb{R}[\hat{d}]) \rightarrow (\alpha : \mathbb{R}[\hat{\alpha}]) \rightarrow (\epsilon : \mathbb{R}[\hat{\epsilon}]) \rightarrow (x : \mathbb{R} \cdot \hat{d}) \xrightarrow{\infty(d+\alpha+\epsilon)+( \hat{\alpha}, \hat{\epsilon})x} \mathbb{R}<br>gauss : \forall (\hat{d} : \mathbb{R}
```
Since RDP and zCDP guarantees can be converted to (ϵ, δ) guarantees, JAZZ provides constructs for converting between variants. For example, the following code uses the Gaussian mechanism twice, each time satisfying (20, 0.25)-RDP. By sequential composition, the total cost is (20, 0.5)-RDP. The program then converts this guarantee to (ϵ, δ) -differential privacy, using $\delta = 10^{-5}$.

 $\lambda^p(x-1)$. RENYI[$\delta = 10^{-5}$ $]\{r_1 \leftarrow \text{gauss } 1 \text{ 20 } 0.25 \text{ x};$ $r_2 \leftarrow$ gauss 2 20 0.25 ($x + x$); $(x : \mathbb{R} \cdot 1) \xrightarrow{(1.08, 10^{-5})x} \mathbb{R}$ return $(r_1 + r_2)$ }

Jazz automatically finds the privacy cost of this function, in (ϵ, δ) -differential privacy, by performing the appropriate conversion. The ability to mix privacy variants in Jazz makes it easy to frame the privacy guarantee of any program in terms of (ϵ, δ) privacy cost, allowing privacy costs to be directly compared. In addition, it enables embedding iterative RDP and zCDP algorithms inside of (ϵ, δ) programs, allowing these programs to take advantage of the improved composition properties RDP and zCDP provide. This approach—leveraging recent variants for composition, but reporting privacy costs in terms of ϵ and δ —is extremely common in recent work on differentially private machine learning [\[2\]](#page-48-1). We make extensive use of variant-mixing in our case studies, described next.

9 CASE STUDIES IN JAZZ

JAZZ enables programmers to write and verify largely the same set of programs as DUET, but JAZZ gives types to many privacy functions that require special typing rules in DUET. Our case studies focus on demonstrating that Jazz retains the ability to express and verify the same set of practical programs as Duet, and that Jazz allows us to verify these programs without the use of special typing rules.

We have implemented a prototype of the Jazz typechecker in Haskell, and re-implemented all of the Duer case studies in Jazz to be compatible with our prototype. A summary of our case study programs appears in Table [3.](#page-44-0)

We present two new representative case study algorithms we have implemented and verified using Jazz: the MWEM algorithm [\[28\]](#page-50-2) for a workload of linear queries, and a recently proposed algorithm for differentially private deep learning with adaptive clipping [\[36\]](#page-50-3). In both case studies, privacy mechanisms (e.g. laplace and exponential) and looping constructs (e.g. aloop—advanced composition) can be expressed with regular functions, provided in a library of primitives. We mark these two case studies with a ∗ in Table [3,](#page-44-0) and describe them in detail in this section. The other case study programs are available in our source code repository.

Technique	Ref.	Privacy Concept
Machine Learning Algorithms		
Noisy Gradient Descent	$[13]$	Composition
Gradient Descent w/ Output Perturbation	[39]	Parallel comp. (sens.)
Noisy Frank-Wolfe	[35]	Exponential mechanism
Variations on Gradient Descent		
Minibatching	$[13]$	Amplification by subsampling
Parallel-composition minibatching		Parallel composition
Gradient clipping	$\lceil 2 \rceil$	Sensitivity bounds
Adaptive gradient clipping*	[36]	Advanced variants
Preprocessing & Deployment		
Hyperparameter tuning	$[17]$	Exponential mechanism
Adaptive clipping		Sparse Vector Technique
Z-Score normalization	$[1]$	Composition
Algorithms for Linear Queries		
Multiplicative Weights (MWEM)*	²⁸	Exponential mechanism

Table 3. List of case studies included with the Jazz implementation. Case studies marked with a * are described in detail in this section.

9.1 MWEM

The MWEM algorithm [\[28](#page-50-2)] generates differentially private synthetic data approximating the target sensitive data by iteratively optimizing the accuracy of a set of workload queries on the synthetic data. In each iteration, the algorithm uses the exponential mechanism to pick a query from the workload for which the synthetic data produces an inaccurate result, uses the Laplace mechanism to run that query on the real data, and uses the result to update the synthetic data via the multiplicative weights update rule. The Jazz program shown below implements the MWEM algorithm. Its inputs are a sensitive dataset X over a domain D , a workload Q of linear queries, the number of iterations to be performed k, the privacy parameter ϵ , initial synthetic data Y_0 (*n* times the uniform distribution over D), and the dimensions of the input data set (matrix) m rows by n columns. The algorithm performs k iterations, invoking laplace and exponential in each iteration. The privacy parameter for each invocation is $\epsilon/2k$, yielding a total privacy cost of ϵ .

```
MWEM \triangleq \lambda^s n. \lambda^s k. \lambda^s \epsilon. \lambda^s X. \lambda^s Q. \lambda^p Y_0.
   seqloop k Y_0 \ll X > (\lambda^p A_{i-1}).q_iIndex \leftarrow exponential (\epsilon / (2 * k)) Q X (\lambda^s X'. \lambda^s q'. |q' A_{i-1} - q' X'|);let q_i = matrixIndex Q (index \mathbb{N}[0]) q_iIndex in
       m_i \leftarrow laplace 1 (\epsilon / (2 * k)) (q_i X);
       return mmap-row X A_{i-1} (\lambda^s x).
          mScale x (\exp (q_i x * (m_i - q_i A_{i-1} / (2 * n))))))
```
The Jazz typechecker produces the following type for this implementation, indicating that the algorithm satisfies ϵ -differential privacy. Note the homogenous matrix type notation used here is $\mathbb{M}[m,n]$ *t* where *m* denotes the number of rows, *n* the number of columns, and *t* the type of each column.

MWEM :
$$
\forall
$$
 (\hat{m} : N) (\hat{n} : N) (\hat{k} : N) (\hat{d} : R⁺) ($\hat{\epsilon}$: R⁺). (\hat{n} : N[\hat{n}]) \rightarrow (k : N[\hat{k}]) \rightarrow (d : R⁺[\hat{d}])
\ndesired privacy
\ndesired privacy
\ndesired privacy
\n \rightarrow (ϵ : R⁺[$\hat{\epsilon}$]) \rightarrow (X : (M[\hat{m} , \hat{n}] D) $\cdot \hat{d}$) \rightarrow (Q : List ((xs : M[1, \hat{n}]) \xrightarrow{xs} N)) \rightarrow (Y₀ : M[\hat{m} , \hat{n}] D)
\n $\xrightarrow{\text{private}}$
\n $\omega(n + k + \epsilon + Q + Y_0) + (\hat{\epsilon}, 0)X$
\n $\xrightarrow{\text{synthetic db}}$
\nM[\hat{m} , \hat{n}] R

On an average of 10 runs, it takes the Jazz typechecker 5.2ms to produce this type for the MWEM algorithm.

Primitives used. This case study demonstrates the composition of a complex iterative algorithm from basic privacy mechanisms encoded as Jazz primitives (e.g. laplace and exponential) and privacy combinators (e.g. seqloop). These primitives with types shown above would require explicit typing rules in the core Duet language. In Jazz, they can be given regular types, as shown below:

exponential : ∀ (*n̂*: N) (*n̂*: N) (*â*: R⁺) (*ε̂*: R⁺) (Γ : ext) (τ : **★**). (*d*: R⁺[*ā*]) → (*ε*: R⁺[*ε̄*])
\nlinear queries
\n
$$
\rightarrow (Q: List ((xs : M[1, n̂]) xs N)) \rightarrow (X: (List τ) · d̂) \rightarrow (φ: (x : τ) λ̄(x+Γ) R)
$$
\n
$$
\xrightarrow{\text{orivacy effect}}
$$
\n
$$
\xrightarrow{\infty(d + \epsilon + Q + \phi) + (\hat{\epsilon}, 0)(X + Γ)}
$$
\n
$$
\xrightarrow{\infty(d + \epsilon + Q + \phi) + (\hat{\epsilon}, 0)(X + Γ)}
$$
\n
$$
\xrightarrow{\infty(\delta : R^+[\delta]) \rightarrow (X: (List R) · â) \rightarrow (Γ : ext). (k: N[k̃]) → (d: R+[ã]) → (ε: R+[ε̅])
$$
\n
$$
\xrightarrow{\infty(k+d+\epsilon+\delta+f)+(k\epsilon,\hat{k}\delta)\Gamma} List R
$$

To typecheck <code>MWEM</code>, the privacy closure rule in JAzz creates a function type for the λ^{P} which has a privacy effect for the body of $\frac{\epsilon}{k}$ because of the two uses of mechanisms which give $\frac{\epsilon}{2k}$ differential privacy. This privacy effect is multiplied by the loop iteration number k as a result of the type of seqloop : $\mathbb{N}[k] \to \tau \to (\tau \xrightarrow{|\Sigma|^{\epsilon}} \tau) \xrightarrow{|\Sigma|^{\epsilon_{\epsilon}}} \tau$ and the type rule for privacy function application. Finally, the new let rule in Jazz for privacy language that tracks latent contextual sensitivities with Φ is used in the let-binding for q_0 to precompute an intermediate value which is used multiple times, without the need for explicit boxing.

9.2 Differentially Private Deep Learning with Adaptive Clipping

The current state-of-the-art in differentially private machine learning is noisy gradient descent [\[3\]](#page-48-3): at each iteration of training, compute the gradient, *clip* the gradient to have bounded $L2$ norm, and add noise in proportion to the clipping parameter. The clipping parameter is typically treated as a hyperparameter, set by the analyst before training.

Recent work by Thakkar et al. [\[36](#page-50-3)] proposed an algorithm for adaptively determining the clipping parameter during training, by adaptively improving the clipping parameter based on a differentially private estimate of

gauss:
$$
(s : sens) \rightarrow (x : \mathbb{R} \cdot s) \xrightarrow{\infty s, (\epsilon, \delta)x} \mathbb{R}
$$

\n $zeros(n) \triangleq increase_{L\infty} 1 n (\lambda^s i. \lambda^s j. 0.0)$
\n $clipUpdate(C^t, d, \gamma, gs, \epsilon, \delta) \triangleq$
\n $\beta \leftarrow gauss \epsilon \delta (mean (\mathbb{I}_{\|d\| \leq C^t} gs));$
\nreturn $C^t - (\beta - \gamma)$
\n $DPAL(X, y, k, \gamma, \epsilon, \delta, \delta') \triangleq$
\nlet $C^0 = MAXNUM in$

let θ_0 = zeros (cols X) in

the percentage of gradients clipped in each iteration.

In each iteration, the implementation computes the gradients for a batch of examples qs , clips each gradient using the current parameter C^t , and uses the Gaussian mechanism to compute a differentially private average gradient q_p . Then, the algorithm updates the clipping parameter for the next iteration C^{t} using clipUpdate, which computes a noisy count β of the number of gradients in qs that are clipped under the clipping parameter C^t and uses the count to update the parameter. The

inputs to the algorithm are the training data X, the training labels y , the number of iterations k , and the target percentage of gradients remaining un-clipped γ . ϵ , δ , and δ' are the privacy cost parameters. The Jazz typechecker typechecks DPAL in 5.6ms (averaged over 10 runs).

Primitives used. This algorithm demonstrates the use of privacy combinators (e.g. aloop) that can be specified as primitives in JAzz but require special typing rules in DUET:

$$
\begin{aligned}\n\text{aloop}: & \forall \ \delta': \mathbb{R}^+, s: \mathbb{R}^+, \Gamma: \text{cxt.}(\delta': \mathbb{R}^+[\delta']) \to (k: \mathbb{N}) \to (y: \text{Matrix } \mathbb{R}) \to (\Gamma: \text{cxt}) \\
&\to (\mathcal{M}: (x: (\text{List } \mathbb{R} \cdot s) \xrightarrow{(\epsilon, \delta)\Gamma} \text{List } \mathbb{R})) \xrightarrow{(\epsilon', k\delta + \delta')\Gamma} \text{List } \mathbb{R} \\
\text{where } & \epsilon' \triangleq 2\epsilon(\sqrt{2k(\log(1/\delta'))})\n\end{aligned}
$$

This version of the adaptive clipping gradient descent algorithm uses advanced composition and (ϵ, δ) -differential privacy, to demonstrate the encoding of aloop as a regular function in Jazz. Our source code repository contains an alternative implementation that uses zero-concentrated differential privacy for improved composition, and converts the privacy guarantee to (ϵ, δ) -differential privacy at the end of the algorithm.

10 RELATED WORK

Verification techniques based on type systems. There are two threads of prior work in type-systembased verification of differential privacy for high-level programs: those based in linear types, and those based on relational refinement types. Reed and Pierce [\[33\]](#page-50-6) proposed Fuzz, the first type system for differential privacy based on linear typing; its fundamental components are a linear type system with an indexed "scaling" modality $!_s$ for tracking the sensitivity of programs and a monadic connective \circ to model randomized computations. An *s*-sensitive function is encoded in Fuzz as a linear function with scaled domain $\mathcal{A} \rightarrow B$ and often notated $A \rightarrow_{S} B$. An ϵ differential privacy mechanism is represented as an ϵ -sensitive function with monadic return type as in $A \sim_{\epsilon} \circ B$. DFuzz [\[26](#page-49-0)] extends Fuzz with dependent types to encode sensitivity and privacy bounds that depend on the values of function arguments. This allows e.g. reasoning about the privacy of iterative algorithms whose privacy cost depend on the number of itarations. Fuzz and DFuzz can be characterized by strong support for higher-order programming and potential for automation via type inference. They support pure differential privacy but approximate and any other recent variants of differential privacy fall out of their scope due to nonlinear scaling. Several recently-proposed approaches allow a Fuzz-like analysis for (ϵ, δ) -differentially private programs: Azevedo de Amorim et al. [\[21](#page-49-4)] leverage a path construction and a Fuzz-like type system. Fuzzi [\[41\]](#page-50-7) integrates a Fuzz-like type system with an expressive program logic. Finally Duer [\[32\]](#page-50-0) proposes

System Sens. Function	Sens. Typing	Priv. Function	Priv. Typing
(D)Fuzz $\tau_1 \rightarrow \tau_2$	$\Gamma \vdash e : \tau$	$\tau_1 \multimap_{\epsilon} \bigcirc \tau_2$	$\Gamma \vdash e : \bigcirc \tau$
$\text{HOARE}^2 \quad \xrightarrow{\Pi s'.\{x :: \tau_1 \mid \mathfrak{D}_{\tau_1}(x_{\lhd}, x_{\rhd}) \leq s'\}} \rightarrow \{y :: \tau_2 \mid \mathfrak{D}_{\tau_2}(y_{\lhd}, y_{\rhd}) \leq ss'\}$	$6 + e :: \tau$	$\{x : \tau_1 \mid \mathfrak{D}_{\tau_1}(x_{\triangleleft}, x_{\triangleright}) \leq 1\}$ $\rightarrow \mathfrak{M}_{\epsilon,\delta}[\{y : z_2 \mid y_3 = y_3\}]$	\mathfrak{G} + e :: $\mathfrak{M}_{\epsilon,\delta}[\tau]$
DUET $\tau \rightarrow \tau$	$\Gamma \vdash e : \tau$	$(\tau \oslash p, \ldots, \tau \oslash p) \rightarrow^* \tau \quad \Gamma \vdash e : \tau$	
JAZZ $(x:\tau) \xrightarrow{\Sigma} \tau$	$\Gamma \vdash e : \tau : \Sigma \quad (x : \tau) \xrightarrow{\Sigma} \tau$		$\Gamma \vdash e : \tau : \Sigma$

Table 4. How each system $-(D)$ Fuzz, HOARE 2 , Due τ and JAzz (this paper) $-(1)$ encodes function sensitivity in types, (2) structures typing judgments for function sensitivity, (3) encodes differential privacy in types, and (4) structures typing judgments for differential privacy.

a two-language design with linear types for tracking sensitivity and privacy; crucial restrictions in the typing rules of the privacy language allow encoding advanced differential privacy variants such as approximate, Rényi, zero-concentrated and truncated-concentrated differential privacy. In Duer privacy functions are *n*-ary and written $(\tau_1 \oslash p_1, \ldots, \tau_n \oslash p_n) \multimap^* \tau$ for privacy quantities p_i such as (ϵ_i, δ_i) in the case of approximate differential privacy.

Unlike previous works based on linear type systems, HOARE² [\[9\]](#page-49-5) uses relational refinement types to encode arbitrary relational properties of programs, including differential privacy. In HOARE², an *s*-sensitive function type is written $\Pi s'$. $\{x :: \tau_1 \mid \mathfrak{D}_{\tau_1}(x_{\lhd}, x_{\rhd}) \leq s'\} \rightarrow \{y :: \tau_2 \mid \mathcal{D}_{\tau_2}(y_{\lhd}, y_{\rhd}) \leq s'\}$ s '} where \mathcal{D}_{τ} is a type-indexed distance metric, and x_{\lhd} and x_{\rhd} are explicit symbolic representation of the "left" and "right" execution of the program in support of encoding relational properties. To account for probabilistic private computations, HOARE² uses an indexed monad $\mathfrak{M}_{\epsilon,\delta}[\tau]$: the type of an (ϵ, δ) -differentially private function is written $\{x : \tau_1 \mid \mathfrak{D}_{\tau_1}(x_{\lhd}, x_{\rhd}) \leq 1\} \to \mathfrak{M}_{\epsilon, \delta}[\{y : \tau_2 \mid \mathfrak{D}_{\tau_1}(x_{\lhd}, x_{\rhd}) \leq 1\}]$ $y_{\leq 0} = y_{\geq 0}$]. A limitation of this encoding is that a function of two arguments which provides different privacy bounds for each argument will report a summed, global privacy bound, because the tracking of privacy occurs in a single global index to the privacy monad $\mathfrak{M}_{\epsilon,\delta}$. Regarding typechecking, even though some automation has been achieved [18], the automation relies heavily on what is achievable with SMT solvers, and has limited application to programs which make generous use of compositional or higher-order programming techniques, or metric-distance relationships between values at non-base types.

To conclude the overview about type-system-based verification techniques, we refer the reader to Table [4,](#page-47-0) comparing different aspects of the reviewed type systems.

Techniques based on couplings and program logics. Approximate couplings [7] are a probabilistic abstraction that witnesses differential privacy properties of programs and have been successfully exploited for verification purposes. The relational Hoare logic apRHL [\[11,](#page-49-6) [12\]](#page-49-7) and its successors apRHL+ [\[10](#page-49-8)] and span-apRHL [\[34\]](#page-50-8) internalize the compositional construction of such couplings and capture from pure and approximate differential privay to more recent variants such as Rényi, zero-concentrated and truncated-concentrated differential privacy. While compared to other methods these program logics are rather expressive going beyond the composition of (a set of predefined) basic mechanisms, derivations in the logics involve complex quantitative reasoning, not always amenable to automation. Even though there has been a successfull report on partial automation [6], e.g. the synthesis of (quantitative relational) loop invariants for iterative algorithms remains challenging. To synthesise couplings, Albarghouthi and Hsu [5] use an alternative approach based on constraint solving which is highly amenable to automation; the approach is however confined to ϵ -DP. Finally, to verify programs that achieve (ϵ , δ)-DP composing basic mechanisms, Barthe et al. [\[8\]](#page-49-9) use a customised program product construction and traditional (non-relational and

non-probabilistic) Hoare logic augmented with mechanism-specific rules. A common limitation of all these approaches is that they are restricted to first order imperative programs.

Techniques based on randomness alignment. LightDP [\[40](#page-50-9)] and ShadowDP [\[37\]](#page-50-10) take a third approach to verifying differential privacy based on randomness alignments. A randomness alignment is an injective function relating the randomness from one execution of a differentially private mechanism to a second execution of the same mechanism (i.e. $\mathcal{M}(x)$ outputs the same result with noise H as $\mathcal{M}(x')$ outputs with noise $f(H)$, where f is the randomness alignment). Both LightDP and ShadowDP are capable of verifying complex low-level mechanisms like the sparse vector technique in just a few seconds. However, both tools target a first-order imperative programming language, and have limited support for higher-order programming.

Techniques based on testing. Since differential privacy mechanisms are randomized, traditional methods of software testing do not apply. Two recent works by Bichsel et al. [\[14\]](#page-49-10) and Ding et al. [\[22\]](#page-49-11) address this challenge by automatically generating neighboring inputs for the mechanism being tested, and sampling from their outputs many times to approximate their output distributions. For privacy mechanisms with major bugs, these tools are able to show that the approximated distributions do not satisfy the claimed differential privacy guarantee. Royce et al. [\[38](#page-50-11)] have implemented a testing tool based on this approach in their open-source library.

11 CONCLUSION

We have presented Jazz, a language and type system for differentially private programming with strong support for both higher-order programming and advanced variants of differential privacy. The key insight of our approach is latent contextual tracking of both privacy and sensitivity, which enables sum, product and function types to describe their privacy effects—even for closure variables—and increased precision for sensitivity analysis.

We have formalized a core subset of Jazz and proved its soundness using a step-indexed logical relation, following a novel strategy. Case studies demonstrate the ability to encode basic privacy mechanisms and privacy combinators as primitives in Jazz, and to compose them to develop more complicated iterative differentially private algorithms.

Jazz extends the expressive power of systems like Fuzz [\[33\]](#page-50-6) to advanced variants of differential privacy. Like Fuzz, it remains incapable of proving the correctness of basic privacy mechanisms like the Laplace mechanism. One interesting avenue for future work lies in combining Jazz with an expressive program logic like apRHL [\[11,](#page-49-6) [12\]](#page-49-7) in the style of Fuzzi [\[41](#page-50-7)]. Such a combined system would provide a complete programming framework supporting higher-order programming and end-to-end privacy proofs.

REFERENCES

- [1] 2019. scikit-learn: Standardization, or mean removal and variance scaling. <https://scikit-learn.org/stable/modules/preprocessing.html#preprocessing-scaler>
- [2] Martin Abadi, Andy Chu, Ian Goodfellow, H. Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. 2016. Deep Learning with Differential Privacy. In Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security (CCS '16). ACM, New York, NY, USA, 308–318.<https://doi.org/10.1145/2976749.2978318>
- [3] Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. 2016. Deep learning with differential privacy. In Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security. 308–318.
- [4] Amal Ahmed. 2004. Semantics of Types for Mutable State. Ph.D. Dissertation. Princeton University.
- [5] Aws Albarghouthi and Justin Hsu. 2018. Synthesizing coupling proofs of differential privacy. PACMPL 2, POPL (2018), 58:1–58:30.<https://doi.org/10.1145/3158146>
- [6] Gilles Barthe, George Danezis, Benjamin Grégoire, César Kunz, and Santiago Zanella Béguelin. 2013. Verified Computational Differential Privacy with Applications to Smart Metering. In 2013 IEEE 26th Computer

Security Foundations Symposium, New Orleans, LA, USA, June 26-28, 2013. IEEE Computer Society, 287–301. <https://doi.org/10.1109/CSF.2013.26>

- [7] Gilles Barthe, Thomas Espitau, Justin Hsu, Tetsuya Sato, and Pierre-Yves Strub. 2019. Relational ★★\star-Liftings for Differential Privacy. Logical Methods in Computer Science 15, 4 (2019).<https://lmcs.episciences.org/5989>
- [8] G. Barthe, M. Gaboardi, E. J. G. Arias, J. Hsu, C. Kunz, and P. Strub. 2014. Proving Differential Privacy in Hoare Logic. In 2014 IEEE 27th Computer Security Foundations Symposium. 411–424.<https://doi.org/10.1109/CSF.2014.36>
- [9] Gilles Barthe, Marco Gaboardi, Emilio Jesús Gallego Arias, Justin Hsu, Aaron Roth, and Pierre-Yves Strub. 2015. Higher-Order Approximate Relational Refinement Types for Mechanism Design and Differential Privacy. In Proceedings of the 42nd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '15). Association for Computing Machinery, New York, NY, USA, 55–68.<https://doi.org/10.1145/2676726.2677000>
- [10] Gilles Barthe, Marco Gaboardi, Benjamin Grégoire, Justin Hsu, and Pierre-Yves Strub. 2016. Proving Differential Privacy via Probabilistic Couplings. In Proceedings of the 31st Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '16). Association for Computing Machinery, New York, NY, USA, 749–758. <https://doi.org/10.1145/2933575.2934554>
- [11] Gilles Barthe, Boris Köpf, Federico Olmedo, and Santiago Zanella Béguelin. 2012. Probabilistic Relational Reasoning for Differential Privacy. In Proceedings of the 39th Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '12). Association for Computing Machinery, New York, NY, USA, 97–110. <https://doi.org/10.1145/2103656.2103670>
- [12] Gilles Barthe, Boris Köpf, Federico Olmedo, and Santiago Zanella-Béguelin. 2013. Probabilistic Relational Reasoning for Differential Privacy. ACM Trans. Program. Lang. Syst. 35, 3, Article Article 9 (Nov. 2013), 49 pages. <https://doi.org/10.1145/2492061>
- [13] Raef Bassily, Adam Smith, and Abhradeep Thakurta. 2014. Private empirical risk minimization: Efficient algorithms and tight error bounds. In Foundations of Computer Science (FOCS), 2014 IEEE 55th Annual Symposium on. IEEE, 464-473.
- [14] Benjamin Bichsel, Timon Gehr, Dana Drachsler-Cohen, Petar Tsankov, and Martin Vechev. 2018. Dp-finder: Finding differential privacy violations by sampling and optimization. In Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security. 508–524.
- [15] Mark Bun, Cynthia Dwork, Guy N Rothblum, and Thomas Steinke. 2018. Composable and versatile privacy via truncated CDP. In Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing. 74–86.
- [16] Mark Bun and Thomas Steinke. 2016. Concentrated differential privacy: Simplifications, extensions, and lower bounds. In Theory of Cryptography Conference. Springer, 635–658.
- [17] Kamalika Chaudhuri and Staal A Vinterbo. 2013. A stability-based validation procedure for differentially private machine learning. In Advances in Neural Information Processing Systems. 2652–2660.
- [18] Ezgi Çiçek, Weihao Qu, Gilles Barthe, Marco Gaboardi, and Deepak Garg. 2019. Bidirectional type checking for relational properties. In Proceedings of the 40th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2019, Phoenix, AZ, USA, June 22-26, 2019, Kathryn S. McKinley and Kathleen Fisher (Eds.). ACM, 533–547.<https://doi.org/10.1145/3314221.3314603>
- [19] Michael R. Clarkson and Fred B. Schneider. 2010. Hyperproperties. J. Comput. Secur. 18, 6 (Sept. 2010), 1157–1210.
- [20] Arthur Azevedo de Amorim, Emilio Jesús Gallego Arias, Marco Gaboardi, and Justin Hsu. 2015. Really Natural Linear Indexed Type Checking. CoRR abs/1503.04522 (2015). arXiv[:1503.04522 http://arxiv.org/abs/1503.04522](http://arxiv.org/abs/1503.04522)
- [21] Arthur Azevedo de Amorim, Marco Gaboardi, Justin Hsu, and Shin-ya Katsumata. 2019. Probabilistic Relational Reasoning via Metrics. In 2019 34th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS). IEEE, 1–19.
- [22] Zeyu Ding, Yuxin Wang, Guanhong Wang, Danfeng Zhang, and Daniel Kifer. 2018. Detecting violations of differential privacy. In Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security. 475–489.
- [23] Cynthia Dwork, Moni Naor, Omer Reingold, Guy N. Rothblum, and Salil Vadhan. 2009. On the Complexity of Differentially Private Data Release: Efficient Algorithms and Hardness Results. In Proceedings of the Forty-First Annual ACM Symposium on Theory of Computing (STOC '09). Association for Computing Machinery, New York, NY, USA, 381–390. <https://doi.org/10.1145/1536414.1536467>
- [24] Cynthia Dwork, Aaron Roth, et al. 2014. The algorithmic foundations of differential privacy. Foundations and Trends® in Theoretical Computer Science 9, 3–4 (2014), 211–407.
- [25] Richard A. Eisenberg and Stephanie Weirich. 2012. Dependently Typed Programming with Singletons. In Proceedings of the 2012 Haskell Symposium (Haskell '12). Association for Computing Machinery, New York, NY, USA, 117–130. <https://doi.org/10.1145/2364506.2364522>
- [26] Marco Gaboardi, Andreas Haeberlen, Justin Hsu, Arjun Narayan, and Benjamin C Pierce. 2013. Linear dependent types for differential privacy. In Proceedings of the 40th annual ACM SIGPLAN-SIGACT symposium on Principles of programming languages. 357–370.

- [27] David K. Gifford and John M. Lucassen. 1986. Integrating functional and imperative programming. In Proceedings of the 1986 ACM Conference on Lisp and Functional Programming. 28–38.
- [28] Moritz Hardt, Katrina Ligett, and Frank McSherry. 2012. A simple and practical algorithm for differentially private data release. In Advances in Neural Information Processing Systems. 2339–2347.
- [29] Min Lyu, Dong Su, and Ninghui Li. 2017. Understanding the Sparse Vector Technique for Differential Privacy. PVLDB 10, 6 (2017), 637–648.<https://doi.org/10.14778/3055330.3055331>
- [30] Frank McSherry. 2009. Privacy integrated queries: an extensible platform for privacy-preserving data analysis. , 19–30 pages.<https://doi.org/10.1145/1559845.1559850>
- [31] Ilya Mironov. 2017. Rényi differential privacy. In 2017 IEEE 30th Computer Security Foundations Symposium (CSF). IEEE, 263–275.
- [32] Joseph P Near, David Darais, Chike Abuah, Tim Stevens, Pranav Gaddamadugu, Lun Wang, Neel Somani, Mu Zhang, Nikhil Sharma, Alex Shan, et al. 2019. Duet: an expressive higher-order language and linear type system for statically enforcing differential privacy. Proceedings of the ACM on Programming Languages 3, OOPSLA (2019), 1–30.
- [33] Jason Reed and Benjamin C Pierce. 2010. Distance makes the types grow stronger: a calculus for differential privacy. In Proceedings of the 15th ACM SIGPLAN international conference on Functional programming. 157–168.
- [34] T. Sato, G. Barthe, M. Gaboardi, J. Hsu, and S. Katsumata. 2019. Approximate Span Liftings: Compositional Semantics for Relaxations of Differential Privacy. In 2019 34th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS). 1–14.<https://doi.org/10.1109/LICS.2019.8785668>
- [35] Kunal Talwar, Abhradeep Guha Thakurta, and Li Zhang. 2015. Nearly optimal private lasso. In Advances in Neural Information Processing Systems. 3025–3033.
- [36] Om Thakkar, Galen Andrew, and H Brendan McMahan. 2019. Differentially private learning with adaptive clipping. arXiv preprint arXiv:1905.03871 (2019).
- [37] Yuxin Wang, Zeyu Ding, Guanhong Wang, Daniel Kifer, and Danfeng Zhang. 2019. Proving differential privacy with shadow execution. In Proceedings of the 40th ACM SIGPLAN Conference on Programming Language Design and Implementation. 655–669.
- [38] Royce J Wilson, Celia Yuxing Zhang, William Lam, Damien Desfontaines, Daniel Simmons-Marengo, and Bryant Gipson. 2020. Differentially Private SQL with Bounded User Contribution. Proceedings on Privacy Enhancing Technologies 2020, 2 (2020).
- [39] Xi Wu, Fengan Li, Arun Kumar, Kamalika Chaudhuri, Somesh Jha, and Jeffrey Naughton. 2017. Bolt-on Differential Privacy for Scalable Stochastic Gradient Descent-based Analytics. In Proceedings of the 2017 ACM International Conference on Management of Data (SIGMOD '17). ACM, New York, NY, USA, 1307–1322.<https://doi.org/10.1145/3035918.3064047>
- [40] Danfeng Zhang and Daniel Kifer. 2017. LightDP: towards automating differential privacy proofs. In Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages. 888–901.
- [41] Hengchu Zhang, Edo Roth, Andreas Haeberlen, Benjamin C Pierce, and Aaron Roth. 2019. Fuzzi: A three-level logic for differential privacy. Proceedings of the ACM on Programming Languages 3, ICFP (2019), 1–28.

$r \in \mathbb{R}$	
$b \in \mathbb{B}$	
$x \in \text{var}$	
$e \in \text{sexpr} \ ::= r \mid e + e \mid e * e \mid e \leq e$	real numbers
$\vert x \vert \lambda^s(x:\tau \cdot s)$. $e \vert \lambda^p(x:\tau \cdot s)$. $e \vert e \vert e$	vars, functions, applications
- t t	unit
inl ^{τ_2} e inr ^{τ_1} e case e of $\{x \Rightarrow e\}$ $\{y \Rightarrow e\}$	sums
(e,e) fst e snd e	add. products
$\left \langle e, e \rangle \right $ let $x, x = e$ in e	mult. products
$e: \tau$	ascription
b if e then e else e	(derived) booleans
let $x = e$ in e	(derived) let
$e \in pexpr ::= return e x : \tau \leftarrow e; e e e$	return, bind, applications
if e then e else e $ $ case e of $\{x \Rightarrow e\}$ $\{y \Rightarrow e\}$	conditionals, case
$let x = e in e$	let
$s \in sens \cong \mathbb{R}^{\infty}$	sensitivities
$\Sigma \in \text{senv} \quad \triangleq \text{var} \rightarrow \text{sens} \mathrel{\mathop{\mathbb{R}}} = \text{sx} + \ldots + \text{sx}$	sensitivity environments
$p \in \text{priv} \quad \triangleq \quad (\mathbb{R}^{\infty}, \mathbb{R}^{\infty})$	privacies
$\Sigma \in \text{penv} \triangleq \emptyset \mid \text{px} \mid \Sigma + \Sigma \mid \Sigma \sqcup \Sigma \mid \Sigma \sqcap \Sigma$	privacy environments
$\tau \in \text{type}$::= $\mathbb{R} \mid \mathbb{B} \mid \text{unit} \mid (x : \tau \cdot s) \xrightarrow{\Sigma} \tau \mid (x : \tau \cdot s) \xrightarrow{\Sigma} \tau$	
$\int \tau^{\Sigma} \Theta^{\Sigma} \tau \vert \tau^{\Sigma} \& \tau \vert \tau^{\Sigma} \otimes^{\Sigma} \tau$	types
$\Gamma \in \text{tenv} \quad \triangleq \text{ var} \rightarrow \text{type} \mathrel{\mathop:}= \{x : \tau, \ldots, x : \tau\}$	type environments

Fig. 19. λ_J: Syntax

APPENDIX

Throughout the appendix we use symbol s instead of d, and Σ instead of Δ as they are interchangeable.

A λ _J: STATIC SEMANTICS

In this section we present some definitions of the static semantics of λ_I not presented in the main document. Figure [19](#page-51-1) presents the syntax of $\lambda_{\rm J}$. Figures [20](#page-52-0) and 20 present the complete sensitivity type system of $\lambda_{\rm J}$. Figure [22](#page-54-0) presents the complete type system of $\lambda_{\rm J}$. They include the usage of Φ and the type rules for the derived expressions: boolean, conditional and let expressions. Figure [23](#page-55-0) presents the sensitivity instantiation or dot product operator and the sensitivity type instantiation operator. Figure [24](#page-56-0) presents the subtyping rules for $\lambda_{\rm J}$. Figure [25](#page-57-0) presents the sensitivity environment substitution environment. Figure [26,](#page-57-1) presents the different lifts operators. Finally, Figure [27](#page-58-0) presents the join and meet operator between types.

B λ _J: DYNAMIC SEMANTICS

Figure [28,](#page-59-0) presents the dynamic semantics of the sensitivity language. Figure [29,](#page-60-0) presents the dynamic semantics of the privacy language.

RLIT	PLUS Γ ; Σ_0 + e_1 : \mathbb{R} ; Σ_1 Γ ; Σ_0 + e_2 : \mathbb{R} ; Σ_2	
$\Gamma : \Sigma_0 \vdash r : \mathbb{R} : \emptyset$	Γ ; Σ_0 + e_1 + e_2 : \mathbb{R} ; Σ_1 + Σ_2	
TIMES $\Gamma : \Sigma_0 \vdash e_1 : \mathbb{R} : \Sigma_1 \qquad \Gamma : \Sigma_0 \vdash e_2 : \mathbb{R} : \Sigma_2 \qquad e_1 \neq r \qquad e_2 \neq r \qquad \qquad \Gamma : \Sigma_0 \vdash e : \mathbb{R} : \Sigma$		L-SCALE
Γ ; Σ_0 + $e_1 * e_2$; $\infty(\Sigma_1 + \Sigma_2)$		$\overline{\Gamma}$: Σ_0 \vdash $r * e : \mathbb{R}$; $r \Sigma$
R-SCALE Γ ; Σ_0 + e : R ; Σ	LEQ Γ ; Σ_0 + e_1 : \mathbb{R} ; Σ_1 Γ ; Σ_0 + e_2 : \mathbb{R} ; Σ_2	
$\Gamma : \Sigma_0 \vdash e * r : \mathbb{R} : r\Sigma$	Γ ; Σ_0 + $e_1 \leq e_2$: $\infty(\Sigma_1 + \Sigma_2)$	
VAR $\Gamma(x) = \tau$	S-LAM $\Gamma, x : \tau_1 : \Sigma_0 + sx + e : \tau_2 : \Sigma$	
Γ ; Σ_0 + sx + x : τ ; x	Γ ; Σ_0 + $\lambda^s(x : \tau_1 \cdot s)$. $e : (x : \tau_1 \cdot s) \stackrel{\Sigma}{\rightarrow} \tau_2 : \emptyset$	
$P-LAM$	$\Gamma, x : \tau_1 : \Sigma_0 + sx + e : \tau_2 : \Sigma$	
	$\Gamma : \Sigma_0 \vdash \lambda^p(x : \tau_1 \cdot s)$. e : $(x : \tau_1 \cdot s) \stackrel{\Sigma}{\rightarrow} \tau_2 : \emptyset$	
$S-APP$	Γ ; Σ_0 + e_1 : $(x : \tau_1 \cdot s') \xrightarrow{\Sigma+s} \tau_2$; Σ_1 Γ ; Σ_0 + $e_2 : \tau_1$; Σ_2 $\Sigma_0 \cdot \Sigma_2 \leq s'$	
	Γ ; Σ_0 + e_1 e_2 ; $[\Sigma_2/x] \tau_2$; Σ_1 + $s\Sigma_2$ + Σ	
UNIT	INL Γ ; Σ_0 + e : τ_1 ; Σ	
Γ ; Σ_0 + tt : unit; \emptyset	Γ ; Σ_0 + inl ^{τ_2} e : τ_1 $\Sigma_{\bigoplus}^{\varnothing}$ τ_2 : \varnothing	
INR	Γ ; Σ_0 + e : τ_2 ; Σ Γ : Σ_0 + inr ^{τ_1} e : τ_1 \mathscr{O}_{\bigoplus} Σ τ_2 ; \varnothing	

Fig. 20. λ_j : Complete sensitivity type system (part 1)

$C \quad \lambda_J$: SOUNDNESS

In this section we present auxiliary definitions used in Section [7.3,](#page-38-0) and the proof of the fundamental property. Figure [30](#page-60-1) presents the join and meet operators for sensitivity environments and sensitivities Σ + s. Figure [31](#page-61-0) presents the subtyping relation between sensible types.

LEMMA C.1 (ASSOCIATIVITY OF THE INSTANTIATION OPERATOR). $\Sigma \cdot (\Sigma_1 + \Sigma_2) = \Sigma \cdot \Sigma_1 + \Sigma \cdot \Sigma_2$

PROOF. By induction on Σ_1 :

S-CASE $\Gamma : \Sigma_0 \vdash e_1 : \tau_{11} \stackrel{\Sigma_{11}}{\to} \tau_{12} : \Sigma_1 \qquad \Gamma, x : \tau_{11} : \Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{11}))x \vdash e_2 : \tau_2 : \Sigma_2 + s_2x$ $\Gamma, \nu : \tau_{12}$; $\Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{12}))x + e_3 : \tau_3$; $\Sigma_3 + s_3\nu$
Γ ; Σ_0 + case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$: $[\Sigma_1 + \Sigma_{11}/x]\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y]\tau_3; (\Sigma_1 \sqcup (s_2\Sigma_1 + s_2\Sigma_{11} + \Sigma_2) \sqcup (s_3\Sigma_1 + s_3\Sigma_{12} + \Sigma_3))$
PRO _{I1} PAIR Γ ; Σ_0 +e : τ_1 $\Sigma_1 \& \Sigma_2$ τ_2 ; Σ Γ ; Σ_0 +e ₁ : τ_1 ; Σ_1 Γ ; Σ_0 +e ₂ : τ_2 ; Σ_2
Γ : Σ_0 + (e ₁ , e ₂) : τ_1 $\Sigma_1 \& \Sigma_2$ τ_2 : \varnothing Γ : Σ_0 + fst e : τ_1 : Σ + Σ_1
PRO _I 2 TIIP Γ ; Σ_0 +e: τ_1 $\Sigma_1 \& \Sigma_2$ τ_2 ; Σ Γ ; Σ_0 +e ₁ : τ_1 ; Σ_1 Γ ; Σ_0 +e ₂ : τ_2 ; Σ_2
Γ ; $\Sigma_0 \vdash \langle e_1, e_2 \rangle : \tau_1^{-\Sigma_1} \otimes^{\Sigma_2} \tau_2 : \varnothing$ Γ ; Σ_0 + snd e : τ_2 ; Σ + Σ_2
UNTUP Γ ; Σ_0 +e ₁ : τ_{11} Σ_{11} \otimes Σ_{12} τ_{12} ; Σ_1 $\Gamma, x_1 : \tau_{11}, x_2 : \tau_{12}$; $\Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{12}))x_2 + e_2 : \tau_2$; $\Sigma_2 + s_1x_1 + s_2x_2$ Γ ; Σ_0 + let $x_1, x_2 = e_1$ in e_2 : $[\Sigma_1 + \Sigma_{11}/x_1][\Sigma_1 + \Sigma_{12}/x_2]\tau_2$; $s_1(\Sigma_1 + \Sigma_{11}) + s_2(\Sigma_1 + \Sigma_{12}) + \Sigma_2$ ASCR Γ ; Σ_0 + e : τ ; Σ τ <: τ' $\Gamma : \Sigma_0 \vdash (e :: \tau') : \tau' : \Sigma$
derived rules
BLIT Γ ; Σ_0 + e_1 : \mathbb{B} ; Σ_1 Γ ; Σ_0 + e_2 : τ ; Σ_2 Γ ; Σ_0 + e_3 : τ ; Σ_3 Γ ; Σ_0 + if e_1 then $\{e_2\}$ else $\{e_3\}$: τ ; Σ_1 + $(\Sigma_2 \sqcup \Sigma_3)$ Γ ; Σ_0 + b : B; \varnothing
LET Γ ; Σ_0 + e_1 : τ_1 ; Σ_1 Γ , x : τ_1 ; Σ_0 + ∞ x + e_2 : τ_2 ; Σ_2 + sx Γ ; Σ_0 + let $x = e_1$ in e_2 : $[\Sigma_1/x] \tau_2$; $s\Sigma_1 + \Sigma_2$

Fig. 21. λ _J: Complete sensitivity type system (part 2)

Case (1) $\Sigma_1 = \emptyset$

SUBPROOF. Trivial as $\Sigma \cdot (\emptyset + \Sigma_2) = \Sigma \cdot \Sigma_2 = \Sigma \cdot \emptyset + \Sigma \cdot \Sigma_2$.

Case (2) $\Sigma_1 = \Sigma'_1 + s_1 x$

RETURN
Γ ; Δ + e : τ ; Σ_1 \widehat{x} = FV(FP ^{∞} (τ))
$\Gamma : \Delta \vdash$ return $e : [\varnothing/\widehat{x}] \tau : \exists \Sigma_1 \Gamma^\infty + FP^\infty(\tau)$
BIND
Γ ; Δ + e ₁ : τ_1 ; Σ_1 Γ , x : τ_1 ; Δ + 0x + e ₂ : τ_2 ; Σ_2
$\Gamma: \Delta \vdash x : \tau_1 \leftarrow e_1 : e_2 : [\emptyset/x] \tau_2 : \Sigma_1 + [\emptyset/x] \Sigma_2$
ΙF
Γ ; Δ + e_1 : \mathbb{B} ; Σ_1 Γ ; Δ + e_2 : τ ; Σ_2 Γ ; Δ + e_3 : τ ; Σ_3
$\Gamma: \Delta \vdash \text{if } e_1 \text{ then } e_2 \text{ else } e_3 : \tau : [\Sigma_1]^{\infty} + (\Sigma_2 \sqcup \Sigma_3)$
P-CASE
Γ ; Δ + e_1 : τ_{11} $\Sigma_{11} \oplus \Sigma_{12}$ τ_{12} ; Σ_1
$\Gamma, x : \tau_{11} : \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2 ; \Sigma_2 \qquad \Gamma, y : \tau_{12} : \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{12}))y + e_3 : \tau_3 ; \Sigma_3$
$\Gamma : \Delta \vdash$ case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$:
$[\Sigma_{11}/x]\tau_2 \sqcup [\Sigma_{12}/y]\tau_3; [\Sigma_1\Gamma^\infty \sqcup ([\Sigma_{11}/x]\Sigma_2 \sqcup [\Sigma_{12}/y]\Sigma_3)]$
$P-APP$
$\Gamma : \Delta \vdash e_1 : (x : \tau_1 \cdot s) \xrightarrow{\Delta} \tau_2 : \Sigma_1 \qquad \Gamma : \Delta \vdash e_2 : \tau_1 : \Sigma_2 \qquad \Delta \cdot \Sigma_2 \leq s$
Γ ; Δ + e ₁ e ₂ : $[\Sigma_2/x] \tau_2$; $[\Sigma_1]^{\infty} + [\Sigma_2/x] \Sigma$
$FP^{\infty}(\mathbb{R}) = \emptyset$
FP^{∞} (unit) = \emptyset
$FP^{\infty}((x:\tau_1\cdot s)\xrightarrow{\Sigma}\tau_2) = [\emptyset/x] [\Sigma^{\infty} + FP^{\infty}(\tau_1) + FP^{\infty}([\emptyset/x]\tau_2)$
$FP^{\infty}((x:\tau_1\cdot s) \xrightarrow{\Sigma} \tau_2) = [\emptyset/x] [\Sigma]^{\infty} + FP^{\infty}(\tau_1) + FP^{\infty}([\emptyset/x]\tau_2)$
$FP^{\infty}(\tau_1^{-\Sigma_1}\oplus^{\Sigma_2} \tau_2)=\left[\Sigma_1\right]_1^{\infty}+\left[\Sigma_2\right]_1^{\infty}+FP^{\infty}(\tau_1)+FP^{\infty}(\tau_2)$ $FP^{\infty}(\tau_1 \stackrel{\Sigma_1}{\alpha} \& \stackrel{\Sigma_2}{\alpha} \tau_2) = \frac{1}{2} \cdot \frac{1}{2} \cdot$
$FP^{\infty}(\tau_1^{-\Sigma_1} \otimes^{\Sigma_2} \tau_2) = \mathcal{Z}_1 \Gamma^{\infty} + \mathcal{Z}_2 \Gamma^{\infty} + FP^{\infty}(\tau_1) + FP^{\infty}(\tau_2)$

Fig. 22. λ _J: Complete privacy type system

SUBPROOF. Let us assume $x \notin \Sigma_2$, and that $r = \Sigma(x)$ if $\Sigma(x)$ is defined, otherwise $r = x$:

$$
\Sigma \cdot ((\Sigma_1' + s_1 x) + \Sigma_2) = \Sigma \cdot ((\Sigma_1' + \Sigma_2) + s_1 x)
$$

\n
$$
= \Sigma \cdot (\Sigma_1' + \Sigma_2) + s_1 r
$$
 (by definition)
\n
$$
= (\Sigma \cdot \Sigma_1' + \Sigma \cdot \Sigma_2) + s_1 r
$$
 (by induction hyp.)
\n
$$
= (\Sigma \cdot \Sigma_1' + s_1 r) + \Sigma \cdot \Sigma_2
$$

\n
$$
= \Sigma \cdot (\Sigma_1' + s_1 x) + \Sigma \cdot \Sigma_2
$$
 (by definition)

and the result holds. Let us assume now that $\Sigma_2 = \Sigma'_2 + s_2x$, and that $r = \Sigma(x)$ if $\Sigma(x)$ is defined, otherwise $r = x$:

$$
\Sigma \cdot ((\Sigma_1' + s_1 x) + (\Sigma_2' + s_2 x)) = \Sigma \cdot ((\Sigma_1' + \Sigma_2') + s_1 x + s_2 x)
$$

\n
$$
= \Sigma \cdot (\Sigma_1' + \Sigma_2') + (s_1 + s_2)r
$$

\n
$$
= \Sigma \cdot (\Sigma_1' + \Sigma_2') + (s_1 + s_2)r
$$
 (by definition)
\n
$$
= (\Sigma \cdot \Sigma_1' + \Sigma \cdot \Sigma_2') + (s_1 + s_2)r
$$
 (by induction hyp.)
\n
$$
= (\Sigma \cdot \Sigma_1' + \Sigma \cdot \Sigma_2') + s_1r + s_2r
$$

\n
$$
= (\Sigma \cdot \Sigma_1' + s_1r) + (\Sigma \cdot \Sigma_2' + s_2r)
$$

\n
$$
= (\Sigma \cdot (\Sigma_1' + s_1 x) + \Sigma \cdot (\Sigma_2' + s_2 x)
$$
 (by definition)

and the result holds. ⊳

Case (3) $\Sigma_1 = \Sigma'_1 + s_1$ Subproof. Similar to previous case. ⊳

LEMMA C.2. If $x \notin dom(\Sigma)$, then $sx(\Sigma(\tau)) = (\Sigma + sx)(\tau)$

PROOF. By induction on τ .

LEMMA C.3. If $\Delta \cdot \Sigma = d$ and $x \notin dom(\Sigma) \cup dom(\Delta)$, then $\Delta \cdot ([\Sigma/x]\Sigma') = (\Delta + dx) \cdot \Sigma'$

PROOF. We prove: if $\Delta \cdot \Sigma_2 = d \in \text{sens}$ and $x \notin dom(\Sigma_2) \cup dom(\Delta)$, then $\Delta \cdot [\Sigma_2/x] \Sigma_3 = dx(\Delta \cdot \Sigma_3)$. We proceed by induction on the structure of Σ_3 .

Case (1) $\Sigma_3 = \emptyset$

SUBPROOF. Trivial as $[\Sigma_2/x] \oslash = dx(\oslash) = \oslash$ and $\Delta \cdot \oslash = 0$.

Case (2) $x \notin dom(\Sigma_3)$

SUBPROOF. Then $[\Sigma_2/x]\Sigma_3 = \Sigma_3$, $\Delta \cdot [\Sigma_2/x]\Sigma_3 = \Delta \cdot \Sigma_3$, and $[s/x](\Delta \cdot \Sigma_3) = \Delta \cdot \Sigma_3$, and the result holds. holds. ⊳

 \Box

Fig. 24. Subtyping

```
\left[\frac{-}{x}\right]_: sensv\times type \rightarrow type
                              [\Sigma/x]\mathbb{R} = \mathbb{R}[\Sigma/x] \mathbb{B} = \mathbb{B}[\Sigma/x]unit = unit
[\Sigma/x]((y:\tau_1 \cdot d) \xrightarrow{\Sigma'} \tau_2) = (y:[\Sigma/x] \tau_1 \cdot d) \xrightarrow{[\Sigma/x] \Sigma'} [\Sigma/x] \tau_2[\Sigma/x](\tau_1 \Sigma_1 \oplus \Sigma_2 \tau_2) = [\Sigma/x]\tau_1 \Sigma_1 \Sigma_1 \oplus [\Sigma/x]\Sigma_2 \Sigma_2 \Sigma_1 \Sigma_1 \tau_2[\Sigma/x](\tau_1^{\Sigma_1} \& \Sigma_2 \tau_2) = [\Sigma/x]\tau_1^{[\Sigma/x]\Sigma_1} \& [\Sigma/x]\tau_2[\Sigma/x](\tau_1 \Sigma_1 \otimes \Sigma_2 \tau_2) = [\Sigma/x]\tau_1 \stackrel{[\Sigma/x]\Sigma_1}{\sim} \otimes^{[\Sigma/x]\Sigma_2} [\Sigma/x]\tau_2\left[\frac{1}{x}\right] : sensv \times sensv \rightarrow sensv
                                          [\Sigma/x]\varnothing = \varnothing[\Sigma/x](\Sigma' + sx) = [\Sigma/x]\Sigma + s\Sigma'[\Sigma/x](\Sigma' + sy) = [\Sigma/x]\Sigma + sy\lfloor x \rfloor : sensv \times (sensv + sens) \rightarrow (sensv + sens)
                               [\Sigma/x](\Sigma' + s) = [\Sigma/x]\Sigma' + s[\Sigma/x]s = s
```
Fig. 25. Sensitivity environment substitution

```
\lceil s \rceil^{s'} = s's > 0\lceil \varnothing \rceil^{s'} = \varnothing\sum f s x \mid s' = \sum s' + \sum s'\sum + 0x \left[ \frac{s'}{s} \right] = \sum \left[ \frac{s'}{s} \right] + 0x\lceil p \rceil^{p'} = pp \neq (0, 0)(0, 0)(p' = (0, 0)\bigcap \varnothing \big[ \frac{P'}{P} \big] = \varnothing\ln x \cdot p' = \ln p' x[\Sigma_1 + \Sigma_2]^\infty = [\Sigma_1]^\infty + [\Sigma_2]^\infty\sum_1 \sqcup \sum_2 \lceil^{\infty} \right] = \sum_1 \lceil^{\infty} \sqcup \sum_2 \lceil^{\infty} \right]\sum_1 \sqcap \sum_2 \lceil \infty \rfloor = \lceil \sum_1 \lceil \infty \rceil \rceil \sum_2 \lceil \infty \rfloor\sum \left[\begin{matrix} P' \\ P' \end{matrix}\right] = \prod_{i=1}^{n}\bigcup_{x \in dom(\Sigma)} (\lceil \Sigma(x) \rceil^1 p)x
```
Fig. 26. Lift operators

Fig. 27. Join and Meet of types and sensitivity environments

$$
\frac{\text{RIT}}{y + r \downarrow 0} \qquad \frac{y + e_1 \downarrow k_1 r_1}{y + e_1 + e_2 \downarrow k_1 + r_1 + r_2} \qquad \frac{\text{TNHS}}{y + e_1 + e_2 \downarrow k_1 + r_1 + r_2} \qquad \frac{\text{TNHS}}{y + e_1 + e_2 \downarrow k_1 + k_1 + r_1 + r_2}
$$
\n
\n
$$
\frac{y + e_1 \downarrow k_1 r_1}{y + e_1 \leq e_2 \downarrow k_1 + k_2 + r_1 + r_2} \qquad \frac{y(x) = v}{y + x \downarrow 0} \qquad \frac{\text{LAM}}{y + \lambda (x : \tau : s) \cdot e \downarrow 1} \cdot \frac{\lambda \text{NT}}{\lambda \times \text{NT} \cdot \text{TN}} \qquad \frac{\lambda \text{FP}}{y + e_1 \cdot e \downarrow k_1 + k_2 + k_1 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + k_2 + k_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + x \downarrow 0} \qquad \frac{\lambda \text{NT}}{y + e_1 \cdot e \downarrow k_1 + k_2 + k_3 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + k_2 + k_3 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + k_2 + k_3 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + r_2 + r_3 + r_4} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + r_2 + r_3 + r_4 + r_4} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + r_1 + r_2} \qquad \frac{\lambda \text{TN}}{y + e_1 \cdot e \downarrow k_1 + r_2 + r_3 + r_4 + r_4} \qquad \frac
$$

Fig. 28. λ _J: Sensitivity dynamic semantics

 $\mathcal{D}(A) \triangleq f : A \to \mathbb{R}$ s.t. $\sum_{x \in A}$ $f(x) = 1$ $\mathbb{I}: \text{expr} \times \text{venv} \rightarrow \mathcal{D}(\text{val})$ $\left[\text{return } e\right]_Y^k \triangleq \lambda x. \quad \begin{cases} 1 & \text{when} & x \approx^{k-j} v \\ 0 & \text{otherwise} \end{cases}$ 0 otherwise where γ ⊢ e $\Downarrow^j v \wedge j \leq k$ $\llbracket x : \tau \leftarrow e_1 : e_2 \rrbracket_Y^{k_1+k_2} \triangleq \lambda y.$ \sum_{k} $v \in val_*^{k_2}(\tau/\gamma)$ $\llbracket \mathbf{e}_1 \rrbracket^{k_1+k_2}_\gamma(v) \times \llbracket \mathbf{e}_2 \rrbracket^{k_2}_{\gamma}$ $\frac{\kappa_2}{\gamma[x\mapsto v]}(y)$ $[\text{gauss } \mu \sigma^2]_Y^k \triangleq \lambda x. \frac{1}{\sqrt{(2\pi\sigma^2)}} e^{\frac{-(r-\mu)^2}{2\sigma^2}}$ where $r = x$ $[\![e_1 \; e_2]\!]_Y^{k_1+k_2+k_3} \triangleq [\![e]\!]_{Y' [x \mapsto v]}^{k_3-1}$ where $\gamma \vdash e_1 \Downarrow_{i=1}^{k_1} \langle \lambda^p x.e.s, \gamma' \rangle$ $\gamma \vdash e_2 \Downarrow^{k_2} v$ $[\![\det x = e_1 \text{ in } e_2]\!]_Y^{k_1+k_2} \triangleq [[\![v/x]\!]_Y^{k_2-1}$ where $\gamma \vdash e_1 \Downarrow^{k_1} v$ $\llbracket \texttt{if } e_1 \texttt{ then } e_2 \texttt{ else } e_3 \rrbracket_Y^{k_1+k_2} \triangleq$ $\int [\mathbf{e}_2]_Y^{k_2}$ when $v = \text{true}$ $\lbrack \lbrack e_3 \rbrack \rbrack_Y^k$ when $v =$ false where $\gamma + e_1 \Downarrow^{k_1} v$ [case e_1 of{ $x \Rightarrow e_2$ } { $y \Rightarrow e_3$ }] $\int_Y^{k_1+k_2}$ \triangleq $\int [\![{\bf e}_2]\!]^{k_2}_{\rm VI}$ $\sum_{y}^{k_2}$ when $v = \text{inl}$ v' $[\![\mathbf{e}_3]\!]_{\scriptscriptstyle \mathcal{V} \mathsf{\Gamma}}^{k_2}$ $y[x \mapsto v']$ when $v = \text{inv}$ where $\gamma + e_1 \Downarrow^{k_1} v$
 $y[y \mapsto v']$ when $v = \text{inv}$ where $\gamma + e_1 \Downarrow^{k_1} v$

Fig. 29. λ _J: Probabilistic semantics

```
Q \cup Q = Q(\Sigma + sx) \sqcup (\Sigma' + s'x) = (\Sigma \sqcup \Sigma') + (s \sqcup s')x \times \notin dom(\Sigma \sqcup \Sigma')\Sigma \sqcup (\Sigma' + sx) = (\Sigma \sqcup \Sigma') + sx  (x \notin dom(\Sigma))(\Sigma + sx) \sqcup \Sigma' = (\Sigma \sqcup \Sigma'))+ sx (x \notin dom(\Sigma))′
))
    (\Sigma + s) \sqcup (\Sigma' + s') = (\Sigma \sqcup \Sigma') + (s \sqcup s') s
                                                                                    ′′ ∉ Σ ⊔ Σ
′
                       \sqcup \sqcup \sqcup : sensv \times sensv \rightarrow sensv
                       Q \sqcap Q = Q(\Sigma + sx) \sqcap (\Sigma' + s'x) = (\Sigma \sqcap \Sigma') + (s \sqcap s')x \times \notin dom(\Sigma \sqcap \Sigma')\Sigma \sqcap (\Sigma' + sx) = (\Sigma \sqcap \Sigma') + sx  (x \notin dom(\Sigma))(\Sigma + sx) \sqcap \Sigma' = (\Sigma \sqcap \Sigma') + sx  (x \notin dom(\Sigma'))(\Sigma + s) \sqcap (\Sigma' + s') = (\Sigma \sqcap \Sigma') + (s \sqcap s') s'' \notin \Sigma \sqcap \Sigma'
```
Fig. 30. Join and Meet of sensitivity environment and sensitivities

BASE $\sigma \in \{ \mathbb{R}, \text{unit} \}$ $\sigma \leq : \sigma$	$\sigma \leq: \sigma$ S-FUN $\sigma'_1 \leq \sigma_1$ $s' \leq s$ $\Sigma_1 \leq \Sigma'_2$ $\Sigma_2 \leq \Sigma'_2$ $\sigma_2 \leq \sigma'_2$ $(x : \sigma_1 \cdot s) \xrightarrow{\Sigma_1 + \Sigma \cdot \Sigma_2} \sigma_2 \prec: (x : \sigma'_1 \cdot s') \xrightarrow{\Sigma'_1 + \Sigma \cdot \Sigma'_2} \sigma'_2$
P-FUN	$\sigma'_1 \leq \sigma_1$ $s' \leq s$ $\sum_1 \leq \sum'_2$ $\sum_2 \leq \sum'_2$ $\sigma_2 \leq \sigma'_2$ $(x : \sigma_1 \cdot s) \xrightarrow{\Sigma_1 + \Sigma_1 \cdot \Sigma_2} \sigma_2 \prec: (x : \sigma'_1 \cdot s') \xrightarrow{\Sigma'_1 + \Sigma_1 \cdot \Sigma'_2} \sigma'_2$
	SUM $\sigma_1 \leq \sigma'_1$ $s_1 \leq s'_1$ $\sigma_2 \leq \sigma'_2$ $s_2 \leq s'_2$ $\sigma_1^{s_1} \oplus^{s_2} \sigma_2 \prec : \sigma'_1^{s'_1} \oplus^{s'_2} \sigma'_2$
	PAIR $\sigma_1 \leq \sigma'_1$ $s_1 \leq s'_1$ $\sigma_2 \leq \sigma'_2$ $s_2 \leq s'_2$ $\sigma_1^{s_1} \&^{s_2} \sigma_2 \prec : \sigma'_1^{s'_1} \&^{s'_2} \sigma'_2$
	TUP $\sigma_1 \leq \sigma'_1$ $s_1 \leq s'_1$ $\sigma_2 \leq \sigma'_2$ $s_2 \leq s'_2$ $\sigma_1^{s_1} \otimes^{s_2} \sigma_2 \prec : \sigma'_1^{s'_1} \otimes^{s'_2} \sigma'_2$

Fig. 31. Subtyping of sensible types

Case (3) $\Sigma_3 = \Sigma_4 + d'x$

SUBPROOF. By induction hypothesis on Σ_4 , we know that $\Delta \cdot ([\Sigma_2/\chi] \Sigma_4) = dx((\Delta \cdot \Sigma_4))$. Therefore

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x] (\Sigma_4 + d'x))
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4 + d' \Sigma_2)
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) + \Delta \cdot d' \Sigma_2
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) + d'(\Delta \cdot \Sigma_2)
$$

\n
$$
= dx(\Delta \cdot \Sigma_4) + d'(\Delta \cdot \Sigma_2)
$$
 (by induction hyp.)
\n
$$
= dx(\Delta \cdot \Sigma_4) + d'dx(x)
$$

\n
$$
= dx(\Delta \cdot \Sigma_4) + dx'(dx)
$$

\n
$$
= dx((\Delta \cdot \Sigma_4) + d'x)
$$
 (by definition of subst)
\n
$$
= dx(\Delta \cdot (\Sigma_4 + d'x))
$$
 (because $x \notin dom(\Delta)$)
\n
$$
= dx(\Delta \cdot \Sigma_3)
$$

And the result holds. ⊳

Case (4) $\Sigma_3 = \Sigma_4 + d'y$

SUBPROOF. By induction hypothesis on Σ_4 , we know that $\Delta \cdot ([\Sigma_2/x]\Sigma_4) = dx(\Delta \cdot \Sigma_4)$. Therefore

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x] (\Sigma_4 + d'y))
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4 + d'y)
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) + \Delta \cdot d'y
$$

\n
$$
= dx (\Delta \cdot \Sigma_4) + \Delta \cdot d'y
$$
 (by induction hyp.)
\n
$$
= dx (\Delta \cdot \Sigma_4 + d'y)
$$
 (by definition as $x \notin dom(sy)$)
\n
$$
= dx (\Delta \cdot \Sigma_3)
$$

And the result holds. ⊳

Case (5) $\Sigma_3 = \Sigma_4 + d'$

SUBPROOF. By induction hypothesis on Σ_4 , we know that $\Delta \cdot (\lceil \Sigma_2 / x \rceil \Sigma_4) = dx (\Delta \cdot \Sigma_4)$. Therefore

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x] (\Sigma_4 + d'))
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4 + d')
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) + s'
$$

\n
$$
= dx (\Delta \cdot \Sigma_4) + s'
$$
 (by induction hyp.)
\n
$$
= dx (\Delta \cdot \Sigma_4 + s')
$$
 (by definition of $\Sigma()$)
\n
$$
= dx (\Delta \cdot (\Sigma_4 + s'))
$$

\n
$$
= dx (\Delta \cdot \Sigma_3)
$$

And the result holds. ⊳

LEMMA C.4. If $\Delta \cdot \Sigma = d$ and $x \notin dom(\Sigma) \cup dom(\Delta)$, then $\Delta \cdot ([\Sigma/x]\Sigma') = (\Delta + dx) \cdot \Sigma'$

PROOF. We prove: if $\Delta \cdot \Sigma_2 = d \in \text{sens}$ and $x \notin dom(\Sigma_2) \cup dom(\Delta)$, then $\Delta \cdot [\Sigma_2/x] \Sigma_3 = dx \cdot (\Delta \cdot \Sigma_3)$. We proceed by induction on the structure of Σ_3 .

Case (1) $\Sigma_3 = \emptyset$ SUBPROOF. Trivial as $[\Sigma_2/\chi] \oslash = dx(\oslash) = \oslash$ and $\Delta \cdot \oslash = 0$. Case (2) $\Sigma_3 = p y$ SUBPROOF. Then $[\Sigma_2/x]\Sigma_3 = \Sigma_3$, $\Delta \cdot [\Sigma_2/x]\Sigma_3 = \Delta \cdot \Sigma_3$, and $[d/x](\Delta \cdot \Sigma_3) = \Delta \cdot \Sigma_3$, and the result holds. ⊳ Case (3) $\Sigma_3 = px$

 \Box

Subproof. Then

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x](px))
$$

\n
$$
= \Delta \cdot ([\Sigma_2 \Gamma^p)
$$

\n
$$
= \Delta \cdot (\bigsqcup_{x \in dom(\Sigma_2)} ([\Sigma_2 \Gamma^1(y)p)y))
$$

\n
$$
= \lceil \Delta \lceil \frac{1}{\chi} \cdot (\bigsqcup_{x \in dom(\Sigma_2)} ([\Sigma_2 \Gamma^1(y)p)y)]
$$

\n
$$
= \bigsqcup_{x \in dom(\Sigma_2)} ([\Delta \Gamma^1(y)] \Sigma_2 \Gamma^1(y)p)y
$$

If $\Delta \cdot \Sigma_2 = d = 0$, then $\bigsqcup_{x \in dom(\Sigma_2)} (\lceil \Delta \lceil^1(y) \rceil \Sigma_2 \lceil^1(y) p) y = 0$. If $\Delta \cdot \Sigma_2 = d > 0$, then $\bigsqcup_{x \in dom(\Sigma_2)} (\lceil \Delta \lceil^1(y) \rceil \Sigma_2 \lceil^1(y) p) y = p$. Therefore $d\Gamma^1 p = \Box$ $\bigsqcup_{x \in dom(\Sigma_2)} (\lceil \Delta \lceil^1(y) \rceil \Sigma_2 \lceil^1(y)p \rceil y.$ $\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \bigsqcup_i$ $\bigcup_{x \in dom(\Sigma_2)} (\lceil \Delta \lceil^1(y) \rceil \Sigma_2 \lceil^1(y)p \rangle y$ $= d \int_0^1 p$ $= \int d\int x \cdot px$ $= dx \cdot px$ $= dx \cdot (\Delta \cdot (px))$ (because $x \notin dom(\Delta))$ $= dx \cdot (\Delta \cdot \Sigma_3)$

And the result holds. ⊳

Case (4) $\Sigma_3 = \Sigma_4 + \Sigma_5$

SUBPROOF. By induction hypothesis on Σ_4 and Σ_5 , we know that $\Delta \cdot ((\Sigma_2/x)\Sigma_4) = dx \cdot (\Delta \cdot \Sigma_4)$, and Δ •($[\Sigma_2/x]\Sigma_5$) = dx •(Δ ⋅ Σ_5). Therefore

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x] (\Sigma_4 + \Sigma_5))
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4 + [\Sigma_2/x] \Sigma_5)
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) + \Delta \cdot ([\Sigma_2/x] \Sigma_5)
$$

\n
$$
= dx \cdot (\Delta \cdot \Sigma_4) + dx \cdot (\Delta \cdot \Sigma_5)
$$
 (by induction hyp.)
\n
$$
= dx \cdot (\Delta \cdot \Sigma_4 + \Delta \cdot \Sigma_5)
$$
 (by definition of $\Delta()$)
\n
$$
= dx \cdot (\Delta \cdot (\Sigma_4 + \Sigma_5))
$$

\n
$$
= dx \cdot (\Delta \cdot \Sigma_3)
$$

And the result holds. ⊳

Case (5) $\Sigma_3 = \Sigma_4 \sqcup \Sigma_5$

SUBPROOF. By induction hypothesis on Σ_4 and Σ_5 , we know that $\Delta \cdot ([\Sigma_2/x]\Sigma_4) = dx \cdot (\Delta \cdot \Sigma_4)$, and Δ •($[\Sigma_2/x]\Sigma_5$) = dx •($\Delta \cdot \Sigma_5$). Therefore

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x] (\Sigma_4 \sqcup \Sigma_5))
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4 \sqcup [\Sigma_2/x] \Sigma_5)
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) \sqcup \Delta \cdot ([\Sigma_2/x] \Sigma_5)
$$

\n
$$
= dx \cdot (\Delta \cdot \Sigma_4) \sqcup dx \cdot (\Delta \cdot \Sigma_5)
$$
 (by induction hyp.)
\n
$$
= dx \cdot (\Delta \cdot \Sigma_4 \sqcup \Delta \cdot \Sigma_5)
$$
 (by definition of $\Delta(_)$)
\n
$$
= dx \cdot (\Delta \cdot (\Sigma_4 \sqcup \Sigma_5))
$$

\n
$$
= dx \cdot (\Delta \cdot \Sigma_3)
$$

And the result holds. ⊳

Case (6) $\Sigma_3 = \Sigma_4 \sqcap \Sigma_5$

SUBPROOF. By induction hypothesis on Σ_4 and Σ_5 , we know that $\Delta \cdot ([\Sigma_2/x]\Sigma_4) = dx \cdot (\Delta \cdot \Sigma_4)$, and $\Delta \cdot ([\Sigma_2/x]\Sigma_5) = dx \cdot (\Delta \cdot \Sigma_5)$. Therefore

$$
\Delta \cdot ([\Sigma_2/x] \Sigma_3) = \Delta \cdot ([\Sigma_2/x] (\Sigma_4 \cap \Sigma_5))
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4 \cap [\Sigma_2/x] \Sigma_5)
$$

\n
$$
= \Delta \cdot ([\Sigma_2/x] \Sigma_4) \cap \Delta \cdot ([\Sigma_2/x] \Sigma_5)
$$

\n
$$
= dx \cdot (\Delta \cdot \Sigma_4) \cap dx \cdot (\Delta \cdot \Sigma_5)
$$
 (by induction hyp.)
\n
$$
= dx \cdot (\Delta \cdot \Sigma_4 \cap \Delta \cdot \Sigma_5)
$$
 (by definition of $\Delta(_)$)
\n
$$
= dx \cdot (\Delta \cdot (\Sigma_4 \cap \Sigma_5))
$$

\n
$$
= dx \cdot (\Delta \cdot \Sigma_3)
$$

And the result holds. ⊳

LEMMA C.5. Let $\Delta \cdot \Sigma = d$ and $x \notin dom(\Sigma) \cup dom(\Delta)$, then $\Delta([\Sigma/x]\tau) = dx(\Delta(\tau))$

PROOF. We prove: let $\Delta \cdot \Sigma' = d \in \text{sens}$ and $x \notin dom(\Sigma') \cup dom(\Delta)$, then $\Delta([\Sigma'/x]\tau) = dx(\Delta(\tau))$. We proceed by induction on τ .

Case (1)
$$
\tau \in \{\mathbb{R}, \mathbb{B}, \text{unit}\}
$$

\nSUBPROOF. Trivial as $\Delta(\tau) = \tau$ and $sx(\tau) = \tau$.
\nCase (2) $\tau = (x : \tau_1) \xrightarrow{\Sigma''} \tau_2$

SUBPROOF.

$$
\Delta([\Sigma'/x]((x:\tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2)) = \Delta((x:[\Sigma'/x]\tau_1 \cdot d') \xrightarrow{[\Sigma'/x]\Sigma''} [\Sigma'/x]\tau_2)
$$
 (by def subst.)
\n
$$
= (x:\Delta([\Sigma'/x]\tau_1 \cdot d')) \xrightarrow{\Delta \cdot([\Sigma'/x]\Sigma'')} \Delta([\Sigma'/x]\tau_2)
$$
 (by def inst.)
\n
$$
= (x:dx(\Delta(\tau_1)) \cdot d') \xrightarrow{\Delta \cdot([\Sigma'/x]\Sigma'')} dx(\Delta(\tau_2))
$$
 (by induction hyp.)
\n
$$
= (x:dx(\Delta(\tau_1)) \cdot d') \xrightarrow{dx(\Delta \cdot \Sigma'')} dx(\Delta(\tau_2))
$$
 (by Lemma 7.4)
\n
$$
= dx((x:\Delta(\tau_1) \cdot d') \xrightarrow{\Sigma''} \Delta(\tau_2))
$$
 (by def subst.)
\n
$$
= dx(\Delta((x:\tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2))
$$
 (by def inst.)

and the result holds. ⊳

Case (3) $\tau = (x : \tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2$ Subproof.

$$
\Delta([\Sigma'/x]((x:\tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2)) = \Delta((x:[\Sigma'/x]\tau_1 \cdot d') \xrightarrow{[\Sigma'/x]\Sigma''} [\Sigma'/x]\tau_2)
$$
 (by def subst.)
\n
$$
= (x:\Delta([\Sigma'/x]\tau_1) \cdot d') \xrightarrow{\Delta([\Sigma'/x]\Sigma'')} \Delta([\Sigma'/x]\tau_2)
$$
 (by def inst.)
\n
$$
= (x:dx(\Delta(\tau_1)) \cdot d') \xrightarrow{\Delta(\Sigma'/x]\Sigma''} dx(\Delta(\tau_2))
$$
 (by induction hyp.)
\n
$$
= (x:dx(\Delta(\tau_1)) \cdot d') \xrightarrow{dx(\Delta \cdot \Sigma'')} dx(\Delta(\tau_2))
$$
 (by Lemma 7.5)
\n
$$
= dx((x:\Delta(\tau_1) \cdot d') \xrightarrow{\Delta \cdot \Sigma''} \Delta(\tau_2))
$$
 (by def subst.)
\n
$$
= dx(\Delta((x:\tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2))
$$
 (by def inst.)

and the result holds. ⊳

Case (4) $\tau = \tau_1^{-\sum_1} \bigoplus_{\substack{2}}^{\sum_2} \tau_2$

 \Box

$$
f_{\rm{max}}
$$

Subproof.

$$
\Delta([\Sigma'/x](\tau_1^{\Sigma_1} \oplus \Sigma_2 \tau_2)) = \Delta([\Sigma'/x]\tau_1^{[\Sigma'/x]\Sigma_1} \oplus^{[\Sigma'/x]\Sigma_2} [\Sigma'/x]\tau_2)
$$
 (by def subst.)
\n
$$
= \Delta([\Sigma'/x]\tau_1)^{\Delta \cdot [\Sigma'/x]\Sigma_1} \oplus^{\Delta \cdot [\Sigma'/x]\Sigma_2} \Delta([\Sigma'/x]\tau_2)
$$
 (by def inst.)
\n
$$
= dx(\Delta(\tau_1))^{(\Delta \cdot [\Sigma'/x]\Sigma_1} \oplus^{\Delta \cdot [\Sigma'/x]\Sigma_2} dx(\Delta(\tau_2))
$$
 (by induction hyp.)
\n
$$
= dx(\Delta(\tau_1))^{dx(\Delta \cdot \Sigma_1)} \oplus^{dx(\Delta \cdot \Sigma_2)} dx(\Delta(\tau_2))
$$
 (by Lemma 7.4)
\n
$$
= dx(\Delta(\tau_1)^{(\Delta \cdot \Sigma_1)} \oplus^{(\Delta \cdot \Sigma_2)} \Delta(\tau_2))
$$
 (by def subst.)
\n
$$
= dx(\Delta(\tau_1^{\Sigma_1} \oplus^{\Sigma_2} \tau_2))
$$
 (by def inst.)

and the result holds. ⊳

Case (5) $\tau = \tau_1^{-\sum_1} \&^{\sum_2} \tau_2$ SUBPROOF. Analogous to $\tau = \tau_1^{-\sum_1} \bigoplus_{\substack{z_2}} \tau_2$ case.

LEMMA C.6. If $\tau < \tau'$ then $\Sigma(\tau) < \Sigma(\tau')$

PROOF. By induction on τ :

Case (1) $\tau = \mathbb{R}$

SUBPROOF. Then $\tau' = \mathbb{R}$ so the result is trivial.

Case (2) $\tau = \mathbb{B}$

SUBPROOF. Then $\tau' = \mathbb{B}$ so the result is trivial.

Case (3) $\tau = \text{unit}$

SUBPROOF. Then $\tau' = \text{unit so the result is trivial.}$

Case (4) $\tau = (x : \tau_1 \cdot d) \xrightarrow{\Sigma'} \tau_2$

SUBPROOF. Then $\tau' = (x : \tau'_1 \cdot d') \xrightarrow{\Sigma''} \tau'_2$ such that $d' <: d, \tau'_1 <: \tau_1, \Sigma' <: \Sigma''$, and $\tau_2 <: \tau'_2$. But $\Sigma((x : \tau_1 \cdot d) \xrightarrow{\Sigma'} \tau_2) = (x : \Sigma(\tau_1) \cdot d) \xrightarrow{\Sigma \cdot \Sigma'} \Sigma(\tau_2)$, then by induction hypotheses $\Sigma(\tau_1') \prec \Sigma(\tau_1)$, and $\Sigma(\tau_2)$ <: $\Sigma(\tau'_2)$. Also by Lemma [C.12,](#page-68-0) $\Sigma \cdot \Sigma'$ <: $\Sigma \cdot \Sigma''$, therefore

 $\Sigma((x:\tau_1\cdot d) \xrightarrow{\Sigma'} \tau_2) = (x:\Sigma(\tau_1)\cdot d) \xrightarrow{\Sigma\cdot\Sigma'} \Sigma(\tau_2) <: (x:\Sigma(\tau'_1)\cdot d') \xrightarrow{\Sigma\cdot\Sigma''} \Sigma(\tau'_2) = \Sigma((x:\tau'_1\cdot d') \xrightarrow{\Sigma''} \tau'_2)$ and the result holds.

Case (5) $\tau = (x : \tau_1 \cdot d) \xrightarrow{\Sigma'} \tau_2$

SUBPROOF. Then $\tau' = (x : \tau_1' \cdot d') \xrightarrow{\Sigma''} \tau_2'$ such that $d' <: d, \tau_1' <: \tau_1, \Sigma' <: \Sigma''$, and $\tau_2 <: \tau_2'$. But $_1$ '*a*) \rightarrow ι_2 such that ι \vee ι , ι_1 \vee ι_1 , \angle \vee \angle \vee and ι_2 \vee ι_2 $\Sigma((x:\tau_1 \cdot d) \xrightarrow{\Sigma'} \tau_2) = (x:\Sigma(\tau_1) \cdot d) \xrightarrow{\Sigma \cdot \Sigma'} \Sigma(\tau_2)$, then by induction hypotheses $\Sigma(\tau_1') < \Sigma(\tau_1)$, and $\Sigma(\tau_2)$ <: Σ(τ_2'). Also by Lemma [C.13,](#page-69-0) Σ·Σ' <: Σ·Σ'', therefore

 $\Sigma((x:\tau_1\cdot d) \xrightarrow{\Sigma'} \tau_2) = (x:\Sigma(\tau_1)\cdot d) \xrightarrow{\Sigma \cdot \Sigma'} \Sigma(\tau_2) \prec : (x:\Sigma(\tau_1')\cdot d') \xrightarrow{\Sigma \cdot \Sigma''} \Sigma(\tau_2') = \Sigma((x:\tau_1'\cdot d') \xrightarrow{\Sigma''} \tau_2')$ and the result holds.

Case (6) $\tau = \tau_1^{-\sum_1} \bigoplus_{\substack{2}}^{\sum_2} \tau_2$

SUBPROOF. Then $\tau' = \tau'_1$ $\Sigma_1' \oplus \Sigma_2'$ τ_2' such that $\tau_1 <: \tau_1', \Sigma_1 <: \Sigma_1', \Sigma_2' <: \Sigma_2',$ and $\tau_2 <: \tau_2'.$ But $\Sigma(\tau_1^{-\Sigma_1} \oplus^{\Sigma_2})$ τ_2) = $\Sigma(\tau_1)$ $\Sigma \cdot \Sigma_1 \oplus \Sigma \cdot \Sigma_2$ $\Sigma(\tau_2)$, then by induction hypotheses $\Sigma(\tau_1)$ <: $\Sigma(\tau_1')$, and $\Sigma(\tau_2)$ <: $\Sigma(\tau_2')$. Also by Lemma [C.12,](#page-68-0) $\Sigma \cdot \Sigma_1 < \Sigma \cdot \Sigma_1'$ and $\Sigma \cdot \Sigma_2 < \Sigma \cdot \Sigma_2'$, therefore

 $\Sigma(\tau_1 \Sigma_1 \oplus \Sigma_2 \tau_2) = \Sigma(\tau_1) \Sigma_1 \Sigma_1 \oplus \Sigma_2 \Sigma_2 \Sigma(\tau_2) \langle \Sigma_1 \Sigma_1 \Sigma_1 \Sigma_2 \Sigma_2 \Sigma_1 \Sigma_2 \Sigma_2 \rangle = \Sigma(\tau_1)$ $\sum_1^{\prime} \bigoplus \sum_2^{\prime} \tau_2^{\prime}$ and the result holds. ⊳

Case (7) $\tau = \tau_1^{-\sum_1} \&^{\sum_2} \tau_2$

 \Box

SUBPROOF. Then $\tau' = \tau'_1$ $\Sigma_1' \& \Sigma_2'$ τ_2' such that $\tau_1 <: \tau_1', \Sigma_1 <: \Sigma_1', \Sigma_2' <: \Sigma_2',$ and $\tau_2 <: \tau_2'.$ But $\Sigma(\tau_1^{-\Sigma_1} \& \Sigma_2)$ τ_2) = $\Sigma(\tau_1)$ $\Sigma \cdot \Sigma_1 \otimes \Sigma^2 \Sigma(\tau_2)$, then by induction hypotheses $\Sigma(\tau_1)$ <: $\Sigma(\tau_1')$, and $\Sigma(\tau_2)$ <: $\Sigma(\tau_2')$. Also by Lemma [C.12,](#page-68-0) $\Sigma \cdot \Sigma_1 < \Sigma \cdot \Sigma_1'$ and $\Sigma \cdot \Sigma_2 < \Sigma \cdot \Sigma_2'$, therefore $\Sigma(\tau_1 \Sigma_1 \& \Sigma_2 \tau_2) = \Sigma(\tau_1) \Sigma_1 \times \Sigma_1 \& \Sigma_2 \Sigma_2 \Sigma(\tau_2) \langle \Sigma_1 \Sigma_1 \Sigma_2 \Sigma_2 \Sigma_1 \Sigma_2 \Sigma_2 \Sigma_2 \rangle = \Sigma(\tau_1')$ \sum_1^{\prime} & \sum_2^{\prime} τ_2^{\prime} and the result holds. ⊳ \Box LEMMA C.7. Let Σ and Σ' Then (1) Σ <: $\Sigma \sqcup \Sigma'$ (2) Σ Π Σ' <: Σ PROOF. By induction of Σ , and noticing that $s \leq s \sqcup s'$, and $s \sqcap s' \leq s$. LEMMA C.8. Let Σ and Σ' Then (1) Σ <: $\Sigma \sqcup \Sigma'$ (2) Σ Π Σ' <: Σ **PROOF.** By definition of the \lt : operator for privacy environments. LEMMA C.9. Let τ and τ' , such that $\tau \sqcup \tau'$ and $\tau \sqcap \tau'$ are defined. Then (1) $\tau < \tau \sqcup \tau'$ (2) $\tau \sqcap \tau' \leq: \tau$ PROOF. Let us prove (1) first by induction by induction on τ : Case (1) $\tau = \mathbb{R}$ SUBPROOF. Then $\tau' = \mathbb{R}$ so the result is trivial. Case (2) $\tau = \mathbb{B}$ SUBPROOF. Then $\tau' = \mathbb{B}$ so the result is trivial. Case (3) $\tau = \text{unit}$ SUBPROOF. Then $\tau' = \text{unit so the result is trivial.}$ Case (4) $\tau = (x : \tau_1 \cdot d) \xrightarrow{\Sigma} \tau_2$ SUBPROOF. Then $\tau' = (x : \tau'_1 \cdot d') \xrightarrow{\Sigma'} \tau'_2$, and $\tau \sqcup \tau' = (x : (\tau_1 \sqcap \tau'_1) \cdot (d \sqcap d')) \xrightarrow{\Sigma \sqcup \Sigma'} (\tau_2 \sqcup \tau'_2)$ By induction hypothesis $(\tau_1 \sqcap \tau_1') < \tau_1$, we know that $d \sqcap d' \leq d$, by Lemma [C.7,](#page-66-0) $\Sigma < \Sigma \sqcup \Sigma'$, and by induction hypothesis $\tau_2 < \tau_2 \sqcup \tau_2'$. Then $(x : \tau_1 \cdot d) \stackrel{\Sigma}{\longrightarrow} \tau_2 < \colon (x : (\tau_1 \sqcap \tau_1') \cdot (d \sqcap d')) \stackrel{\Sigma \sqcup \Sigma'}{\longrightarrow} (\tau_2 \sqcup \tau_2')$ and the result holds. Case (5) $\tau = (x : \tau_1 \cdot d) \xrightarrow{\Sigma'} \tau_2$ SUBPROOF. Then $\tau' = (x : \tau'_1 \cdot d') \xrightarrow{\Sigma'} \tau'_2$, and $\tau \sqcup \tau' = (x : (\tau_1 \sqcap \tau'_1) \cdot (d \sqcap d')) \xrightarrow{\Sigma \sqcup \Sigma'} (\tau_2 \sqcup \tau'_2)$ By induction hypothesis $(\tau_1 \sqcap \tau_1') < \tau_1$, we know that $d \sqcap d' \leq d$, by Lemma [C.8,](#page-66-1) $\Sigma \leq \sqcup \Sigma'$, and by induction hypothesis $\tau_2 < \tau_2 \sqcup \tau_2'$. Then $(x : \tau_1 \cdot d) \xrightarrow{\Sigma} \tau_2 < \tau_1' \cdot (x : (\tau_1 \sqcap \tau_1') \cdot (d \sqcap d')) \xrightarrow{\Sigma \sqcup \Sigma'} (\tau_2 \sqcup \tau_2')$ and the result holds. Case (6) $\tau = \tau_1^{-\sum_1} \bigoplus_{\alpha}^{\sum_2} \tau_2$ SUBPROOF. Then $\tau' = \tau'_1$ $\Sigma'_1 \oplus \Sigma'_2$ τ'_2 , and $\tau \sqcup \tau' = (\tau_1 \sqcup \tau'_1)^{\sum_1 \sqcup \sum'_1} \oplus^{\sum_2 \sqcup \sum'_2} (\tau_2 \sqcup \tau'_2)$. By induction hypotheses $\tau_1 < \tau_1 \sqcup \tau_1'$, and $\tau_2 < \tau_2 \sqcup \tau_2'$, and by Lemma [C.7,](#page-66-0) $\Sigma_1 < \Sigma_1 \sqcup \Sigma_1'$, and $\Sigma_2 < \Sigma_2 \sqcup \Sigma_2'$. Then τ_1' \sum_1^{\prime} \sum_2^{\prime} τ_2^{\prime} \leq : $(\tau_1 \sqcup \tau_1^{\prime})$ \sum_1^{\prime} \sqcup \sum_2^{\prime} τ_2^{\prime} \sqcup τ_2^{\prime} and the result holds. Case (7) $\tau = \tau_1^{-\sum_1} \&^{\sum_2} \tau_2$ SUBPROOF. Analogous to the $\tau = \tau_1^{-\sum_1} \oplus \sum_2^{-1} \tau_2$ case.

Case (8) $\tau = \tau_1^{-\sum_1} \bigoplus_{\substack{2}}^{\sum_2} \tau_2$ SUBPROOF. Analogous to the $\tau = \tau_1^{-\sum_1} \oplus \sum_2^{-1} \tau_2$ case.

LEMMA C.10 (RELATION SUBSUMPTION/WEAKENING). Consider $d \le d'$ and $\sigma \le \sigma'$ then

(1) If $(v_1, v_2) \in \mathcal{V}_d^k[\![\sigma]\!]$, then $(v_1, v_2) \in \mathcal{V}_d^k[\![\sigma']\!]$ (2) If $(e_1, e_2) \in \mathcal{E}_d^k[\![\sigma]\!],$ then $(e_1, e_2) \in \mathcal{E}_{d'}^k[\![\sigma']\!]$ (3) If $(e_1, e_2) \in \mathcal{E}_{p}^k[\sigma]$, then $(e_1, e_2) \in \mathcal{E}_{p'}^k[\sigma']$

Proof. We only present intersting cases. We first prove (1) by induction on τ :

Case (1) $\sigma = \mathbb{R}$

SUBPROOF. Then $v_1 = r_1$, $v_2 = r_2$, $\sigma' = \mathbb{R}$, and $(r_1, r_2) \in \mathcal{V}_d^k[\mathbb{R}]$, i.e. $|r_1 - r_2| \leq s$. But if $s \leq s'$, then it is easy to see that $|r_1 - r_2| \leq s'$, therefore $(r_1, r_2) \in \mathcal{V}_{d'}^k[\mathbb{R}]$ and the result holds. ◄ Case (2) σ = unit

SUBPROOF. Trivial as $\sigma' = \text{unit}$ and $(v_1, v_2) \in \mathcal{V}_d^k$ [[unit]] does not depend on s, i.e. $\forall s', (v_1, v_2) \in$ $\mathcal{V}^k_{d'}$ ′JunitK. ⊳

Case (3) $\sigma = (x : \sigma_1 \cdot d_2) \xrightarrow{\Sigma_1 \cdot \Sigma_2 + d_1 x} \sigma_2$

SUBPROOF. Then $\sigma' = (x : \sigma'_1 \cdot d'_2) \xrightarrow{\sum_1 \cdot \sum'_2 + d'_1 x} \sigma'_2$ where $\sigma'_1 \prec : \sigma_1, \Sigma_2 \prec : \Sigma'_2, d_1 \leq d'_1, d'_2 \prec d_2$ and $\sigma_2 \lt: \sigma'_2$.

Also $v_1 = \langle \lambda^s x. e_1, \gamma_1 \rangle$, $v_2 = \langle \lambda^s x. e_2, \gamma_2 \rangle$, and $(\langle \lambda^s x. e_1, \gamma_1 \rangle, \langle \lambda^s x. e_2, \gamma_2 \rangle) \in \mathcal{V}_d \left[(x : \sigma_1 \cdot d_2) \xrightarrow{\Sigma_1 \cdot \Sigma_2 + d_1 x} \sigma_2 \right]$.

We have to prove that $(\langle \lambda^s x. e_1, \gamma_1 \rangle, \langle \lambda^s x. e_2, \gamma_2 \rangle) \in \mathcal{V}_{d'}^k[(x : \sigma'_1 \cdot d'_2) \xrightarrow{\Sigma_1 \cdot \Sigma'_2 + d'_1 x} \sigma'_2],$ i.e. for any $j < k$, $(v_1, v_2) \in \mathcal{V}_{d_3}^j[\![\sigma'_1]\!], d_3 \le d'_2 \text{ then } (y_1[x \mapsto v_1] \vdash e_1, y_2[x \mapsto v_2] \vdash e_2) \in \mathcal{E}_{d' + \sum_1 \cdot \sum_2' + d'_1 d_3}^j[\![d_3x(\sigma'_2)]\!].$

We know that $d_3 \leq d'_2 \leq d_2$, then by induction hypothesis on $(v_1, v_2) \in \mathcal{V}_{d_3}^j[\sigma'_1]$, we know that $(v_1, v_2) \in \mathcal{V}_{d_3}^j[\![\sigma_1]\!]$. Then we instantiate the premise with $d'' = d_3$ and v_1 and v_2 , so we know that $(\gamma_1[x \mapsto v_1] \mapsto e_1, \gamma_2[x \mapsto v_2] \mapsto e_2) \in \mathcal{E}^j_{d+\sum_1 \sum_2 + d_1 d_3}[[d_3x(\sigma_2)]]$. By Lemma [C.6,](#page-65-0) $d_3x(\sigma_2) \leq id_3x(\sigma'_2)$, by Lemma [C.12,](#page-68-0) $\Sigma_1 \cdot \Sigma_2 \leq \Sigma_1 \cdot \Sigma_2'$, and as $d + \Sigma_1 \cdot \Sigma_2 + d_1 d_3 \leq d' + \Sigma_1 \cdot \Sigma_2' + d'_1 d_3$, then by induction hypothesis we know that $(\gamma_1[x \mapsto v_1] \vdash e_1, \gamma_2[x \mapsto v_2] \vdash e_2) \in \mathcal{E}^j_{d'+\sum'_1 \cdot \sum'_2 + d'_1 d_3}[[d_3x(\sigma'_2)]]$ and the result holds.

Case (4) $\sigma = (x : \sigma_1 \cdot d_2) \xrightarrow{\Sigma_1 \cdot \Sigma_2} \sigma_2$ SUBPROOF. Then $\sigma' = (x : \sigma'_1 \cdot d'_2) \xrightarrow{\Sigma_1 \cdot \Sigma'_2} \sigma'_2$ where $\sigma'_1 \lt: \sigma_1, \Sigma_2 \lt: \Sigma'_2, d'_2 \lt d_2$ and $\sigma_2 \lt: \sigma'_2$. Also $v_1 = \langle \lambda^p x . e_1, \gamma_1 \rangle$, $v_2 = \langle \lambda^p x . e_2, \gamma_2 \rangle$, and $(\langle \lambda^p x . e_1, \gamma_1 \rangle, \langle \lambda^p x . e_2, \gamma_2 \rangle) \in \mathcal{V}_d \llbracket (x : \sigma_1 \cdot d_2) \xrightarrow{\Sigma_1 \cdot \Sigma_2} \sigma_2 \rrbracket$.

We have to prove that $(\langle \lambda^p x e_1, y_1 \rangle, \langle \lambda^s x e_2, y_2 \rangle) \in \mathcal{V}_{d'}^k[(x : \sigma'_1 \cdot d'_2) \xrightarrow{\Sigma_1 \cdot \Sigma'_2} \sigma'_2],$ i.e. for any $j < k$, $(v_1, v_2) \in \mathcal{V}_{d_3}^j[\![\sigma'_1]\!], d_3 \le d'_2$ then $(y_1[x \mapsto v_1] \vdash e_1, y_2[x \mapsto v_2] \vdash e_2) \in \mathcal{E}_{\lceil d' \rceil^{\infty} + \sum_2^{\infty}}^j[\![d_3x(\sigma'_2)]\!].$

We know that $d_3 \leq d'_2 \leq d_2$, then by induction hypothesis on $(v_1, v_2) \in \mathcal{V}_{d_3}^{\perp}[\sigma'_1]$, we know that $(v_1, v_2) \in \mathcal{V}_{d_3}^j[\![\sigma_1]\!]$. Then we instantiate the premise with $d'' = d_3$ and v_1 and v_2 , so we know that $(\gamma_1[x \mapsto v_1] \vdash e_1, \gamma_2[x \mapsto v_2] \vdash e_2) \in \mathcal{E}^j_{\lfloor d \rfloor^{\infty} + \sum_1 \sum_2 \lfloor d_3 x(\sigma_2) \rfloor}$. By Lemma [C.6,](#page-65-0) $d_3x(\sigma_2) \leq d_3x(\sigma_2')$, by Lemma [C.13,](#page-69-0) $\Sigma_1 \cdot \Sigma_2 \leq \Sigma_1 \cdot \Sigma_2'$, then $d\Gamma^{\infty} + \Sigma_1 \cdot \Sigma_2' \leq d'\Gamma^{\infty} + \Sigma_1 \cdot \Sigma_2'$. The result follows from induction hypothesis (3). ⊳

 \Box

Case (5) $\sigma = \sigma_1$ $s_1 \oplus s_2$ σ_2 SUBPROOF. Then $\sigma' = \sigma'_1^{s'_1} \oplus_{s'_2}^{s'_2} \sigma'_2$ where $\sigma_1 \leq s'_1, s_1 \leq s'_1, s_2 \leq s'_2$, and $\sigma_2 \leq s'_2$. We proceed by case analysis on (v_1, v_2) : Case (a) $(v_1, v_2) = (\text{inl } v'_1, \text{inl } v'_2)$ SUBPROOF. Then we know that $(\text{inl } v'_1, \text{inl } v'_2) \in \mathcal{V}_{d+s_1}^k[\![\sigma_1]\!]$, then by induction hypothesis using $s + s_1 \leq s' + s'_1$ and $\sigma_1 \leq s_2$, then $(\text{inl } v'_1, \text{inl } v'_2) \in \mathcal{V}_{s'+s'_1}^k[\sigma'_1]$ and therefore $(\text{inl } v'_1, \text{inl } v'_2) \in$ $\mathcal{V}_{s'}^k$ $\llbracket \sigma'_1 \, s'_1 \oplus s'_2 \, \sigma'_2 \rrbracket$ and the result holds. Case (b) $(v_1, v_2) = (\text{inr } v_1', \text{inr } v_2')$ Subproof. Analogous to previous case. ⊳ Case (c) $(v_1, v_2) = (\text{inl } v_1', \text{inr } v_2')$ and $(v_1, v_2) = (\text{inr } v_1', \text{inl } v_2')$ SUBPROOF. Then $s = \infty$ and as $s \leq s'$, therefore $s' = \infty$, and the result holds immediately. ⊳

Case (6) $\sigma = \sigma_1^{s_1} \&^{s_2} \sigma_2$

SUBPROOF. Then $\sigma' = \sigma'_1 s'_1 \& s'_2 \ \sigma'_2$ where $\sigma_1 \prec : \sigma'_1, s_1 \leq s'_1, s_2 \leq s'_2$, and $\sigma_2 \prec : \sigma'_2$. We know that $(v_1, v_2) = (\langle v_{11}, v_{12} \rangle, \langle v_{21}, v_{22} \rangle)$, such that $(v_{11}, v_{21}) \in \mathcal{V}_{d+s_1}^k[\sigma_1]$ and $(v_{12}, v_{22}) \in \mathcal{V}_{d+s_2}^k[\sigma_2]$. By induction hypotheses we know that $(v_{11}, v_{21}) \in \mathcal{V}^k_{s'+s'_1}[\![\sigma'_1]\!]$ and $(v_{12}, v_{22}) \in \mathcal{V}^k_{s'+s'_2}[\![\sigma'_2]\!]$, and therefore $(\langle v_{11}, v_{12} \rangle, \langle v_{21}, v_{22} \rangle) \in \mathcal{V}_{s'}^k[\sigma_1' {\,}^s_1' \&^s_2' {\,} \sigma_2']$ and the result holds.

Now let us prove (2). We know that if $\gamma_1 \vdash e_1 \Downarrow v_1 \wedge \gamma_2 \vdash e_2 \Downarrow v_2$ then $(v_1, v_2) \in \mathcal{V}_d^{k-j}[\![\sigma]\!]$. We have to prove that $(v_1, v_2) \in \mathcal{V}_{d'}^{k-j}[\![\sigma']\!]$, which follows from (1).

Now let us prove (3). We know that $\forall S \subseteq val^k_*$, if $Pr[y_1 \vdash e_1 \Downarrow^k S] \wedge Pr[y_2 \vdash e_2 \Downarrow^k S]$, then $Pr[y_1 \vdash e_2 \Downarrow^k S]$ $e_1 \downarrow^k S \leq e^{\rho \cdot \epsilon} \Pr[\gamma_2 + e_2 \downarrow^k S] + \rho \cdot \delta$ and $\Pr[\gamma_1 + e_2 \downarrow^k S] \leq e^{\rho \cdot \epsilon} \Pr[\gamma_2 + e_1 \downarrow^k S] + \rho \cdot \delta$. We have to prove that, if $Pr[y_1 \in e_1 \cup k] \cap Pr[y_2 \in e_2 \cup k]$, then $Pr[y_1 \in e_1 \cup k] \leq e^{p' \cdot \epsilon} Pr[y_2 \in e_2 \cup k] \cap Pr[y_1 \in e_1 \cup k]$ and $Pr[y_1 \vdash e_2 \Downarrow^k S] \leq e^{p' \cdot \epsilon} Pr[y_2 \vdash e_1 \Downarrow^k S] + p' \cdot \delta.$

But notice that as $p \in \leq p' \in$, then $e^{p \cdot \epsilon} \leq e^{p' \cdot \epsilon}$, and $e^{p \cdot \epsilon} \Pr[\gamma_2 \vdash e_2 \Downarrow^k S] \leq e^{p' \cdot \epsilon} \Pr[\gamma_2 \vdash e_2 \Downarrow^k S]$. We also know that $p.\delta \leq p'.\delta$, and the result follows.

LEMMA C.11. Consider $k' \leq k$ then

(1) If $(v_1, v_2) \in \mathcal{V}_s^k[\![\sigma]\!]$, then $(v_1, v_2) \in \mathcal{V}_s^{k'}[\![\sigma]\!]$ (2) If $(e_1, e_2) \in \mathcal{E}_s^k[\![\sigma]\!]$, then $(e_1, e_2) \in \mathcal{E}_s^k'[\![\sigma]\!]$ (3) If $(e_1, e_2) \in \mathcal{E}_{p}^k[\![\sigma]\!]$, then $(e_1, e_2) \in \mathcal{E}_{p}^{k'}[\![\sigma]\!]$

PROOF. By induction on k .

LEMMA C.12. Let $dom(\Sigma) \subseteq dom(\Delta')$, then $\forall \Sigma''$, $\Sigma < \colon \Sigma''$, then $\Delta' \cdot \Sigma \leq \Delta' \cdot \Sigma''$.

PROOF. By induction on Σ .

Case (1) $\Sigma = \emptyset$

SUBPROOF. Trivial as $\Sigma'' = \emptyset$, therefore $0 \le 0$.

Case (2)
$$
\Sigma = \Sigma_1 + dx
$$

SUBPROOF. Let $\Sigma'' = \Sigma'_1 + d'x$ such that $d \leq d'$, then we have to prove that $\Delta' \cdot \Sigma_1 + d\Delta'(x) \leq$ $\Delta' \cdot \Sigma_1' + d' \Delta'(x)$, but we know by induction hypothesis that $\Delta' \cdot \Sigma_1 \leq \Delta' \cdot \Sigma_1'$ and $d\Delta'(x) \leq d' \Delta'(x)$, so the result holds immediately. ⊳

Case (3) $\Sigma = \Sigma_1 + d$

SUBPROOF. Let $\Sigma'' = \Sigma'_1 + d'$ such that $d \le d'$, then we have to prove that $\Delta' \cdot \Sigma_1 + d \le \Delta' \cdot \Sigma'_1 + d'$, but we know by induction hypothesis that $\Delta' \cdot \Sigma_1 \leq \Delta' \cdot \Sigma'_1$, so the result holds immediately.

 \Box

LEMMA C.13. Let $dom(\Sigma) \subseteq dom(\Delta)$, then $\forall \Sigma', \Sigma <: \Sigma'$, then $\Delta \cdot \Sigma \leq \Delta \cdot \Sigma'$.

PROOF. By definition of $\Sigma <: \Sigma'$. The contract of the contract
The contract of the contract o

Lemma C.14. .

(1) If $\Gamma : \Delta \vdash e_1 : \tau : \Sigma$ and $\Gamma : \Delta \vdash e_2 : \tau : \Sigma$, then $(\gamma_1 \vdash e_1 \gamma_2 \vdash e_2) \in \mathcal{E}_{\infty}[[\Delta'(\tau)]]$. (2) If Γ ; $\Delta \vdash e_1 : \tau$; Σ and Γ ; $\Delta \vdash e_2 : \tau$; Σ , then $(y_1 \vdash e_1y_2 \vdash e_2) \in \mathcal{E}_{\infty}[\Delta'(\tau)]$.

PROOF. By induction on τ .

LEMMA C.15. If $v_1 \approx^k v_2$ and $v_2 \approx^k v_3$, then $v_1 \approx^k v_3$.

Proof. By induction on $v_1 \approx^k v_2$, and then induction on $v_2 \approx^k v_1$ v_3 .

LEMMA C.16. $\forall j \leq k \ v_1 \approx^k v_2$ then $v_1 \approx^{k-j} v_2$.

Proof. By induction on relation $v_1 \approx^k$ v_2 .

LEMMA C.17. Let $j \leq k$, $[\![e_1]\!]_{\gamma_1}^k = [\![e'_1]\!]_{\gamma_1}^k$, $[\![e_2]\!]_{\gamma_2}^k = [\![e'_2]\!]_{\gamma_2}^j$, and $(\gamma_1 \vdash e'_1, \gamma_2 \vdash e'_2) \in \mathcal{E}_p^j[\![\tau]\!]$, then $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_2) \in \mathcal{E}_{p}^k[\![\tau]\!].$

PROOF. We know that $\forall S \subseteq val^j_*$, then $\sum_{v \in S} [e'_1]_{y_1}^j v \leq e^{p \cdot \epsilon} \sum_{v \in S} [e'_2]_{y_2}^j v + p \cdot \delta$, and we have to prove that $\forall S \subseteq val^k_*$, then $\sum_{v \in S} [\![e_1]\!]^k_{Y_1} v \leq e^{p.\epsilon} \sum_{v \in S} [\![e_2]\!]^k_{Y_2} v + p.\delta$. By weakening lemma [C.16,](#page-69-1) $S \subseteq$ val_*^j , $j \leq k$, and as $[\![e_i]\!]_{Y_i}^k = [\![e'_i]\!]_{Y_i}^j$, then we have to prove that $\sum_{v \in S} [\![e'_1]\!]_{Y_i}^j v \leq e^{p \cdot \epsilon} \sum_{v \in S} [\![e'_2]\!]_{Y_2}^k v + p \cdot \delta$ and the result holds.

To prove the fundamental property we need to prove it along Lemma [7.3.](#page-41-2)

Theorem C.18 (Metric Preservation).

(1) $\Gamma, \Delta \vdash e : \tau : \Sigma \Rightarrow \forall k \geq 0, \forall \Sigma' \sqsubseteq \Delta, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Sigma'}^{k-1}[\Gamma], (\gamma_1 \vdash e, \gamma_2 \vdash e) \in \mathcal{E}_{\Sigma', \Sigma}^k[\Sigma'(\tau)]$ (2) $\Gamma, \Delta \vdash e : \tau : \Sigma \Rightarrow \forall k \geq 0, \forall \Sigma' \sqsubseteq \Delta, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Sigma'}^{\overline{k}-1}[\![\Gamma]\!], (\gamma_1 \vdash e, \gamma_2 \vdash e) \in \mathcal{E}_{\Sigma', \Sigma}^{\overline{k}}[\![\Sigma'(\tau)]\!]\]$ (3) Let Δ_{\emptyset} , such that $\Delta_{\emptyset}(x) = 0$, for all $x \in FV(\tau)$. If $(v_1, v_2) \in V_0^k[\Delta_{\emptyset}(\tau)]$ then $v_1 \approx^k v_2$.

PROOF. We prove all three parts using induction on k first.

We start by proving Part (1) by induction on k and the typing derivation.

Case (1) $\Gamma; \Delta \vdash r : \mathbb{R}$; \varnothing

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 + r, \gamma_2 + r) \in \mathcal{E}_{\Delta' \cdot \emptyset}[\![\Delta'(\mathbb{R})]\!],$ for $\Delta' \sqsubseteq \Delta$. Notice that $\Delta' \oslash = 0$ and $\gamma_1(r) = \gamma_2(r) = r$. Then we have to prove that $(r, r) \in \mathcal{V}_0^k[\mathbb{R}]$, i.e. $|r - r| \leq 0$ which is direct.

Case (2) Γ ; Δ + e_1 + e_2 : \mathbb{R} ; Σ_1 + Σ_2

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash e_1 + e_2, \gamma_2 \vdash e_1 + e_2) \in \mathcal{E}_{\Delta' \cdot (\Sigma_1 + \Sigma_2)}^k[\![\Delta'(\mathbb{R})]\!],$ for $\Delta' \sqsubseteq \Delta$. By induction hypotheses

 $\Gamma; \Delta \vdash e_1 : \mathbb{R}$; $\Sigma_1 \Rightarrow (\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'(\mathbb{R})]$ and $\Gamma; \Delta \vdash e_2 : \mathbb{R}$; $\Sigma_2 \Rightarrow (\gamma_1 \vdash e_2, \gamma_2 \vdash e_2)$ $(e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\mathbb{R})]$ for some $j_1 \leq k$. By unfolding $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k [\Delta'(\mathbb{R})]$, we know that if γ_1 ⊢ $e_1 \Downarrow^{j_1} r_{11}$ and γ_2 ⊢ $e_1 \Downarrow^{j_1} r_{12}$ then $(r_{11}, r_{12}) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j_1}[\mathbb{R}]$, where $|r_{11} - r_{12}| \leq \Delta' \cdot \Sigma_1$.

Also, by unfolding $(y_1 \vdash e_2, y_2 \vdash e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\mathbb{R})]$, if $y_1 \vdash e_2 \Downarrow^{j_2} r_{21}$ and $y_2 \vdash e_2 \Downarrow^{j_2} r_{22}$ then $(r_{21}, r_{22}) \in \mathcal{V}_{\Delta' \cdot \Sigma_2}^{k-j_1-j_2} [\![\mathbb{R}]\!],$ where $|r_{21} - r_{22}| \leq \Delta' \cdot \Sigma_2$.

Then if $y_1 + e_1 + e_2 \Downarrow^{j_1+j_2+1} r'_1$ and $y_2 + e_1 + e_2 \Downarrow^{j_1+j_2+1} r'_2$, where $r'_1 = r_{11} + r_{21}$ and $r'_2 = r_{12} + r_{22}$, we have to prove that $(r'_1, r'_2) \in V^{\frac{k-j_1-j_2-1}{\lambda}[\mathbb{R}],}$ i.e. $|(r_{11} + r_{21}) - (r_{12} + r_{22})| \leq \Delta' \cdot (\Sigma_1 + \Sigma_2)$.

Notice that $|(r_{11} + r_{21}) - (r_{12} + r_{22})| = |(r_{11} - r_{12}) + (r_{21} - r_{22})|$, and by the triangle inequality of the

absolute value, $|(r_{11} - r_{12}) + (r_{21} - r_{22})| \le |(r_{11} - r_{12})| + |(r_{21} - r_{22})|$. Also as $|r_{11} - r_{12}| \le \Delta' \cdot \Sigma_1$ and $|r_{21} - r_{22}| \leq \Delta' \cdot \Sigma_2$, then $|(r_{11} - r_{12})| + |(r_{21} - r_{22})| \leq \Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_2$. By Lemma [C.1,](#page-52-1) $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_2 =$ $\Delta' \cdot (\Sigma_1 + \Sigma_2)$, therefore $|(r_{11} + r_{21}) - (r_{12} + r_{22})| \leq \Delta' \cdot (\Sigma_1 + \Sigma_2)$ and the result holds.

Case (3) $\Gamma; \Delta \vdash e_1 * e_2 : \mathbb{R}$; $\infty(\Sigma_1 + \Sigma_2)$

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash e_1 * e_2, \gamma_2 \vdash e_1 * e_2) \in \mathcal{E}_{\Delta' \cdot \infty(\Sigma_1 + \Sigma_2)}^k[\![\Delta'(\mathbb{R})]\!],$ for $\Delta' \sqsubseteq \Delta$. By induction hypotheses

 $\Gamma \vdash e_1 : \mathbb{R}$; $\Sigma_1 \Rightarrow (\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'(\mathbb{R})]$ and $\Gamma \vdash e_2 : \mathbb{R}$; $\Sigma_2 \Rightarrow (\gamma_1 \vdash e_2, \gamma_2 \vdash e_2)$ $(e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\mathbb{R})]$ for $j_1 \leq k$. By unfolding $(\gamma_1 + e_1, \gamma_2 + e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k [\Delta'(\mathbb{R})]$, we know that if $\gamma_1 \vdash e_1 \Downarrow^{j_1} r_{11}$ and $\gamma_2 \vdash e_1 \Downarrow^{j_1} r_{12}$ then $(r_{11}, r_{12}) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j} [\mathbb{R}]$, where $|r_{11} - r_{12}| \leq \Delta' \cdot \Sigma_1$.

Also, by unfolding $(\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\mathbb{R})]$, if $\gamma_1 \vdash e_2$ $\Downarrow^{j_2} r_{21}$ and $\gamma_2 \vdash e_2$ $\Downarrow^{j_2} r_{22}$ then \sum_{2} $(r_{21}, r_{22}) \in \mathcal{V}_{\Delta' \cdot \Sigma_2}^{k-j_1-j_2} [\![\mathbb{R}]\!], \text{where } |r_{21} - r_{22}| \leq \Delta' \cdot \Sigma_2.$

Then if $\gamma_1 + e_1 * e_2 \Downarrow^{j_1+j_2+1} r'_1$ and $\gamma_2 + e_1 * e_2 \Downarrow^{j_1+j_2+1} r'_2$, where $r'_1 = r_{11} * r_{21}$ and $r'_2 = r_{12} * r_{22}$, we have to prove that $(r'_1, r'_2) \in \mathcal{VV}_{\Delta' \cdot \infty(\Sigma_1 + \Sigma_2)}^{\kappa - j_1 - j_2 - 1}[\mathbb{R}],$ i.e. $|(r_{11} \cdot r_{21}) - (r_{12} \cdot r_{22})| \leq \Delta' \cdot \infty(\Sigma_1 + \Sigma_2).$

Notice that $\Delta' \cdot \infty(\Sigma_1 + \Sigma_2) = \infty(\Delta' \cdot (\Sigma_1 + \Sigma_2)) = s$. There are two cases to analyze, where if $s = \infty$ then the result holds immediately. Let us suppose that $s = 0$. Then by Lemma [C.1,](#page-52-1) $\Delta'(\Sigma_1 + \Sigma_2)$ = $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_1$, also notice that $|r_{11} - r_{12}| \leq \Delta' \cdot \Sigma_1$ and $|r_{21} - r_{22}| \leq \Delta' \cdot \Sigma_2$, then $0 \leq \Delta' \cdot \Sigma_1$ and $0 ≤ Δ'·Σ₂$. Therefore if $Δ'·Σ₁ + Δ'·Σ₁ = 0$, then $Δ'·Σ₁ = 0$ and $Δ'·Σ₂ = 0$. This means that $r₁₁ = r₁₂$ and $r_{21} = r_{22}$, thus $r_{11} * r_{21} = r_{12} * r_{22}$, $|(r_{11} * r_{21}) - (r_{12} * r_{22})| = 0$, and the result holds.

Case (4)
$$
\Gamma
$$
; $\Delta \vdash e_1 \le e_2 : \mathbb{B}$; $\infty(\Sigma_1 + \Sigma_2)$

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash e_1 \leq e_2, \gamma_2 \vdash e_1 \leq e_2) \in \mathcal{E}_{\Delta' \cdot \infty(\Sigma_1 + \Sigma_2)}^k[\![\Delta'(\mathbb{B})]\!],$ for $\Delta' \sqsubseteq \Delta$. By induction hypotheses

 $\Gamma \vdash e_1 : \mathbb{R} : \Sigma_1 \Rightarrow (\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'(\mathbb{B})]$ and $\Gamma \vdash e_2 : \mathbb{R} : \Sigma_2 \Rightarrow (\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'(\mathbb{B})]$ $\mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\![\Delta'(\mathbb{B})]\!]$, for some $j_1 \leq k$. By unfolding $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k [\![\Delta'(\mathbb{B})]\!]$, we know that if $\gamma_1 \vdash e_1 \Downarrow^{j_1} r_{11}$ and $\gamma_2 \vdash e_1 \Downarrow^{j_1} r_{12}$ then $(r_{11}, r_{12}) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j_1} [\mathbb{R}]$, where $|r_{11} - r_{12}| \leq \Delta' \cdot \Sigma_1$.

Also, by unfolding $(y_1 \vdash e_2, y_2 \vdash e_2) \in \mathcal{V}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\mathbb{B})]$, if $y_1 \vdash e_2 \Downarrow^{j_2} r_{21}$ and $y_2 \vdash e_2 \Downarrow^{j_2} r_{22}$ then $(r_{21}, r_{22}) \in \mathcal{V}_{\Delta' \cdot \Sigma_2}^{k-j_1-j_2} [\![\mathbb{R}]\!], \text{where } |r_{21} - r_{22}| \leq \Delta' \cdot \Sigma_2.$

Then if $\gamma_1 \vdash e_1 \leq e_2 \Downarrow^{j_1+j_2+1} b_1$ and $\gamma_2 \vdash e_1 \leq e_2 \Downarrow^{j_1+j_2+1} b_2$, where $b_i \in \{\text{inl t}, \text{inr t t}\}$, we have to prove that $(b_1, b_2) \in \mathcal{V}^{k-j_1-j_2-1}_{\Delta' \cdot \infty(\Sigma_1 + \Sigma_2)}[\mathbb{B}].$

Notice that $\Delta' \cdot \infty(\Sigma_1 + \Sigma_2) = \infty(\Delta' \cdot (\Sigma_1 + \Sigma_2)) = s$. There are two cases to analyze, if $s = \infty$ or $s = 0$. If $s = \infty$ and $b_1 \neq b_2$ then the result holds immediately. If $s = \infty$ and $b_1 = b_2$, let us suppose $b_1 = \text{inl }$ tt (the other case is analogous), then we have to prove that (inl tt, inl tt) \in $\mathcal{V}_{\infty}^{k-j_1-j_2-1}$ [unit], but this is direct as $(\mathsf{tt}, \mathsf{tt}) \in \mathcal{V}_{\infty}^{k-j_1-j_2-1}$ [unit]. Let us suppose that $s = 0$. Then by Lemma [C.1,](#page-52-1) $\Delta' \cdot (\Sigma_1 + \Sigma_2) = \Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_1$, also notice that $|r_{11} - r_{12}| \leq \Delta' \cdot \Sigma_1$ and $|r_{21} - r_{22}| \leq \Delta' \cdot \Sigma_2$, then $0 \leq \Delta' \cdot \Sigma_1$ and $0 \leq \Delta' \cdot \Sigma_2$. Therefore if $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_1 = 0$, then $\Delta' \cdot \Sigma_1 = 0$ and $\Delta' \cdot \Sigma_2 =$ 0. This means that $r_{11} = r_{12}$ and $r_{21} = r_{22}$, thus $r_{11} \le r_{21} = r_{12} \le r_{22}$. Then $b_1 = b_2$, let us suppose $b_1 = \text{inl}$ tt (the other case is analogous), then we have to prove that (inl tt, inl tt) \in $\mathcal{V}_0^{k-j_1-j_2-1}$ [unit], but this is direct as $(\texttt{tt}, \texttt{tt}) \in \mathcal{V}_0^{k-j_1-j_2-1}$ [unit].

Case (5) Γ ; $\Delta \vdash x : \tau$; x

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 + x, \gamma_2 + x) \in \mathcal{E}_{\Delta', x}^k[\![\Delta'(\tau)]\!],$ where $\tau = \Gamma(x)$, for $\Delta' \sqsubseteq \Delta$. Notice that $\Delta' \cdot x = \Delta' \cdot 1x = \Delta'(\overline{x})$, therefore we have to prove that $(\gamma_1 \vdash x, \gamma_2 \vdash \overline{x})$ $(x) \in \mathcal{V}_{\Delta'(\chi)}^{k-j}[\Delta'(\Gamma(x))]$. But $\gamma_1 \vdash x \Downarrow^1 \gamma_1(x)$ and $\gamma_2 \vdash x \Downarrow^1 \gamma_2(x)$ therefore we have to prove that $(\gamma_1(x), \gamma_2(x)) \in \mathcal{V}_{\Delta'(\chi)}^{k-1}[\![\Delta'(\Gamma(x))]$. The result is direct as by definition of $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!]$, we know that $(\gamma_1(x), \gamma_2(x)) \in \mathcal{V}_{\Delta'(x)}^{k-1}[\![\Delta'(\Gamma(x))]$.

Case (6) $\Gamma; \Delta \vdash \lambda^s(x : \tau_1 \cdot s_1)$. $e' : (x : \tau_1 \cdot s_1) \xrightarrow{\Sigma'' + s'x} \tau_2$; \varnothing SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!],$

 $(\gamma_1 \vdash \lambda^s(x : \tau_1 \cdot s_1) \cdot e', \gamma_2 \vdash \lambda^s(x : \tau_1 \cdot s_1) \cdot e') \in \mathcal{E}_{\Delta' \cdot \varnothing}^k[\Delta'(\tau_1 \cdot s_1) \xrightarrow{\Delta' \cdot \Sigma'' + s'x} \Delta'(\tau_2)]$, for $\Delta' \sqsubseteq \Delta$. Notice that $\Delta' \cdot \emptyset = 0$, that $\Delta'((x : \tau_1 \cdot s_1) \xrightarrow{\Sigma'' + s'x} \tau_2) = (x : \Delta'(\tau_1) \cdot s_1) \xrightarrow{\Delta' \cdot \Sigma'' + s'x} \Delta'(\tau_2)$ (as $x \notin dom(\Delta'),$) and that lambdas reduce to closures, therefore we have to prove that

 $(\langle \lambda^s(x : \tau_1 \cdot s_1), e', \gamma_1 \rangle, \langle \lambda^s(x : \tau_1 \cdot s_1), e', \gamma_2 \rangle) \in \mathcal{V}_0^{k-1}[[x : \Delta'(\tau_1) \cdot s_1) \xrightarrow{\Delta' \cdot \Sigma'' + s'x} \Delta'(\tau_2)]]$ Note that as $\Gamma, x : \tau_1; \Delta + s_1x + e' : \tau_2; \Sigma'' + s'x$ and $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\Gamma],$ then $dom(\Sigma'') \subseteq$ $dom(\Delta')$, therefore $\Delta' \cdot \Sigma'' \in \text{ sens}$ (the result is a scalar). Consider $s'' \leq s_1, v_1$ and v_2 such that $(v_1, v_2) \in \mathcal{V}_{s''}^j[\Delta'(\tau_1)]$ for some $j < k$. We have to prove that $(y_1, x \mapsto v_1 + e', y_2, x \mapsto v_2 + e') \in$ $\mathcal{E}_{\Delta', \Sigma'' + s's''}^{j}[[s''x(\Delta'(\tau_2))]]$. Notice that by Lemma [C.2](#page-55-1) $s''x(\Delta'(\tau_2)) = (\Delta' + s''x)(\tau_2)$, therefore we have $''+s$ to prove that $(\gamma_1, x \mapsto v_1 \vdash e', \gamma_2, x \mapsto v_2 \vdash e') \in \mathcal{E}_{\Delta' \cdot \Sigma'' + s's''}^{\mathcal{J}}[[(\Delta' + s''x)(\tau_2)]]$.

to prove that $(y_1, x \mapsto v_1 \in e$, $y_2, x \mapsto v_2 \in e$ $) \in C_{\Delta', \Sigma'' + s's''}$ $[(\Delta + s \ x)(\tau_2)]$.
By induction hypothesis on $\Gamma, x : \tau_1; \Delta + s_1x + e' : \tau_2; \Sigma'' + s'x$, and choosing $\Sigma^{\chi} = \Delta' + s''x$, we know that $\forall \gamma_1, \gamma_2, (\gamma_1, \gamma_2) \in \mathcal{G}_{\mathcal{L}}^{j-1}[\![\Gamma, x : \tau_1]\!]$ then $(\gamma_1 \vdash e', \gamma_2 \vdash e') \in \mathcal{E}_{\Sigma^{\chi} \cdot (\Sigma^{\prime\prime} + s'x)}^j[\![\Sigma^{\chi}(\tau_2)]\!]$. Notice that $\Sigma^{\chi} \cdot (\Sigma^{\prime\prime} + s^\prime x) = (\Delta^\prime + s^{\prime\prime} x) \cdot (\Sigma^{\prime\prime} + s^\prime x) = \Delta^\prime \cdot \Sigma^{\prime\prime} + s^\prime s^{\prime\prime}$. Therefore we know that $(\gamma_1 \vdash e', \gamma_2 \vdash e') \in \mathcal{E}_{\Delta' \cdot \Sigma'' + s's''}^j [\![(\Delta' + s''x)(\tau_2)]\!]$.

 $(y_1 \vdash e, y_2 \vdash e) \in C_{\Delta', \Sigma'' + s's''}$ $\mathbb{I}(\Delta + s \ x)(\tau_2)$.
As $(y_1, y_2) \in \mathcal{G}_{\Delta'}^{k-1}$ [Γ], and by Lemma [C.10](#page-67-0) $(y_1, y_2) \in \mathcal{G}_{\Delta'}^{j}$ [Γ], also $(v_1, v_2) \in \mathcal{V}_{s''}^{j}$ [$\Delta'(\tau_1)$], and $\Delta'(\tau_1)$ = $(\Delta' + sx'')(\tau_1)$ (as x is not free in τ_1), it is easy to see that $(\gamma_1, x \mapsto v_1, \gamma_2, x \mapsto v_2) \in \mathcal{G}_{\Delta' + s''x}^j[\Gamma, x : \tau_1]$. Finally, the result follows by choosing $\gamma_1 = \gamma_1, x \mapsto v_1$, and $\gamma_2 = \gamma_2, x \mapsto v_2$.

Case (7) $\Gamma; \Delta \vdash \langle \lambda^s(x : \tau_1 \cdot s_1), e', \gamma \rangle : (x : \tau_1 \cdot s_1) \xrightarrow{s'x} \tau_2 : \varnothing$

Subproof.

$$
\exists \Gamma', \Delta'_0, \text{dom}(\Sigma'') \subseteq \text{dom}(\Gamma') \subseteq \text{dom}(\Delta'_0)
$$
\n
$$
\forall x_i \in \text{dom}(\Gamma'), \varnothing; \varnothing \vdash \gamma(x_i): \tau'_i, \tau'_i <: \Gamma'(x_i); \varnothing \qquad \Gamma', x : \tau_1; \Delta'_0 + s_1 x + e' : \tau_2; \Sigma'' + s'x
$$
\n
$$
\Gamma; \Delta \vdash \langle \lambda^*(x : \tau_1 \cdot s_1), e', \gamma \rangle : (x : [\varnothing/x_1, ..., \varnothing/x_n] \tau_1 \cdot s_1) \xrightarrow{s'x} [\varnothing/x_1, ..., \varnothing/x_n] \tau_2; \varnothing
$$

By induction hypotheses on $\forall x_i \in dom(\Gamma'), \emptyset; \emptyset \vdash \gamma(x_i) : \tau'_i; \emptyset$, we know that, $\langle \gamma(x_i), \gamma(x_i) \rangle \in$ $\mathcal{W}_0^{k-1}[\![\emptyset(\tau'_i)]\!]$, and by [C.10](#page-67-0) $\langle \gamma(x_i), \gamma(x_i) \rangle \in \mathcal{W}_0^{k-1}[\![\emptyset(\Gamma'(x_i))]$. Therefore $\langle \gamma, \gamma \rangle \in \mathcal{W}_0^{k-1}[\![\Gamma']\!]$, and by Lemma [C.11,](#page-68-1) $\langle \gamma, \gamma \rangle \in \mathcal{V}_{\emptyset}^j[\![\Gamma']\!]$ for $j < k$.

Notice that $\Delta'([\varnothing/x_1, ..., \varnothing/x_n]\tau_1) = [\varnothing/x_1, ..., \varnothing/x_n]\tau_1 = \varnothing([\varnothing/x_1, ..., \varnothing/x_n]\tau_1)$, $\Delta'([\varnothing/x_1, ..., \varnothing/x_n]\tau_2) =$ $[\emptyset/x_1, ..., \emptyset/x_n]$ $\tau_2 = \emptyset([\emptyset/x_1, ..., \emptyset/x_n]$ τ_2), as τ_1 and τ_2 have no free variables. We have to prove that $(\langle \lambda^*(x : \tau_1 \cdot s_1), e', \gamma \rangle, \langle \lambda^*(x : \tau_1 \cdot s_1), e', \gamma \rangle) \in \mathcal{V}_0^k[[x : [\emptyset/x_1, ..., \emptyset/x_n]\tau_1 \cdot s_1) \xrightarrow{s'x} [\emptyset/x_1, ..., \emptyset/x_n]\tau_2]$ Notice that if we choose $\Delta' = 0x_1, ..., 0x_n$, we can use that same Δ' in the induction hypothesis of $\Gamma', x : \tau_1; \Delta'_0 + s_1 x + e' : \tau_2 : \Sigma'' + s'x$, and then we can use the same analogous arguments of the previous case and Lemma [C.10](#page-67-0) to conclude the result.

Case (8) $\Gamma; \Delta \vdash e_1 \ e_2 : [\Sigma_2/x] \tau_2 ; \Sigma_1 + s\Sigma_2 + \Sigma''$

SUBPROOF. Notice that $\Delta' \cdot (\Sigma_1 + s\Sigma_2 + \Sigma'') = (\Delta' \cdot \Sigma_1 + s(\Delta' \cdot \Sigma_2) + \Delta' \cdot \Sigma'')$, for $\Delta' \subseteq \Delta$. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash e_1 \ e_2, \gamma_2 \vdash e_1 \ e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_1 + s(\Delta' \cdot \Sigma_2) + \Delta' \cdot \Sigma''}^k[\![\Delta'([\Sigma_2/\{x\}]\tau_2)]\!],$ i.e. if $\gamma_1 \vdash e_1 \ e_2 \ \Downarrow^j \ v_1'$ and $\gamma_2 \vdash e_1 \ e_2 \ \Downarrow^j \ v_2'$, then $(v_1', v_2') \in \mathcal{V}_{\Delta' \cdot \Sigma_1 + s(\Delta' \cdot \Sigma_2) + \Delta' \cdot \Sigma''} \big[\Delta'([\Sigma_2/x] \tau_2)\big]$. By induction hypotheses we know that

$$
\Gamma + e_1 : (x : \tau_1) \xrightarrow{\Sigma''+sx} \tau_2 : \Sigma_1 \implies (\gamma_1 + e_1, \gamma_2 + e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'((x : \tau_1 \cdot s') \xrightarrow{\Sigma''+sx} \tau_2)]
$$
 and
$\Gamma \vdash e_2 : \tau_1 : \Sigma_2 \Rightarrow (\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} \llbracket \Delta'(\tau_1) \rrbracket$ for some $j_1 \leq k$. As $\Delta'((x : \tau_1 s') \xrightarrow{\Sigma''+s x} \tau_2) = (x : \tau_1 s')$ $\Delta'(\tau_1) \cdot s' \xrightarrow{\Delta' \cdot \Sigma'' + sx} \Delta'(\tau_2)$, by unfolding $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[[x : \Delta'(\tau_1 \cdot s')] \xrightarrow{\Delta' \cdot \Sigma'' + sx} \Delta'(\tau_2)]]$, we know that if $\gamma_1 \vdash e_1 \Downarrow^{j_1} \langle \lambda(x : \tau_1), e'_1, \gamma_1 \rangle$ and $\gamma_2 \vdash e_1 \Downarrow^{j_1} \langle \lambda(x : \tau_1), e'_2, \gamma_2 \rangle$ then $(\langle \lambda^s(x:\tau_1), e'_1, \gamma_1 \rangle, \langle \lambda^s(x:\tau_1 \cdot s'), e'_2, \gamma_2 \rangle) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j} \left[(x : \Delta'(\tau_1 \cdot s')) \xrightarrow{\Delta' \cdot \Sigma'' + sx} \Delta'(\tau_2) \right]$ (1). Also, by unfolding $(y_1 + e_2, y_2 + e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\tau_1 \cdot s')]$, if $y_1 + e_2 \Downarrow^{j_2} v_1$ and $y_2 + e_2 \Downarrow^{j_2} v_2$ then $-\Sigma_2$ $(v_1, v_2) \in \mathcal{V}_{\Delta' \cdot \Sigma_2}^{k-j_1-j_2} \llbracket \Delta'(\tau_1) \rrbracket.$ As $\Delta' \cdot \Sigma_2 \in \text{sens}$, we instantiate (1) with $s'' = \Delta' \cdot \Sigma_2$ (we know that $s'' \leq \Delta \cdot \Sigma_2 \leq s'$), then $(\gamma_1[x \mapsto v_1] \mapsto e'_1, \gamma_2[x \mapsto v_2] \mapsto e'_2) \in \mathcal{E}^{k-j_1-j_2-1}_{\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma'' + \delta(\Delta' \cdot \Sigma_2)}[[\Delta' \cdot \Sigma_2/x] \Delta'(\tau_2)]]$. But $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma'' +$ $s(\Delta' \cdot \Sigma_2) = \Delta' \cdot \Sigma_1 + s(\Delta' \cdot \Sigma_2) + \Delta' \cdot \Sigma''$, and by Lemma [7.6,](#page-42-0) $[\Delta' \cdot \Sigma_2/x] \Delta'(\tau_2) = \Delta'([\Sigma_2/x]\tau_2)$, therefore $(\gamma_1[x \mapsto v_1] \vdash e'_1, \gamma_2[x \mapsto v_2] \vdash e'_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_1 + s(\Delta' \cdot \Sigma_2) + \Delta' \cdot \Sigma''}^{\lambda \cdot \gamma}[\Delta'([\Sigma_2/x] \tau_2)], \text{ i.e. if } \gamma_1[x \mapsto v_1] \vdash e'_1 \Downarrow^3 v''_1$ and $\gamma_2[x \mapsto v_2] \mapsto e'_2 \Downarrow^{j_3} v''_2$, then $(v''_1, v''_2) \in \mathcal{V}_{\Delta' \cdot \Sigma_1 + s(\Delta' \cdot \Sigma_2) + \Delta' \cdot \Sigma''}^{\kappa - j_1 - j_2 - j_3 - 1}$ [$\Delta'([\Sigma_2/x] \tau_2)$]. But notice that by APP:

$$
\frac{\gamma_i \vdash e_1 \Downarrow^{j_1} \langle \lambda x. e'_i, \gamma_i \rangle \qquad \gamma_i \vdash e_2 \Downarrow^{j_2} v_i \qquad \gamma_1[x \mapsto v_i] \vdash e'_i \Downarrow^{j_3} v'_i}{\gamma_i \vdash e_1 e_2 \Downarrow^{j_1+j_2+j_3+1} v'_i}
$$

for $i \in \{1, 2\}$. Notice that $j = j_1 + j_2 + j_3 + 1$, and by premise $\gamma_1[x \mapsto v_i] \vdash e'_i \Downarrow^j v'_i$, we know that $v_i'' = v_i'$ and the result holds immediately.

Case (9) Γ ; Δ \vdash tt : unit ; \varnothing

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \mathsf{t} \mathsf{t}, \gamma_2 \vdash \mathsf{t} \mathsf{t}) \in \mathcal{E}_{\Delta', \emptyset}^k[\![\Delta'(\mathsf{unit})]\!],$ for $\Delta' \sqsubseteq \Delta$. Notice that $\Delta' \odot = 0$, Σ (unit) = unit, and $\gamma_1(tt) = \gamma_2(tt) = t$. Then we have to prove that $(\texttt{tt}, \texttt{tt}) \in \mathcal{V}_0^k$ [[unit]] which is direct.

Case (10) $\Gamma; \Delta \vdash \text{inl}^{\tau_2} e' : \tau_1 \overset{\Sigma''}{} \oplus \,^{\oslash} \tau_2 ; \varnothing$

SUBPROOF. We have to prove that $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \text{inl}^{\tau_2} e', \gamma_2 \vdash \text{inl}^{\tau_2} e') \in \mathcal{E}_{\Delta', \varnothing}^k[\![\Delta'(\tau_1 \Sigma'' \oplus \varnothing \times \Sigma'')\!],$ $[\tau_2]$, for $\Delta' \subseteq \Delta$. Notice that $\Delta' \otimes = 0$, and $\Delta'(\tau_1 \stackrel{\Sigma''}{\otimes} \oplus^{\emptyset} \tau_2) = \Delta'(\tau_1) \stackrel{\Delta' \cdot \Sigma''}{\otimes} \oplus^0 \Delta'(\tau_2)$, then we have to prove that

 $(y_1 + \text{inl}^{\tau_2} e', y_2 + \text{inl}^{\tau_2} e') \in \mathcal{E}_0^k[\![\Delta'(\tau_1) \ \Delta' \cdot \Sigma'' \oplus^0 \ \Delta'(\tau_2)]\!]$, i.e. if $y_1 + \text{inl}^{\tau_2} e' \ \Downarrow^j v_1$ and $y_2 +$ inl^{τ_2} $e' \Downarrow^j v_2$, then $(v_1, v_2) \in \mathcal{V}_0^{k-j} [\Delta'(\tau_1) \Delta' \Sigma'' \oplus^0 \Delta'(\tau_2)].$

By induction hypothesis on $\Gamma \vdash e' : \tau_1 : \Sigma''$, we know that

 $(\gamma_1 \vdash e', \gamma_2 \vdash e') \in \mathcal{E}_{\Delta' \cdot \Sigma''}^k[\Delta'(\tau_1)]$, i.e. if $\gamma_1 \vdash e' \Downarrow^j v'_1$, and $\gamma_2 \vdash e' \Downarrow^j v'_2$ then $(v'_1, v'_2) \in \mathcal{V}_{\Delta' \cdot \Sigma''}^{k-j}[\Delta'(\tau_1)]$. If γ_i \vdash inl^{τ_2} $e' \Downarrow^j v_i$ and γ_i \vdash $e' \Downarrow^j v_i'$, then by INL, $v_i = \text{inl}^{\tau_2} v_i'$. Then we have to prove that $(\text{in} \mathbb{I}^{\tau_2} \ v_1', \text{in} \mathbb{I}^{\tau_2} \ v_2') \in \mathcal{V}_0^{k-j}[\![\Delta'(\tau_1) \Delta' \Sigma'' \oplus^0 \Delta'(\tau_2)]\!]$, i.e. that $(v_1', v_2') \in \mathcal{V}_{\Delta' \Sigma'' \oplus^0}^{k-j}[\![\Delta'(\tau_1)]\!]$, but as $\Delta' \cdot \Sigma'' +$ $0 = \Delta' \cdot \Sigma''$, the result holds immediately.

Case (11) $\Gamma; \Delta \vdash \text{inr}^{\tau_1} e' : \tau_1 \overset{\varnothing \oplus \Sigma''}{\rightarrow} \tau_2 : \varnothing$

SUBPROOF. We have to prove that $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\mathbf{r}]\!], (\gamma_1 \vdash \mathbf{inr}^{\tau_1} \mid e', \gamma_2 \vdash \mathbf{inr}^{\tau_1} \mid e') \in \mathcal{E}_{\Delta', \emptyset}^k[\![\Delta'(\tau_1 \otimes \bigoplus \Sigma'']\!], (\gamma_1 \vdash \mathbf{inr}^{\tau_1} \mid e'), \gamma_2 \vdash \mathbf{inr}^{\tau_2} \mid e' \in \mathcal{E}_{\Delta', \empty$ τ_2), for $\Delta' \subseteq \Delta$. Notice that $\Delta' \otimes = 0$, and $\Delta'(\tau_1 \otimes_{\Theta} \Sigma'' \tau_2) = \Delta'(\tau_1) \otimes \Delta' \Sigma'' \Delta'(\tau_2)$, then we have to prove that

 $(y_1 + \text{inr}^{\tau_1} e', y_2 + \text{inr}^{\tau_1} e') \in \mathcal{E}_0^k[\Delta'(\tau_1) \oplus \Delta'^{\cdot} \Sigma'' \Delta'(\tau_2)], \text{ i.e. if } y_1 + \text{inr}^{\tau_1} e' \Downarrow' v_1 \text{ and } y_2 + \Delta' \Sigma' \Sigma' \Delta'(\tau_2).$ inr^{τ_1} e' $\Downarrow^j v_2$, then $(v_1, v_2) \in \mathcal{V}_0^{k-j} [\Delta'(\tau_1) \circ \bigoplus^{\Delta' \cdot \Sigma''} \Delta'(\tau_2)]$.

By induction hypothesis on $\Gamma \vdash e' : \tau_2 : \Sigma''$, we know that

 $(\gamma_1 \vdash e', \gamma_2 \vdash e') \in \mathcal{E}_{\Delta' \cdot \Sigma''}^k[\Delta'(\tau_2)]$, i.e. if $\gamma_1 \vdash e' \Downarrow^j v'_1$, and $\gamma_2 \vdash e' \Downarrow^j v'_2$ then $(v'_1, v'_2) \in \mathcal{V}_{\Delta' \cdot \Sigma''}^{k-j}[\Delta'(\tau_2)]$.

If γ_i \vdash inr^{τ_1} $e' \Downarrow^j v_i$ and γ_i \vdash $e' \Downarrow^j v_i'$, then by INR, $v_i = \text{inr}^{\tau_1} v_i'$. Then we have to prove that $(\text{inr}^{\tau_1} \ v'_1, \text{inr}^{\tau_1} \ v'_2) \in \mathcal{V}_0^{k-j}[\Delta'(\tau_1) \ ^0 \oplus \Delta' \ \Sigma'' \ \Delta'(\tau_2)]$, i.e. that $(v'_1, v'_2) \in \mathcal{V}_{0+\Delta' \cdot \Sigma''}^{k-j}[\Delta'(\tau_2)]$, but as $0+\Delta' \Sigma'' \ \Delta'(\tau_2)$ $\Delta' \cdot \Sigma'' = \Delta' \cdot \Sigma''$, the result holds immediately.

Case (12) Γ; $\Delta \vdash$ case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\} : [\Sigma_1 + \Sigma_{11}/x]\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y]\tau_3 : \Sigma_1 \sqcup ([\Sigma_1 + \Sigma_2]/y]\tau_2\}$ $\Sigma_{11}/x](\Sigma_2 + s_2x) \sqcup [\Sigma_1 + \Sigma_{12}/y](\Sigma_3 + s_3y))$

SUBPROOF. We have to prove that for any k , $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!],$

 $(y_1 \vdash \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{y \Rightarrow e_3\}, y_2 \vdash \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{y \Rightarrow e_3\}) \in \mathcal{E}^k_{\Delta' \cdot \Sigma''}[\Delta'(\tau')], \text{ for } k \in \mathbb{N}$ $Δ' ⊆ Δ$, where

 $\Sigma'' = \Sigma_1 \sqcup ([\Sigma_1 + \Sigma_{11}/x](\Sigma_2 + s_2x) \sqcup [\Sigma_1 + \Sigma_{12}/y](\Sigma_3 + s_3y)) = \Sigma_1 \sqcup ((s_2\Sigma_1 + s_2\Sigma_{11}\Sigma_2) \sqcup (s_3\Sigma_1 + s_3\Sigma_{12}\Sigma_2)),$ and $\tau' = [\Sigma_1 + \Sigma_{11}/x]\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y]\tau_3$.

By induction hypothesis on $\Gamma; \Delta \vdash e_1 : \tau_{11} \Sigma_{11} \oplus \Sigma_{12} \tau_{12}$; Σ_1 , we know that

 $(y_1 + e_1, y_2 + e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'(\tau_{11} \Sigma_1 \oplus \Sigma_1 z \tau_{12})],$ i.e. if $y_1 + e_1 \Downarrow^{j_1} v_{11}$, and $y_2 + e_1 \Downarrow^{j_1} v_{12}$ then $(v_{11}, v_{12}) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j_1} [\Delta'(\tau_{11}) \Delta' \cdot \Sigma_{12} \Delta'(\tau_{12})]$. Either $v_{11} = \text{inl} \ v'_{11}$ and $v_{12} = \text{inl} \ v'_{12}$, $v_{11} = \text{inr} \ v'_{11}$ and $v_{12} = \text{inr } v'_{12}$, $v_{11} = \text{inl } v'_{11}$ and $v_{12} = \text{inr } v'_{12}$, or $v_{11} = \text{inr } v'_{11}$ and $v_{12} = \text{inl } v'_{12}$. We proceed by case analysis on (v_{11}, v_{12}) :

Case (a) $(v_{11}, v_{12}) = (\text{inl } v'_{11}, \text{inl } v'_{12})$ (the case $(v_{11}, v_{12}) = (\text{inr } v'_{11}, \text{inr } v'_{12})$ is analogous)

SUBPROOF. By Lemma [C.1](#page-52-0) $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_{11} = \Delta' \cdot (\Sigma_1 + \Sigma_{11})$, then $(v'_{11}, v'_{12}) \in \mathcal{V}_{\Delta' \cdot (\Sigma_1 + \Sigma_{11})}^{k-j_1}[[\Delta'(\tau_{11})]]$. Also, by induction hypothesis on $\Gamma, x : \tau_{11}$; $\Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2 : \Sigma_2 + s_2x$, by choosing $\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11})) x \sqsubseteq \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11})) x$ and $k = k - j_1$ (and by weakening lemma [C.11\)](#page-68-0)

 $(\gamma_1[x \mapsto v_{12}'], \gamma_2[x \mapsto v_{22}']) \in \mathcal{G}_{\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))}^{\kappa}[\Gamma, x : \tau_{11}] \text{ (note that } x \notin \text{dom}(\Sigma_1) \cup \text{dom}(\Sigma_{11}),$ therefore $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x)(\tau_{11}) = \Delta'(\tau_{11})$ we know that

 $(\gamma_1[x \mapsto v_{12}'] + e_2, \gamma_2[x \mapsto v_{22}'] + e_2) \in \mathcal{E}_{(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x) \cdot (\Sigma_2 + s_2x)}^{\{k-1\}}[(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x)(\tau_2)]]$ But $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x) \cdot (\Sigma_2 + s_2x) = \Delta' \cdot \Sigma_2 + s_2(\Delta' \cdot (\Sigma_1 + \Sigma_{11})) = \Delta' \cdot (s_2(\Sigma_1 + \Sigma_{11}) + \Sigma_2)$, and by Lemma [C.2](#page-55-0) and because $\Delta' \cdot (\Sigma_1 + \Sigma_{11}) \in \text{sens, then } (\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x)(\tau_2) = (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x(\Delta'(\tau_2)),$ and by Lemma [7.6](#page-42-0) $(\Delta' \cdot (\Sigma_1 + \Sigma_{11})) x(\Delta'(\tau_2)) = \Delta' ([\Sigma_1 + \Sigma_{11}/x] \tau_2)$. Therefore if $\gamma_1[x \mapsto v'_{12}] \vdash e_2 \Downarrow^{j_2} v_{21}$, and $\gamma_2[x \mapsto v_{22}'] \vdash e_2 \Downarrow^{j_2} v_{22}$, then

 $(v_{21}, v_{22}) \in \mathcal{V}_{\Delta' \cdot (s_2 \Sigma_1 + s_2 \Sigma_{11} + \Sigma_2)}^{\kappa - j_1 - j_2} \left[\Delta' (\left[\Sigma_1 + \Sigma_{11}/x \right] \tau_2) \right]$

By following the CASE-LEFT reduction rule:

$$
\frac{\gamma_i \vdash e_1 \Downarrow^{j_1} \text{inl } v'_{1i}}{\gamma_i \vdash \text{case } e_1 \text{of } \{x \Rightarrow e_2\} \{x \Rightarrow e_3\} \Downarrow^{j_1 \vdash p_2} v_{2i}}{\gamma_i \vdash \text{case } e_1 \text{of } \{x \Rightarrow e_2\} \{x \Rightarrow e_3\} \Downarrow^{j_1 + j_2 + 1} v_{2i}}
$$

for $i \in \{1, 2\}$. Then we just have to prove that

 $(v_{21}, v_{22}) \in \mathcal{V}_{\Delta'}^{k-j_1-j_2-1}$
 $(\Sigma_1 \cup (\Sigma_2 \Sigma_1 + \Sigma_2) \cup (\Sigma_3 \Sigma_1 + \Sigma_3 \Sigma_1 + \Sigma_3) \mathbb{Z}^{\Delta'}([\Sigma_1 + \Sigma_{11}/x] \tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y] \tau_3) \mathbb{Z}$. Notice that by definition of the join operator $(s_2\Sigma_1 + s_2\Sigma_{11} + \Sigma_2) <: (s_2\Sigma_1 + s_2\Sigma_{11} + \Sigma_2) \sqcup (s_3\Sigma_1 + s_3\Sigma_{12} + \Sigma_3)$, also $(s_2\Sigma_1 + s_2\Sigma_{11} + \Sigma_2) \sqcup (s_3\Sigma_1 + s_3\Sigma_{12} + \Sigma_3) <: \Sigma_1 \sqcup (s_2\Sigma_1 + s_2\Sigma_{11} + \Sigma_2) \sqcup (s_3\Sigma_1 + s_3\Sigma_{12} + \Sigma_3)$ therefore by Lemma [C.12](#page-68-1) $\Delta' \cdot (s_2 \Sigma_1 + s_2 \Sigma_{11} + \Sigma_2) \leq \Delta' \cdot (\Sigma_1 \sqcup (s_2 \Sigma_1 + s_2 \Sigma_{11} + \Sigma_2) \sqcup (s_3 \Sigma_1 + s_3 \Sigma_{12} + \Sigma_3)).$

Also $[\Sigma_1 + \Sigma_{11}/x]\tau_2 < :[\Sigma_1 + \Sigma_{11}/x]\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y]\tau_3$ therefore by Lemma [C.6,](#page-65-0)

 $\Delta'([\Sigma_1 + \Sigma_{11}/x]\tau_2)$ <: $\Delta'([\Sigma_1 + \Sigma_{11}/x]\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y]\tau_3)$. Finally by Lemma [C.10,](#page-67-0)

 $(v_{21}, v_{22}) \in \mathcal{V}_{\Delta' \cdot (\Sigma_1 \sqcup (s_2 \Sigma_1 + s_2 \Sigma_{11} + \Sigma_2) \sqcup (s_3 \Sigma_1 + s_3 \Sigma_{12} + \Sigma_3))}^{\mathbb{Z}} \llbracket \Delta'([\Sigma_1 + \Sigma_{11}/x] \tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y] \tau_3) \rrbracket$ and the result holds by Lemma [C.11.](#page-68-0) ⊳

Case (b) $(v_{11}, v_{12}) = (\text{inl } v'_{11}, \text{inr } v'_{12})$ (the case $(v_{11}, v_{12}) = (\text{inr } v'_{11}, \text{inl } v'_{12})$ is analogous) SUBPROOF. Then $\Delta' \cdot \Sigma_1 = \infty$. By following the CASE-LEFT reduction rule:

$$
\frac{\gamma_1 + e_1 \Downarrow^{j_1} \text{ in } \mathbb{1} \ v'_{11}}{\gamma_1 + \text{ case } e_1 \text{ of } \{x \Rightarrow e_2\} \ \{x \Rightarrow e_3\} \ \Downarrow^{j_1 + j_2 + 1} \ v_{21}}
$$

and following the CASE-RIGHT reduction rule:

$$
\frac{\gamma_2 + e_1 \Downarrow^{j_1} \text{inr } v'_{12}}{\gamma_2 + \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{x \Rightarrow e_3\} \Downarrow^{j_{12}} v_{22}}}{\gamma_2 + \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{x \Rightarrow e_3\} \Downarrow^{j_1 + j_2 + 1} v_{22}}
$$

And let $j_2 = max(j_{21}, j_{22})$, then we just have to prove that $(v_{21}, v_{22}) \in \mathcal{V}_{\Delta' \cdot (\Sigma_1 \sqcup (s_2 \Sigma_1 + s_2 \Sigma_{11} + \Sigma_2) \sqcup (s_3 \Sigma_1 + s_3 \Sigma_{12} + \Sigma_3))}^{\{ \Delta' (\Sigma_1 + \Sigma_{11}/x) \tau_2 \sqcup (\Sigma_1 + \Sigma_{12}/y) \tau_3) \}}$. As $\Delta' \cdot \Sigma_1 = \infty$, then $\Delta' \cdot (\Sigma_1 \sqcup (s_2 \Sigma_1 + s_2 \Sigma_{11} + \Sigma_2) \sqcup (s_3 \Sigma_1 + s_3 \Sigma_{12} + \Sigma_3)) = \infty$ and the result holds.

Case (13)
$$
\Gamma
$$
; $\Delta \vdash (e_1, e_2) : \tau_1 \xrightarrow{\Sigma_1} \& \Sigma_2 \tau_2 ; \emptyset$

Subproof. We have to prove that

 $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash (e_1, e_2), \gamma_2 \vdash (e_1, e_2)) \in \mathcal{E}_{\Delta', \odot}^k[\Delta'(\tau_1^{\Sigma_1} \&^{\Sigma_2} \tau_2)]], \text{ for } \Delta' \sqsubseteq \Delta. \text{ Notice that } \Delta' \cdot \emptyset = 0, \text{ and } \Delta'(\tau_1^{\Sigma_1} \&^{\Sigma_2} \tau_2) = \Delta'(\tau_1) \stackrel{\Delta' \cdot \Sigma_1}{\times} \&^{\Delta' \cdot \Sigma_$

 $(\gamma_1 + (e_1, e_2), \gamma_2 + (e_1, e_2)) \in \mathcal{E}_0^k[\Delta'(\tau_1) \triangle^{ \prime \cdot \Sigma_1} \& \Delta'(\tau_2)]$, i.e. if $\gamma_1 + (e_1, e_2) \Downarrow (v_{11}, v_{12})$ and $\gamma_2 \vdash (e_1, e_2) \Downarrow^{j} (v_{21}, v_{22}),$ then $((v_{11}, v_{12}), (v_{21}, v_{22})) \in \mathcal{V}_0^{k-j} [\Delta'(\tau_1) \stackrel{\Delta' \cdot \Sigma_1}{\sim} \&^{\Delta' \cdot \Sigma_2} \Delta'(\tau_2)]$, or equivalently $(v_{11},, v_{21}) \in \mathcal{V}_{0+\Delta', \Sigma_1}^{k-j} [\![\Delta'(\tau_1)]\!]$, and $(v_{12},, v_{22}) \in \mathcal{V}_{0+\Delta', \Sigma_2}^{k-j} [\![\Delta'(\tau_2)]\!]$.

By induction hypothesis on $\Gamma \vdash e_1 : \tau_1 : \Sigma_1$ and $\Gamma \vdash e_2 : \tau_2 : \Sigma_2$, we know that $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in$ $\mathcal{E}_{\Delta',\Sigma_1}^k[\Delta'(\tau_1)]$ and $(\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}_{\Delta',\Sigma_2}^k[\Delta'(\tau_2)]$ respectively. This means that if $\gamma_1 \vdash e_1 \Downarrow^{j_1} v'_{11}$, and $\gamma_2 \vdash e_1 \Downarrow^{j_1} v'_1$ then $(v'_1, v'_1) \in \mathcal{V}_{\Delta', \Sigma_1}^{k-j_1} [\Delta'(\tau_1)]$, and that if $\gamma_1 \vdash e_2 \Downarrow^{j_2} v'_2$, and $\gamma_2 \vdash e_2 \Downarrow^{j_2} v'_2$ then $(v'_1, v'_2) \in V^{k-j_2}_{\Delta'}[\Delta'(\tau_2)]$. As reduction is deterministic, then $j = j_1 + j_2$ and $v'_{ij} = v_{ij}$, therefore as $0 + \Delta' \cdot \Sigma_i = \Delta' \cdot \Sigma_i$, the result holds immediately by Lemma [C.11.](#page-68-0)

Case (14) $\Gamma; \Delta \vdash \textsf{fst} \ e' : \tau_1 : \Sigma'' + \Sigma_1$

SUBPROOF. We have to prove that for any k , $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \text{fst } e', \gamma_2 \vdash \text{fst } e') \in$ $\mathcal{E}^k_{\Delta' \cdot (\Sigma'' + \Sigma_1)}[\![\Delta'(\tau_1)]\!]$, for $\Delta' \sqsubseteq \Delta$. By induction hypothesis on $\Gamma \vdash e' : \tau_1 \stackrel{\Sigma_1}{\otimes} \mathcal{E}_2 \tau_2 : \Sigma''$ we know that $(y_1 \vdash e', y_2 \vdash e') \in \mathcal{E}_{\Delta' \cdot \Sigma''}^k[\Delta'(\tau_1 \Sigma_1 \& \Sigma_2)]$, i.e. if $y_1 \vdash e' \Downarrow^j (v_{11}, v_{12})$ and $y_2 \vdash e' \Downarrow^j (v_{21}, v_{22})$, then $((v_{11}, v_{12}), (v_{21}, v_{22})) \in \mathcal{V}_{\Delta' \cdot \Sigma''}^{k-j} [\Delta'(\tau_1) \stackrel{\Delta' \cdot \Sigma_1}{\sim} \&^{\Delta' \cdot \Sigma_2} \Delta'(\tau_2)]$, or equivalently $(v_{11}, v_{21}) \in \mathcal{V}_{\Delta' \cdot \Sigma'' + \Delta' \cdot \Sigma_1}^{k-j} [\Delta'(\tau_1)]$, ·Σ and $(v_{12},, v_{22}) \in \mathcal{V}_{\Delta' \cdot \Sigma'' + \Delta' \cdot \Sigma_2}^{k-j} \llbracket \Delta'(\tau_2) \rrbracket$.

Following the proj1 reduction rule, if:

$$
\frac{\gamma_i \vdash e' \Downarrow^j (v_{i1}, v_{i2})}{\gamma_i \vdash \text{fst } e' \Downarrow^j v_{i1}}
$$

Then we have to prove that $(v_{11}, v_{21}) \in V^{k-j}_{\Delta' \cdot (\Sigma'' + \Sigma_1)}[\Delta'(\tau_1)]$, but as by Lemma [C.1,](#page-52-0) $\Delta' \cdot (\Sigma'' + \Sigma_1) =$ $\Delta' \cdot \Sigma'' + \Delta' \cdot \Sigma_1$, the result holds immediately.

Case (15) snd $e' : \tau_1 : \Sigma'' + \Sigma_2$

Subproof. Analogous to previous case. ⊳

Case (16) $\Gamma; \Delta \vdash \langle e_1, e_2 \rangle : \tau_1 \stackrel{\Sigma_1} \otimes \stackrel{\Sigma_2} \tau_2 : \emptyset$

SUBPROOF. We have to prove that $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \langle e_1, e_2 \rangle, \gamma_2 \vdash \langle e_1, e_2 \rangle) \in \mathcal{E}_{\Delta', \emptyset}^k[\![\Delta'(\tau_1 \cdot \Sigma_1 \otimes \Sigma_2 \cdot \Sigma_1 \cdot \Sigma_1 \cdot \Sigma_2 \cdot \Sigma_1 \cdot \Sigma_2 \cdot \Sigma_1 \cdot \Sigma_2 \cdot \Sigma_1 \cdot \Sigma_2 \cdot \Sigma_1 \cdot \Sigma_1 \cdot \Sigma_2 \cdot \Sigma$ τ_2), for $\Delta' \subseteq \Delta$. Notice that $\Delta' \cdot \emptyset = 0$, and $\Delta'(\tau_1 \stackrel{\sum_{i}^2 \bigcirc \sum_{i}^2}{\alpha_i \otimes \sum_{i}^2} \tau_2) = \Delta'(\tau_1) \stackrel{\Delta' \cdot \sum_{i}^2 \bigcirc \Delta'(\tau_2)}{\Delta' \cdot \sum_{i}^2} \Delta'(\tau_2)$, then we have to prove that

 $(\gamma_1 \vdash \langle e_1, e_2 \rangle, \gamma_2 \vdash \langle e_1, e_2 \rangle) \in \mathcal{E}_0^k[\Delta'(\tau_1) \stackrel{\Delta' \cdot \Sigma_1 \otimes \Delta' \cdot \Sigma_2}{\Delta'(\tau_2)}],$ i.e. if $\gamma_1 \vdash \langle e_1, e_2 \rangle \downarrow^{j_1} \langle v_{11}, v_{12} \rangle$ and $\gamma_2 \vdash \langle e_1, e_2 \rangle \Downarrow^{j_1} \langle v_{21}, v_{22} \rangle$, then $(\langle v_{11}, v_{12} \rangle, \langle v_{21}, v_{22} \rangle) \in \mathcal{V}_0^{k-j} [\Delta'(\tau_1) \Delta' \cdot \Sigma_1 \otimes \Delta' \cdot \Sigma_2 \Delta'(\tau_2)]$, or equivalently $(v_{11}, v_{21}) \in \mathcal{V}_{0+\Delta'}^{k-j} [\Delta'(\tau_1)]$, and $(v_{12}, v_{22}) \in \mathcal{V}_{0+\Delta', \Sigma_2}^{k-j} [\Delta'(\tau_2)]$.

⊳

$$
f_{\rm{max}}
$$

⊳

⊳

By induction hypothesis on $\Gamma \vdash e_1 : \tau_1 : \Sigma_1$ and $\Gamma \vdash e_2 : \tau_2 : \Sigma_2$, we know that $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in$ $\mathcal{E}^k_{\Delta' \cdot \Sigma_1} [\![\Delta'(\tau_1)]\!]$ and $(\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}^k_{\Delta' \cdot \Sigma_2} [\![\Delta'(\tau_2)]\!]$ respectively. This means that if $\gamma_1 \vdash e_1 \Downarrow^{j_1} v'_{11}$, and $\gamma_2 \vdash e_1 \Downarrow^{j_1} v'_1$ then $(v'_1, v'_1) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j_1} [\Delta'(\tau_1)]$, and that if $\gamma_1 \vdash e_2 \Downarrow^{j_2} v'_2$, and $\gamma_2 \vdash e_2 \Downarrow^{j_2} v'_2$ then $(v'_2, v'_2) \in V^{k-j_2}_{\Delta'}[\Delta'(\tau_2)]$. As reduction is deterministic, then $j = j_1 + j_2$ and $v'_{ij} = v_{ij}$, therefore as $0 + \Delta' \cdot \Sigma_i = \Delta' \cdot \Sigma_i$, the result holds immediately by Lemma [C.11.](#page-68-0)

Case (17) Γ; Δ ⊢ let $x_1, x_2 = e_1$ in e_2 : $[\Sigma_1 + \Sigma_{11}/x_1][\Sigma_1 + \Sigma_{12}/x_2]\tau_2$; $s_1(\Sigma_{11} + \Sigma_1) + s_2(\Sigma_{12} + \Sigma_1) + \Sigma_2$ SUBPROOF. We have to prove that for any k , $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \text{let } x_1, x_2 = e_1 \text{ in } e_2, \gamma_2 \vdash \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \text{let } x_1, x_2 = e_1 \text{ in } e_2, \gamma_2 \vdash \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!], (\gamma_1 \vdash \text{let } x_1, x_2 =$ Let $x_1, x_2 = e_1$ in e_2) $\in \mathcal{E}_{\Delta' \cdot (\Sigma'')}^k[[\Delta'(\tau)]]$, for $\Delta' \sqsubseteq \Delta$. where $\Sigma'' = s_1(\Sigma_{11} + \Sigma_1) + s_2(\Sigma_{12} + \Sigma_1) + \Sigma_2$. Suppose

$$
\frac{\gamma_i + e_1 \Downarrow^{j_1} \langle v_{i1}, v_{i2} \rangle \qquad \gamma_i [x_1 \mapsto v_{i1}, x_2 \mapsto v_{i2}] + e_2 \Downarrow^{j_2} v'_i}{\gamma_i + \text{let } x_1, x_2 = e_1 \text{ in } e_2 \Downarrow^{j_1 + j_2 + 1} v'_i}
$$

By induction hypothesis on $\Gamma; \Delta \vdash e_1 : \tau_{11} \Sigma_{11} \Sigma_{12} : \tau_{12} : \Sigma_1$ we know that $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta', \Sigma_1}^k[\Delta'(\tau_{11} \Sigma_{11} \otimes \Sigma_{12} \tau_{12})],$ i.e. if $\gamma_1 \vdash e_1 \Downarrow^{j_1} \langle v_{11}, v_{12} \rangle$ and $\gamma_2 \vdash e_1 \Downarrow^{j_1} \langle v_{21}, v_{22} \rangle$,

then $(\langle v_{11}, v_{12} \rangle, \langle v_{21}, v_{22} \rangle) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j_1} [\Delta'(\tau_{11}) \Delta' \cdot \Sigma_{11} \otimes \Delta' \cdot \Sigma_{12} \Delta'(\tau_{12})]$, or equivalently $(v_{11}, v_{21}) \in \mathcal{V}_{\Delta' \cdot \Sigma_{1} + \Delta' \cdot \Sigma_{11}}^{k-j_1} \llbracket \Delta'(\tau_{11}) \rrbracket$, and $(v_{12}, v_{22}) \in \mathcal{V}_{\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_{12}}^{k-j_1} \llbracket \Delta'(\tau_{12}) \rrbracket$. By Lemma [C.1](#page-52-0) $\Delta' \cdot \Sigma_1$ + $\Delta' \cdot \Sigma_{11} = \Delta' \cdot (\Sigma_1 + \Sigma_{11})$, then $(v_{11}, v_{12}) \in \mathcal{V}_{\Delta' \cdot (\Sigma_1 + \Sigma_{11})}^{k-j}[\Delta'(\tau_{11})]$, and analogously $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_{12} =$ $\Delta' \cdot (\Sigma_1 + \Sigma_{12})$, then $(v_{22}, v_{22}) \in \mathcal{V}_{\Delta' \cdot (\Sigma_1 + \Sigma_{12})}^{k-j} [\Delta'(\tau_{12})]$

Also, by induction hypothesis on $\Gamma, x : \tau_{11}, x : \tau_{12}; \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Delta \cdot (\Sigma_1 + \Sigma_{12}))x_2 + e_2 : \tau_2$; Σ_2 + s_1x_1 + s_2x_2 , by choosing $k = k - j_1$

 $(\gamma_1[x_1 \mapsto v_{11}, x_2 \mapsto v_{12}], \gamma_2[x_1 \mapsto v_{21}, x_2 \mapsto v_{22}]) \in \mathcal{G}_{\Delta' + (\Delta'(\Sigma_1 + \Sigma_{11}))x_1 + (\Delta'(\Sigma_1 + \Sigma_{12}))x_2}^{\Delta - 1}[\Gamma, x : \tau_{11}]$ (note that $x_1 \notin dom(\Sigma_1) \cup dom(\Sigma_{11})$ and $x_2 \notin dom(\Sigma_1) \cup dom(\Sigma_{12})$, therefore $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x_1 +$ $(\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2)(\tau_{1i}) = \Delta'(\tau_{1i})$ we know that

 $(y_1 \vdash e_2, y_2 \vdash e_2) \in \mathcal{E}_{\Sigma'' \cdot (\Sigma_2 + s_1 x_1 + s_2 x_2)}^{k-j_1} \left[\Sigma''(\tau_2) \right],$

for $\gamma_i = \gamma_1[x_1 \mapsto v_{i1}, x_2 \mapsto v_{i2}], \Sigma'' = \Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2$.

But $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2) \cdot (\Sigma_2 + s_1x_1 + s_2x_2) = \Delta' \cdot \Sigma_2 + s_1(\Delta' \cdot (\Sigma_1 + \Sigma_{11})) + s_2(\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2$ (Σ_{12}) = $\Delta' \cdot (s_1(\Sigma_1 + \Sigma_{11}) + s_2(\Sigma_1 + \Sigma_{12}) + \Sigma_2)$, and by Lemma [C.2](#page-55-0) and because $\Delta' \cdot (\Sigma_1 + \Sigma_{1i}) \in \text{sens}$, then $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2)(\tau_2) = ((\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2)(\Delta'(\tau_2)),$ and by Lemma [7.6](#page-42-0) $((\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x_1 + (\Delta' \cdot (\Sigma_1 + \Sigma_{12}))x_2)(\Delta'(\tau_2)) = \Delta'([\Sigma_1 + \Sigma_{11}/x_1][\Sigma_1 + \Sigma_{12}/x_2]\tau_2).$ Therefore if $\gamma_1 \vdash e_2 \Downarrow^{j_2} v'_1$, and $\gamma_2 \vdash e_2 \Downarrow^{j_2} v'_2$, then

 $(v_{21}, v_{22}) \in \mathcal{V}_{\Delta' \cdot (s_1(\Sigma_1 + \Sigma_{11}) + s_2(\Sigma_1 + \Sigma_{12}) + \Sigma_2)}^{\mathbf{k} - j_1 - j_2} [\Delta'([\Sigma_1 + \Sigma_{11}/x_1][\Sigma_1 + \Sigma_{12}/x_2]\tau_2)],$ and the result holds by Lemma [C.11.](#page-68-0) \blacksquare

Case (18) $\Gamma; \Delta \vdash (e' :: \tau) : \tau; \Sigma$

SUBPROOF. We have to prove that for any k , $\forall (y_1, y_2) \in G_{\Delta'}^{k-1}[\![\Gamma]\!], (y_1 + (e' :: \tau), y_2 + (e' :: \tau)) \in$ $\mathcal{E}^k_{\Delta' \cdot \Sigma}[\![\Delta'(\tau)]\!]$, for $\Delta' \sqsubseteq \Delta$. By induction hypothesis on $\Gamma; \Delta \vdash e' : \tau'$; Σ where $\tau' \leq \tau$, we know that $(\gamma_1 \vdash e', \gamma_2 \vdash e') \in \mathcal{E}_{\Delta' \cdot \Sigma}^k[\Delta'(\tau')]$, i.e. if $\gamma_1 \vdash e' \Downarrow^j v_1$ and $\gamma_2 \vdash e' \Downarrow^j v_2$, then $(v_1, v_2) \in \mathcal{V}_{\Delta' \cdot \Sigma}^{k-j}[\Delta'(\tau')]$. Following the ASCR reduction rule, if:

$$
\frac{\gamma_i \vdash e' \Downarrow^j v_i}{\gamma_i \vdash e' :: \tau \Downarrow^{j+1} v_i}
$$

Then we have to prove that $(v_1, v_2) \in \mathcal{V}_{\Delta', \Sigma}^{k-j-1}[\Delta'(\tau)]$. As $\tau' \leq \tau$, by Lemma [C.6](#page-65-0) $\Delta'(\tau') \leq \Delta'(\tau)$, and the result holds immediately by Lemma [C.11.](#page-68-0)

Case (19) $\Gamma; \Delta \vdash \lambda^{\mathcal{P}}(x : \tau_1 \cdot d')$. e' : $(x : \tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2$; \varnothing SUBPROOF. We have to prove that $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!],$

 $(\gamma_1 \vdash \lambda^p(x : \tau_1 \cdot d'))$. e', $\gamma_2 \vdash \lambda^p(x : \tau_1 \cdot d')$. e') $\in \mathcal{E}_{\Delta}^k$ \mathbb{Z}^N $\Delta'(x : \tau_1 \cdot d') \xrightarrow{\Delta' \cdot \Sigma''} \Delta'(\tau_2)$, for $\Delta' \sqsubseteq \Delta$. Notice that $\Delta' \otimes = 0$, and that lambdas reduce to closures, therefore we have to prove that

 $(\langle \lambda^p(x : \tau_1 \cdot d'), e', \gamma_1 \rangle, \langle \lambda^p(x : \tau_1 \cdot d'), e', \gamma_2 \rangle) \in \mathcal{V}_{0}^k[[x : \Delta'(\tau_1) \cdot d') \xrightarrow{\Delta' \cdot \Sigma''} \Delta'(\tau_2)]]$

Consider $j < k$, v_1 and v_2 such that $(v_1, v_2) \in \mathcal{V}_{d''}^j[\![\Delta'(\tau_1)]\!]$, for some $d'' \le d'$. We have to prove that $(y_1, x \mapsto v_1 + e', y_2, x \mapsto v_2 + e') \in \mathcal{E}^j_{(\Delta' + d''x) \cdot \Sigma''}[[d''x(\Delta'(\tau_2))]]$. Notice that by Lemma [C.2](#page-55-0) $d''x(\Delta'(\tau_2)) =$ $(\Delta' + d''x)(\tau_2)$, therefore we have to prove that $(\gamma_1, x \mapsto v_1 + e', \gamma_2, x \mapsto v_2 + e') \in \mathcal{E}^j_{(\Delta' + d''x) \cdot \Sigma''}[(\Delta' + d''x)(\Delta' + d''x)]$ $d''x)(\tau_2)$.

By induction hypothesis on Γ , $x : \tau_1$; $\Delta + d'x + e' : \tau_2$; Σ'' , and choosing $\Sigma^{\chi} = \Delta' + d''x \equiv \Delta' + d'x$, we know that $\forall \gamma_1, \gamma_2, (\gamma_1, \gamma_2) \in \mathcal{G}^{j-1}_{(\Delta'+d''x)}[\Gamma, x : \tau_1]$ then $(\gamma_1 \vdash e', \gamma_2 \vdash e') \in \mathcal{E}^{j}_{(\Delta'+d''x)\cdot \Sigma''}[(\Delta'+d''x)(\tau_2)]$. As $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{j}[\Gamma]$ (by Lemma [C.11\)](#page-68-0), $(v_1, v_2) \in \mathcal{V}_{d''}^{j}[\Delta'(\tau_1)]$, and $\Delta'(\tau_1) = (\Delta' + d''x)(\tau_1)$ (as x is The $\{r_1, r_2\} \subset \mathcal{B}_{\Delta'}[1\mathbb{I}]$ (by Extrima C.1), $\{v_1, v_2\} \subset \mathcal{F}_{d''}[2\mathbb{I}]\}$, and $\Delta(\mathcal{E}_1) = (\Delta + \mathcal{E}_2 \mathbb{I})/(\mathcal{E}_3 \times \mathcal{E}_4)$
not free in τ_1), it is easy to see that $(\gamma_1, x \mapsto v_1, \gamma_2, x \mapsto v_2) \in \mathcal{G}_{$ follows by choosing $\gamma_1 = \gamma_1, x \mapsto v_1$, and $\gamma_2 = \gamma_2, x \mapsto v_2$.

Let us prove now Part (2). We always prove one direction (\leq) as the other is analogous.

Case (1) $\Gamma; \Delta \vdash e_1 \cdot e_2 : [\Sigma_2/x] \tau_2 ; [\Sigma_1 \upharpoonright^\infty + [\Sigma_2/x] \Sigma''$

Subproof. We have to prove that

 $\forall k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!],$ for $\Delta' \sqsubseteq \Delta$, then $(\gamma_1 \vdash e_1 \ e_2, \gamma_2 \vdash e_1 \ e_2) \in \mathcal{E}_{\Delta', \Sigma}^k[\![\Delta'([\![\Sigma_2/x]\!] \tau_2)]\!].$ By induction hypotheses we know that

 $\Gamma; \Delta \vdash e_1 : (x : \tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2 : \Sigma_1 \Rightarrow (\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'((x : \tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2)]$ and $\Gamma; \Delta \vdash e_2 : \tau_1 : \Sigma_2 \Longrightarrow (\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}_{\Delta' \cdot \sum_{i=1}^{\ell-1}}^{\Delta'_{i}} [\Delta'(\tau_1)]$

As $\Delta'((x:\tau_1 \cdot d') \xrightarrow{\Sigma''} \tau_2) = (x:\Delta'(\tau_1) \cdot d') \xrightarrow{\Delta' \cdot \Sigma''} \Delta'(\tau_2)$, by unfolding $(\gamma_1 \vdash e_1, \gamma_2 \vdash e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[[x:\Delta'] \rightarrow \Delta' \cdot \Delta' \cdot \Delta']$ $\Delta'(\tau_1) \cdot d'$ $\xrightarrow{\Delta' \Sigma''}$ $\Delta'(\tau_2)$, we know that if $\gamma_1 \vdash e_1 \Downarrow^{j_1} \langle \lambda^p(x : \tau_1), e'_1, \gamma_1 \rangle$ and $\gamma_2 \vdash e_1 \Downarrow^{j_1} \langle \lambda^p(x : \tau_1), e'_1, \gamma_1 \rangle$ τ_1). e'_2 , γ_2 then

 $(\langle \lambda^p(x:\tau_1), e'_1, \gamma_1 \rangle, \langle \lambda^p(x:\tau_1), e'_2, \gamma_2 \rangle) \in \mathcal{V}_{\Delta' \cdot \Sigma_1}^{k-j_1}[[x:\Delta'(\tau_1) \cdot d'] \xrightarrow{\Delta' \cdot \Sigma''} \Delta'(\tau_2)]]$ (for $d'' > = d'$) (1).

Also, by unfolding $(\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \mathcal{E}_{\Delta' \cdot \Sigma_2}^{k-j_1} [\Delta'(\tau_1)]$, if $\gamma_1 \vdash e_2 \Downarrow^{j_2} v_1$ and $\gamma_2 \vdash e_2 \Downarrow^{j_2} v_2$ then $(v_1, v_2) \in \mathcal{V}_{\Delta' \cdot \Sigma_2}^{k-j_1-j_2} \llbracket \Delta'(\tau_1) \rrbracket.$

By P-APP we know that $\Delta \cdot \Sigma_2 \leq d'$, as $\Delta' \subseteq \Delta$ then $\Delta' \cdot \Sigma_2 \leq d'$. Then we instantiate (1) with $d'' = \Delta' \cdot \Sigma_2$, then for some $j_3 < k - j_1 - j_2$

 $(\gamma_1[x \mapsto v_1] \vdash e'_1, \gamma_2[x \mapsto v_2] \vdash e'_2) \in \mathcal{E}_{\lceil \Delta' \cdot \Sigma_1 \rceil^{\infty} + (\Delta' + (\Delta' \cdot \Sigma_2)x) \cdot \Sigma''}^{\jmath_3}[(\Delta' \cdot \Sigma_2 x)(\Delta'(r_2))]$ (2).

Suppose $\Delta' \cdot \lceil \Sigma_1 \rceil^{\infty} = 0$ (otherwise the result follows immediately). Then $\Delta' \cdot \Sigma = \Delta' \cdot ([\Sigma_2/x] \Sigma'')$. Also as $\Delta' \subseteq \Delta$, and $x \notin dom(\Delta)$, then by Lemma [7.5,](#page-42-1) $\Delta' \cdot ([\Sigma_2/x]\Sigma' = ((\Delta' \cdot \Sigma_2)x) \cdot (\Delta' \cdot \Sigma'') =$ $(Δ' + (Δ'·Σ₂)x)·Σ''$. By Lemma [7.6,](#page-42-0) $[Δ'·Σ₂/x]Δ'(τ₂) = Δ'([Σ₂/x]τ₂)$, then by (1) and weakening $(\text{Lemma C.10}) (\gamma_1[x \mapsto v_1] \vdash e'_1, \gamma_2[x \mapsto v_2] \vdash e'_2) \in \mathcal{E}_{\Delta' \cdot \Sigma}^{j_3} \left[\Delta'([\Sigma_2/x] \tau_2) \right] \tag{3}.$

Notice that $[\![\mathbf{e}_1 \ \mathbf{e}_2]\!]_{Y_i}^k = [\![\mathbf{e}'_i]\!]_{Y_i[\chi \mapsto v_i]}^{k-j_1-j_2-1}$ $\frac{k-j_1-j_2-1}{\gamma_i[x\mapsto v_i]}$, and (3) holds in particular for $j_3=k-j_1-j_2-1 < k-j_1-j_2$ The result follows by Lemma [C.17.](#page-69-0)

Case (2) Γ ; Δ + case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$: $[\Sigma_{11}/x] \tau_2 \sqcup [\Sigma_{12}/y] \tau_3$; $[\Sigma_1 \ulcorner \infty \sqcup [\Sigma_{11}/x] \Sigma_2 \sqcup \Sigma_{12}/y]$ $[\Sigma_{12}/x]\Sigma_3$

SUBPROOF. We have to prove that for any $k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!]$, for $\Delta' \sqsubseteq \Delta$ $(y_1 \vdash \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{y \Rightarrow e_3\}, y_2 \vdash \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{y \Rightarrow e_3\}) \in \mathcal{E}_{\Delta', \Sigma}^k[\Delta'(r)]$ By induction hypothesis on Γ ; $\Delta \vdash e_1 : \tau_{11} \stackrel{\Sigma_{11}}{\sim} \oplus \stackrel{\Sigma_{12}}{\sim} \tau_{12}$; Σ_1 , we know that $(y_1 + e_1, y_2 + e_1) \in \mathcal{E}_{\Delta' \cdot \Sigma_1}^k[\Delta'(\tau_{11} \Sigma_{11} \oplus \Sigma_{12} \tau_{12})],$ i.e. if $y_1 + e_1 \Downarrow^{j_1} v_{11}$, and $y_2 + e_1 \Downarrow^{j_1} v_{12}$ then $(v_{11}, v_{12}) \in$ $\mathcal{V}_{\Delta' \cdot \Sigma_{11}}^{k-j_1} [\Delta'(\tau_{11}) \Delta' \cdot \Sigma_{11} \oplus \Delta' \cdot \Sigma_{12} \Delta'(\tau_{12})]$. Notice that $\Delta' \cdot \Sigma = \Delta' \cdot [\Sigma_1 \upharpoonright^{\infty} \sqcup \Delta' \cdot ([\Sigma_{11}/x] \Sigma_2) \sqcup \Delta' \cdot ([\Sigma_{12}/x] \Sigma_3)$. If $\Delta' \cdot |\Sigma_1|^{ \infty} = \infty$ then the result is trivial and holds immediately. Let us suppose that $\Delta' \cdot |\Sigma_1|^{ \infty} = 0$, then this means that $\Delta' \cdot \Sigma_1 = 0$, i.e. either $v_{11} = \text{inl } v'_{11}$ and $v_{12} = \text{inl } v'_{12}$, or $v_{11} = \text{inr } v'_{11}$ and $v_{12} = \text{inr } v'_{12}.$

Let us suppose that $(v_{11}, v_{12}) = (\text{inl } v'_{11}, \text{inl } v'_{12})$ (the case $(v_{11}, v_{12}) = (\text{inr } v'_{11}, \text{inr } v'_{12})$ is analo-gous). By Lemma [C.1](#page-52-0) $\Delta' \cdot \Sigma_1 + \Delta' \cdot \Sigma_{11} = \Delta' \cdot (\Sigma_1 + \Sigma_{11})$, then $(v'_{11}, v'_{12}) \in \mathcal{V}_{\Delta' \cdot (\Sigma_1 + \Sigma_{11})}^{k-j_1} \left[\Delta'(\tau_{11}) \right]$.

Also, by induction hypothesis on Γ , $x : \tau_{11}$; $\Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2 : \Sigma_2$, by choosing $\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11})) x \sqsubseteq \Delta + (\Delta \cdot (\Sigma_1 + \Sigma_{11})) x, (\gamma_1[x \mapsto v'_{12}], \gamma_2[x \mapsto v'_{22}]) \in \mathcal{G}_{\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11})) x}^{k-j_1 - 1} [\Gamma, x : \tau_{11}]$ (note that $x \notin dom(\Sigma_1) \cup dom(\Sigma_{11})$, therefore $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x)(\tau_{11}) = \Delta'(\tau_{11})$) we know that $(\gamma_1[x \mapsto v_{12}'] \vdash e_2, \gamma_2[x \mapsto v_{22}'] \vdash e_2) \in \mathcal{E}^{k-j_1}_{(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x) \cdot \Sigma_2} [(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x)(r_2)]$

But $\Delta' \cdot \Sigma_1 = 0$, therefore $(\Delta' + (\Delta' \cdot (\Sigma_1 + \Sigma_{11}))x) \cdot \Sigma_2 = (\Delta' + (\Delta' \cdot \Sigma_{11})x) \cdot \Sigma_2$, and $\Delta' \cdot (\Sigma_1 + \Sigma_{11}) = \Delta' \cdot \Sigma_{11}$, and by Lemma [C.2](#page-55-0) and because $\Delta' \cdot \Sigma_{11} \in$ sens, then $(\Delta' + (\Delta' \cdot \Sigma_{11})x)(\tau_2) = (\Delta' \cdot \Sigma_{11})x(\Delta'(\tau_2))$, and by Lemma [7.6](#page-42-0) $(\Delta' \cdot \Sigma_{11})x(\Delta'(\tau_2)) = \Delta'([\Sigma_{11}/x]\tau_2)$.

Then by weakening lemma [C.10](#page-67-0) we know that

 $(\gamma_1[x \mapsto v_{12}'] + e_2, \gamma_2[x \mapsto v_{22}'] + e_2) \in \mathcal{E}^{k-j_1}_{(\Delta' + (\Delta' \cdot \Sigma_{11})x) \cdot \Sigma_2}[\Delta'([\Sigma_{11}/x] \tau_2)]]$. Notice that by Lemma [C.8,](#page-66-0) Σ_2 <: $\Sigma_2 \sqcup \Sigma_3$, and then by Lemma [C.13](#page-69-1) ($\Delta' + (\Delta' \cdot \Sigma_{11}) \times \Delta' \cdot \Sigma_2$ <: $(\Delta' + (\Delta' \cdot \Sigma_{11}) x) \cdot \Sigma_2 \sqcup (\Delta' + (\Delta' \cdot \Sigma_{12}) x) \cdot \Sigma_3$. Also by Lemma [C.9](#page-66-1) $[\Sigma_{11}/x]\tau_2 < :[\Sigma_{11}/x]\tau_2 \sqcup [\Sigma_{12}/y]\tau_3$, therefore by Lemma [C.6,](#page-65-0) $\Delta'([\Sigma_{11}/x]\tau_2) < :$ $\Delta'([\Sigma_{11}/x]\tau_2 \sqcup [\Sigma_{12}/y]\tau_3)$. Once again by Lemma [C.10,](#page-67-0) $(\gamma_1[x \mapsto v'_{12}] \vdash e_2, \gamma_2[x \mapsto v'_{22}] \vdash e_2) \in$ $\mathcal{E}^{k-j_1}_{\Delta'\cdot\Sigma}[\![\Delta'(\tau)]\!]$ (3).

Notice that $\llbracket \mathsf{case}\ e_1 \text{ of }\{x\Rightarrow \mathsf{e}_2\}\ \{y\Rightarrow \mathsf{e}_3\}\rrbracket_{\gamma_i}^k = \llbracket \mathsf{e}_2\rrbracket_{\gamma_i\left[x\right]}^{k-j_1}$ $\frac{\kappa - j_1}{\gamma_i [x \mapsto v_{i2}']},$ then result follows by Lemma [C.17.](#page-69-0) ⊳

Case (3) Γ; Δ + return $e_1 : [\varnothing/\widehat{x}] \tau$; $[\Sigma_1]^{\infty}$ + $\text{FP}^{\infty}(\tau)$

SUBPROOF. Where $\hat{x} = FV(FP^{\infty}(\tau))$. We have to prove that for any k , $\forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!]$, , for Δ ′ [⊑] ^Δ

 $(\gamma_1 \vdash \text{return } e_1, \gamma_2 \vdash \text{return } e_1) \in \mathcal{E}_{\Delta' \cdot (\lceil \Sigma_1 \rceil^{\infty} + \text{FP}^{\infty}(\tau))}^k[\Delta'([\varnothing/\widehat{x}]\tau)]$

Note that $\Delta' \cdot (\sum_{i} \lceil \infty + FP^{\infty}(\tau) \rceil)$ is either ∞ or 0. If $\Delta' \cdot (\sum_{i} \lceil \infty + FP^{\infty}(\tau) \rceil) = \infty$ then the result is direct by Lemma [C.14.](#page-69-2) Let us assume that $\Delta' \cdot (\lceil \Sigma_1 \rceil^{\infty} + \text{FP}^{\infty}(\tau)) = \lceil \Delta' \cdot \Sigma_1 \rceil^{\infty} + \Delta' \cdot \text{FP}^{\infty}(\tau) = 0.$ By induction hypothesis on Γ ; $\Delta \vdash e_1 : \tau$; Σ_1 , we know that

 $(y_1 + e_1, y_2 + e_1) \in \mathcal{E}_{\Delta', \Sigma_1}[\Delta'(\tau)],$ i.e. if $y_1 + e_1 \Downarrow' v_1$, and $y_2 + e_1 \Downarrow' v_2$ then $(v_1, v_2) \in \mathcal{V}_{\Delta', \Sigma_1}^{k-j}[\Delta'(\tau)].$ Notice that $\Delta' \cdot \Sigma_1 = 0$, and $\Delta' \cdot FP^{\infty}(\tau) = 0$, then $\Delta'(\tau) = \Delta_{\emptyset}(\tau)$, where $\forall x_i \in FP^{\infty}(\tau)$, $\Delta_{\emptyset}(x_i) = 0$. Then $(v_1, v_2) \in \mathcal{V}_0^{k-j}[\Delta_{\emptyset}(\tau)]$. Note that $\Delta'([\emptyset/\widehat{x}]\tau) = \Delta_{\emptyset}(\tau)$. Notice that by (3), then $v_1 \approx k-j$ v_2 .

Let $S \subseteq val^k_*$. Let us use notation $v \in S$ iff $\exists v' \in S$ s.t. $v' \approx^{k-j} v$. We have to prove that $Pr[y_1 \in S]$ return $e_1 \parallel^k S$ \leq Pr[γ_2 + return $e_2 \parallel^k S$] (the other direction is analogous). If $v_1 \notin S$ then the result is trivial as Pr[γ_1 ⊢ return $e_1 \Downarrow^k S$] = 0 and $0 \le \Pr[\gamma_2 \vdash \text{return } e_2 \Downarrow^k S$]. Let us suppose that $v_1 \in S$, then we know that $\exists v' \in S$ such that $v' \approx^{k-j} v_1$. As $v_1 \approx^{k-j} v_2$, then by transitivity (Lemma [C.15\)](#page-69-3) we know also that $v' \approx^{k-j} v_2$, therefore $v_2 \in S$ and thus $Pr[y_2 \vdash \text{return } e_2 \Downarrow^k v_2'] = 1$, and $Pr[y_2 \vdash return e_2 \Downarrow k] = 1$, so the result holds.

Case (4) Γ ; $\Delta \vdash x : \tau_1 \leftarrow e_1$; $e_2 : [\varnothing/x] \tau_2$; $\Sigma_1 + \Sigma_2$

SUBPROOF. Let $dval = val^{k-k'}_{*}(\tau_1/\Gamma)$. We have to prove that for any $k, \forall (\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\Gamma],$ for Δ ′ [⊑] ^Δ

 $(\gamma_1 \vdash x : \tau_1 \leftarrow e_1 : e_2, \gamma_2 \vdash x : \tau_1 \leftarrow e_1 : e_2) \in \mathcal{E}_{\Delta'}^k(\Sigma_1 + [\emptyset/x] \Sigma_2) [\Delta'([\emptyset/x] \tau_2)]$

By induction hypothesis on Γ ; $\Delta \vdash e_1 : \tau_1$; $\overline{\Sigma}_1$, we know that

 $(y_1 \vdash e_1, y_2 \vdash e_1) \in \mathcal{E}_{\Delta', \Sigma_1}^k[\Delta'(\tau_1)],$ i.e. let $(\epsilon_1, \delta_1) = \Delta' \cdot \Sigma_1$, $\forall S \subseteq val^k$, for $j \leq k \Pr[y_1 \vdash e_1 \Downarrow^k S] \leq k \Pr[y_1 \vdash e_1 \Downarrow^k S]$ $e^{\epsilon_1} \Pr[\gamma_2 \vdash e_1 \Downarrow^k S] + \delta_1.$

Similarly, by induction hypothesis on Γ , x : τ_1 ; $\Delta + 0x + e_2$: τ_2 ; Σ_2 , choosing $(\gamma_1, \gamma_2) \in$ $G_{\Delta'+0\alpha}^{k-k'-1}[\Gamma, x : \tau_1],$ for some $k' \leq k$, and $\Delta' + 0x \subseteq \Delta + 0x$, we know that $(\gamma_1 \vdash e_2, \gamma_2 \vdash e_2) \in \Delta + 0$. $\mathcal{E}^{k-k'}_{(\Delta'+0x)\Sigma_2}[(\Delta'+0x)(\tau_2)]$. Notice that by Lemma [7.5,](#page-42-1) $(\Delta'+0x)\cdot\Sigma_2 = \Delta' \cdot ([\emptyset/x]\Sigma_2)$ as $x \notin dom(\Delta')$, and that by Lemma [7.4,](#page-41-0) $(\Delta' + 0x)(\tau_2) = \Delta'([\varnothing/x]\tau_2)$. Then let $(\epsilon_2, \delta_2) = \Delta' \cdot [\varnothing/x]\Sigma_2$, $\forall S' \in val_*^{k-k'}$, $\Pr[\gamma_1 \vdash e_2 \Downarrow^{k-k'} S'] \leq e^{\epsilon_2} \Pr[\gamma_2 \vdash e_2 \Downarrow^{k-k'} S'] + \delta_2.$ We have to prove then that $\forall S' \in val^k_*$, let $(\epsilon_1 + \epsilon_2, \delta_1 + \delta_2) = \Delta' \cdot \Sigma_1 + \Delta' \cdot [\emptyset / x] \Sigma_2 = \Delta' \cdot (\Sigma_1 + [\emptyset / x] \Sigma_2)$

$$
\begin{aligned}\n\llbracket x:\tau_1 \leftarrow e_1; e_2 \rrbracket_{\gamma_1}^k S &\leq e^{\epsilon_1+\epsilon_2} (\llbracket x:\tau_1 \leftarrow e_1; e_2 \rrbracket_{\gamma_2}^k S) + \delta_1 + \delta_2 \\
\sum_{v_1 \in S'} \llbracket x:\tau_1 \leftarrow e_1; e_2 \rrbracket_{\gamma_1}^k v_1 &\leq e^{\epsilon_1+\epsilon_2} (\sum_{v_2 \in S'} \llbracket x:\tau_1 \leftarrow e_1; e_2 \rrbracket_{\gamma_2}^k k' v_2) + \delta_1 + \delta_2 \\
\sum_{v_1 \in S'} \sum_{v \in dval} \llbracket e_1 \rrbracket_{\gamma_1}^k (v) \times \llbracket e_2 \rrbracket_{\gamma_1}^{k-k'} (v_1) &\leq e^{\epsilon_1+\epsilon_2} (\sum_{v_2 \in S'} \sum_{v \in dval} \llbracket e_1 \rrbracket_{\gamma_2}^k (v) \times \llbracket e_2 \rrbracket_{\gamma_2}^{k-k'} (v_2) + \delta_1 + \delta_2\n\end{aligned}
$$

As $k-k' \leq k$, by induction hypothesis $(v, v) \in \mathcal{V}_0^{k-k'-1} \llbracket \tau_1/\Gamma \rrbracket$, but $\tau_1/\Gamma = \Delta_{\varnothing}(\tau_1)$, and by weakening lemmas [C.11,](#page-68-0) and [C.10](#page-67-0) $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-k'-1}[\![\Gamma]\!]$, then we can choose $(\gamma_1, \gamma_2) = (\gamma_1[x \mapsto v], \gamma_2[x \mapsto v]$ v]) and know that that $\sum_{v_1 \in S'} [e_2]_{\gamma_1[x \mapsto v]}^{k-k'}(v_1) \leq e^{\epsilon_2} (\sum_{v_2 \in S'} [e_2]_{\gamma_2[x \mapsto v]}^{k-k'}(v_2)) + \delta_2$. Also notice that $\sum_{v_1 \in S'} [e_2]_{\gamma_1[x \mapsto v]}^{k-k'}(v_1)$ is a probability therefore $\sum_{v_1 \in S'} [e_2]_{\gamma_1}^{k-k'}(v_1) \leq min(e^{\epsilon_2} (\sum_{v_2 \in S'} [e_2]_{\gamma_2}^{k-k'}(v_2)) + \delta_2, 1) \leq min(e^{\epsilon_2} (\sum_{v_2 \in S'} [e_2]_{\gamma_2}^{k-k'}(v_2)) + \delta_2, 1)$ δ_2 . Then

$$
\begin{split}\n&= \sum_{v_1 \in S'} \sum_{v \in val} [\![e_1]\!]_{Y_1}^k(v) \times [\![e_2]\!]_{Y_1[x \mapsto v]}^{k-k'}(v_1) \\
&= \sum_{v \in dval} [\![e_1]\!]_{Y_1}^k(v) \times (\sum_{v_1 \in S'} [\![e_2]\!]_{Y_1[x \mapsto v]}^{k-k'}(v_1)) \\
&\leq \sum_{v \in dval} [\![e_1]\!]_{Y_1}^k(v) \times (min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]_{Y_2[x \mapsto v]}^{k-k'}(v_2)), 1) + \delta_2) \\
&= (\sum_{v \in dval} [\![e_1]\!]_{Y_1}^k(v) \times min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]_{Y_2[x \mapsto v]}^{k-k'}(v_2)), 1)) + (\sum_{v \in dval} [\![e_1]\!]_{Y_1}^k(v) \times \delta_2) \\
&\leq \sum_{v \in dval} [\![e_1]\!]_{Y_1}^k(v) \times min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]_{Y_2[x \mapsto v]}^{k-k'}(v_2)), 1) + \delta_2\n\end{split}
$$

Let $S = dval$, then we know that $\sum_{v \in dval} [e_1]_{\gamma_1}^k(v) \le e^{\epsilon_1} (\sum_{v \in dval} [e_1]_{\gamma_2}^k(v)) + \delta_1$. Let $\mu_v = [\![e_1]\!]_{\gamma_1}^k(v) - e^{\epsilon_1} [\![e_1]\!]_{\gamma_2}^k(v)$, then we know that $\sum_{v \in dval} \mu_v \leq \delta_1$.

Then

$$
\sum_{v \in dval} [\![e_1]\!]^k_{Y_1}(v) \times min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2)), 1) + \delta_2
$$
\n
$$
= \sum_{v \in dval} (e^{\epsilon_1} [\![e_1]\!]^k_{Y_2}(v) + \mu_v) \times min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2)), 1) + \delta_2
$$
\n
$$
\leq \sum_{v \in dval} (e^{\epsilon_1} [\![e_1]\!]^k_{Y_2}(v) \times e^{\epsilon_2} \sum_{v_2 \in S'} [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2) + min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2)), 1) \mu_v) + \delta_2
$$
\n
$$
= \sum_{v_2 \in S'} \sum_{v \in dval} e^{\epsilon_1 + \epsilon_2} [\![e_1]\!]^k_{Y_2}(v) \times [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2) + (\sum_{v \in dval} min(e^{\epsilon_2}(\sum_{v_2 \in S'} [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2)), 1) \mu_v + \delta_2
$$
\n
$$
\leq e^{\epsilon_1 + \epsilon_2}(\sum_{v_2 \in S'} \sum_{v \in dval} ([\![e_1]\!]^k_{Y_2}(v) \times [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2)) + (\sum_{v \in dval} \mu_v) + \delta_2
$$
\n
$$
\leq e^{\epsilon_1 + \epsilon_2}(\sum_{v_2 \in S'} \sum_{v \in dval} ([\![e_1]\!]^k_{Y_2}(v) \times [\![e_2]\!]^{k-k'}_{Y_2[x \mapsto v]}(v_2)) + \delta_1 + \delta_2
$$

and the result holds. ⊳

Let us prove now Part 3: Let Δ_{\emptyset} , such that $\Delta_{\emptyset}(x) = 0$, for all $x \in FV(\tau)$. If $(v_1, v_2) \in \mathcal{V}_0^k[\![\Delta_{\emptyset}(\tau)]\!]$ then $v_1 \approx^k v_2$. We prove Part (3) by induction on k and type τ . Case (1) $\tau = (x : \tau_1 \cdot s_1) \xrightarrow{\Sigma'' + s'x} \tau_2$

SUBPROOF. We know that $(\langle \lambda^s x : \tau_1 \cdot s_1 \cdot e_1, \gamma_1 \rangle, \langle \lambda^s x : \tau_1 \cdot s_1 \cdot e_2, \gamma_2 \rangle) \in \mathcal{V}_0^k[[x : \Delta_{\emptyset}(\tau_1) \cdot s_1) \xrightarrow{s'x} \Delta_{\emptyset}(\tau_2)]]$, and that for some Γ, Δ' $(\gamma_1, \gamma_2) \in \mathcal{G}_{\Delta'}^{k-1}[\![\Gamma]\!]$. Take some $\emptyset; \emptyset \vdash v : \tau; \emptyset$. Notice that $\emptyset(\tau_1) = \Delta_{\emptyset}(\tau_1)$ $(\tau_1$ has no free variables). We know by induction hypothesis that $(v, v) \in \mathcal{V}_0^{k-1}[\![\Delta_\varnothing(\tau_1)]\!]$, therefore we know that $(\gamma_1, x \mapsto v \vdash e_1, \gamma_2, x \mapsto v \vdash e_2) \in \mathcal{E}_{0+0s'}^j[(\Delta_{\emptyset} + 0x)(\tau_2)]$. By unfolding of this last definition we know that if γ_i , $x \mapsto v \vdash e_i \Downarrow^j v'_i$, then $(v'_1, v'_2) \in \mathcal{V}_0^{k-j-1}[[(\Delta_{\emptyset} + 0x)(\tau_2)]]$. Then by induction hypothesis we know that $v'_1 \approx^{k-j-1} v'_2$, and the result holds.

Case (2)
$$
\tau = (x : \tau_1 \cdot s_1) \xrightarrow{\Sigma} \tau_2
$$

SUBPROOF. We know that $(\langle \lambda^* x : \tau_1 \cdot s_1 \cdot e_1, \gamma_1 \rangle, \langle \lambda^* x : \tau_1 \cdot s_1 \cdot e_2, \gamma_2 \rangle) \in \mathcal{V}_0^k[(x : \Delta_{\varnothing}(\tau_1) \cdot s_1) \xrightarrow{\Delta_{\varnothing} \cdot \Sigma}$ SUBPROOF. We know that $((λ x : τ₁·s₁.e₁, γ₁), (λ x : τ₁·s₁.e₂, γ₂)) ∈ 'V₀^o[[x : Δ_Ø(τ₁)₅₁) →
Δ_Ø(τ₂)], and that for some Γ, Δ' (γ₁, γ₂) ∈ G_{Δ'}^{k-1}[[Γ]. Take some ∅; ∅ + v :$ $\Delta_{\varnothing}(\tau_1)$ (τ_1 has no free variables). We know by induction hypothesis that $(v, v) \in \mathcal{V}_0^{k-1}[\Delta_{\varnothing}(\tau_1)]$, therefore we know that $(\gamma_1, x \mapsto v \vdash e_1, \gamma_2, x \mapsto v \vdash e_2) \in \mathcal{E}^j_{(\Delta_{\emptyset} + 0x) \cdot \Sigma} [(\Delta_{\emptyset} + 0x)(\tau_2)]$. But $(\Delta_{\emptyset} + 0x) \cdot \Sigma =$ $(0, 0)$, as every value is scaled by 0. By unfolding of this last definition we know that for any v' , if $Pr[y_1, x \mapsto v \vdash e_1 \Downarrow^k v'] \wedge Pr[y_1, x \mapsto v \vdash e_2 \Downarrow^k v'],$ then

$$
\Pr[\gamma_1, x \mapsto v \vdash e_1 \Downarrow^k v'] \le e^0 \Pr[\gamma_1, x \mapsto v \vdash e_2 \Downarrow^k v'] + 0 \wedge \Pr[\gamma_1, x \mapsto v \vdash e_2 \Downarrow^k v'] \le
$$

$$
e^0 \Pr[\gamma_1, x \mapsto v \vdash e_1 \Downarrow^k v'] + 0
$$

i.e. $Pr[y_1, x \mapsto v \vdash e_1 \Downarrow^k v'] = Pr[y_1, x \mapsto v \vdash e_2 \Downarrow^k v'],$ and the result holds. Case (3) $\tau = \mathbb{R}$

SUBPROOF. We know that $(r_1, r_2) \in \mathcal{V}_0^k[\mathbb{R}]$, then $r_1 = r_2$ and the result holds immediately. Case (4) $\tau = \text{unit}$

SUBPROOF. We know that $(t_t, t) \in \mathcal{V}_0^k$ [[unit]], then $tt = tt$ and the result holds immediately. \prec Case (5) $\tau = \tau_1^{-\sum_1} \bigoplus_{\substack{2}}^{\sum_2} \tau_2$

SUBPROOF. We know that either (inl v_1 , inl v_1) $\in V_0^k[\Delta_{\emptyset}(\tau_1)] \oplus \Phi^0 \Delta_{\emptyset}(\tau_2)]$, or (inr v_1 , inr v_1) \in $\mathcal{V}_{\alpha}^{k}[\![\Delta_{\varnothing}(\tau_1)\!] \oplus \emptyset \Delta_{\varnothing}(\tau_2)]$. In the first case (the other is analogous), we know that $(\langle v_1, v_1 \rangle \in \mathcal{V}_{0+0}^k[\![\Delta_{\varnothing}(\tau_1)]\!]$. Then by induction hypothesis $v'_1 \approx^k v'_2$ and the result holds.

Case (6) $\tau = \tau_1^{-\sum_1} \&^{\sum_2} \tau_2$

SUBPROOF. We know that $(\langle v_{11}, v_{12} \rangle, \langle v_{21}, v_{22} \rangle) \in \mathcal{V}_0^k[\Delta_{\emptyset}(\tau_1) \otimes \mathcal{R}^0 \Delta_{\emptyset}(\tau_2)]$, then $(\langle v_{11}, v_{21} \rangle \in \mathcal{V}_{0+0}^k[\Delta_{\emptyset}(\tau_1)]$, and $(\langle v_{12}, v_{22} \rangle \in \mathcal{V}_{0+0}^k \llbracket \Delta_{\varnothing}(\tau_2) \rrbracket$.

 \Box

Then by induction hypotheses $v'_{11} \approx^k v'_{21}$ and $v'_{12} \approx^k v'_{22}$ and the result holds. Case (7) $\tau = \tau_1^{-\sum_1} \otimes^{\sum_2} \tau_2$

Subproof. Analogous to previous case. ⊳

Theorem C.19 (Sensitivity Type Soundness at Base Types). If $\varnothing; \varnothing \vdash e : (x : \mathbb{R} \cdot \infty) \xrightarrow{sx} \mathbb{R}$; \varnothing , $|r_1 - r_2| \leq s', \varnothing \vdash e \ r_1 \Downarrow r'_1, \varnothing \vdash e \ r_2 \Downarrow r'_2, \text{ then } |r'_1 - r'_2| \leq s s'$

PROOF. We know that $\emptyset \vdash e : (x : \mathbb{R} \cdot \infty) \stackrel{sx}{\longrightarrow} \mathbb{R}$; \emptyset therefore by the Fundamental Property (Theorem [C.18\)](#page-69-4), using $\gamma_1 = \emptyset$ and $\gamma_2 = \emptyset$, then $(\emptyset + e, \emptyset + e) \in \mathcal{E}_0^k[[x : \mathbb{R} \cdot \infty) \xrightarrow{sx} \mathbb{R}$, i.e. if $\emptyset \vdash e \Downarrow^{j_1} \langle \lambda x, e', \gamma \rangle$ then $(\langle \lambda x, e', \gamma \rangle, \langle \lambda x, e', \gamma \rangle) \in \mathcal{V}_0^{k-j_1}[[x : \mathbb{R}) \xrightarrow{sx} \mathbb{R}$, for some $k > j_1$.

RETURN $y \vdash e \Downarrow v$	BIND $\gamma \vdash e_1 \Downarrow v_1 \qquad \gamma[x \mapsto v_1] \vdash e_2 \Downarrow v_2$		GAUSS $r \in \mathbb{R}$	
return $e \parallel v$	$\gamma \vdash x : \tau_1 \leftarrow e_1 : e_2 \Downarrow v_2$		γ + gauss $\mu \sigma^2 \Downarrow r$	
IF-TRUE $\gamma \vdash e_1 \Downarrow \text{true}$ $\gamma \vdash e_2 \Downarrow v_2$		IF-FALSE	$\gamma \vdash e_1 \Downarrow$ false $\gamma \vdash e_3 \Downarrow v_3$	
$y \vdash$ if e_1 then $\{e_2\}$ else $\{e_3\} \Downarrow v_2$			$y \vdash$ if e_1 then $\{e_2\}$ else $\{e_3\} \Downarrow v_3$	
CASE-LEFT $\gamma \vdash e \Downarrow \text{inl} \ v \qquad \gamma[x \mapsto v] \vdash e_2 \Downarrow v_2$		CASE-RIGHT	$\gamma \vdash e \Downarrow \text{inr} \ v \qquad \gamma[x \mapsto v] \vdash e_3 \Downarrow v_3$	
γ + case e $\{x \Rightarrow e_2\}$ $\{x \Rightarrow e_3\} \Downarrow v_2$			γ + case e $\{x \Rightarrow e_2\}$ $\{x \Rightarrow e_3\} \Downarrow v_3$	
APP		$\gamma \vdash e_1 \Downarrow \langle \lambda x : \tau \cdot s. e', \gamma' \rangle$ $\gamma \vdash e_2 \Downarrow v$ $\gamma'[x \mapsto v] \vdash e' \Downarrow v'$		
		γ + e ₁ e ₂ $\parallel v'$		

Fig. 32. Non-deterministic sampling semantics for privacy expressions

We know that $\emptyset \vdash e \ r_1 \Downarrow^{k'} r_1'$, and $\emptyset \vdash e \ r_2 \Downarrow^{k'} r_2'$, for some $k' = j_1 + j_2$, and $k > j_1 + j_2$, i.e.

 Δ pp

$$
\frac{\partial F}{\partial t} + e \Downarrow^{j_1} \langle \lambda x. e', \gamma \rangle \qquad \gamma[x \mapsto r_i] + e' \Downarrow^{j_2} r'_i
$$

$$
\varnothing + e r_i \Downarrow^{k'} r'_i
$$

for some y and Γ such that $\Gamma, x : \mathbb{R} \vdash e' : \mathbb{R}$; sx, and $(\gamma, \gamma) \in \mathcal{G}_{\oslash}^{k-j_1-1}[\![\Gamma]\!]$. As $|r_1 - r_2| \leq s'$, $(\text{tan } (r_1, r_2) \in \mathcal{V}_{s'}^{k-j_1-1}[\mathbb{R}].$ We instantiate $(\langle \lambda x, e', \gamma \rangle, \langle \lambda x, e', \gamma \rangle) \in \mathcal{V}_{0}^{k-j_1}[\mathbb{I}(x : \mathbb{R} \cdot \infty) \xrightarrow{\text{ext}} \mathbb{R}]$ with $(r_1, r_2) \in \mathcal{V}_{s'}^{k-j_1-1}[\mathbb{R}]$ to know that $(y[x \mapsto r_1] \vdash e', y[x \mapsto r_2] \vdash e') \in \mathcal{E}_{0+0+ss'}^{k-j_1-1}[\mathbb{R}]$, i.e. if $y[x \mapsto t_1, t_2] \mapsto t_2$ $|r_i| + e' \Downarrow^{j_2} r'_i$ then $(r_1', r_2') \in \mathcal{V}_{ss'}^{k-j_1-j_2-1}[\mathbb{R}]$, meaning that $|r_1' - r_2'| \leq ss'$, which is exactly what we want to prove and the result holds immediately.

THEOREM 7.7 (PRIVACY TYPE SOUNDNESS AT BASE TYPES). If $\varnothing \vdash e : (x : \mathbb{R} \cdot 1) \xrightarrow{(\epsilon, \delta)x} \mathbb{R}$; \varnothing , $|r_1 - r_2| \leq 1$, $\forall r, Pr[\emptyset \vdash e \ r_1 \Downarrow r] \leq e^{\epsilon} Pr[\emptyset \vdash e \ r_2 \Downarrow r] + \delta$

Proof. We proceed analogously to Theorem [C.19.](#page-79-0) But unfolding the definition of related computations, and using a k big enough so both probabilities are defined (and using the fact that two real numbers are semantically equivalent for any index).

D λ _J: TYPE SAFETY

In this section we present auxiliary definitions used in Section [7.2,](#page-37-0) and the proof of type safety.

Non-deterministic sampling big-step semantics of privacy expressions are presented in Figure [32.](#page-80-0) This semantics trivially corresponds with the distribution semantics of Figure [29,](#page-60-0) where $\exists k.\Pr[\llbracket \mathbf{e} \rrbracket]_Y^k = v] > 0 \iff \gamma \vdash \mathbf{e} \Downarrow v.$

The type safety logical relation is defined in Figure [33.](#page-81-0) Its definition is straightforward, split into a value relation V, a computation relation \mathcal{E} , and an environment relation \mathcal{G} . As usual, the

$$
\frac{\emptyset; \emptyset \vdash v : \tau'; \emptyset \qquad \tau' <: \tau \qquad \text{dom}[\Gamma] = \text{dom}(\gamma) \qquad \forall x \in \text{dom}(\gamma). \qquad \gamma(x) \in \mathcal{V}[[\Gamma(x)/\Gamma]]
$$
\n
$$
r \in \text{Atom}[[\mathbb{R}]] \qquad \text{tt} \in \text{Atom}[[\text{unit}]] \qquad \frac{\text{in} \Gamma^2 v \in \text{Atom}[\tau_1 \otimes \oplus \sigma_2] \qquad v \in \mathcal{V}[\tau_1]}{\text{in} \Gamma^2 v \in \mathcal{V}[\tau_1 \otimes \oplus \sigma_2] \qquad \text{in} \mathcal{V}[\tau_1 \otimes \oplus \sigma_2]]}
$$
\n
$$
\frac{\text{in} \tau^{\tau'} v \in \text{Atom}[[\tau_1 \otimes \oplus \sigma_2]] \qquad \text{in} \tau^{\tau'} v \in \mathcal{V}[[\tau_1 \otimes \oplus \sigma_2]]}{\text{in} \tau^{\tau'} v \in \mathcal{V}[[\tau_1 \otimes \oplus \sigma_2]]}
$$
\n
$$
\frac{\langle \lambda^* x : \tau \cdot s'.e, \gamma \rangle \in \text{Atom}[[\langle x : \tau_1 \cdot s' \rangle \xrightarrow{sx} \tau_2]] \qquad \forall v \in \mathcal{V}[[\tau_1], \gamma[x \mapsto v] \vdash e \in \mathcal{E}[[\tau_2]/\langle x : \tau_1 \rangle]]}{\langle \lambda^* x : \tau_1 \cdot s'.e, \gamma \rangle \in \mathcal{V}[[\langle x : \tau_1 \cdot s \rangle \xrightarrow{S} \tau_2]] \qquad \forall v \in \mathcal{V}[[\tau_1], \gamma[x \mapsto v] \vdash e \in \mathcal{E}[[\tau_2]/\langle x : \tau_1 \rangle]]}{\langle \lambda^* x : \tau_1 \cdot s \cdot e, \gamma \rangle \in \mathcal{V}[[\tau_1], \gamma[x \mapsto v] \vdash e \in \mathcal{E}[[\tau_2]/\langle x : \tau_1 \rangle]]}
$$
\n
$$
\frac{\gamma \vdash e \Downarrow v \qquad v \in \mathcal{V}[[\tau]]}{\gamma \vdash e \in \mathcal{E}[[\tau]]} \qquad \frac{\gamma \vdash e \Downarrow v \q
$$

Fig. 33. λ _J: Type Safety Logical Relation

fundamental property of the type safety logical relation states that well-typed open terms are in the relation closed by an adequate environment $\gamma:$ ^{[6](#page-81-1)}

PROPOSITION D.1 (FUNDAMENTAL PROPERTY OF THE TYPE SAFETY LOGICAL RELATION).

(a) Let $\Gamma; \Sigma_0 \vdash e : \tau; \Sigma$, and $\gamma \in \mathcal{G}[\Gamma]$. Then $\gamma \vdash e \in \mathcal{E}[\tau/\Gamma]$. (b) Let $\Gamma; \Sigma_0 \vdash e : \tau; \Sigma$, and $\gamma \in \mathcal{G}[\Gamma]$. Then $\gamma \vdash e \in \mathcal{E}[\tau/\Gamma]$.

PROOF. (a) Sensitivity FP. We proceed by induction on Γ ; Σ_0 \vdash e : τ ; Σ .

First, to deal with the cases of sensitivity and privacy functions, we give the typing rules for sensitivity and privacy closures below:

s-closure

$$
\exists \Gamma', \Sigma'_0, dom(\Sigma'') \subseteq dom(\Gamma') \subseteq dom(\Sigma'_0)
$$

\n
$$
\forall x_i \in dom(\Gamma'), \varnothing; \varnothing \vdash \gamma(x_i): \tau'_i, \tau'_i <: \Gamma'(x_i); \varnothing \qquad \Gamma', x : \tau_1; \Sigma'_0 + s_1 x + e' : \tau_2; \Sigma'' + s'x
$$

\n
$$
\Gamma; \Sigma_0 \vdash \langle \lambda^*(x : \tau_1 \cdot s_1), e', \gamma \rangle : (x : \tau_1/\Gamma' \cdot s_1) \xrightarrow{s'x} \tau_2/\Gamma' ; \varnothing
$$

p-closure

$$
\exists \Gamma', \Sigma'_0, dom(\Sigma'') \subseteq dom(\Gamma') \subseteq dom(\Sigma'_0)
$$

\n
$$
\forall x_i \in dom(\Gamma'), \varnothing; \varnothing \vdash \gamma(x_i) : \tau'_i, \tau'_i <: \Gamma'(x_i); \varnothing \qquad \Gamma', x : \tau_1; \Sigma'_0 + s_1 x + e' : \tau_2; \Sigma''
$$

\n
$$
\Gamma; \Sigma_0 \vdash \langle \lambda^P(x : \tau_1 \cdot s_1), e', \gamma \rangle : (x : \tau_1/\Gamma' \cdot s_1) \xrightarrow{\Sigma''/\Gamma'} \tau_2/\Gamma' ; \varnothing
$$

⁶We use the following operators to remove variables from a type:

 $\tau/\Gamma = [\emptyset/x_1, ..., \emptyset/x_n] \tau, \forall x_i \in dom(\Gamma)$ and $\tau/\gamma = [\emptyset/x_1, ..., \emptyset/x_n] \tau, \forall x_i \in dom(\gamma)$.

Case (1) $\Gamma; \Sigma_0 \vdash x : \Gamma(x); x$

SUBPROOF. By $\gamma \in \mathcal{G}[\Gamma],$ we know that $\gamma(x) \in \mathcal{V}[\Gamma(x)/\Gamma]$. By inspection of the evaluation rules, we know that $\gamma \vdash x \Downarrow \gamma(x)$. We have to prove that $\gamma(x) \in \mathcal{V}[\Gamma(x)/\Gamma]$, which we already know and the result holds the result holds.

Case (2) Γ; Σ_0 *⊢* r : ℝ; ∅

SUBPROOF. Trivial as \emptyset ; $\emptyset \vdash r : \mathbb{R}; \emptyset$.

Case (3) $\Gamma; \Sigma_0 \vdash \mathsf{tt} : \mathsf{unit}; \emptyset$

SUBPROOF. Trivial as \emptyset ;∅ ⊢ tt : unit;∅.

Case (4) $\Gamma; \Sigma_0 \vdash e_1 \ e_2 : \tau; \Sigma$

Subproof. By s-app we know that

S-APP
\n
$$
\frac{\Gamma : \Sigma_0 \vdash e_1 : (x : \tau_1 \cdot s_1) \xrightarrow{\Sigma' + s_2 x} \tau_2 : \Sigma_1 \qquad \Gamma : \Sigma_0 \vdash e_2 : \tau_1 : \Sigma_2 \qquad \Sigma_0 \cdot \Sigma_2 \le s_1}{\Gamma : \Sigma_0 \vdash e_1 \ e_2 : [\Sigma_2 / x] \tau_2 : \Sigma_1 + s_2 \Sigma_2 + \Sigma'}
$$

where $\tau = [\Sigma_2/x] \tau_2$, and $\Sigma = \Sigma_1 + s_2 \Sigma_2 + \Sigma'$. By induction hypotheses we know that $\gamma \vdash e_1 \Downarrow v_1$, $\gamma \vdash e_2 \Downarrow v_2, v_1 \in \mathcal{V}[[x : \tau_1/\Gamma \cdot s_1) \xrightarrow{s_2x} \tau_2/\Gamma \mathbb{I}$ and $v_2 \in \mathcal{V}[[\tau_1/\Gamma \mathbb{I}].$

By inspection of the function predicate, we know that $v_1 \in Atom\left[(x : \tau_1/\Gamma \cdot s_1) \xrightarrow{s_2 x} \tau_2/\Gamma \right]$ and $v_1 =$ $\langle \lambda^s(x : \tau_1' \cdot s_1') \cdot e', \gamma' \rangle$, for some τ_1', s_1', e' and γ' . We also know then that $\gamma'[x \mapsto v_2] \vdash e' \in \mathcal{E}[\![\tau_2/(\Gamma, x \cdot y)]\!]$ $[\tau_1]$, i.e. γ' [$x \mapsto v_2$] $\vdash e' \Downarrow v'$ and $[\Sigma_2/x] \tau_2/\Gamma = [(\Sigma_2/\Gamma)/x] (\tau_2/\Gamma) = [\emptyset/x] (\tau_2/\Gamma) = \tau_2/(\Gamma, x : \tau_1)$, but $v' \in \mathcal{V}[[\tau_2/(\Gamma, x : \tau_1)]]$ and the result holds.

Case (5)
$$
\Gamma
$$
; $\Sigma_0 \vdash \lambda^s(x : \tau_1 \cdot s)$. $e' : (x : \tau_1 \cdot s) \xrightarrow{\Sigma'} \tau_2$; \emptyset

Subproof. We know that

S-LAM
\n
$$
\Gamma, x : \tau_1 : \Sigma_0 + sx + e' : \tau_2 : \Sigma'
$$
\n
$$
\Gamma : \Sigma_0 \vdash \lambda^s (x : \tau_1 \cdot s). e' : (x : \tau_1 \cdot s) \xrightarrow{\Sigma'} \tau_2 : \emptyset
$$

We know that $\gamma \vdash \lambda^s(x : \tau_1 \cdot s)$. $e' \Downarrow \langle \lambda^s(x : \tau_1 \cdot s)$. $e', \gamma \rangle$. We have to prove that $\langle \lambda^s(x : \tau_1 \cdot s)$. $e', \gamma \rangle \in$ $\mathcal{V}[\![((x:\tau_1\cdot s)\xrightarrow{\Sigma'}\tau_2)/\Gamma]\!]$. Suppose $\Sigma'=\Sigma''+s'x$, then $((x:\tau_1\cdot s)\xrightarrow{\Sigma'}\tau_2)/\Gamma=(x:\tau_1/\Gamma\cdot s)\xrightarrow{s'x}(\tau_2/\Gamma)$. First, we have to prove that, $\langle \lambda^s(x : \tau_1 \cdot s) \cdot e', \gamma \rangle \in Atom[[(x : \tau_1/\Gamma \cdot s) \xrightarrow{s'x} (\tau_2/\Gamma)]],$ i.e. that $\exists \Gamma', \Sigma'_0, dom(\Sigma'') \subseteq$ $dom(\Gamma') \subseteq dom(\Sigma'_0), \forall x_i \in dom(\Gamma'), \emptyset; \emptyset \vdash \gamma(x_i) : \tau'_i, \tau'_i \leq: \Gamma'(x_i); \emptyset, \Gamma', \text{ and } x : \tau_1; \Sigma'_0 + sx + e' : \tau_2;$ $\Sigma'' + s'x$. We prove this by choosing $\Gamma' = \Gamma$, $\Sigma'_0 = \Sigma_0$, and $\Sigma'' + s'x = \Sigma'$:

$$
\forall x_i \in dom(\Gamma), \varnothing; \varnothing \vdash \gamma(x_i) : \tau'_i, \tau'_i <: \Gamma(x_i); \varnothing \qquad \Gamma, x : \tau_1; \Sigma_0 + s_1 x + e' : \tau_2; \Sigma'' + s'x
$$
\n
$$
\Gamma; \Sigma_0 \vdash \langle \lambda^s(x : \tau_1 \cdot s_1), e', \gamma \rangle : (x : \tau_1/\Gamma' \cdot s_1) \xrightarrow{s'x} \tau_2/\Gamma' ; \varnothing
$$

Then we have prove that $\forall v' \in \mathcal{V}[\![\tau_1/\Gamma]\!], \gamma[x \mapsto v'] \vdash e' \in \mathcal{E}[\![\tau_2/(\Gamma, x : T_1)]\!].$ By induction hypothesis on $\Gamma, x : \tau_1 : \Sigma_0 + sx + e' : \tau_2 : \Sigma'$, we know that for any $\gamma' \in \mathcal{G}[\Gamma, x : \tau_1],$ $\gamma' \vdash e' \in \mathcal{E}[\![\tau_2/(\Gamma, x : \tau_1)]\!]$. As $\gamma \in \mathcal{G}[\![\Gamma]\!]$ and $v' \in \mathcal{V}[\![\tau_1/(\Gamma, x : \tau_1)]\!]$ $(\tau_1/\Gamma = \tau_1/(\Gamma, x : \tau_1))$, then $\gamma[x \mapsto v'] \in \mathcal{G}[\Gamma, x : \tau_1],$ so we pick $\gamma' = \gamma[x \mapsto v']$ and the result holds.

Case (6) $\Gamma; \Sigma_0 \vdash \lambda^P(x : \tau_1 \cdot s)$. e' : $(x : \tau_1 \cdot s) \xrightarrow{\Sigma'} \tau_2; \emptyset$

Subproof. We know that

 $P-T$ AM

$$
\frac{\Gamma}{\Gamma; x : \tau_1 : \Sigma_0 + sx + e' : \tau_2 : \Sigma'}\n\Gamma; \Sigma_0 \vdash \lambda^P(x : \tau_1 \cdot s). e' : (x : \tau_1 \cdot s) \xrightarrow{\Sigma'} \tau_2 : \varnothing
$$

We know that $\gamma \vdash \lambda^p(x : \tau_1 \cdot s)$. e' $\Downarrow \langle \lambda^p(x : \tau_1 \cdot s)$. $e', \gamma \rangle$. We have to prove that $\langle \lambda^p(x : \tau_1 \cdot s)$. $e', \gamma \rangle \in$ $\mathcal{V}[\left[\left((x:\tau_1\cdot s)\xrightarrow{\Sigma'}\tau_2\right)/\Gamma\right].$ Then $\left((x:\tau_1\cdot s)\xrightarrow{\Sigma'}\tau_2\right)/\Gamma=\left(x:\tau_1/\Gamma\cdot s\right)\xrightarrow{\Sigma'/\Gamma}\left(\tau_2/\Gamma\right).$

First, we have to prove that, $\langle \lambda^p(x : \tau_1 \cdot s), e', \gamma \rangle \in Atom[[x : \tau_1/\Gamma \cdot s)] \xrightarrow{\Sigma'/\Gamma} (\tau_2/\Gamma)$, i.e. that $\exists \Gamma', \Sigma'_0, \text{dom}(\Sigma'') \subseteq \text{dom}(\Gamma') \subseteq \text{dom}(\Sigma'_0), \forall x_i \in \text{dom}(\Gamma'), \varnothing; \varnothing + \gamma(x_i) : \tau'_i, \tau'_i \prec: \Gamma'(x_i), \varnothing, \Gamma', \text{and}$ $x : \tau_1$; $\Sigma'_0 + sx + e' : \tau_2$; Σ' . We prove this by choosing $\Gamma' = \Gamma$, $\Sigma'_0 = \Sigma_0$:

$$
\forall x_i \in dom(\Gamma), \varnothing; \varnothing \vdash \gamma(x_i) : \tau'_i, \tau'_i \prec: \Gamma(x_i); \varnothing \qquad \Gamma, x : \tau_1; \Sigma_0 + s_1 x + e' : \tau_2; \Sigma'
$$

$$
\Gamma; \Sigma_0 \vdash \langle \lambda^P(x : \tau_1 \cdot s_1), e', \gamma \rangle : (x : \tau_1/\Gamma \cdot s_1) \xrightarrow{\Sigma'/\Gamma} \tau_2/\Gamma; \varnothing
$$

Then we have prove that $\forall v' \in \mathcal{V}[\![\tau_1/\Gamma]\!], \gamma[x \mapsto v'] \vdash e' \in \mathcal{E}[\![\tau_2/(\Gamma, x : \tau_1)]\!].$ By induction hypothesis on $\Gamma, x : \tau_1 : \Sigma_0 + sx + e' : \tau_2 : \Sigma'$, we know that for any $\gamma' \in \mathcal{G}[\Gamma, x : \tau_1],$ γ' + e' $\in \mathcal{E}[\![\tau_2/(\Gamma, x : \tau_1)]\!]$. As $\gamma \in \mathcal{G}[\![\Gamma]\!]$ and $v' \in \mathcal{V}[\![\tau_1/(\Gamma, x : \tau_1)]\!]$ $(\tau_1/\Gamma = \tau_1/(\Gamma, x : \tau_1)]$ $\gamma[x \mapsto v'] \in \mathcal{G}[\![\Gamma, x : \tau_1]\!]$, so we pick $\gamma' = \gamma[x \mapsto v']$ and the result holds. Case (7) Γ ; Σ_0 + inl^{τ_2} e' : τ_1 Σ_{\bigoplus} \emptyset τ_2 ; \emptyset

Subproof. We know that

$$
\frac{INL}{\Gamma : \Sigma_0 \vdash e' : \tau_1 : \Sigma}
$$
\n
$$
\frac{\Gamma : \Sigma_0 \vdash \text{inl}^{\tau_2} e' : \tau_1 \overset{\Sigma}{\oplus}^{\emptyset} \tau_2 : \emptyset}{\Gamma : \Sigma_0 \vdash \text{inl}^{\tau_2} e' : \tau_1 \overset{\Sigma}{\oplus}^{\emptyset} \tau_2 : \emptyset}
$$

By induction hypothesis on Γ ; Σ_0 + e' : τ_1 ; Σ we know that $\gamma \vdash e' \Downarrow v'$ and $v' \in \mathcal{V}[\![\tau_1/\Gamma]\!]$. As γ + inl^{τ_2} $e' \Downarrow$ inl $\tau_2/\gamma v'$, we have to prove that inl $\tau_2/\gamma v' \in \mathcal{V}[(\tau_1 \stackrel{\Sigma \oplus \emptyset}{\tau_2})/\Gamma]$. Notice that $(\tau_1 \stackrel{\Sigma \oplus \emptyset}{\sim} \tau_2)/\Gamma = (\tau_1/\Gamma \stackrel{\emptyset \oplus \emptyset}{\sim} \tau_2/\Gamma$, and that $\tau_2/\gamma = \tau_2/\Gamma$ Then we have to prove that $i \ln \Gamma^2/\Gamma v' \in$ $\mathcal{W}[\![\tau_1/\Gamma\!]^\otimes\oplus^\varnothing\tau_2/\Gamma]\!]$, which is direct as we already know that $v'\in\mathcal{W}[\![\tau_1/\Gamma]\!]$.

Case (8) Γ ; Σ_0 + inr^{τ_1} e' : τ_1 Σ_{\bigoplus} \emptyset τ_2 ; \emptyset

SUBPROOF. Analogous to the inl^{τ_2} e' α se. \sim

Case (9) Γ; Σ_0 + case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$: $[\Sigma_1 + \Sigma_{11}/x]\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/y]\tau_3$; $((s_2 * \Sigma_1 +$ $s_2\Sigma_{11} + \Sigma_2 \cup (s_3 * \Sigma_1 + s_3 \Sigma_{12} + \Sigma_3)$

Subproof. We know that

$$
\frac{\sum_{0}^{S-CASE}}{\Gamma; \Sigma_{0} \vdash e_{1} : \tau_{11} \sum_{11} \bigoplus_{12} \tau_{12} ; \Sigma_{1} \qquad \Gamma, x : \tau_{11} ; \Sigma_{0} + (\Sigma_{0} \cdot (\Sigma_{1} + \Sigma_{11}))x \vdash e_{2} : \tau_{2} ; \Sigma_{2} + s_{2}x \qquad \Gamma, y : \tau_{12} ; \Sigma_{0} + (\Sigma_{0} \cdot (\Sigma_{1} + \Sigma_{12}))x \vdash e_{3} : \tau_{3} ; \Sigma_{3} + s_{3}y \qquad \Gamma; \Sigma_{0} \vdash \text{case } e_{1} \text{ of } \{x \Rightarrow e_{2}\} \{y \Rightarrow e_{3}\} : \Sigma_{1} + \Sigma_{11}/x \biguparrow \tau_{2} \sqcup [\Sigma_{1} + \Sigma_{12}/y \biguparrow \tau_{3} ; ((s_{2} * \Sigma_{1} + s_{2} \Sigma_{11} + \Sigma_{2}) \sqcup (s_{3} * \Sigma_{1} + s_{3} \Sigma_{12} + \Sigma_{3}))
$$

where $\tau = [\Sigma_{11}/x] \tau_2 \sqcup [\Sigma_{12}/y] \tau_3$.

By induction hypothesis on Γ ; $\Sigma_0 \vdash e_1$: τ_{11} , $\Sigma_{11} \oplus \Sigma_{12}$, τ_{12} ; Σ_{1} , we know that $\gamma \vdash e_1 \Downarrow v_1$ and $v_1 \in \mathcal{V}[\![\tau_{11}/\Gamma \stackrel{\emptyset \oplus \emptyset}{\oplus} \tau_{12}/\Gamma]\!]$ ($\Sigma_{1i}/\Gamma = \emptyset$). Then either $v_1 = \text{inl}^{\tau_{12}/\Gamma} v_{11}$, or $v_1 = \text{inl}^{\tau_{11}/\Gamma} v_{12}$. Let us suppose $\overline{v_1} = \text{inl}^{\tau_{12}/\Gamma} v_{11}$ (the other case is similar), then $\text{inl}^{\tau_{12}/\Gamma} v_{11} \in \mathcal{V}[\![\tau_{11}/\Gamma \]^{\emptyset} \oplus^{\emptyset} \tau_{12}/\Gamma]\!]$, and thus $v_{11} \in \mathcal{V}[\tau_{11}/\Gamma]$.

Then by induction hypothesis on Γ, $x : \tau_{11}$; $\Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2$; $\Sigma_2 + s_2x$, we know that $\gamma[x \mapsto v_{11}] \vdash e_2 \in \mathcal{E}[\tau/\Gamma]$, therefore $\gamma \vdash e_2 \Downarrow v_2$ and $v_2 \in \mathcal{V}[\tau_2/(\Gamma, x : \tau_{11})]$.

Then by inspection of the evaluation semantics for P-CASE, $\gamma \vdash$ case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$ \downarrow v_2 and we have to prove that $v_2 \in \mathcal{V}$ $[(\Sigma_1 + \Sigma_{11}/\mathbf{x})\tau_2 \sqcup [\Sigma_1 + \Sigma_{12}/\mathbf{y}]\tau_3])/\Gamma$. But $([\Sigma_1 + \Sigma_{11}/\mathbf{x}]\tau_2 \sqcup$ $[\Sigma_1 + \Sigma_{12}/y|\tau_3|]/\Gamma = (\tau_2 \sqcup \tau_3)/\Gamma$, $(x : \tau_{11})$. The result follows from weakening lemma [D.1.](#page-85-0)

(b) Privacy FP. We proceed by induction on Γ ; Σ_0 \vdash e : τ_1 ; Σ .

Case (1) Γ ; Σ_0 ⊢ return $e: [\varnothing/\widehat{x}] \tau_1$; $[\Sigma_1]^{\infty}$ + $\textup{FS}^{\infty}(\tau_1)$

SUBPROOF. By RETURN we know that

RETURN

\n
$$
\Gamma : \Sigma_0 \vdash e_1 : \tau_1 : \Sigma_1 \qquad \widehat{x} = \text{FV}(\text{FS}(\tau_1))
$$
\n
$$
\Gamma : \Sigma_0 \vdash \text{return } e_1 : [\emptyset/\widehat{x}] \tau_1 : [\Sigma_1]^{\infty} + \text{FS}^{\infty}(\tau_1)
$$

where $\tau = [\emptyset/\widehat{x}] \tau$, and $\Sigma = [\Sigma_1]^{\infty} + \text{FS}^{\infty}(\tau_1)$. By induction hypotheses we know that $\gamma \vdash e_1 \Downarrow v_1$, and $v_1 \in \mathcal{V}[\![\tau_1/\Gamma]\!]$.

By inspection of the evaluation semantics $\gamma \vdash$ return $e_1 \Downarrow v_1$. Notice that $\hat{x} \subseteq \Gamma$, then $(\lceil \emptyset / \hat{x} \rceil \tau_1)/\Gamma$ τ_1/Γ , and as $v_1 \in \mathcal{V}[\![\tau_1/\Gamma]\!]$ the result holds immediately.

Case (2) Γ ; Σ_0 + $x : \tau_1 \leftarrow e_1$; $e_2 : [\emptyset / x] \tau_2$; $\Sigma_1 + \Sigma_2$

Subproof. By bind we know that

$$
\dfrac{\text{bind}}{\Gamma: \Sigma_0 \vdash e_1 : \tau_1 : \Sigma_1 \qquad \Gamma, x : \tau_1 : \Sigma_0 + 0x \vdash e_2 : \tau_2 : \Sigma_2}{\Gamma: \Sigma_0 \vdash x : \tau_1 \leftarrow e_1 : e_2 : [\varnothing / x] \tau_2 : \Sigma_1 + [\varnothing / x] \Sigma_2}
$$

where $\tau = [\emptyset/x] \tau_2$, and $\Sigma = \Sigma_1 + [\emptyset/x] \Sigma_2$. By induction hypothesis on Γ ; Σ_0 \vdash e₁ : τ_1 ; Σ_1 , we know that $\gamma \vdash e_1 \in \mathcal{E}[\![\tau_1/\Gamma]\!]$, therefore $\gamma \vdash e_1 \Downarrow v_1$ and $v_1 \in \mathcal{V}[\![\tau_1/\Gamma]\!]$. Also by induction hypothesis on Γ, $x : \tau_1 : \Sigma_0 + 0x + e_2 : \tau_2 : \Sigma_2$, we know that $\gamma[x \mapsto v_1] + e_2 \in \mathcal{E}[[\tau_2/(\Gamma, x : \tau_1)]]$, therefore $\gamma[x \mapsto v_1] \vdash e_2 \Downarrow v_2$ and $v_1 \in \mathcal{V}[\tau_2/(\Gamma, x : \tau_1)]$.

Then by inspection of the evaluation semantics for BIND, $\gamma \vdash x : \tau_1 \leftarrow e_1 : e_2 \Downarrow v_2$. We have to prove that $v_2 \in \mathcal{V}$ $[(\frac{\varnothing}{x}]_{\tau_2})/\Gamma$. But notice that $(\frac{\varnothing}{x}]_{\tau_2})/\Gamma = \tau_2/(\Gamma, x : \tau_1)$ and the result holds immediately.

Case (3) Γ ; Σ_0 + gauss $\mu \sigma^2 : \mathbb{R}$; \varnothing Subproof. By gauss we know that

BIND

$$
\Gamma : \Sigma_0 \vdash \gamma \vdash \text{gauss } \mu \sigma^2 : \mathbb{R} : \varnothing
$$

we know that $\gamma \vdash$ gauss $\mu \sigma^2 \downarrow r$, for some r . But $r \in \mathcal{V}[\mathbb{R}]$ and the result holds.

Case (4) Γ ; Σ_0 + if e_1 {e₂} {e₃} : τ ; $\Sigma_1 \Gamma^\infty \sqcup (\Sigma_2 \sqcup \Sigma_3)$

Subproof. By if we know that in the set

$$
\frac{\Gamma : \Sigma_0 \vdash e_1 : \mathbb{B} : \Sigma_1 \qquad \Gamma : \Sigma_0 \vdash e_2 : \tau : \Sigma_2 \qquad \Gamma : \Sigma_0 \vdash e_3 : \tau : \Sigma_3}{\Gamma : \Sigma_0 \vdash if \ e_1 \{e_2\} \{e_3\} : \tau : |\Sigma_1|^\infty \sqcup (\Sigma_2 \sqcup \Sigma_3)}
$$

where $\Sigma = [\Sigma_1 \upharpoonright^\infty \sqcup (\Sigma_2 \sqcup \Sigma_3)$. By induction hypothesis on Γ ; $\Sigma_0 \vdash e_1 : \mathbb{B}$; Σ_1 , we know that $\gamma \vdash e_1 \Downarrow v_1$ and $v_1 \in \mathcal{V}[\mathbb{B}]$. Unfolding booleans as sums we know that $v_1 \in \mathcal{V}[\text{unit} \, \, \partial \oplus \, \emptyset \, \, \text{unit}]]$. Let us assume that $v_1 = \text{inl}^{\text{unit}}$ tt (the other case is analogous). Then by induction hypothesis on Γ ; Σ_0 + e₂ : τ ; Σ_2 , we know that γ + e₂ $\in \mathcal{E}$ $\lbrack \lbrack \tau/\Gamma \rbrack$, therefore γ + e₂ \downarrow v_2 and $v_2 \in \mathcal{V}$ $\lbrack \lbrack \tau/\Gamma \rbrack$. Then by inspection of the evaluation semantics for if, γ ⊢ if e_1 {e₂} {e₃} $\Downarrow v_2$ but we already know that $v_2 \in \mathcal{V}[\![\tau/\Gamma]\!]$ so the result holds. know that $v_2 \in \mathcal{V}[\![\tau/\Gamma]\!]$ so the result holds.

⊳

Case (5) Γ ; Σ_0 + case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$: $[\Sigma_{11}/x] \tau_2 \sqcup [\Sigma_{12}/y] \tau_3$; $]\Sigma_1 \lceil^\infty \sqcup [\Sigma_{11}/x] \Sigma_2 \sqcup$ $[\Sigma_{12}/\nu]\Sigma_3$

Subproof. By p-case we know that

p-case

$$
\Gamma : \Sigma_0 + e_1 : \tau_{11} \Sigma_{11} \oplus \Sigma_{12} \tau_{12} : \Sigma_1
$$
\n
$$
\Gamma, x : \tau_{11} : \Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2 : \Sigma_2 \qquad \Gamma, y : \tau_{12} : \Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{12}))y + e_3 : \tau_3 : \Sigma_3
$$
\n
$$
\Gamma : \Sigma_0 + \text{case } e_1 \text{ of } \{x \Rightarrow e_2\} \{y \Rightarrow e_3\} :
$$
\n
$$
[\Sigma_{11}/x] \tau_2 \sqcup [\Sigma_{12}/y] \tau_3 : \Sigma_1 \upharpoonright^{\infty} \sqcup [\Sigma_{11}/x] \Sigma_2 \sqcup [\Sigma_{12}/y] \Sigma_3
$$

where $\tau = [\Sigma_{11}/x]\tau_2 \sqcup [\Sigma_{12}/y]\tau_3$, and $\Sigma = [\Sigma_1]^\infty \sqcup [\Sigma_{11}/x]\Sigma_2 \sqcup [\Sigma_{12}/y]\Sigma_3$.

By induction hypothesis on Γ ; $\Sigma_0 + e_1$: τ_{11} $\Sigma_{11} \oplus \Sigma_{12}$ τ_{12} ; Σ_1 , we know that $\gamma + e_1 \Downarrow v_1$ and $v_1 \in \mathcal{V}[\![\tau_{11}/\Gamma \stackrel{\circ}{\otimes} \bigoplus_{i=1}^{\infty} \tau_{12}/\Gamma]\!]$ ($\Sigma_{1i}/\Gamma = \emptyset$). Then either $v_1 = \text{inl}^{\tau_{12}/\Gamma} v_{11}$, or $v_1 = \text{inl}^{\tau_{11}/\Gamma} v_{12}$. Let us suppose $\overline{v_1} = \text{inl}^{\tau_{12}/\Gamma} v_{11}$ (the other case is similar), then $\text{inl}^{\tau_{12}/\Gamma} v_{11} \in \mathcal{V}[\![\tau_{11}/\Gamma\]^{\otimes} \oplus^{\varnothing} \tau_{12}/\Gamma]\!]$, and thus $v_{11} \in \mathcal{V}[\![\tau_{11}/\Gamma]\!]$.

Then by induction hypothesis on Γ , $x : \tau_{11}$; $\Sigma_0 + (\Sigma_0 \cdot (\Sigma_1 + \Sigma_{11}))x + e_2 : \tau_2$; Σ_2 , we know that $\gamma[x \mapsto v_{11}] \vdash e_2 \in \mathcal{E}[\tau/\Gamma]$, therefore $\gamma \vdash e_2 \Downarrow v_2$ and $v_2 \in \mathcal{V}[\tau_2/(\Gamma, x : \tau_{11})]$.

Then by inspection of the evaluation semantics for p-case, γ ⊢ case e_1 of $\{x \Rightarrow e_2\}$ $\{y \Rightarrow e_3\}$ $\|$ v_2 and we have to prove that $v_2 \in \mathcal{V}$ $[(\Sigma_{11}/x)\tau_2 \sqcup [\Sigma_{12}/y]\tau_3])/\Gamma$. But $([\Sigma_{11}/x]\tau_2 \sqcup [\Sigma_{12}/y]\tau_3])/\Gamma =$ $(\tau_2 \sqcup \tau_3)$ /(Γ, $x : \tau_{11}$). The result follows from weakening lemma [D.1.](#page-85-0)

Case (6) Γ ; Σ_0 + e₁ e₂ : $[\Sigma_2/x] \tau_2$; $[\Sigma_1 \Gamma^\infty + [\Sigma_2/x] \Sigma$

Subproof. By p-app we know that

P-APP
\n
$$
\frac{\Gamma : \Sigma_0 \vdash e_1 : (x : \tau_1 \cdot s) \xrightarrow{\Sigma + px} \tau_2 : \Sigma_1 \qquad \Gamma : \Sigma_0 \vdash e_2 : \tau_1 : \Sigma_2 \qquad \Sigma_0 \cdot \Sigma_2 \le s}{\Gamma : \Sigma_0 \vdash e_1 e_2 : [\Sigma_2 / x] \tau_2 : |\Sigma_1|^{\infty} + [\Sigma_2 / x] \Sigma}
$$

where $\tau = [\Sigma_2/x] \tau_2$, and $\Sigma = [\Sigma_1 \int_{-\infty}^{\infty} + [\Sigma_2/x] \Sigma$. By induction hypotheses we know that $\gamma \vdash e_1 \Downarrow v_1$, $\gamma \vdash e_2 \Downarrow v_2, v_1 \in \mathcal{V}[[x : \tau_1/\Gamma \cdot s_1) \xrightarrow{\Sigma/\Gamma} \tau_2/\Gamma \mathbb{I}$ and $v_2 \in \mathcal{V}[[\tau_1/\Gamma \mathbb{I}]]$.

By inspection of the function predicate, we know that $v_1 \in Atom[[x : \tau_1/\Gamma \cdot s_1) \xrightarrow{\Sigma/\Gamma} \tau_2/\Gamma]]$ and $v_1 = \langle \lambda^p(x : \tau_1' \cdot s_1') \ldots \cdot s_n' \rangle$, for some $\tau_1', s_1', \ldots, s_n'$ we also know then that $\gamma'[x \mapsto v_2] \vdash e' \in$ $\mathcal{E}[\![\tau_2/(\Gamma, x : \tau_1)]\!]$, i.e. $\gamma'[\![x \mapsto v_2]\!] \vdash e' \Downarrow v'$ and $[\![\Sigma_2/x]\!] \tau_2/\Gamma = [(\Sigma_2/\Gamma)/x](\tau_2/\Gamma) = [\![\emptyset/x]\!](\tau_2/\Gamma) =$ $\tau_2/(\Gamma, x : \tau_1)$, but $v' \in \mathcal{V}[\![\tau_2/(\Gamma, x : \tau_1)]\!]$ and the result holds.

LEMMA D.1 (WEAKENING). If $v \in \mathcal{V}[\![\tau]\!]$ and $\tau \leq: \tau', FV(\tau') = \varnothing$, then $v \in \mathcal{V}[\![\tau']\!]$.

Proof. Straightforward induction on τ such that $V[\![\tau]\!]$.

Case (1) $\tau \in \{ \mathbb{R}, \text{unit} \}$

- SUBPROOF. Trivial as $\tau \leq \tau$.
- Case (2) $\tau = (x : \tau_1 \cdot s) P \xrightarrow{\Sigma_1} \tau_2$

SUBPROOF. Then $\tau' = (x : \tau_1' \cdot s') \xrightarrow{\Sigma_1'} \tau_2'$, for some $\tau_1' \prec : \tau_1, s' \leq s, \Sigma_1 \prec : \Sigma_1'$, and $\tau_2 \prec : \tau_2'$. We know that $v \in \mathcal{V}[(x : \tau_1 \cdot s) \xrightarrow{\Sigma_1} \tau_2]$ and we have to prove that $v \in \mathcal{V}[(x : \tau_1' \cdot s') \xrightarrow{\Sigma_1'} \tau_2']$. First we have to prove that $v \in Atom[[(x:\tau_1's') \xrightarrow{\Sigma_1'} \tau_2']$, which is direct.

Suppose $v = \langle \lambda^p x : \tau_1 \cdot s.e, \gamma \rangle$. Let $v' \in V[[\tau_1']]$, we have to prove that $\gamma[x \mapsto v'] + e \in \mathcal{E}[[\tau_2']]$, i.e. that $\gamma[x \mapsto v'] \vdash e \Downarrow v''$ and $v'' \in \mathcal{V}[[\tau_2]].$ By induction hypothesis we know that $v' \in \mathcal{V}[[\tau_1]],$ and by

 \Box

 $v \in \mathcal{V}[[x : \tau_1 \cdot s] \xrightarrow{\Sigma_1} \tau_2]]$ we know that $\gamma[x \mapsto v'] \vdash e \in \mathcal{E}[[\tau_2]]$. This means that $\gamma[x \mapsto v'] \vdash e \Downarrow v''$ and $v'' \in \mathcal{V}[\![\tau_2]\!]$. But as $\tau_2 \lt: \tau_2'$ by induction hypothesis $v'' \in \mathcal{V}[\![\tau_2']\!]$ and the result holds. Case (3) $\tau = (x : \tau_1 \cdot s) \xrightarrow{\Sigma_1} \tau_2$

SUBPROOF. Then $\tau' = (x : \tau_1' \cdot s') \xrightarrow{\Sigma_1'} \tau_2'$, for some $\tau_1' \prec : \tau_1, s' \leq s, \Sigma_1 \prec : \Sigma_1'$, and $\tau_2 \prec : \tau_2'$. We know that $v \in \mathcal{V}[(x : \tau_1 \cdot s) \xrightarrow{\Sigma_1} \tau_2]$ and we have to prove that $v \in \mathcal{V}[(x : \tau_1' \cdot s') \xrightarrow{\Sigma_1'} \tau_2']$. First we have to prove that $v \in Atom[[(x : \tau'_1 \cdot s') \xrightarrow{\Sigma'_1} \tau'_2]],$ which is direct.

Suppose $v = \langle \lambda^p x : \tau_1 \cdot s.e, \gamma \rangle$. Let $v' \in V[[\tau_1']]$, we have to prove that $\gamma[x \mapsto v'] + e \in \mathcal{E}[[\tau_2']]$, i.e. that $\gamma[x \mapsto v'] \vdash e \Downarrow v''$ and $v'' \in \mathcal{V}[[\tau_2]]$. By induction hypothesis we know that $v' \in \mathcal{V}[[\tau_1]]$, and by $v \in \mathcal{V}[[x : \tau_1 \cdot s] \xrightarrow{\Sigma_1} \tau_2]]$ we know that $\gamma[x \mapsto v'] + e \in \mathcal{E}[[\tau_2]]$. This means that $\gamma[x \mapsto v'] + e \Downarrow v''$ and $v'' \in \mathcal{V}[\![\tau_2]\!]$. But as $\tau_2 \lt: \tau_2'$ by induction hypothesis $v'' \in \mathcal{V}[\![\tau_2']\!]$ and the result holds. Case (4) $\tau = \tau_1{}^{\oslash} \oplus^{\oslash} \tau_2$

SUBPROOF. Then $\tau' = \tau_1' \otimes_{\Theta} \Theta \tau_2'$, for some $\tau_1 \lt: \tau_1'$ and $\tau_2 \lt: \tau_2'$. We know that $v \in \mathcal{V}[\![\tau_1 \otimes_{\Theta} \Theta \tau_2]\!]$ and we have to prove that $v \in \mathcal{V}[\![\tau_1' \]^{\otimes} \oplus^{\otimes} \tau_2']\!]$. Suppose $v = \text{inl}^{\tau_2''} v'$ (the other case is analogous). We know $\tau''_2 < \tau_2$, and as $\tau_2 < \tau'_2$, then $\tau''_2 < \tau'_2$. First we have to prove that $v \in Atom[\![\tau'_1 \circ \oplus \circ \tau'_2]\!]$, which is direct.

We know that $v' \in \mathcal{V}[\![\tau_1]\!]$, then by induction hypothesis we know that $v' \in \mathcal{V}[\![\tau'_1]\!]$, therefore $\int \sinh^{-\alpha'} v' \in \mathcal{V}[[\tau_1' \otimes \bigoplus^{\emptyset} \tau_2']$ and the result holds.

 \Box

Type safety for open terms follows immediately.

COROLLARY D.2 (TYPE SAFETY AND NORMALIZATION OF λ_I). (a) Let $\vdash e : \tau; \emptyset$, then $\vdash e \Downarrow v$, and $\vdash v : \tau'; \emptyset$, where $\tau' \leq \tau$. (b) Let \vdash $e : \tau; \varnothing$, then \vdash $e \Downarrow v$, and $\vdash v : \tau'; \varnothing$, where $\tau' < \tau$.

Proof. Direct consequence of Prop [D.1.](#page-81-2)