

Multi-fairness under class-imbalance

Arjun Roy^{1,2}[0000-0002-4279-9442], Vasileios Iosifidis²[0000-0002-3005-450], and
Eirini Ntoutsi¹[0000-0002-3005-4507]

¹ Institute of Computer Science, Free University of Berlin, Germany
{arjun.roy,eirini.ntoutsi}@fu-berlin.de

² L3S Research Center, Leibniz University Hannover, Germany
iosifidis@l3s.de

Abstract. Recent studies showed that datasets used in fairness-aware machine learning for multiple protected attributes (referred to as *multi-discrimination* hereafter) are often imbalanced. The *class-imbalance* problem is more severe for the protected group in the critical minority class (e.g., *female +*, *non-white +*, etc.). Still, existing methods focus only on the overall error-discrimination trade-off, ignoring the imbalance problem, and thus they amplify the prevalent bias in the minority classes. To solve the combined problem of *multi-discrimination* and class-imbalance we introduce a new fairness measure, *Multi-Max Mistreatment (MMM)*, which considers both (multi-attribute) protected group and class membership of instances to measure discrimination. To solve the combined problem, we propose Multi-Fair Boosting Post Pareto (MFBPP) a boosting approach that incorporates *MMM*-costs in the distribution update and post-training, selects the optimal trade-off among accurate, class-balanced, and *fair* solutions. The experimental results show the superiority of our approach against state-of-the-art methods in producing the best balanced performance across groups and classes and the best accuracy for the protected groups in the minority class.

Keywords: Multi-discrimination · Class-imbalance · Boosting.

1 Introduction

There are growing concerns about the potential discrimination and unfairness of Machine Learning (ML) models in areas of high societal impact like recidivism, job hiring and loan credit. Over the last years a growing body of works has been proposed to address the problem of fairness and algorithmic discrimination [21]. The vast majority of fairness-aware ML approaches however, assumes that discrimination is due to a single protected attribute e.g., only race or only gender (referred hereafter as *mono-discrimination*). In reality though, the roots of discrimination can be ascribed to *multiple protected attributes* (referred hereafter as *multi-discrimination*³), e.g., a combination of race, gender and age [17].

³ Through the paper we use the terms “multi-discrimination” and “multi-fairness” interchangeably.

The problem of multi-discrimination has attracted attention recently and several approaches to multi-fairness have been proposed [1, 12, 18, 24, 25]. However, none of the existing *multi-discrimination* methods considers class-imbalance and the problem arising out of it. Studies [9, 11, 15] showed that many datasets used in fairness-aware ML research are *class-imbalanced*, i.e., they contain a disproportionately larger amount of instances from the majority class (typically called negative “-” class) comparing to the minority class (typically called positive “+” class). The imbalance is even more pronounced in protected groups like female (vis-a-vis male), non-white (vis-a-vis white) etc. Table 1 highlights the problem in three real-world datasets, which are widely used to evaluate fair-ML algorithms [15]. The Class Imbalance Ratio (*CIR*) is the (+/-) ratio in the

Table 1. Overview of class imbalance ratio (*CIR*) and protected:non-protected group imbalance ratio in the minority “+” class (*GIR*) for different protected attributes.

| Data | n | Minority (+) class | <i>CIR</i> (+:-) | <i>GIR</i> (Prot. : Non-prot) in “+” class |
|--------|-----|---------------------|------------------|--|
| Adult | 45K | > 50k | 1:3 | Race: (1:6), Sex: (1:2) |
| Bank | 40K | <i>subscription</i> | 1:8.9 | Marital (1:3), Age (1:23) |
| Credit | 30K | <i>default pay.</i> | 1.4:3 | Sex (1:1.5), Age (1:6), Marital (1:1.5) |

whole dataset. For the minority ‘+’ class, we also show the Group Imbalance Ratio (*GIR*) which is the ratio between the protected and non-protected groups, for different protected attributes. As seen in Table 1, within the minority ‘+’ class there exist extreme imbalance between the protected and non-protected group. Thus, within the entire data these protected groups have very less ‘+’ examples. The degree of imbalance varies from attribute to attribute. Thus, giving an uniform and equal importance to tackle discrimination for all the protected attributes may not be sufficient. In these circumstances, a classifier can be highly accurate even by completely ignoring these protected ‘+’ examples. On the other hand, a fair classifier whose working principle is to minimize the difference between performance of the two groups, can have high error rate on both protected and non-protected ‘+’ examples (i.e., predicting them as ‘-’). Such a situation may result in an acceptable drop in accuracy (in lieu of fairness), however, may lead to heavy under-performance in the positive outcome of some protected groups.

State-of-the-art *multi-discrimination* methods [1, 12, 18, 19, 24, 25] focus only on error-discrimination trade-off, but ignore this precise imbalance problem. Also, the evaluation strategy presently used ignores to report on this issue of performance of the worst performing group in the minority class. Thus, we need a holistic algorithm approach along with a thorough evaluation mechanism to measure that analyses the performance based on overall error, *multi-discrimination*, imbalance, and protected groups in the minority class. In this work, we target the combined combined problem of *multi-discrimination* and class-imbalance. Our main contributions are as follows:

- i) We extend the definition of multi-group [24] fairness to introduce the notion of *Multi-Max Mistreatment (MMM)*⁴ that evaluates discrimination for multiple protected attributes and across different classes.
- ii) We formulate the *multi-discrimination* under class-imbalance problem as a multi-faceted problem of finding a *MMM*-fair classifier that achieves low overall error, and minimizes performance differences across the classes and groups, to overcome the problem of underrepresented protected groups in the minority (+) class.
- iii) We propose Multi-Fair Boosting Post Pareto (MFBPP) algorithm, an in-processing boosting-based approach coupled with a post-processing Pareto Front selection to solve the multiple problems in-hand.
- iv) We demonstrate an all round evaluation based on accuracy, imbalance, *multi-discrimination*, and accuracy of protected groups in the positive class to show the superiority of our MFBPP against various state-of-the art approaches w.r.t. *multi-discrimination* under class-imbalance.
- v) We offer a flexible alternative of our model to provide solutions per user needs based on user preferences.

The rest of the paper is organized as follows: Related work is summarized in Section 2. In Section 3 we introduce basic notation and our *Multi-Max Mistreatment (MMM)* fairness measure. Our boosting-based method towards an *MMM*-fair classifier is presented in Section 3.1 and the experimental evaluation in Section 5. We conclude this work in Section 6 where we also point to open directions.

2 Related Work

In the following, we summarize related work referring to *multi-discrimination*, and imbalanced learning. Notions built around intersectional discrimination [5, 13] is the most common practice to measure *multi-discrimination*. However, such measures suffer from the drawback of clarity in subgroup definition [6] and scarcity in subgroup distribution [13]. Recently, works [12, 24] towards the more operational *multi-discrimination* measure concerning disjoint groups defined by multiple protected attributes came into light. However, they do not take into account ground truth or class membership which is important to consider in presence of class-imbalance. Our introduced *MMM* notion, overcomes the issue by considering both class and multi-group membership of the instances to measure *multi-discrimination*.

A few existing approaches [1, 12, 18, 19, 24, 25] in supervised learning can handle *multi-discrimination*. [25] introduces fairness-related convex-concave constraints to a logistic regression classifier (FairCons). [1] imposes a set of linear fairness constraints on an exponentiated-gradient reduction method (FairLearn). [12] tackles the fairness-accuracy trade-off by minimizing mutual information between the learning error and the vectorized multiple protected attributes (MI-Fair). [24] applies a Bayes-optimal group-fair classifier (W-ERM)

⁴ The term ‘*multi*’ here refers to both multiple attributes and multiple classes.

to identify the most-discriminated group. Fairness-aware learning as a *mini-max* theory has been already used in the literature [18], searching for a Pareto efficient solution of a multi-objective problem (MiniMax). Recently it has been shown that skewed class distributions can affect the discriminatory behaviour of a model [9–11] in the *mono-discrimination* set-up. None of the existing *multi-discrimination* methods considers class-imbalance. Boosting-based approaches have shown their effectiveness in tackling class-imbalance [3, 23], fairness [8, 11], and multi-class [2] problems. [11] tackles both fairness and class-imbalance but for a single protected attribute (AdaFair).

Our proposed MFBPP considers both *multi-discrimination* and class-imbalance to overcome the limitation of multiple underrepresented groups while delivering accurate solutions across the classes.

3 Basics and *Multi-Max Mistreatment(MMM)* fairness

We assume a dataset $D = (u^{(i)}, s^{(i)}, y^{(i)}) \sim P$ of n instances drawn from the i.i.d distribution P over the domain $U \times S \times Y$, where U is the subspace of *non-protected attributes*, S is the subspace of *protected attributes*, and Y is the class attribute. For simplicity, we assume a binary problem: $Y \in \{+, -\}$ with ‘+’ being the minority (+) class [20]. U and S together define the feature space $X = U \times S$, so $x^{(i)} = (u^{(i)}, s^{(i)})$.

Let the protected subspace consist of k protected attributes: $\{S_1, S_2, \dots, S_k\}$. Each protected attribute is considered to be binary: $\forall_{j=1, \dots, k} S_j \in \{g_j, \bar{g}_j\}$ and where g_j and \bar{g}_j represent the *protected group* and the *non-protected group*, respectively w.r.t. protected attribute S_j . Each group g_j (\bar{g}_j) w.r.t. a protected attribute S_j can be further subdivided based on class information into: *protected positive* g_{j+} , *protected negative* g_{j-} , *non-protected positive* \bar{g}_{j+} and *non-protected negative* \bar{g}_{j-} .

To measure mistreatment in *mono-discrimination* cases, [25] introduced the notion of *Disparate Mistreatment* for a protected feature j as:

$$DM_j = |\delta FNR_j| + |\delta FPR_j| \quad (1)$$

where δFNR_j (δFPR_j) is the discrimination w.r.t. S_j in the positive ‘+’ class (respectively, negative ‘-’ class) defined as:

$$\delta FNR_j = ER(g_{j+}) - ER(\bar{g}_{j+})$$

$$\delta FPR_j = ER(g_{j-}) - ER(\bar{g}_{j-})$$

3.1 *Multi-Max Mistreatment(MMM)* measure

The Disparate Mistreatment measure (c.f., Equation 1) fails to focus on per-class discrimination due to the summation operation. To ensure fair treatment *across all classes*, for a protected attribute S_j , we measure mistreatment as $\max(|\delta FNR_j|, |\delta FPR_j|)$ where the ‘max’ operator enforces focus on each of the

classes. Moreover, we want to ensure fair treatment *across all protected attributes* $S = \{S_1, \dots, S_k\}$. Our goal is therefore, to focus on the most discriminated group defined based on a protected attribute and a class. To this end, we introduce a new *multi-discrimination* notion, called *Multi-Max Mistreatment (MMM)*, that measures the *maximum* discrimination among the protected attributes and for the different classes.

Definition 1. *The Multi-Max Mistreatment (MMM_S) due to multiple-protected attributes $S = \{S_1, \dots, S_k\}$ across all classes $Y = \{+, -\}$, is defined as:*

$$\text{MMM}_S = \max_{S_j \in S} (\max(|\delta FNR_j|, |\delta FPR_j|)) \quad (2)$$

where δFNR_j and δFPR_j measure the mistreatment due to S_j in the (+) and (-) class, respectively.

Definition 2. *Given a tolerance threshold μ , a classifier $f(\cdot)$ is MMM-fair iff the maximum mistreatment w.r.t all the protected attributes $S_j \in S$ across all classes is less than μ i.e., $\text{MMM}_S \leq \mu$.*

In the ideal case, $\mu=0$ which signifies no discrimination w.r.t. any protected attribute and in any class.

4 Multi-Fairness-aware Learning

Our goal is to learn a *MMM-fair* classifier: $f(\cdot) : X \rightarrow Y$ that achieves *equal low* error rates for all the groups (g_j/\bar{g}_j , $j = 1, \dots, k$) in both the classes (+/-). To this end, we first formulate clear objectives (Sec. 4.1) and then, propose a sequential learner approach to find $f(\cdot)$ (Sec. 4.2).

4.1 Multi-discrimination-free Learning under Class-imbalance

We define three objectives for the *MMM-fair* classifier $f(\cdot)$: low overall error (O_1), similar (low) error rates across all classes (O_2), and mitigation of discriminatory outcomes for all protected attributes (O_3).

Objective O_1 targets overall error and is defined as minimizing the classification loss (0-1 loss):

$$O_1 : L(f) = \frac{1}{n} \sum_{(x_i, y_i) \in D} |y_i - f(x_i)| \quad (3)$$

where $f(x_i)$ is the predicted and y_i is the true class of x_i .

Objective O_2 explicitly targets class-imbalance by ensuring balanced performance across both classes. Motivated by [7], we define a balanced loss function to minimize the performance differences between the two classes:

$$O_2 : B(f) = \left| \frac{1}{|D_+|} \sum_{(x_i, y_i) \in D_+} |y_i - f(x_i)| - \frac{1}{|D_-|} \sum_{(x_i, y_i) \in D_-} |y_i - f(x_i)| \right| \quad (4)$$

where $D_Y \subset D$, $Y \in \{+, -\}$ denotes the set of instances belonging to class Y .

O_3 is the *multi-discrimination* objective aiming to mitigate discrimination due to multiple protected attributes $S_j \in S$ and across both classes. We call it MMM_S loss, as on optimization it aims to mitigate MMM_S (c.f. Def. 1):

$$O_3 : \Phi(f) = \max_{S_j \in S} \left(\max_{Y \in \{+, -\}} \left(\frac{1}{|g_{jY}|} \sum_{(x_i, y_i) \in g_{jY}} |y_i - f(x_i)| - \frac{1}{|g_{j\bar{Y}}|} \sum_{(x_i, y_i) \in \bar{g}_{jY}} |y_i - f(x_i)| \right) \right) \quad (5)$$

where $|g_{jY}|$ is the cardinality of group g_j in class $Y \in \{+, -\}$.

The objectives O_3 and O_2 ensure similar performance across all the protected/non-protected groups and the (+/-) classes respectively, thus minimizing the performance bias against the underrepresented protected groups in the minority (+) class, while the objective O_1 would help establish low error rate overall.

4.2 The *MMM*-fair Boosting Post Pareto (MFBPP) Algorithm

Our goal is to develop a classifier that takes into consideration the above three objectives, eventually solving the problem of *multi-discrimination* under class-imbalance. Boosting-based [22] approaches have been promising in tackling class-imbalance [3, 23] and discrimination [8, 11]. However, they have also been criticised for being vulnerable in the presence of noise or outliers. As outliers are more likely to be misclassified, boosting may overshoot over the iterations the weights of those instances [16]. Thus, the ensemble obtained at the end of a predefined number of boosting rounds may produce inferior outcomes than an ensemble produced in an earlier round.

Inspired by the literature, we propose a boosting-based learner that *in-training* modifies the distribution weights to incorporate our objective goals. The new weighting puts more attention to the instances from the protected groups in minority class (as they are frequently misclassified) and might therefore, aggravate the weight overshooting problem. To overcome this drawback, we deploy a *post-training* step to select the best solution (partial ensemble).

In-training: *MMM*-boosted weight distribution update. Let T be the number of boosting rounds. In each round t ($1 \leq t \leq T$) we train a weak learner (a decision stump) based on the current instance weight distribution D_t . In the first round, all instances receive the same weight: $D_1(x_i) = \frac{1}{n}$. In a later round $0 < t + 1 \leq T - 1$, the weight distribution is updated as follows:

$$D_{t+1}(x_i) = \frac{D_t(x_i) \exp(-\alpha_t \text{sign}(y_i h_t(x_i))) f c_t(x_i)}{Z_t} \quad (6)$$

where as in AdaBoost $\alpha_t = \frac{1}{2} \ln \frac{1 - \sum_n D_t(x_i)}{\sum_n D_t(x_i)}$ is the weight of the weak learner h_t , $\text{sign}(y_i h_t(x_i))$ returns -1 if $h_t(x_i) \neq y_i$ and 1 otherwise, and Z_t is the normalization factor which ensures that D_{t+1} is a probability distribution. The term

$f_{c_t}(x_i)$ is our modification, which corresponds to the *multi-discrimination* cost (MMM-cost) for a misclassified instance x_i defined as:

$$f_{c_t}(x_i) = \begin{cases} \max_{1 \leq j \leq k} (cdc_{ij}^{(t)}), & \text{if } h_t(x_i) \neq y_i \\ 1, & \text{otherwise} \end{cases} \quad (7)$$

where $cdc_{ij}^{(t)}$ is the discrimination weight of instance x_i at round t concerning protected attribute S_j , which depends on the group membership of x_i w.r.t S_j . It is defined as:

$$cdc_{ij}^{(t)} = \begin{cases} 1 + |\delta FNR_j^{1:t}|, & \text{if } (\delta FNR_j^{1:t} \geq 0 \wedge x_i \in g_{j+}) \vee (\delta FNR_j^{1:t} \leq 0 \wedge x_i \in \overline{g_{j+}}); \\ 1 + |\delta FPR_j^{1:t}|, & \text{if } (\delta FPR_j^{1:t} \geq 0 \wedge x_i \in g_{j-}) \vee (\delta FPR_j^{1:t} \leq 0 \wedge x_i \in \overline{g_{j-}}); \end{cases} \quad (8)$$

where $\delta FNR_j^{1:t}$ and $\delta FPR_j^{1:t}$ are the cumulative discrimination of the partial ensemble $H_t(x_i) = \sum_{l=1}^t \alpha_l h_l(x_i)$ for S_j as in [11].

In each boosting round t we evaluate the partial ensemble H_t and collect the solution vector $\vec{f}_t = [o_1, o_2, o_3]_t$, where $o_i = O_i(t)$ is a solution point of H_t for the respective objective O_i . In total, T solution vectors are collected. The sequential training stops when the maximum number of iterations T is reached.

Post-training: Selecting Pareto Optimal Solution. Our goal is to find the optimal round $t^* \leq T$ to output the partial-ensemble with the best (O_1, O_2, O_3) objectives trade-off:

$$H_{t^*} = \sum_{l=1}^{t^*} \alpha_l h_l$$

This is achieved in two steps: First, out of all T solutions we select the set of non-dominating optimal solutions. Next, we find the best trade-off solution among the shortlisted ones to get the corresponding optimal t^* .

1. Pareto front computation: Among all solution vectors \vec{f}_t , $t = 1, \dots, T$ collected over the boosting rounds, we find the Pareto Front (PF), i.e., the non-dominated set of Pareto optimal solutions. A solution $\vec{f}_{t'}$ is said to be dominated by a solution \vec{f}_t if 1) $O_i(t) \leq O_i(t') \forall i \in \{1, 2, 3\}$, and 2) $\exists i \in \{1, 2, 3\} O_i(t) < O_i(t')$.

2. Pseudo-weight calculation and choice of best solution : To choose the best solution we use the pseudo-weight algorithm [4] that calculates the relative distance of each solution from the worst (maximum value) solution for each objective. The pseudo-weight w_{ti} for $o_i \in \vec{f}_t$ is given by:

$$w_{ti} = \frac{(o_i^{\max} - o_{ti}) / (o_i^{\max} - o_i^{\min})}{\sum_{i=1}^3 (o_i^{\max} - o_{ti}) / (o_i^{\max} - o_i^{\min})} \quad (9)$$

where o_i^{\max} (o_i^{\min}) is the maximum or worst (minimum or best) objective value achieved in any of the rounds. This way, for each solution $\vec{f}_t = [o_1, o_2, o_3]_t$ we

compute the corresponding pseudo-weight vector $\vec{w}_t = [w_{t1}, w_{t2}, w_{t3}]$. Next, we select the solution with the least relative weighted sum as the best trade-off solution w.r.t all the objectives:

$$\vec{f}_t^* = \operatorname{argmin}_t \{(1 - \vec{w}_t) \cdot \vec{f}_t\} = \operatorname{argmin}_t \left\{ \sum_{i=1}^3 (1 - w_{ti}) o_{ti} \right\} \quad (10)$$

where $(1 - \vec{w}_t)$ is the required transformation as the pseudo-weights vector by its nature assigns bigger weight w_{ti} to a smaller objective solution value o_{ti} .

5 Experiments

We evaluate MFBPP performance against state-of-the-art approaches (Sec. 5.2). To show the utility of our *MMM*-cost (Eq. 7) in tackling balanced error (O_2), we plot balanced loss $B(f)$ with varying *MMM* tolerance thresholds μ (Sec. 5.3). Further, we show the changes in the dataset distribution over training and the effectiveness of our approach in promoting underrepresented protected groups (Sec. 5.3). We plot the O_1, O_2, O_3 losses over the rounds to justify the need for post-training selection. At last, in Sec. 5.4 we show the flexibility of MFBPP to intake user preferences for post-training selection.

5.1 Experimental settings

Baselines: We compare against four state-of-the-art fairness-aware methods: *FairCons* [25]: Tackles *multi-discrimination* fairness-related convex-concave constraints, *FairLearn* [1]: imposes a set of linear fairness constraints on an exponentiated-gradient reduction method to tackle *multi-discrimination*, *MiniMax* [18]: tackles *multi-discrimination* as a mini-max game while searching for a Pareto efficient solution of a multi-objective problem, *W-ERM* [24]: applies a Bayes-optimal group-fair classifier to consider algorithmic fairness across multiple overlapping groups simultaneously to tackle the *multi-discrimination* trade-off, *MI-Fair* [12]: minimizes mutual information between the learning error and the vectorized multiple protected attributes to tackle *multi-discrimination*, and *AdaFair* [11]: uses *mono-discrimination* based boosting algorithm along with summed accuracy and class-imbalance loss to tackle *mono-discrimination* and class-imbalance.

In order to understand the effect of the post-training part as well as the effect of the \mathbb{PF} selection in the post-training part, we also include in the experiments two variations of MFBPP:

- *MFB* that completely discards the post-training part and
- *MFBP* that uses post-training but does not use the Pareto Front \mathbb{PF} set for the final selection but rather selects from all solutions.

Datasets:

We report on three imbalanced real-world datasets (c.f., Table 1). Additionally, we also report on Compas [14] (CIR: 1 : 1.2) to show the usability of our method also for class-balanced scenarios. The protected attributes and protected groups studied in the experiments are *Sex* (g_j ="female"), *Race* (g_j ="non-white"), *Marital status/Mari* (g_j ="married"), *Age* (g_j ="≤ 25 & ≥ 60").

Evaluation Measures:

For O_1 , we report on accuracy (*Acc*), for O_2 on geometric mean (*G.M*) and for O_3 we report on the proposed MMM-fairness, as well as on the *DM* for each protected attribute. Additionally, we report on the accuracy of the worst performing protected group in the minority (+) class (Wg_+).

Experimental setup:

We set the number of weak learners to $T = 500$. We follow the same evaluation setup as in [11, 25] by splitting each dataset randomly into train (50%) and test (50%) and report on the average of 10 random splits.

5.2 Evaluation results

The discriminatory and predictive performance evaluation of the different approaches is shown in Fig 1 and Table 2, respectively.




Fig. 1. Discrimination performance: For each dataset, the overall *MMM* score and the *DM* scores for each protected attribute are shown (lower values are better).

Multi-discrimination: From Fig. 1 we notice that our MFB outperforms all the approaches in all the dataset. MFBPP comes second outperforming the baseline competitors in mitigating *multi-discrimination* (i.e., objective O_3) by producing the lower *MMM* discrimination values in three datasets (Adult: **0.05**, Compas: **0.04**, Credit: **0.01**), while falling behind FairLearn in one dataset (Bank: 0.08). However, in Table 2 we notice that MFB severely underperforms in all the predictive evaluation measures, thus failing to provide a good trade-off between O_1 , O_2 , and O_3 . The closest competitor to us w.r.t. fairness is FairLearn,

Table 2. Predictive performance evaluation. W_{g_+} is the accuracy of the worst performing protected group in the minority (+) class

| | Adult | | | Bank | | | Credit | | | Compas | | |
|-----------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| | Acc | W_{g_+} | $G.M$ |
| AdaFair | 0.84 | 0.63 | 0.76 | 0.88 | 0.62 | 0.76 | 0.81 | 0.33 | 0.57 | 0.65 | 0.50 | 0.64 |
| FairCons | 0.85 | 0.43 | 0.75 | 0.91 | 0.33 | 0.59 | 0.81 | 0.28 | 0.55 | 0.67 | 0.53 | 0.66 |
| FairLearn | 0.83 | 0.54 | 0.73 | 0.88 | 0.21 | 0.46 | 0.79 | 0.21 | 0.45 | 0.65 | 0.55 | 0.64 |
| MiniMax | 0.86 | 0.49 | 0.76 | 0.90 | 0.45 | 0.66 | 0.82 | 0.37 | 0.60 | 0.68 | 0.49 | 0.67 |
| W-ERM | 0.85 | 0.52 | 0.75 | 0.90 | 0.29 | 0.56 | 0.81 | 0.22 | 0.47 | 0.66 | 0.47 | 0.64 |
| MI-Fair | 0.84 | 0.65 | 0.72 | 0.89 | 0.69 | 0.82 | 0.80 | 0.59 | 0.68 | 0.68 | 0.60 | 0.68 |
| MFB | 0.69 | 0.64 | 0.74 | 0.36 | 0.28 | 0.41 | 0.71 | 0.68 | 0.70 | 0.64 | 0.63 | 0.63 |
| MFBP | 0.85 | 0.77 | 0.84 | 0.85 | 0.75 | 0.85 | 0.71 | 0.64 | 0.69 | 0.67 | 0.60 | 0.65 |
| MFBPP | 0.81 | 0.79 | 0.81 | 0.81 | 0.72 | 0.80 | 0.74 | 0.65 | 0.70 | 0.66 | 0.63 | 0.66 |

which however achieves low discrimination by consistently ignoring the minority class (A closer look to Table 2, shows that FairLearn achieves the lowest $G.M$ for all four datasets). Approaches like FairCons, MiniMax, and W-ERM result in different levels of discrimination for the different protected attributes and overall high MMM values. MI-Fair have mixed outcome with high discrimination in Adult, but performed at par with MFBPP in Bank and Compas data. AdaFair trained on one protected attribute (for Adult: sex, for Bank: marital status, for Credit: sex, for Compas: race) does not mitigate discrimination for other protected attributes and consequently also results in high MMM values esp. for Bank and Compas. In case of Adult and Credit datasets, AdaFair, albeit trained for *mono-discrimination* it seems to tackle *multi-discrimination*; the reason is the strong correlation between the protected attributes as revealed by chi-square test with ρ -value ≈ 0 .

Underrepresented protected groups (g_{j_+}): In Table 2 we notice that MFBPP and MFBP both outperform the other approaches on W_{g_+} by far ([5% – 21% \uparrow]). Thus, our proposed methods overcome the issue of bias due to the imbalanced distribution of protected groups (c.f Table 1), ensuring high predictive accuracy for any g_{j_+} . Note that all the other approaches that even after mitigating *multi-discrimination* fail on this task. MI-Fair emerges as the best among the baseline competitor in all the four datasets behind our proposed methods MFBPP, MFBP, and MFB in Adult, Credit, and Compas datasets, while outperforming only MFB in Bank data.

Balanced performance: Table 2 shows that our MFBPP and MFBP outperform the baselines in $G.M$ in the range [4% – 11%] \uparrow for the imbalanced Adult, Bank, and Credit datasets, while being marginally behind MI-Fair, and Minimax in the balanced Compas dataset. We can easily notice that our Acc and $G.M$ values are close to each other for all the datasets with $Acc/G.M \approx 1$. This indicates we achieve $B(f) \approx 0$ (O_2), in all the datasets. Our closest competitors here are MI-Fair, AdaFair and MiniMax. AdaFair explicitly targets class-imbalance for mono-discrimination. MiniMax, and MI-Fair indirectly tackles the problem as they aim at minimizing error for all groups. For other baselines, $Acc/G.M \gg 1$, indicating substantial performance differences between the classes.

Overall accuracy: MFBPP is marginally compromised on the overall Acc in Adult, Credit, and Bank datasets ([12% – 5%] ↓). MiniMax emerged as the winner here, accomplishing the best accuracy in Adult, Credit, and Compas dataset. This is the trade-off we pay to ensure nearly equal performance for all (protected/non-protected) groups across all the classes.




Fig. 2. Visualization of the Pareto front and the selected trade-off solution in the complete solution surface.

Summary: MFBPP provides the best holistic outcome in overall trade-off, outperforms the baselines in mitigating *multi-discrimination*, produces the best predictive performance on underrepresented protected groups ($\forall_j g_{j+}$) in minority class, and equal performance across all classes, while maintaining comparable high accuracy against the baselines. MFB produces the most-fair outcomes but suffers in predictive performance. It overshoots the weight and increases overall error to gain fairness. MFBP solves the overshooting problem but gets outperformed by MFBPP in the fairness task. In Fig 2 we see that the solution surface after the training-MFB phase of our algorithm is very wide spread in the O_1, O_2, O_3 objective space. By computing \mathbb{PF} as in MFBPP, we narrow down the search space. Using the pseudo-weights, we pick a solution each time close to the origin in the objective space (which is desired). Hence, we are always able to deliver a good trade-off solution without any hyper-parameter tuning. FairLearn also tackled the *multi-discrimination* problem consistently well, but by underperforming in the minority class. MiniMax lacks in *multi-discrimination* convergence but produces the most overall accurate (O_1) predictions. FairCons has difficulty in finding the optimal parameters leading to its poor *multi-discrimination* performance. W-ERM apart from Bank dataset (the most imbalanced), always delivers comparable trade-offs. However, the method is very slow. MI-Fair can be argued as the closest competitor in overall trade-off delivering balanced and accurate performance with low discrimination in three out of the four datasets under study.

5.3 Internal analysis

This section aims to analyse MFBPP’s ability to produce state-of-the-art balanced performance while dealing with *multi-discrimination*. In particular, we try to find answers for three significant points: i) How MFBPP ensures high accuracy for the underrepresented protected groups in the imbalanced minority (+) class? ii) How the overshooting problem affects and, is the post-processing step really required? iii) Does the *multi-discrimination* cost (Eq. 7) also tackle the balanced loss and, what happens if we relax cost by varying the *MMM* threshold μ (Def. 2)? Here we focus the study using only the imbalanced data (Table 1).




Fig. 3. Changes in instance weight distribution. For each dataset and protected attribute S_j , we depict the initial distribution S_{in} and the final one S_{fin} .

Answer to point (i): We analyse the changes in weight distribution of the various groups from its initial (*ini*) distribution (actual data representation), to boosted weight till the finally selected partial ensemble point (*fin*) in Fig 3. For any protected attribute S_j , P and Np refer to the respective protected and non-protected groups. Thus, $P(+)$ translates as the protected group in the minority (+) class (g_{j+}). We notice that *ini* weights of each $P(+)$ in every dataset is largely underrepresented. But, in the *fin* weights each $P(+)$ group is boosted significantly. MFBPP increases the weight of the underrepresented groups, thus changing the decision boundary to produce highly accurate and unbiased results for all the groups even in case of high imbalance.




Fig. 4. B(f) loss over boosting rounds with varying *MMM* thresholds μ .

Answer to points (ii): We have already shown the effectiveness of our *MMM* cost (Eq. 7) in mitigating *multi-discrimination*. Now to understand its effect on balanced loss we monitor $B(f)$ over the boosting rounds (Fig 4) for different *MMM*-tolerance thresholds μ . We see that when $\mu = 0$, the shape of the $B(f)$ loss curve is parabolic for Adult and Bank datasets. In Credit data, the loss continues to descent till the final round. The parabolic curve supports our intuition of the possibility of overshooting the weights due to the possible repeated boosting of noisy instances, whereas a consistently descending loss curve for Credit data shows the uncertainty involved in estimating the optimal size of the ensemble. These results justify the necessity of the post-training selection part.

Answer to points (iii): In Fig 4 we also show the effect of different *MMM* threshold μ values on $B(f)$. By increasing μ we relax the *MMM* boost i.e we have $f_{c_t}(x_i) = 1$ in Eq. 6 when discrimination (Eq. 7) is $\leq (1 + \mu)$. We observe the immediate effect on the $B(f)$ loss. In each of the datasets, the effectiveness of MFBPP to tackle class imbalance decreases as the $B(f)$ loss increases while we increase the threshold μ . Thus, showcases the ability of our *MMM* cost in tackling the O_2 along with our *multi-discrimination* objective O_3 .

5.4 Flexibility of MFBPP

Thus far, we use the pseudo-weight method (Eq. 10) to select the best solution among the (PF) solutions. If information on user preferences exists, in the form of a user-preference vector $\vec{u} = [u_1, u_2, u_3]$: $u_1 + u_2 + u_3 = 1$, it can be used to select the best solution according to user needs. In this case, we choose the solution \vec{f}_{t^*} whose corresponding pseudo-weight w_{t^*} is closest according to L1 distance, to the preference vector \vec{u} . To evaluate the effect of such an approach, we mimic four different users and provide their preference vector \vec{u} as an additional input to MFBPP. In particular, we assume the following users: i) $\vec{u} = [0.33, 0.33, 0.33]$ indicating *equal preference* to all O_i , ii) $\vec{u} = [0, 0, 1]$, iii) $\vec{u} = [0, 1, 0]$, iv) $\vec{u} = [1, 0, 0]$, indicating preference only for O_i if $u_i = 1$.




Fig. 5. Performance evaluation for different user preference vectors \vec{u}

As expected, the output changes noticeably with changes with \vec{u} . For all datasets the most accurate classifier (for $\vec{u} = [1, 0, 0]$) delivers Acc at par if not better than the state of the art, whereas the fairest (for $\vec{u} = [1, 0, 0]$) produces state of the art fair predictions. With preference $\vec{u} = [0.33, 0.33, 0.33]$ the classifier consistently produces good trade-off solutions, however, the default version of MFBPP (without \vec{u}) produces better trade-offs.

6 Conclusions and Outlook

In this work we claimed that *multi-discrimination* under class-imbalance is an important multi-faceted problem of finding low overall error, while minimizing performance differences across the classes and groups. Existing multi-discrimination approaches consider only error-discrimination trade-off, and ignore class-imbalance. This way, they achieve *multi-discrimination* by underperforming in the minority (+) class, especially for the underrepresented protected groups. To this end, we propose the *Multi-Max Mistreatment* fairness measure (*MMM*) and a *MMM*-fair boosting post Pareto classifier (MFBPP) to ensure *MMM*-fairness. Our experiments show the superiority of our method in mitigating *multi-discrimination*, producing best balanced performance across groups and classes along with best accuracy for underrepresented protected groups in the minority (+) class, without a significant compromise on overall accuracy. Further, our method is flexible to user needs as it can select the best solution trade-off according to user preferences. In future, we want study the *multi-discrimination* under class-imbalance problems in the more challenging multi-class and multi-label set-up, where the complexity is much harder.

Acknowledgements

The work of the first author is supported by the Volkswagen Foundation under the call “Artificial Intelligence and the Society of the Future” (the BIAS project). We are sincerely thankful to the invaluable suggestion of Prof. Niloy Ganguly from L3S Research Center, in shaping up the paper to its current form.

References

1. Agarwal, A., Beygelzimer, A., Dudík, M., Langford, J., Wallach, H.M.: A reductions approach to fair classification. In: ICML (2018)
2. Brukhim, N., Hazan, E., Moran, S., Mukherjee, I., Schapire, R.E.: Multiclass boosting and the cost of weak learning. *Advances in Neural Information Processing Systems* **34**, 3057–3067 (2021)
3. Chawla, N.V., Lazarevic, A., Hall, L.O., Bowyer, K.W.: Smoteboost: Improving prediction of the minority class in boosting. In: ECML PKDD. pp. 107–119. Springer (2003)
4. Deb, K.: Multi-objective optimization using evolutionary algorithms, vol. 16. John Wiley & Sons (2001)

5. Foulds, J.R., Islam, R., Keya, K.N., Pan, S.: An intersectional definition of fairness. In: ICDE. pp. 1918–1921 (2020)
6. Fredman, S.: Intersectional discrimination in eu gender equality and non-discrimination law. Brussels, UK: European Commission (2016)
7. García, V., Mollineda, R.A., Sánchez, J.S.: A new performance evaluation method for two-class imbalanced problems. In: SSPR. pp. 917–925. Springer (2008)
8. Hickey, J.M., Di Stefano, P.G., Vasileiou, V.: Fairness by explicability and adversarial SHAP learning. In: ECML PKDD 2020. pp. 174–190. Springer (2020)
9. Hu, T., Iosifidis, V., Liao, W., Zhang, H., YingYang, M., Ntoutsis, E., Rosenhahn, B.: Fairnn-conjoint learning of fair representations for fair decisions. In: DS. pp. 581–595. Springer (2020)
10. Iosifidis, V., Fetahu, B., Ntoutsis, E.: Fae: A fairness-aware ensemble framework. In: 2019 IEEE Big Data. pp. 1375–1380 (2019)
11. Iosifidis, V., Ntoutsis, E.: Adafair: Cumulative fairness adaptive boosting. In: CIKM. p. 781–790. CIKM '19 (2019)
12. Kang, J., Xie, T., Wu, X., Maciejewski, R., Tong, H.: Multifair: Multi-group fairness in machine learning. arXiv preprint arXiv:2105.11069 (2021)
13. Kearns, M., Neel, S., Roth, A., Wu, Z.S.: Preventing fairness gerrymandering: Auditing and learning for subgroup fairness. In: ICML. pp. 2564–2572 (2018)
14. Larson, J., Mattu, S., Kirchner, L., Angwin, J.: How we analyzed the compas recidivism algorithm. *ProPublica* (5 2016) **9** (2016)
15. Le Quy, T., Roy, A., Iosifidis, V., Zhang, W., Ntoutsis, E.: A survey on datasets for fairness-aware machine learning. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery* p. e1452
16. Li, A.H., Bradic, J.: Boosting in the presence of outliers: adaptive classification with nonconvex loss functions. *Journal of the American Statistical Association* **113**(522), 660–674 (2018)
17. Makkonen, T.: Multiple, compound and intersectional discrimination: bringing the experiences of the most marginalized to the fore (2002)
18. Martinez, N., Bertran, M., Sapiro, G.: Minimax pareto fairness: A multi objective perspective. In: ICML. pp. 6755–6764. PMLR (2020)
19. Morina, G., Oliinyk, V., Waton, J., Marusic, I., Georgatzis, K.: Auditing and achieving intersectional fairness in classification problems. arXiv preprint (2019)
20. Napierala, K., Stefanowski, J.: Types of minority class examples and their influence on learning classifiers from imbalanced data. *Journal of Intelligent Information Systems* **46**(3), 563–597 (2016)
21. Ntoutsis, E., Fafalios, P., Gadiraju, U., Iosifidis, V., Nejd, W., Vidal, M.E., Ruggieri, S., Turini, F., Papadopoulos, S., Krasanakis, E., et al.: Bias in data-driven artificial intelligence systems—an introductory survey. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery* **10**(3), e1356 (2020)
22. Schapire, R.E.: A brief introduction to boosting. In: Proc. IJCAI, 1999 (1999)
23. Sun, Y., Kamel, M.S., Wong, A.K., Wang, Y.: Cost-sensitive boosting for classification of imbalanced data. *Pattern Recognition* **40**(12), 3358–3378 (2007)
24. Yang, F., Cisse, M., Koyejo, O.O.: Fairness with overlapping groups; a probabilistic perspective. *Advances in Neural Information Processing Systems* **33** (2020)
25. Zafar, M.B., Valera, I., Gomez-Rodriguez, M., Gummadi, K.P.: Fairness constraints: A flexible approach for fair classification. *JMLR* **20**, 1–42 (2019)