EVOLUTIONARY ALGORITHMS FOR LIMITING THE EFFECT OF UNCERTAINTY FOR THE KNAPSACK PROBLEM WITH STOCHASTIC PROFITS

A PREPRINT

Aneta Neumann Optimisation and Logistics School of Computer Science The University of Adelaide Adelaide, Australia Yue Xie Optimisation and Logistics School of Computer Science The University of Adelaide Adelaide, Australia Frank Neumann Optimisation and Logistics School of Computer Science The University of Adelaide Adelaide, Australia

April 13, 2022

ABSTRACT

Evolutionary algorithms have been widely used for a range of stochastic optimization problems in order to address complex real-world optimization problems. We consider the knapsack problem where the profits involve uncertainties. Such a stochastic setting reflects important real-world scenarios where the profit that can be realized is uncertain. We introduce different ways of dealing with stochastic profits based on tail inequalities such as Chebyshev's inequality and Hoeffding bounds that allow to limit the impact of uncertainties. We examine simple evolutionary algorithms and the use of heavy tail mutation and a problem-specific crossover operator for optimizing uncertain profits. Our experimental investigations on different benchmarks instances show the results of different approaches based on tail inequalities as well as improvements achievable through heavy tail mutation and the problem specific crossover operator.

Keywords Stochastic knapsack problem · chance-constrained optimization · evolutionary algorithms

1 Introduction

Evolutionary algorithms [1] have been successfully applied to a wide range of complex optimization problems [2, 3, 4]. Stochastic problems play a crucial role in the area of optimization and evolutionary algorithms have frequently been applied to noisy environments [5].

Given a stochastic function to be optimized under a given set of constraints, the goal is often to maximize the expected value of a solution with respect to f. This however does not consider the deviation from the expected value. Guaranteeing that a function value with a good probability does not drop below a certain value is often more beneficial in real-world scenarios. For example, in the area of mine planning [6, 7], profits achieved within different years should be maximized. However, it is crucial to not drop below certain profit values because then the whole mine operation would not be viable and the company might go bankrupt.

We consider a stochastic version of the knapsack problem which fits the characteristics of the mine planning problem outline above. Here the profits are stochastic and the weights are deterministic. Motivated by the area of chance constrained optimization where constraints can only be violated with a small probability, we consider the scenario where we maximize the function value P for which we can guarantee that the best solution x as a profit less than P with probability at most α_p , i.e. $Prob(p(x) < P) \le \alpha_p$. Note that determining whether $Prob(p(x) < P) \le \alpha_p$ holds for a given solution x and values P and α_p is already hard for very simple stochastic settings where profits are independent and each profit can only take on two different values. Furthermore, finding a solution with a maximal P for which the condition holds poses in general a non-linear objective function that needs to take the probability distribution of p(x) into account. Constraints of the beforehand mentioned type are known as chance constraints [8]. Chance constraints on stochastic components of a problem can only be violated with a small probability, in our case specified by the parameter α_p .

1.1 Related work

Up to recently, only a few problems with chance constraints have been studied in the evolutionary computation literature [9, 10, 11]. They are based on simulations and sampling techniques for evaluating chance constraints. Such approaches require a relatively large computation time for evaluating the chance constraints. In contrast to this, tail inequalities can be used if certain characteristics such as the expected value and variance of a distribution are known. Such approaches have recently been examined for the chance constrained knapsack problem in the context of evolutionary computation [12, 13]. The standard version of the chance-constrained knapsack problem considers the case where the profits are deterministic and the weights are stochastic. Here the constraint bound B can only be violated with a small probability. Different single and multi-objective approaches have recently been investigated [12, 13] and also the case of a dynamically changing constraint has been investigated [14]

Furthermore, chance constrained monotone submodular functions have been studied in [15, 16]. In [15], greedy algorithms that use tail inequalities such as Chebyshev's inequality and Chernoff bounds have been analyzed. It has been shown that they almost achieve the same approximation guarantees in the chance constrained setting as in the deterministic setting. In [16], the use of evolutionary multi-objective algorithms for monotone submodular functions has been investigated and it has been shown that they achieve the same approximation guarantees as the greedy algorithms but perform much better in practice.

Finally, chance constrained problems have been further investigated through runtime analysis for special instances of the knapsack problem [17, 18]. This includes a first study on very specific instances showing when local optima arise [17] and a study on groups of items whose stochastic uniform weights are correlated with each other [18].

All previously mentioned studies concentrated on stochastic weights and how algorithms can deal with the chance constraints with respect to the weight bound of the knapsack problem. In [19], a version of the knapsack problem stochastic profits and deterministic weights has been considered where the goal is to maximize the probability that the profit meets a certain threshold value. In contrast to this, we will maximize the profit under the condition that it is achieved with high probability. We will provide a first study on evolutionary algorithms for giving guarantees when maximizing stochastic profits, a topic that is well motivated by the beforehand mentioned mine planning application but to our knowledge not studied in the literature yet.

The paper is structured as follows. In Section 2, we introduce the problem formulation and tail bounds that will be used to construct fitness functions for dealing with stochastic profit. In Section 3, we derive fitness functions that are able to maximize the profit for which we can give guarantees. Section 4 introduces evolutionary algorithms for the problem and we report on our experimental investigations in Section 5. We finally finish with some conclusions.

2 Problem definition

In this section, we formally introduce the problem and tail inequalities for dealing with stochastic profits that will later be used to design fitness functions. We consider a stochastic version of the classical NP-hard knapsack problem. In the classical problem, there are given n items $1, \ldots, n$ where each item has a profit p_i and a weight w_i , the goal is to maximize the profit $p(x) = \sum_{i=1}^{n} p_i$ under the condition that $w(x) = \sum_{i=1}^{n} w_i x_i \leq B$ for a given weight bound B holds. The classical knapsack problem has been well studied in the literature. We consider the following stochastic version, where the profits p_i are stochastic and the weights are still deterministic. Our goal is to maximize the profit P for which we can guarantee that there is only a small probability α_p of dropping below P. Formally, we tackle the following problem.

$$\max P$$
 (1)

s.t.
$$Pr(p(x) < P) \le \alpha_p$$
 (2)

$$w(x) \le B \tag{3}$$

$$x \in \{0,1\}^n \tag{4}$$

Equation 2 is a chance constraint on the profit and the main goal of this paper is to find a solution x that maximize the value of P such that the probability of getting a profit lower than P is at most α_p .

We denote by $\mu(x)$ the expected profit and by v(x) the variance of the profit throughout this paper.

2.1 Concentration bounds

In order to establish guarantees for the stochastic knapsack problem we make use of well-known tail inequalities that limit the deviation from the expected profit of a solution.

For a solution X weight expected value E[X] and variance Var(X) we can use the lower tail of the following Chebyshev-Cantelli inequality.

Theorem 1 (One-sided Chebyshev's / Cantelli's inequality). Let X be a random variable with expected value E[X] and variance Var[X] > 0. Then, for all $\lambda > 0$,

$$\Pr[X \ge E[X] - \lambda] \ge 1 - \frac{\operatorname{Var}[X]}{\operatorname{Var}[X] + \lambda^2}$$
(5)

We will refer to this inequality as Chebyshev's inequality in the following. Chebyshev's inequality only requires the expected value and variance of a solution, but no additional requirements such as the independence of the random variables.

We use the additive Hoeffding bound given in Theorem 1.10.9 of [20] for the case where the weights are independently chosen within given intervals.

Theorem 2 (Hoeffding bound). Let X_1, \ldots, X_n be independent random variables. Assume that each X_i takes values in a real interval $[a_i, b_i]$ of length $c_i := b_i - a_i$. Let $X = \sum_{i=1}^n X_i$. Then for all $\lambda > 0$,

$$Pr(X \ge E[x] + \lambda) \le e^{-2\lambda^2/(\sum_{i=1}^n c_i^2)}$$
(6)

$$Pr(X \le E[x] - \lambda) \le e^{-2\lambda^2/(\sum_{i=1}^n c_i^2)}$$
(7)

3 Fitness functions for profit guarantees

The main task when dealing with the setting of chance constraint profits is to come up with fitness functions that take the uncertainty into account.

In this section, we introduce different fitness functions that can be used in an evolutionary algorithm to compute solutions that maximize the profit under the uncertainty constraint. We consider the search space $\{0,1\}^n$ and for a given search point $x \in \{0,1\}^n$, item *i* chosen iff $x_i = 1$ holds.

The fitness of a search point $x \in \{0, 1\}^n$ is given by

$$f(x) = (u(x), \hat{p}(x))$$

where $u(x) = \max\{w(x) - B, 0\}$ is the amount of constraint violation of the bound B by the weight that should be minimized and $\hat{p}(x)$ is the discounted profit of solution x that should be maximized. We optimize f with respect to lexicographic order and have $f(x) \ge f(y)$

iff

$$(u(x) < u(y)) \lor ((u(x) = u(y)) \land (\hat{p}(x) \ge \hat{p}(y)).$$

This implies a standard penalty approach where the weight w(x) is reduced until it meets the constraint bound B, and the profit $\hat{p}(x)$ is maximized among all feasible solutions.

The key part if to develop formulations for \hat{p} that take into account the stochastic part of the profits to make the formulations suitable for our chance constrained setting. Therefore, we will develop profit functions that reflect different stochastic settings in the following.

3.1 Chebyshev's inequality

We give a formulation for \hat{p} that can be applied in quite general settings, thereby providing only a lower bound on the value P for which a solution x still meets the profit chance constraint.

We assume that for a given solution only the expected value $\mu(x)$ and the variance v(x) are known. The following lemma gives a condition for meeting the chance constraint based on Theorem 1.

Lemma 1. Let x be a solution with expected profit $\mu(x)$ and variance v(x). If

$$\mu(x) - P \ge \sqrt{\frac{(1-\alpha) \cdot v(x)}{\alpha}}$$

then $Pr(p(x) < P) \le \alpha_p$.

Proof. We have

$$\begin{aligned} Pr(p(x) \ge P) &= Pr(p(x) \ge \mu(x) - (\mu(x) - P)) \\ &\ge 1 - \frac{v(x)}{v(x) + (\mu(x) - P)^2} \end{aligned}$$

The chance constraint is met if

$$1 - \frac{v(x)}{v(x) + (\mu(x) - P)^2} \ge 1 - \alpha_p$$

$$\iff \alpha_p \ge \frac{v(x)}{v(x) + (\mu(x) - P)^2}$$

$$\iff \alpha_p \cdot (v(x) + (\mu(x) - P)^2) \ge v(x)$$

$$\iff \alpha_p \cdot v(x) + \alpha_p \cdot (\mu(x) - P)^2) \ge v(x)$$

$$\iff \alpha_p(\mu(x) - P)^2) \ge (1 - \alpha_p)v(x)$$

$$\iff (\mu(x) - P)^2) \ge ((1 - \alpha_p)/\alpha_p) \cdot v(x)$$

$$\implies \mu(x) - P \ge \sqrt{(1 - \alpha_p)/\alpha_p} \cdot v(x)$$

$$\iff \mu(x) - \sqrt{((1 - \alpha_p)/\alpha_p) \cdot v(x)} \ge P$$

Given the last expression, P is maximal for

$$P = \mu(x) - \sqrt{((1 - \alpha_p)/\alpha_p) \cdot v(x)}$$

We use the following profit function based on Chebyshev's inequality:

$$\hat{p}_{Cheb}(x) = \mu(x) - \sqrt{(1 - \alpha_p)/\alpha_p} \cdot \sqrt{v(x)}$$
(8)

3.2 Hoeffding bound

We now assume that each element *i* takes on a profit $p_i \in [\mu_i - \delta_p, \mu_i + \delta_p]$ independently of the other items. Let $\mu(x) = \sum \mu_i x_i$. we have $p(x) = \mu(x) - \delta_p |x|_1 + p'(x)$ where p'(x) is the sum of $|x|_1$ independent random variable in $[0, 2\delta_p]$. We have $E[p'(x)] = |x|_1\delta_p$ and

$$Pr(p(x) \le \mu(x) - \lambda)$$

$$= Pr(p'(x) \le |x|_1 \delta_p - \lambda)$$

$$\le e^{-2\lambda^2/(4\delta_p^2 |x|_1)} = e^{-\lambda^2/(2\delta_p^2 |x|_1)}$$

based on Theorem 2.

The chance constraint is met if

$$e^{-\lambda^2/(2\delta_p^2|x|_1)} \le \alpha_p$$

$$\iff -\lambda^2/(2\delta_p^2|x|_1) \le \ln(\alpha_p)$$

$$\iff \lambda^2 \ge \ln(1/\alpha_p) \cdot (2\delta_p^2|x|_1)$$

$$\iff \lambda \ge \delta_p \cdot \sqrt{\ln(1/\alpha_p) \cdot 2|x|_1}$$

Therefore, we get the following profit function based on the additive Hoeffding bound from Theorem 2:

$$\hat{p}_{Hoef}(x) = \mu(x) - \delta_p \cdot \sqrt{\ln(1/\alpha_p) \cdot 2|x|_1}$$
(9)

3.3 Comparison of Chebyshev and Hoeffding based fitness functions

In contrast to the fitness function \hat{p}_{Norm} which is an exact reformulation, \hat{p}_{Hoef} and \hat{p}_{Cheb} give a conservative lower bound on the value of P to be maximized. We now consider the setting investigated for the Hoeffding bound and compare it to the use of Chebyshev's inequality. If each element is chosen independently and uniformly at random from an interval of length $2\delta_p$ as done in Section 3.2, then we have $v(x) = |x|_1 \cdot \delta_p^2/3$. Based on this we can establish a condition on α_p which shows when $\hat{p}_{Hoef}(x) \leq \hat{p}_{Cheb}(x)$ holds.

We have

$$\hat{p}_{Hoef}(x) \ge \hat{p}_{Cheb}(x)$$

$$\iff \sqrt{\ln(1/\alpha_p) \cdot 2 \cdot |x|_1} \le \sqrt{\frac{(1-\alpha_p)|x|_1}{3\alpha_p}}$$

$$\iff \ln(1/\alpha_p) \cdot 2 \cdot |x|_1 \le \frac{(1-\alpha_p)|x|_1}{3\alpha_p}$$

$$\iff \ln(1/\alpha_p) \cdot \alpha_p/(1-\alpha_p) \le 1/6$$

Note that the last inequality depends only on α_p but not on δ_p or $|x|_1$. We will use values of $\alpha_p \in \{0.1, 0.01, 0.001\}$ in our experiments and have

$$\ln(1/\alpha_p) \cdot \alpha_p / (1 - \alpha_p) > 1/6$$

for $\alpha_p = 0.1$ and

$$\ln(1/\alpha_p) \cdot \alpha_p / (1 - \alpha_p) < 1/6$$

for $\alpha_p = 0.01, 0.001$. This means that the fitness function based on Chebyshev's inequality is preferable to use for $\alpha_p = 0.1$ as it gives a better (tighter) value for any solution x and the fitness function based on Hoeffding bounds is preferable for $\alpha_p = 0.01, 0.001$. Dependent on the given instance, it might still be useful to use the less tighter fitness function as the fitness functions impose different fitness landscapes.

4 Evolutionary algorithms

We examine the performance of the (1+1) EA, the (1+1) EA with heavy-tailed mutation and a $(\mu+1)$ EA. The $(\mu+1)$ EA uses a specific crossover operator for the optimization of the chance-constrained knapsack problem with stochastic profits together with heavy-tailed mutation. All algorithms use the fitness function f introduced in Section 3 and we will examine different choices of \hat{p} in our experimental investigations.

4.1 (1+1) EA

We consider a simple evolutionary algorithm called (1+1) EA that has been extensively studied in the area of runtime analysis. The approach is given in Algorithm 1. The (1+1) EA starts with an initial solution $x \in \{0, 1\}^n$ chosen uniformly at random. It generates in each iteration a new candidate solution by standard bit mutation, i.e. by flipping each bit of the current solution with a probability of 1/n, where n is the length of the bit string. In the selection step, the algorithm accept the offspring if it is at least as good as the parent. The process is iterated until a given stopping criterion is fulfilled. While the (1+1) EA is a very simple algorithm, it produces good results in many cases. Furthermore, it has the ability to sample new solutions globally as each bit is flipped independently with probability 1/n. In order to overcome large inferior neighborhoods larger mutation rates might be beneficial. Allowing larger mutation rates from time to time is the idea of heavy tail mutations.

4.2 Heavy tail mutations

We also investigate the (1+1) EA with heavy tail mutation instead of standard bit mutation. In each operation of the heavy tail mutation operator (see Algorithm 9, first a parameter $\theta \in [1..n/2]$ is chosen according to the discrete power law distribution $D_{n/2}^{\beta}$. Afterwards, each bit *n* is flipped with probability θ/n . Based on the investigations in [21], we use $\beta = 1.5$ for our experimental investigations.

 Algorithm 1: (1+1) EA

 1: Choose $x \in \{0,1\}^n$ to be a decision vector.

 2: while stopping criterion not met do

 3: $y \leftarrow$ flip each bit of x independently with probability of $\frac{1}{n}$;

 4: if $f(y) \ge f(x)$ then

 5: $x \leftarrow y$;

 6: end if

 7: end while

Algorithm 2: The heavy-tail mutation operator

Input: Individual $x = (x_1, ..., x_n) \in \{0, 1\}^n$ and value β ; 1: Choose $\theta \in [1, ..., n/2]$ randomly according to $D_{n/2}^{\beta}$; 2: for i = 1 to n do 3: if $rand([0, 1]) \leq \theta/n$ then 4: $y_i \leftarrow 1 - x_i$; 5: else 6: $y_i \leftarrow x_i$; 7: end if 8: end for 9: return $y = (y_1, ..., y_n)$;

The heavy-tail mutation operator allows to flip significantly more bits in some mutation steps than standard bit mutation. The use of heavy tail mutations has been shown to be provably effective on the OneMax and Jump benchmark problems in theoretical investigations [21, 22]. Moreover, in [13] has been shown in that the use of heavy tail mutation effective improve performance of single-objective and multi-objective evolutionary algorithms for the weight chance constrained knapsack problem. For details, on the discrete power law distribution and the heavy tail operator, we refer the reader to [21].

4.3 Population-based Evolutionary Algorithm

We also consider the population-based $(\mu + 1)$ -EA shown in Algorithm 3. The algorithm produces in each iteration an offspring by crossover and mutation with probability p_c and by mutation only with probability $1 - p_c$. We use $p_c = 0.8$ for our experimental investigations. The algorithm makes use of the specific crossover operator shown in Algorithm 4 and heavy tail mutation. The crossover operator choose two different individuals x and y from the population P and produces an offspring z. All bit position where x and y are the same are transferred to z. Positions i where x_i and y_i form the set I and are different are treated in a greedy way according to the discount expected value to weight ratio. Setting $p'_i = \mu_i - u(z, i)$ discounts in line 3 the expected profit by an uncertainty value based on the solution z and the impact if element i is added to z.

There are different ways of doing this. In our experiments, where the profits of the elements are chosen independently and uniformly at random, we use the calculation based on Hoeffding bounds and set

$$p'_{i} = \mu_{i} - \delta_{p} \cdot \left(\sqrt{\ln(1/\alpha_{p}) \cdot 2(|z|_{1} + 1)} - \sqrt{\ln(1/\alpha_{p}) \cdot 2|z|_{1}} \right).$$

The expected profit μ_i is therefore discounted with the additional uncertainty that would be added according to the Hoeffding bound when adding an additional element to z. Once, the discounted values p'_i , the elements are sorted according to p'_i/w_i . The final steps tries the elements of I in sorted order and adds element $i \in I$ if it would not violate the weight constraint.

5 Experimental Investigation

In this section, we investigate the (1+1) EA algorithm and the (1+1) EA with heavy-tailed mutation on several benchmarks with chance constraints and compare them to the (μ + 1) EA algorithm with heavy-tailed mutation and new crossover operator.

Algorithm 3: $(\mu + 1)$ EA

```
1: Randomly generate \mu initial solutions as the initial population P;
```

- 2: while stopping criterion not meet do
- 3: Let x and y be two different individual from P chosen uniformly at random;
- 4: **if** $rand([0,1]) \leq p_c$ **then**
- 5: apply the discounted greedy uniform crossover operator to x and y to produce an offspring z.
- 6: **else**
- 7: Choose one individual x from P uniformly at random and let z be a copy of x.
- 8: **end if**
- 9: apply the heavy-tail mutation operator to z;

Algorithm 4: Discounted Greedy Uniform Crossover

Input: Individuals $x = (x_1, \ldots, x_n)$ and $y = (y_1, \ldots, y_n)$; 1: Create $z = (z_1, \ldots, z_n)$ by setting $z_i \leftarrow x_i$ iff $x_i = y_i$ and $z_i \leftarrow 0$ iff $x_i! = y_i$; 2: Let $I = \{i \in \{1, \ldots, n\} \mid x_i! = y_i\}$; 3: Set $p'_i = \mu_i - u(z, i)$ for all $i \in I$; 4: Sort the items $i \in I$ in decreasing order with respect to p'_i/w_i ratio; 5: for each $i \in I$ in sorted order **do** 6: if $w(z) + w_i \leq B$ then 7: $z_i \leftarrow 1$; 8: end if 9: end for 10: return $z = (z_1, \ldots, z_n)$;

5.1 Experimental Setup

Our goal is to study different chance constraint settings in terms of the uncertainty level δ , and the probability bound α . We consider different well-known benchmarks from [23, 24] in their profit chance constrained versions. We consider two types of instances, uncorrelated and bounded strong correlated ones, with n = 100, 300, 500 items. For each benchmark, we study the performance of the (1+1) EA, (1+1) EA with heavy-tailed mutation and (μ + 1) EA with value of $\mu = 10$. We consider all combinations of $\alpha = 0.1, 0.01, 0.001$, and $\delta = 25, 50.0$ for the experimental investigations of the algorithms. We allow 1 000 000 fitness evaluations for each of these problem parameter combinations. For each tested instance, we carry out 30 independent runs and report the average results, standard deviation and statistical test. In order to measure the statistical validity of our results, we use the Kruskal-Wallis test with 95% confidence. We apply the Bonferroni post-hoc statistical correction which is used for multiple comparison of a control algorithm, to two or more algorithms [25]. $X^{(+)}$ is equivalent to the statement that the algorithm in the column outperformed algorithm X. $X^{(-)}$ is equivalent to the statement that X outperformed the algorithm given in the column. If algorithm X^* does appear, then no significant difference was determined between the algorithms.

6 Experimental Results

We consider now the results for the (1+1) EA, (1+1) EA with heavy-tailed mutation and (μ + 1) EA with heavy-tailed mutation and specific crossover algorithm based on Chebyshev's inequality and Hoeffding bounds for the benchmark set.

We first consider the optimization result obtained by the above mentioned algorithms using Chebyshev's inequality for the combinations of α_p and δ_p . The experimental results are shown in Table 1. The results show that (1 + 1) EA

					(1+1) EA		(1+1) EA-HT			$(\mu+1)$ EA		
	B	α_p	δ_p	\hat{p}_{Cheb}	std	stat	\hat{p}_{Cheb}	std	stat	\hat{p}_{Cheb}	std	stat
uncorr_100	2407	0.1	25	11073.5863	36.336192	$2^{(*)}, 3^{(*)}$	11069.0420	46.285605	$1^{(*)}, 3^{(*)}$	11057.4420	59.495722	$1^{(*)}, 2^{(*)}$
			50	10863.1496	85.210231	$2^{(*)}, 3^{(*)}$	10889.4840	37.175095	$1^{(*)}, 3^{(*)}$	10883.7163	53.635972	$1^{(*)}, 2^{(*)}$
		0.01	25	10641.9089	63.402329	$2^{(*)}, 3^{(*)}$	10664.5974	29.489838	$1^{(*)}, 3^{(*)}$	10655.7251	43.869265	$1^{(*)}, 2^{(*)}$
			50	10054.6427	49.184220	$2^{(*)}, 3^{(*)}$	10066.2854	36.689426	$1^{(*)}, 3^{(*)}$	10064.8734	39.556767	$1^{(*)}, 2^{(*)}$
		0.001	25	9368.33053	46.894877	$2^{(*)}, 3^{(*)}$	9368.2483	34.904933	$1^{(*)}, 3^{(*)}$	9365.5257	40.458098	$1^{(*)}, 2^{(*)}$
			50	7475.44948	50.681386	$2^{(*)}, 3^{(*)}$	7490.6387	27.819516	$1^{(*)}, 3^{(*)}$	7497.5054	14.098629	$1^{(*)}, 2^{(*)}$
strong_100	4187	0.1	25	8638.0428	68.740095	$2^{(-)}, 3^{(-)}$	8698.2592	64.435352	$1^{(+)}, 3^{(*)}$	8707.9271	49.633473	$1^{(+)}, 2^{(*)}$
_			50	8441.9311	80.335771	$2^{(-)}, 3^{(-)}$	8483.1151	45.284814	$1^{(+)}, 3^{(*)}$	8481.0022	55.979520	$1^{(+)}, 2^{(*)}$
		0.01	25	8214.8029	56.705379	$2^{(-)}, 3^{(-)}$	8230.9642	42.084563	$1^{(+)}, 3^{(*)}$	8210.1448	55.148757	$1^{(+)}, 2^{(*)}$
			50	7512.3033	71.115520	$2^{(-)}, 3^{(-)}$	7563.5495	37.758812	$1^{(+)}, 3^{(*)}$	7554.7382	53.030592	$1^{(+)}, 2^{(*)}$
		0.001	25	6771.7849	58.314395	$2^{(-)}, 3^{(-)}$	6797.0376	42.944371	$1^{(+)}, 3^{(*)}$	6793.0387	43.492135	$1^{(+)}, 2^{(*)}$
			50	4832.2084	88.887119	$2^{(-)}, 3^{(-)}$	4929.1483	52.858392	$1^{(+)}, 3^{(*)}$	4902.0006	44.976733	$1^{(+)}, 2^{(*)}$
uncorr_300	6853	0.1	25	34150.7224	167.458986	$2^{(*)}, 3^{(-)}$	34218.9806	164.65331	$1^{(*)}, 3^{(*)}$	34319.8500	177.580430	$1^{(+)}, 2^{(*)}$
			50	33749.8625	202.704754	$2^{(*)}, 3^{(-)}$	33827.9115	158.675094	$1^{(*)}, 3^{(*)}$	33992.7669	157.059148	$1^{(+)}, 2^{(*)}$
		0.01	25	33298.9369	215.463952	$2^{(*)}, 3^{(-)}$	33482.2230	186.361325	$1^{(*)}, 3^{(*)}$	33584.5679	129.781221	$1^{(+)}, 2^{(*)}$
			50	32326.5299	203.976688	$2^{(*)}, 3^{(-)}$	32332.5785	190.826414	$1^{(*)}, 3^{(*)}$	32504.2005	178.815508	$1^{(+)}, 2^{(*)}$
		0.001	25	30989.2470	242.861056	$2^{(*)}, 3^{(-)}$	31150.1989	187.329891	$1^{(*)}, 3^{(*)}$	31281.7283	181.280416	$1^{(+)}, 2^{(*)}$
			50	27868.2812	180.822780	$2^{(*)}, 3^{(-)}$	27923.1672	148.146917	$1^{(*)}, 3^{(*)}$	28024.3756	144.125407	$1^{(+)}, 2^{(*)}$
strong_300	13821	0.1	25	24795.3122	143.413609	$2^{(-)}, 3^{(*)}$	24939.0678	94.941101	$1^{(+)}, 3^{(*)}$	24850.2784	135.783162	$1^{(*)}, 2^{(*)}$
-			50	24525.1204	161.185000	$2^{(-)}, 3^{(*)}$	24585.2993	112.692219	$1^{(+)}, 3^{(*)}$	24589.7315	125.724850	$1^{(*)}, 2^{(*)}$
		0.01	25	24047.9634	147.055910	$2^{(-)}, 3^{(*)}$	24138.6765	103.635233	$1^{(+)}, 3^{(*)}$	24121.8843	132.985469	$1^{(*)}, 2^{(*)}$
			50	22982.7691	169.377913	$2^{(-)}, 3^{(*)}$	23088.9710	81.229946	$1^{(+)}, 3^{(*)}$	23057.3537	160.481591	$1^{(*)}, 2^{(*)}$
		0.001	25	21689.9288	168.324844	$2^{(-)}, 3^{(*)}$	21824.5028	77.615607	$1^{(+)}, 3^{(*)}$	21786.4256	126.077269	$1^{(*)}, 2^{(*)}$
			50	18445.0866	125.747992	$2^{(-)}, 3^{(*)}$	18545.0084	98.512038	$1^{(+)}, 3^{(*)}$	18543.0067	96.526569	$1^{(*)}, 2^{(*)}$
uncorr_500	11243	0.1	25	58309.8801	266.319166	$2^{(-)}, 3^{(-)}$	58454.4069	295.624416	$1^{(+)}, 3^{(-)}$	58708.9818	157.245339	$1^{(+)}, 2^{(+)}$
			50	57783.7554	316.155254	$2^{(-)}, 3^{(-)}$	57927.2459	299.811063	$1^{(+)}, 3^{(-)}$	58267.9737	204.854052	$1^{(+)}, 2^{(+)}$
		0.01	25	57262.7885	330.683000	$2^{(-)}, 3^{(-)}$	57538.1166	260.869372	$1^{(+)}, 3^{(-)}$	57770.6524	178.217884	$1^{(+)}, 2^{(+)}$
			50	55916.4463	260.392742	$2^{(-)}, 3^{(-)}$	56086.6031	224.647105	$1^{(+)}, 3^{(-)}$	56321.8437	197.704397	$1^{(+)}, 2^{(+)}$
		0.001	25	54149.7603	364.823822	$2^{(-)}, 3^{(-)}$	54406.8517	249.217045	$1^{(+)}, 3^{(-)}$	54806.6815	170.082092	$1^{(+)}, 2^{(+)}$
			50	50124.9811	265.408552	$2^{(-)}, 3^{(-)}$	50312.3993	286.632525	$1^{(+)}, 3^{(-)}$	50672.0950	197.712768	$1^{(+)}, 2^{(+)}$
strong_500	22223	0.1	25	41104.1611	321.324820	$2^{(*)}, 3^{(*)}$	41523.8952	222.691441	$1^{(*)}, 3^{(*)}$	41458.8477	238.463764	$1^{(*)}, 2^{(*)}$
1			50	40834.8213	243.308935	$2^{(*)}, 3^{(*)}$	41067.8559	229.706142	$1^{(*)}, 3^{(*)}$	41043.6296	173.586544	$1^{(*)}, 2^{(*)}$
1		0.01	25	40248.7094	289.114488	$2^{(*)}, 3^{(*)}$	40567.8724	133.387473	$1^{(*)}, 3^{(*)}$	40448.5671	206.754226	$1^{(*)}, 2^{(*)}$
1			50	38831.0336	298.888606	$2^{(*)}, 3^{(*)}$	39123.3879	120.110352	$1^{(*)}, 3^{(*)}$	38984.3118	169.701352	$1^{(*)}, 2^{(*)}$
1		0.001	25	37201.8768	273.119842	$2^{(*)}, 3^{(*)}$	37490.7767	118.382846	$1^{(*)}, 3^{(*)}$	37395.7375	164.601365	$1^{(*)}, 2^{(*)}$
1			50	32880.2003	272.672330	$2^{(*)}, 3^{(*)}$	33013.4535	172.524052	$1^{(*)}, 3^{(*)}$	32951.6884	206.900731	$1^{(*)}, 2^{(*)}$

Table 1: Experimental results for the Chebyshev based function \hat{p}_{Cheb} .

with heavy-tailed mutation is able to achieve higher average results for the instances with 100, 300, 500 items for type bounded strongly correlated in most of the cases for all α_p and δ_p combinations. It can be observed that for the instance with 100 uncorrelated items the (1 + 1) EA with heavy-tailed mutation outperforms all algorithms for $\alpha = 0.1$ and $\delta = 50$ and for $\alpha = 0.01$ $\delta = 25, 50$, respectively. However, ($\mu + 1$) EA can improve on the optimization result for small α_p and high δ_p values, i.e. $\alpha_p = 0.001$, $\delta_p = 50$.

It can be observed that $(\mu + 1)$ EA obtains the highest mean value for the instance with 300 and 500 items for the uncorrelated type. Furthermore, the statistical tests show that for all combinations of α_p and δ_p (μ + 1) EA significantly outperforms (1 + 1) EA and (1 + 1) EA with heavy-tailed mutation. For example, for the instance with 300, 500 items uncorrelated and for 100 items bounded strongly correlated the statistical tests show that (μ + 1) EA and (1 + 1) EA with heavy-tailed mutation tests show that (μ + 1) EA and (1 + 1) EA with heavy-tailed mutation outperforms (1 + 1) EA. For the other settings there is no statistical significant difference in terms of the results between all algorithms.

Table 2 shows the results obtained by the above mentioned algorithms using Hoeffding bounds for the combinations of α_p and δ_p and statistical tests. The results show that (1+1) EA with heavy-tailed mutation obtains the highest mean values compared to the results obtained by (1+1) EA and (μ + 1) EA for each setting for the instance with 100 items for both types, uncorrelated and bounded strongly correlated. Similar to the previous investigation in the case for the instances with 300 items, the (1+1) EA with heavy-tailed mutation obtains the highest mean values compared to the results obtained by other algorithms in most of the cases. However, the solutions obtained by (μ + 1) EA has significantly better performance than in the case for $\alpha_p = 0.1, 0.001, \delta_p = 25$.

The use of the heavy-tailed mutation when compared to the use of standard bit mutation in (1+1) EA achieves a better performance for all cases. Furthermore, the statistical tests show that for most combinations of α_p and δ_p , the (1+1) EA with heavy-tailed mutation significantly outperforms the other algorithms. Overall, it can be observed that

					(1+1) EA		(1+1) EA-HT			$(\mu+1)$ EA		
	B	α_p	δ_p	\hat{p}_{Hoef}	std	stat	\hat{p}_{Hoef}	std	stat	\hat{p}_{Hoef}	std	stat
uncorr_100	2407	0.1	25	10948.7292	90.633230	$2^{(-)}, 3^{(*)}$	11016.8190	49.768932	$1^{(+)},3^{(+)}$	10981.3880	37.569308	$1^{(*)}, 2^{(-)}$
			50	10707.1094	43.869094	$2^{(-)}, 3^{(*)}$	10793.1175	58.150646	$1^{(+)}, 3^{(+)}$	10708.6094	44.384035	$1^{(*)}, 2^{(-)}$
		0.01	25	10836.0906	91.332983	$2^{(-)}, 3^{(*)}$	10928.3054	45.464936	$1^{(+)}, 3^{(+)}$	10866.9831	45.408500	$1^{(*)}, 2^{(-)}$
			50	10482.6216	46.444510	$2^{(-)}, 3^{(*)}$	10611.1895	69.341044	$1^{(+)}, 3^{(+)}$	10477.2328	47.065426	$1^{(*)}, 2^{(-)}$
		0.001	25	10765.3289	68.565293	$2^{(-)}, 3^{(*)}$	10862.7124	49.091526	$1^{(+)}, 3^{(+)}$	10784.7286	38.187390	$1^{(*)}, 2^{(-)}$
			50	10263.9426	90.504901	$2^{(-)}, 3^{(*)}$	10487.5621	32.625499	$1^{(+)}, 3^{(+)}$	10309.8572	44.811326	$1^{(*)}, 2^{(-)}$
strong_100	4187	0.1	25	8553.1744	74.046187	$2^{(-)}, 3^{(*)}$	8640.05156	39.413105	$1^{(+)},3^{(+)}$	8588.4894	53.878268	$1^{(*)}, 2^{(-)}$
0			50	8264.8129	63.309264	$2^{(-)}, 3^{(*)}$	8398.4354	46.013234	$1^{(+)}, 3^{(+)}$	8273.9670	41.403505	$1^{(*)}, 2^{(-)}$
		0.01	25	8422.9258	70.464985	$2^{(-)}, 3^{(*)}$	8540.2095	63.072560	$1^{(+)}, 3^{(+)}$	8447.8489	59.841707	$1^{(*)}, 2^{(-)}$
			50	7996.0193	65.822419	$2^{(-)}, 3^{(*)}$	8181.2980	45.667034	$1^{(+)}, 3^{(+)}$	8013.1724	56.445427	$1^{(*)}, 2^{(-)}$
		0.001	25	8338.5159	57.880350	$2^{(-)}, 3^{(*)}$	8460.7513	53.402755	$1^{(+)}, 3^{(+)}$	8362.9405	51.607219	$1^{(*)}, 2^{(-)}$
			50	7794.1245	80.411946	$2^{(-)}, 3^{(*)}$	8017.8843	53.266120	$1^{(+)}, 3^{(+)}$	7833.5575	37.293481	$1^{(*)}, 2^{(-)}$
uncorr_300	6853	0.1	25	33831.9693	181.485453	$2^{(-)}, 3^{(-)}$	34118.7631	200.095911	$1^{(+)}, 3^{(*)}$	34129.8891	172.788856	$1^{(+)}, 2^{(*)}$
			50	33380.4952	157.014552	$2^{(-)}, 3^{(-)}$	33715.2964	199.074378	$1^{(+)}, 3^{(*)}$	33662.2668	124.206823	$1^{(+)}, 2^{(*)}$
		0.01	25	33655.5737	234.136500	$2^{(-)}, 3^{(-)}$	34014.3456	200.488072	$1^{(+)}, 3^{(*)}$	33962.8643	161.560953	$1^{(+)}, 2^{(*)}$
			50	32933.5174	291.623690	$2^{(-)}, 3^{(-)}$	33327.8984	235.915481	$1^{(+)}, 3^{(*)}$	33277.4015	142.387738	$1^{(+)}, 2^{(*)}$
		0.001	25	33515.7445	219.707660	$2^{(-)}, 3^{(-)}$	33806.1572	184.532069	$1^{(+)}, 3^{(*)}$	33835.4528	149.327823	$1^{(+)}, 2^{(*)}$
			50	32706.4466	176.599463	$2^{(-)}, 3^{(-)}$	33112.7494	177.218747	$1^{(+)}, 3^{(*)}$	32940.4397	173.836538	$1^{(+)}, 2^{(*)}$
strong_300	13821	0.1	25	24602.1254	171.596469	$2^{(-)}, 3^{(-)}$	24848.3209	100.078545	$1^{(+)}, 3^{(+)}$	24734.7210	127.268428	$1^{(+)}, 2^{(-)}$
_			50	24184.8938	125.755762	$2^{(-)}, 3^{(-)}$	24457.7279	118.679623	$1^{(+)}, 3^{(+)}$	24205.9660	116.049342	$1^{(+)}, 2^{(-)}$
		0.01	25	24476.1412	159.274566	$2^{(-)}, 3^{(-)}$	24638.0751	105.088783	$1^{(+)}, 3^{(+)}$	24538.4199	101.959196	$1^{(+)}, 2^{(-)}$
			50	23653.3561	225.087307	$2^{(-)}, 3^{(-)}$	24060.0806	87.242862	$1^{(+)}, 3^{(+)}$	23830.8655	85.829604	$1^{(+)}, 2^{(-)}$
		0.001	25	24256.4468	173.293324	$2^{(-)}, 3^{(-)}$	24558.9506	105.253206	$1^{(+)}, 3^{(+)}$	24345.4340	144.094192	$1^{(+)}, 2^{(-)}$
			50	23377.6774	143.350899	$2^{(-)}, 3^{(-)}$	23843.7258	114.231223	$1^{(+)}, 3^{(+)}$	23520.1166	112.403711	$1^{(+)}, 2^{(-)}$
uncorr_500	11243	0.1	25	57995.2668	285.959899	$2^{(-)}, 3^{(-)}$	58286.1443	253.880622	$1^{(+)}, 3^{(-)}$	58527.7062	179.624520	$1^{(+)}, 2^{(+)}$
			50	57331.7069	319.089163	$2^{(-)}, 3^{(-)}$	57825.9426	227.649351	$1^{(+)}, 3^{(-)}$	57899.9614	167.585846	$1^{(+)}, 2^{(+)}$
		0.01	25	57757.1719	290.254639	$2^{(-)}, 3^{(-)}$	58023.1930	277.702516	$1^{(+)}, 3^{(-)}$	58224.2474	211.715398	$1^{(+)}, 2^{(+)}$
			50	56787.0897	411.706381	$2^{(-)}, 3^{(-)}$	57367.9869	206.916491	$1^{(+)}, 3^{(+)}$	57309.9927	227.397029	$1^{(+)}, 2^{(-)}$
		0.001	25	57519.6613	379.930530	$2^{(-)}, 3^{(-)}$	57910.4812	250.540248	$1^{(+)}, 3^{(-)}$	58052.4481	182.866780	$1^{(+)}, 2^{(+)}$
			50	56446.5408	273.663433	$2^{(-)}, 3^{(-)}$	57018.3566	253.684943	$1^{(+)}, 3^{(+)}$	56942.4016	183.464200	$1^{(+)}, 2^{(-)}$
strong_500	22223	0.1	25	41060.1634	306.686391	$2^{(-)}, 3^{(*)}$	41397.7895	146.844521	$1^{(+)}, 3^{(+)}$	41186.7266	213.577571	$1^{(*)}, 2^{(-)}$
-			50	40244.7545	272.646652	$2^{(-)}, 3^{(*)}$	40897.9183	231.639926	$1^{(+)}, 3^{(+)}$	40543.1279	221.615657	$1^{(*)}, 2^{(-)}$
1		0.01	25	40800.7084	271.459688	$2^{(-)}, 3^{(*)}$	41204.2676	179.999423	$1^{(+)}, 3^{(+)}$	40967.2373	229.232904	$1^{(*)}, 2^{(-)}$
1			50	39839.2235	271.298804	$2^{(-)}, 3^{(*)}$	40445.3621	157.093438	$1^{(+)}, 3^{(+)}$	40012.5861	189.516720	$1^{(*)}, 2^{(-)}$
1		0.001	25	40561.9235	348.722449	$2^{(-)}, 3^{(*)}$	41038.9246	136.670185	$1^{(+)}, 3^{(+)}$	40768.4056	206.509572	$1^{(*)}, 2^{(-)}$
1			50	39404.7836	249.449911	$2^{(-)}, 3^{(*)}$	40087.0447	167.453651	$1^{(+)}, 3^{(+)}$	39561.6572	216.629134	$, 1^{(*)}, 2^{(-)}$

Table 2: Experimental results for the Hoeffding based function \hat{p}_{Hoef} .

using a heavy-tailed mutation both algorithms achieve higher average results. This can be due to the fact that a higher number of bits can be flipped than in the case of standard bit mutations flipping every bit with probability 1/n.

7 Conclusions

Stochastic problems play an important role in many real-world applications. Based on real-world problems where profits in uncertain environments should be guaranteed with a good probability, we introduced the knapsack problem with chance constrained profits. We presented fitness functions for different stochastic settings that allow to maximize the profit value P such that the probability of obtaining a profit less than P is upper bounded by α_p . In our experimental study, we examined different types of evolutionary algorithms and compared their performance on stochastic settings for classical knapsack benchmarks.

Acknowledgements

We thank Simon Ratcliffe, Will Reid and Michael Stimson for very useful discussions on the topic of this paper. This work has been supported by the Australian Research Council (ARC) through grant FT200100536, and by the South Australian Government through the Research Consortium "Unlocking Complex Resources through Lean Processing".

References

- [1] A. E. Eiben and James E. Smith. *Introduction to evolutionary computing, Second Edition*. Natural Computing Series. Springer, 2015.
- [2] Raymond Chiong, Thomas Weise, and Zbigniew Michalewicz, editors. Variants of evolutionary algorithms for real-world applications. Springer, 2012.
- [3] Christie Myburgh and Kalyanmoy Deb. Evolutionary algorithms in large-scale open pit mine scheduling. In *GECCO*, pages 1155–1162. ACM, 2010.
- [4] Yuki Osada, R. Lyndon While, Luigi Barone, and Zbigniew Michalewicz. Multi-mine planning using a multiobjective evolutionary algorithm. In *IEEE Congress on Evolutionary Computation*, pages 2902–2909, 2013.
- [5] Pratyusha Rakshit, Amit Konar, and Swagatam Das. Noisy evolutionary optimization algorithms A comprehensive survey. Swarm Evol. Comput., 33:18–45, 2017.
- [6] Denis Marcotte and Josiane Caron. Ultimate open pit stochastic optimization. *Computers & Geosciences*, 51:238–246, 2013.
- [7] Luciano Nunes Capponi and Rodrigo de Lemos Peroni. Mine planning under uncertainty. *Insights in Mining Science and Technology, Vol. 2, no. 1, p. 17-25*, 2020.
- [8] Abraham Charnes and William W Cooper. Chance-constrained programming. *Management science*, 6(1):73–79, 1959.
- [9] Daniel H. Loughlin and S. Ranji Ranjithan. Chance-constrained genetic algorithms. In *Proceedings of the 1st* Annual Conference on Genetic and Evolutionary Computation - Volume 1, GECCO'99, page 369–376, 1999.
- [10] R. K. Jana and M. P. Biswal. Stochastic simulation-based genetic algorithm for chance constraint programming problems with continuous random variables. *International Journal of Computer Mathematics*, 81(9):1069–1076, 2004.
- [11] Bo Liu, Qingfu Zhang, Francisco V. Fernández, and Georges G. E. Gielen. An efficient evolutionary algorithm for chance-constrained bi-objective stochastic optimization. *IEEE Trans. Evol. Comput.*, 17(6):786–796, 2013.
- [12] Yue Xie, Oscar Harper, Hirad Assimi, Aneta Neumann, and Frank Neumann. Evolutionary algorithms for the chance-constrained knapsack problem. In *Proceedings of the Genetic and Evolutionary Computation Conference*, *GECCO 2019*, pages 338–346. ACM, 2019.
- [13] Yue Xie, Aneta Neumann, and Frank Neumann. Specific single- and multi-objective evolutionary algorithms for the chance-constrained knapsack problem. In *Proceedings of the Genetic and Evolutionary Computation Conference, GECCO 2020*, pages 271–279. ACM, 2020.
- [14] Hirad Assimi, Oscar Harper, Yue Xie, Aneta Neumann, and Frank Neumann. Evolutionary bi-objective optimization for the dynamic chance-constrained knapsack problem based on tail bound objectives. In ECAI 2020 - 24th European Conference on Artificial Intelligence, volume 325 of Frontiers in Artificial Intelligence and Applications, pages 307–314. IOS Press, 2020.
- [15] Benjamin Doerr, Carola Doerr, Aneta Neumann, Frank Neumann, and Andrew M. Sutton. Optimization of chance-constrained submodular functions. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence*, AAAI 2020, pages 1460–1467. AAAI Press, 2020.
- [16] Aneta Neumann and Frank Neumann. Optimising monotone chance-constrained submodular functions using evolutionary multi-objective algorithms. In *Parallel Problem Solving from Nature, PPSN 2020, Proceedings, Part I*, volume 12269 of *LNCS*, pages 404–417. Springer, 2020.
- [17] Frank Neumann and Andrew M. Sutton. Runtime analysis of the (1 + 1) evolutionary algorithm for the chanceconstrained knapsack problem. In *Proceedings of the 15th ACM/SIGEVO Conference on Foundations of Genetic Algorithms, FOGA 2019*, pages 147–153. ACM, 2019.
- [18] Yue Xie, Aneta Neumann, Frank Neumann, and Andrew M. Sutton. Runtime analysis of RLS and the (1+1) EA for the chance-constrained knapsack problem with correlated uniform weights. In *Proceedings of the Genetic* and Evolutionary Computation Conference, GECCO 2021, pages 1187–1194. ACM, 2021.
- [19] David P. Morton and R. Kevin Wood. *On a stochastic knapsack problem and generalizations*, pages 149–168. Springer US, Boston, MA, 1998.
- [20] Benjamin Doerr. Probabilistic tools for the analysis of randomized optimization heuristics. In Benjamin Doerr and Frank Neumann, editors, *Theory of Evolutionary Computation – Recent Developments in Discrete Optimization*, pages 1–87. Springer, 2020.

- [21] Benjamin Doerr, Huu Phuoc Le, Régis Makhmara, and Ta Duy Nguyen. Fast genetic algorithms. In *Proceedings* of the Genetic and Evolutionary Computation Conference, GECCO 2017, pages 777–784. ACM, 2017.
- [22] Denis Antipov, Maxim Buzdalov, and Benjamin Doerr. Fast mutation in crossover-based algorithms. In Proceedings of the Genetic and Evolutionary Computation Conference, GECCO 2020, pages 1268–1276. ACM, 2020.
- [23] David Pisinger. Where are the hard knapsack problems? *Computers & Operations Research*, 32(9):2271–2284, 2005.
- [24] H. Kellerer, U. Pferschy, and D. Pisinger. Knapsack problems. Springer, Berlin, Germany, 2004.
- [25] Gregory W. Corder and Dale I. Foreman. *Nonparametric statistics for non-statisticians: A step-by-step approach*. Wiley, 2009.