

Defending Backdoor Attacks on Vision Transformer via Patch Processing

Khoa D. Doan, Yingjie Lao, Peng Yang, Ping Li

Cognitive Computing Lab
Baidu Research
10900 NE 8th St. Bellevue, WA 98004, USA

{khoadoan106, laoyingjie, pengyang5612, pingli98}@gmail.com

Abstract

¹Vision Transformers (ViTs) have a radically different architecture with significantly less inductive bias than Convolutional Neural Networks. Along with the improvement in performance, security and robustness of ViTs are also of great importance to study. In contrast to many recent works that exploit the robustness of ViTs against adversarial examples, this paper investigates a representative causative attack, i.e., backdoor. We first examine the vulnerability of ViTs against various backdoor attacks and find that ViTs are also quite vulnerable to existing attacks. However, we observe that the clean-data accuracy and backdoor attack success rate of ViTs respond distinctively to patch transformations before the positional encoding. Then, based on this finding, we propose an effective method for ViTs to defend both patch-based and blending-based trigger backdoor attacks via patch processing. The performances are evaluated on several benchmark datasets, including CIFAR10, GTSRB, and TinyImageNet, which show the proposed novel defense is very successful in mitigating backdoor attacks for ViTs. To the best of our knowledge, this paper presents the first defensive strategy that utilizes a unique characteristic of ViTs against backdoor attacks.

¹The paper will appear in the Proceedings of the AAAI'23 Conference. This work was initially submitted in November 2021 to CVPR'22, then it was re-submitted to ECCV'22. The paper was made public in June 2022. The authors sincerely thank all the referees from the Program Committees of CVPR'22, ECCV'22, and AAAI'23.

1 Introduction

The versatility of machine learning makes it a promising technology for implementing a wide variety of complex systems such as autonomous driving (Grigorescu et al., 2020; Caesar et al., 2020), intrusion detection (Vinayakumar et al., 2019; Berman et al., 2019; Doan et al., 2021c), communication (Huang et al., 2020), pandemic mitigation (Oh et al., 2020; Alimadadi et al., 2020), retrieval (Doan et al., 2022b, 2020b), and targeted advertising (Doan et al., 2019) systems. These examples also illustrate that a large portion of safety-critical applications are benefited from the evolution of machine learning, which meanwhile requires high degrees of security and trustworthiness of these technologies (Yang et al., 2021; Lao et al., 2022a,b; Zhao et al., 2022). Unfortunately, vulnerabilities have emerged from many aspects of machine learning and a wide body of research has been investigated recently to exploit both these vulnerabilities and defensive measures to mitigate attacks against machine learning, especially for deep learning systems (Szegedy et al., 2014; Liu et al., 2018b; Akhtar and Mian, 2018).

One such vulnerability, backdoor attack, allows an adversary with access to the model’s training phase the possibility of injecting backdoors to maliciously alter the machine learning model behavior (Liu et al., 2018c; Chen et al., 2017). These backdoor injection attacks poison the training data or modify the learning algorithm such that an association between a specific adversarial input “trigger” and an adversarial output “behavior” is formed. A trigger is typically locally superimposed on a clean image with an image pattern (i.e., patch-based) (Gu et al., 2019; Liu et al., 2018c) or globally blended (i.e., blending-based) (Barni et al., 2019; Liu et al., 2020; Nguyen and Tran, 2021; Doan et al., 2021a,b, 2022a) for improving the stealthiness. The compromised model will continue to behave normally as intended under the typical usage scenarios with clean inputs. But by exposing the model to the correct triggers, a user with the prerequisite knowledge can then directly control the model’s prediction.

As machine learning continues to improve upon its current success, developers must understand both the vulnerabilities that machine learning brings and valid methods for overcoming these weaknesses. One recent major advance in computer vision tasks is the vision transformer (ViT) (Dosovitskiy et al., 2021), which adapts the multi-head self-attention mechanism from the natural language processing (NLP) tasks. Specifically, during ViT’s training, images are pre-processed as patches, which are treated similarly to words in NLP. It has been shown that ViT can achieve comparable or even better performance to state-of-the-art convolutional neural network (CNN) architectures on various vision tasks (Dosovitskiy et al., 2021; Liu et al., 2021; Wang et al., 2021; Touvron et al., 2021; Yuan et al., 2021; Gkelios et al., 2021; Khan et al., 2021; Chen et al., 2021; Yu et al., 2022; Yu and Li, 2022).

While switching from convolution to self-attention has shown promising outcomes in tackling these vision tasks from the performance perspective, the implications of such fundamental differences on security and robustness are also of paramount importance to study. Several recent works examined the performance of ViT against adversarial examples (Mao et al., 2022; Benz et al., 2021; Bhojanapalli et al., 2021; Naseer et al., 2021; Mahmood et al., 2021; Shao et al., 2021; Naseer et al., 2022; Joshi et al., 2021). However, the vulnerability of ViT against backdoor attacks and the corresponding countermeasures have not been extensively studied. In fact, to the best of our knowledge, only one very recent work looked at this direction (Lv et al., 2021), which proposed a data-free backdoor embedding attack against the vision transformer networks. In contrast to this prior work, we focus on the defensive side. Aligning with the processing of ViT that divides an image into patches, we mainly study the implications of patch transformations on image classification tasks in this paper. Specifically, we utilize two techniques, namely PatchDrop and PatchShuffle, which randomly drop and shuffle patches of an image, respectively. Under these patch processing,

we find that ViT exhibits a different characteristic from CNN models and also responds distinctively between clean samples and backdoor samples. Specifically, PatchDrop is effective in detecting patch-based backdoor attacks, while PatchShuffle can successfully mitigate blending-based backdoor attacks. Therefore, based on patch processing, we propose a novel defensive solution to combat backdoor attacks.

The contributions of this paper are summarized below:

- We first perform an empirical study on the vulnerability of ViTs against both patch-based and blending-based backdoor attacks and find ViTs are still quite vulnerable to backdoor attacks.
- We observe an interesting characteristic of ViTs that clean-data accuracy and backdoor attack success rate of ViTs respond distinctively to patch processing before the positional encoding, which is not seen on CNN models.
- We propose a novel defensive solution to mitigate backdoor attacks on ViTs via patch processing. We analyze two processing methods, i.e., PatchDrop and PatchShuffle, and examine their effectiveness in reducing the attack success rate (ASR) of backdoor attacks. In particular, PatchDrop and PatchShuffle are effective in detecting patch-based and blending-based backdoor attacks, respectively. Together, they are used to effectively detect the backdoor samples without prior knowledge of whether the attack is patch-based or blending-based.
- We comprehensively evaluate the performance of the proposed techniques on a wide range of benchmark settings, including CIFAR10, GTSRB, and TinyImageNet.

2 Related Work

Previous works on deep neural network (DNN) backdoor injection have understood the attack as the process of introducing malicious modifications to a model, $F(\cdot)$, trained to classify the dataset (X, Y) . These changes force an association with specific input triggers, (Δ, m) , to the desired model output, y_t (Gu et al., 2019; Liu et al., 2018c; Bagdasaryan and Shmatikov, 2021; Yao et al., 2019). Through Equation (1), the trigger can be superimposed on any input such that a poisoned input is formed.

$$P(x, m, \Delta) = x \circ (1 - m) + \Delta \circ m \quad (1)$$

Here we use \circ to denote the element-wise product and m is a mask used to determine the region of the input containing the trigger pattern, Δ . In essence, the adversarial goal is to force the model to minimize the compound loss function: $\mathcal{M}(F_\omega(x), y) + c \cdot D(F(P(x, m, \Delta)), F(x_t))$, instead of the original benign loss function such as cross-entropy loss, where $D(\cdot, \cdot)$ defines the similarity between the model’s actual behavior and a target behavior described by the input x_t while the constant c is used to balance the terms (Yao et al., 2019).

The main methodologies used to inject this functionality into the model are contaminating the training data (Chen et al., 2017; Liu et al., 2018c; Gu et al., 2019; Saha et al., 2020), altering the training algorithm (Bagdasaryan and Shmatikov, 2021) or overwriting/retraining the model parameters after deployment (Dumford and Scheirer, 2020). Besides the original patch-based trigger (Gu et al., 2019), various blending-based trigger patterns have also been proposed, including blended (Chen et al., 2017), sinusoidal strips (SIG) (Barni et al., 2019), reflection (ReFool) (Liu et al., 2020), and warping (WaNet) (Nguyen and Tran, 2021). Note that in order to differentiate from the patch used in describing the processing of ViTs, we limit the usage of patch for backdoor

attacks to only “patch-based”. In other words, **only “patch-based” refers to the backdoor attack, while all the other usages of “patch” are related to the ViTs in this paper.** For the backdoor embedding attack on ViT (Lv et al., 2021), it seeks to catch most attention of the victim model by leveraging the unique attention mechanism.

On the other hand, several categories of defensive solutions have also been proposed to combat backdoor attacks in past years (Chen et al., 2019a; Tran et al., 2018; Gao et al., 2019; Liu et al., 2017; Li et al., 2020; Liu et al., 2018a; Cheng et al., 2020; Wang et al., 2019; Chen et al., 2019b; Qiao et al., 2019). One direction is to remove, detect, or mismatch the trigger of inputs through certain processing or transformations of the input images (Liu et al., 2017; Li et al., 2020; Doan et al., 2020a; Udeshi et al., 2022; Qiu et al., 2021; Gao et al., 2019). Note that most of these defensive methods are model-agnostic and mainly target at processing the inputs. Our proposed defensive method follows a similar concept as these input processing methods. For instance, similar to STRIP (Gao et al., 2019) that examines the entropy in predicted classes after a set of input perturbations to check any violation of the input-dependence property of a benign model, we leverage the distinctive performance between the clean sample and backdoor sample against patch processing to detect malicious behaviors. Another advantage of such methods, including the proposed one, is that they only require access to clean samples, which is a more practical setting for defending backdoor attacks.

3 Backdoor Attacks on ViT

3.1 Threat Model

We follow the typical threat model of DNN backdoor attacks (Gu et al., 2019) that a user wishes to establish a model for a specific image classification task by training with data provided by a third party. We assume the adversary has the capability of injecting poisoned data samples into the training dataset, but cannot modify the model architecture, the training setting, or the inference pipeline. Since the user will check the accuracy of the trained model on a held-out validation dataset (clean samples), the adversarial goal is to embed a backdoor into the model through data contamination without degrading the clean-data accuracy over the image classification task. In other words, the model should produce malicious behavior only on images with the trigger for the backdoor, while performing normally otherwise.

3.2 Attack Experimental Results

To understand the security threat on ViTs against the backdoor attacks, we consider two most popular approaches of creating the backdoor triggers: local patch-based triggers, BadNets (Gu et al., 2019) and SinglePixel (Bagdasaryan and Shmatikov, 2021), and global blending-based trigger, ReFool (Liu et al., 2020) and WaNet (Nguyen and Tran, 2021). We evaluate the performance on CIFAR10, GTSRB, and TinyImageNet datasets.

Specifically, we perform the attack experiment by poisoning the training dataset and the corresponding ground-truth labels. For each training dataset, similar to prior works (Gu et al., 2019; Nguyen and Tran, 2021; Liu et al., 2020), we select a small number of samples (less than 10%) and apply the corresponding trigger on each of the selected images.



(a) GTSRB/BadNets



(b) TinyImageNet/ReFool

Figure 1: Clean and backdoor samples with local patch-based trigger (a square in bottom right corner) and global blending-based trigger (an embedded reflection).

Figure 1 shows some examples of both patch-based and blending-based backdoor samples. The labels of the poisoned samples are also changed to the target label. The poisoned training data are then used to train the image classification model. Then, we perform training using two ViT variants, the original ViT (Dosovitskiy et al., 2021) and DeiT (Touvron et al., 2021), and several other popular CNN model architectures, including Vgg11 (Simonyan and Zisserman, 2014), ResNet18 (He et al., 2016), and Big Transfer (BiT) (Kolesnikov et al., 2020). Note that the models are pre-trained on ImageNet-21k and fine-tuned on the corresponding dataset to ensure a consistent experimentation framework. This setup is influenced by the fact that large-scale ViTs and BiT are not trained from scratch on smaller-scale datasets to prevent overfitting. The detailed training settings, statistics of datasets, and model architectures are summarized in the supplementary materials. Each trained model is then evaluated on the held-out test sets of clean and backdoor samples. The backdoor samples are applied with the triggers that are generated using the same mechanism in the corresponding attack strategy for the evaluation.

Table 1: Patch-based Backdoor Attack (BadNets)

Dataset	ViT		DeiT		Vgg11		ResNet18		BiT	
	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack
CIFAR10	98.93	98.47	98.82	97.82	93.44	96.95	96.77	97.17	98.51	97.09
GTSRB	98.68	96.46	98.55	95.62	98.05	91.21	98.86	94.33	98.71	94.77
TinyImageNet	86.46	98.02	87.76	95.77	61.94	88.57	68.67	96.16	80.99	96.94

Table 2: Blending-based Backdoor Attack (WaNet)

Dataset	ViT		DeiT		Vgg11		ResNet18		BiT	
	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack
CIFAR10	97.88	99.98	97.92	99.99	95.06	99.71	96.31	99.92	97.85	99.99
GTSRB	99.08	99.74	97.55	98.27	98.75	99.48	99.28	99.74	99.23	99.98
TinyImageNet	77.48	99.99	83.90	98.53	64.96	99.21	68.23	99.98	75.90	99.99

In Table 1 and Table 2, we show the clean-data and backdoor-data performance of the trained models for BadNets and WaNet, respectively. We can observe that the trained ViT and DeiT with the backdoors have similar, high clean-data accuracies to that of the corresponding benign models (still outperforming other CNN models). However, when the triggers are present, the probabilities of the poisoned ViT models to predict the target label (i.e., ASR) are also quite high, which are above 96% on all datasets. In other words, ViTs are at least as vulnerable against backdoor attacks as the CNN models. In fact, the patch-based backdoor attack on ViTs seems to be even slightly more successful than on other CNN models, which further validates the need for studying the backdoor attacks and countermeasures on ViTs. We observe similar results for SinglePixel and ReFool attacks.

4 Backdoor Attacks vs. Patch Processing

In the previous section, we have shown that backdoor attacks are still quite successful on ViTs. Besides, as we discussed above, it has also recently been shown that ViTs are vulnerable against other types of attacks, although they exhibit certain degrees of improvement in robustness against the transferability of adversarial examples (Mahmood et al., 2021; Shao et al., 2021). While these features of ViTs are similar to the CNN models, ViTs have also been shown to be more robust toward occlusions, distributional shifts, and permutation (Naseer et al., 2021). In this section, we extend the robustness study of the receptive fields of ViTs with respect to the backdoor attack models and compare their performance to CNN models.

4.1 Patch Processing

Following the existing defensive methods that process images at the input space for detecting backdoor attacks (Liu et al., 2017; Li et al., 2020; Doan et al., 2020a; Udeshi et al., 2022; Qiu et al., 2021; Gao et al., 2019), we study the performance of the backdoor attacks on ViT models through input transformations that align with the characteristic of ViTs, i.e., patch processing where the content of the image is randomly perturbed. Specifically, each input image x is represented as a sequence of patches with L elements: $\{x_i\}_{i=1,\dots,L}$. Note that the patch x_i does not necessarily have the same size as the patch size used in the pre-trained ViT model. Perturbing the image’s patches is equivalent to modifying its content. Here, we focus on the question: *How does perturbation influence*

the receptive field of ViTs on image patches when various backdoor triggers are present?

We denote the patch processing on x with a function R and consider the following strategies for performing the patch processing:

- **PatchDrop.** Similar to Naseer et al. (2021), we randomly drop M patches from the total L patches of an image x . We divide the image into $L = l \times l$ patches that belong to a spatial grid of $l \times l$. The number of dropped patches indicates the information loss on the image content.
- **PatchShuffle.** We randomly shuffle the L patches of an image x . The L patches are created in similar spatial grids as those of PatchDrop. PatchShuffle does not remove the content of the image but can significantly impact the receptive fields of the models.

Note that similar forms of patch transformations on ViT models have been considered in prior works (Naseer et al., 2021; Shao et al., 2021), but not in the context of backdoor attacks.

4.2 Performance of Backdoor Attacks against Patch Processing

Similar to the attack experiments, we evaluate the performance on three datasets. We first empirically study the trends of backdoor ASR and clean-data accuracy with respect to patch processing on the corresponding test set for each dataset. We measure the clean-data performance (i.e., test accuracy) and the backdoor performance (i.e., ASR) for each experiment. The results are reported in Figure 2 and Figure 3 for BadNets and ReFool, respectively.




Figure 2: Performance of clean-data accuracy and backdoor attacks with dropped patches on ViT, Vgg11, ResNet18, and BiT.




Figure 3: Performance of clean-data accuracy and backdoor attacks with dropped patches on ViT, Vgg11, ResNet18, and BiT.

For patch-based attacks with PatchDrop, we observe that the clean-data performances of ViT only drop slightly on CIFAR10 and GTSRB even when almost 50% of the image content is removed. In contrast, the clean-data performances drop much more significantly in all the other three CNN models. On TinyImageNet, the clean-data performance of ViT drops more than in the other datasets. However, when the backdoor triggers are present, the attack success rate on ViT decreases significantly, even with a slight loss in the content of the images. In comparison, backdoor attacks on CNN models are more robust to PatchDrop. Interestingly, if we continue to drop more patches, the ASR on the CNN models suddenly increases in several experiments. A possible explanation is that CNN models and backdoor attacks rely on smaller regions of the image than ViT for prediction and achieving the target classes, respectively, which makes the clean-data accuracy of ViT more robust to patch processing. We also notice another important result: the variance in the predictions of the poisoned models is higher for backdoor samples than for the clean samples. We summarize the observations for patch-based attacks with respect to PatchDrop as follows:

- Clean-data accuracy sensitivity: ViT \ll CNN
- ASR sensitivity: ViT $>$ CNN
- **Gap between accuracy and ASR: ViT $>$ CNN**

However, for blending-based attacks with PatchDrop, we do not observe a consistent difference between the ViTs and CNN models, although ViTs are more robust with respect to clean-data accuracy and ASR. Since the trigger is well-blended into the images across the entire pixel space, as in ReFool and WaNet, PatchDrop tends to be less impactful on the backdoor, similar to the robustness of the models on the foreground objects. However, for blending-based attacks with PatchShuffle, we observe that the clean-data performances of ViT drop significantly. In contrast, the ASRs only drop slightly. Such robustness of the trigger is consistent across various patch sizes (i.e., $|x_i|$) on all datasets. For the CNN models, the gaps between clean-data accuracy and ASR are smaller; in some cases, e.g., Vgg11, the gap can become significantly narrow. In previous studies, ViTs exhibit high robustness against patch transformation for larger patch sizes (Naseer et al., 2021). Under our patch processing technique PatchShuffle, the significant robustness of the trigger across all patch sizes, especially the smaller sizes, is interesting. Such performance can possibly be explained that ViTs learn and generalize the spatial invariance of the triggers extremely well. Similarly, we summarize the observations for blending-based attacks with respect to PatchShuffle as follows:

- Clean-data accuracy sensitivity: ViT > CNN
- ASR sensitivity: ViT << CNN
- **Gap between accuracy and ASR: ViT > CNN**

In summary, ViT has distinguishable performance between clean-data performance and ASR against certain patch processing techniques: the ASR drops significantly on ViT for **patch-based attacks with PatchDrop**, while the clean-data performance drops significantly on ViT for **blending-based trigger attacks with PatchShuffle**. As a result, for both cases, ViT has a larger gap between accuracy and ASR than CNN. It is important to note that these characteristics are not observed on CNN models. Therefore, the observed impact of patch processing against backdoor attacks is unique to ViT.

5 Novel Defensive Solution for ViT

5.1 Methodology

Based on our observations above, we propose an effective backdoor detection algorithm that can successfully detect and then remove the poison samples from a backdoor-injected ViT model with high success rates. The key intuition in our algorithm is that the patch processing strategies affect ViTs’ predictions on the backdoor samples differently from the predictive function of the model on the clean data. Our defense algorithm exploits the frequency that ViTs change their predictions on the same sample under different trials of a patch processing strategy and use a threshold to assess if a sample is clean or poisoned. Our defense mechanism only requires access to a small set of K clean samples (less than 1000 on the studied datasets), which can be easily obtained from the held-out validation dataset, for selecting the threshold. When no such clean samples are available, we show that the defenses are still very effective, which enables much wider applicability of the proposed method. The proposed defense consists of the following steps:

- **Step 1 (Offline):** For the small set of clean samples, randomly apply PatchDrop and PatchTranslate on each image for T trials. For each sample x , we calculate $F_d(x) = \sum_{t=1}^T \mathbf{1}\{F(x) \neq F(R_d^{(t)}(x))\}$ and $F_s(x) = \sum_{t=1}^T \mathbf{1}\{F(x) \neq F(R_s^{(t)}(x))\}$, where $R_d^{(t)}$ and $R_s^{(t)}$ denotes the random application of PatchDrop and PatchShuffle, respectively, at trial t . Intuitively, $F_d(x)$ and $F_s(x)$ record the expected number of times the predicted labels on x change to something else after the patch processing.
- **Step 2 (Offline):** Given the sample $\{F_d(x_i)\}_{i=1,\dots,K}$ or $\{F_s(x_i)\}_{i=1,\dots,K}$ created in Step 1, we set the threshold parameter k_d and k_s for PatchDrop and PatchShuffle, respectively, to the values at the n^{th} percentiles to ensure a small false positive rate, as follows:
 - For PatchDrop, we typically select a large value (e.g., 90th percentile). This is because ASRs significantly decrease under patch processing such as PatchDrop.
 - For PatchShuffle, we typically select a small value (e.g., 10th percentile). This is because ASRs do not drop under patch processing such as PatchShuffle while the clean-data accuracies are more affected.
- **Step 3 (During Inference):** For a sample in the inference stage, we randomly apply PatchDrop and PatchShuffle for T trials and record the number of label changes, $F_d(x)$ and $F_s(x)$, respectively. If $F_d(x)$ is greater than the selected k_d threshold for PatchDrop or $F_s(x)$ is smaller than the selected k_s threshold for PatchShuffle, we flag the sample as a backdoor sample. Otherwise, the x is determined as a clean sample.

Note that, the proposed approach does not assume the knowledge of the type of backdoor attack, which ensures its practicality in various scenarios. Furthermore, when the model is benign, i.e., without the backdoor attack, because of the percentile selection rules, only a very small fraction of samples will be identified as false negatives. Formally, our defense approach follows a similar strategy as that of an anomaly detector. Thus, more sophisticated anomaly detection approaches can be used to improve the detection rate while keeping the false negative rate low; however, this is beyond the scope of this paper. The details of the detection algorithm are presented in Algorithm 1.

Algorithm 1 Patch Processing-based Backdoor Detection

Input: Sample x , Threshold k_d (PatchDrop), Threshold k_s (PatchShuffle)

Output: Clean or Backdoor Decision

```

1: function F( $x$ )
2:    $t \leftarrow 0$ ,  $F_d(x) \leftarrow 0$ ,  $F_s(x) \leftarrow 0$ , Predict  $\hat{y} = F(x)$ 
3:   repeat
4:      $t \leftarrow t + 1$ 
5:      $\hat{y}_t = F(R_t(x))$ 
6:      $F_d(x) \leftarrow F_d(x) + 1$  if  $\hat{y}_t \neq \hat{y}$ 
7:      $\hat{y}_t = F(R_s(x))$ 
8:      $F_s(x) \leftarrow F_s(x) + 1$  if  $\hat{y}_t \neq \hat{y}$ 
9:   until  $t = T$ 
10:  return  $F_d(x)$  and  $F_s(x)$ 
11: end function
12: If  $F_d(x) > k_d$ 
13:   or  $F_s(x) < k_s$ ,  $x$  is Backdoor
14: Otherwise,  $x$  is Clean

```

5.2 Analysis of Patch Processing-based Defense

We first provide a qualitative analysis of the proposed defense strategy for detecting both patch-based and blending-based backdoor samples from the backdoor-injected ViT and CNN models.

5.2.1 Patch-based Attacks




Figure 4: TPR and TNR for different numbers of dropped patches (in a spatial grid of 8×8) for CNN models (ResNet18 and Vgg11) and ViTs (ViT and DeiT). TPR: true positive rate, i.e., detection rate. TNR: true negative rate, i.e., clean-sample mis-detection rate.

Figure 4 illustrates the true positive rate (TPR) and true negative rate (TNR) for the patch-based attack, BadNets, when varying the number of dropped patches d in PatchDrop when the spatial grid is 8×8 . Recall that the TPR and TNR indicate the backdoor detection rate and the percentage of clean samples that are not falsely detected as backdoor samples, respectively. As we can observe, the defensive solution with PatchDrop works better for ViT models than for CNN models such as ResNet18 and Vgg11. Furthermore, dropping 10% of the patches can consistently achieve higher TPR and TNR across different datasets. The effectiveness of this defense on ViTs is because the backdoor performance is more sensitive to PatchDrop, as discussed in the previous section.

5.2.2 Blending-based Attacks




Figure 5: TPR and TNR for different sizes of processed patches for CNN models (ResNet18 and Vgg11) and ViTs (ViT and DeiT) under ReFool backdoor attack.

Figure 5 illustrates the TPR and TNR when defending against ReFool with various sizes of the processed patches in PatchShuffle. As we can observe, PatchShuffle generally achieves higher TPRs in ViTs than in CNN models. More importantly, when the patch size is similar to that of the trained patch size in ViTs, defending against ViTs is consistently effective, with optimal TPRs and high TNRs.

6 Defense Experimental Results

This section presents the empirical results in defending against backdoor attacks. In real-world settings, the defender does not know which attack is performed by the adversary. To this end, we consider two practical scenarios.

In the first scenario, the backdoor is successfully injected into the trained model and the victim defends against backdoor attacks (i.e., alleviates its effectiveness) by filtering the backdoor samples during inference. In this experiment, TPR and TNR are reported, as they demonstrate how likely the defense method identifies the backdoor samples and how likely the clean samples are not falsely flagged as backdoor samples, respectively. We also assume that a small set of clean samples are available. The values at the 90th and 10th of the empirical distributions of $F_d(x)$ and $F_s(x)$, for all clean samples x , are selected as the thresholds k_d and k_s for PatchDrop and PatchShuffle, respectively.

In the second scenario, we consider an extreme case where the defender is also the model trainer who receives a possibly poisoned training dataset. The defender aims to obtain the trained model that is free of the backdoor. Here, clean samples are not available, which makes the defending task very difficult. Defending using the proposed defensive solution consists of the following steps:

- (i) train the model on the training dataset for some epochs,
- (ii) use the possibly poisoned, trained model to detect the backdoor samples, and
- (iii) remove the backdoor samples from the training dataset and re-train the model on the filtered dataset.

We observe that only training the model for 50 epochs in step (i) is sufficient for the backdoor to be inserted into the model if the training dataset is poisoned and the clean-data accuracy reaches an acceptable performance compared to the optimal clean-data performance (less than a few percents difference, e.g., $> 90\%$ in CIFAR10). Ideally, we train the models until they reach the optimal accuracies, but this can add significant computation to the training process while only adding a minor improvement in the defense. Therefore, we use 50 epochs on all experiments. In step (ii), we consider the threshold $k_d = 0$ for PatchDrop, and $k_s = T$ for PatchShuffle.

6.1 Defending against the Poisoned Model

Table 3: TPR and TNR of detecting backdoor samples in the poisoned models under BadNets Attack. Best TPRs are bolded. Best TNRs are underlined.

Dataset	ViT		DeiT		Vgg11		ResNet18		BiT	
	TPR	TNR	TPR	TNR	TPR	TNR	TPR	TNR	TPR	TNR
CIFAR10	90.08	<u>99.48</u>	91.88	96.18	88.12	62.88	88.80	89.33	90.00	87.72
GTSRB	94.89	<u>98.78</u>	93.62	97.66	20.15	80.70	93.80	89.99	93.89	92.91
TinyImageNet	95.80	<u>64.75</u>	95.80	64.73	81.30	20.51	99.00	56.48	98.60	42.64

Table 4: TPR and TNR of detecting backdoor samples in the poisoned models under ReFool Attack. Best TPRs are bolded. Best TNRs are underlined.

Dataset	ViT		DeiT		Vgg11		ResNet18		BiT	
	TPR	TNR	TPR	TNR	TPR	TNR	TPR	TNR	TPR	TNR
CIFAR10	90.00	83.20	66.80	81.50	18.00	82.80	48.90	<u>89.30</u>	79.10	66.90
GTSRB	84.10	95.60	83.60	93.60	80.00	98.50	80.20	<u>96.60</u>	83.30	92.10
TinyImageNet	90.90	87.70	85.30	85.00	69.90	97.10	12.00	96.00	5.10	<u>98.90</u>

Table 3 and Table 4 present the defense results when the defender aims to detect whether a sample is a backdoor or clean sample during inference under the local patch-based attack, BadNets, and the global blending-based attack, ReFool, respectively. As we can observe, the proposed defensive solution achieves comparable TPRs (i.e., successfully detects the backdoor samples) in both ViTs ($>90\%$) and CNN models ($>88\%$) across different datasets under BadNets attacks. However, the TNRs of ViTs, including ViT and DeiT, are significantly better than those of CNN

models, including Vgg11, ResNet18, and BiT. Specifically, the proposed defense method only falsely detects clean samples as backdoor samples less than 3% of the time in the trained ViTs, but more than 10% of the time in the trained CNN models. Under ReFool attacks, the defensive solution achieves the best TPR for ViT, while its TNRs are also very high. While the TNRs of ResNet18 and BiT are higher than those of ViTs, their TPRs are significantly lower, especially in the larger-scale TinyImageNet dataset. Overall, we can conclude that the proposed defense method is consistently more effective in ViTs than in CNN models.

6.2 Defending against the Poisoned Training Data

Table 5: Clean-data accuracy and attack success rate after removing the backdoor samples and retraining the models. The second row (in blue) in each dataset displays the relative change w.r.t the models trained without removing the backdoor samples. Best clean-data accuracy for each dataset is bolded.

Dataset	ViT		DeiT		ResNet18		BiT	
	Clean	Attack	Clean	Attack	Clean	Attack	Clean	Attack
CIFAR10	98.94	10.01	98.74	09.96	92.30	15.77	97.10	10.39
	+0.01%	-89.83%	-0.08%	-89.82%	-4.53%	-88.99%	-1.43%	-89.30%
GTSRB	98.38	0.48	97.98	0.47	96.58	0.46	96.89	0.48
	-0.31%	-99.51%	-0.58%	-99.51%	-2.31%	-99.51%	-1.85%	-99.50%
TinyImageNet	85.57	0.51	88.77	0.50	64.79	0.55	72.34	0.52
	-1.03%	-99.48%	+1.15%	-99.48%	-5.65%	-99.43%	-10.68%	-99.46%

We present the clean-data accuracies and ASRs after re-training the models on the filtered data, as described in the second scenario, in Table 5. The attack method is patch-based. We can observe that the proposed defense method successfully reduces the ASRs much closer to ASRs of random guesses in both ViTs and CNN models on all datasets. However, in ViTs, the clean-data accuracies are preserved, while in CNN models, the clean-data accuracies drop more than 4.5% for ResNet18 and almost 1.5% for BiT. The results for Vgg11 are worse than those of ResNet18 and BiT and are reported in supplement materials. As discussed in the previous experiment, a non-trivial number of clean samples can be falsely detected as backdoor samples in CNN models using the proposed patch-processing approach. Thus, while most backdoor samples are removed from the training datasets, the number of clean training samples is also reduced, which leads to the drop in clean-data performance in CNN models. We can also notice that by employing a large-scale pre-trained model (i.e., BiT), the drop in performance can be mitigated compared to smaller models, such as ResNet18 and Vgg11. Nevertheless, we can still observe that the proposed defense is more effective for ViTs than for CNN models.

In conclusion, while ViT is vulnerable to patch-based backdoor attacks, our proposed simple yet effective patch processing based defensive solution can detect backdoor samples with a high detection rate while maintaining a low false negative rate. Because ViT is robust against patch processing on the clean data, processing the images with these strategies can be utilized to obtain useful yet tangible traces for effectively distinguishing the predictions between the clean and backdoor samples.

7 Conclusion

This paper studied several aspects of backdoor attacks against ViT. We first perform an empirical study on the vulnerability of ViT against both patch-based and blending-based backdoor attacks. Then, based upon our observation that ViT exhibits distinguishable performance between clean samples and backdoor samples against patch processing, we proposed a novel defensive solution to counter backdoor attacks on ViT, which is able to reduce the backdoor attack success rate significantly. Two patch processing methods are investigated. The effectiveness of the proposed techniques is comprehensively evaluated. To the best of our knowledge, this paper presented the first defensive strategy that utilizes a unique characteristic of ViT against backdoor attacks.

References

- Naveed Akhtar and Ajmal Mian. Threat of adversarial attacks on deep learning in computer vision: A survey. *IEEE Access*, 6:14410–14430, 2018.
- Ahmad Alimadadi, Sachin Aryal, Ishan Manandhar, Patricia B Munroe, Bina Joe, and Xi Cheng. Artificial intelligence and machine learning to fight COVID-19. *Physiological Genomics*, 52(4): 200–202, 2020.
- Eugene Bagdasaryan and Vitaly Shmatikov. Blind backdoors in deep learning models. In *Proceedings of the 30th USENIX Security Symposium (USENIX Security)*, pages 1505–1521, 2021.
- Mauro Barni, Kassem Kallas, and Benedetta Tondi. A new backdoor attack in CNNs by training set corruption without label poisoning. In *Proceedings of the 2019 IEEE International Conference on Image Processing (ICIP)*, pages 101–105, Taipei, 2019.
- Philipp Benz, Soomin Ham, Chaoning Zhang, Adil Karjauv, and In So Kweon. Adversarial robustness comparison of vision transformer and MLP-Mixer to CNNs. In *Proceedings of the 32nd British Machine Vision Conference (BMVC)*, page 25, Online, 2021.
- Daniel S Berman, Anna L Buczak, Jeffrey S Chavis, and Cherita L Corbett. A survey of deep learning methods for cyber security. *Information*, 10(4):122, 2019.
- Srinadh Bhojanapalli, Ayan Chakrabarti, Daniel Glasner, Daliang Li, Thomas Unterthiner, and Andreas Veit. Understanding robustness of transformers for image classification. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 10211–10221, Montreal, Canada, 2021.
- Holger Caesar, Varun Bankiti, Alex H. Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *Proceedings of the 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 11618–11628, Seattle, WA, 2020.
- Bryant Chen, Wilka Carvalho, Nathalie Baracaldo, Heiko Ludwig, Benjamin Edwards, Taesung Lee, Ian M. Molloy, and Biplav Srivastava. Detecting backdoor attacks on deep neural networks by activation clustering. In *Proceedings of the Workshop on Artificial Intelligence Safety*, Honolulu, HI, 2019a.
- Huili Chen, Cheng Fu, Jishen Zhao, and Farinaz Koushanfar. Deepinspect: A black-box trojan detection and mitigation framework for deep neural networks. In *Proceedings of the Twenty-Eighth*

- International Joint Conference on Artificial Intelligence (IJCAI)*, pages 4658–4664, Macao, China, 2019b.
- Shuo Chen, Tan Yu, and Ping Li. MVT: multi-view vision transformer for 3D object recognition. In *Proceedings of the 32nd British Machine Vision Conference (BMVC)*, page 349, Online, 2021.
- Xinyun Chen, Chang Liu, Bo Li, Kimberly Lu, and Dawn Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017.
- Hao Cheng, Kaidi Xu, Sijia Liu, Pin-Yu Chen, Pu Zhao, and Xue Lin. Defending against backdoor attack on deep neural networks. *arXiv preprint arXiv:2002.12162*, 2020.
- Bao Gia Doan, Ehsan Abbasnejad, and Damith C. Ranasinghe. Februus: Input purification defense against trojan attacks on deep neural network systems. In *Proceedings of the Annual Computer Security Applications Conference (ACSAC)*, pages 897–912, Virtual Event / Austin, TX, 2020a.
- Khoa Doan, Yingjie Lao, and Ping Li. Backdoor attack with imperceptible input and latent modification. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 18944–18957, virtual, 2021a.
- Khoa Doan, Yingjie Lao, Weijie Zhao, and Ping Li. LIRA: learnable, imperceptible and robust backdoor attacks. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 11946–11956, Montreal, Canada, 2021b.
- Khoa Doan, Yingjie Lao, and Ping Li. Marksman backdoor: Backdoor attacks with arbitrary target class. In *Advances in Neural Information Processing Systems (NeurIPS)*, New Orleans, LA, 2022a.
- Khoa D. Doan, Pranjul Yadav, and Chandan K. Reddy. Adversarial factorization autoencoder for look-alike modeling. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management (CIKM)*, pages 2803–2812, Beijing, China, 2019.
- Khoa D Doan, Amir Kimiyaie, Saurav Manchanda, and Chandan K Reddy. Image hashing by minimizing independent relaxed wasserstein distance. *arXiv preprint:2003.00134*, 2020b.
- Khoa D. Doan, Saurav Manchanda, Suchismit Mahapatra, and Chandan K. Reddy. Interpretable graph similarity computation via differentiable optimal alignment of node embeddings. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, pages 665–674, Virtual Event, Canada, 2021c.
- Khoa D Doan, Peng Yang, and Ping Li. One loss for quantization: Deep hashing with discrete wasserstein distributional matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9447–9457, New Orleans, LA, 2022b.
- Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *Proceedings of the 9th International Conference on Learning Representations (ICLR)*, Virtual Event, Austria, 2021.
- Jacob Dumford and Walter J. Scheirer. Backdooring convolutional neural networks via targeted weight perturbations. In *Proceedings of the 2020 IEEE International Joint Conference on Biometrics (IJCB)*, pages 1–9, Houston, TX, 2020.

- Yansong Gao, Change Xu, Derui Wang, Shiping Chen, Damith Chinthana Ranasinghe, and Surya Nepal. STRIP: a defence against trojan attacks on deep neural networks. In *Proceedings of the 35th Annual Computer Security Applications Conference (ACSAC)*, pages 113–125, San Juan, PR, 2019.
- Socratis Gkelios, Yiannis S. Boutalis, and Savvas A. Chatzichristofis. Investigating the vision transformer model for image retrieval tasks. In *Proceedings of the 17th International Conference on Distributed Computing in Sensor Systems (DCOSS)*, pages 367–373, Pafos, Cyprus, 2021.
- Sorin Grigorescu, Bogdan Trasnea, Tiberiu Cocias, and Gigel Macesanu. A survey of deep learning techniques for autonomous driving. *Journal of Field Robotics*, 37(3):362–386, 2020.
- Tianyu Gu, Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. BadNets: Evaluating backdooring attacks on deep neural networks. *IEEE Access*, 7:47230–47244, 2019.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, Las Vegas, NV, 2016.
- Hongji Huang, Song Guo, Guan Gui, Zhen Yang, Jianhua Zhang, Hikmet Sari, and Fumiyuki Adachi. Deep learning for physical-layer 5G wireless techniques: Opportunities, challenges and solutions. *IEEE Wirel. Commun.*, 27(1):214–222, 2020.
- Ameya Joshi, Gauri Jagatap, and Chinmay Hegde. Adversarial token attacks on vision transformers. *arXiv preprint:2110.04337*, 2021.
- Salman Khan, Muzammal Naseer, Munawar Hayat, Syed Waqas Zamir, Fahad Shahbaz Khan, and Mubarak Shah. Transformers in vision: A survey. *arXiv preprint:2101.01169*, 2021.
- Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. In *Proceedings of the 16th European Conference on Computer Vision (ECCV), Part V*, pages 491–507, Glasgow, UK, 2020.
- Yingjie Lao, Peng Yang, Weijie Zhao, and Ping Li. Identification for deep neural network: Simply adjusting few weights! In *Proceedings of the 38th IEEE International Conference on Data Engineering (ICDE)*, pages 1328–1341, Kuala Lumpur, Malaysia, 2022a.
- Yingjie Lao, Weijie Zhao, Peng Yang, and Ping Li. DeepAuth: A DNN authentication framework by model-unique and fragile signature embedding. In *Proceedings of the Thirty-Sixth AAAI Conference on Artificial Intelligence (AAAI)*, Virtual, 2022b.
- Yiming Li, Tongqing Zhai, Baoyuan Wu, Yong Jiang, Zhifeng Li, and Shutao Xia. Rethinking the trigger of backdoor attack. *arXiv preprint arXiv:2004.04692*, 2020.
- Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. Fine-pruning: Defending against backdooring attacks on deep neural networks. In *Proceedings of the 21st International Symposium on Research in Attacks, Intrusions, and Defenses (RAID)*, pages 273–294, Heraklion, Crete, Greece, 2018a.
- Qiang Liu, Pan Li, Wentao Zhao, Wei Cai, Shui Yu, and Victor C. M. Leung. A survey on security threats and defensive techniques of machine learning: A data driven view. *IEEE Access*, 6: 12103–12117, 2018b.

- Yingqi Liu, Shiqing Ma, Yousra Aafer, Wen-Chuan Lee, Juan Zhai, Weihang Wang, and Xiangyu Zhang. Trojaning attack on neural networks. In *Proceedings of the 25th Annual Network and Distributed System Security Symposium (NDSS)*, San Diego, CA, 2018c.
- Yunfei Liu, Xingjun Ma, James Bailey, and Feng Lu. Reflection backdoor: A natural backdoor attack on deep neural networks. In *Proceedings of the 16th European Conference on Computer Vision (ECCV), Part X*, pages 182–199, Glasgow, UK, 2020.
- Yuntao Liu, Yang Xie, and Ankur Srivastava. Neural trojans. In *Proceedings of the 2017 IEEE International Conference on Computer Design (ICCD)*, pages 45–48, Boston, MA, 2017.
- Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 9992–10002, Montreal, Canada, 2021.
- Peizhuo Lv, Hualong Ma, Jiachen Zhou, Ruigang Liang, Kai Chen, Shengzhi Zhang, and Yunfei Yang. DBIA: Data-free backdoor injection attack against transformer networks. *arXiv preprint arXiv:2111.11870*, 2021.
- Kaleel Mahmood, Rigel Mahmood, and Marten van Dijk. On the robustness of vision transformers to adversarial examples. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 7818–7827, Montreal, Canada, 2021.
- Xiaofeng Mao, Gege Qi, Yuefeng Chen, Xiaodan Li, Ranjie Duan, Shaokai Ye, Yuan He, and Hui Xue. Towards robust vision transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12042–12051, New Orleans, LA, 2022.
- Muzammal Naseer, Kanchana Ranasinghe, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Intriguing properties of vision transformers. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 23296–23308, virtual, 2021.
- Muzammal Naseer, Kanchana Ranasinghe, Salman Khan, Fahad Shahbaz Khan, and Fatih Porikli. On improving adversarial transferability of vision transformers. In *Proceedings of the Tenth International Conference on Learning Representations (ICLR)*, Virtual Event, 2022.
- Tuan Anh Nguyen and Anh Tuan Tran. WaNet - imperceptible warping-based backdoor attack. In *Proceedings of the 9th International Conference on Learning Representations (ICLR)*, Virtual Event, Austria, 2021.
- Yujin Oh, Sangjoon Park, and Jong Chul Ye. Deep learning COVID-19 features on CXR using limited training data sets. *IEEE Trans. Medical Imaging*, 39(8):2688–2700, 2020.
- Ximing Qiao, Yukun Yang, and Hai Li. Defending neural backdoors via generative distribution modeling. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 14004–14013, Vancouver, Canada, 2019.
- Han Qiu, Yi Zeng, Shangwei Guo, Tianwei Zhang, Meikang Qiu, and Bhavani M. Thuraisingham. Deepsweep: An evaluation framework for mitigating DNN backdoor attacks using data augmentation. In *Proceedings of the ACM Asia Conference on Computer and Communications Security (ASIA CCS)*, pages 363–377, Virtual Event, Hong Kong, 2021.

- Aniruddha Saha, Akshayvarun Subramanya, and Hamed Pirsiavash. Hidden trigger backdoor attacks. In *Proceedings of the Thirty-Fourth AAAI Conference on Artificial Intelligence (AAAI)*, pages 11957–11965, New York, NY, 2020.
- Rulin Shao, Zhouxing Shi, Jinfeng Yi, Pin-Yu Chen, and Cho-Jui Hsieh. On the adversarial robustness of visual transformers. *arXiv preprint:2103.15670*, 2021.
- Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.
- Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian J. Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *Proceedings of the 2nd International Conference on Learning Representations (ICLR)*, Banff, Canada, 2014.
- Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, pages 10347–10357, Virtual Event, 2021.
- Brandon Tran, Jerry Li, and Aleksander Madry. Spectral signatures in backdoor attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 8011–8021, Montréal, Canada, 2018.
- Sakshi Udeshi, Shanshan Peng, Gerald Woo, Lionell Loh, Louth Rawshan, and Sudipta Chattopadhyay. Model agnostic defence against backdoor attacks in machine learning. *IEEE Trans. Reliab.*, 71(2):880–895, 2022.
- R Vinayakumar, Mamoun Alazab, KP Soman, Prabakaran Poornachandran, Ameer Al-Nemrat, and Sitalakshmi Venkatraman. Deep learning approach for intelligent intrusion detection system. *IEEE Access*, 7:41525–41550, 2019.
- Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y. Zhao. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *Proceedings of the 2019 IEEE Symposium on Security and Privacy (SP)*, pages 707–723, San Francisco, CA, 2019.
- Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 548–558, Montreal, Canada, 2021.
- Peng Yang, Yingjie Lao, and Ping Li. Robust watermarking for deep neural networks via bi-level optimization. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 14821–14830, Montreal, Canada, 2021.
- Yuanshun Yao, Huiying Li, Haitao Zheng, and Ben Y. Zhao. Latent backdoor attacks on deep neural networks. In *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security (CCS)*, pages 2041–2055, London, UK, 2019.
- Tan Yu and Ping Li. Degenerate Swin to Win: Plain window-based transformer without sophisticated operations. *arXiv preprint arXiv:2211.14255*, 2022.
- Tan Yu, Gangming Zhao, Ping Li, and Yizhou Yu. BOAT: Bilateral local attention vision transformer. In *Proceedings of the 33rd British Machine Vision Conference (BMVC)*, London, UK, 2022.

Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Zihang Jiang, Francis E. H. Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-Token ViT: Training vision transformers from scratch on ImageNet. In *Proceedings of the 2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 538–547, Montreal, Canada, 2021.

Weijie Zhao, Yingjie Lao, and Ping Li. Integrity authentication in tree models. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, pages 2585–2593, Washington, DC, 2022.