

Design of Fuzzy Logic Controller for Washing Machine

Kriti Dheerawat¹

The Maharaja Sayajirao University of Baroda

Abstract. Things are becoming more advanced as technology advances, and machines now perform the majority of the manual work. The most often used home appliance is the washing machine for cloths. In this paper, we used the Mamdani approach and created an algorithm based on multi-input multi-output. The algorithm is implemented in Python. The results of this simulation show that the washing machine provides better execution at a low computation cost.

Keywords: Fuzzy Logic Controller, Artificial Intelligence, Mamdani Approach

1 Introduction

Fuzzy logic is one of the agents of Artificial Intelligence that alter and portray uncertain information by analyzing the degree to which the statement is true. It was introduced by Professor Lofti Zadeh at the University of California, USA, in 1965. A related concept was conceived by American philosopher M. Black in (1937)[16]. He introduced the term “linguistic variables” in the year (1973) which defined a variable as a fuzzy set.[13] Many uses of fuzzy set theory have been developed over the years, including fuzzy logic controller (FLC), fuzzy clustering algorithms, fuzzy mathematical programming, and many others.

1.1 Literature Review

In 1975, Mamdani and Assilian[15] have developed the first fuzzy logic controller. In 2012, Zhen and Feng[4] designed a gas heater based on the behavior Model of a FLC. Also, for a liquid level control application, a FLC was designed using MATLAB which was compared to a PID controller. The comparison analysis showed that overshoots and steady-state errors were greatly decreased by the fuzzy logic controllers [12].

A fuzzy inference approach is used in 2007 to calculate wash time where a triangular Membership function was used to determine the turbidity[1]. Pritesh Lohani suggested an improved washer controller microchip in 2009, with inputs for type of dirt, mass of clothes, and degree of dirtiness, and an output of wash time with 25 rules [5].

2 Prerequisites

We require concepts for fuzzy logic controllers described below:

Fuzzy Relation:

Let X_1, X_2, \dots, X_n be non empty sets then a fuzzy relation R is a fuzzy subset of $X_1 \times X_2 \times \dots \times X_n$.

Fuzzy Intersection:t-norm

A fuzzy intersection/t-norm i is a binary operation in a unit interval that satisfies at least following axioms for all $a, b, c, d \in [0, 1]$

- Axiom-i1: $i(a, 1) = a$
- Axiom-i2: $b \leq d$ implies $i(a, b) \leq i(a, d)$
- Axiom-i3: $i(a, b) = i(b, a)$
- Axiom-i4: $i(a, i(b, d)) = i(i(a, b), d)$

Fuzzy Logic Controller:

A general fuzzy controller consists following steps:

- Step-1: Initially we identify input and output variables of the controller and ranges of their values, after that we have to select meaningful linguistic states for each variable and express them by appropriate fuzzy sets.
- Step-2: Fuzzification :In this step a fuzzification function is defined for each input variable to express the associated measurement uncertainty . The following is the fuzzification function for the input variable 'a':

$$f_a : [-b, b] \rightarrow F(\mathbb{R}),$$

where $F : \mathbb{R} \rightarrow [0, 1]$ and $f_a(x_0)$ is a fuzzy number for any $x_0 \in [-b, b]$.

- Step-3: Fuzzy logic control take decision using IF-THEN fuzzy inference rules. First, we convert given fuzzy inference rules of the form:

If x is A and y is B and z is C Then w is W

into fuzzy condition propostions of the form

$$\text{If } (x, y, z) \text{ is } A \times B \times C \text{ then } w \text{ is } W \quad (1)$$

where A,B,C and W are fuzzy numbers choosen from the set of fuzzy numbers that represents the linguistic states and X, Y and Z are universal sets.

- Step-4: The inference engine evaluates the rules contained in the fuzzy rule base utilising fuzzified measurements, and a fuzzified output is produced as a result. For measurements input variables we first calculate degree of compability $R(x, y, z, w)$ by (2)

$$R(x, y, z, w) = i_1[i_2(A(x), B(y), C(z)), W(w)] \quad (2)$$

where i_1, i_2 are t -norms. The membership value for the combined control action W' is therefore given by

$$W'(w) = \bigcup_j \sup_{(x,y,z) \in X \times Y \times Z} \min\{[f_A(x_0) \times f_B(y_0) \times f_C(z_0)], R_j(x, y, z, w)\} \quad (3)$$

\cup taken for union and $f_A(x_0)$, $f_B(y_0)$, and $f_C(z_0)$ are the fuzzy numbers for input variables x_0, y_0, z_0 respectively, defined as:

$$f_A : X \rightarrow F(\mathbb{R}), \quad f_B : Y \rightarrow F(\mathbb{R}), \quad f_C : Z \rightarrow F(\mathbb{R}),$$

Step-5: In this last step of the design process, the designer of a fuzzy controller must select a suitable defuzzification method for convert fuzzy output into crisp value[10].

3 Proposed Design for Fuzzy Washing Machine

Based on inputs and outputs, fuzzy logic is used to model a system. The reduction of computational costs is the ideal factor of a smart washing machine.

Following are the steps for designing FLC for washing Machine

Step-1: We identify ranges of input and outout variables. Step-2 : The fuzzified inputs are measured by $f_A(x_0)$, $f_B(y_0)$, and $f_C(z_0)$ for each $x_0 \in X, y_0 \in Y$ and $z_0 \in Z$.

Step-3: We select the linguistic inference rules. This rules are interpreted as disjunctive.

Step-4: For each rule, we first calculate degree of compability $R_j(x, y, z, w)$ by (2), where minimum operator is used for t-norm.

$$R_j(x, y, z, w) = \min\{\min\{A_j(x), B_j(y), C_j(z)\}, W_j(z)\} \quad (4)$$

The membership value for the combined control action W' is therefore obtained using eq(3) and given by (5)

$$W'(w) = \bigcup_j \sup_{(x,y,z) \in X \times Y \times Z} \min\{[f_A(x_0) \times f_B(y_0) \times f_C(z_0)], R_j(x, y, z, w)\} \quad (5)$$

Simimilarly for each output we can evaluate fuzzy rule

Step-5:The fuzzified outputs wash time obtained from the fuzzy inference engine are converted to crisp values using the centroid method of defuzzification. The overall area of the membership function distribution used to describe the combined control action W is subdivided into several predefined sub-areas, each of whose area and centre of area can be calculated. The following expression can be used to determine the controller's crisp output.

$$\frac{\sum_{i=1}^K A_i f_i}{\sum_{i=1}^K A_i} \quad (6)$$

where K denotes the number of small areas or regions, A_i and f_i represent the area and center of area, respectively, of i -th small region.

4 Conclusion

In this research work, the Mamdani inference approach have been used to design an algorithm for the fuzzy logic controller of a washing machine in Python programming language. We found that performance of the fuzzy controller is easier due to simplicity of the program structure. The simulation results obtain after applying fuzzy controller shows that computation model makes the system more efficient and less expensive. It is clear that the type of dirt on the fabric, the thickness of the fabric, and the volume of the cloths all affect the amount of water, detergent, and wash time utilised. The investigation shows that the suggested fuzzy controller improves the job efficacy of the washing machine with reducing requirement of water, detergent and wash time. Moreover by adding more additional parameters in the system, one can optimise the performance of the machine as per requirement.

5 Acknowledgement

The authors express their sincere thanks to the reviewers for their valuable suggestions for the improvement of the manuscript.

References

1. Raja, K., Ramathilagam, S.(2021): Washing machine using fuzzy logic controller to provide to provide wash quality. *Soft Computing* 25:9957–9965.
<https://doi.org/10.1007/s00500-020-05477-4>
2. Muhammed Ali , Neslihan AVCU (2022): Fuzzy Controller for Optimization of Operation Time in Washing Machine. *European Journal of Science and Technology*. Volume , Issue 34, 561 - 567, 31.03.2022 <https://doi.org/10.31590/ejosat.1083443>
3. Md. Azharul Islam and Md. Sahadat Hossain(2022): Mathematical comparison of defuzzification of fuzzy logic controller for smart washing machine. *J. Bangladesh Acad. Sci.* 46(1); 1-8: June 2022.DOI:10.3329/jbas.v46i1.56864
4. Zhen A, Feng RG(2012) : The design of neural network Fuzzy controller in washing machine. In: Proc. 2012 international conference on computing, measurement, control and sensor network (CMCSN), Shanxi, China, 136–139
5. Lohani P., and Hasan,S.R.(2009): Design of an Improved Controller Microchip For Washing Machine, 16th Annual Electronics New Zealand Conference (pp. 20- 26). Dunedin : Otago University
6. Kumar D, Haider Y(2013) : Fuzzy logic based control system for washing machines. *Int J Comput Sci Technol* 4(2):198–200
7. Anand MS, Tyagi B(2012) : Design and implementation of fuzzy controller on FGPA. *Int J Intell Syst Appl* 10:35–42
8. Alhanjouri M, Alhaddad A (2013) :Optimize wash time of washing machine using fuzzy logic. Islamic University of Gaza
9. Aggarwal M (2011) : Fuzzy logic controller for washing machine, IIT Kharagpur
10. George J. Kirl and Bo Yuan:(1995) *Fuzzy Sets and Fuzzy Logic* (India: PHI).
11. Raja, K., Ramathilagam, S.(2021): Fuzzy logic control system of washing machine using Python. *Malaya Journal of Matematik*, Vol.S, No. 1, 476-479,2021
<https://www.malayajournal.org/articles/MJMS210109>

12. Dharamniwas, Aziz Ahmad, Varun Redhu and Umesh Gupta (2012): Liquid Level Control by Using Fuzzy Logic Controller. International Journal of Advances in Engineering and Technology. ISSN: 2231-1963
13. Outline of a New Approach to the Analysis of Complex Systems and Decision Processes". IEEE Transactions on Systems, Man, and Cybernetics. IEEE Systems, Man, and Cybernetics Society. SMC-3 (1): 28-44. [doi:10.1109/TSMC.1973.5408575](https://doi.org/10.1109/TSMC.1973.5408575). ISSN1083-4419.
14. Dilip K. Pratihar: Soft Computing : Fundamentals and Applications ALPHA SCIENCE INTERNATIONAL LTD.Oxford, U.K.
15. E.H. Mamdani, S. Assilian(1975): An experiment in linguistic synthesis with a fuzzy logic controller. International Journal of Man-Machine Studies, vol. 7, pp. 1-13, 1975
16. M. Black, : Vagueness:(1937) An exercise in logical analysis. Philosophy of Science, vol. 4, no. 4, pp. 427-455.
17. <https://propercloth.com/reference/fabric-thickness-weight/>