Over-the-Air Consensus for Distributed Vehicle Platooning Control

Jihoon Lee*, Yonghoon Jang*, Hansol Kim[‡], Seong-Lyun Kim*, Seung-Woo Ko[§]

*School of EEE, Yonsei University, Seoul, Korea, email: {jhlee, slkim}@ramo.yonsei.ac.kr, matice1116@yonsei.ac.kr

[‡]Dept. of Cont. and Inst. Eng., Korea Maritime and Ocean University, Busan, Korea, email: hansol@kmou.ac.kr [§]Dept. of Smart Mobility Eng., Inha University, Incheon, Korea, email: swko@inha.ac.kr

Abstract-A distributed control of vehicle platooning is referred to as distributed consensus (DC) since many autonomous vehicles (AVs) reach a consensus to move as one body with the same velocity and inter-distance. For DC control to be stable, other AVs' real-time position information should be inputted to each AV's controller via vehicle-to-vehicle (V2V) communications. On the other hand, too many V2V links should be simultaneously established and frequently retrained, causing frequent packet loss and longer communication latency. We propose a novel DC algorithm called over-the-air consensus (AirCons), a joint communication-and-control design with two key features to overcome the above limitations. First, exploiting a wireless signal's superposition and broadcasting properties renders all AVs' signals to converge to a specific value proportional to participating AVs' average position without individual V2V channel information. Second, the estimated average position is used to control each AV's dynamics instead of each AV's individual position. Through analytic and numerical studies, the effectiveness of the proposed AirCons designed on the state-of-the-art New Radio architecture is verified by showing a 14.22% control gain compared to the benchmark without the average position.

I. INTRODUCTION

Vehicle platooning (VP) is one cooperative driving technique, where many autonomous vehicles (AVs) move as one body with the same velocity while maintaining their interdistances [1]. VP has various potentials, such as fuel savings and traffic control (see, e.g., [2]). There have been extensive studies in academia and industry to make VP fully automated without a central controller. Such a distributed platoon control is an analogy to reaching a consensus among multiple agents, referred to as a *distributed consensus* (DC) [3].

For DC to be effectively designed, one essential requirement is not to make the disturbances of one AV's position propagate along with the platoon, referred to as string stability [4]. To this end, it is required to obtain many AVs' kinetic information, including non-line-of-sight (NLoS) AVs. It can be viable via the recent rise of vehicle-to-vehicle (V2V) communications by transmitting a modulated signal embedding each AV's own kinetic information to AVs located in NLoS [5]. On the other hand, practical factors of V2V channels cause unpredictable latency and packet loss. The main research thrust is thus to reach string stability under those considerations. The effect of communication latency is analyzed in [6] that each AV's asynchronous control due to different latency makes VP string unstable. To maintain string stability, synchronizing their control timings is proposed under the assumption that the latency of each V2V link is equivalent. In [7], the stochastic distribution of the resultant latency is derived based on modeling a packet as a Bernoulli trial, which is used to determine several control parameters to achieve string stability in the presence of packet loss.

The above prior works do not consider the issue of training *channel state information* (CSI), which is essential yet challenging in practical scenarios due to the following reasons. First, an AV's high velocity renders the relevant V2V CSIs' coherence times shorter, requiring frequent channel retraining before out-of-date. Second, each AV needs to share its information with multiple AVs nearby. In other words, a large number of V2V links should be established simultaneously using different pilots. A few pilots can be non-orthogonal, causing severe pilot contamination that brings about more frequent packet losses and longer communication latency [8].

To address the above challenges, we design a consensus algorithm for DC control called over-the-air consensus (AirCons), which achieves a consensus among multiple APs in the air without individual V2V CSI training. It is the integrated architecture of communication and control with two key features. First, each AV iteratively exchanges the signal embedding its position information, converging to a specific value proportional to the transmitting AVs' average position. Second, each AV utilizes the estimated average position to adjust its dynamics, which helps achieve string stability. AirCons is different from the over-the-air computation that requires individual CSIs to make all signals coherently combined (see, e.g., [9]). AirCons does not rely on AVs' individual position information. Instead, a superimposed signal is normalized by the sum of CSIs obtained via common pilot transmissions, thereby reducing the burden of training individual V2V CSIs. Besides, this operation enables the convergence to the targeted value closely, which is proved using random matrix theory. We design AirCons based on New Radio (NR) architecture, verified via extensive simulation that AirCons can satisfy string stability with a significant gain on platooning error compared to the benchmark without the average information.

II. SYSTEM MODEL

This section introduces our system model, including network and signal models, and a distributed platoon control.

A. Network Model

We consider the scenario with (N + 1) AVs located on a uni-directional and single-lane highway, as illustrated in Fig. 1. These AVs aim to form a platoon to move from left to right like one body. The rightmost AV, say AV 0, is a leader determining



Fig. 1. A graphical illustration of platooning control with (N + 1) AVs on a straight highway.

the platoon's speed, denoted by v_0 . The remaining AVs are followers, say AV $n \in \{1, ...N\}$, attempting to keep their velocities and inter-distances between adjacent AVs at v_0 and a predetermined target distance d, respectively. To this end, each AV should share its location with the neighboring AVs, helping control their dynamics to stabilize the platoon. The detailed information sharing and platooning control mechanisms are introduced in the sequel.

B. Signal Model

We consider that every AV is equipped with a full-duplex antenna, enabling simultaneous V2V transmission and reception among multiple AVs [10]. Orthogonal Frequency-Division Multiplexing (OFDM) is used as a transmit waveform, where a wide-band channel is divided into multiple narrow-band orthogonal sub-carriers. The number of sub-carriers is given as F. For sub-channel $f \in \{1, \dots, F\}$ at time t, the channel coefficient from AVs m to ℓ is denoted by $h_{\ell,m}^{(f)}(t)$, which is expressed as a product between path-loss and short term fading. Following the common assumption of Rayleigh fading, the channel $h_{\ell,m}^{(f)}(t)$ is modeled as a complex Gaussian random variable $\mathcal{CN}(0, d_{\ell,m}^{-\frac{\eta}{2}})$, where $d_{\ell,m}$ and η are the inter-distance between AVs ℓ and m, and path-loss exponent, respectively.

We denote $x_m^{(f)}(t)$ AV *m*'s baseband signal for sub-channel f at time t, embedding its position information under its power constraint explained in the sequel. Assuming that AVs in $\mathbb{N}^{(f)}$ is granted to transmit their signals using sub-channel f, AV ℓ 's received signal for sub-channel f at time t, denoted by $y_{\ell}^{(f)}(t)$, is given as

$$y_{\ell}^{(f)}(t) = \sum_{m \in \mathbb{N}^{(f)} \setminus \{\ell\}} h_{\ell,m}^{(f)}(t) x_m(t) + z_{\ell}^{(f)}[t], \qquad (1)$$

where $z_{\ell}^{(f)}[t]$ represents an i.i.d. *additive white Gaussian noise* (AWGN) following $\mathcal{CN}(0, \sigma_n^2)$. Note that AV ℓ 's transmit signal is not included in (1), assumed to be perfectly canceled out using a self-interference cancellation technique.

C. Distributed Platooning Control

We explain a distributed platooning control mechanism based on the assumptions below.

Assumption 1 (Given State Information). All AVs know the following two state information.

• Own state information: Each AV knows its own state information, say velocity v_n and absolute location \mathbf{p}_n for AV n, which are obtainable using various positioning techniques, e.g., global positioning system and cellular positioning system [11].

• Leader's state information: A dedicated channel is granted to AV 0. Then, its velocity v_0 and \mathbf{p}_0 are periodically broadcast to the other AVs.

By Assumption 1, each AV can calculate the relative state information concerning the leader AV, given as

$$\alpha_n = \|\mathbf{p}_n - \mathbf{p}_0\|, \quad \beta_n = v_n - v_0, \tag{2}$$

where $||\mathbf{x}||$ represents the Euclidean distance of \mathbf{x} . Given $\{\alpha_n, \beta_n\}$, the aforementioned criteria for stabilizing the platoon are rewritten in terms of α_n and β_n as follows:

$$\alpha_n \to nd, \quad \beta_n \to 0.$$
 (3)

Here, the desired inter-vehicle spacing d is specified in Sec. II-A. To this end, we follow a second-order distributed platooning control, which is widely used in literature (see e.g., [12] and [13]). Specifically, we define a vector $\mathbf{c}_n = [c_{n,1}, c_{n,2}, \cdots, c_{n,N},]^T$, whose element $c_{n,m} = 1$ if AV m's state information obtained via V2V communication is involved to determine AV n's control and $c_{n,m} = 0$ otherwise. Then, AV n can control its accelerator, denoted by μ_n , according to the following equation:

$$\mu_n = \frac{1}{\|\mathbf{c}_n\|} \sum_{m=1}^N \kappa c_{n,m} (\alpha_n - \alpha_m - (n-m)d) - \delta\beta_n + \xi_n,$$
(4)

where κ and δ represent stiffness and damping coefficients, respectively, and ξ_n represents the control term using information obtained via the third-party sensors (e.g., a predecessor AV's position and velocity obtained via RADAR). Note that \mathbf{c}_n , κ , and δ are parameters predetermined by the concerned control policy and assumed to be given advance.

We focus on the terms relevant to other AVs' relative distances, say $\{\alpha_m\}$, which should be delivered through wireless links. To this end, (4) is rewritten as

$$\mu_n = \kappa(\alpha_n - nd) - \delta\beta_n + \frac{\kappa d}{|\mathbb{S}_n|} \sum_{m \in \mathbb{S}_n} m + \xi_n - \frac{\kappa}{|\mathbb{S}_n|} \sum_{m \in \mathbb{S}_n} \alpha_m$$
(5)

where $\mathbb{S}_n = \{m | c_{n,m} = 1\}$ and $|\cdot|$ is a cardinality operator. Two key observations are made as follows. First, every term except the last one can be computed using the state information mentioned in Assumption 1. Second, the last term is determined by the average of relative distances involved in AV *n*'s control, denoted by γ_n as

$$\gamma_n = \frac{1}{|\mathbb{S}_n|} \sum_{m \in \mathbb{S}_n} \alpha_m.$$
(6)

In other words, the information required to control AV *n*'s accelerator is the sum of AVs' relative distance γ_n , not individual $\{\alpha_m\}_{m\in\mathbb{S}_n}$.

III. OVER-THE-AIR CONSENSUS: PRINCIPLE AND DESIGN

This section introduces AirCons, a novel algorithm acquiring the average of AVs' relative distances in the air by exploiting a wireless channel's broadcasting and superposition properties. First, we explain the principle and design of AirCons based on its two key features contrasting from conventional V2V communications.

A. Overview and Key Features

AirCons is designed for each AV to acquire the average of neighbor and its own AVs' relative distances by capturing a superimposed signal transmitted from the neighbors. To explain, AVs keep exchanging their received signals until all of them converge to ζ_n , which is referred to as *consensus*. In results, *consensus* ζ_n is one-to-one mapped to average of neighbor γ_n . After reaching a consensus, each AV's accelerator is updated according to (5). The detailed process to reach a consensus will be explained in Sec. III-B.

We explain how AirCons works from the perspective of an entire platooning network. For stabilizing the platoon, each AV is required to participate in multiple processes to reach different consensuses simultaneously, including not only its one (e.g., γ_n for AV n) but also others ($\{\gamma_m\}$ when $n \in \mathbb{S}_m$). The total number of V2V links relevant to AirCons is thus $\sum_{n=1}^{N} |\mathbb{S}_n|$. It is a heavy burden to establish all individual V2V links by training their CSIs using different pilots. On the other hand, we highlight the following two features of AirCons, deviated from the conventional V2V architecture.

1) Independent Consensus Process: The basic unit to which the sub-carrier is allocated should be a consensus process, not an individual V2V link. In other words, sub-carriers allocated to one consensus process are shared by all involved AVs, while the other AVs are not allowed to use them. As a result, each consensus process can work independently without interfering with the others.

2) Superimposed Channel Estimation: Each AV needs to know superimposed channel coefficients. Consider a consensus group \mathbb{S}_n using sub-carrier f. For a consensus group \mathbb{S}_n , we denote transmitter set $\mathbb{T}_n = \mathbb{S}_n \cup \{n\}$. For AV ℓ , the received superimposed signal is $\sum_{m \in \mathbb{T}_n / \{\ell\}} h_{\ell,m}^{(f)}(t)$. To estimate it, a single pilot waveform is commonly used for AVs in \mathbb{T}_n , denoted by w_n . Assume high signal-to-noise ratio (SNR). When AVs in \mathbb{T}_n transmits w_n simultaneously, AV ℓ can figure out the superimposed channel coefficients from the received signal $\left\{\sum_{m \in \mathbb{T}_n / \{\ell\}} h_{\ell,m}^{(f)}(t)\right\} w_n$, according to (1). The estimated one plays a normalization factor for the consensus, which will be explained in the following subsection.

B. Algorithm Description

In this section, we elaborate on AirCons' algorithm stepby-step on how AVs in \mathbb{S}_n achieve a consensus as the average of their relative distances.

1) Resource Block Configuration and Assumption: A consensus is achieved through K rounds of updating AVs' transmit signals. For one round update explained in the sequel, $2^{|S_n|-1}$ contiguous sub-carriers and two adjacent OFDM symbols are needed, defined as a *resource block* (RB), as illustrated in Fig. 2. The set of the concerned sub-carriers are denoted by $\mathbb{F}_n = \{1, \dots, 2^{|S_n|-1}\}$. The assigned first and second OFDM symbols are used for pilot and data transmissions, respectively.

Next, we assume that all channel coefficients in a RB are equivalent, namely,

$$h_{\ell,m}^{(f_1)}(t_1) = h_{\ell,m}^{(f_2)}(t_2), \tag{7}$$



Fig. 2. A graphical illustration of resource block configuration in AirCons process with multiple rounds.

for $f_1, f_2 \in \mathbb{F}_m$ and $t_1, t_2 \in [(k-1)T, (k-1)T+2\delta]$. Here, δ and T are the durations of symbol and round respectively, and k is the index of round. The assumption will be well justified in the following remark.

Remark 1 (Coherence Time and Bandwidth). It is recommended for NR V2V communications to use a short symbol duration, e.g., $\delta = 16.7$ (μ sec) when using the center frequency of $f_c = 5.9$ (GHz) according to flexible numerology [14]. Denoting a size of consensus group $S = |\mathbb{S}_n| + 1$, the resulting time and frequency ranges of one RB for a consensus process are $2\delta = 33.4$ (μ sec) and $\frac{2^{S-2}}{\delta} = 60 \cdot 2^{S-2}$ (kHz), which will be compared with the following analysis of coherence time and bandwidth to justify (7).

- Coherence Time: Given the relative velocity v = 200 (km/h), the resulting coherence time T_c is $T_c = \frac{c}{f_c v} = 915$ (µsec) with the light speed c, which is larger than one RB's time coverage 2δ .
- Coherence bandwidth: NR specifies V2V channel's delay spread ranging from 5 to 56 (nsec) [15]. The corresponding coherence bandwidth B_c , inversely proportional to the delay spread, is at least 17.8 (MHz). In other words, the flat fading assumption of (7) makes sense when AVs for one consensus is less than 10, i.e., $S \leq 10$.

Hereafter, we focus on a typical consensus group, and all channel coefficients relevant to the typical consensus group at the k-th round is unified as $h_{\ell,m}[k]$, where the index of subcarrier f is omitted for ease of notation. Last, we utilize only an in-phase term for AirCons, defined as

$$a_{\ell,m}[k] = \mathsf{Re}\{h_{\ell,m}[k]\},$$
 (8)

whereas a quadrature term is reserved for future extension.

2) Pilot Encoding & Transmission: Consider the OFDM symbol assigned for pilot transmissions, which will be used to find the sum of in-phase channels' magnitudes, given as

$$\sum_{n \in \mathbb{T}_n / \{\ell\}} |a_{\ell,m}[k]| = \sum_{m \in \mathbb{T}_n / \{\ell\}} \mathsf{b}\left(a_{\ell,m}[k]\right) \cdot a_{\ell,m}[k], \quad (9)$$



Fig. 3. A graphical example of AirCons in step showing how optimal I_m^* is chosen and used for AirCons.

where b(x) = 1 if $x \ge 0$ and b(x) = -1 otherwise. Under the condition without knowledge of individual channel coefficients, AV ℓ attempts to check all possible binary combinations of $\{b(a_{\ell,m}[k])\}_{m \in \mathbb{T}_n/\{\ell\}}$ and find the maximum one, namely,

$$\{\mathsf{b}(a_{\ell,m}[k])\}_{m\in\mathbb{T}_n/\{\ell\}} = \{I_m^*[k]\}_{m\in\mathbb{T}_n/\{\ell\}}$$
(P1)
=
$$\underset{\{I_m\}\in\{-1,1\}^{|\mathbb{S}_n|}}{\operatorname{argmax}} \sum_{m\in\mathbb{T}_n/\{\ell\}} I_m \cdot a_{\ell,m}[k].$$

Problem P1 is implementable by encoding the aforementioned pilot waveform w_n differently for each combination. As an example of one sequence I_m , AV m in \mathbb{T}_n encodes w_n by multiplying the corresponding indicator I_m . AV ℓ 's received signal is given as $\left(\sum_{m \in \mathbb{T}_n/\{\ell\}} h_{\ell,m}[k]I_m\right) \sqrt{P}w_n + e_{\ell}[k]$, where P is the transmit power budget and $e_{\ell}[k]$ represents the AWGN when receiving a pilot waveform. Without loss of generality, the waveform's energy $|w_n|$ is fixed to one. By multiplying the conjugate of w_n , say \overline{w}_n where \overline{x} denotes the conjugate of x, it is coherently demodulated as

where $\tilde{e}_{\ell}[k] = e_{\ell}[k]\bar{w}_n$. When the signal strength is strong enough to ignore the noise term, the real part of (10) becomes proportional to the corresponding argument in P1.

Each binary combination is one-to-one mapped into a different sub-carrier in RB. Given $|\mathbb{S}_n|$ AVs, there exist $2^{|\mathbb{S}_n|}$ binary combinations, which can be reduced in half when considering reversal counterparts. As a result, the number of sub-carriers required for implementing P1 is $\frac{2^{|\mathbb{S}_n|}}{2} = 2^{|\mathbb{S}_n|-1}$, equivalent to the number of sub-carriers in one RB. We can find the optimal binary combination of P1 by choosing the largest received signal strength. The resulting demodulated signal of the *k*-th round are denoted by $r_{\ell}^*[k]$ as

$$r_{\ell}^{*}[k] = \sqrt{P} \left(\sum_{m \in \mathbb{T}_{n}/\{\ell\}} I_{m}^{*}[k] \cdot h_{\ell,m}[k] \right) + \tilde{e}_{\ell}[k].$$
(11)

3) Data Encoding: Each AV encodes its signal embedding its relative distance. Consider AV m in \mathbb{T}_n , whose relative distance is α_m . We assume that α_m stays constant during one consensus process, while it may be changed over different processes. We adopt an *amplitude modulation* (AM) to encode α_m into an initial base-band signal s_m , namely,

$$s_m = \frac{\sqrt{\sigma P} \alpha_m}{L},\tag{12}$$

where σ is a power scaling factor set as 1 unless specified. Given (N + 1) AVs and d desired inter-distance, the normalization factor L is set as the desired maximum platoon length $L = Nd + \Delta$, where Δ is the control error margin.

4) Data Transmission & Reception: In the OFDM symbol duration assigned for the (k+1)-th round's data transmission, each AV in \mathbb{T}_n transmits its signal by mixing the previous transmitted one with the term relevant to the received signals in the k-th round. Specifically, AV m transmits its signal $I_m^*[k] \cdot x_m[k]$, where $x_m[k]$ is defined in a recursive form as

$$x_m[k+1] = \begin{cases} s_m, & \text{if } k = 0, \\ (1-\rho)x_m[k] + \rho \left(\frac{\mathsf{Re}\{y_m^*[k]\}}{\mathsf{Re}\{r_m^*[k]\}}\right), & \text{if } k > 0. \end{cases}$$
(13)

Here, $0 < \rho < 1$ is a weighted factor of the new observations that is the ratio of in-phases between the received data signal and demodulated pilot signals specified in (10), given as

$$y_m^*[k] = \sum_{\ell \in \mathbb{T}_n / \{m\}} h_{m,\ell}[k] I_\ell^*[k] x_\ell[k] + z_m[k],$$
$$r_m^*[k] = \sum_{\ell \in \mathbb{T}_n / \{m\}} h_{m,\ell}[k] I_\ell^*[k] \sqrt{P} + \tilde{e}_m[k].$$

The schematic diagram including each step of AirCons is graphically illustrated in Fig. 3. In the following theorem, we will explain the asymptotic result of (13), which is the main principle of AirCons.

Theorem 1 (Consensus). Consider a high signal-to-noise ratio (SNR) regime. Given $0 < \rho < 1$, all AVs' transmitting signals, say $x_m[k]$ of (13) for $m \in \mathbb{T}_n$, always reach the consensus to a value proportional to weighted average of the relative distances α_m as k increases, namely,

$$\lim_{k \to \infty} x_m[k] = \frac{\sqrt{\rho P}}{L} \sum_{m \in \mathbb{T}_n} w_m \alpha_m, \quad \forall m \in \mathbb{T}_n, \qquad (14)$$

where $\omega = [\omega_1, \cdots, \omega_S]$ is an S-by-1 column vector satisfying $\mathbf{1}^T \omega = 1$ and $\omega \ge 0$.

Proof: See Appendix A.
$$\Box$$

5) Data Decoding: AV n's transmitting signal after the consensus, say $x_n[K]$ specified in Theorem 1, which can be converted into the approximated relative distance sum by dividing $\frac{L}{\sqrt{aP}}$, namely,

$$\tilde{\zeta}_n = \frac{\sqrt{\sigma P}}{L} \left(\lim_{k \to \infty} x_n[k] \right) = \sum_{m \in \mathbb{T}_n} \omega_m \alpha_m.$$
(15)

Since ζ_n includes its own relative position α_n , we calculate average of neighbors γ_n by excluding α_n . That is, $\gamma_n = \frac{\zeta_n(|S_n|+1)-\alpha_n}{|S_n|}$, and the result is inputted into the controller specified in (5), enabling AV *n* to adjust its accelerator μ_n on



Fig. 4. The trajectory of consensus processes with $\rho = 0.2$ (left) and $\rho = 0.9$ (right). Dotted line represents ground truth average. The other parameters are specified in Sec. IV.

time. The deviation from the ground truth ζ_n will be analyzed in the following subsection.

Remark 2 (Effect of ρ). The weighted factor ρ controls the trade-off between convergence speed and the accuracy of the consensus, as shown in Fig. 4. A small ρ updates the signal in a conservative manner by giving more portion to the current value. Eventually, the final consensus result is more close to the ground-truth linear average with slower convergence speed. As ρ increases, on the other hand, the new observation is more involved in the signal, leading to a faster convergence with a certain error compared with the ground truth. Through extensive numerical studies, we set $\rho = 0.9$, to guarantee a fast convergence with an acceptance accuracy.

C. Deviation Analysis

Denote ϵ_n the deviation between the consensus value and the ground truth, namely,

$$\epsilon_n = \tilde{\zeta}_n - \zeta_n, \tag{16}$$

which depends on the realizations of relevant channels, say $\{|a_{m,\ell}[k]|\}$ for all k. Following a similar approach in [16] leads to expressing ϵ_n in closed form as

$$\epsilon_n = \frac{\rho}{S(S-1)} \lim_{z \to 1} \left[\sum_{n,m \in \mathbb{T}_n} \left(\sum_{k=0}^{\infty} v_{n,m}[k] z^{-k} \right) \right],$$

where $v_{n,m}[k] = \frac{\sum_{i \in \mathbb{T}_n / \{n\}} (|a_{n,m}[k]| - |a_{n,i}[k]|)}{\sum_{i \in \mathbb{T}_n / \{n\}} |a_{n,i}[k]|} x_m[k]$ if $n \neq m$ and 0 otherwise. Its expectation over a random sequence of $\{v_{n,m}[k]\}$, say $\mathsf{E}[\epsilon_n]$, is given as

$$\mathsf{E}[\epsilon_n] = \frac{\rho}{S(S-1)} \mathsf{E}\left[\lim_{z \to 1} \sum_{n,m \in \mathbb{T}_n} \left(\sum_{k=0}^{\infty} v_{n,m}[k]\right) z^{-k}\right)\right]$$
$$= \frac{\rho}{S(S-1)} \lim_{z \to 1} \sum_{n,m \in \mathbb{T}_n} \left(\sum_{k=0}^{\infty} \mathsf{E}[v_{n,m}[k])] z^{-k}\right).$$

Here, the term $E[v_{n,m}[k]]$ is lower bounded as

$$E[v_{n,m}(k)] = \sum_{i \in \mathbb{T}_n / \{n\}} E\left[\frac{|a_{n,m}[k]|}{|a_{n,i}[k]|} - 1\right] x_m[k]$$

$$\stackrel{(a)}{\geq} \sum_{i \in \mathbb{T}_n / \{n\}} \left(\frac{E[a_{n,m}[k]]}{E[a_{n,i}[k]]} - 1\right) x_m[k], \quad (17)$$

where (a) follows from Jensen's inequality. The equality condition of (17) is that all channels are time-invariant and

fixed as their expectations defined as $\eta_{\ell,m} = \mathsf{E}[|a_{\ell,m}[k]|]$, and $\tilde{\zeta}_n$ is reduced to $v\alpha$, where $\alpha = [\alpha_1, \cdots, \alpha_S]^T$ and v is a left eigenvalue of the following matrix $U \in \mathbb{R}^{S \times S}$:

$$\boldsymbol{U} = \begin{pmatrix} 1-\rho & \frac{\eta_{1,2}}{\sum_{m \in \mathbb{S}_{n,1}} \eta_{1,m}} & \cdots & \frac{\eta_{1,S}}{\sum_{m \in \mathbb{S}_{n,1}} \eta_{1,m}} \\ \frac{\eta_{2,1}}{\sum_{m \in \mathbb{S}_{n,2}} \eta_{2,m}} & 1-\rho & \cdots & \frac{\eta_{2,S}}{\sum_{m \in \mathbb{S}_{n,2}} \eta_{2,m}} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\eta_{S,1}}{\sum_{m \in \mathbb{S}_{n,S}} \eta_{S,m}} & \frac{\eta_{S,2}}{\sum_{m \in \mathbb{S}_{n,S}} \eta_{S,m}} & \cdots & 1-\rho \end{pmatrix}$$

In other words, $\mathsf{E}[\epsilon_n]$ is lower bounded as

$$\mathsf{E}\left[\epsilon_{n}\right] \geq \boldsymbol{v}\boldsymbol{\alpha} - \zeta_{n}.\tag{18}$$

In the following proposition, we confirm that the above lower bound can be simplified when the inter-distance requirement in (3) is satisfied.

Proposition 1 (Consensus Deviation). Assume that the interdistance between adjacent AVs is equivalent, e.g., $d_{m-1,m} = d_{m,m+1}$ for all $m \in \mathbb{T}_n$. Then, the expectation of the consensus deviation ϵ_n becomes non-negative, e.g., $\mathbb{E}[\epsilon_n] \ge 0$.

]

Through extensive simulations, the tightness of result in Proposition 1 is verified enough to ignore the gap between the two. Besides, the result works well even when there exists a certain level of control error on inter-distance. As a result, AirCons is verified to reach the consensus to the accurate average of relative distances under the condition of equivalent inter-distance with an acceptance relaxation.

IV. NUMERICAL RESULTS

This section provides simulation results to verify the effectiveness of AirCons in terms of stability and control performance. As a benchmark, we consider a leader-predecessor following control mechanism where a leader and predecessor AVs' positions are used to control each AV's accelerator. Simulation parameters are set as follows unless specified otherwise. The number of AVs in a platoon N is 10. Each AV's maximum transmission power P is 23 (dBm). The total bandwidth B is 20 (MHz). A noise spectral density is -174 (dBm/Hz). The path-loss exponent α is set as 4. The target inter-vehicle distance is d = 5 (m).

To check string stability, we model a leader vehicle's turbulence as follows. At the initial stage, the leader vehicle increases its speed with a constant acceleration of 1 (m/s²). After 5 seconds, the leader vehicle repeatedly accelerates and decelerates by setting its accelerator as $10 \sin \frac{t}{2}$ (m/s²). As recalled in Assumption 1, the leader AV's position information is periodically broadcast. We set the broadcasting interval as 10 (ms). Besides, each AV can scan the predecessor AV's inter-distance using RADAR sensors with the interval of 10 (ms). The number of iterations for a consensus is K = 6, and the resultant delay of the average position estimate is $6 \times 0.915 = 5.49$ (ms), where 915 (μ s) is the coherence time specified in Remark 1.

Fig. 5 represents the performance of AirCons with several interesting observations. First, the left-side figure shows each



Fig. 5. Platooning control and the resultant performance of AirCons over time. (Left) Position trajectory of each AV in a platoon. Colored and dotted lines show each AV's actual and desired position, respectively. (Center) Each AV's velocity over time. (Right) The comparison of accumulated position error between AirCons and the benchmark without average information.

AV's trajectory (solid curves) with 10 different colors representing each of them. It is shown that every AV follows the desired path (dotted curves) except the initial phase. Each AV's velocity over time is plotted in the middle figure. It is shown that each AV's velocity follows the leader AV's one once the platoon becomes stabilized, thereby satisfying string stability under the current turbulence setting. The right-side figure represents the accumulated errors of AirCons and benchmarks, both of which meet string stability. On the other hand, the average position information helps reach a consensus faster than the benchmark, resulting in 14.22% reduction of the accumulated error.

V. CONCLUSION

This work has proposed AirCons, a joint communicationand-control design for distributed VP. The main goal of AirCons is to estimate the average position of neighbor AVs instead of individual position information, which is verified via extensive simulations to provide a significant control gain. Exploiting a wireless signal's superposition and broadcasting properties enable multiple AVs' received signals to reach the consensus in the air, which is close to the desired average position. Besides, AirCons do not require establishing individual V2V links, reducing the significant burden of frequent training of many channels. To make the proposed AirCons more practical, we consider several interesting directions for future work, e.g., the extensions to radio resource management and complex driving scenarios.

REFERENCES

- P. Ioannou and C. Chien, "Autonomous intelligent cruise control," *IEEE Trans. Veh. Technol.*, vol. 42, no. 4, pp. 657–672, 1993.
- [2] A. A. Hussein and H. A. Rakha, "Vehicle platooning impact on drag coefficients and energy/fuel saving implications," *IEEE Trans. Veh. Technol.*, vol. 71, no. 2, pp. 1199–1208, 2022.
- [3] H. Seo, J. Park, M. Bennis *et al.*, "Communication and consensus codesign for distributed, low-latency, and reliable wireless systems," *IEEE Internet Things J.*, vol. 8, no. 1, pp. 129–143, 2021.
- [4] G. J. L. Naus, R. P. A. Vugts, J. Ploeg *et al.*, "String-stable CACC design and experimental validation: A frequency-domain approach," *IEEE Trans. Veh. Technol.*, vol. 59, no. 9, pp. 4268–4279, 2010.

- [5] M. Noor-A-Rahim, G. G. M. N. Ali, Y. L. Guan *et al.*, "Broadcast performance analysis and improvements of the lte-v2v autonomous mode at road intersection," *IEEE Transactions on Vehicular Technology*, vol. 68, no. 10, pp. 9359–9369, 2019.
- [6] X. Liu, A. Goldsmith, S. Mahal *et al.*, "Effects of communication delay on string stability in vehicle platoons," in *Proc. ITSC 2001. 2001 IEEE Intell. Transp. Syst. (Cat. No.01TH8585)*, 2001, pp. 625–630.
- [7] F. Ma, J. Wang, S. Zhu *et al.*, "Distributed control of cooperative vehicular platoon with nonideal communication condition," *IEEE Trans. Veh. Technol.*, vol. 69, no. 8, pp. 8207–8220, 2020.
- [8] O. Elijah, C. Y. Leow, T. A. Rahman *et al.*, "A comprehensive survey of pilot contamination in massive MIMO—5G system," *IEEE Commun. Surveys Tuts.*, vol. 18, no. 2, pp. 905–923, 2016.
- [9] H. Jung and S.-W. Ko, "Performance analysis of UAV-enabled overthe-air computation under imperfect channel estimation," *IEEE Wireless Commun. Lett.*, vol. 11, no. 3, pp. 438–442, 2022.
- [10] G. Zhu, J. Xu, K. Huang *et al.*, "Over-the-Air computing for wireless data aggregation in massive iot," *IEEE Wireless Commun.*, vol. 28, no. 4, pp. pp.57–65, 2021.
- [11] S.-W. Ko, H. Chae, K. Han *et al.*, "V2X-based vehicular positioning: Opportunities, challenges, and future directions," *IEEE Wireless Commun.*, vol. 28, no. 2, pp. 144–151, 2021.
- [12] S. Santini, A. Salvi, A. S. Valente *et al.*, "A consensus-based approach for platooning with intervehicular commun. and its validation in realistic scenarios," *IEEE Trans. Veh. Technol.*, vol. 66, no. 3, pp. 1985–1999, 2017.
- [13] —, "Platooning maneuvers in vehicular networks: A distributed and consensus-based approach," *IEEE Trans. Intell. Veh.*, vol. 4, no. 1, pp. 59–72, 2019.
- [14] C. Campolo, A. Molinaro, F. Romeo *et al.*, "5G NR V2X: On the impact of a flexible numerology on the autonomous sidelink mode," in 2019 *IEEE 2nd 5G World Forum (5GWF)*, 2019, pp. 102–107.
- [15] 3GPP, "Study on evaluation methodology of new vehicle-to-everything (V2X) use cases for LTE and NR," 3rd Generation Partnership Project (3GPP), Technical Report (TR) 37.885, 06 2019, version 15.3.0.
- [16] F. Molinari, S. Stanczak, and J. Raisch, "Exploiting the superposition property of wireless communication for average consensus problems in multi-agent systems," in *Proc. 2018 European Control Conference* (ECC), 2018, pp. 1766–1772.

Appendix

A. Proof of Theorem 1

With noise being neglected and k > 1, (13) is rewritten as

$$\begin{aligned} x_{m}[k+1] = &(1-\rho)x_{m}[k] \\ &+ \rho \left(\frac{\mathsf{Re}\{\sum_{\ell \in \mathbb{T}_{n}/\{m\}} h_{m,\ell}[k]I_{\ell}^{*}[k]x_{\ell}[k]\}\}}{\mathsf{Re}\left\{\sum_{\ell \in \mathbb{T}_{n}/\{m\}} h_{m,\ell}[k]I_{\ell}^{*}[k]\right\}} \right) \\ \stackrel{(a)}{=} &(1-\rho)x_{m}[k] + \rho \left(\frac{\sum_{\ell \in \mathbb{T}_{n}/\{m\}} |a_{m,\ell}[k]|x_{\ell}[k]}{\sum_{\ell \in \mathbb{T}_{n}/\{m\}} |a_{m,\ell}[k]|} \right), \end{aligned}$$
(19)

where $a_{m,\ell}[k] = \operatorname{Re}\{h_{m,\ell}[k]\}\$ are specified in (8), and (a) follows from the fact that $I_{\ell}^*[k]$ and $x_{\ell}[k]$ are pure real term. Denote $\mathbf{x}[k] = [x_1[k], x_2[k], ..., x_S[k]]^T$. Then, (19) can be expressed as $\mathbf{x}_m[k+1] = \mathbf{b}_m[k]^T \mathbf{x}[k]$.

$$\mathbf{x}[k+1] = \mathbf{B}[k]\mathbf{x}[k], \qquad (20)$$

where $\mathbf{B}[k] = [\mathbf{b}_1[k], \cdots, \mathbf{b}_S[k]]^T$. Given $\rho \ge 0$, all elements of $\mathbf{b}_m[k]$ are strictly positive and their sum is always one, confirming that $\mathbf{B}[k]$ is a row-stochastic matrix. It is proved in [16] that $\mathbf{x}[k]$ converges to the weighted average of the initial value $\mathbf{x}[0]$, namely,

$$\mathbf{w}^T \mathbf{x}[1] = \sum_{m \in \mathbb{S}_n \cup \{n\}} w_m s_m = \frac{\sqrt{\rho P}}{L} \sum_{m \in \mathbb{T}_n} w_m \alpha_m, \quad (21)$$

which completes the proof.

B. Proof of Proposition 1

Channels are time-invariant. That is $\eta_{m,\ell} = \sqrt{\frac{2}{\pi}} \frac{1}{|m-\ell|}$. Then matrix U is written as follows:

U =

$$\begin{pmatrix} 1-\rho & \frac{1}{2(1-2)} & \cdots & \frac{1}{2(1-S)} \\ \frac{1}{2(2-1)} & \sum_{m\in\mathbb{T}_n/\{1\}} \frac{1}{d(1-m)} & \cdots & \frac{1}{2(2-S)} \\ \vdots & 1-\rho & \cdots & \frac{1}{2(2-S)} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{1}{d(S-1)} & \frac{1}{d(S-m)} & \frac{1}{2(S-2)} & \cdots & 1-\rho \\ \sum_{m\in\mathbb{T}_n/\{S\}} \frac{1}{d(S-m)} & \frac{1}{2(2-S)} & \cdots & 1-\rho \end{pmatrix}$$

$$(22)$$

Since, $\sum_{m \in \mathbb{T}_n / \{\ell\}} \frac{1}{d|\ell-m|} = \sum_{m \in \mathbb{T}_n / \{S+1-\ell\}} \frac{1}{d|S+1-\ell-m|}$, matrix element $u_{m,\ell} = u_{(S+1-m,S+1-\ell)}$. Then matrix U is centro-symmetric matrix. Left eigen vector corresponding to eigen value 1 is denoted as v. Then,

$$\boldsymbol{v}\boldsymbol{U}=1\cdot\boldsymbol{v}.$$

Then, v(U - I) = 0, where I denotes identity matrix and 0 denotes matrix of size $(1 \times S)$ whose elements are zeros. It is obvious that left eigen vector v is symmetric. Since inter-distance of AVs are assumed to be strictly equal, we say $[\alpha_1, \dots, \alpha_S] = [d, 2d, \dots Sd]$. Then, $v\alpha = \frac{1}{2}(S+1)d$ Then, we conclude that $v\alpha = \zeta_n$. Thus proof is completed.