SEMI-SUPERVISED MACHINE LEARNING: A HOMOLOGICAL APPROACH

ADRIÁN INÉS, CÉSAR DOMÍNGUEZ, JÓNATHAN HERAS, GADEA MATA AND JULIO RUBIO

ABSTRACT. In this paper we describe the mathematical foundations of a new approach to semisupervised Machine Learning. Using techniques of Symbolic Computation and Computer Algebra, we apply the concept of *persistent homology* to obtain a new semi-supervised learning method.

INTRODUCTION

Machine Learning and Deep Learning methods have become the state-of-the-art approach for solving data classification tasks. In order to use those methods, it is necessary to acquire and label a considerable amount of data; however, this is not straightforward in some fields, since data annotation is time consuming and may require expert knowledge. This challenge can be tackled by means of semi-supervised learning methods that take advantage of both labelled and unlabelled data. In our team we have applied this Machine Learning paradigm in various applied projects (e.g. [3]). In this paper, we present a new semi-supervised learning method based on techniques from Topological Data Analysis. In particular, we have used a homological approach that consists of studying the persistence diagrams associated with data from binary classification tasks using the bottleneck and Wasserstein distances. In addition, we have carried out a thorough analysis of the developed method using 5 structured datasets. The results show that the semi-supervised method developed in this work outperforms both the results obtained with models trained with only manually labelled data, and those obtained with classical semi-supervised learning methods, improving the models by up to a 16%.

1. CONCEPTUAL PRESENTATION

Our method falls within the discipline of Topological Data Analysis (hereinafter TDA), a field devoted to extracting topological and geometrical information from data. And the problem undertaken is motivated by the challenge of obtaining enough annotated data to apply Machine Learning techniques. To that end, a family of methods that has been successfully applied in the literature is semi-supervised learning. Semi-supervised learning methods provide a means of using unlabelled data to improve models' performance when we have access to a large corpus of data that is difficult to annotate. Traditional semi-supervised learning algorithms, such as Label Spreading [4] and Label Propagation [5], focus on the distance among the data points to annotate unlabelled data points; i.e. on the metric and density characteristics of the data in a dataset. However, there are contexts where metric approaches could be misleading. As shown in Figure 1, distances are not the right discriminators in complex situations and, therefore other ideas are needed. Our inspiration comes from the *Manifold Hypothesis* [2], which explores when high dimensional data could tend to lie in low dimensional manifolds. Roughly speaking, our method works under the hypothesis that each

This work was partially supported by the projects PID2020-115225RB-I00 and PID2020-116641GB-I00, funded by MCIN/AEI/10.13039/501100011033 and by "European Union NextGenerationEU/PRTR".



FIGURE 1. Example with two "connected manifolds"

class in the dataset lies on a manifold. In particular, homological information should be respected when we add an unlabelled point to one of the classes. Our method is therefore as follows: given two sets of data points A and B, corresponding to the points labelled with class 1 and class 2, respectively, we assume there are two manifolds associated with each set, \mathcal{M}_A and \mathcal{M}_B respectively; now, given an unlabelled data point x, if x belongs to class 1, for instance, then $A \cup \{x\}$ would lie on a manifold more similar to \mathcal{M}_A than the manifold corresponding to $B \cup \{x\}$ with respect to \mathcal{M}_B .

All the code developed for this project and also the conducted experiments are available at the project webpage https://github.com/adines/TTASSL.

2. Description of the method

In this section, we describe the semi-supervised learning algorithm that we have designed to tackle binary classification tasks. We start with a set X_1 of points from class 1, a set X_2 of points from class 2, and a set X of unlabelled points. The objective of our algorithms is to annotate the elements of X by using topological properties of X_1 and X_2 . We assume some familiarity with notions employed in TDA such as Vietoris-Rips filtration (we denote the Vietoris-Rips filtration associated with a set X by V_X), persistence diagrams (we denote the persistence diagram associated with a filtration F by P(F)), and the bottleneck and Wasserstein distances (denoted by d_B and d_W respectively). For a detailed introduction to these topics see [6].

Our semi-supervised learning algorithm takes as input the sets X_1 and X_2 , a point $x \in X$, a threshold value t, and a flag that indicates whether the bottleneck or the Wasserstein distance should be used. We denote the chosen distance as d. The output produced by our algorithm is whether the point x belongs to X_1 , X_2 or none of them. In order to decide the output of the algorithm, our hypothesis is that if a point belongs to X_1 , analogously for X_2 , then when adding the point to the

manifold on which X_1 lies, the topological variation will be minimal; whereas if the point does not belong to X_1 , the variation will be greater. In particular, we proceed as follows:

- (1) Construct the Vietoris-Rips filtrations V_{X_1} , V_{X_2} , $V_{X_1 \cup \{x\}}$ and $V_{X_2 \cup \{x\}}$; (2) Construct the persistence diagrams $P(V_{X_1})$, $P(V_{X_2})$, $P(V_{X_1 \cup \{x\}})$ and $P(V_{X_2 \cup \{x\}})$; (3) Compute the distances $d(P(V_{X_1}), P(V_{X_1 \cup \{x\}}))$ and $d(P(V_{X_2}), P(V_{X_2 \cup \{x\}}))$, from now on d_1 and d_2 respectively;
- (4) If both d_1 and d_2 are greater than the threshold t, return none; otherwise, return the set associated with the minimum of the distances d_1 and d_2 .

The algorithm above is diagrammatically described in Figure 2, and it is applied to all the points of the set of unlabelled points X.



FIGURE 2. Example of the application of our method using the bottleneck distance, and using 0.6 as threshold value.

3. EVALUATION

Table 1 presents the results with 5 different datasets taken from the UCI Machine Learning Repository [1], training the models with two machine learning algorithms, which are Support Vector Machines (SVM in the table) and Random Forest (RF), and comparing our method with three classical semi-supervised learning techniques (namely, Label Propagation [5], Label Spreading [4],

TABLE 1. Accuracy results for the SVM and RF classifiers trained with data annotated for each of the annotation methods (classical and homological) together with the results obtained with the initial data (base) in the 5 structured datasets. The best result for each dataset is highlighted in bold face.

	Banknote		Breast Cancer		Ionosphere		Prima Indian		Sonar		Mean (std)	
Method	SVM	RF	SVM	RF	SVM	RF	SVM	RF	SVM	RF	SVM	RF
Base	97.0	88.6	89.3	96.1	80.0	93.3	65.7	60.8	61.3	64.5	78.7(15.2)	80.7(16.7)
Label Propagation	97.4	93.2	90.3	89.3	86.7	86.7	64.3	68.5	58.1	54.8	79.3(17.1)	78.5(16.3)
Label Spreading	97.4	93.2	90.3	89.3	86.7	86.7	64.3	68.5	58.1	54.8	79.3(17.1)	78.5(16.3)
Self Training classifier	95.1	93.6	35.9	35.9	85.0	86.7	66.4	66.4	58.1	67.7	68.1(23.2)	70.1(22.4)
Bottleneck threshold 0.8	99.2	92.4	93.2	91.3	78.3	95.0	63.6	64.3	61.3	64.5	79.1(17.0)	81.5(15.6)
Bottleneck threshold 0.6	99.2	91.3	89.3	90.3	75.0	88.3	59.4	63.6	48.4	45.2	74.3(20.9)	75.7(20.6)
Bottleneck threshold 0.4	97.4	90.5	87.4	85.4	78.3	86.7	63.6	62.9	45.2	45.2	74.4(20.5)	74.1(19.5)
Bottleneck threshold 0.2	97.4	90.5	87.4	85.4	78.3	86.7	63.6	62.9	45.2	45.2	74.4(20.5)	74.1(19.5)
Bottleneck threshold 0.0	97.4	90.5	87.4	85.4	78.3	86.7	63.6	62.9	45.2	45.2	77.1(22.6)	74.1(19.5)
Wasserstein threshold 0.8	97.4	89.8	92.2	88.4	80.0	95.0	68.5	67.8	61.3	64.5	79.9(15.3)	81.1(13.9)
Wasserstein threshold 0.6	99.2	93.6	89.3	87.4	70.0	91.7	61.5	61.5	74.2	61.3	78.9(15.2)	79.1(16.3)
Wasserstein threshold 0.4	97.0	96.2	87.4	87.4	76.7	81.7	60.8	62.9	71.0	71.0	78.6(14.1)	79.8(13.2)
Wasserstein threshold 0.2	97.0	96.2	87.4	87.4	76.7	81.7	60.8	62.9	71.0	71.0	78.6(14.1)	79.8(13.2)
Wasserstein threshold 0.0	97.0	96.2	87.4	87.4	76.7	81.7	60.8	62.9	71.0	71.0	78.6(14.1)	79.8(13.2)

and Self Training) to annotate the unlabelled data. From these results, we can extract several conclusions: our method improves the base results in 8 out of the 10 models and obtains better results than the classical semi-supervised learning techniques in 8 out of the 10 models.

4. CONCLUSIONS AND FURTHER WORK

In this paper, we have studied the application of Topological Data Analysis techniques to the semi-supervised learning setting. The results show that our method can create classification models that achieve better results than those obtained when using classical semi-supervised learning methods. We plan to extend our work in different ways. First of all, the proposed method can be expanded to multi-class classification tasks, and, an iterative version of the algorithm can be easily developed. In addition, we plan to design new semi-supervised learning algorithms based on other notions from TDA, taking further advantage of the *Manifold Hypothesis*.

REFERENCES

- [1] D. Dua and C. Graff. UCI Machine Learning Repository. http://archive.ics.uci.edu/ml. 2017
- [2] C. Fefferman, S. Mitter and H. Narayanan. *Testing the Manifold Hypothesis*. Journal of the American Mathematical Society. Vol. 29 (4), 983–1049. 2016
- [3] A. Inés, C. Domínguez, J. Heras, E. Mata, and V. Pascual. *Biomedical image classification made easier thanks to transfer and semi-supervised learning*. Computer Methods and Programs in Biomedicine. Vol. 198, 105782. 2021
- [4] D. Zhou, O. Bousquet, T. N. Lal, J. Weston and B. Schölkopf. *Learning with local and global consistency*. Advances in Neural Information Processing Systems 16, 321–328. 2004
- [5] X. Zhu and Z. Ghahramani. Learning from Labeled and Unlabeled Data with Label Propagation. Tech. Report. 2002
- [6] A. Zomorodian. Topological data analysis. Advances in Applied and Computational Topology. Vol. 70, 1–39. 2012

Departamento de Matemáticas y Computación. Universidad de La Rioja *Email address*: {adrian.ines, cesar.dominguez, jonathan.heras}@unirioja.es *Email address*: {gadea.mata, julio.rubio}@unirioja.es