

Augmenting Zero-Shot Dense Retrievers with Plug-in Mixture-of-Memories

Suyu Ge^{1*}, Chenyan Xiong², Corby Rosset², Arnold Overwijk², Jiawei Han¹, Paul Bennett²

¹ University of Illinois Urbana-Champaign ² Microsoft Research

{suyuge2, hanj}@illinois.edu

{chenyan.xiong, corbyrosset, arnold.overwijk, paul.n.bennett}@microsoft.com

Abstract

In this paper we improve the zero-shot generalization ability of language models via Mixture-Of-Memory Augmentation (MoMA), a mechanism that retrieves augmentation documents from multiple information corpora (“external memories”), with the option to “plug in” new memory at inference time. We develop a joint learning mechanism that trains the augmentation component with latent labels derived from the end retrieval task, paired with hard negatives from the memory mixture. We instantiate the model in a zero-shot dense retrieval setting by augmenting a strong T5-based retriever with MoMA. Our model, MoMA, obtains strong zero-shot retrieval accuracy on the eighteen tasks included in the standard BEIR benchmark. It outperforms systems that seek generalization from increased model parameters and computation steps. Our analysis further illustrates the necessity of augmenting with mixture-of-memory for robust generalization, the benefits of augmentation learning, and how MoMA utilizes the plug-in memory at inference time without changing its parameters. We plan to open source our code.

1 Introduction

Scaling up language models—with more parameters, compute, and annotation data—improves model generalization ability on downstream applications (Raffel et al., 2019; Brown et al., 2020; Smith et al., 2022), but with diminishing return: *linear* improvements on downstream metrics often require *exponentially* more parameters and computing cost (Kaplan et al., 2020; Hoffmann et al., 2022). Hence, scaling pretrained language models in this way is economically unsustainable (Strubell et al., 2020; Bender et al., 2021; Zhang et al., 2022).

Retrieval augmented language models provide a promising alternative. They allow language models to efficiently access vast resources from an external corpus (Guu et al., 2020; Borgeaud et al., 2022) that serves as a kind of “memory” they can refer to when making predictions, alleviating the need to memorize as much

information in their own network parameters (Roberts et al., 2020). This open-book approach helps language models to better generalize on token prediction tasks and machine translation (Khandelwal et al., 2019; Borgeaud et al., 2022), and tasks which already involve a first-stage retrieval component, e.g., OpenQA (Borgeaud et al., 2022; Izacard et al., 2022). Existing retrieval augmentation methods usually stick to one single retrieval corpus throughout training and inference so that the retrieval component can be indirectly guided by the supervision from end tasks.

In this paper we improve the zero-shot generalization ability of language models using “mixture-of-memory” (MoMA), a new retrieval augmentation mechanism. Instead of a single corpus, MoMA retrieves documents from a “mixture” of multiple external corpora and enjoys the merits of a larger and more comprehensive source of knowledge. This mechanism also allows removing and/or “plugging-in” new corpora during inference time, when more information from the target task is revealed, or as an additional way for users to control the model. Specifically, we apply MoMA on the zero-shot dense retrieval task, which is the foundation of many important real-world applications (Thakur et al., 2021a; Kim, 2022) and also the retrieval component of recent retrieval augmented language models (Guu et al., 2020; Izacard et al., 2022). However, it is not trivial to guide a retrieval model to leverage multiple corpora. We need to jointly train the augmentation component and dense retriever using supervised relevance signals and self-mined hard negatives.

We instantiate MoMA with a T5 encoder-decoder model (Ni et al., 2022) and apply it to the dense retrieval task (Karpukhin et al., 2020). Our end task retriever uses a set of augmenting documents from the mixture-of-memories to enhance its representation of the query with important context; the retriever then uses the enhanced query representation to retrieve a final candidate set. At inference time, we plug in the target task’s corpus to the memory mixture to introduce in-domain context information, without updating any parameter.

We experimented on eighteen zero-shot dense retrieval tasks included in BEIR (Thakur et al., 2021a), the standard ZeroDR benchmark. The results demonstrate the improved zero-shot ability of MoMA. When paired with the ANCE (Xiong et al., 2020) training framework

* Work partly done during Suyu’s internship at Microsoft.

on a T5 model, it outperforms counterparts without the MoMA augmentation component, as well as recent state-of-the-art dense retrieval systems of the same scale, by large margins. To validate its effectiveness when paired with advanced models, we further instantiate MoMA with a contrastively pretrained T5 model. MoMA then achieves comparable or even stronger performance to ZeroDR systems with larger model scales and heavier computation costs.

Our analysis reveals that large and diverse corpora in the memory leads to the best performance; while only using a single corpus during training does not improve performance on unseen target tasks. The learning of augmentation component is also important for MoMA to utilize the diverse information from the mixture. Our analysis and case studies illustrate how MoMA leverages the plug-in memory at testing time to enrich its query representations with in-domain information that was not available in training.

2 Related Work

2.1 Retrieval Augmentation

Recent research has explored two common ways to construct the external memory in retrieval-augmented language models. The first is to retrieve similar tokens for language models to copy from when predicting the next token (Khandelwal et al., 2019; Zhong et al., 2022). The second is to retrieve the related documents (text sequences) from an in-domain corpus as additional input (Guu et al., 2020; Borgeaud et al., 2022). Our work falls into this category as document-based models better align with knowledge-intensive tasks (Petroni et al., 2020), such as retrieval and OpenQA (Chen et al., 2017).

Learning to retrieve useful documents to augment the language model is a challenging task, since human annotations on the usefulness of augmentation documents are costly and seldom available. The most straightforward way is to use representations from raw pretrained language models to find documents similar to the task input, i.e., as unsupervised dense retrieval (Guu et al., 2020; Borgeaud et al., 2022). Adapting dense retrieval models trained for relevance matching is another common choice (Izacard and Grave, 2020b; Lewis et al., 2020; Yu et al., 2021). A more formal solution is to jointly learn the augmentation components end-to-end using supervision from the final task, for example, treating the augmentation as latent variables and applying EM (Zhao et al., 2021), or distilling the augmentation component from feedback of the final model (Izacard and Grave, 2020a). In a parallel work, Izacard et al. (2022) found the most effective one is attention distillation method (ADist), which trains the augmentation component using soft labels derived from the end model’s attention on augmentation documents.

The motivation for query augmentation coincides with the query expansion methods in the traditional IR community, whereby the user’s original query is augmented by new features with similar mean-

ings (Carpineto and Romano, 2012). As feature selection usually requires additional semantic analysis, the efficiency and usability of traditional query expansion methods remain limited when faced with a new domain. To overcome this, recent work relies on dense retrieval results to expand the query (Yu et al., 2021). The retrieved relevant documents serve as pseudo relevance feedback signals for the model, which are concatenated with the original query as the augmented model input. Our work augments queries with feedback from multiple corpora and learns to select important augmentation documents automatically.

2.2 Zero-shot Dense Retrieval

Dense retrieval models trained on a resource rich source tasks, e.g., web search, usually do not perform as well when zero-shot transferred to other domains (Thakur et al., 2021b). This is concerning since many important real-world scenarios do not have the luxury of web corpus training signals and must rely on near zero-shot transfer, e.g., the medical domains (Kim, 2022). Xin et al. (2021) analyzed the challenge of shifting between training and testing domains, and leveraged domain-invariant learning to mitigate the gap. Another common approach is to first generate domain-specific pseudo labels for each task, and then use them to train dense retriever (Thakur et al., 2021b; Wang et al., 2022). Additionally, continuous pretraining the language model also improves its generalization ability in ZeroDR (Izacard et al., 2021; Gao and Callan, 2022; Yu et al., 2022). Following works (Izacard et al., 2021; Yu et al., 2022) further contrastively pretrained the retriever on source or target corpus with a sentence matching loss. Other methods seek better generalization ability in ZeroDR from various resources, for example, combining with sparse retrieval to introduce exact match signals (Formal et al., 2021), using multiple vectors per documents for term-level matching (Khattab and Zaharia, 2020a), or scaling up the retrieval model using larger language models (Ni et al., 2021; Neelakantan et al., 2022).

3 Method

In this section we first describe our Mixture-of-Memory Augmentation. Then we discuss how it is jointly learned with the end system and enables plug-in memory at inference time.

3.1 Mixture-of-Memory Augmentation

Before going to the details of MoMA, we first recap some preliminaries in ZeroDR.

Preliminaries. The dense retrieval (DR) task aims to find relevant documents d from a corpus C for the given query q by representing them in a shared embedding space. Specifically, the retrieval score in DR is often calculated as:

$$f(q, d) = \mathbf{q} \cdot \mathbf{d}; \mathbf{q} = g(q); \mathbf{d} = g(d). \quad (1)$$

It uses dot product as the scoring function to match the embeddings q and d , which is known to support efficient nearest neighbor search (ANN) (Johnson et al., 2019). A pretrained language model is often the encoder of choice $g()$. We use the ST5-EncDec variant of Sentence-T5 (Ni et al., 2022):

$$g(x) = \text{Dec}(\text{Enc}(x)), \quad (2)$$

which feeds in the text sequence (preended by a special [CLS] tokens) to the encoder of T5, $\text{Enc}()$, and uses the output representation of the [CLS] token from the decoder, $\text{Dec}()$, as the text representation. This naturally leverages the attention from decoder to encoder at all Transformer layers (Raffel et al., 2019), as a fine-grained information gathering mechanism.

The *training* of dense retrieval systems often applies standard ranking loss and pairs the relevant documents $d^+ \in D^+$ for each query q with hard negatives $d^- \in D^-$:

$$\mathcal{L} = \sum_q \sum_{d^+ \in D^+} \sum_{d^- \in D^-} l(f(q, d^+), f(q, d^-));$$

$$D^- \sim \text{ANN}_{f(q, \circ)}^C \setminus D^+. \quad (3)$$

Eqn. 3 uses ANCE hard negatives, which are the top-retrieved documents from C using the retriever itself (Xiong et al., 2020). The loss function $l()$ can be any standard ranking loss such as cross entropy. A ZeroDR model is trained on q^s and documents $d^s \in C^s$ from a *source task*, often web search, and tested on *target tasks* q^t and C^t ; supervision signals are only present from the source.

Mixture-of-Memory Augmentation. The key idea of (document-based) retrieval augmented language models is to enrich the representation $g(q)$ with additional contextual input for the model, i.e., augmentation documents d^a retrieved from an external memory \mathcal{M} . Instead of using a single document corpus, MoMA uses multiple corpora to provide richer and more diverse external resources for augmentation. For example, \mathcal{M} can be composed by the source corpus C^s , a general encyclopedia, a domain specific knowledge graph, etc. Then we can retrieve the augmentation documents D^a :

$$D^a = \text{ANN}_{f^a(x, \circ)}^{\mathcal{M}}; \mathcal{M} = \{C_1, \dots, C_M\}. \quad (4)$$

This augmentation component uses another dense retriever $f^a()$ (also a Sentence T5 model), with parameters distinct from those in $g()$. Note that instead of retrieving D^a separately from M different ANN memory sources and merging results, Eqn. 4 combines them into one ANN index. This requires the augmentation component $f^a()$ to be flexible enough handle various corpora in the mixture.

Using the encoder-decoder architecture for $g()$ in Eqn. 2 enables a simple extension to incorporate the augmentation documents using the fusion-in-decoder (FiD) mechanism (Izacard and Grave, 2020b):

$$g^{\text{MoMA}}(q) = \text{Dec}(\text{Enc}(q), \text{Enc}(d_1^a), \dots, \text{Enc}(d_K^a));$$

$$D^a = \{d_1^a, \dots, d_K^a\}. \quad (5)$$




Figure 1: Illustration of the Mixture-of-Memory Augmentation.

It feeds in the K augmentation documents separately to the T5 encoder of $g()$. Then it fuses the encoded documents together with $\text{Enc}(q)$ using one decoder that attends to all encoded vectors, as illustrated in Figure 1.

The FiD approach in Eqn 5 is a nice balance of efficiency and capacity when modeling multiple text sequences (Izacard and Grave, 2020b). It is more efficient than concatenating all text pieces together, while also remaining expressive enough to model the nuances from many sequences. (Izacard and Grave, 2020a; Izacard et al., 2022).

When instantiating MoMA in the dense retrieval setting, we focus on augmenting the query representation q , as queries are often short, ambiguous, and benefit more from additional contextual information (Lavrenko and Croft, 2017; Yu et al., 2021). This leads to the following definition of MoMA:

$$f^{\text{MoMA}}(q, d) = q^a \cdot d;$$

$$q^a = g^{\text{MoMA}}(q), d = g(d), \quad (6)$$

using the construction of $g^{\text{MoMA}}()$ in Eqn. 5 upon the augmentation documents defined in Eqn. 4.

3.2 Joint Learning in MoMA and Inference with Plug In Memory

MoMA has two sets of parameters to learn, in the main model $f^{\text{MoMA}}()$ and the augmentation component $f^a()$. Both have their own T5 encoder-decoder parameters. The two components are bridged by the augmentation documents, which are retrieved by $f^a()$ from \mathcal{M} and used by $f^{\text{MoMA}}()$ to produce query representation q^a .

Main Model Learning. Given the relevance labels from the source task and an augmentation model, training $f^{\text{MoMA}}()$ is straightforward. We can use the standard dense retrieval training to finetune the enriched query encoder $g^{\text{MoMA}}()$ and the document encoder $g()$:

$$\mathcal{L}^{\text{MoMA}} = \sum_{q^s} \sum_{d^+} \sum_{d^-} l(f^{\text{MoMA}}(q^s, d^+), f^{\text{MoMA}}(q^s, d^-));$$

$$d^+ \in D^{s+}, d^- \in D^{s-} \quad (7)$$

$$D^{s-} \sim \text{ANN}_{f^{\text{MoMA}}(q^s, \circ)}^{C^s} \setminus D^{s+}. \quad (8)$$

The training signals come from the source task, including q^s , its relevant documents D^{s+} , and ANCE hard negatives D^{s-} retrieved from the source corpus C^s .

Augmentation Learning. Training $f^a()$ is challenging as it is hard to label whether an augmentation document is useful. Propagating gradients from the final loss to $f^a()$ is also prohibitive as the retrieval operation in Eqn. 4 is discrete. Fortunately, recent research found the attention scores from the FiD decoder to each encoded inputs (Eqn. 5) are good approximations to the usefulness of augmentation documents (Izacard and Grave, 2020a):

$$\text{FidAtt}(d_i^a) = \sum_{\text{layers}} \sum_{\text{positions}} \sum_{\text{heads}} \text{Att}_{\text{Dec} \rightarrow \text{Enc}}(g^{\text{MoMA}}(d_i^a)). \quad (9)$$

It sums the attentions from $g^{\text{MoMA}}()$'s special token at the decoder's [CLS] position over all layers, input positions, and attention heads. Ideally, higher $\text{FidAtt}()$ is assigned to d_i^a that provides useful contextual information.

Previously, FidAtt scores are often used as soft labels for the augmentation model (Izacard and Grave, 2020a; Izacard et al., 2022). Doing so with memory mixtures is risky as it is too sparse and overfits memory resource that appears earlier in the training, which are the only ones available for the decoder to attend on. To improve the learning robustness, we introduce ANCE-style hard negative mining to train the augmentation component as well.

First, we formulate the positive set of augmentation documents as:

$$D^{a+} = D^{s+} \cup \text{Top-N}_{\text{FidAtt}(d_i^a), D^{a+}}. \quad (10)$$

which combines relevant documents D^{s+} and the augmenting ones that received N-highest attention scores from $g^{\text{MoMA}}()$. Then we pair them with hard negatives to formulate the training of $f^a()$ as:

$$\mathcal{L}^a = \sum_{q^s} \sum_{d^+ \in D^{a+}} \sum_{d^- \in D^{a-}} l(f^a(q^s, d^+), f^a(q^s, d^-)); \quad (11)$$

$$D^{a-} \sim \text{ANN}_{f^a(q^s, \circ)}^M \setminus D^{a+}. \quad (12)$$

Notice the negatives for $f^a()$ have comprehensive coverage from multiple corpora.

Iterative Training. The learning of $f^{\text{MoMA}}()$ and $f^a()$ is an iterative process that fits naturally into the training procedure of dense retrieval training with hard negatives. We follow the standard iterations in ANCE and construct the t -th training episode of MoMA:

1. Construct hard negatives D^{s-} via Eqn. 8 using weights $f_{t-1}^{\text{MoMA}}()$ from the last episode;
2. Retrieve augmentation D^a via Eqn. 4 using weights $f_{t-1}^a()$ from the last episode;
3. Train $f_t^{\text{MoMA}}()$ as Eqn. 7;
4. Formulate new positive augmentation documents D^{a+} , using updated attention scores from

$f_t^{\text{MoMA}}()$, and mine negative augmentation documents D^{a-} using $f_{t-1}^a()$;

5. Train $f_t^a()$ following Eqn. 11.

Both $f_0^{\text{MoMA}}()$ and $f_0^a()$ can be initialized with a BM25 warmed-up T5 retriever. Steps 1 and 3 above are inherited from standard dense retrieval training. The rest are introduced by MoMA. The additional computation in the training side mainly resides updating the index for the memory mixture, a standard cost in retrieval-augmented language models (Guu et al., 2020; Izacard et al., 2022).

Zero-Shot Retrieval with Plug in Memories. To perform zero-shot retrieval on unseen tasks, MoMA first retrieves augmented documents using $f^a()$ from \mathcal{M} for the target query q^t , and retrieves target documents $d^t \in C^t$ with the augmented model $f^{\text{MoMA}}()$ without changing any model parameters. MoMA allows $f^a()$ to attend over the target corpus as well if it is plugged in: $\mathcal{M} = \mathcal{M} \cup C^t \setminus C^s$, which conveys in-domain information. The augmenting corpus can also be engineered by users manually to inject their preference or domain knowledge, e.g., as ‘‘memory engineering’’. In this work we focus on swapping out the source corpus for the target corpus; we leave other explorations for future work.

4 Experimental Methodologies

Datasets. We choose the MS MARCO passage dataset (Bajaj et al., 2016) as the source domain dataset, whereas the target domains are from the 18 datasets in BEIR (Thakur et al., 2021b) benchmark, which include including biomedical, scientific and financial texts. More details can be found in Appendix A.1. The evaluation metric NDCG@10 is the same with BEIR benchmark, which measures Normalized Discounted Cumulative Gain (Wang et al., 2013) of top 10 prediction. The higher NDCG@10 value indicates better performance.

Augmenting Corpora. During training, the mixture-of-memory is composed of source training corpus (MARCO), Wikipedia and a medical knowledge graph. We use the Wikipedia chunk preprocessed by (Karpukhin et al., 2020) without further processing¹. The medical knowledge graph is extracted from the Medical Subject Headings (MeSH)², an open-source database for indexing and cataloging of biomedical and health-related information. Since it is hierarchical in structure, we linearize it by concatenating spans with text information. During testing, we directly replace MARCO with the corresponding document sets from BEIR. Each task from BEIR is augmented independently. More dataset and preprocessing details can be found in Appendix A.1.

Baselines and Model Choices. We compare our MoMA with standard sparse and dense retrieval models on BEIR. We also compare MoMA with advanced

¹https://huggingface.co/datasets/wiki_dpr

²<https://www.ncbi.nlm.nih.gov/mesh/>

Table 1: NDCG@10 on the BEIR benchmark. We also include an averaged score on datasets used by Contriever for a fair comparison. The best result each task is marked bold. An * denotes unfair comparison, as NQ is used in training for GTR. †: GenQ generated pseudo labels to train an independent model for each task. ‡: Larger models

	BM25	DPR	ANCE	T5-ANCE	coCondenser	GenQ [†]	ColBERT	Contriever	GTR _{base} [*]	GTR _{large} ^{*‡}	MoMA (T5-ANCE)	MoMA (COCO)
Parameters#	—	110M	110M	110M*2	110M	66M*18	110M	110M	110M	335M	110M*2	110M*2
TREC-COVID	0.656	0.575	0.654	0.653	0.715	0.619	0.677	0.596	0.539	0.557	0.762	0.761
BioASQ	0.465	0.232	0.306	0.322	0.318	0.398	0.474	—	0.271	0.320	0.372	0.371
NFCorpus	0.325	0.210	0.237	0.275	0.307	0.319	0.305	0.328	0.308	0.329	0.307	0.333
NQ	0.329	0.398	0.446	0.452	0.494	0.358	0.524	0.498	0.495	0.547	0.490	0.544
HotpotQA	0.603	0.371	0.456	0.487	0.566	0.534	0.593	0.638	0.535	0.579	0.539	0.589
FiQA-2018	0.236	0.274	0.295	0.294	0.285	0.308	0.317	0.329	0.349	0.424	0.320	0.329
Signal-1M	0.330	0.238	0.249	0.246	0.274	0.281	0.274	—	0.261	0.265	0.258	0.264
TREC-NEWS	0.398	0.366	0.382	0.379	0.389	0.396	0.393	—	0.337	0.343	0.413	0.453
Robust04	0.408	0.344	0.392	0.412	0.399	0.362	0.391	—	0.437	0.470	0.469	0.475
ArguAna	0.414	0.414	0.415	0.415	0.411	0.493	0.233	0.446	0.511	0.525	0.438	0.463
Touché-2020	0.367	0.208	0.240	0.312	0.190	0.182	0.202	0.230	0.205	0.219	0.271	0.299
Quora	0.789	0.842	0.852	0.836	0.863	0.830	0.854	0.865	0.881	0.890	0.847	0.843
DBPedia-entity	0.313	0.236	0.281	0.290	0.356	0.328	0.392	0.413	0.347	0.391	0.347	0.383
SCIDOCS	0.358	0.107	0.122	0.115	0.140	0.143	0.145	0.122	0.149	0.158	0.143	0.145
Fever	0.753	0.589	0.669	0.655	0.678	0.669	0.771	0.758	0.660	0.712	0.723	0.745
Climate-Fever	0.213	0.176	0.198	0.194	0.184	0.175	0.184	0.237	0.241	0.262	0.235	0.233
SciFact	0.665	0.475	0.507	0.566	0.600	0.644	0.671	0.677	0.600	0.639	0.632	0.630
CQADupStack	0.299	0.281	0.296	0.283	0.330	0.347	0.350	0.345	0.357	0.384	0.283	0.294
Contriever Sub Avg	0.437	0.368	0.408	0.416	0.438	0.425	0.445	0.466	0.442	0.471	0.453	0.471
Avg	0.428	0.352	0.391	0.399	0.417	0.410	0.431	—	0.416	0.444	0.436	0.453

Table 2: Computational analysis in the pretraining stage of different models.

Model	Pretraining Corpus	Batch Size	Training Steps
MoMA (T5-ANCE)	0	0	0
MoMA (COCO)	MARCO	128	50k
GTR	NQ, CQA	2048	800k
Contriever	CCNet	2048	500k
	Wikipedia	2048	200k

approaches that are specifically designed for zero-shot generalization. They involve techniques that are not directly comparable with this paper, including pretraining on extra data, in-domain continuous pretraining, and generating target pairs using another pretrained generative model. Besides, some baselines use larger scale language model as their backbone. We list the details of baselines in Appendix A.2.

As a plug-in-and-play method, MoMA can be combined with other techniques. We initiate MoMA on two versions of T5 model checkpoints. The primitive MoMA (T5-ANCE) is built on the original T5 model checkpoint. By comparing it with T5-ANCE, we can clearly observe the performance gain brought by MoMA. To demonstrate it can integrate techniques from other models to achieve higher performances, we apply MoMA with a better pretrained T5-based model. Following previous work (Gao and Callan, 2022; Yu et al., 2022), we continuously trained the T5 model on the MARCO corpus using a sentence-level contrastive loss, combined with the original masked language modeling loss. We then performed the same MoMA training on top of the continuously pretrained T5 checkpoint and denoted it as MoMA (COCO). Both MoMA (T5-ANCE) and MoMA (COCO) are trained iteratively with ANCE-style (Xiong et al., 2020) hard negatives, the only difference is the initialized model start point. We compare their pretraining details with other models in Table 2. Unlike previous work (Yu et al., 2022), we did not include target datasets and augmenting corpora in the COCO pretraining stage. Since MARCO contains

only 0.5M documents, it adds fewer computational overhead compared to other methods listed in the table, e.g., Contriever.

Implementation Details. For MoMA, we use the T5-base (Raffel et al., 2019) architecture (12-layer Transformer, 768 hidden size) by directly loading the checkpoint from HuggingFace³. To warm up the language model for dense retrieval, we followed (Xiong et al., 2020) to further train it using BM25 negatives for 10 epochs. After warming up, we jointly trained the two components for three episodes, each episode including three training epochs. After three joint episodes, the end retriever reaches the best performance on MSMARCO, so we select this checkpoint for evaluation. The ratio between positive and hard negative pairs is 1:7 for both models. The main hyperparameters in MoMA include the total number of grounding documents K and the attention threshold number N in Equation 10. We directly set $K=10$ and $N=5$ without any parameter tuning. More details on hyperparameters and experimental settings can be found in Appendix A.3.

5 Evaluation Results

Our experiments evaluate the zero-shot ability of MoMA, its performance with different memory sources, the influence of memory mixture learning, and the benefits of plug-in memory.

5.1 Zero-Shot Retrieval Accuracy and Efficiency

The retrieval accuracy of MoMA and baselines are listed in Table 1. Besides baselines of similar parameter count, we also include larger models (GTR_{large}) or those using multiple vectors per document (ColBERT). MoMA (COCO) shows the strongest zero-shot accuracy against previous state-of-the-art methods that do continuous contrastive pretraining (coCondenser), generate pseudo labels (GenQ), or consume additional training signals

³<https://huggingface.co/t5-base>

Table 3: Efficiency of MoMA search and training.

Operation	Offline	Online
BM25 Index Build	1.8h	—
BM25 Retrieval Per Query	—	43ms
MoMA Inference		
Encoding of Corpus/Per Doc	1.5h/4.5ms	—
Query Encoding	—	55ms
ANN Retrieval (batched q)	—	9ms
Dense Retrieval Total	—	64ms
MoMA Training		
Encoding of Corpus/Per Doc	1.5h/4.5ms	—
ANN Index Build	10s	—
Neg Construction Per Batch (32 queries)	45ms	—
Back Propagation Per Batch (32 queries)	330ms	—

in both continuous pretraining and finetuning phrases (GTR_{base}). MoMA (T5-ANCE) also achieved nearly comparable zero-shot accuracy against larger models like GTR_{large}, and ColBERT, which scales up the number of vectors per documents (one per token). This confirms that retrieval-augmentation provides another path to improve language models’ generalization ability besides scaling up. MoMA (T5-ANCE) also outperforms T5-ANCE, which MoMA (T5-ANCE) uses as a subroutine for retrieval augmentation, on all but one retrieval task, showing the robustly improved generalization ability from plug-in mixture of memory.

We evaluate the efficiency of MoMA in two stages: offline model training and online inference. In offline training from Table 2, MoMA (T5-ANCE) is **significantly cheaper** than other methods as we do not require pretraining on large external corpora, which saves hundreds of hours training time. MoMA (COCO) additionally pretrain on MARCO for 50k steps, which is far fewer than the other compared methods. In online inference, similar with other retrieval enhanced language models, MoMA imposes a necessary cost of retrieval augmented model upon the baseline T5-ANCE. We further provide detailed efficiency analysis on MoMA in Table 3. The online latency is measured on one query and 100 retrieved documents. Due to the query augmentation, query encoding is more costly and takes about 55ms per query. Even with the augmentation cost, the full dense retrieval total online inference cost is 64ms, only slightly above the BM25 retrieval latency. The ANN retrieval is very efficient, only takes 9ms. In addition, the complexity of ANN retrieval is sub-linear to the corpus size, in most ANN framework such as FAISS. Thus the extra round of ANN retrieval operation in MoMA is not the bottleneck even when the size of memory mixture scales up.

5.2 Performance with Different Memories

Table 4 evaluates how MoMA behaves under different combinations of external memories. Compared with the MoMA (T5-ANCE), MoMA (COCO) may lean towards the MARCO corpus since it is continuously pretrained on it. To avoid unfair comparison between MARCO and other corpora, we choose MoMA (T5-ANCE) as the *Full* model version for ablation studies. Unsurpris-

ingly, using a single out-of-domain memory for retrieval augmentation does not help, for example, even though MARCO is the source domain corpus, solely grounding on it reduces zero-shot accuracy. MeSH as the sole augmenting corpus also lowers performance, even on some medical retrieval tasks such as BioASQ. Interestingly, when we expand the memory to include MARCO, Wiki, and MeSH, but keep the target corpus excluded (*w/o Target*), MoMA exhibits better accuracy compared to the no-memory T5-ANCE. Our conclusion is that more memory sources achieves better generalization, especially when no target domain information is available.

In the *Full* setting, the 3-memory mixture of MARCO, Wiki, and MeSH is jointly learned with final task at training time. At test time, MARCO is swapped out for the target corpus. The *Full* improves zero-shot accuracy over both the *w/o Target* setting (where the target corpus is excluded at test time), and the *w/o Learning* setting (wherein the augmentation component is not learned). As expected, plugging in the target corpus at test time is the most valuable source of generalization power. It is also the most realistic, as access to the target corpus may only be available at testing time.

5.3 Effect of Memory Mixture Learning

To study the effect of our joint learning mechanism on the memory mixture, we compare it with recent state-of-the-art Attention Distillation (ADist), which is first used in Izacard and Grave (2020a) and recently updated in a parallel work Izacard et al. (2022). It jointly trains the augmentation model using attention scores from the end language model as pseudo-labels. We also enrich ADist with relevance labels from MARCO for more direct supervision, which was shown to be effective in distilling a dense retriever from stronger cross-encoder ranking model (Hofstätter et al., 2021). Similar to previous section, to exclude the performance gain brought by contrastive pretraining, we choose MoMA (T5-ANCE) as our own method for comparison. The performances of these joint learning methods are listed in Table 5. We pick six BEIR tasks whose domains are closely related to the augmentation corpora: TREC-COVID, BIOASQ, and NFCorpus are medical search and closely related to MeSH. NQ, HotpotQA, and FEVER are all Wikipedia based. The results show that ADist, either standalone or enriched with MARCO labels, does not improve the final accuracy compared to using a supervised dense retriever as the augmentation component without joint learning. The main difference is that the supervised retriever has been trained effectively using hard negative sampling (Xiong et al., 2020). Jointly learning using soft labels without hard negatives downgraded the augmentation accuracy. Hence, MoMA is a simple technique to learn the end task signals via the attention scores together with hard negatives, which improves quality over a supervised retriever alone.

To further illustrate the joint training process, we track the attention scores of documents from different

Table 4: NDCG@10 of MoMA (T5-ANCE) under different memory compositions: no memory, single memory, and a mixture of memories. *w/o Learning* uses the end retriever to select augmenting documents without use of an augmentation component. *w/o Target* excludes the target from memory.

	No Memory	Single Memory				Memory Mixture		
	T5-ANCE	MARCO	Wiki	MeSH	Target	w/o Learning	w/o Target	Full
TREC-COVID	0.653	0.576	0.592	0.669	0.731	<u>0.759</u>	0.664	0.762
BioASQ	0.322	0.247	0.262	0.219	<u>0.361</u>	0.359	0.271	0.372
NFCorpus	0.275	0.295	0.302	0.282	0.319	<u>0.317</u>	0.301	0.307
NQ	0.452	0.472	0.486	0.393	0.483	0.510	0.484	<u>0.490</u>
HotpotQA	0.487	0.481	0.519	0.462	<u>0.538</u>	0.539	0.520	0.539
FiQA-2018	0.294	0.296	0.286	0.280	0.320	<u>0.304</u>	0.285	0.320
Signal-1M	0.246	0.239	0.225	0.238	<u>0.250</u>	0.248	0.240	0.258
TREC-NEWS	0.379	0.381	0.391	0.372	0.416	0.410	0.398	<u>0.413</u>
Robust04	0.412	0.435	0.443	0.428	0.483	0.446	0.452	<u>0.469</u>
ArguAna	0.415	<u>0.439</u>	0.438	0.442	<u>0.439</u>	0.427	0.438	0.438
Touché-2020	<u>0.312</u>	0.281	0.281	0.252	0.331	0.275	0.272	0.271
Quora	<u>0.836</u>	0.809	0.798	0.835	0.781	0.813	0.812	0.847
DBPedia-entity	0.290	0.340	0.341	0.287	0.335	0.331	<u>0.342</u>	0.347
SCIDOCS	0.115	0.128	0.121	0.130	0.146	0.134	0.127	<u>0.143</u>
Fever	0.655	0.663	<u>0.735</u>	0.610	0.694	0.718	0.737	0.723
Climate-Fever	0.194	0.231	<u>0.238</u>	0.231	0.228	0.222	0.240	0.235
SciFact	0.566	0.583	0.587	0.585	<u>0.624</u>	0.618	0.598	0.632
CQADupStack	0.283	0.207	0.218	0.203	0.283	<u>0.235</u>	0.215	0.283
Avg	0.399	0.395	0.403	0.384	<u>0.431</u>	0.426	0.411	0.436

Table 5: Zero-shot Performances of different distillation methods. We observe consistent trend on all BEIR datasets. We present results on 6 representative datasets from Wikipedia or medical domains.

Distillation Method	TREC-COVID	BIOASQ	NFCorpus	NQ	HotpotQA	FEVER	Avg
Soft Attention Distill							
ADist (Izacard et al., 2022)	0.609	0.185	0.227	0.351	0.387	0.615	0.396
ADist + MSMARCO rel	0.664	0.220	0.255	0.397	0.394	0.624	0.426
w/o Distilling (Fixed)	0.741	0.361	0.301	0.472	0.513	0.684	0.512
MoMA (T5-ANCE)	0.762	0.372	0.307	0.490	0.539	0.723	0.532

memory sources as well as their ratio in the augmentation set in Figure 2. We also split MARCO documents by whether they are labeled as **Relevant (Rel)** for the corresponding query.

Firstly, MoMA learns to increasingly attend to, and retrieve, relevant documents from the memory mixture throughout training. In Figure 2a, more attention is paid to MARCO Relevant documents than to any other type in the memory. Although the number of MARCO Relevant documents is not significant as a percentage of the augmenting set in Figure 2c, a query level analysis confirms that percentage of queries having at least one relevant document in the augmenting set increases from 46% in Epi-0 to 62% in Epi-2.

This apparent discrepancy can be explained by the fact that MARCO has only one relevant label per query on average, leaving plenty of room for other types of documents to be included in the augmenting set.

Secondly, the amount of attention paid to certain types of documents by MoMA is positively correlated with their representation in the augmenting set. This confirms that the joint learning effectively conveys the feedback signals from the end model to the augmentation component. For instance, in Figure 2a, MoMA pays a high level of attention to MARCO Other documents, a signal reflected in the composition of its augmentation set in Figure 2c. Even though MARCO Other doc-

uments were not labeled relevant for the query, they can still prove to be valuable as an augmenting document because they may contain partial information that helps query understanding (Lavrenko and Croft, 2017) or it was simply not annotated in MARCO’s sparse labels (Bajaj et al., 2016). In comparison, the correlation of the two in ADist is weak as the model seems to include 60% augmenting documents from MeSH, far greater than the fraction of medical queries in MARCO.

5.4 Generalization of Plug-In Memory

In the previous section, we observed how MoMA learns to attend to, and retrieve, informative documents from memories on which it was trained. In this section, we examine the zero-shot behavior of MoMA (T5-ANCE) on new corpora plugged-in at test time (keeping Wiki and MeSH as before).

Figure 3 compares documents from the plugged-in target versus the remaining memory mixture in terms of membership in the augmenting set (Doc Ratio) and attention. Again, on all tasks, MoMA (T5-ANCE) heavily attends to – and successfully retrieves – in-domain documents, even if those in-domain documents were only just plugged in. This confirms that the augmentation model achieves the zero-shot ability to capture relevant information from unseen corpora.

In the medical domain, the model pays more attention




Figure 2: Grounding component breakdown for different distillation methods in each learning iteration. We display the regularized doc and att. score ratio of documents from different augmentation sources.




Figure 3: The inclusion of Plug-In memory during testing (grouped by the Wiki and Medical domains).

to MeSH documents, especially on TREC-Covid task since MeSH includes high quality updated information related to COVID-19. Wikipedia documents received more attention on the Wiki-centric tasks like FEVER, as expected. Some tasks may need a small amount of precise information from Wikipedia to answer the detailed question, e.g. in HotpotQA. Similar with the training process, there is a non-trivial correspondence between attention score of a memory and its membership in the augmentation set.

5.5 Case Studies

Table 6 shows examples of how augmenting documents chosen by MoMA can provide valuable contextual information for the query. The first example is a training query from MARCO, where the augmenting documents help disambiguate the query word "rating". In the second one, documents from the official Wiki and HotpotQA's Wiki corpus are descriptions of the two entities in HotpotQA's comparison question. It illustrates how MoMA provides more comprehensive augmentation by incorporating information from different sources.

6 Conclusion

In this paper we propose a new plug-in mixture-of-memory mechanism for the retrieval augmented language models to improve their zero-shot ability on the dense retrieval task. To learn the memory mixture we develop a new joint learning approach that trains the augmentation component using the positive signals from the end task, the language model's attention scores, and

Table 6: MoMA retrieves augmenting documents during training (Marco) and testing (BEIR).

Queries	Augmentation Docs
Training	
[Marco] What is hotel transylvania rated	[Marco] Why is Hotel Transylvania 2 rated PG? It is rated PG for some scary images, action and rude humor. [Wiki] Another review aggregate calculated an average score of 47 out of 100, indicating "mixed or average reviews".
Zero-Shot Testing	
[HotpotQA] Were Scott Derrickson and Ed Wood of the same nationality?	[Wiki] Scott Derrickson (born July 16, 1966) is an American director, screenwriter and producer. [HotpotQA] Edward Davis Wood Jr. (October 10, December 10, 1978) was an American filmmaker, actor, writer, producer, and director.

hard negatives retrieved from the mixture of augmentation corpora. This leads to our final model MoMA (T5-ANCE) and MoMA (COCO) that achieve strong zero-shot accuracy on 18 retrieval tasks included in BEIR. Our analysis shows the importance of augmenting with diverse memory sources and in-domain information for robust generalization. We also share our observations and insights on how the model learns to leverage the augmentation information from multiple corpora during training and testing. We hope our findings and illustrations can inspire more future research in better augmenting language models, to provide other alternatives to achieve generalization ability beyond solely relying on model scale.

Limitations

Although MoMA (T5-ANCE) and MoMA (COCO) achieve strong zero-shot performances, we mainly verify their efficacy from the empirical performances on BEIR tasks, where the target corpora, Wiki and MARCO serve as readily available retrieval sources. In a real-world scenario, the grounding corpora usually need to be customized according to query domains and user needs. Thus, how to choose effective grounding corpora and efficiently evaluate their relative contribution remain an open problem. These analyses will go beyond our empirical settings and reveal a wider application scenario of MoMA.

Ethics Statement

All data in this study are publicly available and used under ethical considerations. Text and figures in the paper are used for illustration only, they do not represent the ethical attitude of the authors.

References

- Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. 2016. MS MARCO: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268*.
- Emily M Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. 2021. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, pages 610–623.
- Alexander Bondarenko, Maik Fröbe, Meriem Beloucif, Lukas Gienapp, Yamen Ajjour, Alexander Panchenko, Chris Biemann, Benno Stein, Henning Wachsmuth, Martin Potthast, and Matthias Hagen. 2020. [Overview of Touché 2020: Argument Retrieval](#). In *Working Notes Papers of the CLEF 2020 Evaluation Labs*, volume 2696 of *CEUR Workshop Proceedings*.
- Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, et al. 2022. Improving language models by retrieving from trillions of tokens. In *International Conference on Machine Learning*, pages 2206–2240. PMLR.
- Vera Boteva, Demian Gholipour, Artem Sokolov, and Stefan Riezler. 2016. A full-text learning to rank dataset for medical information retrieval. In *European Conference on Information Retrieval*, pages 716–722. Springer.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Claudio Carpineto and Giovanni Romano. 2012. A survey of automatic query expansion in information retrieval. *Acm Computing Surveys (CSUR)*, 44(1):1–50.
- Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. 2017. Reading Wikipedia to Answer Open-Domain Questions. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics*, pages 1870–1879.
- Arman Cohan, Sergey Feldman, Iz Beltagy, Doug Downey, and Daniel Weld. 2020. [SPECTER: Document-level representation learning using citation-informed transformers](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 2270–2282, Online. Association for Computational Linguistics.
- Thomas Diggelmann, Jordan Boyd-Graber, Jannis Bulian, Massimiliano Ciaramita, and Markus Leippold. 2020. CLIMATE-FEVER: A dataset for verification of real-world climate claims. *arXiv preprint arXiv:2012.00614*.
- Thibault Formal, Benjamin Piwowarski, and Stéphane Clinchant. 2021. Splade: Sparse lexical and expansion model for first stage ranking. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2288–2292.
- Luyu Gao and Jamie Callan. 2022. Unsupervised corpus aware language model pre-training for dense passage retrieval. In *ACL 2022*.
- Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Ming-Wei Chang. 2020. REALM: Retrieval-augmented language model pre-training. In *ICML*.
- Faegheh Hasibi, Fedor Nikolaev, Chenyan Xiong, Krisztian Balog, Svein Erik Bratsberg, Alexander Kotov, and Jamie Callan. 2017. [DBpedia-Entity v2: A test collection for entity search](#). In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '17, page 1265–1268, New York, NY, USA. Association for Computing Machinery.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. 2022. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*.
- Sebastian Hofstätter, Sheng-Chieh Lin, Jheng-Hong Yang, Jimmy Lin, and Allan Hanbury. 2021. [Efficiently teaching an effective dense retriever with balanced topic aware sampling](#). In *Proceedings of SIGIR 2021*, pages 113–122.

- Sebastian Hofstätter, Sheng-Chieh Lin, Jheng-Hong Yang, Jimmy Lin, and Allan Hanbury. 2021. [Efficiently teaching an effective dense retriever with balanced topic aware sampling](#). In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, page 113–122. Association for Computing Machinery.
- Doris Hoogeveen, Karin M. Verspoor, and Timothy Baldwin. 2015. [CQADupStack: A benchmark data set for community question-answering research](#). In *Proceedings of the 20th Australasian Document Computing Symposium, ADCS '15*, New York, NY, USA. Association for Computing Machinery.
- Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. 2021. Towards unsupervised dense information retrieval with contrastive learning. *arXiv preprint arXiv:2112.09118*.
- Gautier Izacard and Edouard Grave. 2020a. [Distilling knowledge from reader to retriever for question answering](#). *arXiv preprint arXiv:2012.04584*.
- Gautier Izacard and Edouard Grave. 2020b. [Leveraging passage retrieval with generative models for open domain question answering](#).
- Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. 2022. Few-shot learning with retrieval augmented language models. *arXiv preprint arXiv:2208.03299*.
- Jeff Johnson, Matthijs Douze, and Hervé Jégou. 2019. Billion-scale similarity search with gpus. *IEEE Transactions on Big Data*, 7(3):535–547.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.
- Vladimir Karpukhin, Barlas Öğuz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. *arXiv preprint arXiv:2004.04906*.
- Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. 2019. Generalization through memorization: Nearest neighbor language models. *arXiv preprint arXiv:1911.00172*.
- Omar Khattab and Matei Zaharia. 2020a. Colbert: Efficient and effective passage search via contextualized late interaction over bert. In *Proceedings of the 43rd International ACM SIGIR conference on research and development in Information Retrieval*, pages 39–48.
- Omar Khattab and Matei Zaharia. 2020b. [Colbert: Efficient and effective passage search via contextualized late interaction over bert](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, page 39–48, New York, NY, USA. Association for Computing Machinery.
- Yubin Kim. 2022. Applications and future of dense retrieval in industry. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 3373–3374.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019. [Natural questions: A benchmark for question answering research](#). *Transactions of the Association for Computational Linguistics*, 7:452–466.
- Victor Lavrenko and W Bruce Croft. 2017. Relevance-based language models. In *ACM SIGIR Forum*, volume 51, pages 260–267. ACM New York, NY, USA.
- Patrick Lewis, Ethan Perez, Aleksandara Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *arXiv preprint arXiv:2005.11401*.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A Robustly Optimized BERT Pretraining Approach. *arXiv preprint arXiv:1907.11692*.
- Ilya Loshchilov and Frank Hutter. 2019. [Decoupled weight decay regularization](#). In *International Conference on Learning Representations*.
- Jing Lu, Gustavo Hernandez Abrego, Ji Ma, Jianmo Ni, and Yinfei Yang. 2021. [Multi-stage training with improved negative contrast for neural passage retrieval](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6091–6103, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Macedo Maia, Siegfried Handschuh, André Freitas, Brian Davis, Ross McDermott, Manel Zarrouk, and Alexandra Balahur. 2018. [WWW'18 open challenge: Financial opinion mining and question answering](#). In *Companion Proceedings of the The Web Conference 2018, WWW '18*, page 1941–1942, Republic and Canton of Geneva, CHE. International World Wide Web Conferences Steering Committee.
- Arvind Neelakantan, Tao Xu, Raul Puri, Alec Radford, Jesse Michael Han, Jerry Tworek, Qiming Yuan, Nikolas Tezak, Jong Wook Kim, Chris Hallacy, et al. 2022. Text and code embeddings by contrastive pre-training. *arXiv preprint arXiv:2201.10005*.

- Jianmo Ni, Gustavo Hernandez Abrego, Noah Constant, Ji Ma, Keith Hall, Daniel Cer, and Yinfei Yang. 2022. Sentence-t5: Scalable sentence encoders from pre-trained text-to-text models. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 1864–1874.
- Jianmo Ni, Chen Qu, Jing Lu, Zhuyun Dai, Gustavo Hernández Ábrego, Ji Ma, Vincent Y Zhao, Yi Luan, Keith B Hall, Ming-Wei Chang, et al. 2021. Large dual encoders are generalizable retrievers. *arXiv preprint arXiv:2112.07899*.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2019. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32.
- Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vladimir Karpukhin, Jean Mailard, et al. 2020. Kilt: a benchmark for knowledge intensive language tasks. *arXiv preprint arXiv:2009.02252*.
- Yingqi Qu, Yuchen Ding, Jing Liu, Kai Liu, Ruiyang Ren, Wayne Xin Zhao, Daxiang Dong, Hua Wu, and Haifeng Wang. 2021. [RocketQA: An optimized training approach to dense passage retrieval for open-domain question answering](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5835–5847, Online. Association for Computational Linguistics.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2019. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*.
- Adam Roberts, Colin Raffel, and Noam Shazeer. 2020. How much knowledge can you pack into the parameters of a language model? In *EMNLP*.
- Stephen Robertson, Hugo Zaragoza, et al. 2009. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389.
- Shaden Smith, Mostofa Patwary, Brandon Norick, Patrick LeGresley, Samyam Rajbhandari, Jared Casper, Zhun Liu, Shrimai Prabhunoye, George Zerveas, Vijay Korthikanti, et al. 2022. Using deep-speed and megatron to train megatron-turing nlg 530b, a large-scale generative language model. *arXiv preprint arXiv:2201.11990*.
- Ian Soboroff, Shudong Huang, and Donna Harman. 2018. Trec 2018 news track overview.
- Emma Strubell, Ananya Ganesh, and Andrew McCallum. 2020. Energy and policy considerations for modern deep learning research. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 13693–13696.
- Axel Suarez, Dyaa Albakour, David Corney, Miguel Martinez, and José Esquivel. 2018. A data collection for evaluating the retrieval of related tweets to news articles. In *European Conference on Information Retrieval*, pages 780–786. Springer.
- Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021a. BEIR: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. *arXiv preprint arXiv:2104.08663*.
- Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021b. BEIR: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. *arXiv preprint arXiv:2104.08663*.
- James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. 2018. [FEVER: a large-scale dataset for fact extraction and VERification](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 809–819, New Orleans, Louisiana. Association for Computational Linguistics.
- George Tsatsaronis, Georgios Balikas, Prodromos Malakasiotis, Ioannis Partalas, Matthias Zschunke, Michael R Alvers, Dirk Weissenborn, Anastasia Krithara, Sergios Petridis, Dimitris Polychronopoulos, et al. 2015. An overview of the BIOASQ large-scale biomedical semantic indexing and question answering competition. *BMC bioinformatics*, 16(1):1–28.
- Ellen Voorhees, Tasmee Alam, Steven Bedrick, Dina Demner-Fushman, William R. Hersh, Kyle Lo, Kirk Roberts, Ian Soboroff, and Lucy Lu Wang. 2021. [TREC-COVID: Constructing a pandemic information retrieval test collection](#). *SIGIR Forum*, 54(1).
- Ellen M Voorhees et al. 2004. Overview of the trec 2004 robust retrieval track. In *Trec*, pages 69–77.
- Henning Wachsmuth, Shahbaz Syed, and Benno Stein. 2018. [Retrieval of the best counterargument without prior topic knowledge](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 241–251, Melbourne, Australia. Association for Computational Linguistics.
- David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. [Fact or fiction: Verifying scientific claims](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7534–7550, Online. Association for Computational Linguistics.
- Kexin Wang, Nandan Thakur, Nils Reimers, and Iryna Gurevych. 2022. [GPL: Generative pseudo labeling for unsupervised domain adaptation of dense retrieval](#). In *Proceedings of the 2022 Conference of the North*

- American Chapter of the Association for Computational Linguistics: Human Language Technologies*, Seattle, United States. Association for Computational Linguistics.
- Yining Wang, Liwei Wang, Yuanzhi Li, Di He, Wei Chen, and Tie-Yan Liu. 2013. A theoretical analysis of ndcg ranking measures. In *Proceedings of the 26th annual conference on learning theory (COLT 2013)*, volume 8, page 6. Citeseer.
- Guillaume Wenzek, Marie-Anne Lachaux, Alexis Conneau, Vishrav Chaudhary, Francisco Guzmán, Armand Joulin, and Edouard Grave. 2020. [CCNet: Extracting high quality monolingual datasets from web crawl data](#). In *Proceedings of the 12th Language Resources and Evaluation Conference*, pages 4003–4012, Marseille, France. European Language Resources Association.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. [Transformers: State-of-the-art natural language processing](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.
- Ji Xin, Chenyan Xiong, Ashwin Srinivasan, Ankita Sharma, Damien Jose, and Paul Bennett. 2022. [Zero-shot dense retrieval with momentum adversarial domain invariant representations](#). In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 4008–4020, Dublin, Ireland. Association for Computational Linguistics.
- Ji Xin, Chenyan Xiong, Ashwin Srinivasan, Ankita Sharma, Damien Jose, and Paul N Bennett. 2021. Zero-shot dense retrieval with momentum adversarial domain invariant representations. *arXiv preprint arXiv:2110.07581*.
- Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul Bennett, Junaid Ahmed, and Arnold Overwijk. 2020. Approximate nearest neighbor negative contrastive learning for dense text retrieval. *arXiv preprint arXiv:2007.00808*.
- Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. 2018. HotpotQA: A Dataset for Diverse, Explainable Multi-hop Question Answering. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 2369–2380.
- HongChien Yu, Chenyan Xiong, and Jamie Callan. 2021. Improving query representations for dense retrieval with pseudo relevance feedback. *arXiv preprint arXiv:2108.13454*.
- Yue Yu, Chenyan Xiong, Si Sun, Chao Zhang, and Arnold Overwijk. 2022. Coco-dr: Combating distribution shifts in zero-shot dense retrieval with contrastive and distributionally robust learning. *arXiv preprint arXiv:2210.15212*.
- Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. 2022. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*.
- Chen Zhao, Chenyan Xiong, Jordan Boyd-Graber, and Hal Daumé III. 2021. [Distantly-supervised evidence retrieval enables question answering without evidence annotation](#). *arXiv preprint arXiv:2110.04889*.
- Zexuan Zhong, Tao Lei, and Danqi Chen. 2022. Training language models with memory augmentation. *arXiv preprint arXiv:2205.12674*.

A Appendix

A.1 Datasets Details

Evaluation Datasets Target domain datasets used in our experiments are collected in the BEIR benchmark (Thakur et al., 2021b)⁴ and include the following domains:

- Open-domain Question Answering (QA): HotpotQA (Yang et al., 2018), NQ (Kwiatkowski et al., 2019), and FiQA (Maia et al., 2018).
- Bio-Medical Information Retrieval: TREC-COVID (Voorhees et al., 2021), NFCorpus (Boteva et al., 2016), and BioASQ (Tsatsaronis et al., 2015).
- Argument Retrieval: Webis-Touché2020 (Bondarenko et al., 2020) and ArguAna (Wachsmuth et al., 2018).
- News Retrieval: TREC-NEWS (Soboroff et al., 2018) and Robust04 (Voorhees et al., 2004).
- Tweet Retrieval: Signal-1m (Suarez et al., 2018).
- Duplicate Question Retrieval: Quora (Thakur et al., 2021b) and CQADupStack (Hoogeveen et al., 2015).
- Entity Retrieval: DBPedia (Hasibi et al., 2017)
- Citation Prediction: SCIDOCS (Cohan et al., 2020)
- Fact Checking: SciFact (Wadden et al., 2020), FEVER (Thorne et al., 2018), and ClimateFEVER (Diggelmann et al., 2020)

We list the statistics of the BEIR benchmark in Table 7.

Augmenting Corpora Corpus size We first introduce more details on how we preprocessed the Medical Subject Headings (MeSH) Database. We select text information from the Qualifier Record Set and Descriptor Record Set. Each set contains multiple <Concept> elements, which is composed of three sub-elements, i.e., <ConceptName>, <ScopeNote> and <TermList>. Among the sub-elements, <ScopeNote> is the major textual information source, which is usually a short description to a medical term or phenomenon. We directly consider each <ScopeNote> as a document entry and concatenate it with corresponding <ConceptName>.

We list the statistics of the augmenting corpora in Table 8.

A.2 Baselines

We use the baselines from the current BEIR leaderboard (Thakur et al., 2021b) and recent papers. These baselines can be divided into four groups: dense retrieval, dense retrieval with generated queries⁵, lexical retrieval and late interaction.

⁴<https://github.com/beir-cellar/beir>

⁵We separate them from dense retrieval since they usually rely on Seq2seq models to generate pseudo query-document pairs, and they train a model for each dataset *independently* instead of using a single model for all datasets.

Dense Retrieval For dense retrieval, the baselines are the same dual-tower model as ours. We consider **DPR** (Karpukhin et al., 2020), **ANCE** (Xiong et al., 2020), **T5-ANCE**, **coCondenser** (Gao and Callan, 2022) and one recently-proposed model **GTR** (Ni et al., 2021) with different size configuration in this paper.

- **DPR** uses a single BM25 retrieval example and in-batch examples as hard negative examples to train the model. Different from the original paper (Thakur et al., 2021b) that train the DPR on QA datasets, we train DPR on MS MARCO (Bajaj et al., 2016) Dataset for *fair comparison*. Notice that this also lead to better results according to Xin et al. (2022).
- **ANCE** constructs hard negative examples from an ANN index of the corpus. The hard negative training instances are updated in parallel during fine-tuning of the model. The model is a RoBERTa (Liu et al., 2019) model trained on MS MARCO for 600k steps.
- **T5-ANCE** Different with default ANCE setting, we replace the backbone language model RoBERTa with T5-base. All the other model settings are the same with the original ANCE. We include this baseline because as a subroutine for MoMA, it could be viewed as an ablation without memory augmentation. We can directly observe the impact of plug-in mixture of memory by comparing T5-ANCE with MoMA.
- **coCondenser** is a continuous pre-trained model based on BERT, with the equivalent amount of parameters to BERT-base. It enhances the representation ability of [CLS] token by changing the connections between different layers of Transformer blocks. Fine-tuning of coCondenser uses BM25 and self-mined negatives.
- **Contriever** conducts unsupervised contrastive pre-training with data augmentations and momentum queues on Wikipedia and the larger CC-Net (Wenzek et al., 2020) corpora for 500k steps.
- **GTR** initializes the dual encoders from the T5 models (Raffel et al., 2019). It is first pre-trained on Community QA⁶ with 2 billion question-answer pairs then fine-tuned on NQ and MS Marco dataset. In addition, they use the hard negatives released by RocketQA (Qu et al., 2021) when finetuning with MS Marco data and the hard negatives release by (Lu et al., 2021) for Natural Questions. **GTR**_{base} leverages the same T5-base model as MoMA, while **GTR**_{large} is based on T5-large, which is not directly comparable to our method as it triples the parameters.

Dense Retrieval with Generated Queries **GenQ** first fine-tunes a T5-base (Raffel et al., 2019) model on MS MARCO for 2 epochs and then generate 5 queries

⁶Unfortunately, this corpus has not been released by the authors.

Table 7: Statistics of datasets in the BEIR benchmark. The table is taken from the original BEIR benchmark paper (Thakur et al., 2021b).

Split (\rightarrow)				Train	Dev	Test			Avg. Word Lengths		
Task (\downarrow)	Domain (\downarrow)	Dataset (\downarrow)	Title	Relevancy	#Pairs	#Query	#Query	#Corpus	Avg. D / Q	Query	Document
Passage-Retrieval	Misc.	MS MARCO	\times	Binary	532,761	—	6,980	8,841,823	1.1	5.96	55.98
Bio-Medical Information Retrieval (IR)	Bio-Medical	TREC-COVID	\checkmark	3-level	—	—	50	171,332	493.5	10.60	160.77
		NFCorpus	\checkmark	3-level	110,575	324	323	3,633	38.2	3.30	232.26
		BioASQ	\checkmark	Binary	32,916	—	500	14,914,602	4.7	8.05	202.61
Question Answering (QA)	Wikipedia	NQ	\checkmark	Binary	132,803	—	3,452	2,681,468	1.2	9.16	78.88
		HotpotQA	\checkmark	Binary	170,000	5,447	7,405	5,233,329	2.0	17.61	46.30
		FiQA-2018	\times	Binary	14,166	500	648	57,638	2.6	10.77	132.32
Tweet-Retrieval	Twitter	Signal-1M (RT)	\times	3-level	—	—	97	2,866,316	19.6	9.30	13.93
News Retrieval	News	TREC-NEWS	\checkmark	5-level	—	—	57	594,977	19.6	11.14	634.79
		Robust04	\times	3-level	—	—	249	528,155	69.9	15.27	466.40
Argument Retrieval	Misc.	ArguAna	\checkmark	Binary	—	—	1,406	8,674	1.0	192.98	166.80
		Touché-2020	\checkmark	3-level	—	—	49	382,545	19.0	6.55	292.37
Duplicate-Question Retrieval	StackEx.	CQADupStack	\checkmark	Binary	—	—	13,145	457,199	1.4	8.59	129.09
		Quora	\times	Binary	—	5,000	10,000	522,931	1.6	9.53	11.44
Entity-Retrieval	Wikipedia	DBPedia	\checkmark	3-level	—	67	400	4,635,922	38.2	5.39	49.68
Citation-Prediction	Scientific	SCIDocs	\checkmark	Binary	—	—	1,000	25,657	4.9	9.38	176.19
Fact Checking	Wikipedia	FEVER	\checkmark	Binary	140,085	6,666	6,666	5,416,568	1.2	8.13	84.76
		Climate-FEVER	\checkmark	Binary	—	—	1,535	5,416,593	3.0	20.13	84.76
		SciFact	\checkmark	Binary	920	—	300	5,183	1.1	12.37	213.63

Table 8: Statistics of the augmenting corpora.

Datasets	Corpus Size	Avg. Doc Length
MS MARCO	502,939	56.0
MeSH	32,326	16.8
Wiki	21,015,324	100.0

for each passage as additional training data for the target domain to continue to fine-tune the TAS-B (Hofstätter et al., 2021) model.

Lexical Retrieval Lexical retrieval is a score function for token matching calculated between two high-dimensional sparse vectors with token weights. **BM25** (Robertson et al., 2009) is the most commonly used lexical retrieval function. We use the BM25 results reported in Thakur et al. (2021b) for comparison.

Late Interaction We also consider a late interaction baseline, namely **ColBERT** (Khattab and Zaharia, 2020b). The model computes multiple contextualized embeddings for each token of queries and documents, and then uses a maximum similarity function to retrieve relevant documents. This type of matching requires significantly more disk space for indexes and has a higher latency.

A.3 Detailed Experimental Settings and hyperparameters

Our implementation uses PyTorch (Paszke et al., 2019) with Hugging Face Transformers (Wolf et al., 2020). We optimize the model using AdamW (Loshchilov and Hutter, 2019) with a peak learning rate at 5e-6, weight decay of 0.01, and linear learning rate decay. The global batch size is set to 256. The maximum length of query and passage are set to 32 and 128 respectively. We summarize all hyperparameter settings in Table 9. The model is trained with 8 Nvidia A100 80GB GPUs and

Table 9: The hyperparameters of MoMA.

Hyperparameters	Settings
Grounding document number	10
Attention threshold number	5
Negative mining depth	200
Global batch size (query size per batch)	256
Positive number per query	1
Negative number per query	7
Peak learning rate	5e-6
Learning rate decay	0.01
Optimizer	AdamW
Scheduler	Linear
MARCO Maximum query length	32
MARCO Maximum document length	128

FP16 mixed-precision training. The total running time is 6.6 hrs for three episodes of augmentation component training and 6.3 hrs for end retriever training. We detail the training time of each episode in Table 10.

When evaluating on the BEIR benchmark, we follow the setting in GTR (Ni et al., 2021), which use sequences of 64 tokens for the questions and 512 for the documents in all datasets except Trec-News, Robust-04 and ArguAna. In particular, we set the document length to 768 for Trec-News and Robust-04. For ArguAna, we set both question and document length to 128. The above length setting is in accordance to the average query and document lengths in these datasets.

Table 10: Training time for MoMA with three training episodes. We use 8 Nvidia A100 80GB GPUs with FP16 mixed-precision training.

Stage	Augmentation Component	End Retriever
Epi-1	0.8h	1.5h
Epi-2	0.8h	1.5h
Epi-3	0.8h	1.5h
Index refresh	1.4h	0.6h
Refresh number	3	3
Overall	6.6h	6.3h