Dynamic Probabilistic Reliable Broadcast

Veronika Anikina ⊠ ITMO University

João Paulo Bezerra 🖂 LTCI, Télécom Paris, Institut Polytechnique de Paris

Petr Kuznetsov 🖂 LTCI, Télécom Paris, Institut Polytechnique de Paris

Liron Schiff ⊠ Akamai

Stefan Schmid ⊠ Technische Universität Berlin

— Abstract

Byzantine reliable broadcast is a primitive that allows a set of processes to agree on a message broadcast by a dedicated source process, even when some of them are malicious (Byzantine). It guarantees that no two correct processes deliver different messages, and if a message is delivered by a correct process, every correct process eventually delivers one. The primitive is known not to scale, as it requires $\Omega(n^2)$ message exchanges, where *n* is the number of system members. The quadratic cost can be explained by the inherent need for every process to relay a message to every other process.

In this paper, we explore ways to overcome this limitation, by casting the problem to the probabilistic setting. We propose a solution in which every broadcast message is validated by a small set of *witnesses*, which allows us to maintain low latency and small communication complexity. In order to tolerate the *slow adaptive adversary*, we dynamically select witnesses through a novel use of locality-preserving hash functions. Our simulations demonstrate significant scalability gains of our solution with respect to existing protocols.

2012 ACM Subject Classification Theory of computation \rightarrow Design and analysis of algorithms

Keywords and phrases Reliable broadcast; probabilistic algorithms; optimistic algorithms; cryptocurrencies; accountability

Digital Object Identifier 10.4230/LIPIcs...

1 Introduction

Modern distributed computing systems are expected to run in extremely harsh conditions. Besides communicating over weakly synchronous, or even purely asynchronous communication networks, the processes performing distributed computations may be subject to failures: from hardware crashes to security attacks or malicious behavior. In these environments, ensuring that a system never produces *wrong* outputs (*safety* properties) and, at the same time, makes progress by producing *some* outputs is extremely challenging. The distributed computing literature reveals a plethora of negative results, from theoretical lower bounds and impossibility results to empirical studies, that exhibit fundamental scalability limitations.

A popular way to address these challenges is *optimism*: hope for the best, but prepare for the worst [12, 24, 6, 17]. A typical optimistic protocol is tuned to exhibit high performance in *good* runs, believed to be the common case. A good run can have, e.g., timely communication and benevolent participants. At the same time, when communication turns asynchronous and some participants turn rogue, the protocol will preserve safety but may slow down or even stop making progress.



© V. Anikina, J. P. Bezerra, P. Kuznetsov, L. Schiff, S. Schmid; licensed under Creative Commons License CC-BY 4.0 Leibniz International Proceedings in Informatics LIPICS Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

XX:2 Dynamic Probabilistic Reliable Broadcast

In this paper, we explore an alternative form of optimism. What if we prioritize progress over safety? Think of a protocol that would preserve stably high progress guarantees in all runs, but would gracefully degrade safety properties, should the environment get more hostile.

This might be an adequate choice for applications that are able to (temporarily) stand slight inconsistencies. As an example, let us consider *cryptocurrencies*, by far the most popular decentralized application nowadays. Indeed, we may tolerate some overspending of users' accounts as long the responsible parties are eventually detected. Originally, cryptocurrency systems were designed on top of consensus-based blockchain protocols [32, 36]. But consensus is a notoriously hard synchronization problem [15, 12, 6, 7]. It came as a good news that we do not need consensus to implement a cryptocurrency [18, 20], which gave rise to asynchronous, *consensus-free* cryptocurrencies [11, 1, 22] that confirmed to exhibit significant performance gains over the consensus-based protocols. At a high level, these implementations replace consensus with (Byzantine) *reliable broadcast* [2], where a designated sender broadcasts a message so that no two correct processes deliver different messages (*consistency*), either all correct processes deliver a message or none does (*totality*), and if the sender is correct, all correct processes eventually deliver the broadcast message (*validity*). The broadcast algorithm must tolerate a certain fraction of Byzantine (arbitrarily misbehaving) processes, potentially including the sender.

Starting from the classical Bracha's algorithm [3], Byzantine reliable broadcast algorithms [27, 29, 34] are known to scale poorly, as they typically have O(n) per-process communication complexity, where n is the number of processes. The reason for this is their use of quorums [28, 35], i.e., sets of processes that are large enough (typically more than 2/3n) to always intersect in at least one correct process. By relaxing the quorum-intersection requirement to only hold with high probability, the per-process communication complexity can be reduced to $O(\sqrt{n})$ [30]. Guerraoui et al. [19] describe a protocol that replaces quorums with randomly selected samples. A three-phase gossip-based broadcast where each phase consists in exchange with a small (of the order $O(\log n)$), randomly selected set of processes, which would give $O(\log n)$ per-process communication cost. It is shown that assuming a static adversary and an underlying uniform random sampling mechanism, the protocol can be tuned to guarantee almost negligible probabilities of failing the properties of reliable broadcast in realistic settings.

In this paper, we explore an alternative path. Our goal is to develop a reliable-broadcast protocol which guarantees stably high performance in the presence of a *slowly adaptive* adversary. We achieve this by assigning every broadcast message with a dynamically selected small subset of processes that we call the *witnesses* of this message. The witnesses are approached by the receivers to check if no other message has been issued by the same source and with the same sequence number. To anticipate the adversary corrupting the witnesses of any particular events, the processes choose the witness set by applying a carefully tuned *locality-preserving* hash function to the current system state. The state is represented as the set of messages accepted by the process so far. When the communication is close to synchronous, which we take as a common case, the divergence between the states evaluated by different processes and, thus, the witness set for the given broadcast event, is likely to be very small. More generally, we evaluate the divergence in witness-set evaluations as a function of the current "amount of synchrony": the more synchronous is the network, the more accurate is the witness-set evaluation. Notice that we do not need the processes to perfectly agree on the witnesses for any particular event, a sufficient pairwise overlap is enough for making sure that any double-spending attempt is prevented.

Under the realistic assumption that it takes much longer to corrupt a node than to communicate a message, we argue that it is very hard for the adaptive adversary to attack the witnesses before they complete their task. As a result, under normal circumstances, the probabilities of double spending and the loss of progress are negligible, while the witness sets are of size $O(\log n)$. In the protocol, the witnesses take care of making sure that the message is delivered by every correct process, the total communication load per broadcast message remains $O(\log n)$, and the average per-process load in a long run remains $O(\log n)$, similar to sample-based gossiping [19]. However, as our probability analysis shows, we have higher chances of maintaining consistency in the presence of slowly adaptive adversary, due to the fact that we know where to look (the choice of witnesses is "quasi-determistic").

When the network synchrony degrades, i.e., the variance of effective message delays gets higher, there is a chance that witness sets do not always have sufficient overlap. We describe a *recovery* mechanism that can be used to anticipate the potential loss of consistency to prevent using witnesses. In the worst case of complete asynchrony (that we assume to be rare), the communication complexity may coincide with that of conventional quorums and we boil down to the classical reliable broadcast algorithms [2].

We analyse performance and security properties of our witness-based protocols experimentally, via simulations, and we discuss two potential applications of our broadcast protocol: an efficient, broadcast-based cryptocurrency and a generic lightweight accountability mechanism [21].

In Section 2, we describe the system model and in Section 3, we formulate the problem of probabilistic reliable broadcast and present our baseline witness-based protocol. In Section 4, we describe how locality-preserving hashing can be used to implement our witness oracle. In Section 5, we present the outcomes of our simulations and in Section 6, we describe a recovery mechanism that can be used to complement our baseline protocol. In Section 7, we overview the applications of the broadcast protocol and in Section 8, we conclude the paper with discussing related work.

2 System Model

Processes. A system is composed of a set Π of *processes*. Every process is assigned an *algorithm* (we also say *protocol*). Up to $f < |\Pi|/3$ processes can be corrupted by the adversary. Corrupted processes might deviate arbitrarily from the assigned algorithm, in particular they might prematurely stop sending messages. A corrupted process is also called *faulty* (or *Byzantine*), otherwise we call it *correct*.

We assume a slow adaptive adversary: it decides which processes to corrupt depending on the execution, but it takes certain time for the corruption to take effect. When selecting a new process p to corrupt at a given moment in the execution, the adversary can have access to p's private information and control its steps only after p has terminated δ protocol instances, where δ is a predefined parameter.¹ In addition, we assume that previously sent messages by p cannot be altered or suppressed.

Channels. Every pair of processes communicate through *asynchronous authenticated reliable channel*: messages are signed and the channel does not create, drop or duplicate messages,

¹ In this paper we consider broadcast protocols (Section 3), so that an instance terminates for a process when it delivers a message.

XX:4 Dynamic Probabilistic Reliable Broadcast

and there are no bounds on the time required to convey a message from one correct process to another.²

Digital signatures. We use asymmetric cryptographic tools: a pair public-key/private-key is associated with every process in Π [5]. The private key is only known to its owner and can be used to produce a *signature* for a statement, while the public key is known by all processes and is used to *verify* that a signature is valid. We assume a computationally bounded adversary: no process can forge the signature for a statement of a benign process.

3 Probabilistic Reliable Broadcast

The Byzantine reliable broadcast abstraction [2, 5] exports operation broadcast(m), where m belongs to a message set \mathcal{M} , and produces callback deliver(m'), $m' \in \mathcal{M}$. Each instance of reliable broadcast has a dedicated source, i.e., a single process broadcasting a message. In any execution with a set F of Byzantine processes, the abstraction guarantees the following properties:

- (*Validity*) If the source is correct and invokes broadcast(m), then every correct process eventually delivers m.
- (Consistency) If p and q are correct processes and deliver m and m' respectively, then m = m'.
- (*Totality*) If a correct process delivers a message, then eventually every correct process delivers a message.
- (Integrity) If the source p is correct and a correct process delivers m, then p previously broadcast m.

In executions of an ϵ -secure probabilistic reliable broadcast, the properties of reliable broadcast are guaranteed with a (bounded) probability of failure. Formally, let $\epsilon > 0$ (ϵ is called the *security parameter*), in addition to *Integrity*, the following properties are satisfied:

- $(\epsilon Validity)$ If the source is correct and invokes broadcast(m), then every correct process eventually delivers m with probability at least 1ϵ .
- $(\epsilon Consistency)$ If p and q are correct processes and deliver m and m' respectively, then m = m' with probability at least 1ϵ .
- $(\epsilon Totality)$ If a correct process delivers a message, then eventually every correct process delivers a message with probability at least 1ϵ .

Long-lived reliable broadcast. In a *long-lived* execution of reliable broadcast, each process maintains a history of delivered messages and can invoke *broadcast* an unbounded number of times, but correct processes behave sequentially, i.e., wait for the output of a *broadcast* invocation before starting a new one. The abstraction can easily be implemented using an instance of reliable broadcast for each message, by attaching to it the source's *id* and a sequence number [2].

If one uses instances of probabilistic reliable broadcast instead, there is a fixed probability of failure in every instance, therefore, in an infinite run (assuming processes broadcast messages an infinite number of times) the probability of failure converges to 1. We therefore

 $^{^{2}}$ We discuss how the network environment affects the security of the proposed protocols in Sections 4 and 6.

consider the *expected failure time* of a *long-lived probabilistic reliable broadcast* as the expected number of instances by which the protocol fails.

Witness-Based Protocol. We first present an algorithm that implements Byzantine reliable broadcast using a distributed witness oracle ω . Intuitively, every process p_i can query its local oracle module ω_i to map each event e = (id, seq) (a pair of a process identifier and a sequence number) to a set of processes that should validate the seq-th event of process *id*. The oracle module ω_i exports two operations: getPotWitnesses(*id*, seq), which returns a set V_i of processes potentially acting as witnesses for the pair (*id*, seq), and getOwnWitnesses(*id*, seq), that returns a set $W_i \subseteq V_i$ of witnesses particular to p_i , referred to as p_i 's witness-set.

We now describe an algorithm that uses w to implement Byzantine reliable broadcast, a variation of Bracha's algorithm [2] that instead of making every process gather messages from a quorum ³, we delegate this task to the witnesses. Each process waits for replies from a threshold k of its witnesses in W_i to advance to the next protocol phase. Since witness-sets can differ, messages are sent to V_i to guarantee that every process acting as a witness can gather enough messages from the network. The protocol maintains correctness as long as for each correct process p_i , there are at least k correct witnesses and at most k - 1 faulty witnesses in W_i . Moreover, V_i should include the witness-set of every other correct process. In Section 4, we describe a method to select k and a construction of ω that satisfies these criteria with high probability.

3.1 **Protocol Description**

The pseudo-code of a single instance of Byzantine reliable broadcast (parameterized with a pair (id, seq)) is presented in Algorithm 1. Here we assume the set of participants Π ($|\Pi| = n$) to be static: the set of processes remains the same throughout the execution. f denotes the number of faulty nodes tolerated in Π (see 3.2).

Initialization. At the source s, a single instance of Witness-Based Broadcast (**WBB**) parameterized with (s, seq) is initialized when s invokes broadcast(m) (on the application level), where (s, seq) is attached to m. On the remaining processes, the initialization happens when first receiving a protocol message associated to (s, seq). Upon initialization, processes sample V_i and W_i from ω_i , which are fixed for the rest of the instance.

Roles. Each action is tagged with [S], [W] or $[\Pi]$, where [S] is an action performed by the source, [W] is performed by a process acting as witness and $[\Pi]$ by every process. A process p_i can take multiple roles in the same instance and always takes actions tagged with $[\Pi]$, but performs each action *only once per instance*. Moreover, p_i (correct) acts as witness *iff* $p_i \in V_i$. We assume every broadcast m to include the source's signature so that every process can verify its authenticity.

Algorithm 2 uses **WBB** as a building block to validate and deliver messages. Clearly, if the validation procedure satisfies the reliable broadcast properties, then Algorithm 2 implements long-lived reliable broadcast.

3.2 Protocol Correctness

We now present a proof sketch of correctness for Algorithm 1, a detailed proof can be found in Appendix A.

³ A quorum is a subset of processes that can act on behalf of the system. A Byzantine quorum [28] is composed of $q = \lfloor \frac{n+f}{2} \rfloor + 1$ processes, for a system with n processes in which f are Byzantine.

Algorithm 1 Witness Based Broadcast

```
1 [II] upon init - (id, seq):
```

- **2** $V_i \leftarrow \omega_i.getPotWitnesses(id, seq);$
- **3** $W_i \leftarrow \omega_i.getOwnWitnesses(id, seq);$
- 4 [S] operation broadcast(m):
- 5 | send $\langle NOTIFY, m, \Pi \rangle$ to every $w \in V_i$;
- 6 [W] upon receiving $\langle NOTIFY, m, \Pi \rangle$:
- 7 | send $\langle ECHO, m, W \rangle$ to every $p \in \Pi$;
- **s** [Π] **upon** receiving $\langle ECHO, m, W \rangle$:
- 9 send $\langle ECHO, m, \Pi \rangle$ to every $w \in V_i$;
- **10** [W] **upon** receiving $\lfloor \frac{n+f}{2} \rfloor + 1$ (ECHO, m, Π) or f + 1 (READY, m, Π) messages: **11** | send (READY, m, W) to every $p \in \Pi$;
- **12** $[\Pi]$ **upon** receiving $\langle READY, m, W \rangle$ from k witnesses in W_i :
- **13** \lfloor send $\langle READY, m, \Pi \rangle$ to every $w \in V_i$;

14 [W] upon receiving $\langle READY, m, \Pi \rangle$ from $\lfloor \frac{n+f}{2} \rfloor + 1$ processes:

- **15** | send $\langle VALIDATE, m \rangle$ to every $p \in \Pi$;
- **16** [II] **upon** Upon receiving $\langle VALIDATE, m \rangle$ from k witnesses in W_i :
- 17 deliver(m);

Algorithm 2 Long-Lived Reliable Broadcast

```
      Local Variables:

      seq \leftarrow 0;
      /* Sequence number of p_i */

      Hist \leftarrow \emptyset;
      /* Delivered messages */

      1 operation broadcast(v):
      /* Delivered messages */

      2
      seq + +;

      3
      m \leftarrow (v, p_i, seq);

      4
      WBB.broadcast(m);

      5
      upon WBB.deliver(m):

      6
      Hist \leftarrow Hist \cup \{m\};
```

Assumptions. Consider an instance of WBB where $f < |\Pi|/3$ and for every p_i correct:

1. W_i has at least k correct witnesses and at most k - 1 faulty witnesses;

2. for every p_j correct, $W_j \subseteq V_i$.

Then the following theorem holds:

▶ **Theorem 1.** Algorithm 1 implements Byzantine reliable broadcast.

Proof Sketch. Since witness-sets have at least k correct processes, they are responsive and every participant is able to receive enough replies in each phase, and because there are at most k - 1 faulty processes, at least one correct witness reply is received. Moreover,

consistency holds due to witnesses waiting for $\lfloor \frac{n+f}{2} \rfloor + 1$ processes, which guarantees two correct witnesses always receive a message from a common correct process.

Theorem 1 implies the following:

▶ **Theorem 2.** If 1) and 2) are satisfied with probability at least $1 - \epsilon$, then Algorithm 1 implements ϵ -secure probabilistic reliable broadcast.

Complexity. For a single broadcast instance, the message complexity depends on the size of V_i (the set of potential witnesses). Let $|\Pi| = n$ and v the expected size of V_i , the message complexity is $O(n \cdot v)$. We assume that parameters for the witness-oracle (Section 4) are chosen such that v is $\Omega(\log n)$, resulting in a complexity of $O(n \log n)$. Moreover, **WBB**'s worst case latency is 6 message delays.

Witness Oracle

4

The witness oracle is responsible for selecting a set of witnesses for each broadcast message. This selection should be unpredictable in advance so that it is known only with close proximity to the time of receiving the broadcast message. We implement this service locally on each node and require that for every broadcast message and for any pair of nodes, the locally selected witness sets will be similar.

In order to provide unpredictable and yet similar outputs each node uses the hash of the history of broadcast messages it received and verified as a source of randomness. In order to support high rate of broadcast messages, the nodes do not wait or try to establish the same histories before hashing. Instead we use a novel locality sensitive hashing scheme of histories that guarantees that small differences in histories will result with small differences in the selected witness set.

Since each broadcast message in the histories has unique combination of source and per source sequence number, the histories can be regarded as sets. However, existing locality sensitive hashing algorithms for sets, such as those based on MinHash [4], are less sensitive to small differences between sets the bigger the sets. This does not fit well the case of histories which are expected to ever expand. Note that hashing just a sliding window within histories is very "noisy" when nodes do not agree on the same order of broadcast messages (of different nodes).

Another disadvantage of existing locality sensitive hashing algorithms is their vulnerability to messages crafted to manipulate the hash result. For example in MinHash based algorithms, adding an item with extremely small hash value will most likely keep the hash of the entire set constant for long time regardless of insertions of new items. In our case, when using history hash for witness selection, it could allow the adversary to make the witness selection predictable.

Next we show a construction of safe locality sensitive hashing for histories (SLASH), a hashing scheme that guarantees high degree of unpredictability and also similar outputs for similar histories. Later we show how SLASH can be used for witness selection.

4.1 Constructing a safe locality sensitive hashing of histories

We consider a history as a set of binary strings and we assume the existence of a family of one-way functions $H_c = \{h_i : \{0,1\}^* \to \{0,1\}^c\}$. For example, for c = 256, we can use $h_i(x) = SHA256(x \oplus r_i)$ where r_i is a predefined random binary string with length at least c and ' \oplus ' is the bit concatenation operator.

XX:8 Dynamic Probabilistic Reliable Broadcast

We define a family of *SLASH* functions $F_{r,b,H_c} = \{f_i : \mathbb{P}(\{0,1\}^*) \to \mathbb{Z}_r^b\}$, where $b < 2^c$. Each of these functions can hash a set of arbitrary binary strings into a vector in *b*-dimensional mod r ring and should be locality sensitive in the sense that sets with small differences should be hashed to vectors with small distance, i.e., for any function $f_i \in F_{r,b,H_c}$ and sets $S, T \in \mathbb{P}(\{0,1\}^*)$:

$$RingDist_{r,b}(f_i(S), f_i(T)) \le SetDist(S, T)$$
(1)

where SetDist(S,T) is simply the number of items which are on one set but not in the other, i.e., $SetDist(S,T) := |(S \cup T) - (S \cap T)|$, and $RingDist_{r,b}$ is similar to the norm-1 distance in \mathbb{R}^b_r and defined as follows: $RingDist_{r,b}(X,Y) = \sum_{j=0}^{b-1} min(X_j - Y_j \mod r, Y_j - X_j \mod r)$.

Our construction of SLASH functions F_{r,b,H_c} can be described as follows: Each evaluation of $f_i \in F_{r,b,H_c}$ on a set $S \subseteq \{0,1\}^*$ defines a random walk in \mathbb{Z}_r^b where each item x in Saccounts for an independent random step based on the hash of x. More specifically we define f_i as follows:

$$f_i(S) := \langle g(S_0), g(S_1), ..., g(S_{b-1}) \rangle,$$

where $S_y := \{x \in S. \ h_i(x) \equiv y \mod b\}$ and $g(V) = \sum_{v \in V} (-1)^{h_i(v) \div b} \mod r$.

Easy to see that the distance between any two sets is not affected by shared items while each non-shared item increases or decreases the distance by at most 1. Therefore the construction is locally sensitive as defined in inequality 1. The limited impact of any single message also contributes to the safety of the construction since the adversary cannot have lasting effect on the function state by sending one (or even many) messages.

The safety of the *SLASH* construction depends on the unpredictability (e.g., uniform distribution) of the massage hashes. Using one-way functions H_c can only guarantee such condition for the messages sent by benign nodes which can add randomness to the messages, however since each message hash is mapped to one out of only 2*b* possible *SLASH* state updates (*b* dimensions and either increment or decrement operation), malicious nodes can craft messages with designated effect.

In order to mitigate this threat and provide unpredictability, we require that each message sent by node *i* to include a commitment to the *c* bits value that will be used to select the *SLASH* state update for the message that will be sent by node *i* in the future in about δ instances. Such commitment can be the hash of that value where the value itself will be revealed at time in the future. This removes the usability of the crafted messages for the adversary since the gain of sending these packets is unpredictable.

A good δ value should guarantee that after δ messages the *SLASH* state (*b*-dimensional mod *r* values) will distribute (almost) uniformly in \mathbb{Z}_r^b (regardless of previous state). By generalizing known bounds for one dimensional ring[9] we can approximate such δ by $b \cdot r^2$.

4.2 Using SLASH functions for witness-set selection

We consider all node ids to be binary strings of length c and we assume there exists a mapping $M_{r,b}^c: \{0,1\}^c \to \mathbb{Z}_r^b$ from node id space to multi dimensional ring \mathbb{Z}_r^b . In order to select witness-sets, all nodes in the network are initialized with the same *SLASH* function $f \in F_{r,b,H_c}$ and a distance parameter $d \in \mathbb{R}^+$. In addition, during the execution, each node

i maintains a view regarding the set of currently active node ids⁴ $\Pi_i \subseteq \{0,1\}^d$ and the delivered message history D_i .

Upon receiving a new message m, with source s and source sequence number q_s , node i computes $y_i = f(D_i) + M_{r,b}^c(h(s \oplus q_s))$ and then selects the witness set W_i^m as all node ids at distance at most d from y_i , i.e.,

$$W_i^m = \{ v \in \Pi_i.RingDist_{r,b}(M_{r,b}^c(v), y_i) \le d \}.$$

$$\tag{2}$$

However, the selection criteria above allows the adversary to insert or compromise nodes with close proximity ids and wait until the combination of history hash (which can be seen as a random walk) and message hash will select these nodes together as a witness-set for a target message. We adapt the above scheme so that for each node id $v \in \Pi_i$ we use a different instance of the history hash, so ids proximity cannot guarantee joint selection as witnesses. More specifically, instead of comparing any node id v to the same y_i , we maintain a higher (B > b) dimensional *SLASH* of the history which we permute and filter based on h(v) to generate a different history hash, i.e., in Equation 2 we replace y_i with $y_{i,v} = P^B_{h(v),b}(f'(D_i)) + M^c_{r,b}(h(s \oplus q_s))$ where $f' \in F_{r,B,H_c}$ is a *B*-dimensional *SLASH* function and $P^B_{z,b}(x)$ performs a random permutation of *B* dimensional vector *x* and random selection of *b* out of its *B* values according to a pseudo-random generator with seed *z*.

Note that locality sensitive property of the witness selection is unharmed by the above extension since when testing v as witness, all the nodes in the network apply the same permutation and vector index selection on close proximity vectors.

4.3 Probability Analysis

Given the witness-set selection mechanism, we calculate the probability of failure (ϵ , also called security parameter) of a single **WBB** instance. There are two adversary strategies we need to consider: the adversary waits until the history hash reaches a desirable value, or they continuously send messages until they get a favorable witness-set. In the first case, the adversary needs to wait until k out of f random walks in \mathbb{R}^b_r meet in a determined area (of radius d), a detailed discussion of this attack is presented in Appendix D. In the remaining of this section, we focus on the second adversary strategy.

In order to maintain correctness in Algorithm 1, every witness-set of a correct process should have at least k correct witnesses and at most k - 1 faulty witnesses. We first calculate the probability that a single witness-set does not satisfy the conditions above (the details of this calculation can be found in Appendix B). This is equivalent to considering every history of a correct process to be the same, resulting in a single global witness-set (we call it base-line security). Afterwards, we analyse how the probabilities degrade with the increase on the history differences.

Selecting k. The higher k is, the higher is the probability of reaching a correct witness, and the lower k is, the higher is the probability of receiving enough replies. We select k such that both probabilities are the same.

Figure 1 shows the relation between ϵ and the expected witness-set size given that correct processes have a common witness-set. With $|\Pi| = 1024$, f = 0.1 and witness-set size of 100, Figure 1 shows a base-line ϵ value of approximately 10^{-11} . As a comparison, [19] uses a gossip-based protocol to implement probabilistic reliable broadcast, where security depends

⁴ Despite considering Π to be a common set in the probability calculations and correctness proofs, the witness-set selection mechanism does not constrain Π to a static (or common) set.

XX:10 Dynamic Probabilistic Reliable Broadcast

on the sample size (similar to our witness-set size). With similar parameters, they achieve a security parameter of 10^{-8} . However, in our approach ϵ also increases with the difference in histories.

Next, we discuss how ϵ increases with the difference in histories, and describe how to select *SLASH* parameters such that ϵ does not degrade significantly.

Figure 1 Security parameter as a function of the witness-set size (single witness-set). Here, $|\Pi| = 1024$ and f denotes the number of faulty processes in Π .



Uncertainty. Processes with different histories may hash $y_{i,v}$ for the same v to different positions. As a result of the *SLASH* construction, if the histories differ by l messages, the hash positions are distant by at most l. According to the difference between all histories, i.e., the number of messages in any history that are not common to all, the possible values for $y_{i,v}$ will fall within an area of bounded radius. We call this radius the *uncertainty* μ of the hashing, and use μ to give a conservative estimation of the degradation of ϵ in Appendix B.

Increasing the size of the dimensions in \mathbb{R}^b_r (i.e., the value of r) decreases the sensibility of ϵ with the history differences. Intuitively, with larger dimensions the resulting radius dneeded to cover enough area for the witnesses selection is also larger. If μ is proportionally smaller to d, then the resulting impact on the security parameter is also smaller.

Figure 2 Security parameter according to the total difference between histories. 16 dimensions are used for the *SLASH* construction, each with size 2^{16} . Here, $|\Pi| = 1024$ and f = 0.25.



To avoid having unresponsive witnesses, each process p_i uses two different witness-sets: V_i and W_i . The range d chosen for selecting W_i is based on the expected witness-set size, while the range d' for selecting V_i is increased by some constant γ , i.e., $d' = d + \gamma$, where γ is calculated based on how much histories can differ. Although processes only consider

witnesses (and act as one) based on their own local history, in Section 6 we show how one can ensure that a slow process does no try to reach a witness-set that differs too much from others, limiting the histories impact over the security.

As an example, consider a case where the histories of most processes differ by 400 messages when initializing instances. When using an expected witness-set size of 300, with *SLASH* parameters being the same as in Figure 2, setting γ to account for a history difference of 400 (and thus allowing every correct witness to be responsive) will cause ϵ to degrade by a factor of 10². To account for the case when correct processes cannot make progress through their witnesses (e.g. slow processes), we add the possibility of using a *timeout* mechanism and use a recovery protocol, described in Section 6.

5 Simulations

We use simulations to make a comparative analysis between Bracha's reliable broadcast, the probabilistic reliable broadcast from [19] (hereby called *scalable* broadcast) and our witness-based reliable broadcast. We implemented all three protocols in Golang. For the simulation software, we used *Mininet* [25] to run all processes in a single machine. Mininet leverages OS-level virtualization features, such as processes and network namespaces to provide node isolation, allowing control over communication parameters such as bandwidth and network delays between nodes.

Setup. We used a Linode dedicated CPU virtual machine [26] with 64 cores, 512GB of RAM, running Linux 5.4.0-148-generic Kernel with Mininet version 2.3.0.dev6 and Open vSwitch [33] version 2.13.8.

Protocol parameters. For the witness-set sizes in **WBB**, we use $W = 3 \log(n)$ and $V = 4 \log(n)$, with a witness threshold of W/2 + 1. The parameters selected for the *SLASH* construction are the same as in Figure 2, i.e., 256 bits hash and 16 dimensions. To have a comparable communication cost, we also use $4 \log(n)$ as the sample size in the scalable broadcast⁵.

Description. Since in a simulated environment we can change network parameters to modify the system's performance⁶, we analyze normalized values instead of absolute ones, using Bracha's protocol as the base line. Each element in the curves of Figures 3 and 4 is an average over 5 experiments.

In the first simulation, we observe each protocol's performance with a high volume of transmitted messages and how it relates to the number of processes. Each process initiates broadcast of a new message once the previous one was delivered throughout all the experiment. We then measure the achievable throughput (number of delivered messages per second) and average latency for different system sizes as it's show in Figure 3. Both witness-based and scalable broadcast have similar performances throughout the tests, which indicates that the protocols have a similar constant for the chosen parameters. The better asymptotic communication cost is clearly displayed for the probabilistic protocols as the number of nodes increases, but it only undermines the high initial constant with around 100 nodes.

⁵ For simplicity, the same sample size is used in every protocol phase.

⁶ Simulating hundreds of nodes in a single server poses many performance challenges. On intensive throughput tests for a large number of nodes, we use nodes with reduced resources (bandwidth an CPU time), decreasing the overall system's performance. Nevertheless, the relative performance's trend remains the same.

XX:12 Dynamic Probabilistic Reliable Broadcast

Figure 3 Left: Throughput according to the number of nodes. Right: Average latency according to the number of nodes. Each node has 10Mbps bandwidth and the probability of packet loss in channels is 1%. The values are normalized according to Bracha's protocol results.



In the second simulation, we observe each protocol's good case latency (without load) and how it relates to the number of processes. To achieve this, we keep only a single client node issuing messages⁷, we also increase the bandwidth to 100Mbps per node and the base channel's delay to 100ms (the communication impact on latency is more evident with higher base delays). Packet loss is kept at 1%.

Figure 4 Good case latency according to the number of nodes. Each node's bandwidth is set to 100Mbps, channels base delay to 100ms and packet loss to 1%. The values are normalized according to Bracha's protocol results.



As we can observe from Figure 4, starting from 80 processes the number of processes has a significant impact on Bracha's protocol performance. Even though links are not saturated, the higher number of messages increases the probability that longer delays will occur.

Comparing protocols. As we can observe from Figure 3, witness-based protocol demonstrates a stably higher performance than scalable broadcast given a high load of the system, both in terms of throughput and latency. On the other hand, scalable broadcast presents a better latency in good runs than the witnesses-based protocol (Figure 4). This indicates that the witness protocol has a higher base latency, which can be improved by making the source broadcast the initial notify message to all the processes (the same asymptotic complexity is preserved). In addition, starting at 64 nodes, the latency of the witness-based protocol tends to decrease with respect to the other two.

⁷ Only a single instance is active at a time, and the client node issues a new message once the previous one is delivered.

6 Timeout and Recovery

In the construction of our witness oracle (Section 4), the security parameter ϵ depends on the execution. The current "amount of synchrony" affects the discrepancies in the local histories of the correct processes and, thus, the probabilistic guarantees of our broadcast protocol. Indeed, a process whose history diverges too much from the rest of the system might try to validate messages through a non-responsive or corrupted witness set.

In this section, we present an extension of our protocol that includes a consistency fallback: if it takes too long for a process to validate a message, a *timeout* mechanism and a recovery protocol are triggered to ensure safety.

Recovery Protocol. First, to account for time, we modify the **WBB** initialization block: after sampling the witnesses we call the method setTimeout()(Algorithm 3). This method guarantees that a *timeout* is triggered after a predetermined amount of time has passed without a successful validation. Once a process receives a protocol message containing a new message m, it initializes a new instance of message validation and relays m to the corresponding witnesses in a *NOTIFY* message.

Algorithm 3 WBB - Initialization Update

When a *timeout* event is triggered, a process resorts to the recovery protocol outlined in Algorithm 4. The actions on the recovery protocol should be executed by every process, and are performed *only once a process triggers timeout or delivers a message in that instance.*⁸

The idea behind the algorithm is to "recover" any value that could have possibly been delivered in the witness validation procedure, and then execute Bracha's Byzantine reliable broadcast [2]. We achieve this by making processes echo the last **WBB** they acknowledged, so that if a message is delivered by any process using **WBB**, no distinct message can be delivered using the recovery protocol. A detailed description of the protocol, as well as correctness proofs can be found in Appendix C.

6.1 Ensuring close histories

Theorem 1 is guaranteed if processes executing **WBB** select good witnesses, such that consistency is still guaranteed. A problem arises when a process p is too slow and its history differs by a significant amount, causing it's witnesses to be very distinct from other processes. This would in turn reduce the security of the protocol: due to network asynchrony any set of witnesses might be chosen for a particular message. We overcome this problem by providing processes a mechanism to identify when they are too slow, in which case they bypass **WBB** and execute the recovery protocol directly.

⁸ Messages from the recovery protocol received by a process before satisfying any of these conditions are then stored and treated later.

XX:14 Dynamic Probabilistic Reliable Broadcast

Message logs. Processes are required to store a log including current delivered messages and every message for which it sent *READY*, either in **WBB** or in the recovery protocol. Security is maintained by periodically sharing its log with other processes⁹. Formally, each process p proceeds in rounds of Δ seconds, deciding in each round if it will to use **WBB** to validate messages or go direct to the recovery protocol. In the beginning of each round, psends a message with current log to every other process.

For a given $d \ge 0$, in the end of round r, p decides to use **WBB** throughout r + 1 iff:

- 1. There are at least n f logs for which the set of delivered messages differs from p's set of delivered messages by at most d;
- 2. Let readyM be the set with all messages appearing in at least f + 1 READY logs, then p's set of delivered messages also differs from readyM by at most d messages.

Let th_{max} be the maximum achievable throughput (for the purpose of this section we use throughput as the number of new distinct messages any correct process delivers in a second) and γ the maximum tolerable difference between any pair of histories.

▶ **Theorem 3.** As long as $\gamma > 3d + 2\Delta \cdot th_{max}$, no pair of processes select witnesses in round r + 1 with histories that differ by more than γ messages.

In Theorem's 3 proof we assume n = 4f + 1, the proof is relegated to Appendix A. From the first condition, it follows that in order to use witnesses on the next round, each node should receive at least n - f logs in the previous one. γ is defined as in 4.3 according to the desired security parameter, while th_{max} is given by the system's capacity of processing messages. Δ and d can then be adjusted to satisfy Theorem 3.

6.2 Time of Failure

We measure the expected time of failure (When using the aggregated protocol in Algorithm 2) in terms of the number of expected instances for the witness selection mechanism to fail. Let ϵ be the (degraded) probability of failure described in Section 4 after selecting all witness-oracle parameters. If Algorithm 2 uses the witness-oracle construction of Section 4, and ensures close histories as described in 6.1 while providing the recovery protocol, then it implements probabilistic long-lived broadcast with $\frac{1}{\epsilon}$ expected time of failure.

7 Applications and Ramifications

In this section, we briefly overview two potential applications of our broadcast protocol: asynchronous asset transfer and a generic accountability mechanism. We also discuss open questions inspired by these applications.

7.1 Asset Transfer

The users of an asset-transfer system (or a cryptocurrency system) exchange assets via transactions. A transaction is a tuple tx = (s, r, v, seq), where s and r are the sender's and receiver's account id respectively, v is the transferred amount and seq is a sequence number.

⁹ For simplicity of presentation we assume the whole log to be sent each time, however any efficient mechanism for informing the log's content is sufficient (e.g. sending only the changes since previous messages).

Each user p maintains a local set of transactions T and it adds a transaction tx to T (we also say that p commits tx), when p confirms that (i) all previous transactions from s are committed, (ii) s has not issued a conflicting transaction with the same sequence number, and (iii) based on the currently committed transactions, s indeed has the assets it is about to transfer.¹⁰

One can build such an abstraction atop (probabilistic) reliable broadcast: to issue a transaction tx, a user invokes broadcast(tx). When a user receives an upcall deliver(tx) it puts tx on hold until conditions (i)-(iii) above are met and then commits tx. Asset-transfer systems based on classical broadcast algorithms [2] exhibit significant practical advantages over the consensus-based protocols [11, 1]. One can reduce the costs even further by using our optimistic broadcast. The downside is that there is a small probability of *double spending*. A malicious user may make different users deliver conflicting transactions and overspend its account by exploiting "weak" (not having enough correct members) witness sets or over-optimistic evaluation of communication delays in the recovery protocol. We can temporarily tolerate such an overspending and compensate it with a reconfiguration mechanism that detects and evicts misbehaving users from the system, as well as adjusting the total balance. It is appealing to explore whether such a solution would be acceptable in practice.

7.2 Accountability and beyond

As a running example of our optimistic approach, we considered a probabilistic reliable broadcast protocol, where every broadcast event was validated by a set of witnesses. The validation here consists in ensuring that the source does not attempt to broadcast different messages with the same sequence number. As a result, with high probability, all correct processes observe the same sequence of messages issued by a given source.

One can generalize this solution to implement a lightweight accountability mechanism [21]: witnesses collectively make sure that the sequence of events generated by a process corresponds to its specification. Here a process commits not only to the messages it sends, but also to the messages it receives. This way the witnesses may verify if its behavior respects the protocol the process is assigned.

Notice that one can generalize this approach even further, as the verified events do not have to be assigned to any specific process. In the extreme case, we can even think of a probabilistic state-machine replication protocol [24, 6]. What if the processes try to agree on an ever-growing sequence of events generated by all of them in a decentralized way? Every next event (say, at position k) may then be associated with a dynamically determined pseudo-random set of witnesses that try to make sure that no different event is accepted at position k. Of course, we need to make sure that the probability of losing consistency and/or progress is acceptable and a probability analysis of this kind of algorithms is an appealing question for future research.

8 Related Work

Solutions designed for partially synchronous models [13] are inherently *optimistic*: safety properties of consensus are always preserved, but liveness is only guaranteed in sufficiently long periods of synchrony, when message delays do not exceed a pre-defined bound. This kind of algorithms, also known as *indulgent* [17], were originally intended to solve the

 $^{^{10}}$ Please refer to [11] for more details.

XX:16 Dynamic Probabilistic Reliable Broadcast

fundamental consensus problem, which gave rise to prominent partially synchronous statemachine replication protocols [24, 6] and, more recently, partially-synchronous blockchains.

Reliable broadcast protocols [2] provide a weaker form synchronization than consensus: instead of reaching agreement on the total order of events, reliable broadcast only establishes common order on the messages issued by any given source. This partial order turns out handy in implementing "consensus-free" asset transfer [18, 20], by far the most popular blockchain application, and resulting implementations are simpler, more efficient and more robust than consensus-based solutions [1, 11, 22].¹¹ To alleviate $O(n^2)$ communication complexity of classical quorum-based reliable broadcast algorithms [3, 27, 29, 34], one can resort to probabilistic relaxations of its properties [30, 19]. The probabilistic broadcast protocol in [19] achieves, with a very high level of security, $O(n \log n)$ expected complexity and $O(\log n / \log \log n)$ latency by replacing quorums with randomly selected samples of $O(\log n)$ size. In this paper, we propose an optimistic probabilistic reliable broadcast algorithm that, in a good run, exhibits even better security (due to the "quasi-deterministic" though unpredictable choice of witnesses) and, while achieving the same communication complexity, constant expected latency. For simplicity, as a fall-back solution in a bad run, we propose the classical $O(n^2)$ broadcast protocol [2]. However, one can also use the protocol of [19] here, which would give lower costs with gracefully improved security.

In the Algorand blockchain [16, 8], scalable performance is achieved by electing a small-size *committee* for each new block. To protect the committee members from a computationally bound adversary, one can use verifiable random functions (VRF) [31]. The participants use a hash of the last block and their private keys as inputs to the VRF that returns a *proof of selection*. As the proof is revealed only when a committee member proposes the next block, the protocol is protected against an adaptive adversary. The approach was later applied to asynchronous (randomized) Byzantine consensus [10], assuming trusted setup and *public-key infrastructure* (PKI). Similar to [16, 10], we use local knowledge for generating unpredictable process subsets of a fixed expected size. In contrast, our protocol does not assume PKI or trusted setup. We generate pseudo-randomness based on the local states, without relying on external sources (e.g., the blockchain state). However, we only tolerate a *slow* adversary (time to corrupt a node considerably exceeds communication delay).

— References

- Mathieu Baudet, George Danezis, and Alberto Sonnino. Fastpay: High-performance byzantine fault tolerant settlement. In Proceedings of the 2nd ACM Conference on Advances in Financial Technologies, pages 163–177, 2020.
- 2 Gabriel Bracha. Asynchronous Byzantine agreement protocols. Information and Computation, 75(2):130–143, 1987.
- 3 Gabriel Bracha and Sam Toueg. Asynchronous Consensus and Broadcast Protocols. JACM, 32(4), 1985.
- 4 Andrei Z Broder. On the resemblance and containment of documents. In Proceedings. Compression and Complexity of SEQUENCES 1997 (Cat. No. 97TB100171), pages 21–29. IEEE, 1997.
- 5 Christian Cachin, Rachid Guerraoui, and Luís Rodrigues. *Introduction to reliable and secure distributed programming.* Springer Science & Business Media, 2011.
- 6 Miguel Castro and Barbara Liskov. Practical byzantine fault tolerance and proactive recovery. ACM Transactions on Computer Systems (TOCS), 20(4):398–461, 2002.

¹¹ These implementations, however, assume that no account can be concurrently debited. i.e., no conflicting transactions must ever be issued by honest account owners [23].

- 7 Tushar Deepak Chandra, Vassos Hadzilacos, and Sam Toueg. The weakest failure detector for solving consensus. J. ACM, 43(4):685–722, July 1996.
- 8 Jing Chen and Silvio Micali. Algorand. arXiv preprint arXiv:1607.01341, 2016.
- 9 F. R. K. Chung, Persi Diaconis, and R. L. Graham. Random Walks Arising in Random Number Generation. The Annals of Probability, 15(3):1148 – 1165, 1987. doi:10.1214/aop/1176992088.
- 10 Shir Cohen, Idit Keidar, and Alexander Spiegelman. Not a coincidence: Sub-quadratic asynchronous byzantine agreement whp. *arXiv preprint arXiv:2002.06545*, 2020.
- 11 Daniel Collins, Rachid Guerraoui, Jovan Komatovic, Petr Kuznetsov, Matteo Monti, Matej Pavlovic, Yvonne Anne Pignolet, Dragos-Adrian Seredinschi, Andrei Tonkikh, and Athanasios Xygkis. Online payments by merely broadcasting messages. In 50th Annual IEEE/IFIP International Conference on Dependable Systems and Networks, DSN 2020, Valencia, Spain, June 29 - July 2, 2020, pages 26–38. IEEE, 2020.
- 12 Cynthia Dwork, Nancy Lynch, and Larry Stockmeyer. Consensus in the presence of partial synchrony. J. ACM, 35(2):288–323, April 1988.
- 13 Cynthia Dwork, Nancy A. Lynch, and Larry Stockmeyer. Consensus in the presence of partial synchrony. *Journal of the ACM*, 35(2):288–323, April 1988.
- 14 Robert Elsässer and Thomas Sauerwald. Tight bounds for the cover time of multiple random walks. In Proceedings of the 36th International Colloquium on Automata, Languages and Programming: Part I, ICALP '09, page 415–426, Berlin, Heidelberg, 2009. Springer-Verlag. doi:10.1007/978-3-642-02927-1_35.
- 15 Michael J. Fischer, Nancy A. Lynch, and Michael S. Paterson. Impossibility of distributed consensus with one faulty process. JACM, 32(2):374–382, April 1985.
- 16 Yossi Gilad, Rotem Hemo, Silvio Micali, Georgios Vlachos, and Nickolai Zeldovich. Algorand: Scaling byzantine agreements for cryptocurrencies. In *Proceedings of the 26th symposium on operating systems principles*, pages 51–68, 2017.
- 17 Rachid Guerraoui. Indulgent algorithms (preliminary version). In PODC, pages 289–297. ACM, 2000.
- 18 Rachid Guerraoui, Petr Kuznetsov, Matteo Monti, Matej Pavlovic, and Dragos-Adrian Seredinschi. The consensus number of a cryptocurrency. In PODC, 2019. https://arxiv.org/abs/ 1906.05574.
- 19 Rachid Guerraoui, Petr Kuznetsov, Matteo Monti, Matej Pavlovic, and Dragos-Adrian Seredinschi. Scalable byzantine reliable broadcast. In Jukka Suomela, editor, 33rd International Symposium on Distributed Computing, DISC 2019, October 14-18, 2019, Budapest, Hungary, volume 146 of LIPIcs, pages 22:1–22:16. Schloss Dagstuhl Leibniz-Zentrum für Informatik, 2019.
- 20 Saurabh Gupta. A Non-Consensus Based Decentralized Financial Transaction Processing Model with Support for Efficient Auditing. Master's thesis, Arizona State University, USA, 2016.
- 21 Andreas Haeberlen, Petr Kuznetsov, and Peter Druschel. PeerReview: Practical accountability for distributed systems. In *Proceedings of the 21st ACM Symposium on Operating Systems Principles (SOSP'07)*, Oct 2007.
- 22 Petr Kuznetsov, Yvonne-Anne Pignolet, Pavel Ponomarev, and Andrei Tonkikh. Permissionless and asynchronous asset transfer. In *DISC 2021*, volume 209 of *LIPIcs*, pages 28:1–28:19, 2021.
- 23 Petr Kuznetsov, Yvonne-Anne Pignolet, Pavel Ponomarev, and Andrei Tonkikh. Cryptoconcurrency: (almost) consensusless asset transfer with shared accounts. CoRR, abs/2212.04895, 2022. URL: https://doi.org/10.48550/arXiv.2212.04895.
- 24 Leslie Lamport. The Part-Time parliament. ACM Transactions on Computer Systems, 16(2):133–169, May 1998.
- 25 Bob Lantz, Brandon Heller, and Nick McKeown. A network in a laptop: rapid prototyping for software-defined networks. In *Proceedings of the 9th ACM SIGCOMM Workshop on Hot Topics in Networks*, pages 1–6, 2010.

XX:18 Dynamic Probabilistic Reliable Broadcast

- 26 Linode (Akamai). Plan Types Dedicated CPU Compute Instances. https://www.linode. com/docs/products/compute/compute-instances/plans/dedicated-cpu/, 2023. [Online; accessed 10-May-2023].
- 27 Dahlia Malkhi, Michael Merritt, and Ohad Rodeh. Secure reliable multicast protocols in a WAN. In *ICDCS*, pages 87–94. IEEE Computer Society, 1997.
- 28 Dahlia Malkhi and Michael Reiter. Byzantine quorum systems. In Proceedings of the twentyninth annual ACM symposium on Theory of computing, pages 569–578. ACM, 1997.
- 29 Dahlia Malkhi and Michael K. Reiter. A high-throughput secure reliable multicast protocol. Journal of Computer Security, 5(2):113–128, 1997. doi:10.3233/JCS-1997-5203.
- 30 Dahlia Malkhi, Michael K Reiter, Avishai Wool, and Rebecca N Wright. Probabilistic quorum systems. Inf. Comput., 170(2):184–206, November 2001.
- 31 Silvio Micali, Michael Rabin, and Salil Vadhan. Verifiable random functions. In 40th annual symposium on foundations of computer science (cat. No. 99CB37039), pages 120–130. IEEE, 1999.
- 32 Satoshi Nakamoto. Bitcoin: A peer-to-peer electronic cash system, 2008.
- 33 Ben Pfaff, Justin Pettit, Teemu Koponen, Ethan J. Jackson, Andy Zhou, Jarno Rajahalme, Jesse Gross, Alex Wang, Jonathan Stringer, Pravin Shelar, Keith Amidon, and Martín Casado. The design and implementation of open vswitch. In *Proceedings of the 12th USENIX Conference on Networked Systems Design and Implementation*, NSDI'15, page 117–130, USA, 2015. USENIX Association.
- 34 Sam Toueg. Randomized byzantine agreements. In Proceedings of the Third Annual ACM Symposium on Principles of Distributed Computing, PODC '84, pages 163-178, New York, NY, USA, 1984. ACM. URL: http://doi.acm.org/10.1145/800222.806744, doi:10.1145/ 800222.806744.
- 35 Marko Vukolic. The origin of quorum systems. Bulletin of the EATCS, 101:125-147, 2010. URL: http://eatcs.org/beatcs/index.php/beatcs/article/view/183.
- 36 Gavin Wood. Ethereum: A secure decentralised generalised transaction ledger. Ethereum project yellow paper, 151(2014):1–32, 2014.

A Proofs

A.1 Witness-Based Broadcast

▶ **Theorem 1.** Algorithm 1 implements Byzantine reliable broadcast.

Proof. Let p_i be a correct process. Since for every p_j correct: $W_i \subseteq V_j$, all correct witnesses in W_i are guaranteed to receive $\lfloor \frac{n+f}{2} \rfloor + 1$ in each protocol phase. Moreover, p_i 's witness-set is always responsive since there are at least k correct witnesses in W_i . Validity follows directly from the responsiveness of witness-sets, and *Integrity* is satisfied by assumptions over digital signatures (we assume every message to be signed by its source).

Because W_i also has at most k-1 faulty processes, p_i is guaranteed to hear from at least one correct process in lines 12 and 16. *Consistency* holds from the fact that a correct witness has to receive $\lfloor \frac{n+f}{2} \rfloor + 1$ (*READY*, m, Π) in order to send (*VALIDATE*, m). Since $f < |\Pi|/3$, every subset of $\lfloor \frac{n+f}{2} \rfloor + 1$ processes intersects in at least one correct process, thus two correct witnesses cannot send *VALIDATE* for distinct messages (this would require a correct process to send *READY* for distinct messages).

If a correct process delivers m, than at least $\lfloor \frac{n+f}{2} \rfloor + 1$ processes sent $\langle READY, m, \Pi \rangle$ to a correct witness, thus, at least f + 1 correct processes sent $\langle READY, m, \Pi \rangle$ to every witness. Consequently, correct witnesses receive f + 1 readies for a message and are able to trigger line 11 to send $\langle READY, \cdot, W \rangle$. In order to send READY without hearing from f + 1 processes, witnesses gather echoes from $\lfloor \frac{n+f}{2} \rfloor + 1$ processes. Similarly to the Consistency

part of the proof, two correct witnesses cannot then send *READY* for distinct messages. Finally, *Totality* holds from the responsiveness of every W_i since every correct witness sends $\langle READY, m, \Pi \rangle$ to all processes.

A.2 Ensuring Close Histories

We now assume that processes are equipped with loosely synchronized clocks (such that timeout values are much bigger than differences in clock measures). We also assume that n = 4f + 1 and quorums used in all protocols are of size n - f. Consider rounds of communication as defined in 6.1. The following conditions must be satisfied at the end of round r to allow a process p to use **WBB** in round r + 1:

- 1. There are at least n f logs for which the set of delivered messages differs from p's set of delivered messages by at most d;
- 2. Let readyM be the set with all messages appearing in at least f + 1 READY logs, then p's set of delivered messages also differs from readyM by at most d messages.

▶ Lemma 2. If a message m is delivered by a process at round r - 1 or earlier, then at least 2f + 1 correct processes send m in their READY log at round r.

Proof. If a correct process delivers m, then at least 2f + 1 processes sent *READY* for m either in **WBB** or in the recovery protocol, and will include m in the log sent to every process at round r.

▶ **Theorem 4.** As long as $\gamma > 3d + 2\Delta \cdot th_{max}$, no pair of processes select witnesses in round r + 1 with histories that differ by more than γ messages.

Proof. Let p and q be correct processes using **WBB** in round r + 1, and let $Hist_p$ (resp. $Hist_q$) be p's history (resp. q's) of delivered messages by the end of round r. From the first condition, there must be a correct process c that sent it's history $Hist_c$ to p and q such that $Hist_p$ and $Hist_q$ differ from $Hist_c$ by at most d messages. This means that $Hist_p$ differs from $Hist_q$ by at most 2d messages.

From Lemma 2, readyM for both p and q includes every message delivered up to round r-1 (which implies $Hist_c \subseteq readyM$), and from the second condition, $Hist_p$ and $Hist_q$ differ from readyM by at most d messages. Now suppose that no new message is delivered in rounds r and r+1, then by the end of round r+1, the difference between $Hist_p$ and $Hist_q$ can be at most 3d. When considering all new messages that can be delivered, by the end of round r+1 the difference between $Hist_p$ and $Hist_q$ can be at most $3d + 2\Delta \cdot th_{max}$, which is smaller than γ .

B Probability Calculations

For a witness set selection to be successful, enough correct processes should be selected to guarantee progress in the protocol. Moreover, to prevent inconsistency not many faulty processes should be selected. Formally, given $k \ge 0$, the witness set W should satisfy:

- \blacksquare (Liveness) W contains at least k correct witnesses.
- \blacksquare (Consistency) W contains at most k-1 faulty witnesses.

XX:20 Dynamic Probabilistic Reliable Broadcast

We assume the selection of witnesses for different pairs of source s and source's sequence number q_s to be independent, meaning that ids are "shuffled" each time a witness-set is sampled to validate a different message. We can ensure this by performing a transformation on ids before calculating the distance to the history: for a particular identifier v, we compute $v' = h(v \oplus h(s, q_s))$. In the following, we consider every identifier v to be shuffled.

Let $|\Pi| = n$, f be the number of faulty processes in Π , and $y_{i,v} \in \mathbb{Z}_r^b$ be the hashed history used for testing a particular identifier $v \in \Pi$ as witness. In the following size(W), corr(W)and faulty(W) denote random variables indicating the witness set size, its number of correct processes and its number of faulty processes respectively. We now proceed to calculate the probability that W satisfies availability and consistency given d.¹² We first consider W to be the same across all correct processes for simplicity of presentation, and later expand the analysis to include the case where the histories differ.

Satisfying Liveness. Let area(v, d) denote the area of the ball with center v and radius d, and c be the number of bits in the resulting sensitive hash. The particular hash position $y_{i,v}$ falls within this ball with probability $p = \frac{area(v,d)}{2^c}$. The selection can thus be modeled as a sequence of n - f independent coin tosses (the number of correct processes), each of which has a probability p of landing heads (here, landing heads means the process is selected as a witness). The number of heads (k) in the sequence follows a binomial distribution:

$$\Pr(\operatorname{corr}(W) \ge k) = \sum_{i=k}^{n-f} \binom{n-f}{i} p^i (1-p)^{n-f-i}$$

Satisfying Safety. Similarly, the number of faulty witnesses can be modelled as a sequence of f independent coin tosses with probability p of landing heads. The probability of having at most k faulty witnesses selected in then:

$$\Pr(faulty(W) < k) = \sum_{i=0}^{k-1} \binom{f}{i} p^i (1-p)^{f-i}$$

Clearly the probabilities of selection of correct and faulty processes are independent, the security parameter ϵ is then calculated as following:

$$\epsilon = 1 - \Pr(corr(W) \ge k) \cdot \Pr(faulty(W) < k)$$

Adding Uncertainty. Consider the case where histories differ by at most μ messages. For a particular identifier v, the resulting hash position $y_{i,v}$ according to different processes in the witness-set selection procedure will also be at most μ distant from one another. Let $center(y_{i,v})$ be the center-point in the ball with radius μ of potential hash-values, and let $d' = d - \mu$. If $center(y_{i,v})$ falls within the ball with center in v and radius d', any hash position $y_{i,v}$ will fall within the ball delimited by v and d. Thus, all hash positions that fall within the ball delimited by v and d' are common witnesses to all processes. Assuming each $center(y_{i,v})$ for $v \in \Pi$ to be randomly distributed, the probability that a particular one falls within this area is $p' = \frac{area(v,d')}{2^c}$.

¹² Recall that d is the radius in the space in \mathbb{Z}_r^b (with center-point $y_{i,v}$ when testing a particular v) used to select the witnesses and is chosen in advance based on the desired expected number of witnesses in a witness set.

We can then calculate the probability of having at least k correct processes in the set of guaranteed common witnesses W':

$$\Pr(corr(W') \ge k) = \sum_{i=k}^{n-f} \binom{n-f}{i} p'^{i} (1-p')^{n-f-i}$$

Let W_i be the witness-set of a correct process, when a correct process appears in W' it also appears in every W_i (since $W' \subseteq W_i$), consequently:

$$\Pr(\forall W_i, corr(W_i) \ge k) \ge \Pr(corr(W') \ge k)$$

On the other hand, let $d'' = d + \mu$, a process v can be a witness for some process only if $center(y_{i,v})$ falls within the the ball delimited by v and d''. Let $p'' = \frac{area(v,d'')}{2^c}$, the probability of having at most k - 1 faulty processes in the set of all potential witnesses W''is:

$$\Pr(faulty(W'') < k) = \sum_{i=0}^{k-1} \binom{f}{i} p''^{i} (1-p'')^{f-i}$$

And because $W_i \subseteq W''$ for every W_i :

 $\Pr(\forall W_i, faulty(W_i) < k) \ge \Pr(faulty(W'') < k)$

C Recovery Protocol

Protocol Description. A process p_i first sends *RECOVER* to every process and includes the latest **WBB** message it has sent with tag [II]. If a process p_j that has already delivered a message *m* receives *RECOVER*, it replies with *m*. When p_i receives f + 1 replies for *m*, it knows at least one is from a correct process, and can safely deliver it. Moreover, when receiving f + 1 *RECOVER* messages, p_j also sends a *RECOVER* to every process (this threshold ensures that at least one correct process should propose to initiate a reliable broadcast instance).

When p_i receives *RECOVER* from $\lfloor \frac{n+f}{2} \rfloor + 1$ processes, if a unique message $m \neq \bot$ was received so far, it then starts Bracha's broadcast *ECHO* phase for m. Otherwise, p_i waits until it receives f + 1 (*READY*, m, $[\Pi]$) from the recovery messages to start echoing. The traditional Byzantine reliable broadcast is then executed.

Correctness. For a particular instance $f < |\Pi|/3$, we assume that for every correct process p_i , W_i has at most k - 1 faulty witnesses:¹³ In addition, we assume the *timeout* time to be set much smaller than the execution time of δ broadcast instances, such that the adversary cannot change the composition of faulty processes in witness-sets before processes timeout.

Lemma 5. If two correct processes p and q deliver m and m', then m = m'.

Proof. There are three different scenarios according to the algorithm in which p and q deliver messages: both deliver in line 17 (Algorithm1), one delivers in line 17 and the other in lines 28 or 41 (Algorithm 4), or both deliver in lines 28 or 41.

¹³Note that these assumptions are weaker than those of 3.2. This is because the addition of the recovery protocol and a timeout compensate for the non-responsiveness of witness-sets.

Algorithm 4 Recovery Protocol

18 upon triggering timeout: if no message has been delivered then 19 $m_{\Pi} \leftarrow \text{last message sent tagged with } \Pi;$ 20 /* $m_{\Pi} \leftarrow \perp$ if none */ send $\langle RECOVER, m_{\Pi} \rangle$ to every $p \in \Pi$; 21 **22 upon** receiving $\langle RECOVER, m_{\Pi} \rangle$ from p_i : $recHist \leftarrow recHist \cup \{m_{\Pi}\};$ 23 if already delivered m then 24 send $\langle REPLY, m \rangle$ to p_i ; $\mathbf{25}$ **26 upon** receiving f + 1 (*REPLY*, m) messages: if no message has been delivered then 27 28 deliver(m);**29 upon** receiving $(RECOVER, \cdot)$ from f + 1 processes such that no RECOVER was sent: $m_{\Pi} \leftarrow$ last message sent with tag [Π]; 30 send $\langle RECOVER, m_{\Pi} \rangle$ to every $p \in \Pi$; 31 **32 upon** receiving $\langle RECOVER, \cdot \rangle$ from $\lfloor \frac{n+f}{2} \rfloor + 1$ processes such that no ECHO was sent: if there is a unique $m \neq \perp$ such that $\langle \cdot, m, [\Pi] \rangle \in$ recHist then 33 send $\langle ECHO, m \rangle$ to every $p \in \Pi$; 34 **35 upon** having f + 1 (*READY*, m, Π) \in recHist such that no ECHO was sent: send $\langle ECHO, m \rangle$ to every $p \in \Pi$; 36 **37 upon** receiving $\lfloor \frac{n+f}{2} \rfloor + 1$ (ECHO, m) or f + 1 (READY, m) messages: send $\langle READY, m \rangle$ to every $p \in \Pi$; 38 **upon** receiving $\langle READY, m \rangle$ from $|\frac{n+f}{2}| + 1$ processes: 39 if no message has been delivered then $\mathbf{40}$ deliver(m);41

In the first case, since at most k-1 witnesses are faulty in each witness set, correct processes receive messages from at least one correct witness in lines 12 and 16, which guarantees *Consistency* (see proof of Theorem 1).

For the second case, if q delivers m' in line 28, it is guaranteed to receive a reply from at least a correct process r. Since processes only take step in Algorithm 4 after timing out or delivering a message, it must be that r delivered m' in line 17. From the first case, m = m'.

On the other hand, if q delivers m' in line 41, it received $\lfloor \frac{n+f}{2} \rfloor + 1 \langle READY, m' \rangle$. Suppose that $m \neq m'$, then $\lfloor \frac{n+f}{2} \rfloor + 1$ processes sent $\langle ECHO, m' \rangle$ (sufficient to make a correct process send ready for m'). But since p delivers m after receiving $\langle VALIDATE, m \rangle$ from at least a correct witness, it is also the case that at least $\lfloor \frac{n+f}{2} \rfloor + 1$ processes sent $\langle READY, m, [\Pi] \rangle$.

Consequently, a correct process r must have sent both $\langle ECHO, m' \rangle$ and $\langle READY, m, \Pi \rangle$. Two scenarios are possible: if r sent ECHO in line 34, then it had readies for m and m' stored

(since r receives $\lfloor \frac{n+f}{2} \rfloor + 1$ recovery messages, as least one contains a $\langle READY, m, \Pi \rangle$), a contradiction with the guard of line 33. If it was in line 36, then a correct process sent $\langle READY, m', \Pi \rangle$, also a contradiction since two correct processes sent $\langle READY, \cdot, \Pi \rangle$ for distinct messages m and m' (see proof of Theorem 1).

In the third case, suppose p delivers m in line28 and q delivers m' in line41. There is a correct process r that delivers m in line 17 and sent a reply to p, which from the second case above implies m = m'. If both deliver m and m' in line 41, there is at least one correct process that send both $\langle READY, m \rangle$ and $\langle READY, m' \rangle$. Since correct processes do not send readies for distinct messages, m = m'.

▶ Lemma 6. If a correct process delivers a message, then every correct process eventually delivers a message.

Proof. A correct process p can deliver a message in three possible occasions: in line 17 (Algorithm 1), and lines 28 and 41 (Algorithm 4).

If p delivers m in line 17, because p's witness-set has at least one correct witness that sends $\langle ECHO, m, W \rangle$ to everyone, every correct process either times-out or delivers a message in line 17 (using witnesses). Moreover, from Theorem 5, no correct process delivers $m' \neq m$. At least one correct witness w sent $\langle VALIDATE, m \rangle$ to $p, \lfloor \frac{n+f}{2} \rfloor + 1$ processes sent $\langle READY, m, \Pi \rangle$ to w, from which at least f + 1 are correct.

If another process q times-out, it can deliver m by receiving f+1 replies from a *RECOVER* message. Suppose q does not receive enough replies, then at least f+1 correct processes do not deliver m in line 17 (Algorithm 1), that is, they timeout. Consequently, every correct process receives f+1 *RECOVER* messages and also send *RECOVER* (even if they already delivered m). q then gathers $\lfloor \frac{n+f}{2} \rfloor + 1$ *RECOVER* messages, and since there is at least one correct process among them that sent $\langle READY, m, \Pi \rangle$, q echoes m (if m is the only gathered message, line 33).

If q receives a distinct m' before echoing a message, it waits for f+1 RECOVER messages containing $\langle READY, m, \Pi \rangle$, which is guaranteed to happen (since at least f+1 correct processes previously sent $\langle READY, m, \Pi \rangle$). Thus, every correct process echoes m, gathers $\lfloor \frac{n+f}{2} \rfloor + 1$ echoes and sends $\langle READY, m \rangle$. Any process that has not delivered a message then receives $\lfloor \frac{n+f}{2} \rfloor + 1$ readies and deliver m.

In the case where p delivers m in line 28, at least one correct process sent reply to p and delivered m in Algorithm 1, which implies the situation described above.

Now suppose that p delivers m in line 41, and no correct process delivers a message in Algorithm 1. p received $\lfloor \frac{n+f}{2} \rfloor + 1 \langle READY, m \rangle$, which at least f + 1 are from correct processes. Moreover, because correct processes wait for $\lfloor \frac{n+f}{2} \rfloor + 1$ echoes (or f + 1 readies) before sending READY, they cannot send READY for distinct messages m and m', since that would imply that a correct process sent ECHO for both messages. Therefore, every correct process q is able to receive f + 1 readies for m and also send ready for it. q then receives $\lfloor \frac{n+f}{2} \rfloor + 1$ readies and deliver m.

▶ Lemma 7. If a correct process broadcasts m, every correct process eventually delivers m.

Proof. If any correct process delivers m, from Lemma 6 every correct process delivers it. Suppose that p is the source and that no process delivers m before it times-out. p then sends RECOVER (including m) to every process, so that even if p reaches no correct witnesses, correct processes still receive a protocol message and initializes the instance. Since no correct process delivers m before timing-out, they also trigger *timeout* and send RECOVER with m. Because p is correct, it sends no protocol message for $m' \neq m$. Every correct process then gathers enough *RECOVER* messages to send *ECHO* and later *READY*. p eventually gathers $\lfloor \frac{n+f}{2} \rfloor + 1$ readies and deliver m.

Lemmas 5, 6 and 7 imply Theorem 8.

▶ **Theorem 8.** The aggregation of Algorithms 1, 3 and 4 satisfy Validity, Consistency and Totality.

D Security Against Passive Attacks

In the passive attack, the adversary waits until the history hash will be such that the selected witness-set for a malicious message will contain many compromised nodes. The selection of each compromised node depends on what can be considered as an independent random walk (the per node history hash) arriving to a small subspace in \mathbb{Z}_r^b (within a defined distance form the message hash).

The expected ratio of compromised nodes in the witness set is their ratio in the total population. We argue that the number of random walk steps (new transactions) required to obtain a much higher ratio of compromised witnesses can be very high. One key indication that it takes long for multiple random walks to co-exist in the same region in \mathbb{Z}_r^b is the linear speedup in parallel coverage time of \mathbb{Z}_r^b [14].

D.1 The Gathering Time Problem

In order to analyze the passive attack time, we simplify the problem by ignoring the number of naive selected nodes and only consider the time till the number of selected compromised nodes exceeds a given ratio of the expected witness set size. We call this time the Gathering Time since the attacker waits till enough random walks gather in a defined area.

Our problem is related Hitting Time bounds [14] which were well studied in recent years and which consider the time it takes for one (or many) random walks to arrive to a specific destination point. The Gathering Time, differs from the Hitting Time in three aspects: 1) instead of a single destination point we are interested in an entire destination area (subspace) around a given point, 2) we require that the random walks will be at the destination area at the same time and 3) we do not require all random walks to arrive at the destination but instead we are interested in the first time that a subset of them, of a given size, will arrive at the destination area. Next we provide an approximation for a lower bound which we compare to simulated random walks results.

D.2 An Approximated Time Lower Bound

We consider nodes initially mapped to points in \mathbb{Z}_r^b and a witness selection based on L_{∞} distance of $r \cdot q/2$ from a reference point in \mathbb{Z}_r^b . We assume the initial mappings of nodes are uniform and independent and change as independent random walks over time (per given message). Without loss of generality, since the space is symmetric and the initial mappings are uniform, we consider the reference point to be the origin, i.e., the all-zeros *b* dimensional vector.

The probability that a node *i* is found at distance at most $p \cdot r$ is equal to the probability that in all *b* dimensions its location is at most $p \cdot r$, i.e. $Pr(dist_i \leq p \cdot r) = (2p)^b$. Therefore,

the probability that a node is selected equals q^b and the expected witness set size is $n \cdot q^b$. We consider configurations where the witness set size is logarithmic with n, i.e., $n \cdot q^b = c \log_2 n$.

Next, we estimate the expected time until at least k out of f compromised nodes will be selected (for a given message), where $t < \frac{1}{3}$ and s > t are the ratio of compromised nodes in the population and witness set respectively, i.e., $f = t \cdot n$ and $k = s \cdot c \cdot n \cdot q^b = s \cdot c \log_2 n$. We split the space into f equally sized subspaces ordered by their distance (from the reference point). On average each subspace contains one compromised node and the k-th closest node, i_k , will be at the k-th closest subspace. We assume that nodes further than i_k will require more time to be selected and we estimate the gathering time for k out of f nodes by the time till selection of the k-th closest node (i_k).

The distance in the k-th closest sub-space is between $r \cdot p_{k-1}/2$ to $r \cdot p_k/2$ where for any $0 < j \leq f$ we define

$$p_{j-1} := (j^{1/b} \cdot 1/f^{1/b}) = (j/f)^{1/b}.$$

We can see that for every j, the probability to be at the *j*-th subspace is $p_j^b - p_{j-1}^b = 1/f$. By using previous notations we can get that the average distance that the k-th closest node should make (in its worst dimension) till selected, D_k , is

$$D_k = r \cdot p_{k-1}/2 - r \cdot q/2 = q \cdot r/2 \cdot ((s/t)^{1/b} - 1).$$

The expected time for one dimensional walk to travel a distance D_k is D_k^2 . Since there are *b* dimensions and a step of the multi dimensional walk selects and affects only one of the dimensions in random, then it will take an expected time of $T_k := b \cdot D_k^2$ to walk a distance D_k at a specific dimension. Therefore we can obtain the following expression:

$$T_k = \frac{b \cdot r^2}{4} \cdot \left(\frac{c \log_2 n}{n}\right)^{\frac{2}{b}} \cdot \left(\left(\frac{s}{t}\right)^{\frac{1}{b}} - 1\right)^2 \tag{3}$$

We consider this expression as a lower bound since it ignores i_k location in other dimensions other than the worst dimension and it ignores the fact that nodes closer than i_k might get outside of the selection area by the time i_k arrives there and becomes selected.

D.3 Experiments and Predictions

In order to evaluate the approximated lower bound we performed a series of (parallel) random walk simulations. Due to the steep increase in gathering time, we implemented the simulations in C and tested only small scale scenarios (100 nodes and small key sizes). The simulations' results, provided in Figure 5, suggest that the bound is valid.

We used the approximate bound to predict the security of scenarios beyond our random walk and full protocol simulations. Considering realistic parameters, similar to those used in the protocol simulations, with larger numbers of nodes, we obtained the results depicted by Figure 6. The results demonstrate that extremely high number of transactions should be accumulated before enough compromised nodes will be selected as witnesses for a given message.

Note that the higher the number of nodes, we expect the rate of transactions to increase, however such increment is insignificant considering the high number of expected transactions until gathering. **Figure 5** Parallel random walk simulation and approximated bound results (in solid and dashed lines respectively) for the gathering time of at least 3 out of 25 random walks, which corresponds to a system with n = 100 nodes of whom 25 are compromised and an attacker that waits to compromise s = 60% of the witness set which is of size $log_2 n$.



Figure 6 Approximated lower bound for the gathering time for different number of nodes (n) with different compromise ratios (t), considering b = 4 dimensional keys of total size 256 bits and an attacker that waits to compromise s = 66% of the witness set which is of size $4log_2n$.

