Causal health impacts of power plant emission controls under modeled and uncertain physical process interference

Nathan B. Wikle^{1*} and Corwin M. Zigler²

¹Department of Statistics and Actuarial Science, University of Iowa ²Department of Statistics and Data Sciences, University of Texas at Austin

May 15, 2024

Abstract

Causal inference with spatial environmental data is often challenging due to the presence of interference: outcomes for observational units depend on some combination of local and non-local treatment. This is especially relevant when estimating the effect of power plant emissions controls on population health, as pollution exposure is dictated by (i) the location of point-source emissions, as well as (ii) the transport of pollutants across space via dynamic physical-chemical processes. In this work, we estimate the effectiveness of air quality interventions at coal-fired power plants in reducing two adverse health outcomes in Texas in 2016: pediatric asthma ED visits and Medicare all-cause mortality. We develop methods for causal inference with interference when the underlying network structure is not known with certainty and instead must be estimated from ancillary data. Notably, uncertainty in the interference structure is propagated to the resulting causal effect estimates. We offer a Bayesian, spatial mechanistic model for the interference mapping which we combine with a flexible non-parametric outcome model to marginalize estimates of causal effects over uncertainty in the structure of interference. Our analysis finds some evidence that emissions controls at upwind power plants reduce asthma ED visits and all-cause mortality, however accounting for uncertainty in the interference renders the results largely inconclusive.

Keywords: causal inference, interference, air pollution, mechanistic models, BART

1 Introduction

For decades, coal-fired power plant facilities have been a primary source of sulfur dioxide (SO₂) emissions in the United States (Cullis & Hirschler 1980, Orellano et al. 2021). One of six "criteria pollutants" for which the US Environmental Protection Agency (EPA) sets national air quality standards (US EPA 2013), sulfur dioxide is notable for its harm to the environment and human health: SO₂ emissions contribute to acidic deposition (US EPA 2003) and are a key contributor to fine particulate matter (PM_{2.5}), which has been associated with various adverse health outcomes, including respiratory and cardiovascular disease and death (Pope et al. 2009). Consequently, interventions which seek to limit SO₂ emissions from power plants have been a regulatory priority in the United States for decades (Dominici et al. 2014), and recent studies have linked pollution derived from such emissions to impacts on all-cause mortality (Henneman et al. 2023) and asthma (Casey et al. 2020) among other health endpoints.

^{*}Please direct correspondence to Nathan Wikle, Email: nathan-wikle@uiowa.edu

Flue-gas desulfurization (FGD) technologies, or *scrubbers*, are one such intervention. FGD scrubbers are installed at coal-fired power plant facilities, where they remove (or "scrub") SO₂ from the facility's combustion gases before they exit the smokestack. The reduction in SO₂ after scrubber installation can be dramatic — in some cases, desulfurization rates may exceed 95% (Li et al. 2022) — which translates into substantial changes to ambient air quality in populations located downwind. A careful understanding of the health benefits of scrubber installation is critical, both when evaluating their retrospective utility and when deciding which facilities should be targeted for future intervention.

In this paper, we seek to estimate the effect of scrubber installation on downwind health outcomes. Evaluating air quality interventions is challenging when treatment exposure is dictated, in part, by an underlying physical process (Zigler & Papadogeorgou 2021, Zigler et al. 2023). Pollutants are not stagnant, but rather are transported and deposited across space via physical processes such as wind and rain, a phenomenon known as *air pollution transport*. Furthermore, SO₂ emissions react with chemical constituents in the atmosphere to form particulate sulfate (SO₄²⁻), contributing to the secondary formation of harmful ambient PM_{2.5} (Pope et al. 2009, Dominici et al. 2014). Thus, the pathway connecting scrubber interventions to health outcomes is governed by the underlying transport and chemical reaction processes that produce harmful PM_{2.5} from power plant emissions.

A feature of this interconnectedness is the possible dependence of health outcomes at a given location on *multiple* upwind treatments. In the causal inference literature, this is referred to as interference (Cox 1958), and its presence complicates effect estimation (Sobel 2006, Karwa & Airoldi 2018). Without additional assumptions on the structure of interference, the number of potential outcomes grows prohibitively large, rendering causal estimands meaningless (Karwa & Airoldi 2018). One solution is to assume that the extent of interference is limited to some (known) network structure. Then, a unit's "treatment" can be deconstructed as two parts: a *direct* intervention, which is assigned locally to the unit, and an *indirect*, or *neighborhood*, treatment exposure, which is defined via a function which maps the interventions of neighboring units to a scalar exposure level. This function has been called an exposure model (Karwa & Airoldi 2018, van der Laan 2014), exposure mapping (Aronow & Samii 2017), or *interference mapping* (Zigler & Papadogeorgou 2021, Zigler et al. 2023), and can be thought of as an extension of partial interference (Sobel 2006, Hudgens & Halloran 2008, Tchetgen Tchetgen & VanderWeele 2012, Forastiere et al. 2016) to more general interference structures. By restricting the treatment space to direct and indirect components, the number of potential outcomes is greatly reduced and causal estimands can be defined via contrasts of direct and indirect treatments (Aronow & Samii 2017, Karwa & Airoldi 2018, Forastiere et al. 2021, Zigler et al. 2023).

To date, almost all examples of causal inference with an exposure model have assumed that the network structure and form of the exposure model — which together define the extent and strength of interference — are known *a priori*. This may be justified when interference is assumed to result from social contacts, including contacts within neighborhoods (Hudgens & Halloran 2008, Perez-Heydrich et al. 2014, Liu & Hudgens 2014), classrooms (Hong & Raudenbush 2006), households (Basse & Feller 2018), and between buyers and sellers in an (online) marketplace (Doudchenko et al. 2020). In these settings, social networks are included in the data collection process and the exposure models are often convenient summaries (e.g., the assumption of stratified interference (Hudgens & Halloran 2008)). However, there is growing recognition that misspecified interference structures (Sävje

2023) or heterogeneity in the type and strength of network interactions (Qu et al. 2022) can impact the robustness of causal effect estimates, particularly in observational studies. Consequently, causal effect estimates may be sensitive to the amount of uncertainty surrounding the specified interference structure, and estimators which incorporate uncertainty in the interference structure may be desired.

In the context of air pollution, the network structure is not well defined by an obvious measure of contact or adjacency. Instead, the dependencies between outcome units and upwind treatments are dictated by the physical process itself (Zigler et al. 2023). Furthermore, air pollution transport is a *stochastic* process, and uncertainty about this process implies uncertainty in the exposure model. Thus, the principal challenge for the statistician — and the question this paper seeks to answer — is whether knowledge and *uncertainty* about this physical process can be incorporated into the definition of meaningful causal estimands and estimation procedures for observational studies with interference.

Whereas Zigler et al. (2023) approached a similar problem through the *a priori* specification of a deterministic pollution transport model, we estimate the interference structure from available atmospheric pollutant and weather data. We do so using a mechanistic, statistical model of atmospheric sulfate, originally developed by Wikle et al. (2022), to characterize the dynamics of — and uncertainty in — the pollution transport process. Notably, the model's mean and covariance structures are specified via an assumed advection-diffusion process, making it particularly well-suited to the problem of delineating how interventions at any given point might impact pollution at other locations. The mechanistic model is used to define a distribution of a (weighted) bipartite network linking scrubber interventions to outcome units, and the outcome's exposure level is then characterized as a weighted average of the treatment status of upwind power plant facilities. Given its dependence on the learned spatio-temporal pollution transport dynamics, the exposure level represents the annual upwind treatment experienced at each outcome unit. Furthermore, our proposed estimation strategy simultaneously accounts for time-varying uncertainty in the transport process. Thus, the proposed interference network and exposure mapping provides an appropriate framework for the identification of the causal health impacts of emissions controls in populations susceptible to annual exposures to harmful particulates. Importantly, uncertainty in the estimated pollution transport process implies uncertainty in the specified interference structure. This paper proposes a two-stage Bayesian estimation procedure to propagate this uncertainty to the causal effect estimates; this can be viewed as relaxing the assumption of a (single) correctly specified interference structure that is commonly found in previous work on causal inference with network interference (Aronow & Samii 2017). This work joins Ohnishi et al. (2023) as one of the first examples of an inferred interference structure, in either the social network (Aronow & Samii 2017, Forastiere et al. 2021) or spatial interference (Reich et al. 2021, Zigler & Papadogeorgou 2021, Zigler et al. 2023, Wang et al. 2023) literature. Notably, Ohnishi et al. (2023) use a Bayesian nonparametric method to estimate a latent exposure mapping within a set of experimental units, while our method uses a mechanistic model of treatment diffusion, fitted to auxiliary data, to estimate the interference structure in an observational study.

Alongside estimation of the structure of interference, we estimate causal effects of scrubbers on 1) pediatric asthma emergency department (ED) visits and 2) all-cause mortality among Medicare beneficiaries in Texas in 2016. We adopt a flexible, Bayesian nonparametric model of the response surface; we use a log-linear Bayesian additive regression tree (BART) model for count data (Murray

2021). This estimation procedure differs from the parametric procedures considered in Forastiere et al. (2021), Zigler et al. (2023), and Forastiere et al. (2022) — we forgo propensity score modeling and instead rely on the nonparametric BART model for the purposes of confounding adjustment (Hill 2011, Hahn et al. 2020). We advocate for a modular approach to Bayesian inference when estimating causal effects with a probabilistic exposure model — this allows us to propagate the uncertainty in the interference structure to the causal effect estimates while avoiding model feedback (Jacob et al. 2017). We compare the performance of this estimator to one which ignores uncertainty in the interference structure — unsurprisingly, incorporating interference uncertainty typically results in wider posterior credible intervals of the effect estimates. However, the total variance of the modular effect estimates can be decomposed into the sum of the variance due to the uncertain interference structure and the variance due to the outcome model. Thus, we can quantify how much of the uncertainty in the causal effect estimates is attributed to uncertainty in the interference structure. We find that modeling and acknowledging uncertainty in the interference structure has important implications for causal inferences about FGD scrubbers and both pediatric asthma ED visits and all-cause Medicare mortality. In particular, we find little evidence that FGD scrubbers affected the rate of asthma ED visits and all-cause Medicare mortality in Texas in 2016; this is especially true when the estimates include uncertainty in the interference structure.

2 Scrubber Locations and Regional Health Outcomes

In 2016, there were 81 coal-fired power plant facilities operating in the area of the central United States expected to possibly influence air pollution exposure in Texas — of those facilities, 48 were outfitted with scrubbers (Figure 1a). Data on power plants were obtained from the US Environmental Protection Agency (EPA) Air Markets Program Database (AMPD) (US EPA 2016), and include several important facility-level variables, including annual SO₂ emissions totals, operating time, and total heat input.

We consider two health outcomes, both previously linked to exposure to $PM_{2.5}$ from power plants: pediatric asthma emergency department (ED) visits (Garcia et al. 2021) and all-cause mortality among Medicare beneficiaries (Dominici et al. 2014). The asthma ED data were obtained from the Texas Health Care Information Collection (THCIC) Emergency Department Research Data File (THCIC 2022), and include counts of pediatric asthma ED visits in Texas, aggregated into annual counts (or rates) according to patient ZIP code of residence. Note that ZIP codes were converted to their corresponding US Census ZIP Code Tabulation Areas (ZCTAs) using a data crosswalk provided by UDS Mapper (2022). The Medicare data were obtained from the Center for Medicare and Medicaid Services, and were similarly aggregated to annual counts of all-cause mortality for each Texas ZCTA. Figure 1b shows the 2016 pediatric asthma rate for 1,935 Texas ZCTAs; we are unable to include a plot of the Medicare deaths that occurred in 2016, matching the temporal resolution of the power plant emissions and SO₄²⁻ data.



(a) Power plants (scrubbers shown in red)

(b) Asthma ED visits in 2016

Figure 1: Treatment and outcome data from our study of air quality interventions, including (a) the location and scrubber status of 81 coal-fired power plant facilities in the central US in 2016 (the interventional units), and (b) the rate of pediatric asthma ED visits in Texas in 2016, aggregated by ZCTA (the outcome units).

3 Bipartite Causal Inference with Interference

3.1 Potential Outcomes for Bipartite Causal Inference

By themselves, the scrubber and outcome data in Section 2 are of limited use — there is not an obvious correspondence between treatment assignment and outcome unit; scrubbers are assigned to points in space (power plant facilities) while health outcomes are reported by ZCTA. In fact, if we assume the existence of interference, we are left wondering which upwind power plant facilities have the largest impact on air pollution exposure within a particular ZCTA. Zigler & Papadogeorgou (2021) have styled this problem as *bipartite causal inference with interference*, in reference to the directional bipartite network possibly linking the set of treatment locations to a separate set of outcome units. Note that this approach is distinct from efforts which seek to estimate the spillover effect as a function of the distance from a spatially-located treatment, such as those considered in Wang et al. (2023) and Pollmann (2023). Importantly, the bipartite framework naturally accommodates the inclusion of known physical processes which contribute to spillover effects; we briefly describe the framework as it applies to the analysis of air quality interventions.

Let $\mathcal{J} = \{1, \ldots, J\}$ be the collection of power plant facilities in our study — we refer to these as the *interventional units*. The treatment status of interventional unit j is denoted with $S_j \in \{0, 1\}$, where 1 indicates the existence of an FGD scrubber at facility j, and 0 otherwise. The treatment vector $\mathbf{S} = (S_1, \ldots, S_J)$ represents the treatments assigned to all interventional units in \mathcal{J} . Finally, $\mathbf{s} \in \mathcal{S}(\mathcal{J})$ denotes a particular realization of the treatment vector \mathbf{S} , where $\mathcal{S}(\mathcal{J})$ is the space of all possible treatment vectors.

Similarly, let $\mathcal{N} = \{1, \ldots, N\}$ denote the set of *outcome units* at which the health endpoints of

interest are observed. In our analysis \mathcal{N} is the collection of 1,935 Texas ZCTAs at which asthma ED visits and Medicare all-cause mortality were reported in 2016. Let Y_i denote the observed health outcome at ZCTA *i* in 2016. Together, the interventional units, \mathcal{J} , and outcome units, \mathcal{N} , form two disjoint sets of vertices of a bipartite graph. Each set of vertices have associated covariates, which we denote as \mathbf{X}^{int} and \mathbf{X}^{out} for the interventional and outcome units, respectively.

The challenge of bipartite causal inference, then, is in the definition of the edge set between \mathcal{J} and \mathcal{N} . Notably, because of the difference in spatial support between the interventional points (power plant locations) and outcome units (ZCTAs), there is not an obvious one-to-one mapping between \mathcal{J} and \mathcal{N} (Zigler & Papadogeorgou 2021, Zigler et al. 2023). Furthermore, the presence of interference implies the existence of *multiple* edges between an outcome unit $i \in \mathcal{N}$ and the intervention set, \mathcal{J} . Thus, without additional structural assumptions on the extent of interference, unit i's potential outcome, $Y_i(s)$ — the outcome that would be observed at unit $i \in \mathcal{N}$ had the treatment vector $s \in \mathcal{S}(\mathcal{J})$ been assigned — depends on the treatment assignment at *every* interventional point $j \in \mathcal{J}$. This means that the number of potential outcomes is very large: for binary interventions, $S_j \in \{0,1\}$, there are 2^J potential outcomes (i.e., $|\{Y_i(s)\}_{s\in \mathcal{S}(\mathcal{J})}| = 2^J$), only one of which is observed.

3.2 Defining an Exposure Model

The large number of potential outcomes can be alleviated if interference can be characterized or approximated by an exposure model, $g_i : S(\mathcal{J}) \to \mathcal{G}$, which maps the treatment space $S(\mathcal{J})$ to a set of scalar exposure values, \mathcal{G} . Then, relevant causal estimands are defined as contrasts of the exposure values $G_i \in \mathcal{G}$ (and possibly some other function of the treatment assignment, such as the treatment status of the nearest power plant). This approach has been used with some success when estimating spillover effects on social networks, where interference is assumed to occur due to social contacts between individuals (Aronow & Samii 2017, Forastiere et al. 2021). In the social network setting, the exposure mapping is defined as a function of the network topology — for example, Forastiere et al. (2021) define g_i as the proportion of unit *i*'s friends who have received treatment. Note that the social network is typically assumed to be static and measured without error in the data collection process.

Zigler et al. (2023) consider a similar approach in the bipartite setting, wherein they define a weighted adjacency matrix, T, connecting interventional and outcome units. The adjacency matrix defines the edge weights of a bipartite graph, $\mathbb{G} = (\mathcal{J}, \mathcal{N}, T)$. The elements of the adjacency matrix, T_{ij} , can be interpreted as the relative influence of interventional unit j on outcome unit i; larger values of T_{ij} indicate particularly influential power plants connected to outcome unit i.

The interference structure is then characterized by two components — a direct and an indirect treatment. Let $j_{(i)}^*$ denote the interventional unit (power plant) that is geographically closest to outcome unit *i*. We call this the key-associated unit (Zigler et al. 2023), and similarly define $Z_i = S_{j_{(i)}^*}$ to be the key-associated treatment for outcome unit *i*. Thus, $Z_i = 1$ if the nearest power plant to ZCTA *i* is scrubbed, and 0 otherwise. This can be thought of as a "direct" treatment on outcome *i*, which is desirable for two reasons. First, it matches the convention in the social network literature (Forastiere et al. 2021), where every unit receives a corresponding direct treatment assignment. Second, and more importantly, it defines the scrubber status of the power plant which is often of most regulatory

or community interest; causal estimands can then be defined which quantify the effect of scrubber installation at the nearest power plant.

The remaining power plant treatments, $S_{-j_{(i)}^*}$, are then mapped to an "indirect", or *upwind*, exposure level, G_i . This is accomplished with an exposure model, $g_i(S_{-j_{(i)}^*}, T) : \{0, 1\}^{J-1} \to G_i$, where $G_i \in \mathcal{G}_i$ denotes a scalar upwind treatment value. Importantly, $g_i(S_{-j_{(i)}^*}, T)$ is a function of the non-key-associated treatments, $S_{-j_{(i)}^*}$, and the bipartite network's adjacency matrix, T. The utility of the exposure model is determined by how well the adjacency matrix, T, links the interventional units (i.e., power plant facilities) to the outcome units most affected by their treatment. If the structure of interference is well-specified by T, then G_i provides an interpretable summary of the upwind treatment status for outcome unit i.

The potential outcomes notation can now be extended to bipartite settings with upwind interference. In particular, when combined with the familiar no multiple versions of treatment (consistency) assumption (Forastiere et al. 2021), the following upwind interference assumption serves as a modified version of the stable unit treatment value assumption (SUTVA) (Zigler et al. 2023):

Assumption 1 (Upwind Interference) For a fixed T and exposure model $g_i(\cdot, T)$, $\forall i \in \mathcal{N}$, and for any two $(\mathbf{S}, \mathbf{S}') \in \mathcal{S}(\mathcal{J})$ such that $Z_i = Z'_i$ and $G_i = G'_i$, the following equality holds:

$$Y_i(\mathbf{S}) = Y_i(Z_i, G_i) = Y_i(Z'_i, G'_i) = Y_i(\mathbf{S}').$$

In other words, we have assumed that the interference structure is completely characterized by an outcome unit's direct and indirect treatment levels, Z_i and G_i . In the power plant example, this implies that the health outcome of interest — i.e., the rate of pediatric asthma ED visits or all-cause mortality among Medicare beneficiaries — in ZCTA *i* would be the same under any two scrubber allocations, (S, S'), so long as the key-associated and upwind exposure levels (Z_i, G_i) remain the same.

3.3 Causal Estimands for Bipartite Interference

The upwind interference assumption is of critical importance — meaningful causal estimands can now be defined as simple contrasts of $Y_i(Z_i, G_i)$. Two estimands are immediately relevant: a "direct" effect, which considers the effect of an intervention at the key-associated interventional unit, and an "indirect" or "upwind" effect, characterizing the spillover effect from treatments at all other interventional units, as summarized by the upwind exposure level, G_i . We formalize these estimands as follows.

Let $\mu(z,g)$ denote the marginal mean of the potential outcome, $Y_i(z,g)$:

$$\mu(z,g) = E(Y_i(Z_i = z, G_i = g)).$$
(1)

This is the expected value of the potential outcome of the *i*th outcome unit when the key-associated intervention has treatment value z and the upwind treatment level is g. Thus, $\mu(z,g)$ is an average dose-response function (or surface) for different levels of Z_i and G_i . For convenience, we have implicitly assumed that the potential outcome $Y_i(z,g)$ is defined for all values of $g \in \mathcal{G}$ and for all outcome units $i \in \mathcal{N}$; the definition can be suitably modified when the interference structure prohibits certain values of g for some i (Forastiere et al. 2021). Furthermore, we have construed the potential outcomes for each unit as random variables; in Section 5 we discuss how to estimate these unobserved random variables using (nonparametric) Bayesian models.

Using the above notation, we define the direct effect as

$$DE(g) = \mu(1,g) - \mu(0,g),$$
(2)

the expected effect of treating the key-associated unit, while holding the upwind units' treatment level constant. Notably, DE(g) is a function of g, which allows for the possibility that the effect of a scrubber on the closest power plant is heterogeneous with respect to the scrubber intensity of upwind facilities. If desired, we can marginalize over g to define an *average direct effect* of the key-associated treatment, $ADE = \sum_{g \in \mathcal{G}} DE(g)\hat{P}(g)$, where $\hat{P}(g)$ denotes the estimated distribution of G_i across the study domain.

Similarly, we define the indirect (or upwind) effect as

$$IE(z,g) = \mu(z,g) - \mu(z,g_{min}).$$
 (3)

Here, IE(g; z) denotes the expected change in outcome as the upwind treatment exposure changes from some baseline value, g_{min} , to an exposure level g, while the key-associated treatment level is fixed at z. Thus, IE(z, g) represents the expected spillover effect of the upwind (i.e., non-key-associated) treatments, which may vary with g and z. The choice of baseline value g_{min} is application specific, for example, it could be set to zero, or to the minimum level of G_i observed with the data. Finally, the average indirect effect is defined as $AIE(z) = \sum_{g \in G} IE(z, g)\hat{P}(g)$.

4 Estimating the Interference Structure with a Mechanistic Spatial Model

The utility of the bipartite potential outcomes framework, as outlined in Section 3, hinges on the specification of the network adjacency matrix (T) so that the exposure model $(g_i(\cdot, T))$ carries sufficient interpretability to define meaningful direct and indirect causal effects. Of course, the central challenge of this work is that T cannot be observed — there is no preordained network connecting power plant facilities to ZCTAs. Furthermore, simple proximity-based assignment of ZCTAs to power plants would grossly simplify the process of long-range pollution transport. Instead, our knowledge of the underlying mechanisms governing pollution transport — and human exposure to harmful particulate matter — can be leveraged to estimate T.

Estimation of the interference structure consists of two steps: first, we use a mechanistic statistical model of sulfate pollution to estimate the long-range pollution transport dynamics; we then extract T from the fitted model. Notably, the estimated uncertainty about the process dynamics induces a probability distribution on T, which in turn leads to uncertainty in G_i . It's reasonable to ask what is gained from estimating (with uncertainty) the interference structure from observed pollution concentrations, rather than using output from a deterministic chemical transport model. For example, Zigler et al. (2023) characterize T using output from a reduced-complexity atmospheric model (HyADS, see Henneman, Choirat, Ivey, Cummiskey & Zigler (2019)), and there exists a rich body of work developing deterministic physical models of air pollution. However, these deterministic models can be computationally intensive, particularly at the spatial resolution considered in our analysis, and are themselves associated with uncertainty that cannot be easily quantified. Furthermore, pollution transport is an inherently random process — small variations in factors such as wind velocity, precipitation, and chemical reactants contribute to the realized pollution exposure — and it seems desirable that process uncertainty should propagate both to the interference structure and to the causal estimates.

4.1 A mechanistic model of annual sulfate

We define a mechanistic model of annual sulfate concentrations in the US, in which the transport process is estimated, with uncertainty, from three 2016 data sources: coal-fired power plant emissions totals, average atmospheric sulfate concentrations, and average yearly wind velocity. The data are shown in Figure 2a, and were obtained from the EPA AMPD (US EPA 2016), the Atmospheric Composition Analysis Group (van Donkelaar et al. 2019), and the NCEP/NCAR reanalysis database (Kalnay et al. 1996), respectively. Most statistical approaches for modeling air pollution exposures are phenomenological, which would focus in this case on accurately interpolating a surface from observed sulfate measurements (van Donkelaar et al. 2019, Guan et al. 2020), without characterizing how pollution moves from one location to another. Consequently, their ability to link power plant emissions to expected pollution concentrations is limited. In contrast, we use the class of mechanistic statistical models developed by Wikle et al. (2022), in which known process dynamics of pollution transport, defined as a linear stochastic partial differential equation (SPDE), are approximated in discrete space as a multivariate Ornstein-Uhlenbeck (OU) process. This model can be easily fit to the data in Figure 2a, and provides inference on how changes in SO_2 emissions at a specific point dictate changes across the entire sulfate surface. We briefly describe the model, deferring to Wikle et al. (2022) for details.

Let $\eta(\mathbf{s}, t)$ denote the concentration of atmospheric SO₄²⁻ at location $\mathbf{s} \in \mathcal{D} \subset \mathbb{R}^2$ and time $t \in \mathbb{R}^+$, and let $\nu(\mathbf{s}, t)$ denote the corresponding local SO₂ concentration. We model pollution transport as a coupled advection-diffusion process:

$$d\nu(\boldsymbol{s},t) = \left(-\mathcal{L}_{\boldsymbol{\theta}}(\boldsymbol{s},t)\,\nu(\boldsymbol{s},t) + R_{\boldsymbol{\theta}}(\boldsymbol{s},t)\right)dt \tag{4}$$

$$d\eta(\boldsymbol{s},t) = \left(-\mathcal{A}_{\boldsymbol{\theta}}(\boldsymbol{s},t)\eta(\boldsymbol{s},t) + \theta_{3}\nu(\boldsymbol{s},t)\right)dt + \xi(\boldsymbol{s},t)$$
(5)

Equation (4) approximates how emissions from power plants move in space and time, defining the transport of SO₂ across space: $-\mathcal{L}_{\theta}(s,t) = (\Delta_{\theta_1} - \boldsymbol{w} \cdot \nabla_{\theta_2} - \theta_3)$ is an advection-diffusion operator, where Δ_{θ_1} denotes homogeneous diffusion with rate θ_1 (Δ is the Laplace operator in \mathbb{R}^2), $\boldsymbol{w} \cdot \nabla_{\theta_2}$ denotes advection due to wind (\boldsymbol{w} is the wind velocity field, θ_2 is a constant rate of advection), and θ_3 is the rate at which SO₂ is oxidized into SO₄²⁻. Finally, $R_{\theta}(\boldsymbol{s},t)$ represents sources of SO₂ emitted at location \boldsymbol{s} and time t. Note that the operator $\mathcal{L}_{\theta}(\boldsymbol{s},t)$ acts on $\nu(\boldsymbol{s},t)$, the local concentration of SO₂, while the emissions sources, $R_{\theta}(\boldsymbol{s},t)$, are independent of $\nu(\boldsymbol{s},t)$.

Equation (5) approximates how ambient sulfate pollution moves in time and space, defining a similar advection-diffusion process for SO_4^{2-} , with three important distinctions. First, the advection-

diffusion operator $-\mathcal{A}_{\theta}(s,t) = (\Delta_{\theta_1} - \boldsymbol{w} \cdot \nabla_{\theta_2} - \delta)$ is almost identical to $\mathcal{L}_{\theta}(s,t)$, however, θ_3 (the oxidation rate of SO₂ \rightarrow SO₄²⁻) has been replaced with δ , the rate of atmospheric deposition of SO₄²⁻. Second, the source term, $R_{\theta}(s,t)$, has been replaced with $\theta_3\nu(s,t)$, which accounts for the reaction of SO₂ into SO₄²⁻. Third, we have introduced a space-time Gaussian noise process, $\xi(s,t)$, to account for space-time varying sources and sinks of SO₄²⁻ that were otherwise unspecified in the model; the addition of $\xi(s,t)$ makes (5) an SPDE.

Together, (4) and (5) model a physical system in which (i) SO₂ is emitted from the point locations of operating power plants, (ii) SO₂ emissions are advected across space by wind, (iii) SO₂ reacts into SO₄²⁻, which is itself advected across space before eventual atmospheric deposition, and (iv) the system is inherently random, better reflecting possible fluctuations due to changes in weather, elevation, or chemical constituents that are otherwise unaccounted for in the model. However, solving the SPDE remains a challenge. A solution to this problem, as outlined by Wikle et al. (2022), is to approximate (4) and (5) in discrete space with an Ornstein-Uhlenbeck (OU) process (Uhlenbeck & Ornstein 1930). Then, the distributional properties of the OU process are leveraged to define a Gaussian likelihood model for spatial data, where the process dynamics, as specified in (4) and (5), determine the mean and covariance structure of the model.

For the sake of brevity, the discretization details have been confined to the Supplementary Material. Instead, we focus on the resulting mechanistic statistical model: let $\bar{\eta}$ denote the observed annual average SO₄²⁻ concentrations, as shown in Figure 2a. The resulting likelihood model is

$$\bar{\boldsymbol{\eta}} \sim N \bigg(\beta_0 + \boldsymbol{\mu}_{\boldsymbol{\theta}}(\boldsymbol{R}), \, \boldsymbol{\Sigma}_{\boldsymbol{\theta}} \bigg),$$
(6)

where $\mu_{\theta}(\mathbf{R})$ denotes the expected annual average sulfate (as specified by the advection-diffusion process in (4) and (5)) attributable to the annual coal-fired power plant SO₂ emissions totals, \mathbf{R} , and Σ_{θ} denotes the covariance matrix, which has a simultaneous autoregressive (SAR) structure defined according to the specified dynamic process (see the attached Supplementary Material), as well as Wikle et al. (2022), for detailed descriptions of μ_{θ} , Σ_{θ} , and the choice of priors for θ). Note the dependence of μ_{θ} and Σ_{θ} on θ , the (unknown) parameters from the advection-diffusion process. Finally, a small difference with Wikle et al. (2022) is the inclusion of β_0 , which represents "background" SO₄²⁻ from emissions sources outside the study area.

A likelihood derived from (6) was fitted to the 2016 annual average sulfate data (Figure 2a). We used a Bayesian approach for inference: independent half-normal and exponential priors were chosen for θ and β_0 , and posterior samples were obtained via Metropolis-Hastings MCMC. Figure 2b shows $\hat{\mu}_{\bar{\theta}}$, the estimated posterior mean sulfate concentrations attributable to coal-fired power plant SO₂ emissions in 2016, without background sources. Finally, we note that the estimated mean annual sulfate concentrations are comparable to estimates from a deterministic, reduced-complexity atmospheric model, with broadly similar spatial patterns exhibiting more spatial diffusion and higher estimated levels of SO₄²⁻ (Supplementary Material).

Figure 2 illustrates two important advantages of this spatial model. First, because it is mechanistic, it can be used to estimate sulfate concentrations under counterfactual emissions scenarios by estimating how a change in emissions at any power plant impacts SO_4^{2-} across the entire region. This

will prove useful when defining the network adjacency matrix, T, and distinguishes it from alternative phenomenological statistical models of air pollutants, which focus on spatial interpolation rather than mechanism (van Donkelaar et al. 2019, Guan et al. 2020). Second, it includes estimates and uncertainty quantification about the process parameters θ . In contrast, more complex numerical models of air pollution, such as chemical transport models, plume models, and their reduced form hybrids (Foley et al. 2014, Henneman, Choirat, Ivey, Cummiskey & Zigler 2019) are often deterministic (and computationally expensive). Thus, this model's ability to infer (simplified) process dynamics and stochastic fluctuations from data makes it an ideal candidate for defining the dependence between regional outcome units (ZCTAs) and upwind power plant facilities.



(a) Average 2016 sulfate concentrations



Figure 2: A summary of the learned air pollution transport dynamics, including (a) the observed 2016 average sulfate concentrations, overlaid with power plant SO_2 emissions totals and average 2016 wind velocities (at a height of 10 m above ground), and (b) the estimated 2016 sulfate concentrations attributed to coal-fired power plant emissions.

4.2 Estimating the interference structure with uncertainty

The learned dynamics in Section 4.1 can be used to define a probabilistic network adjacency matrix, T, connecting the interventional units, \mathcal{J} , to the outcome units, \mathcal{N} . For a given outcome unit i, we are interested in identifying the upwind power plants that have the greatest *potential* influence on pollution exposure. Consequently, we would expect scrubbers placed at these influential power plants to have a larger effect on pollution exposure. We characterize the relative influence of an interventional unit j on outcome unit i through a source-receptor (SR) matrix, which we define using μ_{θ} , the mean function of our mechanistic spatial model. Let $D_i \subset \mathbb{R}^2$ denote ZCTA i's geographic boundary and let r_j denote an emissions scenario in which power plant j emits 1000 tons of SO₂ in 2016, and all other coal-fired power plant SO₂ emissions are set to zero. Then, T_{ij} is defined as

$$T_{ij} = \frac{1}{|D_i|} \int_{D_i} \boldsymbol{\mu}_{\boldsymbol{\theta}}(\boldsymbol{r}_j), \tag{7}$$

the expected average $\mathrm{SO}_4^{2^-}$ concentration in ZCTA *i* per 1000 tons SO_2 emitted from facility *j*. This calculation is repeated for all outcome unites, $i \in \mathcal{N}$, and for all interventional units, $j \in \mathcal{J}$. The resulting SR matrix defines the edge weights of a bipartite graph, $\mathbb{G} = (\mathcal{J}, \mathcal{N}, T)$; larger values of T_{ij} indicate particularly influential power plants connected to outcome unit *i*. Characterizing an SR matrix by sequentially evaluating emissions from individual sources parallels traditional efforts used to evaluate power plant impacts, but typical reliance on chemical transport modeling for this purpose proves computationally prohibitive for a large number of individual source-population links (Buonocore et al. 2014).

The definition of T in (7) is dependent on the specified process parameters, θ , and the uncertainty around these parameters can be propagated to T. In particular, if $\theta^{(k)} \sim \pi(\theta | \bar{\eta}, \mathbf{R})$ is a sample from the posterior of θ , then $T^{(k)}$ denotes the associated adjacency matrix estimated with $\mu_{\theta^{(k)}}$. Repeating this for all MCMC samples of θ provides samples from $\pi(T | \bar{\eta}, \mathbf{R})$, the distribution over T. In short, we have estimated an interference structure with uncertainty: the pollution transport dynamics are learned from the available sulfate data, and the learned dynamics define the distribution of a weighted network connecting power plant facilities to ZCTAs.

4.3 Defining an exposure model

Finally, we use T to define a (probabilistic) exposure model, g_i . As discussed in Section 3, each outcome unit i is assigned a direct treatment value, $Z_i = S_{j_{(i)}^*}$, which denotes the scrubber status of the key-associated interventional unit, $j_{(i)}^*$. The treatment vector of the remaining interventional units, $S_{-j_{(i)}^*}$, is mapped to an indirect treatment level, G_i . Let

$$G_i \equiv g_i(\mathbf{S}_{-j_{(i)}^*}, T) = \sum_{j \neq j_{(i)}^*} T_{ij} S_j / T_{i\cdot}^*,$$
(8)

where $T_{i\cdot}^* = \sum_{j \neq j_{(i)}^*} T_{ij}$ is the (weighted) degree of node *i*. Note that G_i represents the weighted proportion of treated upwind (i.e., non-key-associated) power plants; treated facilities that are more influential (as measured by *T*) contribute to larger values of G_i . Once again, the estimated uncertainty in $\boldsymbol{\theta}$ can be propagated to G_i by repeatedly calculating $G_i^{(k)}$ using different samples from $\boldsymbol{\theta}^{(k)} \sim \pi(\boldsymbol{\theta}|\bar{\boldsymbol{\eta}}, \boldsymbol{R})$. Direct and indirect causal estimands can now be defined as contrasts of potential outcomes, $Y_i(Z_i, G_i)$, as shown in Section 3.

5 Estimating Causal Effects using Poisson Regression with BART

In the simplified case where G_i is fixed and known, identification of the direct and indirect treatment effects, DE(g) and IE(z,g), requires additional assumptions of unconfoundedness. In particular, the presence of two treatment components to characterize interference necessitates an extension of the familiar ignorable treatment assumption (Zigler et al. 2023):

Assumption 2 (Ignorability of Joint Treatment Assignment)

$$Y_i(z,g) \perp Z_i, G_i \mid \boldsymbol{X}_i^{out}, \, \boldsymbol{h}(\{\boldsymbol{X}_j^{int}\}_{j \in \mathcal{J}}), \, \forall z \in \{0,1\}, \forall g \in \mathcal{G}_i, \forall i \in \mathcal{N}$$

In other words, the assignment of the key-associated treatment, Z_i , and the upwind treatment, G_i , are independent of the potential outcomes, conditional on a set of local (outcome unit) covariates, X_i^{out} , and a (possibly multivariate) function of covariates associated with the interventional units, $h(\{X_j^{int}\}_{j\in\mathcal{J}})$. The need to condition on both outcome and interventional unit covariates is a distinct feature of bipartite networks, as discussed in Zigler et al. (2023), and the exact specification of X_i^{out} and $h(\{X_j^{int}\}_{j\in\mathcal{J}})$ should be guided by application-specific knowledge of potential confounders. In addition, identification of DE(g) and IE(z, g) requires a common assumption of overlap,

$$0 < p\left(Z_i = z, G_i = g \mid \boldsymbol{X}_i\right) < 1,$$

where $X_i \equiv \{X_i^{out}, h(\{X_j^{int}\}_{j \in \mathcal{J}})\}$. Given these two assumptions,

$$\mu(z,g) = \frac{1}{n} \sum_{i=1}^{n} E(Y_i | X_i = x_i, Z_i = z, G_i = g),$$
(9)

and the estimation of $\mu(z,g)$ has been simplified to a more familiar task: estimating the response surface,

$$E(Y_i \mid Z_i = z, G_i = g, \boldsymbol{X}_i = \boldsymbol{x}).$$
(10)

In particular, we estimate (10) with a log-linear Bayesian additive regression trees (BART) model for count data. First introduced by Murray (2021), log-linear BART is an extension of BART for continuous data with Gaussian errors (Chipman et al. 2010) to regression models with Gamma-Poisson likelihoods. Letting Y_i denote the observed count outcome data, the log-linear BART model for Poisson regression is defined as

$$Y_i | \boldsymbol{x}_i, z_i, g_i \sim \operatorname{Pois}\left(\mu_{0i} f_{\boldsymbol{\alpha}}(\boldsymbol{x}_i, z_i, g_i)\right), \tag{11}$$

$$\log f_{\alpha} = \sum_{k=1}^{m} h(\boldsymbol{x}_i, z_i, g_i; \alpha_h).$$
(12)

Here, $\mu_{0i} f_{\alpha}(\boldsymbol{x}_i, z_i, g_i)$ is the conditional expected value of Y_i , μ_{0i} denotes a fixed offset (such as ZCTA population size), and log f_{α} is a flexible sum of m independent regression trees, $h(\boldsymbol{x}_i, z_i, g_i; \alpha_h)$, where α_h denotes the tree parameterization (Murray 2021). Fitting this model is non-trivial; Murray (2021) proposes a mixture of generalized inverse Gaussian distributions as a conjugate prior for the leaf parameters, which allows for a block MCMC update of the tree structure and leaf parameters. The BART-based model — appropriately extended to count data — retains the flexible nonparametric structures that have led to the increased popularity of BART for causal inference (Hill 2011, Dorie et al. 2019, Hahn et al. 2020), and also represents a departure from previous methods for interference based on propensity score modeling (Forastiere et al. 2022, 2021, Zigler et al. 2023). In particular, BART's documented strengths include the ability to prioritize among a potentially high-dimensional set of covariates and nonlinarities among them.

6 Propagating Interference Uncertainty to the Causal Estimates

Finally, we consider how uncertainty in the estimated interference structure might be propagated to the causal effect estimates. This premise assumes that the assumptions of Section 5 hold, at least approximately, for every value of G simulated from the posterior of the process model. As discussed in Section 4.2, the sulfate model — and the corresponding interference structure — was based on our underlying knowledge of the physical sulfate transport process. Consequently, we want to avoid unwanted "feedback" from the health outcome model influencing inference for the treatment model parameters. Furthermore, misspecification of either model may lead feedback from one model to "corrupt" the other, introducing bias or misleading uncertainty quantification of the causal effects.

To combat the possibility of unwanted feedback, we advocate for a *modular* approach to inference, in which the interference structure (i.e., the sulfate model) is estimated without inclusion of the health outcomes data. As discussed in Jacob et al. (2017), Bayesian modularization schemes are increasingly relevant in many applied settings, including studies with uncertain air pollution estimates (Blangiardo et al. 2016, Comess et al. 2022). Rather than targeting the full Bayesian posterior, we instead obtain inference using the "cut function,"

$$\pi^*(\boldsymbol{\alpha}, \boldsymbol{\theta} \mid \boldsymbol{y}, \bar{\boldsymbol{\eta}}) = \pi(\boldsymbol{\alpha} \mid \boldsymbol{y}, \boldsymbol{\theta}) \pi(\boldsymbol{\theta} \mid \bar{\boldsymbol{\eta}}).$$
(13)

Note that (13) is not equivalent to the full Bayesian posterior, as the dependence of $\boldsymbol{\theta}$ on \boldsymbol{y} has been "cut." As discussed in Plummer (2015), sampling from (13) is non-trivial. Typically, inference proceeds via a computationally-intensive, multiple imputation approach: K samples of $\boldsymbol{\theta}$ are first obtained via MCMC from the first module, $\pi(\boldsymbol{\theta} | \boldsymbol{\eta})$. Then, for each $\boldsymbol{\theta}^{(k)}$, independent MCMC chains are run targeting the posterior of the second module, $\pi(\boldsymbol{\alpha} | \boldsymbol{y}, \boldsymbol{\theta}^{(k)})$. The resulting pooled samples provide a Monte Carlo approximation to (13). Furthermore, using Rubin's combining rules for multiple imputation (Rubin 1987) (see the Supplementary Material for details), we can quantify the total variance of an estimator as the sum of the outcome model variance (i.e., the "within variance") and the interference model variance (i.e., the "between" variance). This between/within assessment is an important advantage of this modular approach, as it allows us to quantify how much uncertainty in the causal effect estimates can be attributed to uncertainty in the interference structure. When uncertainty in the estimated interference structure dominates the uncertainty in the causal effect estimates, the interpretations of the effect estimates should be discussed in the context of the estimated interference structure.

In a simulation study designed to investigate the bias and coverage properties of the proposed estimator, we compare the above with a simpler "plug-in" estimator, in which the outcome model is fitted conditional on the posterior mean estimate of the process parameters, $\bar{\theta} = E(\theta|\bar{\eta})$, i.e., uncertainty from the interference structure is *not* propagated to the causal effect estimates. A detailed discussion of the simulation design and results is included in Supplementary Material. In general, we found that the two estimators exhibit similar levels of bias, however their coverage properties often differ. In particular, the plug-in estimator's posterior credible interval coverage rates were almost always lower than the estimator which incorporated uncertainty in the interference structure; this was especially pronounced when the outcome model was otherwise correctly specified. We also compared estimation using a log-linear BART response surface model (Section 5) with a simple parametric alternative. Log-linear BART proved adept at estimating increasingly nonlinear dose-response surfaces, albeit with more conservative uncertainty quantification. Finally, Rubin's combining rules were used to quantify the variance in the estimates attributed to uncertainty in the interference structure; large differences in coverage rates between the two estimators were associated with a high proportion of variance attributed to the interference model.

7 Effects of Scrubbers on Pediatric Asthma and Medicare Mortality in Texas

Using the methods described in the preceding sections, we estimate the effect of scrubber presence at coal-fired power plants in 2016 on all-cause mortality among Medicare beneficiaries and pediatric asthma emergency department visits in Texas during that same year. As described in Section 4, the interference structure is estimated from a mechanistic model connecting power plant SO₂ emissions to annual sulfate concentrations; the model is fitted to the observed 2016 average annual sulfate concentrations, SO₂ emissions totals, and average (10m) wind velocities (Figure 2). Given the estimated interference structure and the scrubber status of the 81 coal-fired power plants operating in the study region in 2016 (Figure 1a), we assign key-associated and upwind treatment levels to 1935 Texas ZC-TAs. Figure 3 shows the spatial distribution of key-associated and upwind treatments across Texas: 55% of the ZCTAs are key-associated with a scrubbed facility, while the median value of \bar{G}_i is 0.74 (range: 0.23–0.91).



(a) Key-associated treatment, Z_i . (b) Mean upwind treatment, \overline{G}_i (c) Standard deviations of G_i .

Figure 3: The key-associated and upwind treatment levels used in the analysis. Note that the distribution of G is summarized using (b) the posterior mean estimate, \bar{G}_i , and (c) the marginal posterior standard deviation.

Twenty eight covariates were used in the analysis (Table 1), including ZCTA-level demographic data obtained from the US census, climate data (such as annual total precipitation, average minimum and maximum daily temperature, and average relative humidity), annual mean black carbon concentrations, smoking prevalence, and power plant characteristics, including the annual operating time and heat input of the key-associated facility, distance to key-associated facility, and two summary statistics of the upwind facilities: the weighted degree, $T_{i\cdot}^* = \sum_{j \neq j_{(i)}^*} T_{ij}$, which quantifies ZCTA *i*'s potential exposure to SO_4^{2-} due to emissions from upwind power plants, and $\sum_{j \neq j_{(i)}^*} \mathrm{heat}_j T_{ij}/T_{i\cdot}^*$, the weighted average of the upwind power plant heat inputs. The ZCTA demographic and climate features were selected for their known relevance to variation in pollution-related health endpoints, and the black carbon concentration as a general marker of urban pollution that is not related to power plants. Power plant characteristics (and their summary functions) are chosen to account for the possibility that certain types of plants are more or less likely to install scrubbers. The inclusion of both of these types of covariates accounts for the possibility that power plants choose to install scrubbers based in part on the knowledge of downwind population features. Further discussion of the types of confounding that should be considered in bipartite networks and with power plants specifically appears in Zigler et al. (2023).

We implemented covariate balancing propensity scores (CBPS) (Imai & Ratkovic 2014, Fong et al. 2018) for the sole purpose of evaluating covariate balance and overlap across treatment levels of Z_i and \bar{G}_i . For binary treatment Z_i , we compared the covariates' absolute standardized mean differences between treated and untreated units (Austin 2009), while balance for continuous treatment \bar{G}_i was assessed using the Pearson correlation between covariate and treatment (Austin 2019). The results are displayed in the Supplementary Material: in general, unadjusted comparisons exhibited moderate to severe imbalance, however, these imbalances were largely resolved after propensity score adjustment. Similarly, propensity score overlap was achieved across treatment levels using CBPS. Even though inference for causal effects will not be based on the CBPS, this analysis indicates plausibility of the BART approach to adjust for observed confounding without extrapolation due to lack of overlap.

| Texas ZCTA Covariates | | |
|-----------------------------------|-------------------------|-------------------------------|
| US Census Data | 11. movement rate | 21. black carbon |
| 1. total population | 12. $\%$ insured | Smoking Data |
| 2. % female | 13. $\%$ renter housing | 22. Smoking rate |
| 3. % kids $(0 - 17 \text{ y.o.})$ | 14. % urban | Power Plant Data |
| 4. median age | 15. population density | 23. key-assoc. operating time |
| 5. % white | Climate Data | 24. heat input |
| 6. % black | 16. precipitation | 25. % capacity |
| 7. % hispanic | 17. minimum daily temp. | 26. distance to key-assoc. |
| 8. % high school graduate | 18. maximum daily temp. | 27. upwind heat input |
| 9. % below poverty level | 19. vapor pressure | 28. weighted degree |
| 10. median income | 20. relative humidity | |

Table 1: Covariates included in the analysis, including demographic, climate, and facility-level data.

We considered two Poisson regressions to model $E(Y_i | \mathbf{X}_i, Z_i, G_i)$: (i) a log-linear BART model (12), where the rate function, $f_{\alpha}(\mathbf{x}_i, z_i, g_i)$, is defined as the log-linear sum of m independent regression trees, and (ii) a parametric Poisson regression model with log-linear rate function,

$$\log f_{LM}(\boldsymbol{x}_i, z_i, g_i) = \boldsymbol{x}'_i \boldsymbol{\beta} + \phi z_i + \gamma g_i + \psi z_i g_i.$$
(14)

In both models, μ_{0i} is included as a population offset. Given the spatial structure of the outcome data, we used Moran's *I* to test for spatial autocorrelation in the fitted models' residuals (Cliff & Ord 1981). The tests found no significant evidence of spatial autocorrelation with either pediatric asthma ED visits or Medicare all-cause mortality as the outcome; this was true for both the parametric and nonparametric regression, and was invariant to the choice of spatial weights matrix or type of residual

(see the Supplementary Material for details). Other settings that do exhibit spatial autocorrelation might benefit from the inclusion of a spatial random effect in the Poisson GLM or nontrivial extensions to the log-linear BART model, possibly following the example of Müller et al. (2007).

Modular Bayesian inference was performed using both the interference uncertainty method described in Section 6 and a simpler plug-in posterior mean estimate of the interference structure; the interference uncertainty method was fitted in parallel using 250 independent draws from $\pi(\theta|\bar{\eta})$. The log-linear BART models were assigned m = 200 additive trees, using the tree splitting rules and leaf prior tuning parameter specification recommended by Murray (2021). Posterior samples for all models were obtained using Metropolis-Hastings MCMC, and all analysis was conducted in R, version 4.1.3 (repository: https://github.com/nbwikle/estimating-interference).



7.1 Medicare all-cause mortality

Figure 4: Estimated direct (DE(g)) and indirect (IE(z,g)) effects of coal-fired power plant scrubbers on the 2016 rate of all-cause mortality among Medicare beneficiaries in Texas.

The estimated direct and indirect (i.e., upwind) effects of scrubbers on all-cause mortality among

Medicare beneficiaries are shown in Figure 4. Notably, there is little evidence that the presence of scrubbers on key-associated power plants had a significant effect on the rate of all-cause mortality among Texas Medicare beneficiaries in 2016 (Figure 4A). The estimates are similar when using either the parametric or log-linear BART outcome models, as well as either the plug-in or interference uncertainty methods. In contrast, the estimated indirect effects, IE(z,g), vary based on the choice of outcome model and modular inference (Figures 4B and C). If we restrict our focus to the log-linear BART estimate with plug-in inference, we see some evidence that an increase in the proportion of scrubbed upwind power plants caused a reduction in all-cause mortality per 1000 Medicare beneficiaries (albeit with large uncertainty bounds). For example, in the absence of a scrubber at the closest power plant, the estimated effect of an increase in the proportion of scrubbed power plants from $g^*=0.25$ to $\bar{g}_{0.5}=0.74$ (the median average exposure level across all ZCTAs) is $\widehat{IE}(0,\bar{g}_{0.5})=0.74$ -13.6 (95% CI: (-44.0, 6.5)). However, the corresponding estimate accommodating uncertainty in the interference is $\widehat{IE}(0,\overline{g}_{0.5}) = -4.5$ (-28.8, 13.9), and in general, the estimate of $\widehat{IE}(z,g)$ with interference uncertainty has shifted towards zero. In other words, the decision to propagate uncertainty in the interference structure had a substantial impact on the magnitude and interpretation of the estimated causal effects. We see similar results when comparing the parametric Poisson estimates — there is little evidence that an increased proportion of upwind scrubbers had a significant effect on the rate of all-cause mortality among Texas ZCTAs in 2016. However, note that the uncertainty bounds for the estimates that propagate uncertainty in the interference structure are much wider than the plug-in alternatives, particularly in the parametric Poisson case when the proportion of variance attributable to the interference structure is large compared to that from the BART models.

7.2 Pediatric asthma ED visits

We performed a similar analysis of the impact of coal-fired power plant scrubbers on the rate of pediatric asthma-related ED visits in Texas in 2016; the results are shown in Figure 5. First, consider the log-linear BART plug-in estimates: $\widehat{DE}(q)$ is concentrated around zero, providing little evidence that the presence of a scrubber at the nearest power plant facility had a significant effect on the rate of pediatric asthma ED visits in 2016. In contrast, the estimated indirect effect curves suggest that the rate of pediatric asthma ED visits was reduced as the proportion of scrubbed upwind power plants increased from 0.25 to 0.7, for example, $I\tilde{E}(0,0.7) = -2.8$ (95% CI: (-5.6,-0.4)). However, once again the addition of uncertainty from the interference estimates advises caution — after accounting for uncertainty in the interference structure, it is no longer clear that an increase in the proportion of scrubbed upwind power plants caused a noticeable reduction in the 2016 rate of pediatric ED visits in Texas. Finally, we note that the parametric Poisson estimates differ substantially from the BART estimates, and in some cases, they suggest that the presence of scrubbers led to an increase in the rate of ED visits. However, there is reason for skepticism of the parametric estimates: the high proportion of variance attributed to uncertainty in the interference structure, combined with the very large uncertainty bounds around the interference uncertainty method's estimates, suggests that the Poisson regression model was not flexible enough to correctly characterize the response surface. In contrast, the log-linear BART model accommodates nonlinearity and interactions between confounders



Figure 5: Estimated direct (DE(g)) and indirect (IE(z,g)) effects of coal-fired power plant scrubbers on the 2016 rate of pediatric asthma ED visits in Texas.

and treatment variables, contributing to the difference in point estimates and uncertainty bounds when compared with the parametric alternative.

8 Discussion

To our knowledge, this analysis represents the first example of an observational study in which the physical mechanism for interference has been estimated from available ancillary data. Our methods are especially relevant when evaluating the effectiveness of point-source air pollution interventions on downwind health outcomes: the impact of a change in emissions is likely non-local, as its effect on downwind pollution concentrations is dependent on the advection and reaction of pollutants across a wide spatio-temporal domain. Consequently, understanding of the pollution transport dynamics is necessary if we wish to characterize the spillover effects of multiple interventions across space. We showed how the mechanistic statistical model developed by Wikle et al. (2022) can be used to estimate

the process dynamics from annual average sulfate concentrations; the estimated dynamics defined a weighted bipartite network linking interventional units to outcome locations, and a corresponding (probabilistic) exposure model was defined on the bipartite network. The need to estimate the dynamics is accompanied by inherent uncertainty, which we accommodate by averaging causal estimates over the range of possible interference structures as indicated by the posterior distribution of the spatio-temporal process.

As with all observational studies, the results from our analysis should be considered in the context of the broader literature on the health impacts of air pollution exposure. For example, a number of studies have linked short and long-term pollution exposure with reduced pediatric lung function (Garcia et al. 2021). while exposure to SO_4^{2-} and $PM_{2.5}$ is associated with a variety of adverse health outcomes (Dominici et al. 2014), including increased risk of mortality (Pope et al. 2009), although the literature on health impacts attributable to $PM_{2.5}$ derived specifically from coal-fired power plants is evolving (Henneman et al. 2023, Henneman, Choirat & Zigler 2019). Consequently, it is worth asking why the estimated direct and indirect effects in Section 7 are not more pronounced. First, we caution that the estimated causal effects are limited to the spatial and temporal extent of our study (i.e., observations from Texas ZCTAs in 2016). Furthermore, we note that estimating the health impacts of *specific interventions* intended to control point-source pollution involves considerable difficulties and uncertainties — such as understanding the spatio-temporal dynamics and complex interactions of the pollution transport process — that are often not present in the more common task of estimating health impacts of (locally-measured) ambient pollution itself.

Our estimates are most comparable to those of Zigler et al. (2023), who estimate the causal effects of emissions controls on Medicare ischemic heart disease (IHD) hospitalizations in the eastern US during 2005, where coal power plant pollution is more prominent than in Texas during 2016 (Henneman, Choirat, Ivey, Cummiskey & Zigler 2019). As with our analysis, Zigler et al. (2023) did not find significant evidence of a direct effect (i.e., the effect of key-associated scrubbers on IHD hospitalizations). However, they did identify a significant reduction in IHD hospitalizations caused by an increase in upwind treatments. In contrast, the estimates from our analysis had wider uncertainty bounds, especially when including uncertainty in the estimated interference structure. We hypothesize that this may be due to (i) health outcomes (i.e., pediatric asthma and all-cause mortality) that are less affected by scrubbers than IHD hospitalizations, (ii) the smaller spatial and temporal extent used in our analysis compared to similar epidemiological studies (e.g., Henneman et al. 2023) (iii) a time frame of study that took place when power plant pollution exposures were reduced relative to earlier years, or (iv) the incorporation of uncertainty in the interference structure. Finally, we note that although our analysis has adjusted for many potential confounders, the regulatory and market incentives driving some power plants to install scrubbers and the process dictating how these decisions propagate into pollution exposures remains incompletely understood, presenting, as with all observational studies, the lingering threat of unmeasured confounding.

This paper focuses on the estimation of an interference network originating from a complex physical system, and its success depends on a number of components, including the proposed bipartite causal inference framework, a mechanistic statistical model of air pollution transport, modularized Bayesian inference, modern extensions to Bayesian nonparametric modeling of count data, and the satisfaction of causal assumptions across different values of the exposure mapping dictated by uncertainty in the physical process model. Consequently, there are several possible extensions to this work. Chief among them is its extension to the spatio-temporal setting — the installation of scrubbers changes over time, as do air pollution dynamics. Thus, the estimation of a spatio-temporal model of air pollution transport, and the corresponding time-varying interference structure, would lead to a more complete understanding of the effects of air pollution controls on health outcomes. In addition, extensions of this work to settings with higher-resolution outcome data, such as point-referenced outcomes, may allow for inferences that are more robust to the problems of ecological fallacy common when using spatially aggregated health data (Diggle & Elliott 1995). Other natural extensions might include adapting log-linear BART to target regularization-induced confounding (Hahn et al. 2020) and better accommodate the estimation of heterogeneous effects, pursuing computational alternatives to the modularized Bayesian inference, or considering other strategies for confounding adjustment such as those based on (generalized) propensity scores. Furthermore, our choice of direct and indirect treatment, Z_i and G_i , corresponds to only one of many possible exposure mappings, and alternative specifications relevant to other scientific questions of interest could be further explored (see, e.g., Section 7 of the Supplementary Material).

Above all, the work offered here is designed as an installment of methodology for observational studies with process-driven interference, which are of anticipated relevance for a variety of problems in the environmental and physical sciences. Dynamic spatio-temporal models (Wikle & Hooten 2010) and scientific machine learning methods (Rackauckas et al. 2021) are increasingly able to learn complex physical processes from massive scientific data sets. When possible, these estimated dynamics can help inform the topology linking interventions located at points or regions in space to relevant outcome units. Examples include assessing the impact of agricultural runoff on the health of downstream ecological systems (Xia et al. 2020), estimating the effect of hydraulic fracturing on the frequency and severity of earthquakes in the surrounding shale play (McClure et al. 2017), or attributing extreme weather events to climate change (Wehner 2023). Furthermore, estimated dynamical processes may be of use in causal settings beyond the bipartite interference framework considered in this paper, perhaps suggesting spatially heterogeneous extensions to the spillover estimands of Wang et al. (2023) and Pollmann (2023), as well as a framework for causal inference with process-driven stochastic interventions (Díaz Muñoz & van der Laan 2012). Ultimately, we believe that the continued development of process-informed causal methods is an important component in the creation and evaluation of effective health and environmental policies.

Acknowledgements

This work was supported by research funding from NIH R01ES026217, R01ES034803, and US EPA 83587201. Its contents are solely the responsibility of the grantee and do not necessarily represent the official views of the USEPA. Further, USEPA does not endorse the purchase of any commercial products or services mentioned in the publication.

We are grateful to Jared Murray for his helpful discussion and code base for the log-linear BART implementation. We also thank three anonymous reviewers for their helpful comments. The authors acknowledge the Texas Advanced Computing Center (TACC) at The University of Texas at Austin for providing HPC resources that have contributed to the research results reported within this paper. URL: http://www.tacc.utexas.edu

Supplementary Material

Supplementary materials can be found at https://github.com/nbwikle/estimating-interference. This includes a discussion of the discrete space approximation of the sulfate model, an assessment of covariate balance and overlap, a detailed simulation study of the proposed estimator, a sensitivity study of the log-linear BART tuning parameters, replication of the analysis without a key-associated treatment, and a test for spatial autocorrelation. We have also included all code and any publicly available data from the analysis.

References

- Aronow, P. M. & Samii, C. (2017), 'Estimating average causal effects under general interference, with application to a social network experiment', *The Annals of Applied Statistics* **11**(4), 1912 1947.
- Austin, P. C. (2009), 'Balance diagnostics for comparing the distribution of baseline covariates between treatment groups in propensity-score matched samples', *Statistics in Medicine* **28**(25), 3083–3107.
- Austin, P. C. (2019), 'Assessing covariate balance when using the generalized propensity score with quantitative or continuous exposures', *Statistical Methods in Medical Research* **28**(5), 1365–1377.
- Basse, G. & Feller, A. (2018), 'Analyzing two-stage experiments in the presence of interference', Journal of the American Statistical Association 113(521), 41–55.
- Blangiardo, M., Finazzi, F. & Cameletti, M. (2016), 'Two-stage bayesian model to evaluate the effect of air pollution on chronic respiratory diseases using drug prescriptions', *Spatial and Spatio-temporal Epidemiology* 18, 1–12. Environmental Exposure and Health.
- Buonocore, J. J., Dong, X., Spengler, J. D., Fu, J. S. & Levy, J. I. (2014), 'Using the community multiscale air quality (cmaq) model to estimate public health impacts of pm2.5 from individual power plants', *Environment International* 68, 200–208.
- Casey, J. A., Su, J. G., Henneman, L. R. F., Zigler, C., Neophytou, A. M., Catalano, R., Gondalia, R., Chen, Y.-T., Kaye, L., Moyer, S. S., Combs, V., Simrall, G., Smith, T., Sublett, J. & Barrett, M. A. (2020), 'Improved asthma outcomes observed in the vicinity of coal power plant retirement, retrofit and conversion to natural gas', *Nature Energy* 5(5), 398–408.
- Chipman, H. A., George, E. I. & McCulloch, R. E. (2010), 'BART: Bayesian additive regression trees', The Annals of Applied Statistics 4(1), 266 – 298.
- Cliff, A. D. & Ord, J. K. (1981), Spatial processes, Pion Limited.

- Comess, S., Chang, H. H. & Warren, J. L. (2022), 'A Bayesian framework for incorporating exposure uncertainty into health analyses with application to air pollution and stillbirth', *Biostatistics*.
- Cox, D. R. (1958), Planning of Experiments, Wiley, New York.
- Cullis, C. & Hirschler, M. (1980), 'Atmospheric sulphur: Natural and man-made sources', Atmospheric Environment (1967) 14(11), 1263–1278.
- Díaz Muñoz, I. & van der Laan, M. (2012), 'Population intervention causal effects based on stochastic interventions', *Biometrics* 68(2), 541–549.
- Diggle, P. & Elliott, P. (1995), 'Disease risk near point sources: statistical issues for analyses using individual or spatially aggregated data.', Journal of Epidemiology & Community Health 49(Suppl 2), S20–S27.
- Dominici, F., Greenstone, M. & Sunstein, C. R. (2014), 'Particulate matter matters', *Science* **344**(6181), 257–259.
- Dorie, V., Hill, J., Shalit, U., Scott, M. & Cervone, D. (2019), 'Automated versus Do-It-Yourself Methods for Causal Inference: Lessons Learned from a Data Analysis Competition', *Statistical Science* 34(1), 43 – 68.
- Doudchenko, N., Zhang, M., Drynkin, E., Airoldi, E., Mirrokni, V. & Pouget-Abadie, J. (2020), 'Causal inference with bipartite designs'.
- Foley, K. M., Napelenok, S. L., Jang, C., Phillips, S., Hubbell, B. J. & Fulcher, C. M. (2014), 'Two reduced form air quality modeling techniques for rapidly calculating pollutant mitigation potential across many sources, locations and precursor emission types', *Atmospheric Environment* 98, 283 – 289.
- Fong, C., Hazlett, C. & Imai, K. (2018), 'Covariate balancing propensity score for a continuous treatment: Application to the efficacy of political advertisements', *The Annals of Applied Statistics* 12(1), 156 – 177.
- Forastiere, L., Airoldi, E. M. & Mealli, F. (2021), 'Identification and estimation of treatment and interference effects in observational studies on networks', *Journal of the American Statistical Association* 116(534), 901–918.
- Forastiere, L., Mealli, F. & VanderWeele, T. J. (2016), 'Identification and estimation of causal mechanisms in clustered encouragement designs: Disentangling bed nets using bayesian principal stratification', Journal of the American Statistical Association 111(514), 510–525.
- Forastiere, L., Mealli, F., Wu, A. & Airoldi, E. M. (2022), 'Estimating causal effects under network interference with bayesian generalized propensity scores', *Journal of Machine Learning Research* 23(289), 1–61.

- Garcia, E., Rice, M. B. & Gold, D. R. (2021), 'Air pollution and lung function in children', *Journal of Allergy and Clinical Immunology* **148**(1), 1–14.
- Guan, Y., Johnson, M. C., Katzfuss, M., Mannshardt, E., Messier, K. P., Reich, B. J. & Song, J. J. (2020), 'Fine-scale spatiotemporal air pollution analysis using mobile monitors on google street view vehicles', JASA 115(531), 1111–1124.
- Hahn, P. R., Murray, J. S. & Carvalho, C. M. (2020), 'Bayesian Regression Tree Models for Causal Inference: Regularization, Confounding, and Heterogeneous Effects (with Discussion)', *Bayesian* Analysis 15(3), 965 – 2020.
- Henneman, L., Choirat, C., Dedoussi, I., Dominici, F., Roberts, J. & Zigler, C. (2023), 'Mortality risk from united states coal electricity generation', *Science* 382(6673), 941–946.
- Henneman, L. R., Choirat, C., Ivey, C., Cummiskey, K. & Zigler, C. M. (2019), 'Characterizing population exposure to coal emissions sources in the united states using the hyads model', Atmospheric Environment 203, 271–280.
- Henneman, L. R., Choirat, C. & Zigler, C. M. (2019), 'Accountability assessment of health improvements in the united states associated with reduced coal emissions between 2005 and 2012', *Epidemi*ology **30**(4), 477–485.
- Hill, J. L. (2011), 'Bayesian nonparametric modeling for causal inference', Journal of Computational and Graphical Statistics 20(1), 217–240.
- Hong, G. & Raudenbush, S. W. (2006), 'Evaluating kindergarten retention policy', Journal of the American Statistical Association 101(475), 901–910.
- Hudgens, M. G. & Halloran, M. E. (2008), 'Toward causal inference with interference', Journal of the American Statistical Association 103(482), 832–842.
- Imai, K. & Ratkovic, M. (2014), 'Covariate balancing propensity score', Journal of the Royal Statistical Society: Series B (Statistical Methodology) 76(1), 243–263.
- Jacob, P. E., Murray, L. M., Holmes, C. C. & Robert, C. P. (2017), 'Better together? statistical learning in models made of modules'.
- Kalnay, E., Kanamitsu, M. & 19 others (1996), 'The ncep/ncar 40-year reanalysis project', Bull. Amer. Meteor. Soc. 77, 437 – 470.
- Karwa, V. & Airoldi, E. M. (2018), 'A systematic investigation of classical causal inference strategies under mis-specification due to network interference'.
- Li, X., Han, J., Liu, Y., Dou, Z. & an Zhang, T. (2022), 'Summary of research progress on industrial flue gas desulfurization technology', *Separation and Purification Technology* **281**, 119849.
- Liu, L. & Hudgens, M. G. (2014), 'Large sample randomization inference of causal effects in the presence of interference', Journal of the American Statistical Association 109(505), 288–301.

- McClure, M., Gibson, R., Chiu, K.-K. & Ranganath, R. (2017), 'Identifying potentially induced seismicity and assessing statistical significance in oklahoma and california', *Journal of Geophysical Research: Solid Earth* 122(3), 2153–2172.
- Müller, P., Shih, Y.-C. T. & Zhang, S. (2007), 'A spatially-adjusted Bayesian additive regression tree model to merge two datasets', *Bayesian Analysis* 2(3), 611 – 633.
- Murray, J. S. (2021), 'Log-linear bayesian additive regression trees for multinomial logistic and count regression models', *Journal of the American Statistical Association* **116**(534), 756–769.
- Ohnishi, Y., Karmakar, B. & Sabbaghi, A. (2023), 'Degree of interference: A general framework for causal inference under interference'.
- Orellano, P., Reynoso, J. & Quaranta, N. (2021), 'Short-term exposure to sulphur dioxide (so2) and allcause and respiratory mortality: A systematic review and meta-analysis', *Environment International* 150, 106434.
- Perez-Heydrich, C., Hudgens, M. G., Halloran, M. E., Clemens, J. D., Ali, M. & Emch, M. E. (2014), 'Assessing effects of cholera vaccination in the presence of interference', *Biometrics* **70**(3), 731–741.
- Plummer, M. (2015), 'Cuts in bayesian graphical models', Statistics and Computing 25, 37–43.
- Pollmann, M. (2023), 'Causal inference for spatial treatments'.
- Pope, C. A., Ezzati, M. & Dockery, D. W. (2009), 'Fine-particulate air pollution and life expectancy in the united states', *New England Journal of Medicine* **360**(4), 376–386.
- Qu, Z., Xiong, R., Liu, J. & Imbens, G. (2022), 'Efficient treatment effect estimation in observational studies under heterogeneous partial interference'.
- Rackauckas, C., Ma, Y., Martensen, J., Warner, C., Zubov, K., Supekar, R., Skinner, D., Ramadhan, A. & Edelman, A. (2021), 'Universal differential equations for scientific machine learning'.
- Reich, B. J., Yang, S., Guan, Y., Giffin, A. B., Miller, M. J. & Rappold, A. (2021), 'A review of spatial causal inference methods for environmental and epidemiological applications', *International Statistical Review* 89(3), 605–634.
- Rubin, D. B. (1987), Multiple Imputation for Nonresponse in Surveys, John Wiley & Sons, Ltd.
- Sävje, F. (2023), 'Causal inference with misspecified exposure mappings: separating definitions and assumptions', *Biometrika* p. asad019.
- Sobel, M. E. (2006), 'What do randomized studies of housing mobility demonstrate?', Journal of the American Statistical Association **101**(476), 1398–1407.
- Tchetgen Tchetgen, E. J. & VanderWeele, T. J. (2012), 'On causal inference in the presence of interference', Statistical Methods in Medical Research 21(1), 55–75.

- THCIC (2022), 'Texas hospital emergency department research data file', https://www.dshs.texas. gov/thcic/Texas-Hospital-Emergency-Department-Research-Data-File-(ED-RDF)/.
- UDS Mapper (2022), 'Uds mapper: Zip code to zcta crosswalk', https://udsmapper.org/ zip-code-to-zcta-crosswalk/.
- Uhlenbeck, G. E. & Ornstein, L. S. (1930), 'On the theory of the brownian motion', *Phys. Rev.* **36**, 823–841.
- US EPA (2003), 'Latest findings on national air quality: 2002 status and trends', https://www.epa. gov/air-trends/historical-air-quality-trends-reports.
- US EPA (2013), 'America's children and the environment. third edition', https://www.epa.gov/ americaschildrenenvironment/americas-children-and-environment-third-edition.
- US EPA (2016), 'Air markets program data', https://ampd.epa.gov/ampd/.
- van der Laan, M. J. (2014), 'Causal inference for a population of causally connected units', *Journal* of Causal Inference **2**(1), 13–74.
- van Donkelaar, A., Martin, R. V., Li, C. & Burnett, R. T. (2019), 'Regional estimates of chemical composition of fine particulate matter using a combined geoscience-statistical method with information from satellites, models, and monitors', *Environmental Science & Technology* 53(5), 2595–2611.
- Wang, Y., Samii, C., Chang, H. & Aronow, P. M. (2023), 'Design-based inference for spatial experiments under unknown interference'.
- Wehner, M. (2023), 'Connecting extreme weather events to climate change', *Physics Today* **76**(9), 40–46.
- Wikle, C. K. & Hooten, M. B. (2010), 'A general science-based framework for dynamical spatiotemporal models', *TEST* 19(3), 417–451.
- Wikle, N. B., Hanks, E. M., Henneman, L. R. F. & Zigler, C. M. (2022), 'A mechanistic model of annual sulfate concentrations in the united states', *Journal of the American Statistical Association* 0(0), 1–12.
- Xia, Y., Zhang, M., Tsang, D. C., Geng, N., Lu, D., Zhu, L., Igalavithana, A. D., Dissanayake, P. D., Rinklebe, J., Yang, X. & Ok, Y. S. (2020), 'Recent advances in control technologies for non-point source pollution with nitrogen and phosphorous from agricultural runoff: current practices and future prospects', *Applied Biological Chemistry* 63(8).
- Zigler, C., Liu, V., Mealli, F. & Forastiere, L. (2023), 'Bipartite interference and air pollution transport: Estimating health effects of power plant interventions'.
- Zigler, C. M. & Papadogeorgou, G. (2021), 'Bipartite Causal Inference with Interference', Statistical Science 36(1), 109 – 123.