Approximation Algorithms for the Graph Burning on Cactus and Directed Trees

Rahul Kumar Gautam, Anjeneya Swami Kare, and S. Durga Bhavani

School of Computer and Information Sciences, University of Hyderabad, Hyderabad, India 19mcpc06@uohyd.ac.in,askcs@uohyd.ac.in,sdbcs@uohyd.ac.in

Abstract. Given a graph $G = (V, E)$, the problem of GRAPH BURNING is to find a sequence of nodes from V , called a burning sequence, to burn the whole graph. This is a discrete-step process, and at each step, an unburned vertex is selected as an agent to spread fire to its neighbors by marking it as a burnt node. A burnt node spreads the fire to its neighbors at the next consecutive step. The goal is to find the burning sequence of minimum length. The Graph Burning problem is NP-Hard for general graphs and even for binary trees. A few approximation results are known, including a 3-approximation algorithm for general graphs and a 2-approximation algorithm for trees. The Graph Burning on directed graphs is more challenging than on undirected graphs. In this paper, we propose 1) A 2 .75-approximation algorithm for a cactus graph (undirected), 2) A 3-approximation algorithm for multi-rooted directed trees (polytree) and 3) A 1 .905-approximation algorithm for single-rooted directed tree (arborescence). We implement all the three approximation algorithms and the results are shown for randomly generated cactus graphs and directed trees.

1 Introduction

In a public information campaign, choosing people who can spread authentic information within a village network in the least possible time is important. This problem is modeled as Graph Burning problem, which is defined as a discrete step sequential process. One node is selected at each time-step t as a source of fire which burns all of its neighbors at the next time step $t+1$. Another node is picked as the source of fire at time $t + 1$, and the process of burning continues till all the nodes of the graph are burned. The burned nodes can burn their neighbors at the next step. The information can be passed from informed nodes in the previous time step. The sequence of nodes selected as fire sources is a burning sequence. An informed node remains in an informed or burned state throughout the process. The goal is to compute the burning sequence of minimum length. The length of the optimal burning sequence is called the burning number of the graph, denoted by $b(G)$. Note that $b(G)$ is a positive integer. The GRAPH Burning problem is similar to the k-centre problem [\[7\]](#page-18-0), in which all the sources

of fire are selected in the first step itself. The applications of Graph Burning problem can be seen in political campaigns [\[9\]](#page-18-1) and satellite communication [\[19\]](#page-19-0).

Let $G(V, E)$ be a finite, connected, unweighted, and undirected graph having a set of vertices V and edges E. Let $S = \{v_0, v_1, v_2, \cdots v_{b-1}\}\$ be a burning sequence. At time t_0 , the vertex v_0 is burnt. At time t_1 , the vertex v_1 is burnt, and the neighbors of vertex v_0 are also burnt. Similarly, at time t_i , the vertex v_i is burnt, and all the vertices which caught fire at the time t_{i-1} will burn their unburned neighbors. The process continues until all the nodes of the graph are burnt. The burning process for the directed graphs is very similar, except that a node burns its out-neighbors.

In this paper, we propose the following approximation algorithms:

- 1. A 2.75-approximation algorithm for the cactus graph.
- 2. A 3-approximation algorithm for the multi-rooted directed trees. This leads to a 2-approximation algorithm for single-rooted directed trees.
- 3. A 1.905-approximation algorithm for the single-rooted directed trees.

2 Related Work

Bonato et al. [\[2\]](#page-18-2) proposed the GRAPH BURNING problem. They studied characteristics and proposed bounds for the Graph Burning problem. Bonato et al. [\[3\]](#page-18-3) and Bessy et al. [\[20\]](#page-19-1) proved that the Graph Burning problem is NP-Complete for general undirected graphs, binary trees, spider graphs, and path forests. Bessy et al. [\[1\]](#page-18-4) proved bounds for general graphs and trees. For a con-nected graph G of order n, Bonato et al. [\[3\]](#page-18-3) gave upper bound $b(G) \leq 2\sqrt{n-1}$ and conjectured an upper bound of $\lceil \sqrt{n} \rceil$. Bessy et al. [\[1\]](#page-18-4) improved the bounds for connected graphs and trees. For connected graph G with n vertices, for $0 < \epsilon < 1, b(G) \leq \sqrt{\frac{32}{19} \cdot \frac{n}{1-\epsilon}} + \sqrt{\frac{27}{19\epsilon}}$ and $b(G) \leq \sqrt{\frac{12n}{7}} + 3$. For a tree T of order *n*, if n_2 is the number of vertices of degree 2 and $n_{\geq 3}$ is the number of vertices with the degree at least three, then $b(T) \leq \lceil \sqrt{(n+n_2) + \frac{1}{4} + \frac{1}{2}} \rceil$ and b(T) $\leq \lceil \sqrt{n} \rceil + n_{\geq 3}$. Land and Lu [\[15\]](#page-19-2) improved the upper for connected graphs $\frac{\sqrt{6}}{2}$ $\frac{1}{\sqrt{n}}$.

The Graph Burning problem is fixed-parametrized tractable (FPT) for parameters: distance to cluster and neighborhood diversity [\[13\]](#page-19-3). Kare et al. [\[13\]](#page-19-3) proved that the problem is polynomial-time solvable for cographs and split graphs. Later, Yasuaki et al. [\[14\]](#page-19-4) proved that the Graph Burning problem is $W[2]$ -Complete for the parameter $b(G)$ and is FPT for the combined parameter of clique-width and the maximum diameter among the connected components. The GRAPH BURNING problem was studied for different classes of graphs such as spider graphs [\[5\]](#page-18-5), generalized Peterson graphs [\[18\]](#page-19-5), dense graphs [\[12\]](#page-19-6) and theta graphs [\[16\]](#page-19-7). Further, several heuristics [\[19](#page-19-0)[,6,](#page-18-6)[8\]](#page-18-7) have been proposed based on centrality measures and the graph structure for the Graph Burning problem. A generalization of GRAPH BURNING problem called k -burning problem is studied in [\[17\]](#page-19-8).

Bonato et al. [\[4\]](#page-18-8) proposed a 3-approximation algorithm for general graphs, a 2-approximation algorithm for trees, and a 1.5-approximation algorithm for disjoint paths. Bonato et al. [\[4\]](#page-18-8) also showed that the Graph Burning problem could be solved in polynomial time on path forests, where the number of paths is constant. Further, they proposed approximation schemes for the path forests where the number of paths is not constant. Recently, Diaz et al. [\[11\]](#page-18-9) proposed an approximation algorithm with approximation factor $3 - 2/b(G)$ for general graphs.

Janssen et al. [\[10\]](#page-18-10) studied the GRAPH BURNING problem for directed graphs. They studied the problem for directed acyclic graphs and directed trees. Janssen et al. [\[10\]](#page-18-10) showed that Graph Burning problem is NP-Complete for directed trees and directed acyclic graphs (DAG). They proved that the Graph Burning problem is FPT for trees with burning number as the parameter and W[2]-Hard for DAG with burning number as the parameter.

The rest of the paper is organized as follows: In section [3,](#page-2-0) we discuss the approximation algorithm for the cactus graph. In section [4,](#page-6-0) we present 3-approximation algorithm for polytrees (directed multi-rooted tree). Section [4.1](#page-10-0) discusses the 1.905-approximation algorithm for directed trees (arborescence).

For $b \in Z^+$, the sources of fire have the corresponding burning ranges $[b 1, b - 2, b - 3, \dots$ 0. Throughout the paper, for any decimal value k, by burning range bk, we mean, $[b * k]$.

3 Approximation algorithm for cactus

Bonato et al. [\[4\]](#page-18-8) proposed a 3-approximation algorithm for the general undirected graphs and a 2-approximation algorithm for trees. A cactus graph is an undirected graph in which any pair of simple cycles share at most one vertex. A cactus graph is structurally close to a tree.

The 3-approximation and $(3-2/b(G))$ -approximation algorithms for general graphs apply to the cactus. There is no known less than 3-approximation algorithm for graphs that contain cycles. This paper proposes a 2.75-approximation algorithm for the cactus graph. The algorithm takes a cactus graph G and a positive integer b as input and returns a burning sequence of length 2.75b or returns **BAD-GUESS** (-1) to indicate that the graph can not be burned in at most b rounds.

If the cactus graph has no articulation point, then the graph is a single cycle, and hence the problem is polynomial time-solvable [\[2\]](#page-18-2). In the rest of the paper, we assume that the cactus graph has at least one articulation point. The algorithm is as follows: For burning number 2.75b, we have the sequence BR , which contains *b* number of burning ranges as shown below.

$$
BR = \underbrace{[1.75b, 1.75b + 1, 1.75b + 2, \cdots, 2b - 1, \underbrace{2b, 2b + 1, \cdots 2.75b - 1}_{BR_2}]}
$$

For the first part $|BR_1| = 0.25b$ and contains burning radii of range at least 1.75b. And for the second part $|BR_2| = 0.75b$ and contains burning radii of range at least $2b - 2$.

Input: The graph $G=(V,E)$ and $b \in Z^+$. Output : Either the algorithm returns a burning sequence or BAD-GUESS (-1).

- 1. Initially, all the vertices of graph G are unmarked.
- 2. Initialize, variables $b_1 = |BR_1| = [0.25b]$, $b_2 = |BR_2| = [0.75b]$ and the corresponding burning sequences $BS_1 = BS_2 = []$ and a random articulation point r.
- 3. If all vertices of the graph are marked,
	- Return (BS_1, BS_2) .
- 4. Select the farthest unmarked node f from r .
	- (a) If there exists a path $P = \{v_1 = f, v_2, \dots, v_k\}$ from the node f towards the root r and v_k is an articulation point such that $0.25b \leq d(f, v_k) \leq$ 1.75b and $b_1 \geq 1$, then
		- Add source of the fire v_k to BS_1 .
		- Mark all vertices u in $\{v \in V(G) : d(v_k, v) \leq 1.75b\}$
		- Decrease b_1 by 1.
	- (b) Else-if $b_2 \geq 1$,
		- Add source of the fire f to BS_2 .
		- Mark all vertices u in $\{v \in V(G) : d(f, v) \leq 2b 2\}.$
		- Decrease b_2 by 1.
	- (c) Else
		- return BAD-GUESS (-1) .
- 5. Repeat steps 3-4 until all the vertices of graph G get marked and return the burning sequence or return -1.

Initially, all the vertices of graph G are unmarked. We take an arbitrary articulation point $r \in V$ as a root. Let the unmarked farthest node from r be f, and $N_x[f]$ be the union of all **unmarked** vertices around f up to burning range $x \in Z^+$ in the burning process. Obviously for any $u, v \in V(G)$, if $u \notin N_{2b-2}[v]$, to burn both the vertices (u and v) we need at least 2 rounds if $b(G) \leq b$. The question is: can we mark all w in $N_{2b-2}[v]$ in less than the $2b-2$ burning range(radius)? Yes, it is possible due to the presence of articulation points in the cactus graph. The importance of articulation points in the graph is shown in Fig. [1.](#page-4-0) If we mark the vertices up to distance 10 around f , then the vertices 5 and 8 are not covered. On the other hand, if we mark the vertices around the vertex v_k up to distance 7, all the vertices are covered, means that $N_{10}[f] \subseteq N_7[v_k]$. With this intuition, we state the following lemma.

Lemma 1. f is the farthest vertex from the root r. If there exists a path $P =$ ${v_1 = f, v_2, \cdots, v_k}$ from the node f towards the root r such that v_k is an articulation point and $0.25b \leq d(f, v_k) \leq 1.75b$, then $N_{2b-2}[f] \subseteq N_{1.75b}[v_k]$.

Fig. 1. f is a farthest unmarked node from the root r and v_k is an articulation point in the path joining f and r. A small radius centered at v_k can cover all unmarked vertices as covered by a larger radius centered at f. Clearly, $N_{10}[f] \subseteq$ $N_7[v_k]$.

Proof. If $0.25b \leq d(f, v_k) \leq 1.75b$, $N_{1.75b}[f] \subseteq N_{1.75b}[v_k]$ since f is the farthest unmarked vertex and $f \in N_{1.75b}[v_k]$. Remaining $u \in (N_{2b-2}[f]\setminus N_{1.75b}[f])$ are within 0.25b distance from v_k . Therefore, $N_{2b-2}[f] \subseteq N_{1.75b}[v_k]$.

Lemma 2. Let f be the farthest unmarked node from the root r . If there is no articulation point v_k towards the root such that $0.25b \leq d(f, v_k) \leq 1.75b$, there exists a cycle of length at least 3b.

Proof. If there is no articulation point v_k such as $0.25b \leq d(f, v_k) \leq 1.75b$, then two parallel paths each of length at least 1.5b exist, and both the paths meet at a point towards the root r from f . Therefore there exists a cycle of length at least 3b.

At each iteration, we find f , the farthest unmarked node from the root r . If there exists an articulation point v_k satisfying constraints of Lemma [2,](#page-4-1) then we add v_k to the burning sequence BS_1 and mark nodes around v_k up to distance 1.75b; otherwise, we add f to the burning sequence BS_2 and mark nodes around f up to distance $2b-2$.

The process is depicted in Algorithm [1.](#page-6-1) The BURN-GUESS-CACTUS(G, b) procedure takes a cactus graph G and a positive integer b as input and returns either a burning sequence or BAD-GUESS to indicate that the graph can not be burned in b rounds.

Lemma 3. If there are k cycles, each of length at least 3b, then there are k arcs (paths) each of length b such that the distance between any pair of arcs is at least b. Here, we say, two arcs A_1 and A_2 are at a distance at least b if for every pair of vertices $v_1 \in A_1$ and $v_2 \in A_2$, $d(v_1, v_2) \geq b$.

Proof. We prove the lemma by induction. The statement is trivially valid for $k = 1$ and $k = 2$. For $k = 2$, we can form arcs around opposite ends of the cycles.

Let us assume that the statement is valid for the number of cycles $k - 1$; we now prove that the statement is true for k cycles too. From any articulation point, consider the farthest node f , which is part of a cycle C. Consider b-length arc centered at f . Any vertex which is at distance less than b from this arc cannot be shared by another cycle as that will contradict the fact that f is the farthest node. Therefore any vertex of other cycles will be at least b distance from the arc C. Using this argument and induction hypothesis, we get k arcs at a pairwise distance at least b.

Lemma 4. If there are $0.75b + 1$ cycles of length at least 3b then $b(G) > b$

Proof. By Lemma [3,](#page-4-2) there are $0.75b + 1$ arcs each of length b such that the arcs are at a pairwise distance of at least b. To completely burn an arc with a single round, we need a burn radius of at least 0.5b.

For the sake of contradiction, let us assume that the graph can be burned in b rounds. There are 0.5b number of burn radii of range at least 0.5b. Therefore, at most 0.5b arcs are completely burned with these radii. The remaining arcs are $0.25b + 1$, each requiring at least 2 rounds to burn the arc completely. So the total number of rounds $0.5b + 2(0.25b + 1) > b$, which is a contradiction. Therefore $b(G) > b$.

Lemma 5 (From [\[4\]](#page-18-8)). For a positive integer b, if there are b vertices at a pairwise distance of at least $2b-1$, then $b(G) \geq b$.

From Lemma [5,](#page-5-0) we have the following Corollary. The proof of the Corollary is very similar to the proof of Lemma [5](#page-5-0) of Bonato et al. [\[4\]](#page-18-8).

Corollary 1. For a positive integer b, if there are $b + 1$ vertices at a pairwise distance of at least $2b-1$ in G, then $b(G) \geq b+1$.

Proof. Let $S = \{x_1, x_2, \dots, x_{b+1}\}\$ be the vertices at a pairwise distance of at least $2b - 1$. If there is a burning sequence of length b, each node in the burning sequence spreads fire to the nodes at a distance of at most $b-1$. For each $x_i \in S$, consider a circle of radius $b-1$. No two circles intersect, as we know the distance between the centers is at least $2b - 1$. To burn a center vertex, we should either put fire at the center vertex or at a vertex in its $b-1$ circle. Any burned vertex in one circle can not spread fire to another circle's center because the distance between the vertex and the other center is greater than $b - 1$. So we should include at least one vertex from each circle in the burning sequence. Therefore, we can not burn the graph in b rounds and hence $b(G) \geq b+1$.

Lemma 6. If algorithm BURN-GUESS-CACTUS(G, b) returns BAD-GUESS, then $b(G) \geq b+1$.

Proof. The algorithm returns **BAD-GUESS**, we have two cases:

- **Case-1:** The number of times, the marking radius $2b-2$ is used, is greater than 0.75b. There are at least $0.75b + 1$ cycles of length at least 3b, by Lemma [4,](#page-5-1) $b(G) \geq b + 1$. In Algorithm [1,](#page-6-1) the case occurs when $b_2 \leq 0$.
- **Case-2:** The sum of the number of times marking radius $2b 2$ and 1.75b are used is greater than b. There are $b + 1$ vertices at a pairwise distance of at least 2b − 1 and hence by Corollary [1,](#page-6-1) $b(G) \ge b+1$. In Algorithm 1, the case occurs when $b_1 + b_2 \leq 0$.

In the algorithm, to get a burning sequence, the burning ranges $2b - 2$ and 1.75b are used 0.75b and 0.25b times, respectively. To get these many radii, the maximum length of the burning sequence needed is 2.75b. With this and Lemma [6,](#page-5-3) we have the following Theorem.

Theorem 1. A polynomial time 2.75-approximation algorithm exists for GRAPH Burning on cactus graphs.

4 3-approximation algorithm for directed trees

No known approximation algorithms exist for graph burning on directed graphs or directed trees. The 2-approximation algorithm of undirected trees will not scale to directed trees as shown in Fig. [2.](#page-6-2) This section presents a 3-approximation algorithm for graph burning on directed trees (polytree). The algorithm leads to a 2-approximation algorithm for graph burning on the single-rooted tree (arborescence).

Fig. 2. When roots are assumed in the sequence $[1, 6, 9, 10]$, known 2approximation algorithm for Tree gives lower bound 5. But the optimal burning number of this tree is 4.

Algorithm 1: Approximation algorithm for cactus graph $G(V, E)$.

	Input : $G = (V, E)$ and a positive integer b.							
	Output: Returns burning sequence or BAD-GUESS (-1).							
	1 BURN-GUESS (G,b) begin							
$\mathbf 2$	$BS_1 \leftarrow \lceil \rceil$							
3	$BS_2 \leftarrow \lceil \rceil$							
4	$b_1 \leftarrow \lceil 0.25b \rceil$							
5	$b_2 \leftarrow \lceil 0.75b \rceil$							
6	$r \leftarrow$ RANDOM-ARTICULATION(G)							
7	$M \leftarrow \phi$							
	\triangleright Set M contains all the marked vertices							
8	while $ M \neq V(G) $ do							
9	$f \leftarrow \arg \max_x \{d(r, x) \text{ where } x \notin M\}$							
	\triangleright A vertex f is the farthest unmarked vertex from r							
10	$v_k \leftarrow$ ARTICULATION-POINT (G, f, r)							
	\triangleright If there is an articulation point v_k towards the root r							
	such that $0.25b \leq d(f, v_k) \leq 1.75b$, ARTICULATION-POINT(G, f, r)							
	returns a vertex v_k ; otherwise ARTICULATION-POINT(G, f, r)							
	returns -1 .							
11	if $v_k \neq -1$ and $b_1 \geq 1$ then							
12	$append(BS_1, v_k)$							
13	$M \leftarrow M \cup \{v \in V(G) : d(v_k, v) \leq 1.75b\}$							
14	$b_1 \leftarrow b_1 - 1$							
15	else if $b_2 \geq 1$ then							
16	$append(BS_2, f)$							
17	$M \leftarrow M \cup \{v \in V(G) : d(f, v) \leq 2b - 2\}$							
18	$b_2 \leftarrow b_2 - 1$							
19	else							
20	$return -1$							
21	return (BS_1, BS_2) \triangleright concatenation of sequence BS_1 with BS_2 .							

Every directed tree has at least one vertex with in-degree zero and one vertex with out-degree zero.

 b -CUTTING process : If T is a directed tree, we remove all the vertices with out-degree zero and in-degree one from the tree. Let the resulting tree be T^1 . We call $T¹$ a 1-cutting tree. Having cut vertices with out-degree zero and indegree one of T^1 , we get a tree T^2 . We call T^2 a 2-cutting tree. Having cut all vertices with out-degree zero and in-degree one of T^2 , we get a tree T^3 . We call T^3 a 3-cutting tree. So after b cutting, the resulting tree is T^b . We call T^b as a b-cutting tree of T.

The *b*-CUTTING process, as given in Algorithm [2](#page-8-0) returns a tree T^b . In the tree, T^b , vertex v with out-degree zero is considered as a center of the fire. We divide the centers into two sets, BS and BS'. The set BS contains all the centers with in-degree 1 and out-degree 0 in tree T^b . The set BS' contains all the centers

Algorithm 2: b-cutting

Input: A tree T and a positive integer b . Output: Resulting tree (T') after b-cutting. 1 b-CUTTING (T, b) : $2 \mid T' \leftarrow T ;$ $3 \mid T'' \leftarrow T ;$ 4 for $i = 1$ to b do $\begin{array}{|c|c|c|}\hline \textbf{5} & \textbf{5} & \textbf{6} \end{array} \textbf{6} \textbf{6} \textbf{6} \textbf{6} \textbf{7} \textbf{7} \textbf{8} \textbf{8} \textbf{8} \textbf{9} \textbf{16} \textbf{16} \textbf{18} \$ 6 if $D^{-}(v) = 1$ and $D^{+}(v) = 0$ then $\begin{array}{cc} \texttt{7} & | & | & | & T'' \leftarrow T'' \backslash \{v\}; \end{array}$ $\begin{array}{c|c|c|c} \mathbf{s} & \mathbf{1} & T' \leftarrow T''; \end{array}$ 9 return T'

with in-degree greater than one and out-degree 0. After *b*-CUTTING if tree T^b is not empty, we do *b*-CUTTING again on $T^b \setminus (BS \cup BS')$. This process is repeated until the tree becomes empty.

b-CUTTING returns tree T^b of T. $\forall c \in V(T^b)$, if $D^-(c) > 1$ and $D^+(c) = 0$ then we add c in BS' and if $D^{-}(c) = 1$ and $D^{+}(c) = 0$, we add c in BS. The GET-CENTER(G, b) procedure, in turn, calls b-CUTTING(T, b) and returns the sets BS and BS'.

Lemma 7. If $|BS| > b$, $b(T) > b$.

Proof. Let $\{c_1, c_2, c_3 \cdots c_{b+1}\}$ be the centers in BS. Each center has an associated directed path of length b. To burn all the centers and vertices in their associated paths in at most b rounds, a vertex should exist that can burn at least two centers and their associated paths.

Let c_i and c_j be the two centers and their associated paths be P_i and P_j respectively. Let $u \in P_i$ and $v \in P_j$ be the farthest nodes in the b-length paths of P_i and P_j respectively. To burn c_i and c_j as well as u and v with a single source of fire, that node should be a common ancestor of c_i and c_j . Such a common ancestor, which is at least at a distance 1 from c_i and c_j , will be at a distance at least $(b+1)$ from u and v. Therefore a single source of fire can not burn two centers and their associated paths in b rounds. Hence $b(T) > b$.

Lemma 8. If $|BS'| > b$ then $b(T) > b$.

Proof. We prove by contradiction, let $b(T) = b$. Let c_i and c_j be centers in BS'. Hence their in-degree is greater than 1. Each center has at least two ancestors, but there can not be more than one common ancestor between any pair of centers, as that would form an undirected cycle. As $BS' > b$, there exists at least $(b+1)$ different ancestors who need at least $(b+1)$ sources of fire to burn these ancestors. Therefore, $b(T) > b$.

Algorithm 3: Burning number for multi-rooted directed tree T.

Input : $T = (V, E)$ and a positive integer b. Output: RETURN burning sequence or -1. 1 GET-CENTERS-FOR-MULTI-ROOTED-TREE $(T, b)(T, b)$ begin $2 \mid i \leftarrow b$ $3 \mid BS \leftarrow \phi$ $4 \mid BS' \leftarrow \phi$ 5 while $i > 0$ and $|V(T)| > 0$ do 6 $\mid T' \leftarrow b$ -CUTTING $(T, b - 1)$ $\triangleright\;V(T')$ is the set of all vertices in tree T' . $\begin{array}{ccc} \texttt{7} & | & \texttt{forecast}\ v \in V(T')\ \end{array}$ 8 if $D^+(v) = 0$ then 9 | | | if $D^{-}(v) \leq 1$ then 10 | | | | $append(BS, v)$ \triangleright After b-cutting, Set BS will contain vertices having at most one in-degree. 11 \vert \vert \vert else 12 | | | | $append(BS', v)$ \triangleright After b-cutting, Set BS' will contain vertices having more than one in-degree. 13 $\vert \vert \vert \vert T \leftarrow T \setminus \{u : d(u, v) \leq b \text{ and } u \in V\}$ \triangleright Remove all vertices from T which are at b distance from the center of fire v . 14 | $i \leftarrow i-1$ 15 if $|BS| > b$ or $|BS'| > b$ then 16 | return -1 17 | return (BS, BS') \triangleright (BS, BS') is concatenation of the two burning sequences BS and BS' .

GET-CENTERS-FOR-MULTI-ROOTED-TREE (T, b) procedure is given in Algorithm [3.](#page-8-1) This procedure, based on the cardinality of $|BS|$ and $|BS'|$, either concludes that $b(T) > b$ or both $|BS| \leq b$ and $|BS'| \leq b$. In the latter case, the graph can be burned in $|BS| + |BS'| + b \leq 3b$ rounds.

Theorem 2. A polynomial time 3-approximation algorithm exists for the multirooted directed tree.

Proof. If the algorithm returns **BAD-GUESS** for b, either $BS > b$ or $|BS'| > b$ and by Lemma [7](#page-8-2) and Lemma [8](#page-8-1) we have $b(T) \geq b + 1$. As the algorithm returns a burning sequence of length $3b + 3$ for $b + 1$, we get a 3-approximation.

Note that, for single-rooted trees, $|BS'| = 0$, in which case, Algorithm [3](#page-8-1) leads to a 2-approximation for single-rooted directed trees.

Theorem 3. A polynomial time 2-approximation algorithm exists for graph burning on the single-rooted directed tree.

4.1 1.905-approximation for single rooted Tree

This paper presents a 1.905-approximation algorithm for arborescence. The procedure is shown in Algorithm [5.](#page-12-0) The algorithm uses two methods GET-CENTERS-FOR-SINGLE-ROOTED-TREE (T, b) given in Algorithm [5](#page-12-0) and MERGE-AND-BURN given in Algorithm [4.](#page-12-1) The GET-CENTERS-FOR-SINGLE-ROOTED-**TREE**(*T, b*) function returns only the set BS, which contains roots of the b height subtrees. Note that $BS' = \phi$ because each node has at most one in-degree in an arborescence. The procedure MERGE-AND-BURN takes the BS set and merges subtrees whose roots have the lowest common ancestor (LCA) within $\leq 0.81b$ distance. The lowest common ancestor of the two roots will be the new root or the center of the fire.

Fig. 3. This flowchart depicts the idea of the 1.905-approximation algorithm.

The main idea of the algorithm is shown as a flowchart in Fig. [3.](#page-11-1)

Lemma 9. If $|BS| > b$ then $b(T) > b$.

Proof. The proof is similar to Lemma [7.](#page-8-2)

Suppose there are $0.81b + 1$ subtrees that are not merged pairwise. We know that the height of each subtree is b except for the last subtree. For each subtree T_v , a b-length path P_i exists from the root of T_v downwards. Take a subpath P'_i of P_i , where P'_i contains all middle 0.62b vertices of P_i ; in other words, P'_i is a subpath obtained after removing $0.19b$ vertices from both ends of path P_i . Let S be the union of the sets of vertices of the subpaths P'_i obtained from the non-merged subtrees.

Algorithm 5: Burning number for directed tree $T(V, E)$.

Input : $T(V, E)$ and a positive integer b. Output: Return burning sequence BS, or -1 in case it fails to burn the tree T. 1 GET-CENTERS-FOR-SINGLE-ROOTED-TREE (T,b) begin 2 | $T' \leftarrow T$ $3 \mid BS \leftarrow [$ $\begin{array}{cc} \textbf{4} & \textbf{[} & \textbf{while } T' \neq \phi \textbf{ do} \end{array}$ 5 $\mid T' \leftarrow b$ -CUTTING $(T', b - 1)$ $\triangleright\;V(T')$ is the set of all vertices in tree T' $\begin{array}{|c|c|c|}\hline \mathbf{6} & \multicolumn{1}{|c|}{\text{ for each }} v\in V(T')\textbf{ do} \hline \end{array}$ 7 if $D^{-}(v) \le 1$ and $D^{+}(v) = 0$ then $\mathbf{8}$ | | | $append(BS, v)$ \triangleright Append center of fire v in the Burning sequence BS . 9 T ′ ← T ′ \ {v} 10 return MERGE-AND-BURN(T, b, BS)

Fig. 4. In this example, for $b = 11$ there are two subtrees T_{12} and T_{32} rooted at 12 and 32, respectively. with paths $P_1 = [12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22]$ and $P_2 = [32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42]$. As $11 * 0.19 \approx 2$, $P'_1 =$ $\left[14, 15, 16, 17, 18, 19, 20\right]$ and $\left.P_{2}^{\prime} = \left[34, 35, 36, 37, 38, 39, 40\right]\right]$

Fig. 5. In this example, for $b = 11$ there are two subtrees T_1 and T_{12} at rooted 1 and 12, respectively. With paths $P_1 = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11]$ and $P_2 =$ $[12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22].$ As $11*0.19\,\approx\,2$, $\,P^\prime_1\,=\, [3, 4, 5, 6, 7, 8, 9]$ and $P'_2 = [14, 15, 16, 17, 18, 19, 20]$.

Lemma 10. A single source of fire with a burning range $b-1$ can burn at most b vertices in S.

Proof. There are two cases as shown in Fig. [4](#page-13-0) and Fig. [5:](#page-14-1) first when there does not exist a directed path from any vertex $u \in P'_i$ to $v \in P'_j$, $\forall i \neq j$. Secondly, when there exists a directed path either from vertex $u \in P_i$ to $v \in P_j$ or vice versa.

CASE-1 If there does not exist a directed path between any two vertices $u, v, u \in P'_i$ and $v \in P'_j$, then there does not exist a lowest common ancestor (ICA) of u and v within b distance. Because if the lowest common ancestor of u and v is within b distance, and roots of subtrees containing P_i and P_j have the lowest common ancestor within 0.81b distance. But we know P_i and P_j belong to non-merged subtrees, so roots of both the subtrees should have LCA greater than 0.81b distance. Therefore, a fire source with a burning range $b-1$ can burn at most b vertices.

CASE-2 There exists a path from u to v where $u \in P'_i$ and $v \in P'_j$ for $i \neq j$. Without loss of generality, let the vertices u and v be closer to the roots of both subtrees. We have $d(u, v) \ge 0.81b$ and $d(u, u') = 0.62b$ where u' is the deepest vertex of P'_i . A fire started at any vertex in P_i burns the deepest vertex $u' \in P_i$, then the top vertex $v \in P'_j$. The fire burns sequentially first the vertices of P'_i , then P'_j , so it can burn only b number of vertices.

According to Lemma [10,](#page-14-0) a burning range $b-1$ can burn only b vertices of the set S . For the burning number b , the sequence of the burning ranges of the sources of fire is $[b-1, b-2, b-3, \cdots, 0]$. The burning number b can burn at most S_b vertices, where

$$
S_b = \sum_{i=b}^{i=1} i = \frac{b*(b+1)}{2} \tag{1}
$$

The remaining task is to find the number of vertices in S. There are $0.81b + 1$ non-merged subtrees. The number of vertices in S :

$$
|S| = \sum_{i=1}^{i=0.81b+1} |P'_i| = \sum_{i=1}^{i=0.81b+1} 0.62b = (0.81b+1) * 0.62b = 0.5022b^2 + 0.62b
$$
 (2)

If $|S| > S_b$, then the lower bound of the burning number of the directed tree T is at least $b + 1$.

Lemma 11. If $|S| > S_b$ then $b(T) > b$.

Proof. A burning range $b - 1$ can burn at most b vertices of the set S. By equation [1,](#page-15-1) burning number b can burn less than the total number of vertices in S as shown in equation [2.](#page-15-2) Therefore, $b(T) > b$.

Theorem 4. A polynomial time 1.905-approximation algorithm exists for the single-rooted directed tree.

Proof. Algorithm uses burning ranges $\{1.905b - 1, 1.905b - 2 \cdots 0\}$ in the whole burning process. If the algorithm fails to burn the entire graph, Lemma [11](#page-15-0) and Lemma [9](#page-11-0) claim that we can not burn the whole graph in less than or equal to b rounds. Therefore, on success, the algorithm returns the burning sequence of length 1.905b.

Name	V	E	3- Approx [4]	$2.75 -$ Aprrox
G_1	303	327	25	19
\mathfrak{G}_2	1152	1223	37	35
$\, G_{3} \,$	2186	2303	46	46
G_4	3270	3435	58	57
G_{5}	4471	4690	67	66
G_6	6743	7012	73	71
G_7	7824	8140	76	79
G_8	9766	10133	82	82
G_9	11250	11669	85	88
\overline{G}_{10}	13197	13658	94	90
G_{11}	15327	15839	103	101
$\,G_{12}$	17244	17812	109	107
G_{13}	19975	20584	115	112
G_{14}	22391	23059	130	115
G_{15}	24011	24719	124	118
G_{16}	26207	26965	127	126
G_{17}	28492	29303	130	126
G_{18}	34172	35083	142	137
G_{19}	37759	38721	151	145
G_{20}	39502	40516	63	159
G_{21}	42323	43388	160	148
G_{22}	45209	46315	166	159
$\, G_{23}$	46857	48012	172	162
G_{24}	48736	49930	172	167

Table 1. Comparison of estimated burning numbers $b(G)$ of different approximation algorithms for randomly generated Cactus Graphs.

Table 2. Comparison of estimated burning numbers $(b(T))$ of different approximation algorithms for randomly Directed Tree.

	\geq	Jur
Name		Approx ్
F_1	3000	S0
F_2	5000	147
$ \vec{r_{3}} $	7000	150
\mathcal{L}_4	9000	148
F_{5}	13000	156
$ F_{\rm e} $	15000	160
\bar{F}_7	17000	161
F_8	19000	161
F_9	23000	165
\bar{T}^0	25000	168
\bar{T}_{11}	27000	170
T_{12}	29000	176
\bar{T}_{13}	33000	176
\bar{T}_{14}	35000	177
\bar{T}_{15}	37000	185
T_{16}	39000	185
\bar{T}_{17}	41000	184
\bar{T}_{18}	43000	188
T_{19}	45000	190
T_{20}	47000	193
T_{21}	49000	188

Random trees	V	Our 2 -Approx	Our 1.905- Approx
T_{1}	1000	32	27
\mathcal{T}_2	2000	38	35
$\overline{T_3}$	3000	44	42
$\overline{T_4}$	4000	50	48
T_5	5000	50	48
T_6	6000	62	60
T_7	7000	58	56
T_8	8000	66	63
T_9	9000	68	65
\overline{T}_{10}	10000	72	69
\overline{T}_{11}	11000	74	71
\overline{T}_{12}	12000	74	73
T_{13}	13000	76	73
$\overline{T_{14}}$	14000	78	75
\mathcal{T}_{15}	15000	80	77
T_{16}	16000	82	79
\overline{T}_{17}	17000	84	81
T_{18}	18000	90	86
T_{19}	19000	90	86
T_{20}	20000	88	86

Table 3. Comparison of estimated burning numbers $(b(T))$ of different approximation algorithms for randomly generated directed trees.

4.2 Experiments and Results

We have implemented the proposed approximation algorithms for 1) cactus graphs, 2) poly-trees, and 3) directed trees. In the first experiment, we generate 24 cactus graphs randomly with orders ranging from 300 to 49,000. The proposed 2.75-approximation algorithm is compared with Bonato et al. [\[4\]](#page-18-8), and the results are shown in Table [1.](#page-16-0) The 2.75-approximation algorithm gives better burning numbers than the 3-approximation algorithm.

As there are no known approximation algorithms for graph burning on directed graphs, we give the results obtained by our 3-approximation algorithm. We generate 21 poly-trees randomly, having vertices ranging from 3000 to 49,000. The results are shown in Table [2.](#page-16-1)

Finally, in the 3rd experiment, the results obtained for single directed trees are shown in Table [3.](#page-17-0) We generated 20 directed trees with the number of vertices ranging from 1000 to 20000. The implementations of our 2-approximation algorithm (Theorem [3\)](#page-9-0), as well as the 1.905-approximation algorithm for directed trees (Theorem [4\)](#page-15-3), are compared. And the results are shown in Table [3.](#page-17-0)

It can be seen that, in all the cases, the 1.905-approximation algorithm yields a lower burning number than the 2-approximation algorithm.

5 Conclusions and Future Work

In this paper, we have proposed an approximation algorithm for Graph Burning on cactus graphs, poly trees, and directed trees. The approximation algorithm for cactus graphs improves the approximation factor from 3 to 2.75. Further, our approximation algorithms for directed trees initiate the study of approximation algorithms for graph burning on directed graphs. The proposed approximation algorithms on directed trees have approximation factors of 3 for the poly tree and 1.905 for the directed tree. We have done experimentation on randomly generated cactus graphs and directed trees of sizes up to 49K to demonstrate the experimental results. The concepts of extracting equal height sub-trees and the merge technique may be explored for the other related problems in information diffusion. In the future, we would like to explore the approximation algorithms for the generalized Graph Burning problem, namely the k-burning problem.

References

- 1. Stéphane Bessy, Anthony Bonato, Jeannette Janssen, Dieter Rautenbach, and Elham Roshanbin. Bounds on the burning number. Discrete Applied Mathematics, 235:16–22, 2018.
- 2. Anthony Bonato, Jeannette Janssen, and Elham Roshanbin. Burning a graph as a model of social contagion. In Algorithms and Models for the Web Graph, WAW 2014, volume 8882, pages 13–22. Lecture Notes in Computer Science, Springer, 2014.
- 3. Anthony Bonato, Jeannette Janssen, and Elham Roshanbin. How to burn a graph. Internet Mathematics, 12(1-2):85–100, 2016.
- 4. Anthony Bonato and Shahin Kamali. Approximation algorithms for graph burning. In Theory and Applications of Models of Computation. TAMC 2019, pages 74–92. Lecture Notes in Computer Science, Springer, 2019.
- 5. Anthony Bonato and Thomas Lidbetter. Bounds on the burning numbers of spiders and path-forests. Theoretical Computer Science, 794:12–19, 2019.
- 6. Zahra Rezai Farokh, Maryam Tahmasbi, Zahra Haj Rajab Ali Tehrani, and Yousof Buali. New heuristics for burning graphs. ArXiv, abs/2003.09314, 2020.
- 7. J. Garcia, R. Menchaca, J. Sanchez, and R. Menchaca. Local search algorithms for the vertex k-center problem. IEEE Latin America Transactions, 16(6):1765–1771, 2018.
- 8. Rahul Kumar Gautam, Anjeneya Swami Kare, and S. Durga Bhavani. Faster heuristics for graph burning. Applied Intelligence, pages 1573–7497, 2021.
- 9. Rahul Kumar Gautam, Anjneya swami kare, and Durga Bhavani. Faster heuristics for graph burning. Applied Intelligence, 2020.
- 10. Remie Janssen. The burning number of directed graphs: Bounds and computational complexity. Theory and Applications of Graphs: Vol. 7 : Iss. 1 , Article 8., 2020.
- 11. Lil María X. Rodríguez Henríquez Jesús García Díaz, Julio César Pérez Sansalvador. Burning graphs through farthest-first traversal. IEEE Access, 10:30395– 30404, 2022.
- 12. Shahin Kamali, Avery Miller, and Kenny Zhang. Burning two worlds: Algorithms for burning dense and tree-like graphs. In Theory and Practice of Computer Science, SOFSEM 2020, pages 113–124. Lecture Notes in Computer Science, Springer, 2020.
- 13. Anjeneya Swami Kare and I Vinod Reddy. Parameterized algorithms for graph burning problem. In International Workshop on Combinatorial Algorithms, pages 304–314. Springer, 2019.
- 14. Yasuaki Kobayashi and Yota Otachi. Parameterized complexity of graph burning. ArXiv, 2021.
- 15. Max R Land and Linyuan Lu. An upper bound on the burning number of graphs. In International Workshop on Algorithms and Models for the Web-Graph, pages 1–8. Springer, 2016.
- 16. Huiqing Liu, Ruiting Zhang, and Xiaolan Hu. Burning number of theta graphs. Applied Mathematics and Computation, 361:246–257, 2019.
- 17. Debajyoti Mondal, N. Parthiban, V. Kavitha, and Indra Rajasingh. Apx-hardness and approximation for the k-burning number problem. ArXiv, 2021.
- 18. Kai Sim, Ta Sheng Tan, and Kok Wong. On the burning number of generalized petersen graphs. Bulletin of the Malaysian Mathematical Sciences Society, 41:1657– 1670, 2017.
- 19. Marek Šimon, Ladislav Huraj, Iveta Luptáková, and Jiří Pospíchal. Heuristics for spreading alarm throughout a network. Applied Sciences, 9:3269, 2019.
- 20. Stéphane Stéphane Bessy, Anthony Bonato, Jeannette Janssen, Dieter Roshanbin Rautenbach, and Elham Roshanbin. Burning a graph is hard. Discrete Applied Mathematics, 232:73–87, 2017.