DIRECTIONAL SOURCE SEPARATION FOR ROBUST SPEECH RECOGNITION ON SMART GLASSES

Tiantian Feng^{1,*}, Ju Lin², Yiteng Huang², Weipeng He² Kaustubh Kalgaonkar², Niko Moritz², Li Wan², Xin Lei², Ming Sun², Frank Seide²

> ¹ University of Southern California, USA ² Meta Platforms Inc., USA

ABSTRACT

Modern smart glasses leverage advanced audio sensing and machine learning technologies to offer real-time transcribing and captioning services, considerably enriching human experiences in daily communications. However, such systems frequently encounter challenges related to environmental noises, resulting in degradation to speech recognition and speaker change detection. To improve voice quality, this work investigates directional source separation using the multi-microphone array. We first explore multiple beamformers to assist source separation modeling by strengthening the directional properties of speech signals. In addition to relying on predetermined beamformers, we investigate neural beamforming in multi-channel source separation, demonstrating that automatic learning directional characteristics effectively improves separation quality. We further compare the ASR performance leveraging separated outputs to noisy inputs. Our results show that directional source separation benefits ASR for the wearer but not for the conversation partner. Lastly, we perform the joint training of the directional source separation and ASR model, achieving the best overall ASR performance.

Index Terms— Source separation, speech recognition, microphone array, multi-talker ASR, smart glasses

1. INTRODUCTION

Recent advances in audio sensing [1,2] and augmented reality (AR) [3] have empowered novel applications for smart glasses, enriching the human experience in daily communications by offering robust and efficient speech-understanding systems [4,5]. Specifically, this work explores the microphone array applications on recently introduced **Project Aria smart glasses** [4], embedded with diverse sensors, including a 7-channel microphone array as shown in Figure 1. Despite the rich and diverse speech cues the advanced smart glasses capture, these in-the-wild signals are frequently coupled with noises from multiple sources, such as background noises, reverberation, and interfering speakers. Such noises can substantially reduce speech intelligibility, leading to degradation in speech recognition. An effective solution to improve voice quality is source separation [6], which separates relevant speech information from ambient sources.

In this paper, we present a comprehensive study of directional source separation on smart glasses. Unlike prior works [7, 8] that focus on single-channel setup, our work leverages multi-channel microphones to perform source separation. Multi-channel microphone arrays have advantages over mono-channel setups in providing spatial information to the received speech signals that are beneficial



Fig. 1: 7-channel microphone locations on Project Aria glasses.

to disambiguating ambient sources. Along with the multi-channel setup, we integrate multiple beamformers as the front-end processor to strengthen the sound sources' directional information. Specifically, this study involves answering the following research questions: **Is directional information beneficial to source separation?** In addition to spatial properties embedded in the multi-channel microphone arrays, we propose to utilize the multiple beamformers to enhance directional information from speech signals, enabling the system to implicitly perform speaker disambiguation and noise suppression. Beamforming [9, 10] is an efficient front-end component aiming to amplify the signal from a specific direction. In a beamformerbased speech pipeline, the beamformer typically provides enhanced speech signals to subsequent systems such as ASR [11].

Can neural beamforming improve source separation? Conventional beamformers rely heavily on ideal assumptions about the environments, making them often limited in practice. Instead of drawing unrealistic hypotheses about the environment, neural beamforming [12–17] is an emerging technique to learn the beamformer weights from the immense volume of microphone array signals accessible from real-life recordings or by simulation. This motivates us to probe neural beamforming in multi-channel source separation [18, 19].

How does source separation connect to speech recognition on smart glasses? One primary goal of source separation is to enhance speech recognition. With this objective, we investigate the impact of source separation on ASR leveraging separated outputs. Increasingly, it is worth exploring whether the joint training of the source separation and ASR model would further benefit speech recognition. In summary, our contributions are summarized as follows:

- To the best of our knowledge, our work is one of the earliest efforts exploring directional source separation on smart glasses. Our empirical results demonstrate the effectiveness of leveraging multiple beamformers to assist source separation modeling.
- We investigate the neural beamforming in source separation, discovering that automatic learning directional characteristics open up possibilities for further enhancing voice quality.
- We conduct comprehensive studies quantifying the impact of source separation on ASR. Our results show that source separa-

^{*}This work was performed while author was an intern at Meta AI



Fig. 2: Proposed directional source separation architecture.

tion benefits the ASR performance for the wearer (1.63% WER reduction) but decreases speech recognition for the conversational partner. Moreover, combining the separation and beamformed outputs provides competitive ASR performance.

 We study joint training of source separation and ASR, demonstrating that joint training achieves the best overall ASR performance.

2. BEAMFORMING DESIGN

As shown in Fig 2, beamforming is one key component of the proposed system. A conventional beamformer algorithm, e.g., Minimum variance distortionless response (MVDR) [10], aims to minimize the estimated beamformer output level while preserving the integrity of the desired signal. However, that approach neglects white noise during optimization and lacks control over null directions, which can vary significantly across different frequencies. To address these limitations, we recently introduced a novel Non-Linearly Constrained Minimum Variance (NLCMV) beamforming technique. The NLCMV beamformer incorporates white noise gain and null direction control into its formulation. Specifically, the objective function $\mathcal{L}[\mathbf{h}(j\omega)]$ of the NLCMV beamformer is below:

$$\boldsymbol{h}^{H}(j\omega) \left[\boldsymbol{\Phi}_{dd}(j\omega) + \phi_{pp}(\omega) \sum_{n=1}^{N} \alpha_{p,n} \cdot \boldsymbol{g}_{n}(j\omega) \boldsymbol{g}_{n}^{H}(j\omega) \right] \boldsymbol{h}(j\omega), \quad (1)$$

which is subject to a nonlinear inequality constraint:

$$c(\omega) = \boldsymbol{h}^{H}(j\omega)\boldsymbol{\Psi}(j\omega)\boldsymbol{h}(j\omega) <= 0, \qquad (2)$$

where $\Phi_{dd}(jw)$ is the covariance matrix of diffuse noise,

$$\Psi(j\omega) = \mathbf{I} - \boldsymbol{g}(j\omega)\boldsymbol{g}^{H}(j\omega) \cdot M \left/ \left[\sum_{m=1}^{M} |G_{m}(j\omega)|^{2} \right] \right.$$

 $G_m(j\omega)$ is the channel response from the target speech source to the *m*th of *M* microphones, *N* is the number of point noise sources, $\phi_{pp}(w)$ is the PSD of point noise, $\alpha_{p,n}$ is the *n*th point noise weight, and **I** is the identity matrix.

3. SOURCE SEPARATION MODELING

Fig 2 shows the architecture of the proposed directional source separation. It consists of front-end multiple beamformers followed by a conventional source separation neural network. The source separation network receives beamformed outputs and is trained to separate wearer and partner speech in a conversational context.

Beamforming Front-end: In this work, the multiple beamformers pre-process the raw multi-channel audio into *K* horizontal steering directions around the smart-glasses device plus one in the speaker's



Fig. 3: Proposed ASR approaches. BF is multiple beamformers.

mouth direction. Here, we use the predetermined beamformer weights with horizontal steering directions K = 4 and K = 12, leading to 5-channel and 13-channel beamformed outputs, respectively. We load the predetermined beamformer weights in neural beamforming and update the weight using back-propagation.

Source Separation Back-end: Our source separation neural network follows an encoder-decoder architecture. From the K + 1beamformed channels, we first extract the STFT features. Next, we feed these time-frequency features to the encoder module consisting of multiple convolutional blocks with gated linear units (GLU) [20] activation function and Dropout layers in between. Subsequently, the encoding output is applied to a 3-layer LSTM, which is then passed to a set of convolutional decoding layers. Then, we send the decoder output to a gating function that returns the STFT masks associated with the wearer and the partner speech from reference audio. In our proposed source separation architecture, we directly apply the first audio channel as the reference audio. Lastly, we compute the masked time-frequency outputs corresponding to the wearer and partner, which are then converted into the wearer and partner speech using the inverse STFT. The optimization objective in source separation modeling combines L1 loss, STFT loss, and Log SI-SDR loss [21].

4. ASR MODELING

4.1. Baseline ASR Modeling

Directional ASR: We apply the directional ASR model reported in [11] as our baseline ASR model. Similar to the beamformer source separation, the directional ASR system first processes the multi-channel raw audio into K + 1 beamformed channels, which are then fed into the ASR network. Our core ASR network follows the Neural Transducer architecture [22–24], including an encoder, a prediction network, and a joiner network. Our ASR modeling also integrates serialized output training (SOT) [25,26] and uses the alignment-restricted RNN-T loss [22] as the ASR training objective. **Interchannel phase differences (IPDs):** In addition to directional ASR modeling, we also design the baseline model using IPD features as the ASR input. IPDs capture the variations in phase between different audio channels, providing spatial properties of sound sources. We use the IPDs ASR system implemented in [11].

4.2. Two-stage ASR Modeling Leveraging Source Separation

We propose a two-stage training ASR system to evaluate the ASR performance using separate audios. Our two-stage ASR system first extracts the wearer and the partner speech using the pre-trained source separation model. The system then computes the log-mel from the separate audios, which are subsequently fed into the ASR model. We deploy the same ASR model in the baseline systems. In addition to relying solely on separate audio, we also study combining the beamformed outputs with the separation output as the ASR input, resulting in K + 3-channel audio.

4.3. Joint ASR Modeling with Source Separation

We also investigate the joint training of ASR and source separation in addition to two-stage ASR training. Instead of training both models from scratch, we propose to load the pre-trained ASR model weights from two-stage ASR training and pre-trained source separation model weights. We combine the ASR training objective with source separation loss to optimize both models in joint training.

5. EXPERIMENTAL SETUPS

5.1. Dataset

We conduct experiments using the open-source Librispeech corpus, which consists of 960 hours of speech from audiobooks in the LibriVox project [27]. To simulate the training data, we generate 100,000 multichannel room impulse responses (RIRs) for rooms with sizes ranging from [5, 5, 2] to [10, 10, 6] meters. We apply the geometry of Aria glasses to simulate multi-channel data. Aria has 7 microphones. We generate the multi-channel signals using image-source methods (ISM) [28]. To better understand the impact of cross-talk and background noises on speech recognition, we generate several test scenarios varying the number of bystanders and SNR range, each containing 3367 utterances from Librispeech.

Furthermore, we add noise from the public noise set [29] to the clean audio segments in both the training and test sets. The SNRs of the mixed audio range from -8 dB to 40 dB relative to the combined audio of the wearer and partner, with an incremental level of 1 dB. Increasingly, we select overlap ratios between the bystanders and the primary speakers, ranging from 5% to 50%. With an overlap ratio of 0%, there is no overlap between bystanders and main speakers (wearer and partner).

Table 1: Source separation performance comparisons, where the evaluation set includes only one distractor.

	PESQ		SI-SDR (dB)	
	Wearer	Partner	Wearer	Partner
Baseline System	2.89	1.80	18.17	8.50
BF-5	2.88	1.82	18.09	8.55
BF-13	2.95	1.86	18.33	8.83
Neural BE-13 (Ours)	3 11 ↑	1 89 ↑	20 44 ↑	9 51 ↑



Fig. 4: Source separation with the different number of distractors.

5.2. Directional Source Separation Training

Our source separation training focuses on Librispeech data. We perform different source separation training with the same architecture except for a different input dimension. We extracted 256-dimensional complex SFTF for each beamformer direction or raw microphone channel. Input features from multiple directions or channels are concatenated. We use an Adam optimizer with a tri-stage learning-rate scheduler. We trained the source separation models for 60 epochs, with a base learning rate of 0.0004, a warmup of 10,000 iterations, and forced annealing after 10 epochs.

5.3. ASR Training

We perform the ASR training in baseline and two-stage systems for 120 epochs. Similar to source separation training, ASR training uses an Adam optimizer, a base learning rate of 0.001, and a warmup of 10,000 iterations. The details about ASR training are also available in [11]. On the other hand, we perform 30 epochs of joint training with the pre-trained ASR model and pre-trained source separation model on Librispeech data. We choose a constant learning rate of 0.0001 and use the equal weights of 1 in combining ASR loss and the source separation loss.

6. SOURCE SEPARATION FINDINGS

6.1. Directional information is beneficial to source separation

We first compare the source separation modeling with and without directional information in Table 1, quantified using the perceptual evaluation of speech quality (PESQ) [30] and Scale-Invariant Signal-to-Distortion Ratio (SI-SDR) [31]. The baseline system directly used the complex STFT features without using beamformer. We refer to the directional source separation modeling as BF-5



Fig. 5: Beam patterns at f = 250 Hz

Table 2: ASR performance comparisons on LibriSpeech data, where the evaluation set includes only one distractor.

ASR Training	Source Separation	Overall	WER Wearer	Partner
IPDs Dir. ASR BF-13	N.A. N.A.	$15.12 \\ 14.14$	$7.99 \\ 8.28$	22.33 20.12
Two-stage Two-stage Two-stage Two-stage Fusion	Baseline BF-13 Neural BF-13 Neural BF-13	$17.28 \\ 17.06 \\ 16.04 \\ 13.70$	6.79 7.13 6.51 6.65	$27.69 \\ 27.07 \\ 25.46 \\ 20.66$
Joint Train Fusion	Neural BF-13	13.25	8.06	18.89

and BF-13, where 5 and 13 indicate the number of beamformed channels. From the comparisons, we identify that increasing beamforming directions improves the source separation, and we observe that BF-13 achieves approximately 0.25 dB performance gain over BF-5 in both wearer and partner output. In addition, we discover that using predetermined beamformer weights, BF-13 yields higher voice quality than the multi-channel source separation system in both PESQ and SI-SDR measures.

6.2. Neural beamforming further improves separation quality

Next, we compare the source separation using neural beamforming to other approaches, as shown in Table 1. We discover that neural BF-13 substantially improves separation quality, leading to a 2.27 dB and a 1.01 dB SI-SDI increase in the wearer and partner signals, respectively. We also observe an increase in PESQ for wearer and partner separation outputs. In addition to evaluating the condition with one distractor, we compare the voice quality varying (2 and 3) distractors nearby. The comparisons in Fig. 4 demonstrate that neural BF-13 is more robust against increased distractors than multi-channel and predetermined beamformer approaches.

6.3. Interpreting neural beamformer weights

Neural beamforming offers encouraging results for source separation, but it is unclear why neural beamforming improves source separation. To unfold what neural beamforming approaches can learn, we perform a detailed beamformer analysis as shown in Fig 5. The plot depicts the beam patterns of the beamformers in 3 different directions. The beam pattern uncovers that neural beamformers have substantial gains (over 10 dB) in the lateral directions (left and right), possibly contributing to the improved source separation.

7. ASR FINDINGS

7.1. Source separation is beneficial to ASR on smart glasses

This paragraph compares the ASR performance between baselines and two-stage ASR systems, as demonstrated in Tab. 2. It is worth noting that two-stage fusion refers to the ASR training that combines



Fig. 6: ASR performance with the different number of distractors.

beamformed outputs with the separation outputs, and the two-stage represents ASR training using only separation outputs. The results show that two-stage ASR training outperforms IPDs and directional ASR for wearer speech, indicating improved quality from the wearer speech. However, partner speech suffers a substantial WER increase among all two-stage systems. This result implies far-field speech separation remains a challenging task, and the relatively lower separation quality for partner speech causes negative impacts on the ASR system. We also observe that the neural beamforming systems yield higher ASR performance than baseline source separation. We perform the two-stage fusion ASR training (with neural BF-13) to resolve this issue from source separation, resulting in overall and wearer ASR performance improvements (WER: 13.70%) compared to the directional ASR system (WER: 14.14%).

7.2. Joint training further improves the ASR performance

Table 2 reveals that joint training with the best ASR system from the two-stage fusion training (with neural BF-13) would improve ASR performance, reducing overall WER to 13.25% compared to 14.14% using directional ASR. Increasingly, we identify that joint training yields an increased WER for the wearer but reduces WER for partner speech compared to two-stage ASR. Unlike source separation modeling that only yields ASR improvements for wearer speech, joint training strikes a delicate balance in improving speech recognition in all main speakers. We further compare the ASR performance using joint training to other ASR modeling approaches with varying distractors, as shown in Figure 6. The comparisons indicate that joint training also yields more robust partner ASR performance with increasing distractors, creating a larger relative WER difference (WER difference increases from 1.76% to 2.86%).

8. CONCLUSION

In this work, we conduct a comprehensive study of directional source separation using the multi-channel microphone array on smart glasses, demonstrating the effectiveness of incorporating directional information in source separation. In addition. Our experiments also imply that learning directional properties further improves voice quality. Lastly, we demonstrate that source separation benefits ASR performance in different use cases. One future work would investigate fairness and efficiency [32] in source separation.

9. REFERENCES

- Nicky Kern, Bernt Schiele, Holger Junker, Paul Lukowicz, and Gerhard Troster, "Wearable sensing to annotate meeting recordings," in *Proceedings. Sixth International Symposium on Wearable Computers*,. IEEE, 2002, pp. 186–193.
- [2] Tiantian Feng, Amrutha Nadarajan, Colin Vaz, Brandon Booth, and Shrikanth Narayanan, "Tiles audio recorder: an unobtrusive wearable solution to track audio activity," in *Proceedings of the 4th ACM Workshop on Wearable Systems and Applications*, 2018, pp. 33–38.
- [3] Arindam Dey, Mark Billinghurst, Robert W Lindeman, and J Edward Swan, "A systematic review of 10 years of augmented reality usability studies: 2005 to 2014," *Frontiers in Robotics and AI*, vol. 5, pp. 37, 2018.
- [4] Kiran Somasundaram, Jing Dong, Huixuan Tang, Julian Straub, Mingfei Yan, et al., "Project aria: A new tool for egocentric multimodal ai research," arXiv preprint arXiv:2308.13561, 2023.
- [5] Yanzhang He, Tara N Sainath, Rohit Prabhavalkar, Ian McGraw, et al., "Streaming end-to-end speech recognition for mobile devices," in 2019 IEEE International Conf. on Acoustics, Speech and Signal Processing (ICASSP), pp. 6381–6385.
- [6] DeLiang Wang and Jitong Chen, "Supervised speech separation based on deep learning: An overview," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 26, no. 10, pp. 1702–1726, 2018.
- [7] Cem Subakan, Mirco Ravanelli, Samuele Cornell, Mirko Bronzi, and Jianyuan Zhong, "Attention is all you need in speech separation," in *IEEE International Conf. on Acoustics, Speech and Signal Processing* (ICASSP), 2021, pp. 21–25.
- [8] Yi Luo, Zhuo Chen, and Takuya Yoshioka, "Dual-path rnn: efficient long sequence modeling for time-domain single-channel speech separation," in 2020 IEEE International Conf. on Acoustics, Speech, and Signal Processing, pp. 46–50.
- [9] Jacob Benesty, Jingdong Chen, and Yiteng Huang, *Microphone array signal processing*, vol. 1, Springer Science & Business Media, 2008.
- [10] Jack Capon, "High-resolution frequency-wavenumber spectrum analysis," *Proceedings of the IEEE*, vol. 57, no. 8, pp. 1408–1418, 1969.
- [11] Ju Lin, Niko Moritz, Ruiming Xie, Kaustubh Kalgaonkar, Christian Fuegen, and Frank Seide, "Directional Speech Recognition for Speaker Disambiguation and Cross-talk Suppression," in *Proc. INTER-SPEECH*, 2023, pp. 3522–3526.
- [12] Bo Li, Tara N Sainath, Ron J Weiss, Kevin W Wilson, and Michiel Bacchiani, "Neural network adaptive beamforming for robust multichannel speech recognition," 2016.
- [13] Tsubasa Ochiai, Shinji Watanabe, Takaaki Hori, John R Hershey, and Xiong Xiao, "Unified architecture for multichannel end-to-end speech recognition with neural beamforming," *IEEE Journal of Selected Topics in Signal Processing*, vol. 11, no. 8, pp. 1274–1288, 2017.
- [14] Tara N Sainath, Ron J Weiss, Kevin W Wilson, Arun Narayanan, and Michiel Bacchiani, "Factored spatial and spectral multichannel raw waveform cldnns," in 2016 IEEE International Conf. on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2016, pp. 5075–5079.
- [15] Weipeng He, Lu Lu, Biqiao Zhang, Jay Mahadeokar, Kaustubh Kalgaonkar, and Christian Fuegen, "Spatial attention for far-field speech recognition with deep beamforming neural networks," in 2020 IEEE International Conf. on Acoustics, Speech and Signal Processing (ICASSP), pp. 7499–7503.
- [16] Xiong Xiao, Shinji Watanabe, Hakan Erdogan, Liang Lu, John Hershey, Michael L Seltzer, et al., "Deep beamforming networks for multichannel speech recognition," in *IEEE International Conf. on Acoustics*, *Speech and Signal Processing (ICASSP)*, 2016, pp. 5745–5749.
- [17] Stefan Braun, Daniel Neil, Jithendar Anumula, Enea Ceolini, and Shih-Chii Liu, "Attention-driven multi-sensor selection," in 2019 International Joint Conf. on Neural Networks (IJCNN). IEEE, 2019, pp. 1–8.

- [18] Bo Li, Tara N Sainath, Arun Narayanan, Joe Caroselli, Michiel Bacchiani, Ananya Misra, Izhak Shafran, Hasim Sak, Golan Pundak, Kean K Chin, et al., "Acoustic modeling for google home.," in *Interspeech*, 2017, pp. 399–403.
- [19] Aditya Arie Nugraha, Antoine Liutkus, and Emmanuel Vincent, "Multichannel audio source separation with deep neural networks," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 24, no. 9, pp. 1652–1664, 2016.
- [20] Yann N Dauphin, Angela Fan, Michael Auli, and David Grangier, "Language modeling with gated convolutional networks," in *International conference on machine learning*. PMLR, 2017, pp. 933–941.
- [21] Ju Lin, Kaustubh Kalgaonkar, Qing He, and Xin Lei, "Speech enhancement for low bit rate speech codec," in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing* (*ICASSP*). IEEE, 2022, pp. 7777–7781.
- [22] Jay Mahadeokar, Yuan Shangguan, Duc Le, Gil Keren, Hang Su, Thong Le, Ching-Feng Yeh, Christian Fuegen, and Michael L Seltzer, "Alignment restricted streaming recurrent neural network transducer," in 2021 IEEE Spoken Language Technology Workshop (SLT). IEEE, 2021, pp. 52–59.
- [23] Niko Moritz, Frank Seide, Duc Le, Jay Mahadeokar, and Christian Fuegen, "An investigation of monotonic transducers for large-scale automatic speech recognition," in 2022 IEEE Spoken Language Technology Workshop (SLT), pp. 324–330.
- [24] Tara N Sainath, Yanzhang He, Bo Li, Arun Narayanan, Ruoming Pang, et al., "A streaming on-device end-to-end model surpassing server-side conventional model quality and latency," in 2020 IEEE International Conference on Acoustics, Speech and Signal Processing, pp. 6059– 6063.
- [25] Naoyuki Kanda, Jian Wu, Yu Wu, Xiong Xiao, Zhong Meng, Xiaofei Wang, Yashesh Gaur, Zhuo Chen, Jinyu Li, and Takuya Yoshioka, "Streaming multi-talker asr with token-level serialized output training," arXiv preprint arXiv:2202.00842, 2022.
- [26] Xuankai Chang, Niko Moritz, Takaaki Hori, Shinji Watanabe, and Jonathan Le Roux, "Extended graph temporal classification for multispeaker end-to-end asr," in 2022 IEEE International Conf. on Acoustics, Speech and Signal Processing, pp. 7322–7326.
- [27] Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur, "Librispeech: an asr corpus based on public domain audio books," in 2015 IEEE International Conf. on Acoustics, Speech and Signal Processing, pp. 5206–5210.
- [28] Eric A Lehmann and Anders M Johansson, "Prediction of energy decay in room impulse responses simulated with an image-source model," *The Journal of the Acoustical Society of America*, vol. 124, no. 1, pp. 269–277, 2008.
- [29] Chandan KA Reddy, Vishak Gopal, Ross Cutler, Ebrahim Beyrami, Roger Cheng, Harishchandra Dubey, et al., "The interspeech 2020 deep noise suppression challenge: Datasets, subjective testing framework, and challenge results," in *INTERSPEECH*, 2020.
- [30] Antony W Rix, John G Beerends, Michael P Hollier, and Andries P Hekstra, "Perceptual evaluation of speech quality - a new method for speech quality assessment of telephone networks and codecs," in 2001 IEEE International Conf. on Acoustics, Speech and Signal Processing, vol. 2, pp. 749–752.
- [31] Jonathan Le Roux, Scott Wisdom, Hakan Erdogan, and John R Hershey, "Sdr-half-baked or well done?," in 2019 IEEE International Conf. on Acoustics, Speech and Signal Processing, pp. 626–630.
- [32] Tiantian Feng, Rajat Hebbar, Nicholas Mehlman, Xuan Shi, Aditya Kommineni, and Shrikanth Narayanan, "A review of speech-centric trustworthy machine learning: Privacy, safety, and fairness," *APSIPA Trans. on Signal and Information Processing*, vol. 12, no. 3, 2023.