MUDD: A New Re-Identification Dataset with Efficient Annotation for Off-Road Racers in Extreme Conditions

Jacob Tyo^{1,2*}, Motolani Olarinre^{1*}, Youngseog Chung¹, Zachary C. Lipton¹

¹Carnegie Mellon University ²DEVCOM Army Research Laboratory { jtyo, young, tolani, zlipton }@cs.cmu.edu

Abstract

Re-identifying individuals in unconstrained environments remains an open challenge in computer vision. We introduce the Muddy Racer re-IDentification Dataset (MUDD), the first large-scale benchmark for matching identities of motorcycle racers during off-road competitions. MUDD exhibits heavy mud occlusion, motion blurring, complex poses, and extreme lighting conditions previously unseen in existing re-id datasets. We present an annotation methodology incorporating auxiliary information that reduced labeling time by over 65%. We establish benchmark performance using state-ofthe-art re-id models including OSNet and ResNet-50. Without fine-tuning, the best models achieve only 33% Rank-1 accuracy. Fine-tuning on MUDD boosts results to 79% Rank-1, but significant room for improvement remains. We analyze the impact of real-world factors including mud, pose, lighting, and more. Our work exposes open problems in reidentifying individuals under extreme conditions. We hope MUDD serves as a diverse and challenging benchmark to spur progress in robust re-id, especially for computer vision applications in emerging sports analytics. All code and data can be found at https://github.com/JacobTyo/MUDD.

1 Introduction

Re-identifying individuals across disjoint camera views is a fundamental task in computer vision. Despite progress, most research assumes controlled capture environments and consistent appearances (Gou et al. 2018). When restricted to such controlled environments, existing solutions do a good job of handling challenges due to occlusion, pose variation, and lighting changes. although further progress is needed (Ye et al. 2021). However, as we show, outside of such controlled environments, current techniques struggle.

In particular, we focus on the task of identifying motorcycle racers during off-road competitions (Figure 1) through mud, dirt, trees, and crowds. Here, appearances can change drastically lap-to-lap as mud accumulates or subsequently flies off. Numbered jerseys that could otherwise be used to easily re-id racers often become obscured by mud, are out of sight of the camera, or get torn. Glare, blurring, and extreme lighting also occur as a single racing event can go from bright fields to deep dark forests. To the best of our knowledge, there exists no public datasets to supports research into



Figure 1: Motorcycle Racer Re-Identification

robust re-id under such conditions.

To spur progress in addressing these challenges, we introduce the Muddy Racer Re-Identification Dataset (MUDD). MUDD contains 3,906 images of 150 identities captured over 10 off-road events by 16 professional motorsports photographers. The imagery exhibits heavy mud occlusions, complex poses, distant perspectives, motion blurring, and more. We also present an efficient annotation methodology incorporating detected racer numbers as auxiliary information to generate high-quality identity clusters for manual verification. This improved labeling time by over 65% compared to more simplistic labeling methods.

We establish benchmark performance using state-of-theart re-id models based on a Omni-Scale CNN Neural Network (Zhou et al. 2019) and ResNet-50 (He et al. 2016). Without fine-tuning, the best models reach only 22% Rank-1 accuracy. But when fine-tuning is incorporated, the best models reach 79% Rank-1 accuracy. Interestingly, pretraining can be performed with ImageNet data (Deng et al. 2009) to achieve nearly identical performance as pretraining on reidentification (re-id) specific datasets. Despite this increase in performance, a considerable gap remains between machine and human performance.

Our analysis reveals open problems in handling mud oc-

^{*}These authors contributed equally.

Photos in the current cluster:



Figure 2: Leveraging detected jersey numbers as auxiliary information enables generating higher quality identity clustering proposals for manual verification. This proposed cluster contains both clean and muddy images of the same rider, whereas proposing clusters with off-the-shelf re-id models fail.

clusion, appearance changes, poses, resolution, and similar outfits. These factors induce intra-class variation and inter-class similarity that current models fail to robustly distinguish. In summary, we introduce a diverse, challenging dataset exposing the limitations of existing re-id techniques. MUDD provides imagery to drive progress in reidentification amidst uncontrolled real-world conditions.

Our contributions are:

- The MUDD dataset containing diverse imagery to evaluate re-id of off-road racers. To our knowledge, this represents the first large-scale dataset of this emerging application domain.
- A method to improve annotation effectiveness by incorporating auxiliary information during labeling.
- Initial benchmarking of state-of-the-art models, which reveal limitations on this dataset and substantial room for further improvement.
- Analysis of failure cases which provide insights to guide future research on robust re-identification for sports analytics and computer vision broadly.



Figure 3: Additional proposed results for the same identity cluster as Figure 2. Our methodology provides high-quality recommendations to simplify manual verification and labeling.

2 Efficient Labeling via Auxiliary Information

One key challenge in constructing re-id datasets is to efficiently group images of the same identity during labeling. Exhaustively labeling identities from scratch can become intractable for a large dataset of images with an unknown number of identities. To assist in this labeling process, images can be clustered into groups using pretrained models, and then manually verified by annotators. However, in constructing MUDD, we found that annotators still spent over 30 minutes on each identity, requiring a more efficient process.

Off-the-shelf re-id models focus on extracting features invariant to nuisance factors like pose, lighting, and blurring while discriminating between identities. However, these features are based on their pretraining dataset and they cannot explicitly leverage domain-specific cues—especially if the domain-specific cues are not available in the pretraining dataset, such as racer numbers. The re-id model treats the image holistically without localizing and recognizing semantic concepts like digits. Therefore, when the models are applied on different image domains, any useful domainspecific cues are not used.

In light of this challenge, we leverage the fact that each identity (i.e. racer) in this dataset is assigned a visible number and we propose directly utilizing this auxiliary information during the clustering and re-id process via a pretrained text detection model (Lyu et al. 2018). This domain knowl-

Table 1: MUDD re-id benchmark results comparing off-the-shelf, from scratch, and fine-tuning training strategies. Fine-tuning provides major accuracy gains indicating the importance of transfer learning.

Training	Backbone	R1	R5	R10	mAP
Best off-the-shelf	OSNet	0.3252	0.5219	0.6327	0.3853
	ResNet-50	0.3164	0.5099	0.6306	0.3634
Trained From Scratch	OSNet	0.2146 (0.03108)	0.4846 (0.04466)	0.6755 (0.03606)	0.2491 (0.0163)
	ResNet-50	0.1591 (0.01154)	0.4155 (0.01564)	0.6194 (0.2826)	0.1923 (0.01853)
Pretrained on Imagenet	OSNet	0.7844 (0.01284)	0.9416 (0.005594)	0.9771 (0.004829)	0.8215 (0.01258)
	ResNet-50	0.762 (0.00817)	0.9442 (0.004079)	0.9787 (0.002729)	0.8073 (0.006272)
Pretrained on MSMT17	OSNet	0.7924 (0.009929)	0.9445 (0.001521)	0.9779 (0.002051)	0.8287 (0.005843)
	ResNet-50	0.7596 (0.02279)	0.9407 (0.0118)	0.9767 (0.006813)	0.8028 (0.02378)
Pretrained on DukeMTMC	OSNet	0.7887 (0.01515)	0.9388 (0.003319)	97.57 (0.004367)	0.826 (0.0117)
	ResNet-50	0.7858 (0.01726)	0.9562 (0.007937)	0.9847 (0.002225)	0.8277 (0.01079)
Pretrained on Market-1501	OSNet	0.7931 (0.01738)	0.9442 (0.006051)	0.9778 (0.00483)	0.827 (0.01546)
	ResNet-50	0.7812 (0.02546)	0.9475 (0.01395)	0.9807 (0.008821)	0.8233 (0.02077)

edge provides strong localization cues to group images with the same numbers. The re-id model alone struggles to consistently spot and match the small digit regions amidst mud, motion, and variations.

Explicitly guiding search and clustering with the auxiliary numbers, even if noisy, complements the holistic re-id model. Our breadth-first attribute search leverages the domain knowledge to effectively explore the data and retrieve number matches. This creates high-quality initial clusters that seed the depth-first re-id search.

In essence, we get the best of both worlds: domain-driven localization from the auxiliary cues, combined with holistic identity discrimination from the re-id model. The re-id model alone lacks the explicit semantic guidance, resulting in poorer search and clustering. Our hybrid approach better utilizes both domain knowledge and learned representations.

Specifically, to generate ground truth labels for specific racers, we first extract all numbers using a pretrained text detection model (Lyu et al. 2018), and also create a re-id embedding using a pretrained OSNet model. Then we iterate over the following process:

- 1. Pick a number that was detected more than 10 times and retrieve all images containing it.
- 2. For each result from Step 1, take the top k nearest neighbors based on the re-id embedding.
- 3. Combine the results for each search by rank, and present to annotators for manual refinement and verification.

This updated process reduced the average time to verify an identity cluster from over 30 minutes to under 10.

Figure 2 shows a proposed cluster from our labeling system. The top section contains all photos where the number 530 was detected. The bottom section shows the most similar images according to the pertained OSNet re-id model. Critically, leveraging the auxiliary number information provides an initial cluster with clean and muddy images of the same racer that can be used as a seed image for a search by the re-id model. Figure 3 shows additional results deeper in the ranking.

3 The MUDD Dataset

MUDD¹ contains 3906 images capturing 150 identities across 10 different off-road events from the Grand National Cross Country (GNCC) racing series. The events span various track conditions, weather, times of day, and racing formats. Images were captured by 16 professional motorsports photographers using a diverse range of high-end cameras.

We gathered a large library of off-road competition photos from the off-road photography platform PerformancePhoto. co. We used YOLOX (Ge et al. 2021) to detect the bounding boxes for people. An embedding was extracted for each cropped bounding box using the general-use re-id model OmniScaleNet (Zhou et al. 2019). We leverage a scene text spotter (Lyu et al. 2018) to extract visible racer numbers as auxiliary information to aid our labeling process, as detailed in Section 2. Importantly, the accuracy of the auxiliary models on MUDD data is low. Our scene text spotter has less than 50% end-to-end accuracy. However, as described in Section 2, even low-accuracy auxiliary information can still drastically improve annotation efficiency by enabling effective search and clustering.

We manually labeled all identities, accelerated by our proposed method. Some individuals occur in multiple events, either with very similar outfits or entirely different ones. To simplify training and evaluation, we provide an event ID and treat the same individual across events as different identities.

MUDD contains several major challenges:

- Heavy mud occlusion Racers accumulate significant mud spatters and caking. This represents a unique occlusion pattern not present in existing re-id datasets.
- Complex poses—Racers exhibit varied poses including leaning, jumping, crashes, and more unseen during regular walking.
- Distance and resolution—Images captured from a distance with small, low-resolution racer crops.
- Dynamic lighting—Outdoor conditions cause glare, shadows, and exposure variations.

¹MUDD is available at https://github.com/JacobTyo/MUDD



Figure 4: Example of successful re-id by the fine-tuned model under moderate mud occlusion. The 10 top retrievals correctly identify the query rider despite mud, pose, and other variations. Green boundaries signify correct matches and red incorrect.



Figure 5: Example of the model correctly matching a clean image of a rider to a muddy image of the same rider when the pose is similar between the query and gallery image. Green boundaries signify correct matches and red incorrect.

- Clothing—Jerseys and numbers that could ease re-id are often obscured by mud, gear, and positioning.
- Motion blur—Racers maneuver at high speeds causing motion-blurring effects, especially combined with panning cameras.

We divided MUDD into train (80%) and test (20%) sets. There is no identity overlap between the sets. We further divided the train set into a train and validation split also with a 90/10 ratio. The validation set was used for model selection, hyperparameter tuning, and ablation studies. All metrics reported on the held-out test set.

The dataset includes identities under a variety of motorcycle and riding gear. It captures both professional and amateur events across multiple states during the first 7 months of 2023. The diversity of identities, environments, perspectives, and conditions exceeds existing re-id datasets.

4 Experiments

We evaluated the performance of models on MUDD in three settings:

- **Off-the-shelf**: Pre-trained state-of-the-art re-id models applied directly to MUDD.
- **Random Initialization**: Models trained from random initialization only on MUDD.
- **Transfer**: Person re-identification pre-trained models fine-tuned on MUDD.

We selected strong open-source implementations of CNN-based architectures, hereafter referred to as OS-Net (Zhou et al. 2019) and ResNet50 (He et al. 2016).

For training, we used triplet loss, and data augmentation of random flips, color jitter, and random crop. Models were optimized using Adam. We tuned hyperparameters like learning rate, batch size, and data augmentation techniques based on the validation set. All models were trained for 100 epochs, using a cosine learning rate schedule with a maximum learning rate of 0.0003. The final performance is reported on the test set at the best checkpoint, and all models were trained on a single NVIDIA 2080Ti GPU. The mean and standard deviation are reported over three random seeds.

4.1 Evaluation Metrics

We adopt the standard re-id metrics cumulative matching characteristic (CMC) rank-1, rank-5, rank-10 and mean Average Precision (mAP). CMC measures rank-k accuracy, the probability of the true match appearing in the top k. The mAP metric computes mean average precision across all queries. Both operate directly on the re-id model output.

5 Results

Table 1 summarizes re-id performance on MUDD.

Off-the-shelf Models Applying pre-trained re-id models directly to MUDD leads to very poor accuracy. The highest Rank-1 is only 32.52% using OSNet pre-trained on Market-1501. This highlights the significant domain gap between existing re-id datasets and MUDD's challenging conditions. Off-the-shelf models fail to generalize.

Training from Scratch Begining with a random initialization, training models directly on MUDD struggles to learn effectively. OSNet is only able to achieve 21.46% Rank-1 accuracy, indicating the difficulty of learning a robust representation from this training data alone.

Fine-tuning Fine-tuning pre-trained models by resuming optimization on MUDD significantly improves accuracy. Fine-tuned OSNet reaches 79.31% Rank-1, over 2.5x higher than off-the-shelf and 3.7x higher than training from scratch. Fine-tuning transfers invariant features and discrimination



Figure 6: Failure case with heavy mud occlusion on the query image. Only 1 out of the top 10 results is a correct match, despite over 20 images of the same rider appearing in the gallery set, most of which are clean. Green boundaries signify correct matches and red incorrect.



Figure 7: Example of successful re-id by the fine-tuned model under light mud occlusion. All top 10 ranked results correctly match the query rider despite mud, blurring, lighting, pose, and complex backgrounds. Green boundaries signify correct matches and red incorrect.

capabilities from larger source datasets, allowing models to adapt to MUDD despite the limited training data.

Interestingly, models pre-trained on generic ImageNet data perform nearly as well as those pre-trained on re-id specific datasets like Market-1501 after fine-tuning. This indicates MUDD represents a significant domain shift even from existing re-id datasets. The ImageNet features still provide a useful initialization for fine-tuning to this new domain.

Architectures We experimented with two CNN-based architectures: OSNet, specifically designed for re-id tasks (Zhou et al. 2019), and ResNet-50, a general-purpose CNN also commonly used for re-id (He et al. 2016). After fine-tuning on MUDD, OSNet achieves slightly higher Rank-1 accuracy (79.31%) than ResNet-50 (78.12%).

This performance gap may stem from OSNet's specialized representations tailored for scale-invariance on people. In contrast, ResNet's more general features still perform competitively, demonstrating the versatility of standard CNNs. Overall, both architectures can adapt to MUDD's domain when fine-tuned, with OSNet's inductive biases providing a small boost. However, substantial room for improvement remains compared to human performance.

Pretraining Datasets We considered models already tailored to the person re-identification task. Starting with models pretrained on one of the re-id datasets of MSMT17 (Wei et al. 2018), DukeMTMC (Ristani et al. 2016), or Market-1501 (Zheng et al. 2015), we fine-tune the models further on MUDD. The performance of these models is comparable across different source datasets, all substantially improving over off-the-shelf and from scratch approaches.

In summary, pre-training provides significant accuracy gains by overcoming the limited training data through trans-

fer learning. However, gaps to human-level performance remain, motivating techniques tailored to MUDD's extreme conditions. The results reinforce the dataset's unique challenges and domain shift from existing re-id datasets.

6 Analysis

Our fine-tuned models demonstrate significant improvements in re-identifying riders compared to off-the-shelf and from-scratch approaches. As seen in Figures 4 and 7, the model is able to correctly match identities even with mud occlusion if the rider's pose is relatively consistent. This indicates that fine-tuning successfully incorporates invariances to mud while still distinguishing small inter-class differences like gear and outfit.

However, challenges remain under more extreme conditions. In the rest of this section, we analyze several key factors that still cause fine-tuned model failures on MUDD:

Mud occlusion As expected, heavy mud occlusion poses significant challenges. Mud induces high intra-class variation as the amount of mud covering a rider can vary drastically across images. It also causes low inter-class variation since mud occludes distinguishing features like jersey numbers and colors. As shown in Figure 6, querying with a muddy image retrieves other muddy images rather than cleaner images of the same identity.

Appearance variation Natural appearance changes of a rider over a race also confuses models. Riders may change gear like goggles or gloves multiple times. Crashes can rip clothing and jerseys. The model must learn to link different levels of mud, gear, and damage of a rider.

Pose variation Complex poses like jumps, crashes, and wheelies are difficult to match, especially combined with



Figure 8: Example of a failure case due to extreme pose variation in the query image. The rider is captured doing a wheelie, leading to incorrect matches despite no mud occlusion. Green boundaries signify correct matches and red incorrect.



Figure 9: Failure case due to pose variation between the query and gallery images. The backward-facing query rider is not matched to forward-facing images of the same identity. Green boundaries signify correct matches and red incorrect.

mud and appearance variation. As seen in Figure 8, a rider doing a wheelie is not matched to more standard riding poses. Even common pose differences like front versus back views are challenging (Figure 9).

Low resolution Images with small, distant crops of riders lack fine details for discrimination. Figure 11 shows a failure case where the query is low resolution.

Similar outfits In some cases, different riders with very similar gear are confused. This is common as racers supported by the same team will typically purposefully coordinate their appearance. An example is shown in Figure 10.

In summary, heavy mud occlusion, appearance changes, pose variations, low resolution, and similar outfits remain open challenges. While fine-tuning offers substantial improvements, significant gaps compared to human performance motivates the need for new techniques tailored to these uncontrolled conditions.

7 Limitations

While MUDD enables new research into re-id under extreme conditions, our work has several limitations to note:

Labeling Bias Our accelerated labeling methodology leveraging auxiliary information could introduce bias. By searching for images matching the same detected number, we preferentially sampled identities with more visible numbers. Not only may this over-represent riders with cleaner jerseys and under-represent heavy mud occlusion, but also many riders choose to have very little numbering. The labeling distribution may not fully reflect the underlying data. Models could overfit to the biases of our annotation process. Collecting additional labeled data with different sampling approaches could help quantify and reduce this bias. **Dataset Size** MUDD contains 3,906 images across 150 identities. While large for this emerging domain, this remains small compared to widely used re-id datasets. The limited data makes learning robust models difficult. Additional identities and examples would likely improve accuracy, but scaling dataset size is costly in this domain.

Capture Bias All MUDD data was captured during the first half of 2023 across 10 events in the GNCC racing series. This induces bias in the environments, rider identities, and more. Performance may not transfer to other off-road competitions like motocross, supercross, and flat track events. Broader capture diversity could improve model robustness.

Camera IDs MUDD lacks camera ID labels denoting which images came from the same capture device. Camera ID is a useful cue for re-id, enabling models to account for consistent environmental factors and biases per device. However, our dataset combines imagery from 16 different independent photographers at unknown shooting locations.

8 Related Work

Person re-identification (re-id) aims to match people across non-overlapping camera views and time horizons (Ye et al. 2021; Zheng, Yang, and Hauptmann 2016; Zheng et al. 2015; Farenzena et al. 2010). Early re-id methods relied on handcrafted features like color histograms, textures, and local descriptors (Farenzena et al. 2010). With the rise of deep learning, Convolutional Neural Network (CNN) (Zhou et al. 2019) and Transformer (He et al. 2021) based approaches now dominate re-id research, spurred by datasets like Market-1501 (Zheng et al. 2015), DukeMTMC-ReID (Ristani et al. 2016), and MSMT17 (Wei et al. 2018).

A few datasets address environmental factors. For example, Xiao et al. (2016) introduce a dataset with a low-resolution challenge set. Occlusions have also been well



Figure 10: Example failure case due to two different riders having very similar jerseys and gear, leading to confusion between their identities. Green boundaries signify correct matches and red incorrect.



Figure 11: Failure case due to low resolution of the query image preventing distinguishing details from being visible. The small, distant crop of the rider cannot be matched accurately. Green boundaries signify correct matches and red incorrect.

studied, spearheaded by datasets with high levels of occlusion (Schwartz and Davis 2009; Wang et al. 2011, 2016; Figueira et al. 2015; Xiao et al. 2016). However, these occlusions are unrelated to the heavy mud occlusion in our dataset. The addition of mud drastically complicates reidentification. Furthermore, no prior datasets exhibit such a complex combination of lighting, diversity, motion, and diverse cameras as our off-road racing dataset.

Prior work has focused on the re-identification of motorcycles and bicycles (Figueiredo et al. 2021; Li and Liu 2022; Yuan, Zhang, and Wang 2018), however these are restricted to street vehicles in urban settings. A highly related domain is identifying athletes in sports imagery. Penate-Sanchez et al. (2020) release a dataset of ultra-runners competing in a 128km race over the course of a day and a night. While this is more similar to the off-road setting in our dataset, they only have 416 different identities between 5 locations at a single event. Furthermore, there is near zero mud in the dataset. Along similar lines, but in even more controlled and limited settings, are the SoccarNet-ReID (Giancola et al. 2022) and DeepSportRadar-ReID (Van Zandycke et al. 2022) datasets, which contain images from broadcast video of soccer and basketball games respectively.

These datasets have driven research to develop methods to deal with the occlusions common in them. Approaches such as invariant representations (Chen et al. 2019), metric learning (Yi et al. 2014), semantic attributes (Shi, Hospedales, and Xiang 2015), part-based (Cheng et al. 2016) and poseaware models (Cho and Yoon 2016), and adversarial learning (Huang et al. 2018) have been proposed to alleviate occlusion problems. Other methods have been developed to handle misalignment, utilizes temporal cues in video (Li et al. 2019), use domain adaptation techniques (Deng et al. 2018), or unsupervised methods (Fan et al. 2018) to reduce label dependencies. Unlike our dataset, these all operate in controlled conditions. Existing models thus fail on our data.

In summary, re-id research has focused on controlled conditions and modest variation. Our dataset introduces realworld challenges absent in existing datasets. Our experiments expose clear gaps between current methods and this application. MUDD provides diverse imagery to spur new techniques for robust re-id under uncontrolled conditions.

9 Conclusion

In this work, we introduce MUDD, the first large-scale dataset to benchmark re-identification of motorcycle racers under extreme conditions. MUDD captures challenging factors including heavy mud occlusion, complex poses, variable lighting, and distant perspectives. We propose an accelerated annotation methodology incorporating detected racer numbers to enable efficient high-quality labeling.

Through initial benchmarking experiments, we demonstrate significant gaps between current re-id techniques and the real-world conditions represented in MUDD. Off-theshelf models fail to generalize to this new domain. Training CNN models like OSNet and ResNet from scratch struggles due to the limited training identities, but fine-tuning pretrained models on MUDD significantly improves accuracy. Interestingly, models pre-trained on generic ImageNet data prove as effective as re-id-specific pre-training.

However, substantial gaps compared to human performance remain even after fine-tuning. Our analysis reveals open challenges including handling heavy mud occlusion, complex poses, low resolution, and similar outfits. These factors induce intra-class variation and inter-class similarity that current models fail to robustly distinguish.

In summary, MUDD exposes clear limitations of existing re-id techniques under uncontrolled conditions. Our work motivates new solutions tailored to the unique challenges of identifying motorcycle racers amidst mud and more. Broader applications such as sports analytics stand to benefit from progress in re-id robustness. MUDD provides diverse, real-world imagery to drive future research towards re-identification in the wild.

References

Chen, Y.-C.; Li, Y.-J.; Du, X.; and Wang, Y.-C. F. 2019. Learning resolution-invariant deep representations for person re-identification. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, 8215–8222.

Cheng, D.; Gong, Y.; Zhou, S.; Wang, J.; and Zheng, N. 2016. Person re-identification by multi-channel parts-based cnn with improved triplet loss function. In *Proceedings of the iEEE conference on computer vision and pattern recognition*, 1335–1344.

Cho, Y.-J.; and Yoon, K.-J. 2016. Improving person reidentification via pose-aware multi-shot matching. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 1354–1362.

Deng, J.; Dong, W.; Socher, R.; Li, L.-J.; Li, K.; and Fei-Fei, L. 2009. Imagenet: A large-scale hierarchical image database. In 2009 IEEE conference on computer vision and pattern recognition, 248–255. Ieee.

Deng, W.; Zheng, L.; Ye, Q.; Kang, G.; Yang, Y.; and Jiao, J. 2018. Image-image domain adaptation with preserved self-similarity and domain-dissimilarity for person re-identification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 994–1003.

Fan, H.; Zheng, L.; Yan, C.; and Yang, Y. 2018. Unsupervised person re-identification: Clustering and fine-tuning. *ACM Transactions on Multimedia Computing, Communica-tions, and Applications (TOMM)*, 14(4): 1–18.

Farenzena, M.; Bazzani, L.; Perina, A.; Murino, V.; and Cristani, M. 2010. Person re-identification by symmetrydriven accumulation of local features. In 2010 IEEE computer society conference on computer vision and pattern recognition, 2360–2367. IEEE.

Figueira, D.; Taiana, M.; Nambiar, A.; Nascimento, J.; and Bernardino, A. 2015. The HDA+ data set for research on fully automated re-identification systems. In *Computer Vision-ECCV 2014 Workshops: Zurich, Switzerland, September 6-7 and 12, 2014, Proceedings, Part III 13, 241–255. Springer.*

Figueiredo, A.; Brayan, J.; Reis, R. O.; Prates, R.; and Schwartz, W. R. 2021. More: a large-scale motorcycle reidentification dataset. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 4034– 4043.

Ge, Z.; Liu, S.; Wang, F.; Li, Z.; and Sun, J. 2021. Yolox: Exceeding yolo series in 2021. *arXiv preprint arXiv:2107.08430*.

Giancola, S.; Cioppa, A.; Deliège, A.; Magera, F.; Somers, V.; Kang, L.; Zhou, X.; Barnich, O.; De Vleeschouwer, C.; Alahi, A.; et al. 2022. SoccerNet 2022 challenges results. In *Proceedings of the 5th International ACM Workshop on Multimedia Content Analysis in Sports*, 75–86.

Gou, M.; Wu, Z.; Rates-Borras, A.; Camps, O.; Radke, R. J.; et al. 2018. A systematic evaluation and benchmark for person re-identification: Features, metrics, and datasets. *IEEE transactions on pattern analysis and machine intelligence*, 41(3): 523–536.

He, K.; Zhang, X.; Ren, S.; and Sun, J. 2016. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 770–778.

He, S.; Luo, H.; Wang, P.; Wang, F.; Li, H.; and Jiang, W. 2021. Transreid: Transformer-based object re-identification. In *Proceedings of the IEEE/CVF international conference on computer vision*, 15013–15022.

Huang, H.; Li, D.; Zhang, Z.; Chen, X.; and Huang, K. 2018. Adversarially occluded samples for person re-identification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 5098–5107.

Li, J.; and Liu, B. 2022. Rider Re-identification Based on Pyramid Attention. In *Chinese Conference on Pattern Recognition and Computer Vision (PRCV)*, 81–93. Springer.

Li, J.; Wang, J.; Tian, Q.; Gao, W.; and Zhang, S. 2019. Global-local temporal representations for video person reidentification. In *Proceedings of the IEEE/CVF international conference on computer vision*, 3958–3967.

Lyu, P.; Liao, M.; Yao, C.; Wu, W.; and Bai, X. 2018. Mask textspotter: An end-to-end trainable neural network for spotting text with arbitrary shapes. In *Proceedings of the European conference on computer vision (ECCV)*, 67–83.

Penate-Sanchez, A.; Freire-Obregón, D.; Lorenzo-Melián, A.; Lorenzo-Navarro, J.; and Castrillón-Santana, M. 2020. TGC20ReId: A dataset for sport event re-identification in the wild. *Pattern Recognition Letters*, 138: 355–361.

Ristani, E.; Solera, F.; Zou, R.; Cucchiara, R.; and Tomasi, C. 2016. Performance measures and a data set for multi-target, multi-camera tracking. In *European conference on computer vision*, 17–35. Springer.

Schwartz, W. R.; and Davis, L. S. 2009. Learning discriminative appearance-based models using partial least squares. In 2009 XXII Brazilian symposium on computer graphics and image processing, 322–329. IEEE.

Shi, Z.; Hospedales, T. M.; and Xiang, T. 2015. Transferring a semantic representation for person re-identification and search. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 4184–4193.

Van Zandycke, G.; Somers, V.; Istasse, M.; Don, C. D.; and Zambrano, D. 2022. Deepsportradar-v1: Computer vision dataset for sports understanding with high quality annotations. In *Proceedings of the 5th International ACM Workshop on Multimedia Content Analysis in Sports*, 1–8.

Wang, S.; Lewandowski, M.; Annesley, J.; and Orwell, J. 2011. Re-identification of pedestrians with variable occlusion and scale. In 2011 IEEE International Conference on Computer Vision Workshops (ICCV Workshops), 1876–1882. IEEE.

Wang, T.; Gong, S.; Zhu, X.; and Wang, S. 2016. Person reidentification by discriminative selection in video ranking. *IEEE transactions on pattern analysis and machine intelligence*, 38(12): 2501–2514.

Wei, L.; Zhang, S.; Gao, W.; and Tian, Q. 2018. Person transfer gan to bridge domain gap for person reidentification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 79–88.

Xiao, T.; Li, S.; Wang, B.; Lin, L.; and Wang, X. 2016. End-to-end deep learning for person search. *arXiv preprint arXiv:1604.01850*, 2(2): 4.

Ye, M.; Shen, J.; Lin, G.; Xiang, T.; Shao, L.; and Hoi, S. C. 2021. Deep learning for person re-identification: A survey and outlook. *IEEE transactions on pattern analysis and machine intelligence*, 44(6): 2872–2893.

Yi, D.; Lei, Z.; Liao, S.; and Li, S. Z. 2014. Deep metric learning for person re-identification. In 2014 22nd international conference on pattern recognition, 34–39. IEEE.

Yuan, Y.; Zhang, J.; and Wang, Q. 2018. Bike-person reidentification: a benchmark and a comprehensive evaluation. *IEEE Access*, 6: 56059–56068.

Zheng, L.; Shen, L.; Tian, L.; Wang, S.; Wang, J.; and Tian, Q. 2015. Scalable person re-identification: A benchmark. In *Proceedings of the IEEE international conference on computer vision*, 1116–1124.

Zheng, L.; Yang, Y.; and Hauptmann, A. G. 2016. Person re-identification: Past, present and future. *arXiv preprint arXiv:1610.02984*.

Zhou, K.; Yang, Y.; Cavallaro, A.; and Xiang, T. 2019. Omni-scale feature learning for person re-identification. In *Proceedings of the IEEE/CVF international conference on computer vision*, 3702–3712.