Divide-and-Conquer Strategy for Large-Scale Dynamic Bayesian Network Structure Learning

Hui Ouyang¹, Cheng Chen², and Ke Tang¹

¹ Department of Computer Science and Engineering, Southern University of Science and Technology, Shenzhen 518055, China

ouyangh2021@mail.sustech.edu.cn,tangk3@sustech.edu.cn

² Research Institute of Trustworthy Autonomous Systems, Southern University of

Science and Technology, Shenzhen 518055, China

chenc3@sustech.edu.cn

Abstract. Dynamic Bayesian Networks (DBNs), renowned for their interpretability, have become increasingly vital in representing complex stochastic processes in various domains such as gene expression analysis, healthcare, and traffic prediction. Structure learning of DBNs from data is challenging, particularly for datasets with thousands of variables. Most current algorithms for DBN structure learning are adaptations from those used in static Bayesian Networks (BNs), and are typically focused on small-scale problems. In order to solve large-scale problems while taking full advantage of existing algorithms, this paper introduces a novel divide-and-conquer strategy, originally developed for static BNs, and adapts it for large-scale DBN structure learning. In this work, we specifically concentrate on 2 Time-sliced Bayesian Networks (2-TBNs), a special class of DBNs. Furthermore, we leverage the prior knowledge of 2-TBNs to enhance the performance of the strategy we introduce. Our approach significantly improves the scalability and accuracy of 2-TBN structure learning. Experimental results demonstrate the effectiveness of our method, showing substantial improvements over existing algorithms in both computational efficiency and structure learning accuracy. On problem instances with more than 1,000 variables, our approach improves two accuracy metrics by 74.45% and 110.94% on average, respectively, while reducing runtime by 93.65% on average.

Keywords: Machine learning \cdot Big data mining \cdot Data stream analysis \cdot Knowledge representation.

1 Introduction

Amidst advancements in deep neural networks, particularly the emergence of Large Language Models (LLMs) [22,19], deep learning has revealed unexpected potential. However, interpretability continues to challenge AI researchers [37,20]. Causal models, represented by Bayesian Networks (BNs) [23], are noted for their superior interpretability. Within this domain, Dynamic Bayesian Networks (DBNs) [21] stand out as a broadly applicable and adaptable model class, adept

at representing complex stochastic processes. Their utilization spans various fields, including gene expression analysis [1], medical care [27], and traffic prediction [14], and etc. Current algorithms for DBN structure learning are primarily adaptations of static BN structure learning algorithms. Identifying the graphical structure of BNs, especially under causal assumptions, remains a significant challenge [12]. Most of these algorithms have focused on small-scale problems. However, real-world scenarios often demand causal structure learning for large-scale problems, as seen in applications like MRI image interpretation [24], human genome analysis [3], and industrial Internet data mining [39].

Recently, a novel divide-and-conquer strategy for large-scale static BN structure learning has been proposed, termed Partition-Estimation-Fusion (PEF) [11]. Employing a divide-and-conquer strategy yields distinct advantages. When the integrated structural learning algorithm, used for solving subproblems, has a time complexity beyond linear, enhanced scalability is expected. Ignoring causal insufficiency, subproblems are considerably less complex compared to the original problem. Effectively dividing nodes to weaken inter-cluster connectivity relative to intra-cluster can reduce the impact of divide-induced causal insufficiency on overall accuracy. Notably, the estimation phase of the PEF, which involves solving different subproblems, is highly parallelizable. For DBN structure learning, works like [9,33] have transformed the problem into two separate static BN learning tasks. In this work, we assert that the PEF strategy can be effectively adapted for the structure learning of 2 Time-sliced Bayesian Networks (2-TBN), a special class of DBNs, to yield strong performance. Furthermore, we enhance the PEF strategy for DBN structure learning by leveraging prior knowledge of 2-TBN. The contributions of this paper are threefold:

- 1. Introducing the divide-and-conquer PEF strategy from static BNs to DBNs;
- 2. Utilizing prior knowledge of 2-TBN to augment the PEF strategy for DBNs;
- 3. Conducting experiments to validate the effectiveness of our proposed strategy in DBN structure learning.

The remainder of this paper is organized as follows. Section 2 provides background on BNs, DBNs, and their structure learning challenges, along with a review of related work. Section 3 details our proposed divide-and-conquer strategy for 2-TBNs. Experimental validation of our approach is presented in Section 4, and Section 5 concludes the paper with a summary and discussion of future research directions.

2 Preliminaries and Related Work

2.1 Bayesian Network

Bayesian Networks (BNs) [23] are a theoretical model used to describe probabilistic relationships, providing a clear representation of causal information. For a set of *n* random variables $X = \{X_1, X_2, \ldots, X_n\}$, a BN $B = (G, \Theta)$ consists of a Directed Acyclic Graph (DAG) G = (V, E) and a parameter set Θ . Here, *V*



Fig. 1: An example of a 2-TBN. (a) The initial model (left) and transition model (right) for a 2-TBN with three variables. (b) The corresponding "unrolled" DBN with six time slices.

and E respectively denote the vertex and edge sets of the DAG G. Each vertex $V_i \in V$ represents a random variable $X_i \in X$, and each edge $(V_i, V_j) \in E$ indicates a directed causal relationship between X_i and X_j . The dependency of each variable X_i is solely on variable(s) $X_{pa(i)} \in X$ associated with its parent nodes $V_{pa(i)} \in V$. The parameter set $\Theta = \{P(X_i|X_{pa(i)})\}$ encompasses all conditional probabilities of the variables given the states of their parents in G. Adhering to the first-order Markov property, these random variables enable a compact representation of the joint probability distribution over all variables:

$$P(X) = \prod_{i=1}^{n} P(X_i | X_{pa(i)})$$
(1)

2.2 Dynamic Bayesian Network

Dynamic Bayesian Networks (DBNs) [21] extend static BNs by integrating time information into the original network structure, enabling the processing of timeseries data. The state changes in a DBN model can be visualized as a series of animation frames, with each frame capturing the current state of the DBN. These frames, often called time slices, contain a observation of random variables. For simplicity, it is commonly assumed that each time slice comprises variables from a consistent set. A DBN is a probabilistic graphical model designed to represent sequential systems, determining the probability distribution over X[t], where $X[t] = \{X_1[t], X_2[t], \ldots, X_n[t]\}$ represents the *n* variables observed over discrete time *t*. DBNs represent a category of graphical models widely recognized as a standard tool for modeling a range of stochastic, time-varying, or non-stationary phenomena. While numerous studies employ various forms of DBNs, we focus on a special class of DBNs in this work, namely 2 Time-sliced Bayesian Network (2-TBN) with an example shown in Figure 1.

A 2-TBN can be defined as a pair of BNs, denoted as (B_0, B_{\rightarrow}) . The BN $B_0 = (G_0, \Theta_0)$ represents the initial joint distribution of the process, expressed as P(X[t=0]), while $B_{\rightarrow} = (G_{\rightarrow}, \Theta_{\rightarrow})$ represents the distribution P(X[t+1]|X[t]). A 2-TBN is a type of DBN that adheres to the first-order Markov property, formulated as $X[t-1] \perp X[t+1]|X[t]$. This implies that the variables in the time slice t+1 are independent of those in time slice t-1, given the variables in time slice t. The initial model B_0 is a basic static BN, comprising a DAG G_0 with the variables X[t=0] and a set of conditional distributions $P(X_i[t=0]|X_{pa(i)G_0})$, where $X_{pa(i)G_0}$ denotes the parents of the variable $X_i[t=0]$ in G_0 . The transition model B_{\rightarrow} is a two-slice temporal BN, consisting of the DAG G_{\rightarrow} with variables $X[t] \cup X[t+1]$ and a set of conditional distributions $P(X_i[t+1]|X_{pa(i)G_{\rightarrow}})$, where $X_{pa(i)G_{\rightarrow}}$ represents the parents of $X_i[t+1]$ in G_{\rightarrow} . The distribution of the transition model B_{\rightarrow} is defined as follows:

$$P(X[t+1]|X[t]) = \prod_{i=1}^{n} P(X_i[t+1]|X_{pa(i)_{G\to}})$$
(2)

The joint probability distribution for a sequence from t = 0 to t = T is obtained by unrolling the 2-TBN:

$$P(X[0:T]) = \prod_{i=1}^{n} P(X_i[t=0]|X_{pa(i)_{G_0}}) \times \prod_{t=0}^{T-1} \prod_{i=1}^{n} P(X_i[t+1]|X_{pa(i)_{G_{\rightarrow}}}) \quad (3)$$

2.3 Structure Learning Problem

Constructing a static BN typically involves two main stages: (a) identifying the structure of the DAG, and (b) determining the parameter set for all conditional probabilities of the variables, given the states of their parent nodes in the DAG. The structure learning problem, as the name suggests, is primarily concerned with identifying the DAG structure of the BN. In the case of a DBN represented by (B_0, B_{\rightarrow}) , structure learning is divided into two components — structure learning of a straightforward static DAG G_0 containing variables X[t = 0], and structure learning of a time slice DAG G_{\rightarrow} containing variables $X[t] \cup X[t+1]$. This graph structure may be identified through expert knowledge, data-driven methodologies, or a blend of both. However, manually constructing large-scale BNs or DBNs is often impractical. Consequently, this paper primarily focuses on a data-driven approach, where DAGs are inferred from observable data rather than relying on expert experience.

The DBN structure learning problem we discuss in this work is formally defined as follows: Given an observable dataset $D = \{d_1, d_2, \ldots, d_m\}$ comprising mdata samples, each sample $d_i \in D$ represents a sequence of length l with instances $(x[t = 0], x[t = 1], \ldots, x[t = l - 1])$. Every instance contains observed values $\{x_1, x_2, \ldots, x_n\}$ corresponding to the random variables $X = \{X_1, X_2, \ldots, X_n\}$ in a specific time slice. The objective is to determine the DAG structures G_0 and G_{\rightarrow} of the 2-TBN in a manner that most effectively captures the causal relationships among the random variables within the time-series process. In practice, a designated structure evaluation metric is typically used to quantify the quality of the derived DAG structure. As the number of nodes increases, there is a recursive surge in the number of DAGs [26]. This relationship is captured by the following equation:

$$|G_n| = \sum_{i=1}^n (-1)^{i-1} C_n^i 2^{i(n-i)} |G_{n-i}|$$
(4)

where $|G_n|$ is the number of DAGs with *n* nodes, while C_n^i denotes the combinations of selecting *i* elements from a total of *n*, and $|G_0|$ is defined as 1. Furthermore, the structure learning of 2-TBN is classified as an NP-hard problem, as is the case with static BN [6].

2.4 Related Work

Static BN structure learning is an NP-hard problem [6], typically addressed using approximation methods. These methods are categorized into constraint-based, score-based, and hybrid approaches. Constraint-based methods, including the PC [30], MMPC [34], and PC-Stable [7] algorithms, rely on Conditional Independence (CI) tests on observations to discern relationships among variables. Within the space of DAGs or Markov Equivalence Classes (MECs), score-based methods use heuristic techniques (Tabu Search (TS) [4], Genetic Algorithm (GA) [13], Greedy Search (GS) [5], etc.) and scoring functions (BDeu [2], BIC [28], K2 [8], etc.) to steer the search. Recent developments in score-based methods, such as NOTEARS [38] and LEAST [39], have reframed BN structure learning as a continuous optimization problem. Hybrid methods, exemplified by MMHC [35], combine constraint-based and score-based strategies, using MMPC to construct the graph skeleton and TS for finalizing the BN. As the number of variables grows, traditional methods often slow down significantly and lose accuracy. To address this, fGES [24], building on GES [5], has demonstrated the ability to manage large-scale problems by narrowing the search space and facilitating parallel search. Additionally, the Partition-Estimation-Fusion (PEF) [11] strategy applies a divide-and-conquer approach, significantly improving the handling of large-scale problems.

Current techniques for learning DBNs structure are largely adaptations of those used in BN structure learning. To illustrate, DBN structure learning can be divided into two independent stages: learning the initial graph G_0 as a static BN structure with a dataset for X[t = 0], and learning the transition graph G_{\rightarrow} with another "static" dataset for all the transitions $X[t] \cup X[t + 1]$. Building on this, [9] has seamlessly integrated the use of GS in BN structure learning into DBN structure learning. The DMMHC [33] algorithm, specifically designed for DBN structure learning, evolves from the MMHC algorithm used in static one. Additionally, numerous studies explore the application of bayesian optimization and evolutionary computation to address this challenge [10,18,36]. When dealing with partially observed systems (incomplete data), structure learning becomes computationally demanding. One effective solution is the Structural

Expectation-Maximization (SEM) [35] algorithm. While these methods have been validated on small benchmark models, they tend to become exceedingly complex as the number of variables increases, reflecting the inherent limitations of current structure learning methodologies.

3 Proposed Method

Due to the inherent limitations of current structure learning methodologies, algorithms tend to become increasingly complex and time-consuming with the addition of more variables. The divide-and-conquer approach is a widely employed strategy for addressing large-scale problems in algorithm design. This strategy provides significant advantages, particularly when existing structure learning algorithms exhibit time complexity beyond linear, enhancing scalability. The Partition-Estimation-Fusion (PEF) [11] strategy, based on the divide-andconquer principle [16,31,17], has been developed for large-scale structure learning in static Bayesian Networks (BNs). Works such as [9,33] approach the problem of Dynamic Bayesian Network (DBN) structure learning by transforming it into two separate static BN structure learning problems. We believe that the PEF strategy can be effectively adapted for the 2 Time-sliced Bayesian Network (2-TBN) structure learning, yielding relevant results.

In essence, the structure learning problem of a 2-TBN can be divided into two distinct "static" tasks:

- Extracting all observation data in time slices t = 0 from the time series into a dataset for X[t = 0] to learn the initial graph G_0 , and
- Combining observation data from adjacent time slices into a single data point, forming another "static" dataset for $X[t] \cup X[t+1]$ to learn the transition graph G_{\rightarrow} .

Following this transformation, the PEF strategy can be employed to learn G_0 and G_{\rightarrow} separately. The PEF strategy comprises the following three steps:

- 1. Partition The nodes (variables) are divided into clusters using a Modified Hierarchical Clustering (MHC) algorithm.
- 2. Estimation Applying an existing structure learning method to estimate a subgraph for each cluster.
- 3. Fusion Merging estimated subgraphs into a comprehensive DAG encompassing all nodes.

Besides introducing the PEF strategy following the transformation of 2-TBN structure learning, this work also includes enhancements to the fusion phase of PEF to fully leverage the prior knowledge of 2-TBN. In the remainder of this section, we will give the details of the partition and estimation phases in Section 3.1, and the enhanced fusion techniques for 2-TBN in Section 3.2.

3.1 Partition and Estimation

Consider a static observation data matrix D_{static} comprising m samples. Each node in the set $V = \{V_1, V_2, \ldots, V_n\}$ corresponds to a data column $X_j \in \mathbb{R}^m$ for $j = 1, 2, \ldots, n$. The Partition step (P-step) in the PEF strategy involves grouping nodes into clusters. This step results in p clusters, labeled as C_i for $i = 1, 2, \ldots, p$, using a MHC method with average linkage. This method autonomously determines the number of clusters p as follows. The PEF strategy considers that the minimum size for clusters should be 0.05n, referring to these as "big clusters". For each iteration $h = 0, 1, \ldots, n - 1$, C_h represents the clusters formed during the h^{th} iteration of bottom-up hierarchical clustering. Specifically, $C_0 = \{\{V_1\}, \{V_2\}, \ldots, \{V_n\}\}$ consists of n singleton clusters, and $C_{n-1} = \{\{V_1, V_2, \ldots, V_n\}\}$ denotes a single cluster comprising all n nodes. The number of big clusters in C_i is denoted by p_i . PEF determines a specific p based on the equation:

$$p = \min\{p_{max}, \max_{0 \le i \le n-1} p_i\}$$

$$\tag{5}$$

where $p_{max} \leq 20$ is the user-defined maximum number of big clusters. After determining p, the highest level l on the dendrogram containing p big clusters is defined by:

$$l = \arg \max_{0 \le i \le n-1} \{i : p_i = p\}$$
(6)

Clusters at level C_l are reordered in descending order of their sizes, such that $S_1 \ge S_2 \ge \ldots \ge S_{n-l}$, where $S_i = |C_i|$. The first *p* clusters are identified as the primary big clusters. MHC then integrates remaining small clusters into these big clusters by continuously merging the closest pairs. In PEF, the distance between two nodes V_i and V_j is defined as:

$$d(i,j) = 1 - |r_{ij}| \in [0,1] \tag{7}$$

where $r_{ij} = cor(X_i, X_j)$ denotes the correlation between X_i and X_j for i, j = 1, 2, ..., n. This correlation is calculated using the covariance $cov(X_i, X_j)$, standard deviations $\sigma_{X_i}, \sigma_{X_j}$, and the formula:

$$cor(X_i, X_j) = \frac{cov(X_i, X_j)}{\sigma_{X_i} \sigma_{X_j}}$$
(8)

The pseudocode for the MHC algorithm is provided in Algorithm 1. It starts with the computation of the dissimilarity matrix $D = (d(i, j))_{n \times n}$, as defined by Equation 7.

During the Estimation step (E-step) of the PEF process, the structure of each subgraph is determined individually. This step functions as a black box within the PEF, allowing users to apply any BN structure learning algorithm for estimating subgraphs without requiring detailed technical knowledge. Usually, this step results in p Partial DAGs (PDAGs). It is important to note that both DAGs and complete PDAGs (CPDAGs) are included within the category of PDAGs. If the time complexity of a chosen structure learning technique exceeds O(n), the

Algorithm 1 Modified Hierarchical Clustering (MHC)

- 1: Perform hierarchical clustering using the dissimilarity matrix $D = (d(i, j))_{n \times n}$.
- 2: Construct the dendrogram T_D from the hierarchical clustering.
- 3: Determine p using Equation 5 and l using Equation 6.
- 4: Reorder clusters in $C \leftarrow C_l$ such that $S_1 \ge \ldots \ge S_{n-l}$.
- 5: while |C| > p do
- $(i^*, j^*) \leftarrow argmin_{(i,j)} \{ d(C_i, C_j) : i < j \land j > p \}.$ $C_{i^*} \leftarrow C_{i^*} \cup C_{j^*}, C \leftarrow C \backslash \{C_{j^*}\}.$ 6:
- 7:
- 8: end while
- 9: return the final clusters $C = \{C_1, C_2, \ldots, C_p\}$.

time to learn small subgraphs in the E-step is significantly reduced compared to estimating a complete DAG. At the same time, E-step is easy to parallelize. Assuming that nodes have been divided into p clusters C_1, C_2, \ldots, C_p during the P-step, and the time to learn a PDAG on C_i is t_i , executing the learning process of p subgraphs in parallel across p cores can minimize the duration of the E-step to $\max\{t_i: i=1,2,\ldots,p\}$. This time is typically influenced by the size of the largest cluster.

Enhanced Fusion for 2-TBN 3.2

During the Fusion step (F-step) of the PEF process, a hybrid method is applied to derive the full DAG structure from the subgraphs estimated in the E-step. The F-step involves two phases. Initially, PEF creates a candidate edge set A to narrow down the search space. It then identifies a subset A^* , consisting of potential edges between subgraphs, through statistical tests. As a result, the candidate edge set A includes A^* along with all edges identified in each subgraph during the E-step. Subsequently, PEF optimizes the DAG structure by iteratively refining edges within set A using a modified Bayesian Information Criterion (BIC) score. The final outcome of the F-step is a DAG. Building on the original F-step, this study incorporates specific prior knowledge of the 2-TBN to enhance the F-step. This prior knowledge is primarily applied in learning the transition graph G_{\rightarrow} :

- Interactions among variables within previous time slice t are not considered, hence there are no connections between nodes belonging to X[t];
- Future observations cannot influence past variables, therefore edges from X[t+1] to X[t] are excluded.

Finding Candidate Edge Set For subgraphs denoted as G_m (m = 1, 2, ..., p), let $z(i) \in \{1, 2, \ldots, p\}$ represent the cluster label of node V_i . Typically, these subgraphs G_m are represented as PDAGs. Neighbors of node V_i in subgraph $G_{z(i)}$ are defined by $N_i(z(i)) = \{V_j \in G_{z(i)} : V_j \to V_i \in G_{z(i)} \lor V_i - V_j \in G_{z(i)}\},\$ where $V_j \rightarrow V_i$ indicates a directed edge, and $V_i - V_j$ an undirected one. The correlation $\tilde{\rho}_{ij}$ between the residuals R_i and R_j , after projecting X_i onto its Divide-and-Conquer Strategy for Large-Scale DBN Structure Learning

Algorithm 2 Find Candidate Edge Set A

1: Input data matrix D_{static} and estimated subgraphs G_1, G_2, \ldots, G_p . 2: Set $\widetilde{A}^* = \emptyset$. 3: for all pairs (V_i, V_j) such that $z(i) \neq z(j)$ do 4: if $\widetilde{\rho}_{ij} = 0$ is rejected at level α then $\tilde{A}^* \leftarrow \tilde{A}^* \cup (V_i, V_i).$ 5:end if 6: 7: end for 8: Set $A^* = \emptyset$. 9: for all $(V_i, V_j) \in \widetilde{A}^*$ do 10: Let $Z = N_i(z(i)) \cup N_j(z(j)) \cup P_{ij}$. if $I_p(X_i; X_j | Z)$ is rejected at level α then 11: $A^* \leftarrow A^* \cup (V_i, V_j).$ 12:13:end if 14: end for 15: return $A = A^* \cup SK(G)$.

neighbors $N_i(z(i))$ in $G_{z(i)}$, is used to filter unlikely edges between subgraphs. Specifically, an initial candidate set \tilde{A}^* includes pairs (V_i, V_j) where $z(i) \neq z(j)$ and the hypothesis $\tilde{\rho}_{ij} = 0$ is rejected at a significance level α using a z-test with Fisher transformation on the correlation coefficient $\tilde{\rho}_{ij}$. Subsequently, a sequential method refines A^* to determine the final candidate edge set A^* between subgraphs. Each node pair (V_i, V_j) in \tilde{A}^* undergoes a conditional independence test considering the union of their updated neighbors, $N_i(z(i)) \cup N_i(z(j)) \cup P_{ij}$, where P_{ij} is defined as the set of neighbors of V_i or V_j in the current candidate set A^* between subgraphs. Let G be the PDAG composed of disconnected subgraphs derived from the E-step, and SK(G) represent the edge set in the skeleton of G, that is, $SK(G) = \{(V_i, V_j) : V_i - V_j \in G \lor V_i \to V_j \in G\}$. The candidate edge set A is generated by appending SK(G) to A^* . The edges in the final output DAG of the method will be a subset of A. The pseudocode for finding the candidate edge set A is outlined in Algorithm 2, where $I_n(X_i; X_i|Z)$ denotes an independence test. In implementation, PEF sorts the node pairs in A^* in ascending order of their p-values in testing against $\tilde{\rho}_{ij} = 0$.

Learning Full DAG Structure In the final phase of the F-step, the PEF method determines the existence and direction of each edge for node pairs $(V_i, V_j) \in A$. This is accomplished by sequentially minimizing a modified BIC score, known as the Risk Inflation Criterion (RIC), over the candidate edge set. The RIC score, defined as:

$$RIC(G) = -2l(G) + \lambda d(G) \tag{9}$$

which includes two components: a log-likelihood component l(G), evaluating how well graph G fits the data; and a regularization term d(G), weighted by $\lambda = 2 \log n$, to encourage sparsity. The PEF employs this score especially when

Algorithm 3 Fuse Subgraphs

1: Input data matrix D_{static} and estimated subgraphs G_1, G_2, \ldots, G_p . 2: Run Algorithm 2 to generate candidate edge set A. 3: Initialize G as the PDAG comprising G_1, G_2, \ldots, G_p . for each pair $(V_i, V_j) \in A$ do 4: if V_i, V_j are adjacent in G then 5:6: Remove the edge from G. 7: end if if $I_p(X_i; X_i | N_i(G) \cup N_i(G))$ then 8: 9: Remove (V_i, V_j) from A. 10: else 11: Set $RIC_{\max} = \max\{RIC(M_1), RIC(M_2)\}.$ if $RIC_{\max} < RIC(M_0)$ then 12:if adding edge $V_i \rightarrow V_j$ induces a cycle then 13:Add edge $V_i \to V_i$ to G. 14:else if adding edge $V_j \to V_i$ induces a cycle then 15:16:Add edge $V_i \to V_j$ to G. else 17:18:Choose the direction leading to a smaller RIC. 19:end if end if 20: 21: end if 22: end for 23: Repeat lines 4 to 22 until the structure of G remains unchanged. 24: return G.

dealing with a large number of nodes $(n > \sqrt{m})$. Conversely, for $n \leq \sqrt{m}$, the standard BIC score with $\lambda = \log m$ is used. For every pair $(V_i, V_j) \in A$, PEF evaluates three models:

- M_0 Absence of an edge between V_i and V_j .
- $\begin{array}{l} \ M_1 \ \text{-} \ V_i \ \text{as a parent of} \ V_j. \\ \ M_2 \ \text{-} \ V_j \ \text{as a parent of} \ V_i. \end{array}$

During this evaluation, all other edges in G remain fixed. An edge is introduced between V_i and V_j if max{ $RIC(M_1), RIC(M_2)$ } < $RIC(M_0)$. Subsequently, PEF decides the direction of the edge, ensuring acyclicity or opting for the model with the lower RIC score based on a predefined tie-breaker. Algorithm 3 illustrates the F-step, which iteratively processes A until no further changes in the structure of G are observed. Upon completion of the F-step, PEF returns the finalized DAG.

Utilization of Prior Knowledge For the structure learning of the initial graph G_0 , no prior knowledge is available. Therefore, the F-step as outlined in Algorithms 2 and 3 can be directly applied. Conversely, for the structure learning of the transition graph G_{\rightarrow} , the previously mentioned prior knowledge can be utilized to enhance the F-step. The improvements are as follows: In line 3 of Algorithm 2, pairs (V_i, V_j) where both V_i and V_j are in X[t] should be skipped. In line 15 of Algorithm 2, pairs $(V_i, V_j) \in SK(G)$ should be removed if both V_i and V_j are in X[t]. From line 10 to 21 in Algorithm 3, do not consider directed edge $V_j \to V_i$ if $V_j \in X[t+1]$ and $V_i \in X[t]$, and vice versa.

4 Experiments

This section experimentally validates the effectiveness of the divide-and-conquer strategy for Dynamic Bayesian Network (DBN) structure learning proposed in this work. Initially, Section 4.1 will detail the sources of our experimental data, followed by a discussion of the experimental setup in Section 4.2. Subsequently, Section 4.3 will present a comparative analysis of the divide-and-conquer strategy against baselines, thereby illustrating its overall efficacy.

4.1 Data Generation

To overcome the limitations of a small variable count in existing public datasets, we have adapted a method from previous research [11,32] to create diverse, large-scale 2 Time-sliced Bayesian Network (2-TBN) datasets that meet our experimental needs. Our data generation approach, slightly modified from the existing method, is described as follows:

- 1. Duplicate an existing network structure a specified number of times.
- 2. While ensuring the final network remains a Directed Acyclic Graph (DAG), interconnect the duplicates by adding 10% of random edges between them.
- 3. Apply step 1 and 2 to generate an initial graph G_0 .
- 4. Apply step 1 and 2 to generate the nodes and intra-connections of X[t+1] in the transition graph G_{\rightarrow} .
- 5. Tile the nodes of X[t+1] in G_{\rightarrow} to nodes of X[t] (excluding intra-connections) and randomly introduce 20% of inter-connections from X[t] to X[t+1].
- 6. Simulate numerous observational data records by G_0 and G_{\rightarrow} .
- 7. Normalize the observed data to ensure uniform mean and standard deviation across all data columns.

The structures of all networks were obtained from the repository of bnlearn R package [29]. Within this repository, we selected 10 well-known static networks: Alarm, Asia, Cancer, Child, Earthquake, Hailfinder, Healthcare, Mildew, Pigs, and Survey. For each static network, we generated a corresponding large-scale 2-TBN with over 1,000 nodes and sampled 1,000 time series sequences of length 6. Consequently, for each problem instance, we have 1,000 X[t = 0] samples for G_0 structure learning and 5,000 $X[t] \cup X[t + 1]$ samples for G_{\rightarrow} structure learning. The details of the number of nodes and edges for each 2-TBN problem instance are presented in Table 1.

| Instance | $\#\mathbf{Nodes}$ | $\#$ Edges of G_0 | $\#$ Edges of G_{\rightarrow} |
|------------|--------------------|---------------------|---------------------------------|
| Alarm | 1036 | 1417 | 1701 |
| Asia | 1000 | 1100 | 1320 |
| Cancer | 1000 | 880 | 1056 |
| Child | 1000 | 1375 | 1650 |
| Earthquake | 1000 | 880 | 1056 |
| Hailfinder | 1008 | 1307 | 1569 |
| Healthcare | 1001 | 1416 | 1700 |
| Mildew | 1015 | 1468 | 1762 |
| Pigs | 1323 | 1954 | 2345 |
| Survey | 1002 | 1103 | 1324 |
| | | | |

Table 1: Number of nodes (variables) and edges for each problem instance.

4.2 Experimental Methodology

Since our divide-and-conquer strategy is built upon existing Bayesian Network (BN) structure learning algorithms (i.e., base algorithms), we selected using the PC-Stable [7] algorithm as the base algorithm specifically. This choice is due to PC-Stable's representation as a well-performing and stable algorithm among current offerings. For our experiments, we utilized the PC-Stable implementation from the TETRAD causal discovery toolbox [25]. In our experiments, we conducted runs of the PC-Stable algorithm both with and without (as baselines) using our divide-and-conquer strategy. Given that the benefits of the divide-and-conquer approach in static BN structure learning have already been established in [11], our primary focus is on enhancements related to the transition model G_{\rightarrow} .

In terms of performance evaluation, given our knowledge of the true graph structures in the generated problem instances, we employ edge classificationbased metrics. This involves classifying the relationship between nodes A and B as either $A \leftarrow B$, $A \rightarrow B$, or no edge, and accordingly, we use the F1 score to assess edge classification accuracy. Notably, many BN structure learning algorithms, including PC-Stable, estimate graphs as Markov Equivalence Classes (MECs) of DAGs rather than as DAGs themselves. This results in graphs with undirected edges (A - B). Following the approach in [24], we evaluate performance using two metrics: F1 Adjacent (disregarding direction) and F1 Arrowhead (considering direction). We also measure the running time (physical time) of the algorithms in seconds. Unless stated otherwise, all experiments were conducted on a Linux server equipped with double Intel(R) Xeon(R) Gold 6336Y CPU @ 2.40GHz, 96 cores, and 768GB of RAM, running Ubuntu 22.04.2 LTS. Due to computational resource constraints, we imposed a one-day runtime limit for each problem instance. Table 2: The results (mean value \pm standard deviation) for testing problem instances are presented in terms of F1 Adjacency (F1 Adj, ×10²), F1 Arrowhead (F1 Arr, ×10²), and Runtime (in seconds). In the comparison, metrics that significantly outperform others, indicated by higher mean values and passing significance tests (Wilcoxon signed-rank test at a 99% confidence level), are highlighted in **bold**.

| Instance | PC-Stable | | | Our Method | | |
|------------|--------------------|--------------------|-------------------------|---------------------|---------------------|-------------------------|
| | F1 Adj | F1 Arr | Runtime | F1 Adj | F1 Arr | Runtime |
| Alarm | $39.34 {\pm} 0.53$ | $31.15 {\pm} 0.53$ | 27411.87 ± 2379.08 | $62.92{\pm}2.25$ | $57.90{\pm}2.25$ | $322.83{\pm}247.25$ |
| Asia | $35.17 {\pm} 0.60$ | $21.66{\pm}0.60$ | $13564.81 {\pm} 930.42$ | $68.62 {\pm} 0.65$ | $61.23 {\pm} 0.65$ | $64.85{\pm}24.40$ |
| Cancer | $23.54{\pm}0.40$ | $13.55 {\pm} 0.40$ | $16661.04{\pm}3284.75$ | $57.64 {\pm} 0.68$ | $47.79 {\pm} 0.68$ | $70.19{\pm}21.44$ |
| Child | $46.36 {\pm} 0.71$ | $37.45{\pm}0.71$ | $24357.04{\pm}2921.17$ | $74.08 {\pm} 1.09$ | $66.94{\pm}1.09$ | $386.68{\pm}537.49$ |
| Earthquake | $23.57 {\pm} 0.33$ | $13.81{\pm}0.33$ | $16139.89{\pm}1984.97$ | $57.73 {\pm} 0.91$ | $47.67 {\pm} 0.91$ | $51.94{\pm}7.48$ |
| Hailfinder | $35.14{\pm}0.27$ | $25.14 {\pm} 0.27$ | $29948.92{\pm}1397.61$ | $49.27 {\pm} 22.43$ | $44.63 {\pm} 22.43$ | $2446.96 {\pm} 3079.47$ |
| Healthcare | $45.64{\pm}0.71$ | $41.09{\pm}0.71$ | $14277.13{\pm}1081.79$ | $76.06 {\pm} 1.19$ | $69.37 {\pm} 1.19$ | $289.80{\pm}619.64$ |
| Mildew | $31.14 {\pm} 1.01$ | $17.43{\pm}1.01$ | 31279.77 ± 2137.75 | $27.47{\pm}14.73$ | $23.01{\pm}14.73$ | $3632.29 {\pm} 3243.75$ |
| Pigs | $0.00 {\pm} 0.00$ | $0.00{\pm}0.00$ | $86400.00 {\pm} 0.00$ | $6.46 {\pm} 1.90$ | $5.38{\pm}1.90$ | $9822.01 {\pm} 1595.96$ |
| Survey | $33.37 {\pm} 0.66$ | $28.68 {\pm} 0.66$ | $10799.27{\pm}1011.99$ | $66.26{\pm}0.93$ | $61.16{\pm}0.93$ | $105.03{\pm}157.52$ |

4.3 Results and Discussion

In this part, we assess the performance of our divide-and-conquer strategy in comparison to its base algorithm, PC-Stable. To ensure robustness and reliability of our experimental results [15], 10 unique problem instances for each base network were generated using varied random seeds. The outcomes are reported as "mean value \pm standard deviation". For each comparative experimental set, a Wilcoxon signed-rank test at a 99% confidence level was conducted to evaluate the presence of significant differences in the results. The experimental results are presented in Table 2. The F1 score is marked as zero if the algorithm fails to vield a reasonable result within one day. Metrics highlighted in **bold** underscore instances where our strategy demonstrates a significantly superior performance compared to the base algorithms, marked by higher mean values and concurrent success in significance tests. As indicated by the results in Table 2, our divide-and-conquer strategy generally exhibits remarkable effectiveness. It consistently surpasses the base algorithm PC-Stable across most metrics. Notably, in the one instance where our method's F1 adjacent score does not significantly outperform the baselines, the discrepancy remains minimal, while the runtime is notably shorter. Moreover, our proposed approach on average improves two accuracy metrics by 74.45% and 110.94%, respectively, while reducing runtime by an average of 93.65%. Hence, under this experimental conditions, our divideand-conquer strategy has demonstrated its efficacy in the structure learning of 2-TBN. It is worth mentioning that in the E-step of the divide-and-conquer strategy, any existing algorithm can be used to solve the sub-problem, making the method highly portable. We also conducted experiments based on other base algorithms and finally obtained similar experimental results.

5 Conclusion

In this paper, we address the challenge of large-scale Dynamic Bayesian Network (DBN) structure learning by implementing a divide-and-conquer strategy, originally developed for static Bayesian Network (BN) structure learning. Our approach enhances the existing Partition-Estimation-Fusion (PEF) strategy by fully leveraging the prior knowledge of 2-Time-sliced Bayesian Networks (2-TBN), a specific class of DBNs, to improve the learning of the transition model structure in 2-TBNs. Our experimental findings confirm the effectiveness of our approach. Looking ahead, future research will explore the extension of the divide-and-conquer strategy to various types of DBNs.

References

- Ajmal, H.B., Madden, M.G.: Dynamic bayesian network learning to infer sparse models from time series gene expression data. IEEE/ACM Transactions on Computational Biology and Bioinformatics 19(5), 2794–2805 (2021)
- Akaike, H.: A new look at the statistical model identification. IEEE Transactions on Automatic Control 19(6), 716–723 (1974)
- Bernaola, N., Michiels, M., Larranaga, P., Bielza, C.: Learning massive interpretable gene regulatory networks of the human brain by merging bayesian networks. bioRxiv pp. 2020–02 (2020)
- 4. Bouckaert, R.R.: Bayesian Belief Networks: From Construction to Inference. Ph.D. thesis, Utrecht University (1995)
- Chickering, D.M.: Learning equivalence classes of bayesian-network structures. Journal of Machine Learning Research 2, 445–498 (2002)
- Chickering, M., Heckerman, D., Meek, C.: Large-sample learning of bayesian networks is np-hard. Journal of Machine Learning Research 5, 1287–1330 (2004)
- Colombo, D., Maathuis, M.H., et al.: Order-independent constraint-based causal structure learning. Journal of Machine Learning Research 15(1), 3741–3782 (2014)
- Cooper, G.F., Herskovits, E.: A bayesian method for the induction of probabilistic networks from data. Machine learning 9, 309–347 (1992)
- Friedman, N., Murphy, K., Russell, S.: Learning the structure of dynamic probabilistic networks. In: Proceedings of the Fourteenth Conference on Uncertainty in Artificial Intelligence. pp. 139–147 (1998)
- Gao, S., Xiao, Q., Pan, Q., Li, Q.: Learning dynamic bayesian networks structure based on bayesian optimization algorithm. In: International Symposium on Neural Networks. pp. 424–431. Springer (2007)
- Gu, J., Zhou, Q.: Learning big gaussian bayesian networks: Partition, estimation and fusion. The Journal of Machine Learning Research 21(1), 6340–6370 (2020)
- Kitson, N.K., Constantinou, A.C., Guo, Z., Liu, Y., Chobtham, K.: A survey of bayesian network structure learning. Artificial Intelligence Review pp. 1–94 (2023)
- Larranaga, P., Kuijpers, C.M., Murga, R.H., Yurramendi, Y.: Learning bayesian network structures by searching for the best ordering with genetic algorithms. IEEE Transactions on Systems, Man, and Cybernetics 26(4), 487–493 (1996)
- 14. Lin, J., Li, Z., Li, Z., Bai, L., Zhao, R., Zhang, C.: Dynamic causal graph convolutional network for traffic prediction. arXiv preprint arXiv:2306.07019 (2023)

- Liu, S., Tang, K., Lei, Y., Yao, X.: On performance estimation in automatic algorithm configuration. In: Proceedings of the 34th AAAI Conference on Artificial Intelligence, AAAI'2020. pp. 2384–2391. New York, NY (Feb 2020)
- Liu, S., Tang, K., Yao, X.: Automatic construction of parallel portfolios via explicit instance grouping. In: Proceedings of the 33rd AAAI Conference on Artificial Intelligence, AAAI'2019. pp. 1560–1567. Honolulu, HI (Jan 2019)
- Liu, S., Tang, K., Yao, X.: Generative adversarial construction of parallel portfolios. IEEE Transactions on Cybernetics 52(2), 784–795 (2022)
- Lou, Y., Dong, Y., Ao, H.: Structure learning algorithm of dbn based on particle swarm optimization. In: 2015 14th International Symposium on Distributed Computing and Applications for Business Engineering and Science (DCABES). pp. 102–105. IEEE (2015)
- Lu, N., Liu, S., He, R., Wang, Q., Tang, K.: Large language models can be guided to evade ai-generated text detection. CoRR abs/2305.10847 (2023). https:// doi.org/10.48550/ARXIV.2305.10847
- Lu, N., Liu, S., Zhang, Z., Wang, Q., Liu, H., Tang, K.: Less is more: Understanding word-level textual adversarial attack via n-gram frequency descend. CoRR abs/2302.02568 (2023). https://doi.org/10.48550/ARXIV.2302.02568
- Murphy, K.P.: Dynamic Bayesian Networks: Representation, Inference and Learning. University of California, Berkeley (2002)
- 22. OpenAI: Gpt-4 technical report (2023)
- Pearl, J.: Bayesian networks: a model of self-activated memory for evidential reasoning. In: Proceedings of the 7th Conference of the Cognitive Science Society, 1985. pp. 329–334 (1985)
- Ramsey, J., Glymour, M., Sanchez-Romero, R., Glymour, C.: A million variables and more: The fast greedy equivalence search algorithm for learning high-dimensional graphical causal models, with an application to functional magnetic resonance images. International Journal of Data Science and Analytics 3, 121–129 (2017)
- Ramsey, J.D., Zhang, K., Glymour, M., Romero, R.S., Huang, B., Ebert-Uphoff, I., Samarasinghe, S., Barnes, E.A., Glymour, C.: Tetrad — a toolbox for causal discovery. In: 8th International Workshop on Climate Informatics. p. 29 (2018)
- Rodionov, V.I.: On the number of labeled acyclic digraphs. Discrete Mathematics 105(1-3), 319–321 (1992)
- Romero, D., Jané, R.: Dynamic bayesian model for detecting obstructive respiratory events by using an experimental model. Sensors 23(7), 3371 (2023)
- 28. Schwarz, G.: Estimating the dimension of a model. The Annals of Statistics pp. $461{-}464~(1978)$
- 29. Scutari, M.: Learning bayesian networks with the bnlearn r package. Journal of Statistical Software **35**, 1–22 (2010)
- Spirtes, P., Glymour, C.N., Scheines, R.: Causation, Prediction, and Search. MIT Press (2000)
- Tang, K., Liu, S., Yang, P., Yao, X.: Few-shots parallel algorithm portfolio construction via co-evolution. IEEE Transactions on Evolutionary Computation 25(3), 595–607 (2021)
- 32. Trabelsi, G., Leray, P., Ayed, M.B., Alimi, A.M.: Benchmarking dynamic bayesian network structure learning algorithms. In: 2013 5th International Conference on Modeling, Simulation and Applied Optimization (ICMSAO). pp. 1–6. IEEE (2013)
- 33. Trabelsi, G., Leray, P., Ben Ayed, M., Alimi, A.M.: Dynamic mmhc: A local search algorithm for dynamic bayesian network structure learning. In: Advances in Intel-

ligent Data Analysis XII: 12th International Symposium, IDA 2013, London, UK, October 17-19, 2013. Proceedings 12. pp. 392–403. Springer (2013)

- 34. Tsamardinos, I., Aliferis, C.F., Statnikov, A.: Time and sample efficient discovery of markov blankets and direct causal relations. In: Proceedings of the 9th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. pp. 673–678 (2003)
- Tsamardinos, I., Brown, L.E., Aliferis, C.F.: The max-min hill-climbing bayesian network structure learning algorithm. Machine Learning 65, 31–78 (2006)
- Wang, H., Yu, K., Yao, H.: Learning dynamic bayesian networks using evolutionary mcmc. In: 2006 International Conference on Computational Intelligence and Security. vol. 1, pp. 45–50. IEEE (2006)
- Zhang, Y., Tiňo, P., Leonardis, A., Tang, K.: A survey on neural network interpretability. IEEE Transactions on Emerging Topics in Computational Intelligence 5(5), 726–742 (2021)
- Zheng, X., Aragam, B., Ravikumar, P.K., Xing, E.P.: Dags with no tears: Continuous optimization for structure learning. Advances in Neural Information Processing Systems 31 (2018)
- Zhu, R., Pfadler, A., Wu, Z., Han, Y., Yang, X., Ye, F., Qian, Z., Zhou, J., Cui, B.: Efficient and scalable structure learning for bayesian networks: Algorithms and applications. In: 2021 IEEE 37th International Conference on Data Engineering (ICDE). pp. 2613–2624. IEEE (2021)