# Expressivity and Approximation Properties of Deep Neural Networks with $\operatorname{ReLU}^k$ Activation

Juncai He<sup>\*</sup> Tong Mao<sup>\*</sup> Jinchao Xu<sup>\*†</sup>

### Abstract

In this paper, we investigate the expressivity and approximation properties of deep neural networks employing the ReLU<sup>k</sup> activation function for  $k \geq 2$ . Although deep ReLU networks can approximate polynomials effectively, deep ReLU<sup>k</sup> networks have the capability to represent higher-degree polynomials precisely. Our initial contribution is a comprehensive constructive proof for polynomial representation using deep ReLU<sup>k</sup> networks. This allows us to establish an upper bound on both the size and count of network parameters. Consequently, we are able to demonstrate a suboptimal approximation rate for functions from Sobolev spaces as well as for analytic functions. Additionally, through an exploration of the representation power of deep ReLU<sup>k</sup> networks for shallow networks, we reveal that deep ReLU<sup>k</sup> networks can approximate functions from a range of variation spaces, extending beyond those generated solely by the ReLU<sup>k</sup> activation function. This finding demonstrates the adaptability of deep ReLU<sup>k</sup> networks in approximating functions within various variation spaces.

## **1** Introduction

Over the past decade, neural networks have achieved remarkable success in a variety of fields, including image recognition [30, 29, 23, 21], speech recognition [40, 24, 45], and natural language processing [8, 3, 26, 53], among others. These achievements have sparked increased interest in the theoretical understanding of neural networks. Theoretically, the generalization error of a neural network can be decomposed into the sum of the approximation error and the sampling error, as detailed in works such as [9]. In practice, the reduction of approximation error depends on carefully designed neural network architectures, whereas the control of sample error requires sufficient and reliable data resources. For instance, the approximation capabilities of neural networks with sigmoid activation functions were explored in various works [10, 25, 2, 39]. Additionally, the universality of neural networks with non-polynomial activation functions was established in [31, 5, 38]. In recent years, due to their simple computational form and the potential to overcome the gradient vanishing problem, neural networks employing the Rectified Linear Unit (ReLU, defined as ReLU(x) = max{0, x}) and ReLU<sup>k</sup> = (ReLU)<sup>k</sup> activation functions have gained widespread use. This paper focuses on the expressivity and approximation properties of neural networks with ReLU<sup>k</sup> activation functions.

<sup>\*</sup>Computer, Electrical and Mathematical Science and Engineering Division, King Abdullah University of Science and Technology, Thuwal 23955, Saudi Arabia.

<sup>&</sup>lt;sup>†</sup>Department of Mathematics, The Pennsylvania State University, University Park, PA 16802, USA.

Given the fact that any ReLU networks are continuous piecewise linear (CPwL) functions, [1] initially demonstrated that any CPwL functions on  $[0, 1]^d$  can be represented by deep ReLU networks with  $\lceil \log_2(d+1) \rceil$  hidden layers. Subsequently, [20] established that shallow ReLU networks cannot represent any piecewise linear function on  $[0, 1]^d$  with  $d \ge 2$ . In contrast, deep ReLU networks with more layers (but fewer parameters) can recover any linear finite element functions. Recently, [17] explored the optimal representation expressivity for continuous piecewise linear functions using deep ReLU networks on [0, 1]. By integrating this expressivity with the Kolmogorov Superposition Theorem [28], a significantly improved approximation rate was achieved. Most recently, through a detailed examination of the basis functions and high-dimensional simplicial mesh characteristics of Lagrange finite element functions, which are a special type of piecewise polynomial functions, the authors in [22] demonstrated that Lagrange finite element functions of any order in arbitrary dimensions can be represented by DNNs with ReLU or ReLU<sup>2</sup> activation functions.

On the other hand, the approximation theory of shallow and deep neural networks with ReLU and ReLU<sup>k</sup> activation functions has been studied from various aspects. For functions from the Barron space, it has been proved in [27] that shallow ReLU networks uniformly with the rate  $\mathcal{O}\left(N^{-\frac{1}{2}-\frac{1}{d}}\right)$  with  $\mathcal{O}(N)$  parameters. This result has been generalized to  $L^p$ -approximation, spectral Barron spaces, and ReLU<sup>k</sup> activation functions in [49, 50, 51, 34]. In particular, a optimal rate  $\tilde{\mathcal{O}}(N^{-\frac{1}{2}-\frac{2k+1}{2d}})$  for functions from the so-called spectral Barron spaces, where  $\tilde{\mathcal{O}}$  indicates up to a constant power of log N. Furthermore, for  $\alpha$ -Hölder functions, [37] proved the approximation rate  $\tilde{\mathcal{O}}\left(N^{-\frac{\alpha}{d}\frac{d+2}{d+4}}\right)$  by shallow ReLU networks. This result is generalized to shallow ReLU<sup>k</sup> networks for  $k = 0, 1, 2, \ldots$  in [56]. In particular, for k = 0, 1, the rate is improved to the optimal rate  $\mathcal{O}\left(N^{-\frac{\alpha}{d}}\right)$ . Compared to shallow neural networks, deep network architectures have significant advantages as demonstrated in [6, 11, 44, 14]. Specifically, by using a bit-extraction technique, it has been proved that fully-connected deep ReLU networks with depth L and width N attain the optimal approximation rate  $\tilde{\mathcal{O}}\left(N^{2}L^{2}\right)$  [46, 47, 48].

For functions with specific compositional structures, deep ReLU networks can achieve significantly better expressivity power or approximation accuracy than their shallow ReLU counterparts [43, 52, 36]. In particular, it has been shown that any function constructed by a shallow ReLU neural network can be represented by a deep ReLU neural network with width d + 4 [33] or a deep convolutional neural network whenever the filter size  $\geq 2$  [58, 18]. In addition, it was demonstrated in [54] that sawtooth functions on [0, 1] with  $2^N$  oscillations can be represented by a deep ReLU network with  $\mathcal{O}(N)$  parameters. In contrast, a shallow ReLU network would require  $\mathcal{O}(2^N)$  parameters to construct such a function. Subsequent studies in [33, 57] showed that multivariate polynomials could be approximated by deep ReLU networks exponentially, achieving an approximation rate of  $\tilde{\mathcal{O}}(N^{-\frac{\alpha}{d}})$  for functions from  $C^{\alpha}(\mathbb{B}^d)$ . Later, a further study of approximating holomorphic functions by deep ReLU networks has been introduced in [42]. Additionally, [41] demonstrated that the sparse grid basis can be exponentially approximated by deep ReLU networks, leading to a suboptimal approximation rate of  $\tilde{\mathcal{O}}(N^{-2})$  for functions from Korobov spaces. However, a foundational aspect of these results is a special expressivity property of deep ReLU networks. A more in-depth and systematic analysis of this result, from the hierarchical basis perspective, is presented in [19].

Given these findings, it is reasonable to anticipate that deep  $\text{ReLU}^k$  networks might also offer superior representation and approximation properties compared to their shallow counterparts and deep ReLU networks. However, the expressivity and approximation properties of neural networks exclusively using the ReLU<sup>k</sup> activation function are not extensively documented in the literature. For example, it has been noted in studies such as [4] and [55] that  $\text{ReLU}^k$  networks can represent any global polynomial, with existence proofs provided to support this claim. Furthermore, the authors in [32] constructed a deep ReLU<sup>2</sup> network with  $\mathcal{O}(n^d)$  neurons, demonstrating its capability to represent all polynomials of degree  $\leq n$  on  $\mathbb{R}^d$ . In this paper, we generalize this to all ReLU<sup>k</sup> networks, providing a constructive proof for polynomial representation and estimating the upper bound of parameter size and count. Specifically, we show that shallow ReLU<sup>k</sup> networks with  $\mathcal{O}(k^d)$  parameters can represent polynomials of degree at most k in  $\mathbb{R}^d$ , and that deep ReLU<sup>k</sup> networks of depth L with  $\mathcal{O}(k^{Ld})$  parameters can represent polynomials of degree  $\leq k^{\tilde{L}}$ . Moreover, deep ReLU<sup>k</sup> networks can approximate analytic functions and functions from Sobolev spaces with suboptimal rates. Additionally, we prove that deep ReLU<sup>k</sup> networks with depth L and width 2(k+1)n can represent functions constructed by any shallow ReLU<sup>k<sup>ℓ</sup></sup> networks of width n for any  $\ell \leq L$ . Together with recent results on variation spaces [51], we demonstrate an approximation error of  $\mathcal{O}(N^{-\frac{1}{2}-\frac{2k^\ell+1}{2d}})$  for functions from the variation space  $\mathcal{K}_1(\mathbb{P}^d_{k^\ell})$  for any  $\ell \leq L$ . This underscores the adaptability of deep ReLU<sup>k</sup> networks in approximating functions from variation spaces without precise knowledge of their regularity, providing new insights into the advantages of deep architectures with ReLU<sup>k</sup> activations.

The rest of this section will formally define our  $\operatorname{ReLU}^k$  network architectures, including bounds on parameter size and count. Section 2 presents the constructive proof for global polynomial representation by  $\operatorname{ReLU}^k$  networks and discusses their approximation properties for analytic functions and functions from Sobolev spaces. Section 3 explores the adaptive approximation properties of deep  $\operatorname{ReLU}^k$  networks for functions in variation spaces. Section 4 offers concluding remarks and reflections on our findings.

**Definition 1.** Let  $k \in \mathbb{N}$ , then we denote the univariate function  $\operatorname{ReLU}^k$  as

$$\sigma_k(x) = \begin{cases} x^k, & x \ge 0, \\ 0, & x < 0. \end{cases}$$
(1.1)

In particular, the ReLU function is the ReLU<sup>k</sup> function with k = 1.

For any vector  $v = (v_1, \ldots, v_n)$ , we abuse the notation and denote the vector mapping

$$\sigma_k(v) = (\sigma_k(v_1), \dots, \sigma_k(v_n)) \in \mathbb{R}^n.$$
(1.2)

**Definition 2** (ReLU<sup>k</sup> networks). Let  $d, k, n \in \mathbb{N}^+$ , B > 0,  $\mathbb{B}^d$  be the unit ball of  $\mathbb{R}^d$  centered at the origin. Denote  $\Sigma_n^k(B)$  be the class of shallow ReLU<sup>k</sup> network on  $\mathbb{B}^d$ 

$$\Sigma_n^k(B) = \left\{ x \mapsto c \cdot \sigma_k(Ax + b) : A \in \mathbb{R}^{n \times d}, \ b \in \mathbb{R}^n, \ c \in \mathbb{R}^n, \ \|A\|_{\max} \le B, \ \|b\|_{\infty} \le B \right\}.$$
(1.3)

where

$$||A||_{\max} := \max_{\substack{1 \le i \le n \\ 1 \le j \le d}} |(A)_{ij}|.$$

In addition, if we suppose further in (1.3) that  $||c||_{\infty} < M$  for some M > 0, we will denote the set as  $\Sigma_{n,M}^k(B)$ . This coincides with the notation in the previous works [49, 50, 51].

The class of fully-connected deep ReLU<sup>k</sup> networks with depth L and width  $\{n_i\}_{i=1}^L$  is defined inductively as

$$\Sigma_{n_{1:L}}^{k}(B) = \{ x \mapsto c \cdot h_{L}(x) : h_{i+1}(x) = \sigma_{k} \left( A_{i}h_{i}(x) + b_{i} \right), \ A_{i} \in \mathbb{R}^{n_{i} \times n_{i-1}}, \ b_{i} \in \mathbb{R}^{n_{i}}, \ c \in \mathbb{R}^{n_{L}}, \\ \|A_{i}\|_{\max} \leq B, \ \|b_{i}\|_{\infty} \leq B, i = 1, \dots, L \},$$
(1.4)

where  $n_0 = d$ ,  $h_0(x) = x$ .

Similarly, if we further require the weights in the output layers to be bounded as  $||c||_{\infty} \leq M$ , then we denote the class as  $\Sigma_{n_1 \dots M}^k(B)$ .

Before introducing our results, we specify that the number of parameters in the fully connected deep ReLU<sup>k</sup> network is  $n_L + \sum_{i=1}^{L} n_i(n_{i-1} + 1)$ . However, deep neural network structures are often considered to be sparse (e.g., [7, 41, 35, 15]), i.e., most of the parameters are fixed to be 0. Such a network is called a sparse deep network. The sparsity remarkably decreases the number of parameters and, thus, the computation cost. The deep  $\operatorname{ReLU}^k$  networks we constructed in this paper are sparse neural networks.

#### $\mathbf{2}$ **Representing Polynomials**

In this section, we construct the  $\text{ReLU}^k$  neural networks that represent polynomials. We will first show how shallow ReLU<sup>k</sup> networks represent polynomials of degree bounded by k, and extend the result to deep networks. As a consequence, we obtain suboptimal approximation rates for analytic functions and functions from Sobolev spaces.

The following lemma shows how monomials with the form  $x^{\alpha}$  of degree n are constructed by *n*-th powers of linear combinations of  $(x_1, \ldots, x_d)$  (see, e.g., [5, 38]). It has been known for many years that the homogeneous polynomial space of degree n is a span of such linear combinations. However, our following lemma construct it explicitly, which allows an estimation of the coefficients.

**Lemma 1.** Let  $n, d \in \mathbb{N}^+$ , and  $\alpha = (\alpha_1, \ldots, \alpha_d) \in \mathbb{N}^d$  with

$$\alpha_1 + \dots + \alpha_d = n_i$$

then the monomial  $x^{\alpha}$  can be written as a linear combination

$$x^{\alpha} = \sum_{n_2,\dots,n_d = -\left\lfloor \frac{n}{2} \right\rfloor}^{n - \left\lfloor \frac{n}{2} \right\rfloor} c_{n_2,\dots,n_d} \left( x_1 + n_2 x_2 + \dots + n_d x_d \right)^n$$
(2.1)

with each  $c_{n_2,...,n_d} \in \left[ -\left(\frac{n}{2}+1\right)^{2d}, \left(\frac{n}{2}+1\right)^{2d} \right].$ 

*Proof.* We prove this inductively on d. Clearly, this is true for d = 1. We assume the result is true for d-1, thus

$$x_1^{\alpha_1} \dots x_{d-1}^{\alpha_{d-1}} = \sum_{\substack{n_2, \dots, n_{d-1} = -\lfloor \frac{j}{2} \rfloor}}^{j-\lfloor \frac{j}{2} \rfloor} c_{n_2, \dots, n_{d-1}} \left( x_1 + n_2 x_2 + \dots + n_{d-1} x_{d-1} \right)^j,$$
(2.2)

where  $j = n - \alpha_d$  and  $c_{n_2,\dots,n_{d-1}} \in \left[-\left(\frac{n}{2}+1\right)^{2(d-1)}, \left(\frac{n}{2}+1\right)^{2(d-1)}\right]$ . Let  $\xi(x)$  be any function of x and consider  $(\xi(x) + n_d x_d)^n$  for  $n_d = -\left\lfloor\frac{n}{2}\right\rfloor,\dots,n-\left\lfloor\frac{n}{2}\right\rfloor$ , then

we can write

$$(\xi(x) + n_d x_d)^n = \sum_{i=0}^n \binom{n}{i} n_d^{n-i} \xi(x)^i x_d^{n-i}.$$

Consequently, for any  $b = (b_0, \ldots, b_n)^T \in \mathbb{R}^{n+1}$ , we have

$$\sum_{s=0}^{n} b_s \left[ \xi(x) + \left( s - \left\lfloor \frac{n}{2} \right\rfloor \right) x_d \right]^n = b^T B_n \lambda$$
(2.3)

where  $\lambda = \left(\xi(x)^n, x_d\xi(x)^{n-1}, \dots, x_d^{n-1}\xi(x), x_d^n\right)^\top$ , and

$$B_{n} = \begin{bmatrix} \binom{n}{0}1 & \binom{n}{1}\left(-\lfloor\frac{n}{2}\rfloor\right) & \dots & \binom{n}{n}\left(-\lfloor\frac{n}{2}\rfloor\right)^{n} \\ \binom{n}{0}1 & \binom{n}{1}\left(1-\lfloor\frac{n}{2}\rfloor\right) & \dots & \binom{n}{n}\left(1-\lfloor\frac{n}{2}\rfloor\right)^{n} \\ \vdots & \vdots & \ddots & \vdots \\ \binom{n}{0}1 & \binom{n}{1}\left(n-\lfloor\frac{n}{2}\rfloor\right) & \dots & \binom{n}{n}\left(n-\lfloor\frac{n}{2}\rfloor\right)^{n} \end{bmatrix}$$

$$= \begin{bmatrix} 1 & \left(-\lfloor\frac{n}{2}\rfloor\right) & \dots & \left(-\lfloor\frac{n}{2}\rfloor\right)^{n} \\ 1 & \left(1-\lfloor\frac{n}{2}\rfloor\right) & \dots & \left(1-\lfloor\frac{n}{2}\rfloor\right)^{n} \\ \vdots & \vdots & \ddots & \vdots \\ 1 & \left(n-\lfloor\frac{n}{2}\rfloor\right) & \dots & \left(n-\lfloor\frac{n}{2}\rfloor\right)^{n} \end{bmatrix} \begin{bmatrix} \binom{n}{0} & 0 & \dots & 0 \\ 0 & \binom{n}{1} & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \binom{n}{n} \end{bmatrix}.$$

$$(2.4)$$

Clearly,  $B_n$  is invertible. Let  $\hat{b} = e_{n-j+1}^T B_n^{-1}$  with

$$e_{n-j+1} = \left(\underbrace{0,\ldots,0}_{n-j}, 1, \underbrace{0,\ldots,0}_{j}\right)^T$$

and  $\xi(x) = x_1 + n_2 x_2 + \dots + n_{d-1} x_{d-1}$ , then we have

$$\sum_{s=0}^{n} \hat{b}_{s}^{T} \left[ x_{1} + n_{2}x_{2} + \dots + n_{d-1}x_{d-1} + \left( s - \left\lfloor \frac{n}{2} \right\rfloor \right) x_{d} \right]^{n} = \hat{b}^{T} B_{n} \lambda = e_{n-j+1} \lambda = \xi(x)^{j} x_{d}^{n-j}$$
$$= (x_{1} + n_{2}x_{2} + \dots + n_{d-1}x_{d-1})^{j} x_{d}^{\alpha_{d}}.$$

Substituting (2.2), we get

$$\sum_{\substack{n_2,\dots,n_{d-1}=-\lfloor\frac{j}{2}\rfloor\\n_2,\dots,n_{d-1}=-\lfloor\frac{j}{2}\rfloor}}^{j-\lfloor\frac{j}{2}\rfloor} c_{n_2,\dots,n_{d-1}} \sum_{s=0}^n \hat{b}_s \left[x_1+n_2x_2+\dots+n_{d-1}x_{d-1}+\left(s-\lfloor\frac{n}{2}\rfloor\right)x_d\right]^n$$
$$=\sum_{\substack{j-\lfloor\frac{j}{2}\rfloor\\n_2,\dots,n_{d-1}=-\lfloor\frac{j}{2}\rfloor\\=x_1^{\alpha_1}\dots x_{d-1}^{\alpha_{d-1}}x_d^{\alpha_d}}.$$

For  $n_2, \ldots, n_d \in \left\{ -\left\lfloor \frac{n}{2} \right\rfloor, \ldots, n - \left\lfloor \frac{n}{2} \right\rfloor \right\}$ , denote

$$c_{n_2,\dots,n_d} := \begin{cases} c_{n_2,\dots,n_{d-1}} \hat{b}_{n_d+\lfloor\frac{n}{2}\rfloor}, & n_2,\dots,n_{d-1} \in \left\{-\lfloor\frac{j}{2}\rfloor,\dots,j-\lfloor\frac{j}{2}\rfloor\right\}\\ 0, & \text{otherwise}, \end{cases}$$

then

$$\sum_{n_2,\dots,n_d=-\lfloor \frac{n}{2} \rfloor}^{n-\lfloor \frac{n}{2} \rfloor} c_{n_2,\dots,n_d} \left( x_1 + n_2 x_2 + \dots + n_d x_d \right)^n = x_1^{\alpha_1} \dots x_d^{\alpha_d}.$$

Finally, let us consider the bounds of  $c_{n_2,\ldots,n_d}$ . Here, we only need to estimate the bounds of  $\hat{b}_s$ . Since  $\hat{b} = e_{n-j+1}^T B_n^{-1}$ , for  $s = 0, \ldots, n$ , we have  $|b_s| \le ||B_n^{-1}||_{\max} = \max_{1 \le i,k \le n+1} |(B_n^{-1})_{ik}|$ .

We can bound  $||B_n^{-1}||_{\text{max}}$  by the norm of the inverse of the Vandermonde matrix in (2.4). Then by [16, Theorem 1], we have

$$||B_n^{-1}||_{\max} \leq \frac{\prod_{s=0}^n \left(1 + \left|s - \left\lfloor\frac{n}{2}\right\rfloor\right|\right)}{\min_{0 \leq i \leq n} \left\{\left(1 + \left|i - \left\lfloor\frac{n}{2}\right\rfloor\right|\right) \prod_{s \neq i} \left|s - i\right|\right\}} = \frac{\prod_{s=0}^n \left(1 + \left|s - \left\lfloor\frac{n}{2}\right\rfloor\right|\right)}{\left(1 + \left|0\right|\right) \prod_{s \neq \left\lfloor\frac{n}{2}\right\rfloor} \left|s - \left\lfloor\frac{n}{2}\right\rfloor\right|}$$

$$= \left(\prod_{m=1}^{n - \left\lfloor\frac{n}{2}\right\rfloor} \frac{1 + m}{m}\right) \times 1 \times \left(\prod_{m=1}^{\left\lfloor\frac{n}{2}\right\rfloor} \frac{1 + m}{m}\right) \leq \left(\frac{n}{2} + 1\right)^2.$$

$$(2.5)$$

Thus

$$|c_{n_2,\dots,n_d}| \le |b_s| |c_{n_2,\dots,n_{d-1}}| \le \left(\frac{n}{2} + 1\right)^2 \left(\frac{n}{2} + 1\right)^{2(d-1)} \le \left(\frac{n}{2} + 1\right)^{2d}$$

This completes the proof of Lemma 1.

By noticing that

$$t^k = \sigma_k(t) + (-1)^k \sigma_k(-t), \quad t \in \mathbb{R},$$

Lemma 1 enables the representation of the polynomials of degree  $\leq k$  by shallow ReLU<sup>k</sup> neural networks, which is also the key to showing the expressively of deep ReLU<sup>k</sup> neural networks.

**Remark 1.** In fact, the choice of  $n_2, \ldots, n_d$  in the proof of Lemma (1) is not the only choice. From (2.4), we can observe that our proof relies on writing  $B_n$  as a product Vandermonde matrix and a diagonal matrix. The attempt to lessen the bound (2.5) resulted in our choice of  $n_2, \ldots, n_d$ . However, we specify that our choice does not necessarily lead to the optimal upper bound M in the next lemma.

**Lemma 2.** Let  $d, k \in \mathbb{N}^+$ ,  $k \ge 2$ ,  $N = 2(k+1)^d$ , and B > 0, then any polynomial

$$P(x) = \sum_{\{\alpha \in \mathbb{N}^d: \|\alpha\|_1 \le k\}} a_{\alpha} x^{\alpha}, \ x \in \mathbb{B}^d$$

with degree  $\leq k$  can be represented by the shallow ReLU<sup>k</sup> network  $\Sigma_{N,M}^{k}(B)$ , where

$$M = B^{-k} \left(\frac{k}{2} + 1\right)^{2(d+1)+k} \left(\sum_{\{\alpha \in \mathbb{N}^d: \|\alpha\|_1 \le k\}} |a_{\alpha}|\right).$$

*Proof.* By applying Lemma 1 with  $d \leftarrow d + 1$  and  $n \leftarrow k$ , we conclude any monomial of degree k can be represented as

$$x_1^{\alpha_1} \dots x_d^{\alpha_d} x_{d+1}^{\alpha_{d+1}} = \sum_{n_2, \dots, n_d = -\left\lfloor \frac{k}{2} \right\rfloor}^{k - \left\lfloor \frac{k}{2} \right\rfloor} c_{n_2, \dots, n_{d+1}} \left( x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1} x_{d+1} \right)^k.$$

Replacing  $x_{d+1}$  by 1, then all monomials of degree  $\leq k$  on variables  $(x_1, \ldots, x_d)$  can be represented as

$$x_1^{\alpha_1} \dots x_d^{\alpha_d} = \sum_{n_2, \dots, n_d = -\lfloor \frac{k}{2} \rfloor}^{k - \lfloor \frac{k}{2} \rfloor} c_{n_2, \dots, n_d} \left( x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1} \right)^k$$
(2.6)

with  $c_{n_2,...,n_{d+1}} = c_{n_2,...,n_{d+1}}(\alpha) \in \left[-\left(\frac{k}{2}+1\right)^{2(d+1)}, \left(\frac{k}{2}+1\right)^{2(d+1)}\right]$ . Then any polynomial  $P(x) = \sum_{k=1}^{n} a_k x^{\alpha}$ 

$$P(x) = \sum_{\{\alpha \in \mathbb{N}^d : \|\alpha\|_1 \le k\}} a_{\alpha} x$$

can be written as

$$P(x) = \sum_{\{\alpha \in \mathbb{N}^d: \|\alpha\|_1 \le k\}} a_{\alpha} \sum_{n_2, \dots, n_{d+1} = -\lfloor \frac{k}{2} \rfloor}^{k - \lfloor \frac{k}{2} \rfloor} c_{n_2, \dots, n_{d+1}}(\alpha) \left(x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1}\right)^k$$
$$= \sum_{n_2, \dots, n_d = -\lfloor \frac{k}{2} \rfloor}^{k - \lfloor \frac{k}{2} \rfloor} \beta_{n_2, \dots, n_{d+1}} \left(x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1}\right)^k$$

where

$$\begin{split} \beta_{n_2,\dots,n_{d+1}} &= \sum_{\{\alpha \in \mathbb{N}^d : \|\alpha\|_1 \le k\}} a_\alpha c_{n_2,\dots,n_{d+1}}(\alpha) \le \sum_{\{\alpha \in \mathbb{N}^d : \|\alpha\|_1 \le k\}} |a_\alpha| \max_{\{\alpha \in \mathbb{N}^d : \|\alpha\|_1 \le k\}} |c_{n_2,\dots,n_{d+1}}(\alpha)| \\ &\le \left(\frac{k}{2} + 1\right)^{2(d+1)} \left(\sum_{\{\alpha \in \mathbb{N}^d : \|\alpha\|_1 \le k\}} |a_\alpha|\right). \end{split}$$

Thus, the polynomial P can be written as

$$P(x) = \sum_{n_2,\dots,n_d=-\lfloor \frac{k}{2} \rfloor}^{k-\lfloor \frac{k}{2} \rfloor} \beta_{n_2,\dots,n_{d+1}} \left[ \sigma_k \left( x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1} \right) + (-1)^k \sigma_k \left( -x_1 - n_2 x_2 - \dots - n_d x_d - n_{d+1} \right) \right]$$

By noticing the inequality  $\sigma_k(ay) = a^k \sigma_k(y)$  for all  $a > 0, y \in \mathbb{R}$ , we can write P as

$$P(x) = \sum_{n_2,\dots,n_d=-\lfloor\frac{k}{2}\rfloor}^{k-\lfloor\frac{k}{2}\rfloor} B^{-k} \left\lceil \frac{k}{2} \right\rceil^k \beta_{n_2,\dots,n_{d+1}} \left[ \sigma_k \left( B \left\lceil \frac{k}{2} \right\rceil^{-1} (x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1}) \right) + (-1)^k \sigma_k \left( -B \left\lceil \frac{k}{2} \right\rceil^{-1} (x_1 + n_2 x_2 + \dots + n_d x_d + n_{d+1}) \right) \right].$$

Clearly, the parameters satisfy

$$\left| B \left\lceil \frac{k}{2} \right\rceil^{-1} \right| \le B$$
 and  $\left| B \left\lceil \frac{k}{2} \right\rceil^{-1} n_j \right| \le B$ 

for all  $j = 2, \ldots, d+1$ , and

$$\left| B^{-k} \left\lceil \frac{k}{2} \right\rceil^k \beta_{n_2,\dots,n_{d+1}} \right| \le B^{-k} \left( \frac{k}{2} + 1 \right)^{2(d+1)+k} \left( \sum_{\{\alpha \in \mathbb{N}^d : \|\alpha\|_1 \le k\}} |a_\alpha| \right)$$

for all  $-\lfloor \frac{k}{2} \rfloor \le n_2, \ldots, n_d \le k - \lfloor \frac{k}{2} \rfloor$ . This proves Lemma 2.

Now, we are ready to prove our first main result, which reveals the way to construct polynomials by deep  $\text{ReLU}^k$  neural networks, as well as an estimation of the upper bound of the parameters.

**Theorem 1.** Let  $d, k, L \in \mathbb{N}^+$ , B > 0, and  $n_1 = \cdots = n_L = 2(k^L + 1)^d$ , then any polynomial

$$P(x) = \sum_{\{\alpha \in \mathbb{N}^d: \|\alpha\|_1 \le k^L\}} a_{\alpha} x^{\alpha}, \ x \in \mathbb{B}^d$$

with degree  $\leq k^L$  can be represented by a deep ReLU<sup>k</sup> network architecture  $\sum_{n_1 \in \mathcal{M}}^k(B)$  with

$$M = B^{-k\frac{k^{L}-1}{k-1}} \left(\frac{k^{L}}{2} + 1\right)^{2(d+1)+k^{L}} \left(\sum_{\{\alpha \in \mathbb{N}^{d}: \|\alpha\|_{1} \le k^{L}\}} |a_{\alpha}|\right).$$

Furthermore, there are  $2(2L+d)(k^L+1)^d$  nonzero parameters in the neural network architecture. Proof. By Lemma 2, P can be represented as

$$P(x) = \sum_{j=1}^{2(k^L+1)^d} c_j \sigma_{k^L}(w_j \cdot x + b_j), \qquad (2.7)$$

where  $w_j \in [-1, 1]^d$ ,  $b_j \in [-1, 1]$  and  $c_j \in [-M', M']$  for  $j = 1, ..., 2(k^L + 1)^d$ , where

$$M' = \left(\frac{k^L}{2} + 1\right)^{2(d+1)+k^L} \left(\sum_{\{\alpha \in \mathbb{N}^d: \|\alpha\|_1 \le k^L\}} |a_{\alpha}|\right).$$

Given  $h_0(x) = x$ , there exists a matrix  $A_1$  with  $2d(k^L + 1)^d$  parameters and bias term  $b = (b_1, \ldots, b_{2d(k^L+1)})$  such that

$$h_{1,j}(x) = \sigma_k(Bw_j \cdot x + Bb_j) = B^k \sigma_k(w_j \cdot x + b_j),$$

 $j = 1, \dots, 2(k^L + 1)^d.$ Given

$$h_i(x) = B^{k\frac{k^i-1}{k-1}} \left( \sigma_{k^i}(w_1 \cdot x + b_1), \dots, \sigma_{k^i} \left( w_{2(k^L+1)^d} \cdot x + b_{2(k^L+1)^d} \right) \right)^\top,$$

the identity matrix  $A_i = BI_{2(k^L+1)^d \times 2(k^L+1)^d}$  with  $2(k^L+1)^d$  parameters and bias term b = $(0, \ldots, 0)$  give

$$\begin{aligned} h_{i+1}(x) &= \sigma_k(A_i h_i(x)) = \sigma_k(B \times B^{k\frac{k^i-1}{k-1}} h_i(x)), \\ &= \left(\sigma_k \left(B^{\frac{k^{i+1}-1}{k-1}} \sigma_{k^i}(w_1 \cdot x + b_1)\right), \dots, \sigma_k \left(B^{\frac{k^{i+1}-1}{k-1}} \sigma_{k^i}\left(w_{2(k^L+1)^d} \cdot x + b_{2(k^L+1)^d}\right)\right)\right)^\top, \\ &= B^{k\frac{k^{i+1}-1}{k-1}} \left(\sigma_{k^{i+1}}(w_1 \cdot x + b_1), \dots, \sigma_{k^{i+1}}\left(w_{2(k^L+1)^d} \cdot x + b_{2(k^L+1)^d}\right)\right)^\top. \end{aligned}$$

Inductively, we have  $h_L(x) = B^{k\frac{k^L-1}{k-1}} \left( \sigma_{k^L}(w_1 \cdot x + b_1), \dots, \sigma_{k^L} \left( w_{2(k^L+1)^d} \cdot x + b_{2(k^L+1)^d} \right) \right)^{\top}$ . Thus, with  $\tilde{c} = B^{-k\frac{k^L-1}{k-1}}(c_1, \dots, c_{2(k^L+1)^d})$ , we have

$$\tilde{c} \cdot h_L(x) = \sum_{j=1}^{2(k^L+1)^d} c_j \sigma_{k^L}(w_j \cdot x + u_j) = P(x).$$

Here, we have

$$\|\tilde{c}\|_{\infty} \le B^{-k\frac{k^{L}-1}{k-1}}M' = M.$$

This implies  $P \in \Sigma_{n_{1:L}}^k(M)$  with  $n_1 = \cdots = n_L = 2(k^L + 1)^d$ . There are  $2d(k^L + 1)^d$  parameters in  $A_1$  and  $2(k^L + 1)^d$  parameters in  $A_2, \ldots, A_L$ . The number of parameters in bias terms is  $L \times 2(k^L + 1)^d$ , and  $2(k^L + 1)^d$  parameters in  $\tilde{c}$ .

**Remark 2.** As we mentioned before, the existence of such representation of the polynomials has been mentioned in previous literature such as [55, 4]. Those results rely on a generalized Vandermonde matrix theory for high-dimensional cases, while our proof in Lemma 1 reduces the problem into 1-dimension Vandermonde matrices. This improvement allows an estimation of the coefficients in the linear combination (2.1), and hence the parameters in the neural networks.

As a consequence of the classical polynomial approximation theory (e.g. [12, Chapter 7]), we can deduce the rate of approximation for analytic functions and for functions from Sobolev spaces.

**Definition 3** (Sobolev spaces). Let  $d \in \mathbb{N}^+$  and  $1 \leq p \leq \infty$ . For  $r \in \mathbb{N}$ , the Sobolev space  $W^{r,p}(\mathbb{B}^d)$ is defined as

$$W^{r,p}(\mathbb{B}^d) = \left\{ f \in L^p(\mathbb{B}^d) : \max_{\{\alpha \in \mathbb{N}^d, \|\alpha\|_1 = r\}} \|D^{\alpha}f\|_{L^p(\mathbb{B}^d)} < \infty \right\}$$
(2.8)

with the norm given by

$$\|f\|_{W^{r,p}(\mathbb{B}^d)}^p = \|f\|_{L^p(\mathbb{B}^d)}^p + \sum_{\{\alpha \in \mathbb{N}^d, \|\alpha\|_1 = r\}} \|D^{\alpha}f\|_{L^p(\mathbb{B}^d)}^p, \quad f \in W^{r,p}(\mathbb{B}^d).$$

For  $r \notin \mathbb{N}$ , let  $\theta = r - |r|$ . The Sobolev semi-norm is

$$|f|_{W^{r,p}}(\mathbb{B}^d) = \begin{cases} \max_{\substack{\{\alpha \in \mathbb{N}^d, \|\alpha\|_1 = r\}\\ \{\alpha \in \mathbb{N}^d, \|\alpha\|_1 = r\} \\ x, y \in \mathbb{B}^d, x \neq y}} \frac{|D^{\alpha}f(x) - D^{\alpha}f(y)|^p}{|x - y|^{d + \theta p}} dx dy \end{pmatrix}^{1/p}, & 1 \le p < \infty. \end{cases}$$

The space  $W^{r,p}(\mathbb{B}^d)$  is defined as

$$W^{r,p}(\mathbb{B}^d) = \left\{ f \in W^{\lfloor r \rfloor, p}(\mathbb{B}^d) : |f|_{W^{r,p}}(\mathbb{B}^d) < \infty \right\}$$
(2.9)

with the norm

$$||f||_{W^{r,p}(\mathbb{B}^d)} = ||f||_{W^{\lfloor r \rfloor,p}(\mathbb{B}^d)} + |f|_{W^{r,p}}(\mathbb{B}^d).$$

**Definition 4** (Analytic functions). Let  $d \in \mathbb{N}^+$ ,  $\rho \in (0,1)$ , f is said to be an analytic function on  $U_{\rho} := \{z \in \mathbb{C}^d : |z_j + \sqrt{z_j - 1}| < \rho^{-1}, j = 1, ..., d\}$  if it is complex differentiable at each  $z \in U_{\rho}$ .

Corollary 1. Let  $d, k, L \in \mathbb{N}^+$ , B > 0, and

$$n_1 = \dots = n_L = 2(k^L + 1)^d$$
.

There exists a sparse deep  $ReLU^k$  network  $\sum_{n=1}^k (B)$  with  $2(2L+d)(k^L+1)^d$  parameters such that

(a) if  $f \in W^{r,p}(\mathbb{B}^d)$  for some r > 0, then

$$\inf_{g \in \Sigma_{n_{1:L}}^k(B)} \|f - g\|_{L^p(\mathbb{B}^d)} \le \inf_{g \in \mathcal{P}_d^{k^L}} \|f - g\|_{L^p(\mathbb{B}^d)} \sim \|f\|_{W^{r,p}(\mathbb{B}^d)} k^{-Lr};$$
(2.10)

(b) if f is analytic on  $U_{\rho} := \{z \in \mathbb{C}^d : |z_j + \sqrt{z_j - 1}| < \rho^{-1}, j = 1, \dots, d\}$ , then for any  $\epsilon > 0$  with  $\rho + \epsilon < 1$ ,

$$\inf_{g \in \Sigma_{n_{1:L}}^k(B)} \|f - g\|_{L^p(\mathbb{B}^d)} \le \inf_{g \in \mathcal{P}_d^{k^L}} \|f - g\|_{L^p(\mathbb{B}^d)} \lesssim \left(\max_{w \in \partial \Gamma_{\rho+\epsilon}} \left| f\left(\frac{w + w^{-1}}{2}\right) \right| \right) k^{Ld} (\rho + \epsilon)^{k^L},$$
(2.11)

where  $\Gamma_{\rho+\epsilon} := \{ w \in \mathbb{C}^d : |w_j| \le (\rho+\epsilon)^{-1}, j=1,\ldots,d \}$ . The corresponding constant depends only on  $d, \rho$ , and  $\epsilon$ .

*Proof.* (a) The first inequality is exactly Theorem 1. The relation

$$\inf_{g \in \mathcal{P}_d^{k^L}} \|f - g\|_{L^p(\mathbb{B}^d)} \sim \|f\|_{W^{r,p}(\mathbb{B}^d)} k^{-Lr}$$

is the classical polynomial approximation theory (see, e.g., [12, Chapter 7]).

(b) Again, the first inequality is Theorem 1. For the second inequality, we apply the classical estimation for analytic functions (see, e.g., [12, Chapter 7] and [13, Lemma A.1] for the multivariate version) and conclude

$$\begin{split} \inf_{g \in \mathcal{P}_d^{kL}} \|f - g\|_{L^2(\mathbb{B}^d)}^2 &\leq \left(\max_{w \in \partial U_{\rho+\epsilon}} |f(w + w^{-1})|\right)^2 \sum_{n=k^L+1}^{\infty} \binom{n+d-1}{d-1} (\rho+\epsilon)^{2n} \\ &\leq C^2 \left(\max_{w \in \partial U_{\rho+\epsilon}} |f(w + w^{-1})|\right)^2 k^{2L} (\rho+\epsilon)^{2k^L}, \end{split}$$

where  $C = C(d, \rho, \epsilon)$  is independent of f and L.

## 3 Adaptive Approximation for Functions from Variation Spaces

In this section, we show the adaptive approximation properties of deep  $\text{ReLU}^k$  neural networks for functions in variation spaces. This result is obtained by studying the representation power of deep  $\text{ReLU}^k$  neural networks for shallow networks.

**Lemma 3.** Let  $d, k, L, n \in \mathbb{N}^+$ , M > 0, and  $n_1 = \cdots = n_L = 2(k+1)n$ . Then there exists a deep ReLU<sup>k</sup> neural network architecture  $\Sigma_{n_{1:L},M'}^k(B')$  with

$$N = [(4L - 2)(k + 1) + d]n$$

nonzero parameters, such that all functions  $f \in \Sigma_{n,M}^{K}(B)$  with  $K \in \{k^1, \ldots, k^L\}$  can be represented this neural network. Furthermore, the parameters in  $\Sigma_{n_1,\ldots,M'}^k(B')$  are bounded as

$$M' = \left(\frac{k}{2} + 1\right)^4 M, \quad B' = B \lor \left(\frac{k}{2} + 1\right)^4.$$

*Proof.* Let  $1 \leq \ell \leq L$ ,  $K = k^{\ell}$ , and  $f \in \Sigma_{n,M}^{K}(B)$ . Then

$$f_n(x) = \sum_{m=1}^n c_m \sigma_K(w_m \cdot x + u_m), \quad x \in \mathbb{B}^d,$$

where  $|c_m| \leq M$ ,  $|u_m| \leq B$ , and  $||w_m||_{\infty} \leq B$  holds for  $m = 1, \ldots, n$ .

Given  $h_0(x) = x$ , there exists a sparse matrix  $A_0 \in \mathbb{R}^{n_1 \times d}$  with  $(A_0)_{i,j} = 0$  for i > n and  $b_0 = (u_1, \ldots, u_n)^{\top}$  such that

$$h_{1,j}(x) = \begin{cases} \sigma_k \left( w_j \cdot x + u_j \right), & j \le n, \\ 0, & \text{otherwise.} \end{cases}$$
(3.1)

Clearly, all the parameters in  $A_0$  and  $b_0$  are bounded by B'.

Given

$$h_{i,j}(x) = \begin{cases} \sigma_{k^i}(w_j \cdot x + u_j), & j \le n, \\ 0, & \text{otherwise} \end{cases}$$

let  $A_i = B' I_{2(k+1)n \times 2(k+1)n}$ , and  $b_i = (0, \dots, 0)^{\top}$ ,

$$h_{i+1,j}(x) = \begin{cases} \sigma_{k^{i+1}}(w_j \cdot x + u_j), & j \le n, \\ 0, & \text{otherwise.} \end{cases}$$

So we get

$$h_{\ell,j}(x) = \begin{cases} \sigma_K(w_j \cdot x + u_j), & j \le n, \\ 0, & \text{otherwise} \end{cases}$$

By (2.6), the function  $y \mapsto y$  can be represented as a linear combination

$$y = \sum_{t=0}^{k} a_t \left( y + t - \left\lfloor \frac{k}{2} \right\rfloor \right)^k = \sum_{t=0}^{k} a_t \left[ \sigma_k \left( y + t - \left\lfloor \frac{k}{2} \right\rfloor \right) + (-1)^k \sigma_k \left( -y - t + \left\lfloor \frac{k}{2} \right\rfloor \right) \right]$$
(3.2)

with  $|a_t| \leq \left(\frac{k}{2} + 1\right)^4$ .

At the  $\ell\text{-th}$  layer, there exists a sparse matrix  $A_\ell \in \mathbb{R}^{n_{\ell+1} \times n_\ell}$  with

$$(A_{\ell})_{2(k+1)(m-1)+2t+1,m} = 1,$$
  
$$(A_{\ell})_{2(k+1)(m-1)+2t+2,m} = -1,$$

for m = 1, ..., n, t = 0, ..., k and proper bias term  $b_\ell$  with  $\|b_\ell\|_{\infty} \leq \frac{k}{2} + 1$  such that

$$h_{\ell+1,2(k+1)(m-1)+2t+1}(x) = \sigma_k \left( \sigma_L(w_m \cdot x + u_m) + t - \left\lfloor \frac{k}{2} \right\rfloor \right)$$
$$h_{\ell+1,2(k+1)(m-1)+2t+2}(x) = \sigma_k \left( -\sigma_L(w_m \cdot x + u_m) - t + \left\lfloor \frac{k}{2} \right\rfloor \right).$$

for m = 1, ..., n, t = 0, ..., k.

At the  $(\ell + 1)$ -th layer, there exists a sparse matrix  $A_{\ell+1} \in \mathbb{R}^{n_{\ell+2} \times n_{\ell+1}}$  with

$$(A_{\ell+1})_{m,2(k+1)(m-1)+2t+1} = a_t,$$
  
$$(A_{\ell+1})_{m,2(k+1)(m-1)+2t+2} = (-1)^k a_t$$

and  $b_{\ell+1} = (0, \ldots, 0)^{\top}$  such that

$$h_{\ell+2,j}(x) = \sum_{t=0}^{k} a_t \left[ \sigma_k \left( \sigma_L(w_j \cdot x + u_j) + t - \left\lfloor \frac{k}{2} \right\rfloor \right) + (-1)^k \sigma_k \left( -\sigma_L(w_j \cdot x + u_j) - t + \left\lfloor \frac{k}{2} \right\rfloor \right) \right]$$
  
=  $\sigma_L(w_j \cdot x + u_j), \quad j \le n,$   
 $h_{\ell+2,j}(x) = 0, \quad \text{otherwise.}$ 

We repeat these two steps up to the L-th layer, then the last hidden layer  $h_L(x)$  is given as either

$$h_{L,j}(x) = \sigma_K(w_j \cdot x + u_j), \quad j \le n,$$
  
 $h_{L,j}(x) = 0, \quad \text{otherwise}$ 

or

$$h_{L,2(k+1)(m-1)+2t+1}(x) = \sigma_k \left( \sigma_K(w_m \cdot x + u_m) + t \right)$$
  
$$h_{L,2(k+1)(m-1)+2t+2}(x) = \sigma_k \left( -\sigma_K(w_m \cdot x + u_m) - t \right).$$

for m = 1, ..., n, t = 0, ..., k.

In either case, by (3.2), there exists  $c \in \left[-\left(\frac{k}{2}+1\right)^4, \left(\frac{k}{2}+1\right)^4\right]^{2(k+1)m}$  such that

$$c \cdot h_L(x) = \sum_{m=1}^n c_m \sigma_K(w_m \cdot x + u_m) = f_n(x).$$

By the form of the matrices  $A_0, \ldots, A_{L-1}$ , the number of parameters is

$$dn + 2(k+1)n + \sum_{j=2}^{L} \left[ 2(k+1)n + 2(k+1)n \right] + 2(k+1)n = N.$$

This completes the proof of Lemma 3.

This lemma enables us to consider the rate of approximation for functions from the variation spaces generated by ReLU<sup>K</sup> activation functions with  $K = k, k^2, \ldots, k^L$ . The approximation theory of such spaces has been studied in [51, 34, 27], etc.

**Definition 5** (Variation space). Let  $K, d \in \mathbb{N}^+$ , denote the dictionary  $\mathbb{P}^d_K$  as

$$\mathbb{P}^d_K = \left\{ x \mapsto \sigma_K(\omega \cdot x + b) : \ \omega \in \mathbb{S}^{d-1}, \ b \in [-1, 1] \right\}.$$

Consider the closure of the convex, symmetric hull of  $\mathbb{P}^d_K$ 

$$\overline{\operatorname{Conv}(\mathbb{P}^d_K)} = \overline{\left\{\sum_{j=1}^n a_j h_j : n \in \mathbb{N}^+, \sum_{j=1}^n |a_j| \le 1, h_j \in \mathbb{P}^d_K\right\}},$$
(3.3)

we define the variation space with the dictionary  $\mathbb{P}^d_L$  as

$$\mathcal{K}_1(\mathbb{P}^d_K) := \left\{ f \in R \times \overline{\operatorname{Conv}(\mathbb{P}^d_K)} : R > 0 \right\}.$$
(3.4)

with the norm

$$\|f\|_{\mathcal{K}_1(\mathbb{P}^d_K)} = \inf\left\{R > 0: \ f \in R \times \overline{\operatorname{Conv}(\mathbb{P}^d_K)}\right\}.$$
(3.5)

We will compare the result with the rate of approximation of shallow  $\operatorname{ReLU}^k$  networks given in [51].

**Theorem 2** (Sigel and Xu, 2022). Let  $k, d \in \mathbb{N}^+$ , then

$$\sup_{f \in \mathcal{K}_1(\mathbb{P}^d_k)} \inf_{f_n \in \Sigma^k_n(2)} \|f - f_n\|_{L^2(\mathbb{B}^d)} \lesssim \|f\|_{\mathcal{K}_1(\mathbb{P}^d_k)} n^{-\frac{1}{2} - \frac{2k+1}{2d}}.$$
(3.6)

Combining this theorem with Lemma 3, we have the following theorem.

**Theorem 3.** Let  $k, n, L \in \mathbb{N}^+$ , and  $n_1 = \cdots = n_L = 2(k+1)n$ , then there exists a deep ReLU<sup>k</sup> network architecture  $\sum_{n_{1:L}}^k (B)$  with  $B = \left(\frac{k}{2} + 1\right)^4$  such that for any  $K = k^\ell$  with  $1 \le \ell \le L$ ,

$$\sup_{f \in \mathcal{K}_1(\mathbb{P}^d_K)} \inf_{f_n \in \Sigma^k_{n_{1:L}}(B)} \| f - f_n \|_{L^2(\mathbb{B}^d)} \le C \| f \|_{\mathcal{K}_1(\mathbb{P}^d_K)} n^{-\frac{1}{2} - \frac{2K+1}{2d}}$$

where N = [(4L-2)(k+1) + d]n, C is a constant independent of n.

**Remark 3.** The index K in the variation spaces defined can be correlated to the regularity of the functions in the spaces (cf. [51]). Suppose the target function has a large but unknown regularity, saying  $f \in \bigcap_{j=1}^{K} \mathcal{K}_1(\mathbb{P}_j^d)$ , then the approximation property of shallow ReLU<sup>k</sup> networks would be bad if the activation function is not chosen properly: If  $k \ll K$ , then the approximation rate that we can achieve is at most

$$\sup_{t \in \mathcal{K}_1(\mathbb{P}^d_k)} \inf_{f_n \in \Sigma^k_n} \|f - f_n\|_{L^2(\mathbb{B}^d)} \lesssim \|f\|_{\mathcal{K}_1(\mathbb{P}^d_k)} n^{-\frac{1}{2} - \frac{2k+1}{2d}}.$$

If k > K,  $\bigcap_{i=1}^{K} \mathcal{K}_1(\mathbb{P}_i^d) \not\subseteq \mathcal{K}_1(\mathbb{P}_k^d)$ , the approximation rate is unknown.

f

However, by taking the depth  $L \geq \lceil \log_k K \rceil$ , the deep ReLU<sup>k</sup> networks we constructed in this section can automatically approximate functions from  $\cap_{j=1}^K \mathcal{K}_1(\mathbb{P}_j^d)$  with this unknown K. The rate of approximation is at least

$$\sup_{f \in \mathcal{K}_1(\mathbb{P}^d_K)} \inf_{f_n \in \Sigma^k_{n_{1:L}}} \|f - f_n\|_{L^2(\mathbb{B}^d)} \le C \|f\|_{\mathcal{K}_1(\mathbb{P}^d_K)} n^{-\frac{1}{2} - \frac{2K+1}{2d}},$$

since  $k^{\lceil \log_k K \rceil} \ge K$ .

## 4 Conclusions

In conclusion, this paper has significantly advanced the understanding of  $\operatorname{ReLU}^k$  neural networks and their capabilities in function approximation and representation. Our constructive proofs have not only demonstrated the representational power of shallow  $\operatorname{ReLU}^k$  networks in polynomial approximation but also paved the way for constructing deep  $\operatorname{ReLU}^k$  networks with an explicit parameterization for any polynomial of degree less than  $k^L$ , scaling efficiently with network depth and dimensions. Furthermore, we established a connection between the coefficients of polynomials and the bounds of neural network parameters, thereby enabling precise estimations of network parameters that uphold the approximation integrity. The elucidation of deep  $\operatorname{ReLU}^k$  networks' ability to approximate functions from Sobolev spaces, albeit with a suboptimal rate, opens new avenues for exploring their application in complex functional spaces. Most notably, our construction that deep  $\operatorname{ReLU}^k$  networks can emulate the function representation of shallower networks with enhanced efficiency underscores the hierarchical strength of depth in neural architectures. Coupled with recent findings on variation spaces, our results underscore the adaptivity and potential of deep  $\operatorname{ReLU}^k$ networks to achieve significant approximation accuracy, contributing to the theoretical foundations that may stimulate further breakthroughs in the application of deep learning across varied domains.

## References

- [1] R. Arora, A. Basu, P. Mianjy, and A. Mukherjee. Understanding deep neural networks with rectified linear units. In *International Conference on Learning Representations*, 2018.
- [2] A. R. Barron. Universal approximation bounds for superpositions of a sigmoidal function. IEEE Transactions on Information theory, 39(3):930–945, 1993.
- [3] A. Bordes, S. Chopra, and J. Weston. Question answering with subgraph embeddings. arXiv preprint arXiv:1406.3676, 2014.
- [4] Q. Chen, W. Hao, and J. He. Power series expansion neural network. *Journal of Computational Science*, 59:101552, 2022.
- [5] C. K. Chui and X. Li. Approximation by ridge functions and neural networks with one hidden layer. Journal of Approximation Theory, 70(2):131–141, 1992.
- [6] C. K. Chui, X. Li, and H. N. Mhaskar. Limitations of the approximation capabilities of neural networks with one hidden layer. Advances in Computational Mathematics, 5:233–243, 1996.

- [7] C. K. Chui, S.-B. Lin, and D.-X. Zhou. Deep neural networks for rotation-invariance approximation and learning. Analysis and Applications, 17(05):737–772, 2019.
- [8] R. Collobert, J. Weston, L. Bottou, M. Karlen, K. Kavukcuoglu, and P. Kuksa. Natural language processing (almost) from scratch. *Journal of machine learning research*, 12(ARTICLE):2493–2537, 2011.
- [9] F. Cucker and D. X. Zhou. Learning theory: an approximation theory viewpoint, volume 24. Cambridge University Press, 2007.
- [10] G. Cybenko. Approximation by superpositions of a sigmoidal function. Mathematics of control, signals and systems, 2(4):303–314, 1989.
- [11] O. Delalleau and Y. Bengio. Shallow vs. deep sum-product networks. Advances in neural information processing systems, 24, 2011.
- [12] R. A. DeVore and G. G. Lorentz. Constructive approximation, volume 303. Springer Science & Business Media, 1993.
- [13] K. Doctor, T. Mao, and H. Mhaskar. Encoding of data sets and algorithms. arXiv preprint arXiv:2303.00984, 2023.
- [14] R. Eldan and O. Shamir. The power of depth for feedforward neural networks. In Conference on learning theory, pages 907–940. PMLR, 2016.
- [15] Z. Fang, H. Feng, S. Huang, and D.-X. Zhou. Theory of deep convolutional neural networks ii: Spherical analysis. *Neural Networks*, 131:154–162, 2020.
- [16] W. Gautschi. On inverses of vandermonde and confluent vandermonde matrices iii. Numerische Mathematik, 29:445–450, 1978.
- [17] J. He. On the optimal expressive power of relu dnns and its application in approximation with kolmogorov superposition theorem. arXiv preprint arXiv:2308.05509, 2023.
- [18] J. He, L. Li, and J. Xu. Approximation properties of deep relu cnns. Research in the mathematical sciences, 9(3):38, 2022.
- [19] J. He, L. Li, and J. Xu. Relu deep neural networks from the hierarchical basis perspective. Computers & Mathematics with Applications, 120:105–114, 2022.
- [20] J. He, L. Li, J. Xu, and C. Zheng. Relu deep neural networks and linear finite elements. Journal of Computational Mathematics, 38(3):502–527, 2020.
- [21] J. He and J. Xu. Mgnet: A unified framework of multigrid and convolutional neural network. Science china mathematics, 62:1331–1354, 2019.
- [22] J. He and J. Xu. Deep neural networks and finite elements of any order on arbitrary dimensions. arXiv preprint arXiv:2312.14276, 2023.
- [23] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pages 770– 778, 2016.

- [24] G. Hinton, L. Deng, D. Yu, G. E. Dahl, A.-r. Mohamed, N. Jaitly, A. Senior, V. Vanhoucke, P. Nguyen, T. N. Sainath, et al. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal processing magazine*, 29(6):82–97, 2012.
- [25] K. Hornik, M. Stinchcombe, and H. White. Multilayer feedforward networks are universal approximators. *Neural networks*, 2(5):359–366, 1989.
- [26] S. Jean, K. Cho, R. Memisevic, and Y. Bengio. On using very large target vocabulary for neural machine translation. arXiv preprint arXiv:1412.2007, 2014.
- [27] J. M. Klusowski and A. R. Barron. Approximation by combinations of ReLU and squared ReLU ridge functions with  $\ell^1$  and  $\ell^0$  controls. *IEEE Transactions on Information Theory*, 64(12):7649–7656, 2018.
- [28] A. N. Kolmogorov. On the representation of continuous functions of many variables by superposition of continuous functions of one variable and addition. In *Doklady Akademii Nauk*, volume 114, pages 953–956. Russian Academy of Sciences, 1957.
- [29] A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. Advances in neural information processing systems, 25, 2012.
- [30] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.
- [31] M. Leshno, V. Y. Lin, A. Pinkus, and S. Schocken. Multilayer feedforward networks with a nonpolynomial activation function can approximate any function. *Neural networks*, 6(6):861– 867, 1993.
- [32] B. Li, S. Tang, and H. Yu. Better approximations of high dimensional smooth functions by deep neural networks with rectified power units. *Communications in Computational Physics*, 27(2):379–411, 2019.
- [33] Z. Lu, H. Pu, F. Wang, Z. Hu, and L. Wang. The expressive power of neural networks: A view from the width. *Advances in neural information processing systems*, 30, 2017.
- [34] L. Ma, J. W. Siegel, and J. Xu. Uniform approximation rates and metric entropy of shallow neural networks. *Research in the Mathematical Sciences*, 9(3):46, 2022.
- [35] T. Mao, Z. Shi, and D.-X. Zhou. Theory of deep convolutional neural networks iii: Approximating radial functions. *Neural Networks*, 144:778–790, 2021.
- [36] T. Mao, Z. Shi, and D.-X. Zhou. Approximating functions with multi-features by deep convolutional neural networks. Analysis and Applications, 21(01):93–125, 2023.
- [37] T. Mao and D.-X. Zhou. Rates of approximation by ReLU shallow neural networks. *Journal of Complexity*, 79:101784, 2023.
- [38] H. N. Mhaskar. Approximation properties of a multilayered feedforward artificial neural network. Advances in Computational Mathematics, 1:61–80, 1993.

- [39] H. N. Mhaskar and C. A. Micchelli. Degree of approximation by neural and translation networks with a single hidden layer. Advances in applied mathematics, 16(2):151–183, 1995.
- [40] T. Mikolov, A. Deoras, D. Povey, L. Burget, and J. Černocký. Strategies for training large scale neural network language models. In 2011 IEEE Workshop on Automatic Speech Recognition & Understanding, pages 196–201. IEEE, 2011.
- [41] H. Montanelli and Q. Du. New error bounds for deep ReLU networks using sparse grids. SIAM Journal on Mathematics of Data Science, 1(1):78–92, 2019.
- [42] J. A. Opschoor, C. Schwab, and J. Zech. Exponential relu dnn expression of holomorphic maps in high dimension. *Constructive Approximation*, 55(1):537–582, 2022.
- [43] T. Poggio, H. Mhaskar, L. Rosasco, B. Miranda, and Q. Liao. Why and when can deep-but not shallow-networks avoid the curse of dimensionality: a review. *International Journal of Automation and Computing*, 14(5):503–519, 2017.
- [44] I. Safran and O. Shamir. Depth separation in ReLU networks for approximating smooth non-linear functions. arXiv preprint arXiv:1610.09887, 14, 2016.
- [45] T. N. Sainath, B. Kingsbury, A.-r. Mohamed, G. E. Dahl, G. Saon, H. Soltau, T. Beran, A. Y. Aravkin, and B. Ramabhadran. Improvements to deep convolutional neural networks for lvcsr. In 2013 IEEE workshop on automatic speech recognition and understanding, pages 315–320. IEEE, 2013.
- [46] Z. Shen, H. Yang, and S. Zhang. Deep network approximation characterized by number of neurons. arXiv preprint arXiv:1906.05497, 2019.
- [47] Z. Shen, H. Yang, and S. Zhang. Optimal approximation rate of ReLU networks in terms of width and depth. Journal de Mathématiques Pures et Appliquées, 157:101–135, 2022.
- [48] J. W. Siegel. Optimal approximation rates for deep ReLU neural networks on sobolev spaces. arXiv preprint arXiv:2211.14400, 2022.
- [49] J. W. Siegel and J. Xu. Optimal approximation rates and metric entropy of ReLUk and cosine networks. arXiv preprint arXiv:2101.12365, 2021.
- [50] J. W. Siegel and J. Xu. High-order approximation rates for shallow neural networks with cosine and ReLUk activation functions. *Applied and Computational Harmonic Analysis*, 58:1– 26, 2022.
- [51] J. W. Siegel and J. Xu. Sharp bounds on the approximation rates, metric entropy, and n-widths of shallow neural networks. *Foundations of Computational Mathematics*, pages 1–57, 2022.
- [52] L. Song, J. Fan, D.-R. Chen, and D.-X. Zhou. Approximation of nonlinear functionals using deep ReLU networks. arXiv preprint arXiv:2304.04443, 2023.
- [53] I. Sutskever, O. Vinyals, and Q. V. Le. Sequence to sequence learning with neural networks. Advances in neural information processing systems, 27, 2014.
- [54] M. Telgarsky. Representation benefits of deep feedforward networks. arXiv preprint arXiv:1509.08101, 2015.

- [55] J. Xu. The finite neuron method and convergence analysis. arXiv preprint arXiv:2010.01458, 2020.
- [56] Y. Yang and D.-X. Zhou. Optimal rates of approximation by shallow ReLU<sup>k</sup> neural networks and applications to nonparametric regression. *arXiv preprint arXiv:2304.01561*, 2023.
- [57] D. Yarotsky. Error bounds for approximations with deep ReLU networks. Neural Networks, 94:103–114, 2017.
- [58] D.-X. Zhou. Universality of deep convolutional neural networks. *Applied and computational harmonic analysis*, 48(2):787–794, 2020.