L-AutoDA: Large Language Models for Automatically Evolving Decision-based Adversarial Attacks

Ping Guo

City University of Hong Kong Hong Kong, Hong Kong SAR CityU Shenzhen Research Institute Shenzhen, China pingguo5-c@my.cityu.edu.hk Fei Liu

City University of Hong Kong Hong Kong, Hong Kong SAR CityU Shenzhen Research Institute Shenzhen, China fliu36-c@my.cityu.edu.hk

Qingchuan Zhao City University of Hong Kong Hong Kong, Hong Kong SAR qizhao@cityu.edu.hk

ABSTRACT

In the rapidly evolving field of machine learning, adversarial attacks pose a significant threat to the robustness and security of models. Amongst these, decision-based attacks are particularly insidious due to their nature of requiring only the model's decision output, which makes them notably challenging to counteract. This paper presents L-AutoDA (Large Language Model-based Automated Decision-based Adversarial Attacks), an innovative methodology that harnesses the generative capabilities of large language models (LLMs) to streamline the creation of such attacks. L-AutoDA employs an evolutionary strategy, where iterative interactions with LLMs lead to the autonomous generation of potent attack algorithms, thereby reducing human intervention. The performance of L-AutoDA was evaluated on the CIFAR-10 dataset, where it demonstrated substantial superiority over existing baseline methods in terms of success rate and computational efficiency. Ultimately, our results highlight the formidable utility of language models in crafting adversarial attacks and reveal promising directions for constructing more resilient AI systems.

CCS CONCEPTS

Theory of computation → Design and analysis of algorithms;
Computing methodologies → Artificial intelligence.

KEYWORDS

Large Language Models, Adversarial Attacks, Automated Algorithm Design, Evolutionary Algorithms

GECCO '24 Companion, July 14-18, 2024, Melbourne, VIC, Australia

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 979-8-4007-0495-6/24/07...\$15.00 https://doi.org/10.1145/3638530.3664121 Xi Lin

City University of Hong Kong Hong Kong, Hong Kong SAR CityU Shenzhen Research Institute Shenzhen, China xi.lin@my.cityu.edu.hk

Qingfu Zhang City University of Hong Kong Hong Kong, Hong Kong SAR CityU Shenzhen Research Institute Shenzhen, China qingfu.zhang@cityu.edu.hk

ACM Reference Format:

Ping Guo, Fei Liu, Xi Lin, Qingchuan Zhao, and Qingfu Zhang. 2024. L-AutoDA: Large Language Models for Automatically Evolving Decision-based Adversarial Attacks. In *Genetic and Evolutionary Computation Conference (GECCO '24 Companion), July 14–18, 2024, Melbourne, VIC, Australia.* ACM, New York, NY, USA, 9 pages. https://doi.org/10.1145/3638530.3664121

1 INTRODUCTION

Deep neural network (DNN) models, despite their remarkable performance across a broad spectrum of domains, remain susceptible to *adversarial attacks* [16, 37], which involve imperceptibly altering the input data to induce incorrect model responses. Such vulnerabilities threaten the integrity and reliability of machine learning applications, particularly in safety-critical scenarios such as autonomous vehicle driving [3] and medical diagnostics [11]. Attackers can engineer *white-box attacks* using comprehensive knowledge of the DNN, or resort to *black-box attacks* when the model's details are concealed [33]. Of particular concern are *decision-based attacks* that necessitate only the model's output label information [21], posing a significant risk to real-world machine applications, such as commercial platforms that generally provide only the decision to users, thereby substantially endangering security and presenting challenges in implementing effective defenses [13, 19].

The escalating arms race in trustworthy artificial intelligence (AI) domain, characterized by the rapid advancement of attack methodologies and the concurrent evolution of defensive strategies [4, 30, 39], highlights the imperative for automating the generation and testing of adversarial attack algorithms [27]. This necessity is particularly acute in the realm of decision-based attacks, which demand extensive manual labor to develop and refine strategic methodologies. Current approaches to decision-based attacks are heavily reliant on handcrafted heuristics [2, 5, 7, 8, 12], posing significant impediments to enhancing their efficiency and efficacy.

The automation of adversarial attack algorithm design, underpinned by automatic program synthesis [18], entails the generation of programs within complex constraints. This area of research, known within the machine learning community as AutoML [14],

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Table 1: Comparison of strengths and weaknesses of differentalgorithm design approaches.

Method	Time	Expertise		Refinement	
		Domain	Extra		
Manual	1-2 Months	1	X	1	
Automatic Synthesis	1-2 Months	1	1	×	
L-AutoDA (Ours)	1-2 Days	×	×	1	

seeks to devise strategies with minimal manual intervention. AutoDA [15] represents the cutting-edge effort in this domain, adopting a random search across a thoughtfully assembled set of algebraic operations to engineer adversarial attack algorithms. However, their method is inherently labor-intensive, particularly in developing domain-specific languages and establishing automated testing infrastructures. Despite the intense investment of efforts and resources, the independent progression of novel algorithms without human expertise presents a substantial challenge [15, 34].

Recent literature has highlighted the potential of large language models (LLMs) for autonomous algorithm design, as demonstrated by initiatives such as Google's FunSearch [35] and the evolutionary algorithm community's AEL [29]. These efforts have corroborated the feasibility of LLMs in the independent generation of algorithms. The advantages of LLMs are manifold: they can decode natural language inputs, obviating the need for domain-specific language encodings and thereby enabling the creation of innovative algorithms beyond the limitations of traditional encoding methods. Furthermore, LLMs can be smoothly integrated into prevailing testing frameworks, requiring only slight modifications to existing test scripts since they can output program code directly, circumventing the need for decoding intermediate encodings. A comparative analysis of this approach with conventional manual algorithm design and automatic program synthesis is delineated in Table 1.

In this research, we exploit the AEL framework for developing decision-based adversarial attacks, introducing L-AutoDA, a cutting-edge automated framework tailored for crafting such attacks. To the best of our knowledge, this work constitutes the first attempt to utilize LLMs in the development and autonomous evaluation of adversarial attack algorithms. By integrating meticulously devised prompts and a population-based methodology within the AEL framework, as detailed in [29], we succeed in deriving innovative strategies. Remarkably, the genesis of all initial algorithms originated exclusively from LLMs and did not depend on established human-centric design principles. This signifies a groundbreaking shift away from conventional approaches, featuring a new paradigm in the autonomous generation of adversarial attack algorithms.

Our contributions are as follows:

- We introduce L-AutoDA, an innovative automated framework that incorporates LLMs to develop decision-based adversarial attack algorithms, marking a pioneering attempt to employ LLMs in this domain and setting the stage for new paradigms in the field.
- Our comparative analysis demonstrates the superiority of LLMs in crafting adversarial attack algorithms over existing methods. The benefits are threefold: *1*) they enable algorithm

generation through natural language interactions, thereby reducing the dependence on human expertise; 2) they exhibit a proficiency to generate more potent algorithms than those conceived by human experts, and 3) they display a capability to produce algorithms that can be integrated seamlessly with existing testing codes.

• The experimental evaluation and analysis highlight the generated algorithms' robust performance, surpassing those that are manually designed. This furnishes new insights into the construction of decision-based adversarial attacks.

2 RELATED WORKS

2.1 Decision-based Adversarial Attacks

Decision-based adversarial attacks constitute the most challenging scenarios for attackers, given that the only information available about the target model is the output label. Despite this obstacle, they pose a considerable threat to machine learning applications. A pioneering study by Ilyas et al. [21] demonstrated the use of Natural Evolution Strategies (NES) to optimize a surrogate function with a limited number of queries to the model. Subsequent advancements have focused on refining gradient estimation techniques. For example, the OPT attack framework introduced by Cheng et al. [7] reformulates the primary optimization challenge. More sophisticated methods, such as the Sign-OPT [8], emphasize the direction of the gradient rather than its magnitude, while the HopSkipJump attack [5] incorporates efficient gradient estimation and combine it with a binary search to closely track the decision boundary. The effectiveness of decision-based attacks is further supported by strategies based on random walks, such as the Boundary Attack [2] and Evolutionary Attack [12].

2.2 Automatically Devising Adversarial Attacks.

The field of adversarial machine learning has increasingly focused on the automated development of attack algorithms [15, 41]. The evolution of attack methods has progressed from basic gradientbased methods such as the Fast Gradient Sign Method (FGSM), which relies on actual gradient data [16], to more sophisticated iterative and optimization-based methods, such as decision-based attacks that require only output label data [2, 5, 7, 8, 12]. Significant research efforts have been invested in the autonomous generation of attack methods utilizing genetic algorithms and evolutionary strategies. To address the prohibitive inefficiency of exploring an unbounded function space of attack algorithms, researchers have introduced a domain-specific language (DSL) to constrain the complexity of functions, thereby achieving the notable efficiency improvements of AutoDA over traditional attack methods [15]. However, creating these algorithms continues to be a labor-intensive process, requiring specialized knowledge to formulate a DSL, develop an associated code generator, and design an appropriate testing framework.

2.3 LLMs for Algorithm Design.

The recent surge in LLMs' capabilities, coupled with their access to extensive training datasets, has significantly enhanced their performance across various research domains [23, 44]. Notably, they excel in executing diverse tasks in a zero-shot fashion [1, 6, 17, 20, 22, 25, 31, 32, 38, 42, 43, 45, 46]. Such progress opens avenues for LLMs to generate and manipulate complex algorithmic structures.

In extending their application, LLMs are now instrumental in the innovation of several algorithmic frameworks. They have been effectively integrated as black-box components in the development of evolutionary algorithms, neural architectures, Monte Carlo Tree Search algorithms, solutions for graph-based combinatorial optimization, genetic programming, and open-ended challenges [44]. While engaging with LLMs through prompts is common, it may result in suboptimal outcomes. A fusion of large language models with evolutionary computation has emerged as a revolutionary advancement [40], facilitating the self-enhancement of algorithms [28, 29], programming codes [26], and mathematical functions [36] through autonomous, iterative refinement within an evolutionary setting.

3 PRELIMINARIES

3.1 Decision-based Adversarial Attacks

Consider a cloud-based image classifier $\mathcal{M} : \mathcal{X} \to \mathcal{Y}$, which maps images from an input space, denoted by \mathcal{X} , to an output space of classification probabilities, denoted by \mathcal{Y} . The input space \mathcal{X} consists of images with *C* channels of $H \times W$ dimensions and is a subset of $[0, 1]^{C \times H \times W}$, while the output space \mathcal{Y} , representing *m* potential class labels, is a subset of $[0, 1]^m$ probability space.

When attackers interact with this classifier, they submit a query image $\mathbf{x} \in X$ and receive the predicted output $\mathcal{M}(\mathbf{x}) \in \mathcal{Y}$. The decision-making process can be clarified by defining the label of input \mathbf{x} as $C(\mathbf{x}) = \arg \max_i \mathcal{M}_i(\mathbf{x})$, which indicates the model's highest confidence prediction. In decision-based attacks, the adversary only gains knowledge of this label.

The attacker's goal in a decision-based attack is to introduce a perturbation δ to the original input x_0 , where the perturbation is minimal yet effective such that $\|\delta\|_p \leq \epsilon$. This perturbation results in a modified input $x_0 + \delta$ that misleads the classifier into assigning a different label. Mathematically, this process is expressed as an optimization problem:

$$\min \|\delta\|_{p} \quad \text{s.t.} \quad C(\mathbf{x}_{0} + \delta) \neq C(\mathbf{x}_{0}). \tag{1}$$

To be deemed successful, a decision-based adversarial attack must ensure the perturbation's magnitude is within a predefined threshold, $\|\delta\|_p \leq \epsilon$. While this work primarily examines *untargeted* attacks bound by the ℓ_2 -norm (p = 2), it also acknowledges the adaptability of our proposed method to facilitate *targeted* attacks by altering the constraint to $C(\mathbf{x}_0 + \delta) = y$, with y being the designated target label.

3.2 Algorithm Evolution using LLMs

In this study, we employ the LLMs to generate the attacking heuristic in an evolutionary framework. It is structured around a cyclical process encompassing key EC stages including initialization, function evaluation, selection, crossover, mutation, and population management, the last of which meditates on diversity and convergence among the proposed solutions. Our methodology draws inspiration from the algorithmic approach developed by Liu *et al.* [29].

Initialization. The initial population is either derived from extant algorithms or is freshly generated using LLMs. Using existing algorithms provides a solid baseline for the evolutionary search, whereas generation from scratch affords the possibility to discover an expansive, novel algorithmic domain. Our methodology involves the latter, leveraging LLMs to generate an initial suite of algorithms. The exploration of evolution using established algorithms remains an integral aspect for formulating robust baselines in future research endeavors.

Evaluating Algorithm. A pivotal component of AEL is assessing the solutions' fitness value. We employ decision-based attack testing as the evaluation mechanism, defining fitness through the measurement of the ℓ_2 distance between the original input and the adversarial output generated by the algorithm.

Generating New Solutions. This stage adheres to the established protocols of EC.

- Selection. Analogous to traditional EC practices, we select a predetermined number of algorithms to be retained through each iteration.
- **Crossover.** We facilitate the crossover operation by submitting a pair of algorithmic candidates, along with guiding prompts, to the LLMs, which in turn, synthesize a potentially superior algorithm. This approach leverages the LLMs' ability to boost the search process beyond the random search capabilities of automated program synthesis.
- Mutation. Introducing variation into the algorithmic pool is paramount for fostering diversity. This is accomplished by instructing the LLMs to introduce minor modifications to the current algorithms.

4 L-AUTODA: LLM-BASED AUTOMATED DECISION-BASED ADVERSARIAL ATTACKS

In this section, we introduce our novel framework, L-AutoDA, which is designed for automatically generating decision-based adversarial attacks. We begin by delineating the problem formulation and examining the search space associated with our framework (Section 4.1). Subsequently, we describe the comprehensive structure of the L-AutoDA framework (Section 4.2) as well as elaborate on the specifics of its implementation (Section 4.3). An illustrative overview of the L-AutoDA architecture is depicted in Figure 1.

4.1 Decision-based Attack Framework

Random Walk Template. We have developed a foundational framework for decision-based adversarial attacks, founded on the random walk paradigm, to establish the function search space, as depicted in Algorithm 1. This framework integrates critical elements from pioneering techniques such as the Evolutionary Attack [12], the Boundary Attack [2], and various other strategies. Although gradient-based frameworks are also prevalent, we leave the exploration of this domain to future research endeavors.

The framework highlights two pivotal components for further improvement: the generate function and the accompanying hyperparameters. The generate function is vital to the algorithm, handling the current adversarial sample x_1 , the original example x_0 , and synthesizing a new adversarial instance x. Hyperparameters are pivotal in steering the algorithm's behavior, influencing factors such as step size and the number of iterations. To streamline GECCO '24 Companion, July 14-18, 2024, Melbourne, VIC, Australia



Figure 1: Overview of the L-AutoDA Framework Methodology. This diagram delineates the two core components of our L-AutoDA framework: the algorithm generation and testing phases. In the algorithm generation phase, we adopt the AEL framework, leveraging LLMs to guide an evolutionary search process. In the testing phase, we employ existing decision-based attack testing code, integrating these algorithms into the attack program to validate their efficacy.

Algorithm 1 Random Walk Framework for Decision-Based Attacks under ℓ_2 perturbation

- 1: **Input:** original example x_0 , adversarial starting point x_1
- 2: Output: An adversarial example *x*.
- 3: Initialization: $x \leftarrow x_1$; $d_{\min} \leftarrow ||x x_0||_2$
- 4: while query budget not reached do
- $x' \leftarrow generate(x, x_0)$ 5:
- $\begin{array}{l} \text{if } x' \text{ is adversarial and } \|x' x_0\|_2 < d_{\min} \text{ then } \\ x \leftarrow x'; d_{\min} \leftarrow \|x' x_0\|_2 \end{array}$ 6:
- 7:
- end if 8:
- Update hyper-parameters. 9:
- 10: end while
- 11: return x

the search process, we adopted the parameter tuning strategy from [15], concentrating our efforts on refining the generate function.

Search Space. We let the LLM to explore the search space of the generate function. While devising a comprehensive algorithm for the generation of perturbations is a viable approach to advance our LLM-based algorithmic framework, the extensive search space complicates the discovery of the optimum algorithmic solution. Future investigations will engage with the wide-ranging possibilities and address the challenges arising from this extensive search space [18].

4.2 L-AutoDA

The L-AutoDA framework represents a cutting-edge system that leverages the AEL paradigm [29] to expedite the creation of novel decision-based adversarial attack algorithms. Central to L-AutoDA is the pursuit of an optimal generate function, which is responsible for generating new adversarial examples during the attack process. The resulting generate functions are seamlessly integrated into existing decision-based attack programs, enhancing the continuous innovation and assessment of diverse attack strategies, as depicted in Figure 1. Subsequent paragraphs detail the workflow within the L-AutoDA framework, beginning with the initialization of a set of candidate algorithms.

Initialization. As L-AutoDA adopts a population-based method to cultivate a diverse array of candidate algorithms, we first need to initialize the population. This process involves providing a carefully constructed prompt:

Initialization Prompt. Given an image org_img, its adversarial image best_adv_img, and a random normal noise std_normal_noise, you need to design an algorithm to combine them to search for a new adversarial example x_new. hyperparams ranges from 0.5 to 1.5. It gets larger when this algorithm outputs more adversarial examples, and vice versa. It can be used to control the step size of the search. Operations you may use include: adding, subtracting, multiplying, dividing, dot product, and 12 norm computation. Design an novel algorithm with various search techniques. Your code should be able to run without further assistance.

Moreover, the input and output parameters and their corresponding messages of the generate function are provided to the AEL framework to further ensure the legitimacy of the generated code.

Population-based Search. Following initialization, L-AutoDA engages in a population-based search within the evolutionary computation paradigm, employing a specialized testing script (as mentioned in Section. 4.3) to evaluate fitness values.

Objective Value. The efficacy of the algorithms is measured by an objective value, denoted as the average distance between adversarial and original images. This value acts as a fitness function within the AEL framework and steers the evolutionary algorithm.

Search Process Guided by the objective value, L-AutoDA applies evolutionary operations, such as selection, crossover, and mutation, to refine the assortment of algorithms. Different from traditional evolutionary algorithms, L-AutoDA implements the above operations leveraging LLMs by interacting with them with prompts and information like the objective value. During this process, the most promising candidates, or "elite" algorithms, are identified and retained. This evolutionary cycle is performed iteratively to enhance the development of more potent adversarial attack algorithms.

Substantial Advantages. L-AutoDA's generative mechanism is harmoniously compatible with conventional decision-based attack programs. It assesses the quality of the generated algorithms by examining the output the attack program produces when provided with the generated generate function. This methodology marks a significant leap from traditional program synthesis, which typically necessitates rigorous validation to confirm the legitimacy and functional integrity of the generated code. By concentrating on the algorithmic output and its effectiveness, L-AutoDA streamlines the search process and demonstrates its superiority.

4.3 Implementation

This section details the implementation of the L-AutoDA algorithm, starting with a comprehensive description of the search space for generate functions, followed by the elucidation of a feedback mechanism for hyperparameter adjustment. It concludes with an overview of the testing script used to evaluate the performance of the evolved algorithms.

Function Specification. The generate function accepts four inputs: the original example x_0 , the adversarial starting point x_1 , standard random noise r, and a dynamically adjusted hyperparameter s. Its objective is to ingeniously integrate these inputs to produce an adversarial example x, with the hyperparameter providing informed control over step size referencing.

Hyper-parameter Tuning. Our approach to hyperparameter tuning adopts the strategy presented in [15]. We introduce a piece-wise linear function f(p) defined as:

$$f(p) = \begin{cases} 0.5 + 2p & 0 \le p \le 0.25\\ \frac{5}{6} + \frac{2p}{3} & 0.25 (2)$$

During each iteration, p is updated in the following manner:

$$p = 0.95p + 0.05k \tag{3}$$

where k represents the discovery of an improved adversarial point, taking on the value of 1 if a better point is found and 0 otherwise. The hyperparameter s is then computed by:

$$s = s \cdot [f(p)]^{0.1} \tag{4}$$

This engenders a compensatory feedback loop, aimed at anchoring p around 0.25.

Testing Script. The AEL framework relies on a fitness function value to guide its evolutionary progress. In this context, a testing

script was devised to evaluate the efficacy of the algorithms produced. To avoid the extensive time requirement associated with processing the entire test set, a representative subset of the dataset was chosen for our experiments. These samples are used to compute the fitness value, utilizing standardized attack settings. This method employs a standardized set of attack parameters to calculate the fitness value. Although this approach may bring about a certain degree of bias, the empirical evaluation results support its effectiveness in accelerating the evolutionary search.

5 EXPERIMENTS

5.1 Experimental Setup

L-AutoDA Generation. The experimental setup for the L-AutoDA algorithm generation is divided into two distinct parts: *1*) settings for the AEL running process and *2*) for the objective value evaluation. Note that our experiments are conducted on CIFAR-10 dataset [24] and a ResNet-18 classification model [10], which is a prevalent benchmark for adversarial attack algorithms.

AEL Settings. In our setting, the AEL framework operates over 20 generations, each comprising 10 algorithm candidates. Moreover, we set the crossover probability at 1.0, ensuring that each pair of selected programs undergoes recombination, and the mutation probability at 0.5 to introduce variability. The default LLM for algorithm generation is GPT-3.5-turbo-1106, with plans to expand testing to additional large language models in subsequent research.

Algorithm Evaluation. In assessing the performance of the devised algorithms, we have tailored our testing procedure to confine each algorithm to a maximum of 8,000 queries. We execute the algorithms on the first eight images of the CIFAR-10 test set to ensure a consistent and manageable testing environment. The adversarial images produced are then used to calculate the ℓ_2 distances relative to their original counterparts. The mean of these distances is computed to serve as the fitness value, which is fed back into the AEL framework, thereby informing the evolutionary search for more effective attack algorithms.

Attack Evaluation. The evaluation process for different attacks is a crucial aspect of the experimental setup, providing a comprehensive assessment of the generated adversarial algorithms' performance.

Datasets. Our evaluation utilizes a subset of the CIFAR-10 dataset, comprising 100 randomly sampled images from each class, to ensure a diverse and representative test bed. To facilitate a fair comparison across all attack algorithms, we introduce a set of 10 images with incorrect labels as the initial starting points for the attacks, ensuring that each algorithm begins from a standardized baseline.

Comparative Algorithms. In our comparative analysis, we establish the Boundary attack [2], which operates under the random walk framework, as the baseline algorithm. Additionally, we include the widely acknowledged SOTA decision-based attack algorithm, the HopSkipJumpAttack (HSJA) [5], which employs a gradient-based approach. To further enrich our comparison, we introduce a variant of HSJA that utilizes a grid search strategy instead of its default geometric progression for step search, denoted as HSJA* in our paper. Our future work anticipates the inclusion of more attack algorithms for a more exhaustive comparison.

Attack Name	Distance (<i>l</i> ₂ -norm)		Attack Success Rate			
# of Queries	2500	5000	10000	2500	5000	10000
Boundary	$1.9107_{1.2665}$	$1.0938_{0.7861}$	$0.4495_{0.3340}$	14.7	26.2	65.5
HSJA	$2.0512_{1.0876}$	$1.2833_{0.7442}$	$0.8978_{0.5360}$	9.2	16.1	24.6
HSJA*	$2.6482_{1.5790}$	$1.6532_{1.0347}$	$1.1306_{0.6987}$	7.9	13.9	19.6
L-AutoDA-20	$1.5202_{0.1337}$	$0.6171_{0.1430}$	$0.3445_{0.2386}$	0.0	0.5	80.3

Table 2: The full test performance of L-AutoDA-20 compared to three baseline algorithms.

Table 3: The performance of L-AutoDA compared to three baseline algorithms using the testing script. The mean distance of 1000 images are documented with the standard variance to be the subscript. The best performance cell is marked with light gray and the text within is bolded.

Boundary	HSJA	HSJA*	L-Auto-20
0.3939	1.3628	1.2839	0.2517



Figure 2: Performance Trajectories of L-AutoDA. This graph illustrates the comparative efficiency of our L-AutoDA framework against the human-best gradient-based (HopSkipJump Attack) and gradient-free (Boundary Attack) methods. L-AutoDA's candidates demonstrate a breakthrough in the 13th generation, surpassing the reference performance lines and continuing to enhance efficiency in subsequent generations.

Detailed Parameters. Delving into the detailed parameter settings, for the Boundary Attack, we set both the spherical and source steps for the Boundary Attack at 0.01, with a step size adaptation rate of 1.5. In the case of the HopSkipJump Attack, the parameter γ is established at 1.0, initial gradient estimation starts with 100 steps, and is limited to a peak of 10,000 steps. Reflecting the adaptive nature of the L-AutoDA-generated algorithms, a negative feedback mechanism is employed to fine-tune the hyperparameter *s*, which is initially set to 0.001.

5.2 Algorithm Generation

The performance of the algorithms generated by L-AutoDA is encapsulated in Figure 2, which demonstrates their compelling capabilities. Remarkably, the initial iteration of L-AutoDA produced algorithms that outperformed HSJA. Although this unexpected result may be partially attributed to the limited subset of images used during testing, it nonetheless underscores the potential of L-AutoDA in rapidly devising effective attack strategies. As the evolutionary process progressed, L-AutoDA continued to refine its algorithms, surpassing both HSJA and Boundary Attack by the 6th generation. This trend of improvement was consistent, with each subsequent generation enhancing the algorithms' effectiveness.

An intriguing aspect was the reduction in the variance of algorithm performance within each generation. This convergence suggests a stabilization of performance across the generated algorithms, indicating that L-AutoDA is not only producing more effective algorithms over time but also more reliable ones.

The results of the final round are documented in Table 3. L-AutoDA's best algorithm within the 20th generation, denoted as L-Auto-20, achieved a mean perturbation distance of 0.2517 across the test images. This represents a significant improvement over the HSJA and Boundary Attack, which achieved mean perturbation distances of 1.3628 and 0.3939, respectively.

5.3 Attack Evaluation

To thoroughly evaluate the algorithms generated, we subjected them to tests on an expanded subset as delineated in our experimental setup. The most effective algorithm produced by the final iteration of L-AutoDA, referred to as L-AutoDA-20, was selected for benchmark comparison.

Overall Results. We have documented the overall full test results in Table 2. The table reveals that L-AutoDA-20 is the most effective algorithm, achieving the lowest mean distance across all query counts. This result is particularly impressive given that L-AutoDA-20 was generated entirely from scratch by the LLM, without any human intervention. As for the success rate, L-AutoDA-20 achieved a 0% success rate at 2500 queries, which is expected given the limited number of queries. The success rate then increased to 80.3% at 10000 queries, surpassing all other algorithms. We delineate the relationship between attack success rate and distance in the following sections.

Attack Success Rate. Figure 3 illustrates the attack success rate with the number of queries. A successful attack is defined by an

L-AutoDA: Large Language Models for Automatically Evolving Decision-based Adversarial Attacks



Figure 3: Attack Success Rate using different numbers of queries using L-AutoDA-20 and other attack algorithms.

 ℓ_2 norm less than 0.5 between the adversarial example and the original image, consistent with the widely accepted standard in the current benchmarks [9]. The figure reveals that L-AutoDA-20's performance is suboptimal at 2500 and 5000 queries. However, there is a notable uptick in success rate when the query count reaches 10000, surpassing all baseline algorithms. This pattern suggests that L-AutoDA sacrifices initial search efficiency to enhance the quality of the search at later stages, particularly after 8000 queries (testing script).

Distance. We present the comparative analysis of the perturbation distances in Figure 4, where we plot the mean ℓ_2 distance between the adversarial and original images against the number of queries used. The shaded areas in the figure represent a 0.25 multiplier of the standard deviation, providing insight into the variability of each algorithm's performance.

From Figure 4, it is evident that L-AutoDA-20 maintains the most consistent performance across all tested query counts, as indicated by the smallest standard deviation values. This consistency suggests that L-AutoDA-20 is less sensitive to the variations in the input data, making it a robust choice for generating adversarial examples. Although this robustness may come at the cost of a reduced attack success rate in the initial phase, it becomes a significant advantage in later stages, particularly beyond 8000 queries.

The stability of L-AutoDA-20 is particularly beneficial when the attack requires subtlety, as it is capable of producing perturbations that are minimally perceptible yet still effective. This characteristic is crucial for scenarios where detectability is a concern and stealth is paramount.

5.4 Additional Results on Median Distance

To avoid the influence of variations with the images and better illustrate the effectiveness of our framework, we have demonstrated the median distance of the adversarial examples generated by different algorithms in Table 4. The results are consistent with the previous analysis, with L-AutoDA-20 achieving the lowest median distance across all query counts.



Figure 4: Distance between adversarial examples and original images using different numbers of queries using L-AutoDA-20 and other attack algorithms. The lines denote the mean value of the test pairs and the shaded areas represent a 0.25 multiplier of the standard deviation.

Table 4: Median distance of L-AutoDA-20 compared to three baseline algorithms. The best performance cell is marked with light gray and the text within is bolded.

	2500	5000	10000
Boundary	1.7374	0.9489	0.3695
HSJA	2.0230	1.2468	0.8646
HSJA*	2.5150	1.5580	1.0618
L-AutoDA-20	1.5301	0.5896	0.2862

5.5 Interpretation of the algorithms

To elucidate the evolutionary process of the generate() function, a representative algorithm from the initial population and the most successful algorithm from the final population were chosen for comparative analysis.

Initial Population. The selected algorithm from the initial population is detailed in Algorithm 2. While the search for adversarial examples is not assured by more efficient search vectors, this algorithm shows its flexibility by exploring different operations. However, since we want to generate adversarial examples that are both effective and efficient, the initial algorithm may not be the most optimal choice and continue to evolve.

Final Population. The generate function output by L-AutoDA is illustrated in Algorithm 3. The algorithm starts by taking the difference between the original example \mathbf{x}_0 and the adversarial starting point \mathbf{x}_1 . By moving along this vector, one can generate examples that are in between the original and the adversarial, which may help in exploring the space around known data points. Furthermore, efficient search is enabled through the inclusion of another normalized vector $\frac{d}{norm}$. Then two scales of noise are added to the example, one with the same direction as the difference vector \mathbf{d} and the other with the same direction as the normalized difference vector $\frac{d}{norm}$. The noise is further scaled by a hyperparameter *s* to control the magnitude of the perturbation. Combined with these

GECCO '24 Companion, July 14-18, 2024, Melbourne, VIC, Australia

Ping Guo, Fei Liu, Xi Lin, Qingchuan Zhao, and Qingfu Zhang

Algorithm 2 generate() (Initial Population)

c	
1:	Input: original example \mathbf{x}_0 , adversarial starting point \mathbf{x}_1 , stan-
	dard normal noise n, hyperparameter s
2:	Output: A new proposed example x
3:	$n_0 \leftarrow \mathcal{N}(0,1)$
4:	$\mathbf{x} \leftarrow s\mathbf{x}_0 + (1-s)\mathbf{x}_1 + n_0\mathbf{n}$
5:	Operation = randChoice(add, sub, mul)
6:	$n_1 \leftarrow \mathcal{U}(0.5, 1.5)$
7:	if Operation == add then
8:	$\mathbf{x} \leftarrow \mathbf{x} + n_1 \mathbf{n}$
9:	else if Operation == sub then
10:	$\mathbf{x} \leftarrow \mathbf{x} - n_1 \mathbf{n}$
11:	else
12:	$\mathbf{x} \leftarrow \mathbf{x} * n_1 \mathbf{n}$
13:	end if
14:	$\mathbf{d} \leftarrow \mathbf{x}_0 - \mathbf{x}_1$

Algorithm 3 generate() (Final Population)

- 1: Input: original example x₀, adversarial starting point x₁, standard normal noise n, hyperparameter s
- 2: Output: A new proposed example x
- 3: $\mathbf{d} \leftarrow \mathbf{x}_0 \mathbf{x}_1$
- 4: $norm = max(\|\mathbf{d}\|_2, \|\mathbf{n}\|_2)$ 5: $\mathbf{x} \leftarrow \mathbf{x}_1 + s(\mathbf{d} + \frac{\mathbf{d}}{norm}) + s(\mathbf{n} + s\frac{\mathbf{n}}{norm})$

search vectors, L-AutoDA is able to generate adversarial examples that are both effective and efficient.

DISCUSSION 6

Expanded Experimental Validation. Although our experimental framework, consisting of 20 generations with 10 individuals per generation, has yielded results surpassing those of manually-designed state-of-the-art algorithms, it has not fully tested the boundaries of our framework or LLMs. We will increase the number of generations and individuals to see if we can obtain better results. We aim to test these limits by increasing the population size and the number of generations. Additionally, initializing the search process with existing algorithms and subsequently refining them represents a promising avenue for further experimentation.

Broader Algorithm Search Space. or expediency and as an initial attempt for automated attack algorithm design using LLMs into the automated design of attack algorithms using LLMs, we confined the search space to that defined by the generate() function. However, this narrow scope may restrict the discovery of optimal algorithms. Future work will seek to exploit the full potential of LLMs by allowing them to craft comprehensive algorithms without such constraints.

Enhancing Prompt Adaptability. Our methodology employed a set of static prompts to assist LLMs in algorithm generation. However, the fixed prompts may not be the best prompts for LLMs to generate algorithms. The effectiveness of these prompts, however, may not represent an optimal use of LLM capabilities. The concept of chain-of-reasoning, which underpins our work and AEL, suggests

a close relationship with adaptive prompt generation. Investigating methods of dynamically generating prompts is an objective of our ongoing research.

Addressing Limitations. While the synthesis of programs using large language models is the focus of our research, it is not without its drawbacks. These models may occasionally yield unsatisfactory outcomes, albeit at a lower rate than traditional approaches. Improving the specificity of constraints within the prompts to ensure the validity of the algorithms produced will be an integral part of our forthcoming efforts.

7 CONCLUSION

In this paper, we have successfully demonstrated the innovative application of LLMs for the automatic design of decision-based adversarial attack algorithms. By leveraging the AEL framework, we have not only streamlined the algorithmic design process, but also achieved a significant reduction in the time and expertise required to develop effective adversarial attacks. Our approach, encapsulated in the L-AutoDA framework, represents a paradigm shift in the field of adversarial machine learning, showcasing the untapped potential of LLMs in the realm of security and algorithm synthesis.

ACKNOWLEDGMENTS

The work described in this paper was supported by the Research Grants Council of the Hong Kong Special Administrative Region, China [GRF Project No. CityU 11215622], by Natural Science Foundation of China [Project No: 62276223] and by Key Basic Research Foundation of Shenzhen, China.

REFERENCES

- [1] Jason Blocklove, Siddharth Garg, Ramesh Karri, and Hammond Pearce. 2023. Chip-Chat: Challenges and Opportunities in Conversational Hardware Design. arXiv preprint arXiv:2305.13243 (2023).
- [2] Wieland Brendel, Jonas Rauber, and Matthias Bethge. 2018. Decision-Based Adversarial Attacks: Reliable Attacks Against Black-Box Machine Learning Models. In 6th International Conference on Learning Representations, (ICLR). OpenReview.net.
- [3] Yulong Cao, Chaowei Xiao, Benjamin Cyr, Yimeng Zhou, Won Park, Sara Rampazzi, Qi Alfred Chen, Kevin Fu, and Z. Morley Mao. 2019. Adversarial Sensor Attack on LiDAR-based Perception in Autonomous Driving. In Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security, (CCS). ACM.
- [4] Anirban Chakraborty, Manaar Alam, Vishal Dey, Anupam Chattopadhyay, and Debdeep Mukhopadhyay. 2021. A survey on adversarial attacks and defences. CAAI Trans. Intell. Technol. (2021). https://doi.org/10.1049/CIT2.12028
- [5] Jianbo Chen, Michael I. Jordan, and Martin J. Wainwright. 2020. HopSkipJumpAttack: A Query-Efficient Decision-Based Attack. In 2020 IEEE Symposium on Security and Privacy, (SP). IEEE.
- Kunming Cheng, Qiang Guo, Yongbin He, Yanqiu Lu, Shuqin Gu, and Haiyang Wu. 2023. Exploring the potential of GPT-4 in biomedical engineering: the dawn of a new era. Annals of Biomedical Engineering (2023), 1-9.
- Minhao Cheng, Thong Le, Pin-Yu Chen, Huan Zhang, Jinfeng Yi, and Cho-Jui Hsieh. 2019. Query-Efficient Hard-label Black-box Attack: An Optimizationbased Approach. In 7th International Conference on Learning Representations, ICLR. OpenReview.net.
- [8] Minhao Cheng, Simranjit Singh, Patrick H. Chen, Pin-Yu Chen, Sijia Liu, and Cho-Jui Hsieh. 2020. Sign-OPT: A Query-Efficient Hard-label Adversarial Attack. In 8th International Conference on Learning Representations, ICLR. OpenReview.net.
- [9] Francesco Croce, Maksym Andriushchenko, Vikash Sehwag, Edoardo Debenedetti, Nicolas Flammarion, Mung Chiang, Prateek Mittal, and Matthias Hein. 2021. RobustBench: a standardized adversarial robustness benchmark. In Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks 1, (NeurIPS).
- Eduardo Dadalto. 2022. ResNet18 trained on CIFAR10. https://huggingface.co/ edadaltocg/resnet18_cifar10. Accessed: 2023-07-01.

L-AutoDA: Large Language Models for Automatically Evolving Decision-based Adversarial Attacks

GECCO '24 Companion, July 14-18, 2024, Melbourne, VIC, Australia

- [11] Junhao Dong, Junxi Chen, Xiaohua Xie, Jianhuang Lai, and Hao Chen. 2023. Adversarial Attack and Defense for Medical Image Analysis: Methods and Applications. *CoRR* (2023). https://doi.org/10.48550/ARXIV.2303.14133 arXiv:2303.14133
- [12] Yinpeng Dong, Hang Su, Baoyuan Wu, Zhifeng Li, Wei Liu, Tong Zhang, and Jun Zhu. 2019. Efficient Decision-Based Black-Box Adversarial Attacks on Face Recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, (CVPR). Computer Vision Foundation / IEEE.
- [13] Ryan Feng, Ashish Hooda, Neal Mangaokar, Kassem Fawaz, Somesh Jha, and Atul Prakash. 2023. Stateful Defenses for Machine Learning Models Are Not Yet Secure Against Black-box Attacks. In Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security, (CCS). ACM, 786–800.
- [14] Matthias Feurer, Aaron Klein, Katharina Eggensperger, Jost Tobias Springenberg, Manuel Blum, and Frank Hutter. 2015. Efficient and Robust Automated Machine Learning. In Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015.
- [15] Qi-An Fu, Yinpeng Dong, Hang Su, Jun Zhu, and Chao Zhang. 2022. AutoDA: Automated Decision-based Iterative Adversarial Attacks. In 31st USENIX Security Symposium, USENIX Security 2022. USENIX Association, 3557–3574.
- [16] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. 2015. Explaining and Harnessing Adversarial Examples. In 3rd International Conference on Learning Representations, (ICLR).
- [17] Jindong Gu, Zhen Han, Shuo Chen, Ahmad Beirami, Bailan He, Gengyuan Zhang, Ruotong Liao, Yao Qin, Volker Tresp, and Philip Torr. 2023. A systematic survey of prompt engineering on vision-language foundation models. arXiv preprint arXiv:2307.12980 (2023).
- [18] Sumit Gulwani, Oleksandr Polozov, Rishabh Singh, et al. 2017. Program synthesis. Foundations and Trends[®] in Programming Languages (2017).
- [19] Ping Guo, Zhiyuan Yang, Xi Lin, Qingchuan Zhao, and Qingfu Zhang. 2024. PuriDefense: Randomized Local Implicit Adversarial Purification for Defending Black-box Query-based Attacks. arXiv preprint arXiv:2401.10586 (2024).
- [20] Zhuolun He, Haoyuan Wu, Xinyun Zhang, Xufeng Yao, Su Zheng, Haisheng Zheng, and Bei Yu. 2023. ChatEDA: A Large Language Model Powered Autonomous Agent for EDA. arXiv preprint arXiv:2308.10204 (2023).
- [21] Andrew Ilyas, Logan Engstrom, Anish Athalye, and Jessy Lin. 2018. Black-box Adversarial Attacks with Limited Queries and Information. In Proceedings of the 35th International Conference on Machine Learning, (ICML) (Proceedings of Machine Learning Research). PMLR.
- [22] Kevin Maik Jablonka, Philippe Schwaller, Andres Ortega-Guerrero, and Berend Smit. 2023. Is GPT-3 all you need for low-data discovery in chemistry? (2023).
- [23] Enkelejda Kasneci, Kathrin Seßler, Stefan Küchemann, Maria Bannert, Daryna Dementieva, Frank Fischer, Urs Gasser, Georg Groh, Stephan Günnemann, Eyke Hüllermeier, et al. 2023. ChatGPT for good? On opportunities and challenges of large language models for education. *Learning and individual differences* 103 (2023), 102274.
- [24] A. Krizhevsky. 2009. Learning Multiple Layers of Features from Tiny Images. Technical Report. Univ. Toronto.
- [25] Peter Lee, Sebastien Bubeck, and Joseph Petro. 2023. Benefits, limits, and risks of GPT-4 as an AI chatbot for medicine. *New England Journal of Medicine* 388, 13 (2023), 1233–1239.
- [26] Joel Lehman, Jonathan Gordon, Shawn Jain, Kamal Ndousse, Cathy Yeh, and Kenneth O. Stanley. 2024. Evolution Through Large Models. Springer Nature Singapore, Singapore, 331–366.
- [27] Deqiang Li, Qianmu Li, Yanfang (Fanny) Ye, and Shouhuai Xu. 2023. Arms Race in Adversarial Malware Detection: A Survey. ACM Comput. Surv. (2023).
- [28] Fei Liu, Xialiang Tong, Mingxuan Yuan, Xi Lin, Fu Luo, Zhenkun Wang, Zhichao Lu, and Qingfu Zhang. 2024. Evolution of Heuristics: Towards Efficient Automatic Algorithm Design Using Large Language Mode. (2024). arXiv:2401.02051
- [29] Fei Liu, Xialiang Tong, Mingxuan Yuan, and Qingfu Zhang. 2023. Algorithm Evolution Using Large Language Model. arXiv preprint arXiv:2311.15249 (2023).
- [30] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. 2018. Towards Deep Learning Models Resistant to Adversarial Attacks. In 6th International Conference on Learning Representations, (ICLR). OpenReview.net.
- [31] Bonan Min, Hayley Ross, Elior Sulem, Amir Pouran Ben Veyseh, Thien Huu Nguyen, Oscar Sainz, Eneko Agirre, Ilana Heintz, and Dan Roth. 2021. Recent advances in natural language processing via large pre-trained language models: A survey. Comput. Surveys (2021).
- [32] Harsha Nori, Nicholas King, Scott Mayer McKinney, Dean Carignan, and Eric Horvitz. 2023. Capabilities of gpt-4 on medical challenge problems. arXiv preprint arXiv:2303.13375 (2023).
- [33] Nicolas Papernot, Patrick D. McDaniel, Ian J. Goodfellow, Somesh Jha, Z. Berkay Celik, and Ananthram Swami. 2017. Practical Black-Box Attacks against Machine Learning. In Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security, AsiaCCS. ACM.
- [34] Esteban Real, Chen Liang, David R. So, and Quoc V. Le. 2020. AutoML-Zero: Evolving Machine Learning Algorithms From Scratch. In Proceedings of the 37th International Conference on Machine Learning, (ICML) (Proceedings of Machine Learning Research). PMLR.

- [35] Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M Pawan Kumar, Emilien Dupont, Francisco JR Ruiz, Jordan S Ellenberg, Pengming Wang, Omar Fawzi, et al. 2023. Mathematical discoveries from program search with large language models. *Nature* (2023), 1–3.
- [36] Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M Pawan Kumar, Emilien Dupont, Francisco JR Ruiz, Jordan S Ellenberg, Pengming Wang, Omar Fawzi, et al. 2023. Mathematical discoveries from program search with large language models. *Nature* (2023), 1–3.
- [37] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian J. Goodfellow, and Rob Fergus. 2014. Intriguing properties of neural networks. In 2nd International Conference on Learning Representations (ICLR).
- [38] Haoye Tian, Weiqi Lu, Tsz On Li, Xunzhu Tang, Shing-Chi Cheung, Jacques Klein, and Tegawendé F Bissyandé. 2023. Is ChatGPT the Ultimate Programming Assistant-How far is it? arXiv preprint arXiv:2304.11938 (2023).
- [39] Yu Wang, Xiaogeng Liu, Yu Li, Muhao Chen, and Chaowei Xiao. 2024. AdaShield: Safeguarding Multimodal Large Language Models from Structure-based Attack via Adaptive Shield Prompting. CoRR (2024).
- [40] Xingyu Wu, Sheng-hao Wu, Jibin Wu, Liang Feng, and Kay Chen Tan. 2024. Evolutionary Computation in the Era of Large Language Model: Survey and Roadmap. arXiv preprint arXiv:2401.10034 (2024).
- [41] Fei Yin, Yong Zhang, Baoyuan Wu, Yan Feng, Jingyi Zhang, Yanbo Fan, and Yujiu Yang. 2023. Generalizable Black-Box Adversarial Attack with Meta Learning. CoRR abs/2301.00364 (2023). arXiv:2301.00364
- [42] Caiyang Yu, Xianggen Liu, Chenwei Tang, Wentao Feng, and Jiancheng Lv. 2023. GPT-NAS: Neural Architecture Search with the Generative Pre-Trained Model. arXiv preprint arXiv:2305.05351 (2023).
- [43] Shujian Zhang, Chengyue Gong, Lemeng Wu, Xingchao Liu, and Mingyuan Zhou. 2023. AutoML-GPT: Automatic Machine Learning with GPT. arXiv preprint arXiv:2305.02499 (2023).
- [44] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. 2023. A survey of large language models. arXiv preprint arXiv:2303.18223 (2023).
- [45] Mingkai Zheng, Xiu Su, Shan You, Fei Wang, Chen Qian, Chang Xu, and Samuel Albanie. 2023. Can GPT-4 Perform Neural Architecture Search? arXiv preprint arXiv:2304.10970 (2023).
- [46] Yongchao Zhou, Andrei Ioan Muresanu, Ziwen Han, Keiran Paster, Silviu Pitis, Harris Chan, and Jimmy Ba. 2022. Large language models are human-level prompt engineers. arXiv preprint arXiv:2211.01910 (2022).