Assessment of the Sparsity-Diversity Trade-offs in Active Users Detection for mMTC

Gabriel Martins de Jesus, Onel Luis Alcaraz López, Richard Demo Souza, Nurul Huda Mahmood, Markku Juntti, Matti Latva-Aho

Abstract—Wireless communication systems must increasingly support a multitude of machine-type communications (MTC) devices, thus calling for advanced strategies for active user detection (AUD). Recent literature has delved into AUD techniques based on compressed sensing, highlighting the critical role of signal sparsity. This study investigates the relationship between frequency diversity and signal sparsity in the AUD problem. Single-antenna users transmit multiple copies of non-orthogonal pilots across multiple frequency channels and the base station independently performs AUD in each channel using the orthogonal matching pursuit algorithm. We note that, although frequency diversity may improve the likelihood of successful reception of the signals, it may also damage the channel sparsity level, leading to important trade-offs. We show that a sparser signal significantly benefits AUD, surpassing the advantages brought by frequency diversity in scenarios with limited temporal resources and/or high numbers of receive antennas. Conversely, with longer pilots and fewer receive antennas, investing in frequency diversity becomes more impactful, resulting in a tenfold AUD performance improvement.

Index Terms—Active user detection, diversity, compressed sensing, massive MTC

I. INTRODUCTION

W ITH the population of connected wireless devices growing by the day, the design of wireless communication systems is becoming increasingly challenging. Electronic devices communicating with each other without any human interaction, i.e., performing machine type communications (MTC), are becoming predominant among all [1]. Indeed, the development of the fifth generation of wireless systems (5G) has been driven by the need to support a massive number of heterogeneous MTC devices, e.g., 10⁶/km², sharing the same radio resources. These are the so-called massive MTC (MTC) scenarios [2], typical for applications such as e.g., industry automation and sensing, and distributed ledgers [3], [4].

Generally, in the mMTC paradigm, communication is established after the active users detection (AUD) phase takes place, which is when the set of active users is detected and identified. When multiple devices, or users, are simultaneously active in a given transmitting opportunity, their signals arrive superimposed to the receiver. This complicates the AUD process since the resultant composite signal could erroneously resemble a transmission from a user that is, in fact, not transmitting. Fortunately, users transmit sporadically, with only a small fraction of the total users becoming active simultaneously, which can be exploited for accurate AUD. Specifically, this sparse user activity encourages the utilization of established compressed sensing (CS) techniques [5]–[7], with the setups designed so that users transmit pilot signals before the data, serving the dual purpose of joint AUD and channel estimation.

A key concept of CS is the sparsity level of the signal, denoted by $S \triangleq 1/K$, where K refers to the count of active users. The CS algorithms can efficiently recover the signals when signal sparsity, time resources, and noise conditions are favorable. In short, for a given number of measurements, the signal is more likely to be recovered when the sparsity level is high (i.e., smaller K, with $S \to \infty$ when K = 0) and/or signal-to-noise-ratio (SNR) is high. The number of measurements required to guarantee a performance level in CS algorithms can be determined based e.g., on the expected sparsity level [8]. Although committing to these requirements can be challenging in some applications since both the pilot and data must be transmitted within the coherence interval of the channel, this is not necessarily the case for mMTC traffic as packets are usually short.

On the other hand, communication diversity is a wellestablished method for performance boosting [4], [9]. Diversity can manifest in signal transmission or reception strategies. For instance, it might involve replicating transmissions in the frequency or time domain, or by deploying multiple antennas in the transmitter or receiver. The inclusion of redundant replicas of the same message increases the likelihood of the signal being correctly detected. In the case of transmission diversity, such robustness comes at the cost of increased channel utilization. For instance, with frequency transmission diversity, utilizing multiple copies decreases the sparsity level, resulting in interference, and leading to potential trade-offs between diversity and sparsity. These trade-offs have been investigated in terms of throughput, packet collisions, and other physical layer aspects in the literature [10], [11].

CS-based AUD has been explored recently in several distinct setups and employing different algorithms [12]–[16], but the effects of the trade-offs between frequency diversity and channel sparsity on AUD is still an open research topic [17]. To identify these trade-offs, herein we consider a scenario where the users transmit their non-orthogonal pilots across

This research has been supported by the Finnish Foundation for Technology Promotion and the Research Council of Finland (former Academy of Finland) Grant 346208 (6G Flagship Programme), CNPq (401730/2022-0, 402378/2021-0, 305021/2021-4) and RNP/MCTIC 6G Mobile Communications Systems (01245.010604/2020-14).

G. M. de Jesus, O. L. A. López, N. H. Mahmood, M. Juntti, and M. Latva-Aho are with the Centre for Wireless Communications, University of Oulu, Finland (email: {gabriel.martinsdejesus, onel.alcarazlopez, nurulhuda.mahmood, markku.juntti, matti.latva-aho}@oulu.fi). R. D. Souza is with the Department of Electrical and Electronic Engineering, Federal University of Santa Catarina, Brazil (email: richard.souza@ufsc.br)

several orthogonal frequency channels, and the base station (BS) implements AUD before data decoding. We use the orthogonal matching pursuit (OMP) algorithm to solve the CS problem due to its straightforward implementation and extend it to the multichannel case. Specifically, we propose a method in which the BS performs AUD independently in each channel, and the final list of detected users is the union of the lists of all channels. We assess the reliability of this protocol and the standard single-channel case in several setups. We show that having a sparser signal is significantly more beneficial to AUD than frequency diversity in most cases where the pilot length is short or multiple antennas are available at the BS. On the other hand, as the pilot length becomes longer and multi-antenna receive diversity is unavailable, investing in frequency diversity becomes more relevant, and a tenfold AUD performance improvement can be achieved.

The remainder of the letter is organized as follows. We describe our system model in Section II, and present the AUD problem and our proposed method in Section III. We provide numerical results in Section IV discussing the sparsity-diversity trade-offs and conclude the letter in Section V.

II. SYSTEM MODEL

Consider an mMTC deployment with uplink frequency channels \mathcal{F} , each denoted by $f \in \mathcal{F}$, with $f = \{1, 2, \dots, F\}$. During a preliminary registering phase, the users connect to the network, engaging in key exchange with the BS. Subsequently, the BS assigns channel resources and unique pilot sequences to the users. Note that herein, a set Q_f of $Q \triangleq |Q_f|$ users operate in channel f, while $Q_f \cap Q_g = \{\emptyset\}, f \neq g$, is not always true if users are allowed to transmit replicas in several channels. The users are single-antenna devices while the BS is equipped with M antennas. Time is divided into transmission opportunity intervals, referred to as frame slots, comprising of T symbols, and with a duration shorter than the coherence interval. We assume perfect time synchronization, and at each frame slot, T_p symbols are dedicated to joint channel estimation and user activity detection. The remaining symbols are dedicated to data transmission. In this 3-phase system, we only tackle the AUD in the present work.

In a grant-free scheme, any user may start a transmission at any time, transmitting its assigned pilot followed by its data. Without loss of generality, we assume all the users have a probability p of becoming active, i.e., starting a transmission. This independent and random transmission pattern may lead to multiple users transmitting simultaneously, resulting in a superposition of signals at the receiver. A way to avoid unrecoverable signals is to assign orthogonal pilots to users. However, $T_p \ge Q$ is required for all pilots to be pair-wise orthogonal, which is generally unfeasible in an mMTC scenario. Instead, a list of non-orthogonal pilots is considered. We denote by $\phi_q \in \mathbb{C}^{T_p \times 1}$ the pilot sequence assigned to the q-th user, with $||\phi_q||_2 = 1$, while the sequences can be arranged to obtain the pilot matrix $\Phi_f = [\phi_1 \ \phi_2 \ \dots \ \phi_Q] \in \mathbb{C}^{T_p \times Q}$.

The channel gains between user $q \in Q_f$ and the BS in channel f are modeled by considering the impact of a large-scale fading term, $\beta_{q,f}$, and a small-scale fading term,



Fig. 1: System model with emphasis on channel f.

 $\mathbf{h}_{q,f} \in \mathbb{C}^{1 \times M}$, with $\mathbb{E}[|\mathbf{h}_{q,j}|^2] = 1$, such that $\mathbf{g}_{q,f} = \beta_{q,f}\mathbf{h}_{q,f}$ [18]. We assume that $\mathbf{h}_{q,f}$ is unknown and changes at each coherence interval cycle while $\beta_{q,f}$ is known by the users, such that power control can be implemented to result in the desired average SNR Γ at the BS. By arranging the channel gain vectors and taking into account the transmit power employed by users, we obtain the system matrix $\mathbf{X}_f \in \mathbb{C}^{Q \times M}$, with each row given by $\mathbf{x}_{q,f} = \sqrt{T_p \rho_{q,f}} \alpha_q \mathbf{g}_{q,f}$, where $\alpha_q = 1$ when the q-th user is active, $\alpha_q = 0$ otherwise, and $\rho_{q,f}$ is the transmit power. Then, at each frame slot, the received signal $\mathbf{Y}_f \in \mathbb{C}^{T_p \times M}$ at the BS in channel $f \in \mathcal{F}$, is given by

$$\mathbf{Y}_f = \mathbf{\Phi}_f \mathbf{X}_f + \mathbf{V}_f,\tag{1}$$

where $\mathbf{V}_f \in \mathbb{C}^{T_p \times M}$ represents complex white Gaussian noise. Since the noise has unitary variance, the resulting average SNR at reception is then controlled by setting $\rho_{q,f} = \Gamma/\beta_{q,f}^2$.

We illustrate the system model in Fig. 1 explicitly for channel f, but the model is valid for the other channels. Note that the grouping of the devices is not representative of their physical location and that our model admits the possibility of a single user operating in multiple different channels.

III. ACTIVE USER DETECTION

To effectively decode the received signal, the BS must first identify the users that are active in the corresponding frame, for which it can utilize its prior knowledge of the pilot sequences of the users. Specifically, on channel f, the BS must identify the non-zero rows of \mathbf{X}_f . Since the number of rows of \mathbf{X}_f is $Q \gg T_p$, this is an under-determined system, thus without a unique solution in general. However, at each frame slot, only a subset $\mathcal{K}_f \subset \mathcal{Q}_f$ of users are active, making the matrix \mathbf{X}_f to be row-sparse, with $K = |\mathcal{K}_f|$ denoting its sparsity. This problem can be solved by applying well-established CS techniques, such as the OMP algorithm. With these techniques, the BS can perform joint AUD and channel estimation to obtain $\hat{\mathcal{K}}_f$ and $\hat{\mathbf{X}}_f$, the estimate of the set of active users and an estimate of their channel conditions, respectively.

A. Multi-Channel AUD with Frequency Diversity

To explore frequency diversity, we propose a protocol in which users transmit copies of the same packets simultaneously across multiple channels. Let each user q be assigned a subset $C_q \subseteq \mathcal{F}$ of channels for transmission. Each user has access to exactly $C = |C_q|$ channels, and the list of users operating in each channel is known at the BS. To maintain the same spectral efficiency, we consider that the total number of users is QF such that QC users operate in each channel while maintaining the same activation probability p. Furthermore, the transmit power per channel is inversely proportional to the number of copies, i.e., $\rho'_{q,f} = \rho_{q,f}/C$, so that users adhere to the same power constraints as in the single-frequency method, leading to the target average SNR after reception.

Several approaches can be implemented to explore the multiple-channel setup. We have implemented four such approaches, three of which did not show any improvement when compared to the single-channel case. We list them below and briefly comment on their possible advantages and the cause of their poor performance when that is the case.

- Strict detection: perform the AUD in each channel independently, but only accept users detected in all their corresponding channels. This results in a low number of false positives but also limits the performance by not considering users that had their signals too attenuated in other channels.
- 2) Iterative detection: perform the AUD sequentially in each channel, detecting users and propagating their detection to the other channels where they transmit, iteratively removing their contribution to the received signal. This requires fewer operations at the BS, as each user needs to be detected only once, but causes many false positives.
- 3) Super-channels: combine the channels into "superchannels" by concatenating the received signals and extending the pilot matrix accordingly. This leads to $\binom{F}{C}$ such channels, and the BS searches only for the users operating exclusively in the *C* channels considered, treating signals of other users as interference. This increases the number of measurements available, but, when $C \neq F$, the interference from other users causes poor performance. When C = F, the extended pilots are not helpful in further differentiating users, causing no improvements.
- 4) Independent detection: perform the AUD in each channel independently, constructing a final list consisting of the union of all lists. This has a better balance of missed detections and false positives while being much simpler than the others in its implementation.

For the sake of brevity, we focus only on approach 4, which performs better than the other methods.

B. Orthogonal Matching Pursuit

Originally proposed in [19], the OMP is a greedy algorithm for CS. Due to its simple implementation and manageable computational complexity, OMP serves as a clear baseline for other algorithms, and thus we adopt it to evaluate our proposal. The basic idea behind OMP is to select the columns of pilot matrix Φ_f that have the highest correlations with the received signal \mathbf{Y}_f and iteratively remove their contribution until a stopping criterion is satisfied.

The OMP receives as inputs the signal \mathbf{Y}_f and the pilot matrix $\mathbf{\Phi}_f$. Initially, the list of detected users is $\hat{\mathcal{K}}_f = \emptyset$, and the residual signal is $\mathbf{R}_f^{(0)} = \mathbf{Y}_f$. At each iteration k, the correlation $s_{q,f}^{(k)} \in \mathbb{C}^{1 \times M}$ of the residual signal to the pilot sequence of user q is calculated as

$$s_{q,f}^{(k)} = ||\phi_q^{\mathsf{T}} \mathbf{R}_f^{(k-1)}||_2.$$
(2)

Then, the BS identifies the user whose pilot sequence has the highest correlation with the residual signal as

$$q^{(k)} = \operatorname*{arg\,max}_{q} s^{(k)}_{q,f},\tag{3}$$

updating the list of detected users as $\hat{\mathcal{K}}_{f}^{(k)} = \hat{\mathcal{K}}_{f}^{(k-1)} \cup q^{(k)}$. At each iteration k > 1, an auxiliary pilot matrix $\Phi_{f}^{(k)} \in \mathbb{C}^{T_{p} \times k}$ is updated as

$$\boldsymbol{\Phi}_{f}^{(k)} = \left[\boldsymbol{\Phi}_{f}^{(k-1)}, \, \boldsymbol{\phi}_{q^{(k)}}\right],\tag{4}$$

with $\Phi_f^{(1)} \triangleq \phi_{q^{(1)}}$. Then, an estimate of the channel is obtained by solving

$$\hat{\mathbf{X}}_{f}^{(k)} = \underset{\mathbf{X}}{\operatorname{arg\,min}} ||\mathbf{Y}_{f} - \boldsymbol{\Phi}_{f}^{(k)}\mathbf{X}||_{2}.$$
(5)

In our implementation, we solve it with the linear least squares method, thus the channel is estimated with

$$\hat{\mathbf{X}}_{f}^{(k)} = {\mathbf{\Phi}_{f}^{(k)}}^{+} \mathbf{Y}_{f}, \tag{6}$$

where $(\cdot)^+$ is the Moore-Penrose inverse operation. The residual signal is then updated with

$$\mathbf{R}_{f}^{(k)} = \mathbf{Y}_{f} - \mathbf{\Phi}_{f}^{(k)} \hat{\mathbf{X}}_{f}^{(k)}, \tag{7}$$

finalizing the k-th iteration. The OMP continues to run until the stopping criterion is met, and the final list of detected users in channel f is denoted by $\hat{\mathcal{K}}_f$. When K is known or estimated at the BS [20], the stopping criterion is k = K. When this value is unknown, a different approach should be considered. For instance, due to the difficulty of obtaining this value in a practical scenario, we consider a threshold approach, allowing the algorithm to run while $s_{q,f}^{(k)} \ge \delta$ for any q. In practice, δ must be carefully selected, as large values lead to many false negatives, while small values lead to many false positives, compromising the accuracy.

IV. NUMERICAL RESULTS

In this section, we analyze the performance of the considered system when varying three main network parameters, namely the number of copies C each user transmits, the length T_p of the pilot sequence, and the activation probability p. We define the balanced accuracy A as

$$A = \frac{1}{2} \left(\frac{|\cup_{f \in \mathcal{F}} \operatorname{TP}_f|}{K} + \frac{|\cup_{f \in \mathcal{F}} \operatorname{TN}_f|}{Q - K} \right),$$
(8)

where $\operatorname{TP}_f = \hat{\mathcal{K}}_f \cap \mathcal{K}_f$ is the list of active users correctly identified, and $\operatorname{TN}_f = (\mathcal{Q}_f \setminus \hat{\mathcal{K}}_f) \cap (\mathcal{Q}_f \setminus \mathcal{K}_f)$ is the list of inactive users correctly identified. The balanced accuracy



Fig. 2: Balanced inaccuracy as a function of the SNR and for several combinations of F and C in the M = 1 setup.

is particularly well-suited for classifiers dealing with unbalanced class distributions, which is the case in mMTC since $K \ll (Q - K)$. In this letter, we utilize its complement, the balanced inaccuracy 1 - A, as the main performance metric. We present the average balanced inaccuracy for 10^5 Monte-Carlo simulations for each considered case. The final results are the minimum achieved in each setup, with the threshold δ optimized for each configuration.

The pilots are generated by drawing symbols from a complex Bernoulli distribution [18], with each sequence designed such that $||\phi_q||_2 = 1$ and each entry is randomly selected from the possible symbols $(\pm 1 \pm i)/\sqrt{2T_p}$. Assuming the channels are subject to Rayleigh fading, each element of $\mathbf{h}_{q,f}$ is distributed following a standard complex normal distribution. Moreover, we set Q = 256 users and p = 1/Q, unless specified otherwise.

A. Impact of the Number of Copies

We start our analysis by evaluating the potential performance gains from diversity in the base scenario described earlier. The number of channels is varied from F = 1 to F = 4, with the corresponding number of copies varied from C = 1 to C = F, for several values of SNR and for M = 1and $T_p = 8$. The results presented in Fig. 2 indicate that, in this specific setup, the added diversity does not improve the system performance but worsens it as the number of copies increases. Here, the sparsity level decreases inversely proportional to C, and the pilot length is not sufficient to provide significant differentiation among the users, causing the BS to often mistakenly select inactive users, as their pilot may be correlated to the superimposed signal. An interesting behavior in this case is the similar performance regardless of F, but dependent on C, as this parameter is what impacts the sparsity level in each channel. This behavior can be further observed for F > 4, but we use F = 4 as the default herein.

B. Impact of the Pilot Length

We continue our analysis aiming to understand the impact of the pilot length in this new scenario. Since the increase of measurements given by a greater T_p serves the purpose of



Fig. 3: Balanced inaccuracy as a function of the pilot length in the M = 1 setup.



Fig. 4: Balanced inaccuracy for number of copies as a function of M, in the $T_p = 20$, SNR = 10 dB and F = 4 setup.

differentiating more precisely between possibly active users, we vary the pilot length from $T_p = 8$ to $T_p = 32$. In this new setup, we compare the performance of the system under three SNR conditions, for deployments with F = 4 and $C = \{1, 2\}$.

For the case with a single antenna BS shown in Fig. 3, as the pilot length increases, increasing the number of copies is favorable compared to C = 1, with performance gains of up to one order of magnitude when SNR = 20 dB. An indiscriminate increase in C is not encouraged, though, as optimal values of C generally vary between C = 2 and C = 3. As T_p increases, the frequency diversity gains, that is, the possibility of a copy of a signal to be detected in different channels, are beneficial to the system as it is more unlikely that a false detection takes place. In the meantime, strong signal attenuation in a different channel is not a game-breaker, as it can facilitate other users to be correctly detected.

As indicated in Fig. 4, with the increase of M, however, severe signal attenuation is less relevant due to the multiple copies collected, and sparsity is favored, as the more accentuated superposition of the pilots generates more errors when C > 1. Fundamentally, spatial diversity in reception plays a similar role to frequency diversity in transmission: obtaining redundant replicas of signals to improve user detection likelihood. But, unlike transmission diversity, reception diversity does not incur the drawback of damaging the signal



Fig. 5: Balanced inaccuracy as a function of pQ in the M = 1 setup with SNR = 20 dB and $T_p = 32$.

sparsity. This significantly impacts the AUD's performance, discouraging the use of frequency diversity when the BS employs multi-antenna reception capabilities. When that is the case, an antenna count of M = 3 with $T_p = 20$ already results in a performance comparable to the setup with M = 1, C = 2, and $T_p = 32$. In some cases, this is preferred as the signal processing is less demanding and the frame can be used to transmit more data, although it comes with the cost of more material resources.

C. Impact of the sparsity level

Lastly, we vary the probability of activation from p = 0.25/Q to p = 8/Q in a setup with F = 4, and $C = \{1, 2, 3, 4\}$, as presented in Fig. 5, where set M = 1, $T_p = 32$ and SNR = 20 dB. The figure can be split into three different regions: $p \le 1/Q$, 1/Q , and <math>p > 2.5/Q. In the first region, the expected value of K is generally below 1, and the diversity gain introduced by the copies significantly improves performance, especially for higher values of C. In the second region, 1 < C < 4 has the best performance, with C = 2 being generally the best option, as with C = 3 the sparsity levels decline quickly. In the third region, however, the sparsity degradation from the introduced diversity starts to severely limit the performance in all cases where $C \neq 1$, and C = 1 is once again preferred.

V. CONCLUSIONS

In this letter, we explored the effects of frequency diversity in CS-based AUD, in a protocol in which users transmit copies of their message across C channels. We maintain the same spectral efficiency when compared to C = 1, which in turn decreases the sparsity level in each channel. We show that the compromise between frequency diversity and sparsity level hugely impacts the performance of the networks when temporal resources like pilot length are limited, users transmit frequently, or when there is an increase in the number of receive antennas, and C = 1 emerges as the preferred choice. However, our results demonstrate the potential of the multicopy scheme given additional resources allocated to extend the pilot length. Under favorable channel conditions, adopting

REFERENCES

- H. Shariatmadari, R. Ratasuk, S. Iraji, A. Laya, T. Taleb, R. Jäntti, and A. Ghosh, "Machine-type Communications: Current Status and Future Perspectives Toward 5G Systems," *IEEE Commun. Mag.*, vol. 53, no. 9, pp. 10–17, 2015.
- [2] X. Chen, D. W. K. Ng, W. Yu, E. G. Larsson, N. Al-Dhahir, and R. Schober, "Massive Access for 5G and Beyond," *IEEE Journal on Sel. Areas in Commun.*, vol. 39, no. 3, pp. 615–637, 2021.
- [3] N. H. Mahmood *et al.*, "White Paper on Critical and Massive Machine Type Communication Towards 6G."
- [4] S. R. Pokhrel, J. Ding, J. Park, O.-S. Park, and J. Choi, "Towards Enabling Critical mMTC: A Review of URLLC Within mMTC," *IEEE Access*, vol. 8, pp. 131796–131813, 2020.
- [5] B. Knoop, F. Monsees, C. Bockelmann, D. Peters-Drolshagen, S. Paul, and A. Dekorsy, "Compressed Sensing k-best Detection for Sparse Multi-user Communications," in 22nd European Signal Process. Conf. (EUSIPCO), 2014, pp. 1726–1730.
- [6] F. Monsees, M. Woltering, C. Bockelmann, and A. Dekorsy, "A Potential Solution for MTC: Multi-Carrier Compressed Sensing Multi-User Detection," in 49th Asilomar Conf. on Signals, Systems and Comput., 2015, pp. 18–22.
- [7] J. W. Choi, B. Shim, Y. Ding, B. Rao, and D. I. Kim, "Compressed Sensing for Wireless Communications: Useful Tips and Tricks," *IEEE Commun. Surveys & Tuts.*, vol. 19, no. 3, pp. 1527–1550, 2017.
- [8] J. A. Tropp and A. C. Gilbert, "Signal Recovery From Random Measurements Via Orthogonal Matching Pursuit," *IEEE Trans. on Inf. Theory*, vol. 53, no. 12, pp. 4655–4666, 2007.
- [9] P. Popovski, J. J. Nielsen, C. Stefanovic, E. d. Carvalho, E. Strom, K. F. Trillingsgaard, A.-S. Bana, D. M. Kim, R. Kotaba, J. Park, and R. B. Sorensen, "Wireless Access for Ultra-Reliable Low-Latency Communication: Principles and Building Blocks," *IEEE Netw.*, vol. 32, no. 2, pp. 16–23, 2018.
- [10] R. Kotaba, C. Navarro Manchón, T. Balercia, and P. Popovski, "Uplink Transmissions in URLLC Systems With Shared Diversity Resources," *IEEE Wireless Commun. Lett.*, vol. 7, no. 4, pp. 590–593, 2018.
- [11] C. Boyd, R. Kotaba, O. Tirkkonen, and P. Popovski, "Non-Orthogonal Contention-Based Access for URLLC Devices with Frequency Diversity," in *IEEE 20th Int. Workshop on Signal Process. Advances in Wireless Commun. (SPAWC)*, pp. 1–5.
- [12] Y. Cui, W. Xu, Y. Wang, J. Lin, and L. Lu, "Side-Information Aided Compressed Multi-User Detection for Up-Link Grant-Free NOMA," *IEEE Trans. on Wireless Commun.*, vol. 19, no. 11, pp. 7720–7731, 2020.
- [13] B. Li, J. Zheng, and Y. Gao, "Compressed Sensing Based Multiuser Detection of Grant-Free NOMA With Dynamic User Activity," *IEEE Commun. Lett.*, vol. 26, no. 1, pp. 143–147, 2022.
- [14] Y. Gao, J. Zheng, and B. Li, "Multiuser Detection of GF-NOMA With Dynamic-Active Users and Temporal-Correlated Channels," *IEEE Commun. Lett.*, vol. 26, no. 10, pp. 2380–2384, 2022.
- [15] Y. Li, Y. Zhan, L. Zheng, and X. Wang, "Device Activity Detection and Channel Estimation for Millimeter-Wave Massive MIMO," *IEEE Trans.* on Commun., pp. 1–1, 2023.
- [16] L. Yang, P. Fan, D. McLernon, and L. Zhang, "Data-Aided Active User Detection With False Alarm Correction in Grant-Free Transmission," *IEEE Wireless Commun. Lett.*, vol. 12, no. 1, pp. 143–147, 2023.
- [17] O. L. A. López, N. H. Mahmood, M. Shehab, H. Alves, O. M. Rosabal, L. Marata, and M. Latva-Aho, "Statistical Tools and Methodologies for Ultrareliable Low-Latency Communication—A Tutorial," *Proc. of the IEEE*, vol. 111, no. 11, pp. 1502–1543, 2023.
- [18] K. Senel and E. G. Larsson, "Grant-Free Massive MTC-Enabled Massive MIMO: A Compressive Sensing Approach," *IEEE Trans. on Commun.*, vol. 66, no. 12, pp. 6164–6175, 2018.
- [19] Y. Pati, R. Rezaiifar, and P. Krishnaprasad, "Orthogonal Matching Pursuit: Recursive Function Approximation With Applications to Wavelet Decomposition," in *Proc. of 27th Asilomar Conf. on Signals, Syst. and Computers*, 1993, pp. 40–44 vol.1.
- [20] O. L. A. López, G. Brante, R. D. Souza, M. Juntti, and M. Latva-aho, "Coordinated Pilot Transmissions for Detecting the Signal Sparsity Level in Massive IoT Networks," *IEEE Trans. on Commun.*, pp. 1–1, 2023.