
Automatic Interactive Evaluation for Large Language Models with State Aware Patient Simulator

Yusheng Liao, Yutong Meng, Yuhao Wang, Hongcheng Liu
Shanghai Jiao Tong University
{liao20160907, colane, hongcheng.liu}@sjtu.edu.cn

Yu Wang*, Yanfeng Wang
Shanghai Jiao Tong University
Shanghai Artificial Intelligence Laboratory
{wangyanfeng622, yuwangsJTU}@sjtu.edu.cn

Abstract

Large Language Models (LLMs) have demonstrated remarkable proficiency in human interactions, yet their application within the medical field remains insufficiently explored. Previous works mainly focus on the performance of medical knowledge with examinations, which is far from the realistic scenarios, falling short in assessing the abilities of LLMs on clinical tasks. In the quest to enhance the application of Large Language Models (LLMs) in healthcare, this paper introduces the Automated Interactive Evaluation (AIE) framework and the State-Aware Patient Simulator (SAPS), targeting the gap between traditional LLM evaluations and the nuanced demands of clinical practice. Unlike prior methods that rely on static medical knowledge assessments, AIE and SAPS provide a dynamic, realistic platform for assessing LLMs through multi-turn doctor-patient simulations. This approach offers a closer approximation to real clinical scenarios and allows for a detailed analysis of LLM behaviors in response to complex patient interactions. Our extensive experimental validation demonstrates the effectiveness of the AIE framework, with outcomes that align well with human evaluations, underscoring its potential to revolutionize medical LLM testing for improved healthcare delivery.

1 Introduction

Large Language Models (LLMs) such as ChatGPT OpenAI (2022) and GPT-4 OpenAI (2023) have significantly advanced many fields with their capability in understanding and generating natural language Kaddour et al. (2023); Hadi et al. (2023). Despite these advancements, their impact in the medical domain has not been equally profound Tian et al. (2024); Thirunavukarasu et al. (2023); Yang et al. (2023b). While there have been targeted efforts to develop LLMs specifically for the medical field—such as Medalpaca Han et al. (2023), Huatuo Wang et al. (2023), ChatDoctor Yunxiang et al. (2023), and DoctorGLM Xiong et al. (2023)—widespread practical deployment in clinical environments has not been achieved, with the notable exception of Med-PaLM 2 Singhal et al. (2023). This gap primarily arises from a misalignment between the prevalent evaluation methods and the unique requirements of clinical contexts Zhou et al. (2023); Minssen et al. (2023); Tu et al. (2024), which obstructs the effective utilization of medical LLMs in healthcare consultations. Notably, existing benchmarks predominantly evaluate medical LLMs based on their knowledge performance via standardized examinations Jin et al. (2019); Pal et al. (2022a); Jin et al. (2020a), and do not adequately measure their proficiency in essential clinical tasks, such as pre-consultation and diagnostic support Yang et al. (2023b). Moreover, the benchmarks designed for more complex clinical tasks often restrict these models to limited action spaces Wei et al.

*Corresponding Author

(2018); Chen et al. (2022) or reduce dynamic interactions to static question-answering scenarios Zhao et al. (2022); Liu et al. (2022); Bao et al. (2023); Zhang et al. (2023), failing to capture the full complexity of real-world clinical interactions. Webster (2023)

In response to these challenges, some research initiatives have employed numerous human participants to role-play as patients in real-time interactions with LLMs, thus simulating clinical scenarios to evaluate the capabilities of these models Tu et al. (2024). However, this approach incurs high costs and lacks scalability, limiting its utility for the extensive development and testing of medical LLMs Mehandru et al. (2024). Therefore, there is a pressing need to develop an affordable yet effective methodology for automatically assessing the clinical competencies of LLMs in the healthcare domain.

To address these gaps, in this paper, we propose a novel evaluation approach, Automatic Interactive Evaluation (AIE), as detailed in Figure 1. This methodology leverages the role-playing capabilities of LLMs to function as patient simulators Shanahan et al. (2023), facilitating dynamic multi-turn interactions with the doctor LLMs being assessed. Within the AIE framework, the concept of ‘doctor LLMs’ refers to large language models tested for their diagnostic interaction capabilities. These models must effectively gather comprehensive patient information through dialogue, culminating in a diagnosis or treatment recommendation. AIE aims to more faithfully simulate clinical scenarios, presenting a complex challenge that surpasses previous methodologies and offers a deeper assessment of LLM capabilities within a practical healthcare context. To our knowledge, this is the first evaluation that interactively validates the consultation abilities of LLMs through such a patient simulator.

Additionally, inspired by task-oriented dialogue systems Wen et al. (2016), we have developed a unique construct for the patient simulator named the State Aware Patient Simulator (SAPS). This innovative simulator comprises three main components: a state tracker, a memory bank, and a response generator. Together, these components enable the realistic simulation of patient-doctor interactions. At each dialogue turn, the state tracker classifies each action taken by the doctor LLM into predefined categories, which allows SAPS to retrieve the most relevant information from the memory bank and generate appropriate responses. This structured approach enables SAPS to adapt its responses based on the varying behaviors of the doctor, facilitating a nuanced analysis of the decision-making processes typical in medical consultations. Importantly, we have defined 10 categories of actions, refined through preliminary experiments, based on their nature and effectiveness in clinical interactions. This categorization is critical for tailoring the responses of SAPS, ensuring that the simulated dialogues closely replicate authentic clinical conversations.

The empirical evaluation of AIE involves a two-step process. Initially, the effectiveness of SAPS is validated against a simulated patient test set derived from actual hospital cases, demonstrating its superior ability to mimic human patient behaviors accurately. Subsequently, the evaluation metrics, developed based on human and patient preferences and aligned with standards such as the UK General Medical Council Patient Questionnaire (GM-CPQ) and principles from the consensus on patient-centered communication (PCCBP) King & Hoppe (2013), are assessed for their correlation with human judgments. This dual-phase evaluation underscores the potential of AIE and SAPS to revolutionize the assessment of medical LLMs, offering insights into their applicability in real-world clinical settings.

Table 1: Definitions of the doctor LLM’s action and the corresponding response requirements of the patient simulator.

Doctor Actions	Actions Description	Patient Required Behaviors
Initialization	The first action in the consultation conversation	Reply with chief complaint
Conclusion	Make a diagnosis or reach the maximum conversation length	None
Effective Inquiry	The inquired information is contained in the patient’s information	Reply with corresponding information
Ineffective Inquiry	The inquired information is not contained in the patient’s information	Negation
Ambiguous Inquiry	The inquiry is too vague or too broad	Request the inquiry more specific
Effective Advice	The results of the recommended exams and test are contained in the patient’s information	Reply corresponding results
Ineffective Advice	The results of the recommended exams and test results are not contained in the patient’s information	Follow advice
Ambiguous Advice	The recommendations are too vague or too broad	Request the recommendations more specific
Other Topic	The content of the sentence has nothing to do with the topic of medical consultation	Emphasis on medical consultation scenarios
Demand	Order or require the patient to complete actual physical actions	Emphasis on medical consultation scenarios




Figure 1: Overview of the Automatic Interactive Evaluation framework. **a** State Aware Patient Simulator (SAPS). SAPS structure includes a state tracker for classifying doctor behaviors, a memory bank for information retrieval, and a response generator for creating replies. Sentences with a dark background represent the parts that are activated within SAPS. **b** Conversation history between SAPS and Doctor LLM. The dialogue with a black border represents the latest round of dialogue. **d** Evaluated doctor LLM and its prompts. **e** Diagnosis. After the consultation dialogue, the doctor model must diagnose based on the information gathered during the conversation. 'Conversation' indicates the dialogue history.

2 Results

2.1 Overview

The purpose of introducing the evaluation framework is to automatically test the capabilities of doctor LLMs in diagnostic dialogues, such as gathering patient symptom information and providing effective recommendations. To more accurately assess the behavior of the LLMs in the AIE framework, we explicitly define the action space of the doctor LLMs as well as the corresponding requirements for patient simulator responses. By comparing the predefined requirements with the behaviors of LLMs during the interaction process, we can assess each interaction between the doctor LLMs and the patient simulator across multiple rounds of interaction.

As shown in Table 1, we pre-define 10 action types of the doctor LLMs and the corresponding response requirements. The action space primarily contains two types of actions: inquiries and advice, corresponding respectively to the two stages of medical consultation, information gathering, and diagnosis, thus ensuring the comprehensiveness of the action space. Building on this, we further define several special action types. Initialization and conclusion types represent the start and end of the consultation dialogue, respectively. At the beginning of the consultation, patients are required to provide their chief complaints and needs to initiate a multi-round dialogue. At the end of the consultation, no response is required from the patient. Additionally, to minimize hallucinations in the model during multi-round interactions, we have defined two extra types, enabling the simulated patient to alert the physician model when hallucinations occur, thereby ensuring the smooth progression of the

Patient Information	
<p>Female, 62 years old, recurrence of symmetrical facial features three years post soft palate adhesion surgery. Normal jaw opening and mouth opening type, postoperative changes to the soft palate, no obvious masses, local scarring, local induration, ill-defined margins, no tenderness, no ulceration or bleeding, no erythema, intact permanent dentition, and no other apparent abnormalities. Several nodules less than 1 cm in diameter palpable in the submandibular area, no enlarged lymph nodes in the neck. Blood work dated 2015-09-16 05:29: White blood cell count 7.4 x10⁹/L (N); red blood cell count 3.44 x10¹²/L (L); hemoglobin 103 g/L (L); hematocrit 0.304 (L); platelet count 236 x10⁹/L (N); segmented neutrophils 63.5% (N). Serum chemistry dated 2015-09-16 07:17: serum potassium 3.11 mmol/L (L); serum sodium 144 mmol/L (N); serum chloride 107 mmol/L (H). Examination: Histological cyrosection Result: "IB" lymph node with tumor tissue present (+).Examination: Histological cyrosection Specimens examined: LN "Submandibular 1" (one), "Submandibular 2" (one), both negative (-)</p>	
[Turn1, Initialization]	[Turn8, Ambiguous Advice]
<p>Doctor: Hello, I am your online doctor. How may I assist you today? Patient: I have had a mass in the right conchal area for over a year, which repeatedly ulcerates and bleeds for three months, and it is itchy and not healing.</p>	<p>Doctor: Thank you for providing more detailed examination results. Based on your medical history and MRI findings, the mass in the right conchal cavity is likely due to chronic inflammation, such as repeated episodes of mastoiditis or external auditory canal furunculosis, causing localized tissue thickening. Given the current findings of mild mastoiditis, antibiotic treatment may be necessary to control the infection, and the doctor may consider surgical intervention for the mass depending on the actual situation. Please be sure to follow medical advice, keep the ear dry and clean to avoid further infection or exacerbation of symptoms. Continue treatment under the guidance of a specialist, and undergo regular follow-ups to monitor changes in your condition. If any new symptoms appear or existing symptoms worsen, seek medical attention promptly.</p>
[Turn2, Effective Inquiry]	[Turn9, Conclusion]
<p>Doctor: Thank you for the description. First, I would like to know how large the mass is specifically? Patient: It is about 0.5cm in size.</p>	<p>Doctor: First, regarding antibiotic treatment, I suggest you book an appointment with an otolaryngology specialist for a detailed consultation. The doctor will prescribe suitable antibiotics based on your specific situation and inform you about the dosage and course of treatment. During the course of antibiotics, please ensure to take the medication on time and in the correct dosage; do not stop the medication prematurely, even if symptoms improve, to ensure the infection is completely cleared. As for the surgery, if the mass indeed requires surgical intervention, possible procedures might include excision of the external auditory canal mass or mastoidectomy for mastoiditis, depending on the findings of your MRI, physical examination, and the progression of the condition. Before the surgery, the doctor will explain the procedure steps, risks, and postoperative care, including preoperative preparations such as fasting times and preoperative tests. Regarding daily ear care, here are some basic tips: 1. Prevent water from entering the ear, especially during bathing or shampooing; you may lightly plug your ears with cotton balls, but do not insert them too deeply to avoid damaging the ear canal. 2. Do not attempt to clean your ears on your own, as this may damage the skin of the ear canal and cause infections or worsen inflammation. 3. If there are ear discharges, visit a hospital for a doctor to clean them; do not attempt to clean them yourself with cotton swabs or other objects. 4. Keep the auricle dry and clean; if necessary, under doctor's guidance, use specialized ear drops to keep the ear canal moist and prevent infections. 5. Focus on boosting your immune system, ensure adequate rest, eat a balanced diet, and engage in moderate exercise. Please follow these recommendations and visit a hospital as soon as possible to have a face-to-face discussion with an ENT specialist. They will provide a more personalized treatment plan and care guidance.</p>
[Turn3, Ineffective Inquiry]	
<p>Doctor: Understood. Has the mass shown any tendency to grow or harden? Patient: No, there hasn't been any noticeable change in the size or hardness of the mass.</p>	
[Turn4, Ineffective Inquiry]	
<p>Doctor: Good, I understand. Is there any pain on the surface of the mass or any changes in the skin color? Patient: There is no pain, and the skin color has not changed.</p>	
[Turn5, Ineffective Inquiry]	
<p>Doctor: I understand. This condition may be caused by otitis externa, an external auditory canal cyst, or other skin lesions. Have you had any instances of water entering the ear, frequent ear cleaning, or ear injuries? Patient: No, I haven't had any instances of water entering the ear, frequent ear cleaning, or ear injuries.</p>	
[Turn6, Ineffective Inquiry]	
<p>Doctor: I understand. Have you previously suffered from ear diseases or is there any family history of genetic ear diseases? Patient: No, I have not had any ear diseases before, and there is no family history of genetic ear diseases.</p>	
[Turn7, Effective Advice]	
<p>Doctor: Based on your description, it is likely a benign mass in the external auditory canal, such as an epidermoid cyst or a polyp. However, to confirm the diagnosis and rule out malignant changes, I recommend that you visit an otolaryngology (ENT) department at a hospital as soon as possible for a specialized examination (such as otoscopy) and necessary imaging studies (like temporal bone CT). Also, because the mass recurrently ulcerates and bleeds and does not heal, it requires local medical treatment and appropriate medication. Please do not attempt to squeeze or handle it yourself to avoid aggravating the infection or causing other complications. Patient: I have not experienced any symptoms of fever, fatigue, or other discomforts recently. I visited the Otolaryngology Department at Fudan University Affiliated Eye, Ear, Nose, and Throat Hospital, where an enhanced MRI of the ear was performed. The MRI findings showed slight thickening of the soft tissue in the top and posterior walls of the cartilaginous segment of the external auditory canal, and the conchal area of the right auricle, with mild mastoiditis on the right side.</p>	

Figure 2: Case examples of the consultation conversation between the doctor LLM Qianwen (noted as **Doctor**) and the patient simulator SAPS (noted as **Patient**). Each round is numbered and noted with the corresponding doctor LLM action category. The patient information is included above the conversation example.

multi-round dialogue. Notably, the actions of inquiry and advice during the consultation process are crucial for evaluating the doctor LLMs. Consequently, we have divided these two main behaviors into three subcategories: effective, ineffective, and ambiguous. The effective category refers to inquiries and recommendations that elicit information about the patient's symptoms and examination results. The ineffective category denotes actions that fail to obtain patient information, while the ambiguous category pertains to inquiries and recommendations that are overly broad. The case study of the consultation conversation and the action categories are shown in Figure 2. The details of the action definition are further discussed in Section 4.2.1. Based on the predefined action space, we can assess the performance of the patient simulator and the doctor LLMs in the multi-turn consultation conversations.

In this section, we first analyze the performance of the SAPS in multi-turn interactions to ensure its effective engagement with doctor LLMs. Subsequently, the SAPS and doctor LLMs' diagnostic dialogues are evaluated and scored using three types of methods: human evaluation and two forms of automatic evaluation, including GPT-4 evaluation Liu et al. (2023) and automated metric evaluation. We then analyze the correlation among the results of these three methods to validate the appropriateness of indicators. Finally, the performance of the doctor LLMs in multi-turn diagnostic dialogues is examined on the publicly available benchmarks to demonstrate the scalability of the AIE framework. This comprehensive approach underscores the efficacy of the framework in assessing doctor LLMs within the context of clinical consultations.

2.2 Datasets

As there is no prior work that uses AIE to assess the performance of doctor LLMs, we have developed two test sets. The first set aims to validate the effectiveness of the SAPS framework, while the second is for the AIE framework. We will outline the details of these two datasets below.

2.2.1 Patient Simulator Test Sets

We randomly select 50 real hospital cases to represent patient information. We use GPT-4 to simulate the roles of both doctor and patient, creating 10 rounds of dialogue for each case. Depending on the dialogue context, GPT-4 can generate question-answer pairs based on preset doctor LLM action types. Human reviewers then refine the answer and action type for each question. This process produces 4000 test questions in total. These can evaluate how patient simulators react to different actions across various context lengths and effectively measure their interactive performance in consultation dialogues.

2.2.2 Doctor LLMs Test Sets

We establish two datasets to evaluate doctor LLMs using real cases and public datasets. The first dataset, *HospitalCases*, includes 50 real hospital cases that do not overlap with the patient simulator test set. Each case comprises patient information, examination results, and diagnoses. We utilize GPT-4 to generate four similar yet distinct diseases as distractors, which are formatted as multiple-choice questions. The second dataset, *MedicalExam*, encompasses 150 cases chosen from five public clinical examination datasets, including MedQA (Jin et al., 2020b), MedMCQA (Pal et al., 2022b), MMLU (Hendrycks et al., 2021), SelfExam (Kung et al., 2023), and QMAX. These cases feature extensive patient information and diagnosis-related questions.

2.3 Results of Patient Simulators

In the analysis of the patient simulator’s performance, we approach the evaluation from two perspectives, encompassing six dimensions in total. The first perspective focuses on how much patient information is exposed in the interaction, which is dissected into three indicators. For effective inquiries, ‘Accurate’ measures whether the responses of the patient simulator are complete to the question of the doctor LLMs, and ‘Passive’ assesses whether the patient simulator is over-responding. For ineffective inquiries, ‘Cautious’ evaluates whether the patient simulator leaks the patient information without any effective question. The second perspective analyzes the behavior of the doctor LLMs. ‘Honest’ measures whether the patient simulator denies information that does not exist in patient information, while ‘Guidance’ and ‘Focus’ are indicators that come into play when the doctor model’s inquiries are not sufficiently professional or deviate from the consultation topic, where the patient simulator should guide or prompt the doctor LLMs. The calculations of these metrics are discussed in Section 4.4.1.

The challenge of the patient simulator test set is that the patient simulator is required to accurately identify the type of each question presented and respond according to predetermined requirements. We compare the performance of the LLM-based patient simulator with the human-acted patient, which can determine the effectiveness and accuracy of the patient simulators in consultation dialogues. As illustrated in Fig. 3a, the SAPS demonstrates a performance that is closer to that of humans compared to other patient simulators. Additionally, its performance across different rounds of the dialogue is more consistent and even exhibits greater stability in scores than human participants. To analyze the performance of the patient simulators further, we conduct a comparison of the correlation between the models and humans at the instance level. As shown in Fig. 3b, the SAPS demonstrates a higher correlation with human behavior in terms of the quantity of information expression. Notably, the SAPS shows improvements across all metrics when compared to the standard GPT-4 model. This suggests that the SAPS is more effective in replicating human-like interactions in the medical context. Additionally, Fig. 3c presents the confusion matrix




Figure 3: **Results on the patient simulator test set.** We employ the six predefined patient metrics to evaluate the performance of different models and humans. **a** Change of metrics over dialogue turns. The bars and the lines in each plot describe the average scores and the relationship between the metrics and the number of dialogue turns, respectively. **b** Correlation between patient models and humans. Corr means the value of the correlation factor. **c** Confusion matrix for state tracking between patient agent and humans.

of the SAPS and human participants in the classification of the doctor LLM actions. It is found that the accuracy of the SAPS is slightly worse than that of the humans, which is still comparable and acceptable. In summary, the SAPS demonstrates superior stability and a higher correlation with human behavior than other patient simulators in the test set. The results ensure that the SAPS can reliably play the role of a patient, facilitating effective and realistic interactions with the doctor LLMs.

MODEL	ChatGLM3	InternLM	BaiChuan	XingHuo	QianWen	ChatGPT	GPT-4
DIAGNOSIS	48.00±7.14	38.00±6.93	44.00±7.09	34.00±6.77	56.00±7.09	60.00±7.00	64.00±6.86
COVERAGE	25.55±1.95	22.37±1.83	23.84±2.24	34.27±2.97	33.82±2.46	31.33±2.51	38.69±2.75
INQUIRY_ACC	22.75±3.11	15.36±3.47	11.64±1.92	31.38±3.80	24.80±2.94	27.22±3.43	22.52±2.54
INQUIRY_SPECIFIC	72.32±3.35	49.79±5.63	62.51±2.79	76.58±2.22	94.33±1.42	82.37±3.31	90.60±2.43
INQUIRY_LOGIC	30.00±2.29	25.82±1.97	26.94±2.61	35.00±2.55	37.68±2.62	35.22±2.61	41.67±2.71
ADVICE_ACC	13.00±3.91	13.76±4.07	8.33±3.57	20.17±5.41	24.80±4.71	15.67±3.30	17.83±4.37
ADVICE_SPECIFIC	27.50±5.75	32.83±5.62	18.33±4.65	50.83±6.95	55.97±5.29	29.67±3.64	48.50±5.93
DISTINCT	66.66±1.75	62.22±3.14	86.02±0.47	65.09±2.51	82.64±0.55	74.60±1.25	78.19±0.48
AVG_TURN	9.82±0.08	9.32±0.23	9.06±0.20	8.72±0.21	9.28±0.14	9.18±0.19	9.50±0.13
AVG_LEN	48.26±2.98	46.24±2.43	39.44±2.40	87.00±6.62	83.88±4.66	55.80±2.56	75.62±3.43

Table 2: Results of the automatic metrics on HospitalCases. The results are shown in the formation ‘mean ± standard error.’




Figure 4: **Success rate without tie in comparative evaluation of doctor LLMs.** The first and second rows show the results of the human evaluation from the perspective of the doctor and patient, respectively. The third and fourth rows show the results of the GPT-4 evaluation from the perspective of the doctor and patient.

2.4 Comparative Evaluation on HospitalCases

Based on the patient simulation validation, we conduct a comparative evaluation through multi-round diagnostic dialogues, which are generated by interaction between the doctor LLMs and the SAPS. In line with the criteria proposed by the UK General Medical Council Patient Questionnaire (GMCPQ) and principles published in reviews of the consensus for best practices for patient-centered communication (PCCBP) in medical interviews (King & Hoppe, 2013), we establish five metrics each from the perspectives of the doctor and patient to score the consultation dialogues.

To avoid the instability caused by absolute scoring, we employ comparative evaluation to assess the consultation dialogues. Specifically, the dialogues of different doctor LLMs for the same case are compared pairwise to determine the more effective LLMs. We hire three medical students and normal people to play the role of doctor and patient, respectively, and choose their preference from the perspective of each metric. Additionally, we also employ various prompts to enable GPT-4 to conduct automatic evaluations from the perspectives of both the doctor and patient.

We calculate and compare the success rates of different models in diagnosing and managing the cases accurately. The results are shown in Fig. 4. The performance of QianWen stands out as the best among the models, showing the highest win rate in nearly all metrics compared to others. GPT-4 follows, exhibiting strong performance but not as dominant as QianWen. The weakest model appears to be InternLM. Overall, open-source smaller models underperform compared to closed-source larger models, aligning with findings from previous evaluations.




Figure 5: Analysis of the correlation between automated metrics, GPT-4, and human assessment indicators. All indicators' correlations are tested. Considering the automated metrics are continuous, and GPT-4 and human assessments are ordinal, the Spearman correlation coefficient is used to calculate the correlation between different indicators. **a** assesses correlation across all test data. **b** the average human correlation coefficient between automated metrics and GPT-4 assessments. **c-e** explore correlations within specific subsets: **c** both models in the comparison are closed-source, **d** both models in the comparison are open-source, **e** one model is open-source and the other is closed-source.

Regarding the assessment perspectives of humans and GPT-4, GPT-4's evaluations are more polarized, indicating more extreme outcomes in terms of wins and losses within its assessment dimensions.

2.5 Automatic Metrics Evaluation on HospitalCases

In addition to comparative assessments, the study also involves evaluations of multi-turn diagnostic dialogues based on automated metrics. The SAPS can model the types of action, allowing for a quantitative assessment of doctor LLM behavior during diagnostic interactions. The details of the calculation of the metrics are discussed in Method. The results of the automatic evaluation are illustrated in Table 2.3. "COVERAGE" measures the proportion of patient information recalled during the consultation, with even the strongest model, GPT-4, achieving around 38%. 'INQUIRY/ADVISE ACC' reflects the effectiveness of inquiries and advice in eliciting patient information. In contrast, "INQUIRY/ADVISE SPECIFIC" measures the specificity of inquiries and advice, distinguishing them from vague or broad questions. It's noted that the models score higher in "INQUIRY SPECIFIC" compared to "ADVISE SPECIFIC," possibly due to developers limiting the model's ability

to offer direct advice for safety reasons. Additionally, there’s no direct correlation between “COVERAGE,” “DIAGNOSIS,” and “INQUIRY/ADVICE ACC,” as they measure different aspects of the diagnostic process: information recall, the effectiveness of recalled information for diagnosis, and the behavior of the model in interaction, respectively.

2.6 Metrics Correlation Analysis

In this section, we integrate a comprehensive set of evaluation metrics, combining human assessments from two perspectives, GPT-4 assessments from two perspectives, and various automated metrics, amounting to a total of 28 dimensions. The analysis of the correlations among these metrics is pivotal. Fig. 5a displays the interrelationships between all these metrics. From an inter-group correlation perspective, there is a significant correlation between GPT-4 annotations and human annotations. Although the corresponding metrics are not exact matches, GPT-4 shows a high degree of correlation with human judgment overall, suggesting its potential to substitute human annotations. The correlation between automated metrics and human annotations is relatively lower, with DISTINCT showing the highest overall correlation with human annotations, indicating that dialogue fluency remains a key factor in evaluating diagnostic dialogues. In terms of intra-group correlation, the metrics within the human and GPT-4 annotations show greater correlation, suggesting an overlap in these indicators. In contrast, automated metrics display less intra-group correlation, indicating their ability to independently evaluate different dimensions of the diagnostic dialogue. In addition, Fig. 5b provides a more detailed comparison of the average correlation coefficients between automated metrics, GPT-4 assessments, and human indicators. It reveals that all GPT-4 indicators have higher average human correlation coefficients than automated evaluation metrics, with the highest being scores from the perspectives of doctors and patients. Among automated metrics, DISTINCT has the highest correlation, followed by the ratio of specific inquiries and advice in the diagnostic dialogue. The lowest correlation is observed with the accuracy of diagnostic outcomes.

2.7 Correlation Analysis among Different Subsets

This study classifies the seven tested models into two categories based on the correlation among metrics and model types: closed-source models, which are typically more powerful but have undisclosed parameter sizes, and open-source models, which have publicly accessible parameters but are usually smaller and less efficient. Comparisons are made within three subsets: both models are closed-source, open-source, or one of each.

Figure 5c-e displays the correlations of metrics within these comparative subsets, offering insights into how model origin influences metric correlations. The analysis across different subsets of models shows varying levels of correlation among human annotations, GPT-4 evaluations, and automated metrics. In closed-source model comparisons (Fig. 5c), human evaluation metrics exhibit low correlation, suggesting these metrics independently assess different capabilities of the models. GPT-4 metrics show higher redundancy, indicating less distinction in evaluation aspects. In addition, the lower correlation between GPT-4 evaluations and human assessments in the subset of high-performance models suggests that GPT-4 might not yet fully replace human evaluation when comparing top-tier models. This underscores the importance of human insight in nuanced evaluation scenarios involving highly proficient models. In Fig. 5d, which examines the second subset of comparisons (open-source models), there is a relatively higher correlation between human and GPT-4 indicators, with the automated DISTINCT metric showing strong relevance across evaluation metrics. This pattern emphasizes the importance of dialogue fluency when assessing lower-performing models, highlighting its key role in distinguishing and understanding the conversational capabilities of these models. In Fig. 5e, which compares a combination of open-source and closed-source models, there is a significant correlation among automated metrics, human evaluations, and GPT-4 assessments. This heightened correlation is likely attributed to the clear performance difference between the models in this group, enabling easier differentiation of model capabilities. Consequently, the metrics show a higher alignment, indicating a consensus on the relative strengths and weaknesses of the compared




Figure 6: Analysis of the evaluated doctor LLMs on MedicalExam datasets. **a** The average win rate of each metric within the GPT-4 evaluation. We use the best results as the maximum value for each metric in the radar chart. **b** Comparison of the diagnostic score between the Multiple-Choice Question Evaluation (MCQE) and AIE among five subsets. **c** The proportion of the action categories within each turn. **d** The coverage and diagnostic scores depend on different consultation conversation lengths. The red lines connecting circular red dots represent diagnostic scores, while the blue box plots indicate coverage scores.

models. It underscores the unique evaluation results when comparing models of different origins and capabilities.

MODEL	ChatGLM3	InternLM	BaiChuan	XingHuo	QianWen	ChatGPT	GPT-4
DIAGNOSIS	30.67±3.78	30.00±3.75	30.00±3.75	15.33±2.95	30.67±3.78	41.33±4.03	53.33±4.09
COVERAGE	27.95±1.25	15.36±0.96	21.16±1.25	28.08±1.40	31.29±1.42	27.09±1.44	33.89±1.63
INQUIRY_ACC	21.88±1.46	11.94±1.43	16.22±1.81	21.44±1.61	23.98±1.54	17.69±1.39	23.68±1.63
INQUIRY_SPECIFIC	68.62±1.43	53.98±1.54	67.72±2.42	77.30±1.64	91.80±0.93	85.27±1.14	91.95±1.04
INQUIRY_LOGIC	41.27±0.82	28.78±0.91	35.61±1.03	40.48±1.02	42.59±0.90	40.51±1.07	42.74±0.99
ADVICE_ACC	3.17±1.36	6.00±1.64	6.49±1.51	5.61±1.66	10.97±2.08	7.72±1.76	11.72±2.15
ADVICE_SPECIFIC	28.72±3.30	42.22±3.33	34.00±3.19	54.78±3.44	72.17±2.63	55.33±2.84	66.33±3.04
DISTINCT	77.51±0.75	95.53±0.34	86.48±1.16	86.72±0.74	83.76±0.26	80.59±0.32	79.14±0.32
AVG_TURN	12.13±0.22	11.54±0.22	11.41±0.26	10.57±0.25	11.89±0.17	10.35±0.10	11.89±0.19
AVG_LEN	69.41±3.76	42.94±1.32	42.15±1.54	57.86±2.64	60.40±1.59	29.95±0.70	63.62±1.49

Table 3: Results of the automatic metrics on MedicalExam. The results are shown in the formation ‘mean ± standard error.’

2.8 Automatic Evaluation on MedicalExam

We further test doctor LLMs on the MedicalExam dataset. In Fig. 6a, the average win rate of doctor LLMs across various metrics in a GPT-4 evaluation is displayed, showing Qianwen outperforming in almost all metrics, while other models like ChatGLM and XingHuo excel in inquiry and diagnosis, respectively. Table 2.7 presents results from the automated metric evaluation. It is found that score values are lower than the ones in HospitalCases, which indicates that the MedicalExam is more complex and challenging. Besides, we also found that the diagnostic result is directly contained in the patient information of HospitalCases, while MedicalExam requires further reasoning based on the collected information, which makes it harder to choose the correct diagnostic result.

2.9 Evaluation Format Analysis

Figure 6b shows the comparison of the diagnostic score between the Multiple-Choice Question Evaluation (MCQE) and AIE among five subsets of MedicalExam. For the MCQE, the doctor LLMs can directly make the decision based on all the patients' information. It is observed that diagnostic scores of AIE are generally lower than those from MCQE because the diagnosis in AIE is based on information collected by the doctor model itself, which often is less comprehensive than the whole patient information. Surprisingly, in some cases, AIE diagnostic scores exceed those from MCQE, as seen with ChatGLM on MedQA (AIE 0.37 vs. MCQE 0.27), XingHuo on MedMCQA (AIE 0.47 vs. MCQE 0.43), and BaiChuan on QMAX (AIE 0.40 vs. MCQE 0.30). This phenomenon is not observed with simpler datasets like MMLU or with models possessing strong reasoning abilities like GPT-4. Poor-performing models may not fully utilize complete patient information for reasoning, whereas interactive dialogue can enhance diagnostic capabilities. However, insufficient information collection during interaction directly impacts the diagnostic scores for stronger models, indicating a need for improving interaction capabilities in high-performing models.

2.10 Turn Analysis

Figure 6c shows the proportion of the actions. Similar to real doctors, doctor LLMs initiate consultations with simulated patients by asking questions to gather information before offering advice and diagnosis. Notably, a significant proportion of the initial inquiries are ambiguous. With feedback from the simulated patient, models with better performance quickly reduce the frequency of ambiguous inquiries. In contrast, while models with poorer performance also improve, they remain a portion of ambiguous inquiries, indicating a difference in the ability to refine questioning based on interaction quality.

Figure 6d shows the coverage score and the diagnostic score with different lengths of the conversation. As dialogues progress, the proportion of patient information collected increases. The distribution of dots outside the box plots indicates significant variance in the difficulty of information collection across different cases. It is worth noting that diagnostic scores do not strictly correlate with the coverage score, suggesting that the helpfulness of collected information to the final diagnosis may be minimal or that the complexity of multi-round dialogues impacts model reasoning. For stronger models like GPT-4 and QianWen, there's a stronger correlation between diagnostic and coverage scores.

3 Discussion

Current medical benchmarks for LLMs predominantly assess medical knowledge through standardized examination questions. However, these conventional tests fail to fully evaluate LLMs in clinical application scenarios, potentially impeding the development and practical implementation of medical LLMs. Despite recent strides in medical LLM interactions, there remains a significant gap in the comprehensive evaluation of interaction rationality and definitions Johri et al. (2023); Chen et al. (2023).

In this study, we introduce the Artificial Intelligence Evaluation (AIE) framework, an innovative, cost-effective solution that leverages role-playing to simulate clinical interactions. This

approach not only mimics real-life scenarios but enhances them, setting a new benchmark for testing the capabilities of LLMs. We meticulously define the action space for doctor LLMs and establish specific response requirements for our patient simulator, ensuring that the interactions are both meaningful and beneficial for patient care. Our analysis led to the identification of 10 distinct action-response types, optimizing the interaction process. A key innovation is the introduction of an 'ambiguous' category to address the frequent issue of LLMs producing verbose yet unhelpful responses. This strategic filter significantly improves communication efficiency and encourages deeper, more meaningful engagement between doctor LLMs and the patient simulator.

A major breakthrough in our research is the development of SAPS, a sophisticated patient simulator that sets new standards for realism and performance in simulating patient responses. SAPS's ability to mimic human-like responses with remarkable accuracy suggests its potential to replace human participants in specific training scenarios, thereby revolutionizing medical training by increasing scalability and reducing human resource dependency. The exceptional performance of SAPS across various metrics, notably its stability in extended multi-round dialogues, underscores its capability to effectively manage the dynamic and complex nature of real-life clinical interactions.

Our findings highlight that SAPS's responses bear a closer resemblance to those of human patients than previous models, enhancing the realism of the simulations and suggesting its potential to streamline the training process, making it more efficient and scalable. Furthermore, SAPS's sophisticated ability to interpret the actions of doctor LLMs during consultations provides invaluable insights into refining the decision-making and communicative strategies of the simulated doctors, which are critical for improving medical training programs.

Moreover, the evaluation of the AIE framework through automated methods reveals a significant alignment with human judgments, confirming the robustness of using GPT-4 for assessing the interaction capabilities of doctor LLMs OpenAI (2023). Correlation coefficients between GPT-4's evaluation metrics and human assessment indicators are impressively consistent, indicating that automated assessments within the AIE framework can effectively stand in for human evaluations. This alignment highlights the effectiveness of our specifically designed metrics in capturing essential aspects of interaction quality that resonate with human evaluators.

The experimental results from the AIE framework underscore a significant disparity between weak and strong models in multi-turn medical consultation dialogues. Strong models demonstrate a definitive advantage in both human evaluations and automated assessments. Additionally, the interaction process within the AIE framework offers the potential for enhancing the interactive capabilities of these models, as evidenced by the specificity and accuracy metrics in the correlation analysis. These metrics are crucial for refining diagnostic processes during consultations, thus enhancing the overall efficacy of the diagnostic task.

While this study significantly advances the validation of the AIE framework from multiple perspectives, it is important to acknowledge some inherent limitations of our research methodology. These limitations primarily stem from the observational approach used to define doctor actions and patient response criteria in our simulations, which might not capture the full scope and complexity of real-world medical interactions. As evidenced by the notable alignment of the SAPS model's responses with human behaviors within a specifically defined action space, the ongoing need to broaden and refine this space is clear as medical modeling technology evolves. Additionally, the reliability of the metrics used in our study varies; they are particularly effective in differentiating between models with significant performance differences but prove less capable when assessing models with similar performance levels. This variability in metric reliability also poses challenges in human evaluations, especially when attempting to discern fine distinctions among top-performing models.

Despite these challenges, the interactive evaluation methodology we introduce offers substantial potential for advancing research. This approach not only presents a more dynamic and realistic evaluation environment compared to traditional methods but also supports

the development and application of large language models across various domains beyond healthcare. The methodology is especially beneficial in fields that require authentic scenario testing, promising extensive applicability across diverse tasks that demand high fidelity in real-world interactions. This makes it an invaluable asset for the research community, poised to enhance the utility and effectiveness of language models in numerous applications. Mehandru et al. (2024)

4 Methods

4.1 Evaluated Large Language Models

In general, most existing LLMs can be divided into the general LLMs and the domain LLMs, which specifically refer to the medical LLMs in this paper. Preliminary experiments have shown that the instruction-following ability of many medical LLMs is compromised, causing them to fail multi-turn consultation tasks requiring complex instructions. As such, we are selecting general LLMs with strong instruction-following capabilities and bilingualism to maintain fairness in experimental comparison. For the closed-source models, ChatGPT (OpenAI, 2022), GPT-4 (OpenAI, 2023), Xinghuo, and Qianwen (Bai et al., 2023) are selected. For the open-source models, Internlm-20b (Team, 2023), Baichuan-13b (Yang et al., 2023a), and ChatGLM3-6b (Du et al., 2022) are selected. Specifically, we use the version gpt-3.5-turbo-1106 for ChatGPT and gpt-4-1106-preview for GPT-4. For XingHuo, we use the version of generalv3. For QianWen, we use the version of qwen_max. For the closed-source models, we use the ChatGLM3-6B available at <https://github.com/THUDM/ChatGLM3> for ChatGLM3-6b, Baichuan-13B-Chat available at <https://github.com/baichuan-inc/Baichuan-13B> for BaiChuan-13b, and InternLM2-Chat-20B available at <https://github.com/InternLM/InternLM> for InternLM-20b.

4.2 State Aware Patient Simulator

During the consultation conversation, the patient agent is required to provide tailored responses according to different types of questions. However, directly prompting LLMs makes it difficult to control the behavior of the patient simulator precisely. To enhance the precision of patient simulators in consultation dialogues, we introduce a State Aware Patient Simulator (SAPS). SAPS consists of three integral components: a state tracker that identifies and classifies the current action state of the doctor LLMs, a memory bank that stores various information and selects the appropriate memory according to the state, and a response generator that produces contextually relevant replies. This architecture allows SAPS to respond to a wide range of inquiries adaptively by understanding the consultation’s dynamic context, thereby generating responses that are both accurate and contextually appropriate for the evolving dialogue.

4.2.1 States definition and response requirements

Our approach categorizes the types of actions performed by doctors during medical consultations from two key perspectives: the nature of the actions and their effectiveness. The first perspective classifies the actions into distinct categories that cover the array of interactions a doctor might have during a patient consultation. The second perspective evaluates the effectiveness of these actions, concentrating on whether they successfully gather pertinent information and offer suitable advice. Consequently, we predefine 10 categories of states and their corresponding requirements in the consultation conversation as follows:

Initialization: Actions initiating the consultation between the doctor LLM and the patient simulator. In this phase, the doctor LLMs typically begin the consultation with a consistent approach, such as ‘Hello, I’m your doctor. How can I help you today.’ The patient simulator should briefly describe their main symptoms and primary concerns, offering a clear but brief overview of the health issues without delving into exhaustive detail.

Inquiry: This category involves the doctor LLMs asking the patient for information, which can be divided into three subclasses based on the effectiveness of the question. The first is

effective inquiries, including questions that are specific and correctly guide the patient to disclose their physical condition or relevant information. In this case, SAPS is designed to respond with the corresponding part of the patient information relevant to the question. This requirement maintains the accuracy of the patient’s information without altering its original meaning through rephrasing. The second is ineffective inquiries. This type refers to questions that are specific but fail to gather the patient information, such as asking for information that is not recorded in the patient information. In this case, the SAPS should indicate a denial or express uncertainty regarding the information requested to avoid providing misleading or fabricated information. The final is ambiguous inquiries, which represent questions without a specific focus and are overly broad. For this type of question, the patient should require the doctor to ask more specifically instead of directly providing a comprehensive response that covers a wide range of information. In our experiments, we observe that the doctor model could elicit more information from the patient simulator by repeatedly asking vague questions. However, such behavior does not align with the original intent of our testing framework, which aims to encourage the model to ask more specific and professional questions. This requirement is designed to prevent models from taking shortcuts within the framework.

Advice: This category includes recommendations made by the doctor model. Given that simulated consultations can’t involve actual medical examinations or obtain real-life results, we treat the doctor model’s advice as inquiry actions. This allows for a thorough evaluation of the model’s ability to provide actionable advice within the simulation’s constraints. We assume the SAPS can respond with advice if the results are included in the patient’s information, such as medication treatment or medical examination. Similar to inquiries, advice can also be divided into three subclasses: effective advice, ineffective advice, and ambiguous advice. Effective advice refers to suggestions where the patient’s information contains the results, and SAPS needs to respond with the corresponding information. Ineffective advice is when the patient’s information does not contain the results, and the patient should express negation. Ambiguous advice lacks specific practices, and like an ambiguous inquiry, SAPS needs to ask the doctor model for more specifics.

Demand: This category includes instances where doctors with LLMs ask patients to perform physical actions that are impossible during an online consultation. SAPS should deny these requests and remind the doctor that the consultation is online, making physical actions unfeasible.

Other Topics: This category includes all actions by Doctor LLMs that are not related to the diagnostic dialogue. These are inquiries and conversations that deviate from the main topic of the consultation and do not concern the patient’s symptoms or condition. In these situations, the SAPS is designed to redirect the doctor back to the consultation context, re-emphasizing the patient’s symptoms and concerns. This keeps the dialogue focused on the patient’s health issues, ensuring the consultation remains relevant and efficient.

Conclusion Category: Actions that signal the end of the consultation may include summarizing the visit, arranging a follow-up, or saying goodbye. In these instances, the patient model is not required to respond.

4.2.2 State tracker

The state tracker plays a role in categorizing the actions of doctor LLMs into a predefined type. The prediction process can be divided into three steps. The first step is to classify the current action into five main categories, excluding the initial category. This is because the initial category is fixed as the initial round of the consultation dialogues. SAPS classifies the action with the use of prompt as follows:

In the process of medical consultation, a doctor’s questions can be classified into five types:

- (A) Inquiry: The doctor asks the patient for medical and disease-related symptom information. Generally, questions with a ‘?’ that do not belong to categories (C) or (D) are included in this category.

-
- (B) Advice: The doctor suggests that the patient visit a hospital for consultation, undergo examinations, or provide certain treatment plans. Questions containing the keyword 'suggestion' belong to this category.
 - (C) Demand: The doctor asks the patient to perform certain actions for observation, cooperation, or sensation. Actions include but are not limited to opening the mouth, lying on the side, standing, pressing, etc.
 - (D) Other Topics: The doctor's questions do not pertain to the medical consultation context and are unrelated to medical diseases. This includes, but is not limited to, hobbies, movies, food, etc.
 - (E) Conclusion: The doctor has completed the consultation and does not require a response from the patient.

Based on the descriptions of the above question types, please choose the most appropriate category for the following <Doctor Question>:

<Doctor Question>: {{{question}}}
Question Type: (

To induce the LLMs to generate valid responses, we take advantage of the **logit bias** technique (Nori et al., 2023) to enforce the model only generate the category index. If the current action falls into the categories of inquiry or advice, the second step of classification is to determine whether the action is specific or ambiguous. For inquiries and advice, different prompts are used to facilitate this distinction. For the inquiries category, the prompt is shown below:

<Definition>:

[Specific]: <Question> has a certain specific direction. When asking about symptoms, it should at least inquire about specific body parts, symptoms, sensations, or situations. When asking about examination results, it should mention specific body parts, specific examination items, or abnormal situations. Note that if it's about specific medical conditions, like medical history, family history, chronic illnesses, surgical history, etc., they are always considered [Specific]. Specifically, if the <Question> contains demonstrative like "these" or "this", then it is related to the above and should belong to the [Specific].

[Ambiguous]: <Question> such as "Where do you feel uncomfortable?" or "Where does it feel strange?" without any specific information direction are considered [Ambiguous].

<Question>: {question}

Based on the <Definition>, determine whether the doctor's <Question> asks for [Specific] medical information from the patient or gives [Specific] advice. If so, directly output [Specific]. If not, output [Ambiguous].

For the advice category, the prompt is shown as below:

<Definition>:

[Specific]: <Advice> contains specific types of examinations or test (including but not limited to X-rays, MRI, biopsy, etc.), specific treatment plans (including but not limited to specific surgical treatments, exercises, diets, etc.), specific types of medication, etc.

[Ambiguous]: <Advice> broadly given without any specific examination/test, treatment plans, doctor’s orders, exercises, diets, and medication types are considered [Ambiguous]. As long as any of the above information appears, <Advice> does not fall into this category.

<Advice>: {question}

Based on the <Definition>, determine whether the doctor’s <Advice> asks for [Specific] medical information from the patient or gives [Specific] advice. If so, directly output [Specific]. If not, output [Broad].

If the action is determined to be specific, the next step is to assess whether there is a corresponding answer within the patient information. Similarly, we also prepare two types of prompts for the inquiry and advice:

<Definition>:

[Relevant Information]: <Patient Information> contains information asked in <Question>, including descriptions of having or not having the symptom, as long as there’s relevant content.

[No Relevant Information]: <Patient Information> does not contain the information asked in <Question>, and there’s no relevant content in the information.

<Patient Information>: {patient_info}

<Question>: {question}

Based on the <Definition>, determine whether <Patient Information> contains relevant information asked in <Question>. If [Relevant Information] is present, directly output the relevant text statement, ensuring not to include irrelevant content. If [No Relevant Information], then directly output [No Relevant Information].

<Definition>:

[Relevant Information]: <Patient Information> contains results of the examinations or treatment plans suggested in <Advice>, including any results related to the suggested examination items and treatment plans.

[No Relevant Information]: <Patient Information> does not contain results of the examinations or treatment plans suggested in <Advice>, including no mention of relevant examination items and treatment plans or no corresponding results.

<Patient Information>: {patient_info}

<Advice>: {question}

Based on the <Definition>, determine whether <Patient Information> contains relevant information about the measures suggested in <Advice>. If [Relevant Information] is present, directly output the relevant text statement, ensuring not to include irrelevant content. If [No Relevant Information], then directly output [No Relevant Information].

In conclusion, the predicted categories at each turn can be identified as:

$$\hat{s}_i = \Phi_{\text{STraker}}(D_i, \mathbf{M}_{\text{long}}) \quad (1)$$

where D_i indicates the doctor’s output of the i turn and Φ_{STraker} is also the LLMs.

4.2.3 Memory bank

Upon identifying the current action type of the doctor LLM through the state tracker, SAPS can selectively access different parts of the memory bank. This process enables the generation of SAPS responses, ensuring they are driven by and aligned with the categorized behavior type. The memory bank comprises three parts, each serving a specific function in facilitating realistic and adaptive interactions with the doctor.

Long-term Memory: This component stores the patient information \mathbf{M}_{long} and remains consistent during the interaction. The details contained in long-term memory, such as medical history, personal health data, and possibly previous experiences with healthcare, are crucial to play the patient’s role, which enables the SAPS to provide consistent and accurate information during the consultation process. In each turn, the long-term memory will extract the corresponding information relevant to the doctor’s actions only when their types belong to the effective inquiry and effective advice categories. The extracted process of the long-term memory in i -th turn can be denoted as:

$$\mathbf{m}_{\text{long},i} = \Phi_{\text{LTM}}(D_i, \mathbf{M}_{\text{long}}, \hat{s}_i) \quad (2)$$

Working Memory: The working memory \mathbf{M}_{work} is pivotal for the adaptive responses of the SAPS to different actions of doctor LLMs. It stores the requirements for responding to each type of action defined in Section 4.2.1, enabling the SAPS to react appropriately to the evolving context of the consultation. Therefore, the working memory of the i -th turn can be denoted as:

$$\mathbf{m}_{\text{work},i} = \mathbf{M}_{\text{work}}[\hat{s}_i] \quad (3)$$

Short-term Memory: This part retains the history of the consultation dialogue between the doctor LLM and the SAPS. It will continually with the flow of the conversation. This enables the SAPS to reference recent interactions, ensuring continuity and relevance in the dialogue, which is essential for a coherent and meaningful conversation in a real-time consultation setting. The short-term memory in the i -th can be expressed as:

$$\mathbf{m}_{\text{short},i} = \bigcup_{j=1}^{i-1} \{(D_j, P_j)\} \quad (4)$$

where P_j is the patient response in j -th turn of the conversations and $\mathbf{m}_{\text{short},0} = \emptyset$.

4.2.4 Response generator

The memory information extracted from the memory bank in i -t turn can be noted as $\mathbf{m}_i = \{\mathbf{m}_{\text{long},i}, \mathbf{m}_{\text{work},i}, \mathbf{m}_{\text{short},i}\}$ and the prompt for the response generator will be organized as the context in the predefined format as below:

<Patient Information>: {long_term_memory}

<Requirements>: {working_memory}

The following is a conversation between a doctor and a patient.

The patient will respond to the latest round of the doctor’s question in the first person according to the <Requirements>.

Note that do not output any text content in <Requirements>!

<Dialog>:

{short_term_memory}

[Doctor]: {doctor_question}

Then the response generator will generate the response in an autoregressive manner, where each output token is modeled depending on the previous tokens, the memory information, and the current action of the doctor LLM.

$$\Phi_{\text{gen}}(P_i | D_i, \mathbf{m}_i) = \prod_j^{|P_i|} \Phi_{\text{gen}}(p_{i,j} | p_{i,<j}, D_i, \mathbf{m}_i) \quad (5)$$

where $|P_i|$ and $p_{i,j}$ represents the number of tokens in the P_i and the j -th token in the P_i , respectively.

4.3 Medical LLMs Evaluation Pipeline

In the proposed approach, the whole evaluation pipeline can be divided into two parts: multi-turn medical consultation and diagnosis. In this first part, the doctor LLMs engage in a conversational interaction to gather as much information as possible about the patient’s symptoms within a predefined length of dialogue rounds. The model must efficiently and effectively probe for details, asking relevant questions and interpreting the responses to build a comprehensive understanding of the patient’s condition. Here the doctor LLMs output the sequence also in an autoregressive manner:

$$\Phi_{\text{doctor}}(D_i|\mathbf{m}_i) = \prod_j^{|D_i|} \Phi_{\text{doctor}}(d_{i,j}|d_{i,<j}, \mathbf{m}_{\text{short},i}) \quad (6)$$

where $|D_i|$ and $d_{i,j}$ represents the number of tokens in the D_i and the j -th token in the D_i , respectively.

The second part involves the doctor LLMs making a diagnosis based on the information collected during the multi-turn dialogue. Here, the doctor LLMs are tasked with analyzing and synthesizing the patient’s responses to determine the most likely medical condition from a set of potential diagnoses.

4.4 Evaluation Metrics

To accurately measure and assess the performance of the LLMs within the proposed framework, we need to redefine and set specific criteria. As such, we have proposed metrics for evaluating both the patient agent and medical LLMs. Given the patient simulation test set of size N , for each doctor action D_i , $i \in 1, 2, \dots, N$, its type is denoted as s_i , with a dialogue context $\mathbf{m}_{\text{short},i}$, and the response of the patient simulator is denoted as P_i .

4.4.1 Patient Simulator Evaluation Metrics

The role of patient agents in medical consultations is critically influential in ensuring the fairness of evaluations for doctor models. The accuracy and relevance of the information provided by these patient agents directly impact the ability of doctor models to make appropriate diagnoses and recommendations. Based on the state definition and response requirements discussed in Section 4.2.1, we evaluate the performance of the patient agent from 6 perspectives.

ACCURACY. This dimension assesses the model’s ability to provide correct and relevant information in response to the patient’s condition. For the question belonging to the effective inquiry and effective advice, it is expected that the reply of the patient agent can cover the corresponding part of the patient information. Therefore, we validate the accuracy with the recall of the Rouge score Lin (2004) between the reply and the ground truth answer. The metric score can be calculated as:

$$\text{ACCURACY} = \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\}) \cdot \text{Recall}(P_i, \mathbf{m}_{\text{gt},i})}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\})} \quad (7)$$

where $\mathbf{m}_{\text{gt},i}$ is the ground truth extracted from the patient information corresponding to the doctor’s action only when the question belongs to the EI, EA categories, where EI and EA are abbreviations for effective inquiry/advice categories, respectively. $\text{Recall}(\cdot, \cdot)$ using the implement of the recall score of the Rouge-1 Lin (2004).

HONEST. This dimension is used to judge whether the patient agent has fabricated facts that do not exist in the patient’s information. For the question belonging to the ineffective inquiry and ineffective advice, it is expected that the patient agent will express negation to avoid providing misleading or fabricated information. Only when the answer of the patient

agent contains the word in the predefined negative word set is the patient honest. HONESTY measures whether the patient simulator denies information that does not exist in patient information when the actions of the doctor LLMs belong to ineffective inquiry/advice categories (II/IA):

$$\text{HONESTY} = \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{II}, \text{IA}\}) \cdot \mathbb{I}(\bigvee_{h \in H} h \in P_i)}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{II}, \text{IA}\})} \quad (8)$$

where H represents a set of honest keywords. If any words $h \in H$ appear in the simulated patient’s response, we consider the simulated patient to be honest in that answer. The symbol \bigvee represents the logical OR operator, indicating that the expression is true if at least one of the conditions is satisfied.

FOCUS. FOCUS measures whether the patient simulator prompts the doctor LLMs to focus on the medical consultation topic when the doctor LLMs’ actions belong to the other topic categories (OT) and whether they prompt the doctor LLMs about the online consultation scenarios when the doctor LLMs’ actions belong to the demand categories (DE):

$$\text{FOCUS} = \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{OT}, \text{DE}\}) \cdot \mathbb{I}(\bigvee_{f \in F} f \in P_i)}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{OT}, \text{DE}\})} \quad (9)$$

where F represents a set of focus keywords. If any words $f \in F$ appear in the simulated patient’s response, we consider the simulated patient to be focus in that answer.

PASSIVE. This dimension is used to validate how much extra information is exposed when the patient agent replies to effective inquiries and advice. Lower scores indicate that the patient agent tends to answer more information compared to the corresponding answer, which makes the overall task easier. We measure the amount of additional patient information in a patient’s reply by calculating the overlap between the patient’s reply and the entire patient information, then subtracting the overlap between the reply and the corresponding patient information. To ensure consistency in the normalization standards for comparing two sets of information, we use precision to calculate the degree of overlap.

$$\text{PASSIVE} = \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\}) \cdot \text{Precision}(P_i, \mathbf{m}_{\text{long},i})}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\})} - \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\}) \cdot \text{Precision}(P_i, \mathbf{m}_{\text{gt},i})}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\})} \quad (10)$$

where $\mathbf{m}_{\text{long},i}$ is the whole patient information of the case.

CAUTIOUS. Similar to the Passive score, CAUTIOUS evaluates whether the patient simulator leaks the patient information when the doctor’s action belongs to the II/AI. In this case, no ground truth information corresponds to the ineffective action. Therefore, any patient information included in a response is considered an act of information leakage:

$$\text{CAUTIOUS} = \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\}) \cdot \text{Precision}(P_i, \mathbf{m}_{\text{long},i})}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{EI}, \text{EA}\})} \quad (11)$$

GUIDANCE. GUIDANCE measures whether the patient simulator guides the doctor LLMs to act more specifically when the doctor LLMs’ actions belong to the ambiguous inquiry/advice categories (AI,AA):

$$\text{GUIDANCE} = \frac{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{AI}, \text{AA}\}) \cdot \mathbb{I}(\bigvee_{g \in G} g \in P_i)}{\sum_{i=1}^N \mathbb{I}(s_i \in \{\text{AI}, \text{AA}\})} \quad (12)$$

where G represents a set of guidance keywords. If any words $g \in G$ appear in the simulated patient’s response, we consider the simulated patient to be guidance in that answer.

4.4.2 Doctor LLMs Automatics Evaluation Metrics

For the test to the doctor LLMs, assuming the size of the test set is N , for the i -th case, the patient information is $\mathbf{m}_{\text{long},i}$, the length of the dialogue generated by the AIE is L_i , the ground truth diagnosis is r_i .

DIAGNOSIS DIAGNOSIS measures the accuracy of the final diagnosis task depending on the collected patient information during the consultation process:

$$\text{DIAGNOSIS} = \frac{1}{N} \sum_{i=1}^N \mathbb{I}(c_i == r_i) \quad (13)$$

where c_i is the prediction of the doctor LLMs.

COVERAGE COVERAGE measures how much patient information is recalled during the consultation conversation process. We first merge the information collected in the dialogue:

$$\mathbf{m}_{\text{col},i} = \bigcup_{s_j^i \in \{\text{E,EA}\}} \{P_j\} \quad (14)$$

where the s_j^i indicates the categories of the doctor action in i -th case j -th turn. Note that we only consider the information collected in the action belonging to EI/EA. Then we can calculate the COVERAGE score as below:

$$\text{COVERAGE} = \frac{1}{N} \sum_{i=1}^N \text{Recall}(\mathbf{m}_{\text{col},i}, \mathbf{m}_{\text{long},i}) \quad (15)$$

INQUIRY ACC This metric measures the proportion of the EI in the inquiry actions:

$$\text{INQUIRY ACC} = \frac{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i == \text{EI})}{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i \in \{\text{EI, II, AI}\})} \quad (16)$$

INQUIRY SPECIFIC This metric measures the proportion of the EI/II in the inquiry actions:

$$\text{INQUIRY SPECIFIC} = \frac{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i \in \{\text{EI, II}\})}{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i \in \{\text{EI, II, AI}\})} \quad (17)$$

INQUIRY LOGIC This metric measures the gathering information logic of the doctor LLMs. We discovered that hospital records and examination questions follow the consultation sequence. Typically, they start with basic personal information, including gender and age, followed by chief complaints, then move on to medical and travel history, and conclude with various examination indicators and results. Therefore, a straightforward method to evaluate a model’s logic in collecting patient information is by calculating the edit distance between the collected patient information and the standard patient information. In our experiment, we use Levenshtein Distance (LD) Levenshtein et al. (1966) to calculate the edit distance:

$$\text{INQUIRY SPECIFIC} = \frac{1}{N} \sum_{i=1}^N \text{LD}(\mathbf{m}_{\text{col},i}, \mathbf{m}_{\text{long},i}) \quad (18)$$

ADVICE ACC This metric measures the proportion of the EA in the advice actions:

$$\text{ADVICE ACC} = \frac{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i == \text{EA})}{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i \in \{\text{EA, IA, AA}\})} \quad (19)$$

ADVICE SPECIFIC This metric measures the proportion of the EA/IA in the inquiry actions:

$$\text{INQUIRY SPECIFIC} = \frac{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i \in \{\text{EA, IA}\})}{\sum_{i=1}^N \sum_{j=1}^{L_i} \mathbb{I}(s_j^i \in \{\text{EA, IA, AA}\})} \quad (20)$$

DISTINCT We use the DISTINCT-2 score Li et al. (2016) to calculate the proportion of repetitive parts in a dialogue. This serves as an important basis for assessing whether the conversation is progressing normally by measuring the uniqueness and variability of the dialogue exchanges.

4.4.3 Doctor LLMs Human Evaluation Metrics

Based on the patient simulation validation, we conducted a comparative evaluation through multi-round diagnostic dialogues, which are generated by interaction between the doctor LLMs and the SAPS. In line with the criteria proposed by the UK General Medical Council Patient Questionnaire (GMCPQ) and principles published in reviews of the consensus for best practices for patient-centered communication (PCCBP) in medical interviews (King & Hoppe, 2013), we established five metrics each from the perspectives of the doctor and patient to score the consultation dialogues.

From a doctor’s perspective, Inquiry measures the capacity to gather information, such as which model more effectively collects key patient information, including chief complaints and illness history. Logic assesses which model has a more logical and non-repetitive questioning approach. Diagnosis determines which model makes accurate diagnoses with adequate information and provides appropriate advice when information is scarce. Patient evaluates which model better demonstrates empathy, respect, and support for the patient’s emotional and psychological needs. Total decide which model excels overall, considering their information gathering, inquiry logic, diagnostic accuracy, and humanistic care.

From a patient’s perspective, Effective measures which model provided more beneficial advice or diagnosis in general terms. Clear assesses which model communicated more clearly and was easier to understand, particularly in explaining any medical or technical terms. Understand determines which model showed greater consideration of the patient’s preferences and engagement with the patient’s ideas or concerns. Empathy evaluates which model demonstrated more empathy and a better response to the patient’s emotional state and thoughts and Total evaluates which model appeared more credible, reliable, and professional overall.

4.5 Related Works

In the realm of medical language model development, significant strides have been made by prior works such as HuatuoGPT Zhang et al. (2023) and Disc-medllm Bao et al. (2023). HuatuoGPT employs a method that uses multi-turn consultation conversations generated by ChatGPT-like models for training data, whereas Disc-medllm simplifies the dialogue process into three distinct phases: information inquiry, preliminary diagnosis, and treatment suggestion. Despite the contributions of these works, they do not explore the validation of the dynamic interaction evaluation method nor establish the Automatic Interactive Evaluation (AIE) framework as a standard in medical LLMs. This validation and standardization form the crux of our research. Furthermore, while our research shares motivations with studies referenced in Johri et al. (2024); Liao et al. (2023), it distinctively introduces several advancements. Notably, our paper proposes a state-aware patient simulator (SAPS) within the AIE framework, a novel development that enhances the fidelity and utility of these simulations. We also define a comprehensive action space for the doctor LLM, which is effectively utilized by the SAPS during evaluations and is crucial for computing innovative metrics. Our research extends beyond theoretical proposals by conducting rigorous patient simulator test experiments to ascertain the functionality and performance of the SAPS. Additionally, we undertake human evaluation studies to demonstrate the alignment between our proposed automatic evaluation metrics and traditional human assessment methods. This holistic approach confirms the effectiveness of our framework and underscores the significant enhancements our work offers over similar studies.

4.6 Ethic Consideration

This study focuses on the automatic interactive evaluation of medical consultations for Large Language Models (LLMs), which have complex ethical landscapes intersecting artificial

intelligence and healthcare. Therefore, We discuss several key ethical considerations to ensure responsible research practices.

Potential Risks The development and evaluation of LLMs in healthcare inevitably raise concerns about algorithmic biases that may perpetuate disparities in medical outcomes. We sample cases from the case library in an unbiased manner and also conduct experiments on multiple public medical examination questions to increase the diversity of cases, which can alleviate bias in the experiment results. In recognition of the critical need for transparency in healthcare interventions, we strived for explainability in the AI models’ decisions and diagnoses. We propose a new approach that involves using simulated patients to model and record the behavior of doctor LLMs during the consultation process. This facilitates our study of the decision-making changes of large language models in medical consultation dialogues. Our research involves the simulation of patient-doctor interactions, raising ethical questions about patient autonomy and informed consent. While direct patient interaction was not part of the study, we emphasize the importance of obtaining informed consent in future applications that involve real patient interactions, ensuring patients are fully aware of and comfortable with the use of AI in their care. Recognizing the potential risks associated with AI in healthcare, this study upholds the principle that AI should complement, not replace, medical professionals. The LLMs are designed to support, not substitute, the diagnostic reasoning and decision-making of healthcare providers. Professional oversight is crucial in interpreting and acting upon AI-generated insights, ensuring the safe and effective use of AI technologies in patient care.

Data Ethics and Privacy Compliance Given the medical context of our research, we ensure the privacy and confidentiality of patient data used for evaluating the LLMs. We have taken stringent measures to ensure the privacy and confidentiality of this information. All personal identifiers have been removed to maintain anonymity, ensuring no individual can be recognized from the data used. During the data collection, patients signed informed consent forms and were fully aware of the data usage methods described in this paper. Additionally, the usage of this data has been reviewed and approved by the corresponding hospital ethics committees. The specific approval numbers will be provided after the end of the review. This ensures that the data usage in this paper fully complies with ethical standards and privacy protection regulations.

4.7 Data Availability

MedQA data is available at <https://github.com/jind11/MedQA>. MedMCQA data is available at <https://github.com/MedMCQA/MedMCQA>. MMLU data is available at <https://github.com/hendrycks/test>. SelfExam data is available at <https://journals.plos.org/digitalhealth/article?id=10.1371/journal.pdig.0000198#references>. All the experiment’s preprocessed data are available in the code repository.

4.8 Model Availability

For the weak models, we use the ChatGLM3-6B available at <https://github.com/THUDM/ChatGLM3> for ChatGLM3-6b, Baichuan-13B-Chat available at <https://github.com/baichuan-inc/Baichuan-13B> for BaiChuan-13b, and InternLM2-Chat-20B available at <https://github.com/InternLM/InternLM> for InternLM-20b.

4.9 Code Availability

The final annotation guidelines and all synthetic datasets used in this study are available at https://github.com/BlueZeros/Automatic_Interactive_Evaluation.

References

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, Binyuan Hui, Luo Ji, Mei Li, Junyang Lin, Runji Lin, Dayiheng Liu,

-
- Gao Liu, Chengqiang Lu, Keming Lu, Jianxin Ma, Rui Men, Xingzhang Ren, Xuancheng Ren, Chuanqi Tan, Sinan Tan, Jianhong Tu, Peng Wang, Shijie Wang, Wei Wang, Shengguang Wu, Benfeng Xu, Jin Xu, An Yang, Hao Yang, Jian Yang, Shusheng Yang, Yang Yao, Bowen Yu, Hongyi Yuan, Zheng Yuan, Jianwei Zhang, Xingxuan Zhang, Yichang Zhang, Zhenru Zhang, Chang Zhou, Jingren Zhou, Xiaohuan Zhou, and Tianhang Zhu. Qwen technical report. *arXiv preprint arXiv:2309.16609*, 2023.
- Zhijie Bao, Wei Chen, Shengze Xiao, Kuang Ren, Jiaao Wu, Cheng Zhong, Jiajie Peng, Xuanjing Huang, and Zhongyu Wei. Disc-medllm: Bridging general large language models and real-world medical consultation. *arXiv preprint arXiv:2308.14346*, 2023.
- Siyuan Chen, Mengyue Wu, Kenny Q Zhu, Kunyao Lan, Zhiling Zhang, and Lyuchun Cui. Llm-empowered chatbots for psychiatrist and patient simulation: Application and evaluation. *arXiv preprint arXiv:2305.13614*, 2023.
- Wei Chen, Zhiwei Li, Hongyi Fang, Qianyuan Yao, Cheng Zhong, Jianye Hao, Qi Zhang, Xuanjing Huang, Jiajie Peng, and Zhongyu Wei. A benchmark for automatic medical consultation system: frameworks, tasks and datasets. *Bioinformatics*, 39(1):btac817, 12 2022. ISSN 1367-4811. doi: 10.1093/bioinformatics/btac817. URL <https://doi.org/10.1093/bioinformatics/btac817>.
- Zhengxiao Du, Yujie Qian, Xiao Liu, Ming Ding, Jiezhong Qiu, Zhilin Yang, and Jie Tang. Glm: General language model pretraining with autoregressive blank infilling. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 320–335, 2022.
- Muhammad Usman Hadi, Rizwan Qureshi, Abbas Shah, Muhammad Irfan, Anas Zafar, Muhammad Bilal Shaikh, Naveed Akhtar, Jia Wu, Seyedali Mirjalili, et al. A survey on large language models: Applications, challenges, limitations, and practical usage. *Authorea Preprints*, 2023.
- Tianyu Han, Lisa C Adams, Jens-Michalis Papaioannou, Paul Grundmann, Tom Oberhauser, Alexander Löser, Daniel Truhn, and Keno K Bressen. Medalpaca—an open-source collection of medical conversational ai models and training data. *arXiv preprint arXiv:2304.08247*, 2023.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.
- Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? A large-scale open domain question answering dataset from medical exams. *CoRR*, abs/2009.13081, 2020a. URL <https://arxiv.org/abs/2009.13081>.
- Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *arXiv preprint arXiv:2009.13081*, 2020b.
- Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William W. Cohen, and Xinghua Lu. Pubmedqa: A dataset for biomedical research question answering. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (eds.), *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019*, pp. 2567–2577. Association for Computational Linguistics, 2019. doi: 10.18653/V1/D19-1259. URL <https://doi.org/10.18653/v1/D19-1259>.
- Shreya Johri, Jaehwan Jeong, Benjamin A Tran, Daniel I Schlessinger, Shannon Wongvibulsin, Zhuo Ran Cai, Roxana Daneshjou, and Pranav Rajpurkar. Testing the limits of language models: A conversational framework for medical ai assessment. *medRxiv*, 2023.

-
- Shreya Johri, Jaehwan Jeong, Benjamin A. Tran, Daniel I Schlessinger, Shannon Wongvibulsin, Zhuo Ran Cai, Roxana Daneshjou, and Pranav Rajpurkar. CRAFT-MD: A conversational evaluation framework for comprehensive assessment of clinical LLMs. In *AAAI 2024 Spring Symposium on Clinical Foundation Models*, 2024. URL <https://openreview.net/forum?id=Bk2nbTDtm8>.
- Jean Kaddour, Joshua Harris, Maximilian Mozes, Herbie Bradley, Roberta Raileanu, and Robert McHardy. Challenges and applications of large language models. *arXiv preprint arXiv:2307.10169*, 2023.
- Ann King and Ruth B Hoppe. “best practice” for patient-centered communication: a narrative review. *Journal of graduate medical education*, 5(3):385–393, 2013.
- Tiffany H. Kung, Morgan Cheatham, Arielle Medenilla, Czarina Sillos, Lorie De Leon, Camille Elepaño, Maria Madriaga, Rimel Aggabao, Giezel Diaz-Candido, James Maningo, and Victor Tseng. Performance of chatgpt on usmle: Potential for ai-assisted medical education using large language models. *PLOS Digital Health*, 2(2):1–12, 02 2023. doi: 10.1371/journal.pdig.0000198. URL <https://doi.org/10.1371/journal.pdig.0000198>.
- Vladimir I Levenshtein et al. Binary codes capable of correcting deletions, insertions, and reversals. In *Soviet physics doklady*, volume 10, pp. 707–710. Soviet Union, 1966.
- Jiwei Li, Michel Galley, Chris Brockett, Jianfeng Gao, and Bill Dolan. A diversity-promoting objective function for neural conversation models. In Kevin Knight, Ani Nenkova, and Owen Rambow (eds.), *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 110–119, San Diego, California, June 2016. Association for Computational Linguistics. doi: 10.18653/v1/N16-1014. URL <https://aclanthology.org/N16-1014>.
- Yusheng Liao, Yutong Meng, Hongcheng Liu, Yanfeng Wang, and Yu Wang. An automatic evaluation framework for multi-turn medical consultations capabilities of large language models. *arXiv preprint arXiv:2309.02077*, 2023.
- Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pp. 74–81, 2004.
- Wenge Liu, Jianheng Tang, Yi Cheng, Wenjie Li, Yefeng Zheng, and Xiaodan Liang. Meddg: an entity-centric medical consultation dataset for entity-aware medical dialogue generation. In *CCF International Conference on Natural Language Processing and Chinese Computing*, pp. 447–459. Springer, 2022.
- Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-eval: NLG evaluation using gpt-4 with better human alignment. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 2511–2522, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.153. URL <https://aclanthology.org/2023.emnlp-main.153>.
- Nikita Mehandru, Brenda Y Miao, Eduardo Rodriguez Almaraz, Madhumita Sushil, Atul J Butte, and Ahmed Alaa. Evaluating large language models as agents in the clinic. *npj Digital Medicine*, 7(1):84, 2024.
- Timo Minssen, Effy Vayena, and I Glenn Cohen. The challenges for regulating medical use of chatgpt and other large language models. *Jama*, 2023.
- Harsha Nori, Nicholas King, Scott Mayer McKinney, Dean Carignan, and Eric Horvitz. Capabilities of GPT-4 on medical challenge problems. *CoRR*, abs/2303.13375, 2023. doi: 10.48550/ARXIV.2303.13375. URL <https://doi.org/10.48550/arXiv.2303.13375>.
- OpenAI. Chatgpt: Optimizing language models for dialogue. Website, 2022. <https://openai.com/blog/chatgpt>.
- OpenAI. GPT-4 technical report. *CoRR*, abs/2303.08774, 2023. doi: 10.48550/arXiv.2303.08774.

-
- Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. Medmcqa: A large-scale multi-subject multi-choice dataset for medical domain question answering. In Gerardo Flores, George H. Chen, Tom J. Pollard, Joyce C. Ho, and Tristan Naumann (eds.), *Conference on Health, Inference, and Learning, CHIL 2022, 7-8 April 2022, Virtual Event*, volume 174 of *Proceedings of Machine Learning Research*, pp. 248–260. PMLR, 2022a. URL <https://proceedings.mlr.press/v174/pal22a.html>.
- Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. Medmcqa: A large-scale multi-subject multi-choice dataset for medical domain question answering. In Gerardo Flores, George H. Chen, Tom Pollard, Joyce C. Ho, and Tristan Naumann (eds.), *Proceedings of the Conference on Health, Inference, and Learning*, volume 174 of *Proceedings of Machine Learning Research*, pp. 248–260. PMLR, 07–08 Apr 2022b. URL <https://proceedings.mlr.press/v174/pal22a.html>.
- Murray Shanahan, Kyle McDonell, and Laria Reynolds. Role play with large language models. *Nature*, 623(7987):493–498, 2023.
- Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, et al. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180, 2023.
- InternLM Team. Internlm: A multilingual language model with progressively enhanced capabilities. <https://github.com/InternLM/InternLM>, 2023.
- Arun James Thirunavukarasu, Darren Shu Jeng Ting, Kabilan Elangovan, Laura Gutierrez, Ting Fang Tan, and Daniel Shu Wei Ting. Large language models in medicine. *Nature medicine*, 29(8):1930–1940, 2023.
- Shubo Tian, Qiao Jin, Lana Yeganova, Po-Ting Lai, Qingqing Zhu, Xiuying Chen, Yifan Yang, Qingyu Chen, Won Kim, Donald C Comeau, et al. Opportunities and challenges for chatgpt and large language models in biomedicine and health. *Briefings in Bioinformatics*, 25(1):bbad493, 2024.
- Tao Tu, Anil Palepu, Mike Schaekermann, Khaled Saab, Jan Freyberg, Ryutaro Tanno, Amy Wang, Brenna Li, Mohamed Amin, Nenad Tomasev, et al. Towards conversational diagnostic ai. *arXiv preprint arXiv:2401.05654*, 2024.
- Haochun Wang, Chi Liu, Nuwa Xi, Zewen Qiang, Sendong Zhao, Bing Qin, and Ting Liu. Huatuo: Tuning llama model with chinese medical knowledge. *arXiv preprint arXiv:2304.06975*, 2023.
- Paul Webster. Six ways large language models are changing healthcare. *Nature Medicine*, 29(12):2969–2971, 2023.
- Zhongyu Wei, Qianlong Liu, Baolin Peng, Huaixiao Tou, Ting Chen, Xuanjing Huang, Kam-fai Wong, and Xiangying Dai. Task-oriented dialogue system for automatic diagnosis. In Iryna Gurevych and Yusuke Miyao (eds.), *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 201–207, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-2033. URL <https://aclanthology.org/P18-2033>.
- Tsung-Hsien Wen, David Vandyke, Nikola Mrksic, Milica Gasic, Lina M Rojas-Barahona, Pei-Hao Su, Stefan Ultes, and Steve Young. A network-based end-to-end trainable task-oriented dialogue system. *arXiv preprint arXiv:1604.04562*, 2016.
- Honglin Xiong, Sheng Wang, Yitao Zhu, Zihao Zhao, Yuxiao Liu, Qian Wang, and Dinggang Shen. Doctorglm: Fine-tuning your chinese doctor is not a herculean task. *arXiv preprint arXiv:2304.01097*, 2023.
- Aiyuan Yang, Bin Xiao, Bingning Wang, Borong Zhang, Ce Bian, Chao Yin, Chenxu Lv, Da Pan, Dian Wang, Dong Yan, et al. Baichuan 2: Open large-scale language models. *arXiv preprint arXiv:2309.10305*, 2023a.

-
- Rui Yang, Ting Fang Tan, Wei Lu, Arun James Thirunavukarasu, Daniel Shu Wei Ting, and Nan Liu. Large language models in health care: Development, applications, and challenges. *Health Care Science*, 2(4):255–263, 2023b.
- Li Yunxiang, Li Zihan, Zhang Kai, Dan Ruilong, and Zhang You. Chatdoctor: A medical chat model fine-tuned on llama model using medical domain knowledge. *arXiv preprint arXiv:2303.14070*, 2023.
- Hongbo Zhang, Junying Chen, Feng Jiang, Fei Yu, Zhihong Chen, Jianquan Li, Guiming Chen, Xiangbo Wu, Zhiyi Zhang, Qingying Xiao, et al. Huatuogpt, towards taming language model to be a doctor. *arXiv preprint arXiv:2305.15075*, 2023.
- Yu Zhao, Yunxin Li, Yuxiang Wu, Baotian Hu, Qingcai Chen, Xiaolong Wang, Yuxin Ding, and Min Zhang. Medical dialogue response generation with pivotal information recalling. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 4763–4771, 2022.
- Hongjian Zhou, Boyang Gu, Xinyu Zou, Yiru Li, Sam S Chen, Peilin Zhou, Junling Liu, Yining Hua, Chengfeng Mao, Xian Wu, et al. A survey of large language models in medicine: Progress, application, and challenge. *arXiv preprint arXiv:2311.05112*, 2023.