Large Deviations in Safety-Critical Hamiltonian Systems with Probabilistic Initial Conditions

Aitor R. Gomez^a, Manuela L. Bujorianu^b, Rafal Wisniewski^a

^aSection of Automation & Control, Aalborg University, DK

^bDepartment of Computer Science, University College London, UK

Abstract

We address the problem of determining the least improbable deviations leading to an unsafe rare event in a weakly perturbed mechanical system with probabilistic initial conditions. These deviations are obtained as the solution to a variational problem formulated using rigorous approximation techniques grounded in the principles of large deviations theory. These types of results have been extended to accommodate stochastic uncertainty in the initial states, which is a common assumption in mechanical systems. Furthermore, we demonstrate the applicability of the method by solving the problem for a rare collision event between two space objects—a high-dimensional and non-linear problem—resulting in the most likely sample paths leading to the realization of the unsafe rare event. The solution is validated against the necessary conditions for optimality derived from the maximum principle. Access to these unsafe sample paths offers relevant information regarding the dangerous configurations of rare events and can be used to design control strategies to reduce the probability of realization.

Key words: safety; rare events; optimal control problem; random initial conditions; large deviations; approximation.

1 Introduction

The many efforts in mathematics, physics and engineering have lead to the well understanding of the behavior of a bast amount of mechanical systems. Yet, achieving full mathematical characterization of all the physical interactions between the system and the environment is virtually impossible and thus, we are always left with unknown uncertainties and/or perturbations that are small in nature and slowly steer the long term behavior of the system away from a reference domain. For safetycritical mechanical systems of this type, it is of utmost interest to analyze the limiting behavior given the presence of unsafe or forbidden regions in the state space. Examples of this are abundant in areas such as spacecraft collision avoidance, air traffic management, missile guidance, telescope and radio pointing, and others [13].

The notion of safety in control engineering is usually associated with critical constraints that can not be violated for the sake of the systems sustainability. Viability

raf@es.aau.dk (Rafal Wisniewski).

kernels [1] and minimal (or maximal) reachability analysis [14] are solid frameworks that have been successfully applied to prove and preserve safety. Both provide indepth insights upon non-deterministic [9] and stochastic [2] systems' trajectories by identifying sets of initial (or final) states for which the system is, in some formal sense, safe. These two concepts are key to guarantee safety, yet their formulations rely on set-valued time propagation of the system dynamics. Exact solutions to these problems are generally very hard-or even impossible-to determine, and numerical approximations are prohibitive when exceeding more than four state dimensions due to Bellman's curse of dimensionality.¹ Such limitations restrict the applicability of these rigorous formulations in systems with relatively large state space dimensions and complex non-linear dynamics.

Barrier certificates [15] emerged from the desire of verifying systems safety while avoiding the difficult computation of reachable sets. Safety verification in nondeterministic systems is based on showing the existence of a function with zero-level set separating the unsafe region of the state space from trajectories of the system departing from a given initial set. When the uncertainties

 $^{^{\}star}$ This paper was not presented at any IFAC meeting. Corresponding author Aitor R. Gomez.

Email addresses: arg@es.aau.dk (Aitor R. Gomez), 1.bujorianu@ucl.ac.uk (Manuela L. Bujorianu),

¹ This is an open area of research and such considerations are made at the current time of writing this report.

and disturbances are of stochastic nature and have no hard bounds, it is more reasonable to define safety from a probabilistic standpoint. A common approach within this framework is using supermartingale theory to construct a stochastic counterpart of a barrier that yields an upper bound on the probability of reaching the unsafe region. Stochastic barriers, and the closely related concept of *p*-safety in reach-avoid problems [20,21], have been designed based on these principles to give probabilistic guarantees of safety. The formulation of reachavoid problems, which involve solving a Fokker-Planck equation, vary slightly as the goal is to classify a set of initial states according to the probability of the system reaching a target set while avoiding a forbidden space. At any rate, closed-form stochastic barrier functions are hard to determine, and combining relaxations (e.g. sumof-square polynomials) with numerical methods is often required to enable approximate solutions.

In this context of safety, analyzing random events of rare occurrence pose additional complexities. These may originate when considering a *small* unsafe region of the state space, or when the stochastic disturbances affecting the system are small. In both cases, reaching the unsafe region is characterized by very low probabilities and, thus, stochastic barrier certificates designed to prove safety in these situations will have either unsound numerical properties or large conservativeness, as manifested in previous analysis [8]. This makes it difficult to accurately compute and apply these methods for safety verification in presence of unsafe rare events (UREs).

In order to overcome these limitations, we leverage results from the theory of large deviations (LDT) to make a safety analysis of the weakly perturbed mechanical system based on approximations of its limiting behaviour. The concept of approximating stochastic processes with LDT is not novel and has been widely employed in various optimal control problems in the past [13,10,5,19,16]. The well-known work of Freidlin and Wentzell [6] established the theory of large deviations for stochastic differential equations, forming the basis for the main results of this paper. Kushner later extended the results for degenerate diffusion processes [12,11], which aligns more accurately with the description of mechanical systems. These results provide a convenient, rigorous and precise mathematical framework that can be used for estimating probabilistic quantities of rare events. The analysis relies on solutions of variational problems, which alleviates the problem of dealing with high dimensional state spaces, as opposed to the complex viscosity solution techniques required for reachability problems. It also gives access to interesting objects, such as the most likely deviations of the systems trajectories, and can be used in combination with other techniques, e.g. importance sampling, to perform simulations of rare events. Additionally, there are readily available numerical tools that can be used to solve variational problems, and thus allow the implementation of the theory in a wide range of applications.

1.1 Organization and Contributions

The basis forming the standard results of large deviations for stochastic differential equations are introduced in section 2. In section 3, we present the corresponding discrepancies that arise when considering probabilistic initial conditions, and reformulate the variational problem accordingly. Section 4 is devoted to a practical example involving the rare event of a spacecraft collision, which represents a multi-dimensional problem with highly non-linear dynamics. For this example, the necessary conditions for optimality are derived using the maximum principle, and the numerical solution is presented and cross-checked with the necessary conditions. Finally, in section 5 we give the final remarks and conclude the paper. The contributions of the paper are the following:

- (1) An interpretation of LDT in terms of safety.
- (2) A framework to analyze unsafe configurations of the system in the presence of rare events.
- (3) Theorem 1, stating a new variational problem which solution is the most likely deviations leading to an URE for a system with stochastic initial conditions.
- (4) A demonstration through a high-dimensional and non-linear example: a collision event between two space objects.

1.2 Notation

We will consider systems with n degrees of freedom, and describe the state space (position and momenta) as $\mathbb{R}^n \times \mathbb{R}^n$. We use $\mathcal{C}^0(I, \mathbb{R}^n \times \mathbb{R}^n)$ to denote the space of continuous functions that maps the time interval I into the state space. Occasionally, we will refer to it as C_I to simplify notation. We will assume a probability space (Ω, \mathcal{F}, P) , identifying Ω with the space of trajectories \mathcal{C}_I . We write $X_t(\omega), X(\omega, \cdot)$ and ϕ indistinctively, denoting a sample path of the process 2 . The bracket notation in $p[\phi|x_0, T]$ denotes a probability density over the sample paths conditioned on the initial state being x_0 and the terminal time T. We use the standard notation $p_z(z) := P(z \in [z, z + dz])$ to denote densities of points z in the Euclidean space. We often use the nota-tion $x := (y, z) \equiv [y^{\top}, z^{\top}]^{\top}$ to gather column vectors $y, z \in \mathbb{R}^n$ into a column vector $x \in \mathbb{R}^{2n}$. The 2-norm of a vector v is denoted as ||v||, and for an invertible matrix Aof appropriate dimensions, the notation $||v||_A$ is equivalent to $\sqrt{v^{\top}A^{-1}v}$. The notation $\nabla_x h$ is used to refer to the gradient of a function h with respect to x. For a set D subset of a topological space E, its boundary is ∂D .

² The usual notation for a sample path is $\omega(t)$, which we replace for $\phi(t)$ following the LDT notation.

2 Problem formulation and Background

2.1 Mechanical System

Consider a mechanical system with n degrees of freedom described by states $r \in \mathbb{R}^n$ and satisfying the second-order differential equation of the following form.

$$\ddot{r} - b(r) = f,\tag{1}$$

where $b : \mathbb{R}^n \to \mathbb{R}^n$ is Lipschitz continuous and denotes modelled forces affecting the system, and f represent the remaining of the external forces that are not included in b. The differential equation (1) is commonly determined from the Euler-Lagrange equation

$$\frac{d}{dt}\frac{\partial L(r,\dot{r})}{\partial \dot{r}} - \frac{\partial L(r,\dot{r})}{\partial r} = f$$

where $L : \mathbb{R}^n \times \mathbb{R}^n \to \mathbb{R}$ is the Lagrangian of the system.

2.2 Weakly Perturbed System

In this work, we will assume that the unmodeled external forces f are Gaussian and small in nature. We also introduce the momentum $v \in \mathbb{R}^n$, or velocity vector, and rewrite the system (1) as a degenerate stochastic differential equation (dSDE) where f is replaced by a Wiener process and the deterministic functions r and v are replaced by stochastic versions R and V, respectively.

$$dR_t = V_t dt,$$

$$dV_t = b(R_t)dt + \sqrt{\epsilon\sigma} dW_t.$$
(2)

Herein, $0 < \epsilon \ll 1$ is a small noise parameter and $\sigma \in \mathbb{R}^{n \times n}$ is the diffusion matrix defining the covariance $a = \sigma \sigma^{\top}$ of the Wiener process. Equivalently, we write the previous system in a compact way, by gathering the states as $X^{\epsilon}(t) := (R(t), V(t))$, parameterized by ϵ .

$$dX_t^{\epsilon} = \underline{b}(X_t^{\epsilon})dt + \sqrt{\epsilon}\underline{\sigma}dW_t, \quad X^{\epsilon}(0) = x_0, \quad (3)$$

and for which function \underline{b} and matrix $\underline{\sigma}$ are defined as

$$\underline{b}(X_t^{\epsilon}) = \begin{bmatrix} V_t \\ b(R_t) \end{bmatrix}, \quad \underline{\sigma} = \begin{bmatrix} 0 \\ \sigma \end{bmatrix}.$$
(4)

Consider as well the unperturbed trajectory of the system, i.e. for $\epsilon=0$

$$\dot{x} = \underline{b}(x), \quad x(0) = x_0. \tag{5}$$

2.3 Safety Problem

Under these considerations, we aim to study the probability of the process $\{R_t\}$ visiting an unsafe compact ³ set $D \subset \mathbb{R}^n$. Events of this type will be characterized by very low probabilities, consequence of the smallness of the noise parameter ϵ or of the set D, or both, earning thus the nomination of Unsafe Rare Event (URE). Many interpretations can be given to D. For instance, a region of space occupied by a piece of debris on a spacecrafts orbit, undesired targets for a missile or other vehicles near aircraft pathways.

The problem of system (2) visiting D shall be conducted using random stopping times, which motivates the following definition.

Definition 2.1 (Hitting time) Consider the system (2) hitting the boundary of the unsafe set D at most once at time

$$\tau^{\epsilon}(\omega) = \inf\{t > 0 : R(\omega, t) \in \partial D\}.$$

This is the *first* hitting time of the boundary which is equal to the first hitting time of D due to the fact that the trajectories of the process are continuous. The involvement of the random state R into the definition of the hitting time makes τ^{ϵ} also a random variable. We can further assume that there exists a density p_{τ} associated to the hitting time such that

$$P_{x_0}[\tau^{\epsilon} \in dt] = p_{\tau}(t)dt. \tag{6}$$

We find a way of incorporating the hitting time defined above into our study by working with the probability distribution over paths of the system, $X^{\epsilon}(\omega, \cdot)$ with $\omega \in \Omega$. The process, as presented in (2) and (3), has path distribution (or path density) conditioned on the initial state being x_0 and terminating at a given time t = T. We write this in the square brackets notation as $p[\phi|x_0, T]$, following the physics literature, so as to denote a functional over the entire measurable function $\phi \in C_I$, with $\phi(0) = x_0$ and interval I := [0, T]. The formal definition of this density is given in the following section.

The function ϕ shall be seen here as a single realization or sample path⁴ of the process $\{X_t^{\epsilon}\}$. It is convenient to specify the continuous functions of time η and ν composing the full state vector of the sample path.

$$\phi(t) := \begin{bmatrix} \eta(t) \\ \nu(t) \end{bmatrix}, \quad \forall t \in I$$
(7)

where $\eta(t)$ and $\nu(t)$ match the dimensions of r(t) and

³ Defining D as a compact set only on \mathbb{R}^n is not a restriction since we can define an unsafe set for V(t) to be large enough. ⁴ See footnote 2.

v(t), respectively. Then define ϕ as the solution of a differential equation with initial condition $\phi(0)=x_0$ and dynamics

$$\begin{aligned} \dot{\eta} &= \nu, \\ \dot{\nu} &= b(\eta) + \sigma w, \end{aligned}$$
 (8)

where $w: I \to \mathbb{R}^n$ is a measurable function representing deviations from the vector field b, which steer the system (8) mimicking the perturbations of the real system (2).

The safety of the system will be analyzed from the perspective of path densities, as detailed in the next section.

2.4 Large Deviations Approximation

Asymptotic solutions have been developed for sufficiently small ϵ that are well known in the mathematical and physics community (see e.g. [6,18,3,4] and the references within), which provide a formal approximation of path densities under certain regularity conditions. In order to introduce these methods, let us briefly analyse the limiting behavior of the weakly perturbed system (3) as a function of the noise parameter. Note that as we decrease ϵ , the process $\{X_t^{\epsilon}\}$ is expected to remain closer to the deterministic trajectory x (the solution of (5)). In the limit $\epsilon \to 0$, we can formally write that

$$P_{x_0}\left\{\omega: \sup_{t\in I} ||X_t^{\epsilon}(\omega) - x_t|| > \delta\right\} \to 0$$

for $\delta > 0$, meaning that the probability of fluctuating away from the deterministic path x decays to zero with decreasing ϵ . This decay in probability allows us to characterize the path density as a low-noise approximation [18]

$$p[\phi|x_0, T] \asymp \exp\left(-\epsilon^{-1}S(\phi, T)\right),\tag{9}$$

where the symbol \approx denotes an asymptotic equivalence and $S: \mathcal{C}_I \to \mathbb{R}_{\geq 0}$ is referred to as the action functional, rate function or path entropy (depending on the field of study) on the interval I. We will simply call it action functional and define it as [12,11]

$$\begin{split} S(\phi,T) &:= \frac{1}{2} \int_0^T ||w||^2 dt \\ &= \frac{1}{2} \int_0^T ||\dot{\nu} - b(\eta)||_a^2 dt, \end{split} \tag{10}$$

if the integral converges, and $S(\phi, T) = +\infty$ otherwise. The value of $S(\phi, T)$ represents the total deviation from the vector field b that a path ϕ undertakes.

Remark 2.1 The path density $p[\phi|x_0, T]$ is not formulated in a rigorous way. The formal interpretation of (9) was first derived by Freidlin and Wentzell [6] to be

$$\lim_{\substack{\epsilon \to 0 \\ \delta \to 0}} \epsilon \ln P_{x_0} \left\{ \omega : \sup_{t \in I} ||X_t^{\epsilon}(\omega) - \phi_t|| < \delta \right\} = -S(\phi, T),$$

which is the main result of the theory of large deviations, known as large deviations principle. This enables the lownoise approximation of the path density in (9).

Note that S is convex with minimum at w = 0 (no perturbations), which yields $\dot{\nu} = b(\eta)$, making the solution of the deterministic system (5) and of the sample path (8) equal, i.e. $\phi = x$. This implies that the deterministic trajectory is the most likely (i.e. exhibiting highest probability density in the sense of the large deviations principle (9)) path for the system to follow.

Consider now only the realizations of $\{X_t^{\epsilon}\}$ that hit the boundary of the unsafe set D, denoted as ∂D , at some time t > 0 assuming that $x_0 \notin D$. These paths are deemed unsafe for the system (2), and can be identified as the elements of the following set.

Definition 2.2 (Set of unsafe paths) Given an initial condition x_0 , a time T and an (unsafe) region D, the unsafe paths are defined as the set of all continuous functions departing from x_0 and reaching ∂D at some time $t \in [0, T]$ with bounded action. That is,

$$\Phi_{x_0,T} := \{ \phi \in \mathcal{C}_I : \phi(0) = x_0, \exists t \in [0,T] \\ s.t. \ \eta(t) \in \partial D, \ S(\phi,T) < \infty \}$$

According to the previous definitions, the most likely trajectory (in the sense of the large deviations principle) hitting D at some time $t \in [0, T]$ if the system departs from x_0 is the path ϕ^* exhibiting maximum density in $\Phi_{x_0,T}$ in the topology induced by the supnorm. Hence,

$$p[\phi^*|x_0, T] = \max_{\phi \in \Phi_{x_0, T}} p[\phi|x_0, T].$$
(11)

Recall from definition 2.1, that the actual time of hitting the unsafe set, τ^{ϵ} , is in fact a random variable. Given its density function p_{τ} , the probability density of the paths hitting D at any time t > 0 can be bounded by the probability density of the paths hitting D and terminating at the worst final time T^* . Following the law of total probability:

$$p[\phi^*|x_0] = \int_0^\infty p[\phi^*|x_0, t] p_\tau(t) dt$$

$$\leq \max_{T>0} p[\phi^*|x_0, T] \int_0^\infty p_\tau(t) dt \qquad (12)$$

$$= p[\phi^*|x_0, T^*],$$

since $\int_0^\infty p_\tau(t)dt = 1$.

The density on the right-hand side of (12) is the maximum density achievable by a sample path on the set Φ_{x_0,T^*} of unsafe paths issued from x_0 and reaching ∂D at $T = T^*$. Finding ϕ^* is equivalent to finding the sample path and terminal time that (simultaneously) infimize the action functional S, according to (11)–(12). It is possible to show that the path density $p[\phi^*|x_0,T^*]$ satisfies another large deviations principle with a new action functional Q, usually referred to as quasipotential ⁵ (see e.g. [6,18,7]). Here, it is defined for a given final set D and initial condition x_0 , as

$$Q(D, x_0) := \inf_{T>0} \min_{\substack{\phi:\phi(0)=x_0, \\ \eta(T)\in\partial D}} S(\phi, T).$$
(13)

Recall from (8) that the differential equation of η is not affected by w directly, thus the minimization of S with respect to ϕ in (13) has the implicit kinematic constraint $\dot{\eta} = \nu$. The quasipotential Q yields the second large deviations principle,

$$p[\phi^*|x_0, T^*] \simeq \exp(-\epsilon^{-1}Q(D, x_0)).$$
 (14)

The previous expression indicates that the most significant contribution to the probability of realizing the event $\{\omega : X^{\epsilon}(\omega, \cdot) \in \Phi_{x_0, T^*}\}$ is given by a pair (T^*, ϕ^*) that solves the following variational problem:

$$\inf_{\substack{T>0\\\eta(T)\in\partial D}} \min_{\substack{\phi:\phi(0)=x_0,\\\eta(T)\in\partial D}} S(\phi,T), \quad \text{s.t.} \ (8). \tag{15}$$

Such extreme path ϕ^* is the solution of (8) with minimal deviation w^* —i.e. w that minimizes the action (10)—hitting D at time T^* . It gives rise to the following (well-known) definition.

Definition 2.3 (Maximum likelihood pathway)

The extreme function ϕ^* solving (15) is the maximum likelihood (ML) pathway, or instanton.

3 Randomness in the initial conditions

In this section, we study the same problem as before but considering the departing state to be random. Specifically $X^{\epsilon}(0) \sim \mathcal{N}(\mu, \Sigma)$ with density p_0 being

$$p_0(x_0) = \frac{1}{\sqrt{(2\pi)^{2n} \det \Sigma}} \exp\left(-S_0(x_0)\right), \qquad (16)$$

and

$$S_0(x_0) := \frac{1}{2} ||x_0 - \mu||_{\Sigma}^2.$$
(17)

This modification introduces additional degrees of freedom to the problem. Determining the most likely path realizing the URE no longer depends uniquely on the path deviations w, but also on the state of departure. This is illustrated in Fig. 1 for two initial points x_1 and x_2 . Clearly, it requires deviating less from the deterministic flow when departing from x_2 . However, it is necessary to analyse the likelihood of the system starting at x_2 , compared to it starting at x_1 , according to p_0 .



Fig. 1. Geometric description of the problem.

A solution to this problem is derived here using the notions of large deviations described in the previous section. First, we put forward the following proposition which introduces a new variational problem. Later, we modify it to obtain an identical problem that can be numerically solved. The solution to the latter is the initial state and the trajectory of the system that exhibit highest probability density (in the sense of the large deviations approximation) from which the system can depart and reach the boundary of the unsafe set D at some time $t \in [0, T]$.

Proposition 3.1 Let $\phi_{x_0}^*(\cdot)$ be the maximum likelihood path hitting the boundary of D at time $T = T^*$ as a function of the departing point x_0 . The state of departure exhibiting highest posterior probability density is the point x_0^* minimizing the following function

$$\Gamma(x_0) = S(\phi_{x_0}^*, T^*) + \epsilon S_0(x_0).$$
(18)

Proof. The proof of the previous proposition arises naturally from Bayes' theorem. In terms of the elements introduced in the previous section, the path density $p[\phi^*|x_0, T^*]$ corresponds now to the likelihood function, and thus we can define the posterior probability as

$$p_0(x_0|\phi^*, T^*) = \frac{p[\phi^*|x_0, T^*]p_0(x_0)}{p[\phi^*|T^*]}$$
(19)
 $\propto p[\phi^*|x_0, T^*]p_0(x_0),$

where \propto indicates that it is a proportional relation. It then holds that the argument that maximizes the posterior distribution $p_0(x_0|\phi^*, T^*)$ is the same argument that maximizes the product $p[\phi^*|x_0, T^*]p_0(x_0)$. That is,

$$\underset{x_0}{\operatorname{argmax}} p_0(x_0 | \phi^*, T^*) = \underset{x_0}{\operatorname{argmax}} p[\phi^* | x_0, T^*] p_0(x_0),$$

allowing us to avoid the density $p[\phi^*|T^*]$, which is just a constant of proportionality and usually hard to determine.

By taking (13), (14) and (16), we find the following

⁵ The usual notation for the quasipotential is V. We use Q so as not to confuse it with the random velocity V(t).

asymptotic equivalence

$$\underset{x_{0}}{\operatorname{argmax}} p[\phi^{*}|x_{0}, T^{*}]p_{0}(x_{0}) \\ \approx \underset{x_{0}}{\operatorname{argmax}} \exp\left(-\frac{1}{\epsilon}S(\phi_{x_{0}}^{*}, T^{*}) - S_{0}(x_{0})\right) \\ = \underset{x_{0}}{\operatorname{argmin}} \left\{S(\phi_{x_{0}}^{*}, T^{*}) + \epsilon S_{0}(x_{0})\right\}$$

The argument that minimizes the last expression is the most likely initial condition from which the system can depart and reach ∂D in the approximate sense of the large deviations principle.

The previous proposition is instrumental to determine the worst initial condition x_0 . However, the optimal path $\phi_{x_0}^*(\cdot)$ as a function of x_0 is unknown to us, and thus can not be determined from (18) directly. To that end, consider the following result.

Theorem 1 For a system (3) with normally distributed initial condition $X^{\epsilon}(0)$ that has density p_0 as defined in (16), the most likely path hitting the boundary of D is characterized by the pair $(T^{\circledast}, \phi^{\circledast})$ where the minimum of the following functional J is attained:

$$\begin{aligned}
\bar{Q}(D) &:= \inf_{T>0} \min_{\phi:\eta(T)\in\partial D} J(\phi,T) \\
&= \inf_{T>0} \min_{\phi:\eta(T)\in\partial D} \{S(\phi,T) + \epsilon S_0(\phi_0)\}.
\end{aligned}$$
(20)

Proof. We depart from Proposition 3.1 and assume that the initial condition x_0 exhibiting highest probability density is the one minimizing the function $\Gamma(x_0)$. Due to the lack of a map $x_0 \mapsto \phi_{x_0}^*(\cdot)$, provided it requires to solve the variational problem (15), both—path and initial condition—have to be determined simultaneously. Similarly with the terminal time T^* . In other words, the initial state x_0 , the final time T and the connecting path ϕ must be determined together. Let J be a function of these elements, defined as

$$J(\phi, x_0, T) = S(\phi, x_0, T) + \epsilon S_0(x_0),$$

for which we consider

$$\inf_{T>0} \inf_{\substack{x_0 \in \mathbb{R}^{2n} \\ n(T) \in \partial D}} \min_{\substack{\phi:\phi(0)=x_0, \\ n(T) \in \partial D}} J(\phi, x_0, T),$$
(21)

and (T^*, x_0^*, ϕ^*) is the tuple where this minimum is attained. Note that the minimization with respect to ϕ is subject to the hard constraint $\phi(0) = x_0$, and later it becomes unconstrained in the minimization with respect to x_0 . Thus, we can express the previous variational problem as a variational problem only on ϕ and T, with $\phi(0)$ unconstrained. This leads to the result in (20).

We can now write an approximation for the product

$$p[\phi^*|x_0^*, T^*]p_0(x_0^*) \asymp \exp\left(-\epsilon^{-1}\bar{Q}(D)\right).$$
 (22)

The function S_0 defines an additional cost on the initial state $\phi_0 \equiv \phi(0)$. To distinguish the solution of this new variational problem from the solution of (15), we introduce the following definition.

Definition 3.1 (Maximum a posteriori pathway) The extreme function ϕ^{\circledast} solving (20) is called the maximum a posteriori (MAP) pathway.

Remark 3.1 Note that S_0 in equation (20) scales with the diffusion parameter ϵ in J. An intuitive interpretation of this phenomenon is that the bigger the process noise, the more spread is the path ensemble, making it more likely for realizations departing closer to μ to hit the unsafe set D.

Remark 3.2 Similarly to remark 3.1, the smaller the covariance of the initial condition Σ in equation (17), the more likely that the realizations with initial conditions closer to μ will hit the unsafe set D

Upon reaching this point, a variational problem has been proposed in (20), whose solutions ϕ^{\circledast} are extreme paths of J representing the least improbable unsafe trajectories. Since the functional J is constructed based on the quasi-potential Q, resulting in a free end-time variational problem, there is generally no unique solution (for sufficient conditions on optimality, the reader is referred to [17]). Heuristically, however, one could solve the variational problem numerically multiple times with different initial guesses in order to collect different local minimizers. The unsafe paths collected can then be used to design control laws that steer the deterministic trajectory of the system away from these minimizers. This could be achieved, for instance, by solving an optimal control problem that maximizes the relative distances to the unsafe paths or by introducing safety filters based on control barrier functions that guarantee a safety distance from the unsafe trajectories.

4 Application: Spacecraft collision

The maximum a posteriori path is determined for a practical example⁶: a collision between two space objects. The problem is solved numerically using CasADi, and the solution is cross-checked with the necessary conditions for optimality drawn from the maximum principle.

Consider two independent systems $\{X_1(t)\}_{t\in I}$ and $\{X_2(t)\}_{t\in I}$, each in \mathbb{R}^6 , with unperturbed dynamics given by the gradient of the gravity potential U,

$$dR_i(t) = V_i(t)dt, dV_i(t) = -\nabla U(R_i(t))dt + \sqrt{\epsilon\sigma} dW_i(t),$$
(23)

and initial conditions $X_i(0) \sim \{\mu_i, \Sigma_i\}$, for $i \in \{1, 2\}$.

⁶ Code at https://github.com/aitor-rg/LDT-safety

For convenience, we assume that both objects have the same noise parameter ϵ and constant diffusion σ with $a_i = \sigma \sigma^{\top}$, and we augment the state vector $X(t) = (X_1(t), X_2(t))$ so that $\mu = (\mu_1, \mu_2)$, $\Sigma = \text{diag}(\Sigma_1, \Sigma_2)$ and $\phi(t) := (\phi_1(t), \phi_2(t))$ with $\phi_i(t) = (\eta_i(t), \nu_i(t))$ for $i \in \{1, 2\}$, as presented in section 2. Additionally, let $\eta(t) = (\eta_1(t), \eta_2(t))$ and $\nu(t) := (\nu_1(t), \nu_2(t))$. The mean initial conditions are defined in such a way that both space objects come to a distance of 7km from each other, as illustrated in Fig. 2 where the deterministic trajectory (continuous black) and the MAP path solution (dashed red) are shown.

The complete variational problem is 7 :

$$\min_{\phi_0, w, T} \left\{ \int_0^T \frac{1}{2} ||w||^2 dt + \frac{\epsilon}{2} ||\phi_0 - \mu||_{\Sigma}^2 \right\}$$
s.t. $\dot{\eta} = \nu$, (24)
 $\dot{\nu} = -\nabla U(\eta) + \sigma w$, $\forall t \in [0, T]$,
 $\phi(0)$ free, $\eta(T) \in \partial D$, $T \in [T_1, T_2]$

where $\nabla U(\eta) := (\nabla U(\eta_1), \nabla U(\eta_2)), a := \text{diag}(a_1, a_2)$ and $D := \{z \in \mathbb{R}^{12} : f(z) \leq 0\}$. The function f is a terminal constraint defining a collision configuration, e.g,

$$f(\phi(T)) = ||\eta_1(T) - \eta_2(T)||^2 - \gamma \le 0,$$

with the parameter $\gamma \geq 0$ being a safety critical relative distance between the two objects.

The Hamiltonian of the variational problem can be defined for an adjoint state $\lambda(t) := (\lambda_{\eta}(t), \lambda_{\nu}(t))$ as

$$H(\phi, w, \lambda) = -\frac{1}{2}w^{\top}w + \begin{bmatrix} \lambda_{\eta} \\ \lambda_{\nu} \end{bmatrix}^{\top} \begin{bmatrix} \nu \\ -\nabla U(\eta) + \sigma w \end{bmatrix}$$

which provides the MAP path and adjoint equations

$$\dot{\phi}^{\circledast} = \nabla_{\lambda} H = \begin{bmatrix} \nu^{\circledast} \\ -\nabla U(\eta^{\circledast}) + a\lambda_{\nu} \end{bmatrix}, \quad (25a)$$

$$\dot{\lambda} = -\nabla_{\phi} H = \begin{bmatrix} 0 & \nabla^2 U(\eta^{\circledast}) \\ -I & 0 \end{bmatrix} \lambda, \quad (25b)$$

since the optimal deviation is $w^{\circledast} = \sigma^{\top} \lambda_{\nu}$ given by the maximizing condition of the maximum principle. This is the optimal deviation from the deterministic vector field satisfying $f(\phi(T)) \leq 0$. If the trajectory of the deterministic system already satisfy this inequality constraint, then the optimal solution would yield $w = \lambda = 0, \forall t \in I$.



Fig. 2. Conjunction geometry and MAP path solution.

The transversality conditions [17] are, with $\alpha \geq 0$

$$\lambda(0) = -\epsilon \nabla_{\phi} S_0(\phi^{\circledast}(0)), \qquad (26a)$$

$$\lambda(T^{\circledast}) = \alpha \nabla_{\phi} f(\phi^{\circledast}(T^{\circledast})), \qquad (26b)$$

$$\alpha f(\phi(T^{\circledast})) = 0, \qquad (26c)$$

for the adjoint state, and the temporal condition

$$H(\phi^{\circledast}(T^{\circledast}), w^{\circledast}(T^{\circledast}), \lambda(T^{\circledast})) = 0.$$
(27)

Note that the ML and MAP path problems differ slightly in the necessary conditions for optimality. The hard constraint $\phi_0 = x_0$ in the ML path problem is replaced by a transversality condition on the co-state λ of the MAP path problem, that is equation (26a), leaving ϕ_0 free.

Conditions (26) and (27) are satisfied by the obtained numerical solution, which implies that ϕ^{\circledast} is an extremal candidate. The initial co-state $\lambda(0)$ obtained from the numerical solver has been used to integrate the differential equation (25b) and compare it to the trajectory of the entire numerical solution, as shown in Fig. 3. The boundary conditions (26) are also shown. The optimal final time is found to be $T^{\circledast} = 4518.1$ seconds and $\alpha = 6.81 \cdot 10^{-10}$.

Finally, we compare the action S and the magnitude of the deviation ||w|| at each time instant $t \in [0, T^{\circledast}]$ for both, the ML and MAP path solutions, as depicted in Fig. 4. As expected, the MAP path requires less action,

⁷ Notice that solving for the path ϕ and solving for the pair (ϕ_0, w) is equivalent given the differential equation (8).



Fig. 3. Numerical solution of λ superposed with the solution of (29b), and boundary conditions (30a) and (30b).

and thus smaller deviations, than the ML path to realize the URE.



Fig. 4. Comparison between the action S and magnitude of the deviation ||w|| exerted by the ML and MAP paths.

5 Conclusions

We have introduced a new tool to aid the analysis of unsafe trajectories for Hamiltonian systems with uncertain initial conditions, particularly for scenarios where unsafe rare events are present and thus conventional safety analysis tools falter. Through a principle of large deviations, we have approximated the path density of system trajectories, and used Bayes theorem to incorporate normal distributions of initial conditions into the analysis. This enabled the identification of the most likely deviations of the system leading to the occurrence of the rare event, providing crucial information about the configuration of these events in terms of unsafe initial conditions and overall trajectories. Both of these, initial conditions and trajectories, could be used to further exploit safety mechanisms by defining control strategies that incorporate these elements into their design. The feasibility of the proposed procedure has been tested under a realistic high-dimensional and non-linear example, and the results are obtained by numerically solving a variational problem which generally has no unique solution (unless certain regularity conditions are satisfied).

References

- [1] J.-P. Aubin. Viability Theory. Birkhäuser, Boston, 2009.
- [2] M. L. Bujorianu. Stochastic Reachability Analysis of Hybrid Systems. 01 2012.
- [3] R. Chetrite and H. Touchette. Non-equilibrium microcanonical and canonical ensembles and their equivalence. *Phys. Rev. Lett.* 111, 120601, 2013.
- [4] A. Dembo and O. Zeitouni. Large Deviations Techniques and Applications, Stochastic Modelling and Applied Probability. Springer, Berlin, Heidelberg, 2010.
- [5] P. Dupuis and H. Kushner. Minimizing escape probabilities: A large deviations approach. 26th IEEE Conference on Decision and Control, 1987.
- [6] M.I. Freidlin and A.D. Wentzell. Random Perturbations of Dynamical Systems. Springer, Berlin, Heidelberg, 1984.
- [7] T. Grafke and E. Vanden-Eijnden. Numerical computation of rare events via large deviation theory. *Chaos: An Interdisciplinary Journal of Nonlinear Science* 29, 2019.
- [8] A. R. Gómez and R. Wisniewski. Stochastic safety in space conjunctions. *IEEE 61st Conference on Decision and Control* (CDC), 2022.
- [9] S. Kaynama, J. Maidens, M. Oishi, I.M. Mitchell, and G.A. Dumont. Computing the viability kernel using maximal reachable sets. *Proceedings of the 15th ACM International Conference on Hybrid Systems: Computation and Control*, 2012.
- [10] S. Kim, S.M. Meerkov, and T. Runolfsson. Aiming control: Design of residence probability controllers. *Automatica*, 28, 557–564, 1992.
- [11] A. Kovaleva. Control of a weakly perturbed lagrangian system with a guaranteed escape rate. 8th IFAC Symposium on Nonlinear Control Systems 43, 2010.
- [12] H. Kushner. Approximation and Weak Convergence Methods for Random Processes, with Applications to Stochastic System Theory. MA: MIT Press, Cambridge, 1984.
- [13] S.M. Meerkov and T. Runolfsson. Residence time control. IEEE Transactions on Automatic Control, 1988.
- [14] I.M. Mitchell. Comparing Forward and Backward Reachability as Tools for Safety Analysis. Springer, Berlin, Heidelberg, 2007.
- [15] S. Prajna and A. Jadbabaie. Safety Verification of Hybrid Systems Using Barrier Certificates. Springer, Berlin, Heidelberg, 2004.
- [16] M. Schmid and J.L. Crassidis. A New Stochastic Control Paradigm Employing Large Deviations Theory. American Institute of Aeronautics and Astronautics, San Diego, California, 2019.
- [17] A. Seierstad and K. Sydsæter. Optimal Control Theory with Economic Applications, volume 1st Edition, Volume 24. North Holland, 1987.
- [18] H. Touchette. Large deviation approach to statistical mechanics. *Physics Reports* 478, 1–69, 2009.
- [19] P Whittle. A risk-sensitive maximum principle. Systems and Control Letters 15, 183–192, 1990.
- [20] R. Wisniewski and M. L. Bujorianu. Safety of stochastic systems: An analytic and computational approach. *Automatica*, 2021.
- [21] R. Wisniewski, M. L. Bujorianu, and C. Sloth. p-safe analysis of stochastic hybrid processes. *IEEE Transactions* on Automatic Control, 65(12):5220–5235, 2020.