

Newman's theorem via Carathéodory

Ali Mohammad Lavasani*, Yaqiao Li†, Mehran Shakerinava‡

June 14, 2024

Abstract

We give a streamlined short proof of Newman's theorem in communication complexity by applying the classical and the approximate Carathéodory's theorems.

Newman's theorem is a fundamental result in communication complexity. It says that using public randomness can only gain a logarithmic advantage in communication cost comparing to private randomness. The standard proof [5, 8, 7] uses the probabilistic method and the Chernoff bound. Here, we apply Carathéodory's theorems directly. Our proof is not too different from the standard proof, as the approximate Carathéodory is proved via a similar method. Though, the alternative proof seems neater. We note that different versions of approximate Carathéodory's theorems and their various applications in computer science have been discussed in [1, 3].

Let $\text{conv}(S)$ denote the convex hull of a set $S \subseteq \mathbb{R}^n$. Let $\|\cdot\|_\infty$ denote the usual L_∞ norm. Let R_ϵ^{pri} and R_ϵ^{pub} denote the communication cost using private and public randomness, respectively.

Proposition 1 (Carathéodory,[2, 4]). *Let $S \subseteq \mathbb{R}^n$. Every $x \in \text{conv}(S)$ can be written as a convex combination of at most $n + 1$ points from S .*

Proposition 2 (Approximate Carathéodory,[1]). *Let $S \subseteq \mathbb{R}^n$ satisfy $\max_{y \in S} \|y\|_\infty \leq 1$. Let $\delta > 0$. For every $x \in \text{conv}(S)$, there exists $x' \in \text{conv}(S)$, such that $\|x - x'\|_\infty \leq \delta$, and x' is a convex combination of at most $O(\frac{\log |S|}{\delta})$ many points from S .*

Theorem 1 (Newman, [6]). *Let $f : \{0, 1\}^n \times \{0, 1\}^n \rightarrow \{0, 1\}$ be a Boolean function. Let $\epsilon, \delta > 0$. Then, $R_{\epsilon+\delta}^{\text{pri}}(f) \leq R_\epsilon^{\text{pub}}(f) + O(\log n + \log \delta^{-1})$.*

Proof. We view $f \in \mathbb{R}^N$ for $N = 2^{n+1}$. By definition of R_ϵ^{pub} , there exists a set of deterministic protocols, denoted by $S = \{P_1, \dots, P_q\}$, where P_i is a Boolean function and $P_i \in \mathbb{R}^N$, satisfying

$$\|f - P\|_\infty \leq \epsilon \tag{1}$$

for some $P \in \mathbb{R}^N$ where P is a probabilistic average of P_i 's, hence, $P \in \text{conv}(S)$. By Proposition 1, there exists a subset $S' \subseteq S$ of size $|S'| \leq N + 1$ such that $P \in \text{conv}(S')$. Because every P_i is a Boolean-valued function, we have $\max_{y \in S'} \|y\|_\infty \leq 1$. By Proposition 2, there exists another point $P' \in \text{conv}(S')$ that can be written as a convex combination of at most $k = O(\frac{\log |S'|}{\delta})$ points from S' , and

$$\|P - P'\|_\infty \leq \delta. \tag{2}$$

*Concordia University, ali.mohammadlavasani@concordia.ca

†Shenzhen University of Advanced Technology, yqlipublic@gmail.com

‡McGill University, mehranshakerinava@gmail.com

WLOG, let $P' = \sum_{i=1}^k \mu_i P_i$, where $\sum_i \mu_i = 1$ and $\mu_i \in [0, 1]$. Now, Alice and Bob compute f using private randomness, as follows: Alice privately samples a random number $i \in [k]$ according to the distribution (μ_1, \dots, μ_k) , she sends i to Bob using at most $\log k + 1 = O(\log \log |S'| + \log \delta^{-1}) = O(\log n + \log \delta^{-1})$ bits. Then, they run the deterministic protocol P_i . By (1) and (2), $\|f - P'\|_\infty \leq \epsilon + \delta$. This gives a private randomness protocol with the desired error and cost. \square

References

- [1] Siddharth Barman. Approximating nash equilibria and dense bipartite subgraphs via an approximate version of caratheodory’s theorem. In *Proceedings of the forty-seventh annual ACM Symposium on Theory of computing*, pages 361–369, 2015.
- [2] Constantin Carathéodory. Über den variabilitätsbereich der koeffizienten von potenzreihen, die gegebene werte nicht annehmen. *Mathematische Annalen*, 64(1):95–115, 1907.
- [3] Cyrille W Combettes and Sebastian Pokutta. Revisiting the approximate carathéodory problem via the frank-wolfe algorithm. *Mathematical Programming*, 197(1):191–214, 2023.
- [4] Jesús De Loera, Xavier Goaoc, Frédéric Meunier, and Nabil Mustafa. The discrete yet ubiquitous theorems of carathéodory, helly, sperner, tucker, and tverberg. *Bulletin of the American Mathematical Society*, 56(3):415–511, 2019.
- [5] Eyal Kushilevitz and Noam Nisan. *Communication Complexity*. Cambridge University Press, 1997.
- [6] Ilan Newman. Private vs. common random bits in communication complexity. *Information processing letters*, 39(2):67–71, 1991.
- [7] Anup Rao and Amir Yehudayoff. *Communication Complexity: and Applications*. Cambridge University Press, 2020.
- [8] Tim Roughgarden et al. Communication complexity (for algorithm gesigners). *Foundations and Trends® in Theoretical Computer Science*, 11(3–4):217–404, 2016.