Received XX Month, XXXX; revised XX Month, XXXX; accepted XX Month, XXXX; Date of publication XX Month, XXXX; date of current version XX Month, XXXX.

Digital Object Identifier 10.1109/OJAP.2020.1234567

Beam Maps of the Canadian Hydrogen Intensity Mapping Experiment (CHIME) Measured with a Drone

WILL TYNDALL¹ **, ALEX REDA**¹ **, J. RICHARD SHAW**² **, KEVIN BANDURA**3,⁴ **, ARNAB CHAKRABORTY**5,⁶ **, EMILY KUHN**1,⁷ **, JOSHUA MacEACHERN**² **, JUAN MENA-PARRA**8,⁹ **,** LAURA NEWBURGH¹, ANNA ORDOG 10,11 , TRISTAN PINSONNEAULT-MAROTTE 2 , **ANNA ROSE POLISH**12**, BEN SALIWANCHIK**13**, PRANAV SANGHAVI**¹ **, SETH R. SIEGEL**5,6,14**, AUDREY WHITMER**¹ **, DALLAS WULF**5,⁶

¹ Department of Physics, Yale University, New Haven, CT 06511 USA ²Department of Physics and Astronomy, University of British Columbia, Vancouver, BC Canada ³Department of Computer Science and Electrical Engineering, West Virginia University, Morgantown, WV, USA ⁴Center for Gravitational Waves and Cosmology, West Virginia University, Morgantown, WV, USA Department of Physics, McGill University, Montreal, QC, Canada ⁶Trottier Space Institute, McGill University, Montreal, QC, Canada ⁷Jet Propulsion Laboratory, California Institute of Technology, 4800 Oak Grove Drive, Pasadena, CA, 91109, USA
⁸Dunlap Institute for Astronomy and Astrophysics, University of Toronto, Toronto, ON, Canada ⁹ David A. Dunlap Department of Astronomy and Astrophysics, University of Toronto, Toronto, ON, Canada ¹⁰Department of Computer Science, Math, Physics, & Statistics, University of British Columbia, Okanagan Campus, Kelowna, BC V1V 1V7, Canada ¹¹Dominion Radio Astrophysical Observatory, Herzberg Astronomy and Astrophysics Research Center, National Research Council Canada, Penticton, BC, Canada ¹² Center for Astrophysics, Harvard and Smithsonian, Cambridge, MA 02138, USA 13 Instrumentation Division, Brookhaven National Laboratory, Upton, NY, 11973, USA ¹⁴ Perimeter Institute for Theoretical Physics, 31 Caroline Street N, Waterloo, ON N25 2YL, Canada CORRESPONDING AUTHOR: Will Tyndall (e-mail: will.tyndall@yale.edu). IEEE OJAP encourages responsible authorship practices and the provision of information about the specific contribution of each author This work was supported by the Natural Sciences and Engineering Research Council (NSERC) of Canada.

ABSTRACT We present beam measurements of the CHIME telescope using a radio calibration source deployed on a drone payload. During test flights, the pulsing calibration source and the telescope were synchronized to GPS time, enabling in-situ background subtraction for the full N^2 visibility matrix for one CHIME cylindrical reflector. We use the autocorrelation products to estimate the primary beam width and centroid location, and compare these quantities to solar transit measurements and holographic measurements where they overlap on the sky. We find that the drone, solar, and holography data have similar beam parameter evolution across frequency and both spatial coordinates. This paper presents the first drone-based beam measurement of a large cylindrical radio interferometer. Furthermore, the unique analysis and instrumentation described in this paper lays the foundation for near-field measurements of experiments like CHIME.

INDEX TERMS Antenna measurements, telescopes, unmanned aerial vehicle (UAV), unmanned aerial system (UAS)

I. INTRODUCTION

Future and current 21 cm intensity mapping telescopes such as CHIME [\[1\]](#page-10-0), CHORD [\[2\]](#page-10-1), HERA [\[3\]](#page-10-2), HIRAX [\[4\]](#page-10-3), LOFAR [\[5\]](#page-10-4), MWA [\[6\]](#page-10-5), SKA [\[7\]](#page-10-6) [\[8\]](#page-10-7) will measure the distribution of neutral hydrogen across a wide range of redshifts for a variety of science goals [\[9\]](#page-10-8). Isolating the cosmological

21 cm signal by removing bright radio foregrounds [\[10\]](#page-10-9)– [\[15\]](#page-11-0) will require precision beam measurements to better than 1% uncertainty [\[10\]](#page-10-9), [\[16\]](#page-11-1)–[\[19\]](#page-11-2). Calibration with well known radio point sources is difficult for stationary (un-steerable) drift scanning instruments, and one promising alternative is to use radio sources onboard drones as piloted calibration references [\[19\]](#page-11-2), [\[20\]](#page-11-3).

tween the drone and solar data maps and fitted primary beam quantities across feed, frequency, and spatial coordinates.

Decades of technical innovations and cost reductions have improved the feasibility of using unmanned aerial vehicles (UAVs) as precision instruments in a research setting, particularly for calibrating microwave and radio telescopes and antennas [\[21\]](#page-11-4)–[\[27\]](#page-11-5). An additional benefit of using drones is the capability of measuring antenna performance on site, within the configuration of the larger array and surrounding environment [\[20\]](#page-11-3), [\[28\]](#page-11-6). With high precision positional accuracy, autopilot software, and carefully designed flightplans, UAV calibration can directly measure the far-field beam pattern of telescopes and arrays. Where the far-field is inaccessible the (complex) near-field electric field could be measured and algorithmically transformed into far-field beam patterns [\[19\]](#page-11-2), [\[21\]](#page-11-4), [\[23\]](#page-11-7), [\[28\]](#page-11-6), [\[29\]](#page-11-8).

CHIME is a radio interferometer operating between 400- 800 MHz to measure redshifted neutral hydrogen. The cylindrical reflectors observe the sky by drift scanning with its large field of view. The resulting primary beam poses a unique challenge for drone beam mapping for several reasons: (1) the far-field is distant, at altitudes in excess of 1 km at all frequencies, (2) it is highly elliptical $(1.2-2°$ East-West, and ∼ 120◦ North-South) with frequency- and declination-dependent variations [\[1\]](#page-10-0), [\[30\]](#page-11-9).

In this paper we present measurements of the CHIME primary beam obtained with drone-based beam mapping techniques. We acquire these measurements at a declination comparable to existing solar [\[30\]](#page-11-9) and holography [\[31\]](#page-11-10) beam patterns. To detect the pulsing drone calibration signal we utilize the pulsar gating mode of CHIME to perform insitu background subtraction. The resulting comparisons we present here provide independent validation of sky-based beam models and demonstrate the synchronization of the calibrator and receiver enabling future measurements of CHIME with a drone-based platform (e.g. polarization, repeatability, near-field to far-field).

Due to flight altitude restrictions, the flight took place squarely in the radiating near-field, hindering quantitative comparisons to the beams obtained from solar and holography datasets. Instead, we compare best-fit main beam parameters and other beam properties across frequency and declination to test the feasibility of these methods. These measurements will inform future near-field beam mapping efforts and near-field to far-field transformations of measured CHIME beams.

In Section [II](#page-1-0) we discuss the methodology used in this paper, including the CHIME telescope and drone instruments, the CHIME configuration developed for drone beam mapping, and the list of performed drone flights. In Section [III](#page-3-0) we describe the data sets and data processing we developed to compare drone beam measurements to solar and holography beam measurements, as well as an independent drone altitude determination. In Section [IV](#page-6-0) we present comparisons be-

II. METHODOLOGY

A. CHIME

The Canadian Hydrogen Intensity Mapping Experiment (CHIME) is a radio interferometer observing from the Dominion Radio Astrophysical Observatory (DRAO) in British Columbia, Canada, whose array center is located at longitude 49.3208N, latitude -119.6236E and height ∼545m above sea level. CHIME's primary science objective is to measure the distribution of neutral hydrogen (HI) over the sky as a biased tracer of the underlying distribution of matter [\[10\]](#page-10-9), [\[32\]](#page-11-11)– [\[39\]](#page-12-0). The statistics of this distribution probe a cosmological standard ruler, the baryon acoustic oscillation (BAO) scale. Tracking the evolution of this scale over cosmic time (i.e. redshift) in turn provides a constraint on the expansion history of the Universe (see most recent results in [\[40\]](#page-12-1) and references therein).

To this end, CHIME is designed to observe the redshifted 21 cm emission of HI over a wide band between 400- 800 MHz, corresponding to redshift $z = 0.8 - 2.5$, considered a critical epoch for constraining competing models of dark energy vis-a-vis their impact on the expansion history. The CHIME instrument is described in more detail in [\[1\]](#page-10-0), briefly, the telescope consists of four parabolic cylinders, 20 m wide (East-West) by 100 m long (North-South). Each cylinder is outfitted with 256 dual-polarization cloverleaf antennas separated by ∼30 cm within the inner 80 m length of the focal line. The telescope has no moving parts; the cylindrical reflectors provide a beam shape which is focused in the transverse East-West direction but extends nearly from horizon-to-horizon in the North-South direction. This accommodates a "driftscan" observing strategy; every 24 hours the telescope observes the entire sky accessible from the CHIME latitude due to the Earth's rotation. This stationary design complicates beam calibration, as we cannot "point" the beam at a suitable calibrator. Alternatively, in this paper, we deploy a remotely controlled drone outfitted with a radiating payload as calibrator source to sample the instrument field of view.

B. Drone Instrumentation

Flights are performed with a payload mounted on a DJI Matrice 600 Pro with a Real-Time Kinematic (RTK) GPS accessory to provide ∼1 cm location accuracy. The payload consists of a broad-band white noise generator, bandpass filters, and a switching board which either passes the white noise signal or terminates on 50 Ω on a trigger. The trigger is generated using a separate GPS clock in the payload. For measurements on CHIME, the signal was set to pulse on at the start of a pulse-per-second trigger from the GPS, remain on for 0.5 s, then turn off for 0.5 s, generating a sequence synchronized to the GPS pulse-per-second. The signal is transmitted from a single-polarization biconical antenna which has a broad beam pattern of $\sim 60^{\circ}$ Full-

FIGURE 1. Photograph of the Matrice 600 Pro drone with payload, in flight at the DRAO during measurements.

width-half-maximum (FWHM). Because the antenna is fixed to the drone body, the drone's heading determines which linear polarization broadcast during flight.

C. CHIME Configuration for Drone Beammapping

The drone noise source is a single mode source seen by all CHIME feeds. After the N^2 correlation there is effectively an equal amount of information in each entry of the visibility matrix and to maximise the sensitivity of the measurements we would like to retain all this information. However this poses a severe data rate challenge. To avoid smearing within an integration frame we must reduce the accumulation time from the standard 10 s down to 2 s, but this increased data rate of around 50 TB/hour can neither be offloaded from the CHIME X-engine nor can any reasonable length of data be stored within the on-site storage. To get around this we used the existing capabilities of the CHIME Science Data Processor (SDP) system to achieve a significant compression of the data [\[1\]](#page-10-0).

First we note that although there is signal in each element of the correlation matrix, for a single mode noise source all of this is captured within the first eigenmode of the matrix. Although any motion of the drone within an integration frame can generate additional modes, at 2 s cadence it is sufficient to record only a small number of the eigenvalues and vectors of the matrix to capture all of the information. Generating this eigendecomposition is computationally costly, and CHIME was designed to be able to do this once per 10 s frame. To fit within the computational footprint we only include data from a single cylinder of the instrument, which further reduces the output data rate. As we use an iterative algorithm for this calculation this gives only an $\sim N^2 = 16$ computational saving, rather than the $N³$ increase we would expect for a full calculation.

The set of modified processing stages we perform on the individual X-engine nodes are:

- Use the existing CHIME pulsar gating capability to take on-off differences of the noise source signal on the full N^2 visibility matrix. This is possible as both CHIME's clock and that of the noise source are locked to the GPS PPS signal. This is then integrated to 2 s cadence.
- The submatrix corresponding to the feeds within cylinder C (the cylinder to the east of the array center, see Figure [3\)](#page-3-1) is extracted.
- The existing eigendecomposition capability is used to calculate the largest 10 eigenvalues and their eigenvectors.

These eigenmodes as well as the full visibility matrix for cylinder C is then sent to the receiver node of the SDP system for the final processing, and writing of the following data products:

- The visibility matrix is written out for a set of 64 frequencies to allow us to verify that the eigendecomposition extracted all of the information.
- For the full set of frequencies we write out the eigenvalues and eigenvectors to allow full sensitivity analysis of the data, as well as measurements of phase variation.
- For the full set of frequencies we write out the 512 autocorrelations from both polarizations of the cylinder C feeds. This gives a simple and compact dataset, but at lower sensitivity and without the ability to constrain phase variations.

The gated power for each feed can be reconstructed using the strongest 10 eigenmodes from a single cylinder. The analysis in this paper uses the first eigenmode only, which sufficiently captures all of the drone signal while allowing for a lower noise floor than what is possible using the directly measured power contained in the autocorrelations.

D. Drone Flights

We performed ten flights over the CHIME telescope; in this paper we present results from the flight at the approximate declination of Virgo A, where independent beam measurements of CHIME from both holography data [\[31\]](#page-11-10) and solar data [\[30\]](#page-11-9) are available. Replicating the trajectory of Virgo A and the Sun through the CHIME primary beam required a 35◦ zenith angle drone flight relative to the array center. Due to altitude restrictions, we performed a low velocity flight at a conservative altitude to maximize the spatial resolution of the transit data. This flight was performed ∼220 m South from the center of the array, corresponding to distances between 180 - 250 m with respect to feed location along the focal line. Relative to the CHIME array center, the flight spanned -100 m to +100 m from East-to-West at an altitude of ∼307 m, in accordance with our flight ceiling limits from TransportCanada. The first flight was flown with a heading of ∼ 0 ◦ [North] to measure co-polarizations corresponding to CHIME's N (YY) polarization, and the second flight was flown with a heading of $\sim 90°$ [East] to measure the orthogonal (XX) polarization. The typical distance from CHIME for these flights ranges from 350 m - 390 m. As a result, this flight plan corresponds to the near-field for all CHIME antennas (the CHIME far-field for a single feed is >1 km). The time for each polarization pass was 3.4 mins.

III. DATA PROCESSING

A. Map Projections

During data processing, each CHIME correlation frame is associated with a concurrent drone position measurement from the RTK unit, which expresses the drone location in latitude, longitude, and height coordinates. A conversion to a local Cartesian reference frame^{[1](#page-3-2)} is performed using the latitude, longitude, and height of a known reference point (in this instance, the center of the CHIME array provided by surveying).

CHIME beam parameters are typically presented in either celestial coordinates (Hour Angle and Declination) or orthographic coordinates ('TelX' and 'TelY') in which the coordinate TelX is always parallel to East and TelY to North, such that the beam is not distorted by sky curvature [\[30\]](#page-11-9). The linear array of the CHIME feeds along the cylinder results in each feed 'seeing' the drone at a different declination (see Figure [2\)](#page-3-3). As a result, we compute the apparent position in RA/Dec or TelX/TelY coordinates using the drone location and relative position of each feed with respect to the center of the CHIME array. An example of one pass from the flight, in each of these coordinates, is shown in Figure [3](#page-3-1)

The mapping between telescope feed and declination crucially depends on the altitude of the drone flight. The altitude must be measured relative to the phase center of the array (where incident rays are focused onto the feedline). We model the phase center of each feed by extending the incident ray to an *image* of the feedline placed beneath the primary reflector at a distance of 5 m (the focal length). This defines the image plane. The height of the CHIME cylinders above ground is \sim 1 m, thus the image plane sits \sim 4 m below the ground surface. As a result, we expect to use an altitude of 307.6 m (corresponding to 311.6 m above the image plane), although we independently constrain the effective altitude in Section [III\)](#page-3-0).

B. Available Datasets

Comparisons are possible between three independent data sets (a) Drone measurements; (b) Solar measurements; and (c) Holography measurements. The overlap between these data sources can be seen in TelX/TelY coordinates in Figure [4.](#page-4-0) In the drone flights described above, because each feed will map to a different declination, the flights mapped out declinations between 10° to 20° DEC and hour angles between -15° +15 $^\circ$ HA. The drone data declination range overlaps with a portion of the data acquired during solar transits to map the CHIME beam shape, which range from -23◦ to +23◦ DEC. The drone data also overlaps with one

FIGURE 2. Optical path of calibration signal from drone-based transmitter as seen by CHIME feeds. The incoming radio waves are focused by the cylindrical reflector onto the feeds, which each observe the drone at a different elevation. In the reference frame of the southernmost feed (Feed 0, black) the drone appears to be higher in the sky than for feeds in the middle (Feed 127, purple) or at the North (Feed 256, yellow) end of the cylinder. The drone altitude in this figure is substantially lower than the flight altitude to exaggerate the feed-dependent parallax. The reference frame of the local cartesian coordinate system is the survey location of the center of the CHIME array (yellow star). See text for more details.

FIGURE 3. Coordinate conversions applied to data from a drone flight at 35 degrees of zenith angle. One transit across the beam of Cylinder C is shown true to scale in a local Cartesian coordinate system (left). The resulting transformations are shown for Cartesian (upper right), Celestial (middle right), and Orthographic (TelX/TelY) (lower right) for each feed using the color scale from Figure [2.](#page-3-3)

¹[PyGeodesy](https://pypi.org/project/PyGeodesy/)

constant declination such as the holographic measurements of Virgo A and the drone flight are curved in TelX/TelY (see Figure [4\)](#page-4-0), which distorts sidelobe features outside $|TeIX| \gtrsim 0.25$. Further, because this range is far larger than the beamwidths, we found any correction to the centroid and FWHM fits of the primary beam are small compared to fitting errors.

Data Set	Solar	Holography	Drone
Frequency Bins	1024	1024	1024
Feeds	1 (B ≤ 10 m)	256	256
Polarizations	\mathcal{L}	2	2
TelX	$-1.0 - +1.0$	$-0.5 - +0.5$	$-0.25 - +0.25$
TelY	$-1.0 - 0$	$(-0.88, -0.70, -0.59,$	$-0.62 - -0.49$
		$-0.46, -0.15, 0.16$	
Declination $(°)$	$-23 - 123$	$(-12.1, 5.0, 12.5,$	$+10 - +20$
		22.0, 40.75, 58.75)	
Hour Angle $(°)$	$-60 - +60$	$-30 - +30$	$-15 - +15$

TABLE 1. Survey coverage and parameter space of each data set. Virgo A for the holographic data set is in bold.

FIGURE 4. Beam characterization measurements have been calculated from three unique data sets acquired in different portions of CHIME's field of view: Solar beam measurements are presented in a continuous semicircular slice. Holographic measurements of galactic radio sources appear as pale yellow arcs. Drone measurements are presented as grids with yellow outlines, while the drone measurement analyzed in this paper is outlined with a dashed yellow line. Comparison of the FWHM and Centroid measurements obtained from these data sets are shown in Figures [9](#page-7-0) & [8.](#page-7-1)

source measured via holography, Virgo A at +12[°] DEC. All three data sets overlap at TelY ~ -0.6 which corresponds to a declination of $\sim 12^{\circ}$.

The drone data presented here are the first eigenmode (from the decomposition described in Section [C\)](#page-2-0) for each feed on Cylinder C, and are measured in the near-field of CHIME. The solar data products are averages of crosscorrelation visibilities of feeds within 10 m of each other, restricted to pairs of feeds within the same cylinder (intracylinder cross-correlations with $B \le 10$ m). The 10 m distance was chosen so that the feed spacing does not resolve the solar power away, and so are an estimate for the average primary beam, averaged across all feeds and cylinders. The holography data directly measures the far-field primary beam of each CHIME feed, and so feeds in Cylinder C can be selected and compared with the drone data. The holography data can also be processed with the same averaging methods used for the solar data for more direct comparisons across those two datasets. The parameter space spanned by these three data sets is given in Table [1.](#page-4-1)

The solar data is projected into the orthographic coordinate system (TelX, TelY) with primary axes aligned North-South and East-West. The advantage of this projection is that it orthogonalizes the features of the beam, and thus we use this projection throughout this paper. However, sources at

C. Main Beam Fitting

We fit a 1d Gaussian function to the flight data in TelX to determine four parameters, as shown in Figure [5:](#page-5-0)

$$
P(\nu, \phi) = Ae^{\frac{(\phi - \phi_0)^2}{2\sigma^2}} + B \tag{1}
$$

where A is the amplitude, B is the background level, ϕ_0 is the centroid location in TelX, and $2.355 * \sigma$ is the fullwidth-half-max (FWHM). Each combination of feed index, frequency, and polarization is analyzed separately for the drone and holography datasets for CHIME cylinder C.

D. Altitude Estimation

While exploring the evolution of the FWHM parameter in frequency and declination space we were able to determine the drone flight altitude with only a mild prior on the drone altitude from the drone sensors. This best-fit altitude differed from the altitude reported by the RTK system by a constant offset of \sim 5 m.

In Figure [6](#page-5-1) we present the FWHM in each polarization as a function of frequency and TelY for all three data sources. The FWHM parameter for each data product has been normalized by the median value in each frequency bin. The solar data spans the shown coordinate space, and is present in the background of each plot in the figure. The holography data is overlaid with the same normalization at the associated source declinations, neatly fitting within the ripple pattern present in the solar FWHM results. The best-fit FWHM results for the drone data are overlaid at the associated TelY \in [-.62, -.49], and fall within the median-valued contour for the solar data at the associated declination.

FIGURE 5. CHIME data acquired during the drone flight. The power measured by feed 190 (corresponding to TelY coordinate -0.59 and declination 13.15◦ **) is shown at three frequencies in both polarizations (XX top, YY bottom). The power has been normalized by the amplitude of the best-fit 1d Gaussian from Equation [1](#page-4-2) (dotted line). The beam narrows with increasing frequency, as expected, and frequency-dependent sidelobe structure beyond the main beam shape is also apparent in the data.**

Using an altitude value of 307.6 m (311.6 m above the image plane) from the drone's internal altimeter and RTK sensors, the drone FWHM results appeared offset by TelY ≈ -0.005 relative to the solar FWHM pattern. We estimated that a \sim 5 m offset in flight altitude would account for this shift in TelY, suggesting the flight altitude was instead 312.6 m (316.6 m above the image plane). To further quantify this offset, we use a Pearson R (PR) correlation coefficient computation as follows. Our geometric model of the drone flight prescribes a TelY value to each telescope feed, defined by the position and altitude of the drone. We can independently determine a mapping between telescope feed and TelY by computing the correlation between the drone and solar FWHM curves. Specifically, for each telescope feed in the drone data we determine the TelY value in the solar data that maximizes the PR correlation coefficient. This associates each feed in the drone data with a best-fit TelY value. This is computed for each feed independently and we do not impose any requirements (e.g., that the FWHM pattern of all feeds taken together must match the solar data with a given geometric model).

The PR coefficients are shown in Figure [7,](#page-6-1) associating each of the 256 feeds used in the drone measurement (xaxis) with a Solar TelY value (y-axis). The results are roughly consistent with a constant altitude offset, a flight height of 315.1 m above the ground (319.1 m above the image plane), indicated in the figure. Figure [7](#page-6-1) also shows

FIGURE 6. Best-fit FWHM as a function of frequency and altitude for the XX (top) and YY (bottom) polarizations. In each panel, the Solar data spans the coordinate space, the Drone data is overlaid for TelY within the range of (-0.62,-0.48), and the Holography measurements from Virgo A are plotted as a band of points at TelY∼ −0.6**. The colors are normalized to the median value within each frequency bin, and a contour at the median value has been traced over the solar data to enhance the appearance of the 30MHz ripple feature. The evolution of the FWHM parameter follows the same contour for all three data sets, and shows the characteristic 30MHz frequency ripple moving predictably as the altitude/declination increases.**

that the PR coefficients give a unique mapping between TelY and feed location for the YY polarization; however for the XX polarization, additional offsets also correlate strongly, although still has a clear maximum at the same location as the YY solution. As we'll show below, we suspect this is because the FWHMs for the XX polarization have more RFI-flagged frequencies and additional substructure in the FWHM pattern beyond the 30 MHz ripple. Figure [7](#page-6-1) also shows the maximum PR points and the varying altitude curves after subtracting the TelY per feed mapping prescribed by the geometric model. This analysis suggests the magnitude of the global altitude offset is $+7.5$ m relative to the altitude reported by the drone. After this correction, a clear linear trend remains between TelY and chime feed. This may indicate there are unaccounted-for offsets (e.g. in the latitude and longitude sensors for the drone), residual effects from the different processing between the data sets (drone data is per-feed, while solar data is formed from short baselines), or effects from the near-field evolution the measurement). In addition, the residual sawtooth pattern is reminscent of the centroid offsets per feed (see Section [C\)](#page-4-3) which were not accounted for in this analysis.

This offset could arise from inaccurate altimeter or RTK readings, a failure to account for height differences between the CHIME Center position provided by surveys and the terrain elevation directly below the drone transit trajectory, or differences between the terrain model used by the drone autopilot software and the site surveying. Additionally, because our drone platform produces several altitude estimation variables in each flight data file, which can be discrepant by up to 10 m, it is not clear which variable (e.g. RTK, barometric altimeter, inertial measurement unit) is ultimately the most accurate. Further investigation is ongoing to assess the height accuracy of the drone sensors.

IV. RESULTS

A. Centroid and FWHM Measurements

From the best-fit 1d Gaussian, we obtain centroid and FWHM parameters as described in [C.](#page-4-3) Both polarizations are measured independently in subsequent transits at the same zenith angle. Figure [8](#page-7-1) shows the best-fit centroid values from the drone and holography data and compares them to photographic measurements performed along the CHIME feedline to measure feed displacement along the focal line [\[41\]](#page-12-2) Because the solar data does not include any feed-level data, it is not represented in Figure [8.](#page-7-1) Although the drone measurements are in the near-field, the centroid values and trend along the focal line from the drone agree with the two far-field measurements and follow the feed displacements. The centroid trend is known, and was previously published in [\[1\]](#page-10-0).

The FWHM parameter is compared for all data sets at TelY ≈ -0.6 as a function of frequency in Figure [9,](#page-7-0) and in particular show the solar data (formed from combining $B \le 10m$, the drone and holography data from a single feed, and the holography data combined to form a data set equivalent to the solar data ($B \le 10m$). The characteristic 30 MHz ripple feature is aligned for both polarizations at all frequencies, as one would expect from Figure [6.](#page-5-1) The amplitude of the ripple feature is is generally comparable between all data sets for the XX polarization, though the solar FWHM is wider than the holography and drone data sets throughout the frequency band. For the YY polarization, we find that the combined-feed holography data matches its solar counterpart very well, while the ripple amplitude is slightly higher for the single-feed holography data compared to the combined-feed holography data. This suggests that feed-to-feed variations may influence the amplitude of the ripple feature. We also find the peak FWHM amplitude found in the drone data is typically significantly higher than the

FIGURE 7. Pearson-R (PR) correlation coefficients calculated between drone data and solar data for each polarization (top XX, middle YY) of the 256 CHIME feeds mapped by the drone. The maximum value in each column (white dots) associates a CHIME feed with a TelY bin in the solar data, restricted to lie within bounds (red lines) to eliminate spurious outliers. Also shown are colored arcs indicating various drone flight altitudes above the ground level. The maximum PR coefficient between the drone and Virgo A holography data occurs at feed 210 (yellow star) and falls along the TelY and feed mapping obtained from correlations with solar data. The bottom panel shows the colored arcs and maximum PR correlation coefficients (white and purple dots) for both polarizations after subtracting the TelY and feed mapping prescribed by the geometric model.

FIGURE 8. Measured centroid position from Drone and Holography data sets as a function of TelX for both XX (left panel) and YY (right panel) polarizations. Centroid positions from all 256 feeds and 1024 frequencies from the drone data set are shown (small navy dots) with the median overplotted (large navy dots). Shaded navy contours indicate 68.2% and 95.4% confidence intervals (equivalent to 1σ **and 2**σ **errors, respectively). Centroid positions from holography of Virgo A are similarly indicated (small yellow dots and large yellow dots). These centroid measurements are consistent with photogrammetric measurements of the feed displacement presented in a doctoral thesis [\[41\]](#page-12-2) (large purple dots). All data sets have been mean-subtracted such that absolute offsets are not included.**

other data sets for YY polarization, which prompted further investigation.

Figure [10](#page-8-0) contains drone transit measurements for frequencies within 676.2-695.7 MHz. This frequency band follows the evolution of the 30 MHz ripple feature in the $FWHM(f)$ curve from a maximum to a minimum, indicated by purple region in Figure [9.](#page-7-0) In both polarizations, we expect to find a well defined main beam at TelX=0.0 that ends at a first null around $\pm 0.04 \leq$ TelX $\leq \pm 0.05$). Wherever the 30 MHz ripple feature reaches a local minimum, (e.g. $f = 695 \text{ MHz}$ plotted in black in Figure [10,](#page-8-0) the main beam and sidelobes are discrete and the best-fit Gaussian FWHM values agree with the solar and holography datasets as expected for both the XX (top panel) and YY (bottom panel) polarizations. Conversely, wherever the 30 MHz ripple reaches a local maximum, the primary beam and first sidelobe are not separated by a null in the drone transit data. Instead, the main beam and first sidelobe are combined and the Gaussian fit finds a FWHM that is wider than expected. Examples can be found in both the XX polarization (e.g. $f = 685.0$ MHz plotted in pink in the top panel of Figure [10\)](#page-8-0) and YY polarization (e.g. $f = 677.5 \text{ MHz}$ plotted in yellow in the bottom panel of Figure [10\)](#page-8-0).

To demonstrate this behavior, we compare both polarizations at $f = 677.5 \text{ MHz}$ (plotted in yellow). The XX polarization data clearly recovers the main beam and two well-defined sidelobes. The YY polarization data only recovers the second sidelobe (centered at TelX $\approx \pm 0.1$) while the first sidelobe (centered at TelX $\approx \pm 0.05$ in XX) been been incorporated into the main beam. This behavior evolves smoothly in both polarizations as we progress along

FIGURE 9. Measured FWHM from Drone, Holography (both for a single feed and an average of baselines B ≤ 10m **to form a data set equivalent to the solar data), and Solar data sets as a function of TelX. These curves can be directly compared because they all originate from a TelY of -0.6, where all three data sets overlap (see Figure [4\)](#page-4-0). The holography and drone measurements are most comparable, because they can be separated into individual feeds. Conversely, the solar measurements are comprised of an average of all intercylinder baselines under 10m. To examine the divergence of the YY Polarization drone FWHM curve from the solar and holography datasets, we investigate transit data in the frequency band (676.2-695.7 MHz) within the purple region in Figure [10.](#page-8-0)**

the gradient of plotted frequencies. The XX polarization recovers the expected first null on either side of the main beam at the highest and lowest plotted frequencies, but intermediate frequencies show the first sidelobe joining the main beam (particularly for $TelX;0)$). The evolution for the YY polarization is similar but not identical—as the plotted frequency decreases, the sharpness of the null diminishes, eroding the distinction between the main beam and the first sidelobe.

The cause of the differences between the celestial source data and the drone data sets (most prominently in the YY polarization) are not entirely understood. One possibility is that this could be due to near-field effects. Where the main beam is widest, near-field effects may combine the main beam and first sidelobe, failing to recover the first order null that exists in the far-field beam, resulting in the behavior described above. It is not clear why this would impact one polarization more than the other, although the two polarizations do have different illumination patterns. Similarly, the amplitude of this discrepancy is not common across all feeds: feed numbers between 80-90 and 220-230

FIGURE 10. First eigenmode data from autocorrelation measurements of the drone transiting at TelY ≈ −0.6 **(feed 210) across CHIME cylinder C. The data shown are not normalized or corrected with the best-fit centroid. The frequency band shown here is reversed from the frequency axis of Figure [9.](#page-7-0) The colored curves thus evolve along the 30 MHz ripple feature in the FWHM**(f) **curve starting from a minima at 695.7 MHz (black), where the FWHM**(f) **values are in agreement with the solar and holography datasets, to a maxima at 676.2 MHz (yellow), where the divergence is highest. In the logarithmic scale shown in Figure [10](#page-8-0) the amplitude appears compressed, but in linear units the amplitude does not appear compressed.**

(see Figure [2\)](#page-3-3) are in agreement with the FWHM amplitudes from other data sets. The discrepancy therefore can't be entirely explained by sampling in the radiating near-field, because feeds 80-90 are \sim 25 m closer to the drone than feed the plotted feed (210). Additional flights would be helpful for investigating this discrepancy, but are beyond the scope of this paper.

B. Trends with Frequency and TelY

The solar and drone data can be compared in the TelX vs. frequency and TelX vs. TelY subspaces to further investigate beam patterns. The drone data is taken from the first eigenmode (see Section [II.](#page-1-0)[C\)](#page-2-0) to increase the signal to noise. As previously described, the solar data is an average of all intercylinder baselines $B \n\leq 10m$. All data has been corrected for the frequency-dependent centroid deviation measured in the Gaussian fits.

First, we compare the drone and solar data as a function of TelX and frequency in Figure [11.](#page-9-0) For this comparison we select a single TelY index for the solar transit data and a single CHIME feed index for the drone data (both corresponding to $TelY = -0.600$, feed 210). The amplitude of the drone and solar data have been normalized in each frequency with the amplitude of the associated best-fit gaussian. These waterfall plots show similar frequency dependent variations in width in the main beam and sidelobe amplitudes and positions.

Specifically, the width decreases with increasing frequency, and is modulated by a 30 MHz ripple aligned between the two data sets (as would be expected from Figure [9\)](#page-7-0). Similarly, the XX polarization has a wider overall beam than the YY polarization, also as expected from the CHIME feed illumination pattern [\[1\]](#page-10-0), [\[42\]](#page-12-3). The drone data has a more pronounced ripple in the XX polarization, whereas the ripple is attenuated in the solar data due to averaging over many baselines (supported by the lower ripple amplitude as described in Section [II.](#page-1-0)[C\)](#page-4-3).

Second, we compare the drone and solar data as a function of TelX and TelY in Figure [12.](#page-9-1) In this figure, a single frequency bin (centered around 690.62 MHz) is selected for the drone and solar data. The TelY axis for the drone data is constructed from each separate feed within cylinder C from the drone transit using the mapping computed in Section [II.](#page-1-0)[D.](#page-4-4) The drone data and solar data are normalized by the amplitude of the best-fit Gaussian along the TelY axis.

For both polarizations, the main beam and sidelobes have similar TelY dependence in both the drone and solar datasets. A notable difference between these datasets is the high signal-to-noise and continuity present in the solar data from coadding in baseline and time. Conversely, each of the TelY values in the drone data comes from the same 3.4 min drone flight, and does not benefit from coadding or averaging, however signal-to-noise improvements are possible with modest increases in flight time.

Comparing the solar and drone data for the YY polarization, the following similarities are apparent: The main beam expands and shrinks at the same values of TelY (expands at TelY=-0.56, two clear 'waists' at TelY ∼-0.53 and - 0.6). The sidelobe levels are higher where the beam widens (TelY=-0.56) and lower at TelY values where the main beam shrinks to a waist. The third order sidelobe is maximal at TelX= \pm 0.125 for the plotted range of TelY, appearing as a continuous pink line.

Turning to the XX polarization, we observe the same similarities across the drone and solar data. The main beam broadens at TelY=-0.55, and shrinks to a waist at TelY=-0.52 and TelY=-0.59 in both data sets. Unlike in polarization YY, the sidelobe levels for polarization XX evolve in TelX and TelY simultaneously—shown by symmetric sloped contours that extend away from waist in the main beam (e.g. starting at TelY=-0.59, and expanding in TelX as TelY decreases to -0.62.)

V. CONCLUSION AND FUTURE DIRECTIONS

The measurements presented in this paper represent the successful determination of CHIME correlator settings for drone-based beam calibration and demonstrate the first use of a drone as a reference calibrator for a large cylindrical radio interferometer. The comparisons between the drone, holography, and solar measurements indicate that the FWHM and centroid position are consistent across all three data sets. Moreover, the evolution of these parameters as a function

FIGURE 11. Waterfall plots of telescope data obtained during Drone measurements (Right Column, single feed [210] in either polarization) and Solar measurements (Left Column, average of intercylinder baselines $(B \leq 10m)$ in either polarization). Similar widths and features are present **in both data sets, and the beamwidths and sidelobe features are comparable. Each frequency is normalized independently to a Gaussian fit peak value to remove the uncalibrated frequency dependence of the drone transmitter.**

FIGURE 12. Waterfall plots of telescope data obtained during Solar measurements (average of intercylinder baselines B ≤ 10 **for a single frequency bin (center 690MHz) in XX (Left Top) and YY (Left Bottom) polarizations) and Drone measurements (all feeds for a single frequency bin (center 690 MHz) in XX (Right Top) and YY (Right Bottom) polarizations).**

of declination, frequency, and feed index are shown to behave similarly in all three data sets, despite differences in measurement technique. This shows that drone beam measurements are possible, even at the relatively slow data cadence of CHIME, by using its pulsar gating mode. The analysis also demonstrates the complexities of measuring a cylindrical array with a drone and highlighted the areas for improvement, in particular a higher precision constraint on drone altitude is essential for this mapping and designing flight trajectories which can more easily be mapped to comparison data sets.

During the same maintenance window, our group conducted nine other drone beam mapping test flights which are prime targets for future analysis. We performed similar East-to-West scans at 45° and 55° zenith angle, North-to-South transits along the focal line of Cylinder C, and gridded flights over the center of the array. In addition, test flights were performed where the drone rotated through 180[°] of heading (and thus, polarization) at several locations above the array to test the polarization response of the feeds as a function of angle.

The RFI from the drone contributes unwanted signal in otherwise low-background sites. We are investigating using a new drone, with higher frequency communications (shifted far beyond the restricted range at DRAO), which also has longer flight times, and improved time and location accuracy.

Now that the correlator firmware and pulsar timing parameter files have been generated, we can return to CHIME to conduct additional drone flights targeting regions of interest within the beam, including two-dimensional polarized properties of the beam maps.

ACKNOWLEDGMENT

The authors would like to acknowledge contributions from the DRAO staff and faculty.

We thank the Dominion Radio Astrophysical Observatory, operated by the National Research Council Canada, for gracious hospitality and expertise. The DRAO is situated on the traditional, ancestral, and unceded territory of the Syilx Okanagan people. We are fortunate to live and work on these lands.

We extend special thanks to Tim Robishaw, Alex Hill, Tom Landecker, Benoit Robert, Kory Phillips, Mandana Amiri, Niko Milutinovic, Michael Rupen, Richard Hellyer, Rick Smegal, and Luna Zagorac for assistance during flights at the DRAO, including coordination across the DRAO telescopes and facilities.

CHIME is funded by grants from the Canada Foundation for Innovation (CFI) 2012 Leading Edge Fund (Project 31170), the CFI 2015 Innovation Fund (Project 33213), and by contributions from the provinces of British Columbia, Québec, and Ontario. Long-term data storage and computational support for analysis is provided by WestGrid, SciNet and the Digital Research Alliance of Canada, and we thank their staff for flexibility and technical expertise that has been essential to this work.

Additional support was provided by the University of British Columbia, McGill University, and the University of Toronto. CHIME also benefits from NSERC Discovery Grants to several researchers, funding from the Canadian Institute for Advanced Research (CIFAR), from Canada Research Chairs, from the FRQNT Centre de Recherche en Astrophysique du Québec (CRAQ) and from the Dunlap Institute for Astronomy and Astrophysics at the University of Toronto, which is funded through an endowment established by the David Dunlap family. This material is partly based on work supported by the Perimeter Institute for Theoretical Physics, which in turn is supported by the Government of Canada through Industry Canada and by the Province of Ontario through the Ministry of Research and Innovation. L.B.N and A.R. acknowledge the support of the National Science Foundation award number 2006911; L.B.N and W.T. acknowledge the support of the NSF award number 1751763; A.O. is partly supported by the Dunlap Institute at the University of Toronto; and K.M.B. is supported by NSF grant 2018490.

REFERENCES

- [1] CHIME Collaboration, Mandana Amiri, Kevin Bandura, Anja Boskovic, Tianyue Chen, Jean-François Cliche, Meiling Deng, Nolan Denman, Matt Dobbs, Mateus Fandino, Simon Foreman, Mark Halpern, David Hanna, Alex S. Hill, Gary Hinshaw, Carolin Höfer, Joseph Kania, Peter Klages, T. L. Landecker, Joshua MacEachern, Kiyoshi Masui, Juan Mena-Parra, Nikola Milutinovic, Arash Mirhosseini, Laura Newburgh, Rick Nitsche, Anna Ordog, Ue-Li Pen, Tristan Pinsonneault-Marotte, Ava Polzin, Alex Reda, Andre Renard, J. Richard Shaw, Seth R. Siegel, Saurabh Singh, Rick Smegal, Ian Tretyakov, Kwinten van Gassen, Keith Vanderlinde, Haochen Wang, Donald V. Wiebe, James S. Willis, and Dallas Wulf. An Overview of CHIME, the Canadian Hydrogen Intensity Mapping Experiment. *The Astrophysical Journal Supplement*, 261(2):29, August 2022.
- [2] Keith Vanderlinde, Adrian Liu, Bryan Gaensler, Dick Bond, Gary Hinshaw, Cherry Ng, Cynthia Chiang, Ingrid Stairs, Jo-Anne Brown, Jonathan Sievers, Juan Mena, Kendrick Smith, Kevin Bandura, Kiyoshi Masui, Kristine Spekkens, Leo Belostotski, Matt Dobbs, Neil Turok, Patrick Boyle, Michael Rupen, Tom Landecker, Ue-Li Pen, and Victoria Kaspi. The canadian hydrogen observatory and radio-transient detector (chord). 2019.
- [3] David R. DeBoer, Aaron R. Parsons, James E. Aguirre, Paul Alexander, Zaki S. Ali, Adam P. Beardsley, Gianni Bernardi, Judd D. Bowman, Richard F. Bradley, Chris L. Carilli, Carina Cheng, Eloy de Lera Acedo, Joshua S. Dillon, Aaron Ewall-Wice, Gcobisa Fadana, Nicolas Fagnoni, Randall Fritz, Steve R. Furlanetto, Brian Glendenning, Bradley Greig, Jasper Grobbelaar, Bryna J. Hazelton, Jacqueline N. Hewitt, Jack Hickish, Daniel C. Jacobs, Austin Julius, MacCalvin Kariseb, Saul A. Kohn, Telalo Lekalake, Adrian Liu, Anita Loots, David MacMahon, Lourence Malan, Cresshim Malgas, Matthys Maree, Zachary Martinot, Nathan Mathison, Eunice Matsetela, Andrei Mesinger, Miguel F. Morales, Abraham R. Neben, Nipanjana Patra, Samantha Pieterse, Jonathan C. Pober, Nima Razavi-Ghods, Jon Ringuette, James Robnett, Kathryn Rosie, Raddwine Sell, Craig Smith, Angelo Syce, Max Tegmark, Nithyanandan Thyagarajan, Peter K. G. Williams, and Haoxuan Zheng. Hydrogen Epoch of Reionization Array (HERA). *Publications of the Astronomical Society of the Pacific*, 129(974):045001, April 2017.
- [4] L. B. Newburgh, K. Bandura, M. A. Bucher, T. C. Chang, H. C. Chiang, J. F. Cliche, R. Davé, M. Dobbs, C. Clarkson, K. M. Ganga, T. Gogo, A. Gumba, N. Gupta, M. Hilton, B. Johnstone, A. Karastergiou, M. Kunz, D. Lokhorst, R. Maartens, S. Macpherson, M. Mdlalose, K. Moodley, L. Ngwenya, J. M. Parra, J. Peterson,

O. Recnik, B. Saliwanchik, M. G. Santos, J. L. Sievers, O. Smirnov, P. Stronkhorst, R. Taylor, K. Vanderlinde, G. Van Vuuren, A. Weltman, and A. Witzemann. HIRAX: a probe of dark energy and radio transients. In *Ground-based and Airborne Telescopes VI*, volume 9906 of *Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series*, page 99065X, Aug 2016.

- [5] M. P. van Haarlem, M. W. Wise, A. W. Gunst, G. Heald, J. P. McKean, J. W. T. Hessels, A. G. de Bruyn, R. Nijboer, J. Swinbank, R. Fallows, M. Brentjens, A. Nelles, R. Beck, H. Falcke, R. Fender, J. Hörandel, L. V. E. Koopmans, G. Mann, G. Miley, H. Röttgering, B. W. Stappers, R. A. M. J. Wijers, S. Zaroubi, M. van den Akker, A. Alexov, J. Anderson, K. Anderson, A. van Ardenne, M. Arts, A. Asgekar, I. M. Avruch, F. Batejat, L. Bähren, M. E. Bell, M. R. Bell, I. van Bemmel, P. Bennema, M. J. Bentum, G. Bernardi, P. Best, L. Bîrzan, A. Bonafede, A. J. Boonstra, R. Braun, J. Bregman, F. Breitling, R. H. van de Brink, J. Broderick, P. C. Broekema, W. N. Brouw, M. Brüggen, H. R. Butcher, W. van Cappellen, B. Ciardi, T. Coenen, J. Conway, A. Coolen, A. Corstanje, S. Damstra, O. Davies, A. T. Deller, R. J. Dettmar, G. van Diepen, K. Dijkstra, P. Donker, A. Doorduin, J. Dromer, M. Drost, A. van Duin, J. Eislöffel, J. van Enst, C. Ferrari, W. Frieswijk, H. Gankema, M. A. Garrett, F. de Gasperin, M. Gerbers, E. de Geus, J. M. Grießmeier, T. Grit, P. Gruppen, J. P. Hamaker, T. Hassall, M. Hoeft, H. A. Holties, A. Horneffer, A. van der Horst, A. van Houwelingen, A. Huijgen, M. Iacobelli, H. Intema, N. Jackson, V. Jelic, A. de Jong, E. Juette, D. Kant, A. Karastergiou, A. Koers, H. Kollen, V. I. Kondratiev, E. Kooistra, Y. Koopman, A. Koster, M. Kuniyoshi, M. Kramer, G. Kuper, P. Lambropoulos, C. Law, J. van Leeuwen, J. Lemaitre, M. Loose, P. Maat, G. Macario, S. Markoff, J. Masters, R. A. McFadden, D. McKay-Bukowski, H. Meijering, H. Meulman, M. Mevius, E. Middelberg, R. Millenaar, J. C. A. Miller-Jones, R. N. Mohan, J. D. Mol, J. Morawietz, R. Morganti, D. D. Mulcahy, E. Mulder, H. Munk, L. Nieuwenhuis, R. van Nieuwpoort, J. E. Noordam, M. Norden, A. Noutsos, A. R. Offringa, H. Olofsson, A. Omar, E. Orrú, R. Overeem, H. Paas, M. Pandey-Pommier, V. N. Pandey, R. Pizzo, A. Polatidis, D. Rafferty, S. Rawlings, W. Reich, J. P. de Reijer, J. Reitsma, G. A. Renting, P. Riemers, E. Rol, J. W. Romein, J. Roosjen, M. Ruiter, A. Scaife, K. van der Schaaf, B. Scheers, P. Schellart, A. Schoenmakers, G. Schoonderbeek, M. Serylak, A. Shulevski, J. Sluman, O. Smirnov, C. Sobey, H. Spreeuw, M. Steinmetz, C. G. M. Sterks, H. J. Stiepel, K. Stuurwold, M. Tagger, Y. Tang, C. Tasse, I. Thomas, S. Thoudam, M. C. Toribio, B. van der Tol, O. Usov, M. van Veelen, A. J. van der Veen, S. ter Veen, J. P. W. Verbiest, R. Vermeulen, N. Vermaas, C. Vocks, C. Vogt, M. de Vos, E. van der Wal, R. van Weeren, H. Weggemans, P. Weltevrede, S. White, S. J. Wijnholds, T. Wilhelmsson, O. Wucknitz, S. Yatawatta, P. Zarka, A. Zensus, and J. van Zwieten. LOFAR: The LOw-Frequency ARray. *Astronomy and Astrophysics*, 556:A2, August 2013.
- [6] S. J. Tingay, R. Goeke, J. D. Bowman, D. Emrich, S. M. Ord, D. A. Mitchell, M. F. Morales, T. Booler, B. Crosse, R. B. Wayth, C. J. Lonsdale, S. Tremblay, D. Pallot, T. Colegate, A. Wicenec, N. Kudryavtseva, W. Arcus, D. Barnes, G. Bernardi, F. Briggs, S. Burns, J. D. Bunton, R. J. Cappallo, B. E. Corey, A. Deshpande, L. Desouza, B. M. Gaensler, L. J. Greenhill, P. J. Hall, B. J. Hazelton, D. Herne, J. N. Hewitt, M. Johnston-Hollitt, D. L. Kaplan, J. C. Kasper, B. B. Kincaid, R. Koenig, E. Kratzenberg, M. J. Lynch, B. Mckinley, S. R. Mcwhirter, E. Morgan, D. Oberoi, J. Pathikulangara, T. Prabu, R. A. Remillard, A. E. E. Rogers, A. Roshi, J. E. Salah, R. J. Sault, N. Udaya-Shankar, F. Schlagenhaufer, K. S. Srivani, J. Stevens, R. Subrahmanyan, M. Waterson, R. L. Webster, A. R. Whitney, A. Williams, C. L. Williams, and J. S. B. Wyithe. The Murchison Widefield Array: The Square Kilometre Array Precursor at Low Radio Frequencies. *Publications of the Astron. Soc. of Australia*, 30:e007, January 2013.
- [7] R. Braun et al. Advancing astrophysics with the Square Kilometre Array. Proceedings of Science, 2015.
- [8] R. S. Booth and J. L. Jonas. An Overview of the MeerKAT Project. *African Skies*, 16:101, March 2012.
- [9] Scott Dodelson, Katrin Heitmann, Chris Hirata, Klaus Honscheid, Aaron Roodman, Uroš Seljak, Anže Slosar, and Mark Trodden. Cosmic Visions Dark Energy: Science. *arXiv e-prints*, page arXiv:1604.07626, Apr 2016.
- [10] J. Richard Shaw, Kris Sigurdson, Michael Sitwell, Albert Stebbins, and Ue-Li Pen. Coaxing cosmic 21 cm fluctuations from the polarized

sky using m -mode analysis. *Physical Review D*, 91(8):083514, April 2015.

- [11] Tiziana Di Matteo, Benedetta Ciardi, and Francesco Miniati. The 21 cm emission from the reionization epoch: extended and point source foregrounds. *Monthly Notices of the Royal Astronomical Society*, 355(4):1053–1065, December 2004.
- [12] A. Datta, J. D. Bowman, and C. L. Carilli. Bright Source Subtraction Requirements for Redshifted 21 cm Measurements. *The Astrophysical Journal*, 724(1):526–538, November 2010.
- [13] Aaron R. Parsons, Jonathan C. Pober, James E. Aguirre, Christopher L. Carilli, Daniel C. Jacobs, and David F. Moore. A Per-baseline, Delayspectrum Technique for Accessing the 21 cm Cosmic Reionization Signature. *apj*, 756(2):165, September 2012.
- [14] Nithyanandan Thyagarajan, Daniel C. Jacobs, Judd D. Bowman, N. Barry, A. P. Beardsley, G. Bernardi, F. Briggs, R. J. Cappallo, P. Carroll, B. E. Corey, A. de Oliveira-Costa, Joshua S. Dillon, D. Emrich, A. Ewall-Wice, L. Feng, R. Goeke, L. J. Greenhill, B. J. Hazelton, J. N. Hewitt, N. Hurley-Walker, M. Johnston-Hollitt, D. L. Kaplan, J. C. Kasper, Han-Seek Kim, P. Kittiwisit, E. Kratzenberg, E. Lenc, J. Line, A. Loeb, C. J. Lonsdale, M. J. Lynch, B. McKinley, S. R. McWhirter, D. A. Mitchell, M. F. Morales, E. Morgan, A. R. Neben, D. Oberoi, A. R. Offringa, S. M. Ord, Sourabh Paul, B. Pindor, J. C. Pober, T. Prabu, P. Procopio, J. Riding, A. E. E. Rogers, A. Roshi, N. Udaya Shankar, Shiv K. Sethi, K. S. Srivani, R. Subrahmanyan, I. S. Sullivan, M. Tegmark, S. J. Tingay, C. M. Trott, M. Waterson, R. B. Wayth, R. L. Webster, A. R. Whitney, A. Williams, C. L. Williams, C. Wu, and J. S. B. Wyithe. Foregrounds in Wide-field Redshifted 21 cm Power Spectra. *The Astrophysical Journal*, 804(1):14, May 2015.
- [15] Aaron Ewall-Wice, Nicholas Kern, Joshua S. Dillon, Adrian Liu, Aaron Parsons, Saurabh Singh, Adam Lanman, Paul La Plante, Nicolas Fagnoni, Eloy de Lera Acedo, David R. DeBoer, Chuneeta Nunhokee, Philip Bull, Tzu-Ching Chang, T. Joseph W. Lazio, James Aguirre, and Sean Weinberg. DAYENU: a simple filter of smooth foregrounds for intensity mapping power spectra. *Monthly Notices of the Royal Astronomical Society*, 500(4):5195–5213, January 2021.
- [16] P. A. Shaver, R. A. Windhorst, P. Madau, and A. G. de Bruyn. Can the reionization epoch be detected as a global signature in the cosmic background? *Astronomy and Astrophysics*, 345:380–390, May 1999.
- [17] S. Peng Oh and Katherine J. Mack. Foregrounds for 21-cm observations of neutral gas at high redshift. *Monthly Notices of the Royal Astronomical Society*, 346(3):871–877, Dec 2003.
- [18] Adrian Liu and Max Tegmark. A method for 21 cm power spectrum estimation in the presence of foregrounds. *Physical Review D*, 83(10):103006, May 2011.
- [19] Chihway Chang, Christian Monstein, Alexandre Refregier, Adam Amara, Adrian Glauser, and Sarah Casura. Beam Calibration of Radio Telescopes with Drones. *Publications of the Astronomical Society of the Pacific*, 127(957):1131, Nov 2015.
- [20] Daniel C. Jacobs, Jacob Burba, Judd Bowman, Abraham R. Neben, Benjamin Stinnett, and Lauren Turner. The external calibrator for hydrogen observatories. *arXiv e-prints*, page arXiv:1610.02607, October 2016.
- [21] Giuseppe Virone, Andrea M. Lingua, Marco Piras, Alberto Cina, Federico Perini, Jader Monari, Fabio Paonessa, Oscar A. Peverini, Giuseppe Addamo, and Riccardo Tascone. Antenna pattern verification system based on a micro unmanned aerial vehicle (uav). *IEEE Antennas and Wireless Propagation Letters*, 13:169–172, 2014.
- [22] G. Pupillo, G. Naldi, G. Bianchi, A. Mattana, J. Monari, F. Perini, M. Poloni, M. Schiaffino, P. Bolli, A. Lingua, I. Aicardi, H. Bendea, P. Maschio, M. Piras, G. Virone, F. Paonessa, Z. Farooqui, A. Tibaldi, G. Addamo, O. A. Peverini, R. Tascone, and S. J. Wijnholds. Medicina array demonstrator: calibration and radiation pattern characterization using a UAV-mounted radio-frequency source. *Experimental Astronomy*, 39(2):405–421, June 2015.
- [23] María García-Fernández, Yuri Álvarez López, Ana Arboleya, Borja González-Valdés, Yolanda Rodríguez-Vaqueiro, María Elena De Cos Gómez, and Fernando Las-Heras Andrés. Antenna diagnostics and characterization using unmanned aerial vehicles. *IEEE Access*, 5:23563–23575, 2017.
- [24] Torsten Fritzel, Rüdiger Strauß, Hans-Jürgen Steiner, Christoph Eisner, and Thomas Eibert. Introduction into an uav-based near-field system for in-situ and large-scale antenna measurements (invited paper). In *2016 IEEE Conference on Antenna Measurements & Applications (CAMA)*, pages 1–3, 2016.
- [25] Cosme Culotta-López, Stuart Gregson, Andrian Buchi, Carlo Rizzo, Diana Trifon, Snorre Skeidsvoll, Inés Barbary, and Joakim Espeland. On the uncertainty sources of drone-based outdoor far-field antenna measurements. In *2021 Antenna Measurement Techniques Association Symposium (AMTA)*, pages 1–6, 2021.
- [26] Juyong Zhang, Jingxin Liu, Fengquan Wu, Xuelei Chen, Jixia Li, Peter T. Timbie, Santanu Das, Ruibin Yan, Jiachen He, and Osinga Calvin. Beam measurements of the tianlai dish radio telescope using an unmanned aerial vehicle [antenna applications corner]. *IEEE Antennas and Propagation Magazine*, 63(6):98–109, 2021.
- [27] Pietro Bolli, Giuseppe Pupillo, Fabio Paonessa, Giuseppe Virone, Stefan J. Wijnholds, and Andrea Maria Lingua. Near-field experimental verification of the em models for the lofar radio telescope. *IEEE Antennas and Wireless Propagation Letters*, 17(4):613–616, 2018.
- [28] Raimund A. M. Mauermayer and Jonas Kornprobst. A cost-effective tethered-uav-based coherent near-field antenna measurement system. *IEEE Open Journal of Antennas and Propagation*, 3:984–1002, 2022.
- [29] Clive G. Parini, Stuart F. Gregson, and Anthony K. Brown. Untethered near-field drone-based antenna measurement system for microwave frequencies using multiple reference antennas for phase and drone location recovery. *IET Microwaves, Antennas & Propagation*, 16(13):798–811, 2022.
- [30] CHIME Collaboration, Mandana Amiri, Kevin Bandura, Anja Boskovic, Jean-François Cliche, Meiling Deng, Matt Dobbs, Mateus Fandino, Simon Foreman, Mark Halpern, Alex S. Hill, Gary Hinshaw, Carolin Höfer, Joseph Kania, T. L. Landecker, Joshua MacEachern, Kiyoshi Masui, Juan Mena-Parra, Laura Newburgh, Anna Ordog, Tristan Pinsonneault-Marotte, Ava Polzin, Alex Reda, J. Richard Shaw, Seth R. Siegel, Saurabh Singh, Keith Vanderlinde, Haochen Wang, James S. Willis, and Dallas Wulf. Using the Sun to Measure the Primary Beam Response of the Canadian Hydrogen Intensity Mapping Experiment. *The Astrophysical Journal*, 932(2):100, June 2022.
- [31] Alex Reda, Tristan Pinsonneault-Marotte, Meiling Deng, Mandana Amiri, Kevin Bandura, Arnab Chakraborty, Simon Foreman, Mark Halpern, Alex S. Hill, Carolin Höfer, Joseph Kania, T. L. Landecker, Joshua MacEachern, Kiyoshi Masui, Juan Mena-Parra, Nikola Milutinovic, Laura Newburgh, Anna Ordog, Sourabh Paul, J. Richard Shaw, Seth R. Siegel, Rick Smegal, Haochen Wang, and Dallas Wulf. Characterization of the John A. Galt Telescope for radio holography with CHIME. In Jonas Zmuidzinas and Jian-Rong Gao, editors, *Millimeter, Submillimeter, and Far-Infrared Detectors and Instrumentation for Astronomy XI*, volume 12190 of *Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series*, page 121902V, August 2022.
- [32] Ue-Li Pen, Lister Staveley-Smith, Jeffrey B. Peterson, and Tzu-Ching Chang. First detection of cosmic structure in the 21-cm intensity field. *Monthly Notices of the Royal Astronomical Society*, 394(1):L6–L10, March 2009.
- [33] Tzu-Ching Chang, Ue-Li Pen, Kevin Bandura, and Jeffrey B. Peterson. An intensity map of hydrogen 21-cm emission at redshift z -0.8. *Nature*, 466(7305):463–465, July 2010.
- [34] K. W. Masui, E. R. Switzer, N. Banavar, K. Bandura, C. Blake, L. M. Calin, T. C. Chang, X. Chen, Y. C. Li, Y. W. Liao, A. Natarajan, U. L. Pen, J. B. Peterson, J. R. Shaw, and T. C. Voytek. Measurement of 21 cm Brightness Fluctuations at z ˜0.8 in Cross-correlation. *The Astrophysical Journal Letters*, 763(1):L20, January 2013.
- [35] E. R. Switzer, K. W. Masui, K. Bandura, L. M. Calin, T. C. Chang, X. L. Chen, Y. C. Li, Y. W. Liao, A. Natarajan, U. L. Pen, J. B. Peterson, J. R. Shaw, and T. C. Voytek. Determination of z ~0.8 neutral hydrogen fluctuations using the 21cm intensity mapping autocorrelation. *Monthly Notices of the Royal Astronomical Society*, 434:L46– L50, July 2013.
- [36] C. J. Anderson, N. J. Luciw, Y. C. Li, C. Y. Kuo, J. Yadav, K. W. Masui, T. C. Chang, X. Chen, N. Oppermann, Y. W. Liao, U. L. Pen, D. C. Price, L. Staveley-Smith, E. R. Switzer, P. T. Timbie, and L. Wolz. Low-amplitude clustering in low-redshift 21-cm intensity maps cross-correlated with 2dF galaxy densities. *Monthly Notices of the Royal Astronomical Society*, 476(3):3382–3392, May 2018.
- [37] Laura Wolz, Alkistis Pourtsidou, Kiyoshi W. Masui, Tzu-Ching Chang, Julian E. Bautista, Eva-Maria Mueller, Santiago Avila, David Bacon, Will J. Percival, Steven Cunnington, Chris Anderson, Xuelei Chen, Jean-Paul Kneib, Yi-Chao Li, Yu-Wei Liao, Ue-Li Pen, Jeffrey B. Peterson, Graziano Rossi, Donald P. Schneider, Jaswant Yadav, and Gong-Bo Zhao. HI constraints from the cross-correlation of eBOSS

galaxies and Green Bank Telescope intensity maps. *arXiv e-prints* , page arXiv:2102.04946, February 2021.

- [38] CHIME Collaboration, Mandana Amiri, Kevin Bandura, Tianyue Chen, Meiling Deng, Matt Dobbs, Mateus Fandino, Simon Foreman, Mark Halpern, Alex S. Hill, Gary Hinshaw, Carolin Höfer, Joseph Kania, T. L. Landecker, Joshua MacEachern, Kiyoshi Masui, Juan Mena-Parra, Nikola Milutinovic, Arash Mirhosseini, Laura Newburgh, Anna Ordog, Ue-Li Pen, Tristan Pinsonneault-Marotte, Ava Polzin, Alex Reda, Andre Renard, J. Richard Shaw, Seth R. Siegel, Saurabh Singh, Keith Vanderlinde, Haochen Wang, Donald V. Wiebe, and Dallas Wulf. Detection of Cosmological 21 cm Emission with the Canadian Hydrogen Intensity Mapping Experiment. *The Astrophysical Journal*, 947(1):16, April 2023.
- [39] CHIME Collaboration, Mandana Amiri, Kevin Bandura, Arnab Chakraborty, Matt Dobbs, Mateus Fandino, Simon Foreman, Hyoyin Gan, Mark Halpern, Alex S. Hill, Gary Hinshaw, Carolin Höfer, T. L. Landecker, Zack Li, Joshua MacEachern, Kiyoshi Masui, Juan Mena-Parra, Nikola Milutinovic, Arash Mirhosseini, Laura Newburgh, Anna Ordog, Sourabh Paul, Ue-Li Pen, Tristan Pinsonneault-Marotte, Alex Reda, J. Richard Shaw, Seth R. Siegel, Keith Vanderlinde, Haochen Wang, D. V. Wiebe, Dallas Wulf, and The Chime Collaboration. A Detection of Cosmological 21 cm Emission from CHIME in Crosscorrelation with eBOSS Measurements of the Lyα Forest. *The Astrophysical Journal*, 963(1):23, March 2024.
- [40] DESI Collaboration, A. G. Adame, J. Aguilar, S. Ahlen, S. Alam, D. M. Alexander, M. Alvarez, O. Alves, A. Anand, U. Andrade, E. Armengaud, S. Avila, A. Aviles, H. Awan, B. Bahr-Kalus, S. Bailey, C. Baltay, A. Bault, J. Behera, S. BenZvi, A. Bera, F. Beutler, D. Bianchi, C. Blake, R. Blum, S. Brieden, A. Brodzeller, D. Brooks, E. Buckley-Geer, E. Burtin, R. Calderon, R. Canning, A. Carnero Rosell, R. Cereskaite, J. L. Cervantes-Cota, S. Chabanier, E. Chaussidon, J. Chaves-Montero, S. Chen, X. Chen, T. Claybaugh, S. Cole, A. Cuceu, T. M. Davis, K. Dawson, A. de la Macorra, A. de Mattia, N. Deiosso, A. Dey, B. Dey, Z. Ding, P. Doel, J. Edelstein, S. Eftekharzadeh, D. J. Eisenstein, A. Elliott, P. Fagrelius, K. Fanning, S. Ferraro, J. Ereza, N. Findlay, B. Flaugher, A. Font-Ribera, D. Forero-Sánchez, J. E. Forero-Romero, C. S. Frenk, C. Garcia-Quintero, E. Gaztañaga, H. Gil-Marín, S. Gontcho A Gontcho, A. X. Gonzalez-Morales, V. Gonzalez-Perez, C. Gordon, D. Green, D. Gruen, R. Gsponer, G. Gutierrez, J. Guy, B. Hadzhiyska, C. Hahn, M. M. S Hanif, H. K. Herrera-Alcantar, K. Honscheid, C. Howlett, D. Huterer, V. Iršič, M. Ishak, S. Juneau, N. G. Karaçaylı, R. Kehoe, S. Kent, D. Kirkby, A. Kremin, A. Krolewski, Y. Lai, T. W. Lan, M. Landriau, D. Lang, J. Lasker, J. M. Le Goff, L. Le Guillou, A. Leauthaud, M. E. Levi, T. S. Li, E. Linder, K. Lodha, C. Magneville, M. Manera, D. Margala, P. Martini, M. Maus, P. Mc-Donald, L. Medina-Varela, A. Meisner, J. Mena-Fernández, R. Miquel, J. Moon, S. Moore, J. Moustakas, N. Mudur, E. Mueller, A. Muñoz-Gutiérrez, A. D. Myers, S. Nadathur, L. Napolitano, R. Neveux, J. A. Newman, N. M. Nguyen, J. Nie, G. Niz, H. E. Noriega, N. Padmanabhan, E. Paillas, N. Palanque-Delabrouille, J. Pan, S. Penmetsa, W. J. Percival, M. M. Pieri, M. Pinon, C. Poppett, A. Porredon, F. Prada, A. Pérez-Fernández, I. Pérez-Ràfols, D. Rabinowitz, A. Raichoor, C. Ramírez-Pérez, S. Ramirez-Solano, C. Ravoux, M. Rashkovetskyi, M. Rezaie, J. Rich, A. Rocher, C. Rockosi, N. A. Roe, A. Rosado-Marin, A. J. Ross, G. Rossi, R. Ruggeri, V. Ruhlmann-Kleider, L. Samushia, E. Sanchez, C. Saulder, E. F. Schlafly, D. Schlegel, M. Schubnell, H. Seo, A. Shafieloo, R. Sharples, J. Silber, A. Slosar, A. Smith, D. Sprayberry, T. Tan, G. Tarlé, P. Taylor, S. Trusov, L. A. Ureña-López, R. Vaisakh, D. Valcin, F. Valdes, M. Vargas-Magaña, L. Verde, M. Walther, B. Wang, M. S. Wang, B. A. Weaver, N. Weaverdyck, R. H. Wechsler, D. H. Weinberg, M. White, J. Yu, Y. Yu, S. Yuan, C. Yeche, E. A. Zaborowski, P. Zarrouk, H. Zhang, ` C. Zhao, R. Zhao, R. Zhou, T. Zhuang, and H. Zou. DESI 2024 VI: Cosmological Constraints from the Measurements of Baryon Acoustic Oscillations. *arXiv e-prints*, page arXiv:2404.03002, April 2024.
- [41] Meiling Deng. Antenna array design, beam calibration of the chime to measure the late-time cosmic acceleration and mapping of the north celestial cap. In *University of British Columbia Open Access Thesis Collection*, 2020.
- [42] Meiling Deng and Duncan Campbell-Wilson. The cloverleaf antenna: A compact wide-bandwidth dual-polarization feed for CHIME. *arXiv e-prints*, page arXiv:1708.08521, August 2017.