

Automated detection of gibbon calls from passive acoustic monitoring data using convolutional neural networks in the ‘torch for R’ ecosystem

Dena J. Clink^{1*}, Jinsung Kim¹, Hope Cross-Jaya¹, Abdul Hamid Ahmad², Moeurk Hong³, Roemun Sala³, H  l  ne Birot³, Cain Agger⁴, Thinh Tien Vu⁵, Hoa Nguyen Thi⁶, Thanh Nguyen Chi⁷, and Holger Klinck¹

¹ *K. Lisa Yang Center for Conservation Bioacoustics, Cornell Lab of Ornithology, Cornell University, Ithaca, NY, USA.*

² *Institute for Tropical Biology and Conservation, Universiti Malaysia Sabah (UMS), Kota Kinabalu, Sabah, Malaysia*

³ *Jahoo, Angdoug Kraleung Village, Sen Monorom Orang , MondulKiri, MondulKiri Province, Cambodia*

⁴ *Wildlife Conservation Society, Cambodia, 21, Street 21 Sangkat Tonle Bassac, Phnom Penh, Cambodia.*

⁵ *Department of Wildlife, Vietnam National University of Forestry, Xuan Mai, Chuong My, Ha Noi, Vietnam.*

⁶ *The Institute for Tropical Biodiversity and Forestry, Xuan Mai, Chuong My, Ha Noi, Vietnam.*

⁷ *Bac Giang Agro-Forestry University, Bich Son Commune, Viet Yen District, Bac Giang Province, Vietnam*

Running title: Gibbon calls using ‘torch for R’

*** Corresponding author email:**

Email: dena.clink@cornell.edu

Abstract:

Automated detection of acoustic signals is crucial for effective monitoring of vocal animals and their habitats across ecologically-relevant spatial and temporal scales. Recent advances in deep learning have made these approaches more accessible. However, there are few deep learning approaches that can be implemented natively in the R programming environment; approaches that run natively in R may be more accessible for ecologists. The ‘torch for R’ ecosystem has made the use of transfer learning with convolutional neural networks accessible for R users. Here, we evaluate a workflow that uses transfer learning for the automated detection of acoustic signals from passive acoustic monitoring (PAM) data. Our specific goals include: 1) present a method for automated detection of gibbon calls from PAM data using the ‘torch for R’ ecosystem; 2) compare the results of transfer learning for six pretrained CNN architectures; and 3) investigate how well the different architectures perform on datasets of the female calls from two different gibbon species: the northern grey gibbon (*Hylobates funereus*) and the southern yellow-cheeked crested gibbon (*Nomascus gabriellae*). We found that the highest performing architecture depended on the test dataset. We successfully deployed the top performing model for each gibbon species to investigate spatial of variation in gibbon calling behavior across two grids of autonomous recording units in Danum Valley Conservation Area, Malaysia and Keo Seima Wildlife Sanctuary, Cambodia. The

fields of deep learning and automated detection are rapidly evolving, and we provide the methods and datasets as benchmarks for future work.

Keywords: R programming environment; torch for R; bioacoustics; deep learning; gibbons; Southeast Asia

Introduction:

Passive acoustic monitoring

Terrestrial applications of passive acoustic monitoring (PAM) – which utilizes autonomous acoustic recording units (ARUs) – have increased dramatically in recent years [reviewed in (Sugai et al., 2019)]. The use of autonomous recording units allows for monitoring at spatial and temporal scales that are generally not achievable using human observers (Gibb et al., 2018). PAM has been used to investigate vocal behavior (Clink et al., 2020), model occurrence probability in the landscape (Vu & Tran, 2019), and for automated detection/classification of calls from long-term PAM recordings (Clink et al., 2023; Dufourq et al., 2021). However, the use of PAM often results in terabytes of acoustic data that require post-processing to obtain useful information about the signals of interest. A major bottleneck in using PAM for monitoring populations is related to extracting relevant information from long-term acoustic recordings (Tuia et al., 2022), and listening to the recordings or manual annotation are time- and cost-prohibitive. Therefore, identifying effective automated approaches is critical for effective use of PAM.

Automated detection/classification

Numerous approaches have been developed for the automated detection and classification of animal sounds from terrestrial PAM data. In the context of PAM, classification can be defined as the assignment of each observation (in this case sound clip) to a respective class (e.g., species, individual) and detection is the use of a sliding window approach to identify signals of interest from background noise in long recordings (Stowell, 2022). Some of the earlier

approaches for automated detection include spectrogram cross-correlation (Katz et al., 2016), or combining band-limited energy summation with a subsequent classifier (Clink et al., 2023; Kalan et al., 2015; Ross, 2013). Recent advances in deep learning have revolutionized image and speech recognition (LeCun et al., 2015), with important cross-over for bioacoustics and the analysis of PAM data. One of the most important innovations was applying convolutional neural network (CNN) architecture, that has been hugely successful for image classification, to audio data (Hershey et al., 2017). There has been a huge increase in the use of deep learning for the automated detection of signals in PAM data in recent years [reviewed in (Stowell, 2022)]. This includes many deep learning applications for terrestrial PAM data, including anurans (LeBien et al., 2020), birds (Kahl et al., 2021; Stowell et al., 2019), bats (Aodha et al., 2018), and primates (Dufourq et al., 2020; Ravaglia et al., 2023).

Convolutional neural networks

In the most fundamental form, deep learning maps the input (e.g., spectrogram image) to the label (e.g., gibbon) via a series of layered transformations so that inputs can be correctly matched to their associated targets (Wani et al., 2020). Traditional approaches to machine learning for acoustic data relied heavily on feature engineering, as early machine learning algorithms required a reduced set of representative features, such as features estimated from the spectrogram including low frequency, high frequency, and duration of the signal. Deep learning does not require feature engineering (Stevens et al., 2020). Convolutional neural networks (CNNs) are useful for processing data that have a 'grid-like topology', such as image or spectrogram data that can be considered a 2-dimensional grid of pixels (Goodfellow et al.,

2016). The ‘convolutional’ layer learns the feature representations of the inputs; these convolutional layers consist of a set of filters which are fundamentally two-dimensional matrices of numbers with the primary parameter being the number of filters (Gu et al., 2018). However, if training data are scarce, the use of CNNs may lead to overfitting as representations of images tend to be large with many variables (LeCun et al., 1995).

Transfer learning for PAM

Transfer learning is an approach wherein the architecture of a pretrained CNN (which is generally trained on a large dataset) is applied to a new classification problem (Dufourq et al., 2022). For example, CNNs trained on the ImageNet dataset of > 1 million images (Deng et al., 2009) such as ResNet have been applied to automated detection/classification of primate and bird species from PAM data (Dufourq et al., 2022; Ruan et al., 2022). Transfer learning in computer vision applications retains the feature extraction or embedding layers, and modifies the last few classification layers to be trained for a new classification task (Dufourq et al., 2022). Transfer learning has been shown to outperform CNNs trained with random initial weights (Tan et al., 2018). Transfer learning is particularly appropriate when there is a paucity of training data (Weiss et al., 2016), such as common in PAM data.

Transfer learning has been applied to PAM data in a variety of ways, with one of the most notable differences in approaches being related to the type of data used to train the model. It is common practice to compare the performance of a variety of different architectures on the same dataset, as oftentimes there are no *a priori* reasons to expect that

one architecture will perform better than another, and performance may vary across signal types and architectures. Dufourq et al. (2022) compared different transfer learning architectures that were pretrained on the ImageNet dataset for the automated detection of Hainan gibbons (*Nomascus hainanus*), black-and-white ruffed lemurs (*Varecia variegata*), Thyolo alethe (*Chamaetylas choloensis*), and the Pin-tailed whydah (*Vidua macroura*). They found that performance was dependent on model configuration, but pre-trained ResNet152V2 had consistently high performance with relatively few training samples (25 samples) and achieved an F1 score of ~0.8 for gibbons and lemurs.

The BEenchmark of ANimal Sounds (BEANS) compared different deep learning and non-deep learning algorithms on 12 datasets (Hagiwara et al., 2022), including a comparison of pretrained ResNets (trained on the ImageNet) dataset to the VGGish (Hershey et al., 2017) model that was pretrained on audio from the YouTube dataset (Gemmeke et al., 2017). They found that performance was variable across datasets and tasks (e.g. classification versus detection), and that the VGGish model generally performed the best, followed by the pretrained ResNets. For the Hainan gibbon dataset they found that the pretrained ResNET 18 architecture performed best, but with a relatively low performance of mean average precision = 0.3. For a few of the classification tasks a non-deep learning algorithm – support vector machine (Cortes & Vapnik, 1995) – performed best. A recent study implemented a transfer learning approach that used embeddings and a subsequently trained new classifier from models pretrained on global data sets of bird vocalizations [BirdNET (Kahl et al., 2021) and Perch (Ghani et al., 2023)]. The authors compared these models to those pretrained on the

YouTube and AudioSet data sets (Ghani et al., 2023) and found that BirdNET and Perch substantially outperformed the other models.

The 'torch for R' ecosystem

The two most popular open-source programming languages are R and Python (Scavetta & Angelov, 2021). Python has surpassed R in terms of overall popularity, but R remains an important language for the life sciences (Lawlor et al., 2022). 'Keras' (Chollet & others, 2015), 'PyTorch' (Paszke et al., 2019) and 'Tensorflow' (Martín Abadi et al., 2015) are some of the more popular neural network libraries; these libraries were all initially developed for the Python programming language. Until recently, deep learning implementations in R relied on the 'reticulate' package which served as an interface to Python (Ushey et al., 2022). However, the recent release of the 'torch for R' ecosystem provides a framework based on 'PyTorch' that runs natively in R and has no dependency on Python (Falbel & Luraschi, 2023). Running natively in R means more straightforward installation, and higher accessibility for users of the R programming environment.

Gibbons & PAM

Gibbons (family Hylobatidae) are small apes that are found throughout Southeast Asia, and most of the ~20 species of gibbons are endangered or critically endangered (IUCN, 2022). All gibbon species have species- and sex-specific loud calls that can be heard at distances of > 1 km (Mitani, 1985), which makes them good candidates for PAM. Traditional methods of monitoring gibbon populations have relied on human observers (Brockelman & Srikosamatara,

1993; Kidney et al., 2016), but these approaches are time- and labor-intensive. A few gibbon species have been studied using PAM, including the Hainan gibbon, *Nomascus hainanus* (Dufourq et al., 2020), cao vit gibbon, *Nomascus nasutus* (Wearn et al., 2024), Northern grey gibbon, *Hylobates funereus* (Clink et al., 2020, 2023), western black crested gibbon, *N. concolor* (Zhong et al., 2021) and the southern yellow-cheeked crested gibbon, *N. gabriellae* (Vu & Tran, 2019). To-date, the automated detection/classification of gibbon signals has been done for four gibbon species, western black-crested gibbon (*Nomascus concolor*) (Zhou et al., 2023), Hainan gibbons (Dufourq et al., 2020), Bornean white-bearded gibbon (*H. albibarbis*) (Owens et al., 2024), and Northern grey gibbons (Clink et al., 2023). However, the increasing accessibility of autonomous recording units and analytical approaches means that more gibbon species will be soon added to the list.

Objectives

The 'torch for R' ecosystem is under rapid development, and there are existing methods and tutorials for image classification using pretrained CNNs (Keydana, 2023). The goals of the current study include: 1) present a method for automated detection of gibbon calls from PAM data using the 'torch for R' ecosystem; 2) compare the results of transfer learning for six CNN architectures AlexNet (Krizhevsky et al., 2017), VGG16, VGG19 (Simonyan & Zisserman, 2014), ResNet18, ResNet50, and ResNet152 (He et al., 2016) pretrained on the 'ImageNet' dataset (Deng et al., 2009); and 3) investigate how well the different architectures perform on datasets of the female calls from two different gibbon species: the northern grey gibbon (*Hylobates funereus*) and the southern yellow-cheeked crested gibbon (*Nomascus gabriellae*). For each

CNN architecture, we evaluated the performance of both binary classification and multi-class classification approaches, as we wanted to see if including more gibbon training samples (regardless of the species) would improve performance. We then deployed the top performing model for each gibbon species to investigate spatial and temporal patterns of variation in gibbon calling behavior across two grids of autonomous recording units in Danum Valley Conservation Area, Malaysia and Keo Seima Wildlife Sanctuary, Cambodia. For both gibbon species, we test the generalizability of the models on data collected from a different site than the training data; this is considered best practice for machine learning (Stowell, 2022).

Materials and Methods:

Acoustic data collection

Acoustic data used for training were collected using Swift or SwiftOne (K. Lisa Yang Center for Conservation Bioacoustics, Cornell Lab of Ornithology, Cornell University, USA) autonomous recording units at two locations in Southeast Asia. The first recording location for training data was Danum Valley Conservation Area (Danum Valley) in Sabah, Malaysia; the gibbon species present here is the northern grey gibbon (hereafter grey gibbons). Acoustic data at Danum Valley were collected using Swift autonomous recording units from February to April 2018 at 40 dB gain, 16 kHz sample rate, and 16-bit resolution. Recordings were saved as 2-hour Waveform Audio File Format (.wav) files, and each file was ~230 MB in size. Danum Valley is considered 'aseasonal' and lacks monsoons that are typical of other areas in Southeast Asia (Walsh & Newbery, 1999). The second recording location, which we used for test data to evaluate the generalizability of model performance, was Maliau Basin Conservation Area which

is ~ 100 km from Danum Valley. Acoustic data at Maliau Basin were collected in August 2019 using Swifts at a 40 dB gain, 48 kHz sampling rate, and 16-bit resolution. Recordings were saved as 40-min files that were approximately ~230 MB in size. The sensitivity of the Swift microphones was $-44 (+/-3)$ dB re 1 V/Pa with ADC clipping level of $-/+ 0.9V$.

The second recording location for training data was Jahoo, Mondulkiri Province, Cambodia, and the southern yellow-cheeked crested gibbons are found here (hereafter crested gibbons). Acoustic data collection was done using SwiftOnes with a 32 dB gain, 32 kHz sample rate, 16-bit resolution, with 1-hour .wav files at ~230 MB size. The sensitivity of the SwiftOne microphones was $-24 (+/-3)$ dB re 1 V/Pa with ADC clipping level of $-/+ 0.9V$. Training data was annotated from recordings collected from March to May 2022. Mondulkiri province experiences a distinct wet season driven by the monsoon from May to September each year. The test dataset for crested gibbons comes from Dakrong Nature Reserve in Vietnam and contains recordings of a recently recognized distinct gibbon species (Van Chuong et al., 2018), the Northern buff-cheeked gibbons (*N. annamensis*), which was originally classified as *N. gabriellae*. Data from this site were collected using a modified smartphone at 0 gain, 16 kHz sample rate, 16-bit resolution, and saved as 1-hour .wav files (Vu et al., 2023). See Figure 1 for a map of the recording locations in Malaysia, Cambodia, and Vietnam, and see Table 1 for a summary of sample size for different datasets. GPS locations of all recording locations are available on Github (see data availability statement).




Figure 1. Map of recording locations in the present study. Northern grey gibbons (*Hylobates funereus*) are found in Danum Valley and Maliau Basin, southern yellow cheeked-crested gibbons (*Nomascus gabriellae*) are found in Jahoo, Cambodia, and northern buff-cheeked gibbons (*Nomascus annamensis*) are found in Dakrong Nature Reserve, Vietnam. Recording locations used for training datasets are indicated in orange and test datasets in grey. Map was created using QGIS (QGIS.org, %Y. QGIS Geographic Information System. QGIS Association. <http://www.qgis.org>).

Table 1. Summary of sample size for training and test sets used in the present study. For Danum Valley and Jahoo test datasets, the models were deployed over the entire sound files, so the number of noise samples is substantially higher than the other datasets.

Dataset	Country	Species	Number of Gibbon samples	Number of Noise samples	Sample rate
Danum Valley Conservation Training Data	Malaysia	Grey gibbon	502	2,254	16 kHz
Jahoo Training Data	Cambodia	Crested gibbon	213	2,130	32 kHz
Maliau Basin Test Data	Malaysia	Grey gibbon	147	81	48 kHz
Dakrong Nature Reserve Test Data	Vietnam	Buff cheeked gibbon	45	173	16 kHz
Danum Valley Test Data	Malaysia	Grey gibbon	383	2,905	16 kHz
Jahoo Test Data	Cambodia	Crested gibbon	296	5,684	32 kHz

Training data preparation

Acoustic samples used for the training data were prepared slightly differently for each species, as the data were compiled from two separate projects. For grey gibbons, we randomly selected 500 hours of acoustic recordings from 06:00 to 10:00 LT, as this is when grey gibbons are most likely to call at this site (Clink et al., 2020). We used a band-limited energy detector implemented using the ‘DetectBLED’ function in the ‘gibbonR’ package (Clink & Klinck, 2019) to isolate sound events in the 0.5 – 1.6 kHz frequency range. One analyst (DJC) created spectrogram images of the clips using the ‘seewave’ R package (Sueur et al., 2008), and assigned each sound event as either a female “gibbon” call or a catch-all “noise” category; this resulted in 502 female grey gibbon calls and 2,254 noise events. See Clink et al. (2023) for

details on the band-limited energy detector implementation and settings. For crested gibbons, we randomly selected 789 hours of recordings and two analysts (JK and HCJ) manually annotated all instances of female gibbon calls using spectrograms created in Raven Pro 1.6.3 (K. Lisa Yang Center for Conservation Bioacoustics at the Cornell Lab of Ornithology, 2023) setting window size = 2,400 samples, contrast = 70, and brightness = 65; all other settings were the default. We also indicated whether the calls were high-, medium- or low-quality, and omitted the low-quality calls from our training dataset. We classified calls as high-quality if they had visible harmonics, indicating the calling animals were close to the recording unit. Medium-quality calls had few visible harmonics but still had clear visible structure stereotypical of the gibbon female call. Low quality calls either had low signal-to-noise ratio (< 10 dB signal-to-noise ratio) or exhibited substantial overlap with another non-gibbon signal. We divided 1-hr recordings into 12-s windows with 6-s overlap and considered all windows that contained at least 80% of the gibbon call as a positive signal. This resulted in 213 female gibbon calls for training. To create a noise class, we used the band-limited energy detector in the 0.5 – 3.0 kHz frequency range on 20 of the randomly selected files described above that were confirmed to not have gibbon calls present. This resulted in over 10,000 noise clips, so to create a more comparable dataset to the grey gibbons we randomly selected 2,130 noise clips to use for training.

Test data preparation

To create test datasets for generalizability, DJC and TTV manually annotated spectrograms indicating the start and stop times of gibbon female calls using Raven Pro 1.6.3

and the default settings. To report the generalizability of our models we annotated nine randomly selected files from Maliau Basin Conservation Area, and for Dakrong Nature Reserve, Vietnam, we included five annotated files that were known to contain gibbon calls. To report the final performance of the models, we annotated 10 randomly selected 2-hour files from the wide array in Danum Valley Conservation Area, Malaysia, and for Jahoo, Cambodia we annotated 10 randomly selected 1-hour files from the wide array. To create test datasets for final model performance evaluation that reflected ‘real-world’ conditions for automated detection, we divided the test recordings into 12-s clips with 6-s hop size or overlap, and then considered clips that were within plus or minus 12-s of the start of the annotated gibbon calls as ‘gibbon’ detections. We annotated all gibbon calls that were visible in the spectrogram and could be confirmed aurally to be gibbon calls, even if the full species-specific structure of the calls was not visible. See Table 1 for summary of sample size for the different training and test datasets.

Spectrogram image preparation

We used the ‘spectro’ function in the ‘seewave’ R package (Sueur et al., 2008) to create spectrograms to input into the models. For all recordings that did not have 16 kHz sample rate we down-sampled the clips before converting to spectrograms to ensure comparable time and frequency resolution. We did not filter before down-sampling, however visual inspection of spectrogram images did not show any signs of aliasing for the gibbon frequency range. We used the default window size and color scheme, but removed all axis labels and specified a frequency range of 0.5 – 1.6 kHz for grey gibbons and 0.5 – 3.0 kHz for crested gibbons. We saved all

spectrogram images as '.jpg' files using the 'jpeg' function in base R. See Figure 2 for representative spectrogram images of the three gibbon species, along with some representative noise images, included in the present study.




Figure 2. Representative spectrogram images of female calls of southern yellow-cheeked crested gibbons (Cambodia), northern buff cheeked/yellow-cheeked crested gibbons (Vietnam), and northern grey gibbons (Malaysia), along with randomly selected images from the 'Noise' category used in the present study. The frequency range is 0.5 – 1.6 kHz for grey gibbons and 0.5 – 3.0 kHz for crested and buff cheeked gibbons. When images were input into the model they did not have axis labels.

Model architecture

CNNs combine convolution and pooling into a sequence of layers; the number of layers is generally referred to as depth, and overall depth and width of the model is generally thought to impact performance (Zeiler & Fergus, 2014). Here, we compare six commonly used CNN architectures, that vary in depth and composition. AlexNet was a pioneering CNN for image

classification, and the introduction of AlexNet in 2012 led to substantial improvement in performance over existing methods. AlexNet contains five convolutional layers with three fully connected layers for a total of eight learned layers (Krizhevsky et al., 2017). Activation functions are used to transform the input signal to the output signal (Sharma et al., 2017), and AlexNet was one of the first to use Rectified Linear Unit (ReLU) activation function, which led to much faster training times (Sapiezko & Mikhael, 2018; Figure 3). The VGG model architecture developed by the Visual Geometry Group (Hershey et al., 2017) is much deeper than AlexNet; here we compare the VGG16 and VGG19 models which have 13 and 16 convolutional layers, respectively. An important difference between AlexNet and the VGG models is that the kernel size (or size of the convolutional filters) is smaller in the VGG models (Yu et al., 2016).

With traditional CNNs, there appears to be a maximum threshold of depth where the addition of more layers does not improve performance. He et al. (2016) noted that there is a 'degradation problem' that happens when networks get deeper, which leads to a decrease in performance that is not related to over-fitting. ResNets use residual connections (skip connections) to train very deep neural networks more efficiently, whereas the VGG relies on a simpler sequential architecture (Sapiezko & Mikhael, 2018); this allows for ResNets to overcome the 'degradation problem'. Models in the ResNet family can be shallow or deep, and we chose to compare ResNet18, ResNet50, and ResNet152 which have 16, 48, and 150 convolutional layers, respectively, along with two fully connected layers. From a practical standpoint, CNNs with fewer layers are less computationally costly to train and deploy, which is why we wanted to compare both shallow and deep architectures, as this might mean they are

more accessible for a higher number of practitioners that do not have access to large computing power.




Figure 3. A simplified overview of the AlexNET CNN architecture for our multiclass classification problem. The CNN takes an image as an input, and then it passes through multiple convolutional layers (for AlexNet there are five convolutional layers; indicated in blue in the figure) which serve to provide a meaningful low dimensional representation of the image. The fully connected layers (green and orange) are used for classification, and in our multiclass problem with three classes (crested gibbons, grey gibbons, and noise) the final output layer (orange) has three dimensions which represent the three classes. This output can be converted to a probability of belonging to each class. For binary classification problems the output layer has one dimension that can be converted to a probability of one of the two classes. The above image was adapted from (Yu et al., 2016), the AlexNet architecture modified from (Krizhevsky et al., 2017), and CNN was drawn using draw.io (<https://www.drawio.com/>).

Model training and validation

We split our original training data into a 70/30 split, using approximately 70% of the data for training, and the remaining 30% for validation and testing. We took the training, validation, and test splits from different recorder locations, ensuring that we followed best practices for model evaluation. We first converted the images to tensors, resized to 224x224 pixels, and applied mean and standard deviation normalization using the ‘torchvision’ R package (Falbel, 2022). We had many more noise samples than gibbon samples, however we

left the dataset unbalanced, as this is more analogous to real-world scenarios of automated detection, and even with unbalanced datasets we achieved acceptable performance (see results). To account for this imbalance, we used a weighted loss function that allowed us to assign weights to different classes (see below for details). Previous work found that when using > 25 samples, fine-tuning the feature extractor layer along with the output layer resulted in better performance (Dufourq et al., 2022), so for all the models we set the 'requires_grad_' parameter to 'TRUE', unfreezing the extractor layers. All models were pretrained on the 'ImageNet' dataset (Deng et al., 2009) and are available in the 'torchvision' R package v 0.5.1 (Falbel, 2022). We compared the performance of models that were allowed to run for 1, 2, 3, 4, 5, and 20 epochs. We allowed for early stopping and set 'patience=2' which specifies the number of epochs without improvement until the training is stopped.

We trained three sets of models for each of the model architectures, a binary model trained either on the 'grey gibbons' or 'crested gibbons' training datasets, and a multiclass model that was trained on both gibbon species along with the noise category. For all models, we set the maximum learning rate = 0.001 (Keydana, 2023), batch size = 32, and used an Adam optimizer (Kingma & Ba, 2014). We used the one-cycle learning rate strategy (Smith & Topin, 2018) implemented using the 'luz_callback_lr_scheduler' function in the 'luz' R package (Falbel, 2023). For binary models, we used the 'nn_bce_with_logits_loss' loss function which combines a sigmoid layer with the binary cross entropy function, and specified the weight of the "Gibbon" class as 0.9. For the multiclass models we used 'nn_cross_entropy_loss' which computes the cross entropy loss between inputs and targets and is useful for multi-class classification

problems (Falbel & Luraschi, 2023), and we specified the weight of the “Noise” class as 0.2, and the weights of the two “Gibbon” classes as 0.48.

Table 2. Summary of training, validation, and test data sample size for initial model training and evaluation.

Data	Species	Training samples (Gibbon)	Training samples (Noise)	Validation samples (Gibbon)	Validation samples (Noise)	Test samples (Gibbon)	Test samples (Noise)
Danum Valley Conservation Training Data	Grey Gibbon	349	1,651	78	206	76	332
Jahoo Training Data	Crested Gibbon	149	819	32	553	30	541

Performance and deployment

To evaluate model performance for the binary models, the output layer had a single dimension, so we used a sigmoid function to convert the output of the CNN predictions on the test datasets to values between 0 and 1. For the multiclass models, the output layer had three dimensions, representing the three classes in our data, and we computed class probabilities by applying a softmax function. We aimed to use the original split of test data (summarized in Table 2) to identify which combination of training data (binary or multi-class), model architecture, and epoch number had the best performance. However, there were many cases where the same model configurations had comparable performance, so we evaluated the performance of all configurations on the test datasets to report the performance of the highest performing model configuration. For all performance evaluations, we used the ‘caret’ package (Kuhn, 2008) to calculate precision, recall, and F1 score. We also report the false positive rate for the wide arrays at Danum Valley and Jahoo, as we deployed the model over the longer

sound files which would allow us to calculate false positive rate more effectively. False positive rates were calculated as the number of false positives divided by the sum of false positives plus true negatives. We considered all detections that were within +/- 12-s of the start time of the annotation of the call to be a true positive detection.

Model deployment

We deployed trained models over the wide arrays at Danum Valley and Jahoo. For Danum Valley we focused on 06:00-08:00 LT (Clink et al., 2020) and for Jahoo we focused on 05:00- 06:00 LT (this study), as these are the peak calling times at these two sites. The model outputs spectrogram images of detections, and a single observer (DJC) manually sorted the images into either true positive (gibbons) or false positives (noise). For cases of uncertainty, we also listened to the sound clip to assist with manual sorting into correct categories. We then created a call event density map using inverse distance weighed interpolation (Wrege et al., 2017) with the R package 'gstat' (Pebesma, 2004). We standardized the number of calling events by the number of hours analyzed for each recorder location. Recorders were deployed on a grid at approximately 750-m spacing for Danum Valley Conservation Area, Malaysia and approximately 2-km spacing for Jahoo, Cambodia. Using an Apple M2 Max with 12 core CPU, 30 core GPU, and 32 GB memory we processed 1-hour files at 32 kHz sample rate or 2-hour files at 16 kHz sample rate in approximately 3 minutes. This estimate includes the image creation step, which can add to the processing time. All analyses were done using R programming language v 4.2.1 (R Core Team, 2022) using the 'GibbonNetR' R package (v1.0.0-beta.1) (Clink & Ahmad, 2024)

Data availability

Scripts needed to run the analyses are located at:

<https://github.com/DenaJGibbon/Gibbon-transfer-learning-multispecies>. Sound clips to reproduce analyses are available on Zenodo: 10.5281/zenodo.10948975.

Results:

Identifying the top performing architectures

We aimed to use the test data from the original split of training data (Table 2) to identify the best performing combinations of CNN architecture, number of epochs, and type of training data (binary or multiclass) to use for further model evaluation. However, we found that multiple model configurations led to similar performance. For crested gibbons, many combinations of CNN architectures and number of epochs resulted in the same performance when training binary classification models (F1 score = 1). For grey gibbons, the ResNet152 architecture trained for 20 epochs (with early stopping) had the highest performance for the binary classification model (F1 score = 0.95). For the multi-class classification models, we found that for crested gibbons, many model combinations had high performance, whereas for grey gibbons the ResNet152 architecture trained for 20 epochs with early stopping had the highest performance (see Online Supplementary Material Table 1).

Evaluating performance on test datasets

We originally planned to identify the best performing model configurations during the initial model training and testing phase, however multiple model configurations had the same performance. Therefore, we evaluated the performance of all model configurations on test datasets from Maliau Basin Conservation Area, Malaysia (grey gibbons) and Dakrong Nature Reserve, Vietnam (crested gibbons). We found that model performance varied based on the test data set (Table 3). For crested gibbons, the multi-class ResNet50 architecture trained for 3 epochs had the highest F1 score (F1 score = 0.87), and for grey gibbons the multi-class VGG19 architecture trained for 5 epochs had the best performance (F1 score = 0.93).

Table 3. Top performing model combinations based on F1 score (bold), recall (italics), and precision (*) for test datasets from Maliau Basin Conservation Area, Malaysia (grey gibbons) and Dakrong Nature Reserve, Vietnam (crested gibbons).

Training Data	N epochs	CNN Architecture	Threshold	Precision	Recall	F1
Crested Gibbon binary	5	resnet50	0.1	0.88	0.47	0.61
Grey Gibbon binary	3	vgg19	0.2	0.92	0.95	0.93
Crested Gibbon Multi-class	3	resnet50	0.1	0.90	0.84	0.87
Grey Gibbon Multi-class	5	vgg19	0.9	0.93	0.94	0.93
Crested Gibbon binary	5	resnet50	0.1	0.88	<i>0.47</i>	0.61
Grey Gibbon binary	3	vgg19	0.1	0.82	<i>0.98</i>	0.90
Crested Gibbon Multi-class	3	resnet50	0.1	0.90	<i>0.84</i>	0.87
Grey Gibbon Multi-class	5	vgg19	0.1	0.70	<i>0.99</i>	0.82
Crested Gibbon binary	5	resnet50	0.5	1.00*	0.20	0.33
Grey Gibbon binary	3	resnet18	0.2	1.00*	0.45	0.62
Crested Gibbon Multi-class	5	vgg19	0.9	1.00*	0.44	0.62
Grey Gibbon Multi-class	3	resnet50	0.9	1.00*	0.28	0.44

Final performance evaluation

To report the final performance of the models, we used the top performing binary models for each gibbon species (ResNet50 for crested gibbons and VGG19 for grey gibbons), and the ResNet50 multi-class model for both species, and ran them over test files from the wide arrays at each site (see methods for details). We found that both models achieved acceptable performance (Table 4; Figure 4) and that false positive rates were low for all models (except the VGG19 binary architecture).

Table 4. Model performance for test files from wide arrays at Danum Valley Conservation Area, Malaysia, and Jahoo, Cambodia. The top performing model for each species (based on F1 score) is indicated in bold.

Species	Architecture	F1	Precision	Recall	FPR	Thresholds
Crested Gibbon (binary)	ResNet50	0.75	0.90	0.64	0.07	0.50
Grey Gibbon (binary)	VGG19	0.74	0.92	0.62	0.35	0.30
Crested Gibbon (multi)	ResNet50	0.82	0.99	0.71	0.01	0.90
Grey Gibbon (multi)	ResNet50	0.77	0.96	0.64	0.08	0.10




Figure 4. Precision, recall, and F1 score as a function of confidence score for test datasets from the wide array for crested and grey gibbons.

Deploying the models

We deployed ResNet50 multi-class models over wide PAM arrays in Danum Valley Conservation Area, Malaysia, and Jahoo, Cambodia. We manually assigned all detections as either true positive (gibbon) or false positive (noise). We found that 285 out of 3,046 were false positives for Danum Valley, resulting in a precision of ~ 0.90 . For Jahoo, we found that 566 out of 2,285 were false positives, resulting in a precision of ~ 0.75 . We found that there were substantial differences in the number of calls detected across recording locations (Figure 5). We found that in some cases the pattern matching ability of the algorithms outperformed visual pattern matching of human observers, as we had to listen to the corresponding clip to determine if the signal was a true or false positive. See Figure 6 for examples of true positive spectrogram images.




Figure 5. Call event density for Danum Valley Conservation Area, Malaysia (top) and Jahoo, Cambodia (bottom). Recorders were placed at ~750-m spacing in Danum Valley and ~2-km at Jahoo. The number of detections was standardized by the number of recording hours at each recorder location.




Figure 6. Spectrogram images of detections from the Danum Valley Conservation Area, Malaysia wide array (grey gibbons), and from the Jahoo, Cambodia wide array (crested gibbons). Images are divided into high-quality (HQ) and low-quality (LQ) subjective categories and names include the corresponding probability as assigned by the CNN. The low-quality images required subsequent aural verification by a human observer to ensure they were classified correctly.

Discussion:

Here, we provide a benchmark for automated detection of gibbon sounds using transfer learning. To our knowledge this is the first implementation of automated detection from PAM data in the “torch for R” environment (Falbel & Luraschi, 2023; Keydana, 2023). We compared the performance of different architectures when trained for a binary classification problem (gibbons vs noise) or trained for a multi-class classification problem (training data included two species of gibbons). Although the two gibbon species are not sympatric, we predicted that including more samples of gibbon calls regardless of the species would improve performance.

Similar to other studies, we found that the best performing architecture was dependent on the signal type (e.g. species of gibbon), however ResNet architectures had consistently high performance. We found that the performance of the multi-class models improved substantially when we used a weighted loss function that allowed us to assign weights to different classes. We were able to process 1-hour sound files with a 32 kHz sample rate in approximately 3 minutes, which substantially reduces processing time relative to human scanning of spectrograms.

Our initial evaluation of model performance used a 70/30 split of training data into training, validation, and test datasets. Although we worked to ensure that there was no data leakage between the training and test clips, the performance values we report from these initial tests are much higher than subsequent evaluations on datasets from different PAM arrays. This highlights the importance of using different test datasets to report the generalizability of trained models (Stowell, 2022). We believe the initial high performance may be due to a lack of diversity in acoustic signals contained in the training and test datasets, along with a smaller number of noise samples relative to real-world deployments for automated detection where a substantial amount of the clips are noise. However, the top performing models also had relatively high performance on test datasets from other sites and gibbon species indicating that this is an effective approach to identify combinations of CNN architectures and training epochs for subsequent testing.

Humans are good at pattern recognition, and tend to learn faster (e.g. with fewer training samples) than machine learning algorithms (Kühl et al., 2022). In our study, there were cases where the algorithm outperformed the human observer in assigning detections to true

positives, as we had to rely on aural confirmation to verify detections were true positives. Overall, we found that the approaches presented here led to acceptable performance, and slight improvements from traditional machine learning automated detection methods for grey gibbons from Danum Valley Conservation Area (F1 score < 0.8) (Clink et al., 2023). We found that our results were comparable, albeit slightly lower, to those found for gibbons using a similar transfer learning approach (Dufourq et al., 2022). We believe the slightly lower performance in our system may be due to the fact we used test data sets from different PAM arrays than the training data. We also found that for crested gibbons, the lower performance was driven by a higher number of false positives. Many of these false positives for crested gibbons were male gibbon calls or insect sounds; the spectrogram of the insect sound was visually similar to the female gibbon call, and many times the human observer had to listen to the clip to verify whether it was a female gibbon call or not.

We found that the range of number of detections per hour in Danum Valley and Jahoo were comparable, although there were clear differences across recording locations within a single site. Gibbon female calls often occur within a duet bout wherein there are multiple replicates of the great call. The number of great calls and the duration of the duets can vary across pairs and it has been shown in cao vit gibbons (*Nomascus nasutus*) the number of great calls emitted in a duet is influenced by pair bond strength (Ma et al., 2022). Therefore, it is possible that the differences we see within sites are due to differences of individual gibbon females recorded at particular ARUs. Duetting in gibbons is density-dependent, and can also be influenced by outside factors such as rainfall (Clink et al., 2020; Cowlshaw, 1992). Territory size of both species is not well-known, and it is unclear how much territory overlap there is between

neighboring groups. However, even if there are differences in home range size across species, this did not impact the number of calls detected per hour.

The field of automated detection is rapidly evolving, and we provide these results as a benchmark for future automated detection approaches. Future areas of research include comparing these results to transfer learning models trained specifically for audio (e.g., VGGish (Hershey et al., 2017)) or models trained on bird calls, that have been found to work well for many bioacoustics classification problems (Ghani et al., 2023). Gibbons tend to be highly vocal, which means that collating training datasets is easier than for less vocal animals. However, future work investigating the impact of the number of training samples on model performance will be informative (Dufourq et al., 2022; Nolasco et al., 2023). In addition, it is possible that a global model trained on all 20 gibbon species may outperform transfer learning models. Therefore, we propose that future work combines multiple gibbon species into a training dataset and trains a deep learning model from scratch. However, in contrast to avian communities in tropical forests, there are generally only one to two gibbon species at a particular site, and it is possible that a simple binary classifier may be sufficient.

As the majority of gibbon species are endangered, and all of them emit loud calls that can be heard several kilometers away (Geissmann, 2002), they are an excellent model for developing PAM and automated detection approaches. In addition to developing effective models for automated detection, more work needs to be done to make these approaches accessible to conservation practitioners. The R programming environment is one of the commonly used languages for ecologists (Scavetta & Angelov, 2021), so implementing this approach using the 'torch for R' ecosystem may make it more accessible to some. However, a

proficiency in coding is still needed to effectively implement these tools. One promising approach for making automated detection using deep learning accessible to non-coders is that found in the BirdNET GUI (<https://github.com/kahst/BirdNET-Analyzer>). In addition, implementing transfer learning in the 'torch for R' environment into a shiny app (similar to (Ruff et al., 2020)) will make the approach presented here more accessible.

Acknowledgements

DJC acknowledges the Fulbright ASEAN Research Award for U.S. Scholars for providing funding for the field research in Danum Valley Conservation Area, Malaysia. We thank the Royal Government of Cambodia and the KSWs REDD+ program for providing funding for field work in Jahoo, Cambodia. We thank Kyle Burrichter for his assistance with field data collection at Jahoo. TVT thanks Dakrong Nature Reserve for permission to conduct the field survey in Vietnam.

Author contributions

DJC and *HK* conceived the ideas and designed methodology; *MH*, *RS*, *HB*, *CA*, *TVT*, *HNT*, and *TNT* collected the data; *JK*, *HCI* and *DJC* analysed the data; *DJC*, *JK*, and *HCI* led the writing of the manuscript. *AHA* provided logistical and in-country and contributed to the ideas and methodology. All authors contributed critically to the drafts and gave final approval for publication.

Conflict of interest

The authors have declared that no competing interests exist.

Ethics statements

Institutional approval for data collection in Malaysia was provided by Cornell University (IACUC 2017–0098). Sabah Biodiversity Centre and the Danum Valley Management Committee provided permission to conduct the research. Research in Jahoo, Cambodia was done with permission from the Royal Government of Cambodia, and permission was provided by Dakrong Nature Reserve in Vietnam.

References

- Alasdair F. Owens, Kimberley Jane Hockings, Muhammad Ali Imron, Shyam Madhusudhana, Mariaty Ayudia Niun, Tatang Mitra Setia, Manmohan D Sharma, Siti Maimunah Soebagio, Frank J. F. Van Veen, & Wendy M. Erb. (2024). Automated detection of Bornean white-bearded gibbon (*Hylobates albibarbis*) vocalisations using an open-source framework for deep learning. *bioRxiv*, 2024.04.15.589517.
<https://doi.org/10.1101/2024.04.15.589517>
- Aodha, O. M., Gibb, R., Barlow, K. E., Browning, E., Firman, M., Freeman, R., Harder, B., Kinsey, L., Mead, G. R., Newson, S. E., Pandourski, I., Parsons, S., Russ, J., Szodoray-Paradi, A., Szodoray-Paradi, F., Tilova, E., Girolami, M., Brostow, G., & Jones, K. E. (2018). Bat detective—Deep learning tools for bat acoustic signal detection. *PLOS Computational Biology*, *14*(3), e1005995. <https://doi.org/10.1371/journal.pcbi.1005995>
- Brockelman, W. Y., & Srikosamatara, S. (1993). Estimation of density of gibbon groups by use of loud songs. *American Journal of Primatology*, *29*(2), 93–108.
<https://doi.org/10.1002/ajp.1350290203>

- Chollet, F. & others. (2015). *Keras*. <https://keras.io>
- Clink, D. J., & Ahmad, A. H. (2024). *gibbonNetR: an R Package for the Use of Convolutional Neural Networks and Transfer Learning on Acoustic Data*.
- Clink, D. J., Hamid Ahmad, A., & Klinck, H. (2020). Gibbons aren't singing in the rain: Presence and amount of rainfall influences ape calling behavior in Sabah, Malaysia. *Scientific Reports*, *10*(1), 1282. <https://doi.org/10.1038/s41598-020-57976-x>
- Clink, D. J., Kier, I., Ahmad, A. H., & Klinck, H. (2023). A workflow for the automated detection and classification of female gibbon calls from long-term acoustic recordings. *Frontiers in Ecology and Evolution*, *11*.
<https://www.frontiersin.org/articles/10.3389/fevo.2023.1071640>
- Clink, D. J., & Klinck, H. (2019). GIBBONR: An R package for the detection and classification of acoustic signals using machine learning. *arXiv Preprint arXiv:1906.02572*.
- Cortes, C., & Vapnik, V. (1995). Support-vector networks. *Machine Learning*, *20*(3), 273–297.
- Cowlshaw, G. (1992). Song Function in Gibbons. *Behaviour*, *121*(1), 131–153.
<https://doi.org/10.1163/156853992X00471>
- Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., & Fei-Fei, L. (2009). Imagenet: A large-scale hierarchical image database. *2009 IEEE Conference on Computer Vision and Pattern Recognition*, 248–255.
- Dufourq, E., Batist, C., Foquet, R., & Durbach, I. (2022). Passive acoustic monitoring of animal populations with transfer learning. *Ecological Informatics*, *70*, 101688.
<https://doi.org/10.1016/j.ecoinf.2022.101688>
- Dufourq, E., Durbach, I., Hansford, J. P., Hoepfner, A., Ma, H., Bryant, J. V., Stender, C. S., Li, W., Liu, Z., Chen, Q., & others. (2021). Automated detection of Hainan gibbon calls for

- passive acoustic monitoring. *Remote Sensing in Ecology and Conservation*, 7(3), 475–487.
- Dufourq, E., Durbach, I., Hansford, J. P., Hoepfner, A., Ma, H., Bryant, J. V., Stender, C. S., Li, W., Liu, Z., Chen, Q., Zhou, Z., & Turvey, S. T. (2020). *Automated detection of Hainan gibbon calls for passive acoustic monitoring* (1.0.0) [Computer software]. Zenodo. <https://doi.org/10.5281/zenodo.3991714>
- Falbel, D. (2022). *torchvision: Models, Datasets and Transformations for Images*. <https://CRAN.R-project.org/package=torchvision>
- Falbel, D. (2023). *luz: Higher Level “API” for “torch.”* <https://CRAN.R-project.org/package=luz>
- Falbel, D., & Luraschi, J. (2023). *torch: Tensors and Neural Networks with “GPU” Acceleration*.
- Geissmann, T. (2002). Duet-splitting and the evolution of gibbon songs. *Biological Reviews*, 77(1), 57–76. <https://doi.org/10.1017/S1464793101005826>
- Gemmeke, J. F., Ellis, D. P., Freedman, D., Jansen, A., Lawrence, W., Moore, R. C., Plakal, M., & Ritter, M. (2017). Audio set: An ontology and human-labeled dataset for audio events. *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 776–780.
- Ghani, B., Denton, T., Kahl, S., & Klinck, H. (2023). Global birdsong embeddings enable superior transfer learning for bioacoustic classification. *Scientific Reports*, 13(1), 22876.
- Gibb, R., Browning, E., Glover-Kapfer, P., & Jones, K. E. (2018). Emerging opportunities and challenges for passive acoustics in ecological assessment and monitoring. *Methods in Ecology and Evolution*. <https://doi.org/10.1111/2041-210X.13101>

- Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep Learning*. MIT Press.
- Gu, J., Wang, Z., Kuen, J., Ma, L., Shahroudy, A., Shuai, B., Liu, T., Wang, X., Wang, G., Cai, J., & others. (2018). Recent advances in convolutional neural networks. *Pattern Recognition*, 77, 354–377.
- Hagiwara, M., Hoffman, B., Liu, J.-Y., Cusimano, M., Effenberger, F., & Zacarian, K. (2022). *BEANS: The Benchmark of Animal Sounds* (arXiv:2210.12300). arXiv. <https://doi.org/10.48550/arXiv.2210.12300>
- He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep residual learning for image recognition. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 770–778.
- Hershey, S., Chaudhuri, S., Ellis, D. P. W., Gemmeke, J. F., Jansen, A., Moore, R. C., Plakal, M., Platt, D., Saurous, R. A., Seybold, B., Slaney, M., Weiss, R. J., & Wilson, K. (2017). CNN architectures for large-scale audio classification. *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 131–135. <https://doi.org/10.1109/ICASSP.2017.7952132>
- IUCN. (2022). *The IUCN Red List of Threatened Species*. The IUCN Red List of Threatened Species. <https://www.iucnredlist.org>
- K. Lisa Yang Center for Conservation Bioacoustics at the Cornell Lab of Ornithology. (2023). *Raven Pro: Interactive Sound Analysis Software (Version 1.6.4) [Computer software]*. [Computer software]. Cornell Lab of Ornithology. <https://ravensoundsoftware.com/>
- Kahl, S., Wood, C. M., Eibl, M., & Klinck, H. (2021). BirdNET: A deep learning solution for avian diversity monitoring. *Ecological Informatics*, 61, 101236.

- Kalan, A. K., Mundry, R., Wagner, O. J. J., Heinicke, S., Boesch, C., & Köhl, H. S. (2015). Towards the automated detection and occupancy estimation of primates using passive acoustic monitoring. *Ecological Indicators*, *54*(July 2015), 217–226.
<https://doi.org/10.1016/j.ecolind.2015.02.023>
- Katz, J., Hafner, S. D., & Donovan, T. (2016). Tools for automated acoustic monitoring within the R package *monitoR*. *Bioacoustics*, *25*(2), 197–210.
<https://doi.org/10.1080/09524622.2016.1138415>
- Keydana, S. (2023). *Deep Learning and Scientific Computing with R torch*. CRC Press.
- Kidney, D., Rawson, B. M., Borchers, D. L., Stevenson, B. C., Marques, T. A., & Thomas, L. (2016). An Efficient Acoustic Density Estimation Method with Human Detectors Applied to Gibbons in Cambodia. *PLOS ONE*, *11*(5), e0155066.
<https://doi.org/10.1371/journal.pone.0155066>
- Kingma, D. P., & Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv Preprint arXiv:1412.6980*.
- Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2017). Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, *60*(6), 84–90.
- Köhl, N., Goutier, M., Baier, L., Wolff, C., & Martin, D. (2022). Human vs. Supervised machine learning: Who learns patterns faster? *Cognitive Systems Research*, *76*, 78–92.
- Kuhn, M. (2008). Caret package. *Journal of Statistical Software*, *28*(5), 1–26.
- Lawlor, J., Banville, F., Forero-Muñoz, N.-R., Hébert, K., Martínez-Lanfranco, J. A., Rogy, P., & MacDonald, A. A. M. (2022). Ten simple rules for teaching yourself R. *PLOS Computational Biology*, *18*(9), e1010372. <https://doi.org/10.1371/journal.pcbi.1010372>

- LeBien, J., Zhong, M., Campos-Cerqueira, M., Velez, J. P., Dodhia, R., Ferres, J. L., & Aide, T. M. (2020). A pipeline for identification of bird and frog species in tropical soundscape recordings using a convolutional neural network. *Ecological Informatics*, *59*, 101113. <https://doi.org/10.1016/j.ecoinf.2020.101113>
- LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, *521*(7553), Article 7553. <https://doi.org/10.1038/nature14539>
- LeCun, Y., Bengio, Y., & others. (1995). Convolutional networks for images, speech, and time series. *The Handbook of Brain Theory and Neural Networks*, *3361*(10), 1995.
- Ma, H., Ma, C., & Fan, P. (2022). Adult male–female social bond advertising: The primary function of coordinated singing intensity in a small ape. *American Journal of Primatology*, *84*(1), e23351. <https://doi.org/10.1002/ajp.23351>
- Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Jia, Y., Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, ... Xiaoqiang Zheng. (2015). *TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems*. <https://www.tensorflow.org/>
- Mitani, J. C. (1985). Gibbon Song Duets and Intergroup Spacing. *Behaviour*, *92*(1/2 (Feb., 1985), 59–96. <https://doi.org/10.1080/0141192032000137321>
- Nolasco, I., Singh, S., Morfi, V., Lostanlen, V., Strandburg-Peshkin, A., Vidaña-Vila, E., Gill, L., Pamuła, H., Whitehead, H., Kiskin, I., Jensen, F. H., Morford, J., Emmerson, M. G., Versace, E., Grout, E., Liu, H., Ghani, B., & Stowell, D. (2023). Learning to detect an animal sound from five examples. *Ecological Informatics*, *77*, 102258. <https://doi.org/10.1016/j.ecoinf.2023.102258>

- Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch: An Imperative Style, High-Performance Deep Learning Library. In *Advances in Neural Information Processing Systems 32* (pp. 8024–8035). Curran Associates, Inc.
<http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf>
- Pebesma, E. J. (2004). Multivariable geostatistics in S: the gstat package. *Computers & Geosciences*, 30(7), 683–691.
- R Core Team. (2022). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. <https://www.R-project.org/>
- Ravaglia, D., Ferrario, V., De Gregorio, C., Carugati, F., Raimondi, T., Cristiano, W., Torti, V., Hardenberg, A. V., Ratsimbazafy, J., Valente, D., & others. (2023). There You Are! Automated Detection of Indris' Songs on Features Extracted from Passive Acoustic Recordings. *Animals*, 13(2), 241.
- Ross, J. C. (2013). *flightcallr: Classify Night Flight Calls Based on Acoustic Measurements*. <https://R-Forge.R-project.org/projects/flightcallr/>
- Ruan, W., Wu, K., Chen, Q., & Zhang, C. (2022). ResNet-based bio-acoustics presence detection technology of Hainan gibbon calls. *Applied Acoustics*, 198, 108939.
<https://doi.org/10.1016/j.apacoust.2022.108939>
- Ruff, Z. J., Lesmeister, D. B., Appel, C. L., & Sullivan, C. M. (2020). *Convolutional neural network and R-Shiny app for identifying vocalizations in Pacific Northwest forests* [Computer software]. Zenodo. <https://doi.org/10.5281/zenodo.4092393>

- Sapieższko, G., & Mikhael, W. B. (2018). An Overview of Recent Convolutional Neural Network Algorithms for Image Recognition. *2018 IEEE 61st International Midwest Symposium on Circuits and Systems (MWSCAS)*, 743–746.
<https://doi.org/10.1109/MWSCAS.2018.8623911>
- Scavetta, R. J., & Angelov, B. (2021). *Python and R for the Modern Data Scientist*. O'Reilly Media, Inc.
- Sharma, S., Sharma, S., & Athaiya, A. (2017). Activation functions in neural networks. *Towards Data Sci*, 6(12), 310–316.
- Simonyan, K., & Zisserman, A. (2014). Very deep convolutional networks for large-scale image recognition. *arXiv Preprint arXiv:1409.1556*.
- Smith, L. N., & Topin, N. (2018). *Super-Convergence: Very Fast Training of Neural Networks Using Large Learning Rates* (arXiv:1708.07120). arXiv.
<https://doi.org/10.48550/arXiv.1708.07120>
- Stevens, E., Antiga, L., & Viehmann, T. (2020). *Deep Learning with PyTorch*. Simon and Schuster.
- Stowell, D. (2022). Computational bioacoustics with deep learning: A review and roadmap. *PeerJ*, 10, e13152. <https://doi.org/10.7717/peerj.13152>
- Stowell, D., Wood, M. D., Pamuła, H., Stylianou, Y., & Glotin, H. (2019). Automatic acoustic detection of birds through deep learning: The first Bird Audio Detection challenge. *Methods in Ecology and Evolution*, 10(3), 368–380. <https://doi.org/10.1111/2041-210X.13103>
- Sueur, J., Aubin, T., & Simonis, C. (2008). Seewave: A free modular tool for sound analysis and synthesis. *Bioacoustics*, 18, 213–226.

- Sugai, L. S. M., Silva, T. S. F., Ribeiro, J. W., & Llusia, D. (2019). Terrestrial Passive Acoustic Monitoring: Review and Perspectives. *BioScience*, 69(1), 15–25.
<https://doi.org/10.1093/biosci/biy147>
- Tan, C., Sun, F., Kong, T., Zhang, W., Yang, C., & Liu, C. (2018). A survey on deep transfer learning. *Artificial Neural Networks and Machine Learning–ICANN 2018: 27th International Conference on Artificial Neural Networks, Rhodes, Greece, October 4-7, 2018, Proceedings, Part III 27*, 270–279.
- Tuia, D., Kellenberger, B., Beery, S., Costelloe, B. R., Zuffi, S., Risse, B., Mathis, A., Mathis, M. W., van Langevelde, F., Burghardt, T., & others. (2022). Perspectives in machine learning for wildlife conservation. *Nature Communications*, 13(1), 1–15.
- Ushey, K., Allaire, J. J., & Tang, Y. (2022). *reticulate: Interface to “Python.”*
- Van Chuong, H., Duc, H. M., Long, H. T., Van Tuan, B., Covert, H. H., & Williams, S. E. (2018). A review of the distribution of a new gibbon species: The northern yellow-cheeked crested gibbon *Nomascus annamensis* Thinh, Mootnick, Thanh, Nadler and Roos, 2010. *Primate Conservation*, 32(1), 185–191.
- Vu, T. T., Doherty, P. F., T. Nguyen, H., Clink, D. J., Nguyen, M. D., Dong, H. T., Cheyne, S. M., Giang, T. T., Phan, D. V., Ta, N. T., & Tran, D. V. (2023). Passive acoustic monitoring using smartphones reveals an alarming gibbon decline in a protected area in the central Annamite Mountains, Vietnam. *American Journal of Primatology*, 85(11), e23544. <https://doi.org/10.1002/ajp.23544>
- Vu, T. T., & Tran, L. M. (2019). An Application of Autonomous Recorders for Gibbon Monitoring. *International Journal of Primatology*, 40(2), 169–186.
<https://doi.org/10.1007/s10764-018-0073-3>

- Walsh, R. P., & Newbery, D. M. (1999). The ecoclimatology of Danum, Sabah, in the context of the world's rainforest regions, with particular reference to dry periods and their impact. *Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences*, 354(1391), 1869–1883. <https://doi.org/10.1098/rstb.1999.0528>
- Wani, M. A., Bhat, F. A., Afzal, S., & Khan, A. I. (2020). *Advances in deep learning*. Springer.
- Wearn, O. R., Trinh-Dinh, H., Ma, C.-Y., Khac Le, Q., Nguyen, P., Van Hoang, T., Van Luong, C., Van Hua, T., Van Hoang, Q., Fan, P.-F., & Duc Nguyen, T. (2024). Vocal fingerprinting reveals a substantially smaller global population of the Critically Endangered cao vit gibbon (*Nomascus nasutus*) than previously thought. *Scientific Reports*, 14(1), Article 1. <https://doi.org/10.1038/s41598-023-50838-2>
- Weiss, K., Khoshgoftaar, T. M., & Wang, D. (2016). A survey of transfer learning. *Journal of Big Data*, 3(1), 1–40.
- Wrege, P. H., Rowland, E. D., Keen, S., & Shiu, Y. (2017). Acoustic monitoring for conservation in tropical forests: Examples from forest elephants. *Methods in Ecology and Evolution*, 8(10), 1292–1301. <https://doi.org/10.1111/2041-210X.12730>
- Yu, W., Yang, K., Bai, Y., Xiao, T., Yao, H., & Rui, Y. (2016). Visualizing and comparing AlexNet and VGG using deconvolutional layers. *Proceedings of the 33 Rd International Conference on Machine Learning*.
- Zeiler, M. D., & Fergus, R. (2014). Visualizing and understanding convolutional networks. *Computer Vision—ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6–12, 2014, Proceedings, Part I 13*, 818–833.

Zhong, E., Guan, Z., Zhou, X., Zhao, Y., Li, H., Tan, S., & Hu, K. (2021). Application of passive acoustic monitoring technology in the monitoring of western black crested gibbons.

Biodiversity Science, 29(1), 109–117.

Zhou, X., Hu, K., Guan, Z., Yu, C., Wang, S., Fan, M., Sun, Y., Cao, Y., Wang, Y., & Miao, G.

(2023). Methods for processing and analyzing passive acoustic monitoring data: An example of song recognition in western black-crested gibbons. *Ecological Indicators*,

155, 110908. <https://doi.org/10.1016/j.ecolind.2023.110908>