Hyper parametric timed CTL

Masaki Waga and Étienne André *

Abstract

Hyperproperties enable simultaneous reasoning about multiple execution traces of a system and are useful to reason about non-interference, opacity, robustness, fairness, observational determinism, etc. We introduce hyper parametric timed computation tree logic (HyperPTCTL), extending hyperlogics with timing reasoning and, notably, parameters to express unknown values. We mainly consider its nest-free fragment, where temporal operators cannot be nested. However, we allow extensions that enable counting actions and comparing the duration since the most recent occurrence of specific actions. We show that our nest-free fragment with this extension is sufficiently expressive to encode properties, e.g., opacity, (un)fairness, or robust observational (non-)determinism. We propose semi-algorithms for model checking and synthesis of parametric timed automata (an extension of timed automata with timing parameters) against this nest-free fragment with the extension via reduction to PTCTL model checking and synthesis. While the general model checking (and thus synthesis) problem is undecidable, we show that a large part of our extended (yet nest-free) fragment is decidable, provided the parameters only appear in the property, not in the model. We also exhibit additional decidable fragments where parameters within the model are allowed. We implemented our semialgorithms on top of the IMITATOR model checker, and performed experiments. Our implementation supports

most of the nest-free fragments (beyond the decidable classes). The experimental results highlight our method's practical relevance.

1 Introduction

Parametric timed automata (PTAs) [AHV93] is an extension of finite-state automata for modeling and verification of real-time systems, where the timing constraints are not fixed but parameterized. PTAs extend the concept of timed automata (TAs) [AD94] by introducing parameters into time bounds, allowing for analyzing a system behavior across a range of timing scenarios.

Hyperproperties enable reasoning simultaneously about multiple execution traces of a system and turn useful to reason about non-interference, opacity, fairness, robustness, observational determinism, etc. We introduce *hyper parametric timed computation tree logic* (HyperPTCTL), extending hyperlogics with not only timing reasoning but also timing parameters able to express unknown values. HyperPTCTL can be used typically to reason about multiple traces on PTAs.

After defining the syntax and semantics of general HyperPTCTL, we mainly consider the nest-free fragment, where temporal operators cannot be nested. However, we extend HyperPTCTL with additional predicates that enable counting actions and comparing the duration since the most recent occurrence of specific actions using diagonal constraints of the form $LAST(\sigma_{\pi_1}) - LAST(\sigma_{\pi_2})$, where σ is a proposition and $\pi_1 \pi_2$ represent two paths. Even without the nesting of temporal operators, we demonstrate that this extension enables encoding classical

^{*}This work is partially supported by JST PRESTO Grant No. JPMJPR22CA, JST CREST Grant No. JPMJCR2012, JSPS KAKENHI Grant No. 22K17873, ANR ProMiS (ANR-19-CE25-0015), and ANR BisoUS (ANR-22-CE48-0012).

[†]M. Waga is with Kyoto University, Kyoto, Japan. É. André is with Université Sorbonne Paris Nord, LIPN, CNRS UMR 7030, F-93430 Villetaneuse, France.

[‡]This is the author (and extended) version of the manuscript of the same name published in IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems (TCAD). The final version is available at https://ieeexplore.ieee.org/.

System PTA $\mathcal{A} \longrightarrow$ Composed PTA $\mathcal{A}^n \rightarrow$ Product PTA $\mathcal{A}^n \times \mathcal{O}_{\psi'}$ Observer PTA $\mathcal{O}_{\psi'}$ Result Ext-HyperPTCTL formula $\psi' \rightarrow$ PTCTL formula $\psi' \rightarrow$ PTCTL formula ψ''

Fig. 1: Our reduction: Nest-Free Ext-HyperPTCTL synthesis (resp. model checking) is reduced to Ext-PTCTL synthesis (resp. model checking) via self-composition; the extended predicates in Ext-PTCTL are evaluated by an observer PTA, which is composed with the PTA \mathcal{A}^n .

tional (non-) determinism—in a timed and paramet- execution traces) in the Ext-HyperPTCTL formula ψ . ric setting. For example, we can use a simple Hy- Then, we construct an observer PTA $\mathcal{O}_{\psi'}$ [Ace+03] perPTCTL formula to encode a *robust observational* to evaluate the extended predicates in the given Nestnon-determinism: "By giving the same sequence of Free Ext-PTCTL formula ψ' . We show that the reinputs at the same timing to the system, it is possi- sult of PTCTL model checking (resp. synthesis) for ble to get the same sequence of outputs but with large the product PTA $\mathcal{A}^n \times \mathcal{O}_{\psi'}$ is the same as the retime difference". A timing parameter in the formula sult of the original problem. Thus, the original probis used to leave the time difference unspecified, and, lem is reduced to PTCTL model checking (resp. synfor example, the feasible values can be synthesized (by thesis). By integrating this reduction with a semiour semi-algorithm). The concrete formula is shown algorithm for PTCTL model checking (resp. synthein Section 4.1. We denote this nest-free but extended sis), we derive a semi-algorithm for Nest-Free Extfragment by Nest-Free Ext-HyperPTCTL.

We consider two problems over parametric formulas and/or models:

- The model checking problem asks whether there exists a valuation for which the model satisfies the formula; and
- The synthesis problem asks for the exact valuations set for which the model satisfies the formula. Ideally, this representation should be given symbolically, e.g., in a decidable logical formalism.

We constructively show that Nest-Free Ext-HyperPTCTL model checking (resp. synthesis) of PTAs is reducible to PTCTL model checking (resp. synthesis) of PTAs. Fig. 1 outlines our reduction. We show a more concrete working example later in Section 5.3. First, we reduce Nest-Free Ext-HyperPTCTL model checking (resp. synthesis) to Nest-Free Ext-PTCTL model checking (resp. synthesis) by taking the self-composition \mathcal{A}^n of the system PTA \mathcal{A} , where n is the number of quantified path Our contributions are summarized as follows:

properties such as opacity, (un)fairness, or observa-variables (i.e., the number of simultaneously reasoned HyperPTCTL model checking (resp. synthesis).

> While Nest-Free Ext-HyperPTCTL model checking of PTAs is trivially undecidable due to the undecidability of reachability-emptiness of PTAs [AHV93], we show that they are decidable for a large part of Nest-Free Ext-HyperPTCTL, provided the parameters only appear in the property, not in the model. We also exhibit additional decidable fragments where parameters in the model are allowed.

> We implemented our approach on top of the existing IMITATOR parametric timed model [And21] and performed a set of experchecker iments. Our implementation HyPTCTLchecker supports most of the nest-free fragment (beyond the decidable classes too—in which case at the risk of non-termination or approximated result). The experimental results show that our approach can handle various properties if the PTA has a moderate size.

1.1 Contributions

- 1. We introduce HyperPTCTL and its extension Ext-HyperPTCTL to count actions and to measure the time since their last occurrence and define their syntax and semantics (Section 4);
- 2. We propose semi-algorithms for Nest-Free Ext-HyperPTCTL model checking (resp. synthesis) of PTAs via reduction to PTCTL model checking (resp. synthesis) of PTAs (Section 5);
- 3. While Nest-Free Ext-HyperPTCTL model checking and synthesis are trivially undecidable, we exhibit several decidable subclasses, with parameters either in the PTA or in the Nest-Free Ext-HyperPTCTL formula (Section 6);
- 4. We implemented our approach and performed experiments. The experimental results suggest the practical relevance of our approach, particularly for the PTAs with moderate size (Section 7).

To the best of our knowledge, our work is not only the first one extending TCTL into hyperlogics, but also the first one to allow for timing parameters in such a TCTL hyper-extension.

2 Related works

2.1 Model checking parametric timed formalisms

First, model checking PTAs against the nonparametric nest-free fragment (without nested operators) of PTCTL is already undecidable, as reachability-emptiness (also called $\exists \diamondsuit$ -emptiness, i.e., the emptiness over the valuations set for which a given location can be reached) is undecidable for general PTAs over dense or discrete time [AHV93], including without any closed inequality [Doy07]. Unavoidability($\forall \diamondsuit$)-emptiness is undecidable too [JLR15]. As a consequence, model checking (P)TCTL against PTAs is undecidable in general too, and synthesis is intractable.

Reachability-emptiness over discrete time for PTAs with 2 parametric clocks¹, arbitrarily many

1. We introduce HyperPTCTL and its extension non-parametric clocks and 1 parameter is decid-Ext-HyperPTCTL to count actions and to mea- able [BO17] and EXPSPACE-complete [GH21].

> In [ET99], a Parameterized Real-Time Computation Tree Logic ("PRTCTL") is defined, with a decidable polynomial model checking algorithm for a fixed number of parameters; the timed model is however severely restricted when compared to TAs.

> In [BR07], model checking PTAs with a single parametric clock (and arbitrarily many nonparametric clocks, but this is equivalent over discrete time [AHV93]) against parametric TCTL is proved to be undecidable over discrete time. Also note that this negative result holds even when adding some further syntactic restrictions (see [BR07, Remark 3.5]). On the positive side, for the "F-PTCTL" fragment (in which equalities are forbidden in all operators, and inequalities with \geq and > are forbidden in the $\forall U$ operators), model checking PTAs with a single parametric clock is proved to be decidable [BR07, Corollary 3.11], and synthesis can be achieved [BR07, Corollary 3.12] thanks to a characterization of the valuations set using a Presburger formula. Emptiness, universality or finiteness ("is the valuations set finite?") follow immediately.

> In [BDR08], model checking non-parametric TAs against parametric TCTL (with integer-valued parameters) is considered over both discrete time and dense time. \exists PTCTL is defined as the existential fragment (over parameters) of PTCTL². Both the discrete time [BDR08, Corollary 7.3] and dense time [BDR08, Theorem 7.5] model checking problems are in 5EXPTIME in the product of the model and the formula, and are in 3EXPTIME for the \exists PTCTL fragment [BDR08, Propositions 7.4 and 7.6].³

Model-checking subclasses of PTAs against TCTL (beyond reachability) is notably considered in [ALR18]: on the one hand, even for the severely restricted class of U-PTAs (a subclass of PTAs

¹ A parametric clock is a clock compared to a parameter in at least one guard or invariant.

² Of the form $\exists p_1, \dots, p_n : \varphi$ with φ without quantifiers over parameters. Note that, throughout this paper, we use \exists to distinguish between existential quantification over parameters (\exists) and over paths (\exists) .

³ Exact complexity is not given in [BDR08], but it is noted that discrete and dense time model checking \exists PTCTL is at least PSPACE-HARD [ACD90; AL02], while discrete and dense time model checking PTCTL is at least 2NEXPTIME-HARD [FR74].

in which parameters can only be compared to a requirement mining from traces rather than model clock as an upper bound [BL09]), and even without checking. Quantifier alternation is allowed. invariants, the emptiness is undecidable for nested TCTL (the proof uses the " $\exists \Box \forall \Diamond_{=0}$ " formula). This ting [Ábr+20] orthogonal to our timed setting. undecidability result comes with two flavors:

- 1. over unbounded (possibly integer-valued) parameters, the proof of which uses 5 clocks and 2 parameters; and
- 2. over bounded rational-valued parameters, the proof of which uses 4 clocks and 1 parameters.

On the other hand, it is then shown in [ALR18] that nest-free TCTL is decidable for L/U-PTAs (a subclass of PTAs in which parameters are partitioned between lower-bound and upper-bound parameters [Hun+02]) without invariants.

2.2 Hyperproperties

Hyperproperties drew recent attention, and various hyperlogics have been introduced by extending conventional temporal logics (e.g., [Cla+14; HZJ21; BPS22; Ger+23; Bar+23; BPS20]).

One of the closest works to our timed hyperlogics (without parameters) is HyperMITL [HZJ21], a timed extension of HyperLTL [Cla+14]. In general, the model checking problem is undecidable, even with very restricting timing constraints; it becomes decidable under certain conditions, notably absence of alternation. For decidable subcases, the authors use a construction based on *self-composition*, which we also use in Section 5.1. However, their construction is primarily for untimed models, while our reduction is for PTAs.

Another closely related work isHyper-MTL [BPS20], another timed extension of HyperLTL. If the time domain is discrete, i.e., the timestamps are integers, HyperMTL model checking is decidable even with quantifier alternation. Although their algorithm covers many interesting properties, it is limited to discrete-time and non-parametric settings.

Both amplitude and timing parameters are considered in [Bar+23] for HyperSTL, but the goal is to undecidability [Mil00].

Parametric probabilities are considered in a set-

Preliminaries 3

For a set X, we denote its powerset by $\mathcal{P}(X)$. For a finite set X, we denote its size by |X|. For sets X, Y, we denote a partial function f from X to Y by $f: X \rightarrow Y$ and denote its domain by $\mathbf{dom}(f) \subseteq X$. For $x \in \mathbb{Z}$ and $N \in \mathbb{N}$, we let $x \mod N \in \{0, 1, \dots, N-1\}$ be such that $x \mod N + yN = x$ for some $y \in \mathbb{Z}$.

3.1 Clocks, clock guards, and parameters

We let \mathbb{T} be the domain of the time, which will be either non-negative reals $\mathbb{R}_{\geq 0}$ (continuous-time semantics) or naturals \mathbb{N} (discrete-time semantics). Let $= \{c_1, \ldots, c_H\}$ be a set of *clocks*, i.e., variables that C evolve at the same rate. A clock valuation is a function $\nu : \mathbb{C} \to \mathbb{T}$. We write $\vec{0}_{\mathbb{C}}$ for the clock valuation assigning 0 to all clocks. Given $d \in \mathbb{T}$, $\nu + d$ denotes the valuation s.t. $(\nu + d)(c) = \nu(c) + d$, for all $c \in \mathbb{C}$. Given $R \subseteq \mathbb{C}$, we define the *reset* of a valuation ν , denoted by $[\nu]_R$, as follows: $[\nu]_R(c) = 0$ if $c \in R$, and $[\nu]_R(c) = \nu(c)$ otherwise.

We assume a set $\mathbb{P} = \{p_1, \ldots, p_M\}$ of parameters, i.e., unknown constants. A parameter valuation v is a function $v: \mathbb{P} \to \mathbb{Q}_{>0}$.⁴ We assume $\bowtie \in \{<, \leq, =, \geq, >\}$. A *(clock) guard g* is a constraint over $\mathbb{C} \cup \mathbb{P}$ defined by a conjunction of inequalities of the form $c \bowtie \gamma$ with $\gamma \in \mathbb{P} \cup \mathbb{N}$. For simplicity, we often use intervals instead of a conjunction of inequalities. Given q, we write $\nu \models v(q)$ if the expression obtained by replacing each c with $\nu(c)$ and each p with v(p) in q evaluates to true. For a finite set $X = \{x_1, x_2, \dots, x_N\}$ of size $N \in \mathbb{N}$, a linear term lt (resp. non-negative linear term $lt_{\geq 0}$) is of the form $\sum_{1 \le i \le N} \alpha_i x_i + d, \text{ with } \alpha_i, d \in \mathbb{Z} \text{ (resp. } \alpha_i, d \in \mathbb{N} \text{)}.$

 $^{^4}$ We choose $\mathbb{Q}_{\geq 0}$ by consistency with most of the PTA literature, but also because, for classical PTAs, choosing $\mathbb{R}_{\geq 0}$ leads

3.2 Parametric timed automata

Parametric timed automata (PTAs) [AHV93] extend timed automata [AD94] with parameters within guards and invariants in place of integer constants.

Definition 1 (PTA). A parametric timed automaton (PTA) \mathcal{A} is an 8-tuple $\mathcal{A} = (\Sigma, L, L_0, \mathbb{C}, \mathbb{P}, I, E, \Lambda)$, where:

- Σ is a finite set of atomic propositions;
- *L* is a finite set of locations;
- $L_0 \subseteq L$ is the set of initial locations,
- C is a finite set of clocks;
- P is a finite set of parameters;
- *I* is the invariant, assigning to every *l* ∈ *L* a clock guard *I*(*l*);
- *E* is a finite set of edges $e = (\ell, g, R, \ell')$, where $\ell, \ell' \in L$ are the source and target locations, $R \subseteq \mathbb{C}$ is a set of clocks to be reset, and *g* is the transition guard;
- Λ: L → P(Σ) is the labeling function assigning the atomic propositions satisfied at each location.

Given a parameter valuation v, we denote by $v(\mathcal{A})$ the non-parametric structure where all occurrences of a parameter p_i have been replaced by $v(p_i)$. We refer as a *timed automaton (TA)* to any structure $v(\mathcal{A})$, by assuming a rescaling of the constants: by multiplying all constants in $v(\mathcal{A})$ by the least common multiple of their denominators, we obtain an equivalent (integervalued) TA, as defined in [AD94].

The PTA in Fig. 2 contains 1 clock c and one parameter p_1 . The invariant of ℓ_0 is " $c \leq p_1$ " and the transition to ℓ_1 is guarded by " $p_1 - 1 < c < p_1$ ", and resets c. Atomic propositions H and L are associated with ℓ_0 and ℓ_1 , respectively. This PTA models a clock generator with drift: the digital signal switches between high (H) and low (L) states in a near periodic manner but with some timing deviation, depending on the value of parameter p_1 .

Let us now recall the concrete semantics of TAs.



Fig. 2: Drifted clock generator example: PTA \mathcal{A}

Definition 2 (Semantics of a TA). For a PTA $\mathcal{A} = (\Sigma, L, L_0, \mathbb{C}, \mathbb{P}, I, E, \Lambda)$ and a parameter valuation v, the semantics of the TA $v(\mathcal{A})$ is given by the timed transition system (TTS) $T_{\mathcal{A}} = (S, S_0, \rightarrow)$, with

- $S = \{(\ell, \nu) \in L \times \mathbb{T}^H \mid \nu \models I(\ell)\},\$
- $S_0 = \{ (\ell_0, \vec{0}_{\mathbb{C}}) \mid \ell_0 \in L_0 \},$
- \rightarrow consists of the discrete and (continuous) delay transition relations:
 - discrete transitions $(\ell, \nu) \stackrel{e}{\mapsto} (\ell', \nu')$, if $(\ell, \nu), (\ell', \nu') \in S$, and there exists $e = (\ell, g, R, \ell') \in E$, such that $\nu' = [\nu]_R$, and $\nu \models g$.
 - delay transitions $(\ell, \nu) \stackrel{d}{\mapsto} (\ell, \nu + d)$, with $d \in \mathbb{T}$, if $\forall d' \in [0, d], (\ell, \nu + d') \in S$.

Moreover, we write $(\ell, \nu) \xrightarrow{(d,e)} (\ell', \nu')$ for a combination of delay and discrete transitions if $\exists \nu'' : (\ell, \nu) \stackrel{d}{\mapsto} (\ell, \nu'') \stackrel{e}{\mapsto} (\ell', \nu')$. We let $\Lambda((\ell, \nu)) = \Lambda(\ell)$.

Given a TA $v(\mathcal{A})$ with concrete semantics (S, S_0, \rightarrow) , we refer to the states S as the concrete states of $v(\mathcal{A})$. For $s = (\ell, \nu) \in S$ and $d \in \mathbb{T}$, we let $s + d = (\ell, \nu + d)$. A path of $v(\mathcal{A})$ from a concrete state s is an alternating *infinite* sequence of concrete states of $v(\mathcal{A})$ and pairs of edges and delays starting from s of the form $s_0(=s), (d_0, e_0), s_1, \ldots$ with $\sum_{i=0}^{\infty} d_i = +\infty$, for each $i = 0, 1, \dots, d_i \in \mathbb{T}, e_i \in E$, and $s_i \stackrel{(d_{i},e_{i})}{\longrightarrow} s_{i+1}$. We denote the set of paths of $v(\mathcal{A})$ from s by $Paths(v(\mathcal{A}), s)$. We let $Paths(v(\mathcal{A})) =$ $\bigcup_{s \in S} Paths(v(\mathcal{A}), s)$. For a path $s_0, (d_0, e_0), s_1, \ldots$ of $v(\mathcal{A})$, a position is a concrete state s satisfying $s = s_i + d$ for some $i \in \mathbb{N}$ and $d \leq d_i$. For a path ρ , we denote its initial position s_0 by $Init(\rho)$. For a position $s = s_i + d$ of a path $\rho = s_0, (d_0, e_0), s_1, \ldots$, the duration $Dur_{\rho}(s)$ is $Dur_{\rho}(s) = d + \sum_{j=0}^{i-1} d_j$. If the path is clear from the context, we just write Dur(s). For positions $s = s_i + d$ and $s' = s_i + d'$ of a path $s_0, (d_0, e_0), s_1, \ldots$, we let s < s' if we have i < j or Dur(s) < Dur(s'). We let $s \leq s'$ if we have s < s'

suffix of ρ , i.e., for $\rho = s_0, (d_0, e_0), s_1, \ldots, \rho'$ is such that $s_i + d, (d_i - d, e_i), s_{i+1}, \dots$ for some $i \in \mathbb{N}$ and $d \in [0, d_i]$. We let $\mathcal{D}^{\rho}_{\rho'}$ be such *i*. We let $\rho \succ \rho'$ if we have $\rho \succeq \rho'$ and $\rho \neq \rho'$. For paths ρ, ρ' satisfying $\rho \succeq \rho'$, we let $Dur(\rho - \rho')$ be the duration of the initial position of ρ' in ρ .

For PTAs \mathcal{A}^1 and \mathcal{A}^2 , we define both parallel composition $\mathcal{A}^1 \parallel \mathcal{A}^2$ and synchronized product $\mathcal{A}^1 \times \mathcal{A}^2$. Intuitively, the parallel composition is to juxtapose two PTAs without synchronization, whereas the synchronized product is to compose two PTAs synchronizing the edges with the propositions. The parallel composition will be used when taking selfcomposition of the systems to handle multiple paths simultaneously, while the synchronized product will be used when composing the systems with observers encoding extended predicates (Section 5.2).

For PTAs $\mathcal{A}^1 = (\Sigma^1, L^1, L^1_0, \mathbb{C}^1, \mathbb{P}^1, I^1, E^1, \Lambda^1)$ and $\mathcal{A}^2 = (\Sigma^2, L^2, L^2_0, \mathbb{C}^2, \mathbb{P}^2, I^2, E^2, \Lambda^2)$, their parallel composition is $\mathcal{A}^1 \parallel \mathcal{A}^2 = (\Sigma^1 \sqcup \Sigma^2, L^1 \times L^2, L_0^1 \times L^2)$ $L^2_0, \mathbb{C}^1 \sqcup \mathbb{C}^2, \mathbb{P}^1 \cup \mathbb{P}^2, I, E, \Lambda)$, with \sqcup denoting disjoint union, $I((\ell^1, \ell^2)) = I^1(\ell^1) \wedge I^2(\ell^2), E$ = $\left\{ \left((\ell^1, \ell^2), g, R, ({\ell^1}', \ell^2) \right) \mid (\ell^1, g, R, {\ell^1}') \in E^1, \ell^2 \right\}$ \in $L^{2} \cup \{(\ell^{1}, \ell^{2}), q, R, (\ell^{2}, \ell^{2'})) \mid (\ell^{2}, q, R, \ell^{2'})$ \in $E^{2}, \ell^{1} \in L^{1} \} \cup \{ ((\ell^{1}, \ell^{2}), g^{1} \land g^{2}, R^{1} \cup R^{2}, (\ell^{1'}, \ell^{2'})) \}$ $(\ell^1, q^1, R^1, {\ell^1}') \in E^1, (\ell^2, q^2, R^2, {\ell^2}') \in E^2\},$ and $\Lambda((\ell^1,\ell^2)) = \Lambda^1(\ell^1) \sqcup \Lambda^2(\ell^2)$. For TAs $v_1(\mathcal{A}_1)$ and $v_2(\mathcal{A}_2)$ satisfying $v_1(p) = v_2(p)$ for any $p \in \mathbb{P}_1 \cap \mathbb{P}_2$, and paths ρ_1 and ρ_2 of $v_1(\mathcal{A}_1)$ and $v_2(\mathcal{A}_2)$, respectively, we let $\rho_1 \parallel \rho_2$ be the path of $(v_1 \cup v_2)(\mathcal{A}_1 \parallel \mathcal{A}_2)$ obtained by parallel composition of ρ_1 and ρ_2 , where $v_1 \cup v_2$ is the parameter valuation such that $(v_1 \cup v_2)$ $v_2(p) = v_1(p)$ if $p \in v_1$ and otherwise $(v_1 \cup v_2)(p) =$ $v_2(p)$. Conversely, for a path ρ of $(v_1 \cup v_2)(\mathcal{A}_1 \parallel \mathcal{A}_2)$ and $i \in \{1, 2\}$, we let $\rho|_i$ be the path of $v_i(\mathcal{A}_i)$ obtained by removing the locations, clock valuations, $\forall \pi_1, \pi_2, \ldots, \pi_n. \varphi_1 \mathcal{W}_{\bowtie\gamma} \varphi_2 \equiv \forall \pi_1, \pi_2, \ldots, \pi_n. \varphi_2 \mathcal{R}_{\bowtie\gamma} (\varphi_1 \lor \varphi_2)$ and edges from \mathcal{A}_{3-i} .

For PTAs $\mathcal{A}^1 = (\Sigma^1, L^1, L^1_0, \mathbb{C}^1, \mathbb{P}^1, I^1, E^1, \Lambda^1)$ and $\mathcal{A}^2 = (\Sigma^2, L^2, L^2_0, \mathbb{C}^2, \mathbb{P}^2, I^2, E^2, \Lambda^2)$, their synchronized product is $\mathcal{A}^1 \times \mathcal{A}^2 = (\Sigma^1 \cup \Sigma^2, L^1 \times L^2, L_0, \mathbb{C}^1 \sqcup$ $\mathbb{C}^2, \mathbb{P}^1 \cup \mathbb{P}^2, I, E, \Lambda$, with $L_0 = \{(\ell_0^1, \ell_0^2) \in L_0^1 \times L_0^2 \mid$ $\Lambda^1(\ell_0^1) \cap \Sigma^2 = \Lambda^2(\ell_0^2) \cap \Sigma^1\}, \ I((\ell^1, \ell^2)) = I^1(\ell^1) \wedge$ $I^{2}(\ell^{2}), E = \left\{ \left((\ell^{1}, \ell^{2}), g, R, (\ell^{1'}, \ell^{2}) \right) \mid (\ell^{1}, g, R, \ell^{1'}) \in \tilde{\exists} p_{1} \tilde{\exists} p_{2} \dots \tilde{\exists} p_{n} \psi, \text{ where } \psi \text{ has no quantifiers over } \ell^{2} \ell$

or s = s'. For paths ρ, ρ' , we write $\rho \succeq \rho'$ if ρ' is a $E^1, \ell^2 \in L^2, \Lambda^1(\ell^{1'}) \cap \Sigma^2 = \Lambda^2(\ell^2) \cap \Sigma^1 \cup U$ $\{((\ell^1, \ell^2), q, R, (\ell^1, {\ell^2}')) \mid (\ell^2, q, R, {\ell^2}') \in E^2, \ell^1 \in E^2,$ $L^1, \Lambda^1(\ell^1) \cap \Sigma^2 = \Lambda^2(\ell^{2'}) \cap \Sigma^1 \bigcup \{ ((\ell^1, \ell^2), g^1 \land g^2, R^1 \sqcup g^2) \} \cup \{ ((\ell^1, \ell^2), g^1 \land g^2) \} \cup \{ (\ell^1, \ell^2), g^1 \land g^2) \} \cup \{ (\ell^2, \ell^2), g^1 \land g^2) \} \cup \{ (\ell^2, \ell^2), g^2 \land g^2) \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell^2, \ell^2) \} \cup \{ (\ell^2, \ell^2) \} \} \cup \{ (\ell$ $R^{2}, (\ell^{1'}, \ell^{2'})) \mid (\ell^{1}, q^{1}, R^{1}, \ell^{1'}) \in E^{1}, (\ell^{2}, q^{2}, R^{2}, \ell^{2'}) \in$ $E^2, \Lambda^1(\ell^{1'}) \cap \Sigma^2 = \Lambda^2(\ell^{2'}) \cap \Sigma^1$, and $\Lambda((\ell^1, \ell^2)) =$ $\Lambda^1(\ell^1) \cup \Lambda^2(\ell^2)$. For a finite set $I = \{1, 2, \dots, n\}$ of indices, we let $X_{i \in I} \mathcal{A}^i = \mathcal{A}^1 \times \mathcal{A}^2 \times \cdots \times \mathcal{A}^n$, where each \mathcal{A}^i is a PTA.

Hyper parametric timed CTL 4

Here, we introduce hyper parametric timed computation tree logic (HyperPTCTL). HyperPTCTL is a generalization of PTCTL [BDR08] with quantifiers over paths to represent hyperproperties.

4.1 Syntax of (Ext-)HyperPTCTL

Definition 3 (Syntax of HyperPTCTL). For atomic propositions Σ and parameters \mathbb{P} , the syntax of HyperPTCTL formulas of the temporal level φ and the top level ψ are defined as follows, where $\sigma \in \Sigma$, \mathcal{V} is the set of path variables, $\pi, \pi_1, \pi_2, \ldots, \pi_n \in \mathcal{V}$, $\gamma \in \mathbb{P} \cup \mathbb{N}, p \in \mathbb{P}, \bowtie \in \{<, \leq, =, \geq, >\}, \text{ and } lt_{\geq 0}$ is a non-negative linear term over \mathbb{P} :

$$\begin{split} \varphi &::= \top \mid \sigma_{\pi} \mid \neg \varphi \mid \varphi \lor \varphi \mid \exists \pi_{1}, \pi_{2}, \dots, \pi_{n}. \varphi \, \mathcal{U}_{\bowtie \gamma} \varphi \\ \mid \forall \pi_{1}, \pi_{2}, \dots, \pi_{n}. \varphi \, \mathcal{U}_{\bowtie \gamma} \varphi \\ \psi &::= \varphi \mid p \bowtie lt_{>0} \mid \neg \psi \mid \psi \lor \psi \mid \tilde{\exists} p \, \psi \end{split}$$

As syntax sugar, we utilize the following formulas:

 $\bot \equiv \neg \top \quad \varphi_1 \land \varphi_2 \equiv \neg (\neg \varphi_1 \lor \neg \varphi_2) \quad \varphi_1 \implies \varphi_2 \equiv \neg \varphi_1 \lor \varphi_2$ $\varphi_1 = \varphi_2 \equiv (\varphi_1 \land \varphi_2) \lor ((\neg \varphi_1) \land (\neg \varphi_2)) \quad \varphi_1 \neq \varphi_2 \equiv \neg (\varphi_1 = \varphi_2)$ $\exists \pi_1, \pi_2, \ldots, \pi_n. \varphi_1 \mathcal{R}_{\bowtie \gamma} \varphi_2 \equiv \neg \forall \pi_1, \pi_2, \ldots, \pi_n. \neg \varphi_1 \mathcal{U}_{\bowtie \gamma} \neg \varphi_2$ $\forall \pi_1, \pi_2, \dots, \pi_n. \varphi_1 \mathcal{R}_{\bowtie \gamma} \varphi_2 \equiv \neg \exists \pi_1, \pi_2, \dots, \pi_n. \neg \varphi_1 \mathcal{U}_{\bowtie \gamma} \neg \varphi_2$ $\exists \pi_1, \pi_2, \dots, \pi_n. \varphi_1 \mathcal{W}_{\bowtie \gamma} \varphi_2 \equiv \exists \pi_1, \pi_2, \dots, \pi_n. \varphi_2 \mathcal{R}_{\bowtie \gamma} (\varphi_1 \lor \varphi_2)$ $\exists \pi_1, \pi_2, \ldots, \pi_n . \Diamond_{\bowtie \gamma} \varphi \equiv \exists \pi_1, \pi_2, \ldots, \pi_n . \top \mathcal{U}_{\bowtie \gamma} \varphi$ $\forall \pi_1, \pi_2, \ldots, \pi_n. \Diamond_{\bowtie \gamma} \varphi \equiv \forall \pi_1, \pi_2, \ldots, \pi_n. \top \mathcal{U}_{\bowtie \gamma} \varphi$ $\exists \pi_1, \pi_2, \ldots, \pi_n. \Box_{\bowtie \gamma} \varphi \equiv \exists \pi_1, \pi_2, \ldots, \pi_n. \perp \mathcal{R}_{\bowtie \gamma} \varphi$ $\forall \pi_1, \pi_2, \ldots, \pi_n. \square_{\bowtie \gamma} \varphi \equiv \forall \pi_1, \pi_2, \ldots, \pi_n. \perp \mathcal{R}_{\bowtie \gamma} \varphi$

 $\tilde{\exists} HyperPTCTL$ is a subclass of HyperPTCTL such that the (top-level) formulas are of the form

parameters. *PTCTL* [BDR08] is a subclass of HyperPTCTL with only one path variable π .⁵ $\exists PTCTL$ [BDR08] is defined analogously.

We extend HyperPTCTL with counters and clocks to constrain the number of occurrences of atomic propositions and to compare the time difference between the occurrences of two atomic proposition σ and path π , $LAST(\sigma_{\pi})$ indicates the time elapsed since the last switching of σ from false to true in π , and $COUNT(\sigma_{\pi})$ indicates the total number of switches of σ from false to true in π . To ensure decidability, we only allow specific forms of constraints. We denote the extended logic as Ext-HyperPTCTL.

Definition 4 (Syntax of Ext-HyperPTCTL). We extend the syntax of HyperPTCTL formulas of the temporal level as follows: $\sigma \in \Sigma$, \mathcal{V} is the set of path variables, $\pi \in \mathcal{V}$, $\bowtie \in \{<, \leq, =, \geq, >\}$, $d, N \in \mathbb{N}$, lt is a linear term over \mathbb{P} , $\Sigma_{COUNT} = \{COUNT(\sigma_{\pi}) \mid \sigma \in \Sigma, \pi \in \mathcal{V}\}$, $cnt_{\geq 0}$ is a non-negative linear term over Σ_{COUNT} (i.e., $cnt_{\geq 0} = \sum_{\sigma \in \Sigma, \pi \in \mathcal{V}} \alpha_{\sigma, \pi} COUNT(\sigma_{\pi})$ for some $\alpha_{\sigma, \pi} \in \mathbb{N}$)⁶, and cnt is a linear term over Σ_{COUNT} (i.e., $cnt = \sum_{\sigma \in \Sigma, \pi \in \mathcal{V}} \alpha_{\sigma, \pi} COUNT(\sigma_{\pi})$ for some $\alpha_{\sigma, \pi} \in \mathbb{Z}$).

$$\varphi ::= \top \mid \sigma_{\pi} \mid LAST(\sigma_{\pi}) - LAST(\sigma_{\pi}) \bowtie lt$$
$$\mid cnt_{\geq 0} \bowtie d \mid (cnt \mod N) \bowtie d \mid \cdots$$

We call $LAST(\sigma_{\pi}) - LAST(\sigma_{\pi}) \bowtie lt, cnt_{\geq 0} \bowtie d$, and $(cnt \mod N) \bowtie d$ as LASTEXPR, COUNTEXPR_{\geq 0}, and COUNTEXPR_{mod}, respectively. We let *Ext-PTCTL* be the subclass of Ext-HyperPTCTL with only one path variable π .

[Drift of clock] Let H be the proposition showing the "high" value of a digital clock. For $p \in \mathbb{P}$, AtMostOneDiff $\equiv (COUNT(H_{\pi_1}) - COUNT(H_{\pi_2})) \mod 4 \in \{0, 1, 3\}$ denotes that the deviation of $COUNT(H_{\pi_1})$ and $COUNT(H_{\pi_2})$ is at most by one, if we keep having AtMostOneDiff in the past, SameCount $\equiv (COUNT(\mathbb{H}_{\pi_1}) - COUNT(\mathbb{H}_{\pi_2})) \mod 4 = 0$ denotes that the number of times the clock became high is identical (mod 4) over two paths; and LargeDeviation $\equiv LAST(\mathbb{H}_{\pi_1}) - LAST(\mathbb{H}_{\pi_2}) \notin [-p, p]$ denotes that the last time the clock became high differs by at least p time units over two paths, i.e., consists in a "large deviation". Then the following Ext-HyperPTCTL formula shows the drift of near periodic clocks of duration at least p time units, globally assuming AtMostOneDiff: $\exists \pi_1, \pi_2$. (AtMostOneDiff) $\mathcal{U}_{\geq 0}$ (SameCount \land LargeDeviation).

Definition 4 (Syntax of Ext-HyperPTCTL). We extend the syntax of HyperPTCTL formulas of the temporal level as follows: $\sigma \in \Sigma$, \mathcal{V} is the set of path tion in Section 5.2.

> [Execution-time opacity] Let Private be the proposition showing the private locations of a (P)TA and Goal be the proposition showing the goal locations. The following Ext-HyperPTCTL formula shows a formulation of opacity focusing on the execution time [And+23], i.e., there are executions of duration p with and without visiting any private locations: $\exists \pi_1, \pi_2. (\neg \operatorname{Goal}_{\pi_1} \land \neg \operatorname{Goal}_{\pi_2}) \mathcal{U}_{=p}$ $(\text{Goal}_{\pi_1} \wedge \text{Goal}_{\pi_2} \wedge COUNT(\text{Private}_{\pi_1}) = 0 \wedge$ $COUNT(Private_{\pi_2}) > 0$). That is, the goal is not reached until, after exactly p time units (which encodes the unknown execution time), the goal is reached for both paths, and one of them did not visit any private location ("COUNT(Private_{π_1}) = 0") while the other one did. Notice that this differs from another style of opacity for TAs in [Cas09].

> [Side-channel timing attack [BPS20]] Let Inv and Idle be the propositions denoting the invocation of a process and the idle state. For $i \in \{1,2\}$, we let SyncInv $\equiv Inv_{\pi_1} = Inv_{\pi_2}$, ImmediateExec_i \equiv Inv_{π_i} \implies $\neg \text{Idle}_{\pi_i},$ $\operatorname{ExecBound}_i \equiv \operatorname{Idle}_{\pi_i}$ $(LAST(Idle_{\pi_i}) \implies$ $\langle p_1 \rangle$, and NearFinish \equiv $LAST(Inv_{\pi_i})$ $(Idle_{\pi_1} = Idle_{\pi_2})$ $(LAST(Idle_{\pi_1}) \implies$ $LAST(Idle_{\pi_2}) \in (-p_2, p_2)$). The following Ext-HyperPTCTL formula shows that the execution time of each process must be similar, which

⁵ Although the original definition in [BDR08] does not use path variables, one can easily check that our definition coincides with the one in [BDR08].

⁶ The restriction of $cnt_{\geq 0}$ is to construct finite observers in Section 5.2. Our implementation accepts any linear term, which is encoded by variables in IMITATOR [And21].

is necessary to prevent side-channel timing attacks: $\forall \pi_1, \pi_2. (\neg \text{SyncInv}) \mathcal{R}_{>0}$ (ImmediateExec₁ \land ImmediateExec₂ \land ExecBound₁ \land ExecBound₂ \land NearFinish). More precisely, for any paths corresponding to two different sequences of process executions, while each pair of processes has been invoked simultaneously, their execution must be within p_1 , and the execution time of each pair of processes must not differ more than p_2 time units.

[Unfairness of schedulers] Let Sub^i and Run^i be the proposition showing the submission **Definition 5** (Path assignments). For path variables and execution of job $i \in$ $\{1,2\}.$ For SyncSub \equiv Sub $_{\pi_1}^1 =$ Sub $_{\pi_2}^2$, SameCount \equiv $(COUNT(\operatorname{Run}_{\pi_1}^1) - COUNT(\operatorname{Run}_{\pi_2}^2)) \mod 4 =$ 0, and Large Deviation $\equiv LA\tilde{S}T(\operatorname{Run}_{\pi_1}^1)$ – $LAST(\operatorname{Run}_{\pi_2}^2) \notin (-5,5)$, the following Ext-HyperPTCTL formula shows unfair scheduling of jobs 1 and 2: $\exists \pi_1, \pi_2$. (SyncSub) $\mathcal{U}_{>0}$ (SameCount \wedge LargeDeviation). That is, given two paths corresponding to two different jobs, if they submit the job at the same time and eventually run, but with a time difference of > 5 time units, then the scheduler is unfair.

observational non-determinism] Robust $\{\operatorname{In}^i$ \in $\{1, 2, \ldots, m\}$ and Let i $\{\operatorname{Out}^i$ $i \in \{1, 2, \ldots, n\}$ be the set of input and output propositions, respectively. SyncIn $\equiv \bigwedge_{i \in \{1,2,\dots,m\}} (\operatorname{In}_{\pi_1}^i = \operatorname{In}_{\pi_2}^i)$ denotes that the inputs in two runs π_1 and π_2 are synchronized, AtMostOneDiff $\equiv \bigwedge_{i \in \{1,2,\dots,n\}} \left(COUNT(\operatorname{Out}_{\pi_1}^i) - \right)$ $COUNT(Out_{\pi_2}^i) \mod 4 \in \{0, 1, 3\}$ denotes that the deviation of the $COUNT(Out_{\pi_1}^i)$ and $COUNT(\operatorname{Out}_{\pi_2}^i)$ is at most one, if we keep having AtMostOneDiff in the past, and LargeDeviation \equiv $\bigvee_{i \in \{1,2,\ldots,n\}} ((COUNT(\operatorname{Out}_{\pi_1}^i)))$ $COUNT(\operatorname{Out}_{\pi_2}^i)) \mod 4 = 0 \wedge LAST(\operatorname{Out}_{\pi_1}^i)$ output proposition that the number of times of such Π , Π' , and d. the proposition became true is identical (mod 4) over two paths but the timing differs at least p Definition 6 (Semantics of HyperPTCTL). Let \mathcal{A}

output timing may deviate more than $p: \exists \pi_1, \pi_2$. $(SyncIn \land AtMostOneDiff) \mathcal{U}_{>0}$ (LargeDeviation).

4.2 Semantics of (Ext-)HyperPTCTL

Before defining the semantics of HyperPTCTL, we formalize the assignments of paths. In addition to the partial function assigning the paths, we use a total preorder to fix the order of the discrete transitions at the same time-point.

 \mathcal{V} and a TA $v(\mathcal{A})$, a path assignment (Π, \leq_{Π}) is a pair of a partial function $\Pi: \mathcal{V} \nrightarrow Paths(v(\mathcal{A}))$ from path variables \mathcal{V} to paths $Paths(v(\mathcal{A}))$ of $v(\mathcal{A})$ and a total preorder \leq_{Π} on $\mathbf{dom}(\Pi) \times \mathbb{N}$ such that for any $\pi, \pi' \in$ **dom**(Π) and $i, j \in \mathbb{N}, i < j$ implies $(\pi, i) \leq_{\Pi} (\pi, j)$ and $(\pi, j) \not \leq_{\Pi} (\pi, i), (\pi, i) \leq_{\Pi} (\pi', j)$ implies $\sum_{k=0}^{i} d_{k}^{\pi} \leq \sum_{k=0}^{j} d_{k}^{\pi'}$, and $\sum_{k=0}^{i} d_{k}^{\pi} < \sum_{k=0}^{j} d_{k}^{\pi'}$ implies $(\pi, i) \leq_{\Pi}$ (π', j) , where d_k^{π} and $d_k^{\pi'}$ are the k-th delay in $\Pi(\pi)$ and $\Pi(\pi')$, respectively.

We let $(\Pi_{\emptyset}, \leq_{\Pi_{\emptyset}})$ be the empty path assignment, i.e., the path assignment satisfying $\mathbf{dom}(\Pi_{\emptyset}) =$ \emptyset . For path assignments $(\Pi, \trianglelefteq_{\Pi})$ and $(\Pi', \trianglelefteq_{\Pi'})$, $(\Pi', \trianglelefteq_{\Pi'})$ is an *extension* of $(\Pi, \trianglelefteq_{\Pi})$ if we have $\mathbf{dom}(\Pi) \subseteq \mathbf{dom}(\Pi')$ and for any $\pi, \pi' \in \mathbf{dom}(\Pi)$ and $i, j \in \mathbb{N}$, we have $(\pi, i) \leq_{\Pi} (\pi', j) \iff (\pi, i) \leq_{\Pi'} (\pi', j)$ and $\Pi(\pi) = \Pi'(\pi)$. For path assignments (Π, \leq_{Π}) and $(\Pi', \trianglelefteq_{\Pi'})$, we let $(\Pi, \trianglelefteq_{\Pi}) \succeq (\Pi', \trianglelefteq_{\Pi'})$ (resp. $(\Pi, \trianglelefteq_{\Pi}) \succ (\Pi', \trianglelefteq_{\Pi'}))$ if $\mathbf{dom}(\Pi) = \mathbf{dom}(\Pi')$ and there is $d \in \mathbb{R}_{\geq 0}$ such that for any $\pi \in \mathbf{dom}(\Pi)$, we have $\Pi(\pi) \succeq \Pi'(\pi)$ (resp. $\Pi(\pi) \succ \Pi'(\pi)$) and $Dur(\Pi(\pi) - \Pi'(\pi)) = d$, and for any $\pi, \pi' \in \mathbf{dom}(\Pi)$ and $i, j \in \mathbb{N}$, we have $(\pi, i) \leq_{\Pi'} (\pi', j) \iff (\pi, i + \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)}) \leq_{\Pi} (\pi', j + \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi)})$, and if $\mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} \geq 1$ holds, $(\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - 1) \leq_{\Pi} (\pi', \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')})$ and $(\pi', \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')}) \not\leq_{\Pi}$ $LAST(\operatorname{Out}_{\pi_2}^i) \notin [-p, p]$ denotes that there is an $(\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - 1)$ also hold. We let $Dur(\Pi - \Pi') = d$ for

time units over two paths. The following Ext- be a PTA over parameters \mathbb{P}_1 ; given a HyperPTCTL HyperPTCTL formula shows robust observational formula over parameters \mathbb{P}_2 , let $\mathbb{P} = \mathbb{P}_1 \cup \mathbb{P}_2$. For a non-determinism assuming AtMostOneDiff, i.e., parameter valuation $v \in (\mathbb{Q}_{>0})^{\mathbb{P}}$ a path assignment even if the inputs are given at the same timing, the (Π, \leq_{Π}) , and a concrete state s of $v(\mathcal{A})$, the satisfaction relation of the temporal level HyperPTCTL formulas is defined as follows:

- $(\Pi, \leq_{\Pi}), s \models_{v, \mathcal{A}} \sigma_{\pi} \text{ if } \pi \in \operatorname{dom}(\Pi) \text{ and } \sigma \in$ $\Lambda(Init(\Pi(\pi)));$
- $(\Pi, \leq_{\Pi}), s \models_{v,\mathcal{A}} \neg \varphi$ if we have $(\Pi, \leq_{\Pi}), s \not\models_{v,\mathcal{A}} \varphi$;
- $(\Pi, \trianglelefteq_{\Pi}), s \models_{v,\mathcal{A}} \varphi_1 \lor \varphi_2$ if $(\Pi, \trianglelefteq_{\Pi}), s \models_{v,\mathcal{A}} \varphi_1$ or $(\Pi, \trianglelefteq_{\Pi}), s \models_{v,\mathcal{A}} \varphi_2$ holds;
- $(\Pi, \leq_{\Pi}), s \models_{v,\mathcal{A}} \exists \pi_1, \pi_2, \dots, \pi_n, \varphi_1 \ \mathcal{U}_{\bowtie \gamma} \ \varphi_2$ if for some extension $(\Pi^1, \trianglelefteq_{\Pi^1})$ of $(\Pi, \trianglelefteq_{\Pi})$ satis- $(\Pi^3, \trianglelefteq_{\Pi^3})$ satisfying $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^3, \trianglelefteq_{\Pi^3}) \succ$ holds.
- $(\Pi, \leq_{\Pi}), s \models_{v,\mathcal{A}} \forall \pi_1, \pi_2, \dots, \pi_n, \varphi_1 \ \mathcal{U}_{\bowtie \gamma} \ \varphi_2$ if for any extension (Π^1, \leq_{Π^1}) of (Π, \leq_{Π}) satisfying $\operatorname{dom}(\Pi^1) = \operatorname{dom}(\Pi) \sqcup \{\pi_1, \pi_2, \dots, \pi_n\}$ and $\Pi^1(\pi_i) \in Paths(v(\mathcal{A}), s)$ for each $i \in$ $\{1, 2, \ldots, n\}$, there is $(\Pi^2, \trianglelefteq_{\Pi^2})$ satisfying $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^2, \trianglelefteq_{\Pi^2}), Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma),$ $(\Pi^2, \trianglelefteq_{\Pi^2}), Init(\Pi^2(\pi_n)) \models_{v,\mathcal{A}} \varphi_2$, and for any $(\Pi^3, \trianglelefteq_{\Pi^3})$ satisfying $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^3, \trianglelefteq_{\Pi^3}) \succ$ $(\Pi^2, \trianglelefteq_{\Pi^2}), \quad (\Pi^3, \trianglelefteq_{\Pi^3}), Init(\Pi^3(\pi_n)) \models_{v,\mathcal{A}} \varphi_1$ holds.

For a PTA \mathcal{A} , a parameter valuation $v \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}}$, and a temporal-level HyperPTCTL formula φ , we write $\mathcal{A} \models_{v} \varphi$ if we have $(\Pi_{\emptyset}, \leq_{\Pi_{\emptyset}}), s_{0} \models_{v,\mathcal{A}} \varphi$, where s_{0} is an initial state of $v(\mathcal{A})$.

For a PTA \mathcal{A} and a parameter valuation $v \in$ $(\mathbb{Q}_{\geq 0})^{\mathbb{P}}$, the satisfaction relation of the top-level HyperPTCTL formulas is defined as follows:

- $\mathcal{A} \models_v p \bowtie lt_{>0}$ if we have $v(p) \bowtie v(lt_{>0})$, where $v(lt_{>0})$ denotes the expression obtained by replacing each p with v(p) in $lt_{>0}$;
- $\mathcal{A} \models_v \neg \psi$ if we have $\mathcal{A} \not\models_v \psi$;
- $\mathcal{A} \models_v \psi_1 \lor \psi_2$ if we have $\mathcal{A} \models_v \psi_1$ or $\mathcal{A} \models_v \psi_2$;

• $\mathcal{A} \models_{v} \tilde{\exists} p \psi$ if there is $v' \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}}$ satisfying v(p') = v'(p') for any $p' \in \mathbb{P} \setminus \{p\}$ and $\mathcal{A} \models_{v'} \psi$.

Consider the formula φ : $\exists p_2(p_2 > p_1 \land \exists \pi_1, \pi_2)$. $(L_{\pi_1} \implies H_{\pi_2})\mathcal{U}_{=p_2}(H_{\pi_1} \land H_{\pi_2})).$ Fix $v(p_1) = 1.8$. For the PTA \mathcal{A} in Fig. 2, we have $\mathcal{A} \models_v \varphi$ with $v(p_2) = 2.0$ and $\Pi^1(\pi_1)$ and $\Pi^1(\pi_2)$ are as follows: in π_1 , we jump from ℓ_0 to ℓ_1 at 1.5 and jump from ℓ_1 to ℓ_0 at 2.0; in π_2 , we jump from ℓ_0 to ℓ_1 at 0.5 and jump from ℓ_1 to ℓ_0 at 1.0.

To define the semantics of Ext-HyperPTCTL, we fying $\operatorname{dom}(\Pi^1) = \operatorname{dom}(\Pi) \sqcup \{\pi_1, \pi_2, \dots, \pi_n\}$ introduce valuations of $COUNT(\sigma_\pi)$ and $LAST(\sigma_\pi)$. and $\Pi^1(\pi_i) \in Paths(v(\mathcal{A}), s)$ for each $i \in A$ counter valuation is a function $\eta: \Sigma \times \mathcal{V} \to \mathbb{N}$. A $\{1, 2, \ldots, n\}$, there is (Π^2, \leq_{Π^2}) satisfying recording valuation is a function $\theta: \Sigma \times \mathcal{V} \to \mathbb{R}_{\geq 0}$. $(\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^2, \leq_{\Pi^2}), Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma), We write \vec{0}_{cnt} and \vec{0}_{rec}$ for the counter and recording $(\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi_n)) \models_{v,\mathcal{A}} \varphi_2$, and for any valuations assigning 0 to all $(\sigma, \pi) \in \Sigma \times \mathcal{V}$, respectively. For a linear term cnt over $\{COUNT(\sigma_{\pi}) \mid$ $(\Pi^2, \trianglelefteq_{\Pi^2}), \quad (\Pi^3, \trianglelefteq_{\Pi^3}), Init(\Pi^3(\pi_n)) \models_{v,\mathcal{A}} \varphi_1 \quad \sigma \in \Sigma, \pi \in \mathcal{V}\}, \text{ we let } \eta(cnt) \text{ be the inequality ob$ tained by replacing $COUNT(\sigma_{\pi})$ with $\eta(\sigma,\pi)$ and $Vars(cnt) = \{\pi \in \mathcal{V} \mid \exists \sigma \in \Sigma, \alpha_{\sigma,\pi} \neq 0\}, \text{ with }$ $cnt = \sum_{\sigma \in \Sigma, \pi \in \mathcal{V}} \alpha_{\sigma, \pi} COUNT(\sigma_{\pi}).$

For paths ρ, ρ' satisfying $\rho \succeq \rho'$, we let $Rising(\sigma, \rho - \rho)$ ρ') be the set of positions s in ρ satisfying $Init(\rho) < \rho'$ $s \leq Init(\rho'), \ \sigma \in \Lambda(s), \ and \ there \ is \ \delta \in \mathbb{T}$ such that for any s' < s, $Dur(s) - Dur(s') < \delta$ implies $\sigma \notin$ $\Lambda(s)$. Notice that $Rising(\sigma, \rho - \rho')$ is finite because $Dur(\rho - \rho')$ is finite and we have no Zeno behavior. For a counter valuation η and path assignments Π, Π' satisfying $\Pi \succeq \Pi'$, $[\eta]_{\Pi - \Pi'}$ is the counter valuation such that for any $(\sigma, \pi) \in \Sigma \times \mathcal{V}, \ [\eta]_{\Pi - \Pi'}(\sigma, \pi) =$ $\eta(\sigma,\pi) + |Rising(\sigma,\Pi(\pi) - \Pi'(\pi))|$ if $\pi \in \mathbf{dom}(\Pi)$ and $[\eta]_{\Pi-\Pi'}(\sigma,\pi) = \eta(\sigma,\pi)$ otherwise. For a recording valuation θ and path assignments Π, Π' satisfying $\Pi \succeq$ $\Pi', \ [\theta]_{\Pi-\Pi'}$ is the recording valuation such that for any $(\sigma, \pi) \in \Sigma \times \mathcal{V}, \ [\theta]_{\Pi - \Pi'}(\sigma, \pi) = Dur(\Pi - \Pi')$ if $\pi \notin \mathbf{dom}(\Pi)$ or $Rising(\sigma, \Pi(\pi) - \Pi'(\pi)) = \emptyset$ and otherwise, $[\theta]_{\Pi-\Pi'}(\sigma,\pi)$ is the duration of $Init(\Pi'(\pi))$ in the suffix of $\Pi(\pi)$ starting from the last position in $Rising(\sigma, \Pi(\pi) - \Pi'(\pi)).$

Definition 7 (Semantics of Ext-HyperPTCTL). Let \mathcal{A} be a PTA over parameters \mathbb{P}_1 ; given an Ext-HyperPTCTL formula over parameters \mathbb{P}_2 , let \mathbb{P} = $\mathbb{P}_1 \cup \mathbb{P}_2$. For a parameter valuation $v \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}}$, a path assignment (Π, \leq_{Π}) , a concrete state s of $v(\mathcal{A})$, and

counter and recording valuations η and θ , the satisfac- For a PTA \mathcal{A} , a parameter valuation $v \in (\mathbb{Q}_{>0})^{\mathbb{P}}$, and tion relation of the temporal level Ext-HyperPTCTL a temporal-level HyperPTCTL formula φ , we write formulas is defined as follows:

- $(\Pi, \leq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}} \sigma_{\pi}$ if $\pi \in \mathbf{dom}(\Pi)$ and $\sigma \in$ $\Lambda(Init(\Pi(\pi)));$
- $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}} LAST(\sigma_{\pi}) LAST(\sigma'_{\pi'}) \bowtie$ *lt* if we have $\pi, \pi' \in \mathbf{dom}(\Pi)$ and $\theta(\sigma, \pi)$ – $\theta(\sigma', \pi') \bowtie v(lt);$
- $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}} cnt_{\geq 0} \bowtie d$ if we have $Vars(cnt_{>0}) \subseteq \mathbf{dom}(\Pi) \text{ and } \eta(cnt_{>0}) \bowtie d;$
- $(\Pi, \leq_{\Pi}), s, \eta, \theta \models_{v,\mathcal{A}} (cnt \mod N) \bowtie d$ if we have $Vars(cnt) \subseteq \mathbf{dom}(\Pi)$ and $(\eta(cnt) \mod N) \bowtie d$;
- $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}}$ $\neg \varphi$ if we have $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \not\models_{v, \mathcal{A}} \varphi;$
- $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}} \varphi_1 \lor \varphi_2$ if we have $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}} \varphi_1 \text{ or } (\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v, \mathcal{A}}$ $\varphi_2;$
- $(\Pi, \leq_{\Pi}), s, \eta, \theta \models_{v,\mathcal{A}} \exists \pi_1, \pi_2, \dots, \pi_n, \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2$ if for some extension $(\Pi^1, \trianglelefteq_{\Pi^1})$ of $(\Pi, \trianglelefteq_{\Pi})$ satisfying $\operatorname{dom}(\Pi^1) = \operatorname{dom}(\Pi) \sqcup \{\pi_1, \pi_2, \dots, \pi_n\}$ and $\Pi^1(\pi_i)$ \in $Paths(v(\mathcal{A}), s)$ for each $i \in \{1, 2, \ldots, n\}$, there is (Π^2, \leq_{Π^2}) satisfying $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^2, \trianglelefteq_{\Pi^2}), Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma),$ $(\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi_n)), [\eta]_{\Pi^1 - \Pi^2}, [\theta]_{\Pi^1 - \Pi^2} \models_{v, \mathcal{A}}$ and for any (Π^3, \leq_{Π^3}) satisfying $\varphi_2,$ $(\Pi^3, \leq_{\Pi^3}), Init(\Pi^3(\pi_n)), [\eta]_{\Pi^1 - \Pi^3}, [\theta]_{\Pi^1 - \Pi^3} \models_{v, \mathcal{A}}$ φ_1 .
- for any extension (Π^1, \leq_{Π^1}) of (Π, \leq_{Π}) satisfying $\operatorname{\mathbf{dom}}(\Pi^1) = \operatorname{\mathbf{dom}}(\Pi) \sqcup \{\pi_1, \pi_2, \dots, \pi_n\}$ and $\Pi^1(\pi_i)$ \in $\varphi_2,$ $\varphi_1.$

 $\mathcal{A} \models_{v} \varphi$ if we have $(\Pi_{\emptyset}, \trianglelefteq_{\Pi_{\emptyset}}), s_{0}, \vec{0}_{\mathrm{cnt}}, \vec{0}_{\mathrm{rec}} \models_{v, \mathcal{A}} \varphi$, where s_0 is an initial state of $v(\mathcal{A})$. The satisfaction relation of the top-level Ext-HyperPTCTL formulas is the same as that of HyperPTCTL.

4.3 Problems

Here, we formalize the problems we consider in this paper. We consider each problem under both continuous-time and discrete-time semantics, i.e., \mathbb{T} is either $\mathbb{R}_{>0}$ or \mathbb{N} . We let \mathbb{P} be the set of parameters shared between the PTA and the (Ext-)HyperPTCTL formula.

(Ext-)HyperPTCTL model checking problem:
INPUT: PTA \mathcal{A} and a top-level (Ext-)HyperPTCTL
formula ψ
PROBLEM: Decide if there is $v \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}}$ satisfying
$\mathcal{A}\models_v \psi$
(
(Ext-)HyperPTCTL parameter synthesis prob-
lem:

INPUT: PTA \mathcal{A} and a top-level (Ext-)HyperPTCTL formula ψ

PROBLEM: Return the set $\{v \in (\mathbb{Q}_{>0})^{\mathbb{P}} \mid \mathcal{A} \models_{v} \psi\}$

The solution to the latter problem can be *effectively* computed whenever its representation is symbolic, and can be represented by decidable formalisms, typically a finite union of polyhedra.

Let ψ be a top-level HyperPTCTL formula with $(\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^3, \leq_{\Pi^3}) \succ (\Pi^2, \leq_{\Pi^2})$, we have no quantifiers over parameters. The *emptiness* of the parameter valuations to have $\mathcal{A} \models_v \psi$ can be checked by model checking of ψ . The universality of the parameter valuations to have $\mathcal{A} \models_v \psi$ can be • $(\Pi, \trianglelefteq_{\Pi}), s, \eta, \theta \models_{v,\mathcal{A}} \forall \pi_1, \pi_2, \dots, \pi_n \cdot \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2$ if checked by model checking of $\neg (\exists p_1 \exists p_2 \dots \exists p_n \neg \psi),$ where $\mathbb{P} = \{p_1, p_2, ..., p_n\}.$

In the rest of this paper, we focus on the nest- $Paths(v(\mathcal{A}), s)$ for each free fragment of HyperPTCTL (e.g., "Nest-Free Hy $i \in \{1, 2, ..., n\}$, there is (Π^2, \leq_{Π^2}) satisfying perPTCTL", "Nest-Free Ext-HyperPTCTL", "Nest- $(\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^2, \leq_{\Pi^2}), Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma),$ Free $\tilde{\exists}$ HyperPTCTL"...), i.e., fragments with no $(\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi_n)), [\eta]_{\Pi^1-\Pi^2}, [\theta]_{\Pi^1-\Pi^2} \models_{v,\mathcal{A}}$ nesting of temporal operators. See Definition 8 for and for any (Π^3, \leq_{Π^3}) satisfying its formal definition. Observe that all our Section 4.1 $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^3, \trianglelefteq_{\Pi^3}) \succ (\Pi^2, \trianglelefteq_{\Pi^2})$, we have fit into this nest-free fragment. The following is the $(\Pi^3, \leq_{\Pi^3}), Init(\Pi^3(\pi_n)), [\eta]_{\Pi^1-\Pi^3}, [\theta]_{\Pi^1-\Pi^3} \models_{v,\mathcal{A}}$ definition of Nest-Free HyperPTCTL. The other fragments are defined similarly.

Definition 8 (Syntax of Nest-Free HyperPTCTL). $reduce^n(\sum_{\sigma \in \Sigma, i \in \{1, 2, ..., n\}} \alpha_{\sigma, \pi_i} COUNT(\sigma_{\pi_i}))$ For atomic propositions Σ and parameters \mathbb{P} , the syntax of Nest-Free HyperPTCTL formulas of the Boolean level \mathcal{B} , the temporal level φ , and the top level ψ are defined as follows, where $\sigma \in \Sigma$, $\pi, \pi_1, \pi_2, \ldots, \pi_n \in \mathcal{V}, \ \gamma \in \mathbb{P} \cup \mathbb{N}, \ p \in \mathbb{P}, \ \bowtie \in \{ < \} \}$ $\leq =, \geq >$, and $lt_{>0}$ is a non-negative linear term over \mathbb{P} :

 $\mathcal{B} ::= \top \mid \sigma_{\pi} \mid \neg \mathcal{B} \mid \mathcal{B} \lor \mathcal{B}$ $\varphi ::= \exists \pi_1, \pi_2, \dots, \pi_n. \mathcal{B}\mathcal{U}_{\bowtie\gamma}\mathcal{B} \mid \forall \pi_1, \pi_2, \dots, \pi_n. \mathcal{B}\mathcal{U}_{\bowtie\gamma}\mathcal{B} \bullet reduce^n((cnt \bmod N) \bowtie d) = (reduce^n(cnt) \bmod d)$ $\psi ::= \varphi \mid p \bowtie lt_{\geq 0} \mid \neg \psi \mid \psi \lor \psi \mid \tilde{\exists} p \psi$

5 **Reduction of Nest-Free Ext-HyperPTCTL** synthesis to **PTCTL** synthesis

5.1 Reduction of path variables via self-composition of PTAs

We show that model checking and parameter synthesis of nest-free (Ext-)HyperPTCTL is reducible to ones of (Ext-)PTCTL by self-composition of PTAs. For a PTA $\mathcal{A} = (\Sigma, L, L_0, \mathbb{C}, \mathbb{P}, I, E, \Lambda)$ and $n \in$ $\mathbb{N}_{>0}$, we let $\mathcal{A}^n = \mathcal{A} || \mathcal{A} || \cdots || \mathcal{A}$, and for each n times $i \in \{1, 2, \ldots, n\}$ and $\sigma \in \Sigma$ (resp. $c \in \mathbb{C}$), we denote the corresponding atomic proposition in Σ^n (resp. clock in \mathbb{C}^n) of the *i*-th component as σ^i (resp. c^i), where Σ^n and \mathbb{C}^n are the sets of atomic propositions and clocks in \mathcal{A}^n . We generalize the projection of paths to such *n*-compositions, i.e., for a path ρ of \mathcal{A}^n , we let $\rho|_i$ be the projection of ρ to the *i*-th component.

We define an auxiliary function $reduce^n$ to "compose" the atomic propositions in (Ext-)HyperPTCTL formulas.

Definition 9 (reduceⁿ). For $n \in \mathbb{N}_{>0}$, the $reduce^n$ function from nest-free level Ext-HyperPTCTL formulas with atomic *level* propositions Σ to nest-free temporal-level Ext- *las* φ_{\exists} PTCTL formulas Σ^n

= $\sum_{\sigma^i \in \Sigma^n} \alpha_{\sigma^i,\pi} COUNT(\sigma^i_{\pi})$:

- $reduce^n(\top) = \top$
- $reduce^n(\sigma_{\pi_i}) = \sigma^i_{\pi}$
- $reduce^n(LAST(\sigma_{\pi_i}) LAST(\sigma_{\pi_j}) \bowtie lt) = LAST(\sigma^i_{\pi}) LAST(\sigma^j_{\pi}) \bowtie lt$
- $reduce^n(cnt_{>0} \bowtie d) = reduce^n(cnt_{>0}) \bowtie d$
- $N) \bowtie d$
- $reduce^n(\neg \varphi) = \neg reduce^n(\varphi)$
- $reduce^{n}(\varphi_{1} \lor \varphi_{2}) = reduce^{n}(\varphi_{1}) \lor reduce^{n}(\varphi_{2})$
- $reduce^n(\exists \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \ \mathcal{U}_{\bowtie \gamma} \ \varphi_2) =$ $\exists \pi$. $reduce^{n}(\varphi_{1}) \mathcal{U}_{\bowtie\gamma} reduce^{n}(\varphi_{2})$
- $reduce^n(\forall \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \quad \mathcal{U}_{\bowtie \gamma} \quad \varphi_2)$ = $\forall \pi. reduce^n(\varphi_1) \mathcal{U}_{\bowtie\gamma} reduce^n(\varphi_2)$

We naturally extend $reduce^n$ to top-level Nest-Free Ext-HyperPTCTL formulas.

Algorithm 1 outlines our reduction of the synthesis problem. The reduction of model checking is similar. Our reduction is inductive on the structure of the Ext-HyperPTCTL formula ψ . Since the path assignment (Π, \leq_{Π}) is empty, for atomic formulas, ψ is satisfied (line 3) or violated (line 4) independent of \mathcal{A} and v. For Boolean cases, we obtain the result from the result of the reduction of the immediate subformula(s) (lines 7 and 9). For the temporal operators, we use the result of the synthesis for the composed PTA \mathcal{A}^n and the reduced formula $reduce^{n}(\psi)$ (line 11). For the remaining cases, the result is independent of \mathcal{A} (line 13) or obtained by un-constraining the result for p (line 16).

The correctness of Algorithm 1 is immediate from the following theorem.

temporal- Theorem 10. For a PTA A, a temporal-*Ext-HyperPTCTL* Nest-Free formu- $\exists \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \quad \mathcal{U}_{\bowtie \gamma} \quad \varphi_2 \quad and$ =with atomic propositions $\varphi_{\forall} = \forall \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \ \mathcal{U}_{\bowtie \gamma} \ \varphi_2$, and a parameis inductively defined as follows, with ter valuation v, we have $\mathcal{A} \models_v \varphi_{\exists}$ (resp. $\mathcal{A} \models_v \varphi_{\forall}$)

Algorithm 1: Outline of our reduction of Nest-Free Ext-HyperPTCTL synthesis to nestfree Ext-PTCTL synthesis. **Input:** A PTA \mathcal{A} and a Nest-Free Ext-HyperPTCTL formula ψ **Output:** The set $\{v \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}} \mid \mathcal{A} \models_{v} \psi\}$ 1 def reduceSynth(\mathcal{A}, ψ): 2 switch ψ do case \top do return $(\mathbb{Q}_{\geq 0})^{\mathbb{P}}$ 3 case σ_{π_i} or $LAST(\sigma_{\pi_i}) - LAST(\sigma_{\pi_i})$ 4 or $cnt_{\geq 0} \bowtie d$ or $(cnt \mod N) \bowtie d$ do // ψ does not hold for empty path assignments return Ø $\mathbf{5}$ case $\neg \psi$ do 6 **return** $(\mathbb{Q}_{>0})^{\mathbb{P}} \setminus \text{reduceSynth}(\mathcal{A}, \psi)$ 7 case $\psi_1 \vee \psi_2$ do 8 return reduceSynth(\mathcal{A}, ψ_1) \cup 9 $reduceSynth(\mathcal{A}, \psi_2)$ case $\exists \pi_1, \pi_2, \ldots, \pi_n. \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2$ or 10 $\forall \pi_1, \pi_2, \ldots, \pi_n. \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2 \mathbf{do}$ // Use nest-free Ext-PTCTL synthesis \mathbf{return} 11 synthesisExtPTCTL($\mathcal{A}^n, reduce^n(\psi)$) case $p \bowtie lt_{>0}$ do 12 return 13 $\{v \in (\mathbb{Q}_{>0})^{\mathbb{P}} \mid v(p) \bowtie v(lt_{>0})\}$ case $\exists p \psi$ do 14 $pre \leftarrow reduceSynth(\mathcal{A}, \psi)$ 1516 return $\{v \in (\mathbb{Q}_{>0})^{\mathbb{P}} \mid \exists v' \in$ pre. $\forall p' \in \mathbb{P} \setminus \{p\}. v(p') = v'(p')\}$

if and only if we have $\mathcal{A}^n \models_v reduce^n(\varphi_{\exists})$ (resp. $\mathcal{A}^n \models_v reduce^n(\varphi_{\forall})$).

Proof (sketch). Since the other cases are similar, we only outline the proof of $\mathcal{A} \models_v \varphi_{\exists} \implies \mathcal{A}^n \models_v$ reduceⁿ(φ_{\exists}). See Appendix A.1 for the details. Suppose $\mathcal{A} \models_v \varphi_{\exists}$ holds. By the semantics of Ext-HyperPTCTL, for some extension ($\Pi^1, \trianglelefteq_{\Pi^1}$) of ($\Pi_{\emptyset}, \trianglelefteq_{\Pi_{\emptyset}}$) satisfying **dom**(Π) = { $\pi_1, \pi_2, \ldots, \pi_n$ } and $\Pi^1(\pi_i) \in Paths(v(\mathcal{A}))$ for each $i \in \{1, 2, \ldots, n\}$, there is a suffix ($\Pi^2, \trianglelefteq_{\Pi^2}$) of ($\Pi^1, \trianglelefteq_{\Pi^1}$) such that we have $Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma), \varphi_2$ holds at ($\Pi^2, \trianglelefteq_{\Pi^2}$), and for any ($\Pi^3, \trianglelefteq_{\Pi^3}$) between ($\Pi^1, \trianglelefteq_{\Pi^1}$) and ($\Pi^2, \trianglelefteq_{\Pi^2}$), φ_1 holds at ($\Pi^3, \trianglelefteq_{\Pi^3}$). Since there are paths ρ and ρ' of $v(\mathcal{A}^n)$ such that

- 1. ρ' is a suffix of ρ and
- 2. for each $i \in \{1, 2, ..., n\}$, we have $\Pi^{1}(\pi_{i}) = \rho|_{i}$ and $\Pi^{2}(\pi_{i}) = \rho'|_{i}$,

we can construct path assignments $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1})$ and $(\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2})$ mapping π to them. Notice that $reduce^n(\varphi_2)$ holds at such $(\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2})$. Moreover, for any path assignment $(\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3})$ between $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1})$ and $(\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2})$, since there is a corresponding path assignment $(\Pi^3, \trianglelefteq_{\Pi^3})$ between $(\Pi^1, \trianglelefteq_{\Pi^1})$ and $(\Pi^2, \trianglelefteq_{\Pi^2})$, $reduce^n(\varphi_1)$ holds at $(\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3})$ Therefore, we have $\mathcal{A}^n \models_v reduce^n(\varphi_3)$.

5.2 Observers for extended predicates

We show that the satisfaction of the additional predicates $LAST(\sigma_{\pi}^{1}) - LAST(\sigma_{\pi}^{2}) \bowtie lt$, $cnt_{\geq 0} \bowtie d$, and $(cnt \mod N) \bowtie d$ in Ext-PTCTL are observable by a PTA, and thus, Ext-PTCTL model checking and synthesis are reducible to PTCTL model checking and synthesis, respectively. Since we consider Ext-PTCTL formulas, we assume $\mathcal{V} = \{\pi\}$ without loss of generality.

For LASTEXPR $LAST(\sigma_{\pi}^{1}) - LAST(\sigma_{\pi}^{2}) \bowtie lt$, since the truth value of $LAST(\sigma_{\pi}^{1}) - LAST(\sigma_{\pi}^{2}) \bowtie lt$ changes only when the truth value of σ_{π}^{1} or σ_{π}^{2} changes from \perp to \top , we can construct an observer by "reevaluating" $LAST(\sigma_{\pi}^{1}) - LAST(\sigma_{\pi}^{2}) \bowtie lt$ when σ^{1} or σ^{2} changes from false to true. Additionally, we use rameter valuations.

is monotonically increasing, we can abstract the pre- PTA $\mathcal{O}_{\varphi} = (\mathcal{P}(\Sigma \cup \{\varphi\}), \mathcal{P}(\Sigma) \times \{0, 1, \dots, N - \varphi\})$ cise value once its value is sufficiently large. There- $1\}^{\Sigma}, L_0, \emptyset, \emptyset, I, E, \Lambda)$, where: $L_0 = \mathcal{P}(\Sigma) \times \{0\}^{\Sigma}$, fore, we can encode the counted value by finite loca- $I(\ell) = \top$ for any $\ell \in L, \Lambda$ is such that tions.

value of $COUNT(\sigma_{\pi})$ is cycling back at $N \in \mathbb{N}$, we can also encode the counted value modulo N by finite locations. Observers were studied in [Ace+03; such that $\tilde{\eta}[pr' \setminus pr + = 1](\sigma) = \tilde{\eta}(\sigma)$ for $\sigma \notin pr' \setminus pr$, And13], and we define them as follows.

Definition 11 (observers for LASTEXPR). Let σ^1, σ^2 $\in \Sigma, \ \bowtie \in \{<, \leq, =, \geq, >\}, \ \text{and} \ lt$ be a linear term over \mathbb{P} . The observer for $\varphi = LAST(\sigma_{\pi}^1) - LAST(\sigma_{\pi}^2) \bowtie lt$ is a PTA $\mathcal{O}_{\varphi} = (L, L, L_0, \{c_{\sigma^1}, c_{\sigma^2}\}, \mathbb{P}, I, E, \Lambda), \text{ where: } L =$ $\mathcal{P}(\{\sigma^1, \sigma^2, \varphi\}) \times \{\top, \bot\}, L_0 \text{ is } L_0 = \{(pr, b) \in L \mid$ $b = \bot$, I is such that $I(\ell) = \top$ for any $\ell \notin L_0$, and for $\ell = (pr, \perp) \in L_0$, $I(\ell)$ is $0 \bowtie lt$ if $\varphi \in pr$ and otherwise, $I(\ell)$ is $\neg(0 \bowtie lt)$, Λ is the identity function, and $E = \{((pr, b), \top, \emptyset, (pr', \top)) \mid pr' \}$ ç $pr, \varphi \in pr \cap pr' \text{ or } \varphi \notin pr \cup pr' \} \cup \{((pr, b), (c_{\sigma^1}))\}$ $c_{\sigma^2} \bowtie lt)[\mathbb{C}_{\Sigma_{\text{rise}}} \coloneqq 0], \mathbb{C}_{\Sigma_{\text{rise}}}, (pr' \cup \{\varphi\}, \top)) \mid pr' \subseteq$ $\{\sigma^1, \sigma^2\}, \Sigma_{\text{rise}} = pr' \setminus pr, \Sigma_{\text{rise}} \neq \emptyset \} \cup \{(pr, b), \neg (c_{\sigma^1} - c_{\sigma^1})\}$ $c_{\sigma^2} \bowtie lt)[\mathbb{C}_{\Sigma_{\mathrm{rise}}} \coloneqq 0], \mathbb{C}_{\Sigma_{\mathrm{rise}}}, (pr', \top)) \mid pr' \subseteq$ $\{\sigma^1, \sigma^2\}, \Sigma_{\text{rise}} = pr' \setminus pr, \Sigma_{\text{rise}} \neq \emptyset\}, \text{ where } \mathbb{C}_{\Sigma_{\text{rise}}} =$ $\{c_{\sigma^i} \mid \sigma^i \in \Sigma_{\text{rise}}\}$ and $(c_{\sigma^1} - c_{\sigma^2} \bowtie lt)[\mathbb{C}_{\Sigma_{\text{rise}}} \coloneqq 0]$ is $-c_{\sigma^2} \bowtie lt \text{ if } \mathbb{C}_{\Sigma_{\text{rise}}} = \{c_{\sigma^1}\}, c_{\sigma^1} \bowtie lt \text{ if } \mathbb{C}_{\Sigma_{\text{rise}}} = \{c_{\sigma^2}\},$ and $0 \bowtie lt$ if $\mathbb{C}_{\Sigma_{\text{rise}}} = \{c_{\sigma^1}, c_{\sigma^2}\}.$

 $cnt_{>0} = \sum_{\sigma \in \Sigma} \alpha_{\sigma,\pi} COUNT(\sigma_{\pi})$ be a non-negative linear term, i.e., $\alpha_{\sigma,\pi} \in \mathbb{N}$. The observer for $\varphi =$ $cnt_{\geq 0} \bowtie d$ is a PTA $\mathcal{O}_{\varphi} = (\mathcal{P}(\Sigma \cup \{\varphi\}), \mathcal{P}(\Sigma) \times \mathcal{O}_{\varphi})$ $\Sigma, \tilde{\eta} \in \{0, 1, \dots, d, d+1\}^{\Sigma}\}$, where $\tilde{\eta}[pr' \setminus pr += 1]$ is $(\ell, \nu) = Init(\Pi'(\pi))$. such that $v[pr' \setminus pr + = 1](\sigma) = v(\sigma)$ for $\sigma \notin pr' \setminus pr$, For $\varphi = LAST(\sigma_{\pi}^{1}) - LAST(\sigma_{\pi}^{2}) \bowtie lt$, by the $\tilde{\eta}[pr' \setminus pr += 1](\sigma) = \tilde{\eta}(\sigma) + 1$ if $\sigma \in pr' \setminus pr$ and construction of \mathcal{O}_{φ} , we have $\nu(\sigma^1) = \theta(\sigma^1)$ and

invariants so that the initial states depend on the pa- Definition 13 (observers for COUNTEXPR_{mod}). Let $cnt = \sum_{\sigma \in \Sigma} \alpha_{\sigma,\pi} COUNT(\sigma_{\pi})$ be a linear term. For COUNTEXPR>0 $cnt_{>0} \bowtie d$, since $COUNT(\sigma_{\pi})$ The observer for $\varphi = (cnt \mod N) \bowtie d$ is a $\Lambda((pr, \tilde{\eta})) = pr \cup \{\varphi\}$ if $\sum_{\sigma \in \Sigma} \alpha_{\sigma, \pi} \tilde{\eta}(\sigma) \mod N \bowtie$ For COUNTEXPR_{mod} (*cnt* mod N) $\bowtie d$, since the d holds and $\Lambda((pr, \tilde{\eta})) = pr$ otherwise, and E = $\{((pr,\tilde{\eta}),\top,\emptyset,(pr',\tilde{\eta}[pr' \setminus pr += 1])) \mid pr,pr' \subseteq$ $\Sigma, \tilde{\eta} \in \{0, 1, \dots, N-1\}^{\Sigma}\}$, where $\tilde{\eta}[pr' \setminus pr += 1]$ is $\tilde{\eta}[pr' \setminus pr += 1](\sigma) = \tilde{\eta}(\sigma) + 1$ if $\sigma \in pr' \setminus pr$ and $\tilde{\eta}(\sigma) < N-1$, and $\tilde{\eta}[pr' \setminus pr + = 1](\sigma) = 0$, otherwise.

> The observers semantically capture the original expressions intuitively because c_{σ^1} and c_{σ^2} correspond to $LAST(\sigma_{\pi}^1)$ and $LAST(\sigma_{\pi}^2)$, and $\tilde{\eta}$ is a sound abstraction of $[\vec{0}_{cnt}]_{\Pi-\Pi'}$.

> Lemma 14 (correctness of the observers). For each $\sigma \in \Sigma$, we let $\alpha_{\sigma} \in \mathbb{N}$ and $\alpha'_{\sigma} \in \mathbb{Z}$. Let $N \in \mathbb{N}, \sigma^1, \sigma^2 \in \Sigma, \bowtie \in \{<, \leq, =, \geq$,>, $d \in \mathbb{N}$, and lt be a linear term over \mathbb{P} . Let φ be one of the following: $LAST(\sigma_{\pi}^{1})$ – $LAST(\sigma_{\pi}^2) \bowtie lt, \sum_{\sigma \in \Sigma} \alpha_{\sigma} COUNT(\sigma_{\pi}) \bowtie d, or$ $(\sum_{\sigma \in \Sigma} \alpha'_{\sigma} COUNT(\sigma_{\pi}) \mod N) \bowtie d$. Let v be a valuation over \mathbb{P} , (Π, \leq_{Π}) be a path assignment satisfying dom(Π) = { π } and $\Pi(\pi) \in Paths(v(\mathcal{O}_{\omega}))$. For any $(\Pi', \trianglelefteq_{\Pi'})$ satisfying $(\Pi, \trianglelefteq_{\Pi}) \succeq (\Pi', \trianglelefteq_{\Pi'})$, we have $\Pi', Init(\Pi'(\pi)), [\vec{0}_{cnt}]_{\Pi-\Pi'}, [\vec{0}_{rec}]_{\Pi-\Pi'} \models_{v,\mathcal{O}_{\omega}} \varphi \text{ if and}$ only if we have $\varphi \in \Lambda(Init(\Pi'(\pi)))$.

Proof (sketch). Let $(\Pi, \trianglelefteq_{\Pi})$ and $(\Pi', \trianglelefteq_{\Pi'})$ be path **Definition 12** (observers for COUNTEXPR ≥ 0). Let assignments satisfying $\mathbf{dom}(\Pi) = \mathbf{dom}(\Pi') = \{\pi\}$, $\Pi(\pi) \in Paths(v(\mathcal{O}_{\varphi})), \text{ and } (\Pi, \trianglelefteq_{\Pi}) \succeq (\Pi', \trianglelefteq_{\Pi'}).$ Let $\eta(\sigma) = |Rising(\sigma, \Pi(\pi) - \Pi'(\pi))|$ and let $\theta \colon \Sigma \to$ $\mathbb{R}_{>0}$ be such that $\theta(\sigma) = Dur(\Pi(\pi) - \Pi'(\pi))$ if $\{0, \overline{1}, \dots, d, d+1\}^{\Sigma}, L_0, \emptyset, \emptyset, I, E, \Lambda\}$, where: $L_0 = Rising(\sigma, \Pi(\pi) - \Pi'(\pi)) = \emptyset$ and otherwise, $\theta(\sigma)$ is $\mathcal{P}(\Sigma) \times \{0\}^{\Sigma}$, $I(\ell) = \top$ for any $\ell \in L$, Λ is such the duration of $Init(\Pi'(\pi))$ in the suffix of $\Pi(\pi)$ startthat $\Lambda((pr, \tilde{\eta})) = pr \cup \{\varphi\}$ if $\sum_{\sigma \in \Sigma} \alpha_{\sigma, \pi} \tilde{\eta}(\sigma) \bowtie d$ ing from the last position in $Rising(\sigma, \Pi(\pi) - \Pi'(\pi))$. holds and $\Lambda((pr, \tilde{\eta})) = pr$ otherwise, and E = Notice that, from their definition, η and θ corre- $\{((pr, \tilde{\eta}), \top, \emptyset, (pr', \tilde{\eta}[pr' \setminus pr += 1])) \mid pr, pr' \subseteq \text{spond to } [\vec{0}_{cnt}]_{\Pi-\Pi'} \text{ and } [\vec{0}_{rec}]_{\Pi-\Pi'}, \text{ respectively. Let} \}$

 $\tilde{\eta}(\sigma) < d$, and $\tilde{\eta}[pr' \setminus pr + = 1](\sigma) = d + 1$, otherwise. $\nu(\sigma^2) = \theta(\sigma^2)$. Moreover, by the definition of Λ , we have $\nu(\sigma^1) - \nu(\sigma^2) \bowtie lt$ \iff $\varphi \in$

 $\Lambda(\ell).$ $\Pi', Init(\Pi'(\pi)), [\vec{0}_{cnt}]_{\Pi - \Pi'}, [\vec{0}_{rec}]_{\Pi - \Pi'} \models_{v, \mathcal{O}_{\varphi}} \varphi \iff if and only if \mathcal{A} \times \mathcal{O}_{\psi} \models_{v} \psi_{noext}.$ $\varphi \in \Lambda(Init(\Pi'(\pi)))$ holds.

For $\varphi = \sum_{\sigma \in \Sigma} \alpha_{\sigma} COUNT(\sigma_{\pi}) \bowtie d$, let $\tilde{\eta}$ be the second element of ℓ . From the construction of \mathcal{O}_{φ} , for any $\sigma \in \Sigma$, we have $\eta(\sigma) = \tilde{\eta}(\sigma)$ if $\eta(\sigma) \leq d$, and otherwise, $\tilde{\eta}(\sigma) = d + 1$. Therefore, if $\eta(\sigma) \leq d$ holds for any $\sigma \in \Sigma$, we have $\sum_{\sigma \in \Sigma} \alpha_{\sigma} \eta(\sigma) \bowtie d \iff$ $\sum_{\sigma \in \Sigma} \alpha_{\sigma} \tilde{\eta}(\sigma) \bowtie d$. If $\eta(\sigma) > d$ holds for some $\sigma \in \Sigma$, since we have $\alpha_{\sigma} \in \mathbb{N}$ for any $\sigma \in \Sigma$, we have $\sum_{\sigma \in \Sigma} \alpha_{\sigma} \eta(\sigma) > d$. Thus, $\sum_{\sigma \in \Sigma} \alpha_{\sigma} \eta(\sigma) \bowtie d$ $d \iff \sum_{\sigma \in \Sigma} \alpha_{\sigma} \tilde{\eta}(\sigma) \bowtie d$ holds. Moreover, by definition of Λ , we have $\sum_{\sigma \in \Sigma} \alpha_{\sigma} \eta(\sigma) \bowtie d \iff \varphi \in$ $\Lambda(Init(\Pi'(\pi)))$. By the semantics of Ext-PTCTL, we have $\Pi', Init(\Pi'(\pi)), [\vec{0}_{cnt}]_{\Pi-\Pi'}, [\vec{0}_{rec}]_{\Pi-\Pi'} \models_{v,\mathcal{O}_{\varphi}}$ $\varphi \iff \varphi \in \Lambda(Init(\Pi'(\pi))).$

For $\varphi = (\sum_{\sigma \in \Sigma} \alpha'_{\sigma} COUNT(\sigma_{\pi}) \mod N) \bowtie d$, let $\tilde{\eta}$ be the second element of ℓ . From the construction of \mathcal{O}_{ω} , for any $\sigma \in \Sigma$, we have $\eta(\sigma) = \tilde{\eta}(\sigma) \mod N$. Therefore, we have $\sum_{\sigma \in \Sigma} \alpha'_{\sigma} \eta(\sigma) \mod N \bowtie d \iff$ $\sum_{\sigma \in \Sigma} \alpha'_{\sigma} \tilde{\eta}(\sigma) \mod N \bowtie d.$ By definition of Λ , we have $\sum_{\sigma \in \Sigma} \alpha'_{\sigma} \eta(\sigma) \mod N \bowtie d \iff \varphi \in \Lambda(Init(\Pi'(\pi)))$. By the semantics of Ext-PTCTL, we have Π' , $Init(\Pi'(\pi)), [\vec{0}_{cnt}]_{\Pi-\Pi'}, [\vec{0}_{rec}]_{\Pi-\Pi'} \models_{v, \mathcal{O}_{\varphi}} \varphi$ if and only if $\varphi \in \Lambda(Init(\Pi'(\pi)))$ holds.

For an Ext-PTCTL formula ψ , we let \mathcal{O}_{ψ} be the PTA $\mathcal{O}_{\psi} = \bigotimes_{ext \in Ext(\psi)} \mathcal{O}_{ext}$, where $Ext(\psi)$ is the set of LASTEXPR, COUNTEXPR $>_0$, and COUNTEXPR_{mod} in ψ . For an Ext-PTCTL formula ψ , we let ψ_{noext} be the PTCTL formula with the same syntax but having $Ext(\psi)$ as additional atomic propositions. The following shows that the model checking and synthesis for Ext-PTCTL formulas are reducible to those for PTCTL formulas. Intuitively, Theorem 15 holds because

- 1. since \mathcal{O}_{ψ} is complete and by Lemma 14, for any path of \mathcal{A} , there is a corresponding path of $\mathcal{A} \times$ \mathcal{O}_{ψ} capturing the semantics of $\operatorname{Ext}(\psi)$, and
- 2. for any path of $\mathcal{A} \times \mathcal{O}_{\psi}$, its projection to \mathcal{A} and \mathcal{O}_{ψ} captures the behavior of \mathcal{A} and $\operatorname{Ext}(\psi)$, respectively.

For a PTA \mathcal{A} , a parameter valuation $v \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}}$, and $\exists \pi_1, \pi_2, \Diamond_{\geq 0}$ (SameCount' \land LargeDeviation),

Thus, by the semantics of Ext-PTCTL, a top-level Ext-PTCTL formula ψ , we have $\mathcal{A} \models_v \psi$

Proof (sketch). Since the other cases are similar, we only outline the proof of $\mathcal{A} \models_v \varphi_{\exists} \implies \mathcal{A} \times \mathcal{O}_{\psi} \models_v$ $\varphi_{\exists \text{noext}}$, where $\varphi_{\exists} = \exists \pi. \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2$. Moreover, since we have $\mathcal{V} = \{\pi\}$, we discuss it based on paths rather than path assignments for simplicity. See Appendix A.2 for a full and more formal proof. Suppose $\mathcal{A} \models_v \varphi_{\exists}$ holds. By the semantics of ExtPTCTL, there is a path ρ_1 of $v(\mathcal{A})$ and a suffix ρ_2 of ρ_1 such that $Dur(\rho_1 - \rho_2) \bowtie v(\gamma)$, φ_2 holds at ρ_2 , and φ_1 holds at any position between ρ_1 and ρ_2 . Since the observer \mathcal{O}_{ψ} is complete, there is a path ρ'_1 of $v(\mathcal{A} \times \mathcal{O}_{\psi})$ satisfying $\rho_1|_{v(\mathcal{A})} = \rho'_1$. Moreover, by taking a suitable suffix of ρ'_1 , there is a path ρ'_2 of $v(\mathcal{A} \times \mathcal{O}_{\psi})$ satisfying $\rho'_2|_{v(\mathcal{A})} = \rho_2$. By Lemma 14, φ_{2noext} holds at ρ'_2 . For any position between ρ'_1 and $\rho_2',$ since there is a corresponding position between ρ_1 and $\rho_2,\,\varphi_{1\,\mathrm{noext}}$ holds at that position. Therefore, we have $\mathcal{A} \times \mathcal{O}_{\psi} \models_{v} \varphi_{\exists \text{noext}}$.

5.3 Worked example

Here, we present an illustrative example of our Ext-HyperPTCTL synthesis semi-algorithm. Consider again the PTA \mathcal{A} in Fig. 2. Let ψ be the Nest-Free Ext-HyperPTCTL formula in Section 4.1.

First, we reduce Nest-Free Ext-HyperPTCTL model checking to Nest-Free Ext-PTCTL model checking via self-composition (Section 5.1). Since ψ contains two path variables π_1 and π_2 , we take the self-composition $\mathcal{A} \parallel \mathcal{A}$ of \mathcal{A} (Fig. 3). The corresponding Nest-Free Ext-PTCTL formula is $reduce^{2}(\psi) = \exists \pi. \varphi_{1}' \ \mathcal{U}_{\geq 0} \ (\varphi_{2}' \land \varphi_{3}'), \text{ where } \varphi_{1}' =$ $reduce^2$ (AtMostOneDiff), $\varphi'_2 = reduce^2$ (SameCount), $\varphi'_3 = reduce^2$ (LargeDeviation). Then, we construct the observers $\mathcal{O}_{\varphi'_1}$, $\mathcal{O}_{\varphi'_2}$, and $\mathcal{O}_{\varphi'_3}$ following Definitions 11 and 13. Figs. 4 and 5 show a part of $\mathcal{O}_{\varphi'_2}$ and $\mathcal{O}_{\varphi'_3}$. Finally, we apply PTCTL synthesis to $(\mathcal{A} \mid\mid \mathcal{A}) \times \mathcal{O}_{\varphi'_1} \times \mathcal{O}_{\varphi'_2} \times \mathcal{O}_{\varphi'_3}$ with $reduce^2(\psi)$. In this case, the synthesized parameter constraint is as follows: $2 \times p_1 > p_2 \wedge 3 \times p_1 + 3 >$ $2 \times p_2 \wedge p_1 + 3 > p_2 \wedge p_1$. We remark that our **Theorem 15** (correctness of the reduction with \mathcal{O}_{ψ}). implementation supports more general formulas, e.g., with





Fig. 5: A part of the observer of $\varphi'_3 = LAST(\mathbb{H}^1_{\pi}) - LAST(\mathbb{H}^2_{\pi}) \notin [-p_2, p_2]$. Most of the edges from initial locations are omitted for simplicity. The initial satisfaction of φ'_3 is conditioned with the invariant.

SameCount'
$$\equiv COUNT(H_{\pi_1}) = COUNT(H_{\pi_2}).$$

6 Decidable subclasses for model checking and synthesis

The model checking problem (and the synthesis counterpart) against general PTAs is trivially undecidable, even for the nest-free existential fragment.

Proposition 16. Model checking PTAs against a Nest-Free $\exists HyperPTCTL$ formula is undecidable.

Proof. The Nest-Free **HyperPTCTL** formula " $\exists \pi. \Diamond_{>0} \sigma$ " is equivalent to the TCTL formula $\exists \Diamond \sigma$ denoting reachability. Reachability-emptiness is known to be undecidable for PTAs [AHV93], which gives the result.

either the model or the formula for which decidability opacity in Section 4.1 is in this class. can be achieved, which we do in the following.

6.1 Non-parametric model against parametric formula

We consider here non-parametric TAs against a restriction of Nest-Free Ext-HyperPTCTL defined as follows:

- 1. parameters cannot be used in LAST, i.e., their syntax is restricted to $LAST(\sigma_{\pi}) - LAST(\sigma_{\pi}) \bowtie$ n, and
- 2. parameters are integer-valued.

(See formal definition in Definition 31 in Appendix B.1.) Put it differently, parameters cannot be used in the extended syntax (the constructs that are turned into observers during our transformation in Section 5.2); we insist that parameters can be used anywhere else in the formula. Let Nest-Free RPExt-HyperPTCTL denote this class (with "RP" denot-This negative result leads us to exhibit subclasses of ing a restricted use of parameters). For instance, the **Theorem 17** (complexity of the model checking *Remark* 19. Over discrete time ($\mathbb{T} = \mathbb{N}$), model checka Nest-Free RPExt-HyperPTCTL formula is in formula (resp. Nest-Free \exists RPExt-HyperPTCTL) re-6EXPTIME.

Proof. We reduce to model checking a non-parametric TA against PTCTL [BDR08]. Recall that our general construction (Section 5) reduces model checking a PTA against a Nest-Free Ext-HyperPTCTL formula to model checking a network of PTAs and a set of observers against a PTCTL formula. Since the observers are created for the extended syntax, and since they do not contain parameters in Nest-Free RPExt-HyperPTCTL, the synchronized product of the multiple TAs (by self-composition) and the observers does not contain parameters.

Now, model checking a non-parametric TA against PTCTL can be done in 5EXPTIME in the synchronized product of the size⁷ of \mathcal{A} and ψ from [BDR08, Theorem 7.5]. Therefore, since $|\mathcal{A}^n| < |\mathcal{A}|^{|\psi|}$ and due to the fact that the observers are in constant size, and come in number at most linear in $|\psi|$ (the size of the formula), model checking a TA against a Nest-Free RPExt-HyperPTCTL formula is in 6EXPTIME.

Observe that this is only an upper bound because

- 1. we only provide a one-way reduction, and
- 2. the complexity in [BDR08, Theorem 7.5] only gives an upper bound anyway.

Remark 18. Following the same reasoning, model checking a TA against a formula expressed in a restriction of Nest-Free RPExt-HyperPTCTL to the case where (top-level) formulas are of the form $\exists p_1 \exists p_2 \dots \exists p_n \psi$, where ψ is a Nest-Free RPExt-HyperPTCTL formula with no quantifiers over parameters (which could be called "Nest-Free ∃RPExt-HyperPTCTL"), is in 4EXPTIME, reusing the fact that model checking a non-parametric TA against ∃PTCTL can be done in 3ExpTIME [BDR08, Proposition 7.6].

problem). Model checking timed automata against ing TAs against a Nest-Free RPExt-HyperPTCTL mains in 6EXPTIME (resp. 4EXPTIME), following [BDR08, Corollary 7.3] (resp. [BDR08, Proposition 7.4]).

> Theorem 20 (effective parameter synthesis). The solution to the parameter synthesis problem for TAs against a Nest-Free Ext-HyperPTCTL formula can be effectively computed.

> *Proof.* As in the proof of Theorem 17, we reduce to model checking a non-parametric TA against PTCTL [BDR08]. The solution of the synthesis problem can be effectively computed using the first-order arithmetic over the structure $\langle \mathbb{R}, +, <, \mathbb{N}, 0, 1 \rangle$ of the real numbers, where \mathbb{N} being the predicate "is a natural number". This arithmetic has a decidable theory with complexity in 3EXPTIME in the size of the sentence [Wei99]. From [BDR08, Theorem 6.5], the solution of the parameter synthesis of a non-parametric TA against PTCTL can be effectively computed. \Box

6.2 L/U-PTAs against Nest-Free Ext-HyperPTCTL

Definition 21 (L/U-PTA [Hun+02]). An L/U-PTA (lower-bound/upper-bound PTA) is a PTA where the set of parameters is partitioned into lower-bound parameters and upper-bound parameters, where each upper-bound (resp. lower-bound) parameter p_i must be such that, for every guard or invariant constraint $c \bowtie p_i$, we have $\bowtie \in \{\leq, <\}$ (resp. $\bowtie \in \{\geq, >\}$).

The PTA in Fig. 2 is an L/U-PTA with an upperbound parameter p_1 . (This is in fact even a U-PTA [BL09].)

The observer fragment PTA in Fig. 5 is not L/U.

Because the mere $\forall \diamond$ -emptiness (emptiness of the valuations set for which a given location is always eventually reachable) is undecidable for L/U-PTAs [JLR15] and so is the nested TCTL fragment [ALR18], we restrict ourselves to the reachability fragment of Nest-Free Ext-HyperPTCTL, i.e.,

⁷ As in [BDR08], by size of a formula ψ , we mean the number of symbols used to write it, and we denote it by $|\psi|$.

where temporal operators are only $\exists \Diamond$ (CTL for reach- integer-valued parameters and *without invariants*. note this fragment.

Theorem $\mathbf{22}$ (decidability of non-parametric Nest-Free ∃-∃◊Ext-HyperPTCTL for L/U-P-TAs). Model checking L/U-PTAs against a nonparametric Nest-Free $\exists \exists d \in Ext-HyperPTCTL$ formula The synthesis is, however, *is* PSPACE-*complete*. intractable.

Proof. We reduce to reachability for L/U-PTAs. Our general construction (Section 5) reduces model checking a PTA against a Nest-Free Ext-HyperPTCTL formula to model checking a network of (L/U-)PTAs and a set of non-parametric observers against a TCTL formula. Here, we consider the reachability fragment only, leading to a reachability property. Reachability-emptiness is PSPACE-complete for L/U-PTAs [Hun+02], and therefore model checking L/U-PTAs against a non-parametric Nest-Free $\exists \exists \forall Ext-HyperPTCTL \text{ formula is } PSPACE-complete$ (the hardness argument following immediately).

The non-parametric Nest-Free ∃-∃◊Ext-HyperPTCTL formula " $\exists \pi. \Diamond \sigma$ " is equivalent to the (T)CTL formula $\exists \Diamond \sigma$ denoting reachability. Reachability-synthesis is known to be intractable⁸ for L/U-PTAs [JLR15], and therefore the synthesis for L/U-PTAs against a non-parametric Nest-Free $\exists \exists \exists \& Ext-HyperPTCTL is intractable.$

By using as proof argument a result from [ALR18] showing that nest-free TCTL emptiness is decidable for L/U-PTAs with integer-valued parameters and without invariants, we can show the following result:

Theorem 23 (decidability of non-parametric Nest-Free Ext-HyperPTCTL for L/U-PTAs). Model checking L/U-PTAs with integer-valued parameters without invariants against a non-parametric Nest-Free Ext-HyperPTCTL formula is PSPACE-complete. The synthesis is however intractable.

Proof. In [ALR18], we showed that nest-free TCTL emptiness is PSPACE-complete for L/U-PTAs with

ability). Let Nest-Free \exists - $\exists \diamond Ext-HyperPTCTL$ de- Again, our general construction reduces model checking a PTA against a Nest-Free Ext-HyperPTCTL formula to model checking a network of (L/U-)PTAs and a set of non-parametric observers against a TCTL formula, which is by definition nest-free. Therefore, model checking L/U-PTAs without invariants against a non-parametric Nest-Free Ext-HyperPTCTL formula is PSPACE-complete.

> The intractability of the synthesis comes from [ALR18, Remark 2].

6.3 (1, *, 1)-**PTAs against** non-parametric formula

We use here a common notation (n, *, m) to denote *n* parametric clocks, arbitrarily many non-parametric clocks and m parameters. We finally show decidability in a restrictive setting, by reduction to the decidable setting of [BO17; GH21].

Theorem 24 (Decidability over discrete time with 1 clock). Model checking a (1, *, 1)-PTA is decidable over discrete time against a non-parametric Nest-Free $\exists \exists \forall Ext-HyperPTCTL with (at most) two path quan$ tifiers for each temporal level formula.

Proof. We reduce to reachability for (2, *, 1)-PTAs. \square Model checking non-parametric Nest-Free $\exists \exists \forall Ext$ -HyperPTCTL reduces to model checking a network of PTAs (including the observers necessary to encode the extended syntax of the formula) against a reachability property. Further, the model contains a single parametric clock, and the formula contains 2 paths quantifiers for each temporal level formula, leading the self-composed model to contain 2 parametric clocks. Since the (unique) parameter is shared between both composed copies, then the resulting composition is a (2, *, 1)-PTA. Reachabilityemptiness is EXPSPACE-complete for (2, *, 1)-PTAs for $\mathbb{T} = \mathbb{N}$ [GH21].

It remains open whether the *synthesis* problem is tractable in this latter case.

This result is not tight in the number of clocks, in the sense that it remains open whether model

⁸ More precisely, it cannot be effectively computed: the result cannot be represented in general using a finite union of polyhedra.

checking a (2, *, 1)-PTA against Nest-Free $\exists \exists \exists \forall Ext-tool HyPTCTLchecker^9$. Given a PTA and a Nest-Free can show undecidability. able [Ben+15]) into two (2,0,1)-PTAs, the synchro- to solve the synthesis problem. Nest-Free ∃HyperPTCTL.

Theorem 25 (Undecidability over discrete time with 2 clocks). Model checking a (2,0,1)-PTA is undecidable over discrete time against a non-parametric Nest-Free $\exists HyperPTCTL$ formula using only $\exists \mathcal{U}$ and two path quantifiers.

Proof (sketch). We reduce from the reachability for (3,0,1)-PTAs [Ben+15]. Let \mathcal{A} be a (4,0,1)-PTA with clocks t, x, y, z. Let us "split" it into two (2, 0, 1)-PTAs with the same structure (same locations and edges), such that the first (resp. second) PTA only contains clock constraints containing t and x (resp. yand z). Add to each location of the first PTA a unique location label with the same name as the location, i.e., $\Lambda(\ell_i) = \{\ell_i\}, \text{ and to the second a primed label i.e.,}$ $\Lambda(\ell_i) = \{\ell'_i\}$. Fix ℓ a target location. Then let \mathcal{A}' be the PTA union of these two PTAs, i.e., starting with an initial non-deterministic choice in 0-time, and then "choosing" between either components (we assume that y and z are renamed into t and x). Reaching ℓ in \mathcal{A} is equivalent to checking the following Nest-Free \exists HyperPTCTL formula in \mathcal{A}' :

$$\exists \pi_1, \pi_2. \left(\bigwedge_i (\ell_i)_{\pi_1} = (\ell'_i)_{\pi_2}\right) \mathcal{U}_{\geq 0} \left(\ell_{\pi_1} \wedge \ell'_{\pi_2}\right)$$

Since $\exists \Diamond$ -emptiness is undecidable for (3, 0, 1)-PTAs [Ben+15] (and therefore for (4,0,1)-PTAs), then model checking this formula against \mathcal{A}' is undecidable. \mathcal{A}' contains only two clocks, and the formula is made of a single $\exists \mathcal{U}$, with only two path quantifiers.

7 Experiments

model checking semi-algorithm using our prototype source manner with all the data to reproduce the experiments.

HyperPTCTL with 2 path quantifiers per tempo- Ext-HyperPTCTL formula, HyPTCTLchecker transral level formula is decidable or not. However, lates them into a PTA and a PTCTL formula via the by allowing $\exists \mathcal{U}$ instead of $\exists \Diamond$ in the formula, we reduction presented in Section 5, and outputs them as The proof encodes a the format supported by IMITATOR [And21], a veri-(4,0,1)-PTA (for which $\exists \diamond$ -emptiness is undecid- fication tool for PTAs. Then, we execute IMITATOR HyPTCTLchecker nization of which is enforced thanks to an $\exists \mathcal{U}$ -based supports all the Nest-Free Ext-HyperPTCTL formulas except for the following operators only because IMITATOR does not support their non-hyper versions: $\exists \pi_1, \pi_2, \ldots, \pi_n$. $\Box_{\bowtie \gamma} \varphi, \exists \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \mathcal{R}_{\bowtie \gamma}$ φ_2 , and $\exists \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \mathcal{W}_{\bowtie \gamma} \varphi_2$. We pose the following research questions.

- RQ1 Is HyPTCTLchecker efficient for practical properties?
- RQ2 How many path variables can HyPTCTLchecker handle at most?

We conducted all the experiments on an AWS EC2 m7i.4xlarge instance (with 16vCPU and 64 GiB RAM) that runs Ubuntu 22.04 LTS. We used IMITA-TOR 3.4-alpha. We set 6 hours as the timeout.

7.1 Benchmarks

Table 1 summarizes the benchmarks we used and the experimental results. The translation time is negligible (typically < 0.05 sec) and is not integrated in Table 1. We used five classes of prop-Deviation, Opacity, Unfair, RobOND, and erties: Deviation, Opacity, Unfair, and RobOND are EF_i . the properties shown in Section 4.1, respectively. EF_i is an artificial property to evaluate the scalability of our semi-algorithm with respect to the number of path variables. Concretely, EF_i is $\exists \pi_1, \pi_2, \ldots, \pi_i. \Diamond_{[p,p]} \bigwedge_{i \in \{1,2,\cdots,i-1\}} COUNT(\mathbf{a}_{\pi_i})$ $COUNT(\mathbf{a}_{\pi_{i+1}}) = 1.$

ClkGen is the PTA in Fig. 2. Coffee (a toy coffee machine), STAC1:n and STAC4:n (two Java programs without timing leaks, translated to PTAs) are based on the PTAs in [And+22]. FIFO, Priority, and R.R. are our original PTAs modeling FIFO, Fixed-Priority,

⁹ HvPTCTLchecker is publicly available atWe experimentally evaluated the efficiency of our https://github.com/MasWag/HyPTCTLChecker in an open-

Tab. 1: Summary of the benchmarks and the runtime of IMITATOR. Columns |L| and $|\mathbb{C}|$ show the number of locations and clocks in the PTAs. Columns $|\mathbb{P}|_{\psi}$ and $|\mathbb{P}|_{\mathcal{A}}$ show the number of parameters used in the properties and the PTAs, respectively. Column $|\mathcal{V}|$ shows the number of the quantified path variables in ψ . "**T.O.**" denotes no termination within 6 hours.

Prop. (ψ)	PTA (\mathcal{A})	L	$ \mathbb{C} $	$ \mathbb{P} _{\psi}$	$ \mathbb{P} _{\mathcal{A}}$	$ \mathcal{V} $	Time [sec.]
Deviation	ClkGen	2	1	1	1	2	4.116
Opacity	Coffee	6	2	0	3	2	0.723
Opacity	STAC1:n	8	2	0	2	2	0.178
Opacity	STAC4:n	9	2	0	5	2	< 0.001
Unfair	FIFO	63	2	0	4	2	71.955
Unfair	Priority	72	2	0	4	2	6.855
Unfair	R.R.	81	3	0	4	2	12550.979
RobOND	Coffee	6	2	1	3	2	3.182
RobOND	$WFAS_0^1$	24	4	1	0	2	1.665
RobOND	$WFAS_0^2$	24	4	1	0	2	2.570
RobOND	WFAS ₁	24	4	1	1	2	67.644
RobOND	$WFAS_2$	24	4	1	2	2	1332.31(
RobOND	ATM	7	2	1	0	2	T.O
RobOND	ATM'	5	2	1	0	2	4179.197
EF_2	Coffee	6	2	1	0	2	0.034
EF_3	Coffee	6	2	1	0	3	159.541
EF_4	Coffee	6	2	1	0	4	Т.О

and Round-Robin schedulers, respectively. $WFAS_i$ is a wireless fire alarm system taken from [Ben+15], where *i* shows the number of parameters. $WFAS_0^1$ and $WFAS_0^2$ are instances of WFAS with different parameter valuations. ATM is a simple PTA model of an ATM from [Dai+18, Fig. 1], and ATM' is its variant without the branch "Check". The PTAs taken from the literature are modified to align with our encoding and evaluation, e.g., by adding locations and edges to encode input and output propositions with labels on locations and by instantiating some parameters to evaluate the scalability.

7.2 RQ1: Performance on practical properties

In Table 1, we observe that for most of the benchmarks, the runtime of IMITATOR is less than a few minutes. Particularly, the runtime for Opacity is always less than one second. This aligns with the efficiency of opacity verification with a similar reduction in [And+22]. For Unfair and RobOND, the runtime largely depends on the complexity of the PTA. For instance, R.R. has more locations and clocks than FIFO and Priority for preemptive scheduling, which blows up the result of the self-composition in Section 5.1 and increases the runtime of IMITATOR. Similarly, having more parameters (in $WFAS_i$) or locations (in ATM) increases the runtime. Nevertheless, HyPTCTLchecker can still handle benchmarks with parameters in properties or PTAs if the PTAs are of mild complexity. Thus, we answer RQ1 as follows.

We failed to verify ATM within 6 hours although it has smaller |L|, $|\mathbb{C}|$, and $|\mathbb{P}|_{\mathcal{A}}$ than WFAS₂. It is difficult to discuss its detail, but this can be partly due to the structure of the PTAs. ATM has two loops whereas ATM' has only one of them. After the selfcomposition, they have four and two loops, respectively. It is possible that this caused a combinatorial explosion of the search space.

7.3 RQ2: Scalability to the number of path variables

In Table 1, we observe that HyPTCTLchecker can handle EF_3 but not EF_4 . This is because the self-composition in Section 5.1 exponentially blows up the PTAs with respect to the number of path variables. Given the simplicity of Coffee and EF_3 , we answer RQ2 as follows.

Answer to RQ2: HyPTCTLchecker can handle at most three path variables in a reasonable time.

Although the above answer might seem quite restrictive, we remark that three path variables are likely enough to capture most of the interesting properties. For example, all the HyperLTL or HyperCTL* formulas in the case studies in [FRS15; BF23] are with at most two path variables (potentially with nested temporal operators, which is out of the scope of our semi-algorithm).

8 Conclusion and perspectives

We introduced HyperPTCTL as the first extension to hyperlogics of parametric timed CTL, enabling reasoning simultaneously on different execution traces. After giving a syntax and semantics for the general logics, we restricted ourselves to a nest-free fragment, extended with COUNT and LAST constructs, allowing for reasoning about the number of actions and the duration from their last occurrence, respectively. To our knowledge, this logic is the first of its kind to reason about parametric timed hyperproperties. Model checking this logic Nest-Free Ext-HyperPTCTL reduces to model checking PTCTL. While this is, in general, undecidable, we exhibited a number of decidable subclasses. In addition, our implementation within HyPTCTLchecker (built on top of the PTA model checker IMITATOR) goes beyond the decidable fragment, and showed good results, both for the nonparametric case and the parametric case.

Future works include exhibiting further decidable subclasses, perhaps forbidding equality ("= p") in the formula, as in [BR07], or with restrictions in the formula, such as in [BL09]. Some of our undecidability results in Section 6 are not tight, i.e., the exact bor-

der between decidability and undecidability remains blurred. Devising and implementing a semi-algorithm for the full HyperPTCTL, beyond the nest-free fragment, is also on our agenda. A comparison of the expressive power between Ext-HyperPTCTL and other hyperlogics is also a possible future direction.

Finally, optimizing IMITATOR in order to address HyperPTCTL will be an interesting challenge. The blowup due to the self-composition may be addressed using partial order (e.g., [ACR17]) or symmetry reductions.

References

- [Åbr+20] Erika Åbrahám, Ezio Bartocci, Borzoo Bonakdarpour, and Oyendrila Dobe. "Parameter Synthesis for Probabilistic Hyper-properties". In: LPAR (May 22–27, 2020). Vol. 73. EPiC Series in Computing. 2020, pp. 12–31. DOI: 10.29007/371f (cit. on p. 4).
- [ACD90] Rajeev Courcoubetis, Alur, Costas Dill. "Model-Checking and David L. Real-Time Systems". In: LICS for (June 4-7, 1990). 1990, pp. 414-425 DOI: 10.1109/LICS.1990.113766 (cit. on p. 3).
- [Ace+03] Luca Aceto, Patricia Bouyer, Augusto Burgueño, and Kim Guldstrand Larsen. "The power of reachability testing for timed automata". In: *Theoretical Computer Science* 300.1-3 (2003), pp. 411–475. DOI: 10.1016/S0304-3975(02)00334-1 (cit. on pp. 2, 13).
- [ACR17] Étienne André, Thomas Chatain, and César Rodríguez. "Preserving Partial Order Runs in Parametric Time Petri Nets". In: Transactions on Embedded Computing Systems 16.2 (Mar. 2017), 43:1–43:26. DOI: 10.1145/3012283 (cit. on p. 21).
- [AD94] Rajeev Alur and David L. Dill. "A theory of timed automata". In: *Theoretical Computer Science* 126.2 (1994), pp. 183–235. DOI: 10.1016/0304-3975(94)90010-8 (cit. on pp. 1, 5).

- [AHV93] Rajeev Alur, Thomas A. Henzinger, and [BDR08] Moshe Y. Vardi. "Parametric real-time reasoning". In: STOC (May 16–18, 1993). 1993, pp. 592–601. DOI: 10.1145/167088.167242 (cit. on pp. 1–3, 5, 16).
- [AL02] Luca Aceto and François Laroussinie. "Is your model checker on time? On the complexity of model checking for timed modal [B logics". In: Journal of Logical and Algebraic Methods in Programming 52-53 (2002), pp. 7–51. DOI: 10.1016/S1567-8326(02)00022-X (cit. on p. 3).
- [ALR18] Étienne André, Didier Lime, and Mathias Ramparison. "TCTL model checking lower/upper-bound parametric timed automata without invariants". In: FORMATS [BF23] (Sept. 4–6, 2018). Vol. 11022. Lecture Notes in Computer Science. 2018, pp. 1–17. DOI: 10.1007/978-3-030-00151-3_3 (cit. on pp. 3, 4, 17, 18).
- [And+22] Étienne André, Didier Lime, Dylan Marinho, and Jun Sun. "Guaranteeing Timed Opacity using Parametric Timed Model Checking". In: ACM Transactions on Software Engineering and Methodology 31.4 (2022), 64:1–64:36 (cit. on pp. 19, 20).
- [And+23] Étienne André, Engel Lefaucheux, Didier Lime, Dylan Marinho, and Jun Sun.
 "Configuring Timing Parameters to Ensure Execution-Time Opacity in Timed [BO17] Automata". In: *TiCSA* (Apr. 23, 2023).
 EPTCS. 2023 (cit. on p. 7).
- [And13] Étienne André. "Observer Patterns for Real-Time Systems". In: *ICECCS* (July 17–19, 2013). Singapore, 2013, pp. 125–134. DOI: [BPS20] 10.1109/ICECCS.2013.26 (cit. on p. 13).
- [And21] Étienne André. "IMITATOR 3: Synthesis of timing parameters beyond decidability". In: *CAV* (July 18–23, 2021). Vol. 12759. Lecture Notes in Computer Science. 2021, pp. 1–14. DOI: 10.1007/978-3-030-81685-8_26 (cit. on pp. 2, 7, 19).
- [Bar+23] Ezio Bartocci, Cristinel Mateis, Eleonora Nesterini, and Dejan Nickovic. "Mining Hyperproperties using Temporal Logics". In: [BPS22] ACM Transactions on Embedded Computing Systems 22.5s (2023), 156:1–156:26. DOI: 10.1145/3609394 (cit. on p. 4).

 Véronique Bruyère, Emmanuel Dall'Olio, and Jean-Francois Raskin. "Durations and parametric model-checking in timed automata". In: ACM Transactions on Computational Logic 9.2 (2008), 12:1–12:23. DOI: 10.1145/1342991.1342996 (cit. on pp. 3, 6, 7, 17).

[Ben+15] Nikola Beneš, Peter Bezděk, Kim Guldstrand Larsen, and Jiří Srba. "Language Emptiness of Continuous-Time Parametric Timed Automata". In: *ICALP*, Part II (July 6– 10, 2015). Vol. 9135. Lecture Notes in Computer Science. 2015, pp. 69–81. DOI: 10.1007/978-3-662-47666-6_6 (cit. on pp. 19, 20).

> Raven Beutner and Bernd Finkbeiner. "AutoHyper: Explicit-State Model Checking for HyperLTL". In: *TACAS*, *Part I* (Apr. 22– 27, 2023). Ed. by Sriram Sankaranarayanan and Natasha Sharygina. Vol. 13993. Lecture Notes in Computer Science. Paris, France: Springer, 2023, pp. 145–163. DOI: 10.1007/978-3-031-30823-9_8 (cit. on p. 21).

- Laura Bozzelli and Salvatore La Torre. "Decision problems for lower/upper bound parametric timed automata". In: *Formal Methods in System Design* 35.2 (2009), pp. 121–151. DOI: 10.1007/s10703-009-0074-0 (cit. on pp. 4, 17, 21).
- Daniel Bundala and Joël Ouaknine. "On parametric timed automata and one-counter machines". In: *Information and Computation* 253 (2017), pp. 272–303. DOI: 10.1016/j.ic.2016.07.011 (cit. on pp. 3, 18).
- Borzoo Bonakdarpour, Pavithra Prabhakar, and César Sánchez. "Model Checking Timed Hyperproperties in Discrete-Time Systems". In: *NFM* (May 11–15, 2020). Ed. by Ritchie Lee, Susmit Jha, and Anastasia Mavridou. Vol. 12229. Lecture Notes in Computer Science. Moffett Field, CA, USA: Springer, 2020, pp. 311–328. DOI: 10.1007/978-3-030-55754-6_18 (cit. on pp. 4, 7).
- Laura Bozzelli, Adriano Peron, and César Sánchez. "Expressiveness and Decidability of Temporal Logics for Asynchronous Hyperproperties". In: *CONCUR* (Sept. 12–16,

2022). Vol. 243. LIPIcs. 2022, 27:1–27:16. DOI: [Ger+23] 10.4230/LIPIcs.CONCUR.2022.27 (cit. on p. 4).

[BR07] Véronique Bruyère and Jean-François Raskin. "Real-Time Model-Checking: Parameters everywhere". In: Logical Methods in Computer Science 3.1:7 (2007), pp. 1–30. DOI: 10.2168/LMCS-3(1:7)2007 (cit. on pp. 3, 21).

- [Cas09] Franck Cassez. "The Dark Side of Timed [G: Opacity". In: ISA (June 25–27, 2009). Vol. 5576. Lecture Notes in Computer Science. Seoul, Korea: Springer, 2009, pp. 21–30. DOI: 10.1007/978-3-642-02617-1_3 (cit. on p. 7).
- [Cla+14] Michael R. Clarkson, Bernd Finkbeiner, Masoud Koleini, Kristopher K. Micinski, Markus N. Rabe, and César Sánchez. "Temporal Logics for Hyperproperties". In: *POST* (Apr. 5–13, 2014). Vol. 8414. Lecture Notes in Computer Science. 2014, pp. 265–284. DOI: 10.1007/978-3-642-54792-8_15 (cit. on p. 4).
- [Dai+18] Liyun Dai, Taolue Chen, Zhiming Liu, Bican Xia, Naijun Zhan, and Kim G. Larsen.
 "Parameter Synthesis Problems for one parametric clock Timed Automata". In: CoRR [1 abs/1809.07177 (2018). arXiv: 1809.07177 (cit. on p. 20).
- [Doy07] Laurent Doyen. "Robust Parametric Reachability for Timed Automata". In: Information Processing Letters 102.5 (2007), pp. 208–213. [JLR15] DOI: 10.1016/j.ipl.2006.11.018 (cit. on p. 3).
- [ET99] E. Allen Emerson and Richard J. Trefler. "Parametric Quantitative Temporal Reasoning". In: *LiCS* (July 2–5, 1999). 1999, pp. 336–343. DOI: 10.1109/LICS.1999.782628 (cit. on p. 3).
- [FR74] Michael J. Fischer and Michael O. Rabin. "Super-Exponential Complexity of Presburger Arithmetic". In: SIAM-AMS. 1974, pp. 27–41 (cit. on p. 3).
- [FRS15] Bernd Finkbeiner, Markus N. Rabe, and César Sánchez. "Algorithms for Model Checking HyperLTL and HyperCTL*". In: *CAV, part I* (July 18–24, 2015). Vol. 9206. [Wei99] Lecture Notes in Computer Science. 2015, pp. 30–48. DOI: 10.1007/978-3-319-21690-4_3 (cit. on p. 21).

- Lina Gerlach, Oyendrila Dobe, Erika Ábrahám, Ezio Bartocci, and Borzoo Bonakdarpour. "Introducing Asynchronicity to Probabilistic Hyperproperties". In: *QEST* (Sept. 20–22, 2023). Vol. 14287. Lecture Notes in Computer Science. 2023, pp. 47–64. DOI: 10.1007/978-3-031-43835-6_4 (cit. on p. 4).
- [GH21] Stefan Göller and Mathieu Hilaire. "Reachability in Two-Parametric Timed Automata with One Parameter is EXPSPACE-Complete". In: STACS (Mar. 16–19, 2021).
 Vol. 187. LIPIcs. 2021, 36:1–36:18. DOI: 10.4230/LIPIcs.STACS.2021.36 (cit. on pp. 3, 18).
- [Hun+02] Thomas Hune, Judi Romijn, Mariëlle Stoelinga, and Frits W. Vaandrager. "Linear parametric model checking of timed automata". In: Journal of Logic and Algebraic Programming 52-53 (2002), pp. 183–220. DOI: 10.1016/S1567-8326(02)00037-1 (cit. on pp. 4, 17, 18).
- [HZJ21] Hsi-Ming Ho, Ruoyu Zhou, and Timothy M. Jones. "Timed hyperproperties". In: Information and Computation 280 (2021), p. 104639. DOI: 10.1016/j.ic.2020.104639 (cit. on p. 4).
 - Aleksandra Jovanović, Didier Lime, and Olivier H. Roux. "Integer Parameter Synthesis for Real-Time Systems". In: *IEEE Transactions on Software Engineering* 41.5 (2015), pp. 445–461. DOI: 10.1109/TSE.2014.2357445 (cit. on pp. 3, 17, 18).
- [Mil00] Joseph S. Miller. "Decidability and Complexity Results for Timed Automata and Semi-linear Hybrid Automata". In: HSCC (Mar. 23–25, 2000). Vol. 1790. Lecture Notes in Computer Science. 2000, pp. 296–309. ISBN: 3-540-67259-1. DOI: 10.1007/3-540-46430-1_26 (cit. on p. 4).
 - Volker Weispfenning. "Mixed Real-Integer Linear Quantifier Elimination". In: ISSAC (July 29–31, 1999). 1999, pp. 129–136. DOI: 10.1145/309831.309888 (cit. on p. 17).

A Omitted proofs

A.1 Full proof of Theorem 10

Before proving Theorem 10, we show a property on path assignments and lemmas between path assignments of the original TAs and the paths of selfcomposed TAs. In the remaining part of this section, we assume that any PTA does not have a selfloop with no guard or reset. Note that removing such edges does not change the semantics. For any edge eof \mathcal{A}^n and $i \in \{1, 2, ..., n\}$, we let $e|_i$ be the projection of e to the *i*-th component.

Proposition 26. Let \mathcal{A} be a PTA, v be a parameter valuation, and $(\Pi, \trianglelefteq_{\Pi})$ be a path assignment of $v(\mathcal{A})$ satisfying dom $(\Pi) = \{\pi_1, \pi_2, \ldots, \pi_n\}$ and $\Pi(\pi) \in$ Paths $(v(\mathcal{A}))$ for any $\pi \in$ dom (Π) . For any $\pi, \pi' \in$ dom (Π) and $i, j \in \mathbb{N}$, if we have $(\pi, i) \trianglelefteq_{\Pi} (\pi', j)$ and $(\pi', j) \trianglelefteq_{\Pi} (\pi, i), \sum_{k=0}^{i} d_k^{\pi} = \sum_{k=0}^{j} d_k^{\pi'}$ holds, where d_k^{π} and d_k^{π} are the k-th delay in $\Pi(\pi)$ and $\Pi(\pi')$, respectively.

Proof. It is immediate from the second requirement on \leq_{Π} in Definition 5.

Lemma 27. Let \mathcal{A} be a PTA, v be a parameter valuation, and $n \in \mathbb{N}_{>0}$. For any path assignment $(\Pi, \trianglelefteq_{\Pi})$ of $v(\mathcal{A})$ satisfying $\operatorname{dom}(\Pi) = \{\pi_1, \pi_2, \ldots, \pi_n\}$, if for any $\pi \in \operatorname{dom}(\Pi)$, $\Pi(\pi) \in \operatorname{Paths}(v(\mathcal{A}))$ holds, there is a path $\rho \in \operatorname{Paths}(v(\mathcal{A}^n))$ of $v(\mathcal{A}^n)$ satisfying the following conditions, where $\mathcal{N}_{\trianglelefteq_{\Pi}}$ is the monotone surjection from $\operatorname{dom}(\Pi) \times \mathbb{N}$ to \mathbb{N} .

- For any $\pi_k \in \mathbf{dom}(\Pi)$, $\Pi(\pi_k) = \rho|_k$ holds.
- For any $i \in \mathbb{N}$, the inverse image $\mathcal{N}_{\leq_{\Pi}}^{-1}(\{i\})$ satisfies $(\pi_k, j) \in \mathcal{N}_{\leq_{\Pi}}^{-1}(\{i\}) \iff e_i|_k = e_j^k$, where e_i is the *i*-th edge of ρ and e_j^k is the *j*-th edge of $\Pi(\pi_k)$.

Proof. For the sake of simplicity, we show the case of n = 2. The proof of the general case is by induction on n. Let $\Pi(\pi_1) = (\ell_0^1, \nu_0^1), (d_0^1, e_0^1), (\ell_1^1, \nu_1^1), \ldots$ and $\Pi(\pi_2) = (\ell_0^2, \nu_0^2), (d_0^2, e_0^2), (\ell_1^2, \nu_1^2), \ldots$ By using the inverse image $\mathcal{N}_{\leq_{\Pi}}^{-1}$, we inductively define $\rho = (\ell_0, \nu_0), (d_0, e_0), (\ell_1, \nu_1), \ldots$ as follows:

- $\ell_0 = (\ell_0^1, \ell_0^2)$ and ν_0 is such that $\nu_0(c) = \nu_0^1(c)$ if c is a clock of the first component, and otherwise, $\nu_0(c) = \nu_0^2(c)$.
- $d_i = \sum_{l=0}^{j} d_l^k \sum_{l=0}^{i-1} d_l$, where $(\pi_k, j) \in \mathcal{N}_{\leq \Pi}^{-1}(\{i\})$.
- e_i is such that:

$$- \text{ if } \mathcal{N}_{\leq \mathbf{n}}^{-1}(\{i\}) = \{(\pi_1, j)\}, \quad e_i = ((\ell^1, \ell^2), g, R, (\ell^{1'}, \ell^2)), \text{ with } \ell_i = (\ell^1, \ell^2) \text{ and } e_j^1 = (\ell^1, g, R, \ell^{1'});$$

- $\text{ if } \mathcal{N}_{\leq \mathrm{II}}^{-1}(\{i\}) = \{(\pi_2, j)\}, \quad e_i = ((\ell^1, \ell^2), g, R, (\ell^1, \ell^{2'})), \text{ with } \ell_i = (\ell^1, \ell^2) \text{ and } e_j^2 = (\ell^2, g, R, \ell^{2'});$
- $\begin{array}{lll} \text{ if } & \mathcal{N}_{\trianglelefteq \Pi}^{-1}(\{i\}) &= \{(\pi_1, j), (\pi_2, k)\}, & e_i &= \\ & ((\ell^1, \ell^2), g^1 \wedge g^2, R^1 \cup R^2, (\ell^{1'}, \ell^{2'})), & \text{ with } \\ & \ell_i &= (\ell^1, \ell^2), & e_j^1 &= (\ell^1, g^1, R^1, \ell^{1'}), & \text{ and } \\ & e_j^2 &= (\ell^2, g^2, R^2, \ell^{2'}). \end{array}$
- For $e_{i-1} = (\ell, g, R, \ell'), \ \ell_i = \ell' \text{ and } \nu_i = [\nu_{i-1} + d_{i-1}]_R.$

Notice that d_i is irrelevant to the choice of $(\pi_k, j) \in \mathcal{N}_{\leq \Pi}^{-1}(\{i\})$ by Proposition 26. From the definition of the edges of $v(\mathcal{A}^2)$, such ρ is a path of $v(\mathcal{A}^2)$. Moreover, we have $\rho|_1 = \Pi(\pi_1)$ and $\rho|_2 = \Pi(\pi_2)$, and $\mathcal{N}_{\leq \Pi}^{-1}(\{i\})$ is such that $(\pi_k, j) \in \mathcal{N}_{\leq \Pi}^{-1}(\{i\})$ if and only if we have $e_i|_k = e_j^k$.

Lemma 28. Let \mathcal{A} be a PTA, v be a parameter valuation, and $n \in \mathbb{N}_{>0}$. For any path $\rho \in Paths(v(\mathcal{A}^n))$ of $v(\mathcal{A}^n)$, there is a path assignment $(\Pi, \trianglelefteq_{\Pi})$ of $v(\mathcal{A})$ satisfying the following conditions, where $\mathcal{N}_{\trianglelefteq_{\Pi}}$ is the monotone surjection from $\operatorname{dom}(\Pi) \times \mathbb{N}$ to \mathbb{N} .

- $\mathbf{dom}(\Pi) = \{\pi_1, \pi_2, \dots, \pi_n\}$ holds.
- For any $\pi_k \in \mathbf{dom}(\Pi)$, $\Pi(\pi_k) = \rho|_k$ holds.
- For any $i \in \mathbb{N}$, the inverse image $\mathcal{N}_{\leq_{\Pi}}^{-1}(\{i\})$ satisfies $(\pi_k, j) \in \mathcal{N}_{\leq_{\Pi}}^{-1}(\{i\}) \iff e_i|_k = e_j^k$, where e_i is the *i*-th edge of ρ and e_j^k is the *j*-th edge of $\Pi(\pi_k)$.

of n = 2. The proof of the general case is by in- $(\pi, j) \in \mathcal{N}_{\leq \Pi}^{-1}(\{i\}) \iff e_i|_k = e_j^k$, we have the folduction on *n*. Let $\rho = (\ell_0, \nu_0), (d_0, e_0), (\ell_1, \nu_1), \dots$ and let Π be such that $\mathbf{dom}(\Pi) = \{\pi_1, \pi_2\}$, and for each $k \in \{1,2\}, \ \Pi(\pi_k) = \rho|_k$. We let $\Pi(\pi_1) = (\ell_0^1, \nu_0^1), (d_0^1, e_0^1), (\ell_1^1, \nu_1^1), \dots \text{ and } \Pi(\pi_2) =$ $(\ell_0^2, \nu_0^2), (d_0^2, e_0^2), (\ell_1^2, \nu_1^2), \dots$ By definition of \mathcal{A}^2 and because of $\Pi(\pi_1) = \rho|_1$ and $\Pi(\pi_2) = \rho|_2$, each e_i in ρ satisfies one of the following, where E is the set of edges in \mathcal{A} :

- $e_i = ((\ell^1, \ell^2), g, R, (\ell^{1'}, \ell^2))$, with $(\ell^1, g, R, {\ell^{1'}}) = e_j^1 \in E$ for some $j \in \mathbb{N}$;
- $e_i = ((\ell^1, \ell^2), g, R, (\ell^1, \ell^{2'})), \text{ with } (\ell^2, g, R, \ell^{2'}) = e_j^2 \in E \text{ for some } j \in \mathbb{N};$
- $e_i = ((\ell^1, \ell^2), g^1 \wedge g^2, R^1 \cup R^2, (\ell^{1'}, \ell^{2'}))$, with $(\ell^1, g^1, R^1, \ell^{1'}) = e_j^1 \in E$ and $(\ell^2, g^2, R^2, \ell^{2'}) =$ $e_l^2 \in E$ for some $j, l \in \mathbb{N}$.

first case, $\mathcal{N}_{\triangleleft_{\Pi}}^{-1}(i) = \{(\pi_2, \overline{j})\}$ for the second case, and $\mathcal{N}_{\leq \pi}^{-1}(i) = \{(\pi_1, j), (\pi_2, l)\}$ for the third case. Since for each $k \in \{1,2\}, \Pi(\pi_k) = \rho|_k$ holds, such $\mathcal{N}_{\triangleleft_{\Pi}}$ is a surjection from $\mathbf{dom}(\Pi) \times \mathbb{N}$ to \mathbb{N} . We let $\trianglelefteq_{\Pi} \subseteq (\mathbf{dom}(\Pi) \times \mathbb{N}) \times (\mathbf{dom}(\Pi) \times \mathbb{N})$ be such that $\begin{array}{lll} (\pi,i) \trianglelefteq_{\Pi} (\pi',j) & \Longleftrightarrow & \mathcal{N}_{\trianglelefteq_{\Pi}}((\pi,i)) \le \mathcal{N}_{\trianglelefteq_{\Pi}}((\pi',j)). \\ \text{Notice that } \trianglelefteq_{\Pi} & \text{is a total preorder and } \mathcal{N}_{\trianglelefteq_{\Pi}} & \text{is} \end{array}$ monotone. By definition of $\mathcal{N}_{\leq n}$, for any $k, k' \in$ $\{1,2\}$ and $i,j \in \mathbb{N}, i < j$ implies $\mathcal{N}_{\leq_{\Pi}}((\pi_k,i)) <$ $\mathcal{N}_{\leq_{\Pi}}((\pi_k, j)), \ \mathcal{N}_{\leq_{\Pi}}((\pi_k, i)) \leq \mathcal{N}_{\leq_{\Pi}}((\pi_{k'}, j)) \text{ implies}$ $\sum_{l=0}^{i} d_l^k \leq \sum_{l=0}^{j} d_l^{k'}, \text{ and } \sum_{l=0}^{i} d_l^k < \sum_{l=0}^{j} d_l^{k'} \text{ implies}$ $\mathcal{N}_{\leq_{\Pi}}((\pi_k, i)) \leq \mathcal{N}_{\leq_{\Pi}}((\pi_{k'}, j)). \text{ By definition}$ of \leq_{Π} , for any $k, k' \in \{1, 2\}$ and $i, j \in \mathbb{N}, i <$ j implies $(\pi_k, i) \leq_{\Pi} (\pi_k, j)$ and $(\pi_k, j) \not\leq_{\Pi} (\pi_k, i)$, $(\pi_k, i) \leq_{\Pi} (\pi_{k'}, j)$ implies $\sum_{l=0}^i d_l^k \leq \sum_{l=0}^j d_l^{k'}$, and $\sum_{l=0}^{i} d_l^k < \sum_{l=0}^{j} d_l^{k'}$ implies $(\pi_k, i) \leq_{\Pi} (\pi_{k'}, j)$. Overall, such $(\Pi, \trianglelefteq_{\Pi})$ is a path assignment.

Lemma 29. Let \mathcal{A} be a PTA, v be a parameter valuation, and $n \in \mathbb{N}_{>0}$. Let (Π, \leq_{Π}) be a path assignment of $v(\mathcal{A})$ satisfying $\mathbf{dom}(\Pi) = \{\pi_1, \pi_2, \dots, \pi_n\}$ and let $\rho \in Paths(v(\mathcal{A}^n))$ be a path of $v(\mathcal{A}^n)$. Let e_i be the *i*-th edge of ρ and e_i^k be the *j*-th edge of $\Pi(\pi_k)$. If for any $\pi_k \in \mathbf{dom}(\Pi)$, we have $\Pi(\pi_k) = \rho|_k$ and

Proof. For the sake of simplicity, we show the case for any $i \in \mathbb{N}$, the inverse image $\mathcal{N}_{\triangleleft_{\Pi}}^{-1}(\{i\})$ satisfies lowing.

- For any ρ' and ρ'' satisfying $\rho \succeq \rho'' \succ \rho'$, there are $(\Pi', \leq_{\Pi'})$ and $(\Pi'', \leq_{\Pi''})$ such that we have $(\Pi, \leq_{\Pi}) \succeq (\Pi'', \leq_{\Pi}'') \succ (\Pi', \leq_{\Pi'})$ and for any $i \in \{1, 2, ..., n\}$, we have $\Pi'(\pi_i) = \rho'|_i$ and $\Pi''(\pi_i) = \rho''|_i.$
- For any $(\Pi', \trianglelefteq_{\Pi'})$ and $(\Pi'', \trianglelefteq_{\Pi''})$ satisfying $(\Pi, \trianglelefteq_{\Pi}) \succeq (\Pi'', \trianglelefteq_{\Pi''}) \succ (\Pi', \trianglelefteq_{\Pi'}), \text{ there are } \rho'$ and ρ'' such that we have $\rho \succeq \rho'' \succ \rho'$ and for any $i \in \{1, 2, ..., n\}$, we have $\Pi'(\pi_i) = \rho'|_i$ and $\Pi^{\prime\prime}(\pi_i) = \rho^{\prime\prime}|_i.$

Proof. For the sake of simplicity, we show the case of n = 2. The proof of the general case is by induction on *n*. Let $\rho = (\ell_0, \nu_0), (d_0, e_0), (\ell_1, \nu_1), \ldots$

For any $\rho' = (\ell_i, \nu_i + d), (d_i - d, e_i), (\ell_{i+1}, \nu_{i+1}), \dots$ and $\rho'' = (\ell_{i'}, \nu_{i'} + d'), (d_{i'} - d', e_{i'}), (\ell_{i'+1}, \nu_{i'+1}), \dots$ We let $\mathcal{N}_{\leq_{\Pi}}$ be such that $\mathcal{N}_{\leq_{\Pi}}^{-1}(i) = \{(\pi_1, j)\}$ for the satisfying $\rho \succeq \rho'' \succ \rho'$, let $\Pi', \Pi'', \leq_{\Pi'}, \text{ and } \leq_{\Pi''}$ be such that $\Pi'(\pi_1) = \rho'|_1$, $\Pi'(\pi_2) = \rho'|_2$, $\Pi''(\pi_1) =$ $\rho''|_1, \Pi''(\pi_2) = \rho''|_2$, and for any $\pi, \pi' \in \mathbf{dom}(\Pi)$ and $l, m \in \mathbb{N}$, we have $(\pi, l) \trianglelefteq_{\Pi'} (\pi', m) \iff$ $(\pi, l + \mathcal{D}_{\Pi(\pi)}^{\Pi''(\pi)}) \trianglelefteq_{\Pi} (\pi'', m + \mathcal{D}_{\Pi(\pi')}^{\Pi''(\pi')})$ and $(\pi, l) \trianglelefteq_{\Pi'}$ $(\pi',m) \iff (\pi,l+\mathcal{D}_{\Pi''(\pi)}^{\Pi'(\pi)}) \leq_{\Pi''} (\pi',m+\mathcal{D}_{\Pi''(\pi')}^{\Pi'(\pi')}).$ By the construction of ρ', ρ'', Π' , and Π'' , we have the following.

- $Dur(\Pi \Pi'') = Dur(\rho \rho'')(= d' + \sum_{i=0}^{i'-1} d_i).$
- $Dur(\Pi'' \Pi') = Dur(\rho'' \rho')(= d + \sum_{i=0}^{i-1} d_i d_i)$ $Dur(\Pi - \Pi'')).$
- For any $k \in \{1,2\}, \ \Pi(\pi_k) = \rho|_k \succeq \rho''|_k =$ $\Pi''(\pi_k).$
- For any $k \in \{1,2\}, \Pi''(\pi_k) = \rho''|_k \succ \rho'|_k =$ $\Pi'(\pi_k).$
- For any $\pi \in \mathbf{dom}(\Pi)$ and $j \in \mathbb{N}, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} \leq j \iff$ $i \leq \mathcal{N}_{\leq_{\Pi}}((\pi, j)).$
- For any $\pi \in \operatorname{dom}(\Pi)$ and $j \in \mathbb{N}$, $\mathcal{D}_{\Pi(\pi)}^{\Pi''(\pi)}$ \leq $j \iff i' \leq \mathcal{N}_{\triangleleft_{\Pi}}((\pi, j)).$

for any $\pi, \pi' \in \operatorname{dom}(\Pi)$, we have $(\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - (\Pi^3, \leq_{\Pi^3}), \operatorname{Init}(\Pi^3(\pi_n)), [\eta]_{\Pi^1 - \Pi^3}, [\theta]_{\Pi^1 - \Pi^3} \models_{v, \mathcal{A}} \varphi_1$ holds By Lemmas 27 and 20 for any code Π^1 $1) \leq_{\Pi} (\pi', \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')}), (\pi', \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')}) \leq_{\Pi} (\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - 1),$ $(\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - 1) \leq_{\Pi} (\pi', \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')}), \text{ and } (\pi', \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')}) \leq_{\Pi}$ $(\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - 1).$ Since $\mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')} = \mathcal{D}_{\Pi(\pi')}^{\Pi'(\pi')} + \mathcal{D}_{\Pi'(\pi')}^{\Pi'(\pi')},$ we have $(\pi, \mathcal{D}_{\Pi'(\pi)}^{\Pi'(\pi)} - 1) \leq_{\Pi''} (\pi', \mathcal{D}_{\Pi''(\pi')}^{\Pi'(\pi')})$ and $\mathcal{D}_{\Pi'(\pi')}^{\Pi'(\pi')}, \text{ we have } (\pi, \mathcal{D}_{\Pi''(\pi)}^{\Pi'(\pi)} - 1) \leq_{\Pi''} (\pi', \mathcal{D}_{\Pi''(\pi')}^{\Pi'(\pi)}) \text{ and } \overline{\Pi}^{1}(\pi) = \rho, \quad \overline{\Pi}^{2}(\pi) = \rho', \text{ and } \underline{\triangleleft}_{\overline{\Pi}^{1}} = \underline{\triangleleft}_{\overline{\Pi}^{2}} (\pi', \mathcal{D}_{\Pi''(\pi')}^{\Pi'(\pi)}) \leq_{\Pi''} (\pi, \mathcal{D}_{\Pi''(\pi)}^{\Pi'(\pi)} - 1). \text{ Overall, we have are such that } (\pi, i) \leq_{\overline{\Pi}^{1}} (\pi, j) \iff i \leq j.$ $(\Pi, \trianglelefteq_{\Pi}) \succeq (\Pi'', \trianglelefteq_{\Pi''}) \succ (\Pi', \trianglelefteq_{\Pi'}).$

For any $(\Pi', \leq_{\Pi'})$ and $(\Pi'', \leq_{\Pi''})$ satisfying $(\Pi, \trianglelefteq_{\Pi}) \succeq (\Pi'', \trianglelefteq_{\Pi''}) \succ (\Pi', \trianglelefteq_{\Pi'}), \text{ we let } \rho' =$ $(\ell_{i'}, \nu_{i'} + d'), (d_{i'} - d', e_{i'}), (\ell_{i'+1}, \nu_{i'+1}), \dots, \text{ where } i = reduce^n(\varphi_2).$ Let $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$ be a path assignment $\min_{\pi \in \mathbf{dom}(\Pi)} \mathcal{N}_{\leq_{\Pi}}((\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)})), \ d = Dur(\Pi - \Pi') - \text{ satisfying } (\overline{\Pi}^1, \leq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^3, \leq_{\overline{\Pi}^3}) \succeq (\overline{\Pi}^2, \leq_{\overline{\Pi}^2}).$ $\sum_{j=0}^{i-1} d_j, \ i' = \min_{\pi \in \mathbf{dom}(\Pi)} \mathcal{N}_{\leq \pi}((\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi''(\pi)})), \text{ and By Lemma 29, for any such } (\overline{\Pi}^3, \leq_{\overline{\Pi}^3}), \text{ there}$ $d' = Dur(\Pi - \Pi'') - \sum_{j=0}^{i'-1} d_j. \text{ Notice that we have is a path assignment } (\Pi^3, \leq_{\Pi^3}) \text{ satisfying}$ $\rho \succeq \rho'' \succ \rho'. \text{ Since we have } \rho|_1 = \Pi(\pi_1), \rho|_2 = \Pi(\pi_2), \ (\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^3, \leq_{\Pi^3}) \succ (\Pi^2, \leq_{\Pi^2}), \text{ and}$ $Dur(\Pi - \Pi'') = Dur(\rho - \rho'')$, and for any $\pi \in \mathbf{dom}(\Pi)$, $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$ for each $i \in \{1, 2, \dots, n\}$. $j \in \mathbb{N}, \mathcal{D}_{\Pi(\pi)}^{\Pi''(\pi)} \leq j \iff i' \leq \mathcal{N}_{\leq_{\Pi}}((\pi, j)) \text{ holds},$ we have $\rho''|_1 = \Pi''(\pi_1)$ and $\rho''|_2 = \Pi''(\pi_2)$. Similarly, since we have $\rho|_1 = \Pi(\pi_1), \ \rho|_2 = \Pi(\pi_2),$ $Dur(\Pi - \Pi') = Dur(\rho - \rho')$, and for any $\pi \in \mathbf{dom}(\Pi)$, $j \in \mathbb{N}, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} \leq j \iff i \leq \mathcal{N}_{\leq_{\Pi}}((\pi, j)) \text{ holds, we } (\overline{\Pi}^3, \leq_{\overline{\Pi}^3}), Init(\overline{\Pi}^3(\pi)), [\eta]_{\overline{\Pi}^1 - \overline{\Pi}^3}, [\theta]_{\overline{\Pi}^1 - \overline{\Pi}^3}$ have $\rho'|_1 = \Pi'(\pi_1)$ and $\rho'|_2 = \Pi'(\pi_2)$.

Proof of Theorem 10 is as follows.

Theorem 10 (recalled). For a PTA \mathcal{A} , a temporal-level Nest-Free Ext-HyperPTCTL formulas $\varphi_{\exists} = \exists \pi_1, \pi_2, \ldots, \pi_n, \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2$ and $\varphi_{\forall} =$ $\forall \pi_1, \pi_2, \ldots, \pi_n. \varphi_1 \ \mathcal{U}_{\bowtie \gamma} \ \varphi_2, \ and \ a \ parameter \ val$ uation v, we have $\mathcal{A} \models_v \varphi_{\exists}$ (resp. $\mathcal{A} \models_v \varphi_{\forall}$) if and only if we have $\mathcal{A}^n \models_v reduce^n(\varphi_{\exists})$ (resp. $\mathcal{A}^n \models_v reduce^n(\varphi_{\forall})).$

Proof of Theorem 10. Suppose $\mathcal{A} \models_v \varphi_{\exists}$ holds. By the semantics of Ext-HyperPTCTL, for some exten- $reduce^{n}(\varphi_{1})$ holds. By Lemmas 28 and 29, for sion (Π^1, \leq_{Π^1}) of $(\Pi_{\emptyset}, \leq_{\Pi_{\emptyset}})$ satisfying **dom** (Π) = any such $\overline{\Pi}^1(\pi)$ and $\overline{\Pi}^2(\pi)$, there are path as- $\{\pi_1, \pi_2, \ldots, \pi_n\}$ and $\Pi^1(\pi_i) \in Paths(v(\mathcal{A}))$ for signments $(\Pi^1, \trianglelefteq_{\Pi^1})$ and $(\Pi^2, \trianglelefteq_{\Pi^2})$ such that each $i \in \{1, 2, ..., n\}$, there is (Π^2, \leq_{Π^2}) satisfying $\mathbf{dom}(\Pi^1) = \mathbf{dom}(\Pi^2) = \{\pi_1, \pi_2, ..., \pi_n\}$,

Particularly, we have $\mathcal{N}_{\leq_{\Pi}}((\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)} - 1)) < (\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^2, \leq_{\Pi^2}), Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma),$ $i \leq \mathcal{N}_{\leq_{\Pi}}((\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi'(\pi)}))$ and $\mathcal{N}_{\leq_{\Pi}}((\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi''(\pi)} - 1)) < (\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi_n)), [\eta]_{\Pi^1 - \Pi^2}, [\theta]_{\Pi^1 - \Pi^2} \models_{v, \mathcal{A}}$ φ_2 , and for any (Π^3, \leq_{Π^3}) satisfying $i' \leq \mathcal{N}_{\leq_{\Pi}}((\pi, \mathcal{D}_{\Pi(\pi)}^{\Pi''(\pi)})).$ Since $\mathcal{N}_{\leq_{\Pi}}$ is monotone, $(\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^3, \leq_{\Pi^3}) \succ (\Pi^2, \leq_{\Pi^2}),$ and Π^2 , there are paths ρ and ρ' of $v(\mathcal{A}^n)$ such that $\rho \succeq \rho'$ holds and for each $i \in \{1, 2, \dots, n\}$, we have $\Pi^1(\pi_i) = \rho|_i$ and $\Pi^2(\pi_i) = \rho'|_i$. Let $\overline{\Pi}^1$ and $\overline{\Pi}^2$, be such that $\operatorname{dom}(\overline{\Pi}^1) = \operatorname{dom}(\overline{\Pi}^2) = \{\pi\},\$ For such $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1})$ and $(\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2})$, we have $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2}), \quad Dur(\overline{\Pi}^1 - \overline{\Pi}^2) \bowtie v(\gamma),$ Since we have $\mathcal{A} \models_v \varphi_{\exists}$, for such $(\Pi^3, \trianglelefteq_{\Pi^3})$, we have $(\Pi^3, \leq_{\Pi^3}), Init(\Pi^3(\pi_n)), [\eta]_{\Pi^1-\Pi^3}, [\theta]_{\Pi^1-\Pi^3} \models_{v,\mathcal{A}} \varphi_1.$ Since for each $i \in \{1, 2, ..., n\}$, we have $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$, for such $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$, we have $\models_{v,\mathcal{A}}$ \square reduceⁿ(φ_1). Therefore, we have $\mathcal{A}^n \models_v reduce^n(\varphi_{\exists})$.

> Suppose $\mathcal{A}^n \models_v reduce^n(\varphi_{\exists})$ holds. By the semantics of Ext-HyperPTCTL, for some extension $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1})$ of $(\Pi_{\emptyset}, \trianglelefteq_{\Pi_{\emptyset}})$ satisfying **dom** $(\overline{\Pi}) = \{\pi\}$ and $\overline{\Pi}^{1}(\pi) \in Paths(v(\mathcal{A}^{n}))$, there is $(\overline{\Pi}^{2}, \leq_{\overline{\Pi}^{2}})$ satisfying $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2}), \quad Dur(\overline{\Pi}^1 - \overline{\Pi}^2) \bowtie v(\gamma),$ $(\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2}), Init(\overline{\Pi}^2(\pi)), [\eta]_{\overline{\Pi}^1 - \overline{\Pi}^2}, [\theta]_{\overline{\Pi}^1 - \overline{\Pi}^2}$ $\models_{v,\mathcal{A}^n}$ reduce^{*n*}(φ_2), and for any $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$ satisfying $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3}) \succ (\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2}),$ $(\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3}), Init(\overline{\Pi}^3(\pi)), [\eta]_{\overline{\Pi}^1 - \overline{\Pi}^3}, [\theta]_{\overline{\Pi}^1 - \overline{\Pi}^3}$ $\models_{v,\mathcal{A}^n}$

 $\{1,2,\ldots,n\}$, we have $\Pi^1(\pi_i) = \overline{\Pi}^1(\pi)|_i$ and tice that we have $\trianglelefteq_{\overline{\Pi}^1} = \oiint_{\overline{\Pi}^2}$ because of $\Pi^2(\pi_i) = \overline{\Pi}^2(\pi)|_i. \quad \text{For such } (\Pi^1, \trianglelefteq_{\Pi^1}) \text{ and } \operatorname{\mathbf{dom}}(\overline{\Pi}^1) = \operatorname{\mathbf{dom}}(\overline{\Pi}^2) = \{\pi\}. \quad \text{For such } \overline{\Pi}^2, \text{ we}$ (Π^2, \leq_{Π^2}) , we have $Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma)$ and have $(\overline{\Pi}^1, \leq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^2, \leq_{\overline{\Pi}^2})$, $Dur(\overline{\Pi}^1 - \overline{\Pi}^2) \bowtie v(\gamma)$, $(\Pi^{2}, \leq_{\Pi^{2}}), Init(\Pi^{2}(\pi_{n})), [\eta]_{\Pi^{1}-\Pi^{2}}, [\theta]_{\Pi^{1}-\Pi^{2}} \models_{v,\mathcal{A}} \varphi_{2}.$ Let $(\Pi^{3}, \leq_{\Pi^{3}})$ be a path assignment satisfy- $\Pi^{1}, \subseteq_{\Pi^{2}}, Init(\overline{\Pi}^{2}(\pi)), [\eta]_{\overline{\Pi}^{1}-\overline{\Pi}^{2}}, [\theta]_{\overline{\Pi}^{1}-\overline{\Pi}^{2}} \models_{v,\mathcal{A}} \varphi_{2}.$ $\inf_{\mathbf{I}_{1}} (\Pi^{1}, \trianglelefteq_{\Pi^{1}}) \succeq (\Pi^{3}, \trianglelefteq_{\Pi^{3}}) \succ (\Pi^{2}, \trianglelefteq_{\Pi^{2}}). \qquad \text{By} \quad reduce^{n}(\varphi_{2}). \quad \text{Let} \ (\overline{\Pi}^{3}, \trianglelefteq_{\overline{\Pi}^{3}}) \text{ be a path assignment}$ $(\overline{\Pi}^{1}, \leq_{\overline{\Pi}^{1}}) \succeq (\overline{\Pi}^{3}, \leq_{\overline{\Pi}^{3}}) \succ (\overline{\Pi}^{2}, \leq_{\overline{\Pi}^{2}}), \text{ and is a path assignment } (\Pi^{3}, \leq_{\Pi^{3}}) \text{ satisfying } \Pi^{3}(\pi_{i}) = \overline{\Pi}^{3}(\pi)|_{i} \text{ for each } i \in \{1, 2, \dots, n\}. \text{ Since } (\Pi^{1}, \leq_{\Pi^{1}}) \succeq (\Pi^{3}, \leq_{\Pi^{3}}) \succ (\Pi^{2}, \leq_{\Pi^{2}}), \text{ and } \Pi^{3}(\pi_{i}) = \overline{\Pi}^{3}(\pi)|_{i} \text{ for each } i \in \{1, 2, \dots, n\}.$ we have $\mathcal{A}^n \models_v reduce^n(\varphi_{\exists})$, for such $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$, we $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$ for each $i \in \{1, 2, \dots, n\}$. have $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$, $Init(\overline{\Pi}^3(\pi))$, $[\eta]_{\overline{\Pi}^1 - \overline{\Pi}^3}$, $[\theta]_{\overline{\Pi}^1 - \overline{\Pi}^3} \models_{v, \mathcal{A}} (\Pi^3, \leq_{\Pi^3})$, $Init(\Pi^3(\pi_n))$, $[\eta]_{\Pi^1 - \Pi^3}$, $[\theta]_{\Pi^1 - \Pi^3} \models_{v, \mathcal{A}} \varphi_1$. $reduce^n(\varphi_1)$. Since for each $i \in \{1, 2, ..., n\}$, we Since for each $i \in \{1, 2, ..., n\}$, we have have $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$, for such (Π^3, \leq_{Π^3}) , we have $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$, for such $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$, we have $(\Pi^{3}, \leq_{\Pi^{3}}), Init(\Pi^{3}(\pi_{n})), [\eta]_{\Pi^{1}-\Pi^{3}}, [\theta]_{\Pi^{1}-\Pi^{3}} \models_{v,\mathcal{A}} \varphi_{1}. \quad (\overline{\Pi}^{3}, \leq_{\overline{\Pi}^{3}}), Init(\overline{\Pi}^{3}(\pi)), [\eta]_{\overline{\Pi}^{1}-\overline{\Pi}^{3}}, [\theta]_{\overline{\Pi}^{1}-\overline{\Pi}^{3}}$ Therefore, we have $\mathcal{A} \models_v \varphi_{\exists}$.

Suppose $\mathcal{A} \models_v \varphi_{\forall}$ holds. Let $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1})$ be a path assignment satisfying $\operatorname{dom}(\overline{\Pi}^1) = \{\pi\}$ and $\overline{\Pi}^1(\pi) \in$ be a path assignment satisfying $\operatorname{dom}(\Pi^1) =$ $Paths(v(\mathcal{A}^n))$. By Lemma 28, there is a path assignditions, where $\mathcal{N}_{\leq_{\Pi}}$ is the monotone surjection from path $\rho \in Paths(v(\mathcal{A}^n))$ of $v(\mathcal{A}^n)$ satisfying the follow- $\operatorname{\mathbf{dom}}(\Pi^1) \times \mathbb{N}$ to \mathbb{N} .

- $\mathbf{dom}(\Pi^1) = \{\pi_1, \pi_2, \dots, \pi_n\}$ holds.
- For any $\pi_k \in \mathbf{dom}(\Pi^1)$, $\Pi^1(\pi_k) = \rho|_k$ holds.
- For any $i \in \mathbb{N}$, the inverse image $\mathcal{N}_{\leq_{\Pi}}^{-1}(\{i\})$ satisfies $(\pi_k, j) \in \mathcal{N}_{\triangleleft_{\Pi}}^{-1}(\{i\}) \iff e_i|_k = e_j^k$, where e_i is the *i*-th edge of ρ and e_i^k is the *j*-th edge of $\Pi^1(\pi_k).$

 $(\Pi^1, \leq_{\Pi^1}),$ there is (Π^2, \leq_{Π^2}) satisfying and $\overline{\Pi}^1(\pi) = \rho$, there is $(\overline{\Pi}^2, \leq_{\overline{\Pi}^2})$ satisfying $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^2, \trianglelefteq_{\Pi^2}), \quad Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma),$ $(\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi_n)), [\eta]_{\Pi^1 - \Pi^2}, [\theta]_{\Pi^1 - \Pi^2} \models_{v,\mathcal{A}}$ $\varphi_2, \text{ and } (\Pi^1, \trianglelefteq_{\Pi^1})$ for \succeq $(\Pi^3, \trianglelefteq_{\Pi^3}) \qquad \succ$ $(\Pi^2, \trianglelefteq_{\Pi^2}),$ $(\Pi^3, \leq_{\Pi^3}), Init(\Pi^3(\pi_n)), [\eta]_{\Pi^1-\Pi^3}, [\theta]_{\Pi^1-\Pi^3} \models_{v,\mathcal{A}} \varphi_1 \qquad \varphi_2, \text{ and}$ holds. By Lemma 29, for any such Π^2 , there is a $(\overline{\Pi}^1, \leq_{\overline{\Pi}^1})$ path ρ' of $v(\mathcal{A}^n)$ such that for each $i \in \{1, 2, \dots, n\}$, $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3}), Init(\overline{\Pi}^3(\pi)), [\eta]_{\overline{\Pi}^1 - \overline{\Pi}^3}, [\theta]_{\overline{\Pi}^1 - \overline{\Pi}^3} \models_{v, \mathcal{A}} \varphi_1$

 $(\Pi^1,\trianglelefteq_{\Pi^1}) \ \succeq \ (\Pi^2,\trianglelefteq_{\Pi^2}), \ \text{ and for each } i \ \in \ \text{such that } (\pi,i) \trianglelefteq_{\overline{\Pi}^2} (\pi,j) \quad \Longleftrightarrow \quad i \ \leq \ j.$ No-Lemma 29, for any such $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$, there satisfying $(\overline{\Pi}^1, \leq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^3, \leq_{\overline{\Pi}^3}) \succ (\overline{\Pi}^2, \leq_{\overline{\Pi}^2})$. is a path assignment $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$ satisfying By Lemma 29, for any such $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$, there $\models_{v,\mathcal{A}}$ $reduce^{n}(\varphi_{1})$. Therefore, we have $\mathcal{A}^{n} \models_{v} reduce^{n}(\varphi_{\forall})$. Suppose $\mathcal{A}^n \models_v reduce^n(\varphi_{\forall})$ holds. Let $(\Pi^1, \trianglelefteq_{\Pi^1})$ $\{\pi_1, \pi_2, \dots, \pi_n\}$ and for any $i \in \{1, 2, \dots, n\},\$ ment (Π^1, \leq_{Π^1}) of $v(\mathcal{A})$ satisfying the following con- $\Pi^1(\pi_i) \in Paths(v(\mathcal{A}))$. By Lemma 27, there is a ing conditions, where $\mathcal{N}_{\leq_{\Pi}}$ is the monotone surjection from $\mathbf{dom}(\Pi) \times \mathbb{N}$ to \mathbb{N} .

- For any $\pi_k \in \mathbf{dom}(\Pi)$, $\Pi(\pi_k) = \rho|_k$ holds.
- For any $i \in \mathbb{N}$, the inverse image $\mathcal{N}_{\leq_{\Pi}}^{-1}(\{i\})$ satisfies $(\pi_k, j) \in \mathcal{N}_{\triangleleft_{\Pi}}^{-1}(\{i\}) \iff e_i|_k = e_j^k$, where e_i is the *i*-th edge of ρ and e_j^k is the *j*-th edge of $\Pi^1(\pi_k).$

Since we have $\mathcal{A}^n \models_v reduce^n(\varphi_{\forall})$, for the extension Since we have $\mathcal{A} \models_{v} \varphi_{\forall}$, for any such $(\overline{\Pi}^{1}, \trianglelefteq_{\overline{\Pi}^{1}})$ of $(\Pi_{\emptyset}, \trianglelefteq_{\Pi_{\emptyset}})$ satisfying $\operatorname{dom}(\Pi) = \{\pi\}$ $(\overline{\Pi}^1, \leq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^2, \leq_{\overline{\Pi}^2}), \quad Dur(\overline{\Pi}^1 - \overline{\Pi}^2) \bowtie v(\gamma),$ any (Π^3, \leq_{Π^3}) satisfying $(\overline{\Pi}^2, \leq_{\overline{\Pi}^2}), Init(\overline{\Pi}^2(\pi)), [\eta]_{\overline{\Pi}^1 - \overline{\Pi}^2}, [\theta]_{\overline{\Pi}^1 - \overline{\Pi}^2}$ $\models_{v,\mathcal{A}}$ φ_2 , and for any $(\overline{\Pi}^3, \leq_{\overline{\Pi}^3})$ satisfying $\succeq \quad (\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3}) \qquad \succ \quad (\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2}),$ we have $\Pi^2(\pi_i) = \rho'|_i$. Let $\overline{\Pi}^2$ be such that holds. By Lemma 29, for any such $\overline{\Pi}^2(\pi)$, $\operatorname{dom}(\overline{\Pi}^2) = \{\pi\}, \ \overline{\Pi}^2(\pi) = \rho'$, and $\trianglelefteq_{\overline{\Pi}^2}$ is there is a path assignment $(\Pi^2, \trianglelefteq_{\Pi^2})$ such

 $(\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^2, \leq_{\Pi^2})$, and for each $i \in \{1, 2, \dots, n\}$, $\sigma^2 \bowtie lt)[\Sigma_{\text{rise}} \coloneqq 0]$ and $\neg (\sigma^1 - \sigma^2 \bowtie lt)[\Sigma_{\text{rise}} \coloneqq 0]$ to we have $\Pi^2(\pi_i)$ $= \overline{\Pi}^2(\pi)|_i.$ (Π^2, \leq_{Π^2}) , we have $Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma)$ and for appropriately chosen ℓ' and ν' . $(\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi_n)), [\eta]_{\Pi^1 - \Pi^2}, [\theta]_{\Pi^1 - \Pi^2} \models_{v,\mathcal{A}} \varphi_2.$ Let (Π^3, \leq_{Π^3}) be a path assignment satisfy- location $(p, \tilde{\eta}) \in \mathcal{P}(\Sigma) \times \{0, 1, \dots, d, d+1\}^{\Sigma}$ of \mathcal{O}_{ψ} , ing $(\Pi^1, \leq_{\Pi^1}) \succeq (\Pi^3, \leq_{\Pi^3}) \succ (\Pi^2, \leq_{\Pi^2})$. By we have $\Lambda((p, \tilde{\eta})) \cap \Sigma = p$. Moreover, since for any Lemma 29, for any such (Π^3, \leq_{Π^3}) , there transition of \mathcal{O}_{ψ} , the guard is \top , it suffices to show is a path assignment $(\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3})$ satisfying $(\overline{\Pi}^1, \trianglelefteq_{\overline{\Pi}^1}) \succeq (\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3}) \succ (\overline{\Pi}^2, \trianglelefteq_{\overline{\Pi}^2}), \text{ and }$ $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$ for each $i \in \{1, 2, \dots, n\}$. Since we have $\mathcal{A}^n \models_v reduce^n(\varphi_{\forall})$, for such $(\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3})$, we have $(\overline{\Pi}^3, \trianglelefteq_{\overline{\Pi}^3}), Init(\overline{\Pi}^3(\pi)), [\eta]_{\overline{\Pi}^1 - \overline{\Pi}^3}, [\theta]_{\overline{\Pi}^1 - \overline{\Pi}^3} \models_{v, \mathcal{A}}$ $reduce^{n}(\varphi_{1})$. Since for each $i \in \{1, 2, \ldots, n\}$, we have $\Pi^3(\pi_i) = \overline{\Pi}^3(\pi)|_i$, for such (Π^3, \leq_{Π^3}) , we have $(\Pi^3, \leq_{\Pi^3}), Init(\Pi^3(\pi_n)), [\eta]_{\Pi^1 - \Pi^3}, [\theta]_{\Pi^1 - \Pi^3} \models_{v, \mathcal{A}} \varphi_1.$ Therefore, we have $\mathcal{A} \models_v \varphi_{\forall}$.

A.2 Detailed proof of Theorem 15

Before proving Theorem 15, we show the completeness of the observers.

Lemma 30 (completeness of the observers). Let \mathcal{A} be a PTA, ψ be an Ext-PTCTL formula, and v be a $\Pi^1(\pi) \in Paths(v(\mathcal{A}))$, there is (Π^2, \leq_{Π^2}) satisfying parameter valuation for the union of the parameters in \mathcal{A} and ψ . For any path ρ of $v(\mathcal{A})$, there is a path ρ' of $v(\mathcal{A} \times \mathcal{O}_{\psi})$ satisfying $\rho'|_{v(\mathcal{A})} = \rho$, where $\rho'|_{v(\mathcal{A})}$ is the projection of ρ' to the path of $v(\mathcal{A})$.

Proof. The result of the general case is immediate from the result of the base cases (i.e., ψ is one of $LAST(\sigma_{\pi}^1) - LAST(\sigma_{\pi}^2) \bowtie$ $\sum_{\sigma \in \Sigma} \alpha_{\sigma} COUNT(\sigma_{\pi}) \qquad \bowtie$ lt,d,and $(\sum_{\sigma \in \Sigma} \alpha'_{\sigma} COUNT(\sigma_{\pi}) \mod N) \bowtie d)$, and we focus on them.

For $\psi = LAST(\sigma_{\pi}^1) - LAST(\sigma_{\pi}^2) \bowtie lt$, since Λ is the identity function, it suffices to show that for any $\ell = (pr, b) \in L = \mathcal{P}(\{\sigma^1, \sigma^2, \varphi\}) \times \{\top, \bot\} \text{ and } pr'_{\Sigma} \subseteq$ $\{\sigma^1, \sigma^2\}$ with $pr \cap \Sigma \neq pr'_{\Sigma}$ and for any clock valuation $\nu \colon \{\sigma^1, \sigma^2\} \to \mathbb{R}_{\geq 0}$, there is another clock valuation ν' and $\ell' = (pr', b') \in L$ satisfying $pr'_{\Sigma} = pr' \cap \Sigma$ and $(\ell, \nu) \rightarrow (\ell', \nu')$. Let $pr_{\Sigma} = pr \cap \Sigma$. If $pr'_{\Sigma} \subsetneq pr_{\Sigma}$, we have $(\ell, \top, \emptyset, \ell') \in E$, and $(\ell, \nu) \rightarrow (\ell', \nu')$ holds for

that $\operatorname{dom}(\Pi^1) = \operatorname{dom}(\Pi^2) = \{\pi_1, \pi_2, \dots, \pi_n\}, pr_{\Sigma}$, there are transitions from ℓ with guards $(\sigma^1 - 1)$ For such appropriate ℓ' . Therefore, $(\ell, \nu) \rightarrow (\ell', \nu')$ is satisfied

> Assume $\psi = \sum_{\sigma \in \Sigma} \alpha_{\sigma} COUNT(\sigma_{\pi}) \bowtie d$. For any that for any $p, p' \in \mathcal{P}(\Sigma)$ and $\tilde{\eta} \in \{0, 1, \dots, d, d+1\}^{\Sigma}$ with $p \neq p'$, there is $\tilde{\eta}' \in \{0, 1, \dots, d, d+1\}^{\Sigma}$ such that $((p, \tilde{\eta}), \top, \emptyset, (p', \tilde{\eta}')) \in E$, which is straightforward from the definition. The proof is similar for $\psi = \left(\sum_{\sigma \in \Sigma} \alpha'_{\sigma} COUNT(\sigma_{\pi}) \bmod N\right) \bowtie d.$

Proof of Theorem 15 is as follows.

Theorem 15 (recalled). For a PTA A, a parameter valuation $v \in (\mathbb{Q}_{\geq 0})^{\mathbb{P}}$, and a top-level Ext-PTCTL formula ψ , we have $\mathcal{A} \models_v \psi$ if and only if $\mathcal{A} \times \mathcal{O}_{\psi} \models_{v} \psi_{\text{noext}}.$

Proof of Theorem 15. Since the other cases are similar, we only show $\mathcal{A} \models_v \varphi_{\exists} \iff \mathcal{A} \times \mathcal{O}_{\psi} \models_v \varphi_{\exists \text{noext}}$ where $\varphi_{\exists} = \exists \pi. \varphi_1 \mathcal{U}_{\bowtie \gamma} \varphi_2$. Suppose $\mathcal{A} \models_v \varphi_{\exists}$ holds. By the semantics of ExtPTCTL, for some extension $(\Pi^1, \trianglelefteq_{\Pi^1})$ of $(\Pi_{\emptyset}, \trianglelefteq_{\Pi_{\emptyset}})$ satisfying **dom** $(\Pi) = \{\pi\}$ and $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^2, \trianglelefteq_{\Pi^2}), \quad Dur(\Pi^1 - \Pi^2) \bowtie v(\gamma),$ $(\Pi^2, \leq_{\Pi^2}), Init(\Pi^2(\pi)), [\eta]_{\Pi^1 - \Pi^2}, [\theta]_{\Pi^1 - \Pi^2}$ $\models_{v,A}$ any $(\Pi^3, \trianglelefteq_{\Pi^3})$ and for satisfying $\varphi_2,$ $(\Pi^1, \trianglelefteq_{\Pi^1})$ $(\Pi^3, \trianglelefteq_{\Pi^3})$ \succeq $(\Pi^2, \leq_{\Pi^2}),$ \succ $(\Pi^3, \leq_{\Pi^3}), Init(\Pi^3(\pi)), [\eta]_{\Pi^1-\Pi^3}, [\theta]_{\Pi^1-\Pi^3} \models_{v,\mathcal{A}} \varphi_1$ holds. By Lemma 30, there is a path ρ^1 of $\mathcal{A} \times \mathcal{O}_{\psi}$ satis fying $\rho^1|_{v(\mathcal{A})} = \Pi^1(\pi)$. Moreover, by taking a suitable prefix of ρ^1 , for the above Π^2 , there is a path ρ^2 of $\mathcal{A} \times \mathcal{O}_{\psi}$ satisfying $\rho^2|_{v(\mathcal{A})} = \Pi^2(\pi)$. For any ρ^3 satisfying $\rho^1 \succeq \rho^3 \succ \rho^2$, since we have $\rho^1|_{v(\mathcal{A})} = \Pi^1(\pi)$ and $\rho^2|_{v(\mathcal{A})} = \Pi^2(\pi)$, by taking a suitable prefix of $\Pi^1(\pi)$, there is a path assignment (Π^3, \leq_{Π^3}) satisfying $(\Pi^1, \trianglelefteq_{\Pi^1}) \succeq (\Pi^3, \trianglelefteq_{\Pi^3}) \succ (\Pi^2, \trianglelefteq_{\Pi^2})$ and $\rho^3|_{\nu(\mathcal{A})} = \Pi^3(\pi)$. Overall, by Lemma 14, for some extension $(\Pi^1_{\mathcal{O}}, \trianglelefteq_{\Pi^1_{\mathcal{O}}})$ of $(\Pi_{\emptyset}, \trianglelefteq_{\Pi_{\emptyset}})$ satisfying $\operatorname{dom}(\Pi) = \{\pi\}$ and $\Pi^1_{\mathcal{O}}(\pi) \in$ $Paths(v(\mathcal{A} \times \mathcal{O}_{\psi})), \text{ there is } (\Pi^2_{\mathcal{O}}, \leq_{\Pi^2_{\mathcal{O}}}) \text{ satisfy-}$ $ing (\Pi^1_{\mathcal{O}}, \trianglelefteq_{\Pi^1_{\mathcal{O}}}) \succeq (\Pi^2_{\mathcal{O}}, \trianglelefteq_{\Pi^2_{\mathcal{O}}}), Dur(\Pi^1_{\mathcal{O}} - \Pi^2_{\mathcal{O}}) \bowtie v(\gamma),$ $\nu' = \nu \text{ and } \ell' = (pr'_{\Sigma} \cup (pr \cap \{\psi\}), \top). \text{ If } pr'_{\Sigma} \not\subseteq (\Pi^2_{\mathcal{O}}, \leq_{\Pi^2_{\mathcal{O}}}), Init(\Pi^2_{\mathcal{O}}(\pi)), [\eta]_{\Pi^1_{\mathcal{O}} - \Pi^2_{\mathcal{O}}}, [\theta]_{\Pi^1_{\mathcal{O}} - \Pi^2_{\mathcal{O}}} \models_{v, \times \mathcal{O}_{\psi}} (pr \cap \{\psi\}), \forall v \in \mathcal{O}_{\mathcal{O}}, \forall v \in \mathcal{O}, \forall v$ $\begin{array}{lll} \varphi_{2\,\text{noext}}, & \text{and for any } (\Pi^{3}_{\mathcal{O}}, \trianglelefteq_{\Pi^{3}_{\mathcal{O}}}) & \text{satisfying} \\ (\Pi^{1}_{\mathcal{O}}, \trianglelefteq_{\Pi^{1}_{\mathcal{O}}}) \succeq (\Pi^{3}_{\mathcal{O}}, \trianglelefteq_{\Pi^{3}_{\mathcal{O}}}) \succ (\Pi^{2}_{\mathcal{O}}, \trianglelefteq_{\Pi^{2}_{\mathcal{O}}}), & \text{we have} \\ (\Pi^{3}_{\mathcal{O}}, \trianglelefteq_{\Pi^{3}_{\mathcal{O}}}), Init(\Pi^{3}_{\mathcal{O}}(\pi)), [\eta]_{\Pi^{1}_{\mathcal{O}} - \Pi^{3}_{\mathcal{O}}}, [\theta]_{\Pi^{1}_{\mathcal{O}} - \Pi^{3}_{\mathcal{O}}} \models_{v, \mathcal{A} \times \mathcal{O}_{\psi}} \\ \varphi_{1\,\text{noext}}. & \text{Therefore, we have } \mathcal{A} \times \mathcal{O}_{\psi} \models_{v} \varphi_{\exists\,\text{noext}}. \end{array}$

Suppose $\mathcal{A} \times \mathcal{O}_{\psi} \models_{v} \varphi_{\exists_{noext}}$ holds. By the semantics of PTCTL, for some extension $(\Pi^1_{\mathcal{O}}, \trianglelefteq_{\Pi^1_{\mathcal{O}}})$ of $(\Pi_{\emptyset}, \leq_{\Pi_{\emptyset}})$ satisfying **dom** $(\Pi) = \{\pi\}$ and $\Pi^{1}_{\mathcal{O}}(\pi) \in$ $Paths(v(\mathcal{A} \times \mathcal{O}_{\psi}))$, there is $(\Pi^2_{\mathcal{O}}, \trianglelefteq_{\Pi^2_{\mathcal{O}}})$ satisfying $(\Pi^1_{\mathcal{O}}, \trianglelefteq_{\Pi^1_{\mathcal{O}}}) \succeq (\Pi^2_{\mathcal{O}}, \trianglelefteq_{\Pi^2_{\mathcal{O}}}), \ Dur(\Pi^1_{\mathcal{O}} - \Pi^2_{\mathcal{O}}) \bowtie v(\gamma),$ $(\Pi^2_{\mathcal{O}}, \trianglelefteq_{\Pi^2_{\mathcal{O}}}), Init(\Pi^2_{\mathcal{O}}(\pi)), [\eta]_{\Pi^1_{\mathcal{O}}-\Pi^2_{\mathcal{O}}}, [\theta]_{\Pi^1_{\mathcal{O}}-\Pi^2_{\mathcal{O}}} \models_{v, \times \mathcal{O}_{\psi}}$ any $(\Pi^3_{\mathcal{O}}, \trianglelefteq_{\Pi^3_{\mathcal{O}}})$ satisfyand for $\varphi_{2\text{noext}},$ $\succeq (\Pi^3_{\mathcal{O}}, \trianglelefteq_{\Pi^3_{\mathcal{O}}}) \succ (\Pi^2_{\mathcal{O}}, \trianglelefteq_{\Pi^2_{\mathcal{O}}}),$ ing $(\Pi^1_{\mathcal{O}}, \trianglelefteq_{\Pi^1_{\mathcal{O}}})$ $(\Pi^3_{\mathcal{O}}, \trianglelefteq_{\Pi^3_{\mathcal{O}}}), Init(\Pi^3_{\mathcal{O}}(\pi)), [\eta]_{\Pi^1_{\mathcal{O}} - \Pi^3_{\mathcal{O}}}, [\theta]_{\Pi^1_{\mathcal{O}} - \Pi^3_{\mathcal{O}}} \models_{v, \mathcal{A} \times \mathcal{O}_{\psi}}$ φ_{1noext} holds. By Lemma 14, the satisfaction of the new propositions in $\Pi^1_{\mathcal{O}}(\pi)$ and $\Pi^2_{\mathcal{O}}(\pi)$ coincide with the satisfaction of the extended predicates in $\Pi^1_{\mathcal{O}}(\pi)|_{v(\mathcal{A})}$ and $\Pi^2_{\mathcal{O}}(\pi)|_{v(\mathcal{A})}$, respectively. By Lemma 30, for any ρ^3 satisfying $\Pi^1_{\mathcal{O}}(\pi)|_{v(\mathcal{A})} \succeq \rho^3 \succeq \Pi^2_{\mathcal{O}}(\pi)|_{v(\mathcal{A})}$, there is an path assignment $(\Pi^3_{\mathcal{O}}, \trianglelefteq_{\Pi^3_{\mathcal{O}}})$ satisfying $(\Pi^1_{\mathcal{O}}, \trianglelefteq_{\Pi^1_{\mathcal{O}}}) \succeq (\Pi^3_{\mathcal{O}}, \trianglelefteq_{\Pi^3_{\mathcal{O}}}) \succ (\Pi^2_{\mathcal{O}}, \trianglelefteq_{\Pi^2_{\mathcal{O}}})$ and $\Pi^3_{\mathcal{O}}|_{v(\mathcal{A})} = \rho^3$. Overall, we have $\mathcal{A} \models_v \varphi_{\exists}$.

B Omitted definition

B.1 Syntax of Nest-Free RPExt-HyperPTCTL

Definition 31 (Syntax of Nest-Free RPExt-Hyper-PTCTL). For atomic propositions Σ and parameters \mathbb{P} , the syntax of Nest-Free RPExt-HyperPTCTL formulas of the Boolean level \mathcal{B} , the temporal level φ , and the top level ψ are defined as follows, where $\sigma \in \Sigma, \gamma \in \mathbb{P} \cup \mathbb{N}, n \in \mathbb{N}, p \in \mathbb{P}$, and lt is a linear term over \mathbb{P} :

$$\begin{split} \mathcal{B} &::= \top \mid \sigma_{\pi} \mid COUNT(\sigma_{\pi}) \bowtie n \\ \mid LAST(\sigma_{\pi}) - LAST(\sigma_{\pi}) \bowtie n \mid \neg \mathcal{B} \mid \mathcal{B} \lor \mathcal{B} \\ \varphi &::= \exists \pi_{1}, \pi_{2}, \dots, \pi_{n}. \mathcal{B} \mathcal{U}_{\bowtie \gamma} \mathcal{B} \\ \mid \forall \pi_{1}, \pi_{2}, \dots, \pi_{n}. \mathcal{B} \mathcal{U}_{\bowtie \gamma} \mathcal{B} \\ \psi &::= \varphi \mid p \bowtie lt_{\geq 0} \mid \neg \psi \mid \psi \lor \psi \mid \tilde{\exists} p \psi \end{split}$$