StyleRemix: Interpretable Authorship Obfuscation via Distillation and Perturbation of Style Elements

Jillian Fisher* \heartsuit Skyler Hallinan* \heartsuit Ximing Lu \heartsuit * Mitchell Gordon \heartsuit Zaid Harchaoui♡ Yejin Choi♡♣ $\%$ University of Washington \bullet Allen Institute for AI {jrfish, hallisky}@uw.edu

Abstract

Authorship obfuscation, rewriting a text to intentionally obscure the identity of the author, is an important but challenging task. Current methods using large language models (LLMs) lack interpretability and controllability, often ignoring author-specific stylistic features, resulting in less robust performance overall.

To address this, we develop STYLEREMIX, an adaptive and interpretable obfuscation method that perturbs specific, fine-grained *style elements* of the original input text. STYLEREMIX uses pre-trained Low Rank Adaptation (LoRA) modules to rewrite an input specifically along various stylistic axes (e.g., formality and length) while maintaining low computational cost. STYLEREMIX outperforms state-of-theart baselines and much larger LLMs in a variety of domains as assessed by both automatic and human evaluation.

Additionally, we release AUTHORMIX, a large set of 30K high-quality, long-form texts from a diverse set of 14 authors and 4 domains, and DISC, a parallel corpus of 1,500 texts spanning seven style axes in [1](#page-0-0)6 unique directions¹.

1 Introduction

Authorship obfuscation, the act of rewriting text to conceal the author, is an important method for preserving the privacy of authors in sensitive contexts, e.g., anonymous discussion forums, double-blind reviews, and health services. However, it is inherently complex, requiring a substantial change in writing style to obscure the author's identity while also preserving the original content and fluency.

Historically, authorship obfuscation methods have manipulated aspects of an author's style to

Style Axis Data Rewrite Input Sounds perfect! $\mathbf{O}_{\mathbf{A}}$ erse inputs/outputs in DISC dataset w/LM Sarcasm **Style Axes** Formality ...perfect. Appears ideal Generated ↓ Sounds great Perf! Data Adapters **Train Style** Formality Models Classifiers AUTHORMIX dataset, collected from **Author Style Data** Author Texts Style Classifiers $\overline{0.25}$ $\overline{\bullet}$ 0.28 $\overline{0.44}$ **Author Style** 0.93 0.61 \blacksquare 0.08 wet Vector 2) Obfuscation Oh, how I just adore listening to jazz! Input $\ddot{\bullet}$ \blacksquare Author/Text **Style Vector** $|0.25 0.93 ...|$ Difference $=$ \mid -0.07 0.39 Vector Mean 0.32 0.54 .. **Style Vector**

1) Pre-Obfuscation

Figure 1: Overview of STYLEREMIX. In preobfuscation, distinct *style elements* are distilled from an LM into individual training sets, which are used to train specialized LoRA adapters. During obfuscation, the user can automatically or manually select the style adapter(s) which, when combined with the base LM, will best steer generations away from the original style.

^{*}Co-first authors

¹We release 1) our code at [https://github.com/](https://github.com/jfisher52/StyleRemix) [jfisher52/StyleRemix](https://github.com/jfisher52/StyleRemix) 2) a demo of STYLEREMIX at [https://huggingface.co/spaces/hallisky/](https://huggingface.co/spaces/hallisky/StyleRemix) [StyleRemix](https://huggingface.co/spaces/hallisky/StyleRemix) and 3) the datasets (AUTHORMIX and DISC) and trained models in a [HuggingFace collection](https://huggingface.co/collections/hallisky/authorship-obfuscation-66564c1c1d59bb62eaaf954f)

obfuscate the original text [\(Karadzhov et al.,](#page-10-0) [2017;](#page-10-0) [Shetty et al.,](#page-11-0) [2017;](#page-11-0) [Bevendorff et al.,](#page-9-0) [2019\)](#page-9-0). These techniques typically use style aspects that are easy to automatically evaluate, such as text length, capitalization frequency, and punctuation, to alter the original text. However, these rule-based methods are often too rigid and lead to a degradation of fluency and grammaticality [\(Fisher et al.,](#page-9-1) [2024\)](#page-9-1).

Recent work demonstrates strong obfuscation performance using LLMs [\(Mahmood et al.,](#page-11-1) [2019;](#page-11-1) [Haroon et al.,](#page-9-2) [2021;](#page-9-2) [Weggenmann et al.,](#page-12-0) [2022;](#page-12-0) [Fisher et al.,](#page-9-1) [2024\)](#page-9-1), but the common challenge among these is a relative lack of interpretability and controllability on the obfuscation; these approaches do not incorporate any author-specific stylometric characteristics of the original author, leading to more generalized and ineffective obfuscations. For example, a method that relies solely on increasing language model fluency might effectively obfuscate more informal writing, but not formal writing.

To address this gap, we introduce STYLEREMIX, an interpretable, inferencetime, author-specific obfuscation method that combines the fluency and steerability of LLMs with author-specific style information. STYLEREMIX first detects unique stylistic elements of the author, either through automatic processes or manually. It then uses this information during obfuscation by integrating style-specific adapters with a base language model (an LLM) to guide the generated text away from the author's original style.

STYLEREMIX avoids high computational costs by utilizing pre-trained Low Rank Adaptation modules (LoRA; [Hu et al.,](#page-10-1) [2021\)](#page-10-1), which we train to rewrite inputs towards specific directions on various stylistic axes (e.g., more/less length, more/less formality, higher/lower grade level). Drawing inspiration from the process of creating a *remix*, where musical elements of a song, such as tempo, key, and instrumentation are adjusted to form an entirely new track, in this work we seek to identify and manipulate different elements of an authorship style, and propose a simple yet effective approach to steer different components of the text with LoRA adapters. Our results show that STYLEREMIX outperforms state-of-the-art authorship obfuscation methods and instruction-based models of similar and larger sizes. Additionally, our method has the added benefit of explainability and is customizable to any unique authorship style.

We make the following contributions:

- (I) We introduce STYLEREMIX, an interpretable, inference-time algorithm designed for authorship obfuscation. This method offers the personalization and flexibility required for effectiveness across various styles and text types.
- (II) We release two datasets:

(1) AUTHORMIX, a comprehensive authorship dataset with over 30K paragraphs spanning four diverse domains (presidential speeches, novels, scholarly articles, and blogs) and 14 author styles, encompassing many more domains and styles than any previous work to our knowledge.

(2) DISTILLED STYLE COMPONENTS DATASET (DISC), a high-quality, validated, parallel dataset over 7 style axes. It features $n = 1.500$ texts rewritten towards 16 distinct style directions for a total corpus size of 24K.

2 Methods

STYLEREMIX is an obfuscation method that leverages *style elements* to adapatively rewrite texts. Specifically, it incorporates information about the style of the original author to guide the obfuscation process. Figure [1](#page-0-1) illustrates this new approach, which consists of two phases.

The pre-obfuscation phase, conducted only once regardless of the number of authors, involves creating a diverse training set for each style axis we aim to modify (e.g., length variations, formality levels, grade level adjustments, etc.). These style-specific datasets are then used to train Low-Rank Adaptation (LoRA) adapters, which are low-parameter modules that can be seamlessly integrated with a larger base model to guide text generation along specific style axes.

In the obfuscation phase, users can choose the style axes that most effectively disguise the original author's style, either automatically or manually. The selected pre-trained LoRA adapters are then used to steer the obfuscated text generation.

2.1 Stage 1: Pre-Obfuscation

Style Axes When selecting the style axis, our goal is to identify "author invariants", which are text properties that are unique to a specific author. The widely accepted author invariants in the field of stylometry (the study of authorship style) in-clude text length and the use of function words^{[2](#page-1-0)}

² Function words are words that express grammatical relationships among other words (if, up, would, etc.).

Figure 2: We compare generations from rewriting a text from AUTHORMIX-Speech using each of the style axis adapters *individually*. This demonstrates the distinct transformation capabilities of each adapter, highlighting variations in tone, formality, and other linguistic features. We choose the direction of the style axes based on the automatic style selection method described in Section [2.2.](#page-3-0)

[\(Peng and Hengartner,](#page-11-2) [2002\)](#page-11-2). Additionally, we incorporate "grade level," which primarily measures discrete features like the number of syllables and sentence and word lengths. Since this measure can vary slightly, we averaged three similar metrics: the Flesch-Kincaid (FK; [Flesch,](#page-9-3) [1948\)](#page-9-3), Linsear Write (L; [O'Hayre\)](#page-11-3), and the Gunning Fog Index (GF; [Gunning,](#page-9-4) [1952\)](#page-9-4) metrics. For the exact formulas, see Appendix [C.1.](#page-16-0)

Beyond formula-based properties, we also explore more abstract style axes such as the use of sarcasm, formality, voice (passive or active), and writing type (persuasive, descriptive, narrative, and expository). Due to the lack of existing formulas, we train model-based classifiers to measure these properties. More details on the training of these models can be found in Appendix [C.1.](#page-16-0)

In total, we identify seven style axes, each with two directions ("higher" or "lower"), except writing style, which has four options. This results in 16 distinct style elements. We acknowledge that this is not an exhaustive list of all author invariants, but we observed noticeable differentiation among the authors in our experimentation using these metrics. For more details, see Appendix [B.5.](#page-14-0)

Adapter Training Data With the above style axes chosen, we create DISC, a 16-style-element parallel dataset which distills each style element from a large LLM. To standardize the style adapter and minimize content dependencies, we create a single base training set and used instruction prompting with a LLM to generate rewrites along the chosen style axes. The base dataset comprises a diverse range of domains to encompass different writing

types. Specifically, we randomly sample 500 paragraphs from sources including Wikipedia, books and plays (Kryściński et al., [2021\)](#page-10-2), and diary-style blogs [\(Schler et al.,](#page-11-4) [2006a\)](#page-11-4). Each paragraph is cleaned and standardized, resulting in paragraphs of 2-5 sentences each. Using GPT-4 Turbo [\(Ope](#page-11-5)[nAI,](#page-11-5) [2023\)](#page-11-5), we then generate new versions of these paragraphs along different style axes and directions ("higher" or "lower") using detailed instruction prompt tuning (see Appendix [C.2\)](#page-16-1). This results in 16 parallel datasets written in different style axis and directions.

Next, we evaluate the generated paragraphs to ensure that they accurately reflect the intended style axis and direction. Table [1](#page-3-1) presents the evaluation results, both automatic and human, for the style training datasets created. The results demonstrate that our datasets effectively capture the desired styles. See Appendix [C.2](#page-16-1) for more details.

Train LoRA Adapters Next, our goal is to train the models to generate text along the chosen style axes. To minimize computational cost [\(Strubell](#page-11-6) [et al.,](#page-11-6) [2019\)](#page-11-6), we bypass model fine-tuning and instead employ *Low Rank Adapation* (LoRA; [Hu](#page-10-1) [et al.,](#page-10-1) [2021\)](#page-10-1) adapters for each of the style axes. By freezing the base model and tuning only a small portion of injected features, LoRA guarantees lightweight training [\(Rebuffi et al.,](#page-11-7) [2017;](#page-11-7) [Houlsby et al.,](#page-10-3) [2019\)](#page-10-3) while also incurring *no additional inference latency*, ensuring both efficient training and deployment. We use Llama-3 8B [\(AI@Meta,](#page-9-5) [2024\)](#page-9-5) as our base model, and train LoRA adapters on top of them for each direction on the style axes. See Appendix [C.3](#page-17-0) for more train-

Table 1: Evaluation of the parallel style training datasets. Automatic evaluation (top) is shown for the original score, as well as the score for the dataset that had instruction to increase (More) or decrease (Less) the given style axis. The highest value is bolded and the lowest value is underlined. Other style axes required human evaluation (below). For this we randomly combine 10% of the high and low datasets (or all four types for Writing Type) and ask three NLP experts to label whether the style axis was high or low; average accuracy is shown.

ing details.

2.2 Stage 2: Obfuscation

Style Axes and Weights Selection During the obfuscation phase, a text or set of texts is presented for obfuscation. If a user has a clear idea of which style axes to adjust, they can input their desired styles and the corresponding weights of the adapters to control the strength of the generation. However, since this information is often unavailable, we develop a straightforward yet effective method for selecting which style axes to modify and the magnitude of the weights of these adapters.

For the given m authors in some genre (e.g. speech, novel), we first create an author vector $x_i \in \mathbb{R}^7$ for each author, which is composed of the automatic evaluation of the seven style axes. After normalizing with respect to all m authors, we calculate the "difference" vector between each author and the average, defined as $\bar{x}_i = x_i - \frac{1}{n}$ $\frac{1}{m}\sum_{j=1}^m \bm{x_j}.$ Using the absolute values in this difference vector $|\bar{x}_i|$, users can select the top k style axes where the specific author deviates most from the average.

Next, the user needs to specify the weight for each chosen style adapter to merge with the base model. This procedure could be manual, but we also provide a heuristic to determine the weights automatically. Building on prior work, we find that LoRA adapters perform well with values in the range [-1.5, 1.5] [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4). Next, we use the number of standard deviations an author vector deviates from the average to map each style axis to a set of predetermined weights w_i . Specifically,

For detailed implementation, see Appendix [C.5.](#page-18-0)

Generation Techniques During generation, we use the adapters corresponding to the selected style axes to rewrite the given text, steering these prominent styles toward the average. In addition, we experiment with multiple methods for combining these LoRA adapters.

- Sequential: We pass in the text through a sequence of adapters iteratively; the output from one adapter serves as the input for the next. This method provides additional interpretability by revealing how the text becomes obfuscated at different stages after altering specific style axes. However, it increases computation time, as it requires a forward pass for each chosen style axis.
- Adapter Merging (AM): We merge the weights of all the adapters before combining them with the base model by *concatenating* their weights [\(Yadav et al.,](#page-12-1) [2023a;](#page-12-1) [Yu et al.,](#page-12-2) [2024\)](#page-12-2). See Appendix [C.4](#page-17-1) for more details.
- Lora H ub⁺: Lora H ub is a framework designed to assemble multiple LoRA adapters with the goal of maximizing performance on specific tasks [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4). It adjusts the weights of the given adapters to optimize the specified objective through gradient-free optimization. We extend this with $LoraHub^+,$ which defines a new objective function L designed to optimize for obfuscation by summing up the automatic evaluations of the selected style axes across a small set of test examples. We also add the fluency score to encourage more fluent text:

$$
L = \sum_{v_i \in \text{selected axes}} \begin{cases} v_i & v_i \leq \frac{1}{m} \sum_{j=1}^m x_i \\ 1 - v_i & v_i > \frac{1}{m} \sum_{j=1}^m x_i \\ + \alpha \cdot s_f & \end{cases}
$$

where v_i represents the automatic evaluation for a selected style axis on the subset of test examples, s_f represents fluency score, and α denotes the discount factor. LoraHub⁺ is used *in conjunction* with adapter merging.

Merging multiple adapters with concatenation is computationally efficient. Specifically, we find that

Model		Llama-2-Chat		Llama-3-Inst	Gemma-Inst	Paraphrase	МT	Stylo	,JD	STYLEREMIX		
Size	7B	13B	8B	70B	7B					Seq.	AM	$AM + LoraHub+$
AUTHORMIX-Speech												
Drop Rate	18.2	24.0	17.6	16.8	23.1	24.1	10.3	15.1	29.2	34.9	41.2	31.4
Grammar	67.8	67.1	67.1	70.2	67.8	71.2	54.9	37.8	56.7	61.7	66.5	63.9
Content	83.8	80.8	80.8	80.2	78.6	83.9	89.1	89.5	56.4	71.3	77.3	73.9
Overall	10.3	13.0	9.5	9.5	12.3	14.4	5.1	5.1	9.4	15.3	21.2	14.8
						AUTHORMIX- Novels						
Drop Rate	12.2	13.7	9.2	11.3	13.3	10.8	7.0	13.5	24.9	19.3	28.6	35.6
Grammar	71.8	73.8	73.1	75.4	70.0	68.3	46.3	36.8	61.2	72.6	68.1	63.5
Content	82.9	80.7	83.1	81.5	81.9	81.3	85.2	88.1	58.6	83.7	76.1	72.9
Overall	7.3	8.2	5.6	6.9	7.6	6.0	2.8	4.4	8.9	11.8	14.8	16.5
						AUTHORMIX-Scholar						
Drop Rate	0.8	1.5	1.6	2.5	0.0	0.8	1.5	4.6	6.1	1.8	9.2	11.5
Grammar	64.3	64.9	64.1	66.6	65.3	69.1	54.5	31.0	62.3	65.8	48.6	44.7
Content	91.7	89.7	88.9	84.0	88.9	91.3	92.8	85.8	60.6	78.0	75.3	68.8
Overall	0.5	0.9	0.9	1.4	0.0	0.5	0.8	1.2	2.3	0.9	3.4	3.5
						AUTHORMIX-Blog						
Drop Rate	17.7	21.3	21.8	18.9	27.5	22.2	9.4	12.1	56.4	34.4	41.0	42.0
Grammar	68.4	69.1	71.3	74.0	69.0	69.8	41.9	29.1	60.6	66.7	64.9	65.3
Content	82.5	79.0	78.1	77.8	77.8	80.4	83.7	85.8	45.1	72.1	73.7	74.2
Overall	10.0	11.6	12.1	10.9	14.8	12.5	3.3	3.0	15.4	16.5	19.6	20.4

Table 2: Comparison of obfuscation methods measured by mean drop rate, grammar, meaning similarity, and overall (the mean product of the metrics), across STYLEREMIX and comparatively sized or larger baselines on each subset of AUTHORMIX. Bold and underline denote the highest and the second-highest score respectively in each row. All metrics displayed in the table are multiplied by 100 for easier viewing of significant figures.

merging four adapters with the base model (using AM) takes less than 5 seconds on average.

3 Experiments

3.1 Datasets

We aimed to test how authorship obfuscation methods perform on a diverse array of author styles and domains. To this end, we develop a new benchmark dataset called AUTHORMIX, covering four distinct domains: presidential speeches, early-1900s fiction novels, scholarly articles, and diary-style blogs. Together, AUTHORMIX contains more than 30 k high-quality paragraphs from 14 authors.

For the presidential domain, we curate and clean speeches from George W. Bush, Barack Obama, and Donald Trump^{[3](#page-4-0)}. For novel domain, we choose a collection of early 1900s fiction writers with strong writing styles: Ernest Hemingway, F. Scott Fitzgerald, and Virginia Woolf. We choose these specific writers in an effort to limit the topic bias in the evaluation metrics.

Lastly, we alter two existing datasets to match the formality of our new domains: the Extended-Brennan Greenstad [\(Brennan et al.,](#page-9-6) [2012\)](#page-9-6), a collection of "scholarly" short (500-word) paragraphs

gathered from Amazon Mechanical Turk (AMT), and the Blog Authorship corpus [\(Schler et al.,](#page-11-8) [2006b\)](#page-11-8), a collection of blogs (diary-style entries) that were posted to blog.com. More details can be found in Appendix [D.3.](#page-20-0)

3.2 STYLEREMIX Configurations

We compare three versions of STYLEREMIX: sequential, adapter merging, and LoraHub+. For sequential, to account for the order of the styles, we average over $n = 3$ shuffled orders. The adapter merging method uses the static standard deviation mapping method described in Section [2.2.](#page-3-0) For these two methods, we select the best method per domain (based on the overall score) using the top $k = 1, 2, 3, 4$ changed styles. Lastly, we run our customized LoraHub method (LoraHub⁺), matching the best styles per domain as the base adapter merging method for direct comparison.

3.3 Baselines

We compare against both SOTA obfuscation methods and equal and larger-size LLMs using instructions. Full details can be found in Appendix [D.](#page-18-1)

Stylometric (Stylo) We use the stylometric obfuscation technique presented by [Karadzhov et al.](#page-10-0) [\(2017\)](#page-10-0), which examines various statistical features

³We select these presidents/authors due to their diverse styles but similar eras to minimize content discrepancies.

that characterize a writer's style, such as sentence length and word frequency, and then modifies the text to align these features with an "average" value, which is established using a training dataset.

Machine Translation (MT) [Keswani et al.](#page-10-5) [\(2016\)](#page-10-5) introduce *round-trip machine translation* by translating a text from English to German, then to French, and then back to English. We use the new M2M translation models [\(Fan et al.,](#page-9-7) [2020\)](#page-9-7).

Paraphraser (Paraphrase) We use the T5-Large paraphraser introduced by [Jung et al.](#page-10-6) [\(2024\)](#page-10-6) which iteratively improves through self-distillation.

JAMDEC (**JD**) This method [\(Fisher et al.,](#page-9-1) [2024\)](#page-9-1) relies on a smaller LLM, GPT2-XL [\(Radford et al.,](#page-11-9) [2019\)](#page-11-9) to overgenerate many new rewrites given the keywords from the original text. It then uses a filter to select the best new rewrite. We run this method using the default settings, and a beam width of 10.

Instruction-tuned LLMs We compare against a suite of instruction-tuned LLMs including Llama-2-Chat (7B, 13B) [\(Touvron et al.,](#page-12-3) [2023\)](#page-12-3), Llama-3- Instruct (8B, 70B) [\(AI@Meta,](#page-9-5) [2024\)](#page-9-5), and Gemma-Instruct (7B) [\(Team et al.,](#page-11-10) [2024\)](#page-11-10). For each model, we provide instruction to "rewrite" the given text. More comparisons of different models can be found in the Appendix [B.2.](#page-13-0) Exact instructions used for generation can be found in Appendix [D.](#page-18-1)

3.4 Automatic Evaluations

In line with previous work, we evaluate authorship obfuscation on four main criteria: obfuscation, con-tent preservation, grammaticality, and overall^{[4](#page-5-0)}. See Appendix [D.5](#page-21-0) for more details.

Obfuscation Classifiers with various machine learning architectures have been used to measure obfuscation [\(Mahmood et al.,](#page-11-1) [2019;](#page-11-1) [Haroon et al.,](#page-9-2) [2021;](#page-9-2) [Fisher et al.,](#page-9-1) [2024\)](#page-9-1). Recent work in authorship obfuscation and style transfer often uses RoBERTa [\(Liu et al.,](#page-10-7) [2019\)](#page-10-7) classifiers [\(Xing et al.,](#page-12-4) [2024a;](#page-12-4) [Uchendu et al.,](#page-12-5) [2021;](#page-12-5) [Liu and May,](#page-10-8) [2024;](#page-10-8) [Hallinan et al.,](#page-9-8) [2023\)](#page-9-8).

In line with this previous work, we fine-tune four RoBERTa large (355M) models, one for each domain in AUTHORMIX; classifiers achieve on average 94.0% accuracy in the evaluation set of each respective domain (for full results, see Appendix [D.5\)](#page-21-0). Using these classifiers, we calculate the drop rate, which is the normalized decrease in the classifier's accuracy when comparing its performance on the original texts to the obfuscated texts. The drop rate can be expressed as:

Drop Rate =
$$
\frac{acc_{\text{orig}} - acc_{\text{obj}}}{acc_{\text{orig}}}
$$

We also report evaluation using an alternative metric to measure obfuscation based on universal authorship representations [\(Soto et al.,](#page-11-11) [2021\)](#page-11-11) in Appendix [F;](#page-23-0) these results corroborate our main findings in [§3.6.](#page-6-0)

Content Preservation We use the embedding similarity of the inputs and their obfuscations in Sentence Transformers [\(Reimers and Gurevych,](#page-11-12) [2019\)](#page-11-12) to gauge semantic similarity.

Language Quality We measure grammaticality via the probability of being grammatically acceptable from TextAttack [\(Morris et al.,](#page-11-13) [2020\)](#page-11-13), a binary RoBERTa-large classifier fine-tuned on the Corpus of Linguistic Acceptability [\(Warstadt et al.,](#page-12-6) [2018\)](#page-12-6).

Overall Task Score The overall success of each obfuscation is measured by the product of the above three metrics: drop rate, similarity score, and CoLA score. This product ensures a high overall task score accurately reflects high scores in all three categories; it is also used in prior work in text rewriting [\(Krishna et al.,](#page-10-9) [2020a;](#page-10-9) [Hallinan et al.,](#page-9-8) [2023;](#page-9-8) [Patel et al.,](#page-11-14) [2023;](#page-11-14) [Xu et al.,](#page-12-7) [2018\)](#page-12-7)

3.5 Human Evaluation

We also conduct human evaluation to verify the quality of the obfuscations from the best STYLEREMIX variant and comparably sized baselines; we omit . We randomly select $n = 20$ texts from each author in AUTHORMIX for annotation via Amazon Mechanical Turk by three workers each. Following the setup of [Fisher et al.](#page-9-1) [\(2024\)](#page-9-1), we instruct each annotator to read both the original and obfuscated text, then respond to five questions rated on a three-point Likert scale (0, 0.5, or 1), measuring grammar, fluency, high content preservation, low content addition, and obfuscation. We discard evaluations where all annotators disagree on the label^{[5](#page-5-1)}. Lastly, we calculate an *overall* score using the weighted product of all five metrics. Further details can be found in Appendix [E.](#page-22-0)

 4 All metrics are bounded between 0 and 1, which ensures the product has the same bounds. Although similarity scores are theoretically bounded from -1 to 1, we observe empirically across all datasets and methods that they are bounded more strictly between 0 and 1; see Appendix [D.5](#page-21-0) for more details

⁵ Pairwise agreement is greater than 93% for all questions

Figure 3: Human evaluation results for mean grammar, fluency, content preserved, less content added, and obfuscation. For each of the metrics, *higher* is better. We also compute the mean overall score, the product of grammar, content preserved, and less style similarity.

3.6 Main Results

STYLEREMIX has the highest overall task score and obfuscation drop rate Table [2](#page-4-1) compares STYLEREMIX to LLMs of all sizes and the four SOTA authorship obfuscation methods on obfuscation, content preservation, grammar, and overall task score. STYLEREMIX has on average 5.5% higher overall task score and up to 12% higher obfuscation drop rate on all domains, with similar scores on content preservation and grammar. Impressively, STYLEREMIX is also more effective at obfuscation than LLMs of much larger magnitudes – such as Llama-2-Chat 13B and Llama-3-Instruct 70B – especially on the Blog domain with a \sim 10% higher overall task score. This shows how a more targeted approach can outperform larger but more generic methods.

Human evaluation shows STYLEREMIX outputs the best overall and most obfuscated generations Figure [3](#page-6-1) shows the result of our human evaluation. All methods have strong grammar and fluency scores, with only slight differences between them. STYLEREMIX beats all other baselines in obfuscation with a score of 83.0%, and ranks second for content preservation, trailing by just 0.4 points behind the significantly larger LLama-3-Instruct 70B. Notably, STYLEREMIX even surpasses the larger Llama-3-Instruct 70B in obfuscation, content preservation, and grammar. In terms of less content added, STYLEREMIX still outperforms strong baselines like Llama-3-Instruct 8B, but loses slightly to

Method	Generation
Original (Blog 3)	100%! I was surprised, but not complaining lol. But yeah Mr. Curphey's now on crutches, hobbling around the classroom and still teaching us like his usual self.
MТ	100 per cent! I was surprised, but I don't complain lol. But yes, Mr. Curphey is now in the gardens to walk through the classrooms and still teach us as his ordinary self.
Stylo.	One hundred percent; i was surprised, but not complaining II, as but yeah Mr. murphy 's now on crutches, sobbing around the classroom and always
JD.	teaching us like his usual self. 100%! I was surprised, but not complaining lol. But yeah Mr. Curphey's now on crutches, hobbling around the classroom and still teaching us like
Para.	his usual self. Mr. Curphey is currently using crutches in the classroom, but he is still teaching us with his usual enthusiasm and enthusiasm. I was taken aback, but I didn't feel any remorse.
Llama-2 Chat (7B)	100%! I was pleasantly surprised, but not complaining. However, Mr. Curphey is now using crutches to move around the classroom, still actively teaching us with his usual dedication.
Llama-3 Inst(8B)	100%! I was taken aback, but I wasn't about to grumble about it, haha! But yes, Mr. Curphey's now on crutches, limping around the classroom, and yet he's still teaching us as himself, business as usual.
Gemma Inst(7B)	100%! I was surprised, but not in a bad way. Mr. Curphey is still teaching us despite being on crutches.
STYLE REMIX	Initially, I experienced a notable degree of surprise, yet my responses remain devoid of significant complaint. Currently, Mr. Curphey, significantly, is navigating our classroom utilizing crutches, effectively maintaining his usual style of instruction, significantly.
Original (Obama)	I recognize that times have changed since I first spoke to this convention. The times have changed, and so have I. I'm no longer just a candidate. I'm the President.
MТ	I recognize that the times have changed since I first spoke to this convention. The times have changed, and that's how I have. I'm not just a candidate anymore. I am the President.
Stylo.	I acknowledge that times have changed since I 1st spoke to this convention, and the times have changed, and so have I. I am no longer just a candidate; and myself 'm the President.
JD.	It's important to remember where we came from, where we're going, and what we're trying to do," he said, adding, "I think it's important for all of us to be. We are the people who built this country, and we have a responsibility to make sure that we preserve it for our children and our children's children, and that's what we're going to do,".
Para.	Since I first addressed this convention, I have seen significant changes. As a result, I have evolved from a candidate to the current President.
Llama-2 Chat (7B)	Since my initial conversation with this convention, time has passed and changes have occurred. As a result, my perspective and circumstances have evolved. I am no longer just a candidate, but the actual President.
Llama-3 Inst(8B)	Since my initial address to this esteemed convention, I have come to ac- knowledge that the times have indeed changed. So too have I. Gone are the days when I stood before you as a mere candidate, eager to make my case. Today, I stand before you as the President, with a wealth of experience and insight gathered during my time in office.
Gemma Inst(7B)	Since my initial address to this esteemed convention, the world has shifted, and I have evolved alongside it. Today, I stand before you not as a candidate, but as the President, ready to tackle the challenges that lie ahead.
STYLE REMIX	Oh, how the world has transformed since I first addressed you all here! Indeed, the world has shifted, and so have I. It's not just about being a candidate anymore—it's about being the President.

Table 3: Examples of obfuscations from baseline methods and STYLEREMIX from texts from AUTHORMIX-Blog and AUTHORMIX-Speech respectively. Green regions highlight where the method obfuscates well and red areas show grammar, content, or obfuscation issues.

methods like Gemma-Instruct 7B and Paraphrase; though these methods may be good abstaining from adding new content, this is likely a byproduct of their generations being too succinct and failing to preserve information or obfuscate, as shown by their low human evaluations on these two metrics.

For overall score, which captures aspects of fluency, content preservation, and obfuscation, STYLEREMIX performs the best, achieving an overall score of 69.9%; the next highest scoring method is Llama-3-Instruct 8B with a score of 66.3%, a significant dropoff. Each individual metric must be high to achieve a high product; this indicates that our method on averages produces the obfuscations with the best overall quality, balancing between grammar, content preservation, and obfuscation, rather than optimizing for just one dimension.

Qualitatively, STYLEREMIX generates more flexible, directed obfuscations compared to other methods Qualitative results demonstrate that, as designed, STYLEREMIX provides a strong, personalized obfuscation compared to the more general results of other methods and models. Ta-ble [3](#page-6-2) presents two randomly^{[6](#page-7-0)} selected texts along with the generations from various models and methods. Consistent with previous work [\(Fisher et al.,](#page-9-1) [2024\)](#page-9-1), the rule-based methods (MT and Stylo result in poor grammar or loss of content. Conversely, methods based on LLMs tend to maintain grammar and content preservation more effectively.

The most significant difference is evident in the *style* of the generated text. Other methods sometimes struggle to clearly obfuscate and instead generally mimic the original author's style or default to a more formal "model"-like writing style. In contrast, STYLEREMIX stands out by providing a more personalized and targeted obfuscation. For instance, in the Blog example (top), STYLEREMIX generates text that is more formal, uses highergrade level language, and is longer compared to the original text. Meanwhile, in the Speech example (bottom), it adopts a more sarcastic, less formal tone, and incorporates more function words.

We also find that this multi-style mixture approach often results in noticeably different sentence structures and punctuation. For example, in the speech text (bottom), the order of the first sentence is reversed compared to the original, a feature not observed in any other generation. Additional generations are available in Appendix [B.6.](#page-15-0)

To further highlight the steerability of STYLEREMIX, we display a randomly selected text from AUTHORMIX-Speech and random generations created using an adapter in the optimal steering direction^{[7](#page-7-1)} for each of the seven style axes in Figure [2.](#page-2-0) Each generation demonstrates how the choice of adapter significantly transforms the text and influences the type of obfuscation.

3.7 Ablations and Other Studies

Our automatic method of style selection results in better obfuscation than random selection

# Styles	\blacksquare	$\frac{2}{2}$	3		5		
Speeches 17.0 17.7 21.2 19.2					6.0	17.0	11.4
Novels	8.6	11.2	13.0	14.4	16.3	11.2	21.8
Scholar	$1.1 -$	1.8	2.3	3.4	0.8	6.0	16.9
Blog	13.1	16.5	19.6	18.9	12.1	10.5	6.4

Table 4: Overall task score on the base adapter merging method using different number of style adapters. We compare the overall task score using $1-7$ style adapters. For all automatic evaluations see Table [6](#page-14-1)

Although STYLEREMIX can be used with any arbitrary method of choosing the style axes to change, we do find that choosing based on difference between the average style vector and the author vector improves obfuscation on average by 6% over random selection of the same number of weights. We note that the grammar and content remained about equal. More details can be found in Appendix [B.1](#page-13-1)

Shuffling style adapters when using STYLEREMIX-Sequential leads to some variation For STYLEREMIX-Sequential we experiment with shuffling the order of the chosen style adapters over $n = 3$ random shuffling. We found that the order of the styles does have some effect on the obfuscation drop rate (standard deviation of $3\% - 6\%$) but little effect on the grammar or content preservation (standard deviation of $1\% - 2\%$). This was seen strongly when choosing 3+ styles and in domains with strong style differences among the authors (Speech and Blog). More details are in Appendix [B.3](#page-13-2)

Changing 5+ style axes decreases grammaticality Table [4](#page-7-2) shows how the overall task score changes the number of styles chosen to use the adapter merging method increases. At first, both obfuscation drop rate and overall score steadily increase as we increase the number of style adapters, which corresponds with changing more elements of the original text. However, for AUTHORMIX Speech, Scholar, and Blog, we see a sudden decrease in overall task score when using 5 styles. Investigating this, we found that using $5+$ style adapters leads to an average of ∼ 16% decrease in grammar and a ∼5% decrease in overall score. More details can be found in Appendix [B.4.](#page-14-2)

4 Related Work

Authorship Obfuscation Methods Traditional authorship obfuscation methods leverage stylometric insights, such as author invariant features,

⁶Texts were filtered by a length threshold.

⁷The optimal direction is calculated based on the automatic style selection method in Section [2.2](#page-3-0)

to obfuscate texts [\(Karadzhov et al.,](#page-10-0) [2017;](#page-10-0) [Man](#page-11-15)[soorizadeh et al.,](#page-11-15) [2016;](#page-11-15) [Xing et al.,](#page-12-8) [2024b\)](#page-12-8). However, these methods have been shown to have issues with grammar and fluency due to their strict rulebased approach [\(Fisher et al.,](#page-9-1) [2024\)](#page-9-1).

To reduce this behavior, model-based approaches have been developed, such as Mutant-X, a genetic algorithm which utilizes an internal classifier to iteratively "mutate" a sentence [\(Mah](#page-11-1)[mood et al.,](#page-11-1) [2019\)](#page-11-1). Later work improves on this with an *ensemble* of classifiers rather than a single one [\(Haroon et al.,](#page-9-2) [2021\)](#page-9-2) or via variational autoencoders as the base model to generate deferentially private generations [\(Weggenmann et al.,](#page-12-0) [2022\)](#page-12-0). Most recently, [Fisher et al.](#page-9-1) [\(2024\)](#page-9-1) demonstrate the efficacy of smaller LLMs for authorship obfuscation through over-generation and filtering. However, this method's reliance on a heavy decoding algorithm to generate diverse candidates makes it impractical. Some obfuscation methods have also incorporated authorship information [\(Jones et al.,](#page-10-10) [2022;](#page-10-10) [Shetty et al.,](#page-11-0) [2017\)](#page-11-0). Although these both showed promise, they require extensive training and are only applicable in specific use cases.

Parameter Efficient Learning Parameterefficient adapters, small modules tuned on top of a frozen large model for effective transfer learning, have been proposed for vision [\(Rebuffi et al.,](#page-11-7) [2017\)](#page-11-7) and NLP [\(Houlsby et al.,](#page-10-3) [2019\)](#page-10-3). Others have extended these methods by tuning specific layers and embeddings [\(Li and Liang,](#page-10-11) [2021;](#page-10-11) [Lester](#page-10-12) [et al.,](#page-10-12) [2021\)](#page-10-12), or by making the adapter matrices an addition to the original model weights themselves rather than additional injected layers [\(Hu et al.,](#page-10-1) [2021;](#page-10-1) [Lu et al.,](#page-10-13) [2023\)](#page-10-13).

Adjacent to parameter-efficient training strategies are model merging techniques, which seek to integrate model knowledge by combining their weights [\(Matena and Raffel,](#page-11-16) [2021\)](#page-11-16); this is efficient and prevents additional inference cost. Merging has been explored extensively in previous work, to combine diverse, targeted domain models [\(Jang et al.,](#page-10-14) [2023;](#page-10-14) [Ramé et al.,](#page-11-17) [2023\)](#page-11-17), or over the same model trained with different seeds or hyperparameters to improve robustness [\(Wortsman et al.,](#page-12-9) [2022;](#page-12-9) [Ramé](#page-11-18) [et al.,](#page-11-18) [2022\)](#page-11-18). Model merging has even been explored with parameter-efficient adapters like LoRA [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4). Other lines of work expand on merging techniques, creating strategies beyond simply averaging model weights. [\(Yadav et al.,](#page-12-10) [2023b;](#page-12-10) [Stoica et al.,](#page-11-19) [2023;](#page-11-19) [Yu et al.,](#page-12-11) [2023\)](#page-12-11).

Controllable Generation Previous work introduces methods to control the content of a generation [\(Lu et al.,](#page-10-15) [2021\)](#page-10-15) or steer the style of the generation [\(Liu et al.,](#page-10-16) [2021;](#page-10-16) [Lu et al.,](#page-10-13) [2023\)](#page-10-13). However these types of controllable generation are less practical for authorship obfuscation, which requires a steerability of the content and the style.

Style Transfer Style transfer techniques have utilized both simple models [\(Hu et al.,](#page-10-17) [2022\)](#page-10-17) and more advanced machine learning models [\(Jin et al.,](#page-10-18) [2022;](#page-10-18) [Hallinan et al.,](#page-9-8) [2023\)](#page-9-8). Most approaches depend on training generation models with a dataset, which can be natural or synthetic [\(Jin et al.,](#page-10-18) [2022\)](#page-10-18). These methods also interpret "style" in various ways, ranging from comprehensive notions like specific authors (e.g., Shakespeare and Hemingway) [\(Krishna](#page-10-19) [et al.,](#page-10-19) [2020b\)](#page-10-19) to particular stylistic elements (e.g., formality and sentiment) [\(Fu et al.,](#page-9-9) [2018\)](#page-9-9). Notably, recent, effective style transfer techniques resemble the approach we use, which involves fine-tuning a LLM [\(Hallinan et al.,](#page-9-8) [2023;](#page-9-8) [Krishna et al.,](#page-10-19) [2020b\)](#page-10-19).

5 Conclusion

In this work, we introduce STYLEREMIX, a novel and interpretable method for authorship obfuscation. By targeting specific fine-grained stylistic elements and leveraging Low Rank Adaptation (LoRA) modules, STYLEREMIX provides a more interpretable and controllable approach than existing methods based on large language models or other state-of-the-art techniques while still maintaining excellent performance. We show our new method outperforms a suite of strong, state-of-theart baselines in four diverse domains overall in both automatic and human evaluation.

Additionally, as part of this work, we release a new authorship attribution dataset, AUTHORMIX. This dataset includes two new domains: presidential speeches and fiction books, which were carefully selected to ensure a high degree of topic matching, thereby enriching the dataset's applicability and depth. Furthermore, we develop DISC, a collection of 16 parallel, human-validated datasets spanning various stylistic dimensions, which can be employed in future research to further explore and refine the nuances of stylistic text manipulation. These resources aim to advance the field of authorship obfuscation and provide a solid foundation for subsequent studies.

6 Limitations and Ethical Considerations

One limitation of STYLEREMIX is the requirement of needing trained LoRA adapters and the corresponding style datasets for their training. This necessitates an additional pre-obfuscation step involving separate style corpi and computational training time. However, this is a one-time expense, and the same style adapters can be utilized for multiple authors. In return, users benefit from a more interpretable method for authorship obfuscation.

During obfuscation, STYLEREMIX does require a slightly higher computational time and memory due to the extra style LoRA adapters compared to using a finetuned model with instructions. For the sequential version of STYLEREMIX, the computational time is multiplied by the number of styles. The base adapter merging variation outperforms the sequential version and is also more efficient: the time is only increased by a small amount from merging adapters then adding them to the base model, rather than requiring multiple model forward-passes. In inference, no extra time is added, since LoRA weights are seamlessly added to the original model [\(Hu et al.,](#page-10-1) [2021\)](#page-10-1); see Appendix [C.4](#page-17-1) for further analysis. Finally, we note that for the adapter merging with LoraHub, there is also additional time over the base adapter merging to identify the optimal weights.

An additional limitation is that STYLEREMIX is developed and tested only on English. However, we believe that the framework (identifying style axes, training LoRA adapters, evaluating original text on these axes, and perturbing based on these evaluations) could be generalized to any language. As such, we believe our pipeline can be effectively adapted to obfuscate other languages; we leave the exploration of these adaptations to future work.

Lastly, our work also has some potential risks. Though the intention of authorship obfuscation is to protect identities in sensitive situations, there is a possibility that malicious users could misuse our method. We acknowledge this as a potential risk for any authorship obfuscation method, which is inherent when creating these methods.

7 Acknowledgements

This research was supported by the DARPA MCS program through NIWC Pacific (N66001-19-2- 4031), IARPA 2022-22072200003, and NSF IFML CCF-2019844.

References

AI@Meta. 2024. [Llama 3 model card.](https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md)

- Nikolay Babakov, David Dale, Ilya Gusev, Irina Krotova, and Alexander Panchenko. 2023. Don't lose the message while paraphrasing: A study on content preserving style transfer. In *Natural Language Processing and Information Systems*, pages 47–61, Cham. Springer Nature Switzerland.
- Janek Bevendorff, Martin Potthast, Matthias Hagen, and Benno Stein. 2019. [Heuristic authorship obfuscation.](https://api.semanticscholar.org/CorpusID:189810935) In *Annual Meeting of the Association for Computational Linguistics*.
- Michael Brennan, Sadia Afroz, and Rachel Greenstadt. 2012. [Adversarial stylometry: Circumventing author](https://doi.org/10.1145/2382448.2382450)[ship recognition to preserve privacy and anonymity.](https://doi.org/10.1145/2382448.2382450) *ACM Transactions on Information and System Security (TISSEC)*, 15.
- Angela Fan, Shruti Bhosale, Holger Schwenk, Zhiyi Ma, Ahmed El-Kishky, Siddharth Goyal, Mandeep Baines, Onur Celebi, Guillaume Wenzek, Vishrav Chaudhary, Naman Goyal, Tom Birch, Vitaliy Liptchinsky, Sergey Edunov, Edouard Grave, Michael Auli, and Armand Joulin. 2020. Beyond english-centric multilingual machine translation. *arXiv preprint*.
- Jillian Fisher, Ximing Lu, Jaehun Jung, Liwei Jiang, Zaid Harchaoui, and Yejin Choi. 2024. [JAMDEC:](https://doi.org/10.18653/v1/2024.naacl-long.87) [Unsupervised authorship obfuscation using con](https://doi.org/10.18653/v1/2024.naacl-long.87)[strained decoding over small language models.](https://doi.org/10.18653/v1/2024.naacl-long.87) In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 1552–1581, Mexico City, Mexico. Association for Computational Linguistics.
- Rudolph Flesch. 1948. A new readability yardstick. *Journal of applied psychology*, 32(3):221.
- Zhenxin Fu, Xiaoye Tan, Nanyun Peng, Dongyan Zhao, and Rui Yan. 2018. [Style transfer in text: Exploration](https://doi.org/10.1609/aaai.v32i1.11330) [and evaluation.](https://doi.org/10.1609/aaai.v32i1.11330) *Proceedings of the AAAI Conference on Artificial Intelligence*, 32(1).
- Robert Gunning. 1952. The technique of clear writing. *(No Title)*.

Project Gutenberg. [\[link\].](https://www.gutenberg.org/)

- Skyler Hallinan, Faeze Brahman, Ximing Lu, Jaehun Jung, Sean Welleck, and Yejin Choi. 2023. [Steer:](https://api.semanticscholar.org/CorpusID:265150161) [Unified style transfer with expert reinforcement.](https://api.semanticscholar.org/CorpusID:265150161) *ArXiv*, abs/2311.07167.
- Muhammad Haroon, Muhammad Fareed Zaffar, Padmini Srinivasan, and Zubair Shafiq. 2021. [Avengers](https://arxiv.org/abs/2109.07028) [ensemble! improving transferability of authorship](https://arxiv.org/abs/2109.07028) [obfuscation.](https://arxiv.org/abs/2109.07028) *CoRR*, abs/2109.07028.
- Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. 2019. [Parameter-efficient transfer learning for nlp.](https://api.semanticscholar.org/CorpusID:59599816) *ArXiv*, abs/1902.00751.
- J. Edward Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, and Weizhu Chen. 2021. [Lora: Low-rank adaptation of large](https://api.semanticscholar.org/CorpusID:235458009) [language models.](https://api.semanticscholar.org/CorpusID:235458009) *ArXiv*, abs/2106.09685.
- Zhiqiang Hu, Roy Ka-Wei Lee, Charu C. Aggarwal, and Aston Zhang. 2022. [Text style transfer: A review and](https://doi.org/10.1145/3544903.3544906) [experimental evaluation.](https://doi.org/10.1145/3544903.3544906) *SIGKDD Explor. Newsl.*, 24(1):14–45.
- Chengsong Huang, Qian Liu, Bill Yuchen Lin, Tianyu Pang, Chao Du, and Min Lin. 2023. [Lorahub: Effi](https://api.semanticscholar.org/CorpusID:260155012)[cient cross-task generalization via dynamic lora com](https://api.semanticscholar.org/CorpusID:260155012)[position.](https://api.semanticscholar.org/CorpusID:260155012) *ArXiv*, abs/2307.13269.
- Joel Jang, Seungone Kim, Bill Yuchen Lin, Yizhong Wang, Jack Hessel, Luke Zettlemoyer, Hannaneh Hajishirzi, Yejin Choi, and Prithviraj Ammanabrolu. 2023. [Personalized soups: Personalized large lan](https://api.semanticscholar.org/CorpusID:264289231)[guage model alignment via post-hoc parameter merg](https://api.semanticscholar.org/CorpusID:264289231)[ing.](https://api.semanticscholar.org/CorpusID:264289231) *ArXiv*, abs/2310.11564.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. [Mistral 7b.](https://arxiv.org/abs/2310.06825) *Preprint*, arXiv:2310.06825.
- Di Jin, Zhijing Jin, Zhiting Hu, Olga Vechtomova, and Rada Mihalcea. 2022. [Deep learning for text](https://doi.org/10.1162/coli_a_00426) [style transfer: A survey.](https://doi.org/10.1162/coli_a_00426) *Computational Linguistics*, 48(1):155–205.
- Keenan Jones, Jason R. C. Nurse, and Shujun Li. 2022. [Are you robert or roberta? deceiving online author](https://arxiv.org/abs/2203.09813)[ship attribution models using neural text generators.](https://arxiv.org/abs/2203.09813) *Preprint*, arXiv:2203.09813.
- Jaehun Jung, Peter West, Liwei Jiang, Faeze Brahman, Ximing Lu, Jillian Fisher, Taylor Sorensen, and Yejin Choi. 2024. [Impossible distillation: from](https://arxiv.org/abs/2305.16635) [low-quality model to high-quality dataset & model](https://arxiv.org/abs/2305.16635) [for summarization and paraphrasing.](https://arxiv.org/abs/2305.16635) *Preprint*, arXiv:2305.16635.
- Georgi Karadzhov, Tsvetomila Mihaylova, Yasen Kiprov, Georgi Georgiev, Ivan Koychev, and Preslav Nakov. 2017. The case for being average: A mediocrity approach to style masking and author obfuscation. *International Conference of the Cross-Language Evaluation Forum for European Languages*, pages 173–185.
- Yashwant Keswani, H. Trivedi, Parth Mehta, and Prasenjit Majumder. 2016. Author masking through translation. In *Conference and Labs of the Evaluation Forum*.
- Kalpesh Krishna, John Wieting, and Mohit Iyyer. 2020a. [Reformulating unsupervised style transfer as para](https://api.semanticscholar.org/CorpusID:222291619)[phrase generation.](https://api.semanticscholar.org/CorpusID:222291619) *ArXiv*, abs/2010.05700.
- Kalpesh Krishna, John Wieting, and Mohit Iyyer. 2020b. [Reformulating unsupervised style transfer as para](https://arxiv.org/abs/2010.05700)[phrase generation.](https://arxiv.org/abs/2010.05700) *Preprint*, arXiv:2010.05700.
- Wojciech Kryściński, Nazneen Rajani, Divyansh Agarwal, Caiming Xiong, and Dragomir Radev. 2021. [Booksum: A collection of datasets for long-form](https://arxiv.org/abs/2105.08209) [narrative summarization.](https://arxiv.org/abs/2105.08209)
- Brian Lester, Rami Al-Rfou, and Noah Constant. 2021. [The power of scale for parameter-efficient prompt](https://api.semanticscholar.org/CorpusID:233296808) [tuning.](https://api.semanticscholar.org/CorpusID:233296808) In *Conference on Empirical Methods in Natural Language Processing*.
- Xiang Lisa Li and Percy Liang. 2021. [Prefix-tuning:](https://api.semanticscholar.org/CorpusID:230433941) [Optimizing continuous prompts for generation.](https://api.semanticscholar.org/CorpusID:230433941) *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, abs/2101.00190.
- Alisa Liu, Maarten Sap, Ximing Lu, Swabha Swayamdipta, Chandra Bhagavatula, Noah A. Smith, and Yejin Choi. 2021. [DExperts: Decoding-time con](https://doi.org/10.18653/v1/2021.acl-long.522)[trolled text generation with experts and anti-experts.](https://doi.org/10.18653/v1/2021.acl-long.522) In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 6691–6706, Online. Association for Computational Linguistics.
- Jialin Liu, Antoine Moreau, Mike Preuss, Baptiste Roziere, Jeremy Rapin, Fabien Teytaud, and Olivier Teytaud. 2020. [Versatile black-box optimization.](https://arxiv.org/abs/2004.14014) *Preprint*, arXiv:2004.14014.
- Shuai Liu and Jonathan May. 2024. [Style transfer](https://api.semanticscholar.org/CorpusID:270560619) [with multi-iteration preference optimization.](https://api.semanticscholar.org/CorpusID:270560619) *ArXiv*, abs/2406.11581.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. [Roberta: A robustly optimized bert pretraining ap](https://api.semanticscholar.org/CorpusID:198953378)[proach.](https://api.semanticscholar.org/CorpusID:198953378) *ArXiv*, abs/1907.11692.
- Ximing Lu, Faeze Brahman, Peter West, Jaehun Jang, Khyathi Raghavi Chandu, Abhilasha Ravichander, Lianhui Qin, Prithviraj Ammanabrolu, Liwei Jiang, Sahana Ramnath, Nouha Dziri, Jillian R. Fisher, Bill Yuchen Lin, Skyler Hallinan, Xiang Ren, Sean Welleck, and Yejin Choi. 2023. [Inference-time policy](https://api.semanticscholar.org/CorpusID:258865629) [adapters \(ipa\): Tailoring extreme-scale lms without](https://api.semanticscholar.org/CorpusID:258865629) [fine-tuning.](https://api.semanticscholar.org/CorpusID:258865629) In *Conference on Empirical Methods in Natural Language Processing*.
- Ximing Lu, Peter West, Rowan Zellers, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. 2021. [Neuro-](https://doi.org/10.18653/v1/2021.naacl-main.339)[Logic decoding: \(un\)supervised neural text genera](https://doi.org/10.18653/v1/2021.naacl-main.339)[tion with predicate logic constraints.](https://doi.org/10.18653/v1/2021.naacl-main.339) In *Proceedings*

of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 4288–4299, Online. Association for Computational Linguistics.

- Asad Mahmood, Faizan Ahmad, Zubair Shafiq, Padmini Srinivasan, and Fareed Zaffar. 2019. [A girl](https://api.semanticscholar.org/CorpusID:197621394) [has no name: Automated authorship obfuscation us](https://api.semanticscholar.org/CorpusID:197621394)[ing mutant-x.](https://api.semanticscholar.org/CorpusID:197621394) *Proceedings on Privacy Enhancing Technologies*, 2019:54 – 71.
- Muharram Mansoorizadeh, Taher Rahgooy, Mohammad Aminian, and Mehdy Eskandari. 2016. Author obfuscation using wordnet and language models. In *Conference and Labs of the Evaluation Forum*.
- Michael Matena and Colin Raffel. 2021. [Merging](https://api.semanticscholar.org/CorpusID:244345933) [models with fisher-weighted averaging.](https://api.semanticscholar.org/CorpusID:244345933) *ArXiv*, abs/2111.09832.
- Tsvetomila Mihaylova, Georgi Karadzhov, Preslav Nakov, Yasen Kiprov, Georgi Georgiev, and Ivan Koychev. 2016. Su@ pan'2016: Author obfuscation—notebook for pan at clef 2016.
- University of Virginia Miller Center of Public Affairs. Presidential speeches: Downloadable data.
- John Morris, Eli Lifland, Jin Yong Yoo, Jake Grigsby, Di Jin, and Yanjun Qi. 2020. Textattack: A framework for adversarial attacks, data augmentation, and adversarial training in nlp. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 119–126.

John O'Hayre. *Gobbledygook Has Gotta Go*.

OpenAI. 2023. [Gpt-4 turbo.](https://www.openai.com/gpt-4) Accessed: 2024-06-05.

- Ajay Patel, Nicholas Andrews, and Chris Callison-Burch. 2023. [Low-resource authorship style trans](https://arxiv.org/abs/2212.08986)[fer: Can non-famous authors be imitated?](https://arxiv.org/abs/2212.08986) *Preprint*, arXiv:2212.08986.
- Roger Peng and Nicolas Hengartner. 2002. [Quantitative](https://doi.org/10.1198/000313002100) [analysis of literary style.](https://doi.org/10.1198/000313002100) *Roger D. Peng*, 56.
- Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. [Exploring the](http://jmlr.org/papers/v21/20-074.html) [limits of transfer learning with a unified text-to-text](http://jmlr.org/papers/v21/20-074.html) [transformer.](http://jmlr.org/papers/v21/20-074.html) *Journal of Machine Learning Research*, 21(140):1–67.
- Alexandre Ramé, Guillaume Couairon, Mustafa Shukor, Corentin Dancette, Jean-Baptiste Gaya, Laure Soulier, and Matthieu Cord. 2023. [Rewarded soups:](https://api.semanticscholar.org/CorpusID:259096117) [towards pareto-optimal alignment by interpolating](https://api.semanticscholar.org/CorpusID:259096117) [weights fine-tuned on diverse rewards.](https://api.semanticscholar.org/CorpusID:259096117) *ArXiv*, abs/2306.04488.
- Alexandre Ramé, Matthieu Kirchmeyer, Thibaud Rahier, Alain Rakotomamonjy, Patrick Gallinari, and Matthieu Cord. 2022. [Diverse weight averag](https://api.semanticscholar.org/CorpusID:248887264)[ing for out-of-distribution generalization.](https://api.semanticscholar.org/CorpusID:248887264) *ArXiv*, abs/2205.09739.
- Sylvestre-Alvise Rebuffi, Hakan Bilen, and Andrea Vedaldi. 2017. [Learning multiple visual domains](https://api.semanticscholar.org/CorpusID:215826266) [with residual adapters.](https://api.semanticscholar.org/CorpusID:215826266) *ArXiv*, abs/1705.08045.
- Nils Reimers and Iryna Gurevych. 2019. [Sentence-bert:](https://api.semanticscholar.org/CorpusID:201646309) [Sentence embeddings using siamese bert-networks.](https://api.semanticscholar.org/CorpusID:201646309) In *Conference on Empirical Methods in Natural Language Processing*.
- Jonathan Schler, Moshe Koppel, Shlomo Argamon, and James W Pennebaker. 2006a. Effects of age and gender on blogging. In *AAAI spring symposium: Computational approaches to analyzing weblogs*, volume 6, pages 199–205.
- Jonathan Schler, Moshe Koppel, Shlomo Argamon, and James W Pennebaker. 2006b. Effects of age and gender on blogging. In *AAAI spring symposium: Computational approaches to analyzing weblogs*, volume 6, pages 199–205.
- Rakshith Shetty, Bernt Schiele, and Mario Fritz. 2017. A4nt: Author attribute anonymity by adversarial training of neural machine translation. In *USENIX Security Symposium*.
- Rafael A. Rivera Soto, Olivia Elizabeth Miano, Juanita Ordoñez, Barry Y. Chen, Aleem Khan, Marcus Bishop, and Nicholas Andrews. 2021. [Learning uni](https://api.semanticscholar.org/CorpusID:243865314)[versal authorship representations.](https://api.semanticscholar.org/CorpusID:243865314) In *Conference on Empirical Methods in Natural Language Processing*.
- George Stoica, Daniel Bolya, Jakob Bue Bjorner, Taylor N. Hearn, and Judy Hoffman. 2023. [Zipit! merg](https://api.semanticscholar.org/CorpusID:258480011)[ing models from different tasks without training.](https://api.semanticscholar.org/CorpusID:258480011) *ArXiv*, abs/2305.03053.
- Emma Strubell, Ananya Ganesh, and Andrew McCallum. 2019. [Energy and policy considerations for](https://api.semanticscholar.org/CorpusID:174802812) [deep learning in nlp.](https://api.semanticscholar.org/CorpusID:174802812) *ArXiv*, abs/1906.02243.
- Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, Pouya Tafti, Léonard Hussenot, Pier Giuseppe Sessa, Aakanksha Chowdhery, Adam Roberts, Aditya Barua, Alex Botev, Alex Castro-Ros, Ambrose Slone, Amélie Héliou, Andrea Tacchetti, Anna Bulanova, Antonia Paterson, Beth Tsai, Bobak Shahriari, Charline Le Lan, Christopher A. Choquette-Choo, Clément Crepy, Daniel Cer, Daphne Ippolito, David Reid, Elena Buchatskaya, Eric Ni, Eric Noland, Geng Yan, George Tucker, George-Christian Muraru, Grigory Rozhdestvenskiy, Henryk Michalewski, Ian Tenney, Ivan Grishchenko, Jacob Austin, James Keeling, Jane Labanowski, Jean-Baptiste Lespiau, Jeff Stanway, Jenny Brennan, Jeremy Chen, Johan Ferret, Justin Chiu, Justin Mao-Jones, Katherine Lee, Kathy Yu, Katie Millican, Lars Lowe Sjoesund, Lisa Lee, Lucas Dixon,

Machel Reid, Maciej Mikuła, Mateo Wirth, Michael Sharman, Nikolai Chinaev, Nithum Thain, Olivier Bachem, Oscar Chang, Oscar Wahltinez, Paige Bailey, Paul Michel, Petko Yotov, Rahma Chaabouni, Ramona Comanescu, Reena Jana, Rohan Anil, Ross McIlroy, Ruibo Liu, Ryan Mullins, Samuel L Smith, Sebastian Borgeaud, Sertan Girgin, Sholto Douglas, Shree Pandya, Siamak Shakeri, Soham De, Ted Klimenko, Tom Hennigan, Vlad Feinberg, Wojciech Stokowiec, Yu hui Chen, Zafarali Ahmed, Zhitao Gong, Tris Warkentin, Ludovic Peran, Minh Giang, Clément Farabet, Oriol Vinyals, Jeff Dean, Koray Kavukcuoglu, Demis Hassabis, Zoubin Ghahramani, Douglas Eck, Joelle Barral, Fernando Pereira, Eli Collins, Armand Joulin, Noah Fiedel, Evan Senter, Alek Andreev, and Kathleen Kenealy. 2024. [Gemma:](https://arxiv.org/abs/2403.08295) [Open models based on gemini research and technol](https://arxiv.org/abs/2403.08295)[ogy.](https://arxiv.org/abs/2403.08295) *Preprint*, arXiv:2403.08295.

- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. [Llama 2: Open foundation and fine](https://arxiv.org/abs/2307.09288)[tuned chat models.](https://arxiv.org/abs/2307.09288) *Preprint*, arXiv:2307.09288.
- Adaku Uchendu, Zeyu Ma, Thai Le, Rui Zhang, and Dongwon Lee. 2021. [Turingbench: A benchmark](https://api.semanticscholar.org/CorpusID:237589233) [environment for turing test in the age of neural text](https://api.semanticscholar.org/CorpusID:237589233) [generation.](https://api.semanticscholar.org/CorpusID:237589233) In *Conference on Empirical Methods in Natural Language Processing*.
- Alex Warstadt, Amanpreet Singh, and Samuel R. Bowman. 2018. [Neural network acceptability judgments.](https://api.semanticscholar.org/CorpusID:44072099) *Transactions of the Association for Computational Linguistics*, 7:625–641.
- Benjamin Weggenmann, Valentin Rublack, Michael Andrejczuk, Justus Mattern, and Florian Kerschbaum. 2022. [Dp-vae: Human-readable text anonymization](https://doi.org/10.1145/3485447.3512232) [for online reviews with differentially private varia](https://doi.org/10.1145/3485447.3512232)[tional autoencoders.](https://doi.org/10.1145/3485447.3512232) In *Proceedings of the ACM Web Conference 2022*, WWW '22, page 721–731, New York, NY, USA. Association for Computing Machinery.
- Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes,

Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. 2022. [Model soups: averaging weights of multiple](https://api.semanticscholar.org/CorpusID:247362886) [fine-tuned models improves accuracy without increas](https://api.semanticscholar.org/CorpusID:247362886)[ing inference time.](https://api.semanticscholar.org/CorpusID:247362886) *ArXiv*, abs/2203.05482.

- Eric Xing, Saranya Venkatraman, Thai Le, and Dongwon Lee. 2024a. Alison: Fast and effective stylometric authorship obfuscation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19315–19322.
- Eric Xing, Saranya Venkatraman, Thai Le, and Dongwon Lee. 2024b. [Alison: Fast and effective stylo](https://doi.org/10.1609/aaai.v38i17.29901)[metric authorship obfuscation.](https://doi.org/10.1609/aaai.v38i17.29901) *Proceedings of the AAAI Conference on Artificial Intelligence*, 38:19315– 19322.
- Jingjing Xu, Xu Sun, Qi Zeng, Xiaodong Zhang, Xuancheng Ren, Houfeng Wang, and Wenjie Li. 2018. [Unpaired sentiment-to-sentiment translation: A cy](https://doi.org/10.18653/v1/P18-1090)[cled reinforcement learning approach.](https://doi.org/10.18653/v1/P18-1090) In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 979–988, Melbourne, Australia. Association for Computational Linguistics.
- Prateek Yadav, Derek Tam, Leshem Choshen, Colin Raffel, and Mohit Bansal. 2023a. [Ties-merging: Re](https://arxiv.org/abs/2306.01708)[solving interference when merging models.](https://arxiv.org/abs/2306.01708) *Preprint*, arXiv:2306.01708.
- Prateek Yadav, Derek Tam, Leshem Choshen, Colin Raffel, and Mohit Bansal. 2023b. [Ties-merging: Resolv](https://api.semanticscholar.org/CorpusID:259064039)[ing interference when merging models.](https://api.semanticscholar.org/CorpusID:259064039) In *Neural Information Processing Systems*.
- Le Yu, Yu Bowen, Haiyang Yu, Fei Huang, and Yongbin Li. 2023. [Language models are super mario: Absorb](https://api.semanticscholar.org/CorpusID:265034087)[ing abilities from homologous models as a free lunch.](https://api.semanticscholar.org/CorpusID:265034087) *ArXiv*, abs/2311.03099.
- Le Yu, Bowen Yu, Haiyang Yu, Fei Huang, and Yongbin Li. 2024. [Language models are super mario: Absorb](https://arxiv.org/abs/2311.03099)[ing abilities from homologous models as a free lunch.](https://arxiv.org/abs/2311.03099) *Preprint*, arXiv:2311.03099.

A Code and Artifacts

The code for STYLEREMIX is available on Github at [https://github.com/jfisher52/](https://github.com/jfisher52/StyleRemix) [StyleRemix](https://github.com/jfisher52/StyleRemix). In addition, we release a demo of our method at [https://huggingface.co/](https://huggingface.co/spaces/hallisky/StyleRemix) [spaces/hallisky/StyleRemix](https://huggingface.co/spaces/hallisky/StyleRemix), which allows for arbitrary inputs and rewrites with multiple LoRA adapters across multiple style axes.

Finally, we release the rest of our datasets and trained classifiers and LoRA adapters [in a HuggingFace collection.](https://huggingface.co/collections/hallisky/authorship-obfuscation-66564c1c1d59bb62eaaf954f) Notably, the collection includes AUTHORMIX at [https://huggingface.co/datasets/](https://huggingface.co/datasets/hallisky/AuthorMix) [hallisky/AuthorMix](https://huggingface.co/datasets/hallisky/AuthorMix) and DISC at [https:](https://huggingface.co/datasets/hallisky/DiSC) [//huggingface.co/datasets/hallisky/DiSC](https://huggingface.co/datasets/hallisky/DiSC).

B Extended Ablations and Other Studies

B.1 Random Selection of Styles

In Section [2.2,](#page-3-0) we describe a simple automatic method to select the style axes to change for each author. It requires creating an author vector, which is composed of the ten style axes automatic evaluations, and finding the difference for each author compared to the average vector of all authors in a domain. In order to test the efficacy of our style axes selection method, we compare the results of STYLEREMIX when selecting the styles axes in this way and randomly (over $n = 3$ different seeds).

Figure [4](#page-14-3) shows the average and standard deviation of the drop rate, grammar score, content preservation score and overall task score for each domain randomly choosing $1 - 4$ styles (circles) and using our automatic method of style axes selection (stars). First, we notice that overall, the grammar and content preservation is mostly similar for both random and the automatic method. However, we do see a large difference in obfuscation drop rate, especially in speech (18% average) and Scholar (8 average). These datasets have more modern, similar styles, which might need a more targeted obfuscation rather than the novels (which are written in older English) and the blog (which are very informal).

B.2 Comparing with Different LLMs

For the main experiment we showed the comparison with different like-sized LLMs. Here we provide more comparisons with Mistral V2 [\(Jiang](#page-10-20) [et al.,](#page-10-20) [2023\)](#page-10-20) and Gemma (2B) [\(Team et al.,](#page-11-10) [2024\)](#page-11-10) to the three variations of STYLEREMIX. We show results for all three criteria as well as the overall task

	Mistral	Gemma	STYLEREMIX							
	V ₂	2B	Seq.	AM	$AM + LordHub+$					
AUTHORMIX-Speech										
Drop Rate	25.8	24.7	34.9	41.2	31.4					
Grammar	67.6	70.6	61.7	66.5	63.9					
Content	81.0	78.2	71.3	77.3	73.9					
Overall	14.1	13.6	15.3	21.2	14.8					
AUTHORMIX-Novels										
Drop Rate	12.0	13.5	19.3	28.6	35.6					
Grammar	69.7	72.2	72.6	68.1	63.5					
Content	80.1	78.2	83.7	76.1	72.9					
Overall	6.7	7.6	11.8	14.8	16.5					
		AUTHORMIX-Scholar								
Drop Rate	0.8	1.5	1.8	9.2	11.5					
Grammar	66.8	69.5	65.8	48.6	44.7					
Content	88.9	87.3	78.0	75.3	68.8					
Overall	2.3	2.8	3.6	3.4	3.5					
AUTHORMIX-Blog										
Drop Rate	23.7	21.9	34.4	41.0	42.0					
Grammar	68.3	71.3	66.7	64.9	65.3					
Content	78.3	77.1	72.1	73.7	74.2					
Overall	12.7	12.0	16.5	19.6	20.4					

Table 5: Results of automatic evaluation on other LLMs and methods compared to STYLEREMIX.

score. We see continue to have the highest overall and obfuscation rate compared to these models.

B.3 Shuffling Styles using the Sequential Method

One version of STYLEREMIX described in Section [2.2](#page-3-0) is the sequential method, which runs the original text through each adapter sequentially. We hypothesized that the order in which the styles were rewritten might affect the final outcome. To test this, we randomly shuffled the order of the adapters of the styles axes over $n = 3$ different seeds when changing $2 - 4$ styles and tested automatic evaluations as we did in the main experiment.

Figure [5](#page-14-4) shows the average and standard deviation for all the automatic evaluations for each domain and different number of styles changed. We first note that grammar and content preservation remains similar, with very low standard deviation. However, for specific domains, the obfuscation drop rate has a large variation between the three random shuffles. This most diverse obfuscation drop rates seen in Speech (∼ 14% standard deviation) and Blog (\sim 9% standard deviation). This indicates that the order of adapter in the sequential method could contribute to the overall efficacy of the method. Future work could experiment more with these findings.

Figure [5](#page-14-4) shows the automatic evaluations when we shuffle $2 - 4$ style axes adapters.

Figure 4: Base model merging with random styles, $n = 3$

Figure 5: Seq. shuffle $n = 3$

B.4 Number of Styles Change

In STYLEREMIX the user can decide how many style adapters to use during obfuscation. We tested how obfuscation drop rate, grammar, and content preservation is affected when more style adapter are added. For this experiment, we used the base model adapter method and selected $1 - 7$ styles using the difference from the author vector to the average domain vector.

Table [6](#page-14-1) shows all the automatic evaluations for each number of style. At first, we see a stead increase in both obfuscation drop rate and overall score as we increase style adapters. This corresponds with changing more elements of the original text. However, as mentioned in our main paper, we see on average a 5% decrease in overall task score when using 4 to 5 style adapters. Then, as the number of style adapter increase, we see a stead decrease in content preservation and grammar. This correlates with a qualitative decrease in generations seen as we increase the styles over 5.

B.5 Author Style Vector Analysis

In the pre-obfuscation phase, we choose 7 specific style axes to train the LoRA adapters; length, use of function words, grade level, voice, use of sarcasm, formality, and writing intent. Some of these style axes have rule-based evaluations, and others have classifier-based evaluations. We used these automatic evaluations to create a unique author vector for each author in a domain and use the difference in this vector compared to other authors in the same

# of Styles	1	2	3	4	5	6	7			
AUTHORMIX-Speech										
Drop Rate	28.9	33.3	41.2	42.3	13.6	47.4	44.6			
Grammar	70.0	68.1	66.5	63.5	61.4	52.9	46.1			
Content	84.1	78.0	77.3	71.7	72.2	67.7	55.4			
Overall	17.0	17.7	21.2	19.2	6.0	17.0	11.4			
AUTHORMIX-Novels										
Drop Rate	14.2	19.3	24.2	26.7	36.1	32.9	83.7			
Grammar	73.2	71.4	69.5	69.9	61.3	49.8	50.4			
Content	82.7	80.9	77.6	77.4	73.7	68.4	51.6			
Overall	8.6	11.2	13.0	14.4	16.3	11.2	21.8			
	AUTHORMIX-Scholar									
Drop Rate	2.3	3.8	5.3	9.2	2.3	50.4	73.5			
Grammar	57.7	55.7	54.9	48.6	48.1	38.6	48.4			
Content	79.8	82.7	78.4	75.3	71.7	30.8	47.5			
Overall	1.1	1.8	2.3	3.4	0.8	6.0	16.9			
AUTHORMIX-Blog										
Drop Rate	25.4	31.2	41.0	42.9	34.3	38.3	41.4			
Grammar	67.3	68.9	64.9	62.6	55.3	46.4	44.0			
Content	76.8	76.8	73.7	70.2	63.7	59.1	35.3			
Overall	13.1	16.5	19.6	18.9	12.1	10.5	6.4			

Table 6: Results of automatic evaluation on the base adapter merging method using different number of style adapters. We show the obfuscation drop rate, grammar, content preservation, and overall task score using $1 - 7$ style adapters.

Figure 6: PCA, clustering analysis

domain to choose the styles axes to change during obfuscation. Although these selected style axes are just a subsample of suitable options, we wanted to explore how well these author vectors separate the authors in our test data set.

To analyze this, we first created an author vector for each author by taking the average of each automatic evaluation over the paragraphs in the authors test set. This resulted in 14 (authors), vectors with 7 (style axes) entries each. We then performed a principle component analysis (PCA) to reduce the size of the vector dimension to explain at least 90% of the variance in the data (it went from 7 to 4 dimensions). We note that the first two dimensions account for 70% of the variation.

Figure [6](#page-15-1) compares all the authors (across all domains) using the first and second component of the PCA. First, we notice that the Scholar (triangles) and Speech (circle) domains have distinct clusters away from the other two domains. The most spread out domain is Blog (square) with one author quite different from the rest. Lastly, we see that the novel (start) dataset is closely clustered together, but are quite similar to 4 of the blog authors. We note that four of the blog authors have more storytelling writing styles, while the last one has a more diary-like, very informal writing style. This seems consistent then that it would cluster similarly as novels.

Overall, this analysis showed starting evidence that our style axes vectors were able to separate the diverse writing styles. Future research could continue to explore the types of style axes that are most important when obfuscating.

B.6 More Qualitative Examples

In Appendix [G](#page-26-0) we provide more examples from each author in the AUTHORMIX. We note that we selected these samples by *randomly* selecting 3, paragraphs of less than 45 words for each author and then selecting the example from these three. For STYLEREMIX, we used the base model adapter method with 3 style adapters. From these examples, especially the Blog and Novels, we see the qualitative benefits of STYLEREMIX and it's flexibility to adapt to different original author styles.

B.7 Tradeoff between Obfuscation, Content Preservation, and Grammar

We want to note that there is a natural trade-off between authorship obfuscation, content preservation, and grammar. For example, a naive copying baseline would have high grammar and perfect content preservation but low obfuscation. On the other extreme, a complete gibberish output would score very low on grammar and content but high on obfuscation.

This phenomenon is well-documented in the context of style transfer. To assess the overall quality of generations where there are multiple objectives, previous work in style transfer [\(Krishna et al.,](#page-10-19) [2020b;](#page-10-19) [Hallinan et al.,](#page-9-8) [2023;](#page-9-8) [Xu et al.,](#page-12-7) [2018;](#page-12-7) [Patel](#page-11-14) [et al.,](#page-11-14) [2023\)](#page-11-14) proposes taking the *product* (or geometric mean) of the metrics (instead of drop rate, for style transfer we have target style strength, still bounded). The intuition is that these style transfer systems should *jointly optimize all metrics* rather than just one or two; this is reflected in taking a product.

In line with this past style transfer work, we choose to use the product, as we think high-quality obfuscations should jointly prioritize the three metrics of fluency, meaning similarity, and obfuscation, and so that we do not encourage systems that only optimize one or two of these metrics. However, we note that certain aspects might be more important for users than others, and they might not want to use an equally weighted total.

However, as an alternative overall metric, *we present the overall score as an equally weighted average* of the drop rate, grammar, and content score below, rather than a product. See these results in Table [7.](#page-17-2) We note that this was used in other authorship obfuscation papers as an overall total metric as well [\(Fisher et al.,](#page-9-1) [2024\)](#page-9-1). Here, we again see STYLEREMIX performs best overall in 3 of the 4 datasets. Note that the decrease in performance on Scholar split of AUTHORMIX is due to the very low obfuscation rate among all methods, which results in only a difference of 5% between STYLEREMIX and the main method.

C Method Details

C.1 Style Axes Selection and Evaluation

We choose seven different style axes. The first three style axes have rule-based evaluation; length, use of function words, and grade level. For length, we evaluate using the average words per sentence and for function words we use the number of function words. Additionally, we incorporated "grade level," which primarily measures the number of syllables. Since this measure can vary slightly, we averaged three similar metrics: the Flesch-Kincaid (FK; [Flesch,](#page-9-3) [1948\)](#page-9-3), Linsear Write (L; [O'Hayre\)](#page-11-3), and the Gunning Fog Index (GF; [Gunning,](#page-9-4) [1952\)](#page-9-4) metrics. The exact formulas are given below; for more details, see [https://github.com/textstat/textstat.](https://github.com/textstat/textstat)

• Flesch-Kincaid is computed via:

$$
KF = 0.39 \left(\frac{\text{total words}}{\text{total sentences}}\right) + 11.8 \left(\frac{\text{total syllables}}{\text{total words}}\right) - 15.59
$$

- Linsear Write is computed by:
	- 1. Take a 100-word sample from the text
	- 2. Make a score starting with 0. For every "easy" word $(< 2$ syllables), add 1 point. Otherwise add 3 points ("hard" words have $>$ 3 syllables).
	- 3. Divide points by number of sentences in the 100-word sample.
	- 4. Divide by 2 if the points $<$ 20, otherwise divide by 2 and subtract 1.
- Gunning Fog is computed by selecting a passage around 100-words long, then applying the following formula:

$$
GF = 0.4 \left[\left(\frac{\text{words}}{\text{sentences}} \right) + 100 \left(\frac{\text{complex words}}{\text{words}} \right) \right]
$$

where complex words are words with three or more syllables.

The next four style axes have model-based evaluation; use of sarcasm, voice (active or passive), formality, and writing intent (descriptive, expository, narrative, and persuasive). Although these were chosen arbitrarily, we believe they do reflect some unique aspects of authorship style. However, these styles do require a unique classifier to automatically evaluate a text. For formality we used a RoBERTa-base [\(Liu et al.,](#page-10-7) [2019\)](#page-10-7) based formality classifier [\(Babakov et al.,](#page-9-10) [2023\)](#page-9-10), found at [https://huggingface.co/s-nlp/roberta-base](https://huggingface.co/s-nlp/roberta-base-formality-ranker)[formality-ranker.](https://huggingface.co/s-nlp/roberta-base-formality-ranker)

However, for the other three axes (voice, sarcasm, and writing intent) there was not a reliable, existing model, so we trained our own classifiers. We follow the same procedure to make DISC detailed in Section [2.1,](#page-1-1) but 1) with *different* base training data, to ensure that there is no overlap between the classifier and adapter data and 2) only for the following style elements: voice passive, voice active, sarcasm less, sarcasm more, and persuasive, expository, narrative, and descriptive. With the new datasets of length 1500 for each style element, we then train RoBERTA-large [\(Liu et al.,](#page-10-7) [2019\)](#page-10-7) discriminators for the voice, sarcasm, and writing intent categories, splitting the train into 85% train and 15% dev set. We set the seed to 0 and train with a batch size of 128, learning rate of 5e-5, and for 5 epochs.

For all models, we choose the checkpoint with the best evaluation accuracy product (to ensure high accuracy for all classes); this corresponded to 100%, 99.1%, 45.5% for sarcasm, voice, and type respectively. Each model took approximately 1 hour to train using 1 NVIDIA A100 GPU with 80 GB of VRAM.

C.2 DISC Training Data and Evaluations

We use GPT4-Turbo [\(OpenAI,](#page-11-5) [2023\)](#page-11-5) to distill the style axes into 16 parallel training sets. We collect 1500 paragraphs from Wikipedia, books and plays, and blogs, then prompt GPT4 with the following: "Rewrite the following paragraph to include the same content but specific prompt\n Paragraph: paragraph \n Rewrite: " where paragraph is the original data. Depending on the target style, we change the specific prompt to:

- Length short: "being more succint"
- Length long: " being more verbose."
- Lower grade-level: "using language an early elementary school student can understand."
- Higher grade-level: "use high school reading level or above."
- More function words: "using far less function words (i.e. pronouns, determiners, and conjunctions)."
- Less function words: "using far more function words (i.e. pronouns, determiners, and conjunctions)."

			Llama-2-Chat Llama-3-Inst Gemma-Inst Paraphrase MT					Stylo JD		StyleRemix		
Dataset	7B	13B	8B	70 _B	7B					Sea.	AM	AM+LoraHub ⁺
Speech	56.60	57.30		55.17 55.73 56.50		59.73		51.43 47.47 47.43 55.97 61.67 56.40				
Novels	55.63	56.07	55.13	56.07	55.07	53.47	46.17	46.13	48.23	58.53	57.60 57.33	
Scholar	52.27	52.03	51.53	51.03	51.40	53.73	49.60	40.47	43.00	48.53	44.37 41.67	
Blog	56.20	56.47	57.07	56.90	58.10	57.47	45.00	42.33	54.03	57.73	59.87	60.50

Table 7: Results from Table [2,](#page-4-1) but now using an **equal-weighted average** as the overall score rather than the product of metrics, across all domains and models.

- More sarcasm: "with more sarcasm."
- Less sarcasm: "with less sarcasm."
- More formal: "with more formal language."
- More informal: "with more formal language."
- Active voice: "with active voice."
- Passive voice: "with passive voice."
- Persuasive writing style: "with persuasive writing style."
- Expository writing style: "with expository writing style."
- Narrative writing style: "with narrative writing style."
- Descriptive writing style: "with descriptive writing style."

We use sampling with a temperature of 1.0. As a result of this prompting, we achieve $1500 \cdot 16 =$ 24000 generations spanning 16 unique style directions from GPT-4.

We then validate the quality of this data. For axes with available automatic metrics, specifically length, function words, grade level, and formality, we run their respective metrics on the original texts, and on the GPT-4 generations in both directions, ie., we run the formality classifier on the original texts, and on both the more and less formal GPT-4 generations. For the axes without automatic evaluation, we instead randomly evaluate 10% of them. Specifically, we randomly combine generated data from the same style axis but different directions (such as more and less sarcasm), and ask annotators (three NLP experts) to label if the style axis is high or low (or the specific type for Writing Type), then compute the accuracy.

Table [1](#page-3-1) shows the results. For the metrics that we can automatically evaluate, our generated data captures the desired axes and directions well; for example, the texts steered towards higher length have the highest average number of words per sentence. For sarcasm and voice, human evaluations of 97.7% and 93.7% respectively indicate that the generations match the targeted directions. For writing intent, the human evaluation accuracy is 77.7% which is still a good number as the task of discriminating between four classes is inherently more complex.

C.3 Style Adapter Training

We train LoRA adapters [\(Hu et al.,](#page-10-1) [2021\)](#page-10-1) using each of the 16 generated parallel datasets. Specifically, we train LLama-3 8B (base model) on the following prompt for each of the datasets:

<bos>### Original:{original} \n ### Rewrite: {rewrite} <eos>

where original and rewrite denote the original text and rewrite is the text we generated from GPT-4. Note that the format we train on is the same for all parallel datasets to make future model merging more effective.

We train the 16 LoRA modules each for 5 epochs with a seed of 0, batch size of 6, and a max sequence length of 512; we choose the checkpoint with the best eval loss and have an early stopping criteria of 5. For LoRA parameters, we use use $r = 32$, the rank of the matrix, and the alpha and dropout values of 32 and 0.01 respectively. Overall, each LoRA adapter involves training 13 million parameters each, about 0.16% of the total parameters in LLama-3 8B.

All of our models train well over time on both train and eval loss; please see our repository for exact training curves and loss numbers for the 16 models. We train each of the models on a single A100 80GB GPU for about 2 hours each.

C.4 Concatenating Style Adapters

Given a model with weights W_0 of dimension $d \times d$ LoRA freezes W_0 and trains two matrices: A of size $r \times d$ and B of size $d \times r$. At inference, we use the new weights of $W = W_0 + BA$.

In the situation when we have n LoRA adapaters, parameterized by $A_1...A_n$ and $B_1...B_n$ and want to ensemble them for inference, we use **con**catenation. Specifically, we concatenate each of the $A_1...A_n$ matrices resulting in a matrix $A_{1...n}$ of size $nr \times d$. Similarily, we concatenate each of $B_1...B_n$ resulting in a matrix $B_{1...n}$ of size $d \times nr$. We then can combine the matrices the same way to get new weights of $W = W_0 + B_{1...n}A_{1...n}$. Notably, we have no additional inference latency by concatenating the vectors, only a slightly increased fixed matrix multiplication cost.

C.5 Style and Weight Selection

As described in our paper, we developed an automatic method for selecting the style axes to change, direction, and weights of the adapters. First, we create an author vector for each author in a domain, which is a vector with 10 automatic evaluations: average words/sentences, average number of function words, average grade level (using FK, L, GF) [\(Flesch,](#page-9-3) [1948;](#page-9-3) [O'Hayre;](#page-11-3) [Gunning,](#page-9-4) [1952\)](#page-9-4), average likelihood score from formality classifier [\(Babakov](#page-9-10) [et al.,](#page-9-10) [2023\)](#page-9-10), average likelihood score from sarcasm classifier (see Appendix [C.1](#page-16-0) for more details), average likelihood from a voice classifier (see Appendix [C.1](#page-16-0) for more details), average classification into each of the four writing intents. We label this vector for author *i* as $x_i \in \mathbb{R}^{10}$.

In order to select the k number of styles axes to change, we use the other authors in the same domain as a baseline. Specifically, we average the values from all authors in the domain and find the styles of author i that are furthest from this average vector. More specifically, we use the following formula:

$$
s
$$
 to change $=$ top_k $\left(\left| x_i - \sum_{j=1}^m x_j \right| \right),$

where we have m total authors in the domain and $top_k(y)$ is a function which selects the rows of y with the highest values. Similarly, we use the sign of this difference to decide on the direction of the change. For example, if the sign of the difference is negative, then the author's style value is lower than the average and we will implement a higher direction (driving the style up to average).

Once the styles axes are selected, we use different methods for choosing the adapter weights

for each style axes. First, we also use the author difference vector to select the weight of the adapter. To do this, we calculate the number of standard deviation the author's value is from the average vector. We then use this metric to map to a static weight; see Table [12.](#page-22-1) We note that these weights were selected in line with past work [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4).

Second, we employ a non-gradient based optimization method called LoraHub [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4). This method uses a few validation examples to optimize the values. For this method, we developed our our loss function which is the sum of the chosen style axes automatic evaluations as well as the grammar. Specifically,

$$
L = \sum_{v_i \in \text{selected axes}} \begin{cases} v_i & v_i \leq \frac{1}{m} \sum_{j=1}^m x_i \\ 1 - v_i & v_i > \frac{1}{m} \sum_{j=1}^m x_i \end{cases}
$$

where v_i represents the style value for a selected style axis of the obfuscated text and the grammar score. In Table [9,](#page-19-0) we show the difference between the base initial weights, chosen using the static method, to the once optimized using LoraHub.

Table 8: This shows the static mapping used in the base adapter merging method. We use the number of standard of deviations an authors automatic style score is from the average style score of all authors in that domain. The static values were chosen base on past work [\(Huang](#page-10-4) [et al.,](#page-10-4) [2023\)](#page-10-4)

D Experimental Details

In this section we provide full details of the experimentation used in this paper. We start with the dataset in Appendix [D.3,](#page-20-0) method implementations for each method in Appendix [D.4,](#page-20-1) and our evaluation methodology in Appendix [D.5.](#page-21-0)

D.1 Software

We used Python 3.10.13, Pytorch 2.1.2, Hugging-Face Transformers 4.39.3. and NLTK 3.8.1. All code is licensed under the Apache License 2.0.

D.2 Hardware

All experiments were run on eitiher a single NVIDIA A100 GPU or 4 NIVIDIA A100 GPUs

Table 9: Comparison of the initial base weights, chosen using the standard deviation to static mapping, and the optimized LoraHub weights, found using our customized loss function. We show the style axes changed, the base weights and the LoraHub weights for each author in each domain.

with 80GB memory. We estimate our total computational use to be approximately 80 GPU hours.

D.3 Data

Table 10: Details of AUTHORMIX, including the number of samples for the test/eval/train for each domain.

As mentioned, we wanted to use a test dataset which had a wide range of diverse authorship styles as well as domains. For this reason, we decided to create a new data set on authorship obfuscation called AUTHORMIX. This dataset is composed for four domains; presidential speeches, early 1900s fiction novels, scholarly articles, and dairy-style blog entries. Altogether, AUTHORMIX contains over 30,000 high-quality paragraphs from 14 authors.

For the presidential domain, we curate and clean a novel collection of high-quality presidential speeches from George W. Bush ($n = 38$), Barack Obama ($n = 29$), and Donald Trump ($n = 26$)^{[8](#page-20-2)}, transcribed by the Miller Center [\(Miller Center of](#page-11-20) [Public Affairs\)](#page-11-20)^{[9](#page-20-3)} at the University of Virginia. We broke the speeches naturally into paragraphs and then selected all paragraphs between $2 - 5$ sentences. This resulted in a total of $n = 13K$ paragraphs.

Similarly, we also decided to develop a new collection of early 1900s fiction writers from the with strong writing styles, therefore we choose text from books by Ernest Hemingway, F. Scott Fitzgerald, and Virginia Woolf which were collected from Project Gutenberg [\(Gutenberg\)](#page-9-11). We selected the top 4 most popular books on Project Gutenberg

for each author and then again, used the natural paragraphs from each author. We selected all paragraphs between $2 - 5$ sentences. This resulted in a total of $n = 9K$ paragraphs.

Lastly, we altered the existing data from two current datasets, the Extended-Brennan Greenstad [\(Brennan et al.,](#page-9-6) [2012\)](#page-9-6) which is a collection of "scholarly" short (500-word) paragraphs gathered from Amazon Mechanical Turk (AMT) and the Blog Authorship corpus [\(Schler et al.,](#page-11-8) [2006b\)](#page-11-8), a collection of blogs (diary-style entries) that were posted to blog.com. We note, these datasets match those used in [\(Haroon et al.,](#page-9-2) [2021\)](#page-9-2), [\(Mahmood](#page-11-1) [et al.,](#page-11-1) [2019\)](#page-11-1), and [\(Fisher et al.,](#page-9-1) [2024\)](#page-9-1). For the AMT dataset, we used authors "h", "pp", and "qq" and we artificially created paragraphs by chunking the text into a random collection of 2-5 sentences (as the text is not naturally broken into paragraphs). For the Blog dataset, we used authors "5546", "11518", "25872", "30102", "30407", we used the natural paragraphs. Then, to match the speech and novel domains, we edited to include all paragraphs between 2 − 5 sentences and 3 words. This resulted in $n = 500$ and $n = 8K$ paragraphs for the AMT and Blog accordingly.

D.3.1 Artifact Terms of Use

Our artifacts allow for fair use under Project Gutenberg [\(Gutenberg\)](#page-9-11): [https://gutenberg.](https://gutenberg.org/policy/terms_of_use.html) [org/policy/terms_of_use.html](https://gutenberg.org/policy/terms_of_use.html)

D.4 Method Implementation

D.4.1 Baselines

For each baseline, we use the optimal set of hyperparameters reported in its respective paper.

Stylometric (Stylo) We used [\(Karadzhov et al.,](#page-10-0) [2017\)](#page-10-0) method for AO using stylometric methods, which was originally proposed in the PAN-2016 Author Masking Shared Task competition [\(Mi](#page-11-21)[haylova et al.,](#page-11-21) [2016\)](#page-11-21). This method calculates metrics for 12 features that are indicative of style, then modifies the text, so these metrics align with an "average" value. The "averages" were calculated using a combination of training sets including the PAN-2016 Author Obfuscation task [\(Mihaylova](#page-11-21) [et al.,](#page-11-21) [2016\)](#page-11-21) and public domain books from Project Gutenberg [\(Gutenberg\)](#page-9-11). Examples of the metrics this method uses include the average number of words per sentence, word frequency, and the use of uppercase letters. Changes employed include actions such as sentence splitting and merging, sub-

⁸These presidents were selected due to their diverse styles but similar time periods, which minimizes content discrepancies.

⁹<https://data.millercenter.org>

stitution of words with synonyms, and alterations in spelling. For a full list of metrics and proposed changes, see the [\(Karadzhov et al.,](#page-10-0) [2017\)](#page-10-0). To further enhance the obfuscation process, the method introduces "noise" by modifying words that differ between English and British English and introducing additional functional words. We make no changes to the hyperparameters used in the original method.

Machine Translation (MT) We used a roundtrip machine translation method proposed by [Keswani et al.](#page-10-5) [\(2016\)](#page-10-5). In this method, they translate the original text from English to German, German to French, and then French back to English. We enhanced their method by use of the new M2M translation model [\(Fan et al.,](#page-9-7) [2020\)](#page-9-7), which does not rely on English as an intermediate language.

JAMDEC (**JD**) This method was proposed by [Fisher et al.](#page-9-1) [\(2024\)](#page-9-1) and uses a small language model, GPT2-XL [\(Radford et al.,](#page-11-9) [2019\)](#page-11-9), as the base model. For this method, they use a three stage approach where they extract the keywords of text (to guide generation to have the same content), overgenerate using diverse constrained beam search, and then filter based on grammar and content overlap. We used this model's default parameters, with a beam width of 10, and only using the likelihood keyword extractors, which was recommended to be just as effective but take less time. More details of this methods' implementation can be found [\(Fisher](#page-9-1) [et al.,](#page-9-1) [2024\)](#page-9-1).

Paraphrasing We used the paraphrasing model from [Jung et al.](#page-10-6) [\(2024\)](#page-10-6). This model uses Google T5 [\(Raffel et al.,](#page-11-22) [2020\)](#page-11-22) as the base and is finetuned on the dataset DIMPLE, which is a dataset of 4M high-quality pairs of paraphrases.

Instruction LLMs Lastly, we wanted to compare with LLMs of similar and bigger sizes. For these, we opted to use instruction tuned models which could easily follow instruction to rewrite the text. For each model, we used a temperature of 1.0 and a top-p of 0.9. Table [11](#page-22-2) shows the exact prompts used to generate the generations from each of the baseline LLMs.

D.4.2 STYLEREMIX

Style and Weight Selection We used the described automatic style and weight selection described in the paper and in Appendix [C.](#page-16-2) We note

that almost all values were less than 3 standard deviations, with the majority between $0 - 2$.

Adapter Merging We used three different ablation of our methods; sequential, adapter merging base, and adapter merging LoraHub+. For the sequential method, we averaged results over $n = 3$ random shuffling of style axes orders. For the adapter merging base method we used the weight adapter found from mapping using the standard deviations.

For the adapter merging LoraHub+, we build on the prior LoraHub method [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4). We used the weights selected using our mapping method as the initial values and then used a nongradient based optimization [\(Liu et al.,](#page-10-21) [2020\)](#page-10-21) over a new customized loss function. The loss function adds together the automatic evaluations from the author vector (described in Appendix [C.5\)](#page-18-0) for the specific style axes that are being considered for merging. Note, that since we are optimizing by finding the lowest loss, if the direction of the style axes is "higher" we take $1 - value$ and if the direction is "lower" we just add the value. Lastly, we also add the grammar score into the loss to maintain good fluency. Then, a non-gradient based optimization method is use [\(Liu et al.,](#page-10-21) [2020\)](#page-10-21). Note, we use non-gradient based due to the large number of parameters of the model. We provide a comparison of the base weights chosen and the optimized LoraHub weights in Table [9.](#page-19-0)

Hyperparameter Selection To tune the hyperparameters of STYLEREMIX, we use the validation split of AUTHORMIX.

D.5 Evaluation Methodology and Other **Details**

Obfuscation: Classifier We train classifiers over each of the four domains in AUTHORMIX to measure obfuscation during evaluation using their respective training and development sets. Specifically, for each of AUTHORMIX- { speech, novels, scholar, blog }, we train a RoBERTa-Large classifier [\(Liu et al.,](#page-10-7) [2019\)](#page-10-7) with a learning rate of 5e-5, batch size of 64, seed of 0, a max length of 256, and for 10 epochs. We set an early stopping threshold of 5, and choose the best checkpoint based on the best evaluation accuracy product (to ensure high accuracy for all classes).

Overall, our final evaluation accuracy products for AUTHORMIX- {speech, novels, scholar, blog }

Model	Instruction
Llama 2	"[INST] «SYS» \n You are a helpful assistant.\n \n «/SYS» \nPlease rewrite the following: <paragraph>[/INST] Rewrite: "</paragraph>
Llama 3	"[INST] «SYS» \n You are a helpful assistant.\n \n \div(SYS) \n Please rewrite the following: <paragraph>[/INST] Rewrite: "</paragraph>
Gemma	"You are a helpful assistant.\n\nPlease rewrite the following: <paragraph>Rewrite: "</paragraph>
Mistral	" \leq \le

Table 11: The instruction used for prompting the LLMs used as baselines.

Table 12: This shows the static mapping used in the base adapter merging method. We use the number of standard of deviations an authors automatic style score is from the average style score of all authors in that domain. The static values were chosen base on past work [\(Huang et al.,](#page-10-4) [2023\)](#page-10-4)

are 74.5%, 85.6%, 100%, and 70.8%, while the average overall accuracies are 90.6%, 95.8%, 100%, and 93.3%. Further training details including loss functions can be found in our repository. We train each of these models with a single NVIDIA A100 80 GB GPU for approximately 2 hours.

Content Preservation: Cosine Similarity We compute neural text embeddings on the inputs and their obfuscations in Sentence Transformers [\(Reimers and Gurevych,](#page-11-12) [2019\)](#page-11-12). Next, we use the cosine similarity between the two vectors to gauge semantic similarity and get a approximation of content preservatinon. Note that though the cosine similarity can output values from -1 to 1, we find on all of our validation dataset (across all datasets and methods) all similarities between inputs and their obfuscations are non-negative, with a bound of 0 to 1. If the similarity metric were to, in a very rare case, have a negative value, we would set the value to 0 so that we could have a still meaningful overall product of metrics; however, we never observe this.

Grammar: CoLA To ensure both fluency and grammaticality, we use TextAttack [\(Morris et al.,](#page-11-13) [2020\)](#page-11-13), a RoBERTa-large model [\(Liu et al.,](#page-10-7) [2019\)](#page-10-7) fine-tuned on the Corpus of Linguistic Acceptability (CoLA; [Warstadt et al.,](#page-12-6) [2018\)](#page-12-6) which includes 10,600 sentences with binary annotations for linguistic acceptability.

E Human Evaluation

We omit the MT and Stylo methods from human evaluation as [Fisher et al.](#page-9-1) [\(2024\)](#page-9-1) show that JamDec outperforms them in previous work for both automatic and human evaluation. We also omit 13B and 70B models for fair comparison. Finally, we report human evaluation for the best performing STYLEREMIX.

We used workers from Amazon Mechanical Turk (AMT) who voluntarily opt-in to the task to annotate $n = 20$ text from each author. Each text was annotated by $n = 3$ authors, who were paid at a rate of 15\$/hour. Our annotators are from Englishspeaking countries. A screenshot of the interface is shown in Figure [7](#page-25-0)

Our agreement numbers for the five metrics we collect, grammaticality, fluency, content preservation, low content addition, and obfsucation are 99.8, 98.2, 95.3, 93.8, and 93.5% respectively.

To compute the overall score, it would be unfair to take the product of our metrics (grammaticality, fluency, content preservation, low content addition, and obfuscation), since content preservation and fluency have two metrics representing their category, while obfuscation has only one; rewrites that simply output fluent, content-preserving texts would score higher than more balanced obfuscations which sacrifice small amounts of content preservation. Instead, we take a *weighted* product. Our overall product is computed as:

This product fairly takes the product of the three major categories (fluency, content preservation, and obfuscation), which aligns with our automatic metrics.

F Alternative Obfuscation Evaluation **Metrics**

To verify the obfuscation effectiveness of STYLEREMIX, we run an alternative evaluation to measure drop rate using the method from Learning Universal Authorship Representations (LUAR; [Soto et al.,](#page-11-11) [2021\)](#page-11-11) and train models to learn authorship embeddings for each of the four domains in our AuthorMix dataset (speech, novels, scholar, and blog) using the training data. We use the default hyperparameters from the codebase (ie, training for 20 epochs, using sentencetransformers/paraphrase-distilroberta-base-v1 as the base model, etc).

Next, we create authorship embeddings for all authors by passing their validation data into the trained models with their respective domain where they are aggregated, resulting in a single embedding for each author. To perform authorship attribution and obtain predictions for a set of input data of size N over some domain (such as speech), we first pass the input data through the trained model to extract individual embeddings before they are aggregated, resulting in N input embeddings. For each of these input embeddings, we calculate the cosine similarity with each validation authorship embedding in the specified domain. The predicted authorship style is the one with the highest cosine similarity.

As with our RoBERTa models, we can compute the drop rate for the LUAR method. Recall that the drop rate is the drop in accuracy of the classifier evaluated on the original text and the obfuscated text, where accuracy represents how many of the text the classifier correctly identified the author. For each domain in AuthorMix, we obtain the initial classification accuracy with the LUAR method using the test set. Then, we calculate the LUAR drop rate for our StyleRemix methods and for the baselines.

In Table [13,](#page-24-0) we display Table [2](#page-4-1) from the main obfuscation results, but now add two new rows which we compute: [NEW] Drop Rate w/ LUAR, the drop rate with LUAR, and [NEW] Overall (using Drop Rate w/ LUAR), the overall obfuscation quality, equivalent to the product of the grammar, content and Drop Rate w/ LUAR which we compute.

Across all datasets, the new authorship attribution results with LUAR aligns with our RoBERTa based results and reinforces the strong obfuscation results of StyleRemix over baselines. Specifically, across all datasets, StyleRemix has the highest LUAR drop rate on the speech, novels, and scholar datasets, and the second-highest LUAR drop rate on the blog dataset, beating much larger baselines like Llama-3-70b-Inst. This is the same as the previous obfuscation results and underlines the effectiveness of StyleRemix for obfuscation. Furthermore, the new overall metric with LUAR drop rate confirms the results from the original overall metric: over all datasets, StyleRemix generates the best overall obfuscations, beating all baselines.

Overall, our additional evaluation using LUAR authorship attribution confirm the previous result obtained with the RoBERTa classifiers and demonstrates the excellent anonymization capabilities of StyleRemix.

Table 13: Comparison of obfuscation methods measured by 1) mean drop rate, grammar, meaning similarity, and overall (the same metrics and results as in Table [2\)](#page-4-1) and 2) additionally with an alternative, LUAR-based drop rate metric and a new overall score computed with this drop rate. Bold and underline denote the highest and the second-highest score respectively in each row. All metrics displayed in the table are multiplied by 100 for easier viewing of significant figures.

Thanks for participating in this HIT! Please read the instructions carefully.

In this HIT, you'll be asked to give feedback on the effectiveness for a method to hide (obfuscate) a specific authors' writing style. You will be
given the <mark>original text</mark> (written by Author A) and a rewritten text which ase consider the following attributes of the <mark>rewritten text</mark> in comparison to the <mark>original text</mark>

Characteristics of a good rewritten text:

- . Sensible: The rewritten text should be grammatically correct and make logical sense
-
- sensitive. In the contract least should be present in the rewritten text. The rewritten text should NOT be a
paraphrase or summary of the original text, but instead contain all the original content and sentiment. However
- . Style: The rewritten text should be stylistically different from the original text. In other words, you should have a hard time identifying that the rewritten text was written by Author A.
- You will be asked the following 5 questions to evaluate the quality of the rewritten text
- 1. Grammar: How grammatically correct is the rewritten text? · Tip: Does the rewritten text have good grammar?
- 2. Fluency: How fluent (natural sounding) is the rewritten text?
- 3. Content Preservation: How much content is preserved in the rewritten text compared to the original text?
	- o Tip: This means the rewritten text should contain all the important information (e.g., names, places, actions) from the original text Tip: The rewritten text **should NOT** be a summary or paraphrase of the original text.
	-
- Tip: The rewritten text **should NOT** be a summary or paraphrase of the original text.
4. Content Addition: Is there <u>new content added</u> in the rewritten text not in the **original text?**
• Tip: The rewritten text should 5. Style: How similar is the style between the rewritten text and the original text?
- ∘ Tip: Style can compose of many factors including word choice, punctuation, use of slang, sentence structure, etc.
∘ Tip: Having different styles means that you would not guess that Author A wrote the rewritten text.

Examples (click to expand/collapse)

Example 1: للعامل

- l<mark>g*inal Text:*</mark>
| was wondering if you could recommend any good cheese?| am having a dinner party and would love to serve some as an
| appetizer.
- P_{out} uppeazer.
ritten Text 1: **Contract Contract Contract Contract Property** and a dinner partie and would love to give to people.
Grammar: <mark>Cad</mark> Fluency: **Cad Content Preservation: Fair Content Addition: Fair Content Contract Cood Style: Fair**
- **Rewritten Text 2:** .
e you could offer a recommendation for? Tonight, there is a dinner party I am hosting and giving some at the
- ecervicer / Zex.ex you could offer a recommendation for? Tonight, there is a dinner party I am hosting and giving some at the
The thermonistic good.
Grammar: <mark>tagin</mark> Fluency: <mark>The T</mark>Content Preservation: <mark>Trance/Coop Cont</mark>

$example$ **Original Text**

- המושב ו Land
A recent NC State University graduate won the cheese-rolling women's ' championship in 2022. She said she "practiced
for hours", rolling down many hills in preparation. **Rewritten Text 1:**
- Rewritten Text 1:

Search 2022 a NC State University studant (who had just graduated) won the cheese-rolling women's championship.
 Grammar: <u>Exaces University</u> recent graduate won the cheese-rolling women's championship
-
-

Example 3:

- and the moment writing a lengthy indictment against our century. When my brain begins to reel from my literary
Tahors. I make an occasional cheese dip.
-
- labors, Imake an occasional cheese dip.
 Rewritten Text 1:

Ham at the moment drafting a lengthy indictment against our era. When my brain begins to weaken from all my

likerary labors, Isometimes make an aromatic cheese
-
- **Rewritten Text 2:**
First community and the head withing a massive rant about how messed up our century is. But hey, when my head
starts spinning from all that heavy thinking and writing, I take a breather and whip up some

Figure 7: Instructions used in the human evaluation

Fair I have some doubt the the two texts are written by the same autho **Bad** The authors of the two text are definitely the same.

G Further Examples

Llama2 (7B) What are the key takeaways from the Nepal case study?

More qualitative examples of different methods.