# Self-Instructed Derived Prompt Generation Meets In-Context Learning: Unlocking New Potential of Black-Box LLMs

Zhuo Li<sup>1,2\*</sup>, Yuhao Du<sup>1,2\*</sup>, Jinpeng Hu<sup>3</sup>, Xiang Wan<sup>1</sup>, Anningzhe Gao<sup>1†</sup>

<sup>1</sup>Shenzhen Research Institute of Big Data <sup>2</sup>The Chinese University of Hong Kong, Shenzhen <sup>3</sup>Hefei University of Technology {zhuoli3, yuhaodu}@link.cuhk.edu.cn, jinpenghu@hfut.edu.cn, {wanxiang, gaoanningzhe}@sribd.cn

#### Abstract

Large language models (LLMs) have shown success in generating high-quality responses. In order to achieve better alignment with LLMs with human preference, various works are proposed based on specific optimization process, which, however, is not suitable to Black-Box LLMs like GPT-4, due to inaccessible parameters. In Black-Box LLMs case, their performance is highly dependent on the quality of the provided prompts. Existing methods to enhance response quality often involve a prompt refinement model, yet these approaches potentially suffer from semantic inconsistencies between the refined and original prompts, and typically overlook the relationship between them. To address these challenges, we introduce a self-instructed in-context learning framework that empowers LLMs to deliver more effective responses by generating reliable derived prompts to construct informative contextual environments. Our approach incorporates a self-instructed reinforcement learning mechanism, enabling direct interaction with the response model during derived prompt generation for better alignment. We then formulate querying as an in-context learning task, using responses from LLMs combined with the derived prompts to establish a contextual demonstration for the original prompt. This strategy ensures alignment with the original query, reduces discrepancies from refined prompts, and maximizes the LLM's in-context learning capability. Extensive experiments demonstrate that the proposed method not only generates more reliable derived prompts but also significantly enhances LLMs' ability to deliver more effective responses, including Black-Box models such as GPT-4.

#### Introduction

The emergence of Large Language Models (LLMs) has significantly advanced the field of Natural Language Processing (NLP), achieving remarkable results across various tasks (OpenAI et al. 2023; Srivastava et al. 2022; Brown et al. 2020; Touvron et al. 2023; Devlin 2018). The success of these models is highly dependent on the quality of the input prompts, as ambiguous or insecure prompts can lead to low-quality and unreliable responses (Zhou et al. 2022; Zamfirescu-Pereira et al. 2023; Liu et al. 2023). Additionally, the high training costs associated with the large parameter sizes of these LLMs make it challenging to fine-tune for alignment when handling downstream tasks. In particular, for **Black-Box** LLMs, training is impossible. Therefore, utilizing better prompts to guide the models in generating the desired outputs has become an effective approach in applying LLMs to various tasks.

To this end, several approaches are proposed to find the optimal prompts that can generally promote LLMs across various tasks. A popular approach that improves the quality of the prompts is prompt engineering, which aims to refine the prompts with templates designed manually (Tam et al. 2021; Reynolds and McDonell 2021). However, this approach is limited in specific scenarios and requires the creation of new templates when transitioning to a new scenario, resulting in a high manual workload and limited usability (Webson and Pavlick 2021). Therefore, some methods are proposed to rewrite prompts, which usually leverage the powerful capabilities of LLMs (e.g., GPT-4) by directly asking the model to refine the prompts (Zhou et al. 2022; Fernando et al. 2023), or by training a dedicated prompt refinement model to enhance prompt quality (Cheng et al. 2023; Deng et al. 2022; Kong et al. 2024).

While these methods have achieved significant results, several challenges may limit their practical use on downstream tasks. For example, previous methods often require extensive data collection (Cheng et al. 2023; Huang et al. 2024) and complex template design (Webson and Pavlick 2021), and the lack of interaction with the queried model (e.g., response model) that is used in downstream tasks during rewritten can result in prompts not fully compatible with it (Deng et al. 2022; Cheng et al. 2023). Moreover, the prompt rewriting process may introduce semantic inconsistencies between the refined and original prompts, potentially leading to less effective responses, as shown in Tab. 1. Given these considerations, we raise the following question:

Is there a more effective way to prompt the response model (e.g., Black-Box GPT-4) than solely generating a refined prompt?

Based on the success of in-context learning (ICL) with LLMs, which improves model performance with additional closely related demonstrations (Dong et al. 2022), we propose a novel framework to stimulate LLMs to generate more helpful and reliable responses by automatically constructing an informative in-context environment for the original prompt. Instead of training a prompt refinement model

<sup>\*</sup>These authors contributed equally.

<sup>&</sup>lt;sup>†</sup>Corresponding author.

Case 1	Original Prompt Refined Prompt	Human knowledge is a collection of definitions and observations. What is your opinion about this proposition ? What is the foundation of human knowledge and how do we acquire and organize it?
	Justification	The refined prompt diverges significantly from the original prompt by altering the focus and depth of inquiry.
Case 2	Original Prompt Refined Prompt	Describe the health benefits of green tea. Discuss the antioxidant properties of green tea and its role in preventing cancer.
	Justification	The refined prompt loses context. The original prompt asks about the health benefits of green tea in general, while the refined one focuses only on its antioxidant properties and role in cancer prevention, ignoring other benefits.
Case 3	Original Prompt Refined Prompt	Generate a product idea for a mobile application. Generate a product idea for a mobile application that helps users meet dietary goals through personalized nutrition and meal planning.
	Justification	The refined prompt overly narrows the focus compared to the original prompt. It limits the potential product ideas to only those related to a specific topic, neglecting other innovative possibilities within the mobile application space.

Table 1: Failed refined prompt cases. Case 1 is from directly asking Llama3-Instruct (Touvron et al. 2023) for a prompt refinement. Both Case 2 and Case 3 are from BPO (Cheng et al. 2023). *Justification* provides an analysis from GPT-4 on how the refined prompts fail to serve as an effective evolution compared with the original ones. More cases are provided in supplementary materials.

that might alter the original intent, we design a *derived* prompt generation model optimized by a self-instructed reinforcement learning (RL) objective. By integrating the response model into the RL training process, our method eliminates the need for training data collection and ensures closer alignment between the derived prompt and the response model. Moving beyond directly querying LLMs with the derived prompt as the final response, we example the derived prompt-response pair as a semantically relevant and high-quality demonstration (Liu et al. 2021) for the original prompt. This approach preserves the original prompt's information while leveraging the benefits of highquality in-context environment, which contains semantically similar information and response. Therefore, it effectively helps stimulate the LLMs' inherent knowledge, resulting in higher-quality and more helpful responses for original prompt. Extensive experiments on various downstream datasets show significant performance improvements in response quality than prompt refinement methods, where our method also improves Black-Box models (e.g., GPT-4) in producing higher-quality response, demonstrating a promising and interpretable paradigm for aligning LLMs without the modifications. We highlight our advantages as follows:

- Novel framework and preserving original intent. We introduce a new framework to align LLMs with human preference which can be applied to **Black-Box** models. Our framework automatically constructs informative incontext learning (ICL) environments to stimulate LLMs for higher-quality and more helpful responses, which is achieved by a high-quality demonstration for the original prompt based on the derived prompt, preserving its original intent of user prompt while leveraging the benefits of in-context learning.
- Data collection free and Better alignment. We propose to a self-instructed RL objective for effective derived prompt generation model optimization, where we integrate the response model into this training process, eliminating the need for extensive training data collection and better aligning derived prompts with it.
- Significant improvements. Extensive experiments on various downstream datasets demonstrate significant im-

provements in response quality over existing prompt refinement methods, including enhancements in Black-Box models (e.g., GPT-4), showcasing a promising and interpretable paradigm for aligning LLMs without modifications.

#### Background

**Supervised Fine-Tuning** Supervised Fine-Tuning (SFT) with annotated text descriptions is widely used to adapt LLMs into downstream tasks. Given prompt-response pairs (x, y) sampled from a distribution  $\mathcal{D}$ , SFT objective function is defined as:

$$\mathcal{L}_{\text{SFT}} = -\mathbb{E}_{(x,y)\sim\mathcal{D}}\left[\sum_{i} \log \pi_{\text{SFT}}(y_i|x, y_{< i})\right], \quad (1)$$

where  $\pi$  indicates a LLM policy and  $y_{<i}$  refers to all tokens before the *i*-th token in response *y*. In prompt rewritten task, *x* and *y* usually indicate original and refined prompt, respectively. For example, Cheng et al. (2023) collects various original-refined prompt pairs as (x, y) with the help of GPT-4 and then designs to optimize a prompt refinement model by minimizing Eq. 1.

**Reinforcement Learning from Human Feedback** Reinforcement Learning from Human Feedback (RLHF) is another effective tuning method for improving the alignment of LLMs with human preferences, which typically involves two steps: reward modeling and RL training. In reward modeling, a reward model  $\mathcal{R}$  is designed to measure response quality to an input prompt:  $\mathcal{L}_{\text{Reward}} =$  $-\mathbb{E}_{(x,y_c,y_r)\sim \mathcal{D}}[\log(\sigma(\mathcal{R}(x,y_c) - \mathcal{R}(x,y_r)))]$ , where  $y_c$  and  $y_r$  indicate good and bad response, respectively.  $\sigma$  is the sigmoid function. Generally, RL training uses the PPO algorithm (Schulman et al. 2017) with an additional Kullback-Leibler (KL) regularization as below:

$$\mathcal{L}_{\text{RLHF}} = \mathbb{E}_{(x \sim \mathcal{D}, y \sim \pi_{\theta}(y|x))} \left[ \mathcal{R}(x, y) - \beta \log \frac{\pi_{\theta}(y|x)}{\pi_{\text{SFT}}(y|x)} \right],$$
(2)

where  $\beta > 0$  is a hyper-parameter that controls the influence of the KL penalty. Training a prompt rewritten model



Figure 1: (a) Traditional methods directly replace the original prompt with a refined one, potentially risking semantic inconsistencies and ineffective responses. (b) Our method uses a derived prompt to create an in-context demonstration, ensuring high-quality responses while maintaining the integrity of the original prompt.

using Eq. 2 is still impractical because it requires collecting a dataset of original prompts and refinements, for obtaining a basic rewriter  $\pi_{SFT}$  and a specific reward model which can evaluate the quality of generated refined prompt.

#### **Motivation**

As shown in Fig. 1(a), previous methods that directly replace the original prompt with a refined prompt to query LLMs often overlook valuable information contained in the original prompt, leading to ineffective responses due to essential semantic inconsistencies between the original and rewritten prompts. Fig. 1(b) gives a illustration to our methods, which addresses this issue by generating a derived prompt that is used to query the response model. The derived prompt and its response are then employed to construct a semantically similar, high-quality demonstration for the original prompt. This in-context query process promotes the model's in-context learning capabilities more effectively, ensuring high-quality responses while consistently querying the original prompt, thereby avoiding ineffective results.

#### Methodology

#### **Task Formulation**

We first define the concept of a derived prompt and its generation process. A derived prompt x' is a transformation of the original prompt x that maintains close relevance and shows improved expression, without necessarily being a rewritten or refined prompt. Our goal is to train an effective generation model  $\pi$  that is initialized by a LLM (e.g., Llama3-Instruct) and can reliably produce a derived prompt  $x' \sim \pi(\cdot|x)$  given original prompt. Consequently, a higher-quality response y'can be generated by query a response model  $\mathcal{M}$ , still serving as a useful and effective feedback for x, due to their similar semantics. Generally, the model  $\pi$  can be a frozen Black-Box model (e.g., GPT-4) or a learnable model (e.g., the Llama family (Touvron et al. 2023)). In this research, we focus on optimizing a trainable model  $\pi$  parameterized by  $\theta \in \mathbb{R}^d$ , with the goal of x' to be more semantically derived to x and better aligned with  $\mathcal{M}$ .

<b>Algorithm 1:</b> Self-instructed RL for derived prompt generation model training.	
<b>Input</b> : Training Dataset $\mathcal{D}$ , DPG instruction $x_{DPG}$ ,	
a LLM initialized $\pi$ , frozen response model	
$\mathcal M$ and reward model $\mathcal R$ .	
<b>Output:</b> Derived Prompt Generation Model $\pi_{\theta}$ .	
1 Initialize $\pi_{\theta} \leftarrow \pi$ ;	
2 Initialize $\pi_{\text{ref}} \leftarrow \pi$ ;	
<b>3 for</b> Random Sample $a x$ in $\mathcal{D}$ <b>do</b>	
4   Obtain $X = \text{Concat}([x_{\text{DPG}}, x]);$	
5 Prompt $\pi_{\theta}$ to obtain derived prompt $x' \sim \pi_{\theta}(X)$ ;	
6 Prompt $\mathcal{M}$ to generate response $y' \sim \mathcal{M}(x')$ ;	
7 Compute reward value by $\mathcal{R}(x', y')$ ;	
8 Compute KL penalty by $\beta \log \frac{\pi_{\theta}(x' X)}{\pi_{\text{ref}}(x' X)}$ ;	
9 Update derived prompt generation model $\pi_{\theta}$ by	
maximizing $\mathcal{R}(x',y') - \beta \log \frac{\pi_{\theta}(x' X)}{\pi_{\text{ref}}(x' X)};$	
10 end	

# Self-instructed RL for Derived Prompt Generation Model

As mentioned in previous section, directly using Eq. 1 and 2 to optimize a derived prompt generation model  $\pi_{\theta}$  typically introduces onerous data collection and lacks of alignment between derived prompts and response model, leading to suboptimal compatibility with downstream tasks. To address these issues, we propose a self-instructed RL objective for effective refinement model training.

Let  $D = \{x_i\}_{i=1}^N$  denote a training data set of length N, which only includes the original prompts. Assume that we have a reliable reward model  $\mathcal{R}$ , which measures the response quality of the response model  $\mathcal{M}$  when using the derived prompt x'. Instead of utilizing pre-collected x' to optimize the model  $\pi_{\theta}$  in an offline mode, we aim to leverage the reward for  $\mathcal{M}$  response to x' to direct the optimization, which can further generate desirable x' that is better aligned with  $\mathcal{M}$  (We freeze  $\mathcal{M}$  during  $\pi_{\theta}$  training since the parameters of  $\mathcal{M}$  are inaccessible). To this end, we design to maximum the following objective:

$$\mathbb{E}_{(x \sim \mathcal{D}, x' \sim \pi_{\theta}(x'|x), y' \sim \mathcal{M}(x'))} \left[ \mathcal{R}(x', y') - \beta \log \frac{\pi_{\theta}(x'|x)}{\pi_{\text{ref}}(x'|x)} \right],$$
(3)

where x' is from the derived prompt generation model  $\pi_{\theta}(x)$ and y' is from the response model  $\mathcal{M}(x')$ ,  $\pi_{ref}$  is the reference model identically initialized by  $\pi$  and  $\beta$  is a hyperparameter for stable model training.

It is important to note that Eq. 3 relies on the  $\pi_{\theta}$  model having basic derived prompt generation capabilities. Given an original prompt x,  $\pi_{\theta}$  can directly rewrite it instead of performing the task in x (e.g., answering the question posed by x). Therefore, previous methods (Kong et al. 2024; Huang et al. 2024) necessitate an SFT stage to transform the pre-trained  $\pi$  into a prompt rewriter  $\pi_{\text{SFT}}$ , which initializes both  $\pi_{\theta}$  and  $\pi_{\text{ref}}$ , demanding extensive data collection of (x, x') pairs. Note that a well pre-trained  $\pi_{\theta}$  model (e.g., Llama3-Instruct) should inherently possess basic capabilities of instruction-following (Ouyang et al. 2022) and paraphrasing. Therefore, we propose to use a derived prompt generation (DPG) instruction  $x_{DPG}$  to overcome the necessity of SFT. Specifically, we manually design a  $x_{DPG}$ , which is provided in supplementary materials. As expected,  $\pi_{\theta}$  can still generate a useful derived prompt x' based its instructionfollowing capability:

$$X = \text{Concat}([x_{\text{DPG}}, x]),$$
  

$$x' \sim \pi_{\theta}(X).$$
(4)

With the help of  $x_{DPG}$ , our method can effectively eliminate the need for data collection and additional training costs introduced by SFT. Additionally, by strategically leveraging the  $\mathcal{M}$  into the training process of  $\pi_{\theta}$ , the generated derived prompts will be more in line with the preferences of the response model. Our final training objective is shown below:

$$\mathbb{E}_{(x \sim \mathcal{D}, x' \sim \pi_{\theta}(x'|X), y' \sim \mathcal{M}(x'))} \left[ \mathcal{R}(x', y') - \beta \log \frac{\pi_{\theta}(x'|X)}{\pi_{\text{ref}}(x'|X)} \right].$$
(5)

We summarize the training process in Alg. 1.

### Intent-consistency Oriented In-context Query Framework for Inference

Although the derived prompt generation model trained using Eq. 5 can produce higher-quality, semantically rich, and more compatible x' for the response model, there remains a risk of semantic inconsistency and intent shift due to the uncontrollability of the generation process. Consequently, directly replacing the original prompt with the derived prompt would not be the optimal solution to make full use of it.

To address the mentioned issue and better activate the LLM's inherent knowledge, we propose a general in-context query framework to mitigate potential semantic inconsistencies, where we leverage high-quality, relevant in-context demonstrations derived from the original prompt. Therefore, this approaches can effectively enhance LLM ability to better respond to the user's original query. As shown in Alg. 2, we construct an intent-consistent in-context query by filling the following template using (x, x', y'), where x, x', y' indicates the original prompt, its corresponding derived prompt and the LLM response to the derived prompt, respectively. This in-context query requires the better LLM respond to the original question x by emulating the quality, style, and level of detail of the response y' given to x':

### Question: {Derived Prompt x'}.
### Response: {Response y'}.

Given the above Question and Response as an example, emulate the way it responds to the question to reply to the following question:

*### Question: {Original Prompt x}.* 

Algorithm 2: Intent-consistency oriented in-context
query framework for inference.

	<b>Input</b> : Inference prompt $x$ , DPG instruction $x_{DPG}$ ,
	derived prompt generation model $\pi$ and a
	LLM to be quried.
	Output: Final response to user.
1	Obtain $X = \text{Concat}([x_{\text{DPG}}, x]);$
2	Generate refined prompt $x' \sim \pi(x' X)$ ;
•	<b>Drompt I I M to obtain response <math>u' = I I M(w')</math></b>

- 3 Prompt LLM to obtain response  $y' \sim \text{LLM}(x')$ ;
- 4 Fulfill the in-context query template with (x, x', y');

5 Query LLM and obtain final response;

This in-context query framework ensures that the final response aligns more closely with the original intent included in x, while maintaining the enhanced response characteristics corresponding to the derived prompt. Therefore, it mitigates potential discrepancies between the refined prompt and the original prompt, leading to responses that are more helpful, reliable, and consistent with user expectations.

#### **Implementation Details**

**Reward Model**  $\mathcal{R}$ . Recall that we use the generated response y' corresponding to the derived prompt x' to guide the optimization of  $\pi_{\theta}$ . To effectively evaluate the quality of generated pairs (x', y'), which determines the effectiveness of  $\pi_{\theta}$ , we employ a high-performance reward model that assigns a numerical score  $\mathcal{R}(x, y)$  to the response y of a model given a user query x, and reflects various aspects of response quality, including helpfulness, relevance, and coherence. This reward model is trained on hh-rlhf helpful dataset (Bai et al. 2022a) based on GPT2-Large. While theoretically, any reasonable reward model  $\mathcal{R}$  can also be used.

**Response Model**  $\mathcal{M}$ . In the training process of the derived prompt generation model, we require a response model  $\mathcal{M}$  that generates a response y' to the derived prompt x' for maximizing Eq. 5. Theoretically,  $\mathcal{M}$  can be any LLMs capable of generating responses to given input prompts (e.g., the Llama family and GPT-4). In our experiment, we choose both White-Box model like Llama series and Black-Box model like GPT-4 as our query model.

#### **Experiments**

In this section, we conduct extensive experiments on various downstream datasets to comprehensively evaluate our method when compared with baseline methods. Ablation studies demonstrate the superior and necessity of our proposed self-instructed RL method for derived prompt generation, and also shows that ICL can serve as a flexible playand-plug module to generally boosting existing methods to achieve better performance. We provide detailed training settings in supplementary materials.

#### **Experimental Setup**

**Datasets.** To train a derived prompt generation model by Eq. 5, we utilize the BPO training dataset by following previous work (Huang et al. 2024; Cheng et al. 2023), which

	Quary Model	Method		Vicuna Eval		BPO-test Eval			Dolley Eval			Self-Instruct Eval			
$\pi_{\theta}$	Query Model	A	В	A Win	B Win	Tie	A Win	B Win	Tie	A Win	B Win	Tie	A Win	B Win	Tie
	CPT 4	OURS	OP	90.0	3.8	6.2	71.0	24.5	4.5	80.5	15.5	4.0	76.2	5.6	18.3
		OURS	BPO	88.8	7.5	3.7	74.0	25.5	7.5	71.0	27.0	2.0	71.4	21.0	7.6
	CPT 2.5	OURS	OP	93.8	2.5	3.7	77.5	19.5	3.0	79.5	6.0	4.5	84.5	9.9	5.6
	011-5.5	OURS	BPO	85.0	11.3	3.7	71.0	14.5	4.5	77.0	20.0	3.0	86.1	9.9	4.0
Llama3	Llama3-8B	OURS	OP	82.5	15.0	2.5	65.5	30.0	4.5	59.0	34.0	7.0	78.9	15.1	6.0
		OURS	BPO	81.3	35.0	1.2	63.0	34.0	3.0	51.0	47.0	2.0	75.8	22.2	2.0
	Llama2-7B	OURS	OP	82.5	15.0	2.5	76.0	21.5	2.5	69.5	28.5	2.0	78.1	17.5	4.4
	Liamaz-7D	OURS	BPO	81.3	17.5	1.2	68.0	28.5	2.5	67.5	28.5	4.0	73.4	24.6	2.0
	Owen2-7B	OURS	OP	91.3	5.0	3.7	85.0	10.5	4.5	82.5	13.0	4.5	90.8	9.2	0
		OURS	BPO	92.5	7.5	0.0	81.5	13.5	5.0	82.5	16.0	1.5	81.0	17.8	1.2
	Llama3-8B	OURS	OP	85.0	12.5	2.5	67.5	28.0	4.5	61.5	35.0	3.5	77.0	13.9	9.1
		OURS	BPO	78.8	21.2	0.0	66.0	30.0	4.0	53.0	40.5	1.5	73.8	21.4	4.8
Llama 2	Llama2-7B	OURS	OP	86.3	12.5	1.2	74.5	22.0	3.5	74.5	23.0	2.5	84.1	13.0	2.9
Liamaz		OURS	BPO	85.0	10.0	5.0	66.0	29.5	4.5	67.5	32.0	0.5	72.2	25.9	9.9
	Owen2 7P	OURS	OP	91.3	8.7	0	83.0	13.0	4.0	85.0	11.0	4.0	92.1	7.5	0.4
	Qwen2-7B	OURS	BPO	85.0	15.0	3.0	79.0	17.5	3.5	78.5	20.5	1.0	84.5	14.7	0.8
	L 1	OURS	OP	81.3	17.5	1.2	74.5	23.0	2.5	59.5	36.5	4.0	77.8	12.7	9.5
Qwen2	Liama3-8B	OURS	BPO	78.8	21.2	0.0	69.5	26.0	4.5	54.5	42.5	3.0	69.8	27.8	2.4
	Liama 2.7D	OURS	OP	92.5	7.5	0.0	74.0	23.5	2.5	71.0	23.0	6.0	84.1	11.1	4.8
	Liama2-/B	OURS	BPO	78.8	21.2	0.0	67.0	29.5	3.5	73.0	23.5	3.5	77.4	21.0	1.6
	Owen2 7P	OURS	OP	96.3	2.5	1.2	86.5	8.0	5.5	82.0	13.0	5.0	84.5	14.7	0.8
	Qwell2-7B	OURS	BPO	95.0	3.8	1.2	67.0	15.0	4.0	78.0	19.0	3.0	91.7	8.0	0.3

Table 2: A comprehensive comparison of OURS method, BPO and OP (Orginal Prompt) for different  $\pi_{\theta}$  across four evaluation datasets. Query Model indicates the LLM used to response to the input prompt.

is constructed from four meticulously selected datasets and comprises 14K diverse samples. In order to comprehensively evaluate the performance of our method, we adopt wide-used instruction datasets for assessment, including Dolly Eval (Conover et al. 2023), Vicuna Eval (Chiang et al. 2023), Self-Instruct Eval (Wang et al. 2022) and BPO test Eval (Cheng et al. 2023). We provide detailed description in supplementary materials.

**Derived Prompt Generation Model.** We particularly focus training an effective  $\pi_{\theta}$  based on the popular LLMs such as LLaMA (Touvron et al. 2023) and Qwen (Yang et al. 2024a). Specifically, considering that our method relies on an instruction-following capability for derived prompt generation, we apply our method to to Llama2-chat (Touvron et al. 2023), Llama3-8B-Instruct (Touvron et al. 2023) and Qwen2-7B-Instruct (Yang et al. 2024a), which are all abbreviated as Llama3, Llama2 and Qwen2, respectively.

**Queried Model.** A queried model is an frozen model used to generate responses to various prompt inputs, where we employ Llama2-chat (Llama2-7B), Llama3-Instruct (Llama3-8B), Qwen2-7B-Instruct (Qwen2-7B), GPT-3.5-turbo (GPT-3.5) and GPT-4o (GPT-4).

**Baselines and Evaluation Metrics.** To demonstrate the effectiveness of our approach in help LLMs generate more effective response, we conduct a comprehensive comparison of the quality of the responses using original prompts and those refined through BPO method (Cheng et al. 2023), due

to all we mainly focus on better prompt Black-Box model to generate more helpful response. Following the common practice of employing LLMs for evaluation (Zheng et al. 2024; Wang et al. 2023), we utilize GPT-40 to assess the impact of our method, where we adopt prompts from the MTbench dataset (Zheng et al. 2024). To further ensure the fairness of our evaluation and to mitigate any potential position bias, we implement a random shuffling during each evaluation. In our results analysis, we mainly report Win Rates, which is computed by (A Win – B Win)%.

#### Results

We use OP to denote the responses obtained by the LLM from Original Prompt, where BPO and OD indicates that of **BPO** refined prompt and Our Derived prompt, respectively. ICL represents the in-context learning environment. OURS indicates OD + ICL. As shown in Tab. 2, our method shows an overall performance improvement than baseline methods, specifically for Black-Box model. Our method show multiple significant advantages:

**Stability Across Datasets:** Our method demonstrates excellent performance and higher win rates across all four evaluation datasets compared to OP and BPO. The ICL queries generated by our method effectively promote the LLM to produce high-quality, more helpful, and comprehensive responses to the original questions, showcasing its robustness in handling various tasks, whether complex or simple.

Consistency Across Models: Our method shows consis-

	Me	thod	Vi	cuna Eval	1	Se	lf-Instruc	:
	A	В	A Win	B Win	Tie	A Win	B Win	Tie
#1	OD	OP	78.8	11.2	10.0	66.3	15.5	18.2
#2	BPO	OP	68.8	15.0	16.2	66.3	21.4	12.3
#3	OD	BPO	72.5	21.3	6.2	42.1	8.7	49.2
#4	BPO	OP	68.8	15.0	16.2	66.3	21.4	12.3
#5	BPO + ICL	OP	76.3	11.3	12.4	69.4	21.4	9.2
#6	BPO + ICL	BPO	68.8	2.5	28.7	71.1	19.4	9.5
#7	OD + ICL	OD	60.0	2.5	37.5	52.4	9.1	37.3
#8	BPO + ICL	BPO	68.8	2.5	28.7	71.1	19.4	9.5
#9	OD + ICL	BPO + ICL	75.0	11.3	13.7	68.9	21.4	10.7

Table 3: Comparison of different Black-Box optimization methods across Vicuna Eval and Self-Instruct based on querying GPT-4.

tent performance improvement between different models. For example, in the Vicuna Eval dataset, the average OURS win rates in Llama3, Llama2 and Qwen2 are 73.6%, 76.3%, 80.8% compared to OP, and those are 65.0%, 69.2% and 68.8% compared with BPO, respectively. These consistent higher results demonstrate that our method maintains high performance and robustness across a variety of underlying models, ensuring reliable results independent to models.

**Cross-Model Transferability:** Tab. 2 also shows that the  $\pi_{\theta}$  trained on Llama3 and constructed ICL queries can achieve better response quality on other models (e.g., Llama2 and Qwen2). For example, the model trained on Llama3 and 74.0% on Qwen2 compared with OD, and that are 12.5% and 58.0% compared with BPO. This suggests that our method has good cross-model transferability and can maintain high performance across different models.

**Improved Black-Box Model Performance:** Our method significantly improved the response quality of black box models such as GPT-4 and GPT-3.5. For instance, when training on Llama3, the average win rates of our method on GPT-4 compared with OP and BPO are 67.1% and 56.1%, respectively. And thoese on GPT-3.5 are 74.3% and 69.9%, respectively. The significant improvement indicates that our method effectively promote Black-Box LLM generate high-quality response. Similarly, in other datasets, the win rates of our method on GPT series models are also significantly higher than those of other methods.

#### **Ablation Study**

To further illustrate the advantages of our proposed selfinstructed RL method (OD) and the importance of the ICL environment (ICL), we use derived prompts generated by Llama3-8B to query GPT-4, where the generated response are then evaluated by GPT-4. Tab. 3 presents the comparison various combinations of OD and ICL with other methods using two evaluation datasets: Vicuna Eval (Chiang et al. 2023) and Self-Instruct (Wang et al. 2022). By comparing #1 and #2, it can be observed that from the perspective of prompt refinement, our OD already exhibits higher quality than BPO, thereby promoting LLMs to generate more helpful responses. In Vicuna Eval, OD's win rate is 67.6%, significantly higher than BPO's 53.8% and those are 50.8% and 44.9% in Self-Instruct Eval, where we achieve 5.9% performance improvement. The comparison between OD and BPO in #3 also support this analysis.

In #5, when BPO is augmented by ICL, it significantly improves performance, achieving a win rate of 65.0% in Vicuna Eval and 48.0% in Self-Instruct. This is a noticeable improvement over BPO alone (#4), which has a win rate of 53.8% in Vicuna Eval and 44.9% in Self-Instruct. Furthermore, when BPO + ICL is compared directly with BPO (#6), BPO + ICL achieves a win rate of 66.3% and 51.7% in two datasets, demonstrating our proposed ICL query formulation is a general framework suitable with various prompt refinement methods.

Finally, #7, #8, and #9 examine the combination of OD with ICL. When OD is combined with ICL and BPO (#7 and #8), significant higher win rates demonstrate that our proposed ICL querying framework is suitable to various methods and promptes LLMs generate more helpful response. When compared with BPO + ICL (#9), OD + ICL achieves an impressive win rate of 63.9% in Vicuna Eval and 47.5% in Self-Instruct, suggesting that the OD + ICL combination consistently provides stable and superior performance improvements across different environments.

In summary, our derived prompts enhanced by selfinstructed RL are more effective than BPO prompts, in promoting LLMs to produce high-quality responses. Additionally, our proposed ICL querying formulation is a flexible, effective, and general framework that can enhance various prompt refinement methods in obtaining better responses to the original queries.



Figure 2: Win rates comparison in Vicuna Eval among w/o training, SFT and RL. Based on Llama3-8B for generation of derived prompt.

# Independent Analysis of Self-Instructed RL and ICL Query Framework

In this section, we mainly focus on independently analyzing how our proposed self-instructed RL and ICL query framework perform. Fig. 2 shows two advantages of our methods:

Effectiveness of ICL framework: Without training, directly using LLM to generate derived prompts combined with ICL (OD + ICL) has already achieved excellent results, achieves 39.1% win rates improvement. This supervising performance indicates that our proposed ICL framework is highly general and effective even without additional optimization.

Original Prompt	Describe the health benefits of green tea.
BPO Prompt	Discuss the antioxidant properties of green tea and its role in preventing cancer.
Derived Prompt	Explore the multifaceted health advantages of green tea, delving into its rich antioxidant profile, impact on cardiovascular well-being, potential in weight management, cognitive enhancements, cancer risk reduction, dental health support, diabetes management aid, anti-inflammatory properties, skin health benefits, and liver health promotion. Emphasize the importance of integrating green tea into a holistic healthy lifestyle for optimal effectiveness.
Original Response	Green tea is a popular beverage known for its numerous health benefits. Here are some of the key advantages associated with drinking green tea: Rich in Antioxidants, Heart Health, Weight Management, Brain Function, Cancer Prevention, Improved Dental Health.
BPO Response	Green tea is renowned for its potent antioxidant properties, primarily attributed to the presence of polyphenols, particularly catechins like epigallocatechin gallate (EGCG). These antioxidants play a crucial role in protecting cells from damage caused by free radicals, which are unstable molecules that can lead to oxidative stress and contribute to various diseases, including cancer. Here's how the antioxidant properties of green tea, particularly its catechins, may help in preventing cancer: 1. Neutralizing Free Radicals 2. Anti-Inflammatory Effects 3. Apoptosis Induction 4. Inhibition of Tumor Growth 5. DNA Repair 6. Protection Against Ultraviolet Radiation 7. Enhancing Immune Function
ICL Response	Green tea, a popular beverage originating from China, has gained global recognition not only for its delightful taste but also for its numerous health benefits. Let's explore the multifaceted advantages of green tea across various aspects of health: 1. Antioxidant Richness: Green tea is abundant in antioxidants 2. Cardiovascular Well-being: Studies suggest that regular consumption of green tea may help lower the risk of cardiovascular diseases 3. Weight Management: Green tea is often touted for its potential in aiding weight management 4. Cognitive Enhancements: The caffeine content in green tea can provide a mild stimulatory effect, promoting alertness and focus5. Cancer Risk Reduction: Several studies have suggested that the antioxidants in green tea may help reduce the risk of certain types of cancer 6. Dental Health Support: Green tea has antibacterial properties that can help inhibit the growth of harmful bacteria in the mouth 7. Diabetes Management Aid: Research indicates that green tea may help regulate blood sugar levels and improve insulin sensitivity 8. Anti-inflammatory Properties: The polyphenols in green tea possess anti-inflammatory properties9. Skin Health Benefits: Green tea's antioxidant and anti-inflammatory properties can benefit the skin 10. Liver Health Promotion: Green tea may support liver health by promoting detoxification processes 11. Holistic Integration: To reap the full benefits of green tea, it's crucial to integrate it into a holistic healthy lifestyle

Figure 3: Detailed cases study. We compare quality of different types of responses by querying GPT-4.

Effectiveness of self-instructed RL: After optimization with RL, our methods achieves a higher win rates increasing from 17.6% to 67.6% on OD vs OP, and that from 39.1% to 86.2% on OD + ICL vs OP, which is also better than using SFT. This highlights the significant advantage of our proposed RL in generating higher quality derived prompts.

## **Case Study**

As shown in Fig 3, BPO significantly alters the original prompt's intent, restricting the response to the relationship between green tea and cancer while neglecting other benefits. In contrast, our derived prompt maintains consistency with the original prompt's content and expands upon it. Consequently, the comparison between the original response and the ICL response reveals that our approach not only effectively covers the information present in the original response, but also stimulates the LLM's intrinsic knowledge, resulting in more comprehensive and detailed descriptions.

## **Related Work**

**Prompt Refinement** Prompts are crucial for guiding LLMs to produce more helpful response, leading to extensive research on improving their quality. Initially, prompt optimization relied on manually crafted templates (Reynolds and McDonell 2021), a labor-intensive process with interpretation challenges (Webson and Pavlick 2021). Recent studies automate this process using techniques like gradient-based search (Shin et al. 2020; Pryzant et al. 2023), paraphrasing (Haviv, Berant, and Globerson 2021; Jiang et al. 2020) and leveraging LLMs to generate prompts (Zhou et al. 2022; Fernando et al. 2023; Yang et al. 2024b; Cheng et al. 2023). Additionally, RL based methods are designed to optimize a prompt rewritten model through reward functions and task-specific templates (Deng et al. 2022; Kong et al. 2024; Zhang et al. 2022; Huang et al. 2024).

**RLHF** RLHF has been widely explored to align LLMs with human preferences (Stiennon et al. 2020; Ouyang et al. 2022; Bai et al. 2022b; Lee et al. 2023). Common approaches include building a reward model using maximum likelihood estimation (MLE) and optimizing it with the Proximal Policy Optimization (PPO) algorithm (Schulman et al. 2017). However, replicating PPO's success has proven challenging for the open-source community due to the high resource demands. To address this, some research has shifted to offline direct preference learning (Zhao et al. 2023; Rafailov et al. 2024; Li et al. 2023), which bypasses reward modeling and directly optimizes a loss target using an offline dataset. Among these methods, ours and Cheng et al. (2023) fall into better alignment with Black-Box model.

**Improving In-Context Learning** Several approaches have been introduced to enhance in-context learning (ICL) performance by improving the selection of in-context examples. Some methods focus on refining template selection (Yin et al. 2023), while others aim to enhance the choice of examples (Liu et al. 2021; Rubin, Herzig, and Berant 2021). Additionally, Wan et al. (2023) introduces a criterion for evaluating examples based on some criteria. Other recent innovations include flipped learning (Ye et al. 2022) and noisy channel prompting (Min et al. 2021). For multiple-choice problems, Xu et al. (2023) suggests using K-nearest neighbors for label assignment, and Yang et al. (2023) proposes iterative context updates.

# Conclusion

In this paper, we introduced an innovative method for enhancing LLM performance using an automatically generated in-context learning framework. By creating derived prompts through a self-instruct RL mechanism, our approach enriches the context of the original prompts. Extensive experiments reveal that our framework significantly improves response quality, even for Black-Box models like GPT-4. Excellent performance suggests that our method offers a promising paradigm for aligning LLMs without modifications, thereby improving their overall usability and effectiveness in various applications.

# References

Bai, Y.; Jones, A.; Ndousse, K.; Askell, A.; Chen, A.; Das-Sarma, N.; Drain, D.; Fort, S.; Ganguli, D.; Henighan, T.; et al. 2022a. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv* preprint arXiv:2204.05862.

Bai, Y.; Kadavath, S.; Kundu, S.; Askell, A.; Kernion, J.; Jones, A.; Chen, A.; Goldie, A.; Mirhoseini, A.; McKinnon, C.; et al. 2022b. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*.

Brown, T.; Mann, B.; Ryder, N.; Subbiah, M.; Kaplan, J. D.; Dhariwal, P.; Neelakantan, A.; Shyam, P.; Sastry, G.; Askell, A.; et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33: 1877– 1901.

Cheng, J.; Liu, X.; Zheng, K.; Ke, P.; Wang, H.; Dong, Y.; Tang, J.; and Huang, M. 2023. Black-box prompt optimization: Aligning large language models without model training. *arXiv preprint arXiv:2311.04155*.

Chiang, W.-L.; Li, Z.; Lin, Z.; Sheng, Y.; Wu, Z.; Zhang, H.; Zheng, L.; Zhuang, S.; Zhuang, Y.; Gonzalez, J. E.; et al. 2023. Vicuna: An open-source chatbot impressing gpt-4 with 90%\* chatgpt quality. *See https://vicuna. lmsys. org* (accessed 14 April 2023), 2(3): 6.

Conover, M.; Hayes, M.; Mathur, A.; Xie, J.; Wan, J.; Shah, S.; Ghodsi, A.; Wendell, P.; Zaharia, M.; and Xin, R. 2023. Free dolly: Introducing the world's first truly open instruction-tuned llm. *Company Blog of Databricks*.

DeepSpeed. 2024. DeepSpeed. https://www.deepspeed.ai/. Accessed: 2024-08-08.

Deng, M.; Wang, J.; Hsieh, C.-P.; Wang, Y.; Guo, H.; Shu, T.; Song, M.; Xing, E. P.; and Hu, Z. 2022. Rlprompt: Optimizing discrete text prompts with reinforcement learning. *arXiv preprint arXiv:2205.12548*.

Devlin, J. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Dong, Q.; Li, L.; Dai, D.; Zheng, C.; Wu, Z.; Chang, B.; Sun, X.; Xu, J.; and Sui, Z. 2022. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*.

Fernando, C.; Banarse, D.; Michalewski, H.; Osindero, S.; and Rocktäschel, T. 2023. Promptbreeder: Self-referential self-improvement via prompt evolution. *arXiv preprint arXiv:2309.16797.* 

Haviv, A.; Berant, J.; and Globerson, A. 2021. BERTese: Learning to speak to BERT. *arXiv preprint arXiv:2103.05327*.

Huang, Z.; Wang, X.; Zhang, F.; Xu, Z.; Zhang, C.; Zheng, X.; and Huang, X. 2024. Enhancing the Capability and

Robustness of Large Language Models through Reinforcement Learning-Driven Query Refinement. *arXiv preprint arXiv:2407.01461.* 

Jiang, Z.; Xu, F. F.; Araki, J.; and Neubig, G. 2020. How can we know what language models know? *Transactions of the Association for Computational Linguistics*, 8: 423–438.

Kong, W.; Hombaiah, S. A.; Zhang, M.; Mei, Q.; and Bendersky, M. 2024. PRewrite: Prompt Rewriting with Reinforcement Learning. *arXiv preprint arXiv:2401.08189*.

Lee, H.; Phatale, S.; Mansoor, H.; Lu, K.; Mesnard, T.; Bishop, C.; Carbune, V.; and Rastogi, A. 2023. Rlaif: Scaling reinforcement learning from human feedback with ai feedback. *arXiv preprint arXiv:2309.00267*.

Li, Z.; Xu, T.; Zhang, Y.; Yu, Y.; Sun, R.; and Luo, Z.-Q. 2023. Remax: A simple, effective, and efficient method for aligning large language models. *arXiv preprint arXiv:2310.10505*.

Liu, J.; Shen, D.; Zhang, Y.; Dolan, B.; Carin, L.; and Chen, W. 2021. What Makes Good In-Context Examples for GPT-3? *arXiv preprint arXiv:2101.06804*.

Liu, P.; Yuan, W.; Fu, J.; Jiang, Z.; Hayashi, H.; and Neubig, G. 2023. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*, 55(9): 1–35.

Min, S.; Lewis, M.; Hajishirzi, H.; and Zettlemoyer, L. 2021. Noisy channel language model prompting for few-shot text classification. *arXiv preprint arXiv:2108.04106*.

OpenAI, R.; et al. 2023. GPT-4 technical report. *ArXiv*, 2303: 08774.

Ouyang, L.; Wu, J.; Jiang, X.; Almeida, D.; Wainwright, C.; Mishkin, P.; Zhang, C.; Agarwal, S.; Slama, K.; Ray, A.; et al. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744.

Pryzant, R.; Iter, D.; Li, J.; Lee, Y. T.; Zhu, C.; and Zeng, M. 2023. Automatic prompt optimization with" gradient descent" and beam search. *arXiv preprint arXiv:2305.03495*.

Rafailov, R.; Sharma, A.; Mitchell, E.; Manning, C. D.; Ermon, S.; and Finn, C. 2024. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36.

Reynolds, L.; and McDonell, K. 2021. Prompt programming for large language models: Beyond the few-shot paradigm. In *Extended abstracts of the 2021 CHI conference on human factors in computing systems*, 1–7.

Rubin, O.; Herzig, J.; and Berant, J. 2021. Learning to retrieve prompts for in-context learning. *arXiv preprint arXiv:2112.08633*.

Schulman, J.; Wolski, F.; Dhariwal, P.; Radford, A.; and Klimov, O. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Shin, T.; Razeghi, Y.; Logan IV, R. L.; Wallace, E.; and Singh, S. 2020. Autoprompt: Eliciting knowledge from language models with automatically generated prompts. *arXiv* preprint arXiv:2010.15980.

Srivastava, A.; Rastogi, A.; Rao, A.; Shoeb, A. A. M.; Abid, A.; Fisch, A.; Brown, A. R.; Santoro, A.; Gupta, A.; Garriga-Alonso, A.; et al. 2022. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*.

Stiennon, N.; Ouyang, L.; Wu, J.; Ziegler, D.; Lowe, R.; Voss, C.; Radford, A.; Amodei, D.; and Christiano, P. F. 2020. Learning to summarize with human feedback. *Advances in Neural Information Processing Systems*, 33: 3008–3021.

Tam, D.; Menon, R. R.; Bansal, M.; Srivastava, S.; and Raffel, C. 2021. Improving and simplifying pattern exploiting training. *arXiv preprint arXiv:2103.11955*.

Touvron, H.; Martin, L.; Stone, K.; Albert, P.; Almahairi, A.; Babaei, Y.; Bashlykov, N.; Batra, S.; Bhargava, P.; Bhosale, S.; et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Wan, X.; Sun, R.; Dai, H.; Arik, S. O.; and Pfister, T. 2023. Better zero-shot reasoning with self-adaptive prompting. *arXiv preprint arXiv:2305.14106*.

Wang, Y.; Kordi, Y.; Mishra, S.; Liu, A.; Smith, N. A.; Khashabi, D.; and Hajishirzi, H. 2022. Self-instruct: Aligning language models with self-generated instructions. *arXiv* preprint arXiv:2212.10560.

Wang, Y.; Yu, Z.; Zeng, Z.; Yang, L.; Wang, C.; Chen, H.; Jiang, C.; Xie, R.; Wang, J.; Xie, X.; et al. 2023. Pandalm: An automatic evaluation benchmark for llm instruction tuning optimization. *arXiv preprint arXiv:2306.05087*.

Webson, A.; and Pavlick, E. 2021. Do prompt-based models really understand the meaning of their prompts? *arXiv* preprint arXiv:2109.01247.

Xu, B.; Wang, Q.; Mao, Z.; Lyu, Y.; She, Q.; and Zhang, Y. 2023. *k* NN prompting: Beyond-context learning with calibration-free nearest neighbor inference. *arXiv preprint arXiv:2303.13824*.

Yang, A.; Yang, B.; Hui, B.; Zheng, B.; Yu, B.; Zhou, C.; Li, C.; Li, C.; Liu, D.; Huang, F.; et al. 2024a. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*.

Yang, J.; Hui, B.; Yang, M.; Li, B.; Huang, F.; and Li, Y. 2023. Iterative forward tuning boosts in-context learning in language models. *arXiv preprint arXiv:2305.13016*.

Yang, S.; Zhao, H.; Zhu, S.; Zhou, G.; Xu, H.; Jia, Y.; and Zan, H. 2024b. Zhongjing: Enhancing the chinese medical capabilities of large language model through expert feedback and real-world multi-turn dialogue. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, 19368–19376.

Ye, S.; Kim, D.; Jang, J.; Shin, J.; and Seo, M. 2022. Guess the instruction! flipped learning makes language models stronger zero-shot learners. *arXiv preprint arXiv:2210.02969.* 

Yin, F.; Vig, J.; Laban, P.; Joty, S.; Xiong, C.; and Wu, C.-S. J. 2023. Did you read the instructions? rethinking the effectiveness of task definitions in instruction learning. *arXiv preprint arXiv:2306.01150*. Zamfirescu-Pereira, J.; Wong, R. Y.; Hartmann, B.; and Yang, Q. 2023. Why Johnny can't prompt: how non-AI experts try (and fail) to design LLM prompts. In *Proceedings* of the 2023 CHI Conference on Human Factors in Computing Systems, 1–21.

Zhang, T.; Wang, X.; Zhou, D.; Schuurmans, D.; and Gonzalez, J. E. 2022. Tempera: Test-time prompting via reinforcement learning. *arXiv preprint arXiv:2211.11890*.

Zhao, Y.; Joshi, R.; Liu, T.; Khalman, M.; Saleh, M.; and Liu, P. J. 2023. Slic-hf: Sequence likelihood calibration with human feedback. *arXiv preprint arXiv:2305.10425*.

Zheng, L.; Chiang, W.-L.; Sheng, Y.; Zhuang, S.; Wu, Z.; Zhuang, Y.; Lin, Z.; Li, Z.; Li, D.; Xing, E.; et al. 2024. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36.

Zhou, Y.; Muresanu, A. I.; Han, Z.; Paster, K.; Pitis, S.; Chan, H.; and Ba, J. 2022. Large language models are human-level prompt engineers. *arXiv preprint arXiv:2211.01910*.

# Supplementary Materials For Self-Instructed Derived Prompt Generation Meets In-Context Learning: Unlocking New Potential of Black-Box LLMs

# **Failed Refined Prompt Cases**

In this section, we provide more failed refined prompt cases. In this situation, directly querying the response model (e.g., GPT-4) with the refined prompt would definitely obtain useless response

Original Prompt	Compose a rap verse about a topic of your choosing.
Refined Prompt	Compose a rap verse about the topic of Artificial Intelligence (AI).
Original Prompt Refined Prompt	<ul><li>Write a tweet that is opinionated and captures the essence of the following text: The use of artificial intelligence is fundamentally changing the way that business is done.</li><li>Write a tweet that expresses an opinion about how artificial intelligence is revolutionizing business.</li></ul>
Original Prompt	What was the average house price in San Francisco?
Refined Prompt	What was the average house price in San Francisco in 2020?
Original Prompt	Open up a discussion about a given topic.
Refined Prompt	Let's discuss the current and future impact of artificial intelligence (AI) on society. Consider its applications, potential benefits, drawbacks, and ethical considerations.
Original Prompt	why do people from barcelona talk so weird?
Refined Prompt	What are some characteristics of the Barcelona accent?
Original Prompt	what is the Adam
Refined Prompt	Who is Adam in the Bible?
Original Prompt Refined Prompt	Tell me about Hong KongTell me about Hong Kong's response to COVID-19. (Please provide specific information on measures takenby the government, such as border control, mask mandates, and vaccination efforts.)
Original Prompt	Who is JFK?
Refined Prompt	Who is JFK?Who is the current president of the United States? Provide accurate and detailed responses.

Table 4: Failed refined prompt cases.

# Instruct-guided Derived Prompt Generation Template x<sub>DPG</sub>

Recall in Section Self-instructed RL for Derived Prompt Generation Model, we design a derived prompt generation instruction  $x_{\text{DPG}}$  to ask the model  $\pi_{\theta}$  to generate a derived prompt, instead of using a  $\pi_{\text{SFT}}$ . Here we proved the specific template shown as below:

*###* Instruction: Please provide a more comprehensive, easily understandable, and answerable version of the following question. Ensure that necessary contextual information is added during the rewrite, but do not limit the understanding and response to the question. Avoid confining the question to just a few aspects, allowing the responder to think from multiple angles. Only return the refined question and do not explain. Here is my original question:".

*### Question:* {*Original Prompt x*}.

As shown in Alg. 1, we firstly concatenate  $x_{DPG}$  with original prompt x together as X, which will be then sent to  $\pi_{\theta}$  to obtain the derived prompt x'.

# **Experiments**

**Training Settings.** For training settings, we use ReMax (Li et al. 2023) to train the derived prompt generation model facilitated by DeepSpeed ZeRO-2 (DeepSpeed 2024). We set the temperature parameter to  $\tau = 1.0$  and use nucleus sampling with a parameter of top<sub>p</sub> = 0.9 for all models. The maximum length for derived prompt generation and response model is set to 256 tokens. We conduct experiments on 4 NVIDIA A100 GPUs. All experiments are trained with a learning rate of  $1 \times 10^{-6}$  for 2 epoch with decay, where the KL penalty  $\beta$  is set to 0.05 for all models. Our batch size is set to 1. **Reward Evaluation** In addition to GPT-4 as evaluator for comparing the quality of response promoted by different methods, we also adopt Reward Score into quantitative evaluation, which provides more comprehensive understanding to our methods. Therefore, we train a Llama3-8B-Instruct as derived prompt generation model and then query GPT-4. As shown in Tab. 5, we can observe our method can prompote GPT-4 generate more useful and higher quality response in the view of Reward Score, except for Dolley Eval.

Dataset	Method	Reward Score	$\delta$
	OURS	3.97	-
Vicuna	OP	3.72	↑ 0.25
	BPO	3.83	↑ 0.14
	OURS	3.19	-
<b>BPO-Text</b> Eval	OP	1.89	↑ 1.30
	BPO	2.42	↑ 0.77
	OURS	3.24	-
Dolley Eval	OP	2.05	↑ 1.19
	BPO	3.25	↓ -0.01
	OURS	2.79	-
Self-Instruct Eval	OP	0.72	↑ 2.07
	BPO	1.78	↑ 1.01

Table 5: Comparison of different Black-Box optimization methods across Vicuna Eval and Self-Instruct based on querying GPT-4.

## **GPT-4** Original Prompt-based Justification Prompt

In this section, we give a GPT-4 based pair-wise justification prompt shown as below.

*### System message:* 

Please act as an impartial judge and evaluate the quality of the responses provided by two AI assistants to the user question displayed below. You should choose the assistant that follows the user's instructions and answers the user's question better. Your evaluation should consider factors such as the helpfulness, relevance, accuracy, depth, creativity, and level of detail of their responses. Begin your evaluation by comparing the two responses and provide a short explanation. Avoid any position biases and ensure that the order in which the responses were presented does not influence your decision. Do not allow the length of the responses to influence your evaluation. Do not favor certain names of the assistants. Be as objective as possible. After providing your explanation, output your final verdict by strictly following this format: '[[A]]' if assistant A is better, '[[B]]' if assistant B is better, and '[[C]]' for a tie. Prompt template:

{User Question} {Original Prompt}

[The Start of Assistant A's Answer] {answer a} [The End of Assistant A's Answer]

[The Start of Assistant B's Answer] {answer b} [The End of Assistant B's Answer]

#### More Case Study

In this section, we provide two more examples shown as below.

Original Prompt	number one song pick
BPO Prompt	Please recommend a number one song.
Derived Prompt	What is the most iconic, influential, and enduring song in music history, and what cultural, historical, and artistic factors contribute to its status as the most beloved and widely recognized single song among music lovers of all ages and genres?
Original Response	Of course! I'd be happy to recommend a number one song for you. However, I would need some more information from you to make a recommendation that suits your taste. Could you please tell me what kind of music you enjoy listening to? For example, pop, rock, hip-hop, electronic, or something else? This will help me give you a more accurate and personalized recommendation.
BPO Response	Of course! I'd be happy to help you with that. Can you please provide me with some more details or preferences regarding the number one song you would like me to recommend? For example, are you interested in a particular genre, era, or mood?
ICL Response	<ul> <li>Ah, an infriguing question! The most iconic, influential, and enduring song in music history is a subjective matter, but there are several candidates that stand out for their cultural, historical, and artistic significance. Here are some of the most notable contenders:\n\n</li> <li>1. "(Happy Birthday to You\" - Written in 1893 by Patty Hill and Mildred J. Hill, this song has become the most widely recognized and beloved birthday song in the world, sung on countless birthdays across generations and cultures. Its widespread popularity can be attributed to its simplicity, catchiness, and the sentimental value it holds for people of all ages.\n</li> <li>2. "(Yesterday\" by The Beatles - Released in 1965, this Paul McCartney-penned ballad is one of the most covered songs in history, with over 2.200 recorded versions. Its timeless melody and poignant lyrics have made it a classic that crosses genres and generations, resonating with people of all ages and musical tastes.\n</li> <li>3. "(Stairway to Heaven\" by Led Zeppelin - This epic rock ballad, written by Jimmy Page and Robert Plant, is widely considered one of the greatest songs ever written. Its soaring guitar rifts, poetic lyrics, and powerful vocals have made it a staple of classic rock radio and a cultural touchstone for generations of music fans.\n</li> <li>4. "Bohemian Rhapsody\" by Queen - This operatic rock anthem, penned by Freddie Mercury, is a masterclass in songwriting and vocal performance, with its complex structure, memorable chorus, and iconic music video. Its enduring popularity has made it a cultural phenomenon, with references in popular culture ranging from \"The Simpsons\" to \"The Muppets.\"n</li> <li>5. "Imagine\" by John Lennon - Released in 1971, this powerful ballad has become an anthem for peace and unity, with its haunting melody and poignant lyrics resonating with people around the world. Its enduring popularity and political relevance have cemented its status as one of them est counce, morvable factors:\n\n1. Cultural signif</li></ul>

Figure 4

Original Prompt	List uses of AI.
BPO Prompt	List one specific and impactful use of AI in any field.
Derived Prompt	What are some examples of artificial intelligence being used in various industries and aspects of daily life?
Original Response	Sure, here's an example of a use of Al:\n\n 1. Virtual Personal Assistants: Virtual personal assistants, powered by AI, can help individuals manage their daily tasks and schedules, such as setting reminders, sending emails, and even making appointments. Examples of virtual personal assistants include Amazon's Alexa, Google Assistant, and Apple's Siri. These assistants can learn and adapt to a user's preferences and habits over time, making them increasingly useful and efficient.",
BPO Response	Sure! Here's an example of a specific and impactful use of AI in the field of healthcare:\n\n 1. Medical Imaging Analysis: AI algorithms can be trained to analyze medical images such as X-rays, CT scans, and MRIs to detect diseases and abnormalities. For instance, AI-powered systems can identify breast cancer from mammography images with a high degree of accuracy, allowing doctors to make more accurate diagnoses and provide more effective treatments. According to a study published in the journal Nature Medicine, AI-powered breast cancer detection systems have been shown to be more accurate than human radiologists in detecting breast cancer. This technology has the potential to revolutionize the way breast cancer is diagnosed and treated, and could potentially save thousands of lives each year.
ICL Response	<ul> <li>Sure, here are some examples of artificial intelligence (AI) being used in various industries and aspects of daily life:</li> <li>1. Healthcare:int* Diagnostic tools: AI-powered diagnostic tools are being used to diagnose diseases such as cancer, diabetes, and hear disease by analyzing medical images and patient data. Int* Personalized medicine: AI is being used to create personalized treatment plans for patients based on their genetic profiles, medical history, and lifestyle. Int* Drug discovery: AI is being used to analyze large amounts of data to identify potential new drugs and drug targets, potentially leading to faster and more effective drug development.<sup>1</sup></li> <li>7. Finance:<sup>1</sup>Mt* Fraud detection: AI-powered fraud detection systems are being used to identify and prevent fraudulent transactions in banking, insurance, and e-commerce.<sup>1</sup>Mt* Ortfolio management: AI is being used to analyze financial management. AI is wered personal financial management. AI is wered personal financial management and excernere-o.<sup>1</sup>Mt* Portfolio management: AI-powered personal financial management and tools are being used to help individuals manage their finances, create budgets, and make investment decisions.<sup>1</sup>n</li> <li>7. Transportation:<sup>1</sup>Mt* Autonomus vehicles: AI is being used to develop autonomous vehicles that can drive themselves, potentially reducing accidents and improving traffic flow.<sup>1</sup>Mt* Preticitive maintenance: AI-powered predictive maintenance systems are being used to consumption and lowering emissions.<sup>1</sup>n</li> <li>4. Retali:<sup>1</sup>Mt* Personalized to monitor and maintain vehicles, predicting when maintenance will be required and reducing campaigns based on individual customer preferences and behavior.<sup>1</sup>Mt* Recommendation systems: AI-powered mercommendation systems: AI-powered mercommendation systems: AI-powered incommentary and sessessment: AI-powered mercommendation systems are being used to customer bersonalized learning; AI-powered tearning tools are being used to calibre educational content t</li></ul>