

input (IQ)

```
graph TD; Input["input (IQ)"] --> SI["SI"]; Input --> CI["CI"]; SI --> SI_conv1["conv"]; SI_conv1 --> SI_pool1["pool"]; SI_pool1 --> SI_conv2["conv"]; SI_conv2 --> SI_pool2["pool"]; SI_pool2 --> SI_conv3["conv"]; SI_conv3 --> SI_fc1["fc"]; SI_fc1 --> SI_fc2["fc"]; CI --> CI_conv1["conv"]; CI_conv1 --> CI_pool1["pool"]; CI_pool1 --> CI_conv2["conv"]; CI_conv2 --> CI_pool2["pool"]; CI_pool2 --> CI_conv3["conv"]; CI_conv3 --> CI_fc1["fc"]; CI_fc1 --> CI_fc2["fc"]; SI_fc2 --> Concat["concat"]; CI_fc2 --> Concat; Concat --> Softmax["softmax"];
```

The diagram illustrates a neural network architecture. It begins with an 'input (IQ)' block at the top. This input splits into two parallel paths: 'SI' (left) and 'CI' (right). Each path consists of three sequential stages: a 'conv' (convolution) layer, a 'pool' (pooling) layer, and another 'conv' layer. Following these, each path has two 'fc' (fully connected) layers. The outputs from the final 'fc' layers of both the SI and CI paths are combined in a 'concat' (concatenation) block. Finally, the concatenated output is passed through a 'softmax' layer to produce the final result.

SI

CI

conv

conv

pool

pool

conv

conv

pool

pool

conv

conv

fc

fc

fc

fc

concat

softmax