

Sorts the work-item task list based on dim list and order. Additionally, creates barriers on the lowest dimension based on value transition.

Sort_by

```
_dims : std::array<size_t, N>
constexpr Sort_by( std::array<size_t, N>
dims );
```

Groups work-items by alternate dimension, and optionally by a value and creates a barrier before value transition.

Group_by

```
_dim : size_t
_val : size_t
_has_val : bool
constexpr Group_by( size_t dim )
constexpr Group_by( size_t dim, size_t
val)
```

Synchronization Attribute Objects

Flash_buffers are used to unify device and host buffers. Flash_buffers default to device buffers, unless accessed via host, were then a programmable prefetch stride will be used.

Flash_buffer

```
_data : T *
_size : size_t
_prefetch_bytes : size_t
_device_ctx_handle : size_t
Flash_buffer( size_t, T *=nullptr, size_t = 4096 )
constexpr Flash_buffer( T *, size_t = 4096 )
/* runtime setters & getters */
/* operator overload for array */
```

Memory Attribute Object

A mixin object used to encapsulate attributes and arguments for runtime dispatch (via virtual tag dispatching).

```
template<size_t num_inputs, KernelDECL
KD, kernel_t k_type,
typename ... attrs_args>
KernelDefinition
```

```
_input_programs : std::string
_kernel_name : std::optional<std::string>
KernelDefinition( std::string impl,
std::string kernel_name )
get_method() : constexpr std::string
get_kernel_type() : constexpr : kernel_t
get_kernel_impl() : std::string
get_method_ovr() : std::string
operator(...) : void
```

```
temaplate<size_t N> KernelDECL
```

```
_kernel_name : char[N]
kernel_loc : std::string
KernelDECL(char[N] kernel_name )
```

Fundamental Kernel Description Object

Attribute to partition arguments to multiple devices. Partitioning work with a map function, and the kernel to partition buffers based on work-item set.

Part_by

```
_part_func :
std::vector<std::pair<size_t,size_t>>(
std::vector<std::pair<size_t,size_T>> )
_complete_indep : bool
constexpr Part_by( func * ptr)
```

Partitioning Attribute Object

Searchable

```
_search_strategy : search_t
Searchable(search_t)
```

This attribute allows the runtime to search for the implementation by kernel_name

Tag Attribute Object