

Ex. KernelDefiniton : using MATMULT = KernelDefinition<2, "elmatmult_generic", kernel_t::INT_BIN, sort_by<3>, float *, float * >;

Application Space

```
__global__ void elmatmult_generic( float * a,
                                   float * b,
                                   float * c)
{
    int x = threadIdx.x;
    c[x] = a[x] * b[x];
    return;
}
```



FLASH Sub-Space

```
__global__ void elmatmult_generic( float * a, float * b,
                                   float * c, size_t ** ind)
{
    //for CUDA kernels: first dimension must be less than 6 (0-5)
    //The second dimension is the index in subspace, relative to the
    //task group.
    //ind converts subspace indices to application space
    int x = ind[0][threadIdx.x];
    c[x] = a[x] * b[x];

    return;
}
```

Ex. KernelDefiniton : using MATMULT = KernelDefinition<2, "elmatmult_generic", kernel_t::INT_BIN, part_by<part_ptr>, float *, float * >;

Application Space

```
__global__ void elmatmult_generic( float * a,
                                   float * b,
                                   float * c)
{
    int x = threadIdx.x;
    c[x] = a[x] * b[x] + x;
    return;
}
```



FLASH Sub-Space

```
__global__ void elmatmult_generic( float * a, float * b,
                                   float * c, size_t ** ind)
{
    //for CUDA kernels: first dimension must be less than 6 (0-5)
    //The second dimension is the index in subspace, relative to the
    //task group.
    //ind converts subspace indices to application space
    int x = ind[0][threadIdx.x];
    c[threadIdx.x] = a[threadIdx.x] * b[threadIdx.x] + x;

    return;
}
```