

HIP

```
int main() {  
  
    //X+1 lines  
    hipMalloc((void**)&deviceA, NUM * sizeof(float));  
    hipMalloc((void**)&deviceB, NUM * sizeof(float));  
    hipMalloc((void**)&deviceC, NUM * sizeof(float));  
  
    //2X+2 lines  
    hipMemcpy(deviceB, hostB, NUM*sizeof(float), X lines  
        hipMemcpyHostToDevice);  
    hipMemcpy(deviceC, hostC, NUM*sizeof(float),  
        hipMemcpyHostToDevice);  
  
    //2X +3 lines  
    hipLaunchKernelGGL(vectoradd_float,  
        dim3(WIDTH/THREADS_PER_BLOCK_X, HEIGHT/  
            THREADS_PER_BLOCK_Y),  
        dim3(THREADS_PER_BLOCK_X,  
            THREADS_PER_BLOCK_Y),  
        0, 0,  
        deviceA ,deviceB ,deviceC ,WIDTH ,HEIGHT);  
  
    //2X+4 lines  
    hipMemcpy(hostA, deviceA, NUM*sizeof(float),  
        hipMemcpyDeviceToHost);  
  
    return 0;  
}
```

FLASH

```
//Kernel Definition: 1st line  
using MATMULT = KernelDefinition<2, "elmatmult_generic", kernel_t::INT_BIN, float *, float * >;  
  
int main(int argc, const char * argv[]){  
    /*Preparing Inputs/Outputs */  
    size_t sz = 512;  
    auto chunk = aligned_vector<float>(6*sz, 2);  
    float * A = chunk.data(), *B = A + sz, *C = B + sz;  
    float * E = C + sz, *F = E + sz, *G = F + sz;  
    /*End of Preparing Inputs/Outputs */  
  
    //initializing runtime: 2nd line.  
    RuntimeObj ocrtr(flash_rt::get_runtime("ALL_CPU") , MATMULT{ argv[0] });  
  
    //Run kernel : 3rd line  
    ocrtr.submit(MATMULT{}, A, B, C).sizes(sz,sz,sz).exec((size_t)32, (size_t)1, (size_t)1);  
    return 0; }
```

```
int main(int RAJA_UNUSED_ARG(argc), char **RAJA_UNUSED_ARG(argv[]))  
{  
    /* Allocate and initialize vector data */  
  
    // _rajacuda_vector_add_start  
    //initialize + execute lambda : 1st  
    RAJA::forall<RAJA::cuda_exec<CUDA_BLOCK_SIZE>>>(RAJA::RangeSegment(0, N),  
        [=] RAJA_DEVICE (int i) {  
            c[i] = a[i] + b[i];  
        });  
  
    return 0  
}
```

KOKKOS

```
int main (int argc, char ** argv){  
  
    /* Parameter encapsulation */ : line 1st  
    KokkosKernels::Experiment::Parameters params;  
  
    /* moving data into params object: X + 2 lines  
    /* parse_inputs (params, argc, argv) ) */  
  
    /*initializing runtime : line X + 3 lines*/  
    Kokkos::initialize( Kokkos::InitArguments(  
        num_threads, -1, device_id ) );  
  
    /*Kernel Definition : line X + 4*/  
    using crsMat_t = KokkosSparse::CrsMatrix<double,  
        int, Kokkos::Cuda, void, size_t>;  
  
    /*Run kernel : X + 5 */  
  
    KokkosKernels::Experiment::run_experiment<crsMat_t  
>(params);  
  
    /*Run kernel : X + 6 */  
    Kokkos::finalize();  
    return 0; }
```

RAJA