

# KOKKOS

```
int main (int argc, char ** argv){  
  
  /* Parameter encapsulation */ : line 1st  
  KokkosKernels::Experiment::Parameters params;  
  
  /* moving data into params object: line 2nd + X parms  
  /* parse_inputs (params, argc, argv) */  
  
  /*initializing runtime : line 3rd + X*  
  Kokkos::initialize( Kokkos::InitArguments( num_threads, -1, device_id ) );  
  
  /*Kernel Definition : line 4th + X*  
  using crsMat_t = KokkosSparse::CrsMatrix<double, int, Kokkos::Cuda,  
void, size_t>;  
  
  /*Run kernel : 5th + X *  
  KokkosKernels::Experiment::run_experiment<crsMat_t>(params);  
  
  /*Run kernel : 6th + X *  
  Kokkos::finalize();  
  return 0; }
```



> 50% code  
reduction +  
100% host code  
portability

# FLASH

```
//Kernel Definition: 1st line  
using MATMULT = KernelDefinition<2, "elmatmult_generic", kernel_t::INT_BIN, float *, float * >;  
  
int main(int argc, const char * argv[]){  
  /*Preparing Inputs/Outputs */  
  size_t sz = 512;  
  auto chunk = aligned_vector<float>(6*sz, 2);  
  float * A = chunk.data(), *B = A + sz, *C = B + sz;  
  float * E = C + sz, *F = E + sz, *G = F + sz;  
  /*End of Preparing Inputs/Outputs */  
  
  //initializing runtime: 2nd line.  
  RuntimeObj ocrtr(flash_rt::get_runtime("ALL_CPU") , MATMULT{ argv[0] });  
  
  //Run kernel : 3rd lines  
  ocrtr.submit(MATMULT{ }, A, B, C).sizes(sz,sz,sz).exec((size_t)32, (size_t)1, (size_t)1);  
  return 0; }
```



100% host code  
portability

```
int main(int RAJA_UNUSED_ARG(argc), char **RAJA_UNUSED_ARG(argv[]))  
{  
  /* Allocate and initialize vector data */  
  
  // _rajacuda_vector_add_start  
  //initialize + execute lambda : 1st  
  RAJA::forall<RAJA::cuda_exec<CUDA_BLOCK_SIZE>>(RAJA::RangeSegment(0, N),  
    [=] RAJA_DEVICE (int i) {  
      c[i] = a[i] + b[i];  
    });  
  
  return 0  
}
```

# RAJA