

```

int main( int argc, char* argv[] )
{
    /* Prepare inputs */

    // Get platform 1st line
    err = clGetPlatformIDs(1, &cpPlatform, NULL);

    // Get ID for the device 2nd line
    err = clGetDeviceIDs(cpPlatform, CL_DEVICE_TYPE_GPU, 1, &device_id,
NULL);

    // Create a context 3rd line
    context = clCreateContext(0, 1, &device_id, NULL, NULL, &err);

    // Create a command queue 4th line
    queue = clCreateCommandQueue(context, device_id, 0, &err);

    // Create the compute program from the source buffer 5th line
    program = clCreateProgramWithSource(context, 1,
        (const char **) & kernelSource, NULL, &err);

    // Build the program executable 6th line
    clBuildProgram(program, 0, NULL, NULL, NULL, NULL);

    // Create the compute kernel in the program we wish to run 7th line
    kernel = clCreateKernel(program, "vecAdd", &err);

```

```

// Create the input and output arrays in device memory for our calculation X + 8 lines
d_a = clCreateBuffer(context, CL_MEM_READ_ONLY, bytes, NULL, NULL);
d_b = clCreateBuffer(context, CL_MEM_READ_ONLY, bytes, NULL, NULL);
d_c = clCreateBuffer(context, CL_MEM_WRITE_ONLY, bytes, NULL, NULL);

// Write our data set into the input array in device memory 2X + 9 lines
err = clEnqueueWriteBuffer(queue, d_a, CL_TRUE, 0,
        bytes, h_a, 0, NULL, NULL);
err |= clEnqueueWriteBuffer(queue, d_b, CL_TRUE, 0,
        bytes, h_b, 0, NULL, NULL);

// Set the arguments to our compute kernel 3X + 10 lines
err = clSetKernelArg(kernel, 0, sizeof(d_mem), &d_a);
err |= clSetKernelArg(kernel, 1, sizeof(cl_mem), &d_b);
err |= clSetKernelArg(kernel, 2, sizeof(cl_mem), &d_c);
err |= clSetKernelArg(kernel, 3, sizeof(unsigned int), &n);

// Execute the kernel over the entire range of the data set 3X + 11 lines
err = clEnqueueNDRangeKernel(queue, kernel, 1, NULL, &globalSize, &localSize,
        0, NULL, NULL);

// Wait for the command queue to get serviced before reading back results
clFinish(queue); 3X + 12 lines

// Read the results from the device 3X + 13 lines
clEnqueueReadBuffer(queue, d_c, CL_TRUE, 0,
        bytes, h_c, 0, NULL, NULL );

return 0;
}

```

## OpenCL (FPGA)