

```

1 undolog_a =
  undolog_create(&a);
2 persist(undolog_a);
3 a = new_value;
4 persist(a);
5 undolog_delete(undolog_a);

```

(a) Logging (undo) on CPU

```

1 undolog_a =
  NearPM_undolog_create(...);
2 a = new_value;
3 persist(a);

```

(b) Logging (undo) on NearPM

```

1 redolog_a =
  redolog_create(new_value);
2 persist(redolog_a);
3 a = value(redolog_a);
4 persist(a);
5 redolog_delete(redolog_a);

```

(c) Logging (redo) on CPU

```

1 redolog_a =
  rlog_create(new_value);
2 persist(redolog_a);
3 NearPM_applylog(...);

```

(d) Logging (redo) on NearPM

```

1 ckpoint_a =
  ckpoint_create(&a);
2 persist(ckpoint_a);
3 a = new_value;

```

(e) Checkpointing on CPU

```

1 NearPM_ckpoint_create(...);
2 a = new_value;

```

(f) Checkpointing on NearPM

```

1 shadowcpy(newpage, oldpage);
2 (...) //write new_value
3 persist(new_value);
4 switch_page(newpage, oldpage);

```

(g) Shadow paging on CPU

```

1 NearPM_shadowcpy(...);
2 (...) //write new_value
3 persist(new_value);
4 switch_page(newpage, oldpage);

```

(h) Shadow paging on NearPM