

Method	Pipeline	Complexity
(a) CAReg + PaDim	<p>The PaDim pipeline processes the Support Set through CAReg to produce Registered Features. These features are then processed by a Gaussian Distribution Estimator to create a Normal Distribution. A Test Sample is also processed by CAReg and compared against the Normal Distribution to produce an Anomaly Score.</p>	<p>Memory Cost: $\mathcal{N}(\mu, \Sigma) \in \mathbb{R}^{H \times W \times D^2}$</p> <p>Modeling: $\mathcal{O}(KHW D^2)$ Inference: $\mathcal{O}(HWD^3)$</p>
(b) CAReg + OrthoAD	<p>The OrthoAD pipeline processes the Support Set through CAReg to produce Registered Features. These features are then processed by a Gaussian Distribution Estimator to create a Normal Distribution. This distribution is then processed by a Low-Rank Approximation to create a Semi-Orthogonal Embedding. A Test Sample is also processed by CAReg and compared against the Semi-Orthogonal Embedding to produce an Anomaly Score.</p>	<p>Memory Cost: $\mathcal{N}(\mathbf{W}^T \mu, \mathbf{W}^T \Sigma \mathbf{W}) \in \mathbb{R}^{H \times W \times D'^2}$</p> <p>Modeling: $\mathcal{O}(KHW D'^2)$ Inference: $\mathcal{O}(HWD'^3)$</p>
(c) CAReg + PatchCore	<p>The PatchCore pipeline processes the Support Set through CAReg to produce Registered Features. These features are then processed by Coreset Sampling to create a Memory Bank. A Nearest Neighbor Search is performed on the Memory Bank to create a Normal Distribution. A Test Sample is also processed by CAReg and compared against the Normal Distribution to produce an Anomaly Score.</p>	<p>Memory Cost: $\mathcal{M} \in \mathbb{R}^{\gamma K \times (H \times W) \times D}$</p> <p>Modeling: $\mathcal{O}(KHW D)$ Inference: $\mathcal{O}(\gamma K H^2 W^2 D^2)$</p>