Oracle® Fusion Cloud EPM REST API for Oracle Enterprise Performance Management Cloud



E96323-83

ORACLE

Oracle Fusion Cloud EPM REST API for Oracle Enterprise Performance Management Cloud,

E96323-83

Copyright © 2017, 2024, Oracle and/or its affiliates.

Primary Author: EPM Information Development Team

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Documentation Accessibility

Documentation Feedback

- 1 Creating and Running an EPM Center of Excellence
- 2 Implementation Best Practices for EPM Cloud REST APIs

3 About the REST APIs for EPM Cloud

3-1
3-2
3-14
3-14
3-15
3-15

4 OAuth 2 and Basic Authentication for EPM Cloud REST APIs

Authentication with OAuth 2 - Only for OCI (Gen 2) Environments	4-1
Basic Authentication - for Classic and OCI (Gen 2) Environments	4-9

5 Sample Integration Scenarios

5-1
5-2
5-3
5-4
5-4
5-5



Scenario 7: Cloning an Instance	5-6
Scenario 8: Sample Starter Kit for Consultants - Business Intelligence Cloud Integration	5-6
Scenario 9: Using Groovy Business Rules to Call REST APIs from Oracle and Other	
Companies	5-7

6 Quick Reference Table – REST API Resource View

7 REST Resources and Methods

Supported REST Methods	7-1
REST API Methods	7-2
Error Handling	7-2
Versioning	7-2
Current REST API Version	7-2
Status Codes	7-3

8 Planning REST APIs

8-1
8-2
8-2
8-3
8-5
8-6
8-7
8-10
8-12
8-13
8-19
8-22
8-25
8-29
8-31
8-32
8-33
8-36
8-37
8-37
8-38
8-39
8-42
8-45



Export Audit	8-47
Export Job Console	8-50
Sort Members	8-57
Import Exchange Rates	8-59
Auto Predict	8-60
Import Cell-Level Security	8-62
Export Cell-Level Security	8-65
Import Valid Intersections	8-67
Export Valid Intersections	8-70
Execute a Report Bursting Definition	8-72
Export Library Documents	8-73
Import Library Documents	8-76
Execute Job Code Samples	8-78
Retrieve Job Status	8-80
Retrieve Job Status Details	8-82
Retrieve Child Job Status Details	8-85
Working with Members	8-87
Add Member	8-87
Get Member	8-89
Get Applications	8-91
Manage Planning Units	8-93
List All Planning Units	8-94
Get Planning Unit History and Annotations	8-97
Get a Planning Unit Owner Photo	8-100
Get Planning Unit Promotional Path	8-101
Get Available Planning Unit Actions	8-103
Get Filters with All Possible Values	8-105
Change Planning Unit Status	8-107
Get User Preferences	8-108
Working with Data Slices	8-109
Import Data Slices	8-110
Export Data Slices	8-112
Clear Data Slices	8-123
Getting and Setting Substitution Variables	8-125
Get All Substitution Variables Defined for the Application	8-126
Get a Substitution Variable Defined for the Application	8-128
Create or Update All Substitution Variables Defined for the Application	8-129
Get Substitution Variables Defined at the Plan Type Level	8-130
Get Derived Substitution Variables at the Plan Type Level	8-131
Get a Substitution Variable Defined at the Plan Type Level	8-133
Get a Derived Substitution Variable Defined at the Plan Type Level	8-134
Create and Update Substitution Variables at the Plan Type Level	8-135

Deleting Substitution Variables	8-136
Delete a Substitution Variable at the Plan Type Level	8-137
Delete a Substitution Variable for the Application	8-138
Delete Substitution Variables at the Plan Type Level	8-139
Delete Substitution Variables for the Application	8-140
Working with Connections	8-142
View a Connection	8-142
View All Connections	8-144
Update a Connection	8-146

9 Migration REST APIs

URL Structure for Migration	9-3
Migration Status Codes	9-3
Getting API Versions for Migration APIs	9-4
Get REST API Versions for Migration	9-4
Get Information About a Specific REST API Version for Migration	9-7
Import and Export Files	9-11
LCM Import (v1)	9-11
LCM Import (v2)	9-17
LCM Export (v1)	9-22
LCM Export (v2)	9-27
Upload and Download Files	9-31
Upload	9-31
Download	9-36
View and Delete Files	9-40
List Files (v11.1.2.3.600)	9-41
List Files (v2)	9-44
Delete Files (v11.1.2.3.600)	9-46
Delete Files (v2)	9-49
Delete Files (v3)	9-51
Manage Services	9-53
Get Information About All Services	9-53
Get Idle Session Timeout	9-57
Set Idle Session Timeout	9-58
Restart the Service Instance (v1)	9-60
Restart the Service Instance (v2)	9-63
Run Recreate on a Service (11.1.2.3.600)	9-77
Run Recreate on a Service (v2)	9-83
Manage Application Snapshots	9-99
Get Information About All Application Snapshots	9-100
Get Information About a Specific Application Snapshot	9-102

Upload Application Snapshot (v1)	9-106
Upload Application Snapshot (v2)	9-109
Download Application Snapshot (v1)	9-114
Download Application Snapshot (v2)	9-124
Copy Application Snapshot (v1)	9-128
Copy Application Snapshot (v2)	9-133
Rename Application Snapshot (v1)	9-135
Rename Application Snapshot (v2)	9-137
Copy to and from the Object Store	9-139
Copy from Object Store (v1)	9-139
Copy from Object Store (v2)	9-142
Copy to Object Store (v1)	9-146
Copy to Object Store (v2)	9-150
Working with Essbase	9-154
Export Essbase Data (v2)	9-154
Essbase Block Analysis Report	9-157
Get Essbase Query Governor Execution Time	9-159
Set Essbase Query Governor Execution Time	9-160
Copy a File Between Instances (v1)	9-162
Copy a File Between Instances (v2)	9-164
Clone an Environment	9-166
Provide Feedback (v11.1.2.3.600)	9-172
Provide Feedback (v2)	9-175
Send Email (v1)	9-177
Send Email (v2)	9-179
Skip Updates (v1)	9-182
Skip Updates (v2)	9-184
List or Restore Backups - Only for OCI (Gen2) Environments	9-186
List Backups - Only for OCI (Gen 2) Environments	9-186
Restore Backup - Only for OCI (Gen 2) Environments	9-187

10 Security REST APIs

Get Restricted Data Access	10-1
Set Restricted Data Access	10-3
Get Virus Scan on File Upload	10-5
Set Virus Scan on File Upload	10-6
Manage Permission for Manual Access to Database (v1)	10-7
Manage Permission for Manual Access to Database (v2)	10-9
Set Encryption Key (v1)	10-11
Set Encryption Key (v2)	10-14
View or Update the IP Allowlist - Only for OCI (Gen 2) Environments	10-16

ORACLE[®]

View the IP Allowlist - Only for OCI (Gen 2) Environments	10-17
Update the IP Allowlist - Only for OCI (Gen 2) Environments	10-18

11 Viewing and Setting the Daily Maintenance Window Time

Get the Build Version and Daily Maintenance Time (v1)	11-1
Get the Build Version and Daily Maintenance Window Time (v2)	11-8
Setting the Daily Maintenance Time (v1)	11-10
Setting the Daily Maintenance Time (v2)	11-13
Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v1)	11-15
Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v2)	11-19

12 Managing Users, Groups, and Roles

Add Users to an Identity Domain (v1)	12-2
Add Users to an Identity Domain (v2)	12-8
Remove Users from an Identity Domain (v1)	12-12
Remove Users from an Identity Domain (v2)	12-16
Assign Users to a Predefined Role or Application Role (v1)	12-19
Assign Users to a Predefined Role or Application Role (v2)	12-27
Remove Users' Role Assignment (v1)	12-33
Remove Users' Role Assignment (v2)	12-40
Add Users to a Group (v1)	12-46
Add Users to a Group (v2)	12-51
Remove Users from a Group (v1)	12-54
Remove Users from a Group (v2)	12-59
Update Users	12-62
Add a User to a Batch of Groups	12-66
Remove a User from a Batch of Groups	12-71
Add Groups (v1)	12-76
Add Groups (v2)	12-80
Remove Groups (v1)	12-83
Remove Groups (v2)	12-88
User Group Report (v1)	12-91
User Group Report (v2)	12-95
User Access Report (v1)	12-100
User Access Report (v2)	12-104
User Audit Report (v1)	12-106
User Audit Report (v2)	12-109
Role Assignment Report (v1)	12-111
Role Assignment Report for Users (v2)	12-116
Role Assignment Report for Groups (v2)	12-121

Get Available Roles 12-12	<u> </u>
Role Assignment Audit Report for OCI (Gen 2) Environments 12-12	29
Invalid Login Report for OCI (Gen 2) Environments 12-13	34
Group Assignment Audit Report 12-13	39
Adding Users to a Team for Account Reconciliation 12-14	12
Adding Users to a Team for Financial Consolidation and Close and Tax Reporting 12-14	15
Removing Users from a Team for Account Reconciliation 12-14	18
Removing Users from a Team for Financial Consolidation and Close and Tax Reporting 12-15	50

13 Usage Simulation REST APIs

Simulate Concurrent Usage	13-1

14 Reporting REST APIs

Generate Report for Account Reconciliation	14-1
Generate Report for Financial Consolidation and Close and Tax Reporting	14-5
Generate User Details Report for Account Reconciliation	14-9
Generate User Details Report for Financial Consolidation and Close and Tax Reporting	14-11
Retrieve Job Status for a Report	14-14
Execute Reports for Data Management	14-16

15 Data Integration REST APIs

URL Structure for Data Integration	15-1
Getting API Versions for Data Integration APIs	15-1
Get API Versions for Data Integration APIs	15-2
Get Information about a Specific API Version for Data Integration APIs	15-3
Lock and Unlock POV	15-4
Running Integrations	15-10
Running a Pipeline	15-22
Import Data Mapping	15-25
Export Data Mapping	15-27
Export Data Integration	15-29
Import Data Integration	15-31
Retrieve Job Status	15-33

16 Data Management REST APIs

URL Structure for Data Management	16-1
Getting API Versions for Data Management APIs	16-1
Get API Versions for Data Management APIs	16-2



Get Information about a Specific API Version for Data Management APIs	16-3
Running Data Rules in Data Management	16-4
Running Batch Rules	16-7
Retrieve Job Status	16-9

17 Account Reconciliation APIs

URL Structure for Account Reconciliation	17-1
Getting API Versions for Account Reconciliation REST APIs	17-1
Get API Versions for Account Reconciliation REST APIs	17-2
Get Information about a Specific API Version for Account Reconciliation REST APIs	17-4
Execute a Job in Account Reconciliation	17-5
Retrieve Periods with a Specific Status	17-7
Change Period Status (Reconciliation Compliance)	17-9
Create Reconciliation (Reconciliation Compliance)	17-11
Delete Profile	17-12
Import Pre-Mapped Balances (Reconciliation Compliance)	17-14
Import Pre-Mapped Transactions (Reconciliation Compliance)	17-15
Import Balances (Reconciliation Compliance)	17-17
Import Profiles (Reconciliation Compliance)	17-19
Import Rates (Reconciliation Compliance)	17-20
Import Pre-Mapped Transactions (Transaction Matching)	17-22
Import Attribute Values	17-24
Monitor Reconciliations (Reconciliation Compliance)	17-26
Import Reconciliation Attributes (Reconciliation Compliance)	17-28
Run Auto Match (Transaction Matching)	17-31
Purge Transactions (Transaction Matching)	17-32
Retrieve Job Status (Reconciliation Compliance)	17-36
Retrieve Job Status (Transaction Matching)	17-37
Export Application Properties	17-40
Import Application Properties	17-42
Export Background Image	17-44
Import Background Image	17-46
Export Logo Image	17-48
Import Logo Image	17-49
Working with Connections in Account Reconciliation	17-51
Create a Connection	17-51
View All Connections	17-53
Update a Connection	17-54
Delete a Connection	17-56
Set Application Access Level	17-57
Retrieve Application Access Level	17-58

View Reconciliation Comments	17-59
Archive Matched Transactions (Transaction Matching)	17-61
Purge Archived Transactions (Transaction Matching)	17-62
Unmatch Matched Transactions (Transaction Matching)	17-64
Update Unmatched Transactions (Transaction Matching)	17-66

18 Financial Consolidation and Close REST APIs

Getting API Versions for Financial Consolidation and Close APIs	18-1
Get Information about a Specific API Version for Financial Consolidation and Close APIs	18-1
Perform Journal Actions for Financial Consolidation and Close	18-2
Perform Journal Period Updates for Financial Consolidation and Close	18-4
Retrieve Journals for Financial Consolidation and Close	18-6
Retrieve Journal Details for Financial Consolidation and Close	18-9
Export Consolidation Journals	18-12
Import Consolidation Journals	18-14
Copy Data	18-16
Clear Data	18-18
Validate Metadata	18-20
Generate an Intercompany Matching Report	18-21

19 Task Manager REST APIs

Getting API Versions for Task Manager APIs	19-1
Deploy Task Manager Templates	19-1
Update Task Status for Event Monitoring	19-5
Working with Connections in Task Manager	19-7
Create a Connection	19-8
View All Connections	19-11
Update a Connection	19-13
Delete a Connection	19-16

20 Supplemental Data Manager REST APIs

Getting API Versions for Supplemental Data Manager APIs	20-1
Import Supplemental Collection Data for Financial Consolidation and Close	20-1
Deploy Form Templates	20-4

21 Enterprise Journal REST APIs

Getting API Versions for Enterprise Journal APIs	21-1
Monitor Enterprise Journals for Financial Consolidation and Close	21-1



Execute an Enterprise Journals Job	21-4
Retrieve Enterprise Journals for Financial Consolidation and Close	21-10
Retrieve Enterprise Journal Content for Financial Consolidation and Close	21-12
Retrieve Enterprise Journal Content by Year and Period for Financial Consolidation and Close	21-14
Update Enterprise Journal Posting Status for Financial Consolidation and Close	21-16
Update Validation Status of Enterprise Journals for Financial Consolidation and Close	21-18

22 Tax Reporting REST APIs

URL Structure for Tax Reporting	22-1
Getting API Versions for Tax Reporting APIs	22-1
Get Information about a Specific API Version for Tax Reporting	22-1
Copy Data	22-2
Clear Data	22-4

23 Enterprise Profitability and Cost Management REST APIs

URL Structure for Enterprise Profitability and Cost Management	23-1	
Getting API Versions for Enterprise Profitability and Cost Management	23-2	
Getting Information About a Specific REST API Version for Enterprise Profitability and Cost		
Management	23-2	
Calculate Model	23-3	
Clear Data By Point of View	23-7	
Copy Data by Point of View	23-10	
Delete Point of View	23-13	
Generate Model Documentation Report	23-16	
Validate Model	23-18	

24 Profitability and Cost Management REST APIs

URL Structure for Profitability and Cost Management	24-2
Get API Versions for Profitability and Cost Management REST APIs	24-2
Get Information about a Specific API Version for Profitability and Cost Management	24-5
Apply Data Grants	24-7
Copy ML POV Data	24-9
Create File-Based Application	24-13
Deploy ML Cube	24-16
Enable File-Based Application	24-19
Essbase Data Load for Profitability and Cost Management	24-22
Export Query Results	24-25
Export Template for Profitability and Cost Management	24-29
Generate Program Documentation Report	24-32



Generate Program Documentation Report - Run as a Job	24-35
Import Template for Profitability and Cost Management	24-39
Merge Slices for Profitability and Cost Management	24-42
Optimize ASO Cube	24-43
Retrieve Task Status for Profitability and Cost Management	24-47
Run ML Calculations	24-48
Run ML Clear POV	24-52
Run ML Rule Balancing	24-56
Update Dimensions As a Job	24-60

25 Narrative Reporting REST APIs

26 Enterprise Data Management Cloud REST APIs

- A Common Helper Functions for Java
- B CSS Common Helper Functions for Java
- C Common Helper Functions for cURL
- D CSS Common Helper Functions for cURL
- E CSS Common Helper Functions for Groovy

F REST API Examples with Postman

Example: Using REST APIs to Upload with Postman	F-1
Example: Using REST APIs to Upload to an External Directory with Postman	F-3
Example: Using REST APIs to Upload a Snapshot with Postman	F-4

G Profitability and Cost Management Common Helper Functions

Profitability and Cost Management Common Helper Functions for Java	G-1
Profitability and Cost Management Common Helper Functions for cURL	G-11



H Sample Starter Kit for Consultants - Integration with Business Intelligence Cloud Service

Installing the Scripting Engine and Deploying Demo Scripts	H-2
SQL Application Express REST API client	H-2
Business Intelligence REST API Client	H-5
Planning REST API Client	H-6
Helper Functions	H-8
Integration of Planning to Business Intelligence Cloud Service	H-10
Groovy Sample – PBCSBICSIntegration.groovy	H-10
Groovy Sample – PbcsRestClient.groovy	H-13
Groovy Sample – PbcsRestClient.groovy	H-23
Groovy Sample – BicsRestClient.groovy	H-34
Groovy Sample – ApexRestClient.groovy	H-46
Troubleshooting the Integration	H-56



Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.



Documentation Feedback

To provide feedback on this documentation, click the feedback button at the bottom of the page in any Oracle Help Center topic. You can also send email to epmdoc_ww@oracle.com.



1 Creating and Running an EPM Center of Excellence

A best practice for EPM is to create a CoE (Center of Excellence).

An **EPM CoE** is a unified effort to ensure adoption and best practices. It drives transformation in business processes related to performance management and the use of technology-enabled solutions.

Cloud adoption can empower your organization to improve business agility and promote innovative solutions. An EPM CoE oversees your cloud initiative, and it can help protect and maintain your investment and promote effective use.

The EPM CoE team:

- Ensures cloud adoption, helping your organization get the most out of your Cloud EPM investment
- · Serves as a steering committee for best practices
- Leads EPM-related change management initiatives and drives transformation

All customers can benefit from an EPM CoE, including customers who have already implemented EPM.

How Do I Get Started?

Click to get best practices, guidance, and strategies for your own EPM CoE: Introduction to EPM Center of Excellence.

Learn More

- Watch the Cloud Customer Connect webinar: Creating and Running a Center of Excellence (CoE) for Cloud EPM
- Watch the videos: Overview: EPM Center of Excellence and Creating a Center of Excellence.
- See the business benefits and value proposition of an EPM CoE in *Creating and Running an EPM Center of Excellence*.





2

Implementation Best Practices for EPM Cloud REST APIs

Use the implementation best practices listed in this topic when working with the EPM Cloud REST APIs.

Best practices:

- Before using the REST APIs, complete the prerequisites.
- Use the correct authentication, as described in OAuth 2 and Basic Authentication for EPM Cloud REST APIs.
- Understand the URL structure.
- Know how to get the current REST API version.
- Review the sample scenarios to get started quickly.
- Be aware of REST API compatibility.
- Use the Quick Reference to find all of the Oracle Enterprise Performance Management Cloud REST APIs at a glance.

Troubleshooting

For help with troubleshooting REST API issues, see Diagnosing REST API Issues in Oracle Enterprise Performance Management Cloud Operations Guide.



3 About the REST APIs for EPM Cloud

Review these topics to learn about the REST APIs for Oracle Enterprise Performance Management Cloud and understand important prerequisites and authentication.

Overview of the REST APIs:

- About REST API for Oracle Enterprise Performance Management Cloud
- Implementation Best Practices for EPM Cloud REST APIs
- EPM Cloud REST API Compatibility
- About the Samples
- Audience
- Prerequisites
- OAuth 2 and Basic Authentication for EPM Cloud REST APIs

About REST API for Oracle Enterprise Performance Management Cloud

This guide describes REST APIs for Oracle Enterprise Performance Management Cloud.

These REST APIs allow service administrators and infrastructure consultants to perform administration tasks in EPM Cloud. This guide assumes that the audience has technical and functional expertise in using and working with REST APIs. See Audience.

EPM Cloud includes these cloud services:

- Planning
- FreeForm
- Planning Modules
- Account Reconciliation
- Financial Consolidation and Close
- Enterprise Profitability and Cost Management
- Profitability and Cost Management
- Tax Reporting
- Narrative Reporting
- Oracle Enterprise Data Management Cloud

You can integrate EPM Cloud environments using:

- A set of REST APIs
- The EPM Automate Utility, a command line tool that is implemented on top of the REST APIs



 Groovy business rules, as described in Oracle Enterprise Performance Management Cloud Groovy Rules Java API Reference.

EPM Cloud REST API Compatibility

These tables summarize the compatibility for Oracle Enterprise Performance Management Cloud REST APIs.

- EPM Platform
- Planning, FreeForm, Strategic Workforce Planning, and Sales Planning
- Migration
- Security
- Daily Maintenance Window Time
- Managing Users, Groups, and Roles
- Usage Simulation
- Reporting
- Data Integration
- Data Management
- Account Reconciliation
- Financial Consolidation and Close
- Task Manager
- Supplemental Data Manager
- Enterprise Journals
- Tax Reporting
- Enterprise Profitability and Cost Management
- Profitability and Cost Management

NOTE: These abbreviations are used in the column headings: **PLN** (Planning), **FF** (FreeForm), **SWP** (Strategic Workforce Planning), **SP** (Sales Planning), **FCC** (Financial Consolidation and Close), **AR** (Account Reconciliation), **EPCM** (Enterprise Profitability and Cost Management), **PCM** (Profitability and Cost Management), and **TR** (Tax Reporting)

For detailed information about REST APIs, see Quick Reference Table – REST API Resource View.

EPM Platform

Table 3-1 EPM Platform

EPM Platform Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Execute a Report Bursting Definition	~	~		~		~
Update a Connection	~	\checkmark		~		~
View a Connection	~	~		~		~
View all Connections	\checkmark	\checkmark		\checkmark		~



Planning, FreeForm, Strategic Workforce Planning, and Sales Planning

Planning, FreeForm, Strategic Workforce Planning, and Sales	PLN, FF, SWP,	FCC	AR	EPCM	РСМ	TR
Planning Tasks Getting API Versions for Planning	SP V	~		~		2
Get Information about a Specific REST API Version for Planning	2	2		2		2
Get Job Definitions	~	~		~		~
Execute a Job	~	~		~		~
Retrieve Job Status	\checkmark	\checkmark		~		\checkmark
Retrieve Job Status Details	~	~		\checkmark		~
Retrieve Child Job Status Details	~	~		\checkmark		~
Add Member	~	~		\checkmark		~
Get Member	~	~		\checkmark		~
Get Applications	~	~		\checkmark		~
List All Planning Units	~	~				
Get Planning Unit History and Annotations	~	~				
Get a Planning Unit Owner Photo	\checkmark	~				
Get Planning Unit Promotional Path	\checkmark	~				
Get Available Planning Unit Actions	\checkmark	\checkmark				
Get Filters with All Possible Values	\checkmark	\checkmark		\checkmark		
Change Planning Unit Status	\checkmark	\checkmark				
Get User Preferences	\checkmark	\checkmark		\checkmark		\checkmark
Import Data Slice	\checkmark	\checkmark		\checkmark		\checkmark
Export Data Slice	\checkmark	\checkmark		\checkmark		\checkmark
Clear Data Slice	\checkmark	\checkmark		\checkmark		\checkmark
Get All Substitution Variables Defined for the Application	~	\sim		~		~
Get a Substitution Variable Defined for the Application	~	\sim		~		
Create or Update All Substitution Variables Defined for the Application	~	\sim		~		
Get Substitution Variables Defined at the Plan Type Level	~	\sim		~		
Get Derived Substitution Variables at the Plan Type Level	~	\sim		~		
Get a Derived Substitution Variable Defined at the Plan Type Level	~	~		~		
Delete a Substitution Variable at the Plan Type Level	~	~		~		
Delete a Substitution Variable for the Application	~	~		~		
Delete Substitution Variables at the Plan Type Level	~	\sim		~		

Table 3-2	Planning, FreeForm,	Strategic Workforce Plannin	g. and Sales Planning
	r iaining, r icci orin,	Ollalegie Workforde Flammin	g, and bales r lanning

Planning, FreeForm, Strategic Workforce Planning, and Sales Planning Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Delete Substitution Variables for the Application	\checkmark	\checkmark		~		

Table 3-2(Cont.) Planning, FreeForm, Strategic Workforce Planning, and SalesPlanning

Migration

Table 3-3 Migration

Migration Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Migration Status Codes	\checkmark	\checkmark	~	~	~	~
Get REST API Versions for Migration	\checkmark	\checkmark	\checkmark	~	\checkmark	~
Get Information about a Specific Version of Migration Sample Code	~	\sim	~	~	~	~
Import and Export Files						
LCM Import (v1)	\checkmark	~	~	\checkmark	\checkmark	\checkmark
LCM Import (v2)	\checkmark	~	~	\checkmark	\checkmark	\checkmark
LCM Export (v1)	~	\checkmark	~	\checkmark	\checkmark	\checkmark
LCM Export (v2)	\checkmark	~	~	\checkmark	\checkmark	\checkmark
Upload and Download Files						
Upload	\checkmark	~	~	\checkmark	\checkmark	\checkmark
Download	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
View and Delete Files						
List Files (v11.1.2.3.600)	\checkmark	~	~	\checkmark	\checkmark	\checkmark
List Files (v2)	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
Delete Files (v11.1.2.3.600)	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
Delete Files (v2)	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
Delete Files (v3)	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
Manage Services						
Get Information About All Services	\checkmark	~	~	\checkmark	\checkmark	\checkmark
Get Idle Session Timeout	\checkmark	~	~	\checkmark	\checkmark	\checkmark
Set Idle Session Timeout	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
Restart the Service Instance (v1)	\checkmark	\checkmark	~	\checkmark	\checkmark	\checkmark
Restart the Service Instance (v2)	~	\checkmark	~	\checkmark	\checkmark	\checkmark
Run Recreate on a Service (11.1.2.3.600)	~	~	~	~	~	~
Run Recreate on a Service (v2)	~	~	~	\checkmark	\checkmark	\checkmark
Manage Application Snapshots						
Get Information About All Application Snapshots	~	~	~	~	~	~
Get Information About a Specific Application Snapshot	~	~	~	~	~	~



Migration Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Upload Application Snapshot (v1)	~	~	~	~	~	~
Upload Application Snapshot (v2)	\checkmark	\checkmark	\checkmark	\checkmark	~	~
Download Application Snapshot (v1)	\checkmark	~	~	~	~	1
Download Application Snapshot (v2)	\checkmark	\checkmark	\checkmark	\checkmark	~	~
Copy Application Snapshot (v1)	\checkmark	\checkmark	~	~	\checkmark	~
Copy Application Snapshot (v2)	\checkmark	\checkmark	~	~	\checkmark	~
Rename Application Snapshot (v1)	\checkmark	\checkmark	~	~	\checkmark	~
Rename Application Snapshot (v2)	~	\checkmark	~	~	\checkmark	~
Copy to and from the Object Store						
Copy to Object Store (v1)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Copy to Object Store (v2)	\checkmark	~	~	~	\checkmark	~
Copy from Object Store (v1)	\checkmark	~	~	\checkmark	\checkmark	~
Copy from Object Store (v2)	\checkmark	~	~	\checkmark	~	~
Working with Oracle Essbase						
Export Essbase Data (v2)	\checkmark	\checkmark		\checkmark		\checkmark
Essbase Block Analysis Report	\checkmark	\checkmark				\checkmark
Get Essbase Query Governor Execution Time	~	~		~		\checkmark
Set Essbase Query Governor Execution Time	~	~		~		\checkmark
Other						
Copy a File Between Instances (v1)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Copy a File Between Instances (v2)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Clone an Environment	\checkmark	~	~	\checkmark	\checkmark	\checkmark
List Backups - Only for OCI (Gen 2) Environments	~	~	~	~	~	\checkmark
Restore Backup - Only for OCI (Gen 2) Environments	~	~	~	~	~	\checkmark
Provide Feedback (v11.1.2.3.600)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	~
Provide Feedback (v2)	\checkmark	\checkmark	\checkmark	\checkmark	~	~
Send Email (v1)	~	\checkmark	~	~	\checkmark	~
Send Email (v2)	~	\checkmark	~	~	\checkmark	~
Skip Updates (v1)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	~
Skip Updates (v2)	~	~	~	~	\checkmark	~

Table 3-3 (Cont.) Migration

Security

Table 3-4 Security

Security Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Get Restricted Data Access	\checkmark	\checkmark	~	\checkmark	~	~
Set Restricted Data Access	\checkmark	\checkmark	~	~	~	~
Get Virus Scan on File Upload	\checkmark	\checkmark	\checkmark	\checkmark	~	~
Set Virus Scan on File Upload	\checkmark	~	~	\checkmark	~	~
Manage Permission for Manual Access to Database (v1)	~	\sim	~	~	~	~
Manage Permission for Manual Access to Database (v2)	~	\sim	~	~	~	~
Set Encryption Key (v1)	\checkmark	~	~	\checkmark	~	~
Set Encryption Key (v2)	\checkmark	~	~	\checkmark	~	~
View the IP Allowlist - Only for OCI (Gen 2) Environments	~	~	~	~	~	~
Update the IP Allowlist - Only for OCI (Gen 2) Environments	~	\sim	~	~	~	~

Daily Maintenance Window Time

Table 3-5 Daily Maintenance Window Time

Daily Maintenance Window Time Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Get the Build Version and Daily Maintenance Time (v1)	~	~	~	~	~	~
Get the Build Version and Daily Maintenance Window Time (v2)	~	~	~	~	~	~
Setting the Daily Maintenance Time (v1)	\checkmark	~	~	\checkmark	\checkmark	~
Setting the Daily Maintenance Time (v2)	\checkmark	\checkmark	\checkmark	~	~	\checkmark
Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v1)	~	~	~	~	~	~
Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v2)	~	~	~	~	~	~

Managing Users, Groups, and Roles

Table 3-6 Managing Users, Groups, and Roles

Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Add Users to an Identity Domain (v1)	~	\checkmark	~	~	~	\checkmark

ORACLE

Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Add Users to an Identity Domain (v2)	~	~	~	~	~	~
Remove Users from an Identity Domain (v1)	~	~	\checkmark	~	~	\checkmark
Remove Users from an Identity Domain (v2)	~	~	~	~	~	~
Assign Users to a Predefined Role or Application Role (v1)	~	~	~	~	~	~
Assign Users to a Predefined Role or Application Role (v2)	~	~	~	~	~	~
Remove Users' Role Assignment (v1)	\checkmark	~	~	~	\checkmark	V
Remove Users' Role Assignment (v2)	~	\checkmark	~	~	\checkmark	~
Add Users to a Group (v1)	~	\checkmark	~	~	\checkmark	~
Add Users to a Group (v2)	~	\checkmark	~	~	\checkmark	V
Remove Users from a Group (v1)	~	\checkmark	~	~	\checkmark	V
Remove Users from a Group (v2)	~	\checkmark	~	~	\checkmark	V
Update Users	~	\checkmark	~	~	\checkmark	V
Add a User to a Batch of Groups	~	\checkmark	~	~	\checkmark	~
Remove a User from a Batch of Groups	~	\checkmark	~	~	\checkmark	V
Add Groups (v1)	\checkmark	\checkmark	~	~	\checkmark	V
Add Groups (v2)	\checkmark	\checkmark	~	\checkmark	\checkmark	V
Remove Groups (v1)	\checkmark	\checkmark	~	\checkmark	\checkmark	V
Remove Groups (v2)	\checkmark	\checkmark	~	~	\checkmark	V
User Group Report (v1)	\checkmark	\checkmark	~	~	\checkmark	V
User Group Report (v2)	\checkmark	\checkmark	~	\checkmark	\checkmark	V
User Access Report (v1)	\checkmark	\checkmark	~	\checkmark	\checkmark	V
User Access Report (v2)	\checkmark	\checkmark	~	\checkmark	\checkmark	V
User Audit Report (v1)	~	\checkmark	~	~	\checkmark	V
User Audit Report (v2)	~	\checkmark	~	~	\checkmark	V
Group Assignment Audit Report	~	~	~	~	\checkmark	V
Role Assignment Report (v1)	~	~	~	~	\checkmark	V
Role Assignment Report for Users (v2)	~	~	~	~	\checkmark	~
Role Assignment Report for Groups (v2)	~	\checkmark	~	~	\checkmark	V
Get Available Roles	~	\checkmark	~	~	\checkmark	V
Role Assignment Audit Report for OCI (Gen 2) Environments	~	~	~	~	~	~
Invalid Login Report for OCI (Gen 2) Environments	~	~	~	\sim	~	~
Group Assignment Audit Report	~	\checkmark	~	~	\checkmark	~
Adding Users to a Team for Account Reconciliation			~			
Removing Users from a Team for Account Reconciliation			~			

Table 3-6 (Cont.) Managing Users, Groups, and Roles



Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Adding Users to a Team for Financial Consolidation and Close and Tax Reporting		~				~
Removing Users from a Team for Financial Consolidation and Close and Tax Reporting		~				~

Table 3-6 (Cont.) Managing Users, Groups, and Roles

Usage Simulation

Table 3-7 Usage Simulation

Data Integration Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Simulate Concurrent Usage	~	\checkmark				\checkmark

Reporting

Table 3-8 Reporting

Data Integration Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Generate Report for Account Reconciliation			~			
Generate Report for Financial Consolidation and Close and Tax Reporting		~				~
Generate User Details Report for Account Reconciliation			~			
Generate User Details Report for Financial Consolidation and Close and Tax Reporting		~				~
Retrieve Job Status for a Report		\checkmark	~			\checkmark
Execute Reports for Data Management	~	~	~	~	~	~

Data Integration

Table 3-9 Data Integration

Data Integration Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Get API Versions for Data Integration APIs	~	~	~	~	~	~



Data Integration Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Get Information about a Specific API Version for Data Integration APIs	~	~	~	~	~	~
Running Integrations	\checkmark	\checkmark	\checkmark	~	\checkmark	\checkmark
Running a Pipeline	\checkmark	\checkmark		\checkmark		~
Import Data Mapping	\checkmark	\checkmark	\checkmark	~	\checkmark	\checkmark
Export Data Mapping	\checkmark	\checkmark	\checkmark	\checkmark	~	\checkmark
Export Data Integration	\checkmark	\checkmark		\checkmark	~	\checkmark
Import Data Integration	\checkmark	\checkmark		\checkmark	~	\checkmark
Lock and Unlock POV	\checkmark	\checkmark	\checkmark	\checkmark	~	\checkmark
Retrieve Job Status	\checkmark	\checkmark	\checkmark	\checkmark	~	\checkmark

Table 3-9 (Cont.) Data Integration

Data Management

Table 3-10Data Management

Data Management Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Get API Versions for Data Management APIs	~	~	~	~	~	~
Get Information about a Specific API Version for Data Management APIs	~	~		~	~	~
Running Data Rules in Data Management	\checkmark	~	~	~	~	~
Running Batch Rules	\checkmark	\checkmark	\checkmark	\checkmark	~	1
Execute Reports for Data Management	\checkmark	\checkmark	\checkmark	\checkmark	~	1
Retrieve Job Status	\checkmark	\checkmark	\checkmark	\checkmark	~	1

Account Reconciliation

Table 3-11 Account Reconciliation

Account Reconciliation Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	PCM	TR
Get API Versions for Account Reconciliation REST APIs			~			
Get Information about a Specific API Version for Account Reconciliation RES ⁻ APIs	Г		~			
Retrieve Job Status for a Report			~			
Generate Report for Account Reconciliation			~			



Account Reconciliation Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Generate User Details Report for Account Reconciliation			\checkmark			
Export Application Properties			~			
Import Application Properties			~			
Export Background Image			\checkmark			
Import Background Image			\checkmark			
Export Logo Image			\checkmark			
Import Logo Image			\checkmark			
Create a Connection			~			
View All Connections			~			
Update a Connection			~			
Delete a Connection			~			
Set Application Access Level			~			
Retrieve Application Access Level			~			
Delete Profile			~			
Execute a Job in Account Reconciliation			~			
Retrieve Periods with a Specific Status			~			
Create Reconciliation (Reconciliation Compliance)			~			
Change Period Status (Reconciliation Compliance)			~			
Import Pre-Mapped Balances (Reconciliation Compliance)			~			
Import Pre-Mapped Transactions (Reconciliation Compliance)			~			
Import Balances (Reconciliation Compliance)			~			
Import Profiles (Reconciliation Compliance)			~			
Import Rates (Reconciliation Compliance)			~			
Import Reconciliation Attributes (Reconciliation Compliance)			~			
Import Attribute Values			\checkmark			
Monitor Reconciliations (Reconciliation Compliance)			~			
Retrieve Job Status (Reconciliation Compliance)			~			
View Reconciliation Comments			~			
Import Pre-Mapped Transactions (Transaction Matching)			\checkmark			
Run Auto Match (Transaction Matching)			~			
Purge Transactions (Transaction Matching)			~			

Table 3-11 (Cont.) Account Reconciliation



Account Reconciliation Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Archive Matched Transactions (Transaction Matching)			~			
Purge Archived Transactions (Transaction Matching)			~			
Unmatch Matched Transactions (Transaction Matching)			~			
Retrieve Job Status (Transaction Matching)			~			
Update Unmatched Transactions (Transaction Matching)			~			

Table 3-11 (Cont.) Account Reconciliation

Financial Consolidation and Close

Table 3-12 Financial Consolidation and Close

Financial Consolidation and Close Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Getting API Versions for Financial Consolidation and Close APIs		~				
Get Information about a Specific API Version for Financial Consolidation and Close APIs		~				
Export Consolidation Journals		\checkmark				
Import Consolidation Journals		\checkmark				
Perform Journal Actions for Financial Consolidation and Close		~				
Perform Journal Period Updates for Financial Consolidation and Close		~				
Retrieve Journals for Financial Consolidation and Close		\sim				
Retrieve Journal Details for Financial Consolidation and Close		\sim				
Copy Data		\checkmark				
Clear Data		\checkmark				
Validate Metadata		\checkmark				
Generate an Intercompany Matching Report		~				
Generate Report for Financial Consolidation and Close and Tax Reporting		~				~
Generate User Details Report for Financial Consolidation and Close and Tax Reporting		~				~
Retrieve Job Status for a Report		\checkmark				~

Task Manager

Table 3-13 Task Manager

Task Manager Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Update Task Status for Event Monitoring		~				~
Create a Connection		\checkmark				~
Delete a Connection		\checkmark				~
Update a Connection		\checkmark				~
View All Connections		\checkmark				~
Deploy Task Manager Templates		V				~

Supplemental Data Manager

Table 3-14 Supplemental Data Manager

Supplemental Data Manager Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Deploy Form Templates		~				
Import Supplemental Collection Data for Financial Consolidation and Close		~				

Enterprise Journals

Table 3-15 Enterprise Journals

Enterprise Journals Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Execute an Enterprise Journals Job		~				
Monitor Enterprise Journals for Financial Consolidation and Close		~				
Retrieve Enterprise Journals for Financial Consolidation and Close		~				
Retrieve Enterprise Journal Content for Financial Consolidation and Close		~				
Retrieve Enterprise Journal Content by Year and Period for Financial Consolidation and Close		~				
Update Enterprise Journal Posting Status for Financial Consolidation and Close		~				
Update Validation Status of Enterprise Journals for Financial Consolidation and Close		~				



Tax Reporting

Table 3-16Tax Reporting

Tax Reporting Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Getting API Versions for Tax Reporting APIs						~
Get Information about a Specific API Version for Tax Reporting						~
Clear Data						\checkmark
Copy Data						\checkmark
Generate Report for Financial Consolidation and Close and Tax Reporting		~				~
Generate User Details Report for Financial Consolidation and Close and Tax Reporting		~				~
Retrieve Job Status for a Report		~				~

Enterprise Profitability and Cost Management

Table 3-17 Enterprise Profitability and Cost Management

Enterprise Profitability and Cost Management Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Calculate Model				~		
Clear Data By Point of View				\checkmark		
Copy Data by Point of View				\checkmark		
Delete Point of View				\checkmark		
Generate Model Documentation Report				\checkmark		
Validate Model				~		

Profitability and Cost Management

Table 3-18 Profitability and Cost Management

Profitability and Cost Management Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Apply Data Grants					~	
Copy ML POV Data					\checkmark	
Create File-Based Application					\checkmark	
Deploy ML Cube					\checkmark	
Enable File-Based Application					\checkmark	
Essbase Data Load for Profitability and Cost Management					~	

Profitability and Cost Management Tasks	PLN, FF, SWP, SP	FCC	AR	EPCM	РСМ	TR
Export Template for Profitability and Cost Management					~	
Generate Program Documentation Report					~	
Generate Program Documentation Report - Run as a Job					\sim	
Import Template for Profitability and Cost Management					\sim	
Merge Slices for Profitability and Cost Management					\sim	
Optimize ASO Cube					\checkmark	
Retrieve Task Status for Profitability and Cost Management					\sim	
Run ML Calculations					\checkmark	
Run ML Clear POV					\checkmark	
Run ML Rule Balancing					\checkmark	
Update Dimensions As a Job					~	

Table 3-18 (Cont.) Profitability and Cost Management

About the Samples

Samples are described for selected integration scenarios and REST API reference sections. A working knowledge of Java, cURL, and Groovy is required to understand these samples.

The Java samples in this guide are coded using pure Java instead of third-party libraries such as Apache HTTP Client. The only JAR files you will need outside of JDK will be for JSON parsing.

This document does not teach REST concepts. As a prerequisite, a prior knowledge of REST programming is required to understand the examples, samples, scenarios, and reference sections.

Audience

This guide is intended primarily as a tool for infrastructure consultants and administrators of EPM Cloud.

Infrastructure consultants can use the documentation to build custom integration to provide basic and innovative services on top of these cloud services, including Planning, Planning Modules, Account Reconciliation, and Profitability and Cost Management.

Service administrators use this documentation to perform selected administrative tasks using REST APIs and EPM Automate. Completing administrative tasks using EPM Automate and REST APIs as an alternative to using the user interface requires considerable technical and functional expertise. Only technically competent administrators should use this guide to perform these administrative tasks.

Prerequisites

Prerequisites to using the REST APIs and the EPM Automate Utility include the following:

- Access as a valid user to the cloud service with prerequisites set up for the service. See Getting Started with Oracle Enterprise Performance Management as an Administrator and Getting Started with Oracle Enterprise Performance Management as a User.
- Technical and functional knowledge to understand and execute the EPM Automate Utility and REST APIs, and to administer the product.
- Knowledge of Java, cURL, Groovy, and REST programming.
- Jobs are required for many EPM Automate utility commands and REST APIs. Jobs are actions, such as importing or exporting data that can be started immediately or scheduled for a later time; for example, importing or exporting data. Be sure that you understand how to use jobs as described in Managing Jobs.
- Data load rules define how Data Management loads data from a file. You must have predefined data load rules to load data using REST APIs and EPM Automate Utility. You can also load data using batches defined in Data Management. Using a batch, Service Administrators can combine many load rules in a batch and execute them in serial or parallel mode.
- Business rules are required for some jobs. For example for Planning, you use Calculation Manager to create business rules, which are then deployed into a Planning application. Learn about business rules in *Designing with Calculation Manager for Oracle Enterprise Performance Management Cloud*

URL Structure

For the URL structure to use, see the topic for the REST API:

- Planning and Budgeting REST API URL
- Migration REST API URL
- Data Management REST API URL
- Account Reconciliation REST API URL
- Enterprise Profitability and Cost Management REST API URL
- Profitability and Cost Management REST API URL

In the description and examples of all REST APIs, this guide uses state The state URL> is the first part of your service URL, before the context. For example, if your service URL
is https://epm-acme.epm.us-phoenix-1.ocs.oraclecloud.com/epmcloud, your state URL is
https://epm-acme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is
https://epm2-acme.epm.us6.oraclecloud.com/epmcloud, your state-URL> is https://epm2-acme.epm.us6.oraclecloud.com.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ <code>internal/"</code> in the URL.



For details on the URL structure, see Differences Between Classic and OCI EPM Cloud Environments. To learn about accessing Oracle Cloud and Oracle Enterprise Performance Management Cloud, see Getting Started with Oracle Cloud and Getting Started with Oracle Enterprise Management Cloud for Administrators. 4

OAuth 2 and Basic Authentication for EPM Cloud REST APIs

All HTTP requests to the REST APIs require authentication. Review these topics to understand OAuth 2 and basic authentication for EPM Cloud REST APIs.

The REST APIs for EPM Cloud support authentication with OAuth 2 and basic authentication:

- Authentication with OAuth 2 Only for OCI (Gen 2) Environments
- Basic Authentication for Classic and OCI (Gen 2) Environments

EPM Cloud REST APIs can connect to Oracle Enterprise Performance Management Cloud through API Gateways, such as Google APIGEE, IBM Data Power, and other reverse proxy servers.

For this to work, configure the gateway or reverse proxy by setting the target as the URL of your EPM Cloud environment without any context such as /epmcloud. Example: https://epm-idDomain.epm.dataCenterRegion.oraclecloud.com. Then, use the reverse proxy URL instead of the EPM Cloud URL in the REST API. For configuration information, see the documentation of your gateway or proxy server.

While configuring the proxy settings, be sure to pass the response code from EPM Cloud to EPM Cloud REST API without modifying it in any manner to allow REST API processing code to correctly process response codes such as 200, 206, 400, 404, 500, 501, and so on. For example, for IBM Datapower, set proxy HTTP Response to ON. Additionally, the API gateway should allow HTTP methods (GET, POST, PUT, PATCH, and DELETE).

Note that REST APIs cannot be run by users who are set up for basic authentication with multifactor authentication (MFA).

Authentication with OAuth 2 - Only for OCI (Gen 2) Environments

In EPM Cloud environments on Oracle Cloud Infrastructure (OCI) / Gen 2 architecture, you can use an OAuth 2 access token to issue REST APIs on EPM Cloud to satisfy the requirement of avoiding the use of passwords in your environment.

Setting Up Authentication with OAuth 2

In order to access EPM Cloud REST APIs with OAuth 2, an EPM Cloud Service Administrator has to request the Domain Administrator to set up an OAuth 2 client and provide the Identity Domain Cloud Service (IDCS) URL and Client ID.

Overview of the steps:

- Step 1. Register an OAuth client. This is a one-time setup step that requires user interaction with IDCS Administrator privileges.
- Step 2. Obtain and securely store the first refresh token. This step requires user interaction. It is a one-time step for each user that needs to invoke REST APIs with OAuth 2.



• Step 3. Obtain an access token from the refresh token. This step is easily automated. Once automation has been implemented, it can run without user interaction.

The following sections provide detailed information about each step.

Step 1: Register an OAuth Client

Registering an OAuth client is a one-time process. The first step is to update the service provider configuration to authorize requests from the REST client application. As a security measure, any client application that accesses Oracle Cloud resources must be authorized to do so. An IDCS Administrator enables this authorization by registering a client and providing the appropriate registration information to the client's users.

A client application in IDCS is used to obtain an access token. A valid access token (also called a Bearer token) is sufficient authorization to invoke a REST API.

Oracle Enterprise Performance Management Cloud uses a role-based access control mechanism to permit only authorized users access to the service. For details, see About EPM Cloud User and Role Management. This requires that any OAuth 2 access token used to access EPM Cloud REST APIs contains a user context.

A grant type is a standard method to obtain an access token. There are a few different Grant Types as listed here that could be used to obtain an access token. An access token obtained by any of the supported grant types is acceptable as long as the access token is in the context of the user that would be invoking the REST APIs.

In this document, we describe the use of the Device Code Grant Type. EPM Automate has built-in support for the Device Code Grant type.

While the Device Code Grant Type would work in a majority of environments, it might not be right for every implementation. Any of the Grant Types that allow creating an access token with a user context would be suitable for EPM Cloud REST APIs. In addition to the Device Code Grant Type, the following Grant Types support access tokens in the context of an end user:

- Authorization Code Grant Type
- Resource Owner Password Credentials Grant Type
- Assertion Grant Type when access token is in the context of the end user
- Implicit Grant Type

The next section highlights the steps to create a sample OAuth 2 client using the Device Code Grant Type to request an access token. It also demonstrates how to use the access token to invoke EPM Cloud's Get Daily Maintenance Window REST API.

Refer to the Oracle Identity Cloud Service documentation for more details on the Supported Access Grant Types.

The Identity Cloud Service Administrator follows the steps in this topic to create a public client using the Identity Cloud Service Administrator console. The IDCS Administrator then shares the Identity Cloud Service tenant URLand client ID with the EPM Cloud Service Administrator.

If you have an Oracle Identity Cloud Services domain, log in to the Oracle IDCS Administrator console to register an OAuth 2 Client as described in Detailed Information for Using IDCS Administrator Console to Register an OAuth 2 Client.

If your domain is a domain under Oracle Identity and Access Management, follow the instructions in Detailed Information for Using IAM Console to Register an OAuth 2 Client.



Detailed Information for Using IDCS Administrator Console to Register an OAuth 2 Client

- **1.** From the **Applications** drawer, click **Add** at the top of the page.
- 2. In the Add Application dialog box, select Mobile Application.
- 3. In the App Details section, enter a name for the REST client.
- 4. Optional: Add other details.
- 5. Click Next.
- 6. In the Authorization section, under Allowed Grant Types, unselect the Implicit check box and select the Refresh Token and Device Code check boxes.
- 7. Under the Token Issuance Policy section:
 - a. Under Grant the client access to Identity Cloud Service Admin APIs, click Add.
 - b. Select Identity Domain Administrator.
 - c. Click Add to close the pop-up.
- 8. Click Next and then Finish to complete creating this OAuth 2 client application.
- 9. Note the client ID value on the pop-up.
- 10. Click Activate to activate the client, and then click OK.

Detailed Information for Using IAM Console to Register an OAuth 2 Client

- 1. Log in to your account at https://cloud.oracle.com/
- Click the hamburger menu on the top left and choose Identity and Security and then click Domains on the dialog box.
- 3. From the Domains table, choose the appropriate domain (OracleIdentityCloudService by default). This brings you to the Domain Overview page.
- Note the Domain URL in the Domain Information section of the page. This is the tenantbase-URL that will be required to request a token.
- 5. To create an OAuth 2 client, click **Applications** in the Identity Domain.
- 6. Click the Add application button,
- 7. Choose **Mobile Application** on the pop-up menu and then click the **Launch Workflow** button.
- 8. Enter a name and a description to document the use of this OAuth 2 client.
- 9. Click the Next button on the bottom left.
- On the Client configuration step, in the Authorization section, select Refresh token and Device code and unselect Implicit.
- 11. In the Token Issuance policy section:
 - a. Enable Add app roles.
 - **b.** Click the **Add roles** button.
 - c. Choose Identity Domain Administrator on the slide-in dialog box.
 - d. Click the Add button to close the slide-in dialog box.
- 12. Click Finish to complete the configuration and Activate to activate the application.
- **13.** Note the Client ID value in the General Information section of the OAuth Configuration.

The IDCS Administrator provides the IDCS URL and client ID to the EPM Cloud Service Administrator.

Step 2. Obtain and securely store the first refresh token

After the Domain Administrator has registered the REST client and provided the IDCS URL and client ID, an EPM Cloud user executes the following steps to get a valid refresh token.

1. Issue the following unauthenticated request to the Identity Cloud Service URL:

```
curl --location --request POST 'https://tenant-base-url/oauth2/v1/device' \
--header 'Content-Type: application/x-www-form-urlencoded;charset=utf-8' \
--data-urlencode 'response_type=device_code' \
--data-urlencode 'scope=urn:opc:idm:_myscopes__ offline_access' \
--data-urlencode 'client_id=<CLIENT ID OF OAUTH2 APPLICATION>'
```

Here, the value of tenant-base-url is the IDCS URL provided by the Domain Administrator or the Domain URL from the IAM console. It is of the form idcs-<alphanumericvalue>.identity.oraclecloud.com. Similarly, the value for the CLIENT ID OF THE OAUTH2 APPLICATION is also provided by the Domain Administrator or retrieved from the Application's General Information section in IAM. It is an alphanumeric value.

A valid response contains a device code, user code, and verification URI:

```
{
   "expires_in": 300,
   "device_code": "4d03f7bc-f7a5-4795-819a-5748c4801d35",
   "user_code": "SDFGHJKL",
   "verification_uri": "https://tenant-base-url/ui/v1/device"
}
```

The user_code from the response is needed in the second step below, while device_code from the response is needed in the third step below.

Note: Steps 2 and 3 are time-sensitive because the user code and device code expire 300 seconds (5 minutes) after creation. If the codes expire before these steps can be completed, redo the first step of this section to issue an unauthenticated request to the IDCS URL to receive a new pair of user and device codes.

2. Open the verification uri in a supported web browser.

At this stage, it is important to know that if a user already has an active browser session, the user will not be prompted for re-authentication. If the token is to be generated in context of the currently signed-in user, then proceed with 2b. However, if the token is to be generated in the context of a different user, please sign-out of the current session and navigate to the verification_uri and continue with 2a.

- a. When prompted for credentials, authenticate the user who will be invoking the REST API. These credentials could be credentials for a SAML 2.0 compliant Identity Provider or a native IDCS credential.
- **b.** When prompted for a code in the browser session, enter the user_code from the response payload.
- c. When the Successful message is displayed, it is recommended to log out of the browser session and close the browser window.

 Within 5 minutes of executing the first step of this section and after executing the second step, issue the following request to the Identity Cloud Service URL:

```
curl --location --request POST 'https://tenant-base-url/oauth2/v1/token' \
--header 'Content-Type: application/x-www-form-urlencoded;charset=utf-8' \
--data-urlencode 'grant_type=urn:ietf:params:oauth:grant-type:device_code' \
--data-urlencode 'device_code=<DEVICE CODE FROM THE PAYLOAD OF RESPONSE IN
FIRST STEP>' \
--data-urlencode 'client id=<CLIENT ID OF THE OAUTH2 APPLICATION>'
```

Here the value of tenant-base-url is the IDCS URL provided by the Domain Administrator, the device_code value is obtained from the response in Step 1, and client_id is the same client_id used in the first step of this section.

The response contains the first refresh token:

```
{
    "access_token": "eyJ4NXQjUzI.....evRJChXTRfzn6WlCw",
    "token_type": "Bearer",
    "expires_in": 3600,
    "refresh_token": "AQIDBAWF1.....RVkxNCB7djF9NCA="
}
```

Secure and Protect the Tokens and Client ID

With OAuth 2, tokens are used instead of user credentials to access resources on EPM Cloud. A refresh token and client ID are used to get a new access token and a new refresh token. Thus, to ensure security of EPM Cloud, it is important to securely encrypt and store the client_id and any tokens. The REST client must securely store the refresh token and client id.

For EPM Automate, use the encrypt command to create an epw file for OAuth 2.

Step 3: Obtain an Access Token from the Refresh Token

This step is required every time a new access token is required. The REST client uses the latest refresh token and client id to get an access token. It uses the access token as authorization to invoke REST APIs. It also ensures that the latest refresh token and client ID are stored securely.

The REST client uses the Refresh Token Grant type to get a new access token and a new refresh token. As mentioned above, this step can be automated. Once automated, it does not require user interaction.

To obtain a valid access token with this Grant Type, the REST client issues the following request to the IDCS URL:

```
curl --location --request POST 'https://tenant-base-url/oauth2/v1/token' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--data-urlencode 'grant_type=refresh_token' \
--data-urlencode 'client_id=<DECRYPTED CLIENT ID OF OAUTH2 APPLICATION FROM
SECURE STORE>' \
--data-urlencode 'refresh token=<DECRYPTED REFRESH TOKEN FROM SECURE STORE>'
```



Here, the value of tenant-base-url is the IDCS URL provided by the Domain Administrator, and the refresh_token and client_id are obtained from the secure store where there were previously stored.

Note: While the client_id and refresh_token are stored securely, it is important that both refresh_token and client_id are decrypted to use in any request. All requests to Oracle IDCS and EPM Cloud are securely transmitted using the https protocol.

Example response:

```
{
"access_token": "eyJj5M4QjUkI.....abSjZaa86PlseS4lrt7R2",
   "token_type": "Bearer",
   "expires_in": 3600,
   "refresh_token": "AAyyilYBAWD4....FVkxefd8kjoJr6HJPA="
}
```

The REST client saves the new refresh token for future use (see Secure and Protect the Token and Client ID) and uses the access token as authorization while invoking the REST API (see Use the Access Token).

Use the Access Token

In order to invoke an EPM Cloud REST API, the REST client must provide the access token (obtained in the previous step) in the authorization header as follows:

Authorization: Bearer <access token>

For example, to get the Automated Maintenance Window start time, the client application submits a GET request to this EPM Cloud endpoint /interop/rest/v1/services/ dailymaintenance using the access token in the authorization header.

```
curl --location --request GET 'https://epm-host/interop/rest/v1/services/
dailymaintenance' \
--header "Authorization: Bearer eyJ5M4QjUkI...abSjZaa86PlseS4lrt7R2"
```

Frequently Asked Questions

OAuth 2 was set up following the documentation before EPM Cloud Release 23.07. Is that configuration still valid?

Yes, the existing configuration will continue to work with existing OAuth 2 support for REST APIs and EPM Automate. However, it is highly recommended to use the updated procedure as it provides greater clarity and might be required for future updates.

How do I change my existing configuration created before EPM Cloud Release 23.07 to be consistent with the current procedure?

The following steps will bring your existing configuration in line with the documented configuration:

- For the Oracle Cloud Services, on the Configuration tab under Resources, unselect the Is Refresh Token Allowed checkbox.
- For the OAuth 2 client application, under Token Issuance Policy, remove the Resource or Resources selected and add the Identity Administrator Role to the Client as described in Step 7 for IDCS Administrator console or Step 11 for IAM console.



For EPM Automate, create a new epw file using the updated instructions in EPM Automate Commands, and then save the new refresh token and client id and use it to authorize access.

Can the expiry time of a refresh token be modified?

The expiry time of the refresh token is configurable in Identity Cloud Service by the Domain Administrator on a per EPM Cloud environment basis. The client requesting the refresh token cannot modify the expiry time or duration. The client should request a new refresh token before the old one expires, in order to not repeat the initial setup again. The default expiry period is 604800 seconds, which is 7 days.

What error is returned when the refresh token has expired?

Executing a refresh token grant flow with an expired refresh token results in a 400 Bad *Request* response and the following payload:

```
{ "error": "invalid_grant",
   "error_description": "Token is expired for client : <CLIENT_ID>",
   "ecid": "UsbMB0KCV00000000"
}
```

What error is returned when the refresh token is invalid?

Executing a refresh token grant flow with an invalid refresh token results in a 400 Bad Request response and the following payload:

```
{ "error": "invalid_grant",
   "error_description": "The given token in the request is invalid",
   "ecid": "UsbMB0KCV00000000"
}
```

What errors are returned for other issues?

A 400 Bad Request response with the following payloads are returned when there is an error:

Invalid request (for example, not all request parameters are supplied):

```
{
    "error": "invalid_request",
    "error_description": "The request contains invalid parameters or values"
}
```

Invalid grant (for example, using a token that has already been used) :

```
{
    "error": "invalid_grant",
    "error_description": "The token has already been consumed"
}
```



Invalid scope (for example, providing invalid scope):

```
{
    "error": "invalid_scope",
    "error_description": "Invalid scope"
}
```

What error is returned when an invalid or expired access token is provided?

When an invalid or expired access token is provided in a request, the server responds with a 401 Unauthorized response with the following HTML in the payload:

```
<html>
<head><title>401 Authorization Required</title></head>
<body>
<center><h1>401 Authorization Required</h1></center>
<hr>
</body>
</html>
```

Can a token be requested with multiple scopes?

Multiple scopes across different resources (EPM Cloud environments) are not supported by Identity Cloud Service. Each token request can support only one resource. Requests for multiple scopes within the same resource are supported with space delimited scopes. Requesting multiple scopes across different resources results in a *400 Bad Request* response with the following payload:

```
{
"error": "invalid_scope",
"error_description": "Invalid scope"
}
```

Can a valid token received for one EPM Cloud environment be used to access all EPM Cloud environments in the same IDCS domain?

The EPM Cloud Service Administrator for an environment provisions each user with predefined and application roles and specific access for that environment. The same user may be provisioned with different privileges on different environments in the same IDCS domain. The functionality that a user is able to perform on any EPM Cloud environment is dependent on the roles and access the user has on that environment. Thus, a valid, unexpired bearer token received for one EPM Cloud environment can be used across all EPM Cloud environments in the same IDCS domain for authentication purposes. However, the authorization of what a particular user can do on a particular EPM Cloud environment is dependent on the roles the user has on that environment.

What information is logged in the access log with OAuth?

The access log shows the user name, just as it does with basic authorization. The client ID and access token are not logged.

When using multiple scripts to run EPM REST APIs, the refresh token grant type seems to fail randomly with a message that the token is already consumed. What is the resolution?



Each refresh token is a single use token. After first use, the same token cannot be reused. Trying to use a particular token after it has already been used results in the message, *The token is already consumed*.

The right way is to set up each script with its own refresh token. To do that, execute the procedure to obtain and save the first refresh token once for each script requiring a refresh token, and then set up each script to use its own refresh token. All scripts can still use the same clientID.

Basic Authentication - for Classic and OCI (Gen 2) Environments

In EPM Cloud environments on Classic or OCI (Gen 2) architecture, the REST APIs support basic authentication (name and password).

If your environment is on Classic Oracle Cloud Infrastructure, use a username in the format identitydomain.username.

If your environment is on OCI (Gen 2) Oracle Cloud Infrastructure, you can use basic authentication by supplying a username in the format of identitydomain.username or only username (without identity domain).

HTTP requests to Oracle Enterprise Performance Management Cloud should supply HTTP Basic Authentication credentials through the **Authorization** header.

Finding Your Identity Domain

If your environment is on Classic Oracle Cloud Infrastructure, ensure that you are correctly specifying your identity domain when logging into an environment using REST APIs.

Use one of these methods to identify your identity domain:

- Look in the Activity Report for your environment. The name of the identity domain is displayed at the top left corner of the Activity Report. See "About the Activity Report" in *Getting Started with EPM Cloud for Administrators*.
- Derive the identity domain name from the URL that you use to access the environment.
 For example, in this fictitious URL, https://epm exampleDomain.epm.dataCenter.oraclecloud.com/, the identity domain name is
 exampleDomain.

The test and production environments of a subscription usually share the same identity domain. For example, for test environments like as this fictitious URL, https://epm-test-exampleDomain.epm.dataCenter.oraclecloud.com/, the identity domain can be derived as the string enclosed between "test-" and the next ".", in this case, **exampleDomain**.

For production environments like this fictitious URL, https://epm-exampleDomain.epm.dataCenter.oraclecloud.com/, the identity domain can be derived as the string enclosed between the first "-" and next ".", in this case, exampleDomain.

Note: In this guide, URLs are shown in the following format: https://<BASE-URL>

When using PowerShell to call EPMCloud REST API, ensure that the Authorization header is always specified. For example:

```
$headers = @{
"Authorization" = "Basic " +
[System.Convert]::ToBase64String([System.Text.Encoding]::UTF8.GetBytes($userNa
me+":"+$userPassword))
}
Invoke-RestMethod -Method 'Get' -Uri $url -Headers $headers
```



Sample Integration Scenarios

This section provides selected sample scenarios for EPM Cloud REST APIs to help you get started.

Related Topics

- Scenario 1: Import Metadata into Applications
 This scenario shows how to use EPM Cloud REST APIs to import metadata into applications.
- Scenario 2: Import Data, Run a Calculation Script, and Copy Data from a Block Storage Database to an Aggregate Storage Database
 This scenario shows how to use the EPM Cloud REST APIs to import data, run a calculation script, and copy data from a block storage database to an aggregate storage database.
- Scenario 3: Export and Download Metadata and Data This scenario shows how to use the EPM Cloud REST APIs to export and download metadata and data.
- Scenario 4: Remove Unnecessary Files from a Service Instance This scenario shows how to use the EPM Cloud REST APIs to remove unnecessary files from a service instance.
- Scenario 5: Archive Backups from the Service to Onpremise This scenario shows how to use the EPM Cloud REST APIs to archive backups from the service to onpremise.
- Scenario 6: Refreshing the Application This scenario shows how to use the EPM Cloud REST APIs to refresh the application.
- Scenario 7: Cloning an Instance This scenario shows how to use the EPM Cloud REST APIs to clone an instance.
- Scenario 8: Sample Starter Kit for Consultants Business Intelligence Cloud Integration This scenario provides a sample starter kit for consultants to integrate with Oracle Business Intelligence Cloud.
- Scenario 9: Using Groovy Business Rules to Call REST APIs from Oracle and Other Companies

The scenario shows how to use the Oracle Enterprise Performance Management Cloud Groovy object model to call Oracle REST APIs and REST APIs developed by other companies.

Scenario 1: Import Metadata into Applications

This scenario shows how to use EPM Cloud REST APIs to import metadata into applications.

Example 5-1 Java

```
public void integrationScenarioImportMetadataIntoApplication() throws
Exception {
    uploadFile("accounts.zip");
    executeJob("IMPORT METADATA", "accountMetadata",
```



```
"{importZipFileName:accounts.zip}");
    executeJob("CUBE_REFRESH", null, null);
}
```

Common Functions: See Common Helper Functions for Java.

Dependent APIs: see Java Sample – UploadFile.java and Java Sample – ExecuteJob.java in Upload and Download Files.

Example 5-2 cURL

```
funcIntegrationScenarioImportMetadataIntoApplication() {
   funcUploadFile "DemoApplication_HSS_Vision.zip"
   funcExecuteJob "IMPORT_METADATA" "accountMetadata"
   "{importZipFileName=accounts.zip}"
   funcExecuteJob "CUBE_REFRESH" "cubeRefresh"
}
```

Example 5-3 Groovy

```
def integrationScenarioImportMetadataIntoApplication() {
    uploadFile("DemoApplication_HSS_Vision.zip")
    executeJob("IMPORT_METADATA", "accountMetadata",
    "importZipFileName=accounts.zip");
    executeJob("CUBE_REFRESH", "cubeRefresh", null);
}
```

Common functions: See CSS Common Helper Functions for Groovy

Scenario 2: Import Data, Run a Calculation Script, and Copy Data from a Block Storage Database to an Aggregate Storage Database

This scenario shows how to use the EPM Cloud REST APIs to import data, run a calculation script, and copy data from a block storage database to an aggregate storage database.

Example 5-4 Java

```
public void integrationScenarioImportDataRunCalcCopyToAso() throws Exception {
    uploadFile("data.csv");
    executeJob("IMPORT_DATA", "loadingq1data", "{importFileName:data.csv}");
    executeJob("CUBE_REFRESH", null, null);
    executeJob("PLAN_TYPE_MAP", "CampaignToReporting", "{clearData:false}");
}
```

Common Functions: See Common Helper Functions for Java.

Dependent APIs: see Java Sample – UploadFile.java and Java Sample – ExecuteJob.java in Upload and Download Files.



Example 5-5 cURL

```
funcIntegrationScenarioImportDataRunCalcCopyToAso() {
   funcUploadFile "data.csv"
   funcExecuteJob "IMPORT_DATA" "loadingq1data" "{importFileName=data.csv}"
   funcExecuteJob "CUBE_REFRESH","cubeRefresh"
   funcExecuteJob "PLAN_TYPE_MAP" "CampaignToReporting" "{clearData=false}"
}
```

Example 5-6 Groovy

```
def integrationScenarioImportDataRunCalcCopyToAso() {
    uploadFile("data.csv");
    executeJob("IMPORT_DATA", "loadingq1data", "importFileName=data.csv");
    executeJob("CUBE_REFRESH", "cubeRefresh", null);
    executeJob("PLAN_TYPE_MAP", "CampaignToReporting", "clearData=false");
}
```

Scenario 3: Export and Download Metadata and Data

This scenario shows how to use the EPM Cloud REST APIs to export and download metadata and data.

Example 5-7 Java

```
public void integrationScenarioExportMetadataAndDataAndDownloadFiles() throws
Exception {
    executeJob("EXPORT_METADATA", "exportentitymetadata",
    "{exportZipFileName:entitydata.zip}");
    executeJob("EXPORT_DATA", "Forecastdata",
    "{exportFileName:forecastdata.zip}");
    listFiles();
    downloadFile("entitydata.zip");
    downloadFile("forecastdata.zip");
}
```

Common Functions: See Common Helper Functions for Java.

Dependent APIs: see Java Sample – DownloadFile.java and Java Sample – ExecuteJob.java in Upload and Download Files.

Example 5-8 cURL

```
funcIntegrationScenarioExportMetadataAndDataAndDownloadFiles() {
   funcExecuteJob "EXPORT_METADATA" "exportentitymetadata"
   "{exportZipFileName=entitydata.zip}"
   funcExecuteJob "EXPORT_DATA" "Forecastdata"
   "{exportFileName=forecastdata.zip}"
   funcListFiles
   funcDownloadFile "entitydata.zip"
   }
}
```



Example 5-9 Groovy

```
def integrationScenarioExportMetadataAndDataAndDownloadFiles() {
    executeJob("EXPORT_METADATA", "exportentitymetadata",
    "exportZipFileName=entitydata.zip");
    executeJob("EXPORT_DATA", "Forecastdata",
    "exportFileName=forecastdata.zip");
    listFiles();
    downloadFile("entitydata.zip");
    downloadFile("forecastdata.zip");
}
```

Scenario 4: Remove Unnecessary Files from a Service Instance

This scenario shows how to use the EPM Cloud REST APIs to remove unnecessary files from a service instance.

Example 5-10 Java

```
public void integrationScenarioRemoveUnnecessaryFiles() throws Exception {
    listFiles();
    deleteFile("entitymetadata.csv");
    deleteFile("forecastdata.csv");
}
```

Common Functions: See Common Helper Functions for Java.

Dependent APIs: See Java Sample — ListFiles.java and Java Sample — DeleteFile.java in View and Delete Files.

Example 5-11 cURL

```
funcIntegrationScenarioRemoveUnnecessaryFiles() {
   funcListFiles
   funcDeleteFile "entitymetadata.csv"
   funcDeleteFile "forecastdata.csv"
}
```

Example 5-12 Groovy

```
def integrationScenarioRemoveUnnecessaryFiles() {
    listFiles();
    deleteFile("entitymetadata.csv");
    deleteFile("forecastdata.csv");
}
```

Scenario 5: Archive Backups from the Service to Onpremise

This scenario shows how to use the EPM Cloud REST APIs to archive backups from the service to onpremise.



Example 5-13 Java

```
public void integrationScenarioExportDataAndDownloadFiles() throws Exception {
    executeJob("EXPORT_DATA", "entitydata",
    "{exportFileName:entitydata.zip}");
    executeJob("EXPORT_DATA", "forecastdata",
    "{exportFileName:forecastdata.zip}");
    listFiles();
    downloadFile("entitydata.zip");
    downloadFile("forecastdata.zip");
}
```

Common Functions: See Common Helper Functions for Java.

Dependent APIs: See Java Sample — ExecuteJob.java and Java Sample — DownloadFile.java in Upload and Download Files.

Example 5-14 cURL

```
funcIntegrationScenarioExportDataAndDownloadFiles() {
   funcExecuteJob "EXPORT_DATA" "entitydata"
   "{exportFileName:entitydata.zip}"
   funcExecuteJob "EXPORT_DATA" "forecastdata"
   "{exportFileName:forecastdata.zip}"
   funcListFiles
   funcDownloadFile "entitydata.zip"
}
```

Example 5-15 Groovy

```
def integrationScenarioExportDataAndDownloadFiles() {
    executeJob("EXPORT_DATA", "entitydata", "exportFileName:entitydata.zip");
    executeJob("EXPORT_DATA", "forecastdata",
"exportFileName:forecastdata.zip");
    listFiles();
    downloadFile("entitydata.zip");
    downloadFile("forecastdata.zip");
}
```

Scenario 6: Refreshing the Application

This scenario shows how to use the EPM Cloud REST APIs to refresh the application.

Example 5-16 Java

```
public void integrationScenarioRefreshTheApplication() throws Exception {
    uploadFile("accounts.zip");
    executeJob("IMPORT_METADATA", "accountMetadata",
    "{importZipFileName:accounts.zip}");
    executeJob("CUBE_REFRESH", null, null);
}
```

Common Functions: See Common Helper Functions for Java.



Dependent APIs: See Java Sample — ExecuteJob.java and Java Sample — UploadFile.java in Upload and Download Files.

Example 5-17 cURL

```
funcIntegrationScenarioRefreshTheApplication() {
   funcUploadFile "accounts.zip"
   funcExecuteJob "IMPORT_METADATA" "accountMetadata"
"{importZipFileName:accounts.zip}"
   funcExecuteJob "CUBE_REFRESH" "cubeRefresh"
}
```

Example 5-18 Groovy

```
def integrationScenarioRefreshTheApplication() {
    uploadFile("accounts.zip");
    executeJob("IMPORT_METADATA", "accountMetadata",
    "importZipFileName:accounts.zip");
    executeJob("CUBE_REFRESH", "cubeRefresh", null);
}
```

Scenario 7: Cloning an Instance

This scenario shows how to use the EPM Cloud REST APIs to clone an instance.

There are three ways to clone an environment. For this scenario, use one of the following procedures:

- Use Clone Environment user interface
- Use EPM Automate
- Use a REST API

Scenario 8: Sample Starter Kit for Consultants - Business Intelligence Cloud Integration

This scenario provides a sample starter kit for consultants to integrate with Oracle Business Intelligence Cloud.

A sample starter kit can be used by infrastructure consultants to plan integration for Planning with Business Intelligence Cloud.

Prerequisites

- You have accounts for Business Intelligence Cloud, Planning, and Oracle Application Express.
- You have considerable technical and functional expertise with Business Intelligence Cloud, Planning, Oracle Application Express, REST, Groovy, and scripting.

For detailed information, see Sample Starter Kit for Consultants - Integration with Business Intelligence Cloud Service.



Scenario 9: Using Groovy Business Rules to Call REST APIs from Oracle and Other Companies

The scenario shows how to use the Oracle Enterprise Performance Management Cloud Groovy object model to call Oracle REST APIs and REST APIs developed by other companies.

These tutorials show you how to call a Data Management REST API to execute a data load rule and how to call the Google Places REST API from a Groovy script to add or update employee address information in Planning.

To learn how to use Groovy business rules to call Oracle and external REST APIs:

- Calling a REST API from Oracle Using Groovy
- Calling a REST API from Other Companies Using Groovy

To get an introduction to Groovy business rules:

- Learning Groovy in Oracle EPM Cloud video
- Creating a Groovy Business Rule in Designing with Calculation Manager for Oracle Enterprise Performance Management Cloud
- Introduction to Groovy Business Rules tutorial
- Additional Groovy Tutorials
- EPM Cloud Groovy Rules Java API Reference



6

Quick Reference Table – REST API Resource View

The REST resources provide powerful APIs that you can use to manage Oracle Enterprise Performance Management Cloud as an alternative to using the web-based user interface.

These tables summarize the REST resource paths.

- EPM Platform
- Planning, FreeForm, Strategic Workforce Planning, and Sales Planning
- Migration
- Security
- Daily Maintenance Window Time
- Managing Users, Groups, and Roles
- Usage Simulation REST APIs
- Reporting REST APIs
- Data Integration REST APIs
- Data Management REST APIs
- Account Reconciliation
- Financial Consolidation and Close
- Task Manager
- Supplemental Data Manager
- Enterprise Journals
- Tax Reporting
- Enterprise Profitability and Cost Management
- Profitability and Cost Management

EPM Platform

Table 6-1 EPM Platform

Rest Resource	Request	More Information
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs</pre>	POST	Execute a Report Bursting Definition
<pre>/HyperionPlanning/rest/epm/{api_version}/ applications/{application}/connections/ {connectionRef}</pre>	GET	Update a Connection
<pre>/HyperionPlanning/rest/epm/{api_version}/ applications/{application}/connections/ {connectionRef}</pre>	GET	View a Connection



Table 6-1 (Cont.) EPM Platform

Rest Resource	Request	More Information
/HyperionPlanning/rest/epm/{api_version}/ applications/{application}/connections	GET	View All Connections

Planning, FreeForm, Strategic Workforce Planning, and Sales Planning

Rest Resource	Request	More Information
/HyperionPlanning/rest/	GET	Getting API Versions for Planning
/HyperionPlanning/rest/{api_version}	GET	Get Information about a Specific REST API Version for Planning
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobdefinitions	GET	Get Job Definitions
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Execute a Job
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs/ {jobIdentifier}	GET	Retrieve Job Status
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs/ {jobIdentifier}/details	GET	Retrieve Job Status Details
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs/ {jobIdentifier}/childjobs/ {childJobIdentifier}/details	GET	Retrieve Child Job Status Details
/HyperionPlanning/rest/{api_version}/ applications/{application}/dimensions/ {dimname}/members	POST	Add Member
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/dimensions/ {dimname}/members/{member}</pre>	GET	Get Member
/HyperionPlanning/rest/{api_version}/ applications	GET	Get Applications
<pre>/HyperionPlanning/rest/{version}/ applications/{application}/planningunits? q={"scenario":"scenarioName","version":"ver sionName"}}&offset=10&limit=10</pre>	POST	List All Planning Units
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/planningunits? q={"scenario":{"scenario"},"version": {"version"}}&offset={offset}&limit={limit}</pre>	GET	Get Planning Unit History and Annotations
/HyperionPlanning/rest/{api_version}/ applications/{application}/users/{userId}/ photo	GET	Get a Planning Unit Owner Photo



Rest Resource	Request	More Information
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/planningunits/ {puIdentifier}/promotionpath</pre>	GET	Get Planning Unit Promotional Path
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/ planningunits{puhIdentifier}/ availableactions</pre>	POST	Get Available Planning Unit Actions
/HyperionPlanning/rest/{api_version}/ applications/{application}/pufilters	GET	Get Filters with All Possible Values
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/planningunits/ {puhIdentifier}/actions</pre>	POST	Change Planning Unit Status
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/userpreferences</pre>	GET	Get User Preferences
/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/importdataslice	POST	Import Data Slice
/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/exportdataslice	POST	Export Data Slice
/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/cleardataslice	POST	Clear Data Slice
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/ substitutionvariables</pre>	GET	Get All Substitution Variables Defined for the Application
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/ substitutionvariables/MyPeriod</pre>	GET	Get a Substitution Variable Defined for the Application
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/ substitutionvariables</pre>	POST	Create or Update All Substitution Variables Defined for the Application
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables</pre>	GET	Get Substitution Variables Defined at the Plan Type Level
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables? q={"derivedValues":true}</pre>	GET	Get Derived Substitution Variables at the Plan Type Level
/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables/CurrYear	GET	Get a Substitution Variable Defined at the Plan Type Level
<pre>HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables/MyPeriod? q={"derivedValues":true}</pre>	GET	Get a Derived Substitution Variable Defined at the Plan Type Level

Table 6-2(Cont.) Planning, FreeForm, Strategic Workforce Planning, and SalesPlanning



Rest Resource	Request	More Information
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables</pre>	POST	Create and Update Substitution Variables at the Plan Type Level
/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables/subvarname	DELETE	Delete a Substitution Variable at the Plan Type Level
/HyperionPlanning/rest/{api_version}/ applications/{application}/ substitutionvariables/subvarname	DELETE	Delete a Substitution Variable for the Application
/HyperionPlanning/rest/{api_version}/ applications/{application}/plantypes/ {plantype}/substitutionvariables:delete	POST	Delete Substitution Variables at the Plan Type Level
/HyperionPlanning/rest/{api_version}/ applications/{application}/	POST	Delete Substitution Variables for the Application

Table 6-2(Cont.) Planning, FreeForm, Strategic Workforce Planning, and SalesPlanning

Migration

Table 6-3 Migration

substitutionvariables:delete

Rest Resource	Request	More Information
Getting REST API Versions for Migration		
/interop/rest/	GET	Get REST API Versions for Migration
/interop/rest/{api_version}	GET	Get Information about a Specific Version of Migration Sample Code
Import and Export Files		
<pre>/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}/migration? q={type:"import"}</pre>	POST	LCM Import (v1)
/interop/rest/v2/snapshots/import	POST	LCM Import (v2)
<pre>/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}/ migrationq={type:"export"}</pre>	POST	LCM Export (v1)
/interop/rest/v2/snapshots/export	POST	LCM Export (v2)
Upload and Download Files		
/interop/rest/11.1.2.3.600/ applicationsnapshots/ {applicationSnapshotName}/contents	POST	Upload
/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}/contents	GET	Download
View and Delete Files		



Table 6-3	(Cont.) Migration	
	(Cont.) Migration	

Rest Resource	Request	More Information
/interop/rest/{api_version}/ applicationsnapshots	GET	List Files (v11.1.2.3.600)
/interop/rest/v2/files/list	GET	List Files (v2)
/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}	DELETE	Delete Files (v11.1.2.3.600)
/interop/rest/v2/files/delete	DELETE	Delete Files (v2)
/interop/rest/v3/files/delete	POST	Delete Files (v3)
Manage Services		
/interop/rest/{api_version}/services	GET	Get Information About All Services
/interop/rest/{api_version}/config/ services/idlesessiontimeout	GET	Get Idle Session Timeout
/interop/rest/{api_version}/config/ services/idlesessiontimeout	PUT	Set Idle Session Timeout
/interop/rest/{api_version}/services/ {service type}/resetservice	POST	Restart the Service Instance (v1)
/interop/rest/v2/config/services/reset	POST	Restart the Service Instance (v2)
<pre>/interop/rest/{api_version}/services/ {servicename}/recreate</pre>	POST	Run Recreate on a Service (11.1.2.3.600)
/interop/rest/v2/config/services/recreate	POST	Run Recreate on a Service (v2)
Manage Application Snapshots		
/interop/rest/{api_version}/ applicationsnapshots	GET	Get Information About All Application Snapshots
/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}	GET	Get Information About a Specific Application Snapshot
<pre>/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}/contents? q={"isLast":false,"isFirst": true,"chunkSize":14,"fileSize":55445}</pre>	POST	Upload Application Snapshot (v1)
/interop/rest/v2/files/upload	POST	Upload Application Snapshot (v2)
/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}/content	GET	Download Application Snapshot (v1)
/interop/rest/v2/files/download	POST	Download Application Snapshot (v2)
/interop/rest/v1/services/{servicename}/ copysnapshot	POST	Copy Application Snapshot (v1)
/interop/rest/v2/snapshots/copyfrominstance	POST	Copy Application Snapshot (v2)
/interop/rest/v1/renamesnapshot	PUT	Rename Application Snapshot (v1)



Rest Resource	Request	More Information
/interop/rest/v2/snapshots/rename	PUT	Rename Application Snapshot (v2)
Copy to and from the Object Store		
/interop/rest/v1/services/copytoobjectstore	POST	Copy to Object Store (v1)
/interop/rest/v2/objectstorage/copyto	POST	Copy to Object Store (v2)
/interop/rest/v2/objectstorage/copyfrom	POST	Copy from Object Store (v2)
/interop/rest/v1/services/copyfile	POST	Copy a File Between Instances (v1)
Working with Oracle Essbase		
/interop/rest/v2/essbase/export	POST	Export Essbase Data (v2)
/interop/rest/diag/v1/services/ essbaseblockanalysisreport	POST	Essbase Block Analysis Report
/interop/rest/{api_version}/config/ services/essbaseqrygovexectime	GET	Get Essbase Query Governor Execution Time
/interop/rest/{api_version}/config/ services/essbaseqrygovexectime	PUT	Set Essbase Query Governor Execution Time
Other		
/interop/rest/v1/services/copyfile	POST	Copy a File Between Instances (v1)
/interop/rest/v2/files/copyfrominstance	POST	Copy a File Between Instances (v2)
/interop/rest/v1/services/clone	POST	Clone an Environment
/interop/rest/v2/backups/list	GET	List Backups - Only for OCI (Gen 2) Environments
/interop/rest/v2/backups/restore	POST	Restore Backup - Only for OCI (Gen 2) Environments
/interop/rest/{api_version}/feedback	POST	Provide Feedback (v11.1.2.3.600)
/interop/rest/v2/services/feedback	POST	Provide Feedback (v2)
/interop/rest/< <i>api_version</i> >/services/ sendmail	POST	Send Email (v1)
/interop/rest/v2/mails/send	POST	Send Email (v2)
/interop/rest/v1/services/skipupdate	POST	Skip Updates (v1)
/interop/rest/v2/services/skipupdate	POST	Skip Updates (v2)

Table 6-3 (Cont.) Migration

Security

Table 6-4 Security

Rest Resource	Request	More Information
/interop/rest/{api_version}/config/ services/restricteddataaccess	GET	Get Restricted Data Access
/interop/rest/{api_version}/config/ services/restricteddataaccess	PUT	Set Restricted Data Access
/interop/rest/{api_version}/config/ services/virusscanonfileupload	GET	Get Virus Scan on File Upload

Rest Resource	Request	More Information
/interop/rest/{api_version}/config/ services/virusscanonfileupload	PUT	Set Virus Scan on File Upload
/interop/rest/{api_version}/services/ dataaccess?accessType={allow revoke}&disableEmergencyAccess={true false}	PUT	Manage Permission for Manual Access to Database (v1)
/interop/rest/v2/services/ setmanualdataaccess	PUT	Manage Permission for Manual Access to Database (v2)
/interop/rest/{api_version}/services/ encryptionkey	PUT	Set Encryption Key (v1)
/interop/rest/v2/services/setencryptionkey	PUT	Set Encryption Key (v2)
/interop/rest/epmociservice/v2/ipallowlist	GET	View the IP Allowlist - Only for OCI (Gen 2) Environments
/interop/rest/epmociservice/v2/ipallowlist	POST	Update the IP Allowlist - Only for OCI (Gen 2) Environments

Table 6-4 (Cont.) Security

Daily Maintenance Window Time

Table 6-5 Daily Maintenance Window Time

Rest Resource	Request	More Information
/interop/rest/{api_version}/services/ dailymaintenance	GET	Get the Build Version and Daily Maintenance Time (v1)
/interop/rest/v2/maintenance/ getdailymaintenancestarttime	GET	Get the Build Version and Daily Maintenance Window Time (v2)
/interop/rest/{api_version}/services/ dailymaintenance?StartTime={N}	PUT	Setting the Daily Maintenance Time (v1)
/interop/rest/v2/maintenance/ setdailymaintenancestarttime	PUT	Setting the Daily Maintenance Time (v2)
/interop/rest/{api_version}/services/ maintenancewindow	POST	Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v1)
/interop/rest/v2/maintenance/ rundailymaintenance	POST	Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v2)

Managing Users, Groups, and Roles

Table 6-6 Managing Users, Groups, and Roles

Rest Resource	Request	More Information
/interop/rest/security/ <api_version>/users</api_version>	POST	Add Users to an Identity Domain (v1)
/interop/rest/security/v2/users/add	POST	Add Users to an Identity Domain (v2)
<pre>/interop/rest/security/<api_version>/users? filename=<filename></filename></api_version></pre>	DELETE	Remove Users from an Identity Domain (v1)



Rest Resource	Request	More Information
/interop/rest/security/v2/users/remove	POST	Remove Users from an Identity Domain (v2)
/interop/rest/security/ <api_version>/users</api_version>	PUT	Assign Users to a Predefined Role or Application Role (v1)
/interop/rest/security/v2/role/assign/user	PUT	Assign Users to a Predefined Role or Application Role (v2)
/interop/rest/security/< <i>api_version</i> >/users	PUT	Remove Users' Role Assignment (v1)
/interop/rest/security/v2/role/unassign/ user	PUT	Remove Users' Role Assignment (v2)
/interop/rest/security/ <api version="">/groups</api>	PUT	Add Users to a Group (v1)
/interop/rest/security/v2/groups/ adduserstogroup	PUT	Add Users to a Group (v2)
/interop/rest/security/ <api_version>/groups</api_version>	PUT	Remove Users from a Group (v1)
/interop/rest/security/v2/groups/ removeusersfromgroup	PUT	Remove Users from a Group (v2)
/interop/rest/security/< <i>api_verion</i> >/users	PUT	Update Users
/interop/rest/security/ <api_version>/groups</api_version>	PUT	Add a User to a Batch of Groups
/interop/rest/security/ <api_version>/groups</api_version>	PUT	Remove a User from a Batch of Groups
/interop/rest/security/ <api_version>/groups</api_version>	POST	Add Groups (v1)
/interop/rest/security/v2/groups/add	POST	Add Groups (v2)
/interop/rest/security/ <api_version>/groups</api_version>	DELETE	Remove Groups (v1)
/interop/rest/security/v2/groups/remove	POST	Remove Groups (v2)
/interop/rest/security/ <api_version>/ usergroupreport</api_version>	POST	User Group Report (v1)
/interop/rest/security/v2/report/ usergroupreport	GET	User Group Report (v2)
<pre>/interop/rest/{api_version}/reports? q={type:provisionreport,fileName:provreport .csv,format:simplified,usertype,serviceuser s}</pre>	POST	User Access Report (v1)
/interop/rest/v2/reports/useraccess	POST	User Access Report (v2)
<pre>/interop/rest/{api_version}/reports? q={type:userauditreport,fileName:useraudit report.csv,since:2017-12-10,until:2018-06-1 0}</pre>	POST	User Audit Report (v1)
/interop/rest/v2/reports/useraudit	POST	User Audit Report (v2)
/interop/restp{api_version}/reports/ groupaudit	POST	Group Assignment Audit Report
/interop/rest/security/{api_version}/ roleassignmentreport	POST	Role Assignment Report (v1)
/interop/rest/security/v2/report/ roleassignmentreport/user? userlogin= <userlogin>&rolename=<rolename></rolename></userlogin>	GET	Role Assignment Report for Users (v2)

Table 6-6 (Cont.) Managing Users, Groups, and Roles



Rest Resource	Request	More Information
<pre>/interop/rest/security/v2/report/ roleassignmentreport/group? groupname=<groupname>&rolename=<rolename></rolename></groupname></pre>	GET	Role Assignment Report for Groups (v2)
/interop/rest/security/v2/role/ getavailableroles	GET	Get Available Roles
/interop/rest/security/{api_version}/ roleassignmentauditreport/	POST	Role Assignment Audit Report for OCI (Gen 2) Environments
/interop/rest/security/{api_version}/ invalidloginreport/	POST	Invalid Login Report for OCI (Gen 2) Environments
/interop/rest/{api_version}/reports/ groupaudit	POST	Group Assignment Audit Report
/armARCS/rest/{version}/jobs	POST	Adding Users to a Team for Account Reconciliation
/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs	POST	Adding Users to a Team for Financial Consolidation and Close and Tax Reporting
/armARCS/rest/{version}/jobs	POST	Removing Users from a Team for Account Reconciliation
/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs	POST	Removing Users from a Team for Financial Consolidation and Close and Tax Reporting

Table 6-6 (Cont.) Managing Users, Groups, and Roles

Usage Simulation

Table 6-7 Usage Simulation

Rest Resource	Request	More Information
/interop/rest/v1/concurrentusage/run	POST	Simulate Concurrent Usage

Reporting

Table 6-8 Reporting

Rest Resource	Request	More Information
/arm/rest/fcmapi/{api_version}/report	POST	Generate Report for Account Reconciliation
/HyperionPlanning/rest/fcmapi/ {api_version}/report	POST	Generate Report for Financial Consolidation and Close and Tax Reporting
<pre>/arm/rest/fcmapi/{api_version}/rc/export/ users</pre>	POST	Generate User Details Report for Account Reconciliation
/HyperionPlanning/rest/fcmapi/ {api_version}/fcm/export/users	POST	Generate User Details Report for Financial Consolidation and Close and Tax Reporting
/arm/rest/fcmapi/{api_version}/job/ {module}/{jobIdentifier}	GET	Retrieve Job Status for a Report
/aif/rest/{api_version}/jobs	POST	Execute Reports for Data Management



Chapter 6

Data Management/Data Integration

Table 6-9	Data Management
	Dulu munugement

Rest Resource	Request	More Information
/aif/rest/	GET	Get API Versions for Data Management APIs
/aif/rest/{api_version}	GET	Get Information about a Specific API Version for Data Management APIs
/aif/rest/{api_version}	GET	Retrieve Job Status (Data Management), Retrieve Job Status (Data Integration)
/aif/rest/V1/snapshots	POST	Import Data Integration
/aif/rest/V1/snapshots	POST	Export Data Integration
/aif/rest/{api_version}/jobs	POST	Running Data Rules in Data Management
/aif/rest/{api_version}/jobs	POST	Running Integrations
/aif/rest/{api_version}/jobs	POST	Running a Pipeline
/aif/rest/{api_version}/jobs	POST	Running Batch Rules
/aif/rest/{api_version}/jobs	POST	Import Data Mapping
/aif/rest/{api_version}/jobs	POST	Export Data Mapping
/aif/rest/V1/POV	POST	Lock and Unlock POV
/aif/rest/{api_version}/jobs	POST	Execute Reports for Data Management

Account Reconciliation

	Table 6-10	Account Reconciliation
--	------------	------------------------

Rest Resource	Request	More Information
/armARCS/rest/	GET	Get API Versions for Account Reconciliation REST APIs
/armARCS/rest/< <i>api_version</i> >	GET	Get Information about a Specific API Version for Account Reconciliation REST APIs
GET /arm/rest/fcmapi/{api_version}/job/ {module}/{jobIdentifier}	GET	Retrieve Job Status for a Report
/arm/rest/fcmapi/{api_version}/report	POST	Generate Report for Account Reconciliation
<pre>/arm/rest/fcmapi/{api_version}/rc/export/ users</pre>	POST	Generate User Details Report for Account Reconciliation
/armARCS/rest/{version}/jobs	POST	Adding Users to a Team for Account Reconciliation
/armARCS/rest/{version}/jobs	POST	Removing Users from a Team for Account Reconciliation
<pre>/arm/rest/fcmapi/{api_version}/rc/export/ applicationproperties</pre>	POST	Export Application Properties
<pre>/arm/rest/fcmapi/{api_version}/rc/import/ applicationproperties</pre>	POST	Import Application Properties



Table 6-10 (Cont.) Account Reconciliation

Rest Resource	Request	More Information
/arm/rest/fcmapi/{api version}/rc/export/	POST	Export Background Image
backgroundImage	FUSI	Export Background Image
/arm/rest/fcmapi/{api_version}/rc/import/ backgroundImage	POST	Import Background Image
/arm/rest/fcmapi/{api_version}/rc/export/ logo	POST	Export Logo Image
/arm/rest/fcmapi/{api_version}/rc/import/ logo	POST	Import Logo Image
/arm/rest/fcmapi/{api_version}/{module}/ connections	POST	Create a Connection
<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections</pre>	GET	View All Connections
<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections/{id}</pre>	PUT	Update a Connection
<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections/{id}</pre>	DELETE	Delete a Connection
/armARCS/rest/{api version}/appaccess	POST	Set Application Access Level
/armARCS/rest/{api_version}/appaccess	GET	Retrieve Application Access Level
/armARCS/rest/{api_version}/jobs	POST	Execute a Job in Account Reconciliation
<pre>/armARCS/rest/periods?status={status}</pre>	GET	Retrieve Periods with a Specific Status
/armARCS/rest/{api_version}/jobs	POST	Create Reconciliation (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Delete Profile
/armARCS/rest/{api_version}/jobs	POST	Change Period Status (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Pre-Mapped Transactions (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Profiles (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Rates (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Balances (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Pre-Mapped Balances (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Reconciliation Attributes (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Attribute Values
/armARCS/rest/{api_version}/jobs/{job_id}	GET	Retrieve Job Status (Reconciliation Compliance)
<pre>/armARCS/rest/{api_version}/period/ {period}/reconciliation/{accountId}/ comments</pre>	GET	View Reconciliation Comments



Rest Resource	Request	More Information
/armARCS/rest/{api_version}/jobs	POST	Monitor Reconciliations (Reconciliation Compliance)
/armARCS/rest/{api_version}/jobs	POST	Import Pre-Mapped Transactions (Transaction Matching)
/armARCS/rest/{api_version}/jobs	POST	Run Auto Match (Transaction Matching)
/arm/rest/{api_version}/jobs	POST	Purge Transactions (Transaction Matching)
/arm/rest/{api_version}/jobs/{job_id}	GET	Retrieve Job Status (Transaction Matching)
/arm/rest/{api_version}/jobs	POST	Archive Matched Transactions (Transaction Matching)
/arm/rest/{api_version}/jobs	POST	Purge Archived Transactions (Transaction Matching)
/arm/rest/{api_version}/jobs	POST	Unmatch Matched Transactions (Transaction Matching)
<pre>/arm/rest/{api_version}/dataSources/ {dataSource}/transactions/{transaction}</pre>	POST	Update Unmatched Transactions (Transaction Matching)

Table 6-10 (Cont.) Account Reconciliation

Financial Consolidation and Close

Rest Resource	Request	More Information
/HyperionPlanning/rest/	GET	Getting API Versions for Financial Consolidation and Close APIs
<pre>/fccs/rest/{api_version}</pre>	GET	Get Information about a Specific API Version for Financial Consolidation and Close APIs
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Export Consolidation Journals
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Import Consolidation Journals
/HyperionPlanning/rest/{api_version}/ applications/{application}/journals/ {journal}/actions	POST	Perform Journal Actions for Financial Consolidation and Close
/HyperionPlanning/rest/{api_version}/ applications/{application}/journalPeriods/ {period}/actions	POST	Perform Journal Period Updates for Financial Consolidation and Close
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/journals? q={"scenario","year","period","status"}&off set=0&limit=5</pre>	GET	Retrieve Journals for Financial Consolidation and Close



Rest Resource	Request	More Information
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/journals/ {journal label}? q={"scenario","year","period"}&lineItems=tr ue</pre>	GET	Retrieve Journal Details for Financial Consolidation and Close
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Copy Data
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Clear Data
/HyperionPlanning/rest/{api_version}/ applications/{application}/ validatemetadata?logFileName= <filename of<br="">exported results</filename>	POST	Validate Metadata
<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs</pre>	POST	Generate an Intercompany Matching Report
<pre>/interop/rest/{api_version}/services/ dataaccess?accessType={allow revoke}&disableEmergencyAccess={true false}</pre>	PUT	Manage Permission for Manual Access to Database (v1)
/interop/rest/v2/services/ setmanualdataaccess	PUT	Manage Permission for Manual Access to Database (v2)
/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs	POST	Adding Users to a Team for Financial Consolidation and Close and Tax Reporting
/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs	POST	Removing Users from a Team for Financial Consolidation and Close and Tax Reporting
/HyperionPlanning/rest/fcmapi/ {api_version}/report	POST	Generate Report for Financial Consolidation and Close and Tax Reporting
/HyperionPlanning/rest/fcmapi/ {api_version}/fcm/export/users	POST	Generate User Details Report for Financial Consolidation and Close and Tax Reporting

Table 6-11 (Cont.) Financial Consolidation and Close

Task Manager

Table 6-12 Task Manager

Rest Resource	Request	More Information
/HyperionPlanning/rest/cmapi/{api_version}/ updateTasksForEventMonitoring	POST	Update Task Status for Event Monitoring
/HyperionPlanning/rest/fcmapi/ {api_version}/{module}/connections	POST	Create a Connection
/HyperionPlanning/rest/fcmapi/ {api_version}/{module}/connections/{id}	DELETE	Delete a Connection
/HyperionPlanning/rest/fcmapi/ {api_version}/{module}/connections/{id}	PUT	Update a Connection
/HyperionPlanning/rest/fcmapi/ {api_version}/{module}/connections	GET	View All Connections

Table 6-12 (Cont.) Task Manager

Rest Resource	Request	More Information
<pre>/HyperionPlanning/rest/cmapi/{api_version}/ jobs</pre>	POST	Deploy Task Manager Templates

Supplemental Data Manager

Table 6-13 Supplemental Data Manager

Rest Resource	Request	More Information
/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs	POST	Deploy Form Templates
/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs	POST	Import Supplemental Collection Data for Financial Consolidation and Close

Enterprise Journals

Table 6-14 Enterprise Journals

Rest Resource	Request	More Information
/HyperionPlanning/rest/ej/{api_version}/ jobs	POST	Execute an Enterprise Journals Job
/HyperionPlanning/rest/ej/{api_version}/ jobs	POST	Monitor Enterprise Journals for Financial Consolidation and Close
/HyperionPlanning/rest/ej/v1/ejjournals	GET	Retrieve Enterprise Journals for Financial Consolidation and Close
/HyperionPlanning/rest/ej/v1/ejjournals/ {instanceId}	GET	Retrieve Enterprise Journal Content for Financial Consolidation and Close
/HyperionPlanning/rest/ej/v1/ ejjournalcontent?q={"year","period"}	GET	Retrieve Enterprise Journal Content by Year and Period for Financial Consolidation and Close
/HyperionPlanning/rest/ej/v1/ejjournals/ {instanceId}/poststatus	POST	Update Enterprise Journal Posting Status for Financial Consolidation and Close
/HyperionPlanning/rest/ej/{api_version}/ ejjournals/{identifier}/validationstatus	POST	Update Validation Status of Enterprise Journals for Financial Consolidation and Close

Tax Reporting

Table 6-15 Tax Reporting

Rest Resource	Request	More Information
/HyperionPlanning/rest/	GET	Getting API Versions for Tax Reporting APIs



Rest Resource	Request	More Information
/HyperionPlanning/rest/{api_version}	GET	Get Information about a Specific API Version for Tax Reporting
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Copy Data
/HyperionPlanning/rest/{api_version}/ applications/{application}/jobs	POST	Clear Data

Table 6-15(Cont.) Tax Reporting

Enterprise Profitability and Cost Management

Table 6-16 Enterprise Profitability and Cost Management

Rest Resource	Request	More Information
/epm/rest	GET	Get API Versions for Profitability and Cost Management REST APIs
/HyperionPlanning/rest/v3/applications/ {AppName}/jobs/	POST	Calculate Model
/HyperionPlanning/rest/v3/applications/ {AppName}/jobs/	POST	Clear Data By Point of View
/HyperionPlanning/rest/v3/applications/ {AppName}/jobs/	POST	Copy Data by Point of View
/HyperionPlanning/rest/v3/applications/ {AppName}/jobs/	POST	Delete Point of View
/HyperionPlanning/rest/v3/applications/ {AppName}/jobs/	POST	Generate Model Documentation Report
<pre>/HyperionPlanning/rest/v3/applications/ {AppName}/jobs/</pre>	POST	Validate Model

Profitability and Cost Management

Table 6-17 Profitability and Cost Management

Rest Resource	Request	More Information
<pre>/epm/rest/{api_version}/applications/ {application}/jobs/applyDataGrants</pre>	POST	Apply Data Grants
<pre>/epm/rest/{api_version}/applications/ {application}/povs/{srcPOVMemberGroup}/ jobs/copyPOVJob/{destPOVMemberGroup}</pre>	POST	Copy ML POV Data
<pre>/epm/rest/{api_version}/fileApplications/ {application}</pre>	POST	Create File-Based Application
/epm/rest/{api_version}/applications/ {application}/jobs/ledgerDeployCubeJob	POST	Deploy ML Cube
<pre>/epm/rest/{api_version}/fileApplications/ {application}/enableApplication</pre>	POST	Enable File-Based Application



Rest Resource	Request	More Information
<pre>/epm/rest/{api_version}/applications/ {application}/jobs/essbaseDataLoadJob</pre>	POST	Essbase Data Load for Profitability and Cost Management
<pre>/epm/rest/{api_version}/applications/ {application}/jobs/exportQueryResultsJob</pre>	POST	Export Query Results
<pre>/epm/rest/{api_version}/applications/ {application}/jobs/templateExportJob? fileName={fileName}</pre>	POST	Export Template for Profitability and Cost Management
<pre>epm/rest/{api_version}/applications/ {application}/povs/{POV}/ programDocumentationReport? queryParameter={"fileType":"PDF","useAlias" :"true"}</pre>	GET	Generate Program Documentation Report
<pre>/epm/rest/{api_version}/applications/ <applicationname>/povs/<povname>/jobs/ programDocReportJob</povname></applicationname></pre>	POST	Generate Program Documentation Report - Run as a Job
<pre>/epm/rest/{api_version}/applications/ {application}/templateImportJob</pre>	POST	Import Template for Profitability and Cost Management
<pre>/epm/rest/{api_version}/applications/ {application}/jobs/mergeSlices</pre>	POST	Merge Slices for Profitability and Cost Management
<pre>/epm/rest/v1/applications/{AppName}/jobs/ optimizeASOCube</pre>	POST	Optimize ASO Cube
<pre>/epm/rest/{api_version}/applications/jobs/ ChecktaskStatusJob/{processName}</pre>	GET	Retrieve Task Status for Profitability and Cost Management
<pre>/epm/rest/{api_version}/applications/ {application}/povs/{povGroupMember}/jobs/ runLedgerCalculationJob</pre>	POST	Run ML Calculations
<pre>/epm/rest/{api_version}/applications/ {application}/povs/{povGroupMember}/jobs/ clearPOVJob</pre>	POST	Run ML Clear POV
<pre>/epm/rest/{api_version}/applications/ {application}/povs/{povGroupMember}/ ruleBalance? queryParameter={"modelViewName":"modelViewN ame"</pre>	POST	Run ML Rule Balancing
<pre>/epm/rest/{api_version}/fileApplications/ {application}/jobs/updateDimension</pre>	POST	Update Dimensions As a Job

Table 6-17 (Cont.) Profitability and Cost Management

7 REST Resources and Methods

This section describes the REST APIs for Oracle Enterprise Performance Management Cloud.

Completing administrative tasks using REST APIs as an alternative to using the user interface requires considerable technical and functional expertise. Only technically competent EPM Cloud Administrators should use this guide to perform EPM Cloud Administrator administrative tasks. For prerequisites to using these REST APIs, see Prerequisites.

The predefined and application roles assigned to the user of the REST API determine which APIs can be executed.

Supported REST Methods

You can use the Oracle Enterprise Performance Management Cloud REST APIs to create and manage resources for selected functionality. These APIs provide an alternative to using the selected components in the web-based user interface.

You can use one of a variety of methods to access the REST APIs. For example, you can access the REST API through client applications such as:

- Web browsers
- cURL

You can also use the REST APIs in REST client applications that are developed in languages such as:

- JavaScript
- Ruby
- Perl
- Java
- Groovy

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

REST describes any simple interface that transmits data over a standardized interface (such as HTTP) without an additional messaging layer, such as SOAP. REST provides a set of design rules for creating stateless services that are viewed as resources, or sources of specific information, and can be identified by their unique URIs. RESTful web services are services that are built according to REST principles and, as such, are designed to work well on the web. Typically, RESTful web services are built on the HTTP protocol and implement operations that map to the common HTTP methods, such as GET, POST, PUT, and DELETE to retrieve, create, update, and delete resources, respectively.



REST API Methods

You can create, view, update, or delete Oracle Enterprise Performance Management Cloud resources using standard HTTP method requests, as summarized in the following table.

Table 7-1 REST API Methods

Method	Description
GET	Retrieve information about the REST API resource
POST	Create a REST API resource
PUT	Update a REST API resource
DELETE	Delete a REST API resource or related component

Error Handling

All REST APIs return JSON output appropriate for the API invoked. HTTP Status codes other than 200 are used as appropriate to indicate various failures, along with JSON for detailed error messages.

Versioning

The Oracle Enterprise Performance Management Cloud REST API web services are versioned at the API level and expect the version to be included in the URL as shown here. An error will occur if the API version is missing or the provided version is not supported by the API.

For each service's API, you can get version and details for a specific REST API version. For details, see the service's API topics or Current REST API Version.

Important: The version number is case-sensitive. For example, if the version number is listed as v1 with a lowercase v, you cannot enter the version number with a capital V as in this incorrect example, V1, which would result in an error. Instead, you must enter the version number with a lowercase v as in this correct example: v1.

Examples:

```
https://https://<BASE-URL>/HyperionPlanning/rest/{api_version}/applications/
{applicationName}/jobs
```

https://https://<BASE-URL>/interop/rest/{api version}/applicationsnapshots

where $\{api_version\}$ is the current REST API version for the product, for example, v3 for Planning.

Current REST API Version

Use the *Getting API Versions* topic for the Oracle Enterprise Performance Management Cloud business process to get the API version number and details for a specific REST API.

Planning: See Getting API Versions for Planning



- Migration: See Getting API Versions for Migration APIs
- Data Management: See Getting API Versions for Data Integration APIs
- Account Reconciliation: See Getting API Versions for Account Reconciliation REST APIs
- Financial Consolidation and Close: See Getting API Versions for Financial Consolidation and Close APIs
- Profitability and Cost Management: See Get API Versions for Profitability and Cost Management REST APIs
- Profitability and Cost Management: See Getting API Versions for Enterprise Profitability and Cost Management

Status Codes

When you call any of the Oracle Enterprise Performance Management Cloud REST APIs, one of the following standard HTTP status codes is returned in the response header.

HTTP Status Codes	Description
200 OK	The request was successfully completed. A 200 status is returned for a successful GET or POST method.
201 Created	The request has been fulfilled and resulted in a new resource being created. The response includes a Location header containing the canonical URI for the newly created resource.
	A 201 status is returned from a synchronous resource creation or an asynchronous resource creation that completed before the response was returned.
202 Accepted	The request has been accepted for processing, but the processing has not been completed. The request may or may not eventually be acted upon, as it may be disallowed at the time processing actually takes place.
	When specifying an asynchronous (_detached=true_resource creation, for example, when deploying an application, or update, for example, when redeploying an application, a 202 is returned if the underlying operation does not complete in a reasonable amount of time.
	The response contains a Location header of a job resource that the client should poll to determine when the job has finished. It also returns an entity that contains the current state of the job.
400 Bad Request	The request could not be processed because it contains missing or invalid information, such as a validation error on an input field, a missing required value, and so on.
401 Unauthorized	The request is not authorized. The authentication credentials included with this request are missing or invalid.
403 Forbidden	The user cannot be authenticated. The user does not have authorization to perform this request.
404 Not Found	The request includes a resource URI that does not exist
405 Method Not Allowed	The HTTP verb specified in the request (DELETE, GET, POST, PUT) is not supported for this request URI.
406 Not Acceptable	The resource identified by this request is not capable of generating a representation corresponding to one of the media types in the Accept header of the request.
415 Not Acceptable	The client's ContentType header is not correct.

Table 7-2 Status Codes



Table 7-2	(Cont.)	Status	Codes
-----------	---------	--------	-------

HTTP Status Codes	Description
500 Internal Server Error	The server encountered an unexpected condition that prevented it from fulfilling the request.
503 Service Unavailable	The server is unable to handle the request due to temporary overloading or maintenance of the server.

8 Planning REST APIs

Use the Planning REST APIs to get the REST API version, manage and execute jobs, and work with members, applications, planning units, user preferences, data slices, and substitution variables.

Note:

You can also use these APIs with FreeForm.

These REST APIs are available for Planning. They are also available for FreeForm, as shown in EPM Cloud REST API Compatibility.

- URL Structure for Planning
- Resources and Available Actions
- Getting API Versions for Planning
- Manage Jobs
- Working with Members
- Get Applications
- Manage Planning Units
- Get User Preferences
- Working with Data Slices
- Getting and Setting Substitution Variables
- Deleting Substitution Variables
- Working with Connections

Before you work with the REST APIs, be sure you are familiar with the Implementation Best Practices for EPM Cloud REST APIs.

Note: We have removed the following fields from the exception response in REST APIs for Planning and Planning Modules:

- message
- localizedMessage

URL Structure for Planning

This topic shows the general URL structure for Planning REST APIs.

Use the following URL structure to access the Planning REST resources:

https://<BASE-URL>/HyperionPlanning/rest/{api version}/{path}



Where:

• <BASE-URL>: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- api_version: API version you are developing with. The current REST API version for Planning is v3.
- *path*: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ <code>internal/"</code> in the URL.

Resources and Available Actions

In the response, the Links section of the response parameters lists links to other resources and available actions for the current resource.

Name	Description
links	Describes links to other resources and actions applicable on the current resource
rel	Relationship type; the relationship between the current state and the state to which the client will transition
href	The target resource's URI. If the value of rel is "self", this URI is how the resource is accessed currently
action	The HTTP method. For POST, data indicates the parameters and values with which it was invoked

Table 8-1 Resources and Available Actions

Getting API Versions for Planning

You can get information on REST API versions using a set of REST resources, as summarized here.

Important: The version number is case-sensitive. For example, if the version number is listed as v3 with a lowercase v, you cannot enter the version number with a capital V as in this incorrect example, V3, which would result in an error. Instead, you must enter the version number with a lowercase v as in this correct example: v3.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.




Table 8-2 Getting REST API Versions

Task	Requ est	REST Resource
Get REST API Versions for Planning	GET	/HyperionPlanning/rest/
Get Information about a Specific REST API Version for Planning	GET	/HyperionPlanning/rest/{api_version}

Get REST API Versions for Planning

You can use REST APIs to get information about which versions are available and supported. Multiple versions might be supported simultaneously.



Service Administrator, Power User, User, Viewer

REST Resource

GET /HyperionPlanning/rest/

Request

Supported Media Types: application/json

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-3 Parameters

Name	Description
items	Version of the API you are developing with
version	The version, such as v3
lifecycle	Possible values: active, deprecated
isLatest	Whether this resource is the latest, true or false

Example of Response Body

The following shows an example of the response body in JSON format.

"items": [{

{



```
"version": "v1",
        "lifecycle": "deprecated",
        "isLatest": false,
        "links": [{
            "rel": "canonical",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v1"
        }, {
            "rel": "successor-version",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v2"
        }]
    }, {
        "version": "v2",
        "lifecycle": "deprecated",
        "isLatest": false,
        "links": [{
            "rel": "canonical",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v2"
        }, {
            "rel": "predecessor-version",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v1"
        }, {
            "rel": "successor-version",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3"
        }1
    }, {
        "version": "v3",
        "lifecycle": "active",
        "isLatest": true,
        "links": [{
            "rel": "canonical",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3"
        }, {
            "rel": "predecessor-version",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v2"
        }]
    }],
    "links": [{
        "rel": "self",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/"
    }, {
        "rel": "canonical",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/"
    }, {
        "rel": "current",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3"
```

}]

}

Get Information about a Specific REST API Version for Planning

You can use REST APIs to get information about a specific REST API version for Planning.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

GET /HyperionPlanning/rest/{api_version}

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-4 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V3	Path	Yes	None

Response Body

Supported Media Types: application/json

Parameters

The following table summarizes the response parameters.

Table 8-5 Parameters

Attribute	Description	
version	The version, such as v3	
lifecycle	Lifecycle of the resource, active or deprecated	
isLatest	Whether this resource is the latest, true or false	

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "version": "v3",
    "lifecycle": "active",
    "isLatest": true,
    "links": [{
        "rel": "canonical",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3"
```



```
}, {
    "rel": "predecessor-version",
    "href": "https://<BASE-URL>/HyperionPlanning/rest/v2"
}]
```

Manage Jobs

}

You can manage jobs using a set of REST resources, as summarized here.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. For additional details, see Job Types.

Jobs:

- Get Job Definitions
- Execute a Job
- Retrieve Job Status
- Retrieve Job Status Details
- Rules
- Ruleset
- Plan Type Map
- Import Data
- Export Data
- Export Metadata
- Import Metadata
- Cube Refresh
- Clear Cube
- Administration Mode
- Compact Cube
- Restructure Cube
- Merge Data Slices
- Optimize Aggregation
- Import Security
- Export Security
- Export Audit
- Export Job Console
- Sort Members
- Import Exchange Rates
- Auto Predict



- Import Cell-Level Security
- Export Cell-Level Security
- Import Valid Intersections
- Export Valid Intersections
- Execute a Report Bursting Definition
- Export Library Documents
- Import Library Documents

Get Job Definitions

Use this resource to get job definitions for the types of jobs that can be scheduled to run.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. For additional details, see Job Types.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/
jobdefinitions

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-6 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
jobIdentifier	The ID of the job, such as 224	Path	Yes	None
q	Query string	Query	No	None



Table 8-6 (Cont.) Parameters

Name	Description	Туре	Required	Default
jobType	Optionally, retrieve job definitions for a particular job	2		
	type, such as RULES.			
	These jobs are supported:			
	Rules			
	Ruleset			
	Plan Type Map			
	Import Data			
	Export Data			
	Export Metadata			
	Import Metadata			
	Cube Refresh			
	Clear Cube			
	Administration Mode			
	Compact Cube			
	Restructure Cube			
	Merge Data Slices			
	Optimize Aggregation			
	Import Security			
	Export Security			
	Export Audit			
	Export Job Console			
	Sort Members			
	Import Exchange Rates			
	Auto Predict			
	Import Cell-Level Security			
	Export Cell-Level Security			
	Import Valid Intersections			
	Export Valid Intersections			
	Execute a Report Bursting Definition			
	Export Library Documents			
	Import Library Documents			

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobdefinitions

Specifying an optional jobType, RULES:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobdefinitions?
q={"jobType":"RULES"}

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.



Name	Description
items	Collection of job definitions
јоbТуре	Job type, such as RULESET. These jobs are supported:
	Rules
	Ruleset
	Plan Type Map
	Import Data
	Export Data
	Export Metadata
	Import Metadata
	Cube Refresh
	Clear Cube
	Administration Mode
	Compact Cube
	Restructure Cube
	Merge Data Slices
	Optimize Aggregation
	Import Security
	Export Security
	Export Audit
	Export Job Console
	Sort Members
	Import Exchange Rates
	Auto Predict
	Import Cell-Level Security
	Export Cell-Level Security
	Import Valid Intersections
	Export Valid Intersections
	Execute a Report Bursting Definition
	Export Library Documents
jobName	The exact name of the job, such as Financial Statements - Forecast.
type	Application type

Table 8-7 Parameters

Example of Response Body

The following shows an example of the response body specifying jobType with a value of RULESET.

```
{
   "items": [{
      "jobType": "RULESET",
      "jobName": "Financial Statements - Forecast",
      "links": null
   }, {
      "jobType": "RULESET",
      "jobName": "Financial Statements - Plan",
      "links": null
   }, {
      "jobType": "RULESET",
   }
}
```

```
"jobName": "Revenue Forecast",
        "links": null
    }, {
        "jobType": "RULESET",
        "jobName": "Revenue Plan",
        "links": null
    }, {
        "jobType": "RULESET",
        "jobName": "RS 60 RTP vars test2",
        "links": null
    }],
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
vision/jobdefinitions?q=%7BjobType:RULESET%7D",
        "action": "GET"
    }],
}
```

Execute a Job

Use this resource to execute several jobs simultaneously by providing the job name and type. The job is expected to be defined in Planning with all the required parameters saved with the job definition. For some job types, the parameters can be either provided or overwritten at runtime.

This topic describes general information for executing a job. Details for each job type are described in separate topics for individual jobs.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. For additional details, see Job Types.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs.

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/jobs

Request

Supported Media Types: application/json

Parameters

This table summarizes the request parameters that are generic to all jobs. The following tables describe parameters specific to individual jobs.

Note that all parameter names and values are case sensitive.

Table 8-8 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None



Table 8-8 (Cont.) Parameters

Name	Description	Туре	Required	Default
application	Name of the application for which the job will be executed	Path	Yes	None

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs

```
{"jobType":"jobType","jobName":"jobName","parameters":
{"parameter1":"value","parameter2":"value2"}}
```

Response

Supported Media Types: application/json

Parameters

This table summarizes the response parameters that are generic to all jobs. The following topics describe parameters specific to individual jobs:

- Rules
- Ruleset
- Plan Type Map
- Import Data
- Export Data
- Export Metadata
- Import Metadata
- Cube Refresh
- Clear Cube
- Administration Mode
- Compact Cube
- Restructure Cube
- Merge Data Slices
- Optimize Aggregation
- Import Security
- Export Security
- Export Audit
- Export Job Console
- Sort Members
- Import Exchange Rates
- Auto Predict
- Import Cell-Level Security



- Export Cell-Level Security
- Import Valid Intersections
- Export Valid Intersections
- Execute a Report Bursting Definition
- Export Library Documents
- Import Library Documents

Table 8-9 Parameters

Name	Description
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 = cancel pending; 3 = cancelled; 4 = invalid parameter; Integer.MAX_VALUE = unknown
details	Details about the job status, such as "Metadata import was successful" for metadata import
jobID	The ID of the job, such as 145
jobName	The name of the job, such as Refresh Database.
descriptiveStatus	The status of the job, such as Completed or Error

Rules

Use this REST API to launch a business rule.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator, Power User (if Rule Launch access is granted)

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/
jobs

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For parameters that are common to all jobs, see Execute a Job.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Table 8-10 Rules

Name	Description	Required	Default
јорТуре	Rules or RULES (both parameters are supported)	Yes	None



Table 8-10 (Cont.) Rules

Name	Description	Required	Default
jobName	The name of a business rule exactly as it is defined in the Planning application.	Yes	None
	Example : RollupUSSales		
parameters	Optionally you can specify the runtime prompts and their values required to execute the business rule.	No, unless default values for the run time prompts are not provided in	Default values for the runtime prompts as provided in Calculation
	Note: The rule is executed against the plan type to which it was deployed.	Calculation Manager.	Manager will be used.
	The value must use JSON syntax.		

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs

```
{
   "jobType":"Rules",
   "jobName":"Operating Expense Adj Plan",
   "parameters":
        {
            "MyScenario1":"Current",
            "MyVersion1":"BU Version_1",
            "ToEntity":"CA",
            "Rule_Level_Var":"AZ",
            "planType":"Plan1"
        }
}
```

Ruleset

Launches a business ruleset.

Supports rulesets with no runtime prompts or runtime prompts with default values. You can add parameters to rulesets for greater flexibility. Use the sample rulesets and POST requests below to help you quickly understand different scenarios when running this job. For details about rulesets, see Designing Business Rulesets.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. For information about creating rulesets, see *Designing with Calculation Manager for Oracle Enterprise Performance Management Cloud*.

Required Roles

Service Administrator, Power User (if Rule Launch access is granted)

Request

Supported Media Types: application/json

Parameters



The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Require d	Default
јорЛуре	Ruleset or RULESET (both parameters are supported).	Yes	None
jobName	The name of a business ruleset exactly as is defined in the Planning application.	Yes	None
	Example: RollupUSSales		
parameters		No	Default values for the runtime prompts as provided in Calculation Manager will be used.

Table 8-11 Ruleset

Example URL and Payload

https://<BASE URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs

```
{
   "jobType":"Ruleset",
   "jobName":"Calculate Plan Operating Expenses"
}
```

Example Ruleset Scenarios and POST Requests

These examples based on the Vision application illustrate how to run rulesets with parameters. For each example, review the sample ruleset in Calculation Manager to understand the sample POST request.

Example 1: Ruleset "Revenue Plan" when variables are merged and not hidden

In Revenue Plan, by default the variables are merged and hidden. When variables are hidden, the default values defined in Calculation Manager will be used when executing the ruleset and any values provided in the payload will be ignored.

Sample Ruleset in Calculation Manager

lame				Application	Туре	Description
🛛 🎇 Revenue Plan				Vision		
🤪 Copy Chanr	nel			Vision	Plan1	
🤪 Revenue Pla	an			Vision	Plan1	
Useass Vaviable	-					
Usages Variable	S					
_	S					
Usages Variables	S					
Merge Variables						Lice As Override
_	Name	Scope	Is Hidden	Value		Use As Override Value
Merge Variables		Scope Application	Is Hidden	Value		



Sample POST request

```
{
   "jobType":"Ruleset",
   "jobName":"Revenue Plan",
   "parameters":
   {
        "Version":"Worst Case",
        "Department":"No Entity"
   }
}
```

Example 2: Ruleset "Revenue Plan" when variables are not merged and not hidden

lame				Application	Туре	Descri
🛛 🞇 Revenue Plan				Vision		
🤪 Copy Chan	nel			Vision	Plan1	
🤪 Revenue Pl	an			Vision	Plan1	
u	2					
Usages Variable	5					
_						
Merge Variables						
_						
_	Name	Scope	Is Hidden	Value		Use As Ove Value
Merge Variables		Scope Application	Is Hidden	Value •		
Merge Variables	Name		Is Hidden	Value •		
Merge Variables	Name Department	Application	Is Hidden	•		

Sample POST request

```
{
  "jobType":"Ruleset",
  "jobName":"Revenue Plan",
  "parameters":
  {
    "Copy Channel.Department":"No Entity",
    "Copy Channel.Version":"Worst Case",
    "Revenue Plan.Department":"New Entity",
    "Revenue Plan.Version":"Best Case"
  }
}
```

Example 3: Ruleset "Calculate Plan Operating Expenses" with nested ruleset ("Revenue Plan") and variables are merged and not hidden

Sample Ruleset in Calculation Manager



lame					Application	Туре	Description
🛛 🏡 Calculate Plan Operating Expenses					Vision		
🤪 Operating Expenses Plan					Vision	Plan1	
🤪 Operating Expense Adj Plan					Vision	Plan1	
🤪 Copy Channel					Vision	Plan1	
🔺 🎇 Revenue Plan					Vision		
😝 Copy Chann	el				Vision	Plan1	
🤪 Revenue Pla	n				Vision	Plan1	
Usages Variables	Name	Scope	Is Hidden	Value		l	Jse As Override Value
		 b c 			=		
Operating Expenses Plan	n Version	Application					

Sample POST request

```
{
   "jobType":"Ruleset",
   "jobName":"Calulate Plan Operating Expenses",
   "parameters":
   {
        "Department":"Unspecified Entity",
        "Version":"Most Likely"
   }
}
```

Example 4: Ruleset "Calculate Plan Operating Expenses" with a nested ruleset ("Revenue Plan") and variables that are not merged and not hidden

Sample Ruleset in Calculation Manager



ame				A	Application	Туре	Description
🖓 Calculate Plan Operatin	ig Expenses			V	/ision		
🤪 Operating Expenses	s Plan			V	/ision	Plan1	
🤪 Operating Expense	Adj Plan			V	/ision	Plan1	
🤪 Copy Channel				V	/ision	Plan1	
🔺 🎇 Revenue Plan				V	/ision		
🤪 Copy Channel				V	/ision	Plan1	
🤪 Revenue Plan				V	/ision	Plan1	
Jsages Variables							
Merge Variables							
Merge Variables	Name	Scope	Is Hidden	Value		=	Use As Override Value
Merge Variables Rule/RuleSet Name Operating Expenses Plan	Version	Application		Value			Use As Override Value
Merge Variables	Version		Is Hidden	Value			Use As Override Value
Merge Variables Rule/RuleSet Name Operating Expenses Plan	Version	Application		Value •			Use As Override Value
Merge Variables Rule/RuleSet Name Operating Expenses Plan Operating Expense Adj Plan	Version Version	Application Application		Value			Use As Override Value
Merge Variables Rule/RuleSet Name Operating Expenses Plan Operating Expense Adj Plan Copy Channel	Version Version Department	Application Application Application		Value			Use As Override Value
Merge Variables Rule/RuleSet Name Operating Expenses Plan Operating Expense Adj Plan	Version Version Department Version	Application Application Application Application		Value			Use As Override Value
Merge Variables Rule/RuleSet Name Operating Expenses Plan Operating Expense Adj Plan Copy Channel	Version Version Department Version Department	Application Application Application Application		Value			Use As Override Value

Sample POST request

In this example, the same rule, Copy Channel, appears twice – once under Calculate Plan Operating Expenses, and once under Revenue Plan. This demonstrates how to provide the variables with their fully qualified paths.

```
{
    "jobType":"Ruleset",
    "jobName":"Calculate Plan Operating Expenses",
    "parameters":
    {
        "Operating Expenses Plan.Version":"Most Likely",
        "Operating Expense Adj Plan.Version":"What If",
        "Copy Channel.Department":"Unspecified Entity",
        "Copy Channel.Version":"Working",
        "Revenue Plan.Copy Channel.Department":"New Entity",
        "Revenue Plan.Copy Channel.Version":"Best Case",
        "Revenue Plan.Revenue Plan.Department":"No Entity",
        "Revenue Plan.Revenue Plan.Version":"Worst Case"
    }
}
```

Optionally, you can provide the sequence indexes in the paths, as shown below.

{
 "jobType":"Ruleset",



```
"jobName":"Calculate Plan Operating Expenses",
"parameters":
{
    "(1)Operating Expenses Plan.Version": "Most Likely",
    "(2)Operating Expense Adj Plan.Version": "What If",
    "(3)Copy Channel.Department": "Unspecified Entity",
    "(3)Copy Channel.Version": "Working",
    "(4.1)Revenue Plan.Copy Channel.Department": "New Entity",
    "(4.1)Revenue Plan.Copy Channel.Version": "Best Case",
    "(4.2)Revenue Plan.Revenue Plan.Department": "No Entity",
    "(4.2)Revenue Plan.Revenue Plan.Version": "Worst Case"
}
```

Example 5: Ruleset "Revenue Plan" with variables that are merged and not hidden

This example shows two Revenue Plan rules within a ruleset. This demonstrates how to differentiate the variables when there are multiple variables with the same paths within the same parent in the ruleset.

Sample Ruleset in Calculation Manager

lame				Application	Туре	Description
🛚 🞇 Revenue Plan				Vision		
🤪 Copy Chann	nel			Vision	Plan1	
🤪 Revenue Pla	n			Vision	Plan1	
🤪 Revenue Pla	an			Vision	Plan1	
Usages Varia<u>b</u>le s	•					
Merge Variables	•					
_	Name	Scope	Is Hidden	Value		Use As Override
Merge Variables		Scope Application	Is Hidden	Value		Use As Override Value

Sample POST request

```
{
   "jobType":"Ruleset",
   "jobName":"Revenue Plan",
   "parameters":
   {
        "Version":"Worst Case",
        "Department":"New Entity"
   }
}
```

Example 6: Ruleset "Revenue Plan" with variables that are not merged and not hidden



This example shows two Revenue Plan rules within a ruleset. This demonstrates how to differentiate the variables when there are multiple variables with the same paths within the same parent in the ruleset.

Sample Ruleset in Calculation Manager

lame				Application	Туре	Description
🛛 🎇 Revenue Plan				Vision		
🤪 Copy Chan	nel			Vision	Plan1	
🤪 Revenue Pl	an			Vision	Plan1	
🤪 Revenue Pl	an			Vision	Plan1	
Merge Variables		Scope	Is Hidden	Value		
Rule/RuleSet Name	Name	Scope	Is Hidden	Value		Use As Override Value
Rule/RuleSet Name		Scope Application	Is Hidden	Value -		
Rule/RuleSet Name	Name		Is Hidden	Value •	=	
Rule/RuleSet Name Copy Channel	Name Department	Application		Value •		Value
Rule/RuleSet Name Copy Channel	Name Department Version	Application		Value	=	Value
Merge Variables Rule/RuleSet Name Copy Channel Revenue Plan Revenue Plan	Name Department Version Department	Application Application Application		Value C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.	E	

Sample POST request

```
{
   "jobType":"Ruleset",
   "jobName":"Revenue Plan",
   "parameters":
   {
      "(1)Copy Channel.Department":"No Entity",
      "(1)Copy Channel.Version":"Worst Case",
      "(2)Revenue Plan.Department":"New Entity",
      "(2)Revenue Plan.Version":"Best Case",
      "(3)Revenue Plan.Version":"What If",
      "(3)Revenue Plan.Department":"Unspecified Entity"
   }
}
```

Plan Type Map

Copies data from a block storage cube to an aggregate storage cube or from one to another based on the settings specified in a job of type plan type map.

For details about data maps, see Defining Data Maps in Administering Data Integration for Oracle Enterprise Performance Management Cloud.

This API is not supported for Financial Consolidation and Close or Tax Reporting.



Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Table 8-12	Plan ⁻	Туре	Мар
------------	-------------------	------	-----

Name	Description	Requir ed	Default
јоbТуре	Plan Type Map or PLAN_TYPE_MAP (both parameters are supported)	Yes	None
jobName	The name of a job of type plan type map that is already defined in the application.	Yes	None
	Example: CampaignToReporting		
parameters	Optionally, you can specify these parameters:	No	None
	 clearData - Whether the data in the target database should be moved before copying data (defult: true). The value must use JSON syntax. Example: {clearData:false} 		
	• overrideMembersMap - A map containing the dimension name as the key and a member selection string as a value. Members specified in the map will replace the members in the data map definition during execution.		
	 overrideExclusionMembersMap - A map containing the dimension name as the key and a member selection string as a value. Members specified in the map will be excluded from the member selection in the data map definition during execution. Any members from the evaluated exclusion selection not present in the evaluated member selection from the data map definition will be ignored. 		
	 Notes: The override parameters execute this data map using the specified override members map, clearing data in the target region beforehand if requested. The data map push will error out when the override members map contains members from unmapped dimensions of the target location. 		
	 The member selection string is a comma-separated string consisting of member names, functions or expressions. 		

Example URL and Payload

```
https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs
```

```
{
  "jobType": "PLAN_TYPE_MAP",
  "jobName": "MapReporting",
  "parameters": {
     "cubeLinkName": "name",
     "clearData": true
  }
}
```

Examples of overriding selections of the data map:

```
{
  "jobType": "PLAN TYPE MAP",
  "jobName": " MapReporting",
  "parameters": {
    "cubeLinkName": "MapChannels",
    "clearData": true,
    "overrideMembersMap": {
      "Period": "ILvl0Descendants(Q1)"
    },
    "overrideExclusionMembersMap": {
     "Period": "Jan"
    }
  }
}
  "overrideMembersMap": {
    "Period": "ILvl0Descendants(Q1)"
  }
  "overrideMembersMap": {
    "Period": "ILvl0Descendants(Q1)",
    "Account": "Sales"
  }
```

Examples of excluding members:

```
"overrideExclusionMembersMap": {
    "Period": "Jan"
}
"overrideExclusionMembersMap": {
    "Period": "Jan, Feb, &CurrMonth, ILvl0Descendants(Q1), YearTotal, Red"
}
```



Import Data

Use this REST API to import data from a file in the repository into the application using the import data settings specified in a job of type Import Data.

You can override some of the parameters of the job definition while executing this job from a REST API.

You can also import data using the parameter values provided, without an explicit predefined Import Data job definition.

For Planning, Financial Consolidation and Close, and Tax Reporting, you can review the rejected data records that have errors. To do this, specify an error file that captures the data records that are not imported for each dimension. If an errop file is specified, the ZIP file is stored in the Outbox where you can download the file using Inbox/Outbox Explorer or tools like EPM Automate or REST APIs, for example, with the Download API.

Required Roles

Service Administrator

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јоbТуре	Import Data or IMPORT_DATA (both parameters are supported)	Yes	None
jobName	Name of this job.	No	Import Data
	Example: dailydataload		
importFileName	You can specify the name of the ZIP, CSV or TXT (Oracle Essbase format data file) file from which data is to be imported.	Yes	None
	If the parameter passed to import data is in Essbase format, the ZIP file must contain an Essbase format TXT file.		
	For other import jobs, the ZIP file may contain one or more CSV files that identify the import sequence in the file names; for example data1-3.csv, data2-3.csv, and data3-3.csv.		
	The value must use JSON syntax.		
sourceType	Paramter to specify the source of data.	Yes	None
	Allowed value is Planning or Essbase.		

Table 8-13 Import Data



Table 8-13 (Cont.) Import Data

Name	Description	Required	Default
delimiter	Parameter to specify a delimiter. Allowed value is comma or tab.	No	comma
	This is only applicable when the source type is Planning.		
dateFormat	Parameter to specify the data format.	No	MM-DD-YYYY
	Allowed value is one of the following: MM-DD-YYYY, DD-MM-YYYY, or YYYY-MM-DD.		
includeMetaData	Parameter to specify to include metadata from the data file.	No	false
	Allowed value is true or false.		
	This is only applicable when the source type is Planning.		
cube	Parameter to specify the cube name.	Yes	None
	This is only applicable (and becomes mandatory) when the source type is Essbase.		
errorFile	Paramter to specify the errorFile to store the rejected records (maximum 1,000).	No	No error files are created
	The error file is zipped with the name of this parameter. The ZIP file is stored in the Outbox. You can download it with the Download API. This API overrides any existing error file with the same name.		
	Example: ImportDataErrorFile.zip		
stopOnError	Parameter to stop the import process if an intermediate error is encountered during the import, for example, if data load finds an unknown member or invalid data value. This setting can only be used when sourceType is Essbase.	No	true
	When using this option, if you specified an error file, you can then review the rejected data record that has the error. The record is included in a ZIP file that is stored in the outbox where you can download it for review, for example, with the Download API. Allowed value is true or false.		

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payloads

Example 1: Executes the import data job ImportJob and overrides the importFileName parameter.

```
{"jobType":"IMPORT_DATA","jobName":"ImportJob",
"parameters":{
    "importFileName":"myImportfile123.zip"
    }
}
```



Example 2: Executes the import data job ImportJob and overrides the delimiter, dateFormat, and includeMetaData parameters.

```
{"jobType":"IMPORT_DATA","jobName":"ImportJob",
"parameters":{
    "delimiter":"comma",
    "dateFormat":"MM-DD-YYYY",
    "includeMetaData":"false"
    }
}
```

Example 3: Executes the import data job ImportJob defined with sourceType as Essbase and overrides the sourceType and cube parameters.

```
{"jobType":"IMPORT_DATA","jobName":"ImportJob",
"parameters":{
    "sourceType":"Essbase",
    "cube":"Plan1"
    }
}
```

Example 4: Executes the ImportData job ImportDataJob and overrides the errorFile parameter with a value ImportDataErrorFile.zip. If error records are found during the Import Data operation, a ZIP file called ImportDataErrorFile.zip is created in the Planning repository. The generated error file can be downloaded from the Outbox from the job status page or using the Download REST API or EPM Automate downloadfile command.

```
{"jobType": "IMPORT_DATA",
    "jobName": "ImportDataJob",
    "parameters": {
        "errorFile":"ImportDataErrorFile.zip"
    }
}
```

Example 5: Executes the ImportData job ImportDataJob_Sample defined with sourceType as Essbase, and overrides the stopOnError parameter with the value as true. The data load will stop loading in case of an intermediate error.

```
{
    "jobType": "IMPORT_DATA",
    "jobName": "ImportDataJob_Sample",
    "parameters": {
        "importFileName":"importDataFile_Essabse.txt",
        "cube":"Plan1",
        "stopOnError":"true"
    }
}
```

Example 6: Executes the import data job with all the mandatory parameters.

```
{
  "jobType": "IMPORT_DATA",
  "parameters":{
```



```
"sourceType": "Planning",
   "importFileName": "myImportfile123.zip",
   "delimiter": "comma"
}
```

Example 7: Executes the import data job with all the mandatory parameters. The sourceType parameter is specified as Essbase, and cube provides the cube name. Default values are assumed for other non-mandatory parameters.

```
"jobType": "Import Data",
   "parameters":{
      "sourceType": "Essbase",
      "cube": "Plan1",
      "importFileName": "EssbasePlan1 data.zip"
   }
}
```

Export Data

}

{

Use this REST API to export application data into a file using the export data settings, including file name, specified in a job of type export data. The file containing the exported data is stored in the repository.

You can override some of the parameters of the job definition while executing this job with a REST API.

You can also export application data into a file using the parameter values provided, without an explicit predefined Export Data job definition.

Exporting data supports substitution variables. You can use substitution variables while providing the rowMembers, columnMembers, and povMembers definitions. See Exporting Data and Creating and Assigning Values to Substitution Variables in Administering Planning.

Required Roles

Service Administrator

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Table 8-14 Export Data

Name	Description	Required	Default
јор⊥λЪ	Export Data or EXPORT_DATA (both parameters are supported)	Yes	None



Table 8-14 (Cont.) Export Data

Name	Description	Required	Default
jobName	The name of this job.	No	Export Data
	Example: dailydataexport		
exportFileName	The file name for the exported data. Data is exported as a ZIP file only. The exported file is stored in the Planning repository. The value must use JSON syntax.	No	The file name for the exported data will be the same as jobName.
delimiter	Parameter to specify a delimiter.	No	comma
	Allowed value is comma or tab.		
exportSmartListAs	Parameter to specify how Smart Lists are exported. Allowed value is label or name.	No	label, which signifies that Smart View labels will be exported.
includeDynamicMemb ers	Parameter to include or exclude dynamic members. Allowed value is true or false.	No	true, which signifies that dynamic members will be exported.
cube	Parameter to specify the cube from which to export data.	Yes	None
rowMembers	Parameter to specify the row members. Example: "Name,Price,Discount %"	Yes	None
columnMembers	Parameter to specify the column members. Example : "Name,Price,Discount %"	Yes	None
povMembers	Parameter to specify the POV members. Example : "Name,Price,Discount %"	Yes	None
exportDataDecim alScale	Parameter to specify the number of decimal positions (0-16) that will be returned when exporting data from Essbase. If the default None is selected, the data that is returned will not be formatted and will return as Essbase returns it. Selecting a numeric value will result in the exported data displaying that number of digits to the right of the decimal point, wherever applicable. For example, specifying 3 in the Decimals field will result in the exported data to display three digits to the right of the decimal point. Selecting 0 formats the data to display a whole number. Example : A value 27.07000001 can be formatted and written as 27.07 in the export data file if the value for this parameter is set to 2.	No	None

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payloads

Example 1: Executes the export data job ExportJobDaily and overrides the exportFileName parameter.

```
{"jobType":"EXPORT_DATA","jobName":"ExportJobDaily",
    "parameters":{
        "exportFileName":"myExportfile.zip"
        }
}
```



Example 2: Executes the export data job ExportJobDaily and overrides the delimiter, exportSmartListAs, and includeDynamicMembers parameters.

```
{"jobType":"EXPORT_DATA","jobName":"ExportJobDaily",
"parameters":{
    "delimiter":"tab",
    "exportSmartListAs":"name",
    "includeDynamicMembers":"true"
    }
```

Example 3: Executes the export data job ExportJobDaily and overrides the cube parameter only. This job will now execute for the cube Vis1ASO.

```
{"jobType":"EXPORT_DATA","jobName":"ExportJobDaily",
"parameters":{
    "cube":"Vis1ASO
    }
}
```

Example 4: Executes the export data job ExportJobDaily and overrides the cube name along with the rowMembers, columnMembers, and povMembers parameters. This job will now execute for the cube Vis1ASO.

```
{"jobType":"EXPORT_DATA","jobName":"ExportJobDaily",
"parameters":{
    "cube":"Vis1ASO",
    "rowMembers":"Current,Variance,Actual,Scenario",
    "columnMembers":"Statistics,Account",
    "povMembers":"Period,Year,Version,Entity,Product,Channel"
    }
}
```

Example 5: Executes the export data job ExportJobDaily and overrides the cube name along with the parameters rowMembers, columnMembers, and povMembers. We use substitution variables while overriding the rowMembers, columnMembers, and povMembers definition. This job executes for the cube VislASO.

```
{"jobType":"EXPORT_DATA","jobName":"ExportJobDaily",
    "parameters":{
        "cube":"Vis1ASO",
        "rowMembers":"ILv10Descendants(&Param1)",
        "columnMembers":"ILv10Descendants(&Param2)",
        "povMembers":"Period,Year,Version,&Param3,Product,Channel"
        }
}
```

Example 6: Executes the export data job ExportJobDaily and overrides the cube name along with the parameters exportDataDecimalScale, rowMembers, and columnMembers. We use

substitution variables while overriding the rowMembers, columnMembers, and povMembers definition. This job executes for the cube Vis1ASO.

```
{"jobType":"EXPORT_DATA","jobName":"ExportJobDaily",
"parameters":{
    "cube":"Vis1ASO",
    "rowMembers":"ILv10Descendants(&Param1)",
    "columnMembers":"ILv10Descendants(&Param2)",
    "povMembers":"Period,Year,Version,&Param3,Product,Channel",
    "exportDataDecimalScale":"2"
    }
}
```

Example 7: Executes the export data job with all the mandatory parameters, cube, rowMembers, columnMembers, and povMembers. Default values are assumed for other non-mandatory parameters.

```
{"jobType": "EXPORT_DATA",
"parameters": {
    "cube": "Vis1ASO",
    "rowMembers": "ILv10Descendants(&Param1)",
    "columnMembers": "ILv10Descendants(&Param2)",
    "povMembers": "Period,Year,Version,&Param3,Product,Channel"
    }
}
```

Example 8: Executes the export data job with all the mandatory parameters, cube, rowMembers, columnMembers, and povMembers. Decimal precision is set to 3. Default values are assumed for other non-mandatory parameters.

```
{"jobType": "EXPORT_DATA",
"parameters":{
    "cube": "Plan1",
    "rowMembers": "ILvl0Descendants(&Param1)",
    "columnMembers": "ILvl0Descendants(&Param2)",
    "povMembers": "Period,Year,Version,&Param3,Product,Channel",
    "exportDataDecimalScale": 3
    }
}
```

Example 9: Executes the export data job with all the mandatory parameters, cube, rowMembers, columnMembers, and povMembers. Decimal precision is set to 3. Dynamic members are not exported. Default values are assumed for all other non-mandatory parameters.

```
{"jobType": "EXPORT_DATA",
"parameters":{
    "cube": "Plan1",
    "rowMembers": "ILvl0Descendants(&Param1)",
    "columnMembers": "ILvl0Descendants(&Param2)",
    "povMembers": "Period,Year,Version,&Param3,Product,Channel",
    "exportDataDecimalScale": 3,
    "includeDynamicMembers": false
```



}

}

Import Metadata

Imports metadata from a file in the Planning repository into the application using the import metadata settings specified in a Planning job of type import metadata.

You can also override some of the parameters of the job definition while executing this job from a REST API.

For Planning, Financial Consolidation and Close, and Tax Reporting, you can specify an error file that captures the metadata records that are not imported for each dimension. If an error file is specified, a separate error file is created for each dimension. The error files are then zipped together and the zip file is stored in the Outbox where you can download the file using Inbox/ Outbox Explorer or tools like EPM Automate or REST APIs, for example, with the Download API.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Require d	Default
јоbТуре	Import Metadata or IMPORT_METADATA (both parameters are supported)	Yes	None
jobName	The name of a job of type import metadata exactly as it is already defined in the Planning application.	Yes	None
	Example: importAccount		

Table 8-15 Import Metadata

Table 8-15	(Cont.)	Import	Metadata
------------	---------	--------	----------

Name	Description	Require d	Default
importZipFileName	Optionally, you can specify the name of the ZIP file from which metadata is to be imported. The contents of the ZIP file that you specify take precedence over the file names defined in the job. The ZIP file may contain one or more CSV files.	No	The import file name defined in the job definition.
	The file names containing metadata for dimensions should match the import file names defined in the job or end with _DIMENSIONNAME.csv, for example, metadata_Entity.csv, metadata_HSP_SmartLists.csv, and metadata_Exchange Rates.csv.		
	Only metadata for the dimensions for which metadata import is set up in the job is imported. Metadata for other dimensions, if contained in the ZIP file, is ignored.		
	Example: {importZipFileName:importAccount.zip}		
refreshCube	You can override the option to perform a refresh cube action defined in the job.	No	"Refresh Database if Import Metadata is
	Allowed values are either true or false.		successful" parameter of the job definition.
errorFile	Optionally, create a separate error file for each dimension. The error files are zipped with the name of this parameter. The ZIP file is stored in the Outbox. You can download it with the Download API. This API overrides any existing error file with the same name Example : ImportMetaDataErrorFile.zip	No	No error files are created.

For a sample URL, see Sample URL and Payload in Execute a Job.

```
Sample Payload
```

Example: Executes the job ImportMetaDataJob and overrides only the importZipFileName parameter.

```
{
  "jobType": "IMPORT_METADATA",
  "jobName": "ImportMetaDataJob",
  "parameters": {
      "importZipFileName": "myMetaDataDailyJob.zip"
  }
}
```

Example: Executes the job ImportMetaDataJob and overrides the errorFile parameter with a value ImportMetaDataErrorFile.zip. If there are error records found during the Import Metadata operation for one or more dimensions, a ZIP file called

ImportMetaDataErrorFile.zip is created in the repository that contains one error CSV file for each failed dimension. The generated error file can be downloaded from the Outbox from the job status page or using the Download REST API or EPM Automate downloadfile command.

{
 "jobType": "IMPORT_METADATA",

```
"jobName": "ImportMetaDataJob",
"parameters": {
        "errorFile":"ImportMetaDataErrorFile.zip"
}
```

Export Metadata

}

Use this REST API to export metadata into a file using the settings specified in a Planning job of type export metadata. The file containing the exported metadata is stored in the Planning repository.

You can also override some of the parameters of the job definition while executing this job from a REST API.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Require d	Default
јоbТуре	Export Metadata or EXPORT_METADATA (both parameters are supported)	Yes	None
jobName	The name of a job of type export metadata exactly as it is already defined in the Planning application.	Yes	None
	Example: dailyAccountExport		
exportZipFileName	Optionally, you can specify a file name for the exported metadata. Metadata is exported as a ZIP file only.	No The file name for exported metada	
	The value must use JSON syntax.		be the same as Job Name
	Example : {exportZipFileName:Accountexport.zip}		

Table 8-16 Export Metadata

Example Payload

Example: Executes the export metadata job "ExportMetadataDaily" and overrides the exportZipFileName parameter.

```
{
    "jobType": "EXPORT METADATA",
    "jobName": "ExportMetadataDaily",
    "parameters": {
```



```
"exportZipFileName": "dailyMetaData.zip"
}
```

Cube Refresh

}

Use this REST API to refresh the Planning application cube. Typically, you refresh the cube after importing metadata into the application.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
jobType	Cube Refresh or CUBE_REFRESH (both parameters are supported)	Yes	None
jobName	Name of the job to run. You must use the exact name of a job that is already defined in the application.	Yes	None
	Example: refreshcube		
allowedUsersDuri ngCubeRefresh	Possible values: Administrators or All Users	No	None
terminateActiveR equestsBeforeCub eRefresh	Possible values: true or false	No	None
logOffAllUsersBe foreCubeRefresh	Possible values : true or false	No	None
allowedUsersAfte rCubeRefresh	Possible values: Administrators or All Users	No	None

Table 8-17 Cube Refresh

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

{"jobType":"CUBE_REFRESH","jobName":"CubeRefresh"}



Sample Payload overriding parameters:

```
{"jobType":"CUBE_REFRESH","jobName":"MyRefreshCube","parameters":
{"allowedUsersDuringCubeRefresh":" All Users",
"terminateActiveRequestsBeforeCubeRefresh":"false","logOffAllUsersBeforeCubeRe
fresh":"true","allowedUsersAfterCubeRefresh":"Administrators"}}
```

Clear Cube

Use this REST API to clear specific data within input and reporting cubes.

You can clear the data using member selection or a valid MDX query. Using member selection, you can also optionally clear related supporting details, comments, and attachments. You can also elect to do a physical or logical clear of data. This gives you more flexibility and granularity when clearing the cube.

NOTE: The Clear Cube job deletes the data you specify within input and reporting cubes, but it does not delete the application definition in the application's relational tables.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
jobType	Clear Cube or CLEAR_CUBE (both parameters are supported)	Yes	None
jobName	Name of the job to run. Important: You must use the exact name of a job that is already defined in the application.	Yes	None
	Example : ClearPlan1		
cube	Valid ASO cube name	No	As per the job definition

Table 8-18 Clear Cube



Name	Description	Required	Default
members	Valid member selection that is comma separated. Applicable only for Partial Clear Job, for an ASO cube, defined with member selection. Example: "ILv10Descendants (E xchange Rates), Total	No	As per the job definition
	Expense"		
mdxQuery	Valid MDX query. Applicable only for Partial Clear Job, for an ASO cube, defined with MDX query support. Example: "Crossjoin({[Apr], [May],[Jun]}, {[Expense1]})"	No	As per the job definition
clearSupportingDeta ils	Specify if supporting details should be cleared. Allowed values: true or false. Applicable only for Partial Clear Job, for an ASO cube, defined with member selection.	No	As per the job definition
clearComments	Specify if comments should be cleared. Allowed values: true or false. Applicable only for Partial Clear Job, for an ASO cube, defined with member selection.	No	As per the job definition
clearAttachments	Specify if attachments should be cleared. Allowed values: true or false. Applicable only for Partial Clear Job, for an ASO cube, defined with member selection.	No	As per the job definition
clearPhysicalOnEssb ase	Specify if this is a physical clear on Essbase. Allowed values: true or false. Applicable only for Partial Clear Job, for an ASO cube, defined with member selection or MDX query support.	No	As per the job definition

Table 8-18 (Cont.) Clear Cube

For a sample URL, see Sample URL and Payload in Execute a Job.



Sample Payload

{"jobType":"CLEAR CUBE", "jobName":"ClearPlan1"}

Example: Executes the clear job Clear_Partial_Basic, which is defined with member selection, and overrides the cube and members parameters.

```
{
   "jobType": "Clear Cube",
   "jobName": "Clear_Partial_Basic",
   "parameters": {
        "cube": "HP1_ASO",
        "members": "ILv10Descendants(Exchange Rates),Siblings(Total Expense)"
   }
}
```

Example: Executes the clear job Clear_Partial_Basic, which is defined with member selection, and overrides the cube, clearSupportingDetails, clearComments, and other parameters.

```
{
    "jobType": "Clear Cube",
    "jobName": "Clear_Partial_Basic",
    "parameters": {
        "cube":"HP1_ASO",
        "members":"ILv10Descendants(Exchange Rates),Siblings(Total Expense)",
        "clearSupportingDetails":"false",
        "clearComments":false,
        "clearAttachments":false,
        "clearPhysicalOnEssbase":false
    }
}
```

Example: Executes the clear job Clear_Partial_Advanced, which is defined with the MDX query, and overrides the mdxQuery parameter.

```
{
   "jobType": "Clear Cube",
   "jobName": "Clear_Partial_Advanced",
   "parameters": {
        "mdxQuery":"Crossjoin({[Apr],[May],[Jun]},{[Expense1]})"
   }
}
```

Example: Executes the clear job Clear_Partial_Advanced, which is defined with the MDX query, and overrides the cube, mdxQuery, and clearPhysicalOnEssbase parameters.

```
{
   "jobType": "Clear Cube",
   "jobName": "Clear_Partial_Advanced",
   "parameters": {
        "cube":"HP1_ASO",
        "mdxQuery":"Crossjoin({[Apr],[May],[Jun]},{[Expense1]})",
        "clearPhysicalOnEssbase":false
```

}

Administration Mode

Changes the login level for a Planning application. If you set login level to Administrators, all Interactive Users and Planners will be logged off of the application upon completion of the job. For details on administration mode, see Scheduling Jobs.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јоbТуре	Administration Mode	Yes	None
jobName	The job name to be used for this job execution. Example: AppAdminJob	No	Administration Mode
loginLevel	Specify the login level for users using loginLevel. Possible values are Administrators or All Users	Yes	None

Table 8-19 Parameters

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example: This request will change the login level of the application to "Administrators" level.

```
{
   "jobType": "Administration Mode",
   "jobName": "AppAdminJob",
   "parameters": {
        "loginLevel": "Administrators"
   }
}
```



Compact Cube

Use this REST API to compact the outline file of an ASO cube.

Compaction helps keep the outline file at an optimal size. Compacting the outline does not clear the data. For more information, see Scheduling Jobs.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Table 8-20 Parameters

Name	Description	Required	Default
јоbТуре	Compact Cube	Yes	None
jobName	The job name to be used for this job execution.	No	Compact Outline
	Example: CompactCube		
cubeName	Name of the ASO cube	Yes	None

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example: This request will compact the outline of Vis1ASO ASO cube.

```
{
   "jobType": "Compact Cube",
   "jobName": "CompactCube",
   "parameters": {
        "cubeName": "Vis1Aso"
   }
}
```

Restructure Cube

Performs a full restructure of a BSO cube to eliminate or reduce fragmentation. For more information, see Scheduling Jobs.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

REST Resource

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јорДуре	Restructure Cube	Yes	None
jobName	The job name to be used for this job execution. Example: RestructureCube	No	Restructure Cube
cubeName	Name of the BSO cube	Yes	None

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example: This request will restructure Plan1 BSO

```
{
   "jobType": "Restructure Cube",
   "jobName": "RestructureCube",
   "parameters": {
        "cubeName": "Plan1"
   }
}
```

Merge Data Slices

Merges incremental data slices of an ASO cube. Fewer slices improve a cube's performance. You can merge all incremental data slices into the main database slice or merge all incremental data slices into a single data slice without changing the main database slice. You can optionally remove cells that have a value of zero. For more information, see Scheduling Jobs.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json



Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јорТуре	Merge Data Slices	Yes	None
jobName	The job name to be used for this job execution. Example: MergeDataSlice	No	Merge Data Slices
cubeName	Name of the ASO cube	Yes	None
keepZeroCells	Possible values are true or false	Yes	None
mergeSliceType	Possible values are <i>allIncrementalSlicesI</i> <i>nMain</i> (Merge all into the main slice)	Yes	None
	Or allIncrementalSlicesI nOneIncremental (Merge all incremental into a single incremental slice)		

Table 8-22 Parameters

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example: This request will merge all incremental data slices in the main data slice and keep zero value cells.

```
{
  "jobType": "Merge Data Slices",
  "jobName": "MergeDataSlice",
  "parameters": {
      "cubeName": "VisASO",
      "mergeSliceType": "allIncrementalSlicesInMain",
      "keepZeroCells": "true"
}
```

Optimize Aggregation

}

Improves the performance of ASO cubes. This job has two actions: Enable query tracking and Execute aggregation process. It performs an aggregation, optionally specifying the maximum disk space for the resulting files, and optionally basing the view selection on user querying patterns. This API is only applicable to aggregate storage databases. For information about scheduling jobs, see Scheduling Jobs.

Before using this API, you must first enable query tracking to capture tracking statistics on the aggregate storage cube. Then, after you enable query tracking, you must allow sufficient time to collect user data-retrieval patterns before you execute the aggregation process based on

query data. The execute aggregation process deletes existing aggregated views and generates optimized views based on the collected query tracking data.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/jobs/
{jobId}
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Table 8-23 Parameters

Name	Description	Required	Default
jobType	Optimize Aggregation	Yes	None
jobName	The job name to be used for this job execution	No	Optimize Aggregation
parameters	Parameters required for the job	Yes	None
cubeName	Name of the ASO cube	Yes	None
type	Can take one of these values: enableQueryTracking or executeAggregationP rocess	Yes	None
useQueryData	Aggregate the views the server selects based on collected user querying patterns. This option is only available if query tracking is turned on. Permissible values: true or false . Default: false. Applicable only if type is executeAggregationP rocess .		None



Name	Description	Required	Default
includeAlternateRol lups	Include secondary hierarchies (with default level usage) in the view selection. Permissible values: disable or enable . Default: disable (no secondary hierarchies are considered). Applicable only if type is executeAggregationP rocess .	No	None
growthSizeRatio	Aggregates the views the server selects until the maximum growth of the aggregated database exceeds the limits you specify. The value can be a real number such as 1.01. Default is that the database will grow without any growth ratio limit. Applicable only if type is executeAggregationP rocess .	No	None

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: This request will enable query tracking on the Vis1ASO cube.

```
{
   "jobType": "Optimize Aggregation",
   "jobName": "CubeOptimizeAggr",
   "parameters": {
        "cubeName": "Vis1ASO",
        "type": "enableQueryTracking"
   }
}
```

Example 2: This request will execute the aggregation process on the Vis1ASO cube.

```
{
   "jobType": "Optimize Aggregation",
   "jobName": "CubeOptimizeAggr",
   "parameters": {
        "cubeName": "Vis1ASO",
        "type": "executeAggregationProcess"
    }
}
```



}

}

Example 3: This request will execute aggregation process on the Vis1ASO cube. Aggregation process will use the query tracking data, will not include alternate roll ups, and use growth size ratio as 1.01.

```
{
   "jobType": "Optimize Aggregation",
   "jobName": "CubeOptimizeAggr",
   "parameters": {
        "cubeName": "Vis1ASO",
        "type": "executeAggregationProcess",
        "useQueryData": "true",
        "includeAlternateRollups": "disable",
        "growthSizeRatio": "1.01"
   }
}
```

Import Security

Imports the security records or access control list (ACL) records from a Comma Separated Values (CSV) file. For information about access permissions to application artifacts, see Setting Up Access Permissions.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Excel File Format

- Object Name: The name of the object for which the ACL is defined
- Name: The name of the user or group for which the ACL is defined
- Parent: The name of the parent of the object
- Is User: The flag (Y or N) that determines if the ACL is defined for a user or for a group
- Object Type: The type of object, for example, Forms folder
- Access Type: The type of privilege, such as READ or READWRITE
- · Access Mode: Additional information, such as if the ACL is applicable on the descendants
- Remove: To remove a particular ACL, set this to Y

All possible values:

Object Type:

- SL_FORM Form
- SL_COMPOSITE Composite Form
- SL_TASKLIST Tasklist
- SL_CALCRULE Rule
- SL_FORMFOLDER Form Folder
- SL_CALCFOLDER Rule Folder
- SL_DIMENSION Dimension



- SL_CALCTEMPLATE Template
- SL_REPORT Management Report

• SL_REPORTSSHOT - Management Report Snapshot

Access Type:

- NONE None
- READ Read
- WRITE Write
- READWRITE Read Write
- LAUNCH Launch

Access Mode:

- MEMBER
- CHILDREN
- @ICHILDREN
- @DESCENDANTS
- @IDESCENDANTS

CSV File Example:

Object Name, Name, Parent, Is User, Object Type, Access Type, Access Mode, Remove "Exchange Rates to USD", "ats_user3", "Y", "SL_FORM", "READWRITE", "MEMBER", "N" "Exchange Rates to USD", "ats_user4", "Y", "SL_FORM", "READWRITE", "MEMBER", "N" "Exchange Rates to USD", "ats_user15", "Y", "SL_FORM", "READ", "MEMBER", "N" "Exchange Rates to USD", "ats_user10", "Y", "SL_FORM", "READ", "MEMBER", "N" "Calculate Benefits", "group_1", "N", "SL_COMPOSITE", "READWRITE", "MEMBER", "N"

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
jobType	Import Security	Yes	None
jobName	The job name to be used for this job execution. Example: ImportSecurity	No	Import Security

Table 8-24 Parameters



Name	Description	Required	Default
fileName	The input CSV file for import. The file containing the ACL records should be present in the Planning Cloud repository.	Yes	None
clearAll	Clear existing access permissions when importing new access permissions. Possible values are true or false	No	False
errorFile	Optionally, create a separate error file for recording any errors that occur during the import process. The file containing the error messages is stored in the Outbox. You can download it with theDownload API. This API overrides any existing error file with the same name.	No	None

Table 8-24 (Cont.) Parameters

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Imports security records from the input file ImportSecurityRecordsFile.csv. **Existing security records are retained**.

```
{
   "jobType": "Import Security",
   "jobName": "ImportSecurity",
   "parameters": {
        "fileName": "ImportSecurityRecordsFile.csv"
   }
}
```

Example 2: Imports security records from the input file ImportSecurityRecordsFile.csv. Clears existing security records before importing.

```
{
   "jobType": "Import Security",
   "jobName": "ImportSecurity",
   "parameters": {
        "fileName": "ImportSecurityRecordsFile.csv"
        "clearAll": "true"
```



}

Example 3: Imports security records from the input file ImportSecurityRecordsFile.csv and exports the error messages to the file SecurityImportErrors.txt. Existing security records are retained.

```
{
  "jobType": "Import Security",
  "jobName": "ImportSecurity",
  "parameters": {
     "fileName": "ImportSecurityRecordsFile.csv"
     "clearAll": "true"
     "errorFile": "SecurityImportErrors.txt"
  }
}
```

Export Security

Exports the security records or access control list (ACL) records for specified users or groups to a Comma Separated Values (CSV) file. For information about access permissions to application artifacts, see Setting Up Access Permissions.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Table 8-25 Parameters

Name	Description	Required	Default
јорДуре	Export Security	Yes	None
jobName	The name of this job. Example: ExportSecurity	No	Export Security



Name	Description	Required	Default
fileName	The name of the file to which records should be exported. The file containing the exported data is stored in the Planning repository. If fileName is not specified, a file is auto-generated with a name containing the user name, current date, and time stamp. For example, test_admin_Security Records_2019-02-26- 04-34-45-420.csv.	No	The file name is auto- generated
exportUsers	Comma separated user names. Only ACL records related to the specified users are exported.	No	None
exportGroups	Comma separated user names. Only ACL records related to the specified groups are exported.	No	None

Table 8-25 (Cont.) Parameters

Notes:

- This job can take only exportGroups or exportUsers at one time. If you need to export groups and users, you must run the job twice, once with each parameter.
- If a user name or group name contains a comma, escape the comma in the request. For example, if a user name is test, User, the request should contain test\\,User.
- For the file format, see the definition in Import Security Records.

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Exports all security records to the ExportSecurityRecordsFile.csv file.

```
{
   "jobType": "Export Security",
   "jobName": "ExportSecurity",
   "parameters": {
        "fileName": "ExportSecurityRecordsFile.csv"
   }
}
```



Example 2: Exports security records of two groups, group1 and group2, to the ExportSecurityRecordsFile.cv file.

```
{
    "jobType": "Export Security",
    "jobName": "ExportSecurity",
    "parameters": {
        "exportGroups": "group1, group2"
        "fileName": "ExportSecurityRecordsFile.csv"
    }
}
```

Example 3: Exports security records of two users, test1 and test, User2 to the ExportSecurityRecordsFile.csv file. Note that one user name contains a comma in it.

```
{
    "jobType": "Export Security",
    "jobName": "ExportSecurity",
    "parameters": {
        "exportUsers": "test1, test\\,User2"
        "fileName": "ExportSecurityRecordsFile.csv"
    }
```

Export Audit

}

This REST API exports the audit records for a number of days.

The audit records are exported to a Comma Separated Values (CSV) file. The output CSV file contains the first character as a Byte Order Mark (BOM) character \ufeff. The API writes an encrypted application identifier following the BOM character. This application identifier is written between double-quotes. Headers for the CSV file follow the application identifier. For more information, see Auditing Tasks and Data.

You can use an optional excludeApplicationId parameter to not write the application identifier in the export file. Exported audit reports without the application identifier cannot be imported back into the application.

The generated CSV file is compressed and the output is a ZIP file. The file can be downloaded using the Download REST API.

Required Roles

Service Administrator

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.



Name	Description	Required	Default
јоbТуре	Export Audit	Yes	None
jobName	The job name to be used for this job execution. Example: ExportAudit	No	Export Audit
userNames	Comma separated user names. Audit records created by only the specified users are exported. If not specified, audit records created by all users are exported.	No	None
fileName	The name of the file to which records should be exported. The file containing the exported data is stored in the Oracle Planning and Budgeting Cloud repository. If fileName is not specified, a file is auto- generated with a name containing the user name, current date, and time stamp. For example, test_admin_AuditRec ords_2019-02-26-04- 34-45-420.zip	No	The file name is auto- generated

Table 8-26 Parameters

Name	Description	Required	Default
nDays	 Number of days for which audit records should be exported. Possible values are: 1: Export audit records for the last 24 hours 2: Export audit records for the last two days 7: Export audit records for the last seven days 30: Export audit records for the last 30 days 60: Export audit records for the last 60 days 180: Export all existing audit records for the last 180 days All: Export all audit records Note: Audit information is maintained for up to 365 days from the current system date. 	No	7
excludeApplication d	Optionally, you can specify if the application identifier should be written in the export file. Possible values: true or false	No	false
	This parameter can benefit those customers who do not want the application identifier to be included in the export file to help import into their own systems. This export file cannot be used to import into an EPM Cloud environment.		

Table 8-26 (Cont.) Parameters

Notes:

• This job does not export records based on group names.

• If a user name contains a comma, escape the comma in the request. For example, if a user name is test, User then add test\\,User to the request.

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Exports the last 180 days of audit records to the ExportAuditLast180Days.zip file.

```
{
  "jobType": "Export Audit",
  "jobName": "Export180DaysAudit",
  "parameters": {
    "fileName": "ExportAuditLast180Days.zip",
        "ndays": "180"
  }
}
```

Example 2: Exports the last seven days of audit records created by planner1 and planner2. Records are exported to a zip file with an auto-generated file name.

```
{
  "jobType": "Export Audit",
  "jobName": "AllAuditRecordsOfPlanners",
  "parameters": {
        "userNames": "planner1, planner2"
   }
}
```

Example 3: Exports the last 180 days of audit records to the ExportAuditLast180Days.zip file. The application identifier will be not written in the generated file. This export file cannot be used to import into an EPM Cloud environment.

```
{
  "jobType": "Export Audit",
  "jobName": "Export180DaysAudit",
  "parameters": {
     "fileName": "ExportAuditLast180Days.zip",
     "ndays": "180",
     "excludeApplicationId": "true"
  }
}
```

Export Job Console

Use this REST API to export the job console records to a Comma Separated Values (CSV) file.

The output CSV file contains the first character as a Byte Order Mark (BOM) character, \ufeff. The API writes an encrypted application identifier following the BOM character. This application identifier is written between double-quotes. Headers for the CSV file follow the application identifier.

You can use an optional excludeApplicationId parameter to not write the application identifier in the export file. Exported job console data files without the application identifier cannot be imported back into the application.

The generated CSV file is compressed and the output is a ZIP file. The file can be downloaded using the Download REST API.

To view pending jobs, see Viewing Pending Jobs and Recent Activity.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јорТуре	Export Job Console	Yes	None
jobName	The job name to be used for this job execution. Example: ExportWeeklyJobStat usRecords	No	Export Job Console
userNames	Comma separated user names. Job console records created by only the specified users are exported. If not specified, job console records created by all users are exported.	No	None

Table 8-27 Parameters

Name	Description	Required	Default
fileName	The name of the file to which records should be exported. The file containing the exported data is stored in the Planning repository. If fileName is not specified, a file is auto- generated with a name containing the user name, current date, and time stamp. For example, test_admin_JobConso leRecords 2019-02-2	No	The file name is auto- generated
	6-04-34-45-420.zip		
ndays	 Number of days for which audit records should be exported. Possible values are. 1: Export job console records for the last 24 hours 2: Export job console records for the last two days 7: Export job console records for the last seven days 30: Export job console records for the last 30 days 60: Export job console records for the last 40 days All: Export all job console records 	No	7
jobNames	Comma-separated job names for which job console records should be exported.	No	None

Table 8-27(Cont.) Parameters

Name
Name jobTypes

Table 8-27 (Cont.) Parameters

Name	Description	Required	Default
name	Description MERGE_DATA_SLI CES Optimize Aggregation or OPTIMIZE_AGGRE GATION Import Security or SECURITY_IMPORT Export Security or SECURITY_EXPORT Export Audit or AUDIT_EXPORT Export Job Console or JOBCONSOLE_EXP ORT Sort Members or SORT_MEMBERS Smart Push or SMART_PUSH Import Exchange Rates or IMPORT_EXCHAN GE_RATES Execute Bursting Definition or EXECUTE_MR_BUR ST		
jobStatusCodes	Comma-separated status code of the jobs for which job records are exported. Possible values are: 1 - Processing 2 - Completed successfully 3 - Failed with errors 4 - Completed with unknown status 5 - Completed with threshold violation status 6 - Pending cancellation 7 - Cancelled 8 - Completed with errors 9 - Completed with warnings all - All jobs with any status	No	2

Table 8-27 (Cont.) Parameters



Name	Description	Required	Default
exportErrorDetails	If true, exports the details of failed/error jobs as separate error log file in the final output file. Job status details of jobs having one of the status listed below are exported in separate files. • Error • Unknown • Completed with Threshold Exception • Completed with Errors • Completed with Warnings	No	true
topCountDuration	Filters the top <i>n</i> job status records by completion time. This is useful for finding the longest running jobs. For example, enter 10 for this parameter to review the top 10 longest running jobs, as in this example: "topCountDuration ":"10"	No	0 Represents all records
excludeApplicationI d	Optionally, you can specify if the application identifier should be written in the export file. Possible values: true or false	No	false
	This parameter can benefit those customers who do not want the application identifier to be included in the export file to help import into their own systems. This export file cannot be used to import into an EPM Cloud environment.		

Table 8-27 (Cont.) Parameters

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Exports the job console records for all default parameters into the NewFile.csv file. Exports status of all Rule jobs completed in the last seven days.

```
{
    "jobType":"JOBCONSOLE_EXPORT",
    "jobName":"AllJobConsoleExports",
    "parameters":{"fileName":"NewFile.csv"}
}
```

Example 2: Exports the job console records for Rule and Export Data jobs that completed normally or with an error status over the last month into the exportFile.csv file. Job details of the failed jobs are exported in separate files in the final compressed file.

```
{
    "jobType":"JOBCONSOLE_EXPORT",
    "parameters":{"fileName":"exportFile.csv", "jobTypes": "Rules,
EXPORT_DATA", "jobStatusCodes": "2,3", "ndays":"30"}
}
```

Example 3: Exports the job console records for the jobs named Daily Consolidation and Smart Push to a Reporting Cube. Includes jobs that completed normally or with an error status over the last month into the exportFile.csv file. Job details of the failed jobs are not exported in separate files because exportErrorDetails is false.

```
{
    "jobType":"JOBCONSOLE_EXPORT",
    "parameters":{"fileName":"exportFile.csv", "jobNames":"Daily
Consolidation, Smart Push to Reporting Cube", "jobStatusCodes": "2,3",
"ndays":"30", "exportErrorDetails":"false"}
}
```

Example 4: Exports the top 10 longest running jobs:

```
{
    "jobType":"JOBCONSOLE_EXPORT",
    "parameters":{"fileName":"exportFile.csv", "jobStatusCodes": "all",
"ndays":"all", "jobTypes":"all", "exportErrorDetails":"false",
"topCountDuration":"10"}
}
```

Example 5: Exports the job console records for all default parameters into to the NewFile.csv file. This exports status of all Rule jobs completed in the last seven days. The application identifier will be not written in the generated file. This export file cannot be used to import into an EPM Cloud environment.

```
{
    "jobType":"JOBCONSOLE_EXPORT",
    "jobName":"AllJobConsoleExports",
    "parameters":{
    "fileName":"NewFile.csv",
```

```
"excludeApplicationId": "true"
}
```

Sort Members

Sorts the dimension members of a business process.

You can sort Entity, Account, Scenario, Version, and user-defined custom dimension members. You cannot sort Period, Years, or Currency dimension members. This feature is only supported for the Planning, Module, and Free Form business processes. For more information, see Sorting Members.

For Planning Module applications, you cannot sort these dimensions:

- Any dense dimension
- The "Plan Element" dimension, even if it is renamed, from Financials
- The "Project Element" dimension, even if it is renamed, from Projects

After sorting members, administrators must perform a cube refresh.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јорТуре	Sort Members	Yes	None
jobName	The job name to be used for this job execution. Example: SortEntity	No	Sort Members
member	Parent member whose children or descendants are being sorted.	Yes	None
order	Order of sorting. Possible values are:	No	ascending
	• ascending		
	• descending		

Table 8-28 Parameters



Name	Description	Required	Default
type	Sort children or descendants. Possible values are:	No	children
	 children - sorting by children affects only members in the level immediately below the specified member descendants - sorting by descendants affects all descendants of the specified member. 		

Table 8-28	(Cont.)	Parameters
------------	---------	------------

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Sorts the child members of the Account dimension in ascending order.

```
{
  "jobType": "Sort Members",
  "jobName": "SortAccount",
  "parameters":
  {
   "member":"Account"
  }
}
```

Example 2: Sorts the child members of the Account dimension in descending order.

```
{
   "jobType": "Sort Members",
   "jobName": "SortAccountDesc",
   "parameters":
   {
    "member":"Account", "order":"descending"
   }
}
```

Example 3: Sorts the descendants of member account200 in descending order.

```
{
   "jobType": "Sort Members",
   "jobName": "SortAccount200Desc",
   "parameters":
```



```
{
"member":"account200", "order":"descending", "type":"descendants"
}
```

Import Exchange Rates

}

Export the Exchange Rates template in the Planning repository and change the rates if required. You can then import the rates into the application using the Import Exchange Rates settings specified in a Planning job of type import exchange rates. For more information, see Job Types.

You can also override some of the parameters of the job definition while executing this job from a REST API.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default	
јоbТуре	Import Exchange Rates or IMPORT_EXCHANGE_RAT ES (both parameters are supported)	Yes	None	
jobName	The name of the job to be used for this job execution. Important : You must use the exact name of a job that is already defined in Planning as described in Managing Jobs.	Yes	None	
	Example: importNewExchangeRa te			

Table 8-29 Import Exchange Rates



Name	Description	Required	Default
importFileName	Optionally, you can specify the name of the CSV file from which exchange rates are to be imported.	No	The source file of the job definition
	If you specify a file name, the Import Exchange Rate file name in the job is ignored.		
includeMetaData	You can override the option to include metadata. Allowed value is true or false.	No	Include Metadata parameter of the job definition

Table 8-29 (Cont.) Import Exchange Rates

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Executes the import exchange rates job MyExchangeRates and overrides the importFileName parameter.

```
{"jobType":"Import Exchange Rates","jobName":"MyExchangeRates",
"parameters":{
    "importFileName":"ExportExchangeRatesTemplate.csv"
    }
}
```

Example 2: Executes the import exchange rates job MyExchangeRates and overrides the importFileName and includeMetaData parameters.

```
{"jobType":"Import Exchange Rates","jobName":"MyExchangeRates",
"parameters":{
    "importFileName":"ExchangeRateTemplate2.csv",
    "includeMetaData":"false"
    }
}
```

Auto Predict

Schedule predictions using the Auto Predict job. With Auto Predict, administrators can define a prediction to predict future performance based on historical data and schedule a job to run that prediction definition, automating the prediction process. For details about Auto Predict, see Setting Up Predictions to Run Automatically in *Administering Planning*.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Job Types.

Required Roles

Service Administrator



Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јорТуре	Auto Predict	Yes	None
jobName	The name used to define Auto Predict in the user interface in Overview, then Actions, and then Auto Predict. This name will be used for the job execution. Important : You must use the exact name of a job that is already defined in Planning as described in Managing Jobs.	Yes	None
	Example: Prediction1		
forceRun	If this is set to true, the job will always execute. If not, the job executes only for the first time. In subsequent attempts, if there is no change in the job definition, this message displays: "Auto Prediction definition hasn't changed since the last time the Auto Predict job ran; the job will not execute. If you want to run the Auto Predict definition, for example if there are new actual values, you can run the Auto Predict definition from the Auto Predict page. From the Actions menu, click Actions and then click Run."		False

Table 8-30 Import Exchange Rates



Name	Description	Required	Default
paginatedDim	Speeds up an Auto Predict job by running predictions in parallel in separate prediction threads. For the parallel jobs to be efficient, choose a dimension that will result in evenly spread data for each prediction thread. Example: Entity	No	False

Table 8-30 (Cont.) Import Exchange Rates

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload

Example 1: Executes the Auto Predict job ASO->BSO.

```
{
  "jobType": "Auto Predict",
  "jobName": "ASO->BSO",
  "parameters": {
      "forceRun": true,
      "paginatedDim": "Entity"
  }
}
```

Import Cell-Level Security

This REST API imports cell-level security settings from a ZIP file that contains an Excel file with cell-level security definitions into Planning or Tax Reporting business processes. Cell-level security enables Service Administrators to restrict who can view data in the application by defining rules that remove read or write access to cells that a user would normally have access to due to their regular security.

The file must be present in the Inbox. You can use the Upload REST API to upload the file. Any rejected records are generated in an Excel file that is zipped and copied to the Outbox.

The best method to get the import file format template is to export cell-level security from the application.

The following is a general explanation of the Excel file. The file contains two Excel worksheets:

- Rules contains cell-level security definitions, dimensions included, properties such as Unspecified Valid, and Additional Dims Required
- 2. Sub Rules contains member selections and exclusions

The Rules worksheet has the following column headings:

- Name
- Position



- Description
- Enabled
- Valid Cubes This column can contain either All or a list of comma-separate names of cubes, such as Plan1, Plan2
- Anchor Dim Name
- Anchor Dimension Apply to Unselected Members
- Dim1
- Dim1 Required
- Dim2
- Dim2 Required
- DimX
- DimX Required

The Sub Rules worksheet has the following column headings:

- Name This column must contain the name of the Rules from the first worksheet
- Users
- User Groups
- Restriction This column can contain Deny Read or Deny Write
- Anchor Members
- Anchor Exclusion
- Dim1 Members
- Dim1 Exclusion
- Dim2 Members
- Dim2 Exclusion
- DimX Members
- DimX Exclusion

Required Roles

Service Administrator

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/
jobs

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For parameters that are common to all jobs, see Execute a Job.



Name	Description	Required	Default
јорТуре	Import Cell-Level Security or IMPORT_CELL_LEVEL_SECURITY	Yes	None
jobName	The name of the job to be used. This job name appears on the job console.	No	Import Cell-Level Security Definitions
	Example : ImportCLSPlan1		
fileName	The name of the ZIP file containing the input Excel file. The file must be present in the Inbox.	Yes	None
	Before using this REST API, you can use the Upload REST API to upload the file.		
errorFile	Optionally, create a separate error file for recording any errors that occur during the import process. If this is not specified, an error file is auto- generated with a name containing the user name, current date, and time stamp. For example, admin_ImportError_2020- 02-26-04-34-45-420.txt. The file containing the error messages is stored in the Outbox. You can download it using the Download API. This API overrides any existing error file with the same name.	No	The file is auto-generated

Table 8-31 Import Cell-Level Security

For a sample URL, see the sample URL and payload in Execute a Job

Example 1: Imports cell-level security records from the input file ImportCLSRecordsFile.zip.

```
{
   "jobType": "Import Cell-Level Security",
   "jobName": "ImportCLSJob",
   "parameters": {
        "fileName": "ImportCLSRecordsFile.zip"
   }
}
```

Example 2: Imports cell-level security records from the input file ImportCLSRecordsFile.zip and exports the error messages to the file ImportCLSFileLog.txt.

```
{
    "jobType": "Import Cell-Level Security",
    "jobName": "ImportCLSJob",
    "parameters": {
        "fileName": "ImportCLSRecordsFile.zip",
        "errorFile": "ImportCLSRecordsFileLog.txt"
    }
}
```



Export Cell-Level Security

This REST API exports cell-level security settings from Planning or Tax Reporting into a ZIP file that contains an Excel file. Cell-level security enables Service Administrators to restrict who can view data in the application by defining rules that remove read or write access to cells that a user would normally have access to due to their regular security.

The generated file is compressed, and the output is a ZIP file that is added to the Outbox. You can download the file using the Download REST API.

Note the following requirements for the format of the Excel file used with this REST API.

The exported Excel file contains two worksheets with these names:

- 1. Rules
- 2. Sub Rules

The Rules worksheet has the following column headings:

- Name
- Position
- Description
- Enabled
- Valid Cubes This column contains either All or a list of comma-separate names of cubes, such as Plan1, Plan2
- Anchor Dim Name
- Anchor Dimension Apply to Unselected Members
- Dim1
- Dim1 Required
- Dim2
- Dim2 Required
- DimX Members
- DimX Required

The Sub Rules worksheet has the following column headings:

- Name This column contains the names of the Rules from the first sheet
- Users
- User Groups
- Restriction This column can contain Deny Read or Deny Write
- Anchor Members
- Anchor Exclusion
- Dim1 Members
- Dim1 Exclusion
- Dim2 Members
- Dim2 Exclusion



- DimX Members
- DimX Exclusion

Required Roles

Service Administrator

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/
jobs

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For parameters that are common to all jobs, see Execute a Job.

Table 8-32 Export Cell Level Security

Name	Description	Required	Default
јоbТуре	Export Cell-Level Security or EXPORT_CELL_LEVEL_SECURITY	Yes	None
jobName	The name of the job to be used. This job name appears on the job console.	No	Export Cell-Level Security Definitions
	Example : ExportCLSDPlan1		
fileName	The name of the ZIP file that will be created to hold the Excel file containing cell-level security information. The file containing the exported data is stored in the Outbox.	Yes	None
names	Optionally, include a comma-separated list of cell-level security definitions in the application. Information from each definition is exported to a separate Excel file and then zipped. For example, the list could contain CLSDAccountPeriod, CLSDEntityPe riod, CLSDProductPeriod.	No	All records are exported
	If this parameter is not provided, all cell-level security records are exported.		

For a sample URL, see the sample URL and payload in Execute a Job

Example 1: Exports all cell-level security records to the file ExportCLSDRecordsFile.zip.



Sample Payload

```
{
   "jobType": "Export Cell-Level Security",
   "jobName": "ExportCellLevelSecurityJob",
   "parameters": {
        "fileName": "ExportCLSDRecordsFile.zip"
   }
}
```

Example 2: Exports three cell-level security records with names CLSDAccountPeriod, CLSDEntityPeriod, and CLSDProductPeriod to the file Export3CLSDRecordsFile.zip.

```
{
    "jobType": "Export Cell-Level Security",
    "jobName": "ExportCellLevelSecurityJob",
    "parameters": {
        "fileName": "Export3CLSDRecordsFile.zip",
        "names": "CLSDAccountPeriod, CLSDEntityPeriod, CLSDProductPeriod"
    }
}
```

Import Valid Intersections

This REST API imports valid intersections groups from a ZIP file that contains an Excel file with valid intersection definitions into a Financial Consolidation and Close, Planning, or Tax Reporting business process.

The Excel file must be present in the Inbox. You can use the Upload REST API to upload the file. Any rejected records are generated in an Excel file that is zipped and copied to the Outbox.

The following is a general explanation of the Excel file. The file contains two Excel worksheets:

- 1. Rules defines the intersection group, dimensions included, and properties such as Unspecified Valid and Additional Dims Required
- 2. Sub Rules provides member selections and exclusions

The Rules worksheet has the following column headings.

- Name
- Position
- Description
- Enabled
- Valid Cubes This column can contain either All or a list of comma-separate names of cubes, such as Plan1, Plan2
- Anchor Dim Name
- Anchor Dimension Apply to Unselected Members
- Dim1
- Dim1 Required
- Dim2



- Dim2 Required
- DimX
- DimX Required

The Sub Rules worksheet must have the following column headings:

- Name This column must contain the name of the Rule from the first worksheet
- Users
- User Groups
- Restriction This column can contain Deny Read or Deny Write
- Anchor Members
- Anchor Exclusion
- Dim1 Members
- Dim1 Exclusion
- Dim2 Members
- Dim2 Exclusion
- DimX Exclusion

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

REST Resource

POST	<pre>/HyperionPlanning/rest/{api_version}/applications/{application}/</pre>
jobs	

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For parameters that are common to all jobs, see Execute a Job.

Table 8-33 Import Valid Intersections

Name	Description	Required	Default
јорТуре	Import Valid Intersections or IMPORT_VALID_INTERSECTIONS	Yes	None
jobName	The name of the job to be used for this job execution, exactly as it is defined in the application.	No	Import Valid Intersections
	Example: ImportVIAccountPeriod		



Name	Description	Required	Default
fileName	The name of the ZIP file containing the input Excel file. The file must be present in the Outbox.	Yes	None
	Before using this REST API, you can use the Upload REST API to upload the file.		
errorFile	Optionally, identify the name of a text file for recording any errors that occur during the import process. If this is not specified, an error file is auto- generated with a name containing the user name, current date, and time stamp. For example, admin_ImportError_2020-02-26- 04-34-45-420.txt.	No	The file name is auto- generated
	The file containing the error messages is stored in the Outbox. You can download it using the Download REST API.		

Table 8-33 (Cont.) Import Valid Intersections

For a sample URL, see the sample URL and payload in Execute a Job

Example 1: Imports valid intersections records from the input file ImportVIRecordsFile.zip.

```
{
   "jobType": "Import Valid Intersections",
   "jobName": "ImportVIJob",
   "parameters": {
        "fileName": "ImportVIRecordsFile.zip"
   }
}
```

Example 2: Imports valid intersections records from the input file ImportVIRecordsFile.zip and exports the error messages to the file ImportVIRecordsFileLog.txt.

```
{
   "jobType": "Import Valid Intersections",
   "jobName": "ImportVIJob",
   "parameters": {
        "fileName": "ImportVIRecordsFile.zip",
        "errorFile": "ImportVIRecordsFileLog.txt"
   }
}
```



Export Valid Intersections

This REST API exports valid intersection groups (certain cell intersections filtered by rules when users enter data or select runtime prompts) from Financial Consolidation and Close, Planning, or Tax Reporting business processes.

The output is a ZIP file that is added to the Outbox. You can download the file using the Download REST API.

Note the following requirements for the format of the Excel file used with this REST API.

The exported Excel file contains two worksheets with these names:

- 1. Rules
- 2. Sub Rules

The Rules worksheet has the following column headings:

- Name
- Position
- Description
- Enabled
- Anchor Dim Name
- Anchor Dimension Apply to Unselected Members
- Dim1
- Dim1 Required
- Dim2
- Dim2 Required
- DimX
- DimX Required

The Sub Rules worksheet has the following column headings:

- Name This column contains the names of the Rules from the first worksheet
- Anchor Members
- Anchor Exclusion
- Dim1 Members
- Dim1 Exclusion
- Dim2 Members
- Dim2 Exclusion
- DimX Members
- DimX Exclusion

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator



REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/
jobs

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For parameters that are common to all jobs, see Execute a Job.

Table 8-34	Export Valid	Intersections
------------	--------------	---------------

Name	Description	Required	Default
јорТуре	Export Valid Intersections or EXPORT_VALID_INTERSECTIONS	Yes	None
jobName	The name of the job to be used. This job name appears on the job console.	No	Export Valid Intersections
	Example : ExportVIRecords		
fileName	The name of the ZIP file that will be created to hold the Excel file containing valid intersection records. The file containing the exported data is stored in the Outbox.	Yes	None
names	If provided, exports some of the records using the names in a comma- separated list of valid intersection record names. For example, the list could contain VIAccountPeriod, VIEntityPeriod , VIProductPeriod.	No	All records are exported
	If this parameter is not provided, all valid intersection records are exported.		

For a sample URL, see the sample URL and payload in Execute a Job

Sample Payload

Example 1: Exports all valid intersections records to the file ExportVIRecordsFile.zip.

```
{
   "jobType": "Export Valid Intersections",
   "jobName": "ExportVIJob",
   "parameters": {
        "fileName": "ExportVIRecordsFile.zip"
   }
}
```



Example 2: Exports three valid intersection records with names VIAccountPeriod, VIEntityPeriod, and VIProductPeriod to the file Export3VIRecordsFile.zip.

```
{
   "jobType": "Export Valid Intersections",
   "jobName": "ExportVIJob",
   "parameters": {
        "fileName": "Export3VIRecordsFile.zip",
        "names": "VIAccountPeriod, VIEntityPeriod, VIProductPeriod"
   }
}
```

Execute a Report Bursting Definition

You can execute bursting for a single report or book for more than one member of a single dimension, and publish a PDF or Excel output for each member.

The bursting definition must be present in the folder that you specify with the burstingDefinitionName parameter.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/
jobs

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For parameters that are common to all jobs, see Execute a Job.

Table 8-35 Execute a Report Bursting Definition

Name	Description	Required	Default
јоbТуре	Execute Bursting Definition or EXECUTE_MR_BURST (both parameters are supported)	Yes	None
jobName	The name of the job to be used. This job name appears on the job console.	No	Execute Bursting Definition
	Example : MonthlySalesBurstDev		
burstingDefinitionN ame	Bursting definition name with the complete path to where the bursting definition is stored.	Yes	None
	Example :/Library/Jan/ MonthlySalesBurstDef		



For a sample URL, see the sample URL and payload in Execute a Job

Sample Payload

Example 1: Executes the bursting definition named MonthlySalesBurstDev that is present in the Library folder.

```
{
  "jobType":"Execute Bursting Definition",
  "jobName":"Execute MonthlySalesBurstDef",
  "parameters": {
    "burstingDefinitionName":"Library/MonthlySalesBurstDef"
}
```

Example 2: Executes the bursting definition named MonthlySalesBurstDev that is present in the Reports subfolder under the Library folder.

```
{
  "jobType":"Execute Bursting Definition",
  "jobName":"Execute MonthlySalesBurstDef",
  "parameters": {
    "burstingDefinitionName":"Library/Reports/MonthlySalesBurstDef"
```

Export Library Documents

}

Creates a job to copy a document from the library. The Copy Artifact from Library (Export Library Document) job copies the content of a library document to the default download location, where you can download it to your local computer. Using REST APIs allows you to automate the tasks of exporting documents and downloading them.

You can use the Inbox/Outbox Explorer to view the details of the copied file. Use the Download REST API to download the file.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. For additional details, see Job Types.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јоbТуре	Copy Artifact From Library or Export Library Document or COPY_ARTIFACT_FRO M_LIBRARY (all values are supported)	Yes	None
jobName	The name of this job. Example: Copy_Quarterly_Sales	No	Export Library Document
idOrFullyQualifiedN ame	The name of the document. This can be the document name with a fully qualified path or UUID.	Yes	None
saveAsFile	The output file name, in the default download location, to which the document should be copied. If you don't provide the extension in saveAsFile, the file	No	Name of the document
	will take the extension from the document being copied. If a file with the same name exists, the job will error out unless the overwrite flag is passed as true.		
	The default output file name is the name of the document. The extension of the document is used as the extension of the output file name.		
overwrite	If a file with the same name exists in the default download location, the file will not be overwritten by default unless the overwrite flag is passed as true.	No	false

Table 8-36 Parameters



Name	Description	Required	Default
errorFile	The error file name, in the default download location, which contains the details (including errors) of the operation. Any existing error file with the same name is overwritten. If you don't provide the extension in errorFile, the file will use .log as the default extension. Use the Inbox/Outbox Explorer to view the details of the error file. Use the Download REST API to download the		None
exportFormat	file. The format of the copied document. Allowed values are file and zip.	No	file
	 file - copies the document in its original binary format. For example, if the document is a PDF or Microsoft Word document, it is copied as a PDF or a Microsoft Word document. zip - copies the document in its original binary format and zips it. 		

Table 8-36	(Cont.) Parameters
------------	--------------------

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload Example

Copies a document called WeeklySales.txt, identified with the complete path of the document, to the default download location and compresses it. The output file name will be WeeklySales.zip. If a file with the same name exists in the Inbox/Outbox, the existing file will be overwritten. An error file with the name WeeklySalesErrorLog.log will be created with the details of the activity.

```
"jobType": "COPY_ARTIFACT_FROM_LIBRARY",
"jobName": "Copy Invalid SKU Q1 List",
```

{

```
"parameters":
    {
        "artifactName": "Library/folder1/WeeklySales.txt",
        "saveAsFile": "WeeklySales.txt",
        "overwrite": "true",
        "errorFile": "WeeklySalesErrorLog.log",
        "exportFormat": "zip"
    }
}
```

Import Library Documents

Creates a job to import documents from the library. The Import Document to Library job imports the content from a local source to the library in the specified upload location. Using REST APIs allows you to automate the tasks of uploading library artifacts.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. For additional details, see Job Types.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs.

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Name	Description	Required	Default
јорТуре	Import Document to Library or IMPORT_DOCUMENT_ TO_LIBRARY	Yes	None
jobName	The name of this job. Example: Import_Annual_Report	No	Import Document to Library
name	The name of the document or ZIP file containing documents being imported.	Yes	
description	Brief description of the document being imported. For ZIP files, this description applies to all documents within it.		None

Table 8-37Parameters



Name	Description	Required	Default
idOrFullyQualifiedD estinationPath	The library destination path where the document(s) will be imported. This can be a path with folders or UUID of the folder.	Yes	None
overwrite	If a file with the same name exists in the default download location, the file will not be overwritten by default unless the overwrite flag is	No	false
deleteAfterImport	passed as true. Determines whether the file should be deleted from the local source after import.	No	false
	For imports using a ZIP file, the source file will be deleted only if all contained documents are imported successfully.		
errorFile	The error file name, in the default download location, which contains the details (including errors) of the operation. Any existing error file with the same name is overwritten.	No	None
	If you don't provide the extension in errorFile, the file will use .log as the default extension.		
	Use the Inbox/Outbox Explorer to view the details of the error file. Use the Download REST API to download the file.		

Table 8-37 (Cont.) Parameters

For a sample URL, see Sample URL and Payload in Execute a Job.

Sample Payload Example

Imports a document called FinancialReport2022.xlsx into a folder called Insights with a description. If a file with the same name exists, it will be overwritten. An error file named FinancialReport2022ImportLog.log will be created with details of the activity.

```
{
    "jobType": "IMPORT_DOCUMENT_TO_LIBRARY",
    "jobName": "ImportSingleDocument",
    "parameters": {
        "name": "FinancialReport2022.xlsx",
        "description": "Annual Financial Report for 2022",
        "idOrFullyQualifiedDestinationPath": "Library/Insights",
        "overwrite": true,
        "deleteAfterImport": false,
        "errorFile": "FinancialReport2022ImportLog.log"
    }
}
```

Sample Payload Example: Importing a ZIP File

Imports a ZIP file named Reports2022.zip into the folder Reports. The import process generates a common log file, Reports2022ImportLog.log, which aggregates the details and outcomes of all child jobs associated with the documents contained within the Reports2022.zip file.

```
{
    "jobType": "IMPORT_DOCUMENT_TO_LIBRARY",
    "jobName": "ImportMultipleDocuments",
    "parameters": {
        "name": "Reports2022.zip",
        "description": "Collection of Financial Reports for 2022",
        "idOrFullyQualifiedDestinationPath": "Library/Reports",
        "overwrite": true,
        "deleteAfterImport": false,
        "errorFile": "Reports2022ImportLog.log"
    }
}
```

Execute Job Code Samples

Example 8-1 Java Sample – executeJob.java

```
//
// BEGIN - Execute a Job (EXPORT_DATA, EXPORT_METADATA, IMPORT_DATA,
IMPORT_METADATA, CUBE_REFRESH, ...)
//
public void executeJob(String jobType, String jobName, String parameters)
throws Exception {
    String urlString = String.format("%s/HyperionPlanning/rest/%s/
applications/%s/jobs", serverUrl, apiVersion, applicationName);
    JSONObject payload = new JSONObject();
    payload.put("jobName",jobName);
    payload.put("jobType",jobType);
    payload.put("parameters",new JSONObject(parameters));
```

```
String response = executeRequest(urlString, "POST", payload.toString());
System.out.println("Job started successfully");
getJobStatus(fetchPingUrlFromResponse(response, "self"), "GET");
//
// END - Execute a Job (EXPORT_DATA, EXPORT_METADATA, IMPORT_DATA,
IMPORT_METADATA, CUBE_REFRESH, ...)
//
```

Example 8-2 cURL Sample – ExecuteJob.sh

```
funcExecuteJob() {
    url="$SERVER URL/HyperionPlanning/rest/$API VERSION/
applications/$APP NAME/jobs"
    encodedJobName=$(echo $2 | sed -f urlencode.sed)
    if [ ! -z "$3" ]; then
param="{\"jobType\":\"$1\", \"jobName\":\"$encodedJobName\", \"parameters\":$3}"
    else
            param="{\"jobType\":\"$1\",\"jobName\":\"$encodedJobName\"}"
    fi
    funcExecuteRequest "POST" $url $param
   output=`cat response.txt`
   status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started executing job successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Example 8-3 Groovy Sample – ExecuteJob.groovy

```
else {
                                             params.put(param[0], param[1]);
                                     }
                             }
                    }
                    payload.put("jobName",jobName);
                    payload.put("jobType", jobType);
                    payload.put("parameters", params);
            1
            else {
                    payload.put("jobName",jobName);
                    payload.put("jobType",jobType);
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", payload);
    if (response != null) {
        getJobStatus(fetchPingUrlFromResponse(response, "self"), "GET");
    }
}
```

Retrieve Job Status

Use this REST API to poll the server to get the processing state for a job with a specified ID.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/jobs/
{jobIdentifier}
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-38 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
applicationName	The name of the application	Path	Yes	None
jobIdentifier	The ID of the job	Path	Yes	None



Response

Parameters

The following table summarizes the response parameters.

Table 8-39 Parameters

Name	Description
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 = cancel pending; 3 = cancelled; 4 = invalid parameter; Integer.MAX_VALUE = unknown
details	Details about the job status, such as "Metadata import was successful" for metadata import
jobID	The ID of the job, such as 224
jobName	The name of the job, such as Refresh Database
descriptiveStatus	The status of the job, such as Completed or Error

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body for metadata import:

```
{
   "status": 0,
   "details": "Metadata import was successful",
   "jobId": 224,
   "jobName": "Import Account Metadata",
    "descriptiveStatus": "Completed",
   "links": [{
        "rel": "self",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/test2/jobs/224",
        "action": "GET"
    }, {
        "rel": "job-details",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/test2/jobs/224/details",
        "action": "GET"
    }]
}
The following shows an example of the response body when an error occurs
during cube refresh:
{
   "status": 1,
   "details": "An error occurred while updating the relational database.",
    "jobStatus": "Error",
   "jobId": 145,
    "jobName": "Refresh Database",
    "links": [{
        "rel": "self",
        "href": "https://<SERVICE NAME>-
```

```
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/PS4app1/jobs/145",
    "action": "GET"
    }}, {
        "rel": "job-details",
        "href": "https://<SERVICE_NAME>-
```

The following shows an example of the response body when an error occurs during cube refresh:

```
{
   "status": 1,
   "details": "An error occurred while updating the relational database.",
    "jobStatus": "Error",
   "jobId": 145,
    "jobName": "Refresh Database",
    "links": [{
        "rel": "self",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/PS4app1/jobs/145",
        "action": "GET"
   }}, {
        "rel": "job-details",
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/test2/jobs/145/details",
        "action": "GET"
    }]
}
```

Retrieve Job Status Details

Use this REST API to poll the server to get execution details for a Job with the specified Job ID.

The job types for which details are returned by this service are: IMPORT_DATA, EXPORT_DATA, EXPORT_DATA, EXPORT METADATA, and IMPORT METADATA.

Supports paging for jobs of type IMPORT_DATA, IMPORT_METADATA, EXPORT_DATA, and EXPORT METADATA using the offset and limit query parameters shown in the table.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator



REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/jobs/ {jobIdentifier}/details

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-40 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
jobIdentifier	The ID of the job, such as 224	Path	Yes	None
q				
msgType	Optionally, return messages for a particular message type. If no messageType is provided, returns messages of types ERROR, WARNING, and INFO.	Query	No	None
offset	For paging of jobs. Indicates the actual index from which the records are returned. It is 0 based.	Query	No	0
limit	For paging for jobs. Controls how many items to return. Defaults to 25 if not specified.	Query	No	25

Example Requests

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs/145/details

Optionally specifying messageType:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs/145/
details?q={"messageType":"ERROR"}

Optionally specifying paging for jobs of type IMPORT_DATA and EXPORT_DATA with the offset and limit:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs/145/
details?q={"messageType":"ERROR"}&offset=0&limit=5}

Response

The following table summarizes the response parameters.

Name	Description
items	Version of the API you are developing with
recordsRead	The name of the application
recordsRejected	The ID of the job for records rejected
recordsProcessed	The ID of the job for records processed

Table 8-41 Parameters



Table 8-41 (Cont.) Parameters

Name	Description
dimensionName	For paging of jobs. Indicates the actual index from which the records are returned. It is 0 based.
loadType	For paging for jobs. Controls how many items to return. Defaults to 25 if not specified.

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body for metadata import with messageType = ERROR:

```
{
   "items": [{
        "links": [{
            "rel": "child-job-details",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
test2/jobs/224/childjobs/12/details?
limit=10&q=%7BmessageType:ERROR%7D&offset=10",
            "action": "GET"
        }],
        "recordsRead": 8,
        "recordsRejected": 0,
        "recordsProcessed": 8,
        "dimensionName": "Entity",
        "loadType": "Metadata Import"
    }, {
        "links": [{
            "rel": "child-job-details",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
test2/jobs/224/childjobs/13/details?
limit=10&q=%7BmessageType:ERROR%7D&offset=10",
            "action": "GET"
        }],
        "recordsRead": 2,
        "recordsRejected": 0,
        "recordsProcessed": 2,
        "dimensionName": "Job",
        "loadType": "Metadata Import"
    }],
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
test2/jobs/224/details?limit=10&q=%7BmessageType:ERROR%7D&offset=10",
        "action": "GET"
    }],
}
```



Retrieve Child Job Status Details

Use this REST API to get the execution details for the child Job with the specified ID.

Certain types of jobs, such as metadata import and export, create child jobs for each dimension being exported or imported.

The job types for which child details are returned by this service are IMPORT_METADATA and EXPORT_METADATA. Supports paging for jobs of type IMPORT_DATA and EXPORT_DATA using the offset and limit query parameters shown in the table.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/jobs/ {jobIdentifier}/childjobs/{childJobIdentifier}/details

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-42 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
applicationName	The name of the application	Path	Yes	None
jobIdentifier	The ID of the job, such as 224	Path	Yes	None
childJobIdentifier	The ID of the child job	Path	Yes	None
childJobID	The ID of the child job, such as 8	Path	Yes	None
q				
messageType	Optionally, return messages for a particular message type. If no messageType is provided, returns messages of types ERROR, WARNING, and INFO.	Query	Yes	None
offset	For paging of jobs. Indicates the actual index from which the records are returned. It is 0 based.	Query	No	0
limit	For paging of jobs. Controls how many items to return. Defaults to 25 if not specified.	Query	No	25

Example Requests

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs/145/ childjobs/123/details

Optionally specifying messageType:



https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs/145/ childjobs/123/details?q={"messageType":"ERROR"}

Optionally specifying paging for jobs of type IMPORT_METADATA and EXPORT_METADATA with an offset and limit:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/jobs/145/ childjobs/123/details?q={"messageType":"ERROR"}&offset=0&limit=5

Response

The following table summarizes the response parameters.

Table 8-43 Parameters

Name	Description
items	The number of records read, such as 8
msgType	Message type, such as INFO
msgCategory	Message category, such as Argument parsing
msgText	Message text

Supported Media Types: application/json

Example of Response Body

The following example shows a response body with messageType = INFO, offset=5, limit=5. Notice the prev and next links.

```
{
    "items": [{
        "msgType": "INFO",
        "msgCategory": "Argument parsing",
        "msgText": "The column alias mapping list specified with the /C2A
switch did not match a key in the Command Properties file \"null\" so it will
be used as the mapping directly: \"(<ignoreUndefined>,@Plan*)\"."
    }, {
        "msqType": "INFO",
        "msgCategory": "Unclassified",
        "msgText": "Header record fields: Entity, Parent, Alias: Default,
Alias: SLAliases, Valid For Consolidations, Data Storage, Two Pass
Calculation, Description, Formula, UDA, Smart List, Data Type, Hierarchy
Type, Enable for Dynamic Children, Number of Possible Dyn..."
    }, {
        "msqType": "INFO",
        "msgCategory": "Dimension, member, or cube retrieval",
        "msgText": "Located and using \"Entity\" dimension for loading data
in \"Test2\" application."
    }, {
        "msqType": "INFO",
        "msgCategory": "Unclassified",
        "msgText": "HspOutlineLoad::dateFormatSpecified is true,
SessionHalDateFormat stored on session: M/d/yy, sessionId: 759992870"
    }, {
        "msqType": "INFO",
        "msgCategory": "Dimension, member, or cube retrieval",
        "msgText": "Load dimension \"Entity\" has been unlocked successfully."
```

```
}],
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
test2/jobs/224/childjobs/12/details?limit=5&offset=5",
        "action": "GET"
    }, {
        "rel": "prev",
        "href": "https:<BASE-URL>/HyperionPlanning/rest/v3/applications/test2/
jobs/224/childjobs/12/details?offset=0&limit=5",
        "action": "GET"
    }, {
        "rel": "next",
        "href": "https:/<BASE-URL>/HyperionPlanning/rest/v3/applications/
test2/jobs/224/childjobs/12/details?offset=10&limit=5",
        "action": "GET"
    }],
}
```

Working with Members

You can get and add members using a set of REST resources, as summarized below.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Task	Request	REST Resource
Add Member	POST	<pre>/HyperionPlanning/rest/{api_version}/applications/ {application}/dimensions/{dimensionname}/members</pre>
Get Member	GET	/HyperionPlanning/rest/{api_version}/applications/ {application}/dimensions/{dimension}/members/{member}

Table 8-44 Working with Members

Add Member

Use this REST API to add a new member to the application outline in the specified dimension and plan type and under the specified parent member.

Note:

Prerequisite: The parent member must be enabled for dynamic children and a cube refresh must have happened after the parent was enabled.

Required Roles

Service Administrator

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/dimensions/ {dimname}/members

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-45 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application to which to add a member	Path	Yes	None
dimname	Name of the dimension to which to add a member	Path	Yes	None

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/dimensions/ Entity/members

{"memberName":"North America","parentName":"Enterprise Global"}

Response

Payload Parameters:

The following table summarizes the payload parameters.

Name	Description
name	Name of the member, such as North America
children	Whether the member has children
description	Description of the member
parentName	Name of the parent, such as Enterprise Global
dataType	Data type, if available
objectType	Type of object
dataStorage	Storage attribute for the member, such as STOREDATA
dimName	Dimension name
twoPass	Boolean value to indicate whether the member has the Two-Pass Calculation associated attribute
instance	Information about the instance
type	Type of member
detail	Detailed information in case of error
status	Request status, such as 400
errorPath	Path of the error, if available

Table 8-46 Parameters



Name	Description
title	Error title, if available
errorCode	Error code, if available
errorDetails	Error details, if available
message	Message text
localizedMessage	Localized message, if available

Table 8-46 (Cont.) Parameters

Example of Response Body

Sample response body where the member is added successfully

```
{
    "name": "North America",
    "children": null,
    "description": null,
    "parentName": "Enterprise Global",
    "dataType": "UNSPECIFIED",
    "objectType": 33,
    "dataStorage": "STOREDATA",
    "dimName": "Entity",
    "twoPass": false,
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
Vision/dimensions/Entity/members/North%20America",
        "action": "GET"
    }]
}
```

Sample response when an error occurs when adding the member:

```
{
    "detail": "Error occurred adding member. Unable to find parent
<Enterprise GlobalX> defined for a dynamic member.",
    "status": 400,
    "message": "com.hyperion.planning.HspRuntimeException: Error occurred
adding member. Unable to find parent <Enterprise GlobalX> defined for a
dynamic member.",
    "localizedMessage": "com.hyperion.planning.HspRuntimeException: Error
occurred adding member. Unable to find parent <Enterprise GlobalX> defined
for a dynamic member."
}
```

Get Member

Gets the specified member's properties.

Required Roles

Service Administrator



REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/dimensions/
{dimname}/members/{member}
```

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-47 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to get member properties	Path	Yes	None
dimname	Name of the dimension for which to get member properties	Path	Yes	None
member	Name of the member for which to get member properties	Path	Yes	None

Request Payload:

The following table summarizes the payload parameters.

Name	Description
name	Name of the member, such as North America
children	Whether the member has children
description	Description of the member
parentName	Name of the parent, such as Enterprise Global
dataType	Data type, if available
objectType	Type of object
dataStorage	Storage attribute for the member, such as STOREDATA
dimName	Dimension name
twoPass	Boolean value to indicate whether the member has the Two-Pass Calculation associated attribute

Table 8-48 Parameters

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/dimensions/ Entity/North America

{"memberName":"North America","parentName":"Enterprise Global"}

Example of Response Body

Sample response body where the member is added successfully

```
{
    "name": "North America",
    "children": null,
    "description": null,
    "parentName": "Enterprise Global",
    "dataType": "UNSPECIFIED",
    "objectType": 33,
    "dataStorage": "STOREDATA",
    "dimName": "Entity",
    "twoPass": false,
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
Vision/dimensions/Entity/members/North%20America",
        "action": "GET"
    }]
}
```

Get Applications

This REST API returns a list of applications to which the specified user is assigned. It also provides certain key information about the application.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api version}/applications

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-49 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None

Response

Supported Media Types: application/json

Parameters:



Name	Description
Items	A list of applications
name	Application name
type	Product type. Possible values: HFM, HP
adminMode	Indicates if the application's login level is set to Administrators. Returns a Boolean value where true indicates that the login level for the application is set to Administrators and false indicates that the login level is set to All Users.
theme	Current theme of the application. Possible values:
	 REDWOOD_ORACLE_R13 REDWOOD_LIGHT_R13 REDWOOD_DARK_R13
webBotDetails	Web bot details of the application
webBotAppId	Web bot application ID register for the application
dpEnabled	Indicates if decision package is enabled in the application. Returns a Boolean value true when enabled.
unicode	Indicates if the application is Unicode enabled. Returns a Boolean value where true indicates that the application is Unicode enabled.
appStorage	Returns the storage type of the application, such as Default, Multidim, or ASO.
аррТуре	Business process type. Possible values are PBCS, EPBCS, and so on.
hybrid	Indicates if the hybrid configuration is enabled in the application. Returns a Boolean value true when enabled.

Table 8-50Parameters

Example of Response Body

```
{
    "type": "HP",
    "items": [
        {
            "appType": "PBCS",
            "webBotDetails": "null",
            "helpServerUrl": "https://www.oracle.com",
            "workpaceServerUrl": "https://<BASE-URL>",
            "appStorage": "Multidim",
            "unicode": true,
            "name": "Vision",
            "type": "HP",
            "adminMode": "true",
            "theme": "REDWOOD_LIGHT_R13",
            "hybrid": "true"
        }
    ],
```

```
"links": [
{
"rel": "self",
"href": "https://<BASE-URL>",
"action": "GET"
}
]
}
```

Manage Planning Units

You can manage planning units using a set of REST resources, as summarized here.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

For detailed information on managing planning units, see Managing Approvals.

Note: The manage planning unit resources use the parameters puldentifier and puhldentifier:

- puIdentifier: Planning unit identifier
- puhIdentifier: Planning unit hierarchy identifier

Use the following format for these parameters:

puIdentifier:

"scenarioName"::"versionName"::"pmMember"

• pmMember:

"Entity: SecondaryMember"

• puhIdentifier

"scenarioName"::"versionName"

Table 8-51 Managing Planning Units

Task	Reque st	REST Resource
List All Planning Units	POST	<pre>/HyperionPlanning/rest/{version}/applications/ {application}/planningunits? q={"scenario":"scenarioName","version":"versionName"}&of fset=10&limit=10</pre>
Get Planning Unit History and Annotations	GET	<pre>/HyperionPlanning/rest/{api_version}/applications/ {application}/planningunits?q={"scenario": {"scenario"},"version": {"version"}}&offset={offset}&limit={limit}</pre>
Get a Planning Unit Owner Photo	GET	/HyperionPlanning/rest/{api_version}/applications/ {application}/users/{userId}/photo
Get Planning Unit Promotional Path	GET	<pre>/HyperionPlanning/rest/{api_version}/applications/ {application}/planningunits/{puIdentifier}/promotionpath</pre>



Table 8-51 (Cont.) Managing Planning Units

Task	Reque st	REST Resource
Get Available Planning Unit Actions	GET	<pre>/HyperionPlanning/rest/{api_version}/applications/ {applicationName}/planningunits{puhIdentifier}/ availableactions</pre>
Get Filters with All Possible Values	GET	/HyperionPlanning/rest/{api_version}/applications/ {application}/pufilters
Change Planning Unit Status	POST	/HyperionPlanning/rest/{api_version}/applications/ {application}/planningunits/{puhIdentifier}/actions

List All Planning Units

You can use REST APIs to return a list of planning units for the specified application and owned by the user initiating the REST API. (Note that this does not return all planning units for all applications and users.)

Paging is supported if the optional offset and limit parameters are provided.

Required Roles

Service Administrator

REST Resource

POST

```
/HyperionPlanning/rest/{version}/applications/{application}/planningunits?
q={"scenario":"scenarioName","version":"versionName"}&offset=10&limit=10
```

Request

Supported Media Types: application/x-www-form-urlencoded

Parameters:

The following table summarizes the client request.

Table 8-52 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
q	Paging options for planning units. Possible values are described in the following rows.	Query	No	Limit = 25
scenario	Scenario for the application; required	Query	No	None
version	Version for the application; required	Query	No	None
offset	Indicates the actual index from which the records are returned; 0 based.	Query	No	1
limit	Controls how many items to return; defaults to 25 if not specified.	Query	No	25

Request Payload:



The following table summarizes the payload parameters.

Name	Description	Туре	Required
filter	Name, type, and values to filter on. Example:	Payload	No
	<pre>filter={name:"SubStatus",type: values:[0,4]}</pre>	3,	

Table 8-53 Parameters

Example URL and Payload

```
https://<BASE-URL>/HyperionPlanning/rest/{version}/applications/{application}/
planningunits?
```

```
q={"scenario":"scenarioName","version":"versionName"}&offset=10&limit=10
```

Example without filters:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/planningunits? q={"scenario":"Forecast","version":"BU Version 1"}

Example with two filters, multiple values provided:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/planningunits? q={"scenario":"Forecast","version":"BU Version 1"}

Payload:

```
filter={name:"Status",type:4,values:
[2,5]}&filter={name:"SubStatus",type:3,values:[0,4]}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description
name	Planning unit name, such as Marketing
value	Planning unit value
owner	Planning unit owner, such as Admin
version	Planning unit version, such as BU Version_1
entity	Planning unit entity, such as Marketing
status	Planning unit status, such as Under Review
scenario	Planning unit scenario, such as Forecast
Formatted value	Formatted value, if any
puName	Planning unit name, such as Marketing
subStatus	Planning unit substatus
secMember	Secondary dimension member, if any
puAlias	Planning unit alias, such as Marketing
versionAlias	Version alias, if any

Table 8-54 Parameters



Example of Response Body

```
{
    "items": [{
        "name": null,
        "value": -1.0,
        "owner": "admin",
        "version": "BU Version 1",
        "entity": "Marketing",
        "status": "Under Review",
        "scenario": "Forecast",
        "formattedValue": "",
        "puName": "Marketing",
        "subStatus": "",
        "secMember": null,
        "puAlias": "Marketing",
        "scenarioAlias": null,
        "versionAlias": null,
        "puId": 50410,
        "links": [{
            "rel": "promotion-path",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/
%22Forecast%22::%22BU%20Version 1%22::%22Marketing%22::%22%22/promotionpath",
            "action": "GET"
        }, {
            "rel": "annotations-and-history",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/
%22Forecast%22::%22BU%20Version 1%22::%22Marketing%22::%22%22/
historyandannotations?q=%7B%22annotSeq%22:-1,%22loqSeq%22:-1%7D",
            "action": "GET"
        }, {
            "rel": "actions",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/%22Forecast%22::%22BU%20Version 1%22/actions",
            "action": "POST",
            "data": {
                "pmMembers": "Marketing"
        }, {
            "rel": "change-status",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/
%22Forecast%22::%22BU%20Version 1%22::%22Marketing%22::%22%22/actions/6",
            "action": "POST",
            "data": {
                "pmMembers": "Marketing",
                "comments": "comments"
            }
        }]
    }],
    "links": [{
        "rel": "self",
```

```
"href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits?
q=%7Bscenario:%22Forecast%22,version:%22BU+Version 1%22%7D",
        "action": "POST",
        "data": {
            "filter": [{
                "name": "Status",
                "type": 4,
                "values": [2, 5],
                "defIndex": 0
            }, {
                "name": "SubStatus",
                "type": 3,
                "values": [0, 4],
                "defIndex": 0
            }]
        }
    }],
    "type": "HP"
}
```

Get Planning Unit History and Annotations

You can use REST APIs to return a merged list of history and annotations for the planning unit that the requesting user owns for the specified Scenario, Version, and PM Member.

If both annotSeq and logSeq are < 0, parent level nodes are returned. If annotSeq or logSeq is provided, the replies to that annotation or history are returned respectively.

If both annotSeq and logSeq are < 0, parent level nodes are returned. If annotSeq or logSeq is provided, the replies to that annotation or history are returned respectively.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
planningunits/{puIdentifier}/historyandannotations?
q={annotSeq=-1,logSeq=-1}&offset=10&limit=10
```

Request

Supported Media Types: application/x-www-form-urlencoded

Parameters:

The following table summarizes the client request.

Table 8-55 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
scenario	Scenario for the application; required	Path	Yes	None



Table 8-55 (Cont.) Parameters

Name	Description	Туре	Required	Default
version	Version for the application; required	Path	Yes	None
pmMember	Entity; secondary member	Path	Yes	None
offset	Indicates the actual index from which the records are returned; 0 based.	Query	No	1
limit	Controls how many items to return; defaults to 25 if not specified.	Query	No	25

Example URL and Payload

```
https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/planningunits/
Forecast::"BU Version_1"::Marketing::/historyandannotations?
q={annotSeq:-1,logSeq:-1}
```

Filter can include name, type, and values to filter on. For example: filter={name:"SubStatus", type:3, values:[0,4]}

Response

Supported Media Types: application/x-www-form-urlencoded

Parameters:

Name	Description
comment	Comment entered by the planning unit owner when performing an action
hasHistory	True if the planning unit has history
logSeq	Sequence of the action performed on the planning unit
staticImage	Whether a static image exists for this note
authorImagePath	The path to the user image for the user who performed the action
commentTitle	The author name and the action the author performed
commentDate	The date when the action was performed or the annotation was added
commentSubTitle	Processing state of the planning unit when the action was performed
parentAnntSeq	Sequence of the annotation or the parent annotation added to the planning unit
isChildNode	true if this is a reply to an annotation

Table 8-56 Parameters

Example of Response Body

```
{
    "items": [{
        "comment": "Enough justification provided, Approving it.",
```



```
"hasHistory": false,
        "logSeq": -1,
        "staticImage": true,
        "authorImagePath": "/Images/GhostUser.png",
        "commentTitle": "admin",
        "commentDate": "8/22/14 3:41 PM",
        "commentSubTitle": "",
        "parentAnntSeq": 1,
        "isChildNode": false,
        "links": [{
            "rel": "annotation-replies",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/%22Forecast%22::%22BU%20Version 1%22::%22Marketing%22::/
historyandannotations?q=%7B%22annotSeq%22:1,%22loqSeq%22:-1%7D",
            "action": "GET"
        }]
    }, {
        "comment": "",
        "hasHistory": true,
        "logSeg": 2,
        "staticImage": true,
        "authorImagePath": "/Images/GhostUser.png",
        "commentTitle": "Originate by admin",
        "commentDate": "4/22/14 12:26 PM",
        "commentSubTitle": "Under Review",
        "parentAnntSeq": -1,
        "isChildNode": false,
        "type": "HP",
        "links": [{
            "rel": "annotation-replies",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/%22Forecast%22::%22BU%20Version 1%22::%22Marketing%22::/
historyandannotations?q=%7B%22annotSeq%22:-1,%22loqSeq%22:2%7D",
            "action": "GET"
        }1
    }, {
        "comment": "",
        "hasHistory": true,
        "logSeg": 1,
        "staticImage": true,
        "authorImagePath": "/Images/GhostUser.png",
        "commentTitle": "Originate by admin",
        "commentDate": "4/22/14 12:26 PM",
        "commentSubTitle": "Under Review",
        "parentAnntSeq": -1,
        "isChildNode": false,
        "type": "HP",
        "links": [{
            "rel": "annotation-replies",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/%22Forecast%22::%22BU%20Version 1%22::%22Marketing%22::/
historyandannotations?q=%7B%22annotSeq%22:-1,%22loqSeq%22:1%7D",
            "action": "GET"
        }]
   }],
"type": "HP",
```

```
"links": [{
    "rel": "self",
    "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/
%22Forecast%22::%22BU%20Version_1%22::%22Marketing%22::%22%22/
historyandannotations?q=%7B%22annotSeq%22:-1,%22logSeq%22:-1%7D",
    "action": "GET"
    }],
    "type": "HP",
}
```

Get a Planning Unit Owner Photo

You can use REST APIs to get an image for the requested planning unit owner if a photo is uploaded for the owner.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/users/ {userId}/photo

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-57 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
userID	The identifier of the user for whom to retrieve a photo	Path	Yes	

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/users/5000100/
photo

Response

Supported Media Types: In case of success, returns application/octet-stream. In case of error, returns application/json.

Error Response:



Name	Description
detail	Detail about the status of the planning unit photo for this user. For example: PU photo not available, make sure that a valid user identifier is provided.
status	HTTP status, such as 400.
message	Informational message about the status of the photo for this user.
localizedMessage	A localized informational message about the status.

Table 8-58 Parameters

Example of Error Response Body

The following shows an example of the response body in JSON format.

```
{
    "detail": "PU photo not available, make sure the a valid user identifier
is provided.",
    "status": 400,
    "message": "java.lang.RuntimeException: PU photo not available, make sure
the a valid user identifier is provided.",
    "localizedMessage": "java.lang.RuntimeException: PU photo not available,
make sure the a valid user identifier is provided."
}
```

Get Planning Unit Promotional Path

You can use REST APIs to get a list of promotion path nodes for a given application, user, and planning unit. The planning unit is identified by the provided scenario, version, and PM member.

The list can have up to three nodes: the node before the current location, the node at the current location, and the one after the current location. If the planning unit is at the starting location or the last location in the path, only two nodes are returned.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/
planningunits{puIdentifier}/promotionpath

Request

Parameters:

The following table summarizes the client request.

Table 8-59 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None



Table 8-59 (Cont.) Parameters

Name	Description	Туре	Required	Default
application	The name of the application	Path	Yes	None
puIdentifier	The name of the planning unit, such as Sales	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/planningunits/ Forecast::"BU Version 1"::Dev/promotionpath

Response

Supported Media Types: application/json

Parameters:

Table 8-60 Parameters

Name	Description
Items	Planning unit promotional path information
name	Name of the planning unit
ownerType	Planning unit owner type
group	Returns whether the owner is a group of users or an individual users, true or false
staticImage	Returns whether the image is a static manage, true or false
nodeImagePath	Path to the planning unit owner photo
ownerName	Name of the planning unit owner
currentLoc	Returns if this is the current location of the planning unit, true or false

Example of Response Body

```
{
    "items": [{
        "name": "ent_111: Regular Coke",
        "ownerType": 0,
        "group": false,
        "staticImage": true,
        "nodeImagePath": "../ui themes/tadpole/images product/pm/75X89/
PUOwner.png",
        "ownerName": "Planner1",
        "currentLoc": true
    }, {
        "name": "Total Entity",
        "ownerType": 0,
        "group": false,
        "staticImage": false,
        "nodeImagePath": "v3/applications/PS4app1/puphoto?app0wner=50001",
```

```
"ownerName": "admin",
    "currentLoc": false
}],
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/Forecast::%22BU%20Version_1%22::Dev/promotionpath",
        "action": "GET"
    }],
}
```

Get Available Planning Unit Actions

You can use REST APIs to return a list of the next set of applicable actions available for the planning units, consisting of the specified scenario, version, and PM Members (Entity: Secondary member) that are owned by the requesting user.

Required Roles

Service Administrator

REST Resource

POST

```
/HyperionPlanning/rest/{api_version}/applications/{application}/
planningunits{puhIdentifier}/availableactions
```

Request

Parameters:

The following table summarizes the client request.

Table 8-61 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
puIdentifier	The name of the planning unit, such as Sales	Path	Yes	None
q	Optionally, return limited or full approvals functionality. Options are listed here.	Query	No	None
0	Returns limited approvals functionality - useful for mobile clients	Query	No	None
1	Returns full approvals functionality; default is 1.	Query	No	None

URL and Payload Examples

https://<BASE-URL>/rest/v3/applications/PS4app1/planningunits/Forecast::"BU
Version 1"/availableactions?q={"options":1}

Payload examples:

pmMembers=pmMemberNames

pmMembers=Dev, Marketing



Response

Supported Media Types: application/json

Parameters:

Table 8-62 Parameters

Name	Description
Items	Planning unit available actions
actionId	ID of the action
Name	Name of the action

Example of Response Body

```
{
    "items": [{
        "actionId": 6,
        "name": "Promote"
    }, {
        "actionId": 3,
        "name": "Sign Off"
    }, {
        "actionId": 1,
        "name": "Reject"
    }, {
        "actionId": 7,
        "name": "Delegate"
    }, {
        "actionId": 8,
        "name": "Take Ownership"
    }, {
        "actionId": 9,
        "name": "Originate"
    }, {
        "actionId": 10,
        "name": "Freeze"
    }],
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4 HP2/planningunits/Current::%22BU%20Version 1%22/availableactions?
q=%7Boptions:1%7D",
        "action": "GET",
        "data": {
            "pmMembers": "ent 111: Regular Coke"
        }
    }],
}
```



Get Filters with All Possible Values

Returns all filter types with all possible values by which users can filter planning units for a given application. For every value, there is a label (in the client locale) representation and an integer value. The labels are shown to end users to pick from, but whenever possible, the client should submit the integer value that is unique to the server. Every application supports several types of filters that are indicated by the type field.

Name is optional. The defIndex is the index in the value array for the default selection value.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/pufilters

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-63 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
d	Optionally, return filters for limited or full functionality. Options are listed here.	Query	No	None
0	Returns filters for limited Approvals functionality - useful for mobile clients.	Query	No	None
1	Returns filters for full Approvals functionality; default is 1.	Query	No	None

Example URL

https://<BASE-URL>-/HyperionPlanning/rest/v3/applications/PS4app1/pufilters?
q={"options":"0"}

Response

Supported Media Types: application/json

Parameters:

Name	Description	
Names	Planning unit available actions	
aliases	Aliases for values to be displayed instead of labels if user preference is defined as such	
name	Name for the filter	



Name	Description
type	Type of the filter
values	Integer values; usually the client will submit this value to indicate the selected filter
labels	Labels for values to be displayed in the client for the filter
defIndex	Index of the value to be displayed as the default value

Table 8-64 (Cont.) Parameters

Example of Response Body

```
{
    "items": [{
        "aliases": ["Forecast"],
        "name": "Scenarios",
        "type": 1,
        "values": [50218],
        "labels": ["Forecast"],
        "defIndex": 0
    }, {
        "aliases": ["BU Version 1"],
        "name": "Versions",
        "type": 2,
        "values": [1500],
        "labels": ["BU Version_1"],
        "defIndex": 0
    }, {
        "aliases": null,
        "name": "SubStatus",
        "type": 3,
        "values": [0, 1, 2, 3, 4, 10008, 10009, 10000],
   "labels": ["", "Processing", "Aborted", "Validating", "No Additional
Approval Required", "Invalid Data", "Additional Approval Required", "Failed"],
        "defIndex": 0
    }, {
        "aliases": null,
        "name": "Status",
        "type": 4,
        "values": [2, 3, 4, 5, 6],
        "labels": ["Under Review", "Approved", "Signed Off", "Not Signed
Off", "Frozen"],
        "defIndex": 0
    }],
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/pufilters?q=%7Boptions:%220%22%7D",
        "action": "GET"
    }],
}
```

Change Planning Unit Status

You can use REST APIs to change the status of the planning units consisting of the specified scenario, version, and PM Members (Entity: Secondary member) that are owned by the requesting user.

An error will display if the planning units belong to same hierarchy but different levels, or if the statuses for the planning units are not the same.

Supported actions for limited approvals functionality are: "PROMOTE" (6), "SIGN_OFF" (3), "APPROVE" (2), "DELEGATE" (7), "TAKE_OWNERSHIP" (8), "ORIGINATE" (9), "FREEZE" (10)

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
planningunits/{puhIdentifier}/actions
```

Request

Supported Media Types: application/x-www-form-urlencoded

Parameters:

The following table summarizes the client request.

Table 8-65 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/planningunits/
Forecast::"BU Version 1"/actions

Payload

actionId=actionId&pmMembers=pmMemberNames&comments=comments

Response

Supported Media Types: application/json

Example of Response Body

```
{
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/planningunits/Forecast::%22BU%20Version_1%22/actions",
```

```
"action": "POST",
   "data": {
        "pmMembers": "\"Dev\"",
        "action": "PROMOTE",
        "comments": "\"Promoting the PU\""
   }
}]
```

Get User Preferences

}

Returns the requesting user's display preferences.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/{api_version}/applications/{application}/
userpreferences

Request

Parameters:

The following table summarizes the client request.

Table 8-66 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
userpreferences	The requesting user's display preferences	path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/PS4app1/userpreferences

Response

Supported Media Types: application/json

Table 8-67 Parameters

ame Description	
decimal separator	Preference for decimal separator
scale	Preference for scale
thousandsSeparator	Preference for the thousands separator



Name	Description
thousandsSeparator	Preference for the style of negative numbers
negativeStyle	Preference for the minimum precision
minPrecision	Preference for the minimum precision
maxPrecision	Preference for the maximum precision
showPUAlias	Preference for showing the planning unit alias
currSymbol	Preference for the currency symbol
type	The type of application, such as HP

Table 8-67 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "decimalSeparator": "",
    "scale": 0,
    "thousandsSeparator": "",
    "negativeStyle": 255,
    "minPrecision": 0,
    "maxPrecision": 0,
    "showPUAlias": false,
    "currSymbol": "",
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
PS4app1/userpreferences",
        "action": "GET"
    }]
}
```

Working with Data Slices

You can import, export, and clear data slices, as summarized here. Note that attribute dimensions are not supported in the payload.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Task	Request	REST Resource
Import Data Slice	POST	<pre>/HyperionPlanning/rest/{api_version}/applications/ {application}/plantypes/{plantype}/importdataslice</pre>
Export Data Slice	POST	<pre>/HyperionPlanning/rest/{api_version}/applications/ {application}/plantypes/{plantype}/exportdataslice</pre>
Clear Data Slice	POST	/HyperionPlanning/rest/{api_version}/applications/ {application}/plantypes/{plantype}/cleardataslice

Table 8-68Working with Data Slices

Import Data Slices

Can be used to import data given a JSON data grid with a point of view, columns, and one or more data rows. Data will be imported only for cells that the user has read-write access to. Imports data of types Text, Date and Smart List along with numeric data. Returns JSON with details on the number of cells that were accepted, the number of cells that were rejected, and the first 100 cells that were rejected. You can set custom parameters to view rejected cells to understand the reason for the rejection.

Required roles

Service Administrator

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/plantypes/
{plantype}/importdataslice

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-69 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to import the data slice	Path	Yes	None
plantype	Name of the plan type for which to import the data slice	Path	Yes	None

Example URL and Payload:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/plan1/
importdataslice
Payload Parameters

The Payload is JSON with the following parameters.

Table 8-70 Parameters

Name	Description
dataGrid	JSON data grid



Name	Description		
aggregateEssbaseData	True or false.		
	If true, the values being saved will be added to the existing values. Only numeric values can be aggregated. Cells with Smart list, Text and Date data types will be rejected.		
	If false, the data values will be overwritten. A value of "#missing" will clear the cell value as shown in the example. The default is false.		
	Note : Values provided in the "data" section of the JSON payload will be used even for cells with supporting details provided. For cells with supporting details, make sure the total calculated for the incoming supporting details matches the value provided in the row "data" section.		
	See the following table for examples.		
cellNotesOption	Possible values are: "Overwrite", "Append", and "Skip".		
-	 "Overwrite": The existing cell notes will be overwritten. An empty array for cell notes [] will indicate deletion of existing cell notes. A value of "null" will leave the existing cell notes intact. "Append": New cell notes will be appended to existing cell notes. "Skip": Cell notes will not be processed. 		
dateFormat	Date format used in the input data grid. Valid formats are: "MM-DD- YYYY", "DD-MM-YYYY", "YYYY-MM-DD", "MM/DD/YYYY", "DD/MM/ YYYY", "YYYY/MM/DD"		
strictDateValidation	Optionally, influence how Date cell values are validated. When set to true, date values are validated against the dateFormat specified in the payload and are rejected if the format for the value does not conform to the dateFormat. If set to false, date values are interpreted more leniently. Default is true.		
customParams			
PostDataImportRuleNames	Optionally, provide the post data import rule names. This is primarily used by Data Management for planners. Default is false.		
includeRejectedCells	Optionally, indicate if the response should include the first 100 rejected cells. Default is true.		
includeRejectedCellsWith Details	Optionally, indicate if the response should include the reasons why cells are rejected. Default is false.		

Table 8-70 (Cont.) Parameters

Table 8-71 Import Data Slice Examples

Source Cell	Target Cell	Resulting Target Cell
Supporting Detail (SD)	#missing	SD
SD	Value	Add SD value to the existing value, do not add SD
Value	SD	Delete SD, add Value to the existing value
SD1	SD2	Delete SD2, add SD value to the existing value, do not add SD1

Sample payload:

```
{
```

"aggregateEssbaseData":true,
"cellNotesOption":"Overwrite",

```
"dateFormat":"DD/MM/YYYY",
   "strictDateValidation":true,
    "dryRun": true,
    "customParams":{
        "PostDataImportRuleNames":"Post data rule 1, \"post, data rule
2\"",
        "IncludeRejectedCells":true,
        "IncludeRejectedCellsWithDetails":true
    },
```

Supported Media Types: application/json

JSON Output

The rejected cells consist of cells that the user does not have read-write access to; cells where row or column member names are invalid and do not exist; cells where the data is invalid (for example, an invalid Smart List value); and cells that are non-numeric (Smart List, Text, or Date type) with data when <code>aggregateEssbaseData</code> is set to true.

{

"numAcceptedCells": 3,

"numRejectedCells": 9,

```
"rejectedCells": ["[BaseData, FY15, Plan, Working, 410, P_160, Jan, Project
Number]", "[BaseData, FY15, Plan, Working, 410, P_160, Feb, Project Number]",
"[BaseData, FY15, Plan, Working, 410, P_160, Mar, Project Number]", "[BaseData,
FY15, Plan, Working, 410, P_160, Jan, Request Date]", "[BaseData, FY15, Plan,
Working, 410, P_160, Feb, Request Date]", "[BaseData, FY15, Plan, Working, 410,
P_160, Mar, Request Date]", "[BaseData, FY15, Plan, Working, 410,
P_160, Mar, Request Date]", "[BaseData, FY15, Plan, Working, 410,
Project Type]", "[BaseData, FY15, Plan, Working, 410, P_160, Feb, Project Type]",
"[BaseData, FY15, Plan, Working, 410, P_160, Mar, Project Type]"],
```

Export Data Slices

Use this REST API to export data for a specified region.

The exported data will be in the form of a JSON grid with pov, columns, and 0 or more data rows. Data will be exported only for cells for which the user has read-write access.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/plantypes/
{plantype}/exportdataslice
```

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.



Table 8-72 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to export the data slice	Path	Yes	None
plantype	Name of the plan type for which to export the data slice	Path	Yes	None

Example URL and payload:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/plan1/
exportdataslice
Payload Parameters

The Payload is JSON with the following parameters.

Name	Description
gridDefinition	JSON grid definition to define the region
exportPlanningData	True or false. Optionally, you can provide the parameter exportPlanningData, which, when set to true, will export supporting details and cell notes along with Essbase numeric data. Default is false.
suppressMissingBlocks	True or false. Optionally, you can set suppressMissingBlocks to true to suppress blocks with missing data.
suppressMissingRows	True or false. Optionally, you can set suppressMissingRows to true to suppress rows with missing data.
suppressMissingColumns	True or false. Optionally, you can set suppressMissingColumns to true to suppress rows with missing data.

Table 8-73 Parameters

Supported Media Type: application

Sample Payload

Example 1: Providing dimension names as follows in the gridDefinition is recommended and is more efficient.

```
{
    "exportPlanningData": false,
    "gridDefinition": {
        "suppressMissingBlocks": true,
        "pov": {
            "dimensions": [
              "HSP_View",
              "Year",
              "Scenario",
              "Version",
              "Entity",
              "Product"
        ],
```



```
"members": [
      [
         "BaseData"
      ],
      [
         "FY15"
      ],
      [
         "Plan"
      ],
      [
         "Working"
      ],
      [
         "410"
      ],
      [
         "P_160"
      ]
   ]
},
"columns": [
   {
      "dimensions": [
       "Period"
      ],
      "members": [
       [
           "IDescendants(Q1)"
         1
      ]
   },
   {
      "dimensions": [
         "Period"
      ],
      "members": [
        [
            "IDescendants(Q2)"
         ]
      ]
   }
],
"rows": [
   {
      "dimensions": [
        "Account"
      ],
      "members": [
         [
            "Project Number",
            "Request Date",
            "Project Type",
            "Project Investment"
         ]
      ]
```

}] }

OR

No dimension names provided is less efficient:

```
{
   "exportPlanningData": true,
   "gridDefinition": {
     "suppressMissingBlocks": true,
      "pov": {
         "members": [
            ["BaseData"], ["FY15"], ["Plan"], ["Working"], ["410"],
["P_160" ]
         ]
      },
      "columns": [
         {
            "members": [
               [
                  "IDescendants(Q1)"
               ]
            ]
         },
         {
            "members": [
               [ "IDescendants(Q2)" ]
            ]
         }
     ],
      "rows": [
         {
            "members": [
               [
                  "Project Number",
                  "Request Date",
                  "Project Type",
                  "Project Investment"
               ]
            ]
         }
     ]
   }
}
```

JSON Output



The following shows an example of the response body with exportPlanningData : true.

```
"pov": [
   "BaseData",
   "FY15",
   "Plan",
   "Working",
   "410",
   "P 160"
],
"columns": [
   [
      "Jan",
      "Feb",
      "Mar",
      "Q1",
      "Apr",
      "May",
      "Jun",
      "Q2"
   ]
],
"rows": [
   {
      "headers": [
         "Project Number"
      ],
      "data": [
         "1",
          "2",
          "3",
          " ",
          " ",
          " ",
          "",
          .....
      ],
      "cellNotes": [
          [
             {
                "contents": "Internal Project<br/>
             },
             {
                "contents": "Project delayed<br/>
             }
          ],
          [],
          [],
          [],
          [],
          [],
          [],
          []
```



{

```
]
      },
      {
          "headers": [
             "Request Date"
          ],
          "data": [
             "",
             "",
"",
             "",
"",
             "",
             "",
             ....
          ]
      },
      {
          "headers": [
             "Project Type"
          ],
          "data": [
             "Other",
             "IT",
             "Construction",
             "",
"",
             "",
             "",
""
          ]
      },
      {
          "headers": [
             "Project Investment"
          ],
          "data": [
             "100000",
             "110000",
             "200000",
             "410000",
             "",
             "",
             "",
""
          ],
          "cellNotes": [
             [],
             [
                {
                    "contents": "Internal + External investments made
here.<br/>"
                }
             ],
             [],
             [],
```



```
[],
         [],
         [],
         []
      ],
      " supportingDetail": [
         null,
         {
             "items": [
                {
                   "value": "60000",
                   "position": 0,
                   "label": "Internal",
                   "generation": 0,
                   "operator": "+"
                },
                {
                   "value": "50000",
                   "position": 1,
                   "label": "External",
                   "generation": 0,
                   "operator": "+"
                }
            ]
         },
         null,
         null,
         null,
         null,
         null,
         null
      ]
   }
]
```

Example 2: Suppress missing blocks, rows, and columns when exporting a data slice:

```
{
    "exportPlanningData": false,
    "gridDefinition": {
        "suppressMissingBlocks": true,
        "suppressMissingColumns": true,
        "pov": {
            "dimensions": [
               "HSP_View",
               "Year",
               "Scenario",
               "Version",
               "Entity",
               "Product"
               "Product"
               "Start and start and star
```



}

```
],
   "members": [
     [
        "BaseData"
      ],
      [
         "FY15"
      ],
      [
         "Plan"
      ],
      [
         "Working"
      ],
      [
         "410"
      ],
      [
         "P_160"
      ]
   ]
},
"columns": [
   {
      "dimensions": [
       "Period"
      ],
      "members": [
        [
         "IDescendants(Q1)"
         ]
      ]
   },
   {
      "dimensions": [
         "Period"
      ],
      "members": [
       [
           "IDescendants(Q2)"
         ]
      ]
   }
],
"rows": [
  {
      "dimensions": [
        "Account"
      ],
      "members": [
         [
            "Project Number",
            "Request Date",
            "Project Type",
            "Project Investment"
         ]
```

```
]
         }
     ]
   }
}
JSON Output:
{
   "pov": [
      "BaseData",
      "FY15",
      "Plan",
      "Working",
      "410",
      "P 160"
  ],
   "columns": [
      [
         "Jan",
         "Feb",
         "Mar",
         "Q1",
         "Apr",
         "May",
         "Jun",
         "Q2"
      ]
  ],
   "rows": [
      {
         "headers": [
            "Project Number"
         ],
         "data": [
            "1",
            "2",
            "3",
            ]
      },
      {
         "headers": [
           "Project Type"
         ],
         "data": [
            "Other",
            "IT",
            "Construction",
            ....
         ]
      },
```



Example payload with multiple dimensions:

```
{
   "exportPlanningData": false,
   "gridDefinition": {
      "suppressMissingBlocks": true,
      "pov": {
         "dimensions": [
            "HSP View",
            "Scenario",
            "Version",
            "Product"
         ],
         "members": [
            [
               "BaseData"
            ],
            [
               "Plan"
            ],
            [
                "Working"
            ],
            [
                "P 160"
            ]
         ]
      },
      "columns": [
         {
            "dimensions": [
               "Year", "Period"
            ],
            "members": [
                [
                   "FY19"
               ],
                [
                   "IDescendants(Q1)"
```



```
]
            ]
         },
         {
            "dimensions": [
               "Year", "Period"
            ],
            "members": [
              [
                  "FY20"
              ],
               [
                  "IDescendants(Q1)"
               ]
            ]
         }
     ],
      "rows": [
         {
            "dimensions": [
               "Entity", "Account"
            ],
            "members": [
               [
                  "410",
                  "420"
               ],
               [
                  "Project Number",
                  "Request Date",
                  "Project Type",
                  "Project Investment"
               ]
            ]
         },
         {
            "dimensions": [
              "Entity", "Account"
            ],
            "members": [
                [
                  "430"
               ],
               [
                  "Project Investment"
               ]
            ]
        }
     ]
  }
}
```



Clear Data Slices

Use this REST API to clear Planning and Essbase data for a specified region. In order to run this operation, the user must be an administrator.

Required Roles

Service Administrator

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/plantypes/
{plantype}/cleardataslice

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-74 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to export the data slice	Path	Yes	None
plantype	Name of the plan type for which to export the data slice	Path	Yes	None

Example URL and Payload:

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/plan1/ cleardataslice

Payload Parameters

The Payload is JSON with the following parameters.

Table 8-75 Parameters

Name	Description
gridDefinition	JSON grid definition to define the region
clearEssbaseData	True or false. If true, will clear Essbase numeric data. Default is true.
clearPlanningData	True or false. If true, will delete the cell notes, attachments, and supporting details. Default is false.

Sample Payload

Providing dimension names as follows in the gridDefinition is recommended and is more efficient.

{

"clearEssbaseData":true,



```
"clearPlanningData":false,
"gridDefinition" : {
"suppressMissingBlocks" : true,
"pov" : {
"dimensions" : [ "HSP_View", "Year", "Scenario", "Version", "Entity", "Product" ],
"members" : [["BaseData"], ["FY15"], ["Plan"], ["Working"], ["410"], ["P_160"]]
},
"columns" : [ {
"dimensions" : [ "Period" ],
"members" : [["IDescendants(Q1)"]]
}, {
"dimensions" : [ "Period" ],
"members" : [["IDescendants(Q2)"]]
}],
"rows" : [ {
"dimensions" : [ "Account" ],
"members" : [[ "Project Number", "Request Date", "Project Type", "Project Investment" ]]
}]
}
}
OR
No dimension names provided is less efficient:
{
"clearEssbaseData":true,
"clearPlanningData":false,
"gridDefinition" : {
"suppressMissingBlocks" : true,
"pov" : {
"members" : [["BaseData"], ["FY15"], ["Plan"], ["Working"], ["410"], ["P_160"]]
},
"columns" : [ {
"members" : [["IDescendants(Q1)"]]
}, {
"members" : [["IDescendants(Q2)"]]
```

}],

"rows" : [{

"members" : [["Project Number", "Request Date", "Project Type", "Project Investment"]]

}]

}

}

Response

Supported Media Types: application/json

JSON Output

The following shows an example of the response body with clearEssbaseData true and clearPlanningData false. There is one rejected cell due to the presence of supporting details because clearPlanningData is false:

{

"numClearedCells": 31,

"numRejectedCells": 1

"rejectedCells": ["Project Investment, Feb, BaseData, FY15, Plan, Working, 410, P_160"],

}

Getting and Setting Substitution Variables

You can use REST APIs to get and set substitution variables at the plan level and application level, as summarized here.

You can also use REST APIs to delete substitution variables. See Deleting Substitution Variables.

Required Roles

Service Administrator, Power User (with Rule Launch access)

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 8-76 Getting and Setting Substitution Variables

Task	Request	REST Resource
Get All Substitution Variables Defined for the Application	GET	<pre>/HyperionPlanning/rest/ {api_version}/applications/ {application}/ substitutionvariables</pre>
Get a Substitution Variable Defined for the Application	GET	/HyperionPlanning/rest/ {api_version}/applications/ {application}/ substitutionvariables/MyPeriod



Task	Request	REST Resource
Create or Update All Substitution Variables Defined for the Application	POST	/HyperionPlanning/rest/ {api_version}/applications/ {application}/ substitutionvariables
Get Substitution Variables Defined at the Plan Type Level	GET	/HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/substitutionvariables
Get Derived Substitution Variables at the Plan Type Level	GET	<pre>/HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/substitutionvariables? q={"derivedValues":true}</pre>
Get a Substitution Variable Defined at the Plan Type Level	GET	/HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/substitutionvariables/ CurrYear
Get a Derived Substitution Variable Defined at the Plan Type Level	GET	HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/substitutionvariables/ MyPeriod?q={"derivedValues":true}
Create and Update Substitution Variables at the Plan Type Level	POST	/HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/substitutionvariables

Table 8-76 (Cont.) Getting and Setting Substitution Variables

Get All Substitution Variables Defined for the Application

You can use REST APIs to retrieve all substitution variables defined for the application (all plan types).

Required Roles

Service Administrator, Power User (with Rule Launch access)

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
substitutionvariables
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.



Table 8-77 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/ substitutionvariables

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-78 Parameters

Name Description		
items	Collection of information about the resource	
name	Name of the substitution variable, such as CurrYear	
value	Value of the substitution variable, such as FY16	
planType	Plan type, such as Plan1, or ALL for all plan types	

Example of Response Body

The following shows an example of the response body.

```
{
    "items": [{
        "name": "CurrYear",
        "value": "FY16",
        "planType": "ALL"
    }, {
        "name": "CurrYear",
        "value": "FY17",
        "planType": "Plan2"
    },{
        "name": "CurrPeriod",
        "value": "Jan",
        "planType": "Plan1"
    }, {
        "name": "CurrPeriod",
        "value": "Feb",
        "planType": "ALL"
    }]
}
```



Get a Substitution Variable Defined for the Application

You can use REST APIs to retrieve a substitution variable defined for the application.

Required Roles

Service Administrator, Power User (with Rule Launch access)

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
substitutionvariables/CurrPeriod
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-79 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/ substitutionvariables/CurrPeriod

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-80 Parameters

Name	Description
name	Name of the substitution variable, such as CurrPeriod
value	Value of the substitution variable, such as Jan
planType	Plan type, such as Plan1, or ALL for all plan types

Example of Response Body

The following shows an example of the response body.

```
{
    "name": "CurrPeriod",
    "value": "Jan",
```



```
"planType": "ALL",
"links": [{
    "rel": "self",
    "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
vision/substitutionvariables/CurrPeriod",
    "action": "GET"
  }]
}
```

Create or Update All Substitution Variables Defined for the Application

Can be used to create or update substitution variables for the application.

Variables in the payload that exit in the application at the defined scope will be updated; new variables will be created at the defined scope.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
substitutionvariables
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-81 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/ substitutionvariables

Example Payload

With the following payload, CurrYear at the application level will be updated, and CurrPeriod will be created at the Plan3 level.

```
{
    "items": [{
        "name": "CurrYear",
        "value": "FY18",
        "planType": "ALL"
    }, {
        "name": "CurrPeriod",
        "
}
```

```
"value": "Dec",
"planType": "Plan3"
}]
```

}

Supported Media Types: application/json

Example of a successful response

```
Http status code: 204 (No content)
```

Example of an error response

Http status: 400

To confirm the results, you can go to the application to see the updates.

Get Substitution Variables Defined at the Plan Type Level

You can use REST APIs to retrieve a list of retrieve a list of substitution variables defined at the plan type level.

Required Roles

Service Administrator, Power User (with Rule Launch access)

Rest Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plantype}/substitutionvariables
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-82 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
plantype	The plan type for which to get substitution variables	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/Plan1/
substitutionvariables



Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-83 Parameters

Name	Description
items	Collection of information for the resource
name	Name of the substitution variable, such as CurrPeriod
value	Value of the substitution variable, such as Jan
planType	Name of the plan type, such as Plan1

Example of Response Body

The following shows an example of the response body.

```
{
    "items": [{
        "name": "CurrPeriod",
        "value": "Jan",
        "planType": "Plan1"
    }]
}
```

Get Derived Substitution Variables at the Plan Type Level

You can use REST APIs to retrieve a list of derived substitution variables at the plan type level.

Required Roles

Service Administrator, Power User (with Rule Launch access)

Rest Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plan}/substitutionvariables?q={"derivedValues":true}
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.



Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
plantype	Name of the plan type for which to get substitution variables	Path	Yes	None
d	Options for returning derived values, as described in the following row	Query	No	
derivedValues	If set to true, the derived list shows all variables available at run time to be used against the plan type. This includes variables defined at the application level and at the plan type level.	Query	No	derivedValues = true when getting derived substitution
	If a substitution variable with the same name is defined both at the plan type level and at the application level, the plan type level is returned.			variables

Table 8-84 Parameters

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/Plan1/
substitutionvariables?q={"derivedValues":true}

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-85 Parameters

Name	Description
items	Collection of information about the resource
name	Name of the substitution variable, such as CurrYear
value	Value of the substitution variable, such as FY16
planType	Name of the plan type, such as Plan1, or ALL for all plan types

Example of Response Body

The following shows an example of the response body.

```
{
    "items": [{
        "name": "CurrYear",
        "value": "FY16",
        "planType": "ALL"
    }, {
        "name": "CurrPeriod",
        "value": "Jan",
        "planType": "Plan1"
    }]
}
```



Get a Substitution Variable Defined at the Plan Type Level

You can use REST APIs to retrieve a substitution variable defined at the plan type level.

Required Roles

Service Administrator, Power User (with Rule Launch access)

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plantype}/substitutionvariables/CurrYear
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-86 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/vision/plantypes/plan1/
substitutionvariables/CurrYear

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-87 Parameters

Name	Description
name	Name of the substitution variable, such as CurrYear
value	Value of the substitution variable, such as FY16
planType	Name of the plan type, such as Plan1

Example of Response Body

The following shows an example of the response body.

```
{
    "name": "CurrYear",
    "value": "FY17",
```



```
"planType": "Plan1",
"links": [{
    "rel": "self",
    "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
vision/plantypes/plan1/substitutionvariables/CurrYear",
    "action": "GET"
  }]
}
```

Get a Derived Substitution Variable Defined at the Plan Type Level

You can use REST APIs to retrieve a derived substitution variable defined at the plan type level.

Required Roles

Service Administrator, Power User (with Rule Launch access)

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plan}/substitutionvariables/CurrPeriod?q={"derivedValues":true}
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-88 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
plan	Name of the plan type for which to get substitution variables	Path	Yes	None
q	Options for returning derived values. The value is described in the following row.	Query	No	derivedValues = false
derivedValues	true	Query	No	false
	If set to true, the derived list shows all variables available at run time to be used against the plan type. This includes variables defined at the application level and at the plan type level.			
	If a substitution variable with the same name is defined both at the plan type level and at the application level, the plan type level is returned.			

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/Plan1/
substitutionvariables?q={"derivedValues"=true}



Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 8-89 Parameters

Name	Description
items	Collection of information about the resource
name	Name of the substitution variable, such as CurrYear
value	Value of the substitution variable, such as FY16
planType	Name of the plan type, such as Plan1, or ALL for all plan types

Example of Response Body

The following shows an example of the response body.

```
{
    "name": "CurrPeriod",
    "value": "Jan",
    "planType": "ALL",
    "links": [{
        "rel": "self",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
vision/plantypes/plan1/substitutionvariables/CurrPeriod?
q=%7B%22derivedValues%22:true%7D",
        "action": "GET"
    }]
}
```

Create and Update Substitution Variables at the Plan Type Level

You can use REST APIs to create and update substitution variables at the plan type level. Variables in the payload that exist at the plan type level are updated. New variables are created at the plan type level.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plantype}/substitutionvariables
```

Request

Supported Media Types: application/json

Parameters



The following table summarizes the client request.

Table 8-90 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
plantype	Name of the plan type for which to get and set substitution variables	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/Plan1/
substitutionvariables

Response

Supported Media Types: application/json

Example of a successful response

```
Http status code: 204 (No content)
```

Example of an error response

Http status: 400

To confirm the results, you can go to the application to see the updates.

Deleting Substitution Variables

You can use REST APIs to delete substitution variables at the plan level and application level, as summarized here.

Before deleting substitution variables, you can use REST APIs to get information on what substitution variables are defined for the application or plan type. See Getting and Setting Substitution Variables.

Required Roles

Service Administrator

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Task	Request	REST Resource
Delete a Substitution Variable at the Plan Type Level	DELETE	<pre>/HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/substitutionvariables/ subvarname</pre>



Task	Request	REST Resource
Delete a Substitution Variable for the Application	DELETE	<pre>/HyperionPlanning/rest/ {api_version}/applications/ {application}/ substitutionvariables/subvarname</pre>
Delete Substitution Variables at the Plan Type Level	POST	<pre>/HyperionPlanning/rest/ {api_version}/applications/ {application}/plantypes/ {plantype}/ substitutionvariables:delete</pre>
Delete Substitution Variables for the Application	POST	/HyperionPlanning/rest/ {api_version}/applications/ {application}/ substitutionvariables:delete

Table 8-91 (Cont.) Deleting Substitution Variables

Delete a Substitution Variable at the Plan Type Level

Use this REST API to delete a substitution variable defined at the plan type level.

Before deleting substitution variables, you can use REST APIs to get information on what substitution variables are defined for the application or plan type. See Getting and Setting Substitution Variables.

Required Roles

Service Administrator

REST Resource

```
Delete /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plantype}/substitutionvariables/subvarname
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-92 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, v3	Path	Yes	None
plantype	The name of the plan type for which to delete the substitution variable	Path	Yes	None
subvarname	Name of the substitution variable to be deleted	Path	Yes	None

Example URL

The following URL will delete CurrPeriod at Plan1.



https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/Plan1/ substitutionvariables/CurrPeriod

Response

Supported Media Types: application/json

Example of a successful response

Http status code: 204 (No content)

Example of an error response

Http status: 400

Delete a Substitution Variable for the Application

Use this REST API to delete a substitution variable defined at the application level.

Before deleting substitution variables, you can use REST APIs to get information on what substitution variables are defined for the application or plan type. See Getting and Setting Substitution Variables.

Required Roles

Service Administrator

REST Resource

DELETE /HyperionPlanning/rest/{api_version}/applications/{application}/ substitutionvariables/subvarname

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-93 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, v3	Path	Yes	None
subvarname	The name of the substitution variable to be deleted	Path	Yes	None

Example URL

The following URL will delete CurrPeriod at the application level.

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/ substitutionvariables/CurrPeriod

Response

Supported Media Types: application/json



Example of a successful response

Http status code: 204 (No content)

Example of an error response

Http status: 400

Delete Substitution Variables at the Plan Type Level

Use this REST API to delete substitution variables at the plan type level. Variables in the payload that exist at the plan type level are deleted.

Before deleting substitution variables, you can use REST APIs to get information on what substitution variables are defined for the application or plan type. See Getting and Setting Substitution Variables.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
plantypes/{plantype}/substitutionvariables:delete
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-94 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, v3	Path	Yes	None
plantype	The name of the plan type for which to delete the substitution variables	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/plantypes/Plan1/
substitutionvariables:delete

Example Payload

{

The following payload will delete CurrYear and CurrPeriod at the Plan1 level.

```
"items": [{
"name": "CurrYear",
"value": "FY23",
"planType": "Plan1"
```



```
}, {
    "name": "CurrPeriod",
    "value": "Jan",
    "planType": "Plan1"
}]
```

1

Supported Media Types: application/json

Example of a successful response

Http status code: 204 (No content)

Example of an error response

Http status: 400

Delete Substitution Variables for the Application

Use this REST API to delete substitution variables defined for the application (for all plan types). Variables that exist at the plan type level or application level are deleted.

Before deleting substitution variables, you can use REST APIs to get information on what substitution variables are defined for the application or plan type. See Getting and Setting Substitution Variables.

Required Roles

Service Administrator

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
substitutionvariables:delete
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 8-95 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, v3	Path	Yes	None

Example URL

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/Vision/ substitutionvariables:delete



Example Payload

The following payload will delete CurrPeriod at the application level and CurrYear at Plan1.

```
{
    "items": [{
        "name": "CurrPeriod",
        "value": "Jan",
        "planType": "ALL"
    }, {
        "name": "CurrYear",
        "value": "FY23",
        "planType": "Plan1"
    }]
}
```

Response

Supported Media Types: application/json

Example of a successful response

Http status code: 204 (No content)

Example of an error response

Http status: 400

Example of Response Body

The following shows an example of the response body.

```
{
    "items": [{
        "name": "CurrYear",
        "value": "FY16",
        "planType": "ALL"
    }, {
        "name": "CurrYear",
        "value": "FY17",
        "planType": "Plan2"
    },{
        "name": "CurrPeriod",
        "value": "Jan",
        "planType": "Plan1"
    }, {
        "name": "CurrPeriod",
        "value": "Feb",
        "planType": "ALL"
    }]
}
```



Working with Connections

Use these REST APIs to work with connections.

With multiple environments, using REST APIs saves you time and effort by automating the process of logging in and configuring connections. For information about accessing environments, see Accessing EPM Cloud.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using these REST APIs requires prerequisites. See Prerequisites.

Task	Request	REST Resource
View a Connection	GET	<pre>/HyperionPlanning/rest/epm/{api_version}/ applications/{application}/connections/ {connectionRef}</pre>
View all Connections	GET	/HyperionPlanning/rest/epm/{api_version}/ applications/{application}/connections
Update a Connection	POST	/HyperionPlanning/rest/epm/{api_version}/ applications/{application}/connections/ {connectionRef}

Table 8-96 Working with Connections

View a Connection

Use this REST API to view details for a connection that is saved in an application.

Required Roles

Service Administrator

REST Resource

```
GET /HyperionPlanning/rest/epm/{api_version}/applications/{application}/
connections/{connectionRef}
```

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-97 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to view the connection	Path	Yes	None
connectionRef	The connection to view. The value can be either a connection name or ID.	Path	Yes	None

Supported Media Types: application/json

Payload Parameters:

The following table summarizes the parameters.

Table 8-98 Parameters

Parameters	Description
items	Collection of information about the resource
id	Unique identifier for the connection, such as 1c89922d-92ba-46c1-850f- e2a8a416ddf2
name	Name of the connection, such as Connection29
description	Description of the connection, such as Planning
url	The URL of the connection, such as https:// <service_name>- <tenant_name>.<service_type>.<dcx>.oraclecloud.com/ HyperionPlanning</dcx></service_type></tenant_name></service_name>
username	The username for the connection, such as admin
domain	The domain name for the connection
modified	The time stamp of the last modification to the connection details, such as 2021-01-18 12:23:49.0
modifiedBy	The last service administrator to modify the connection details, such as admin

Example Response

The identity domain information as shown as part of the response.

```
{
    "id": "f83b3da2-9505-415e-b7f7-3cf113cc94e4",
    "name": "Connection1",
    "description": "Test Connection",
    "url": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning",
    "username": "admin",
    "domain": "<DOMAIN NAME>",
    "modified": "2021-02-02 09:16:02.0",
    "modifiedBy": "admin",
    "links": [
        {
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/
rest/epm/v1/applications/epbcs1/connections/f83b3da2-9505-415e-
b7f7-3cf113cc94e4",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```



View All Connections

Use this REST API to view details for all of the connections saved in an application.

This API supports paging, so you can filter the number of connections you see in the output using the offset and limit parameters shown in the table.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/epm/{api_version}/applications/{application}/
connections

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-99 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to view connections	Path	Yes	None
offset	For paging of jobs. Indicates the actual index from which the records are returned. It is 0 based.	Query	No	0
limit	For paging for jobs. Controls how many items to return. Defaults to 25 if not specified.	Query	No	25

Example URL

https://<BASE-URL>/HyperionPlanning/rest/epm/v1/applications/epbcs1/connections?
offset=2&limit=2

Response

The following table summarizes the parameters.

Table 8-100 Parameters

Parameters	Description
items	Collection of information about the resource
id	Unique identifier for the connection, such as 1c89922d-92ba-46c1-850f- e2a8a416ddf2
name	Name of the connection, such as Connection29
description	Description of the connection, such as Planning
url	The URL of the connection, such as https://< <i>BASE-URL</i> >/ HyperionPlanning



Parameters	Description
username	The username for the connection, such as admin
domain	The domain name for the connection
modified	The time stamp of the last modification to the connection details, such as 2021-01-18 12:23:49.0
modifiedBy	The last service administrator to modify the connection details, such as admin

Table 8-100 (Cont.) Parameters

Example Response

The identity domain information as shown as part of the response.

```
{
    "links": [
        {
            "href": "https://<BASE-URL>/HyperionPlanning/rest/epm/v1/
applications/epbcs1/connections?offset=2&limit=2",
            "action": "GET",
            "rel": "self",
            "data": null
        },
        {
            "href": "https://<BASE-URL>/HyperionPlanning/rest/epm/v1/
applications/epbcs1/connections?offset=0&limit=2",
            "action": "GET",
            "rel": "prev",
            "data": null
        },
        {
            "href": "https://<BASE-URL>/HyperionPlanning/rest/epm/v1/
applications/epbcs1/connections?offset=4&limit=2",
            "action": "GET",
            "rel": "next",
            "data": null
        }
    ],
    "items": [
        {
            "id": "1c89922d-92ba-46c1-850f-e2a8a416ddf2",
            "name": "Connection20",
            "url": "https://<BASE-URL>/HyperionPlanning",
            "username": "admin",
            "modified": "2021-01-18 12:23:49.0",
            "modifiedBy": "admin",
            "links": [
                    "href": "https://<BASE-URL>/HyperionPlanning/rest/epm/v1/
applications/epbcs1/connections/1c89922d-92ba-46c1-850f-e2a8a416ddf2",
                    "action": "GET",
                    "rel": "Self",
                    "data": null
                }
```

```
]
        },
        {
            "id": "ec94a10e-717b-449a-89ce-0c16b1688caa",
            "name": "Connection29",
            "url": "https://<BASE-URL>/HyperionPlanning",
            "username": "admin",
            "domain": "<DOMAIN NAME>",
            "modified": "2021-01-18 12:23:49.0",
            "modifiedBy": "admin",
            "links": [
                 {
                     "href": "https://<BASE-URL>/HyperionPlanning/rest/epm/v1/
applications/epbcs1/connections/ec94a10e-717b-449a-89ce-0c16b1688caa",
                     "action": "GET",
                     "rel": "Self",
                     "data": null
                }
            1
        }
    ],
    "type": null
1
```

Update a Connection

Use this REST API to update a specific connection that is saved in an application.

You can update the values using either a plain text password or encrypted password. The response returns the updated connection details.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/epm/{api_version}/applications/{application}/
connections/{connectionRef}

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 8-101 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application for which to update a connection	Path	Yes	None
connectionRef	The connection to refer to. The value can be either a connection name or ID.	Path	Yes	None



Name	Description
name	Name of the connection, such as Connection29
description	Description of the connection, such as Planning
url	The URL of the connection, such as https:// <base-url>/HyperionPlanning</base-url>
username	The username for the connection, such as admin
password	The password of the connection
encryptedPassword	The password of the connection in the encrypted format using the EPM Automate encrypt command. See encrypt.

Table 8-102 Parameters for Connection Information that Can Be Modified

Example Body

Example 1:

```
{
    "name": "<NEW_CONNECTION_NAME>",
    "description": "<NEW_DESCRIPTION>",
    "url": "https://<BASE-URL>/HyperionPlanning",
    "username": "<NEW_USERNAME>",
    "password": "<NEW_PASSWORD>"
}
```

Example 2:

```
{
    "name": "<NEW_CONNECTION_NAME>",
    "description": "<NEW_DESCRIPTION>",
    "url": "https://<BASE-URL>/HyperionPlanning",
    "username": "<NEW_USERNAME>",
    "encryptedPassword": "<ENCRYPTED_PASSWORD>"
}
```

Response

Supported Media Type: application/json

Table 8-103	Parameters	

Parameters		
items		
id	Unique identifier for the connection, such as 1c89922d-92ba-46c1-850f- e2a8a416ddf2	
name	Name of the connection, such as Connection29	
description	Description of the connection, such as Planning	
url	The URL of the connection, such as https://< <i>BASE-URL</i> >/ HyperionPlanning	
domain	The domain name for the connection	
username	The username for the connection, such as admin	



Parameters	Description
modified	The time stamp of the last modification to the connection details, such as 2021-01-18 12:23:49.0
modifiedBy	The last service administrator to modify the connection details, such as admin

Table 8-103 (Cont.) Parameters

Example Response

The identity domain information as shown as part of the response.

```
{
    "id": "<ID>",
   "name": "<NEW CONNECTION NAME>",
    "description": "<NEW DESCRIPTION>",
   "url": "https://<BASE-URL>/HyperionPlanning",
    "domain": "<DOMAIN NAME>",
    "username": "<NEW USERNAME>",
    "modified": "2021-02-02 09:16:02.0",
    "modifiedBy": "admin",
    "links": [
        {
            "href": "https://<BASE-URL>/HyperionPlanning/rest/epm/v1/
applications/epbcs1/connections/f83b3da2-9505-415e-b7f7-3cf113cc94e4",
            "action": "GET",
            "rel": "self",
            "data": null
        }
   1
}
```

9 Migration REST APIs

Use the Migration REST APIs to get API versions, work with files, manage services and application snapshots, work with users, and skip updates.

Some Migration REST APIs are version 11.1.2.3.600 and others are version v1 or v2. Passing the incorrect version will result in 404 errors when the API is invoked. Be sure to use the correct version for the API. Be sure to use the correct version for the API. Migration REST API versions are as follows.

These Migration APIs are version 11.1.2.3.600:

- Delete Files (v11.1.2.3.600)
- Download
- Get Information About All Application Snapshots
- Get Information About All Services
- Get Information About a Specific Application Snapshot
- List Files (v11.1.2.3.600)
- Provide Feedback (v11.1.2.3.600)
- Run Recreate on a Service (11.1.2.3.600)
- Upload

These Migration APIs are version v1:

- Clone an Environment
- Copy a File Between Instances (v1)
- Copy Application Snapshot (v1)
- Copy from Object Store (v1)
- Copy to Object Store (v1)
- Download Application Snapshot (v1)
- Get Essbase Query Governor Execution Time
- Get the Build Version and Daily Maintenance Window Time (v1)
- LCM Import (v1)
- LCM Export (v1)
- Manage Permission for Manual Access to Database (v1)
- Rename Application Snapshot (v1)
- Restart the Service Instance (v1)
- Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v1)
- Send Email (v1)
- Set Encryption Key (v1)



- Set Essbase Query Governor Execution Time
- Setting the Daily Maintenance Time (v1)
- Skip Updates (v1)
- Upload Application Snapshot (v1)

These Migration APIs are version v2:

- Copy a File Between Instances (v2)
- Copy Application Snapshot (v2)
- Copy from Object Store (v2)
- Copy to Object Store (v2)
- Delete Files (v2)
- Download Application Snapshot (v2)
- Export Essbase Data (v2)
- Get Essbase Query Governor Execution Time
- Get Idle Session Timeout
- Get the Build Version and Daily Maintenance Window Time (v2)
- Get Virus Scan on File Upload
- LCM Import (v2)
- LCM Export (v2)
- List Backups Only for OCI (Gen 2) Environments (v2)
- List Files (v2)
- Manage Permission for Manual Access to Database (v2)
- Provide Feedback (v2)
- Rename Application Snapshot (v2)
- Restore Backup Only for OCI (Gen 2) Environments (v2)
- Restart the Service Instance (v2)
- Run Recreate on a Service (v2)
- Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v2)
- Send Email (v2)
- Set Encryption Key (v2)
- Set Essbase Query Governor Execution Time
- Set Idle Session Timeout
- Set Virus Scan on File Upload
- Setting the Daily Maintenance Time (v2)
- Skip Updates (v2)
- Update the IP Allowlist Only for OCI (Gen 2) Environments
- Upload Application Snapshot (v2)
- View the IP Allowlist Only for OCI (Gen 2) Environments



This Migration API is version v3:

Delete Files (v3)

URL Structure for Migration

This topic shows the general URL structure for the Migration REST APIs.

Some Migration REST APIs are version 11.1.2.3.600 and others are version v1 or v2. Be sure to use the correct version for the API. Passing the incorrect version will result in 404 errors when the API is invoked.

You can find an API version using REST APIs as described here: Getting API Versions for Migration APIs. For a list of all of the Migration APIs and their version numbers, see Migration REST APIs.

Use this URL structure to access the Migration REST resources:

https://<BASE-URL>/interop/rest/{api version}/{path}

Where:

• <BASE-URL>: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- {*api* version}: API version you are developing with.
- {path}: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ <code>internal/"</code> in the URL.

Migration Status Codes

The status code returned in the response of REST API calls identifies the status of the operation.

Status Code	Description
0	Operation success
-1	Operation in progress
+ve	Operation failed, with the status signifying an error

Table 9-1 Status Code

Getting API Versions for Migration APIs

You can manage versions using the set of REST resources summarized in the following table.

Important: The version number is case-sensitive. For example, if the version number is listed as v1 with a lowercase v, you cannot enter the version number with a capital v as in this incorrect example, V1, which would result in an error. Instead, you must enter the version number with a lowercase v as in this correct example: v1.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-2 Manage Versions of Migration APIs

Task	Request	REST Resource
Get REST API Versions for Migration	GET	/interop/rest/
Get Information About a Specific REST API Version for Migration	GET	<pre>/interop/rest/{apiVersion}</pre>

Get REST API Versions for Migration

Returns information about which REST APIs are available and supported. Multiple versions may be supported simultaneously.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

GET /interop/rest/

Request

Supported Media Types: application/json

Table 9-3 Parameters

Name	Description	
Details	In case of errors, details are published with the error string	
Status	See Migration Status Codes	
Items	Detailed information about the API	
Version	The version	
Lifecycle	Possible values: active, deprecated	
Latest	Whether this version is the latest	
Links	Detailed information about the link	
Href	Links to API call	
Action	The HTTP call type	
Rel	Possible values: self	
Data	Parameters as key value pairs passed in the request	



Name	Description
lifecycle	The stage in the lifecycle, such as active
version	The version, such as 11.1.2.3.600, v1, and v2, for example, "version": "11.1.2.3.600", "v1", v2"
serviceType	The service type, such as PCMCS
serverVersion	The server version, such as 21.05.70
buildVersion	The build version, such as 21.05.52

Table 9-3 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "links": [
        {
            "href": "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/interop/rest/11.1.2.3.600",
            "rel": "self",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": 0,
    "items": [
        {
            "latest": true,
            "links": [
                {
                    "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/interop/rest/11.1.2.3.600",
                    "rel": "version",
                    "data": null,
                    "action": "GET"
               }
            ],
            "lifecycle": "active",
            "version": "11.1.2.3.600",
            "serviceType": "PCMCS",
            "serverVersion": "21.05.70",
            "buildVersion": "21.05.52"
        }
    ],
}
```

Getting API Versions of Migration APIs Sample Code

Prerequisites: json.jar

Common functions: See Common Helper Functions for Java



```
Example 9-1 Java Sample – getVersionsOfLCM.java
```

```
//
//
// BEGIN - List all the versions in PBCS
11
public void getLCMVersions() throws Exception {
    String urlString = String.format("%s/interop/rest", serverUrl);
    String response = executeRequest(urlString, "GET", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        JSONArray fileList = json.getJSONArray("items");
        System.out.println("List of files are :");
        JSONObject jObj = null;
        for(int i=0; i<fileList.length();i++) {</pre>
     System.out.println("Version :" + jObj.getString("version"));
          System.out.println("Lifecycle :" + jObj.getString("lifecycle"));
          System.out.println("Latest :" + jObj.getString("latest"));
          System.out.println("Link :" + ((JSONObject) ((JSONArray)
jObj.getJSONArray("links")).get(0)).getString("href") + "\n");
        }
    }
}
11
// END - List all the versions in PBCS
11
```

Example 9-2 cURL Sample – GetVersionsOfLCM.sh

Prerequisites: jq

Common functions: See Common Helper Functions for cURL

```
funcGetLCMVersions() {
   url=$SERVER URL/interop/rest
    funcExecuteRequest "GET" $url
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "List of versions :"
        count=`echo $output | jg '.items | length'`
        i=0
        while [ $i -lt $count ]; do
            echo "Version : " `echo $output | jq '.items['$i'].version'`
            echo "Lifecycle :" `echo $output | jq '.items['$i'].lifecycle'`
            echo "Latest :" `echo $output | jq '.items['$i'].latest'`
            echo "Link :" `echo $output | jq '.items['$i'].links[0].href'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jg '.details'`
        echo "Error occurred. " $error
    fi
```

```
funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Example 9-3 Groovy Sample – GetVersionsOfLCM.groovy

Prerequisites: json.jar

}

Common functions: See CSS Common Helper Functions for Groovy

```
def getLCMVersions() {
   def url;
    try {
            url = new URL(serverUrl + "/interop/rest/")
    } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
    }
    response = executeRequest(url, "GET", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0 ) {
        def items = object.items
        println "List of versions :"
        items.each{
            println "Version : " + it.version
            println "Lifecycle : " + it.lifecycle
            println "Latest : " + it.latest
            println "Link : " + it.links[0].href + "\n"
        }
    } else {
        println "Error occurred while listing versions"
        if (object.details != null)
                println "Error details: " + object.details
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Get Information About a Specific REST API Version for Migration

Returns information about a specific version.

Some Migration REST APIs are version 11.1.2.3.600, and others are other versions, such as v1 or v3. Passing the incorrect version will result in 404 errors when the API is invoked. Be sure to use the correct version for the API; api_version could be 11.1.2.3.600, v1, or v2.

Required Roles

Service Administrator, Power User, User, Viewer



REST Resource

GET /interop/rest/{api version}

Request

Parameters:

The following table summarizes the client request.

Table 9-4 Parameters

Name	Description	Туре	Default
api_version	Specific API version	Path	Yes

Response

Supported Media Types: application/json

Table 9-5 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible values: self, recreate service
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "status":0,
    "details":null,
    "links":[{
        "data":null,
        "action":"GET",
        "href":"https://<BASE-URL/interop/rest/11.1.2.3.600",
        "rel":"self"
        },{
        "data":null,
        "action":"GET",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/services",
        "rel": "recreate service"
        },{
        "data":null,
        "action":"GET",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/applications",
        "rel":"application service"
        },{
```



```
"data":null,
    "action":"GET", "href":"https://<BASE-URL>/interop/rest/
11.1.2.3.600/applicationsnapshots "rel":"application snapshot service"
    },{
    "data":null,
    "action":"POST",
    "rel":"feedback services",
    "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/feedback"
}]
}
```

Get Information about a Specific Version of Migration Sample Code

Example 9-4 Java Sample – getInfoAboutSpecificVersion.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN - List version details
11
public void getLCMVersionDetails() throws Exception {
   String urlString = String.format("%s/interop/rest/%s", serverUrl,
apiVersion);
    String response = executeRequest(urlString, "GET", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        JSONArray linksArray = json.getJSONArray("links");
        System.out.println("Version " + apiVersion + " details :");
        JSONObject jObj = null;
        for(int i=0; i < linksArray.length(); i++) {</pre>
            jObj = (JSONObject)linksArray.get(i);
            System.out.println("Service :" + jObj.getString("rel"));
            System.out.println("URL :" + jObj.getString("href"));
            System.out.println("Action :" + jObj.getString("action") + "\n");
        }
    }
}
11
// END - List version details
11
```

Example 9-5 cURL Sample – GetInfoAboutSpecificVersion.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcGetLCMVersionDetails() {
    url=$SERVER_URL/interop/rest/$API_VERSION
    funcExecuteRequest "GET" $url
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
```



```
if [ $status == 0 ]; then
   echo "Version $API VERSION details :"
   count=`echo $output | jq '.links | length'`
   i=0
   while [ $i -lt $count ]; do
        echo "Service : " `echo $output | jq '.links['$i'].rel'`
        echo "URL :" `echo $output | jq '.links['$i'].href'`
        echo "Action :" `echo $output | jq '.links['$i'].action'`
        echo ""
        i=`expr $i + 1`
   done
else
   error=`echo $output | jq '.details'`
   echo "Error occurred. " $error
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Example 9-6 Groovy Sample – GetInfoAboutSpecificVersion.groovy

Prerequisites: json.jar

}

Common Functions: See CSS Common Helper Functions for Groovy

```
def getLCMVersionDetails() {
   def url;
    try {
            url = new URL(serverUrl + "/interop/rest/" + apiVersion)
    } catch (MalformedURLException e) {
           println "Malformed URL. Please pass valid URL"
            System.exit(0);
    }
    response = executeRequest(url, "GET", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0) {
        def links = object.links
        println "Version " + apiVersion + " details :"
        links.each{
           println "Service : " + it.rel
           println "URL : " + it.href
           println "Action : " + it.action + "\n"
        }
    } else {
        println "Error occurred while fetching version details"
        if (object.details != null)
                println "Error details: " + object.details
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



Import and Export Files

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-6Import and Export Files

Task	Request	REST Resource
LCM Import (v1)	POST	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration?q={type:"import"}</pre>
LCM Import (v2)	POST	/interop/rest/v2/snapshots/import
LCM Export (v1)	POST	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration?q={type:"export"}</pre>
LCM Export (v2)	POST	/interop/rest/v2/snapshots/export

LCM Import (v1)

Initiates import of a Migration snapshot so that the contents of the application snapshot are imported into the application. You can complete these tasks for imported users: set a specific password for all users in the snapshot, set a unique temporary password for each user in the snapshot, and force password reset at first login.

The presence of status -1 in the response indicates that the import is in progress. You should use the job status URI to determine whether the import is complete.

If the Job completes with status 1, the task details will be mentioned in the items from which the source, destination, and URL to fetch the first set of errors is available. All issues for a particular task can be fetched in the manner of pagination. Acceptable values for msgtype are: error/warn/info; limit represents the number of issues requested per request, and offset marks the beginning number to fetch the issues.

This API is version 11.1.2.3.600.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

Identity Domain Administrator role is required to import user and predefined roles

REST Resource

POST /interop/rest/{api_version}/applicationsnapshots/{applicationSnapshotName}/
migration?q={type:"import"}



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-7 Tasks for LCM Import

Task	Request	REST Resource
LCM Import	POST	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration?q={type:"import"}</pre>
Import Status; the 9 in the resource is used as an example here	GET	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration/9</pre>
Details	GET	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration/9/0/details? limit=25&msgtype=error&offset=0</pre>

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-8 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
applicationSnapsho tName	Application snapshot that is to be imported	Path	Yes	None
type	Type of migration being performed, import	Query	Yes	None
importUsers	Whether to import users; true imports users and their predefined role assignments. The import fails if the user does not have the Identity Domain Administrator role.	Query	No	false
userPassword	The default password for the imported users.	Query	No	A unique temporary password is assigned to each user
resetPassword	Whether to force reset password for the imported users on first login, true or false	Query	No	true

Response

Supported Media Types: application/json



Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request
items	Details about the resource
source	From where the navigation is being performed
destination	To where the navigation is being performed
name	Name of the task, usually "Task Information"
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Table 9-9 Parameters

Examples of Response Body

The following are examples of the response body in JSON format.

Example 1: Job is in Progress

```
{
    "details":null,
    "status":-1,
    "links":[{
        "data":null,
        "action":"POST",
        "rel":"self",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migrationq={type:"import"}"
        },{
        "data":null,
        "action":"POST",
        "rel":"Job Status",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/2"
    }]
}
```

Example 2: Job Completes with Errors

```
{"status":1,
"items":[{
    "source":"/Nasdaq/HSS-Shared Services",
    "name":"Task Information",
    "destination":"Shared Services",
    "links":[{
        "data":null,
        "action":"GET",
    "
```



```
"rel":"Job Details",
      "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=25&offset=0&msqtype=error"}]
  },
   {"source":"/Artifact Snapshot/HP-SS2",
  "name":"Task Information",
   "destination":"",
   "links":[{
      "data":null,
      "action":"GET",
      "rel":"Job Details",
      "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/1/details?
limit=25&offset=0&msqtype=error"}]
   }],
   "details":null,
   "links":[{
      "data":null,
      "action":"POST",
      "rel":"self",
      "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1"}
      1}
         }
```

Example 3: Each Type of Task Informaton is Requested

```
{"status":0,
"items":[{
   "msgType":"error",
   "artifact": "/Native Directory/Groups",
   "msgText":"EPMIE-00069: Failed to find user during group children import.
User user0026 not found. Please ensure that a user exists in the system.",
      "msgCategory":"14000: Error reported.",
   "msgCategory":"14000: Error reported."
   },{
   "msgType":"error",
  "artifact":"/Native Directory/Groups",
   "msqText":"EPMIE-00069: Failed to find user during group children import.
User user0025 not found. Please ensure that a user exists in the system.",
   "msgCategory":"14000: Error reported." }
  ],
"details":null,
"links":[{
   "data":null,
   "action":"GET",
   "rel":"self",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&msgtype=error&offset=25"},
   {"data":null,
  "action":"GET",
   "rel":"next",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
```



```
applicationsnapshots/ss2/migration/1/0/details?
limit=2&offset=27&msgType=error"},
    {"data":null,
    "action":"GET",
    "rel":"prev",
    "href":https://<BASE-URL>/rest/11.1.2.3.600/applicationsnapshots/ss2/
migration/1/0/details?limit=2&offset=23&msgType=error
    }]
    }
```

Java Sample – IcmImport.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
{"status":0,
"items":[{
   "msgType":"error",
   "artifact": "/Native Directory/Groups",
   "msgText":"EPMIE-00069: Failed to find user during group children import.
User user0026 not found. Please ensure that a user exists in the system.",
      "msgCategory":"14000: Error reported.",
   "msgCategory":"14000: Error reported."
   },{
   "msqType":"error",
   "artifact": "/Native Directory/Groups",
   "msgText":"EPMIE-00069: Failed to find user during group children import.
User user0025 not found. Please ensure that a user exists in the system.",
   "msgCategory":"14000: Error reported." }
  ],
"details":null,
"links":[{
   "data":null,
   "action":"GET",
   "rel":"self",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&msgtype=error&offset=25"},
   {"data":null,
   "action":"GET",
   "rel":"next",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&offset=27&msqType=error"},
   {"data":null,
   "action":"GET",
   "rel":"prev",
   "href":https://<BASE-URL>/rest/11.1.2.3.600/applicationsnapshots/ss2/
migration/1/0/details?limit=2&offset=23&msgType=error
   }]
      }
```

cURL Sample – LcmImport.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
{"status":0,
"items":[{
   "msgType":"error",
   "artifact": "/Native Directory/Groups",
   "msgText":"EPMIE-00069: Failed to find user during group children import.
User user0026 not found. Please ensure that a user exists in the system.",
      "msgCategory":"14000: Error reported.",
   "msgCategory":"14000: Error reported."
   },{
   "msgType":"error",
   "artifact":"/Native Directory/Groups",
   "msgText":"EPMIE-00069: Failed to find user during group children import.
User user0025 not found. Please ensure that a user exists in the system.",
   "msgCategory":"14000: Error reported." }
  ],
"details":null,
"links":[{
   "data":null,
   "action":"GET",
   "rel":"self",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&msgtype=error&offset=25"},
   {"data":null,
   "action":"GET",
   "rel":"next",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&offset=27&msgType=error"},
   {"data":null,
   "action":"GET",
   "rel":"prev",
   "href":https://<BASE-URL>/rest/11.1.2.3.600/applicationsnapshots/ss2/
migration/1/0/details?limit=2&offset=23&msgType=error
   }]
      }
```

Groovy Sample - LcmImport.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
{"status":0,
"items":[{
    "msgType":"error",
    "artifact":"/Native Directory/Groups",
    "msgText":"EPMIE-00069: Failed to find user during group children import.
User user0026 not found. Please ensure that a user exists in the system.",
    "msgCategory":"14000: Error reported.",
    "msgCategory":"14000: Error reported."
    },{
    "msgType":"error",
    "artifact":"/Native Directory/Groups",
```

```
"msgText":"EPMIE-00069: Failed to find user during group children import.
User user0025 not found. Please ensure that a user exists in the system.",
   "msgCategory":"14000: Error reported." }
   ],
"details":null,
"links":[{
   "data":null,
   "action":"GET",
   "rel":"self",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&msgtype=error&offset=25"},
   {"data":null,
   "action":"GET",
   "rel":"next",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&offset=27&msgType=error"},
   {"data":null,
   "action":"GET",
   "rel":"prev",
   "href":https://<BASE-URL>/rest/11.1.2.3.600/applicationsnapshots/ss2/
migration/1/0/details?limit=2&offset=23&msgType=error
   }1
      }
```

Sample cURL Command Basic Auth

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/x-www-form-urlencoded' 'https://<BASE-URL>
/interop/rest/11.1.2.3.600/applicationsnapshots/<APPLICATION-SNAPSHOT-NAME>/
migration?
q={type:"import",importUsers:"true"}'
```

Sample cURL Command OAuth 2.0

```
curl -X POST --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/x-www-form-urlencoded' 'https://<BASE-URL>
/interop/rest/11.1.2.3.600/applicationsnapshots/<APPLICATION-SNAPSHOT-NAME>/
migration?
q={type:"import",importUsers:"true"}'
```

LCM Import (v2)

The LCM Import (v2) REST API initiates import of a Migration snapshot so that the contents of the application snapshot are imported into the application. You can complete these tasks for imported users: set a specific password for all users in the snapshot, set a unique temporary password for each user in the snapshot, and force password reset at first login.

The presence of status -1 in the response indicates that the import is in progress. You should use the job status URI to determine whether the import is complete.

If the Job completes with status 1, the task details will be mentioned in the items from which the source, destination, and URL to fetch the first set of errors is available. All issues for a



particular task can be fetched in the manner of pagination. Acceptable values for msgtype are: error/warn/info; limit represents the number of issues requested per request, and offset marks the beginning number to fetch the issues.

This API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

Identity Domain Administrator role is required to import user and predefined roles.

REST Resource

POST /interop/rest/v2/snapshots/import

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-10 Tasks for LCM Import

Task	Request	REST Resource
LCM Import	POST	/interop/rest/v2/snapshots/import
Import Status	GET	/interop/rest/v2/status/migration/22
Details	GET	/interop/rest/v2/status/migration/22/0/details? limit=25&offset=0&msgtype=info

Request

Support Media Types: application/json

The following table summarizes the request parameters.

Table 9-11 Parameters

Name	Description	Туре	Required	Default
snapshotName	Application snapshot that is to be imported	Payload	Yes	None
importUsers	Whether to import users; true imports users and their predefined role assignments. The import fails if the user issuing the request does not have the Identity Domain Administrator role.	Payload	No	false



Table 9-11 (Cont.) Parameters

Name	Description	Туре	Required	Default
userPassword	The default password for the imported users.	Payload	No	A unique temporar y password is assigned to each user
resetPassword	Whether to force reset password for the imported users on first login, true or false	Payload	No	true

Example URL and Payload

https://<BASE-URL>/interop/rest/v2/snapshots/import

```
{
    "snapshotName": "Artifact Snapshot",
    "parameters": {
        "importUsers": true,
        "userPassword": "epm_cloud",
        "resetPassword": false
    }
}
```

Response

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request
items	Details about the resource
source	From where the navigation is being performed
destination	To where the navigation is being performed
name	Name of the task, usually "Task Information"
links	Details of the first URL to be requested to get the job details; rel is "Job Details"



Examples of Response Body

The following are examples of the response body in JSON format.

Example 1: Import is in Progress

```
{
    "details": null,
    "status": -1,
    "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/snapshots/import",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": "https://<BASE-URL>/interop/rest/v2/status/migration/24",
            "action": "POST",
            "rel": "Job Status",
            "data": null
        }
    1
}
```

Example 2: Import Completes

```
{
    "details": null,
    "status": 0,
    "items": [
        {
            "name": "Task Information",
            "source": "/Artifact Snapshot/HSS-Shared Services",
            "destination": "Shared Services",
            "links": [
                {
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/24/0/details?limit=25&offset=0&msgtype=warning",
                     "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "/Artifact Snapshot/HP-Vision",
            "destination": "Vision",
            "links": [
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/24/1/details?limit=25&offset=0&msgtype=warning",
                    "action": "GET",
                     "rel": "Job Details",
```

```
"data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "/Artifact Snapshot/DOCREP-Document Repository",
            "destination": "Document Repository",
            "links": [
                {
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/24/2/details?limit=25&offset=0&msgtype=warning",
                    "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "/Artifact Snapshot/CALC-Calculation Manager",
            "destination": "Calculation Manager",
            "links": [
                {
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/24/3/details?limit=25&offset=0&msgtype=warning",
                    "action": "GET",
                     "rel": "Job Details",
                    "data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "/Artifact Snapshot/FDMEE-FDM Enterprise Edition",
            "destination": "FDM Enterprise Edition",
            "links": [
                {
                     "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/24/4/details?limit=25&offset=0&msgtype=warning",
                    "action": "GET",
                     "rel": "Job Details",
                    "data": null
                }
            ]
        }
    ],
    "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/status/migration/24",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```

Sample cURL Command Basic Auth

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/json' -d '{"snapshotName":"<SNAPSHOT-
NAME>","parameters":
{"importUsers":<TRUE/FALSE>,"userPassword":"<PASSWORD>","resetPassword":<TRUE/
FALSE>}}'
'https://<BASE-URL>/interop/rest/v2/snapshots/import'
```

Sample cURL Command OAuth 2.0

```
curl -X POST --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/json' -d '{"snapshotName":"<SNAPSHOT-
NAME>","parameters":
{"importUsers":<TRUE/FALSE>,"userPassword":"<PASSWORD>","resetPassword":<TRUE/
FALSE>}}'
'https://<BASE-URL>/interop/rest/v2/snapshots/import'
```

LCM Export (v1)

Initiates a repeat export of a Migration artifact based on the settings that were used to export artifacts using the Migration artifact export screen. This REST API is version 11.1.2.3.600.

You can also use EPM Automate to automate the repeat export of artifacts.

The presence of status -1 in the response indicates that the reexport is in progress. You should use the job status URI to determine whether the reexport is complete.

If the Job completes with status 1, the task details will be mentioned in the items from which the source, destination, and URL to fetch the first set of errors is available. All issues for a particular task can be fetched in the manner of pagination. Acceptable values for msgtype are: error/warn/info; limit represents the number of issues requested per request, and offset marks the beginning number to fetch the issues.

This API is version v1.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/{api_version}/applicationsnapshots/{applicationSnapshotName}/
migration?q={type:"export}

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
LCM Export	POST	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration?q={type:"export"}</pre>
Export Status	GET	/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration/8
Details	GET	<pre>/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/migration/8/0/details? limit=25&msgtype=error&offset=0</pre>

Table 9-13 Tasks for LCM Export

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-14 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
applicationSnapsho tName	Application snapshot that has to be exported	Path	Yes	None
type	Type of migration being performed, can be export or import	Query	Yes	None

Response

Supported Media Types: application/json

Table 9-15 Parameters

Attribute	Description
details	In case of errors, details are published with the error string
status	See Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible values. Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the re-export operation
data	Parameters as key value pairs passed in the request
items	Details about the resource
source	From where the navigation is being performed
destination	To where the navigation is being performed
name	Name of the task, usually "Task Information"
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Examples of Response Body

The following are examples of the response body in JSON format.



Example 1: Export is in Progress

```
{
   "status":-1,
  "links":[{
     "data":null,
      "action":"POST",
      "rel":"self",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migrationg={type:"export"}"
      },{
      "data":null,
      "action":"POST",
      "rel":"Job Status",
   "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/8"
   }],
   "details":null
```

Example 2: Export Completes with Errors

```
{"status":1,
"items":[{
   "source":"/Nasdaq/HSS-Shared Services",
   "name": "Task Information",
   "destination": "Shared Services",
   "links":[{
     "data":null,
     "action":"GET",
      "rel":"Job Details",
      "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=25&offset=0&msgtype=error"}]
   },
   {"source":"/Artifact Snapshot/HP-NASDAQ",
  "name": "Task Information",
   "destination":"",
   "links":[{
     "data":null,
      "action":"GET",
      "rel":"Job Details",
      "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/1/details?
limit=25&offse=0&msgtype=error"}]
   }],
   "details":null,
   "links":[{
      "data":null,
      "action":"POST",
      "rel":"self",
      "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1"}
1}
```



Example 3: Information on Each Task is Requested

```
{"status":0,
"items":[{
     "msgType":"error",
     "artifact": "/Native Directory/Groups",
     "msgText":"EPMIE-00069: Failed to find user during group children
import. User user0026 not found. Please ensure that a user exists in the
system.",
          "msgCategory":"14000: Error reported.",
     "msgCategory":"14000: Error reported."
     },{
     "msgType":"error",
     "artifact":"/Native Directory/Groups",
     "msqText":"EPMIE-00069: Failed to find user during group children
import. User user0025 not found. Please ensure that a user exists in the
system.",
     "msgCategory":"14000: Error reported." }
     ],
"details":null,
"links":[{
     "data":null,
     "action":"GET",
     "rel":"self",
     "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&msqType=error&offset=25"},
     {"data":null,
     "action":"GET",
     "rel":"next",
     "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?
limit=2&offset=27&msqType=error"},
     {"data":null,
     "action":"GET",
     "rel":"prev",
     "href":https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2/migration/1/0/details?limit=2&offset=23&msgType=error
     }]
          }
```

Java Sample - LcmExport.java

Prerequisites: json.jar

Common functions: See Appendix A, Common Helper Functions for Java.

```
//
// BEGIN - Export an application snapshot
//
public void exportSnapshot(String applicationSnapshotName) throws Exception
{
    JSONObject params = new JSONObject();
    params.put("type","export");
    String urlString = String.format("%s/interop/rest/%s/
applicationsnapshots/%s/migration?q=%s", serverUrl, apiVersion,
```

```
URLEncoder.encode(applicationSnapshotName, "UTF-8"), params.toString());
String response = executeRequest(urlString, "POST", null);
System.out.println("Export started successfully");
getMigrationJobStatus(fetchPingUrlFromResponse(response, "Job Status"),
"POST");
}
//
// END - Export an application snapshot
//
```

cURL Sample – LcmExport.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcExportSnapshot() {
   param=$(echo "{type:export}" | sed -f urlencode.sed)
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/migration?q=$param
    funcExecuteRequest "POST" $url
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started exporting successfully"
        funcGetMigrationStatus "POST"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – LcmExport.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def exportSnapshot(applicationSnapshotName) {
    def url;
    try {
        String snapshotName = URLEncoder.encode(applicationSnapshotName,
    "UTF-8");
        JSONObject params = new JSONObject();
        params.put("type","export");
        url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/
        applicationsnapshots/" + snapshotName + "/migration?q=" + params.toString());
        } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
               System.exit(0);
        }
        response = executeRequest(url, "POST", null, "application/x-www-form-
urlencoded");
```



```
if (response != null) {
    getMigrationJobStatus(fetchPingUrlFromResponse(response, "Job
Status"), "POST");
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

LCM Export (v2)

The LCM Export (v2) REST API initiates a repeat export of a Migration artifact based on the settings that were used to export artifacts using the Migration artifact export screen.

The presence of status -1 in the response indicates that the reexport is in progress. You should use the job status URI to determine whether the reexport is complete.

If the job completes with status 1, the task details will be mentioned in the items from which the source, destination, and URL to fetch the first set of errors is available. All issues for a particular task can be fetched in the manner of pagination. Acceptable values for msgtype are: error/warn/info; limit represents the number of issues requested per request, and offset marks the beginning number to fetch the issues.

This API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

```
POST /interop/rest/v2/snapshots/export
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-16	Tasls LCM	Export
------------	-----------	--------

Task	Request	REST Resource
LCM Export	POST	/interop/rest/v2/snapshots/export
Export Status	GET	/interop/rest/v2/status/migration/28
Details	GET	/interop/rest/v2/status/migration/28/1/details? limit=25&offset=0&msgtype=info



Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-17 Parameters

Name	Description	Туре	Required	Default
SnapshotName	Application snapshot that has to be exported	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/v2/snapshots/export

```
{
    "snapshotName": "Artifact Snapshot"
}
```

Response

Supported Media Types: application/json

Table 9-18 Parameters

Attribute	Description
details	In case of errors, details are published with the error string
status	See Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible values. Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the re-export operation
data	Parameters as key value pairs passed in the request
items	Details about the resource
source	From where the navigation is being performed
destination	To where the navigation is being performed
name	Name of the task, usually "Task Information"
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Examples of Response Body

The following are examples of the response body in JSON format.

Example 1: Export is in Progress

```
{
    "details": null,
```



```
"status": -1,
    "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/snapshots/export",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": "https://<BASE-URL>/interop/rest/v2/status/migration/28",
            "action": "POST",
            "rel": "Job Status",
            "data": null
        }
    ]
}
```

Example 2: Export Completes

```
{
    "details": null,
    "status": 0,
    "items": [
        {
            "name": "Task Information",
            "source": "Shared Services",
            "destination": "/Artifact Snapshot1/HSS-Shared Services",
            "links": [
                {
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/28/0/details?limit=25&offset=0&msgtype=info",
                    "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "Vision",
            "destination": "/Artifact Snapshot1/HP-Vision",
            "links": [
                {
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/28/1/details?limit=25&offset=0&msgtype=info",
                    "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            1
        },
        {
            "name": "Task Information",
            "source": "Document Repository",
            "destination": "/Artifact Snapshot1/DOCREP-Document Repository",
```

```
"links": [
                {
                    "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/28/2/details?limit=25&offset=0&msgtype=info",
                    "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "Calculation Manager",
            "destination": "/Artifact Snapshot1/CALC-Calculation Manager",
            "links": [
                {
                     "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/28/3/details?limit=25&offset=0&msgtype=info",
                    "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            ]
        },
        {
            "name": "Task Information",
            "source": "FDM Enterprise Edition",
            "destination": "/Artifact Snapshot1/FDMEE-FDM Enterprise Edition",
            "links": [
                {
                     "href": "https://<BASE-URL>/interop/rest/v2/status/
migration/28/4/details?limit=25&offset=0&msgtype=info",
                    "action": "GET",
                    "rel": "Job Details",
                    "data": null
                }
            1
        }
    ],
    "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/status/migration/28",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H'Content-Type: application/json' -d
'{"snapshotName":"Artifact Snapshot"}''https://<BASE-URL>/interop/rest/v2/
snapshots/export'
```



Upload and Download Files

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-19 Upload and Download Files

Task	Request	REST Resource
Upload	POST	<pre>/interop/rest/11.1.2.3.600/applicationsnapshots/ {applicationSnapshotName}/contents</pre>
Download	GET	/interop/rest/{api_version}/applicationsnapshots/ {applicationSnapshotName}/contents

Upload

Uploads a file from the current directory on the local machine to the repository. Files on the repository cannot be accessed directly.

If a file already exists, the API gives an error and does not overwrite it. Use this command to upload data, metadata, and back up snapshots to a service instance. See About EPM Automate in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud*.

If a -1 status is returned and it is the last chunk to be uploaded, this means that an LCM artifact snapshot has been uploaded and zip extraction is in progress. The client pings the URL until the status is a positive integer. This job is done asynchronously.

Note: The entire path to the file must be encoded, for example, changing / to 2F and spaces to 20.

For example, change this path to an .HTML file in the apr directory:

apr/2020-03-04 23 07 20/2020-03-04 23 07 20.html

to this:

apr%2F2020-03-04%2023_07_20%2F2020-03-04%2023_07_20.html

This REST API is version 11.1.2.3.600.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role



REST Resource

POST /interop/rest/11.1.2.3.600/applicationsnapshots/{applicationSnapshotName}/
contents

Note:

For Data Management uploads, use the following JSON format for the query parameter:

/interop/rest/11.1.2.3.600/applicationsnapshots/
{applicationSnapshotName}/contents?extDirPath=inbox

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/octet-stream

The following table summarizes the client request.

Table 9-20 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
applicationSnapsho tName	Name of the application snapshot or file name to be uploaded (for example, "Artifact Snapshot.zip" or s112.csv). A file with this name is created in the repository. If a file or folder with this name exists in the repository, an error indicates that a file or folder exists	Path	Yes	None

Name	Description	Туре	Required	Default
Name extDirPath	Used to support upload of Data Management files. Supported values include:	Query	No	None
	 inbox - Upload files into the inbox; except for Profitability and Cost Management, Oracle Enterprise Performance Management Cloud business processes look in this location for files to process profitinbox - Upload files to be processed by Profitability and Cost Management to_be_imported - Upload a Narrative Reporting snapshot that is to be imported during the next daily maintenance of the environment outbox - Upload files to the outbox for all EPM Cloud business processes except for Profitability and Cost Management <i>profitoutbox</i> - Upload files to the outbox for Profitability and Cost Management You can also use a directory under inbox, outbox, profitinbox, and profitoutbox, for example, inbox/ <i>directory_name</i> Example: "extDirPath= inbox/<i>directory_name</i>" to 			
	upload files to a directory within the inbox for processing by Data Management.			
	Upload : /interop/rest/11.1.2.3.600/ applicationsnapshots/applicationSnapshotName/ contents?extDirPath=inbox%2Fdm_folder			
	Example: "extDirPath=inbox" where inbox is the folder where the Data Management file is to be uploaded Example of query parameters in JSON format for Data Management Upload: /interop/rest/11.1.2.3.600/ applicationsnapshots/{applicationSnapshotName}/ contents?extDirPath=inbox			

Table 9-20 (Cont.) Parameters

Response

Supported Media Types: application/json

Table 9-21 Parameters

Name	Description		
details	In case of errors, details are published with the error string		
status	See Migration Status Codes		
links	Detailed information about the link		
href	Links to API call		
action	The HTTP call type		
rel	Possible values: self, recreate service		
data	Parameters as key value pairs passed in the request		

Example of Response Body



The following shows an example of the response body in JSON format.

```
{
    "status":0,
    "details":null,
    "links":[{
        "data":null,
        "action":"POST",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/applicationsnapshots/
{applicationSnapshotName}/contents
```

REST API Examples with Postman

See REST API Examples with Postman.

Upload Sample Code

```
Example 9-7 Java Sample – 11.1.2.3.600
```

Prerequisites: json.jar

```
/**
 *
 * Simple Implementation class to execute Upload functionality for API
version 11.1.2.3.600
 */
public class UploadFile
{
   private final static String userName ; // User name
   private final static String password ; // Password
   private final static String serverUrl; // Server URL
   private String filePath ; //zip File to be Uploaded
   private String extDirPath = "inbox"; // keep it null for uploading to
root directory
    private String details = null;
    public void uploadFile() {
        boolean status = true;
        trv {
            status = sendFileContents(filePath, extDirPath);
            if(status)
                System.out.println("Uploaded contents to " + new
File(filePath).getName());
            else
                System.err.println(details);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```



```
private boolean sendFileContents (String filePath, String extDirPath)
            throws Exception {
        HttpURLConnection connection = null;
        FileInputStream content = null;
        File file = new File(filePath);
        try {
            String restURL = String.format(
                    "%s/interop/rest/11.1.2.3.600/applicationsnapshots/%s/
contents",
                    serverUrl, URLEncoder.encode(file.getName(), "UTF-8"));
            if(null != extDirPath)
                restURL = restURL + "?extDirPath="+extDirPath;
            URL url = new URL(restURL);
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod("POST");
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            String creds = null;
            creds = userName + ":" + password;
            connection.setRequestProperty("Authorization",
                    "Basic " + new
sun.misc.BASE64Encoder().encode(creds.getBytes()));
            connection.setRequestProperty("Content-Type", "application/octet-
stream");
            content = new FileInputStream(file);
            OutputStream paramOutputStream = connection.getOutputStream();
            if (content != null) {
                byte[] arrayOfByte = new byte[4096];
                boolean hasMore = true;
                while (hasMore) {
                    int j = content.read(arrayOfByte);
                    if (j < 0) {
                        hasMore = false;
                        continue;
                    }
                    paramOutputStream.write(arrayOfByte, 0,
j);
                }
            }
            int statusCode = connection.getResponseCode();
            String responseBody =
getStringFromInputStream(connection.getInputStream());
            if (statusCode == 200 && responseBody != null) {
                int commandStatus = getCommandStatus(responseBody);
                if (commandStatus == -1) {
```

```
getJobStatus(fetchPingUrlFromResponse(responseBody, "Job
Status"), "GET");
                }
                if (commandStatus == 0) {
                    return true;
                }
                else{
                    details = getDetails(responseBody);
                }
            }
            return false;
        } finally {
            if (null != content)
                content.close();
            if (connection != null)
                connection.disconnect();
        }
    }
/**
* Method to retrieve the error message
 * @param response
 * @return String details
 * @throws Exception
*/
    private String getDetails (String response) throws Exception {
        JSONObject json = new JSONObject(response);
        if (!JSONObject.NULL.equals(json.get("details")))
            return json.getString("details");
        else
            return "NA";
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Download

Downloads a file from the repository to the current directory in the local environment.

If the content type of the response is application/JSON, then an error with details is displayed on the server. Otherwise, the content of the file is streamed through the response.

Note: The entire path to the file must be encoded, for example, changing / to %2F and spaces to %20. This API can be used to download files up to 1GB in a single request.



For example, change this path to an .HTML file in the apr directory:

apr/2020-03-04 23 07 20/2020-03-04 23 07 20.html

to this:

apr%2F2020-03-04%2023 07 20%2F2020-03-04%2023 07 20.html

This REST API is version 11.1.2.3.600.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

GET /interop/rest/{api_version}/applicationsnapshots/{applicationSnapshotName}/
contents

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

The following table summarizes the GET request parameters.

Name	Description	Туре	Required	Default
applicationSnapsho tName	Application snapshot name or file name to download (for example, "Artifact Snapshot" or s112.csv).	Path	Yes	None
	The entire applicationSnapshotName must be encoded before sending the request.			
	To download a particular file, provide the path to that file as the value of applicationSnapshotName. For example, to download a Data Management file called s112.csv in the inbox, refer to the file as "inbox\s112.csv" in the path parameter.			
	To download the Activity Reports or access log, use the fully qualified file name as shown in the output of List Files.			
	For example, to download a specific file from the apr directory, use the following format: pr%2F2020-03-04%0A23_07_20%2F2020-03-04%0A23_07 _20.html apr%2F%0A2020-03-04%2023_07_20%2F%0Aaccess_log. zip apr%2F%0A2020-03-04%2023_07_20%2F%0Aactivityrep ort.json.			



Table 9-22 (Cont.) Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None

Example of Request

https://<BASE-URL>/interop/rest/11.1.2.3.600/applicationsnapshots/Vision.zip/
contents

Table 9-23 Parameters

Name	Description
Details	In case of errors, details are published with the error string
Status	See Migration Status Codes
Links	Detailed information about the link
Href	Links to API call
Action	The HTTP call type
Rel	Possibly value: self
Data	Parameters as key value pairs passed in the request

Response

Supported Media Types: application/json or application/octet-stream

Example of Response Body

The following shows an example of the response body in JSON format in case there is an error during download.

```
{
   "details": "Invalid file : Vision.zip",
   "status":1,
   "links":[{
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/Vision.zip/contents",
        "action":"GET",
        "rel":"self",
        "data":null
    }]
}
```

Download Sample Code

Example 9-8 Java Sample – downloadFile.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java.

public class DownloadFile600 {



```
private String serverUrl; // PBCS server URL
    private String apiVersion = "11.1.2.3.600";
    private String userName; // Server Username
   private String password; // Server Password
    private static String fileName; // file to be downloaded.
   public DownloadFile600(String userName, String password, String
serverUrl, String apiVersion) {
        super();
        this.serverUrl = serverUrl;
        this.apiVersion = apiVersion;
        this.userName = userName;
        this.password = password;
    }
    public void downloadFile(String fileName) throws Exception {
        HttpURLConnection connection = null;
        InputStream inputStream = null;
        FileOutputStream outputStream = null;
        try {
            fileName = fileName.replaceAll("/", "\\\\");
            URL url = new URL(String.format("%s/interop/rest/%s/
applicationsnapshots/%s/contents", serverUrl,
                    apiVersion, URLEncoder.encode(fileName, "UTF-8")));
            System.out.println("DOWNLOAD URL: " + url);
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod("GET");
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization",
                    "Basic " + new sun.misc.BASE64Encoder().encode((userName
+ ":" + password).getBytes()));
            int status = connection.getResponseCode();
            if (status == 200) {
                if (connection.getContentType() != null &&
connection.getContentType().equals("application/json")) {
                    JSONObject json = new
JSONObject(getStringFromInputStream(connection.getInputStream()));
                    System.out.println("Error downloading file : " +
json.getString("details"));
                } else {
                    inputStream = connection.getInputStream();
                    outputStream = downloadContent(connection, inputStream);
                }
            } else {
                throw new Exception("Http status code: " + status);
        } finally {
            if (connection != null)
                connection.disconnect();
            if (outputStream != null)
                outputStream.close();
```

```
if (inputStream != null)
                inputStream.close();
        }
    }
    private FileOutputStream downloadContent(HttpURLConnection connection,
InputStream inputStream)
            throws FileNotFoundException, IOException {
        FileOutputStream outputStream;
        String downloadedFileName = fileName;
        if (fileName.lastIndexOf("/") != -1) {
            downloadedFileName = fileName.substring(fileName.lastIndexOf("/")
+ 1);
        }
        String ext = ".zip";
        if (connection.getHeaderField("fileExtension") != null) {
            ext = "." + connection.getHeaderField("fileExtension");
        }
        if (fileName.lastIndexOf(".") != -1 && fileName.lastIndexOf(".") != 0)
            ext = fileName.substring(fileName.lastIndexOf(".") + 1);
        outputStream = new FileOutputStream(new File(downloadedFileName +
ext));
        int bytesRead = -1;
        byte[] buffer = new byte[5 * 1024 * 1024];
        while ((bytesRead = inputStream.read(buffer)) != -1)
            outputStream.write(buffer, 0, bytesRead);
        System.out.println("File download completed.");
        return outputStream;
    }
}
```

View and Delete Files

This table shows the REST APIs to view and delete files. These REST APIs are version 11.1.2.3.600 and v2.

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-24 View and Delete	Files
----------------------------	-------

Task	Request	REST Resource	_
List Files (v11.1.2.3.600)	GET	/applicationsnapshots	
List Files (v2)	GET	/interop/rest/v2/files/list	



Task	Request	REST Resource
Delete Files (v11.1.2.3.600)	DELETE	/applicationsnapshots/ {applicationSnapshotName}
Delete Files (v2)	DELETE	/interop/rest/v2/files/delete
Delete Files (v3)	POST	/interop/rest/v3/files/delete

List Files (v11.1.2.3.600)

This API (v11.1.2.3.600) lists the files in the Planning repository and returns information about the available file and application snapshots.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

This API provides details such as name, type, size and last modified time. Size and last modified are not available for LCM snapshots. See About EPM Automate in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud*.

This REST API is version 11.1.2.3.600.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

GET /interop/rest/{api version}/applicationsnapshots

Supported Media Types: application/json

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Response

Table 9-25 Parameters

Name	Description
Details	Will be published in case of error with the error string
Status	See Migration Status Codes
Items	



Name	Description
Name	Name of the application snapshot
Туре	Can be LCM or EXTERNAL
	Type signifies if this snapshot is for LCM or EXTERNAL. LCM indicates that the file is an LCM snapshot. EXTERNAL indicates that files are not LCM, such as Planning files.
Size	Size of the application snapshot in bytes. Available only for type EXTERNAL
Lastmodifiedtim e	Time in Long value as per the last modified time of the file. Available only for type EXTERNAL
Links	Detailed information about the link
Href	Link to API call/ status API
Action	The HTTP call type
Rel	Will be self
Data	Parameters as key value pairs passed in the request

Table 9-25 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "status":0,
    "items":[{
        "name":"sample.csv",
        "type":"EXTERNAL",
        "size":"18",
        "lastmodifiedtime":"1422534438000"
        },{
        "name":"snapshot1",
        "type":"LCM",
        "size":null,
        "lastmodifiedtime":null
    }],
    "details":null,
    "links":[{
        "data":null,
        "action":"GET",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots",
        "rel":"self"
    }]
}
```

```
List Files Sample Code
```

Example 9-9 Java Sample – listFiles.java

Prerequisites: json.jar



```
Common Functions: See Common Helper Functions for Java
```

```
11
// BEGIN - List all the files in PBCS
11
public void listFiles() throws Exception {
    String urlString = String.format("%s/interop/rest/%s/
applicationsnapshots", serverUrl, apiVersion);
    String response = executeRequest(urlString, "GET", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        if (json.get("items").equals(JSONObject.NULL))
            System.out.println("No files found");
        else {
            System.out.println("List of files :");
            JSONArray itemsArray = json.getJSONArray("items");
            JSONObject jObj = null;
            for (int i=0; i < itemsArray.length(); i++) {</pre>
                jObj = (JSONObject)itemsArray.get(i);
                System.out.println(jObj.getString("name"));
            }
        }
    }
}
11
// END - List all the files in PBCS
11
```

Example 9-10 cURL Sample- ListFiles.sh

Prerequisites: json.jar

Common Functions: See Common Helper Functions for cURL

```
funcListFiles() {
    url=$SERVER_URL/interop/rest/$API_VERSION/applicationsnapshots
    funcExecuteRequest "GET" $url
    list=`cat response.txt | jq 'select(.items != null) | .items[].name'`
    if [[ ! -z $list ]]; then
        echo $list
    else
        echo "No files found"
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)
```

Example 9-11 Groovy Sample- ListFiles.groovy

Prerequisites: json.jar



See CSS Common Helper Functions for Groovy

```
def listFiles() {
   def url;
    try {
            url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/
applicationsnapshots")
    } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
    }
    response = executeRequest(url, "GET", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0 ) {
        def items = object.items
        if (items == null) {
            println "No files found"
        }
        else {
            println "List of files :"
            items.each{
                println it.name
            }
        }
    } else {
        println "Error occurred while listing files"
        if (object.details != null)
                println "Error details: " + object.details
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

List Files (v2)

This REST API (v2) lists the files in the repository and returns information about the available file and application snapshots.

This API provides details such as name, type, size and last modified time. Size and modified time are not available for LCM snapshots. See About EPM Automate in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud*.

This REST API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role



REST Resource

GET /interop/rest/v2/files/list

Supported Media Types: application/json

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Example URL

https://<BASE-URL>/interop/rest/v2/files/list

Response

Table 9-26 Parameters

Name	Description
Details	Will be published in case of error with the error string
Status	See Migration Status Codes
Items	
Name	Name of the file or application snapshot
Туре	Can be LCM or EXTERNAL
	Type signifies if this is an LCM snapshot or not. LCM indicates that the file is an LCM snapshot. EXTERNAL indicates that the file is not an LCM snapshot, such as a Planning file.
Size	Size of the file in bytes. Available only for type EXTERNAL
Lastmodifiedtim e	Last modified time of the file in milliseconds since 1970-01-01. Available only for type EXTERNAL
Links	Detailed information about the link
Href	Link to API call/ status API
Action	The HTTP call type
Rel	Will be self
Data	null

Example of Response Body

The following shows an example of the response body in JSON format.

```
"status":0,
"items":[{
"name":"sample.csv",
"type":"EXTERNAL",
```



{

```
"size":"18",
"lastmodifiedtime":"1422534438000"
},{
"name":"Artifact Snapshot",
"type":"LCM",
"size":null,
"lastmodifiedtime":null
}],
"details":null,
"links":[{
"data":null,
"action":"GET",
"href": "https://<BASE-URL>/interop/rest/v2/files/list",
"rel":"self"
}]
```

List Files Sample Code

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H
'Content-Type: application/json' 'https://<BASE-URL>/interop/rest/v2/files/
list'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Delete Files (v11.1.2.3.600)

1

Use the Delete Files (v11.1.2.3.600) REST API to delete a file from the Planning repository.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

Specify the filename with path separators in percent-encoding format, for example, using %5C as the encoded value for \ (file separator). For a file named inbox/file1.csv, pass it as inbox%5Cfile1.csv. If you are calling the cURL command to trigger the REST API, you can use a backslash \ for the path separator without URL encoding. See About EPM Automate in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.

This REST API is version 11.1.2.3.600.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role



REST Resource

DELETE /interop/rest/{api_version}/applicationsnapshots/
{applicationSnapshotName

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-27 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
applicationSnapsho	Application snapshot name that needs to be deleted	Path	Yes	None
tName				

Response

Supported Media Types: application/json

Table 9-28 Parameters

Parameters	Description	
Details	Published if there is an error with the error string	
Status	See Migration Status Codes	
Links	Detailed information about the link	
Href	Links to the API call	
Action	The HTTP call type	
Rel	Possible value: self	
Data	Parameters as key value pair passed in the request	

Example of Response Body

```
{
    "status":0,
    "links":[{
        "data":null,
        "action":"DELETE",
        "rel":"self",
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss2"
    }],
```

```
"details":null
```

}

Delete Files Sample Code

Example 9-12 Java Sample – deleteFile.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN - Delete a file in PBCS
11
public void deleteFile(String fileName) throws Exception {
   String urlString = String.format("%s/interop/rest/%s/applicationsnapshots/
%s", serverUrl, apiVersion, fileName);
   String response = executeRequest(urlString, "DELETE", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0)
        System.out.println("File deleted successfully");
    else
        System.out.println("Error deleting file : " +
json.getString("details"));
}
//
// END - Delete a file in PBCS
11
```

Example 9-13 cURL Sample – DeleteFile.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcDeleteFile() {
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER_URL/interop/rest/$API_VERSION/
applicationsnapshots/$encodedFileName
    funcExecuteRequest "DELETE" $url
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Deleted successfully"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Example 9-14 Groovy Sample – DeleteFile.groovy

Prerequisites: json.jar



Common Functions: CSS Common Helper Functions for Groovy

```
def deleteFile(filename) {
    def url;
    try {
        String encodedFileName = URLEncoder.encode(filename, "UTF-8");
        url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/
applicationsnapshots/" + encodedFileName)
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "DELETE", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0)
       println "File deleted successfully"
    else {
        println "Error occurred while deleting file"
        if (object.details != null)
           println "Error details: " + object.details
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Delete Files (v2)

The Delete Files (v2) REST API deletes a file from the repository. This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. This API is backwards compatible.

Filenames that use a backslash \ as path separators must be handled using escape characters, for example, using \\ as the value for \ (the file separator). For a file named inbox\file1.csv, pass it as inbox\\file1.csv.

For more information on deleting files, see EPM Automate Commands in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.

Note: To delete files using EPM Groovy rules, use the v11.2.3.600 version of the same API instead of the v2 version.

This REST API is v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role



REST Resource

DELETE /interop/rest/v2/files/delete

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-29 Parameters

Name	Description	Туре	Required	Default
fileName	Application snapshot name that needs to be deleted	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/v2/files/delete

```
{
"fileName": "inbox/file1.csv",
}
```

Response

Supported Media Types: application/json

Table 9-30 Parameters

Parameters	Description	
Details	Published if there is an error with the error string	
Status	See Migration Status Codes	
Links	Detailed information about the link	
Href	Links to the API call	
Action	The HTTP call type	
Rel	Possible value: self	
Data	Parameters as key value pair passed in the request	

Example of Response Body

```
{
```

"status":0,



```
"links":[{
    "data":null,
    "action":"DELETE",
    "rel":"self",
    "href":"https://<BASE-URL>/interop/rest/v2/files/delete"
}],
"details":null
```

Sample cURL command

}

```
curl -X DELETE -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D
respHeader.txt -H 'Content-Type: application/json' -d
'{"fileName":"FILE_TO_BE_DELETED"}' 'https://<BASE-URL>/interop/rest/v2/files/
delete'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Delete Files (v3)

The Delete Files (v3) REST API deletes a file from the repository. This topic describes the simplified v3 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v3 API easier to use. This API is backwards compatible.

Filenames that use a backslash \ as path separators must be handled using escape characters; for example, using \\ as the value for \ (the file separator). For a file named inbox\file1.csv, pass it as inbox\\file1.csv.

For more information on deleting files, see EPM Automate Commands in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.

This API is v3.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/v3/files/delete

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-31 Parameters

Name	Description	Туре	Required	Default
fileName	File name to delete	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/v3/files/delete

```
{
"fileName": "inbox/file1.csv",
}
```

Response

Supported Media Types: application/json

Table 9-32 Parameters

Parameters	Description	
Details	Published if there is an error with the error string	
Status	See Migration Status Codes	
Links	Detailed information about the link	
Href	Links to the API call	
Action	The HTTP call type	
Rel	Possible value: self	
Data	Parameters as key value pair passed in the request	

Example Response Body

```
{
   "status":0,
   "links":[{
        "data":null,
        "action": "POST",
        "rel":"self",
        "href":"https://<EPM-CLOUD-BASE-URL>/interop/rest/v3/files/delete"
   }],
   "details":null
}
```



Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"fileName":"FILE_TO_BE_DELETED"}' 'https://<BASE-URL>/interop/rest/v3/files/
delete'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Manage Services

You can manage all available services using the following REST resources.

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-33	Manage	Services
------------	--------	----------

Task	Request	REST Resource
Get Information About All Services	GET	<pre>/interop/rest/{api_version}/services</pre>
Get Idle Session Timeout	GET	/interop/rest/{api_version}/config/ services/idlesessiontimeout
Set Idle Session Timeout	PUT	/interop/rest/{api_version}/config/ services/idlesessiontimeout
Restart the Service Instance (v1)	POST	/interop/rest/{api_version}/services/ {service_type}/resetservice
Restart the Service Instance (v2)	POST	/interop/rest/v2/config/services/reset
Run Recreate on a Service (11.1.2.3.600)	GET	/interop/rest/{api_version}/services/ {servicename}/recreate
Run Recreate on a Service (v2)	POST	/interop/rest/v2/config/services/ recreate

Get Information About All Services

Returns information about all services that you can perform in a Planning environment.

This API is version 11.1.2.3.600.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/{api_version}/services

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Response

Supported Media Types: application/json

Name	Description
api_version	Specific API version
details	In case of errors, details are published with the error string
status	See Migration Status Codes
details	In case of error, details are published with the error string
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self, PBCS recreate service, PBCS reset service - details are for PBCS recreate service
data	Parameters as key value pair passed in the request

Table 9-34 Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "details":null,
    "status":0,
    "links":[{
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/services",
        "rel":"self",
        "data":null,
        "action":"GET"
        },{
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/services/PBCS/
recreate",
        "rel":"PBCS recreate service",
        "data":null,
        "action":"POST"
        },{
    }
}
```

```
"href":"https://<EPM-CLOUD-BASE-URL>/interop/rest/11.1.2.3.600/
services/PBCS/resetservice",
    "rel":"PBCS reset service",
    "data":null,
    "action":"POST"
    }]
}
```

Get Information About All Services Sample Code

Java Sample – getInfoAboutAllServices.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN - Get services
11
public void getServices() throws Exception {
    String urlString = String.format("%s/interop/rest/%s/services",
serverUrl, apiVersion);
    String response = executeRequest(urlString, "GET", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        JSONArray linksArray = json.getJSONArray("links");
        System.out.println("Services list :");
        JSONObject jObj = null;
        for(int i=0; i < linksArray.length(); i++) {</pre>
            jObj = (JSONObject)linksArray.get(i);
            System.out.println("Service :" + jObj.getString("rel"));
            System.out.println("URL :" + jObj.getString("href"));
            System.out.println("Action :" + jObj.getString("action") + "\n");
        }
    }
}
11
// END - Get services
11
```

cURL Sample - GetInfoAboutAllServices.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcGetServices() {
    url=$SERVER_URL/interop/rest/$API_VERSION/services
    funcExecuteRequest "GET" $url
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Services list :"
        count=`echo $output | jq '.links | length'`
```



```
i=0
        while [ $i -lt $count ]; do
            rel=`echo $output | jq '.links['$i'].rel'`
            rel=`echo "$rel" | tr -d "\""`
            if [ "$rel" != "self" ]; then
                echo "Service : " `echo $output | jq '.links['$i'].rel'`
                echo "URL :" `echo $output | jq '.links['$i'].href'`
                echo "Action :" `echo $output | jq '.links['$i'].action'`
                echo ""
            fi
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – GetInfoAboutAllServices.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def getServices() {
   def url;
    try {
       url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/services")
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "GET", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0) {
        def links = object.links
        println "Services list :"
        links.each{
            if(!it.rel.equals("self")) {
                println "Service : " + it.rel
                println "URL : " + it.href
                println "Action : " + it.action + "\n"
            }
        }
    } else {
        println "Error occurred while fetching services list"
        if (object.details != null)
            println "Error details: " + object.details
    }
}
```



Get Idle Session Timeout

Returns the session timeout (in minutes) of the Oracle Enterprise Performance Management Cloud environment. After a session is idle for this duration, users are redirected to the Login page.

This API is version v2.

Required Roles

Service Administrator

REST Resource

```
GET /interop/rest/{api_version}/config/services/idlesessiontimeout
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Table 9-35 Parameters

Name	Description	Туре	Require d	Default
api_version	Specific API version (v2)	Path	Yes	None

Response

Supported Media Types: application/json

Table 9-36 Parameters

Name	Description	
details	In case of errors, details are published with the error string	
status	 0 - Operation success +ve - Operation failed, with the status signifying an error 	
timeout	Session Timeout value in minutes	
href	Link to API call	
action	HTTP call type	
rel	Possible value: self	
data	null	



Example of Response Body

```
{
    "details": null,
    "links": [{
        "rel": "self",
        "href": "<uri>/interop/rest/v2/config/services/
idlesessiontimeout",
        "data": "null",
        "action": "GET"
    }],
    "status": "0",
    "items": [{
        "timeout": "30"
    }]
}
```

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -H
'Content-Type: application/json' 'https://<BASE-URL>/interop/rest/v2/config/
services/idlesessiontimeout '
```

Set Idle Session Timeout

Changes the session timeout (in minutes) of the Oracle Enterprise Performance Management Cloud environment. The new session timeout becomes active after the next daily maintenance of the environment.

Use this API to change the default session timeout (75 minutes) to a different value. After a session is idle for the duration specified using this API, the user is redirected to the Login page.

This API is version v2.

Required Roles

Service Administrator

REST Resource

PUT /interop/rest/{api version}/config/services/idlesessiontimeout

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json



Table 9-37 Parameters

Name	Description	Туре	Require d	Default
api_version	Specific API version (v2)	Path	Yes	None
timeout	Session timeout value	Payload	Yes	None

Example of Request Body

```
{
    "timeout": "30"
}
```

Response

Supported Media Types: application/json

Table 9-38 Parameters

Name	Description	
details	In case of errors, details are published with the error string	
status	 0 - Operation success +ve - Operation failed, with the status signifying an error 	
href	Link to API call	
action	HTTP call type	
rel	Possible value: self	
data	null	

Example of Response Body

```
{
    "links": [{
        "rel": "self",
        "href": "<uri>/interop/rest/v2/config/services/
idlesessiontimeout",
        "data": null,
        "action": "PUT"
    }],
    "details": "null",
    "status": 0,
    "items": null
}
```

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"timeout":"30"}' 'https://<BASE-URL>/interop/rest/v2/config/services/
idlesessiontimeout
```



Restart the Service Instance (v1)

Use the Restart the Service Instance (v1) REST API to restart the service instance with a REST API.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

You can also use an optional AutoTune parameter to auto-tune the environment before restarting it to ensure that Essbase index caches for Block Storage Option (BSO) cubes are optimized for your application.

This API is version v1.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/{api version}/services/{service type}/resetservice

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Payload: JSON

Name	Description	Туре	Require d	Default
api_version	Specific API version	Path	Yes	None
service_type	Value for the service type. Service type can be one of the following: PBCS for Planning and Budgeting, EPBCS for Enterprise Planning and Budgeting, FCCS for Financial Consolidation and Close, TRCS for Tax Reporting, EDMCS for Enterprise Data Management, PCMCS for Profitability and Cost Management, or ARCS for Account Reconciliation.	Path	Yes	None
comment	Comment about executing the restart	Payload	Yes	None
autotune	If set to true, runs the auto tune algorithm before the restart. This ensures that Essbase index caches for BSO cubes are optimized for your application.	Payload	No	false



Example of Request Body

```
{
   "comment": "Reset requested by Administrator",
   "autotune": "true"
}
```

Response

Table 9-40 Parameters

Name	Description	
Details	In case of errors, details are published with the error string	
Status	See Migration Status Codes	
Links	Detailed information about the link	
Href	Links to API call or status API	
Action	The HTTP call type	
Rel	Possible values: self and/or Job Status.	
	If the value is set to Job Status, you can use the href to get the status of the reset service	
Data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "details":null,
    "status":0,
    "links":[{
        "href":"https://<BASE-URL>/interop/rest/v1/services/PBCS/
resetservice",
        "rel":"self",
        "data":null,
        "action":"POST"
        },{
        "href":"https://<BASE-URL>/interop/rest/v1/services/PBCS/resetservice/
777",
        "rel":"Job Status",
        "data":null,
        "action":"GET"
    }]
}
```

Restart the Service Sample Code

Example 9-15 Java Sample – ResetServices.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN - Reset services
11
public void hardReset(String comment) throws Exception {
    Scanner in = new Scanner(System.in);
    System.out.println("Are you sure you want to restart the service instance
(yes/no): no ?[Press Enter]");
    String s = in.nextLine();
    if (!s.equals("yes")) {
        System.out.println("User cancelled the reset command");
        System.exit(0);
    }
    JSONObject params = new JSONObject();
    params.put("comment", java.net.URLEncoder.encode(comment));
      params.put("autotune", "true");
    String urlString = String.format("%s/interop/rest/%s/services/PBCS/
resetservice", serverUrl, lcmVersion);
   String response = executeRequest(urlString, "POST", params.toString(),
"application/json");
    getJobStatus(fetchPingUrlFromResponse(response, "Job Status"),"GET");
}
11
// END - Reset services
11
```

Example 9-16 cURL Sample – ResetServices.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcHardReset() {
   echo "Are you sure you want to restart the service instance (yes/no): no ?
[Press Enter] "
   read toCreate
    if [ $toCreate != "yes" ]; then
        echo "User cancelled the reset command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$LCM VERSION/services/PBCS/resetservice
    comment=$(echo $1 | sed -f urlencode.sed)
    param="{\"comment\":\"$comment\", \"autotune\":\"true\"}"
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started hard reset succesfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
```



```
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Example 9-17 Groovy Sample – ResetServices.groovy

```
Prerequisites: json.jar
```

}

Common Functions: See CSS Common Helper Functions for Groovy

```
def hardReset(comment) {
    def userInput = System.console().readLine 'Are you sure you want to
restart the service instance (yes/no): no ?[Press Enter] '
    if (userInput.equals("yes")) {
        def url;
        JSONObject params = new JSONObject();
        try {
            params.put("comment", comment);
            params.put("autotune", "true");
            url = new URL(serverUrl + "/interop/rest/" + lcmVersion + "/
services/PBCS/resetservice");
        } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
        }
        response = executeRequest(url, "POST", params.toString(),
"application/json");
        response = executeRequest(url, "POST", payload);
        if (response != null) {
            getJobStatus(fetchPingUrlFromResponse(response, "Job
Status"), "GET");
       }
    } else {
        println "User cancelled the resetservice command"
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Restart the Service Instance (v2)

Use the Restart the Service Instance (v2) REST API to restart the service instance.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. This API is backwards compatible.

You can also use an optional AutoTune parameter to auto-tune the environment before restarting it to ensure that Essbase index caches for Block Storage Option (BSO) cubes are optimized for your application.



This REST API is version v2.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/config/services/reset

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Payload: JSON

Table 9-41Parameters

Name	Description	Туре	Require d	Default
api_version	Specific API version	Path	Yes	None
comment	Comment about executing the restart	Payload	Yes	None
autotune	If set to true, runs the auto tune algorithm before the restart. This ensures that Essbase index caches for BSO cubes are optimized for your application.	Payload	No	false

Example of Request Body

```
{
   "comment": "Reset requested by Administrator",
   "parameters": {
        "autotune": "false"
    }
}
```

Response

Table 9-42 Parameters

Name	Description	
Details	In case of errors, details are published with the error string	
Status	See Migration Status Codes	
Links	Detailed information about the link	
Href	Links to API call or status API	



Name	Description
Action	The HTTP call type
Rel	Possible values: self and/or Job Status.
	If the value is set to Job Status, you can use the href to get the status of the reset service
Data	Parameters as key value pairs passed in the request

Table 9-42 (Cont.) Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "details": null,
    "status": 0,
    "links": [{
        "href": "https://<URL>/interop/rest/v2/config/services/reset",
        "rel": "self",
        "data": null,
        "action": "POST"
    },
    {
        "href": "https://<URL>/interop/rest/v2/config/status/service/
hardreset/1",
        "rel": "Job Status",
        "data": null,
        "action": "GET"
    }]
}
```

Sample cURL Command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d ' {"comment":"<COMMENT>","parameters":
{"autotune":"false"}}' 'https://<BASE-URL>/interop/rest/v2/config/services/
reset'
```

Sample cURL Code

#!/bin/sh

```
USERNAME="<USERNAME>"
PASSWORD="<PASSWORD>"
SERVER URL="<SERVICE URL>"
```

APP_NAME="Vision" API_VERSION="v2"

```
funcRemoveTempFiles() {
   for var in "$@"
   do
```



```
if [ -f $var ]; then
            rm $var
        fi
    done
}
funcPrintErrorDetails() {
   contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr -d
[:space:]`
   if [ ! -z $contentType ] && [[ $contentType = *"application/json"* ]];
then
        output=`cat $1`
        error=`echo $output | jq '.details'`
        echo "Error details: " $error
    fi
}
funcExecuteRequest() {
    if [ ! -z "$4" ]; then
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $4" -d "$3" $2`
    else
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $3" $2`
    fi
    if [ $statusCode != 200 ]; then
        echo "Error executing request"
        if [ $statusCode != 000 ]; then
            echo "Response error code : " $statusCode
            funcPrintErrorDetails "response.txt"
            funcRemoveTempFiles "respHeader.txt" "response.txt"
        fi
        exit 0
    fi
}
funcGetStatus() {
   output=`cat response.txt`
    count=`echo $output | jq '.links | length'`
   i=0
   pingUrl=""
    while [ $i -lt $count ]; do
        rel=`echo $output | jq '.links['$i'].rel'`
        rel=`echo "$rel" | tr -d "\""`
        if [ "$rel" == "Job Status" ]; then
                pingUrl=`echo $output | jq '.links['$i'].href'`
                pingUrl=`echo "$pingUrl" | tr -d "\""`
        fi
        i=`expr $i + 1`
    done
    echo $pingUrl
    completed="false"
```



```
while [ $completed != "true" ]; do
        statusCode2=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD"
-o "pingResponse.txt" -H "Content-Type: application/json" "$pingUrl"`
        if [ $statusCode2 == 200 ]; then
            status2=`jq '.status' pingResponse.txt`
            if [ $status2 != -1 ]; then
                completed="true"
                echo "Job completed"
            else
                echo "Please wait..."
                sleep 20
            fi
        else
            echo "Please wait..."
            sleep 20
        fi
        funcRemoveTempFiles "pingResponse.txt"
    done
}
funcHardReset() {
    echo "Are you sure you want to restart the service instance (yes/no): no?
[Press Enter] "
   read toReset
    if [ $toReset != "yes" ]; then
        echo "User cancelled the reset command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$API VERSION/config/services/reset
    comment=$(echo $1)
    param="{\"comment\":\"${comment}\",\"parameters\":
{\"autotune\":\"false\"}}"
    funcExecuteRequest "POST" "$url" "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ "${status}" == -1 ]; then
        echo "Started hard reset succesfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcRecreateService() {
    removeAll=$1
    essbaseChange=$2
    tempServiceType=$3
    echo "Are you sure you want to recreate the EPM environment (yes/no): no?
```

```
[Press Enter] "
   read toCreate
    if [ $toCreate != "yes" ]; then
        echo "User cancelled the recreate command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$API VERSION/config/services/recreate
    param="{\"parameters\":{\"removeAll\":\"${removeAll}}
\", \"essbaseChange\":\"${essbaseChange}\", \"tempServiceType\":\"$
{tempServiceType}\"}}"
    funcExecuteRequest "POST" "$url" "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ status == -1 ]; then
        echo "Started recreating the environment successfully"
                funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
if [[ "$#" != "1" ]]; then
    echo "Mandatory argument missing"
    echo "Usage: EPMRestSamples <option>"
    echo " where <option> is -recreate or -reset"
    exit 1
fi
if [ "${1}" == "-reset" ]; then
    funcHardReset "POC Exit Criteria Check - cURL"
elif [ "${1}" == "-recreate" ]; then
    funcRecreateService "false" "default" ""
else
   echo "Incorrect usage"
    echo "Usage: EPMRestSamples <option>"
   echo " where <option> is -recreate or -reset"
    exit 1
fi
```

Sample Java Code

```
package com.oracle.test;
import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStreamWriter;
```

```
import java.net.HttpURLConnection;
import java.net.URL;
import java.util.Scanner;
import java.util.Base64;
import org.json.JSONArray;
import org.json.JSONObject;
/*
 * EPM Rest Samples.
 * The userName variable uses the format <domain>.<username>.
*/
public class EPMRestSamples {
                                       // EPMCloud user name
   private String userName;
   private String password;
                                       // EPMCloud user password
   private String serverUrl;
                                       // EPMCloud server URL
   private String apiVersion="v2";
                                       // Version of the EPMCloud Rest API
   private long startTime;
   private long endTime;
   private long maxLoopTime=(60 * 60 * 1000);
   public static void main(String[] args) {
       try {
            if(null == args || args.length != 1) {
                System.err.println("Mandatory argument missing");
                System.err.println("Usage: EPMRestSamples <option>");
                System.err.println(" where <option> is -recreate or -reset");
                System.exit(1);
            }
            // TODO: Use appropriate username, password, and URL
            EPMRestSamples samples = new EPMRestSamples(
                "<USERNAME>", "<PASSWORD>", "<SERVICE URL>");
            String option = args[0];
            if("-reset".equalsIgnoreCase(option)) {
                samples.hardReset("POC Exit Criteria Check - Java");
            }
            else if("-recreate".equalsIgnoreCase(option)) {
               samples.recreateService("false", "default", "");
            1
            else {
                System.err.println("Incorrect usage");
                System.err.println("Usage: EPMRestSamples <option>");
                System.err.println(" where <option> is -recreate or -reset");
                System.exit(1);
            }
        }
       catch (Throwable x) {
            System.err.println("Error: " + x.getMessage());
        }
    }
```

```
public EPMRestSamples(String userName, String password, String serverUrl)
throws Exception {
        this.userName = userName;
        this.password = password;
        this.serverUrl = serverUrl;
    }
    private String getStringFromInputStream(InputStream is) {
        BufferedReader br = null;
        StringBuilder sb = new StringBuilder();
        String line;
        try {
            br = new BufferedReader(new InputStreamReader(is));
            while ((line = br.readLine()) != null) {
                sb.append(line);
            }
        }
        catch (IOException e) {
            e.printStackTrace();
        finally {
            if (br != null) {
                try { br.close(); }
                catch (IOException e) { e.printStackTrace(); }
        }
        return sb.toString();
    }
    private String executeRequest(String urlString, String requestMethod,
String payload, String contentType) throws Exception {
        HttpURLConnection connection = null;
        try {
            URL url = new URL(urlString);
            Base64.Encoder encoder = Base64.getEncoder();
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod(requestMethod);
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization", "Basic " +
encoder.encodeToString((userName + ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", contentType);
            if (payload != null) {
                OutputStreamWriter writer = new
OutputStreamWriter(connection.getOutputStream());
                writer.write(payload);
                writer.flush();
            }
            int status = connection.getResponseCode();
            if (status == 200 || status == 201) {
```

```
return getStringFromInputStream(connection.getInputStream());
            }
            throw new Exception("Http status code: " + status);
        }
        finally {
            if (connection != null) { connection.disconnect(); }
        }
    }
   private void getJobStatus(String pingUrlString, String methodType) throws
Exception {
        boolean completed = false;
        while (!completed) {
            String pingResponse = null;
            try {
                pingResponse = executeRequest(pingUrlString, methodType,
null, "application/json");
            catch (Exception e) {
                if(e instanceof java.net.ConnectException || e instanceof
java.net.SocketException) {
                    if(System.currentTimeMillis()<endTime) {</pre>
                        System.out.println("Processing. Please wait...");
                        Thread.sleep(60000);
                        continue;
                    }
                    throw new Exception("Command timeout..");
                ł
                throw e;
            }
            JSONObject json = new JSONObject(pingResponse);
            int status = json.getInt("status");
            if (status == -1) {
                try {
                    System.out.println("Processing. Please wait...");
                    Thread.sleep(20000);
                }
                catch (InterruptedException ie) {
                    completed = true;
                    throw ie;
                }
            }
            else {
                if (status > 0) {
                    System.out.println("Error occurred: " +
json.getString("details"));
                }
                else {
                    System.out.println("Execution completed successfully");
                completed = true;
```

```
}
       }
    }
    public String fetchPingUrlFromResponse(String response, String retValue)
throws Exception {
        String pingUrlString = null;
        JSONObject jsonObj = new JSONObject(response);
        int resStatus = jsonObj.getInt("status");
        if (resStatus == -1) {
            JSONArray lArray = jsonObj.getJSONArray("links");
            for (int i = 0; i < lArray.length(); i++) {</pre>
                JSONObject arr = lArray.getJSONObject(i);
                if (arr.get("rel").equals(retValue))
                    pingUrlString = (String) arr.get("href");
            }
        }
        return pingUrlString;
    }
    public void hardReset(String comment) throws Exception {
        Scanner in = new Scanner(System.in);
        System.out.print("Are you sure you want to restart the service
instance (yes/no): no? [Press Enter] ");
        String s = in.nextLine();
        if (!s.equals("yes")) {
            System.out.println("User cancelled the recreate command");
            System.exit(0);
        }
        JSONObject params = new JSONObject();
        params.put("comment", comment);
        JSONObject innerParams = new JSONObject();
        innerParams.put("autotune", "true");
        params.put("parameters", innerParams);
        String urlString = String.format("%s/interop/rest/%s/config/services/
reset", serverUrl, apiVersion);
        startTime=System.currentTimeMillis();
        endTime = startTime+maxLoopTime;
        String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
        getJobStatus(fetchPingUrlFromResponse(response, "Job Status"),"GET");
    }
    public void recreateService(String removeAll, String essbaseChange,
String tempServiceType) throws Exception {
        Scanner in = new Scanner(System.in);
        System.out.print("Are you sure you want to recreate the EPM
environment (yes/no): no ?[Press Enter] " );
        String s = in.nextLine();
        if (!s.equals("yes")) {
```

```
System.out.println("User cancelled the recreate command");
            System.exit(0);
        }
        JSONObject params = new JSONObject();
        JSONObject innerParams = new JSONObject();
        innerParams.put("tempServiceType", tempServiceType);
        innerParams.put("essbaseChange", essbaseChange);
        innerParams.put("removeAll", removeAll);
        params.put("parameters", innerParams);
        String urlString = String.format("%s/interop/rest/%s/config/services/
recreate", serverUrl, apiVersion);
        startTime=System.currentTimeMillis();
        endTime = startTime+maxLoopTime;
        String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
        getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
    }
}
```

Sample Groovy Code

```
package com.groovy
import org.json.JSONObject
import groovy.json.JsonSlurper
// TODO: Use appropriate username, password, and url
username="<USERNAME>"
password="<PASSWORD>"
serverUrl="<SERVICE URL>"
endTime=0
maxLoopTime=(60 * 60 * 1000)
apiVersion = "v2"
userCredentials = username + ":" + password
basicAuth = "Basic " + userCredentials.bytes.encodeBase64().toString()
def getResponse(is) {
    BufferedReader br = new BufferedReader(new InputStreamReader(is))
    StringBuilder sb = new StringBuilder()
    String line
    while ((line = br.readLine()) != null) {
        sb.append(line+"\n")
    }
    br.close()
    return sb.toString()
}
def getJobStatus(pingUrlString, methodType) {
```



```
def pingUrl = new URL(pingUrlString)
    def completed = false
    while (!completed) {
        try {
            pingResponse = executeRequest(pingUrl, methodType, null,
"application/json")
        }
        catch(exp) {
            if(exp instanceof java.net.ConnectException || exp instanceof
java.net.SocketException) {
                if(System.currentTimeMillis()<endTime) {</pre>
                    println("Processing. Please wait...")
                    Thread.sleep(60000)
                    continue
                }
                throw new Exception ("Command timeout..")
            }
        }
        status = getJobStatusFromResponse(pingResponse)
        if (status == "Processing") {
            try {
                println "Processing. Please wait..."
                Thread.sleep(5000)
            }
            catch (InterruptedException e) {
                completed = true
            }
        }
        else {
            println "Execution completed successfully"
            completed = true
        }
    }
}
def getJobStatusFromResponse(response) {
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == -1) { return "Processing" }
    else if (status == 0) { return "Completed" }
   else { return object.details }
}
def executeRequest(url, requestType, payload, contentType) throws Exception {
   HttpURLConnection connection = (HttpURLConnection) url.openConnection()
    connection.setDoOutput(true)
    connection.setInstanceFollowRedirects(false)
    connection.setRequestMethod(requestType)
    connection.setRequestProperty("Content-Type", contentType)
    connection.setRequestProperty("Authorization", basicAuth)
    connection.setUseCaches(false)
    if (payload != null) {
        OutputStreamWriter writer = new
```

```
OutputStreamWriter(connection.getOutputStream())
        writer.write(payload)
        writer.flush()
    }
    int statusCode
    try { statusCode = connection.responseCode }
    catch (all) { throw all }
    def response
    if (statusCode == 200 || statusCode == 201) {
        if (connection.getContentType() != null && !
connection.getContentType().startsWith("application/json")) {
            println "Error occurred in server"
            System.exit(0)
        }
        InputStream is = connection.getInputStream()
        if (is != null) { response = getResponse(is) }
    }
    else {
        if (statusCode == 503) {
            throw new Exception ("Service Unavailable")
        }
        InputStream is = connection.getErrorStream()
        if (is != null && connection.getContentType() != null &&
            connection.getContentType().startsWith("application/json")) {
            println getJobStatusFromResponse(getResponse(is))
        }
    }
    connection.disconnect()
    return response
def getUrlFromResponse(scenario, response, relValue) {
    def object = new JsonSlurper().parseText(response)
    def pingUrlStr
    if (object.status == -1) {
        println "Started - " + scenario
        def links = object.links
        links.each{
            if (it.rel.equals(relValue)) {
                pingUrlStr=it.href
        }
    }
    else {
        println "Error details: " + object.details
        System.exit(0)
    }
    return pingUrlStr
}
def hardReset(comment) {
```

```
def scenario = "Hard reset"
    def toReset = System.console().readLine 'Are you sure you want to restart
the service instance (yes/no): no? [Press Enter] '
    if (!toReset.equals("yes")) {
        println "User cancelled the resetService command"
        System.exit(0)
    }
    def url
    JSONObject params = new JSONObject()
    JSONObject innerParams = new JSONObject()
    try {
        params.put("comment", comment)
        innerParams.put("autotune", "true")
        params.put("parameters", innerParams)
        url = new URL(serverUrl+"/interop/rest/" + apiVersion + "/config/
services/reset")
   }
    catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0)
    }
    endTime=System.currentTimeMillis() +maxLoopTime
    response = executeRequest(url, "POST", params.toString(), "application/
json")
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job
Status"), "GET")
    }
def recreateService(removeall,essabaseoption,tempServiceType) {
    def scenario="Recreate"
    def toCreate = System.console().readLine 'Are you sure you want to
recreate the EPM environment (yes/no): no? [Press Enter] '
    if (!toCreate.equals("yes")) {
        println "User cancelled the recreate command"
        System.exit(0)
    }
    def url
    JSONObject params = new JSONObject()
    JSONObject innerParams = new JSONObject()
    try {
        innerParams.put("tempServiceType", tempServiceType)
        innerParams.put("essbaseChange", essabaseoption)
        innerParams.put("removeAll", removeall)
        params.put("parameters", innerParams)
        url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/config/
```

```
services/recreate")
   }
    catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0)
    }
    endTime=System.currentTimeMillis() +maxLoopTime
    response = executeRequest(url, "POST", params.toString(), "application/
json")
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job
Status"), "GET")
   }
}
if (this.args == null || this.args.length != 1) {
   println "Mandatory argument missing"
    println "Usage: EPMRestSamples <option>"
   println " where <option> is -recreate or -reset"
    System.exit(1)
}
def option = this.args[0]
if("-reset".equalsIgnoreCase(option)) {
   hardReset("POC Exit Criteria Check - Groovy");
}
else if("-recreate".equalsIgnoreCase(option)) {
   recreateService("false", "default", "");
}
else {
   println "Incorrect usage"
   println "Usage: EPMRestSamples <option>"
   println " where <option> is -recreate or -reset"
   System.exit(1)
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Run Recreate on a Service (11.1.2.3.600)

The Run Recreate on a Service (v11.1.2.3.600) REST API restores an environment to a clean state by recreating the deployment.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.



You re-create the deployment to complete these tasks:

- Clean up an environment before importing a full snapshot.
- Change the business process that can be deployed in an environment.
- Change the Essbase version in use in Oracle Enterprise Performance Management Cloud environments other than Narrative Reporting, Oracle Enterprise Data Management Cloud, and Account Reconciliation, which do not use Essbase.
 By default, EPM Standard Cloud Service and EPM Enterprise Cloud Service environments are deployed with Hybrid-enabled Essbase, while legacy environments are deployed with Non-Hybrid Essbase. Downgrading the deployment of Hybrid-enabled Essbase in EPM Standard Cloud Service and EPM Enterprise Cloud Service environments is required, if you are importing a snapshot from an environment that has a Non-Hybrid Essbase version. Upgrading the deployment of Non-Hybrid Essbase in Epd to:
 - Support the extended dimensionality in existing legacy Financial Consolidation and Close environments
 - Enable hybrid block storage (BSO) applications in legacy Enterprise Planning and Planning Modules environments

For detailed information about Hybrid Essbase and the considerations for upgrading to Hybrid Essbase, see About Essbase in EPM Cloud in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.

Caution:

- This API deletes the existing application and, optionally, all user defined artifacts from the environment. Additionally, it re-creates the database and removes all existing data. After recreating the service, you can create a new business process or import one using REST APIs, Migration, or EPM Automate.
- This API deletes migration history. As a result, the Migration Status Report available in Migration will not contain historic information.
- Before using this API, perform a complete backup of the environment. You can create a backup snapshot by executing runDailyMaintenance.

This API is version 11.1.2.3.600.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/{api version}/services/{servicename}/recreate

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded



Table 9-43 P	arameters
--------------	-----------

Name	Description	Туре	Require d	Default
api_version	Specific API version	Path	Yes	None
servicename	Name of the service for which recreate needs to be run, such as PBCS	Path	Yes	None
tempServiceType	Optionally, convert an environment to a different service environment. The business processes that you can deploy in an environment is governed by the type of subscription that you have. For example, if you have an EPM Standard Cloud Service subscription, you cannot create a FreeForm application after converting the environment from Account Reconciliation to Planning. If you have an EPM Enterprise Cloud Service subscription, you can create any business process in your environment after changing the service type appropriately. See "About the New EPM Cloud Services" in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.	Payload	No	None
	The behavior of this parameter is dependent on your subscription. For details and examples, see Recreate in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.			
	Acceptable tempServiceType values:			
	 ARCS to convert an environment to an Account Reconciliation environment 			
	 EDMCS to convert an environment to an Oracle Enterprise Data Management Cloud environment 			
	 EPRCS to convert an environment to a Narrative Reporting environment 			
	 PCMCS to convert an environment to a Profitability and Cost Management Cloud environment 			
	 PBCS to convert a Profitability and Cost Management environment to a Planning, Enterprise Planning, or Enterprise Profitability and Cost Management environment 			
	Note : You can create a Tax Reporting or Financial Consolidation and Close application in a new Planning environment. You do not need to change the service type of the environment.			
	When you run this REST API with tempserviceType, the serviceType change can be verified by making a REST call to /interop/ rest.			
removeAll	If set to true, deletes all the snapshots and the content of the Inbox and Outbox folders	Payload	No	None

Name	Description	Туре	Require d	Default
essbaseChange	Optionally, upgrade or downgrade the current Essbase version. The REST API retains the current Essbase version if you do not specify this option. Permissible values are:	Payload	No	None
	 upgrade to change from Non-Hybrid Essbase to Hybrid Essbase downgrade to change from Hybrid Essbase to Non-Hybrid Essbase 			
	Caution : Before using this option, read and understand the information available in About Essbase in EPM Cloud in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.			

Table 9-43 (Cont.) Parameters

Response

Table 9-44 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self and/or Job Status.
	If the value is set to Job Status, you can use the href to get the status of the recreate service
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
   "details":null,
   "status":0,
   "links":[{
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/services/PBCS/
recreate",
        "rel":"self",
        "data":null,
        "action":"POST"
        },{
        "href":"https://<BASE-URL>/interop/rest/11.1.2.3.600/services/PBCS/
recreate/777",
        "rel":"Job Status",
        "data":null,
        "action":"GET"
```

```
}]
```

}

Run Recreate on a Service Sample Code

```
Example 9-18 Java Sample – runRecreateOnAService.java
```

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
//
// BEGIN - Recreate services
//
public void recreateService(String serviceName, String serviceType, String
removeAll, String essbaseChange) throws Exception {
    Scanner in = new Scanner(System.in);
    System.out.println("Are you sure you want to recreate the EPM environment
(yes/no): no ?[Press Enter]");
    String s = in.nextLine();
    if (!s.equals("yes")) {
        System.out.println("User cancelled the recreate command");
        System.exit(0);
    }
```

```
JSONObject params = new JSONObject();
//params.put("tempServiceType", serviceType);
params.put("removeAll", removeAll);
params.put("essbaseChange", essbaseChange);
    String parameters = "parameters="+ URLEncoder.encode(params.toString(),
"UTF-8");
    String urlString = String.format(
                                                      "%s/interop/rest/%s/
services/%s/recreate", serverUrl, apiVersion, serviceName);
    String response = executeRequest(urlString, "POST", parameters,
"application/x-www-form-urlencoded");
    getJobStatus(fetchPingUrlFromResponse(response, "Job Status"),"GET");
}
11
// END - Recreate services
11
```

Example 9-19 cURL Sample – RunRecreateOnAService.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcRecreateService() {
    echo "Are you sure you want to recreate the EPM environment (yes/no):
    no ?[Press Enter]"
        read toCreate
        if [ $toCreate != "yes" ]; then
            echo "User cancelled the recreate command"
```



```
exit 0
        fi
        url=$SERVER URL/interop/rest/$API VERSION/services/EPM/recreate
        json=$(echo "{\"removeAll\":\"true\",\"essbaseChange\":\"upgrade\"}"
| sed -f urlencode.sed)
        param="parameters=$json"
        funcExecuteRequest "POST" $url $param "application/x-www-form-
urlencoded"
        output=`cat response.txt`
        status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started recreating the environment successfully"
                funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Example 9-20 Groovy Sample – RunRecreateOnAService.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def recreateService(serviceName) {
   def toCreate = System.console().readLine 'Are you sure you want to
recreate the EPM environment (yes/no): no ?[Press Enter]'
    if (!toCreate.equals("yes")) {
       println "User cancelled the recreate command"
        System.exit(0)
    }
    def url;
    JSONObject params = new JSONObject();
    try {
            //params.put("tempServiceType", serviceType);
         params.put("removeAll", "true");
         params.put("essbaseChange", "upgrade");
        url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/
services/" + serviceName + "/recreate");
    } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
    }
    response = executeRequest(url, "POST", "parameters="+param.toString(),
"application/x-www-form-urlencoded");
    if (response != null) {
        getJobStatus(response, "GET");
    }
}
```

Common Functions

See Common Helper Functions for Java



- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Run Recreate on a Service (v2)

•

Use the Run Recreate on a Service (v2) REST API to restore an environment to a clean state by recreating the deployment.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. This API is backwards compatible.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See About the REST APIs. Using this REST API requires prerequisites. See Prerequisites.

You re-create the deployment to complete these tasks:

- Clean up an environment before importing a full snapshot.
- Change the business process that can be deployed in an environment.
- Change the Essbase version in use in Oracle Enterprise Performance Management Cloud environments other than Narrative Reporting, Oracle Enterprise Data Management Cloud, and Account Reconciliation, which do not use Essbase.
 By default, EPM Standard Cloud Service and EPM Enterprise Cloud Service environments are deployed with Hybrid-enabled Essbase, while legacy environments are deployed with Non-Hybrid Essbase. Downgrading the deployment of Hybrid-enabled Essbase in EPM Standard Cloud Service and EPM Enterprise Cloud Service environments is required, if you are importing a snapshot from an environment that has a Non-Hybrid Essbase version. Upgrading the deployment of Non-Hybrid Essbase in legacy environments is required to:
 - Support the extended dimensionality in existing legacy Financial Consolidation and Close environments
 - Enable hybrid block storage (BSO) applications in legacy Enterprise Planning and Planning Modules environments

For detailed information about Hybrid Essbase and the considerations for upgrading to Hybrid Essbase, see About Essbase in EPM Cloud in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.

Caution:

- This API deletes the existing application and, optionally, all user defined artifacts from the environment. Additionally, it re-creates the database and removes all existing data. After recreating the service, you can create a new business process or import one using REST APIs, Migration, or EPM Automate.
- This API deletes migration history. As a result, the Migration Status Report available in Migration will not contain historic information.
- Before using this API, perform a complete backup of the environment. You can create a backup snapshot by executing runDailyMaintenance.

This API is version v2.

Required Roles

Service Administrator



REST Resource

POST /interop/rest/v2/config/services/recreate

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Payload: JSON

Table 9-45 Parameters

Name	Description	Туре	Require d	Default
api_version	Specific API version	Path	Yes	None



Name	Description	Туре	Require d	Default
tempServiceType	Optionally, convert an environment to a different service environment. The business processes that you can deploy in an environment is governed by the type of subscription that you have. For example, if you have an EPM Standard Cloud Service subscription, you cannot create a FreeForm application after converting the environment from Account Reconciliation to Planning. If you have an EPM Enterprise Cloud Service subscription, you can create any business process in your environment after changing the service type appropriately. See "About the New EPM Cloud Services" in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.	Payload	No	None
	The behavior of this parameter is dependent on your subscription. For details and examples, see Recreate in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.			
	Acceptable tempServiceType values:			
	ARCS to convert an environment to an Account Reconciliation environment			
	EDMCS to convert an environment to an Oracle Enterprise Data Management Cloud environment			
	EPRCS to convert an environment to a Narrative Reporting environment			
	 PCMCS to convert an environment to a Profitability and Cost Management Cloud environment 			
	 PBCS to convert a Profitability and Cost Management environment to a Planning, Enterprise Planning, or Enterprise Profitability and Cost Management environment 			
	Note : You can create a Tax Reporting or Financial Consolidation and Close application in a new Planning environment. You do not need to change the service type of the environment.			
	When you run this REST API with tempserviceType, the serviceType change can be verified by making a REST call to /interop/ rest.			
removeAll	If set to true, deletes all the snapshots and the content of the Inbox and Outbox folders	Payload	No	None



Name	Description	Туре	Require d	Default
essbaseChange	Optionally, upgrade or downgrade the current Essbase version. The REST API retains the current Essbase version if you do not specify this option. Permissible values are:	Payload	No	None
	 upgrade to change from Non-Hybrid Essbase to Hybrid Essbase downgrade to change from Hybrid Essbase to Non-Hybrid Essbase 			
	Caution : Before using this option, read and understand the information available in About Essbase in EPM Cloud in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.			

Table 9-45 (Cont.) Parameters

Example of Request Payload

```
{
  "parameters": {
    "removeAll": "true",
    "tempServiceType": "ARCS",
    "essbaseChange": "default"
  }
}
```

Response

Table 9-46 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self and/or Job Status.
	If the value is set to Job Status, you can use the href to get the status of the recreate service
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
   "details": null,
   "status": 0,
   "links": [{
        "href": "https://<BASE-URL>/interop/rest/v2/config/services/recreate",
```

```
"rel": "self",
    "data": null,
    "action": "POST"
    },
    {
        "href": "https://<BASE-URL>/interop/rest/v2/config/status/service/
recreate/1",
        "rel": "Job Status",
        "data": null,
        "action": "GET"
    }]
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d ``{"parameters":
{"removeAll":"false","essbaseChange":"upgrade", "tempServiceType":"PCMCS"}}"'
'https://<BASE-URL>/interop/rest/v2/config/services/recreate
```

Sample cURL code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
#!/bin/sh
```

```
USERNAME="<USERNAME>"
PASSWORD="<PASSWORD>"
SERVER URL="<SERVICE URL>"
APP NAME="Vision"
API VERSION="v2"
funcRemoveTempFiles() {
    for var in "$@"
    do
        if [ -f $var ]; then
            rm $var
        fi
    done
}
funcPrintErrorDetails() {
   contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr -d
[:space:]`
    if [ ! -z $contentType ] && [[ $contentType = *"application/json"* ]];
then
        output=`cat $1`
        error=`echo $output | jq '.details'`
        echo "Error details: " $error
    fi
}
```



```
funcExecuteRequest() {
    if [ ! -z "$4" ]; then
       statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $4" -d "$3" $2`
    else
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $3" $2`
    fi
    if [ $statusCode != 200 ]; then
        echo "Error executing request"
        if [ $statusCode != 000 ]; then
            echo "Response error code : " $statusCode
            funcPrintErrorDetails "response.txt"
            funcRemoveTempFiles "respHeader.txt" "response.txt"
        fi
        exit 0
    fi
}
funcGetStatus() {
   output=`cat response.txt`
    count=`echo $output | jq '.links | length'`
    i=0
   pingUrl=""
    while [ $i -lt $count ]; do
       rel=`echo $output | jq '.links['$i'].rel'`
        rel=`echo "$rel" | tr -d "\""`
        if [ "$rel" == "Job Status" ]; then
                pingUrl=`echo $output | jq '.links['$i'].href'`
                pingUrl=`echo "$pingUrl" | tr -d "\""`
        fi
        i=`expr $i + 1`
    done
    echo $pingUrl
    completed="false"
    while [ $completed != "true" ]; do
        statusCode2=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD"
-o "pingResponse.txt" -H "Content-Type: application/json" "$pingUrl"`
        if [ $statusCode2 == 200 ]; then
            status2=`jg '.status' pingResponse.txt`
            if [ $status2 != -1 ]; then
                completed="true"
                echo "Job completed"
            else
                echo "Please wait..."
                sleep 20
            fi
        else
            echo "Please wait..."
            sleep 20
        fi
        funcRemoveTempFiles "pingResponse.txt"
```

```
done
}
funcHardReset() {
    echo "Are you sure you want to restart the service instance (yes/no): no?
[Press Enter] "
   read toReset
    if [ $toReset != "yes" ]; then
        echo "User cancelled the reset command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$API VERSION/config/services/reset
    comment=$(echo $1)
   param="{\"comment\":\"${comment}\", \"parameters\":
{\"autotune":\"false\"}}"
    funcExecuteRequest "POST" "$url" "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ "${status}" == -1 ]; then
        echo "Started hard reset succesfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcRecreateService() {
    removeAll=$1
    essbaseChange=$2
    tempServiceType=$3
   echo "Are you sure you want to recreate the EPM environment (yes/no): no?
[Press Enter] "
   read toCreate
    if [ $toCreate != "yes" ]; then
        echo "User cancelled the recreate command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$API VERSION/config/services/recreate
    param="{\"parameters\":{\"removeAll\":\"${removeAll}}
\", \"essbaseChange\":\"${essbaseChange}\", \"tempServiceType\":\"$
{tempServiceType}\"}}"
    funcExecuteRequest "POST" "$url" "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
```



```
if [ \$status == -1 ]; then
        echo "Started recreating the environment successfully"
                funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
if [[ "$#" != "1" ]]; then
    echo "Mandatory argument missing"
    echo "Usage: EPMRestSamples <option>"
   echo " where <option> is -recreate or -reset"
   exit 1
fi
if [ "${1}" == "-reset" ]; then
    funcHardReset "POC Exit Criteria Check - cURL"
elif [ "${1}" == "-recreate" ]; then
    funcRecreateService "false" "default" ""
else
   echo "Incorrect usage"
    echo "Usage: EPMRestSamples <option>"
   echo " where <option> is -recreate or -reset"
    exit 1
fi
```

Sample Java Code

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
package com.oracle.test;
import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStreamWriter;
import java.net.HttpURLConnection;
import java.net.URL;
import java.util.Scanner;
import java.util.Base64;
import org.json.JSONArray;
import org.json.JSONObject;
/*
* EPM Rest Samples.
* The userName variable uses the format <domain>.<username>.
*/
public class EPMRestSamples {
```

```
private String userName;
                                        // EPMCloud user name
                                        // EPMCloud user password
    private String password;
   private String serverUrl;
                                        // EPMCloud server URL
   private String apiVersion="v2";
                                        // Version of the EPMCloud Rest API
   private long startTime;
   private long endTime;
    private long maxLoopTime=(60 * 60 * 1000);
    public static void main(String[] args) {
       try {
            if(null == args || args.length != 1) {
                System.err.println("Mandatory argument missing");
                System.err.println("Usage: EPMRestSamples <option>");
                System.err.println(" where <option> is -recreate or -reset");
                System.exit(1);
            }
            // TODO: Use appropriate username, password, and URL
            EPMRestSamples samples = new EPMRestSamples(
                "<USERNAME>", "<PASSWORD>", "<SERVICE URL>");
            String option = args[0];
            if("-reset".equalsIgnoreCase(option)) {
                samples.hardReset("POC Exit Criteria Check - Java");
            }
            else if("-recreate".equalsIgnoreCase(option)) {
                samples.recreateService("false", "default", "");
            l
            else {
                System.err.println("Incorrect usage");
                System.err.println("Usage: EPMRestSamples <option>");
                System.err.println(" where <option> is -recreate or -reset");
                System.exit(1);
            }
        ł
       catch (Throwable x) {
            System.err.println("Error: " + x.getMessage());
        }
    }
    public EPMRestSamples(String userName, String password, String serverUrl)
throws Exception {
       this.userName = userName;
       this.password = password;
       this.serverUrl = serverUrl;
    }
    private String getStringFromInputStream(InputStream is) {
       BufferedReader br = null;
       StringBuilder sb = new StringBuilder();
       String line;
       try {
```

```
br = new BufferedReader(new InputStreamReader(is));
            while ((line = br.readLine()) != null) {
                sb.append(line);
            1
        }
        catch (IOException e) {
            e.printStackTrace();
        }
        finally {
            if (br != null) {
                try { br.close(); }
                catch (IOException e) { e.printStackTrace(); }
        }
        return sb.toString();
    }
    private String executeRequest (String urlString, String requestMethod,
String payload, String contentType) throws Exception {
        HttpURLConnection connection = null;
        try {
            URL url = new URL(urlString);
            Base64.Encoder encoder = Base64.getEncoder();
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod(requestMethod);
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization", "Basic " +
encoder.encodeToString((userName + ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", contentType);
            if (payload != null) {
                OutputStreamWriter writer = new
OutputStreamWriter(connection.getOutputStream());
                writer.write(payload);
                writer.flush();
            }
            int status = connection.getResponseCode();
            if (status == 200 || status == 201) {
                return getStringFromInputStream(connection.getInputStream());
            }
            throw new Exception("Http status code: " + status);
        }
        finally {
            if (connection != null) { connection.disconnect(); }
        }
    }
    private void getJobStatus(String pingUrlString, String methodType) throws
Exception {
        boolean completed = false;
```



```
while (!completed) {
            String pingResponse = null;
            try {
                pingResponse = executeRequest(pingUrlString, methodType,
null, "application/json");
            catch (Exception e) {
                if (e instanceof java.net.ConnectException || e instanceof
java.net.SocketException) {
                    if(System.currentTimeMillis()<endTime) {</pre>
                        System.out.println("Processing. Please wait...");
                        Thread.sleep(60000);
                        continue;
                    }
                    throw new Exception("Command timeout..");
                }
                throw e;
            }
            JSONObject json = new JSONObject(pingResponse);
            int status = json.getInt("status");
            if (status == -1) {
                try {
                    System.out.println("Processing. Please wait...");
                    Thread.sleep(20000);
                }
                catch (InterruptedException ie) {
                    completed = true;
                    throw ie;
                }
            }
            else {
                if (status > 0) {
                    System.out.println("Error occurred: " +
json.getString("details"));
                }
                else {
                    System.out.println("Execution completed successfully");
                }
                completed = true;
            }
        }
    }
   public String fetchPingUrlFromResponse(String response, String retValue)
throws Exception {
        String pingUrlString = null;
        JSONObject jsonObj = new JSONObject(response);
        int resStatus = jsonObj.getInt("status");
        if (resStatus == -1) {
            JSONArray lArray = jsonObj.getJSONArray("links");
            for (int i = 0; i < lArray.length(); i++) {
                JSONObject arr = lArray.getJSONObject(i);
```

```
if (arr.get("rel").equals(retValue))
                    pingUrlString = (String) arr.get("href");
            }
        }
        return pingUrlString;
    }
    public void hardReset(String comment) throws Exception {
        Scanner in = new Scanner(System.in);
        System.out.print("Are you sure you want to restart the service
instance (yes/no): no? [Press Enter] ");
        String s = in.nextLine();
        if (!s.equals("yes")) {
            System.out.println("User cancelled the recreate command");
            System.exit(0);
        }
        JSONObject params = new JSONObject();
        params.put("comment", comment);
        JSONObject innerParams = new JSONObject();
        innerParams.put("autotune", "true");
        params.put("parameters", innerParams);
        String urlString = String.format("%s/interop/rest/%s/config/services/
reset", serverUrl, apiVersion);
        startTime=System.currentTimeMillis();
        endTime = startTime+maxLoopTime;
        String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
        getJobStatus(fetchPingUrlFromResponse(response, "Job Status"),"GET");
    }
    public void recreateService(String removeAll, String essbaseChange,
String tempServiceType) throws Exception {
        Scanner in = new Scanner(System.in);
        System.out.print("Are you sure you want to recreate the EPM
environment (yes/no): no ?[Press Enter] " );
        String s = in.nextLine();
        if (!s.equals("yes")) {
            System.out.println("User cancelled the recreate command");
            System.exit(0);
        }
        JSONObject params = new JSONObject();
        JSONObject innerParams = new JSONObject();
        innerParams.put("tempServiceType", tempServiceType);
        innerParams.put("essbaseChange", essbaseChange);
        innerParams.put("removeAll", removeAll);
        params.put("parameters", innerParams);
        String urlString = String.format("%s/interop/rest/%s/config/services/
recreate", serverUrl, apiVersion);
```

```
startTime=System.currentTimeMillis();
endTime = startTime+maxLoopTime;
String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
}
```

Sample Groovy Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
package com.groovy
import org.json.JSONObject
import groovy.json.JsonSlurper
// TODO: Use appropriate username, password, and url
username="<USERNAME>"
password="<PASSWORD>"
serverUrl="<SERVICE URL>"
endTime=0
maxLoopTime=(60 * 60 * 1000)
apiVersion = "v2"
userCredentials = username + ":" + password
basicAuth = "Basic " + userCredentials.bytes.encodeBase64().toString()
def getResponse(is) {
    BufferedReader br = new BufferedReader(new InputStreamReader(is))
    StringBuilder sb = new StringBuilder()
    String line
    while ((line = br.readLine()) != null) {
        sb.append(line+"\n")
    }
   br.close()
    return sb.toString()
}
def getJobStatus(pingUrlString, methodType) {
    def pingUrl = new URL(pingUrlString)
    def completed = false
    while (!completed) {
        try {
            pingResponse = executeRequest(pingUrl, methodType, null,
"application/json")
        catch(exp) {
            if(exp instanceof java.net.ConnectException || exp instanceof
java.net.SocketException) {
```

```
if(System.currentTimeMillis()<endTime) {</pre>
                    println("Processing. Please wait...")
                    Thread.sleep(60000)
                    continue
                }
                throw new Exception ("Command timeout..")
            }
        }
        status = getJobStatusFromResponse(pingResponse)
        if (status == "Processing") {
            try {
                println "Processing. Please wait..."
                Thread.sleep(5000)
            ł
            catch (InterruptedException e) {
                completed = true
            }
        }
        else {
            println "Execution completed successfully"
            completed = true
        }
    }
}
def getJobStatusFromResponse(response) {
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == -1) { return "Processing" }
    else if (status == 0) { return "Completed" }
    else { return object.details }
}
def executeRequest(url, requestType, payload, contentType) throws Exception {
   HttpURLConnection connection = (HttpURLConnection) url.openConnection()
    connection.setDoOutput(true)
    connection.setInstanceFollowRedirects(false)
    connection.setRequestMethod(requestType)
    connection.setRequestProperty("Content-Type", contentType)
    connection.setRequestProperty("Authorization", basicAuth)
    connection.setUseCaches(false)
    if (payload != null) {
       OutputStreamWriter writer = new
OutputStreamWriter(connection.getOutputStream())
        writer.write (payload)
        writer.flush()
    }
    int statusCode
    try { statusCode = connection.responseCode }
    catch (all) { throw all }
    def response
    if (statusCode == 200 || statusCode == 201) {
```

```
if (connection.getContentType() != null && !
connection.getContentType().startsWith("application/json")) {
            println "Error occurred in server"
            System.exit(0)
        }
        InputStream is = connection.getInputStream()
        if (is != null) { response = getResponse(is) }
    }
    else {
        if (statusCode == 503) {
            throw new Exception ("Service Unavailable")
        }
        InputStream is = connection.getErrorStream()
        if (is != null && connection.getContentType() != null &&
            connection.getContentType().startsWith("application/json")) {
            println getJobStatusFromResponse(getResponse(is))
        }
    }
    connection.disconnect()
    return response
}
def getUrlFromResponse(scenario, response, relValue) {
    def object = new JsonSlurper().parseText(response)
    def pingUrlStr
    if (object.status == -1) {
        println "Started - " + scenario
        def links = object.links
        links.each{
            if (it.rel.equals(relValue)) {
                pingUrlStr=it.href
        }
    }
    else {
        println "Error details: " + object.details
        System.exit(0)
    }
    return pingUrlStr
}
def hardReset(comment) {
    def scenario = "Hard reset"
    def toReset = System.console().readLine 'Are you sure you want to restart
the service instance (yes/no): no? [Press Enter] '
    if (!toReset.equals("yes")) {
        println "User cancelled the resetService command"
        System.exit(0)
    }
    def url
```

```
JSONObject params = new JSONObject()
    JSONObject innerParams = new JSONObject()
    try {
        params.put("comment", comment)
        innerParams.put("autotune", "true")
        params.put("parameters", innerParams)
        url = new URL(serverUrl+"/interop/rest/" + apiVersion + "/config/
services/reset")
    }
    catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0)
    }
    endTime=System.currentTimeMillis() +maxLoopTime
    response = executeRequest(url, "POST", params.toString(), "application/
json")
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job
Status"), "GET")
   }
def recreateService(removeall,essabaseoption,tempServiceType) {
    def scenario="Recreate"
    def toCreate = System.console().readLine 'Are you sure you want to
recreate the EPM environment (yes/no): no? [Press Enter] '
    if (!toCreate.equals("yes")) {
       println "User cancelled the recreate command"
        System.exit(0)
    }
    def url
    JSONObject params = new JSONObject()
    JSONObject innerParams = new JSONObject()
    try {
        innerParams.put("tempServiceType", tempServiceType)
        innerParams.put("essbaseChange", essabaseoption)
        innerParams.put("removeAll", removeall)
        params.put("parameters", innerParams)
        url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/config/
services/recreate")
   }
    catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0)
    }
    endTime=System.currentTimeMillis() +maxLoopTime
    response = executeRequest(url, "POST", params.toString(), "application/
json")
```



```
if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job
Status"), "GET")
    }
}
if (this.args == null || this.args.length != 1) {
    println "Mandatory argument missing"
    println "Usage: EPMRestSamples <option>"
   println " where <option> is -recreate or -reset"
    System.exit(1)
}
def option = this.args[0]
if("-reset".equalsIgnoreCase(option)) {
   hardReset("POC Exit Criteria Check - Groovy");
}
else if("-recreate".equalsIgnoreCase(option)) {
    recreateService("false", "default", "");
}
else {
   println "Incorrect usage"
    println "Usage: EPMRestSamples <option>"
   println " where <option> is -recreate or -reset"
   System.exit(1)
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Manage Application Snapshots

You can manage the file system artifacts or application snapshots using the following REST resources.

Note: The password of the source EPM Cloud environment must have already been encrypted using EPM Automate. The encrypted password must then be passed as one of the parameters for the copysnapshot REST API. See the *encrypt* command in Command Reference in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud*.

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Get Information About All Application Snapshots	GET	<pre>/interop/rest/{api_version}/ applicationsnapshots</pre>
Get Information About a Specific Application Snapshot	GET	/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}
Upload Application Snapshot (v1)	POST	/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName
Upload Application Snapshot (v2)	POST	/interop/rest/v2/files/upload
Download Application Snapshot (v1)	GET	/interop/rest/{api_version}/ applicationsnapshots/ {applicationSnapshotName}
Download Application Snapshot (v2)	POST	/interop/rest/v2/files/download
Copy Application Snapshot (v1)	POST	/interop/rest/v1/services/ {servicename}/copysnapshot
Copy Application Snapshot (v2)	POST	/interop/rest/v2/snapshots/ copyfrominstance
Rename Application Snapshot (v1)	PUT	/interop/rest/{api_version}/ renamesnapshot
Rename Application Snapshot (v2)	PUT	/interop/rest/v2/snapshots/rename

Table 9-47 Manage Application Snapshots

Get Information About All Application Snapshots

This API returns information about all application snapshots that are available in an Planning instance. It provides details such as name, type, size, and last modified time. Type signifies whether it is a Migration snapshot or an external snapshot. Size and last modified time are not available for Migration type snapshots.

This API is version 11.1.2.3.600.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/{api_version}/applicationsnapshots

Response

Supported Media Types: application/json

Table 9-48 Parameters

Name	Description	
api_version	Specific API version	



Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
items	Detailed information about the API
name	Name of the application snapshot
type	Possible values: LCM, EXTERNAL
size	Size of the application snapshot in bytes. Available only for type EXTERNAL
lastmodifiedtim e	Time in Long value as per the last modified time of the file. Will be available only for type ${\tt EXTERNAL}$
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	Parameters as key value pairs passed in the request

Table 9-48 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "status":0,
    "items":[{
        "name":"sample.csv",
        "type":"EXTERNAL",
        "size":"18",
        "lastmodififedtime":"1422534438000"
        },{
        "name":"snapshot1",
        "type":"LCM",
        "size":null,
        "lastmodififedtime":null
    }],
    "details":null,
    "links":[{
        "data":null,
        "action":"GET",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots",
        "rel":"self"
    }]
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



Get Information About a Specific Application Snapshot

Returns information about all the operations that can be performed on a particular application snapshot. It provides details on operations such as Migration import and export, upload, download, and delete.

This API is version 11.1.2.3.600.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/{api_version}/applicationsnapshots/{applicationSnapshotName}

Request

The following table summarizes the GET request parameters.

Table 9-49 Parameters

Name	Description	Туре	Required	Default
applicationSnapsho tName	Application snapshot name to retrieve the details	Path	Yes	N/A

Response

Supported Media Types: application/json

Table 9-50 Parameters

Name	Description
details	In the case of an error, details are published with the error string
status	See Migration Status Codes
items	Detailed information about the API
name	Name of the application snapshot
type	Possible values: LCM, EXTERNAL
canexport	Identifies whether this application snapshot can be exported using Migration. Applicable only to Migration application artifacts
canimport	Identifies whether this application snapshot can be imported using Migration. Applicable only to Migration application artifacts
canupload	Identifies whether the application snapshot can be uploaded
candownload	Identifies whether the application snapshot can be downloaded
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible values: self, import, export, upload, download, or delete depending on the operation permitted on an application snapshot
data	Parameters as key value pairs passed in the request



Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "status":0,
    "items":[{
        "name": "snapshot1",
        "type":"LCM",
        "canexport":true,
        "canimport":true,
        "canupload":true,
        "candownload":true
    }],
    "details":null,
    "links":[{
        "data":null,
        "action":"GET",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/snapshot1",
        "rel":"self"
        },{
        "data":null,
        "action":"GET",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/snapshot1/contents",
        "rel":"download"
        },{
        "data":null,
        "action":"POST",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/snapshot1/contents?
isLast=true&chunkSize=52428800&isFirst=true",
        "rel":"upload"
        },{
        "data":null,
        "action":"POST",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/snapshot1/migrationg={type:"export}"
        "rel":"export"
        },{
        "data":null,
        "action": "POST",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/snapshot1/migrationq={type:"import}",
        "rel":"import"
        },{
        "data":null,
        "action":"DELETE",
        "href":"https://<BASE URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/ss1",
        "rel":"delete"
    }]
}
```



Java Sample – getInfoAboutSpecificSnapshots.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN - Get application snapshot details
11
public void getApplicationSnapshotDetails(String snapshotName) throws
Exception {
    String urlString = String.format("%s/interop/rest/%s/applicationsnapshots/
%s", serverUrl, apiVersion, snapshotName);
   String response = executeRequest(urlString, "GET", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        System.out.println("Application details :");
        JSONArray itemsArray = json.getJSONArray("items");
        JSONObject item = (JSONObject) itemsArray.get(0);
        System.out.println("Application snapshot name : " +
item.getString("name"));
        System.out.println("Application snapshot type : " +
item.getString("type"));
        System.out.println("Can be exported flag : " +
item.getString("canExport"));
        System.out.println("Can be imported flag : " +
item.getString("canImport"));
        System.out.println("Can be uploaded flag : " +
item.getString("canUpload"));
        System.out.println("Can be downloaded flag : " +
item.getString("canDownload"));
        JSONArray linksArray = json.getJSONArray("links");
        JSONObject jObj = null;
        System.out.println("Services details :");
        for(int i=0; i < linksArray.length(); i++) {</pre>
            jObj = (JSONObject)linksArray.get(i);
            System.out.println("Service :" + jObj.getString("rel"));
            System.out.println("URL :" + jObj.getString("href"));
            System.out.println("Action : " + jObj.getString("action") + "\n");
    }
}
11
// END - Get application snapshot details
11
```

cURL Sample - GetInfoAboutSpecificSnapshots.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcGetApplicationSnapshotDetails() {
    url=$SERVER URL/interop/rest/$API VERSION/applicationsnapshots/$1
    funcExecuteRequest "GET" $url
   output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Application details :"
        echo "Application snapshot name : " `echo $output | jq
'.items[0].name'
        echo "Application snapshot type : " `echo $output | jq
'.items[0].type'
        echo "Can be exported flag : " `echo $output | jq
'.items[0].canExport'
        echo "Can be imported flag : " `echo $output | jq
'.items[0].canImport'`
        echo "Can be uploaded flag : " `echo $output | jq
'.items[0].canUpload'`
        echo "Can be downloaded flag : " `echo $output | jg
'.items[0].canDownload'`
        count=`echo $output | jq '.links | length'`
        i=0
        echo "Services details :"
        while [ $i -lt $count ]; do
            echo "Service : " `echo $output | jq '.links['$i'].rel'`
           echo "URL :" `echo $output | jq '.links['$i'].href'`
           echo "Action :" `echo $output | jq '.links['$i'].action'`
           echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – GetInfoAboutSpecificSnapshots.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def getApplicationSnapshotDetails(applicationSnapshotName) {
    def url;
    try {
        String snapshotName = URLEncoder.encode(applicationSnapshotName,
    "UTF-8");
        url = new URL(serverUrl + "/interop/rest/" + apiVersion + "/
    applicationsnapshots/" + snapshotName)
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
}
```

```
response = executeRequest(url, "GET", null);
def object = new JsonSlurper().parseText(response)
def status = object.status
if (status == 0) {
   println "Application details :"
   println "Application snapshot name : " + object.items[0].name
   println "Application snapshot type : " + object.items[0].type
   println "Can be exported flag : " + object.items[0].canExport
   println "Can be imported flag : " + object.items[0].canImport
   println "Can be uploaded flag : " + object.items[0].canUpload
   println "Can be downloaded flag : " + object.items[0].canDownload
   def links = object.links
   println "Services details :"
   links.each{
       println "Service : " + it.rel
       println "URL : " + it.href
       println "Action : " + it.action + "\n"
    }
} else {
   println "Error occurred while fetching application snapshot details"
   if (object.details != null)
            println "Error details: " + object.details
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Upload Application Snapshot (v1)

This API uploads an application snapshot to the Planning repository. The client needs to call upload API multiple times based on the size of file to upload. The client needs to break the existing stream into a number of chunks depending on the logic that each chunk size is not greater than 50 * 1024 * 1024 bytes.

This API is version v1.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/{api_version}/applicationsnapshots

Supported Media Types: application/octet-stream

The following table summarizes the client request.



Table 9-51 Parameters

Name	e Description		Default
api_version	Specific API version	Path	N/A
applicationSnapsho tName	Name of the application snapshot to be uploaded. A file with this name is created in the Planning repository. If a file or folder with this name exists in the repository, an error is thrown indicating that a file or folder exists.		N/A
isLast	If the chunk being passed is the last one then set to true	Query	N/A
chunkSize	Size of the chunk being passed in bytes	Query	N/A
isFirst	If the chunk being passed is the first one and there will be subsequent requests for upload then set as true	Query	N/A
fileSize	The size of the file being uploaded	Query	N/A

Response

Supported Media Types: application/json

Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Is self, which denotes the URL of this REST API.	
data	Parameters as key value pairs passed in the request	

Example of Response Body

```
{
   "status":0,
   "details":null,
   "links":[{
        "data":null,
        "action":"POST",
        "href":"https://<BASE URL>/interop/rest/v1/applicationsnapshots/
ss2.zip/contents,
        "rel":"self"
   }]
}
```

Examples of Uploading with Postman

To upload a file named snapshot.zip of size 12606 bytes, select request method as POST and Basic Authorization header for all the requests.

Example Request 1: Create a File

Parameters



```
https://<BASE URL>//interop/rest/v1/applicationsnapshots/snapshot.zip/contents?
q=PARAMETERS ->
{"isFirst":true,"chunkSize":14,"fileSize":"12606","isLast":false} // utf-8
encoded value of it
```

```
{"isFirst":true,"chunkSize":14,"fileSize":"12606","isLast":false} // utf-8
encoded value of it
```

URL and Response

```
https://<BASE URL>/interop/rest/v1/applicationsnapshots/snapshot.zip/contents?
q=%7B%22isFirst%22%3Atrue%2C%22chunkSize%22%3A14%2C%22fileSize%22%3A%223318004
%22%2C%22isLast%22%3Afalse%7D
```

```
{
    "links": [
        {
            "rel": "self", {
                "href": "https://<BASE URL>/interop/rest/v1/applicationsnapshots/
snapshot.zip/contents?
q=%7B%22isFirst%22:true,%22chunkSize%22:14,%22fileSize%22:%223318004%22,%22isL
ast%22:false%7D",
            "data": null,
                "action": "POST"
        }
    ],
    "details": null,
    "status": 0
}
```

Example Request 2: Upload the Content

Parameters

https://<BASE URL>/interop/rest/v1/applicationsnapshots/snapshot.zip/contents?q=

{"startRange":"0","isFirst":false,"chunkSize":12606,"isLast":false,"fileSize":"12
606","endRange":"12605","chunkNo":1} // encoded value of it (Ensure the value of
the parameters chunkSize and fileSize is equivalent to the total size of the file
and endRange is set to fileSize - 1.)

URL and Response

```
https://<BASE URL>/interop/rest/v1/applicationsnapshots/snapshot.zip/contents?
q=%7B%22startRange%22%3A%220%22%2C%22isFirst%22%3Afalse%2C%22chunkSize%22%3A12
606%2C%22isLast%3A%22false%22%7D
```

To select the file, select tab Body, radio button Binary, and select File, Send.

Example Request 3: Extract the Content Out of the Zip File

Parameters

https://<<BASE URL>/interop/rest/v1/applicationsnapshots/snapshot.zip/contents?q=

```
{"isFirst":false,"chunkSize":14,"fileSize":"12606","isLast":true} // utf-8
encoded value of it
```

URL and Response

```
https://<BASE URL>/interop/rest/v1/applicationsnapshots/snapshot.zip/contents?
q=%7B%22isFirst%22%3Afalse%2C%22chunkSize%22%3A14%2C%22fileSize%22%3A%2212606%
22%2C%22isLast%22%3Atrue%7D
```

To select the file:, select tab Body, radio button Binary, select File, Send.

Upload Application Snapshot (v2)

The Upload Application Snapshot (v2) REST API uploads an application snapshot to Oracle Enterprise Performance Management Cloud. The client needs to call upload API multiple times based on the size of the file to upload. The client needs to break the existing stream into a number of chunks depending on the logic that each chunk size is not greater than 50 * 1024 * 1024 bytes.

This API is version v2.



Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/v2/files/upload

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

 Table 9-53
 Tasks for Upload Application Snapshot

Task	Reques t	REST Resource
Create file	POST	/interop/rest/v2/files/upload
Upload content	PATCH	/interop/rest/v2/files/upload/7224986735511603
Extract the content out of zip file	POST	/interop/rest/v2/files/upload/7224986735511603/complete
Extraction status	GET	/interop/rest/v2/status/jobs/7224986735511603

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 9-54 Parameters

Name	Description	Туре	Required	Default
fileName	Name of the application snapshot to upload. A file with this name is created in EPM Cloud. If a file or folder with this name already exists, an error is thrown indicating that a file or folder exists.	Payload	Yes	None
fileSize	The size of the file to upload	Payload	Yes	None

Response

Supported Media Types: application/json



Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Is self, which denotes the URL of this REST API.	
data	Parameters as key value pairs passed in the request	

Table 9-55 Parameters

Examples of Uploading with Postman

To upload a file named snapshot.zip of size 12606 bytes, select Basic Authorization header for all the requests.

Example URL and Payload to Create the File

Request Method: POST

Supported Media Types: application/json

https://<BASE URL>/interop/rest/v2/files/upload

```
{
   "fileName": "snapshot.zip",
   "fileSize": "2468889"
}
```

Example Response 1

```
{
    "status":0,
    "details":null,
    "links":[{
        "data":null,
        "action":"POST",
        "href":"https://<BASE URL>/interop/rest/v2/interop/rest/v2/files/
upload,
        "rel":"self"
    }]
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"fileName": "snapshot.zip", "fileSize":"2468889"}' 'https://<BASE URL>/
interop/rest/v2/files/upload'
```



Example URL and Payload to Upload the Content

Request Method: PATCH

Supported Media Types: application/octet-stream

Chunk-Range has to be passed as a Header parameter (0-2468889)

Note:

Ensure the value of the fileSize is equivalent to the total size of the file and end Range is set to fileSize -1.

https://<BASE URL>/interop/rest/v2/files/upload/7224986735511603

To select the file: Select tab Body, radio button Binary, and choose File to upload.

Example Response 2

```
{
   "details": null,
   "status": 0,
   "links": [
        {
            "href": " https://<BASE URL>/interop/rest/v2/files/upload/
7224986735511603",
            "action": "PATCH",
                "rel": "self",
                "data": null
            }
        ]
}
```

Sample cURL command

```
curl -X PATCH -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt
-H 'Content-Type: application/octet-stream' -H
'Chunk-Range: 0-2468888' --data-binary '@snapshot.zip' 'https://<BASE URL>/
interop/rest/v2/files/upload/7232824317092320'
```

Example URL and Payload to Extract the Content Out of the Zip File

Request method: POST

Supported Media Types: application/json

https://<BASE URL>/interop/rest/v2/files/upload/7224986735511603/complete

Example Response 3

```
{
    "details": null,
```



```
"status": -1,
    "links": [
        {
            "href": "http://slcar282.usdv1.oraclecloud.com:13017/interop/
rest/v2/files/upload/7224986735511603/complete",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": "http://slcar282.usdv1.oraclecloud.com:13017/interop/
rest/v2/status/jobs/7293659723083015",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    ]
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json'
'https://<BASE URL>/interop/rest/ v2/files/upload/7232824317092320/complete'
```

Example URL and Payload Extraction Status

Request method: POST

Supported Media Types: application/json

This API request needs to be requested when the status code received in the example 3 response is -1.

https://<BASE URL>/interop/rest/v2/status/jobs/7293659723083015

Example Response 4



Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json'
'https://<BASE URL>/interop/rest/ v2/status/jobs/7293659723083015'
```

Download Application Snapshot (v1)

Downloads the application snapshot from EPM repository to the local location from where client is being run. After receiving the response, if the content type is application/json then there would be an error on server and refer to details. Else, if it's application/octet-stream, then the content to be downloaded is part of the response and can read from the response body.

Note:

The entire path to the file must be encoded; for example, changing / to \$2F.

For example, change this path to an .HTML file in the apr directory:

apr/2020-03-04 23 07 20/2020-03-04 23 07 20.html

to this:

apr%2F2020-03-04%2023 07 20%2F2020-03-04%2023 07 20.html

This API is version v1.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

GET /interop/rest/{api_version}/applicationsnapshots/{applicationSnapshotName}/
contents

Supported Media Types: application/x-www-form-urlencoded

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

The following table summarizes the GET request parameters.



Table 9-56 Parameters

Name	Description	Туре	Required	Default
applicationSnapsho tName	Application snapshot name or file name to download (for example, "Artifact Snapshot" or s112.csv).	Path	Yes	None
	The entire applicationSnapshotName must be encoded before sending the request.			
	To download a particular file, provide the path to that file as the value of applicationSnapshotName. For example, to download a Data Management file called s112.csv in the inbox, refer to the file as "inbox\s112.csv" in the path parameter.			
	To download the Activity Reports or access log, use the fully qualified file name as shown in the output of List Files.			
	For example, to download a specific file from the apr directory, use the following format:			
	pr%2F2020-03-04%0A23_07_20%2F2020-03-04%0A23_ 07_20.html			
	apr%2F%0A2020-03-04%2023_07_20%2F%0Aaccess_lo g.zip			
	apr%2F%0A2020-03-04%2023_07_20%2F%0Aactivityr eport.json.			
api_version	Specific API version	Path	Yes	None

Example of Request

https://<BASE URL>/interop/rest/v1/applicationsnapshots/Vision.zip/contents

Response

Supported Media Types: application/json

Response Header

fileExtension: This will have the file extension that can be used to create a file locally. Can contain values such as zip or csv.

Table 9-57 Parameters

Attribute	Description	
details	Published in case of errors with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Possible value: self	
data	Parameters as key value pairs passed in the request	



Example of Response Body

The following shows an example of the response body in JSON format in case there is an error during download.

```
{
   "details":"Not a valid file.",
   "status":8,
   "links":[{
        "href":"https://<BASE URL>/interop/rest/v1/applicationsnapshots/
s112.csv/contents",
        "action":"GET",
        "rel":"self",
        "data":null
    }]
}
```

Download Sample Code

Java Sample - downloadFile.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java.

```
public class DownloadV1 {
    private String serverUrl ; // PBCS server URL
    private String apiVersion = "v1";
   private String userName ; // Server Username
   private String password ; //Server Password
   private static String fileName ; //snapshot to be downloaded.
   private String domain ;
    public void downloadFile(String fileName) throws Exception {
        HttpURLConnection connection = null;
        InputStream inputStream = null;
        FileOutputStream outputStream = null;
        trv {
            fileName = fileName.replaceAll("/", "\\\\");
            URL url = new URL(
                    String.format(
                            "%s/interop/rest/%s/applicationsnapshots/%s/
contents",
                            serverUrl, apiVersion,
                            URLEncoder.encode(fileName, "UTF-8")));
            System.out.println("DOWNLOAD URL: " + url);
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod("GET");
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty(
```

```
"Authorization",
                "Basic "
                        + new sun.misc.BASE64Encoder().encode((userName
                                + ":" + password).getBytes()));
        int status = connection.getResponseCode();
        if (status == 200) {
            if (connection.getContentType() != null
                    && connection.getContentType().equals(
                            "application/json")) {
                JSONObject json = new JSONObject(
                        getStringFromInputStream (connection
                                .getInputStream()));
                System.out.println("Error downloading file : "
                        + json.getString("details"));
            } else {
                String response = getStringFromInputStream(connection
                        .getInputStream());
                String pingURL = fetchPingUrlFromResponse(response,
                        "Job Status");
                getJobStatusDownload(pingURL, "GET");
            }
        } else {
            throw new Exception("Http status code: " + status);
        }
    } finally {
        if (connection != null)
            connection.disconnect();
        if (outputStream != null)
            outputStream.close();
        if (inputStream != null)
            inputStream.close();
    }
private void downloadContent(String downloadURL) throws Exception {
   HttpURLConnection connection = null;
    InputStream inputStream = null;
   FileOutputStream outputStream = null;
   try {
        URL url = new URL(downloadURL);
        connection = (HttpURLConnection) url.openConnection();
        connection.setRequestMethod("GET");
        connection.setInstanceFollowRedirects(false);
        connection.setDoOutput(true);
        connection.setUseCaches(false);
        connection.setDoInput(true);
        connection.setRequestProperty(
                "Authorization",
                "Basic "
                        + new sun.misc.BASE64Encoder().encode((userName
                                + ":" + password).getBytes()));
        connection.setRequestProperty("Content-Type",
                "application/x-www-form-urlencoded");
```

}

```
int status = connection.getResponseCode();
            if (status == 200) {
                if (connection.getContentType() != null
                        && connection.getContentType().equals(
                                "application/json")) {
                    JSONObject json = new JSONObject(
                            getStringFromInputStream(connection
                                     .getInputStream()));
                    System.out.println("Error downloading file : "
                            + json.getString("details"));
                } else {
                    inputStream = connection.getInputStream();
                    String downloadedFileName = fileName;
                    if (fileName.lastIndexOf("/") != -1) {
                        downloadedFileName = fileName.substring(fileName
                                .lastIndexOf("/") + 1);
                    }
                    String ext = ".zip";
                    if (connection.getHeaderField("fileExtension") != null) {
                        ext = "." +
connection.getHeaderField("fileExtension");
                    if (fileName.lastIndexOf(".") != -1
                            && fileName.lastIndexOf(".") != 0)
                        ext = fileName.substring(fileName.lastIndexOf(".") +
1);
                    outputStream = new FileOutputStream(new File(
                            downloadedFileName + ext));
                    int bytesRead = -1;
                    byte[] buffer = new byte[5 * 1024 * 1024];
                    while ((bytesRead = inputStream.read(buffer)) != -1)
                        outputStream.write(buffer, 0, bytesRead);
                    System.out.println("File download completed.");
                }
            } else {
                throw new Exception ("Http status code: " + status);
            ł
        } finally {
            if (connection != null)
                connection.disconnect();
            if (outputStream != null)
                outputStream.close();
            if (inputStream != null)
                inputStream.close();
        }
    }
        private void getJobStatusDownload(String pingUrlString, String
methodType)
            throws Exception {
        boolean completed = false;
        while (!completed) {
```

```
String pingResponse = executeRequest(pingUrlString, methodType,
                    null, "application/x-www-form-urlencoded");
            JSONObject json = new JSONObject(pingResponse);
            int status = json.getInt("status");
            if (status == -1) {
                try {
                    System.out.println("Please wait...");
                    Thread.sleep(20000);
                } catch (InterruptedException e) {
                    completed = true;
                    throw e;
                }
            } else {
                if (status > 0) {
                    System.out.println("Error occurred: "
                            + json.getString("details"));
                } else {
                    String downloadURL =
fetchPingUrlFromResponse (pingResponse,
                            "Download link");
                    downloadContent(downloadURL);
                }
                completed = true;
            }
        }
    }
}
```

cURL Sample - DownloadFile.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

#!/bin/sh



```
if [ "$rel" == "Download link" ]; then
                                pingUrlC=`echo $output | jq
'.links['$i'].href'`
                                pingUrlC=`echo "$pingUrlC" | tr -d "\""`
                fi
                i=`expr $i + 1`
       done
       #request has to be get
        statusWrite=`curl -s -w "%{http code}" -u "$USERNAME:$PASSWORD" --
request GET -D "respHeader.txt" -o "$1" -H "Content-Type: application/x-www-
form-urlencoded" "$pingUrlC"`
        if [ $statusWrite == 200 ]; then
                 contentType=`echo $(grep 'Content-Type:' respHeader.txt) |
tr -d [:space:]`
                 #contentbody=`cat writeResponse.txt`
                 if [ ! -z $contentType ] && [[ $contentType = *"application/
json"* ]]; then
                         echo "Error occurred. "
                 else
                        fileExtension=`echo $(grep -r "fileExtension: "
respHeader.txt | awk '{print ($2)}') | tr -d [:space:]`
                          if [ ! -z $fileExtension ]; then
                if [[ ! $filepath =~ \.$fileExtension$ ]]; then
                   mv "$1" "$1".$fileExtension
                fi
            fi
                    echo "Downloade file successfully"
                 fi
fi
 funcRemoveTempFiles "response.txt" "respHeader.txt"
}
funcDownloadFile() {
       filepath="/u01/$FILENAME"
    encodedFileName=$(echo $FILENAME | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/contents
      statusCode=`curl -X GET -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
H "Content-Type: application/x-www-form-urlencoded" -D "respHeader.txt" -o
"response.txt" $url`
              if [ $statusCode == 200 ]; then
                contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr
-d [:space:]`
             contentbody=`cat response.txt`
                if [ -z $contentType ] && [[ $contentType = *"application/
```

```
json"* ]]; then
            output=`cat $filepath`
            error=`echo $output | jq '.details'`
            echo "Error occurred. " $error
            funcRemoveTempFiles $filepath
        else
            funcGetStatus "GET"
        fi
               else
                        echo "Error executing request"
                        if [ $statusCode != 000 ]; then
                                 echo "Response error code : " $statusCode
                                 funcPrintErrorDetails "response.txt"
                                 funcRemoveTempFiles "respHeader.txt"
"response.txt"
                        fi
                        exit 0
               fi
#funcRemoveTempFiles "respHeader.txt" "response.txt"
funcDownloadFile $FILENAME
Groovy Sample – DownloadFile.groovy
Prerequisites: json.jar
Common Functions: See CSS Common Helper Functions for Groovy
class DownloadV1 {
    def serverUrl ; // PBCS server URL
    def apiVersion = "v1";
    def userName ; //Server Username
    def password ; //Server Password
    def fileName ; //Snapshot to be downloaded
    void downloadFile(def fileName) throws Exception {
        HttpURLConnection connection = null;
        InputStream inputStream = null;
        FileOutputStream outputStream = null;
        try {
            fileName = fileName.replaceAll("/", "\\\\");
            URL url = new URL(String.format("%s/interop/rest/%s/
applicationsnapshots/%s/contents", serverUrl,
                    apiVersion, URLEncoder.encode(fileName, "UTF-8")));
            println "DOWNLOAD URL: "+url
            connection = (HttpURLConnection) url.openConnection();
```

```
connection.setRequestMethod("GET");
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization",
                    "Basic " + new sun.misc.BASE64Encoder().encode((userName
+ ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", "application/x-www-
form-urlencoded");
            int status = connection.getResponseCode();
            if (status == 200) {
                if (connection.getContentType() != null &&
connection.getContentType().equals("application/json")) {
                    JSONObject json = new
JSONObject(getStringFromInputStream(connection.getInputStream()));
                    println "Error downloading file : " +
json.getString("details")
                } else {
                    def response =
getStringFromInputStream(connection.getInputStream());
                    def pingURL = fetchPingUrlFromResponse(response, "Job
Status");
                    getJobStatusDownload(pingURL, "GET");
                }
            } else {
                throw new Exception("Http status code: " + status);
        } finally {
            if (connection != null)
                connection.disconnect();
            if (outputStream != null)
                outputStream.close();
            if (inputStream != null)
                inputStream.close();
        }
    }
    private void downloadContent(def downloadURL) throws Exception {
        HttpURLConnection connection = null;
        InputStream inputStream = null;
        FileOutputStream outputStream = null;
        try {
            URL url = new URL(downloadURL);
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod("GET");
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization",
```

```
"Basic " + new sun.misc.BASE64Encoder().encode((userName
+ ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", "application/x-www-
form-urlencoded");
            int status = connection.getResponseCode();
            if (status == 200) {
                if (connection.getContentType() != null &&
connection.getContentType().equals("application/json")) {
                    JSONObject json = new
JSONObject(getStringFromInputStream(connection.getInputStream()));
                    System.out.println("Error downloading file : " +
json.getString("details"));
                } else {
                    inputStream = connection.getInputStream();
                    def downloadedFileName = fileName;
                    if(fileName.lastIndexOf("/") != -1) {
                        downloadedFileName =
fileName.substring(fileName.lastIndexOf("/") + 1);
                    }
                    String ext = ".zip";
                    if(connection.getHeaderField("fileExtension") !=null) {
                        ext = "."+connection.getHeaderField("fileExtension");
                    }
                    if(fileName.lastIndexOf(".") != -1 &&
fileName.lastIndexOf(".") != 0)
                        ext = fileName.substring(fileName.lastIndexOf(".")+1);
                    outputStream = new FileOutputStream(new
File(downloadedFileName+ext));
                    int bytesRead = -1;
                    byte[] buffer = new byte[5 * 1024 * 1024];
                    while ((bytesRead = inputStream.read(buffer)) != -1)
                        outputStream.write(buffer, 0, bytesRead);
                    System.out.println("File download completed.");
                }
            } else {
                throw new Exception("Http status code: " + status);
        } finally {
            if (connection != null)
                connection.disconnect();
            if (outputStream != null)
                outputStream.close();
            if (inputStream != null)
                inputStream.close();
        }
    }
    private void getJobStatusDownload(def pingUrlString, def methodType)
throws Exception {
        boolean completed = false;
        while (!completed) {
            def pingResponse = executeRequest(pingUrlString, methodType,
null, "application/x-www-form-urlencoded");
            JSONObject json = new JSONObject(pingResponse);
```

```
int status = json.getInt("status");
            if (status == -1) {
                try {
                    System.out.println("Please wait...");
                    Thread.sleep(20000);
                } catch (InterruptedException e) {
                    completed = true;
                    throw e;
                }
            } else {
                if (status > 0) {
                    println "Error occurred: " + json.getString("details")
                } else {
                    def downloadURL = fetchPingUrlFromResponse(pingResponse,
"Download link");
                    downloadContent(downloadURL);
                completed = true;
        }
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Download Application Snapshot (v2)

The Download Application Snapshot (v2) REST API downloads the application snapshot from EPM repository to the local location from where client is being run.

This API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

```
POST /interop/rest/v2/files/download
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Table 9-58 Tasks for Download Application Snapshot

Task	Request	REST Resource
Initiate download	POST	/interop/rest/v2/files/download
Status of compression of file	GET	/interop/rest/v2/status/download/7234359469022936
Download link	GET	/interop/rest/v2/files/download/7234359469022936
Deletion of temporary file (Applicable to snapshots)	DELETE	/interop/rest/v2/files/download/7234359469022936

Request

Supported Media Types: application/json

The following table summarizes the GET request parameters.

Table 9-59 Parameters

Name	Description Type	Required	Default
fileName	Application snapshot name or to download (for example, Payload "Artifact Snapshot").	Yes	None

Response

Supported Media Types: application/json

Response Header

fileExtension:This will have the file extension that can be used to create a file locally. Can contain values such as zip or csv.

Table 9-60 Parameters

Attribute	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	Parameters as key value pairs passed in the request

Example of Downloading with Postman

To download a file named snapshot.zip, select Basic Authorization header for all the requests.

Example URL and Payload to Initiate Download

Request Method: POST



Supported Media Types: application/json

```
https://<BASE URL>/interop/rest/v2/files/download
{
    "fileName": "snapshot.zip"
```

Example Response 1

}

```
{
    "details": null,
    "status": -1,
    "links": [
        {
            "href": " https://<BASE URL>/interop/rest/v2/files/download",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": " https://<BASE URL>/interop/rest/v2/status/download/
7236073834203988",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    1
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"fileName":"snapshot.zip"}' 'https://interop/rest/v2/files/download'
```

Example URL for Status of Compression File

Request Method: GET

Supported Media Types: application/json

https://<BASE URL>/interop/rest/v2/status/download/7236073834203988

Example Response 2



```
"action": "GET",
    "rel": "self",
    "data": null
},
{
    "href": "https://<BASE URL>/v2/files/download/7236073834203988",
    "action": "GET",
    "rel": "Download link",
    "data": null
    }
]
```

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json'
'https://<BASE URL>/interop/rest/v2/status/download/7237042873146169'
```

Example URL and Payload for Download Link

Request method: POST

Supported Media Types: application/json

https://<BASE URL>/interop/rest/v2/files/download/7236073834203988

Example Response 3

After receiving the response, if the content type is application/json, then there would be an error on the server and refer to details. Otherwise, if it's application/octet-stream, then the content to be downloaded is part of the response and can read from the response body.

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o snapshot.zip -D respHeader.txt -
H 'Content-Type: application/json'
'https://<BASE URL>/interop/rest/v2/files/download/7237042873146169'
```

Example URL and Payload for Deletion of Temporary File

Request method: DELETE

Supported Media Types: application/json

https://<BASE URL>/interop/rest/v2/files/download/7236073834203988

Example Response 4



Sample cURL command

```
curl -X DELETE -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D
respHeader.txt -H 'Content-Type: application/json'
'https://<BASE URL>/interop/rest/v2/files/download/7237042873146169'
```

Copy Application Snapshot (v1)

Use this API (v1) to copy a snapshot from one environment (source) to another environment (target).

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

This API is executed on the target environment after details are provided for the source environment from which the snapshot is to be copied.

Prerequisites: The password of the source EPM Cloud environment must have already been encrypted using EPM Automate. The encrypted password must then be passed as one of the parameters for the copysnapshot REST API. See the *encrypt* command in Command Reference in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.

This REST API is version v1.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/v1/services/{servicename}/copysnapshot

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Trigger copysnapshot	POST	/interop/rest/{api_version}/services/{servicename}/copysnapshot
Retrieve copysnapshot status	GET	/interop/rest/{api_version}/services/{servicename}/ copysnapshot/777
Request		
Supported Media Types: application/x-www-form-urlencoded		

Table 9-61 Tasks for Copy Application Snapshot

Response

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the POST request parameters.

Table 9-62 Parameters

Name	Description		Required	Default	
api_version	Specific API version, such as v1		Yes	None	
serviceName	Name of the service, such as PBCS	Path	Yes	None	
snapshotName	Name of the snapshot to be copied	Form	Yes	None	
userName	User with access to the source instance	Form	Yes	None	
fpwd	The encrypted password for the source user to be passed as a string. The encrypted password must then be passed as one of the parameters for the REST API.	Form	Yes	None	
	For information on encrypting and generating the password.epw password file with EPM Automate, see the encrypt command in Command Reference in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.				
sourceURL	The URL of the source instance	Form	Yes	None	
	Note: This API also supports the previous name of this parameter, targetURL.				

Table 9-63 Parameters

Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status of the copy snapshot	
data	Parameters as key value pairs passed in the request	

Example of Response Body



The following shows an example of the response body in JSON format.

```
{"status":-1, "items": null, "links":[{"rel":"self", "href":"https://<BASE
URL>/interop/rest/v1/services/PBCS/copysnapshot","data":null,"action":"POST"},
{"rel":"Job Status","href":"https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/interop/rest/v1/services/
PBCS/copysnapshot/1502357937045","data":null,"action":"GET"}],"details":null
```

Java Sample – CopySnapshot.java

```
11
// BEGIN - copysnapshotfrominstance
11
public void copysnapshot() throws Exception {
String snapshotName = "SNAPSHOT NAME";
String srcUserName = "USER NAME";
String targetURL = "https://<BASE URL>";
String srcEPWfilePath = "C:\\logs\\pwd.epw";
String srcDomain = null;
String urlString = String.format("%s/interop/rest/v1/services/PBCS/
copysnapshot", serverUrl);
String fpwd = fetchPwdFromFile(srcEPWfilePath);
String params = null;
if (null == srcDomain) {
params = "snapshotName=" + snapshotName + "&userName=" + srcUserName +
"&fpwd=" + fpwd + "&sourceURL="
                    + targetURL;
} else {
params = "snapshotName=" + snapshotName + "&userName=" + srcUserName +
"&fpwd=" + fpwd + "&sourceURL="
                    + targetURL + "&dom=" + srcDomain;
}
String response = executeRequest(urlString, "POST", params, "application/x-
www-form-urlencoded");
getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
private String fetchPwdFromFile(String filePath) {
        BufferedReader br = null;
        try {
            br = new BufferedReader(new FileReader(filePath));
            String line = null;
            String pwdString = null;
            while ((line = br.readLine()) != null) {
                pwdString = line;
            return pwdString;
        } catch (Exception e) {
```

cURL Sample - copysnapshot.sh

```
funcCopySnapshot() {
        url=$SERVER URL/interop/rest/v1/services/PBCS/copysnapshot
        snapshotName="SNAPSHOT NAME"
        srcUserName="USER NAME"
        targetURL="https://<BASE URL>";
        srcEPWfilePath="pwd.epw"
        srcDomain=""
        fpwd=`cat $ srcEPWfilePath`
if [ "X" == "X$ srcDomain " ]; then
param="snapshotName=$snapshotName&userName=$srcUserName
&fpwd=$fpwd&sourceURL=$targetURL"
else
param="snapshotName=$snapshotName&userName=$srcUserName
&fpwd=$fpwd&targetURL=$sourceURL&dom=$srcDomain"
fi
        funcExecuteRequest "POST" $url $param "application/x-www-form-
urlencoded"
        output=`cat response.txt`
        status=`echo $output | jq '.status'`
        if [ \$ status == -1 ]; then
        echo "Started Copysnapshot"
        funcGetStatus "GET"
        else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
        fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

```
Groovy Sample – copysnapshot.groovy
```

```
def copy() {
   def url;
   def params;
   try {
    snapshotName = "test";
    srcUserName = "epm default cloud admin";
    sourceURL = "https://<BASE URL>";
   srcEPWfilePath = "pwd.epw";
    fpwd = fetchPwdFromFile(srcEPWfilePath);
    srcDomain = null;
   //println fpwd
    if (null == srcDomain) {
           params = "snapshotName=" + snapshotName + "&userName=" +
srcUserName + "&fpwd=" + fpwd + "&targetURL=" + targetURL;
    } else {
           params = "snapshotName=" + snapshotName + "&userName=" +
srcUserName + "&fpwd=" + fpwd + "&targetURL=" + targetURL + "&dom=" +
srcDomain;
   }
   //println params
   url = new URL(serverUrl + "/interop/rest/v1/services/PBCS/copysnapshot");
   } catch (MalformedURLException e) {
   println "Incorrect URL. Please a pass valid URL"
   System.exit(0);
   }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
       getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
    }
}
def fetchPwdFromFile(filePath) {
        BufferedReader br = null;
        try {
           br = new BufferedReader(new FileReader(filePath));
            String line = null;
            String pwdString = null;
            while ((line = br.readLine()) != null) {
                pwdString = line;
            }
            return pwdString;
        } catch (Exception e) {
        } finally {
            if (null != br)
                try {
```

```
br.close();
} catch (IOException e) {
    // TODO Auto-generated catch block
    e.printStackTrace();
}
return null;
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Copy Application Snapshot (v2)

}

Use this REST API (v2) to copy a snapshot from one environment (source) to another environment (target).

This API is executed on the target environment after details are provided for the source environment from which the snapshot is to be copied.

Prerequisites: The password of the source EPM Cloud environment must have already been encrypted using EPM Automate. The encrypted password must then be passed as one of the parameters for the copyfrominstance REST API. See the *encrypt* command in Command Reference in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.

This REST API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

```
POST /interop/rest/v2/snapshots/copyfrominstance
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Trigger copysnapshot	POST	/interop/rest/v2/snapshots/copyfrominstance
Retrieve copysnapshot status	GET	/interop/rest/v2/status/jobs/777

Table 9-64 Tasks for Copy Application Snapshot

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.

Table 9-65 Parameters

Name	Description	Туре	Required	Default
snapshotName	Name of the snapshot to be copied	Payload	Yes	None
userName	User with the Service Administrator predefined role in the source instance	Payload	Yes	None
fpwd	The encrypted password for the source user to be passed as a string.	Payload	Yes	None
	For information on encrypting and generating the password.epw password file with EPM Automate, see the encrypt command in Command Reference in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.			
sourceURL	The URL of the source instance	Payload	Yes	None

Example URL and Payload

https://<BASE URL>/interop/rest/snapshots/copyfrominstance

```
{
   "snapshotName": "<NAME>",
   "userName": "<USERNAME>",
   "fpwd": "e0VQTUFUfWtWV3czam8xdDJlcFZJbUVhSVQ3VWc9PS5lcHcyMDE1LmFkbW",
   "sourceURL": "https://<BASE URL>"
}
```

Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API

Table 9-66 Parameters



Name	Description
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status of the copy snapshot
data	null

Table 9-66 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "status": -1,
    "items": null,
    "links": [{
        "rel": "self",
        "href": "https://<BASE URL>/interop/rest/v2/snapshots/
copyfrominstance",
        "data": null,
        "action": "POST"
    }, {
        "rel": "Job Status",
        "href": "https://<BASE URL>/interop/rest/v2/status/jobs/
1502357937045",
        "data": null,
        "action": "GET"
    }],
    "details": null
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"snapshotName":"SNAPSHOT_TO_BE_COPIED",
"sourceURL":"SOURCE_URL","userName":"USER_NAME","fpwd":"ENCRYPTED_PASSWORD"}'
'https://<BASE_URL>/interop/rest/v2/snapshots/copyfrominstance'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Rename Application Snapshot (v1)

This API renames a snapshot in EPM Cloud instances to a desired name. This gives you flexibility in naming your snapshots.

This REST API is version v1.



Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

PUT /interop/rest/{api_version}/renamesnapshot

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 9-67 Parameters

Name	lame Description		Required	Default
{api_version}	The version of the API, such as v1.	Path	Yes	None
snapshotName	The name of the snapshot to be renamed.	Form	Yes	None
newSnapshotName	The desired name of the existing snapshot.	Form	Yes	None

Response

Supported Media Types: application/json

Table 9-68 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "links":[{
   "https://<BASE URL>/interop/rest/v1/renamesnapshot",
        "rel":"self",
        "data":null,
        "action":"PUT"
    }
  ],
   "details":null,
   "status":0
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Rename Application Snapshot (v2)

The Rename Application Snapshot (v2) REST API renames a snapshot in EPM Cloud instances to a desired name. This gives you flexibility in naming your snapshots.

This API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

PUT /interop/rest/v2/snapshots/rename

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.



Table 9-69 Parameters

Name	Description	Туре	Required	Default
snapshotName	The name of the snapshot to be renamed.	Payload	Yes	None
newSnapshotName	The desired name of the existing snapshot.	Payload	Yes	None

Example URL and Payload

https://<BASE URL>/interop/rest/v2/snapshots/rename

```
{
    "snapshotName": "Artifact Snapshot",
    "newSnapshotName": "Backup_snapshot"
}
```

Response

Supported Media Types: application/json

Parameters:

Table 9-70 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	null

Example of Response Body

```
{
   "details": null,
   "status": 0,
   "links": [
        {
            "href": " https://<SERVICE_NAME>-
            <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/interop/
rest/v2/snapshots/rename",
            "action": "PUT",
            "rel": "self",
            "data": null
        }
```



Sample cURL Command

]

}

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H
'Content-Type: application/json' -d '{"snapshotName":"Artifact Snapshot",
"newSnapshotName":
"Original snapshot"}' 'https://<BASE URL>/interop/rest/v2/snapshots/rename'
```

Copy to and from the Object Store

This table table shows the REST APIs to copy a file or a backup snapshot from the outbox of the current cloud environment (the source) to the Oracle Object Storage Cloud (the target). It also shows the REST APIs to copy a file or a backup snapshot from the Oracle Object Storage Cloud (the source) to the cloud environment (the target). These REST APIs are version v1 and v2.

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-71 Application Snapshot Service


Task	Request	REST Resource
Copy to Object Store (v1)	POST	/interop/rest/v1/services/copytoobjectstore
Copy to Object Store (v2)	POST	/interop/rest/v2/objectstorage/copyto
Copy from Object Store (v1)	POST	/interop/rest/v1/services/copyfromobjectstore
Copy from Object Store (v2)	POST	/interop/rest/v2/objectstorage/copyfrom

Copy from Object Store (v1)

Use the Copy from Object Store (v1) REST API to copy a file or a backup snapshot from the Oracle Object Storage Cloud (the source) to the cloud environment (the target). If you are copying a backup snapshot, this API copies it from the Object Storage bucket and extracts its contents in Oracle Enterprise Performance Management Cloud.

This topic describes the v1 version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.





Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-72 Tasks for Copy from Object Store

Task	Request	REST Resource
Trigger copyfromobjectstor e	POST	/interop/rest/v1/services/copyfromobjectstore
Retrieve copyfromobjectstor e status	GET	/interop/rest/v1/services/jobs/777

Request

Supported Media Types: application/json



Table 9-73 Parameters

Name	Description	Туре	Required	Default
url	The URL of the Object Store, appended with the bucket name and the name of the object to be copied. The URL format:	Form	Yes	None
	<pre>https:// swiftobjectstorage.region_identifier.oracleclou d.com/v1/namespace/bucket name/object name</pre>			
	Components of this URL:			
	 region_identifier is a Oracle Cloud Infrastructure hosting region. 			
	 namespace is the top-level container for all buckets and objects. Each Oracle Cloud Infrastructure tenant is assigned a unique system-generated and immutable Object Storage namespace name at account creation time. Your tenancy's namespace name, for example, axaxnpcrorw5, is effective across all regions. bucket_name is the name of a logical container where you store your data and files. Buckets are organized and maintained under compartments. A system generated bucket name, for example, bucket-20210301-1359 reflects the current year, month, day, and time. 			
	 object_name is the name of the snapshot or file that you want to copy from Oracle Object Storage Cloud. For more information, see these topics in Oracle Cloud Infrastructure Documentation: 			
	 Regions and Availability Domains Understanding Object Storage Namespaces Managing Buckets 			
username	The ID of a user who has the required access rights to write to Oracle Object Storage Cloud.	Form	Yes	None
	For users created in a federated identity provider, specify the fully-qualified name of the user (for example, exampleIdP/jdoe or exampleIdP/john.doe@example.com, where exampleIdP is the name of the federated identity provider). For other users, provide the User ID.			
password	The Swift password or auth token associated with the user. This password is not the same as the password that you use to sign into the Object Storage Console. Auth token is an Oracle-generated token that you use to authenticate with third-party APIs, for example to authenticate with a Swift client. For instructions to create this token, see To create an auth token in Oracle Cloud Infrastructure Documentation.	Form	Yes	None
targetfile	Name of the target filename (with path) of the downloaded artifact. When copying snapshots, do not specify the ZIP extension.	Form	Yes	None
	Examples: Artifact Snapshot_24_Sept_2020, inbox/ File_new.txt			

Response

Supported Media Types: application/json



Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Table 9-74 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{"status":-1, "items": null, "links":[{"rel":"self", "href":"https://<BASE
URL>/interop/rest/v1/services/
copyfromobjectstore","data":null,"action":"POST"},{"rel":"Job
Status","href":"https://<BASE URL>/interop/rest/v1/services/jobs/
1502357937045","data":null,"action":"GET"}],"details":null
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Copy from Object Store (v2)

Use the Copy from Object Store (v2) REST API to copy a file or a backup snapshot from the Oracle Object Storage Cloud (the source) to the cloud environment (the target). If you are copying a backup snapshot, this API copies it from the Object Storage bucket and extracts its contents in Oracle Enterprise Performance Management Cloud.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. This API is backwards compatible.

Note:

The Object Storage requires an *Other Web Services Provider* type. Ensure that you have access to the Web service you are connecting. You must also have URLs for the Web service and an login details if required. For information see, Connecting to External Web Services in *Administering Planning*.

This REST API is version v2.



Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/objectstorage/copyfrom

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-75 Tasks

Task	Request	REST Resource
Trigger copyfromobjectstor e	POST	/interop/rest/v2/objectstorage/copyfrom
Retrieve copyfromobjectstor e status	GET	/interop/rest/v2/status/jobs/777

Request

Supported Media Types: application/json



Table 9-76 Parameters

Name	Description	Туре	Required	Default
url	The URL for Oracle Cloud Object Storage, appended with the bucket name and an optional object name.	Payload	Yes	None
	This is the URL format: :			
	https://			
	swiftobjectstorage.region_identifier.oracleclou			
	d.com/v1/namespace/bucket_name/object_name			
	Components of this URL:			
	 region_identifier is a Oracle Cloud Infrastructure hosting region. 			
	• namespace is the top-level container for all buckets and objects. Each Oracle Cloud Infrastructure tenant is assigned a unique system-generated and immutable Object Storage namespace name at account creation time. Your tenancy's namespace name, for example, axaxnpcrorw5, is effective across all regions.			
	 bucket_name is the name of a logical container where you store your data and files. Buckets are organized and maintained under compartments. A system-generated bucket name, for example, bucket-20210301-1359 reflects the current year, month, day, and time. 			
	 object_name is the name of the snapshot or file that you want to copy from Oracle Object Storage Cloud. 			
	For more information, see these topics in Oracle Cloud Infrastructure Documentation:			
	Regions and Availability Domains			
	Understanding Object Storage Namespaces			
	Managing Buckets			
userName	The ID of a user who has the required access rights to write to Oracle Object Storage Cloud.	Payload	Yes	None
	For users created in a federated identity provider, specify the fully-qualified name of the user (for example, exampleIdP/jdoe or exampleIdP/john.doe@example.com, where exampleIdP is the name of the federated identity provider). For other users, provide the User ID.			
password	The Swift password or auth token associated with the user. This password is not the same as the password that you use to sign into the Object Storage Console. Auth token is an Oracle-generated token that you use to authenticate with third-party APIs, for example to authenticate with a Swift client. For instructions to create this token, see To create an auth token in Oracle Cloud Infrastructure Documentation.	Payload	Yes	None
targetFile	Name of the target filename (with path) of the downloaded artifact. When copying snapshots, do not specify the ZIP extension.	Payload	Yes	None
	Examples: Artifact Snapshot_24_Sept_2020, inbox/ File_new.txt			

Example URL and Payload

```
{
    "url":"https://swiftobjectstorage.<region_identifier>.oraclecloud.com/v1/
namespace/bucket_name/object_name",
    "userName": "epm_user",
    "password": "epm_password",
    "targetFile": "Artifact snapshot"
}
```

https://<BASE URL>/interop/rest/v2/objectstorage/copyfrom

Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Table 9-77 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "details": null,
    "status": -1,
    "items": null,
    "links": [
        {
            "href": " https://<BASE URL>/interop/rest/v2/objectstorage/
copyfrom",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": " https://<BASE URL>/interop/rest/v2/status/jobs/
4003051833546274",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
```



```
]
```

}

Sample cURL Command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H
'Content-Type: application/json' -d
'{"url":"OBJECT_STORAGE_URL","userName":"USER_NAME","password":"PASSWORD",
"targetFile":"FILEPATH/FILENAME"}' 'https://<BASE_URL>/interop/rest/v2/
objectstorage/copyfrom'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Copy to Object Store (v1)

Use the Copy to Object Store (v1) REST API to copy a file or a backup snapshot from the current cloud environment (the source) to the Oracle Object Storage Cloud (the target). You can copy any file or snapshot available in the EPM Cloud. For example, if you export data to a file, the exported file is stored in the Outbox. You can then use this API to copy the file directly to Oracle Object Storage, assuming you have an account.

This topic describes the v1 version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

Note:

The Object Storage requires an *Other Web Services Provider* type. Ensure that you have access to the Web service you are connecting. You must also have URLs for the Web service and an login details if required. For information see, Connecting to External Web Services in *Administering Planning*.

This REST API is version v1.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v1/services/copytoobjectstore

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-78 Tasks for Copy to Object Store

Task	Request	REST Resource
Trigger copytoobjectstore	POST	/interop/rest/v1/services/copytoobjectstore
Retrieve copytoobjectstore status	GET	/interop/rest/v1/services/jobs/777

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.



Table 9-79 Parameters

Name	Description	Туре	Required	Default
url	Oracle Object Storage Cloud bucket with an optional object name appended. The URL format without object name: https:// swiftobjectstorage.region_identifier.oracleclou d.com/v1/namespace/bucket_name	Form	Yes	None
	The URL format with object name:			
	<pre>https:// swiftobjectstorage.region_identifier.oracleclou d.com/v1/namespace/bucket_name/object_name</pre>			
	Components of this URL:			
	 region_identifier is an Oracle Cloud Infrastructure hosting region. namespace is the top-level container for all buckets and objects. Each Oracle Cloud Infrastructure tenant is assigned a unique system-generated and immutable Object Storage namespace name at account creation time. Your tenancy's namespace name, for example, axaxnpcrorw5, is effective across all regions. bucket_name is the name of a logical container where you store your data and files. Buckets are organized and maintained under compartments. A system generated bucket name, for example, bucket-20210301-1359 reflects the current year, month, day, and time. object_name, optionally, is name that you want to use for the file on Oracle Object Storage Cloud. If an object name is not specified, the file will be copied with its original name. For more information, see these topics in Oracle Cloud Infrastructure Documentation: Regions and Availability Domains Understanding Object Storage Namespaces 			
username	Managing Buckets The ID of a user who has the required access rights to write	Form	Yes	None
	to Oracle Object Storage Cloud. For users created in a federated identity provider, specify the fully-qualified name of the user (for example, exampleIdP/ jdoe or exampleIdP/john.doe@example.com, where exampleIdP is the name of the federated identity provider). For other users, provide the User ID.			
password	The Swift password or auth token associated with the user. This password is not the same as the password that you use to sign into the Object Storage Console. Auth token is an Oracle-generated token that you use to authenticate with third-party APIs, for example to authenticate with a Swift client. For instructions to create this token, see To create an auth token in Oracle Cloud Infrastructure Documentation.	Form	Yes	None
filepath	Name of the file (with path) to be copied to the Store. If you are copying a snapshot, do not specify the ZIP extension. Examples: Artifact Snapshot, inbox/File.txt	Form	Yes	None

Sample Request Payload

```
url: https://swiftobjectstorage.<region_identifier>.oraclecloud.com/v1/
epmclouddev/epm_artifact_snapshot
username: <username>
password: <password>
filepath: Artifact Snapshot
```

Response

Supported Media Types: application/json

Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status	
data	Parameters as key value pairs passed in the request	

Table 9-80 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "status": -1,
    "items": null,
    "links": [{
        "rel": "self",
        "href": "https://<BASE URL>/interop/rest/v1/services/
copytoobjectstore",
        "data": null,
        "action": "POST"
    }, {
        "rel": "Job Status",
        "href": "https://<BASE URL>/interop/rest/v1/services/jobs/
1502357937045",
        "data": null,
        "action": "GET"
    }],
    "details": null
}
```

The password parameter value is clear text.

```
copyToObjectStore Sample code:
public void copyToObjectStore() throws Exception {
```



```
String filepath = "FILE NAME/FILE PATH";
String username = "USER NAME";
String url = "https://
swiftobjectstorage.<region_identifier>.oraclecloud.com/v1/<namespace>/
<bucket_name>";
String password = "PASSWORD";
String urlString = String.format("%s/interop/rest/v1/services/
copytoobjectstore", serverUrl);
String params = "url=" + url + "&userName=" + username + "&password=" +
password + "&filepath=" +filepath;
String response = executeRequest(urlString, "POST", params,
"application/x-www-form-urlencoded");
getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Copy to Object Store (v2)

Use the Copy to Object Store (v2) REST API to copy a file or a backup snapshot from the current cloud environment (the source) to the Oracle Object Storage Cloud (the target). You can copy any file or snapshot available in the EPM Cloud. For example, if you export data to a file, the exported file is stored in the Outbox. You can then use this API to copy the directly to Oracle Object Storage, assuming you have an account.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. This API is backwards compatible.

Note:

The Object Storage requires an *Other Web Services Provider* type. Ensure that you have access to the Web service you are connecting. You must also have URLs for the Web service and an login details if required. For information see, Connecting to External Web Services in *Administering Planning*.

This REST API is version v2.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/objectstorage/copyto



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-81 Tasks

Task	Request	REST Resource
Trigger copytoobjectstore	POST	/interop/rest/v2/objectstorage/copyto
Retrieve copytoobjectstore status	GET	/interop/rest/v2/status/jobs/777

Request

Supported Media Types: application/json

The following table summarizes the request parameters.



Table 9-82 Parameters

Name	Description	Туре	Required	Default
url	The URL for Oracle Cloud Object Storage, appended with the bucket name and an optional object name.	Payload	Yes	None
	This is the URL format without the object name:			
	<pre>https:// swiftobjectstorage.region_identifier.oraclecl oud.com/v1/namespace/bucket_name</pre>			
	This is the URL format with the object name: https:// swiftobjectstorage.region_identifier.oracleclou d.com/v1/namespace/bucket name/object name			
	Components of this URL:			
	 region_identifier is a Oracle Cloud Infrastructure hosting region. 			
	 namespace is the top-level container for all buckets and objects. Each Oracle Cloud Infrastructure tenant is assigned a unique system-generated and immutable Object Storage namespace name at account creation time. Your tenancy's namespace name, for example, axaxnpcrorw5, is effective across all regions. 			
	 bucket_name is the name of a logical container where you store your data and files. Buckets are organized and maintained under compartments. A system-generated bucket name, for example, bucket-20210301-1359 reflects the current year, month, day, and time. 			
	 object_name, optionally, is a name that you want to use for the file on Oracle Object Storage Cloud. If an object name is not specified, the file will be copied with its original name. 			
	For more information, see these topics in Oracle Cloud Infrastructure documentation:			
	Regions and Availability Domains			
	 Understanding Object Storage Namespaces Managing Buckets 			
userName	The ID of a user who has the required access rights to write to Oracle Object Storage Cloud.	Payload	Yes	None
	For users created in a federated identity provider, specify the fully-qualified name of the user (for example, exampleIdP/jdoe or exampleIdP/john.doe@example.com, where exampleIdP is the name of the federated identity provider). For other users, provide the User ID.			
password	The Swift password or auth token associated with the user. This password is not the same as the password that you use to sign into the Object Storage Console. Auth token is an Oracle-generated token that you use to authenticate with third-party APIs, for example to authenticate with a Swift client. For instructions to create this token, see To create an auth token in Oracle Cloud Infrastructure Documentation.	Payload	Yes	None

Name	Description	Туре	Required	Default
filePath	Name of the file (with path) to be copied to the Object Store. If you are copying a snapshot, do not specify the ZIP extension.	Payload	Yes	None
	Examples: Artifact Snapshot, inbox/File.txt			

Table 9-82 (Cont.) Parameters

Example URL and Payload

```
https://<BASE URL>/interop/rest/v2/objectstorage/copyto
```

```
{
    "url": "https://swiftobjectstorage.<region_identifier>.oraclecloud.com/v1/
epmclouddev/epm_artifact_snapshot",
    "userName": "username",
    "password": "password",
    "filePath": "Artifact Snapshot"
}
```

Response

Supported Media Types: application/json

Table 9-83	Parameters
------------	------------

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "status": -1,
    "items": null,
    "links": [{
        "rel": "self",
        "href": "https://<BASE URL>/interop/rest/v2/objectstorage/copyto",
        "data": null,
        "action": "POST"
    }, {
        "rel": "Job Status",
    }
}
```

```
"href": "https://<BASE URL>/interop/rest/v2/status/jobs/
1502357937045",
    "data": null,
    "action": "GET"
    }],
    "details": null
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"url":"OBJECT_STORAGE_URL","userName":"USER_NAME","password":"PASSWORD","fil
ePath":"FILEPATH/FILENAME"}' 'https://<BASE_URL>/interop/rest/v2/
objectstorage/copyto'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Working with Essbase

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-84 Working with Essbase

Task	Request	REST Resource
Export Essbase Data (v2)	POST	/interop/rest/v2/essbase/export
Essbase Block Analysis Report	POST	/interop/rest/diag/v1/services/essbaseblockanalysisreport
Get Essbase Query Governor Execution Time	GET	/interop/rest/{api_version}/config/services/ essbaseqrygovexectime
Set Essbase Query Governor Execution Time	PUT	/interop/rest/{api_version}/config/services/ essbaseqrygovexectime

Export Essbase Data (v2)

The Export Oracle Essbase (v2) REST API exports level 0 or all data for the specified cube. Export data files are written to the Outbox directory as a zip file. You can download it using the EPM Automate downloadFile command or the Download REST API. Running an export places



the cube into read-only mode and prevents any write activity during the period of the execution of the export.

This API is version v2.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/essbase/export

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-85 Parameters

Name	Description	Туре	Required	Default
cubeName	Name of the BSO or ASO cube	Payload	Yes	None
fileName	Name of a zip file in which the Essbase data will be exported. This file will be available in the outbox from where it can be downloaded.	Payload	Yes	None
level	The value is 0 or ALL, Level 0 and ALL are valid for BSO cubes. Only level 0 is valid for ASO cubes.	Payload	Yes	level=0

Example URL and Payload

https://<BASE URL>V/interop/rest/v2/ essbase/export

```
{
   "cubeName": "Plan1",
   "fileName": "Plan1Export.zip",
   "parameters": {
        "level": "0"
   }
}
```

Response

Supported Media Types: application/json



Attribute	Description
details	In case of errors, details are published with the error string
status	See Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible values. Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the re-export operation
data	Parameters as key value pairs passed in the request

Table 9-86Parameters

Examples of Response Body

The following are examples of the response body in JSON format.

Example 1: Export is in Progress

```
{
    "details": "Essbase Database Export",
    "status": -1,
    "items": null,
    "links": [
        {
            "href": "https://<BASE URL>/interop/rest/v2/essbase/export",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": "https://<BASE URL>/interop/rest/v2/status/jobs/
19974850954170405",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    ]
}
```

Example 2: Export Completes Successfully

```
"data": null
}
]
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"cubeName": "Plan1","fileName": "Plan1Export.zip","parameters":{"level":
"0" }}' 'https://<BASE URL>/interop/rest/v2/essbase/export'
```

Essbase Block Analysis Report

}

Use this REST API to create an Oracle Essbase Block Analysis Report that helps you analyze Oracle Essbase data to support the tuning of Block Storage Option (BSO) cubes (generally, used for calculations) in your application. The Essbase Block Analysis report is helpful to resolve performance issues resulting from patterns of data; for example, repeated numbers in Essbase BSO cubes.

The Essbase Block Analysis report provides information in these areas:

- **Percentage of blocks with only Zero:** Shows the blocks that contain only zeros as a percentage of all the blocks contained in the export file.
- Top 10 Repeated Numerical Cell Values By Percentage of Numerical Cells: Shows the top 10 repeated values as a percentage of all the values in the export file.
- **Top 100 Dense Member Combinations with Repeated Values:** Shows the top 100 dense combinations with repeated values in the cube. The "Cell Value" column shows a value for each member, in the order it appears in the hierarchy, as a different column. For example, if Period is across the column, there will be a different column for January, February, and so on. Other dense dimension(s) appear in the rows. This should help you identify the locations of the repeated values.

Before executing this API, use the Export Essbase Data (v2) API to export the data from the cube for which you want to create the Block Analysis report to a zip file. You may export levelo or all data as needed. Execute this API to create the Block Analysis report for this zip file. The report is created in the outbox; you can use the Download API to download it to a local computer or the Send Email (v1) or Send Email (v2) API to email it.

This API is version v1.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/diag/v1/services/essbaseblockanalysisreport



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters:

Table 9-87 Parameters

Name	Description	Туре	Required	Default
exportDataFile	Name of the zip file that contains the Essbase data that was previously exported from a BSO cube	Payload	Yes	None
reportFile	Name for the HTML formatted Block Analysis Report file	Payload	Yes	None

Sample URL and Payload

https//<BASE URL>/interop/rest/diag/v1/services/essbaseblockanalysisreport

{"zipFilename":"essbaseexport.zip","outputFileName":"Essbase.html"}

Response

Supported Media Types: application/json

Name	Description
details	Detailed status of the operation performed.
status	See Migration Status Codes
links	Detailed information about the link and HTTP call type
items	Detailed information about the API
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you
	can use the href to get the status
data	Parameters as key value pairs passed in the request

Table 9-88 Parameters

Example of Response Body



```
phoenix223599.appsdev1.fusionappsdphx1.oraclevcn.com:9380/interop/rest/
diag/v1/services/essbaseblockanalysisreport,
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": http://
phoenix223599.appsdev1.fusionappsdphx1.oraclevcn.com:9380/interop/rest/
diag/v1/services/jobs/537707435156101,
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    ]
}
```

Get Essbase Query Governor Execution Time

This API returns the Oracle Essbase Query Governor Execution Time (maximum number of seconds that a query can run before Essbase Server terminates it) of all the Essbase cubes.

This API is version v2.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/{api version}/config/services/essbaseqrygovexectime

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Table 9-89 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None

Response

Supported Media Types: application/json



Parameters	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Can be self and/or Job Status. If set to Job Status, you can use the href	
	to get the status of the import operation	
data	Parameters as key value pairs passed in the request	

Table 9-90 Parameters

Example of Response Body

```
{
    "details": null,
    "status": 0,
    "items": [
        {
             "qryexectime": "600"
        }
    ],
    "links": [
        {
            "href": "<uri>/interop/rest/v2/config/services/
essbaseqrygovexectime",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```

Set Essbase Query Governor Execution Time

This API sets the Oracle Essbase Query Governor Execution Time (maximum number of seconds that a query can run before the Essbase Server terminates it) for all the Essbase cubes.

The governor value can be set to any value from 0 to 70000.

This API is version v2.


Required Roles

Service Administrator

REST Resource

PUT /interop/rest/{api_version}/config/services/essbaseqrygovexectime





Request

Supported Media Types: application/json

Table 9-91 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
qryexectime	Query Governor Execution Time Value	Payload	Yes	None

Example of Request Body

```
{
    "qryexectime": "600"
}
```

Response

Supported Media Types: application/json

Table 9-92 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href
	to get the status of the import operation
data	Parameters as key value pairs passed in the request

Example of Response Body

```
{
    "links": [{
        "rel": "self",
        "href": "<uri>/interop/rest/v2/config/services/
essbaseqrygovexectime",
        "data": null,
        "action": "PUT"
    }],
    "details": "null",
```

"status": 0, "items": null

Copy a File Between Instances (v1)

}

Use this API (v1) to copy a file from one environment (source) to another environment (target).

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

This API is executed on the target environment after details are provided for the source environment from which the file is to be copied. This feature gives you flexibility in copying files from one cloud environment to another.

Prerequisites: The password of the source EPM Cloud environment must have already been encrypted using EPM Automate. The encrypted password must then be passed as one of the parameters for the Copy File REST API. See the encrypt command in Command Reference in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud.*

This REST API is version v1.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/v1/services/copyfile

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the POST request parameters.

Table 9-93 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version, such as v1	Path	Yes	None
sourceFileName	Name of the file to be copied	Form	Yes	None
userName	User with access to the source instance	Form	Yes	None



Table 9-93(Cont.) Parameters

Name	Description	Туре	Required	Default
pwd	The location and name of the file containing the encrypted password for the user. The encrypted password must then be passed as one of the parameters for the Copy File REST API. For information on encrypting and generating the password.epw file with EPM Automate, see the encrypt command in Command Reference in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.	Form	Yes	None
sourceURL	The URL of the source instance	Form	Yes	None
targetFileName	Name of the file to be copied to the target environment	Form	Yes	None

Response

Supported Media Types: application/json

Table 9-94 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{"status":-1, "items": null, "links":[{"rel":"self", "href":"https://<<BASE
URL>/interop/rest/v1/services/copyfile","data":null,"action":"POST"},
{"rel":"Job Status","href":"https://<BASE URL>/interop/rest/v1/services/jobs/
1502357937045","data":null,"action":"GET"}],"details":null
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Copy a File Between Instances (v2)

Use this REST API (v2) to copy a file from one environment (source) to another environment (target).

This API is executed on the target environment after details are provided for the source environment from which the file is to be copied. This feature gives you flexibility in copying files from one cloud environment to another.

Prerequisites: The password of the source EPM Cloud environment must have already been encrypted using EPM Automate. The encrypted password must then be passed as one of the parameters for the Copy File REST API. See the encrypt command in Command Reference in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud*.

This REST API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/v2/files/copyfrominstance

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.

Table 9-95 Parameters

Name	Description	Type Require		d Default	
sourceFileName	Name of the file to copy	Payload	Yes	None	
userName	User with the Service Administrator predefined role in the source instance	Payload	Yes	None	
pwd	The location and name of the file containing the encrypted password for the user. For information on encrypting and generating the password.epw file with EPM Automate, see the encrypt command in Command Reference in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.	Payload	Yes	None	
sourceURL	The URL of the source instance	Payload	Yes	None	



Table 9-95(Cont.) Parameters

Name	Description	Туре	Required	Default
targetFileName	Name of the file to be copied to the target environment	Payload	Yes	None

Example URL and Payload

https://<BASE URL>/interop/rest/files/copyfrominstance

```
{
   "sourceFileName": "<NAME>",
   "userName": "<USERNAME>",
   "pwd": "<PASSWORDFILE>",
   "sourceURL": "https://<BASE URL>,"
   "targetFileName": "<NAME>"
}
```

Response

Supported Media Types: application/json

Table 9-96	Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	null

Example of Response Body

The following shows an example of the response body in JSON format.

```
"status": -1,
"items": null,
"links": [{
    "rel": "self",
    "href": "https://<BASE URL>/interop/rest/v2/files/copyfrominstance",
    "data": null,
    "action": "POST"
    }, {
        "rel": "Job Status",
        "href": "https://<BASE URL>/interop/rest/v2/status/jobs/
1502357937045",
        "data": null,
        "action": "GET"
```

```
}],
"details": null
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"sourceFileName":"FILE_TO_BE_COPIED",
"sourceURL":"SOURCE_URL","userName":"USER_NAME","targetFileName":"TARGET_FILEN
AME","pwd":"ENCRYPTED_PASSWORD"}' 'https://<BASE_URL>/interop/rest/v2/files/
copyfrominstance'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Clone an Environment

}

Use this REST API to clone the current environment and, optionally, identify domain artifacts (users and predefined roles), Data Management records, audit records, Job Console records, contents of the inbox and outbox, and stored snapshots.

This API is executed on the source environment after details are provided for the target environment to be cloned. It is an alternative to using the Clone Environment feature in a browser or the EPM Automate cloneEnvironment command.

Prerequisites: The password of the target EPM Cloud environment must have already been encrypted using EPM Automate. The encrypted password string must then be passed as one of the parameters for the Clone Environment REST API. See the encrypt command in *Working with EPM Automate for Oracle Enterprise Performance Management Cloud*.

For considerations with cloning an environment, see Cloning EPM Cloud Environments in Administering Migration for Oracle Enterprise Performance Management Cloud.

This REST API is version v1.

Required Roles

Service Administrator

Identity Domain Administrator role is required to clone users and predefined roles.

REST Resource

```
POST /interop/rest/v1/services/clone
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Request

Supported Media Types: <code>application/json</code>

The following table summarizes the POST request parameters.

Table 9-97 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version, such as v1	Path	Yes	None
targetUsername	sername The ID of a Service Administrator in the target environment. If you plan to clone user and role assignments in the target environment, this user must also have the Identity Domain Administrator role.		Yes	None
targetEncryptPassw ord	The encrypted password of the user identified by targetUsername to be passed as a string.	Payload	Yes	None
	For information on encrypting and generating the password.epw file with EPM Automate, see encrypt in Working with EPM Automate for Oracle Enterprise Performance Management Cloud.			
targetURL	The URL of the environment that will become the cloned environment	Payload	Yes	None
snapshotName	Optionally, the name of a snapshot that should be used for cloning. This snapshot must be present in the source environment.	Payload	No	Last maintena nce snapshot
migrateUsers	Whether to clone users and their predefined and application role assignments, True or False. For this option to work, the user identified by targetUsername must have the Identity Domain Administrator role in the target environment.	Payload	No	False
maintenanceStartTi me	Whether to reset the maintenance start time of the cloned environment to that of the source environment. To keep the current maintenance start time of the target environment, set this value to False.	Payload	No	True
dataManagement	Whether to clone the Data Management records of the source to the target environment for all environments other than Oracle Enterprise Data Management Cloud and Narrative Reporting, True or False.	Payload	No	True
applicationAudit	Whether to clone the application audit data in the source to the target environment for FreeForm, Planning, Planning Modules, Financial Consolidation and Close, and Tax Reporting environments, True or False. Including application audit data while cloning an environment makes the target environment keep the application audit history.	Payload	No	True
jobConsole	Whether to clone the job console data in the source to the target environment for FreeForm, Planning, Planning Modules, Financial Consolidation and Close, and Tax Reporting environments, True or False. Including job console data while cloning an environment makes the target environment keep the job console history.	Payload	No	True



Table 9-97 (Cont.) Parameters

Name	Description	Туре	Required	Default
storedSnapshotsAnd Files	Whether to clone the contents of the inbox, outbox, and stored snapshots in the source to the target environment for all environments, True or False. Including stored snapshots and files while cloning an environment makes sure that the stored snapshots and files are not lost. This is useful especially while cloning a Classic environment to an OCI (Gen 2) environment.		No	False

Example URL and Payload

```
{
    "targetURL":"https://<BASE URL>,targetUserName":"cloneUser@oracle.com",
    "targetEncryptPassword":"<targetUserEncryptedPasswordString>",
    "parameters":{"snapshotName":"Artifact Snapshot"
    "migrateUsers":"true", "maintenanceStartTime":"true", "dataManagement":"true",
    "jobConsole":"true", "applicationAudit":"true",
    "storedSnapshotsAndFiles":"false"}
}
```

Response

Supported Media Types: application/json

Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status	
intermittentSta tus	Status of each step performed; can be polled regularly from the job status URL	

Table 9-98 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{"intermittentStatus":null, "links":[{"rel":"Job Status","href":"https://
<<BASE URL>/interop/rest/v1/services/
status","data":null,"action":"GET"}],"details":null,"status":-1"items":null)
```

Java Sample - CloneEnvironment.java

Prerequisites: json.jar



Common functions: See Appendix A, Common Helper Functions for Java.

```
11
    // BEGIN - Clone Environment
    11
    public void cloneEnvironment() throws Exception {
        String targetUrl = "https://<BASE URL>";
        String targetUsername = "<Target User name>";
        String encryptedPwdString =
fetchPwdFromFile("epw file Path") ; //"<Target system encrypted password>";
        String snapshotToClone = "Artifact Snapshot";
        JSONObject params = new JSONObject();
        JSONObject payload = new JSONObject();
         //Optional parameters if not passed default values will be picked
         /*
         params.put("snapshotName", snapshotToClone);
         params.put("migrateUsers", Boolean.TRUE.toString());
         params.put("maintenanceStartTime", Boolean.TRUE.toString());
         params.put("dataManagement", Boolean.TRUE.toString());
         */
         //Mandatory parameters
         payload.put("targetURL", targetUrl);
         payload.put("targetUserName", targetUsername);
         payload.put("targetEncryptPassword", encryptedPwdString);
         payload.put("parameters", params);
     String urlString = String.format("%s/interop/rest/v1/services/clone",
serverUrl);
     String response = executeRequest(urlString, "POST", payload.toString(),
"application/json");
     getMigrationJobStatus(fetchPingUrlFromResponse(response, "Job
Status"), "GET");
private String fetchPwdFromFile(String filePath) {
        BufferedReader br = null;
        try {
           br = new BufferedReader(new FileReader(filePath));
            String line = null;
            String pwdString = null;
            while ((line = br.readLine()) != null) {
                pwdString = line;
            }
            return pwdString;
        } catch (Exception e) {
        } finally {
            if (null != br)
                try {
                    br.close();
                } catch (IOException e) {
                    // TODO Auto-generated catch block
                    e.printStackTrace();
                }
```



```
}
return null;
}
//
// END - Clone Environment
//
```

cURL Sample - cloneEnvironment.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcCloneEnvironment() {
    url="$SERVER URL/interop/rest/v1/services/clone"
    local targetUrl="<TargetSystemURL>"
    local targetUserName="<TargetSystemUsername>"
    local targetEncryptedPassword= $(cat $EPWfilePath)
#"<TargetSystemEncryptedPasswordString>"
    #optionalParams="{\"snapshotName\":\"Artifact
Snapshot\", \"migrateUsers\":\"true\", \"maintenanceStartTime\":\"true\", \"dataM
anagement\":\"true\"}"
param="{\"targetURL\":\"$targetUrl\",\"targetUserName\":\"$targetUserName\",\"
targetEncryptPassword\":\"$targetEncryptedPassword\"}"
#, \"parameters\":\"$optionalParams\"}"
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=$(cat response.txt)
    status=$(echo $output | jq '.status')
    if [ \$status == -1 ]; then
        echo "CloneEnvironment is in progress.."
        funcGetStatus "GET"
    else
        error=$(echo $output | jq '.details')
        echo "Error occurred. " $error
    fi
}
```

Groovy Sample – cloneEnvironment.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def cloneEnvironment(targetURL,targetUsername,targetEncyptedPasswordFile){
   String scenario = "Clone Environment";
   def targetEncyptedPassword = fetchPwdFromFile(targetEncyptedPasswordFile);
   def json = new JsonBuilder()
   //Optional parameter to be set if needed
   //def optionalParams = [snapshotName: "Artifact Snapshot", migrateUsers:
   "true", maintenanceStartTime: "true", dataManagement:"true"]
```



```
def payload = new JsonBuilder()
        payload targetURL: targetURL,
                targetUserName: targetUsername,
                targetEncryptPassword: targetEncyptedPassword //,
                //parameters: optionalParams
    params=payload.toString();
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/v1/services/clone");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/json");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
}
def fetchPwdFromFile(filePath) {
        BufferedReader br = null;
        try {
            br = new BufferedReader(new FileReader(filePath));
            String line = null;
            String pwdString = null;
            while ((line = br.readLine()) != null) {
                pwdString = line;
            }
            return pwdString;
        } catch (Exception e) {
        } finally {
            if (null != br)
                try {
                    br.close();
                } catch (IOException e) {
                    // TODO Auto-generated catch block
                    e.printStackTrace();
                }
        }
        return null;
}
```

Sample cURL Command Basic Auth

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/
json' -d '{"targetURL":
" https://<BASE URL>","targetUserName":"<TARGET-
USERNAME>","targetEncryptPassword":"<TARGET-ENCRYPTED-PASSWORD>",
"parameters":{"snapshotName":"<SNAPSHOT-
NAME>","migrateUsers":"true","maintenanceStartTime":"<TRUE/</pre>
```

```
FALSE>","dataManagement":
    "<TRUE/FALSE>","jobConsole":"<TRUE/FALSE>","applicationAudit":"<TRUE/
FALSE>","storedSnapshotsAndFiles":"<TRUE/FALSE>"}}'
'https://<EPM-CLOUD-BASE-URL>/interop/rest/v1/services/clone'
```

Sample cURL Command OAuth 2.0

```
curl -X POST --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/json' -d '{"targetURL":
" https://<BASE URL>","targetUserName":"<TARGET-
USERNAME>","targetEncryptPassword":"<TARGET-ENCRYPTED-PASSWORD>",
"parameters":{"snapshotName":"<SNAPSHOT-
NAME>","migrateUsers":"true","maintenanceStartTime":"<TRUE/
FALSE>","dataManagement":
"<TRUE/FALSE>","jobConsole":"<TRUE/FALSE>","applicationAudit":"<TRUE/
FALSE>","storedSnapshotSAndFiles":"<TRUE/FALSE>"}'
'https://<EPM-CLOUD-BASE-URL>/interop/rest/v1/services/clone'
```

Provide Feedback (v11.1.2.3.600)

This feedback service sends feedback or reports an issue to Oracle.

This API is version 11.1.2.3.600.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

POST /interop/rest/{api_version}/feedback

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 9-99 Parameters

Name	Description	
details	Published in case of errors with the error string	
status	See Migration Status Codes	
items	Details about the resource	
issueRef	Feedback reference to contact Oracle support	



Name	Description
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	Parameters as key value pairs passed in the request

Table 9-99 (Cont.) Parameters

Example of Response Body

Supported Media Types: application/json

The following shows an example of the response body in JSON format.

```
{
   "details":null,
   "status":0,
   "items":[{"issueRef":"UDR_default_fin_superuser_2015_09_14_11_10_18"}],
   "links":[{
        "data":null,
        "action":"POST",
        "rel":"self",
        "href":"https://<BASE_URL>/interop/rest/{api_version}/feedback"
   }]
}
```

Java Sample - ProvideFeedback.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN - Provide Feedback
11
public void provideFeedback(String description) throws Exception {
   JSONObject params = new JSONObject();
   JSONObject config = new JSONObject();
    config.put("URL", serverUrl);
   params.put("configuration", config);
   params.put("description", description);
    String urlString = String.format("%s/interop/rest/%s/feedback",
serverUrl, lcmVersion);
   String response = executeRequest(urlString, "POST", params.toString(),
"application/json");
   JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        System.out.println("Feedback successful");
    } else {
        System.out.println("Error occurred: " + json.getString("details"));
    }
```



```
}
//
// END - Provide Feedback
//
```

cURL Sample – ProvideFeedback.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

```
Common Functions: See Common Helper Functions for cURL
```

```
funcProvideFeedback() {
    url=$SERVER URL/interop/rest/$LCM VERSION/feedback
    description=$(echo $1 | sed -f urlencode.sed)
   param="{\"configuration\":
{\"URL\":\"$SERVER URL\"},\"description\":\"$description\"}"
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Feedback successful"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – ProvideFeedback.groovy

Prerequisites: json.jar

See CSS Common Helper Functions for Groovy

```
def provideFeedback(description) {
   def url;
    JSONObject params = new JSONObject();
    try {
        JSONObject config = new JSONObject();
        config.put("URL", serverUrl)
        params.put("configuration", config);
        params.put("description", description);
        url = new URL(serverUrl + "/interop/rest/" + lcmVersion + "/
feedback");
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params.toString(), "application/
json");
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0) {
        println "Feedback successful"
```

```
} else {
    println "Error occurred while listing files"
    if (object.details != null)
        println "Error details: " + object.details
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Provide Feedback (v2)

}

The Provide Feedback (v2) feedback service sends feedback or reports an issue to Oracle.

This API is version v2.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

POST /interop/rest/v2/services/feedback

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: multipart/form-data

Name	Description	Туре	Require d	Default
fileName	The name of the zip file that you want Oracle support to use to resolve the current issue.	Multipa rt	Yes	None
file	Multiple files like EPM Automate scripts or Fiddler traces required to be submitted to Oracle can be zipped altogether and uploaded.	Multipa rt	Yes	None
configuration	Details of the client, OS, URL, and description of the issue.	Multipa rt	Yes	None



Example URL and Payload

```
https://<BASE URL>/interop/rest/v2/services/feedback
```

```
configuration:{"Configuration":{"Operating_System": "Windows
10","EPMAutomate_Version":"22.11.12","Java_Vendor":"Oracle Corporation",
"Java_Version":"1.8.0_341","URL":"http://
slcar287.usdv1.oraclecloud.com:12847"},"description":"Issue description"}
```

Response

Supported Media Types: application/json

Name	Description	
details	Published in case of errors with the error string	
status	See Migration Status Codes	
items	Details about the resource	
issueRef	Feedback reference to contact Oracle support	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Possible value: self	
data	Parameters as key value pairs passed in the request	

Table 9-100 Parameters

Example of Response Body

```
"details": null,
    "status": 0,
    "items": [
        {
            "issueRef":
"UDR default epm default cloud admin 2022 10 11 01 47 10"
        }
    ],
    "links": [
        {
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcx>.oraclecloud.com/interop/rest/v2/services/
feedback",
            "action": "POST",
            "rel": "self",
            "data": null
        }
    ]
}
```



Sample cURL Command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: multipart/form-data' -F 'fileName=abc.zip' -
F'configuration={"configuration":{"Operating_System": "Windows 10",
"EPMAutomate_Version":"22.11.12","Java_Vendor":"Oracle
Corporation","Java_Version":"1.8.0_341","URL":"https://<BASE
URL>","description":"abc"}}' -F 'file=@/
C:/Users/abc/Sample.zip' 'https://<BASE URL>/interop/rest/v2/services/
feedback'
```

Send Email (v1)

Use the Send Mail (v1) REST API to send an email to specified recipients, optionally attaching files from EPM Cloud. You can attach any file up to 10 MB in size, other than a snapshot, that is available in EPM Cloud environments. This API can be incorporated into REST API programs and scripts to notify users of various conditions or to send reports.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the process is complete. The presence of status -1 in the response indicates that the process is in progress. Any non-zero status except -1 indicates failure.

This REST API is version v1.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/<api version>/services/sendmail

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-101 Tasks

Task	Request	REST Resource
Trigger sendmail	POST	/interop/rest/ <api_version>/services/sendmail</api_version>
Retrieve sendmail status	GET	/interop/rest/ <api_version>/services/jobs/777</api_version>



Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 9-102 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
to	The recipient email addresses separated by semi-colons	Form	Yes	None
subject	The subject for the email	Form	Yes	None
body	The body of the email providing details.	Form	Yes	None
attachments	One or more file names separated by commas to be added as attachments to the email, for example, outbox/ Errorfile.txt or inbox/Errorfile2.txt You can attach any file up to 10 MB in size, other than a snapshot, that is available in EPM Cloud environments.	Form	No	None

Sample Request Payload

```
to:abc@oracle.com
subject:EPM
body:EPM weekly email
attachments:apr/2021-08-10 11_30_25/2021-08-10 11_30_25.html
```

Response

Table 9-103	Parameters
-------------	------------

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Example of Response Body

```
{
    "status": -1,
    "items": null,
    "links": [{
        "rel": "self",
        "href": "https://<BASE URL>/interop/rest/v1/services/sendmail",
```



```
"data": null,
    "action": "POST"
}, {
    "rel": "Job Status",
    "href": "https://<BASE URL>/interop/rest/v1/services/jobs/
1502357937045",
    "data": null,
    "action": "GET"
    }],
    "details": null
}
```

JobID is appended only to the API used to fetch the status of the progress.

Sample code:

```
public void sendMail() throws Exception {
    String to = "RECIPIENT EMAIL ADDRESS";
    String subject = "SUBJECT OF THE MAIL";
    String body = "BODY OF THE MAIL";
    String attachments = "NAME OF THE FILE TO BE ATTACHED";
    String urlString = String.format("%s/interop/rest/v1/services/sendmail",
    serverUrl);
    String params = "to=" + to + "&subject=" + subject + "&body=" + body +
    "&attachments=" +attachments;
    String response = executeRequest(urlString, "POST", params,
    "application/x-www-form-urlencoded");
    getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Send Email (v2)

Use the Send Mail (v2) REST API to send an email to specified recipients, optionally attaching files from EPM Cloud. You can attach any file up to 10 MB in size, other than a snapshot, that is available in EPM Cloud environments. This API can be incorporated into REST API programs and scripts to notify users of various conditions or to send reports.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. This API is backwards compatible.

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the process is complete. The presence of status -1 in the response indicates that the process is in progress. Any non-zero status except -1 indicates failure.

This REST API is version v2.

Required Roles

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/mails/send

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 9-104 Tasks

Task	Request	REST Resource
Trigger sendmail	POST	/interop/rest/v2/mails/send
Retrieve sendmail status	GET	/interop/rest/v2/status/jobs/777

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-105 Parameters

Name	Description	Туре	Required	Default
to	The recipient email addresses separated by semi-colons	Payload	Yes	None
subject	The subject for the email	Payload	Yes	None
body	The body of the email providing details.	Payload	Yes	None
parameters	Parameters for this REST API	Payload	No	None
attachments	One or more file names separated by commas to be added as attachments to the email, for example, outbox/ Errorfile.txt or inbox/Errorfile2.txt You can attach any file up to 10 MB in size, other than a snapshot, that is available in EPM Cloud environments.	Payload	No	None

Sample URL and Payload

https://<BASE URL>/interop/rest/v2/mails/send

```
{
    "to": "<EMAIL_ADDRESS>",
    "subject": "EPM",
    "body": "EPM weekly email",
```



```
"parameters": {
    "attachments":"apr/Feedback 2022-03-01 07_42_04/access_log.zip"
}
```

Response

}

Table 9-106	Parameters
-------------	------------

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Example of Response Body

```
{
    "status": -1,
    "items": null,
    "links": [{
        "rel": "self",
        "href": "https://<BASE URL>/interop/rest/v2/mails/send",
        "data": null,
        "action": "POST"
    }, {
        "rel": "Job Status",
        "href": "https://<BASE URL>/interop/rest/v2/status/jobs/
1502357937045",
        "data": null,
        "action": "GET"
    }1,
    "details": null
}
```

Sample cURL Command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"subject":"SUBJECT_OF_THE_MAIL",
"to":"RECIPIENT_EMAIL_ADDRESS","body":"BODY_OF_THE_MAIL","parameters":
{"attachments":"NAME_OF_THE_FILE_TO_BE_ATTACHED"}}' 'https://<BASE_URL>/
interop/rest/v2/mails/send'
```

Common Functions

See Common Helper Functions for Java

- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Skip Updates (v1)

Use the Skip Updates (v1) API to add, list, or remove a skip update request. Using this API, you can ask Oracle to skip applying a monthly update to an environment, or remove all previous skip update requests so that the environment is updated to the main code line. This allows you to skip updates to an EPM Cloud production environment at times when you need to complete time-sensitive tasks, for example, closing a quarter, without creating a service request.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

You can also list the skip update requests currently specified for an environment. You can set skip update requests for a maximum of two update cycles. You cannot skip updates for an environment that is on a one-off patch. Additionally, you cannot skip monthly updates that are more than two months apart from the update that the environment is currently on. For example, if the environment is currently on 20.12, you can skip 21.01 and 21.02 updates, but not 21.03. This gives you better control over monthly and weekly updates.

This REST API is version v1.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v1/services/skipupdate

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-107 Parameters

Name	Description	Туре	Required	Default
type	The desired action to be performed (Add, List, or Remove)	Form	Yes	None



Table 9-107 (Cont.) Parameters

Name	Description	Туре	Required	Default
version	The version to be skipped from update, for example, 20.12	Form	No (Yes, only when the type is Add)	None
comment	The business reason for skipping an update, such as Year End	Form	No (Yes, only when the type is Add)	None

Response

Supported Media Types: application/json

Table 9-108 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "links":[{
   "https://<BASE URL>/interop/rest/v1/services/skipupdate",
        "rel":"self",
        "data":null,
        "action":"POST"
    }
  ],
   "details":null,
   "status":0
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



Skip Updates (v2)

Use the Skip Updates (v2) REST API to add, list, or remove a skip update request. Using this API, you can ask Oracle to skip applying a monthly update to an environment, or remove all previous skip update requests so that the environment is updated to the main code line. This allows you to skip updates to an EPM Cloud production environment at times when you need to complete time-sensitive tasks, for example, closing a quarter, without creating a service request.

You can also list the skip update requests currently specified for an environment. You can set skip update requests for a maximum of two update cycles. You cannot skip updates for an environment that is on a one-off patch. Additionally, you cannot skip monthly updates that are more than two months apart from the update that the environment is currently on. For example, if the environment is currently on 22.10, you can skip 22.11 and 22.12 updates, but not 23.01. This gives you better control over monthly and weekly updates.

This REST API is version v2.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/services/skipupdate

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 9-109 Parameters

Name	Description	Туре	Required	Default
type	The desired action to be performed (Add, List, or Remove)	Payload	Yes	None
version	The version to be skipped from update, for example, 22.12	Payload	No (Yes, only when the type is Add)	None
comment	The business reason for skipping an update, such as Year End	Payload	No (Yes, only when the type is Add)	None



Example URL and Payload

```
https://<BASE URL>/interop/rest/v2/services/skipupdate
{
    "type":"Add",
    "parameters": {
        "version": "22.12",
        "comment": "Year end"
    }
}
```

Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	null

Table 9-110 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "status": 0,
   "items": null,
   "links": [{
        "rel": "self",
        "href": "https://<BASE URL>/interop/rest/v2/services/skipupdate",
        "data": null,
        "action": "POST"
   }
   "details": null
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"type":"Add","parameters":
{"version":"22.10","comment":"Year End"}}' 'https://<BASE URL>/interop/
rest/v2/services/skipupdate'
```



Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

List or Restore Backups - Only for OCI (Gen2) Environments

In OCI (Gen 2) environments, you can use a REST APIs to list available backup snapshots archived by Oracle in the Oracle Object Storage Cloud, or to restore an available backup snapshot archived by Oracle in the Oracle Object Storage Cloud (that is, copy it to the environment).

Table 9-111 List or Restore Backups

Task	Request	REST Resource
List Backups - Only for OCI (Gen 2) Environments	GET	/interop/rest/v2/backups/list
Restore Backup - Only for OCI (Gen 2) Environments	POST	/interop/rest/v2/backups/restore

List Backups - Only for OCI (Gen 2) Environments

In OCI (Gen 2) environments, you can list available backup snapshots archived by Oracle in the Oracle Object storage Cloud.

You can then restore available backup snapshots (copy them to the environment), To restore backup snapshots in OCI (Gen 2) environments, see Restore Backup. After copying the backup, you can archive it or use it to restore the current environment by yourself. With the List Backups and Restore Backup APIs, you no longer have to create a service request to request a backup from an OCI environment.

This API is version v2.

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

GET /interop/rest/v2/backups/list

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Response

Supported Media Types: application/json

Attribute	Description
details	Published in case of errors with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
intermittentSta	Stats of each step perormed; can be polled regularly from the job status URL
tus	

Table 9-112 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "details": null,
   "links": [{
        "href": "https://<BASE URL>/interop/rest/v2/backups/list",
        "rel": "self",
        "data": null,
        "action": "GET"
   }],
   "status": 0,
   "items": ["2022-02-16T05:49:15/Artifact_Snapshot.zip",
   "2022-02-18T05:44:54/Artifact_Snapshot.zip"]
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Restore Backup - Only for OCI (Gen 2) Environments

In OCI (Gen 2) environments, you can restore an available backup snapshot archived by Oracle in Oracle Object Storage (that is, copy it to the environment).

To view available backup snapshots, see List Backups. If a backup snapshot is available, you can copy it to the current environment using the Restore Backup API.

After copying the backup, you can archive it or use it to restore the current environment by yourself. With the List Backups and Restore Backup APIs, you no longer have to create a service request to request a backup from an OCI environment.

This REST API is version v2.



Required Roles

Required Roles

Service Administrator

Power User assigned to the Migration Administrator Profitability and Cost Management application role

REST Resource

POST /interop/rest/v2/backups/restore

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.

Table 9-113 Parameters

Name	Description	Туре	Required	Default
backupName	The name of the backup snapshot, as listed in the response for List Backups	Payload	Yes	None



Name	Description	Туре	Required	Default
targetName	The name of the backup snapshot, without an extension, in the target environment	Payload	No	If you do not specify this parameter, the backup snapshot is restored to the target environme nt pre- pended with the current timestamp, for example, 2022-03- 10T06:37 :48_Arti fact_Sna pshot.zi p or 2022-03- 30T06:22 :35_EPRC S_Backup .tar.gz.
				. car . 92.

Table 9-113 (Cont.) Parameters

Example of Request Body

```
{
    "backupName": "2022-02-16T21:00:02/Artifact_Snapshot_2021-12-16T21:00:02",
    "parameters": {
        "targetName": "Backup_16Dec"
    }
}
```

Response

Supported Media Types: application/json

Table 9-114Parameters

		المعمد
Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	



Table 9-114	(Cont.) Parameters	

Name	Description
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status of the copy snapshot
	Status of each step performed; can be polled regularly from the job status URL
tus	

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "http://<BASE URL>/interop/rest/v2/backups/restore",
            "data": null,
            "action": "POST"
        },
        {
            "rel": "Job Status",
            "href": "http://<BASE URL>/interop/rest/v2/status/jobs/
4534730166024804",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



10 Security REST APIs

This section describes the REST APIs to manage security features in Oracle Enterprise Performance Management Cloud.

Task	Request	REST Resource
Get Restricted Data Access	GET	/interop/rest/{api_version}/config/ services/restricteddataaccess
Set Restricted Data Access	PUT	/interop/rest/{api_version}/config/ services/restricteddataaccess
Get Virus Scan on File Upload	GET	/interop/rest/{api_version}/config/ services/virusscanonfileupload
Set Virus Scan on File Upload	PUT	/interop/rest/{api_version}/config/ services/virusscanonfileupload
Manage Permission for Manual Access to Database (v1)	PUT	<pre>/interop/rest/{api_version}/ services/dataaccess? accessType={allow revoke}&disableEmergencyAccess={tru e false}</pre>
Manage Permission for Manual Access to Database (v2)	PUT	/interop/rest/v2/services/ setmanualdataaccess
Set Encryption Key (v1)	PUT	/interop/rest/{api_version}/ services/encryptionkey
Set Encryption Key (v2)	PUT	interop/rest/v2/services/ setencryptionkey
View the IP Allowlist - Only for OCI (Gen 2) Environments	GET	/interop/rest/epmociservice/v2/ ipallowlist
Update the IP Allowlist - Only for OCI (Gen 2) Environments	POST	/interop/rest/epmociservice/v2/ ipallowlist

Table 10-1 Security

Get Restricted Data Access

The Get Restricted Data Access REST API returns *true* if the environment is configured so that "Submit Application Snapshot" cannot be selected by a Service Administrator while submitting Provide Feedback; otherwise, returns *false*.

This REST API is version v2.

Required Roles

Service Administrator



REST Resource

GET /interop/rest/{api_version}/config/services/restricteddataaccess

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the GET request parameters:

Table 10-2 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None

Response

Supported Media Types: application/json

Table 10-3 Parameters

Name	Description
details	Detailed status of the operation performed.
status	See Migration Status Codes
links	Detailed information about the link and HTTP call type
items	Detailed information about the API
dataAccessRestr iction	Whether the restricted data access is enabled
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Example of Response Body



```
],
   "links": [
        {
            "href": "<uri>/interop/rest/v2/config/services/
restricteddataaccess",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -H
'Content-Type: application/json' 'https://<BASE-URL>/interop/rest/v2/config/
services/restricteddataaccess'
```

Set Restricted Data Access

The Set Restricted Data Access REST API enables/disables the selection of "Submit Application Snapshot" by the Service Administrator while submitting Provide Feedback.

This REST API is version v2.

Required Roles

Service Administrator

REST Resource

PUT /interop/rest/{api_version}/config/services/restricteddataaccess

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the PUT request parameters:

Table 10-4 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
dataAccessRestrict ion	Enable/Disable restricted data access; possible values are <i>true</i> and <i>false</i>	Payload	Yes	None



Example of Request Body

```
{
    "dataAccessRestriction": "true"
}
```

Response

Supported Media Types: application/json

Name	Description
details	Detailed status of the operation performed.
status	See Migration Status Codes
links	Detailed information about the link and HTTP call type
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
error	Detailed information about the error
data	Parameters as key value pairs passed in the request

Example of Response Body

```
{
   "details": null,
   "status": 0,
   "items": null,
   "links": [
        {
            "href": "<uri>/interop/rest/v2/config/services/
restricteddataaccess",
            "action": "PUT",
            "rel": "self",
            "data": null
        }
   ]
}
```

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H
'Content-Type: application/json' -d '{"dataAccessRestriction":"true"}'
'https://<BASE-URL>/interop/rest/v2/config/services/restricteddataaccess'
```



Get Virus Scan on File Upload

The Get Virus Scan on File Upload REST API returns *true* if virus scan on file upload is enabled; otherise, it returns *false*.

This API is version v2.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/{api_version}/config/services/virusscanonfileupload

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Table 10-6Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None

Response

Supported Media Types: application/json

Table 10-7 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
items	Detailed information about the API
scanfiles	Indicates whether the virus scan is enabled
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request



Example of Response Body

```
{
    "details": null,
    "links": [{
        "rel": "self",
        "href": "<uri>/interop/rest/v2/config/services/
virusscanonfileupload",
        "data": "null",
        "action": "GET"
    }],
    "status": "0",
    "items": [{
        "scanfiles": "true"
    }]
}
```

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -H
'Content-Type: application/json' 'https://<BASE-URL>/interop/rest/v2/config/
services/virusscanonfileupload'
```

Set Virus Scan on File Upload

The Set Virus Scan on File Upload REST API enables/disables the virus scan on a file upload.

This API is version v2.

Required Roles

Service Administrator

REST Resource

PUT /interop/rest/{api_version}/config/services/virusscanonfileupload

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

Table 10-8 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None



Table 10-8 (Cont.) Parameters

Name	Description	Туре	Required	Default
scanfiles	Enable/Disable virus scan	Payload	Yes	None

Response

Supported Media Types: application/json

Table 10-9 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Example of Response Body

```
{
    "links": [{
        "rel": "self",
        "href": "<uri>/interop/rest/v2/config/services/
virusscanonfileupload",
        "data": null,
        "action": "PUT"
    }],
    "details": "null",
    "status": 0,
    "items": null
}
```

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"virusscan":"true"}' 'https://<BASE-URL>/interop/rest/v2/config/services/
virusscanonfileupload'
```

Manage Permission for Manual Access to Database (v1)

Use this API (v1) to manage permission for manual access to database by Oracle.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not



require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

This gives you the ability to allow or disallow Oracle personnel to manually access your database in emergency situations when an environment is unresponsive and you have not yet created a service request to investigate the issue.

In an emergency situation, Oracle follows an internal process whereby a high-level development executive, after an independent verification process, permits manual access to the database without your explicit approval. You can also prohibit Oracle from manually accessing the EPM Cloud database, even if a service request to remedy a database issue is open.

This API is version v1.

Required Roles

Service Administrator

REST Resource

```
PUT /interop/rest/{api_version}/services/dataaccess?accessType={allow|
revoke}&disableEmergencyAccess={true|false}
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 10-10 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
accessType	Allow or revoke the manual access to database by Oracle, where the value can be allow or revoke	Query	Yes	None
disableEmergencyAc cess	Whether to prohibit all manual access to the database. The possible values are true and false. Setting this parameter value to true stops Oracle from manually accessing the database even if a service request is open. Oracle does not recommend setting this parameter value to true because Oracle cannot access the database if access is required to troubleshoot and fix a down environment. If the environment is down, you will not be able to issue this REST API to allow Oracle to manually access the database.	Query	No	False

Response

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Table 10-11 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
Copy
{
    "links": [1]
    0: {
        "rel":"self", "href":"https://<BASE-URL>/interop/rest/v1/services/
    dataaccess?accessType=allow&disableEmergencyAccess=true"
        "data":"null",
        "action":"PUT,
        }-
        -
        "details":"null",
        "status":"0"
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Manage Permission for Manual Access to Database (v2)

Use this REST API (v2) to manage permission for manual access to database by Oracle.

This gives you the ability to allow or disallow Oracle personnel to manually access your database in emergency situations when an environment is unresponsive and you have not yet created a service request to investigate the issue.

In an emergency situation, Oracle follows an internal process whereby a high-level development executive, after an independent verification process, permits manual access to the database without your explicit approval. You can also prohibit Oracle from manually accessing the EPM Cloud database, even if a service request to remedy a database issue is open.



This API is version v2

Required Roles

Service Administrator

REST Resource

PUT /interop/rest/v2/services/setmanualdataaccess

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 10-12 Parameters

Name	Description	Туре	Required	Default
accessType	Allow or revoke the manual access to database by Oracle, where the value can be allow or revoke	Payload	Yes	None
parameters				
disableEmergencyAc cess	Whether to prohibit all manual access to the database. The possible values are true and false. Setting this parameter value to true stops Oracle from manually accessing the database even if a service request is open. Oracle does not recommend setting this parameter value to true because Oracle cannot access the database if access is required to troubleshoot and fix a down environment. If the environment is down, you will not be able to issue this REST API to allow Oracle to manually access the database.	Payload	No	False

Example URL and Payload

https://<BASE URL>/interop/rest/v2/services/setmanualdataaccess

```
{
    "accessType": "Revoke",
    "parameters": {
        "disableEmergencyAccess": "False"
    }
}
```

Response

Supported Media Types: application/json



Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	null

Table 10-13 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "details": null,
   "status": 0,
   "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/services/
setmanualdataaccess",
            "action": "PUT",
            "rel": "self",
            "data": null
        }
   ]
}
```

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"accessType":"Revoke","parameters":
{"disableEmergencyAccess":"True"}}' 'https://<BASE-URL>/interop/rest/v2/
services/setmanualdataaccess'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Set Encryption Key (v1)

Provides a Bring Your Own Key (BYOK) solution to include Oracle EPM Cloud in your standard key management rotation.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not



require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

The API can be used to set and remove a user-defined encryption key for access to database used in an Oracle EPM Cloud instance.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

This API is version v1.

Required Roles

Service Administrator

Table 10-14 Set Encryption Key Tasks

Task	Request	REST Resource
Execute a Job	PUT	/interop/rest/{api_version}/services/ encryptionkey
Retrieve Job Status	GET	/interop/rest/v1/services/jobs/{jobID}

REST Resource

PUT /interop/rest/{api_version}/services/encryptionkey

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 10-15 Parameters

Name	Description	Туре	Required	Default
Кеу	The user-defined encryption key. If empty or no key is passed, encryption is reset.	Form	No	None

Response

Supported Media Types: application/json



Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Table 10-16 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
  "details":null,
  "status":-1,
  "links":[{
     "href":"https://<BASE-URL>/interop/rest/v1/services/encryptionkey",
     "rel":"self",
     "data":null,
     "action":"PUT"
     },{
     "href":"https://<BASE-URL>/interop/rest/v1/services/jobs/777",
     "rel":"Job Status",
     "data":null,
     "action":"GET"
   }]
}
```

cURL Sample - setencryptionkey.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcSetEncryptionKey() {
    url=$SERVER_URL/interop/rest/v1/services/encryptionkey
    key="xcfddrerghgArfh" #use a strong key to set the encryption
key
    param="key=$key"
    funcExecuteRequest "PUT" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == -1 ]; then
    echo "Setting Encryption Key"
    funcGetStatus "GET"
    else
    error=`echo $output | jq '.details'`
```

```
echo "Error occurred. " $error
        fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcResetEncryptionKey() {
        url=$SERVER URL/interop/rest/v1/services/encryptionkey
        param=""
        funcExecuteRequest "PUT" $url $param "application/json"
        output=`cat response.txt`
        status=`echo $output | jq '.status'`
        if [ \$ status == -1 ]; then
        echo "Resetting Encryption Key"
        funcGetStatus "GET"
        else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
        fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

```
}
```

Set Encryption Key (v2)

The Set Encryption Key (v2) REST API provides a Bring Your Own Key (BYOK) solution to include Oracle EPM Cloud in your standard key management rotation.

The API can be used to set and remove a user-defined encryption key for access to database used in an Oracle EPM Cloud instance.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

This API is version v2.

Required Roles

Service Administrator

REST Resource

PUT interop/rest/v2/services/setencryptionkey

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Table 10-17 Set Encryption Key Tasks

Task	Request	REST Resource
Execute a Job	PUT	/interop/rest/v2/services/setencryptionkey
Retrieve Job Status	GET	/interop/rest/v2/status/jobs/777

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 10-18 Parameters

Name	Description	Туре	Required	Default
parameters				
key	The user-defined encryption key. If empty or no key is passed, encryption is reset.	Payload	No	None

Example URL and Payload

https://<BASE URL>/interop/rest/v2/services/setencryptionkey

{"parameters": {"key": "se!m+a2J"}}

Response

Supported Media Types: application/json

Table 10-19 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	null

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "status": -1,
    "items": null,
    "links": [{
```



```
"rel": "self",
    "href": "https://<BASE-URL>/interop/rest/v2/services/
setencryptionkey",
    "data": null,
    "action": "PUT"
    }, {
        "rel": "Job Status",
        "href": "https://<BASE-URL>/interop/rest/v2/status/jobs/
8921378039543483",
        "data": null,
        "action": "GET"
    }],
    "details": null
}
```

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"parameters":{"key":"abc"}}' 'https://
<BASE-URL>/interop/rest/v2/services/setencryptionkey'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

View or Update the IP Allowlist - Only for OCI (Gen 2) Environments

In OCI (Gen 2) environments, you can use a REST API to update or list the IP allowlist.

- Use the POST method with the action parameter set to add to add the IP addresses and Classless Inter-Domain Routings (CIDRs) to the allowlist of your environment.
- Use the POST method with the action parameter set to remove to remove the IP addresses and CIDRs from the allowlist of your environment.
- Use the GET method to list IP addresses and CIDRs in the allowlist of your environment.

Table 10-20 IP Allowlist

Task	Request	REST Resource	
View the IP allowlist	GET	/interop/rest/epmociservice/v2/ipallowlist	
Update the IP allowlist	POST	/interop/rest/epmociservice/v2/ipallowlist	



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

View the IP Allowlist - Only for OCI (Gen 2) Environments

In OCI (Gen 2) environments, you can use a REST API to list the IP allowlist.

Use the GET method to list IP addresses and CIDRs in the allowlist of your environment.

This REST API is version v2.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/epmociservice/v2/ipallowlist

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Response

Supported Media Types: application/json

Table 10-21 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status.
items	List of IP addresses and CIDRs that are set as the allowlist for your environment.

Example of Response Body

The following shows an example of the response body in JSON format.

"links": [

{



```
{
            "rel": "self",
            "href": "https://<BASE-URL>/interop/rest/epmociservice/v2/
ipallowlist",
             "data": null,
             "action": "GET"
        }
    ],
    "details": null,
    "status": 0,
    "items": [
        "ip address1/24",
        "ip address2",
        "ip address3",
        "ip address4",
        "ip address5"
    ]
}
```

Update the IP Allowlist - Only for OCI (Gen 2) Environments

In OCI (Gen 2) environments, you can use a REST API to update the IP allowlist.

Use the POST method with the action parameter set to add to add the IP addresses and Classless Inter-Domain Routings (CIDRs) to the allowlist of your environment.

Use the POST method with the action parameter set to remove to remove the IP addresses and CIDRs from the allowlist of your environment.

This REST API is version v2.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/epmociservice/v2/ipallowlist

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.



Name	Description	Туре	Required	Default
fileName	The path to a filename with a list of IP addresses and CIDRs that you want to add to or remove from the allowlist.	Payload	Yes	None
	If you want the file to be uploaded to the default location, the path is not required and you only need to specify the file name.			
	Example : IPList.txt			
	Each line in the file must be an IP address or CIDR in the following format:			
	xxx.xxx.xxx			
	xxx.xxx.xxx/n			
	Note:			
	 Only IP V4 IP addresses are supported. Use CIDR format, rather than individual IP addresses, to specify a continuous range of IP addresses. 			
action	Use add to add IP addresses and CIDRs to the allowlist of your environment.	Payload	Yes	None
	Use remove to remove IP addresses and CIDRs from the allowlist.			

Table 10-22 Parameters

Examples of Request Body

Example 1: Add to the IP Allow List

```
{
    "fileName" : "IPList.txt",
    "action" : "add"
}
```

Example 2: Remove from the IP Allow ILst

```
{
   "fileName" : "IPList.txt",
   "action" : "remove"
}
```

Response

Supported Media Types: application/json

Table 10-23 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link



Name	Description
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status of the copy snapshot

Table 10-23 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "http://<BASE-URL>interop/rest/epmociservice/v2/
ipallowlist",
            "data": null,
            "action": "POST"
        },
        {
            "rel": "Job Status",
            "href": "http://<BASE-URL>/interop/rest/epmociservice/v2/status/
jobs/2126145698194859",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



11

Viewing and Setting the Daily Maintenance Window Time

Use these REST APIs to get the current build version and daily maintenance window time, and to set the daily maintenance window time. You can also run the daily maintenance while skipping the scheduled daily maintenance.

Task	Request	REST Resource
Get the Build Version and Daily Maintenance Time (v1)	GET	/interop/rest/{api_version}/services/dailymaintenance
Get the Build	GET	/interop/rest/v2/maintenance/
Version and Daily Maintenance Window Time (v2)		getdailymaintenancestarttime
Setting the Daily Maintenance Time (v1)	PUT	<pre>/interop/rest/{api_version}/services/dailymaintenance? StartTime={N}</pre>
Setting the Daily Maintenance Time (v2)	PUT	/interop/rest/v2/maintenance/ setdailymaintenancestarttime
Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v1)	POST	/interop/rest/{api_version}/services/maintenancewindow
Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v2)	POST	/interop/rest/v2/maintenance/rundailymaintenance

Table 11-1 Getting and Setting the Daily Maintenance Time

Get the Build Version and Daily Maintenance Time (v1)

This API (v1) returns information about the current build version and the scheduled daily maintenance window time.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

This API is version v1.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See About the REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Required Roles

Service Administrator

REST Resource

GET /interop/rest/{api version}/services/dailymaintenance

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

The following table summarizes the request parameters.

Table 11-2 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None

Response

Supported Media Types: application/json

Table 11-3 Parameters

Parameters	De scr ipti on
details	In
	cas
	eo
	err
	ors
	det
	ails
	are
	pul
	list
	ed
	wit
	h
	the
	err
	or
	str
	ng



status Se e Mig rati on Sta tus Co des ltems Det aile d info rm atio n abo ut the API	Parameters	De scr
status Se e Mig rati on Sta tus Co des items Det aile d info rm atio n abo ut the		
items e Mig rati on Sta tus Co des Det aile d info rm atio n abo ut the		
items Mig rati on Sta tus Co des Det aile d info rm atio n abo ut the	status	Se
items ration Status Co des Det aile d info rm ation n abo ut the		е
items on Sta tus Co des des aile d info rm atio n abo ut the		Mig
items Sta tus Co des items Det aile d info rm atio n abo ut the		
items Litems Lit		
items Co des items Det aile d info rm atio n abo ut the		
items des items des aile d info rm atio n abo ut the		tus
items Det aile d info rm atio n abo ut the		
aile d info rm atio n abo ut the		
d info rm atio n abo ut the	items	
info rm atio n abo ut the		
rm atio n abo ut the		
atio n abo ut the		
n abo ut the		
abo ut the		atio
ut the		
the		

Table 11-3 (Cont.) Parameters



Parameters	D
	S
	ip o
amwTime	S
	h
	ul d
	st
	t
	tir
	e
	th di
	y
	rr
	ni
	n
	Ci W
	d
	W
	ir
	2. h
	ſ
	fc
	m
	in E
	E /ل
	C
	tii
	e
	n bj
	d
	a
	0
	ir tr
	S
	C
	e
	tii
	eze
	e
	W
	e
	th "s
	S O'
	T
	ež
	01
	" 0
	U,

Table 11-3 (Cont.) Parameters



Parameters	De sc ip or
	or
	I.
	pa
	an
	et ri:
	e.
buildVersion	Ci
bullaversion	re
	t
	bu
	d
	Ve
	si
	n
links	D
	ai
	d
	in
	rn
	at
	n
	at
	ut th
	lir
href	Li
nrei	Li ks
	to
	A
	Ca
action	т
	e
	Ĥ
	TI
	Ca
	ty
	е
rel	Po
	SS
	bl
	Va
	ue
	se

Table 11-3 (Cont.) Parameters



Parameters	De sc
	ipt on
data	Pa
	an
	ete
	rs
	as
	ke
	va
	UE
	pa
	S
	pa
	Se
	in
	th
	re
	ue
	t

Table 11-3 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"details":null,
"links":[
{
    "rel":"self","href":"https://<BASE-URL>/interop/rest/v1/services/
dailymaintenance",
"data":"null",
"action":"GET"}],
"status":"0",
"items":[
{
    "amwTime":"19",
    "buildVersion":"16.10.17"}
]
```

Get Build Version and Daily Maintenance Time Sample Code

Example 11-1 Java Sample – GetMaintenanceDetails.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
//
// BEGIN
//
public void getMaintenanceDetails () throws Exception {
   String urlString = String.format("%s/interop/rest/vl/services/
```



```
dailymaintenance", serverUrl);
    String response = executeRequest(urlString, "GET", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        JSONArray fileList = json.getJSONArray("items");
        System.out.println("List of items are :");
        JSONObject jObj = null;
        for(int i=0; i<fileList.length(); i++) {</pre>
            jObj = (JSONObject)fileList.get(i);
            System.out.println("build version :" +
jObj.getString("buildVersion"));
            System.out.println("AMW time :" + jObj.getString("amwTime"));
            System.out.println("Link :" + ((JSONObject))
((JSONArray)json.getJSONArray("links")).get(0)).getString("href") + "\n");
        }
    }
}
//
// END
11
```

Example 11-2 cURL Sample – GetMaintenanceDetails.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

```
Common Functions: See Common Helper Functions for cURL
```

```
funcGetMaintenanceDetails () {
   url=$SERVER URL/interop/rest/v1/services/dailymaintenance
    funcExecuteRequest "GET" $url
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "List of items :"
        count=`echo $output | jq '.items | length'`
        i=0
        while [ $i -lt $count ]; do
            echo "Build Version : " `echo $output | jq
'.items['$i'].buildVersion'`
            echo "AMW Time :" `echo $output | jq '.items['$i'].amwTime`
            echo "Link :" `echo $output | jq '.links[0].href'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Example 11-3 Groovy Sample – GetMaintenanceDetails.groovy

Prerequisites: json.jar

```
Common Functions: See CSS Common Helper Functions for Groovy
```

```
def getMaintenanceDetails () {
    def url;
    try {
            url = new URL(serverUrl + "/interop/rest/v1/services/
dailymaintenance ")
    } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
    response = executeRequest(url, "GET", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
   if (status == 0 ) {
       def items = object.items
        println "List of items :"
        items.each{
            println "Build Version : " + it.buildVersion
            println "AMW Time : " + it.amwTime
            println "Link : " + it.links[0].href + "\n"
        }
    } else {
        println "Error occurred while listing versions"
        if (object.details != null)
                println "Error details: " + object.details
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Get the Build Version and Daily Maintenance Window Time (v2)

This REST API (v2) returns information about the current build version and the scheduled daily maintenance window start time.

This API is version v2

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See About the REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Required Roles

Service Administrator

REST Resource

GET /interop/rest/v2/maintenance/getdailymaintenancestarttime



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

The following table summarizes the request parameters.

Table 11-4 Parameters

Name	Description	Туре	Require d	Default
showTimeZone	Displays the time in the time zone specified while setting it	Query	No	false

Example URL

https://<BASE URL>/interop/rest/v2/maintenance/getdailymaintenancestarttime? showTimeZone=true

Response

Supported Media Types: application/json

Table 11-5 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
items	Detailed information about the API
amwTime	Scheduled start time of the daily maintenance window in 24-hour format in Etc/UTC timezone by default or in the specified time zone when the "showTimeZone" optional parameter is true.
buildVersion	Current build version
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	null

Example of Response Body

The following shows an example of the response body in JSON format.

```
"details": null,
"status": 0,
"items": [
```

{



```
{
            "buildVersion": "22.09.40",
            "amwTime": "19:00",
            "timeZone": "Etc/UTC"
        }
    ],
    "links": [
        {
            "href": "https://<BASE URL>/interop/rest/v2/maintenance/
getdailymaintenancestarttime",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```

Sample cURL command

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' 'https://<BASE URL>/interop/rest/v2/
maintenance/getdailymaintenancestarttime?showTimeZone=true'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Setting the Daily Maintenance Time (v1)

Use this REST API (v1) to set the daily maintenance window start time.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

Use this REST API to set the daily maintenance window time.

Note:

To ensure that the use of this API does not interfere with the Oracle requirement for creating backups, this API will not change the maintenance start time if the daily maintenance process did not run in the last 36 hours.

This API is version v1.

Required Roles

Service Administrator



REST Resource

PUT /interop/rest/{api version}/services/dailymaintenance?StartTime={N}

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See About the REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

The following table summarizes the request parameters.

Table 11-6 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
StartTime	Scheduled Time (in HH:00 format using a 24 hour clock) at which the maintenance process should start and an optional time zone. Acceptable start time value range is 00:00 - 23:00. If the start time is not to be set in UTC, specify a valid standard time zone; for example, "14:00 America/ Los_Angeles" for 2:00 pm Pacific Standard Time.	Query	Yes	None

Response

Supported Media Types: application/json

Table 11-7 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"links": [1]
0: {
"rel":"self",
"href":"https://<BASE-URL>/interop/rest/v1/services/dailymaintenance?
StartTime=23"
```



```
"data":"null",
"action":"PUT,
}-
-
"details":"null",
"status":"0"
}
```

Maintenance Window Time Sample Code

Example 11-4 Java Sample – SetMaintenanceDetails.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN
11
public void setMaintenanceDetails () throws Exception {
    String urlString = String.format("%s/interop/rest/v1/services/
dailymaintenance?StartTime=23", serverUrl);
    String response = executeRequest(urlString, "PUT", null);
    JSONObject json = new JSONObject(response);
    int resStatus = json.getInt("status");
    if (resStatus == 0) {
        System.out.println("Updated successfully");
    }
}
11
// END
11
```

Example 11-5 cURL Sample – SetMaintenanceDetails.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
uncSetMaintenanceDetails () {
    rl=$SERVER_URL/interop/rest/v1/services/dailymaintenance?StartTime=23
    funcExecuteRequest "PUT" $url
    output='cat response.txt'
    status='echo $output | jq '.status''
    if [ $status == 0 ]; then
        echo "Updated Successfully"
    else
        error='echo $output | jq '.details''
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```



Example 11-6 Groovy Sample – SetMaintenanceDetails.groovy

```
Prerequisites: json.jar
```

Common Functions: See CSS Common Helper Functions for Groovy

```
def setMaintenanceDetails () {
    def url;
    try {
            url = new URL(serverUrl + "/interop/rest/v1/services/
dailymaintenance?StartTime=23 ")
    } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
    }
    response = executeRequest(url, "PUT", null);
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == 0) {
        println "Updated Successfully"
    } else {
        println "Error occurred while listing versions"
        if (object.details != null)
                println "Error details: " + object.details
    }
}
```

Setting the Daily Maintenance Time (v2)

Use this REST API (v2) to set the daily maintenance window start time.

Note:

To ensure that the use of this API does not interfere with the Oracle requirement for creating backups, this API will not change the maintenance start time if the daily maintenance process did not run in the last 36 hours.

This API is version v2


Required Roes

Service Administrator

REST Resource

PUT /interop/rest/v2/maintenance/setdailymaintenancestarttime





Request

The following table summarizes the request parameters.

Table 11-8 Parameters

Name	Description	Туре	Required	Default
StartTime	Scheduled time (in HH:00 format using a 24 hour clock) at which the maintenance process should start and an optional time zone. Acceptable start time value range is 00:00 - 23:00 If the start time is not to be set in UTC, specify a valid standard time zone; for example, "14:00 America/ Los_Angeles" for 2:00 pm Pacific Standard Time.		Yes	None

Example URL and Payload

https://<BASE URL>/interop/rest/v2/maintenance/setdailymaintenancestarttime

{"startTime":"08:00"}

Response

Supported Media Types: application/json

Table 11-9 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	null

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "details": null,
    "status": 0,
    "items": null,
    "links": [
```



```
{
    "href": " https://<BASE-URL>/interop/rest/v2/maintenance/
setdailymaintenancestarttime",
    "action": "PUT",
    "rel": "self",
    "data": null
    }]
}
```

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"startTime":"08:00"}' 'https://<BASE-
URL>/interop/rest/v2/maintenance/setdailymaintenancestarttime'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v1)

Use this API (v1) if you want to run daily maintenance while skipping the scheduled daily maintenance.

This topic describes the original version of this REST API. You can also use the simplified v2 version of the REST API. The v2 version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use. The v2 version is backwards compatible.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See About the REST APIs. Using this REST API requires prerequisites. See Prerequisites.

This API is version v1.

Required Roles

Service Administrator

REST Resource

POST /interop/rest/{api version}/services/maintenancewindow

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Request

The following table summarizes the request parameters.

Table 11-10 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
skipNext	Specifies if the set maintenance time should be used, true or false	String	Yes	false

Response

Supported Media Types: application/json

Table 11-11 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Possible value: self
data	Parameters as key value pairs passed in the request

- Java Code using skipNext: DailyMaintenanceWithSkipNextv1.java Main method: runDailyMaintenanceWithSkipNext() Helper method waitForCompletion
- Curl Code using skipNext: Main method: funcSetMaintenancewithSkipNext
- Groovy Code using skipNext: DailyMaintenanceWithSkipNextv1.groovy Main method: runDailyMaintenanceWithSkipNext()

Maintenance Window Time Sample Code

Example 11-7 Java Sample – SetMaintenanceDetails.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
public class DailyMaintenanceWithSkipNextv1 {
    private String userName ; // PBCS user name
    private String password ; // PBCS user password
    private String serverUrl ; // PBCS server URL
    private String lcmVersion = "v1"; // Version of the PBCS API that you are
```

public void runDailyMaintenanceWithSkipNext(String comment) throws



```
Exception {
        Scanner in = null;
        try {
            String skipNext = "false";
            JSONObject params = new JSONObject();
            /*Parameter to Skip the next scheduled maintenance report to be
run .
            It is either true or false
            If true the scheduled daily maintenance is run
            If false the scheduled daily maintenance is skipped*/
            params.put("skipNext", skipNext);
            String urlString = String.format(
                    "%s/interop/rest/%s/services/maintenancewindow",
serverUrl,
                    lcmVersion);
            String response = executeRequest(urlString, "POST",
                    params.toString(), "application/json");
            waitForCompletion(fetchPingUrlFromResponse(response, "Job
Status"), "GET");
        } catch (Exception e) {
        } finally {
            in.close();
        }
    }
    private void waitForCompletion(String pingUrlString, String methodType)
            throws Exception {
        boolean completed = false;
        while (!completed) {
            try {
                String pingResponse = executeRequest(pingUrlString,
methodType,
                        null, "application/x-www-form-urlencoded");
                JSONObject json = new JSONObject(pingResponse);
                int status = json.getInt("status");
                if (status == -1) {
                    try {
                        System.out.println("Please wait...");
                        Thread.sleep(20000);
                    } catch (InterruptedException e) {
                        completed = true;
                        throw e;
                    }
                } else {
                    if (status > 0) {
                        System.out.println("Error occurred: "
                                + json.getString("details"));
                    } else {
```

```
System.out.println("Completed");
        }
        completed = true;
     }
     catch (Exception e) {
        System.out.println(e.getMessage());
        // services are down, waiting to come up
        Thread.sleep(60000);
     }
}
```

Example 11-8 cURL Sample – SetMaintenanceDetails.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
#!/bin/sh
SERVER URL=""
USERNAME=""
PASSWORD=""
API VERSION=""
DOMAIN=""
funcSetMaintenancewithSkipNext () {
        url=$SERVER URL/interop/rest/v1/services/maintenancewindow
        skipNext="false"
        param="{\"skipNext\":\"$skipNext\"}"
        funcExecuteRequest "POST" $url $param "application/json"
        output=`cat response.txt`
        status=`echo $output | jq '.status'`
        if [ \$status == -1 ]; then
          echo "Started Daily Maintainence succesfully"
                funcGetStatus "GET"
        else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
        fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
```

}

Example 11-9 Groovy Sample – SetMaintenanceDetails.groovy

Prerequisites: json.jar



```
Common Functions: See CSS Common Helper Functions for Groovy
```

```
class DailyMaintenanceWithSkipNextv1 {
    def userName // PBCS user name
    def password // PBCS user password
    def serverUrl // PBCS server URL
    def lcmVersion = "v1"; // Version of the PBCS API that you are
    void runDailyMaintenanceWithSkipNext() throws Exception {
        def skipNext = "false"; //true or false based on requirement
        JSONObject params = new JSONObject();
        params.put("skipNext", skipNext);
        String urlString = String.format("%s/interop/rest/%s/services/
maintenancewindow", serverUrl, lcmVersion);
        String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
        waitForCompletion(fetchPingUrlFromResponse(response, "Job Status"));
    }
}
```

Running Daily Maintenance While Skipping the Scheduled Daily Maintenance (v2)

Use this REST API (v2) if you want to run daily maintenance with an option to skip the next scheduled daily maintenance.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See About the REST APIs. Using this REST API requires prerequisites. See Prerequisites.

This API is version v2

Required Roles

Service Administrator

REST Resource

POST /interop/rest/v2/maintenance/rundailymaintenance



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 11-12 Parameters

Name	Description	Туре	Required	Default
skipNext	Specifies if the next scheduled daily maintenance time should be skipped, true or false	String	Yes	false

Example URL and Payload

https://<BASE URL>/interop/rest/v2/maintenance/rundailymaintenance

Response

Supported Media Types: application/json

{"skipNext":"true"}

Table 11-13 Parameters

Parameters	Description		
details	In case of errors, details are published with the error string		
status	See Migration Status Codes		
links	Detailed information about the link		
href	Links to API call		
action	The HTTP call type		
rel	Possible value: self		
data	Null		

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "details": null,
   "status": -1,
   "items": null,
   "links": [
        {
            "href": " https://<BASE-URL>/interop/rest/v2/maintenance/
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d '{"skipNext":"true"}' 'https://<BASE
URL>/interop/rest/v2/maintenance/rundailymaintenance'
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



This section describes the REST APIs to manage users, groups, and roles.

Task	Request	REST Resource
Add Users to an Identity Domain (v1)	POST	<pre>/interop/rest/security/<api_version>/ users</api_version></pre>
Add Users to an Identity Domain (v2)	POST	/interop/rest/security/v2/users/add
Remove Users from an Identity Domain (v1)	DELETE	/interop/rest/security/ <api_version>/ users?filename=<filename></filename></api_version>
Remove Users from an Identity Domain (v2)	POST	/interop/rest/security/v2/users/remove
Assign Users to a Predefined Role or Application Role (v1)	PUT	/interop/rest/security/< <i>api_version</i> >/ users
Assign Users to a Predefined Role or Application Role (v2)	PUT	/interop/rest/security/v2/role/assign/ user
Remove Users' Role Assignment (v1)	PUT	/interop/rest/security/< <i>api_version</i> >/ users
Remove Users' Role Assignment (v2)	PUT	/interop/rest/security/v2/role/ unassign/user
Add Users to a Group (v1)	PUT	/interop/rest/security/ <api_version>/ groups</api_version>
Add Users to a Group (v2)	PUT	/interop/rest/security/v2/groups/ adduserstogroup
Remove Users from a Group (v1)	PUT	/interop/rest/security/< <i>api_version</i> >/ groups
Remove Users from a Group (v2)	PUT	/interop/rest/security/v2/groups/ removeusersfromgroup
Update Users	PUT	/interop/rest/security/< <i>api_verion</i> >/ users
Add a User to a Batch of Groups	PUT	/interop/rest/security/< <i>api_version</i> >/ groups
Remove a User from a Batch of Groups	PUT	/interop/rest/security/< <i>api_version</i> >/ groups
Add Groups (v1)	POST	/interop/rest/security/< <i>api_version</i> >/ groups
Add Groups (v2)	POST	/interop/rest/security/v2/groups/add
Remove Groups (v1)	DELETE	/interop/rest/security/< <i>api_version</i> >/ groups
Remove Groups (v2)	POST	/interop/rest/security/v2/groups/remove
User Group Report (v1)	POST	/interop/rest/security/ <api_version>/ usergroupreport</api_version>
User Group Report (v2)	GET	/interop/rest/security/v2/report/ usergroupreport



Task	Request	REST Resource
User Access Report (v1)	POST	<pre>/interop/rest/{api_version}/reports? q={type:provisionreport,fileName:provre port.csv,format=simplified,usertype=ser viceusers}</pre>
User Access Report (v2)	POST	/interop/rest/v2/reports/useraccess
User Audit Report (v1)	POST	<pre>/interop/rest/{api_version}/reports? q={type:userauditreport,fileName:userau ditreport.csv,since=2017-12-10,until=20 18-06-10}</pre>
User Audit Report (v2)	POST	/interop/rest/v2/reports/useraudit
Role Assignment Report (v1)	POST	/interop/rest/security/{api_version}/ roleassignmentreport
Role Assignment Report for Users (v2)	GET	<pre>/interop/rest/security/v2/report/ roleassignmentreport/user? userlogin=<userlogin>&rolename=<rolenam e=""></rolenam></userlogin></pre>
Role Assignment Report for Groups (v2)	GET	<pre>/interop/rest/security/v2/report/ roleassignmentreport/group? groupname=<groupname>&rolename=<rolenam e=""></rolenam></groupname></pre>
Get Available Roles	GET	/interop/rest/security/v2/role/ getavailableroles
Role Assignment Audit Report for OCI (Gen 2) Environments	PUT	/interop/rest/security/{api_version}/ roleassignmentauditreport/
Invalid Login Report for OCI (Gen 2) Environments	PUT	/interop/rest/security/{api_version}/ invalidloginreport/
Group Assignment Audit Report	POST	/interop/rest/{api_version}/reports/ groupaudit
Adding Users to a Team for Account Reconciliation	POST	/armARCS/rest/{version}/jobs
Adding Users to a Team for Financial Consolidation and Close and Tax Reporting	POST	/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs
Removing Users from a Team for Account Reconciliation	POST	/armARCS/rest/{version}/jobs
Removing Users from a Team for Financial Consolidation and Close and Tax Reporting	POST	<pre>/HyperionPlanning/rest/{api_version}/ applications/{application}/fcmjobs</pre>

Table 12-1 (Cont.) Manage Users

Add Users to an Identity Domain (v1)

Creates a batch of users in an identity domain using an ANSI or UTF-8 encoded Comma Separated Value (CSV) file that was previously uploaded to the environment. The CSV file should not include the account of the user who executes this command. You can use the Upload REST API to upload the file. The file should be deleted after the API executes. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed. The file format is as follows:

```
First Name,Last Name,Email,User Login
Jane,Doe,jane.doe@example.com,jdoe
John,Doe,john.doe@example.com,john.doe@example.com
```

This API sends each new user an email with details about their accounts (user name and password) if resetpassword is set to true. If resetpassword is set to false, the email is not sent. If you set resetpassword to false, you should specify userpassword. Otherwise, a unique temporary password will be assigned to each user, but, because no email is sent, the passwords will not be known to the users so they will not be able to log in.

See Importing a Batch of User Accounts in *Getting Started with Oracle Cloud* for a detailed description of the CSV file format.

If a user definition in the CSV file matches a user account that exists in the identity domain, no changes will be made to the existing user account. This API creates accounts only for new users whose account information is included in the file. Because user accounts are common to all service environments that an identity domain supports, new users are available to all the environments that share the identity domain.

This API should be run only by an Identity Domain Administrator in the identity domain where users are to be created. In addition, the user running the API must also be the Service Administrator of the environment where the API is targeted.

The API is asynchronous and returns the Job ID. The presence of status -1 in the response indicates that the creation of users is in progress. Use the job status URI to determine whether the creation of users is complete. Any non-zero status except -1 indicates failure of adding users.

Note:

This API assigns one password (value of userpassword) to all the users specified in the CSV file. Assigning the same password to all users may be desirable if you are creating users purely for testing purposes.

If you are creating real EPM Cloud users and want to assign a specific password to each user, use this API for a single user at a time. That is, specify a single user in the CSV file and provide a password for this user in the API. Then, specify the other user in the CSV file and provide a different password for this user in the API.

When you add users using this API, unlike when you add users from My Services, Oracle Cloud does not send automatic emails to each newly added user. You should manually email credentials (login name and password) to each new user. Additionally, you should force new users to change password at first login by specifying resetpassword as true.

This API is version v1.

Required Roles

Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)



REST Resource

POST /interop/rest/security/<api_version>/users

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-2 Tasks for Add Users to an Identity Domain

Task	Request	REST Resource
Add users	POST	/interop/rest/security/< <i>api_version</i> >/users
Add users status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/ <jobid></jobid>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the POST request parameters.

Table 12-3 Parameters

Name	Description	Туре	Required	Default
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing the users to add, such as addUsers.csv.	Form	Yes	None
userpassword	Optionally, indicates the default password that you want to assign to all the new users who are created in the identify domain. If specified, this password must meet the minimum identity domain password requirements. If specified, the value of the user password parameter is used as the password for all users specified in the CSV file. Assigning the same password to all users may be desirable if you are creating users purely for testing purposes. If you are creating real EPM Cloud users and want to assign a specific password to each user, use this command without specifying a valid for the userpassword optional parameter.	Form	No	None
resetpassword	Optionally, indicates whether new users must change password at the first login. Unless this parameter is set to false, new users will be forced to change the password at the first login. This parameter sends each new user an email with details about their accounts (user name and password) if resetPassword is set to true.	Form	No	true
	If resetPassword is set to false, the email is not sent.			
	Note: If you set resetPassword to false, you should specify userPassword. Otherwise, a unique temporary password will be assigned to each user, but, because no email is sent, the passwords will not be known to the users, so they will not be able to log in.			



Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Table 12-4 Parameters

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
  "links": [
   {
     "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/users",
     "data": {
       "jobType": "ADD USERS",
        "filename": "<filename>",
       "resetpassword": "<true|false>"
                                            },
      "action": "POST"
    },
    {
     "rel": "Job Status",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/users",
     "data": null,
     "action": "GET"
   }
 ],
 "details": null,
 "status": -1,
  "items": null
}
```

Example 2: Job Completes with Errors

```
{
"links": [
{
```



```
"rel": "self",
    "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/",
    "data": null,
    "action": "GET"
    }
  ],
    "details": "Failed to add users. Input file <fileName> is not found.
Specify a valid file name.",
    "status": 1,
    "items": null
}
```

Example 3: Job Completes without Errors

```
{
  "links": [
   {
      "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/",
     "data": null,
      "action": "GET"
    }
 ],
  "details": "Processed - 3, Succeeded - 2, Failed - 1.",
  "status": 0,
  "items": [
    {
    "UserName":"<USERNAME>","Error Details": "User <USERNAME> already exists.
Please provide a different user name."
    }
   1
)
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void addUsers(String fileName, String userPassword, boolean
resetPassword) {
    try {
        String url = this.serverUrl + "/interop/rest/security/
<api_version>/users";
        Map<String, String> reqHeaders = new HashMap<String, String>();
        reqHeaders.put("Authorization", "Basic " + DatatypeConverter
            .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
    Map<String, String> reqParams = new HashMap<String, String>();
    reqParams.put("filename", fileName);
    reqParams.put("userpassword", userPassword);
    reqParams.put("resetpassword", resetPassword + "");
    Map<String, String> resetResult = CSSRESTHelper.callRestApi(new
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcAddUsers() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/users"
    params="filename=$1&userpassword=$2&resetpassword=$3"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="AddUsers"
    statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def addUsers(fileName, resetPassword, userPassword) {
    String scenario = "Creating users in " + fileName;
    String params = "jobtype=ADD USERS&filename="+ fileName
+"&resetpassword="+ resetPassword +"&userpassword="+ userPassword;
    def url = null;
    def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
```



Sample cURL Command Basic Auth

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/x-www-form-urlencoded' -d
'filename=<CSV-FILE-NAME>&resetpassword=<TRUE/FALSE>&userpassword=<PASSWORD>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Sample cURL Command OAuth 2.0

```
curl -X POST --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/x-www-form-urlencoded' -d
'filename=<CSV-FILE-NAME>&resetpassword=<VALUE>&userpassword=<PASSWORD>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Add Users to an Identity Domain (v2)

The Add Users to an Identity Domain (v2) REST API adds users that are provided in the request payload. It sends each new user an email with details about their accounts (user name and password) if resetpassword is set to true. If resetpassword is set to false, the email is not sent. If you set resetpassword to false, you should specify userpassword; otherwise, a unique temporary password will be assigned to each user; but, because no email is sent, the users will not know that password and they will not be able to log in. If a user definition in the payload matches a user account that exists in the identity domain, no changes are made to the existing user account. This API creates accounts only for new users whose account information is provided in the payload. Because user accounts are common to all service environments that an identity domain supports, new users are available to all the environments that share the identity domain.

This API should be run only by an Identity Domain Administrator in the identity domain where users will be created. In addition, the user running the API must also be assigned a predefined role in the environment where the API is targeted. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of adding users.

This API is version v2.

Required Roles

Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

REST Resource

```
POST /interop/rest/security/v2/users/add
```



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-5 Tasks for Add Users to an Identity Domain

Task	Request	REST Resource
Add users	POST	/interop/rest/security/v2/users/add

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.

Table 12-6 Parameters

Name	Description	Туре	Required	Default
users	List of users to add	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/users/add

```
{
    "users":
    [
        {
            "firstname": "Jane",
            "lastname": "Doe",
            "email": "jane.doe@example.com",
            "userlogin": "jdoe",
            "resetpassword": true
        },
        {
            "firstname": "chris",
            "lastname": "west",
            "email": "chris.west@example.com",
            "userlogin": "chris",
            "password": "userPassword",
            "resetpassword": false
            }
    ]
}
```

Response

Supported Media Types: application/json



Name	Description	
links	Detailed information about the link and HTTP call type	
status	Identifies the status of the operation0: Operation succeeded1: Operation failed	
error	Detailed information about the error	
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed and reason why they failed.	

Table 12-7Parameters

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/users/add",
        "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 3,
        "failed": 0,
        "faileditems": null
    }
}
```

Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/users/add",
        "action": "POST"
    },
    "status": 1,
    "error": {
        "errorcode": "EPMCSS-21146",
        "errormessage": "Failed to add users. Invalid or insufficient
parameters specified. Provide all required parameters for the REST API."
    },
    "details": null
}
```

Example 3: Job Completes with Partial Errors

{
 "links": {



```
"href": "https://<BASE-URL>/interop/rest/security/v2/users/add",
            "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        {
                         "userlogin": "jdoe",
                         "errorcode": "EPMCSS-21150",
                         "errormessage": "Failed to add user. Invalid email
jdoe.com. Please provide a valid email."
               },
                {
                         "userlogin": "chris",
                         "errorcode": "EPMCSS-21151",
                         "errormessage": "Failed to add user. Missing
[firstname]. Please provide value: [firstname]."
                }
        1
    }
}
```

Sample cURL Command Basic Auth

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/json' -d'{"users":
[{"firstname":"<FIRSTNAME>","lastname":"<LASTNAME>",
"email":"<EMAIL>","userlogin":"<USERLOGIN>","password":"<PASSWORD>","resetpass
word":<TRUE/FALSE>}]}'
'https://<BASE-URL>/interop/rest/security/v2/users/add'
```

Sample cURL Command OAuth 2.0

```
curl -X POST --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/json' -d '{"users":
  [{"firstname":"<FIRSTNAME>","lastname":"<LASTNAME>",
  "email":"<EMAIL>","userlogin":"<USERLOGIN>","password":"<PASSWORD>","resetpass
word":<TRUE/FALSE>}]}
' 'https://<BASE-URL>/interop/rest/security/v2/users/add'
```

Remove Users from an Identity Domain (v1)

Deletes the identity domain accounts identified in an ANSI or UTF-8 encoded CSV file that was uploaded to the environment. Before running this command, use the Upload REST API to upload the file. The file format is as follows:

User Login jane.doe@example.com jdoe@example.com

This API should be run only by Service Administrators who are also assigned to the Identity Domain Administrator role in the identity domain from which users are to be removed. The CSV file should not include the account of the user who executes this command. Because user accounts are common to all service environments that an Identity Domain Administrator supports, deleting an account for one environment deletes it for all environments that share the Identity Domain Administrator. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

The API is asynchronous and returns the Job ID. The presence of status -1 in the response indicates that the removal of users is in progress. Use the job status URI to determine whether the removal of users is complete. Any non-zero status except -1 indicates failure of removing users.

This API is version v1.

Required Roles

Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

REST Resource

DELETE /interop/rest/security/<api version>/users?filename=<filename>

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-8 Tasks for Remove Users from an Identity Domain

Task	Request	REST Resource
Remove users	DELETE	/interop/rest/security/ <api_version>/users?filename=<filename></filename></api_version>
Remove users status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the DELETE request parameters.



Name	Description	Туре	Required	Default
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file name of a CSV file containing the login names of the users to be removed, for example, removeUsers.csv.		Yes	None

Table 12-9Parameters

Response

Supported Media Types: application/json

Table 12-10 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
  "links": [
    {
     "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/users?
filename=<filename>",
     "data": {
        "jobType": "REMOVE USERS",
        "filename": "<filename>"
     },
      "action": "DELETE"
    },
    {
     "rel": "Job Status",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/",
     "data": null,
      "action": "GET"
   }
 ],
 "details": null,
 "status": -1,
```



```
"items": null
```

}

Example 2: Job Completes with Errors

```
{
  "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/",
        "data": null,
        "action": "GET"
    }
  ],
  "details": "Failed to remove users. Input file <filename> is not found.
Specify a valid file name.",
    "status": 1,
    "items": null
}
```

Example 3: Job Completes without Errors

```
{
  "links": [
   {
     "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/",
     "data": null,
     "action": "GET"
   }
 ],
  "details": "Processed - 3, Succeeded - 1, Failed - 2.",
 "status": 0,
  "items": [
     {
          "UserName":"<USERNAME>","Error Details": "User <USERNAME> is not
found. Verify that the user exists."
   },
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java.

```
public void removeUsers(String fileName) {
    try {
        String url = this.serverUrl + "/interop/rest/security/
<api_version>/users";
        Map<String, String> reqHeaders = new HashMap<String, String>();
        reqHeaders.put("Authorization", "Basic " + DatatypeConverter
            .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
```



```
Map<String, String> reqParams = new HashMap<String, String>();
reqParams.put("filename", fileName);
Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                                 "DELETE");
        String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
        System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL.

```
funcRemoveUsers() {
    url="$SERVER_URL/interop/rest/security/<api_version>/users"
    params="filename=$1"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="RemoveUsers"
    statusMessage=$(funcCSSRESTHelper "DELETE" "$url" "$header"
    "$USERNAME" "$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

CSS Common Helper Functions for Groovy.

```
def deleteUsers(fileName) {
    String scenario = "Deleting users in " + fileName;
    String params = null;
   def url = null;
   def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/<api version>/users?
filename=" + fileName);
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    response = executeRequest(url, "DELETE", null, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
```



Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Sample cURL Command Basic Auth

```
curl -X DELETE -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/x-www-form-urlencoded'
'https://<BASE-URL>/interop/rest/security/v1/users?filename=<CSV-FILE-NAME>'
```

Sample cURL Command OAuth 2.0

```
curl -X DELETE --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/x-www-form-urlencoded'
'https://<BASE-URL>/interop/rest/security/v1/users?filename=<CSV-FILE-NAME>'
```

Remove Users from an Identity Domain (v2)

The Remove Users from an Identity Domain (v2) REST API deletes the accounts indentified in an identity domain that are provided in the request payload.

This API should be run only by a user who is assigned to the Identity Domain Administrator role in the identity domain from which users are to be removed. In addition, this user should also have a predefined role in the environment on which the API is run. The payload should not include the account of the user who executes this command. Because user accounts are common to all service environments that an identity domain supports, deleting an account for one environment deletes it for all environments that share the identity domain. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of removing users.

This API is version v2.

Required Roles

Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

REST Resource

POST /interop/rest/security/v2/users/remove






Table 12-11 Tasks for Remove Users from an Identity Domain

Task	Request	REST Resource
Remove users	POST	/interop/rest/security/v2/users/remove

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.

Table 12-12 Parameters

Name	Description	Туре	Required	Default
users	List of user login IDs of the users to remove	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/users/remove

Response

Supported Media Types: application/json

Table 12-1	L3 Par	ameters
------------	--------	---------

Name	Description
links	Detailed information about the link and HTTP call type
status	Identifies the status of the operation
	O: Operation succeeded
	• 1: Operation failed



Table 12-13 (Cont.) Parameters

Name	Description
error	Detailed information about the error
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed and reason for why it failed.

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/users/
remove",
        "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 2,
        "succeeded": 2,
        "failed": 0,
        "faileditems": null
    }
}
```

Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/users/
remove",
        "action": "POST"
    },
    "status": 1,
        "error": {
            "errorcode": "EPMCSS-21147",
            "errormessage": "Failed to remove users. Invalid or
insufficient parameters specified. Provide all required parameters for the
REST API."
        },
        "details": null
}
```

Example 3: Job Completes with Partial Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/users/
remove",
        "action": "POST"
```

```
},
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
        {
                         "userlogin": "jdoe",
                         "errorcode": "EPMCSS-21174",
                         "errormessage": "Failed to remove user. User jdoe
does not exist. Provide a valid userlogin."
                },
                 {
                        "userlogin": "chris",
                         "errorcode": "EPMCSS-21174",
                         "errormessage": " Failed to remove user. User chris
does not exist. Provide a valid userlogin."
                }
        ]
    }
}
```

Sample cURL Command Basic Auth

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/json' -d '{"users":[{"userlogin":"<USERLOGIN>"},
{"userlogin":"<USERLOGIN>"}]}'
'https://<BASE-URL>/interop/rest/security/v2/users/remove'
```

Sample cURL Command OAuth 2.0

```
curl -X POST --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/json' -d '{"users":[{"userlogin":"<USERLOGIN>"},
{"userlogin":"<USERLOGIN>"}]}'
'https://<BASE-URL>/interop/rest/security/v2/users/remove'
```

Assign Users to a Predefined Role or Application Role (v1)

This API assigns users included in an ANSI or UTF-8 encoded CSV file to a pre-defined or application role. Use this API to assign users (including the user who invokes this API) to a pre-defined role or to assign a user with application roles.

To assign a user to an application role, that user should already have a pre-defined role assigned to them.

Use double quotation marks to enclose role names that contain space characters in the CSV file. Before using this API, use the Upload REST API to upload files to the environment. The file should be deleted after the API executes.



The file format is as follows:

```
User Login
jane.doe@example.com
jdoe
```

The API is asynchronous and returns the Job ID. The presence of status -1 in the response indicates that assigning users is in progress. Use the job status URI to determine whether the assignment of roles is complete. Any non-zero status except -1 indicates failure of assigning users. With this API, you can see which records failed and the reason why they failed, in addition to how many records passed and failed.

This API is version v1.

Required Roles

For predefined roles:

Classic environments: Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

OCI environments: Service Administrator, or Identity Domain Administrator and any predefined role (Power User, User, or Viewer)

For application roles:

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/<api version>/users

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-14 Tasks for Assign Users to Roles

Task	Request	REST Resource	
Assign role	PUT	/interop/rest/security/ <api_version>/users</api_version>	
Assign role status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/ <jobid></jobid>	

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the PUT request parameters.



Name	Description	Туре	Required	Default	
api_version	Specific API version	Path	Yes	None	
jobtype	ASSIGN_ROLE	Form	Yes	None	
filename	The name of the ANSI or UTF-8 encoded CSV file containing the login IDs of the users whose role assignment is to be modified, such as assignRoles.csv.	Form	Yes	None	

Name	Description	Туре	Required	Default
rolename	The name of a pre-defined or application role applicable to the service. An incorrect role name will result in an error.	Form	Yes	None
	It identifies one of the following:			
	• If you are assigning users to a pre-defined identity domain role, roleName should identify a pre-defined role applicable to the service. See Understanding Predefined Roles in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.			
	 Acceptable values for services other than Oracle Enterprise Data Management Cloud: Service Administrator 			
	 Power User 			
	 User (do not use Planner, which was used in earlier versions of the service) 			
	- Viewer			
	 Acceptable values for Oracle Enterprise Data Management Cloud: Service Administrator User 			
	 If you are assigning users to an application role, roleName should identify an application role listed in the assign roles tab of Access Control. Acceptable values for FreeForm, Planning, Planning Modules, Sales Planning, Strategic Workforce Planning, Financial Consolidation and Close, and Tax Reporting applications: 			
	 Approvals Administrator 			
	 Approvals Ownership Assigner 			
	 Approvals Supervisor 			
	 Approvals Proess Designer 			
	 Ad Hoc Grid Creator 			
	 Ad Hoc User 			
	 Ad Hoc Read Only User 			
	 Calculation Manager Administrator 			
	 Create Integration 			
	 Drill Through 			
	 Run Integration 			
	 Mass Allocation 			
	 Task List Access Manager 			
	Acceptable values for Account Reconciliation :			
	 Manage Alert Types 			
	 Manage Announcements 			
	 Manage Data Loads 			
	 Manage Organizations 			
	 Manage Periods 			
	 Manage Profiles and Reconciliations 			
	 Reconciliation Manage Currencies 			
	 Reconciliation Manage Public Filters and Lists 			
	 Reconciliation Manage Reports 			
	 Reconciliation Manage Teams 			
	 Reconciliation Manage Users 			
	 Reconciliation Commentator 			

Table 12-15 (Cont.) Parameters

Name	Description	Туре	Required	Default
	 Reconciliation Preparer 			
	 Reconciliation Reviewer 			
	 Reconciliation View Jobs 			
	 Reconciliation View Profiles 			
	 View Audit 			
	 View Periods 			
	 Acceptable values for Oracle Enterprise Data Management Cloud applications: Application Creator 			
	– Auditor			
	 View Creator 			
	 Acceptable values for Oracle Enterprise Profitability Cost Management applications: Ad Hoc Grid Creator Ad Hoc Read Only User 	and		
	 Ad Hoc Kead Only Oser Ad Hoc User 			
	 Clear POV Data Copy POV Data 			
	 Create/Edit Rule 			
	 Create Integration 			
	 Create Model 			
	 Create POV 			
	 Create Profit Curve 			
	 Delete Calculation History 			
	 Delete Galculation History Delete Model 			
	 Delete Nodel Delete POV 			
	– Delete Rule			
	– Drill Through			
	 Edit POV Status 			
	 Edit Profit Curve 			
	 Mass Edit of Rules 			
	 Run Calculation 			
	 Run Integration 			
	 Run Profit Curve 			
	 Run Rule Balancing 			
	 Run Trace Allocation 			
	 Run Validation 			
	 View Calculation History 			
	 View Model 			
	 Acceptable values for Oracle Enterprise Profitability 	and		
	Cost Management applications: – Ad Hoc Grid Creator	and		
	 Ad Hoc Read Only User 			
	 Ad Hoc User 			
	 Clear POV Data 			
	 Copy POV Data 			
	 Create/Edit Rule 			
	 Create Integration 			
	 Create Model 			
	Create ROV			

Table 12-15 (Cont.) Parameters

Create POVCreate Profit Curve



Name	Description	Туре	Required	Default
	 Delete Calculation History 			
	 Delete Model 			
	 Delete POV 			
	 Delete Rule 			
	 Drill Through 			
	 Edit POV Status 			
	 Edit Profit Curve 			
	 Mass Edit of Rules 			
	 Run Calculation 			
	 Run Integration 			
	 Run Profit Curve 			
	 Run Rule Balancing 			
	 Run Trace Allocation 			
	 Run Validation 			
	 View Calculation History 			
	 View Model 			
	For a description of these roles, see Managing Role Assignments at the Application Level in Administering Access Control for Oracle Enterprise Performance Management Cloud.			

Table 12-15 (Cont.) Parameters

Response

Supported Media Types: application/json

Table 12-16 Parameters

Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status	
data	Parameters as key value pairs passed in the request	
items	Details about the resource	
links	Details of the first URL to be requested to get the job details; rel is "Job Details"	

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "links": [
        {
            "rel": "self",
            "
```

```
"href": "https://<BASE-URL>/interop/rest/security/<api version>/users",
      "data": {
        "jobType": "ASSIGN ROLE",
        "filename": "<filename>",
        "rolename": "<rolename>"
     },
      "action": "PUT"
    },
    {
      "rel": "Job Status",
      "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobid>",
      "data": null,
     "action": "GET"
    }
 ],
 "details": null,
 "status": -1,
  "items": null
}
```

Example 2: Job Completes with Errors

```
{
   "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/
<jobid>",
        "data": null,
        "action": "GET"
    }
   ],
   "details": " Failed to assign role for users. Input file <filename> is not
found. Specify a valid file name.",
   "status": 1,
   "items": null
}
```

Example 3: Job Completes without Errors

```
{
   "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/
<jobid>",
        "data": null,
        "action": "GET"
    }
   ],
   "details": "Processed - 3, Succeeded - 2, Failed - 1.",
   "status": 0,
   "items": [
    {
     }
}
```



```
"UserName":"<USERNAME>","Error_Details": "User <USERNAME> is not
found. Verify that the user exists."
    }
]
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java.

```
public void assignRole(String fileName, String roleName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ASSIGN_ROLE");
            reqParams.put("rolename", roleName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL.

```
funcAssignRole() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/users"
    params="filename=$1&jobtype=ASSIGN_ROLE&rolename=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="AssignRole"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```



Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy.

```
def assignUsersRoles(fileName, roleName) {
    String scenario = "Assigning users in " + fileName + " with role " +
roleName;
    String params = "jobtype=ASSIGN ROLE&filename="+ fileName +"&rolename="+
roleName;
   def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Sample cURL Command Basic Auth

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/x-www-form-urlencoded' -d
'jobtype=ASSIGN_ROLE&filename=<CSV-FILE-NAME>&rolename=<ROLENAME>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Sample cURL Command OAuth 2.0

```
curl -X PUT --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/x-www-form-urlencoded' -d
'jobtype=ASSIGN_ROLE&filename=<CSV-FILE-NAME>&rolename=<ROLENAME>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Assign Users to a Predefined Role or Application Role (v2)

The Assign Users to a Predefined Role or Application Role (v2) REST API assigns a predefined or an application role to users provided in the REST API payload. To assign a user to an application role, that user should already have a pre-defined role assigned to them.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates that assigning users to roles failed. With this API, you can see which



records failed and the reason why they failed, in addition to how many records passed and failed.

This API is version v2.

Required Roles

For predefined roles:

Classic environments: Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

OCI environments: Service Administrator, or Identity Domain Administrator and any predefined role (Power User, User, or Viewer)

For application roles:

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/v2/role/assign/user

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-17 Tasks for Assign Users to Roles

Task	Request	REST Resource
Assign role	PUT	/interop/rest/security/v2/role/assign/user

Request

Supported Media Types: application/json

The following table summarizes the PUT request parameters.

Description Name Туре Required Default The name of a pre-defined or application role applicable Payload rolename Yes None to the service. An incorrect role name will result in an error. It identifies one of the following: If you are assigning users to a pre-defined role, roleName should identify a pre-defined role applicable to the service. See "Understanding Predefined Roles" in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators. Acceptable values for services other than Oracle Enterprise Data Management Cloud: Service Administrator Power User User (do not use Planner, which was used in earlier versions of the service) Viewer Acceptable values for Oracle Enterprise Data Management Cloud: Service Administrator User If you are assigning users to an application role, roleName should identify an application role listed in the tab of Access Control. Acceptable values for FreeForm, Planning, Planning Modules, Sales Planning, Strategic Workforce Planning, Financial Consolidation and Close, and Tax Reporting applications: Approvals Administrator Approvals Ownership Assigner **Approvals Supervisor Approvals Process Designer** Ad Hoc Grid Creator Ad Hoc User Ad Hoc Read Only User **Calculation Manager Administrator Create Integration** Drill Through **Run Integration** Mass Allocation Task List Access Manager Acceptable values for Account Reconciliation: Manage Alert Types Manage Announcements Manage Data Loads **Manage Organizations Manage Periods Manage Profiles and Reconciliations Reconciliation Manage Currencies** _ **Reconciliation Manage Public Filters and Lists Reconciliation Manage Reports Reconciliation Manage Teams**

Table 12-18 Parameters

Name	Description	Туре	Required	Default
	 Reconciliation Manage Users 			
	 Reconciliation Commentator 			
	 Reconciliation Preparer 			
	 Reconciliation Reviewer 			
	 Reconciliation View Jobs 			
	 Reconciliation View Profiles 			
	– View Audit			
	 View Periods 			
	 Acceptable values for Oracle Enterprise Data 			
	Management Cloudapplications:			
	 Application Creator 			
	– Auditor			
	 View Creator 			
	Acceptable values for Enterprise Profitability and			
	Cost Management applications:			
	 Ad Hoc Grid Creator Ad Hoc Brad Only Horn 			
	 Ad Hoc Read Only User 			
	– Ad Hoc User			
	- Clear POV Data			
	- Copy POV Data			
	– Create/Edit Rule			
	Create Integration			
	- Create Model			
	- Create POV			
	Create Profit Curve			
	 Delete Calculation History 			
	– Delete Model			
	– Delete POV			
	– Delete Rule			
	– Drill Through			
	– Edit POV Status			
	– Edit Profit Curve			
	 Mass Edit of Rules 			
	– Run Calculation			
	– Run Integration			
	– Run Profit Curve			
	 Run Rule Balancing 			
	 Run Trace Allocation 			
	 Run Validation 			
	 View Calculation History 			
	 View Model 			
	For a description of these roles, see "Managing Role			
	Assignments at the Application Level" in Administering			
	Access Control for Oracle Enterprise Performance Management Cloud .			
users	List of user login IDs of the users whose role assignment is to be modified.	Payload	Yes	None

Table 12-18 (Cont.) Parameters



Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/role/assign/user

```
{
    "rolename": "Service Administrator",
    "users": [
        {
            "userlogin": "jdoe"
            },
        {
            "userlogin": "chris"
            }
        ]
}
```

Response

Supported Media Types: application/json

Name	Description	
links	Detailed information about the link and HTTP call type	
status	 Identifies the status of the operation 0: Operation Success 1: Operation Failed 	
error	Detailed information about the error	
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed and reason for why it failed.	

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/role/assign/
user",
        "action": "PUT"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 3,
        "succeeded": 3,
        "failed": 0,
        "faileditems": null
    }
}
```



Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/role/assign/
user",
        "action": "PUT"
    },
    "status": 1,
    "error": {
        "errorcode": "EPMCSS-21000",
        "errormessage": "Failed to assign role. Invalid role name <rolename>.
Please provide a valid role name."
    },
    "details": null
}
```

Example 3: Job Completes with Partial Errors

```
{
    "links": {
            "href": "https://<BASE-URL>/interop/rest/security/v2/role/assign/
user",
            "action": "PUT"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
            {
                "userlogin": "jdoe",
                "errorcode": "EPMCSS-21002",
                "errormessage": "Failed to assign role. User jdoe does not
exist. Provide a valid userlogin."
            },
            {
                "userlogin": "chris",
                "errorcode": "EPMCSS-21002",
                "errormessage": "Failed to assign role. User chris does not
exist. Provide a valid userlogin."
            }
        1
    }
}
```

Sample cURL Command Basic Auth

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -H
'Content-Type: application/json' -d '{"rolename":"<ROLENAME>","users":
```



```
[{"userlogin":"<USERLOGIN>"}, {"userlogin":"<USERLOGIN>"}]}'
'https://<BASE-URL>/interop/rest/security/v2/role/assign/user'
```

Sample cURL Command OAuth 2.0

```
curl -X PUT --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/json' -d '{"rolename":"<ROLENAME>","users":
[{"userlogin":"<USERLOGIN>"}, {"userlogin":"<USERLOGIN>"}]}'
'https://<BASE-URL>/interop/rest/security/v2/role/assign/user'
```

Remove Users' Role Assignment (v1)

Removes one role currently assigned to the users (including the user who invokes this API) whose login IDs are included in the ANSI or UTF-8 encoded CSV file that is used with this command. Before running this API, upload the file to the environment using the Upload REST API. The file should be deleted after the API executes. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

Use double quotation marks to enclose role names that contain the space character.

The API is asynchronous and returns the Job ID. The presence of status -1 in the response indicates that the removal of role assignments is in progress. Use the job status URI to determine whether unassigning roles is complete. Any non-zero status except -1 indicates failure of unassigning roles.

This API is version v1.

Required Roles

For predefined roles:

Classic environments: Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

OCI environments: Service Administrator, or Identity Domain Administrator and any predefined role (Power User, User, or Viewer)

For application roles:

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/<api_version>/users

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Unassign role	PUT	/interop/rest/security/ <api_version>/users</api_version>
Unassign role status	GET	/interop/rest/security/ <api_version>/jobs/<jobid></jobid></api_version>

Table 12-20 Tasks for Unassign Users to Roles

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the PUT request parameters.

Table 12-21Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
jobtype	UNASSIGN_ROLE	Form	Yes	None
filename	The name of the ANSI or UTF-8 encoded CSV file containing the users whose role assignment is to be revoked, such as unssignRole.csv.	Form	Yes	None
	The CSV file must have been uploaded already using the Upload REST API. The CSV file should not include the account of the user who executes this command.			
	File format example:			
	User Login			
	<email></email>			
	<firstname2.lastname2></firstname2.lastname2>			



rolename	The name of a pre-defined or application role applicable to	Form	Yes	None
	the service. An incorrect role name will result in an error.		100	None
	 the service. An incorrect role name will result in an error. If you are removing users from a pre-defined role, roleName should identify a pre-defined Roles in <i>Getting Started with Oracle Enterprise Performance Management Cloud for Administrators.</i> Acceptable values for services other than Oracle Enterprise Data Management Cloud: Service Administrator Power User User (do not use Planner, which was used in earlier versions of the service) Viewer Acceptable values for Oracle Enterprise Data Management Cloud: Service Administrator Power User User (do not use Planner, which was used in earlier versions of the service) Viewer Acceptable values for Oracle Enterprise Data Management Cloud: Service Administrator User If you are removing users from an application role, roleName should identify an application role listed in the assign roles tab of Access Control. Acceptable values for Oracle Planning, Oracle Planning Modules, Oracle Financial Consolidation and Close, Sales Planning, Strategic Workforce Planning, and Oracle Tax Reporting applications: Approvals Administrator Approvals Supervisor Ad Hoc Grid Creator Ad Hoc Grid Creator Ad Hoc Creat Integration Drill Through Run Integration Manage Allocation Manage Poriods Manage Proides Manage Proides Manage Proides Manage Proides Manage Proides Manage Periods Manage Proides Manage Proi			

Table 12-21 (Cont.) Parameters

lame	Description	Туре	Required	Default
	 Reconciliation Commentator 			
	 Reconciliation Preparer 			
	 Reconciliation Reviewer 			
	 Reconciliation View Jobs 			
	 Reconciliation View Profiles 			
	 View Audit 			
	 View Periods 			
	 Acceptable values for Oracle Enterprise Data 			
	Management Cloud applications:			
	 Application Creator 			
	– Auditor			
	- View Creator			
	 Acceptable values for Oracle Enterprise Profitability an Cost Management applications; 	Id		
	Cost Management applications: – Ad Hoc Grid Creator			
	 Ad Hoc Brad Only User 			
	 Ad Hoc User Ad Hoc User 			
	 Clear POV Data 			
	 Copy POV Data 			
	– Create/Edit Rule			
	 Create Integration 			
	 Create Model 			
	 Create POV 			
	 Create Profit Curve 			
	 Delete Calculation History 			
	 Delete Model 			
	– Delete POV			
	 Delete Rule 			
	– Drill Through			
	 Edit POV Status 			
	 Edit Profit Curve 			
	 Mass Edit of Rules 			
	 Run Calculation 			
	 Run Integration 			
	 Run Profit Curve 			
	 Run Rule Balancing 			
	 Run Trace Allocation 			
	– Run Validation			
	 View Calculation History 			
	 View Model 			
	For a description of these roles, see <i>Managing Role</i>			
	Assignments at the Application Level in Administering			
	Access Control for Oracle Enterprise Performance			
	Management Cloud.			

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is Job Details

Table 12-22 Parameters

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
  "links": [
    {
     "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/users",
     "data": {
       "jobtype": "UNASSIGN ROLE",
       "filename": "<fileName>",
        "rolename": "<roleName>"
     },
     "action": "PUT"
   },
    {
     "rel": "Job Status",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobid>",
     "data": null,
     "action": "GET"
   }
 ],
 "details": null,
 "status": -1,
  "items": null
}
```

Example 2: Job Completes with Errors

```
{
  "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/
```

```
<jobid>",
    "data": null,
    "action": "GET"
    }
  ],
    "details": "Failed to unassign role for users. Input file <filename> is not
found. Specify a valid file name.",
    "status": 1,
    "items": null
}
```

Example 3: Job Completes without Errors

```
{
  "links": [
    {
      "rel": "self",
      "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobid>",
      "data": null,
      "action": "GET"
    }
 ],
  "details": "Processed - 3, Succeeded - 2, Failed - 1.",
  "status": 0,
  "items": [
    {
        "UserName":"<USERNAME>","Error Details": "User <USERNAME> is not
found. Verify that the user exists."
    }
 ]
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
"PUT");
String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
System.out.println(jobStatus);
} catch (Exception e) {
    e.printStackTrace();
}
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL.

```
funcUnassignRole() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/users"
    params="filename=$1&jobtype=UNASSIGN_ROLE&rolename=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="UnassignRole"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy.

```
def unassignUsersRoles(fileName, roleName) {
    String scenario = "Un-assigning users in " + fileName + " with role " +
roleName;
   String params = "jobtype=UNASSIGN ROLE&filename="+ fileName
+"&rolename="+ roleName;
    def url = null;
    def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```



Sample cURL Command Basic Auth

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -H'Content-Type: application/x-www-
form-urlencoded' -d
' jobtype=UNASSIGN_ROLE&filename=<CSV-FILE-NAME>&rolename=<ROLENAME>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Sample cURL Command OAuth 2.0

```
curl -X PUT --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H 'Content-
Type: application/x-www-form-urlencoded' -d
'jobtype=UNASSIGN_ROLE&filename=<CSV-FILE-NAME>&rolename=<ROLENAME>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Remove Users' Role Assignment (v2)

The Remover Users' Role Assignment (v2) REST API removes a pre-defined or application role from users provided in the REST API payload. To unassign a user from an application role, the user should exist in Oracle Enterprise Performance Management Cloud.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates that removing users from roles failed. With this API, you can see which records failed and the reason why they failed, in addition to how many records passed and failed.

This API is version v2.

Required Roles

For predefined roles:

Classic environments: Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

OCI environments: Service Administrator, or Identity Domain Administrator and any predefined role (Power User, User, or Viewer)

For application roles:

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/v2/role/unassign/user



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-23 Tasks for Unassign Users to Roles

Task	Request	REST Resource
Unassign role	PUT	/interop/rest/security/v2/role/unassign/user

Request

Supported Media Types: application/json

The following table summarizes the PUT request parameters.



Table 12-24 Parameters

Name	Description	Туре	Required	Default
rolename	The name of a pre-defined or application role applicable to the service. An incorrect role name will result in an error.	Payload	Yes	None
rolename	 to the service. An incorrect role name will result in an error. If identifies one of the following: If you are removing users from a pre-defined role, roleName should identify a pre-defined role applicable to the service. See "Understanding Predefined Roles" in Getting Started with Oracle Enterprise Performance Management Cloud for Administrators. Acceptable values for services other than Oracle Enterprise Data Management Cloud: Service Administrator Power User User (do not use Planner, which was used in earlier versions of the service) Viewer Acceptable values for Oracle Enterprise Data Management Cloud: Service Administrator User (administrator User (administrator User If you are removing users from an application role, roleName should identify an application role listed in the Manage Application Roles tab of Access Control. Acceptable values for FreeForm, Planning, Planning Modules, Sales Planning, Strategic Workforce Planning, Financial Consolidation and Close, and Tax Reporting applications: Approvals Administrator Approvals Queresion Ad Hoc Grid Creator Ad Hoc Grid Creator Ad Hoc Read Only User Calculation Manager Administrator Drill Through Run Integration 	Payload	Yes	None
	 Mass Allocation Task List Access Manager Acceptable values for Account Reconciliation: 			
	 Manage Alert Types 			
	 Manage Announcements 			
	 Manage Data Loads 			
	 Manage Data Loads Manage Organizations 			
	 Manage Organizations Manage Periods 			
	 Manage Periods Manage Profiles and Reconciliations 			
	 Reconciliation Manage Currencies Reconciliation Manage Public Filters and Lists 			
	· · · · · · · · · · · · · · · · · · ·			
	 Reconciliation Manage Reports 			

Table 12-24 (Cont.) Parameters

Name	Description	Туре	Required	Default
	 Reconciliation Manage Teams 			
	 Reconciliation Manage Users 			
	 Reconciliation Commentator 			
	 Reconciliation Preparer 			
	 Reconciliation Reviewer 			
	 Reconciliation View Jobs 			
	 Reconciliation View Profiles 			
	– View Audit			
	 View Periods 			
	 Acceptable values for Oracle Enterprise Data Management Cloudapplications: Application Creator Auditor 			
	– View Creator			
	 Acceptable values for Enterprise Profitability and Cost Management applications: Ad Hoc Grid Creator 			
	 Ad Hoc Read Only User 			
	- Ad Hoc User			
	- Clear POV Data			
	- Copy POV Data			
	 Create/Edit Rule 			
	- Create Integration			
	– Create Model			
	– Create POV			
	 Create Profit Curve 			
	 Delete Calculation History 			
	– Delete Model			
	- Delete POV			
	– Delete Rule			
	– Drill Through			
	- Edit POV Status			
	- Edit Profit Curve			
	 Mass Edit of Rules 			
	– Run Calculation			
	– Run Integration			
	– Run Profit Curve			
	- Run Rule Balancing			
	 Run Trace Allocation 			
	 Run Validation View Colorian Listers 			
	- View Calculation History			
	 View Model For a description of these values and "Managing Bala 			
	For a description of these roles, see "Managing Role Assignments at the Application Level" in Administering Access Control for Oracle Enterprise Performance Management Cloud.			
isers	List of user login IDs of the users whose role assignment is to be removed.	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/role/unassign/user

```
{
    "rolename": "Service Administrator",
    "users": [
        {
            "userlogin": "jdoe"
            },
        {
            "userlogin": "chris"
        }
    ]
}
```

Response

Supported Media Types: application/json

Nome	Description
Name	Description
links	Detailed information about the link and HTTP call type
status	Identifies the status of the operation
	0 - Operation Success
	• 1 - Operation Failed
error	Detailed information about the error
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed and reason for why it failed.

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/role/
unassign/user",
        "action": "PUT"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 3,
        "failed": 0,
        "faileditems": null
    }
}
```



Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/role/
unassign/user",
        "action": "PUT"
    },
    "status": 1,
    "error": {
        "error": {
            "errorcode": "EPMCSS-21008",
            "errormessage": "Failed to unassign role. Invalid role name
<rolename>. Please provide a valid role name."
    },
    "details": null
}
```

Example 3: Job Completes with Partial Errors

```
{
    "links": {
            "href": "https://<BASE-URL>/interop/rest/security/v2/role/
unassign/user",
            "action": "PUT"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
            {
                "userlogin": "jdoe",
                "errorcode": "EPMCSS-21010",
                "errormessage": "Failed to unassign role. User jdoe does not
exist. Provide a valid userlogin."
            },
            {
                "userlogin": "chris",
                "errorcode": "EPMCSS-21010",
                "errormessage": "Failed to unassign role. User chris does not
exist. Provide a valid userlogin."
            }
        1
    }
}
```

Sample cURL Command Basic Auth

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
-d '{"rolename":"<ROLENAME>","users":
```



```
[{"userlogin":"<USERLOGIN>"}, {"userlogin":"<USERLOGIN>"}]}' 'https://<BASE-
URL>/interop/rest/security/v2/role/unassign/user'
```

Sample cURL Command OAuth 2.0

```
curl -X PUT --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H 'Content-
Type: application/json' -d '{"rolename":"<ROLENAME>","users":
[{"userlogin":"<USERLOGIN>"}, {"userlogin":"<USERLOGIN>"}]}' 'https://<BASE-
URL>/interop/rest/security/v2/role/unassign/user'
```

Add Users to a Group (v1)

Adds a batch of users to an existing group in Access Control using an ANSI or UTF-8 encoded CSV file that was uploaded to the environment. Use the Upload REST API to upload the file. The file should be deleted after the API executes. The file format is as follows:

```
User Login
<user name>
<email>
```

Note:

A user is added to the group only if both these conditions are met:

- User login IDs included in the file exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain

This API should be run only by a service administrator in the identity domain where users are to be added to the group.

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the assignment of users to the group is complete. The presence of status -1 in the response indicates that the addition of users to a group is in progress. Any non-zero status except -1 indicates failure of adding users. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

This API is version 1.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

```
PUT /interop/rest/security/<api version>/groups
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-26 Tasks for Add Users to Group

Task	Request	REST Resource
Add users to group	PUT	/interop/rest/security/ <api_version>/groups</api_version>
Add users to group status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/ <jobid></jobid>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-27 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
jobtype	The string should have the value ADD_USERS_TO_GROUP. This value denotes that the users are being added to the group.	Form	Yes	None
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing the users to add, such as addUsersToGroup.csv.	Form	Yes	None
	The file must have been uploaded already using the Upload REST API.			
groupname	The name of group to which the users must be added. This group must be a pre-existing group.	Form	Yes	None

Response

Supported Media Types: application/json

Table 12-28 Parameters

Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status	
data	Parameters as key value pairs passed in the request	
items	Details about the resource	



Table 12-28 (Cont.) Parameters

Name	Description	
links	Details of the first URL to be requested to get the job details; rel is "Job Details"	

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
  "links": [
    {
     "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/groups",
      "data": {
        "jobType": "ADD USERS TO GROUP",
        "filename": "<fileName>",
        "groupName": "<groupName>",
     },
      "action": "GET"
    },
    {
      "rel": "Job Status",
     "href": "https://<EPM-CLOUD-BASE-URL>/interop/rest/security/
<api version>/jobs/<jobId>",
     "data": null,
      "action": "GET"
    }
 ],
 "details": null,
 "status": -1,
  "items": null
}
```

Example 2: Job Completes with Errors

```
{
  "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/
<jobID>",
        "data": null,
        "action": "GET"
     }
  ],
  "details": "Failed to add users to group. Input file <fileName> is not
found. Specify a valid file name.",
    "status": 1,
    "items": null
}
```



Example 3: Job Completes without Errors

```
{
  "links": [
    {
      "rel": "self",
      "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobId>",
      "data": null,
      "action": "GET"
    }
 ],
  "details": "Processed - 3, Succeeded - 2, Failed - 1.",
  "status": 0,
  "items": [
    {
        "UserName":"<USERNAME>","Error Details": "User <USERNAME> is not
found. Verify that the user exists."
    }
   ]
}
```

Sample Code

Java Sample Code

Prerequisites: json.jar

Common Functions: See: CSS Common Helper Functions for Java

```
public void addUsersToGroup(String fileName, String groupName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ADD USERS TO GROUP");
            reqParams.put("groupname", groupName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```



Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcAddUsersToGroup() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1&jobtype=ADD_USERS_TO_GROUP&groupname=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="AddUsersToGroup"
    statusMessage=$ (funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
Example 8-15 Groovy Sample Code
Common Functions: See CSS Common Helper Functions for Groovy.
def addUsersToGroup(fileName, groupName) {
    String scenario = "Adding users in " + fileName + " to group " +
groupName;
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def addUsersToGroup(fileName, groupName) {
    String scenario = "Adding users in " + fileName + " to group " +
groupName;
    String params = "jobtype=ADD USERS TO GROUP&filename="+ fileName
+"&groupname="+ groupName;
   def url = null;
   def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
       println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL



See CSS Common Helper Functions for Groovy

Add Users to a Group (v2)

The Add Users to a Group (v2) REST API adds a batch of users to an existing group provided in the REST API payload.

Note:

A user is added to the group only if both these conditions are met:

- User login IDs provided in payload should exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of adding users to group. With this API, you can see which records failed and the reason why they failed, in addition to how many records passed and failed.

This API is version v2.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/v2/groups/adduserstogroup

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-29 Tasks for Add Users to Group

Task	Request	REST Resource	
Add users to group	PUT	/interop/rest/security/v2/groups/adduserstogroup	

Request

Supported Media Types: application/json

The following table summarizes the PUT request parameters.



Name	Description	Туре	Required	Default
groupname	The name of the group to which the users must be added. This group must be a pre-existing group.	Payload	Yes	None
users	List of user login IDs of the users to add to the group.	Payload	Yes	None

Table 12-30 Parameters

Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/groups/adduserstogroup

Response

Supported Media Types: application/json

Table 12-31 Parameters

Name	Description	
links	Detailed information about the link and HTTP call type	
status	Identifies the status of the operation	
	• 0 - Operation Success	
	• 1 - Operation Failed	
error	Detailed information about the error	
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed and reason for why it failed.	

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
adduserstogroup",
        "action": "PUT"
    },
    "status": 0,
```

```
"error": null,
   "details": {
        "processed": 3,
        "succeeded": 3,
        "failed": 0,
        "faileditems": null
   }
}
```

Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
adduserstogroup",
        "action": "PUT"
    },
    "status": 1,
    "error": {
        "errorcode": "EPMCSS-21021",
        "errormessage": "Failed to add users to group. Group <groupname> does
not exist. Provide a valid groupname."
    },
    "details": null
}
```

Example 3: Job Completes with Partial Errors

```
"links": {
            "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
adduserstogroup",
            "action": "PUT"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
            {
                "userlogin": "jdoe",
                "errorcode": "EPMCSS-21031",
                "errormessage": "Failed to add user to group. User jdoe does
not exist. Provide a valid userlogin."
            },
            {
                "userlogin": "chris",
                "errorcode": "EPMCSS-21031",
                "errormessage": "Failed to add user to group. User chris does
not exist. Provide a valid userlogin."
            }
        ]
```



}

}

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"groupname":"G1","users":[{"userlogin":"jdoe"},{"userlogin":"chris"}]}'
'https://<BASE-URL>/interop/rest/security/v2/groups/adduserstogroup'
```

Remove Users from a Group (v1)

Removes users from a group listed in an ANSI or UTF-8 encoded CSV file from a group maintained in Access Control. You can use the Upload REST API to upload the file to the environment. The file format is as follows:

User Login jdoe john.doe@example.com

Note:

A user is removed from a group only if both of these conditions are met:

- User logins included in the file exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain

This API can be run only by a service administrator in the identity domain from which users are to be removed.

The presence of status -1 in the response indicates that the removal of users is in progress. Use the job status URI to determine whether the removal of users is complete. Any non-zero status except -1 indicates failure of removing users. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

This API is version v1.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/<api version>/groups



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-32 Tasks for Remove Users from Group

Task	Request	REST Resource
Remove users from group	PUT	/interop/rest/security/ <api_version>/groups</api_version>
Remove users from group status	GET	/interop/rest/security/ <api_version>/jobs/<jobid></jobid></api_version>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-33 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
jobtype	The string should have the value REMOVE_USERS_FROM_GROUP. This value denotes that the users are being removed from the group.	Form	Yes	None
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the users to be removed, for example, removeUsersFromGroup.csv.	Form	Yes	None
	The file must have been uploaded already using the Upload REST API.			
groupname	The name of group from which the users must be removed. This group must be a pre-existing group.	Form	Yes	None

Response

Supported Media Types: application/json

Table 12-34 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request



Table 12-34 (Cont.) Parameters

Name	Description
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
  "links": [
    {
      "rel": "self",
      "href": "https://<BASE-URL>/interop/rest/security/<api version>/groups",
      "data": {
        "jobType": "REST REMOVE USERS FROM GROUP",
        "filename": "<filename>"
        "groupName": "<groupName>"
     },
      "action": "PUT"
    },
    {
      "rel": "Job Status",
      "href": "https://<EPM-CLOUD-BASE-URL>/interop/rest/security/
<api version>/jobs/<jobID>",
     "data": null,
      "action": "GET"
    }
 ],
 "details": null,
  "status": -1,
 "items": null
}
```

Example 2: Job Completes with Errors

```
{
   "links": [
        {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/
<jobId>",
        "data": null,
        "action": "GET"
      }
   ],
   "details": "Failed to remove users. Input file <filename> is not found.
Specify a valid file name.",
   "status": 1,
```



"items": null

}

Example 3: Job Completes without Errors

```
{
  "links": [
    {
      "rel": "self",
     "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobId>",
      "data": null,
      "action": "GET"
    }
 ],
  "details": "Processed - 3, Succeeded - 2, Failed - 1.",
  "status": 0,
  "items": [
    {
         "UserName":"<USERNAME>","Error Details": "User <USERNAME> is not
found. Verify that the user exists."
   }
 ]
 }
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void removeUsersFromGroup(String roleName) {
        try {
                        String url = this.serverUrl + "/interop/rest/
security/" + apiVersion + "/groups";
                        Map<String, String> reqHeaders = new HashMap<String,</pre>
String>();
                        reqHeaders.put("Authorization", "Basic " +
DatatypeConverter
                                                          .printBase64Binary((th
is.userName + ":" + this.password).getBytes(Charset.defaultCharset())));
                        Map<String, String> reqParams = new HashMap<String,</pre>
String>();
                        reqParams.put("filename", fileName);
                         reqParams.put("jobtype","REMOVE USERS FROM GROUP);
                         reqParams.put("groupname", "groupName);
                        Map<String, String> restResult =
CSSRESTHelper.callRestApi(new HashMap(), url, reqHeaders, reqParams,
                                                         "PUT");
                        String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult);
                         System.out.println(jobStatus);
```



```
} catch (Exception e) {
    e.printStackTrace();
}
```

Shell Script Sample Code

}

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL.

```
funcRemoveUsersFromGroup() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1&jobtype=REMOVE_USERS_FROM_GROUP&groupname=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="RemoveUsersFromGroup"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def removeUsersFromGroup(fileName, groupName) {
    String scenario = "Removing users in " + fileName + " from group " +
groupName;
   String params = "jobtype=REMOVE USERS FROM GROUP&filename="+ fileName
+"&groupname="+ groupName;
   def url = null;
   def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
       getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



Remove Users from a Group (v2)

The Remove Users from a Group (v2) REST API removes a batch of users from an existing group provided in the REST API payload.

Note:

A user is removed from a group only if both of these conditions are met:

- User login IDs included in the request payload should exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of removing users from group. With this API, you can see which records failed and the reason why they failed, in addition to how many records passed and failed.

This API is version v2.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/v2/groups/removeusersfromgroup

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-35 Tasks for Remove Users from Group

Task	Request	REST Resource
Remove users from group	PUT	/interop/rest/security/v2/groups/removeusersfromgroup

Request

Supported Media Types: application/json

The following table summarizes the request parameters.



Name	Description	Туре	Required	Default
groupname	The name of group from which the users must be removed. This group must be a pre-existing group.	Payload	Yes	None
users	List of userlogin IDs of the users to be removed from group.	Payload	Yes	None

Table 12-36 Parameters

Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/groups/removeusersfromgroup

Response

Supported Media Types: application/json

Table 12-37 Parameters

Name	Description Detailed information about the link and HTTP call type	
links		
status	 Identifies the status of the operation 0: Operation Success 1: Operation Failed 	
error	Detailed information about the error	
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed and reason for why it failed.	

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
removeusersfromgroup",
        "action": "PUT"
    },
```



```
"status": 0,
"error": null,
"details": {
    "processed": 3,
    "succeeded": 3,
    "failed": 0,
    "faileditems": null
}
```

}

Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
removeusersfromgroup",
        "action": "PUT"
    },
    "status": 1,
    "error": {
        "errorcode": "EPMCSS-21022",
        "errormessage": "Failed to remove users from group. Group <groupname>
does not exist. Provide a valid groupname."
    },
    "details": null
}
```

Example 3: Job Completes with Partial Errors

```
{
   "links": {
            "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
removeusersfromgroup",
            "action": "PUT"
   },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
            {
                "userlogin": "jdoe",
                "errorcode": "EPMCSS-21032",
                "errormessage": "Failed to remove user from group. User jdoe
does not exist. Provide a valid userlogin."
            },
            {
                "userlogin": "chris",
                "errorcode": "EPMCSS-21032",
                "errormessage": "Failed to remove user from group. User chris
does not exist. Provide a valid userlogin."
           }
```

] }

Sample cURL command

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"groupname":"G1","users":[{"userlogin":"jdoe"}, {"userlogin":"chris"}]}'
'https://<BASE-URL>/interop/rest/security/v2/groups/removeusersfromgroup'
```

Update Users

Modifies attributes such as email, first name, and last name of Oracle Enterprise Performance Management Cloud users in an identity domain using the new values identified in an ANSI or UTF-8 encoded comma-separated value (CSV) file that was uploaded to the environment. Before using this API, use the Upload REST API to upload the file. Use double quotation marks to enclose fields that contain space charaters in the CSV file. The file should be deleted after the API executes. The file format is as follows:

Firt Name, Last Name,Email, User Login
Jane,Doe,<emailAddress>,jdoe
John,Doe,<emailAddress>,<emailAddress>

This API should be run only by Service Administrators who are also assigned to the Identity Domain Administrator role in the identity domain in which users are to be updated. The CSV file should not include the account of the user who executes this command. It updates all properties of the user identified by *User Login*. Because user accounts are common to all service environments that an Identity Domain Administrator supports, updating an account for one environment updates it for all environments that share the Identity Domain.

With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

The API is asynchronous and returns the Job ID. The presence of status -1 in the response indicates that the updating of users is in progress. Use the job status URI to determine whether the process is complete. Any non-zero status except -1 indicates failure.

This API is version v1.

Required Roles

Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

REST Resource

PUT /interop/rest/security/<api verion>/users



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-38 Tasks for Updating Users

Task	Request	REST Resource
Update users	PUT	/interop/rest/security/ <api_verion>/users</api_verion>
Update users status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/ <jobid></jobid>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-39 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
jobtype	UPDATE_USERS	Form	Yes	None
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing the users to update, such as updateUsers.csv.	Form	Yes	None

Response

Supported Media Types: application/json

Table 12-40 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Examples of Response Body

The following examples show the contents of the response body in JSON format:



Example 1: Job is in Progress

```
{
    "links": [
        {
            "rel": "self",
            "href": " https://<BASE-URL>/interop/rest/security/<api version>/
users",
            "data": {
                "jobType": "UPDATE USERS",
                "filename": "<filename>"
            },
            "action": "UPDATE"
        },
        {
            "rel": "Job Status",
            "href": " https://<EPM-CLOUD-BASE-URL>/interop/rest/security/
<api version>/jobs/<jobID>",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```

Example 2: Job Completes with Errors

```
{
"links": [
{
    "rel": "self",
    "href": "https://<BASE-URL>/interop/rest/security/
<api_version>/jobs/",
    "data": null,
    "action": "GET"
}
],
"details": "Failed to update users. Input file <filename> not found. Specify
a valid file name.",
    "status": 1,
    "items": null
}
```

Example 3: Job Completes without Errors

```
{
"links": [
{
"rel": "self",
"href": "https://<BASE-URL>/interop/rest/security/
<api_version>/jobs/",
"data": null,
"action": "GET"
```



Java Sample Code

```
Prerequisites: json.jar
Common Functions: See: CSS Common Helper Functions for Java
    public void updateUsers(String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "UPDATE USERS");
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcUpdateUsers() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/users"
    params="filename=$1&jobtype=UPDATE_USERS"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="UpdateUsers"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
```



```
echo $statusMessage
}
Groovy Sample Code
Common Functions: See CSS Common Helper Functions for Groovy
def updateUsers(fileName) {
    String scenario = "Updating users from " + fileName ;
    String params = "jobtype=UPDATE USERS&filename="+ fileName;
    def url = null;
    def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
```

Sample cURL Command Basic Auth

```
curl -X PUT -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/x-www-
form-urlencoded' -d
'jobtype=UPDATE_USERS&filename=<CSV-FILE-NAME>' 'https://<BASE-URL>/interop/
rest/security/v1/users'
```

Sample cURL Command OAuth 2.0

```
curl -X PUT --header "Authorization: Bearer <OAUTH_ACCESS_TOKEN>" -H
'Content-Type: application/x-www-form-urlencoded' -d
'jobtype=UPDATE_USERS&filename=<CSV-FILE-NAME>'
'https://<BASE-URL>/interop/rest/security/v1/users'
```

Add a User to a Batch of Groups

Adds an existing user to a batch of groups in Access Control using an ANSI or UTF-8 encoded CSV file that was uploaded to the environment. Use the Upload REST API to upload the file. The file should be deleted after the API executes. With this API, you can see which records



failed and the reason why they failed in addition to how many records passed and failed. The file format is as follows:

Group Name GroupA GroupB

The user is added to the groups only if these conditions are met:

- · The user must exist in the identity domain that services the environment
- The user must be assigned to a pre-defined role in the identity domain
- The groups provided must exist in Access Control and must not be pre-defined groups

Additionally, the user running this API must be authorized to perform this action. This API should be run only by a service administrator in the environment where the user is to be added to the groups.

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the assignment of a user to the groups is complete. The presence of status -1 in the response indicates that the addition of a user to groups is in progress. Any non-zero status except -1 indicates failure of adding a user.

This API is version v1.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/<api_version>/groups

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-41 Tasks for Adding a User to a Batch of Groups

Task	Request	REST Resource
Add a user to groups	PUT	/interop/rest/security/ <api_version>/groups</api_version>
Add a user to groups status	GET	/interop/rest/security/ <api_version>/jobs/<jobid></jobid></api_version>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.



Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
jobtype	The string should have the value ADD_USER_TO_GROUPS. This value denotes that the user is being added to the groups.	Form	Yes	None
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing the groups to add the user to, such as addUserToGroups.csv.	Form	Yes	None
	The file must have been uploaded already using the Upload REST API.			
	File format example:			
	Group Name GroupA GroupB			
username	The name of the user to add to the provided list of groups. This user must already exist.	Form	Yes	None

Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Table 12-43 Parameters

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "links": [
        {
            "href": https://<BASE-URL>/interop/rest/security/<api_version>/
     groups,
            "rel": "self",
```

```
"data": {
                "jobType": "ADD_USER_TO_GROUPS",
                "filename": "<filename>",
                "username": "<username>"
            },
            "action": "PUT"
        },
        {
            "href": https://<EPM-CLOUD-BASE-URL>/interop/rest/security/
<api version>/jobs/<jobId>,
            "rel": "Job Status",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```

Example 2: Job Completes with Errors

```
{
  "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/v1/jobs/<jobID>",
        "data": null,
        "action": "GET"
    }
  ],
  "details": "Failed to add user to groups. Input file <fileName> is not
found. Specify a valid file name.",
    "status": 1,
    "items": null
}
```

Example 3: Job Completes without Errors

```
{
  "links": [
    {
      "rel": "self",
      "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobId>",
      "data": null,
      "action": "GET"
   }
  ],
  "details": "Processed - 3, Succeeded - 2, Failed - 1.",
  "status": 0,
  "items": [
    {
            "GroupName":"<GROUPNAME>","Error Details": "Group <GROUPNAME> is
not found. Verify that the group exists."
```

```
}
 1
}
Java Sample Code
Prerequisites: json.jar
Common Functions: See: CSS Common Helper Functions for Java
public void addUserToGroups(String fileName, String userName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ADD USER TO GROUPS");
            reqParams.put("username", userName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcAddUserToGroups() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1&jobtype=ADD_USER_TO_GROUPS&username=$2"
    header="Content-Type: application/x-www-form-urlencoded"
    cssRESTAPI="AddUserToGroups"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```



Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def addUserToGroups(fileName, userName) {
    String scenario = "Adding users in " + fileName + " to group " + userName;
    String params = "jobtype=ADD USER TO GROUPS&filename="+ fileName
+"&username="+ userName;
    def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Remove a User from a Batch of Groups

Removes a user from a batch of groups listed in an ANSI or UTF-8 encoded CSV file maintained in Access Control. You can use the Upload REST API to upload the file to the environment. The file format is as follows:

Group Name GroupA GroupB

A user is removed from groups only if these conditions are met:

- The user must exist in the identity domain that services the environment
- The user must be assigned to a pre-defined role in the identity domain
- The groups provided must exist in Access Control and must not be pre-defined groups

Additionally, the user running this API must be authorized to perform this action. This API should be run only by a service administrator in the environment where a user is to be removed from the groups. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

The presence of status -1 in the response indicates that the removal in progress. Use the job status URI to determine whether the removal is complete. Any non-zero status except -1 indicates failure.

This API is version v1.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

PUT /interop/rest/security/<api_version>/groups

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-44 Tasks for Remove a User from a Batch of Groups

Task	Request	REST Resource
Remove a user from groups	PUT	/interop/rest/security/< <i>api_version</i> >/groups
Remove a user from groups status	GET	/interop/rest/security/ <api_version>/jobs/<jobid></jobid></api_version>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-45 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
jobtype	The string should have the value REMOVE_USER_FROM_GROUPS. This value denotes that the user is being removed from the groups.	Form Yes Non that the		
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the groups from which the user is to be removed, for example, removeUserFromGroups.csv.	Form	Yes	None
	The file must have been uploaded already using the Upload REST API.			
	File format:			
	Group Name			
	GroupA			
	GroupB			
username	The name of the user to remove from the provided list of groups. This user must already exist.	Form	Yes	None

Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Table 12-46 Parameters

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "links": [
       {
            "href": https://<BASE-URL>/interop/rest/security/<api version>/
groups,
            "rel": "self",
            "data": {
                "jobType": "REMOVE USER FROM GROUPS",
                "filename": "<filename>",
                "username": "<username>"
            },
            "action": "PUT"
        },
        {
            "href": https://<EPM-CLOUD-BASE-URL>/interop/rest/security/
<api version>/jobs/<jobId>,
            "rel": "Job Status",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```



Example 2: Job Completes with Errors

```
{
   "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/jobs/
<jobId>",
        "data": null,
        "action": "GET"
    }
  ],
  "details": "Failed to remove user from groups. File <filename> is not
found. Specify a valid file name.",
    "status": 1,
    "items": null
}
```

Example 3: Job Completes without Errors

```
{
  "links": [
    {
      "rel": "self",
      "href": "https://<BASE-URL>/interop/rest/security/<api version>/jobs/
<jobId>",
      "data": null,
      "action": "GET"
   }
 ],
  "details": "Processed - 3, Succeeded - 1, Failed - 2.",
  "status": 0,
  "items": [
    {
        "GroupName":"<GROUPNAME>","Error Details": "Group <GROUPNAME> is not
found. Verify that the group exists."
   },
         "GroupName":"<GROUPNAME>","Error Details": "Group <GROUPNAME> is not
found. Verify that the group exists."
   }
 1
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void removeUserFromGroups(String fileName, String userName) {
    try {
        String url = this.serverUrl + "/interop/rest/security/" +
        apiVersion + "/groups";
        Map<String, String> reqHeaders = new HashMap<String, String>();
```

```
reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "REMOVE USER FROM GROUPS");
            reqParams.put("username", userName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL.

```
funcRemoveUserFromGroups() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1&jobtype=REMOVE_USER_FROM_GROUPS&username=$2"
    header="Content-Type: application/x-www-form-urlencoded"
    cssRESTAPI="RemoveUserFromGroups"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

```
J
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def removeUserFromGroups(fileName, userName) {
    String scenario = "Removing users in " + fileName + " from group " +
    userName;
    String params = "jobtype=REMOVE_USER_FROM_GROUPS&filename="+ fileName
+"&username="+ userName;
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
    groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
```

```
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
    "GET");
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Add Groups (v1)

Adds groups in Access Control using an ANSI or UTF-8 encoded CSV file that was uploaded to the environment. Use the Upload REST API to upload the file. The file should be deleted after the API executes. The file format is as follows:

Group Name, Description GroupA, GroupADescription GroupB, GroupBDescription

The user running this API must be authorized to perform this action. This API should be run only by a service administrator in the environment where groups are to be added. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether adding groups is complete. The presence of status -1 in the response indicates that the addition is in progress. Any non-zero status except -1 indicates failure of adding a group.

This API is version v1.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

POST /interop/rest/security/<api version>/groups

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Task	Request	REST Resource
Create groups	POST	/interop/rest/security/ <api_version>/groups</api_version>
Create groups status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/ <jobid></jobid>

Table 12-47 Tasks for Adding a Batch of Groups

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-48 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing the groups to add, such as addGroups.csv.	Form	Yes	None
	The file must have been uploaded already using the Upload REST API.			
	File format example:			
	Group Name, Description			
	GroupA, GroupADescription			
	GroupB, GroupBDescription			

Response

Supported Media Types: application/json

Table 12-49 Parameters

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request
items	Details about the resource
links	Details of the first URL to be requested to get the job details; rel is "Job Details"

Examples of Response Body

The following examples show the contents of the response body in JSON format:



Example 1: Job is in Progress

```
{
    "links": [
        {
            "href": "http://<BASE-URL>/interop/rest/security/<api version>/
groups",
            "rel": "self",
            "data": {
                "jobType": "ADD GROUPS",
                "filename": "<filename>"
            },
            "action": "POST"
        },
        {
            "href": "http://<BASE-URL>/interop/rest/security/<api version>/
jobs/<jobId ",
            "rel": "Job Status",
            "data": null,
            "action": "GET"
        }
    ],
    "status": -1,
    "details": null,
    "items": null
}
```

Example 2: Job Completes with Errors

```
{
    "links": [
        {
            "href": "http://<BASE-URL>/interop/rest/security/<api version>/
groups",
            "rel": "self",
            "data": {
                "jobType": "ADD GROUPS",
                "filename": ""
            },
            "action": "POST"
        }
   ],
    "status": 1,
    "details": "EPMCSS-20671: Failed to create groups. Invalid or
insufficient parameters specified. Provide all required parameters for the
REST API. ",
    "items": null
}
```

Example 3: Job Completes without Errors



```
"action": "GET",
            "href": " http://<BASE-URL>/interop/rest/security/<api version>/
jobs/<jobId>",
            "rel": "self"
        }
    ],
    "status": 0,
    "details": "Processed - 4, Succeeded - 3, Failed - 1. ",
   "items": [
    {
        "GroupName":"<GROUPNAME>","Error Details": "Failed to create a group
with the name <GROUPNAME>. This group already exists in the system. Provide a
different group name."
     }
   1
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See: CSS Common Helper Functions for Java

```
public void addGroups(String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcAddGroups() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
```



```
cssRESTAPI="addGroups"
statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def addGroups(fileName) {
    String scenario = "Creating Groups in " + fileName;
    String params = "filename="+ fileName;
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Add Groups (v2)

The Add Groups (v2) REST API adds groups that are provided in the request payload. These groups can be viewed in Access Control.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The user running this API must be authorized to perform this action. This API should be run only by a Service Administrator in the environment where groups are to be added. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of adding groups.

This API is version v2.



Required Roles

Service Administrator or Access Control - Manage

REST Resource

POST /interop/rest/security/v2/groups/add

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-50 Tasks for Add Users to Group

Teek	Deguest	
Task	Request	REST Resource
Add groups	POST	/interop/rest/security/v2/groups/add
	Request	
	Supported Mec	lia Types: application/json

The following table summarizes the POST request parameters.

Table 12-51 Parameters

Name	Description	Туре	Required Default	
groups	List of groups to add.	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/security/v2/groups/add

```
{
    "groups":
    [
        {
            "groupname": "GroupA",
            "description": "GroupADescription"
        },
        {
            "groupname": "GroupB",
            "description": "GroupBDescription"
        }
    ]
}
```



Response

Supported Media Types: application/json

Name	Description
links	Detailed information about the link and HTTP call type
status	Identifies the status of the operation
	0 - Operation succeeded
	• 1 - Operation failed
error	Detailed information about the error
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed, and the reason for why they failed.

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/add",
        "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 2,
        "failed": 0,
        "faileditems": null
    }
}
```

Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/add",
        "action": "POST"
    },
    "status": 1,
    "error": {
        "errorcode": "EPMCSS-21119",
        "errormessage": "Failed to add groups. Invalid or insufficient
parameters specified. Provide all required parameters for the REST API."
    },
    "details": null
}
```



Example 3: Job Completes with Partial Errors

```
{
    "links": {
            "href": "https://<BASE-URL>/interop/rest/security/v2/groups/add",
            "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
        {
                         "groupname": "GroupA",
                         "errorcode": "EPMCSS-21140",
                         "errormessage": "Failed to add group. Group already
exists in System. Provide different group name."
               },
                {
                         "groupname": "GroupB",
                         "errorcode": "EPMCSS-21140",
                         "errormessage": "Failed to add group. Group already
exists in System. Provide different group name."
                }
        1
    }
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"groups":[{"groupname":"GroupA","description":"GroupADescription"},
{"groupname":"GroupB","description":"GroupBDescription"}]}'
'https://<BASE-URL>/interop/rest/security/v2/groups/add'
```

Remove Groups (v1)

Removes groups listed in an ANSI or UTF-8 encoded CSV file maintained in Access Control. You can use the Upload REST API to upload the file to the environment. The file format is as follows:

Group Name GroupA GroupB

The user running this API must be authorized to perform this action. This API should be run only by a service administrator in the environment where a group is to be removed.

The presence of status -1 in the response indicates that the removal in progress. Use the job status URI to determine whether the removal is complete. Any non-zero status except -1



indicates failure. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

This API is version v1.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

DELETE /interop/rest/security/<api_version>/groups

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-53 Tasks for Remove Groups

Task	Request	REST Resource
Remove groups	DELETE	/interop/rest/security/< <i>api_version</i> >/groups
Remove groups status	GET	/interop/rest/security/< <i>api_version</i> >/jobs/< <i>jobId</i> >

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-54 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
filename	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the groups to be removed, for example, removeGroups.csv.	Query	Yes	None
	The file must have been uploaded already using the Upload REST API.			
	Group Name GroupA GroupB			

Response

Supported Media Types: application/json



Name	Description	
details	In the case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Possible values: self or Job Status. If the value is set to Job Status, you can use the href to get the status	
data	Parameters as key value pairs passed in the request	
items	Details about the resource	
links	Details of the first URL to be requested to get the job details; rel is "Job Details"	

Table 12-55 Parameters

Examples of Resonse Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "status": -1,
    "items": null,
    "links": [
        {
            "href": " http://<BASE-URL>/interop/rest/security/<api_version>/
groups?filename=<filename>",
            "rel": "self",
            "data": {
                "jobType": "REMOVE GROUPS",
                "filename": "<filename>"
            },
            "action": "DELETE"
        },
        {
            "href": " http://<BASE-URL>/interop/rest/security/<api version>/
jobs/<jobId>",
            "rel": "Job Status",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null
}
```

Example 2: Job Completes with Errors

```
groups",
    "rel": "self",
    "data": {
        "jobType": "REMOVE_GROUPS",
        "filename": ""
        },
        "action": "DELETE"
     }
    ],
    "status": 1,
     "details": "EPMCSS-20673: Failed to delete groups. Invalid or
insufficient parameters specified. Provide all required parameters for the
REST API. ",
     "items": null
}
```

Example 3: Job Completes without Errors

```
{
    "links": [
        {
            "data": null,
            "action": "GET",
            "href": " http://<BASE-URL>/interop/rest/security/<api version>/
jobs/<jobId>",
            "rel": "self"
        }
   ],
   "status": 0,
    "details": "Processed - 3, Succeeded - 2, Failed - 1. ",
    "items": [
    {
        "GroupName":"<GROUPNAME>","Error Details": "Group <GROUPNAME> is not
found. Verify that the group exists."
     }
   1
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void removeGroups(String fileName) {
    try {
        String url = this.serverUrl + "/interop/rest/security/" +
    apiVersion + "/groups";
        Map<String, String> reqHeaders = new HashMap<String, String>();
        reqHeaders.put("Authorization", "Basic " + DatatypeConverter
            .printBase64Binary((this.userName + ":" +
    this.password).getBytes(Charset.defaultCharset())));
    Map<String, String> reqParams = new HashMap<String, String>();
        reqParams.put("filename", fileName);
    }
}
```

```
Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                "DELETE");
        String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
        System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL.

```
FuncRemoveGroups() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="removeGroups"
    statusMessage=$(funcCSSRESTHelper "DELETE" "$url" "$header"
    "$USERNAME" "$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def removeGroups(fileName) {
    String scenario = "Deleting Groups in " + fileName;
    String params = null;
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups?filename=" + fileName);
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "DELETE", null, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
```

Common Functions

See Common Helper Functions for Java

- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Remove Groups (v2)

The Remove Groups (v2) REST API remove groups that are provided into request payload. These groups are maintained in Access Control.

This topic describes the simplified v2 version of this REST API. This version contains all parameters in the payload and does not require URL encoding while calling the REST APIs. This makes the v2 API easier to use.

The user running this API must be authorized to perform this action. This API should be run only by a Service Administrator in the environment where groups are to be removed. With this API, you can see which records failed and the reason why they failed in addition to how many records passed and failed.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of adding groups.

This API is version v2.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

POST /interop/rest/security/v2/groups/remove

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-56 Tasks for Remove Groups

Task	Request	REST Resource
Remove groups	POST	/interop/rest/security/v2/groups/remove

Request

Supported Media Types: application/json

The following table summarizes the POST request parameters.

Table 12-57 Parameters

Name	Description	Туре	Required	Default
groups	List of groups to remove.	Payload	Yes	None



Example URL and Payload

```
{
    "groups":
    [
    {
        "groupname": "GroupA"
    },
    {
        "groupname": "GroupB"
    }
    ]
}
```

https://<BASE-URL>/interop/rest/security/v2/groups/remove

Response

Supported Media Types: application/json

Table 12-58	Parameters
-------------	------------

Name	Description
links	Detailed information about the link and HTTP call type
status	Identifies the status of the operation
	 0 - Operation succeeded 1 - Operation failed
error	Detailed information about the error
details	Detailed status of the operation performed. Total number of records processed, succeeded, and failed, and the reason for why they failed.

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job Completes without Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
remove",
        "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 2,
        "failed": 0,
        "faileditems": null
    }
}
```



Example 2: Job Completes with Errors

```
{
    "links": {
        "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
remove",
        "action": "POST"
    },
    "status": 1,
        "error": {
            "errorcode": "EPMCSS-21120",
               "errormessage": "Failed to remove groups. Invalid or
insufficient parameters specified. Provide all required parameters for the
REST API."
        },
        "details": null
}
```

Example 3: Job Completes with Partial Errors

```
{
    "links": {
            "href": "https://<BASE-URL>/interop/rest/security/v2/groups/
remove",
            "action": "POST"
    },
    "status": 0,
    "error": null,
    "details": {
        "processed": 5,
        "succeeded": 3,
        "failed": 2,
        "faileditems":
        ſ
        {
                        "groupname": "GroupA",
                        "errorcode": "EPMCSS-21125",
                        "errormessage": "Failed to remove group. GroupA
does not exist. Provide a valid groupname."
                },
                {
                       "groupname": "GroupB",
                        "errorcode": "EPMCSS-21125",
                        "errormessage": "Failed to remove group. Group GroupB
does not exist. Provide a valid groupname."
                }
        ]
    }
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
```



'{"groups":[{"groupname":"GroupA"},{"groupname":"GroupB"}]}' 'https://<BASE-URL>/interop/rest/security/v2/groups/remove'

User Group Report (v1)

Generates a User Group Report of users in the system and writes the report to the filename provided. This report lists the direct or indirect membership of users assigned to the group. It can be downloaded using the Download API.

The report indicates whether the user assignment to group is direct (as member of a group) or indirect (as member of a group that is a child of a nested group). The report identifies the user's login name, first name, last name, email address, assigned group, and type of assignment in the following format. It is identical to the CSV version of the report created from the User Group Report tab in Access Control.

For example, assume that user jdoe is a member of group Test1, which is a child of nested group Test2. In this scenario, the report will display the following information for jdoe:

User, First Name, Last Name, Email, Direct, Group

jdoe, John, Doe, jdoe@example.com, Yes, test1

jdoe, John, Doe, jdoe@example.com, No, test2

This is an asynchronous job and returns the Job ID.

This API is version v1.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- · Any predefined role and the Access Control View application role

REST Resource

POST /interop/rest/security/<api version>/usergroupreport

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-59 Tasks for User Group Report

Task	Request	REST Resource
User Group Report	POST	
		/interop/rest/security/ <api version="">/usergroupreport</api>



Task	Request	REST Resource
User Group Report Status	GET	/interop/rest/security/ <api_version>/jobs/<jobid></jobid></api_version>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-60Parameters

Name	Description	Туре	Required	Default
api_version	The specific API version, v1	Path	Yes	None
filename	The name of the file where the report is to be populated, such as userGroupReport.csv.	Form	Yes	None

Response

Supported Media Types: application/json

Table 12-61 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
   "details": null,
   "links": [
      {
        "href": "https://<BASE-URL>/interop/rest/security/<api_version>/
        usergroupreport",
        "rel": "self",
        "data": {
            "jobType": "GENERATE_USER_GROUP_REPORT",
            "intervalue")
```



Example 2: Job Completes with Errors

Example 3: Job Completes without Errors

```
{
   "details": null,
   "links": [
        {
         "href": "https://<BASE-URL>/interop/rest/security/<api_version>/
        jobs/<jobid>",
                                "rel": "self",
                              "data": null,
                             "action": "GET"
        }
        j,
        "status": 0,
        "items": null
}
```

Java Sample Code

Prerequisites: json.jar



Common Functions: See Common Helper Functions for Java

```
11
// BEGIN
11
public void generateUserGroupReport(String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/usergroupreport";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            regParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, regHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
// END
//
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcGenerateUserGroupReport() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/usergroupreport"
    params="filename=$1"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="generateUserGroupReport"
    statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def generateUserGroupReport(fileName) {
   String scenario = "Generating User Group Report in " + fileName;
   String params = "jobtype=GENERATE_USER_GROUP_REPORT&filename="+ fileName;
```



```
def url = null;
def response = null;
try {
    url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
usergroupreport");
} catch (MalformedURLException e) {
    println "Please enter a valid URL"
    System.exit(0);
}
response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
if (response != null) {
    getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

User Group Report (v2)

Generates a User Group Report for users in the system.

This report lists the direct or indirect membership of users assigned to the group. You can create a query for a specific user or a group or a combination of users and groups.

The report indicates whether the user assignment to an EPM group is direct (as member of a group) or indirect (as member of a group that is a child of a nested group). The report identifies the user's login name, first name, last name, email address, assigned group, and type of assignment.

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure in generating a User Group Report.

This API is version v2.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

GET /interop/rest/security/v2/report/usergroupreport?
userlogin=<userlogin>&groupname=<groupname>






	Table 12-62	Tasks for User Gro	oup Report
--	-------------	--------------------	------------

Task	Request	REST Resource
User Group	GET	/interop/rest/security/v2/report/usergroupreport?
Report		userlogin=< userlogin>&groupname= <groupname></groupname>

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 12-63 Request Parameters

Name	Description	Туре	Required	Default
userlogin	Generate usergroupreport for the specified user.	Query	No	The report is created for all users.
groupname	Generate usergroupreport for the users belonging to the specified group name.	Query	No	The report is created for all groups.

Response

Supported Media Types: application/json

Table 12-64 Response Parameters

Parameters	Description
links	Detailed information about the link
status	Status of the operation0: Operation succeeded1: Operation failed
error	Detailed information about the error
details	Records matching the request

Examples of Response Body

The following show examples of the response body in JSON format.

Example 1: REST API Issued without userlogin and groupname Query Parameters Completes without Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
```



```
usergroupreport",
    "action": "GET"
 },
 "status": 0,
  "error": null,
  "details": [
    {
      "userlogin": "Jade",
      "firstname": "Jade",
      "lastname": "Clark",
      "email": "jade.clark@example.oracle.com",
      "groups": [
        {
          "direct": "Yes",
          "groupname": "Interactive User"
        },
        {
          "direct": "No",
          "groupname": "Strategic Planner"
        }
      ]
    },
    {
      "userlogin": "Jeff",
      "firstname": "Jeff",
      "lastname": "Clark",
      "email": "jeff.clark@discard.oracle.com",
      "groups": [
        {
          "direct": "Yes",
          "groupname": "Analyst"
        },
        {
          "direct": "No",
          "groupname": "Strategic Planner"
        }
      ]
    }
 ]
}
```

Example 2: REST API Issued with userlogin and groupname Query Parameters Completes without Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
usergroupreport? userlogin='Jade'&groupname='Interactive User'",
    "action": "GET"
   },
   "status": 0,
   "error": null,
   "details": [
    {
        "userlogin": "Jade",
        "userlogin": "Jade",
        "
}
```



```
"firstname": "Jade",
"lastname": "Clark",
"email": "jade.clark@example.oracle.com",
"groups": [
        {
            "direct": "Yes",
            "groupname": "Interactive User"
        }
    ]
}
```

}

Example 3: REST API Issued Only with a userlogin Query Parameter Completes without Errors

```
{
  "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
usergroupreport?userlogin='Jade'",
    "action": "GET"
 },
 "status": 0,
  "error": null,
  "details": [
    {
      "userlogin": "Jade",
      "firstname": "Jade",
      "lastname": "Clark",
      "email": "jade.clark@example.oracle.com",
      "groups": [
        {
          "direct": "Yes",
          "groupname": "Interactive User"
        },
        {
          "direct": "No",
          "groupname": "Strategic Planner"
        }
      ]
    }
 1
}
```

Example 4: REST API Issued Only with a groupname Query Parameter Completes without Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
usergroupreport?groupname='Strategic Planner'",
    "action": "GET"
   },
   "status": 0,
   "error": null,
```



```
"details": [
   {
      "userlogin": "Jade",
      "firstname": "Jade",
      "lastname": "Clark",
      "email": "jade.clark@example.oracle.com",
      "groups": [
         {
          "direct": "No",
          "groupname": "Strategic Planner"
        }
     ]
    },
    {
     "userlogin": "Jeff",
      "firstname": "Jeff",
      "lastname": "Clark",
      "email": "jeff.clark@example.oracle.com",
      "groups": [
        {
          "direct": "No",
          "groupname": "Strategic Planner"
        }
     ]
    }
 ]
}
```

Example 5: Job Completes with Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
usergroupreport",
    "action": "GET"
   },
   "status": 1,
   "error": {
        "error": {
            "errormessage": "Failed to generate User Group Report. Authorization
failed. Please provide valid authorized user."
    },
    "details": null
}
```

Sample cURL Commands

Sample cURL command using Basic Auth

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/report/usergroupreport'
```

curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/report/usergroupreport?
userlogin=< userlogin>&groupname=<groupname>

Sample cURL command using oAuth

```
curl --location --request GET 'https://<BASE-URL>/interop/rest/security/v2/
report
/usergroupreport' --header "Authorization: Bearer <OAUTH_TOKEN>"
```

```
curl --location --request GET 'https://<EPM-CLOUD-BASE-URL>/interop/rest/
security/v2/report
/usergroupreport/?userlogin=< userlogin>&groupname=<groupname>' --header
"Authorization: Bearer <OAUTH TOKEN>"
```

User Access Report (v1)

Generates an access report of users in the system and writes the report to the filename provided. This report can then be downloaded using the download command.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

This API is version v1.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

```
POST /interop/rest/{api_version}/reports?
q={type:provisionreport,fileName:provreport.csv,format:simplified,usertype,servic
eusers}
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Table 12-65	Tasks for	User	Access	Report
-------------	-----------	------	--------	--------

Task	Request	REST Resource
User Access Report	POST	<pre>/interop/rest/{api_version}/reports? q={type:provisionreport,fileName:provreport.csv,format:s implified,usertype:serviceusers}</pre>

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 12-66 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
fileName	File where report is to be populated	Query	Yes	None
type	Type of report being generated: provisionreport	Query	Yes	None
format	The format of the csv file, classic or simplified	Query	No	classic
usertype	Wheter to generate the report only for Identity Domain Administrators, IDAdmins or ServiceUsers	Query	No	ServiceU sers

Response

Supported Media Types: application/json

Table 12-67 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

Example 1: Job is in Progress

```
{
    "links": [
        {
            "rel": "self",
            "href": "https://<BASE-URL>/interop/rest/{api_version}/reports?
q={type=provisionreport,fileName=provreport.csv,format=simplified,usertype=ser
```

```
viceusers}",
    "data": null,
    "action": "POST"
    },
    {
        "rel": "Job Status",
        "href": "https://<BASE-URL>/interop/rest/v1/reports/
3180399797144693",
        "data": null,
        "action": "GET"
     }
    ],
    "status": -1,
    "details": null
}
```

Java Sample – ProvisionReport.java

Prerequisites: json.jar

Common Functions: See Common Helper Functions for Java

```
11
// BEGIN
11
public void provisionReport (String fileName, String type) throws Exception {
    JSONObject params = new JSONObject();
   params.put("fileName",java.net.URLEncoder.encode(fileName));
   params.put("type", java.net.URLEncoder.encode(type));
   params.put("format", "simplified");
    params.put("usertype", "usertype", "serviceusers"));
   String urlString = String.format("%s/interop/rest/%s/reports?q=%s",
serverUrl, lcmVersion, params.toString());
   String response = executeRequest(urlString, "POST", params.toString(),
"application/x-www-form-urlencoded");
   getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
}
11
// END
11
```

cURL Sample - provisionreport.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcProvisionReport () {
    url=$SERVER_URL/interop/rest/$LCM_VERSION/reports/
    param=$ (echo
"q={type:$reporttype,fileName:$fileName,format:$mode,usertype:$usertype}" |
sed -f urlencode.sed)
    url=$url?$param
```

```
funcExecuteRequest "POST" $url $param "application/json"
    output='cat response.txt'
    status='echo $output | jq '.status''
if [ $status == -1 ]; then
    echo "copying snapshot in progress"
    funcGetStatus "GET"
else
    error='echo $output | jq '.details''
    echo "Error occured. " $error
fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Groovy Sample – provisionreport.groovy

Prerequisites: json.jar

}

Common Functions: See CSS Common Helper Functions for Groovy

```
def provisionReport (fileName, type) {
        def url;
                                   JSONObject param = new
JSONObject();
        try {
            param.put("fileName", fileName);
            param.put("type",type);
            param.put("format",mode);
            param.put("usertype", usertype);
            url = new URL(serverUrl + "/interop/rest/" + lcmVersion + "/
reports?q=" + param.toString());
        } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
        }
        response = executeRequest(url, "POST", param.toString(),
"application/x-www-form-urlencoded");
        if (response != null) {
            getJobStatus(fetchPingUrlFromResponse(response, "Job
Status"), "GET");
       }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy



User Access Report (v2)

The User Access Report (v2) REST API generates an access report of users provisioned in the environment and writes the report to the filename provided. This report can then be downloaded using the download command.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

This API is version v2.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

POST /interop/rest/v2/reports/useraccess

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

	Table 12-68	Tasks for User Access Report
--	-------------	------------------------------

Task	Reques	t REST Resource
User Access Report	POST	/interop/rest/v2/reports/useraccess

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 12-69 Parameters

Name	Description	Туре	Required	Default
fileName	File where report is to be populated	Payload	Yes	None
format	The format of the csv file, classic or simplified	Payload	No	classic
usertype	Wheter to generate the report only for Identity Domain Administrators, IDAdmins or ServiceUsers	Payload	No	ServiceU sers



Example URL and Payload

```
https://<BASE-URL>/interop/rest/v2/reports/useraccess
{
    "fileName": "provisionreport.csv",
    "parameters": {
        "format": "simplified",
        "usertype": "IDAdmins"
    }
}
```

Response

Supported Media Types: application/json

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	null

Table 12-70 Parameters

Example of Response Body

The following example show the contents of the response body in JSON format.

```
{
    "details": null,
    "status": -1,
    "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/reports/useraccess",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": "https://<BASE-URL>/interop/rest/v2/status/jobs/
22747066997747363",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    ]
}
```



Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type: application/json' -d
'{"fileName":"provisionreport.csv","parameters":
{"format":"simplified","usertype":"IDAdmins"}}
' 'https://<BASE-URL>/interop/rest/v2/reports/useraccess'
```

User Audit Report (v1)

Generates a user audit report in the system and writes the report to the filename provided. The output CSV file contains the first character as a Byte Order Mark(BOM) character \ufeff. The API writes an encrypted application identifier following the BOM character. This application identifier is written between double quotes. Headers for the CSV file follow the application identifier. The report contains the details regarding the users logged into the system in a given time range.

The generated CSV file is compressed and the output is a ZIP file. The file can be downloaded using the Download REST API.

This is an asynchronous command, so use the job status URI to determine whether the operation is complete.

This API is version v1.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

```
POST /interop/rest/{api_version}/reports?
q={type:userauditreport,fileName:userauditreport.csv,since:2017-12-10,until:2018
-06-10}
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-71 Tasks for User Audit Report

Task	Request	REST Resource
User Audit Report	POST	<pre>/interop/rest/{api_version}/reports? q={type:userauditreport,fileName:useraudit report.csv,since:2017-12-10,until:2018-06-10}</pre>



Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-72 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
fileName	File where report is to be populated	Query	Yes	None
since	Report generation start date	Query	Yes	None
until	Report generation end date	Query	Yes	None
type	Type of report being generated , provisionreport or userauditreport	Query	Yes	None

Response

Supported Media Types: application/json

Table 12-73	Parameters
-------------	------------

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "links": [
      {
         "rel": "self",
         "href": "https://<BASE-URL>/interop/rest/{api version}/reports?
q={type:userauditreport,fileName:useraudit
report.csv, since: 2017-12-10, until: 2018-06-10}",
         "data": null,
         "action": "POST"
     },
      {
         "rel": "Job Status",
         "href": "https://<BASE-URL>/interop/rest/v1/reports/
3180621025673301",
         "data": null,
         "action": "GET"
```

```
}
],
"status": -1,
"details": null
}
```

User Audit Report Sample Code

Example 12-1 Java Sample – UserAuditReport.java

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
11
// BEGIN
11
public void userAuditReport (String fileName, String type, String since,
String until) throws Exception {
    JSONObject params = new JSONObject();
    params.put("fileName",java.net.URLEncoder.encode(fileName));
   params.put("type",java.net.URLEncoder.encode(type));
    params.put("since", java.net.URLEncoder.encode(since));
    params.put("until", java.net.URLEncoder.encode(until));
    String urlString = String.format("%s/interop/rest/%s/reports?q=%s",
serverUrl, lcmVersion, params.toString());
   String response = executeRequest(urlString, "POST", params.toString(),
"application/x-www-form-urlencoded");
    waitForCompletion(fetchPingUrlFromResponse(response, "Job Status"));}
11
// END
11
```

Example 12-2 cURL Sample – userauditreport.sh

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See Common Helper Functions for cURL

```
funcUserAuditReport () {
    url=$SERVER_URL/interop/rest/$LCM_VERSION/reports/
    param=$(echo
"q={type:$reporttype,fileName:$fileName,since:$since,until:$until}" | sed -f
urlencode.sed)
    url=$url?$param
    funcExecuteRequest "POST" $url $param "application/json"
    output='cat response.txt'
    status='echo $output | jq '.status''
    if [ $status == -1 ]; then
        echo "copying snapshot in progress"
        funcGetStatus "GET"
```



```
else
    error='echo $output | jq '.details''
    echo "Error occured. " $error
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Example 12-3 Groovy Sample – userauditreport.groovy

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Groovy

```
def userAuditReport (fileName, type, since, until) {
        def url;
        JSONObject param = new JSONObject();
        try {
            param.put("fileName", fileName);
            param.put("type",type);
            param.put("since", since);
            param.put("until", until);
            url = new URL(serverUrl + "/interop/rest/" + lcmVersion + "/
reports?g=" + param.toString());
        } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
        }
        response = executeRequest(url, "POST", param.toString(),
"application/x-www-form-urlencoded");
        if (response != null) {
            waitForCompletion(fetchPingUrlFromResponse(response, "Job
Status"));
        }
1
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

User Audit Report (v2)

The User Audit Report (v2) REST API generates a user audit report in the environment and writes the report to the filename provided. The output CSV file contains the first character as a Byte Order Mark(BOM) character \ufeff. The API writes an encrypted application identifier following the BOM character. This application identifier is written between double quotes. Headers for the CSV file follow the application identifier. The report contains the details regarding the users logged into the environment in a given time range.

The generated CSV file is compressed and the output is a ZIP file. The file can be downloaded using the Download REST API.



This is an asynchronous command, so use the job status URI to determine whether the operation is complete.

This API is version v2.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

```
POST /interop/rest/v2/reports/useraudit
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-74 Task for User Audit Report

Task	Request	REST Resource
User Audit Report	POST	/interop/rest/v2/reports/useraudit

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 12-75 Parameters

Name	Description	Туре	Required	Default
fileName	File where report is to be populated	Payload	Yes	None
since	Report generation start date	Payload	Yes	None
until	Report generation end date	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/interop/rest/v2/reports/useraudit

```
{
    "fileName": "userauditreport.csv",
    "since": "2022-10-01",
    "until":"2022-11-01"
}
```



Response

Supported Media Types: application/json

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "details": null,
    "status": -1,
    "links": [
        {
            "href": "https://<BASE-URL>/interop/rest/v2/reports/useraudit",
            "action": "POST",
            "rel": "self",
            "data": null
        },
        {
            "href": "https://<BASE-URL>/interop/rest/v2/status/jobs/
22747152577657842",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    ]
}
```

Sample cURL command

```
curl -X POST -s -u '<USERNAME>:<PASSWORD>' -o response.txt -D respHeader.txt -
H 'Content-Type:application/json' -d
'{"fileName":"userauditreport.csv","until":"2022-11-01",
"since":"2022-10-01"}''https://<BASE-URL>/interop/rest/v2/reports/useraudit'
```

Role Assignment Report (v1)

Generates a Role Assignment Report (.CSV). This report lists the predefined roles (for example, Service Administrator) and application roles (for example, Approvals Ownership



Assigner, Approvals Supervisor, Approvals Administrator, and Approvals Process Designer, which are Planning application roles) assigned to users. This report matches the CSV version of the Role Assignment Report generated from Access Control. Additionally, it can generate reports containing Identity Domain Administrator on the system by specifying the user type. The API writes the report to the filename provided, and the report can then be downloaded using the Download REST API.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

The presence of status -1 in the response indicates that the generation of Role Assignment Report is in progress. Use the job status URI to determine whether the generation of Role Assignment Report is complete. Any non-zero status except -1 indicates failure of generating Role Assignment Report.

This API is version v1.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

POST /interop/rest/security/{api version}/roleassignmentreport

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-77 Tasks for User Assignment Report

Task	Request	REST Resource
Role Assignment Report	POST	/interop/rest/security/{api_version}/ roleassignmentreport/
Role Assignment Report Status	GET	<pre>/interop/rest/security/{api_version}/jobs/{jobId}</pre>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-78 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None



Table 12-78 (Cont.) Parameters

Name	Description	Туре	Required	Default
filename	File name for the file where the report is to be populated, such as roleAssignmentReport.csv	Form	Yes	None
usertype	User type for which to generate the report. This paramenter is optional. If provided values can be either ServiceUsers or IDAdmins.	Form	No	ServiceUs ers

Response

Supported Media Types: application/json

Table 12-79 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following show examples of the response body in JSON format.

Example 1: Job is in Progress

```
{
    "links": [
         {
             "data": {
                  "jobType": "GENERATE_ROLE_ASSIGNMENT_REPORT",
"filename": "<filename>"
                  "usertype": "<USER TYPE>"
             },
             "action": "POST",
             "href": "https://<BASE-URL>/interop/rest/security/<api version>/
jobs/<jobId>",
             "rel": "Job Status"
         }
    ],
    "status": -1,
    "details": null,
    "items": null
}
```



Example 2: Job Completes with Errors

```
{
    "links": [
        {
            "data": {
                "jobType": "GENERATE ROLE ASSIGNMENT REPORT",
                "filename": "<filename>"
                "usertype": "<USER TYPE>"
            },
            "action": "POST",
            "href": "https://<BASE-URL>/interop/rest/security/{api version}/
roleassignmentreport",
            "rel": "self"
        }
   ],
    "status": 1,
    "details": "EPMCSS-20665: Failed to generate Role Assignment Report.
Invalid or insufficient parameters are specified. Provide all required
parameters for the REST API. ",
    "items": null
}
```

Example 3: Job Completes without Errors

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void generateRoleAssignmentReport(String filename, String userType) {
    try {
        String url = this.serverUrl + "/interop/rest/security/" +
    apiVersion + "/roleassignmentreport";
        Map<String, String> reqHeaders = new HashMap<String, String>();
        reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                      .printBase64Binary((this.userName + ":" +
    this.password).getBytes(Charset.defaultCharset())));
```



```
Map<String, String> reqParams = new HashMap<String, String>();
reqParams.put("filename", filename);
reqParams.put("usertype", userType);
Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
"POST");
String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
System.out.println(jobStatus);
} catch (Exception e) {
e.printStackTrace();
}
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcGenerateRoleAssignmentReport() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/
roleassignmentreport"
    params="filename=$1&usertype=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="generateRoleAssignmentReport"
    statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def generateRoleAssignmentReport(filename, userType) {
    String scenario = "Generating Role assignment report in " + filename + "
with usertype as " + userType;
    String params = "jobtype=GENERATE ROLE ASSIGNMENT REPORT&filename="+
filename "&usertype=" + userType;
    def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
roleassignmentreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
```

```
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Role Assignment Report for Users (v2)

Generates a Role Assignment Report of users in the environment. The report lists the roles assigned to users. It identifies the user's login name, first name, last name, email address and assigned roles. The report can be created for a specific user or a role or a combination of users and roles.

The report includes:

- Predefined roles (such as Service Administrator)
- Application roles (such as Approvals Assign Ownerships, Approvals Supervise, Approvals Administer, and Approvals Design Process).

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of getting Role Assignment Report for users.

This API is version v2.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

```
GET /interop/rest/security/v2/report/roleassignmentreport/user?
userlogin=<userlogin>&rolename=<rolename>
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Task	Request	REST Resource
Role Assignment Report for Users	GET	/interop/rest/security/v2/report/roleassignmentreport/
Report for Osers		user?userlogin= <userlogin>&rolename=<rolename></rolename></userlogin>



Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 12-81 Parameters

Name	Description	Туре	Required	Default
userlogin	Generates roleassignmentreport for the specified user only. If a user login is not specified, the report is generated for all the users.	Query	No	All Users
rolename	Generates roleassignmentreport for the specified role only. If a role name is not specified, the report is generated for all the roles.	Query	No	All Roles
	The Role name can be either Predefined or Application Role (for example, Power User or Access Control - Manage).			

Response

Supported Media Types: application/json

Table 12-82 Parameters

Parameters	Description
links	Detailed information about the link and HTTP call type
status	See Migration Status Codes
error	Detailed information about the error
details	Lists records matching the request

Example of Respose Body

The following show examples of the response body in JSON format.

Response 1: REST API Issued without userlogin or rolename Query Parameters Completes without Errors



```
"rolename": "Service Administrator",
          "roletype": "Predefined",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Ad Hoc - Creater",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
      ]
    },
    {
      "userlogin": "Jeff",
      "firstname": "Jeff",
      "lastname": "Clark",
      "email": "jeff.clark@example.com",
      "roles": [
        {
          "rolename": "Service Administrator",
          "roletype": "Predefined",
          "grantedthroughgroup": "idcsgroup"
        },
        {
          "rolename": "Ad Hoc - Read Only User",
          "roletype": "Application",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Application - Mass Allocate",
          "roletype": "Application",
          "grantedthroughgroup": "Analyst->idcsgroup"
        }
     ]
    }
 ]
}
```

Response 2: REST API Issued with userlogin and rolename Query Parameters Completes without Errors



```
"roles": [
        {
            {"rolename": "Service Administrator",
            "roletype": "Predefined",
            "grantedthroughgroup": ""
        }
      ]
      }
]
```

```
Response 3: REST API Issued with Only rolename Query Parameter Completes without Errors
```

```
{
  "links": {
    "href": "https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/user?rolename='Ad Hoc - Read Only User'",
    "action": "GET"
 },
 "status": 0,
  "error": null,
  "details": [
   {
      "userlogin": "Jade",
     "firstname": "Jade",
     "lastname": "Clark",
      "email": "jade.clark@example.com",
      "roles": [
       {
          "rolename": "Ad Hoc - Read Only User",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
     ]
    },
    {
     "userlogin": "Jeff",
      "firstname": "Jeff",
      "lastname": "Clark",
      "email": "jeff.clark@example.com",
      "roles": [
        {
          "rolename": "Ad Hoc - Read Only User",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
     ]
    }
 ]
}
```



Response 4: REST API Issued with Only userlogin Query Parameter Completes without Errors

```
{
  "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/user?userlogin='Jade'",
    "action": "GET"
 },
  "status": 0,
  "error": null,
  "details": [
    {
      "userlogin": "Jade",
      "firstname": "Jade",
      "lastname": "Clark",
      "email": "jade.clark@example.com",
      "roles": [
        {
          "rolename": "Service Administrator",
          "roletype": "Predefined",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Ad Hoc - Creater",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
     ]
    }
 ]
}
```

Response 5: Job Completes with Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/user",
   "action": "GET"
   },
   "status": 1,
   "error": {
      "errorcode": "EPMCSS-21206",
      "errormessage": "Failed to generate Role Assignment Report for Users.
Authorization failed. Please provide valid authorized user."
   },
   "details": null
}
```



Sample cURL Commands

Sample cURL command using Basic Auth

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/report/roleassignmentreport/user'
```

curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/report/roleassignmentreport/user?
userlogin=<userlogin>&rolename=<rolename>'

Sample cURL command using oAuth

```
curl --location --request GET 'https://<BASE-URL>/interop/rest/security/v2/
report
/roleassignmentreport/user' --header "Authorization: Bearer <OAUTH_TOKEN>"
```

```
curl --location --request GET 'https://<BASE-URL>/interop/rest/security/v2/
report
/roleassignmentreport/user?userlogin=<userlogin>&rolename=<rolename>' --
header "Authorization: Bearer <OAUTH TOKEN>"
```

Role Assignment Report for Groups (v2)

Generates a Role Assignment report of groups in the environment. The report lists the roles assigned to groups. It identifies the group's name, description, type and assigned roles. The report can be created for a specific group or a role or a combination of groups and roles.

The report includes:

- Predefined roles (such as Service Administrator)
- Application roles (such as Approvals Assign Ownerships, Approvals Supervise, Approvals Administer, and Approvals Design Process)

The API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of getting Role Assignment Report for groups.

This API is version v2.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

GET /interop/rest/security/v2/report/roleassignmentreport/group?
groupname=<groupname>&rolename>



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-83 Tasks for Role Assignment Report for Grou

「ask	Reque st	REST Resource
Role Assignment Report for Groups	GET	<pre>/interop/rest/security/v2/report/ roleassignmentreport/group? groupname=<groupname>&rolename=<rolename></rolename></groupname></pre>

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 12-84 Parameters

Name	Description	Туре	Required	Default
groupname	Generates roleassignmentreport for the specified group only. If a group name is not specified, the report is generated for all the groups.	Query	No	All Groups
	The group name can be either EPM or IDCS group.			
rolename	Generates roleassignmentreport for the specified role only. If a role name is not specified, the report is generated for all the roles.	Query	No	All Roles
	The Role name can be either Predefined or Application Role (for example, Power User or Access Control - Manage).			

Response

Supported Media Types: application/json

Table 12-85 Parameters

Parameters	Description
links	Detailed information about the link and HTTP call type
status	See Migration Status Codes
error	Detailed information about the error
details	Lists records matching the request

Example of Response Body

The following show examples of the response body in JSON format.



Response 1: REST API Issued without groupname or rolename Query Parameters Completes without Errors

```
{
  "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/group",
    "action": "GET"
 },
  "status": 0,
  "error": null,
  "details": [
    {
      "groupname": "idcsgroup",
      "description": "Sample IDCS Group",
      "type": "IDCS",
      "roles": [
        {
          "rolename": "Service Administrator",
          "roletype": "Predefined",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Application - Mass Allocate",
          "roletype": "Application",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Ad Hoc - Read Only User",
          "roletype": "Application",
          "grantedthroughgroup": "Analyst"
        }
      1
    },
    {
      "groupname": "FinancialAnalyst",
      "description": "Sample EPM Group",
      "type": "EPM",
      "roles": [
        {
          "rolename": "Application - Mass Allocate",
          "roletype": "Application",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "DataIntegration-Create",
          "roletype": "Application",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "DataIntegration-Run",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
      1
    },
```

```
"groupname": "GroupPU",
      "description": "Sample IDCS GroupPU",
      "type": "IDCS",
      "roles": [
        {
          "rolename": "PowerUser",
          "roletype": "Predefined",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Approval-Supervise",
          "roletype": "Application",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "DataIntegration-Run",
          "roletype": "Application",
          "grantedthroughgroup": "Analyst->FinancialAnalyst"
        }
     ]
    }
 ]
}
```

Response 2: REST API Issued with groupname and rolename Query Parameters Completes without Errors

```
{
  "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/group?groupname='idcsgroup'&rolename='Service
Administrator'",
    "action": "GET"
 },
  "status": 0,
  "error": null,
  "details": [
    {
      "groupname": "idcsgroup",
      "description": "Sample IDCS Group",
      "type": "IDCS",
      "roles": [
        {
          "rolename": "Service Administrator",
          "roletype": "Predefined",
          "grantedthroughgroup": ""
        }
     1
    }
 ]
}
```



Response 3: REST API Issued with Only rolename Query Parameter Completes without Errors

```
{
  "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/group?rolename='Application - Mass Allocate'",
    "action": "GET"
 },
  "status": 0,
  "error": null,
  "details": [
    {
      "groupname": "idcsgroup",
      "description": "Sample IDCS Group",
      "type": "IDCS",
      "roles": [
        {
          "rolename": "Application - Mass Allocate",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
      ]
    },
    {
      "groupname": "FinancialAnalyst",
      "description": "Sample EPM Group",
      "type": "EPM",
      "roles": [
        {
          "rolename": "Application - Mass Allocate",
          "roletype": "Application",
          "grantedthroughgroup": ""
        }
      1
    }
 1
}
```

Response 4: REST API Issued with Only groupname Query Parameter Completes without Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/group?groupname='idcsgroup'",
    "action": "GET"
   },
   "status": 0,
   "error": null,
   "details": [
    {
        "groupname": "idcsgroup",
        "description": "Sample IDCS Group",
        "type": "IDCS",
    }
}
```

```
"roles": [
        {
          "rolename": "Service Administrator",
          "roletype": "Predefined",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Application - Mass Allocate",
          "roletype": "Application",
          "grantedthroughgroup": ""
        },
        {
          "rolename": "Ad Hoc - Read Only User",
          "roletype": "Application",
          "grantedthroughgroup": "Analyst"
        }
     ]
    }
 1
}
```

Response 5: Job Completes with Errors

```
{
   "links": {
     "href": " https://<BASE-URL>/interop/rest/security/v2/report/
roleassignmentreport/group",
     "action": "GET"
   },
   "status": 1,
   "error": {
     "error": {
        "errormessage": "Failed to generate Role Assignment Report for Groups.
Authorization failed. Please provide valid authorized user."
   },
   "details": null
}
```

Sample cURL Commands

Sample cURL command using Basic Auth

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/report/roleassignmentreport/group
```

curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/report/roleassignmentreport/
group?groupname=<groupname>&rolename=<rolename>'



Sample cURL command using oAuth

```
curl --location --request GET 'https://<BASE-URL>/interop/rest/security/v2/
report
/roleassignmentreport/group' --header "Authorization: Bearer <OAUTH_TOKEN>"
curl --location --request GET 'https://<BASE-URL>/interop/rest/security/v2/
report
/roleassignmentreport/group?groupname=<groupname>&rolename=<rolename>' --
header "Authorization: Bearer <OAUTH_TOKEN>"
```

Get Available Roles

Returns all the application roles that are visible along with predefined roles that are available for an Oracle Enterprise Performance Management Cloud service.

This API is synchronous and returns the outcome of the operation in the response. Any nonzero status indicates failure of getting available roles.

This REST API is version v2.

Required Roles

Service Administrator or Access Control - Manage

REST Resource

GET /interop/rest/security/v2/role/getavailableroles



Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-86 Tasks for Getting Available Roles

Task	Request	REST Resource
Get Available Roles	GET	/interop/rest/security/v2/role/getavailableroles

Request

Supported Media Types: application/json

Response

Supported Media Types: application/json



Parameters	Description
links	Detailed information about the link
status	 Status of the operation 0: Operation succeeded 1: Operation failed
error	Detailed information about the error
details	Records matching the request

Table 12-87Parameters

Examples of Response Body

The following show examples of the response body in JSON format.

Example 1: Job Completes without Errors

```
{
 "links": {
    "href": " https://<BASE URL>/interop/rest/security/v2/role/
getavailableroles",
    "action": "GET"
 },
 "status": 0,
 "error": null,
  "details": [
    {
      "name": "Ad Hoc - Create",
      "id": "HP:0016"
    },
    {
      "name": "Ad Hoc - Read Only User",
      "id": "HP:0017"
    },
    {
      "name": "Ad Hoc - User",
      "id": "HP:0015"
    },
    {
      "name": "Announcements - Manage",
      "id": "HP:0021"
    },
    {
      "name": "User",
      "id": "HUB:003"
    },
    {
      "name": "Viewer",
      "id": "HUB:004"
   },
    . . .
 ]
}
```



Example 2: Job Completes with Errors

```
{
   "links": {
    "href": " https://<BASE-URL>/interop/rest/security/v2/role/
getavailableroles",
    "action": "GET"
   },
   "status": 1,
   "error": {
        "error": {
            "errormessage": "Failed to get available roles. Authorization failed.
Please provide valid authorized user."
    },
    "details": null
}
```

Sample cURL Commands

Sample cURL command using Basic Auth

```
curl -X GET -s -u '<USERNAME>:<PASSWORD>' -H 'Content-Type: application/json'
'https://<BASE-URL>/interop/rest/security/v2/role/getavailableroles'
```

Sample cURL command using oAuth

```
curl --location --request GET 'https://<BASE-URL>/interop/rest/security/v2/
role/getavailableroles'
--header "Authorization: Bearer <OAUTH TOKEN>"
```

Role Assignment Audit Report for OCI (Gen 2) Environments

Users with a Service Administrator role can use this API to generate a Role Assignment Audit Report of users with their pre-defined and application roles on OCI (Gen 2) Environments. This allows you to automate reporting on users role and application role assignments. The report shows all the changes made to the predefined role and application role assignments within the provided time frame. This report can be generated for the previous 90 days from the current date. You can download the report using the Download REST API. The report shows the timestamp (UTC) in the Date and Time column in 24-hour format.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

The presence of status -1 in the response indicates that the generation of the report is in progress. Use the job status URI to determine whether the generation of the report is complete. Any non-zero status except -1 indicates failure of generating the report.

The default retention period for audit data is 30 days; however, you can extend the retention period up to a maximum of 90 days from the Identity Console. If you want a longer duration of audit data, download a Role Assignment Audit Report and archive it.



Note:

This command is applicable to OCI environments only.

This API is version v1.

Required Roles

- Service Administrator
- Any predefined role and the Identity Domain Administrator role
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

POST /interop/rest/security/{api version}/roleassignmentauditreport

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Task	Request	REST Resource
Role Assignment Audit Report	POST	/interop/rest/security/{api_version}/ roleassignmentauditreport/
Role Assignment Audit Report Status	GET	<pre>/interop/rest/security/{api_version}/jobs/{jobId}</pre>

Request

Supported Media Types: application/x-www-form-urlencoded

Table 12-89 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
from_date	The start date for the report (in YYYY-MM-DD format)	Form	Yes	None
to_date	The end date for the report (in YYYY-MM-DD format)	Form	Yes	None
filename	CSV file where the report is to be populated, such as roleAssignmentAuditReport.csv	Form	Yes	None

Response

Supported Media Types: application/json



Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request

Table 12-90 Parameters

Sample Role Assignment Audit Report

	A	В	С	D	E
1	User Name	Role	Action	Administrator	Date and Time
2	jane.doe@example.com	User	Assign	epm.admin@example.com	July 09, 2021 03:54:52 UTC
3	jane.doe@example.com	Run Integrations	Assign	epm.admin@example.com	July 09, 2021 03:54:52 UTC
4	john.doe@example.com	Service Administrator	Assign	epm.admin@example.com	July 09, 2021 03:51:28 UTC
5	john.smith@example.com	Power User	Unassign	epm.admin@example.com	July 09, 2021 03:53:04 UTC
6	john.smith@example.com	User	Assign	epm.admin@example.com	July 09, 2021 03:54:06 UTC

Information on deleted users who were previously assigned to predefined roles in the environment is listed with the display name (first and last name) of the user in the User Name column. In such cases, the Role column indicates the predefined role that the user had before the user's account was deleted. This change does not apply to application roles, if any, that were assigned to the deleted user; such assignments are shown with the User Login Name of the user. For an example, see the information in the red box in the following illustration.

····_

	А	В	С	D	E
1	User Name	Role	Action	Administrator	Date and Time
2	Jane Doe	User	Assign	epm.admin@example.com	July 09, 2021 03:54:52 UTC
3	jane.doe@example.com	Run Integrations	Assign	epm.admin@example.com	July 09, 2021 03:54:52 UTC
4	john.doe@example.com	Service Administrator	Assign	epm.admin@example.com	July 09, 2021 03:51:28 UTC
5	john.smith@example.com	Power User	Unassign	epm.admin@example.com	July 09, 2021 03:53:04 UTC
6	john.smith@example.com	User	Assign	epm.admin@example.com	July 09, 2021 03:54:06 UTC

Examples of Response Body

The following show examples of the response body in JSON format.

Response 1: Job is in Progress

```
"to date": "<toDate>",
                "filename": "<filename>",
                "from date": "<fromDate>"
            },
            "action": "POST"
        },
        {
            "rel": "Job Status",
            "href": "https://<BASE-URL>/interop/rest/security/<api version>/
jobs/3023387588778806",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```

Response 2: Job Completes with Errors

```
{
    "links": [
       {
            "data": {
                "jobType": "GENERATE ROLE ASSIGNMENT AUDIT REPORT",
            "from date": " ",
            "to date": " ",
                "filename": " "
            },
            "action": "POST",
            "href": "https://<BASE-URL>/interop/rest/security/{api version}/
roleassignmentauditreport",
            "rel": "self"
        }
   ],
    "status": 1,
    "details": "EPMCSS-20678: Failed to generate Role Assignment Audit
Report. Invalid or insufficient parameters specified. Provide all required
parameters for the REST API. ",
    "items": null
}
```

Response 3: Job Completes without Errors

```
{
    "links": [
        {
            "data": null,
            "action": "GET",
            "href": " https://<BASE-URL>/interop/rest/security/<api_version>/
jobs/<jobID>",
            "rel": "self"
        }
    ],
```

```
"status": 0,
"details": null,
"items": null
```

}

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void generateRoleAssignmentAuditReport(String fromDate, String
toDate,String fileName) {
     try {
       String url = this.serverUrl + "/interop/rest/security/" + apiVersion
+ "/roleassignmentauditreport";
       Map<String, String> reqHeaders = new HashMap<String, String>();
       reqHeaders.put("Authorization", "Basic " + DatatypeConverter
            .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
       Map<String, String> reqParams = new HashMap<String, String>();
       reqParams.put("from date", fromDate);
        reqParams.put("to date", toDate);
       regParams.put("filename", fileName);
       Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
"POST");
       String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
       System.out.println(jobStatus);
    } catch (Exception e) {
       e.printStackTrace();
    }
}
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcGenerateRoleAssignmentAuditReport() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/
roleassignmentauditreport"
    params="from_date=$1&to_date=$2&filename=$3"
        header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
        cssRESTAPI="generateRoleAssignmentAuditReport"
        statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
        echo $statusMessage
}
```



Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def generateRoleAssignmentAuditReport(from date, to date, fileName) {
    String scenario = "Generating Role assignment audit report in " +
fileName;
    String params =
"jobtype=GENERATE ROLE ASSIGNMENT AUDIT REPORT&from date="+from date+"&to date
="+to date+"&filename="+ fileName;
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
roleassignmentauditreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Invalid Login Report for OCI (Gen 2) Environments

Users who have both a Service Administrator role and an Identity Domain Administrator role can use this API to generate an Invalid Login Report on OCI (Gen 2) environments. This allows you to automate reporting on unsuccessful login attempts. This report shows unsuccessful login attempts for users within the provided time frame. This report can be generated for the previous 90 days from the current date. You can download the report using the Download REST API. This report shows all the unsuccessful login attempts to the corresponding Identity Cloud Service. These may not all be to this particular EPM Cloud instance.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

The presence of status -1 in the response indicates that the generation of the report is in progress. Use the job status URI to determine whether the generation of the report is complete. Any non-zero status except -1 indicates failure of generating the report.

The default retention period for audit data is 30 days; however, you can extend the retention period up to a maximum of 90 days from the Identity Console. If you want a longer duration of audit data, download an Invalid Login Report and archive it.

This API is version v1.

Required Roles

Identity Domain Administrator and any predefined role (Service Administrator, Power User, User, or Viewer)

ORACLE

REST Resource

POST /interop/rest/security/{api_version}/invalidloginreport

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-91 Tasks for Invalid Login Report for OCI (Gen 2) Environments

Task	Request	REST Resource
Invalid Login Report	POST	/interop/rest/security/{api_version}/invalidloginreport/
Invalid Login Report Status	GET	<pre>/interop/rest/security/{api_version}/jobs/{jobId}</pre>

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-92 Parameters

Name	Description	Туре	Required	Default
api_version	Specific API version	Path	Yes	None
from_date	The start date for the report (in YYYY-MM-DD format)	Form	Yes	None
to_date	The end date for the report (in YYYY-MM-DD format)	Form	Yes	None
filename	CSV file where the report is to be populated, such as InvalidLoginReport.csv	Form	Yes	None

Response

Supported Media Types: application/json

Table 12-93 Parameters

Parameters	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status
data	Parameters as key value pairs passed in the request



Sample Invalid Login Report

	А	В	с
1	User Name	IP Address	Access Date and Time
2	john.doe@example.com	xxx.xx.xx5	July 15, 2021 11:14:58 UTC
3	jane.doe@example.com	xxx.xx.xx.xx9	July 15, 2021 11:14:58 UTC
4	john.smith@example.com	xxx.xx.xx.xx3	July 15, 2021 11:14:57 UTC

Examples of Response Body

The following show examples of the response body in JSON format.

Response 1: Job is in Progress

```
{
    "links": [
        {
            "rel": "self",
            "href": "https://<BASE-URL>/interop/rest/security/<api version>/
invalidloginreport",
            "data": {
                "jobType": "GENERATE INVALID LOGIN REPORT",
                "to date": "<toDate>",
                "filename": "<filename>",
                "from date": "<fromDate>"
            },
            "action": "POST"
        },
        {
            "rel": "Job Status",
            "href": "https://<BASE-URL>/interop/rest/security/<api version>/
jobs/<job id>",
            "data": null,
            "action": "GET"
        }
    ],
    "details": null,
    "status": -1,
    "items": null
}
```

Response 2: Job Completes with Errors

Response 3: Job Completes without Errors

```
{
    "links": [
        {
            "data": null,
            "action": "GET",
            "href": " https://<BASE-URL>/interop/rest/security/<api_version>/
jobs/<jobID>",
            "rel": "self"
        }
        ,
        "status": 0,
        "details": null,
        "items": null
}
```

Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
public void generateInvalidLoginReport(String fromDate, String toDate, String
fileName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/invalidloginreport";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("from date", fromDate);
            reqParams.put("to date", toDate);
            regParams.put("filename", fileName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
```



```
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
    System.out.println(jobStatus);
    catch (Exception e) {
        e.printStackTrace();
    }
}
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcGenerateInvalidLoginReport() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/
invalidloginreport"
    params="from_date=$1&to_date=$2&filename=$3"
        header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
        cssRESTAPI="generateInvalidLoginReport"
        statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
        echo $statusMessage
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def generateInvalidLoginReport(from date, to date, fileName) {
    String scenario = "Generating Invalid Login report in" + fileName;
    String params =
"jobtype=GENERATE INVALID LOGIN REPORT&from date="+from date+"&to date="+to da
te+"&filename="+ fileName;
    def url = null;
    def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
invalidloginreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
```

Common Functions

See Common Helper Functions for Java



- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Group Assignment Audit Report

Generates a group assignment audit report. The report contains details on the users and groups that were added to or removed from Access Control groups in a given date range. This report is in CSV format. Each row of the report provides the user or group that was added or removed, the group to which the user or group was added or removed from, the Service Administrator who performed the action, and the date and time when the action was completed. The API writes the report to the filename provided, and the report can then be downloaded using the Download REST API.

This is an asynchronous job and uses the job status URI to determine if the operation is complete.

The presence of status -1 in the response indicates that the generation of Group Assignment Audit Report is in progress. Use the job status URI to determine whether the generation of the report is complete. Any non-zero status except -1 indicates failure of generating the report.

This API is version v2.

Required Roles

- Service Administrator
- Any predefined role and the Access Control Manage application role
- Any predefined role and the Access Control View application role

REST Resource

POST /interop/rest/{api version}/reports/groupaudit

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Table 12-94 Tasks for Group Assignment Audit Report

Task	Request	REST Resource
Group Assignment Audit Report	POST	/interop/rest/{api_version}/reports/groupaudit
Group Assignment Audit Report Status		/interop/rest/{api_version}/jobs/{jobId}

Request

Supported Media Type: application/json

The following table summarizes the request parameters.



Table 12-95 Parameters

Name	Description	Туре	Required	Default	
api_version	Specific API version	Path	Yes	None	
filename	The CSV file where the report is to be populated, such as	Payload	Yes	None	
	groupAssignmentAuditReport.csv				
from_date	The start date for the report (in YYYY-MM-DD format)	Payload	Yes	None	
to_date	The end date for the report (in YYYY-MM-DD format)	Payload	Yes	None	

Example Payload

```
{
fileName":"groupauditreport_test.csv",
"from_date":"2022-03-26",
"to_date":"2022-05-30"
}
```

Response

Supported Media Types: application/json

Table 12-96 Parameters

Parameters	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "https://<BASE-URL>/interop/rest/{api_version}/reports/
groupaudit",
            "data": null,
            "action": "POST"
        },
        {
            "rel": "Job Status",
        }
}
```



Java Sample Code

Prerequisites: json.jar

Common Functions: See CSS Common Helper Functions for Java

```
//
    //BEGIN
    11
    public void groupAssignmentAuditReport(String fileName, String from date,
String to date)
            throws Exception {
        JSONObject params = new JSONObject();
        params.put("fileName", fileName);
        params.put("from date", from date);
        params.put("to date", to date);
        String urlString = String.format("%s/interop/rest/%s/reports/
groupaudit", serverUrl, apiVersion);
        String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
        getJobStatus(fetchPingUrlFromResponse(response, "Job Status"), "GET");
    }
    //
    // END
    11
```

Shell Script Sample Code

Prerequisites: jq (http://stedolan.github.io/jq/download/linux64/jq)

Common Functions: See CSS Common Helper Functions for cURL

```
funcgroupAssignmentAuditReport () {
    url=$SERVER_URL/interop/rest/v2/reports/groupaudit
    fileName="groupAssignmentAuditReport.csv"
    from_date="2022-03-01"
    to_date="2022-05-30"

param="{\"fileName\":\"$fileName\",\"from_date\":\"$from_date\",\"to_date\":\"
$to_date\"}"
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=$ (cat response.txt)
    status=$ (echo $output | jq '.status')
    echo "Status :$status"
    if [ $status == -1 ]; then
        echo "group assignment audit report generation in progress"
```



```
funcGetStatus "GET"
else
    error='echo $output | jq '.details''
    echo "Error occured. " $error
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample Code

Common Functions: See CSS Common Helper Functions for Groovy

```
def groupAssignmentAuditReport (fileName, from date, to date) {
        String scenario = "Group Assignment Audit Report";
        def url;
        def payload = new JsonBuilder()
      payload fileName:fileName,
            from date: from date,
            to date:to date
     url = new URL(serverUrl + "/interop/rest/v2/reports/groupaudit");
     params=payload.toString();
     response = executeRequest(url, "POST", params, "application/
json");
     if (response != null) {
       getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
     }
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Adding Users to a Team for Account Reconciliation

Adds Oracle Enterprise Performance Management Cloud users listed in a UTF8 formatted CSV file to an existing team in Access Control for Account Reconciliation. The file must be uploaded to the environment before using this API, and the file should be deleted after the API executes. Use the Upload REST API to upload the file.

A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:

```
User Login, primary_user
jdoe, yes
jane.doe@example.com,no
```

The users are added only if both these conditions are met:

- · User login IDs included in the file exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain



The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the process is complete. The presence of status -1 in the response indicates that the update is in progress. Any non-zero status except -1 indicates failure for the update.

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles

REST Resource

POST /armARCS/rest/{version}/jobs

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Name	Data Type	Description
version	String	The version of the API you are developing with. For the current release, the version is v1.
jobName	String	The name of the job, ADD_USERS_TO_TEAM.
fileName	String	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the users to be added, for example, addUsersToTeam.csv.
		The file must have been uploaded already using the Upload REST API. The CSV file should not include the account of the user who executes this command.
		A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:
		User Login, primary_user jdoe, yes jane.doe@example.com,no
teamName	String	The name of an existing team in Access Control, such as Team1

Table 12-97 Parameters



Example URL and Payload

```
{
   "jobName":"ADD_USERS_TO_TEAM",
    "parameters":{
        "fileName":"users.csv",
        "teamName":"Team1"
   }
}
```

https://<BASE-URL>/armARCS/rest/v1/jobs/

Response

Supported Media Types: application/json

Table 12-98Parameters

Name	Description	
status	-1 - In Progress	
	0 - Success	
	1 - Failure	
details	In case of errors, details are published with the error string	
descriptiveStat	The status of the job, such as Completed or Error.	
us		
items	Collection of notification categories	
links	Detailed information about the link	
href	Links to the API call	
action	The HTTP call type	
rel	Possible value: self	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "details": "In Process",
  "links": [
        {
            "rel": "self",
            "href": "https://<BASE-URL>/armARCS/rest/v1/jobs/1000000053010",
            "action": "GET"
        }
    ],
    "status": -1,
    "type": "ARCS",
    "link": null,
    "items": null,
    "error": null
}
```



Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Adding Users to a Team for Financial Consolidation and Close and Tax Reporting

Adds Oracle Enterprise Performance Management Cloud users listed in a UTF8 formatted CSV file to an existing team in Access Control. The file must be uploaded to the environment before using this API, and the file should be deleted after the API executes. Use the Upload REST API to upload the file.

A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:

```
User Login, primary_user
jdoe, yes
jane.doe@example.com,no
```

The users are added only if both these conditions are met:

- User login IDs included in the file exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the process is complete. The presence of status -1 in the response indicates that the update is in progress. Any non-zero status except -1 indicates failure for the update.

Note:

This feature uses a Planning REST API to run a job. Details about Planning REST APIs are described here: Planning REST APIs.

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/fcmjobs



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Name	Description	Туре	Require d	Default
api_version	The version of the API you are developing with; for the current release, it is $v3$	Path	Yes	None
application	The name of the application, for example, FCCS or TRCS	Path	Yes	None

Example of Request Body

The following table summarizes the parameters of the JSON request.

Table 12-100 Parameters

Name	Description		
jobName	The name of the job, ADD_USERS_TO_TEAM		
fileName	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the users to be added, for example, addUsersToTeam.csv.		
	The file must have been uploaded already using the Upload REST API. The CSV file should not include the account of the user who executes this command.		
	A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:		
	User Login, primary_user jdoe, yes jane.doe@example.com,no		
teamName	The name of an existing team in Access Control, for example, Team1		

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/FCCS/fcmjobs

```
{
   "jobName":"ADD_USERS_TO_TEAM",
    "parameters":{
        "fileName":"users.csv",
```



```
"teamName":"Team1" }
}
```

Response

Supported Media Types: application/json

Table 12-101 Parameters

Name	Description	
jobName	ADD_USERS_TO_TEAM	
jobID	The ID of the job, such as 100000000114040	
status	-1 - In Progress	
	0 - Success	
	1 - Failure	
details	In case of errors, details are published with the error string	
descriptiveStat us	The status of the job, such as Completed or Error	
items	Collection of notification categories	
links	Detailed information about the link	
href	Links to the API call	
action	The HTTP call type	
rel	Possible value: self	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
   "jobName": "ADD USERS TO TEAM",
  "jobId":10000000114040,
   "descriptiveStatus":",
   "detail":"In Progress",
   "status":-1,
   "items":null,
   "links":[
      {
         "rel":"self",
         "href":"https://<BASE-URL>/HyperionPlanning/rest/v3/applications/
FCCS/fcmjobs/10000000114040",
         "action":"GET"
      }
   ]
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL



See CSS Common Helper Functions for Groovy

Removing Users from a Team for Account Reconciliation

Removes Oracle Enterprise Performance Management Cloud users listed in a UTF8 formatted CSV file from an existing team in Access Control for Account Reconciliation. The file must be uploaded to the environment before using this API, and the file should be deleted after the API executes. Use the Upload REST API to upload the file.

A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:

User Login, primary_user jdoe, yes jane.doe@example.com,no

The users are removed only if both these conditions are met:

- · User login IDs included in the file exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain

The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the process is complete. The presence of status -1 in the response indicates that the update is in progress. Any non-zero status except -1 indicates failure for the update.

Required Roles

Service Administrator

REST Resource

```
POST /armARCS/rest/{version}/jobs
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the parameters of the JSON request.

Name	Data type	Description
version	String	The version of the API you are developing with. For the current release, the version is $v1$.
jobName	String	The name of the job, REMOVE_USERS_FROM_TEAM.



Name	Data type	Description
fileName	String	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the users to be remved, for example, removeUsersFromTeam.csv.
		The file must have been uploaded already using the Upload REST API. The CSV file should not include the account of the user who executes this command.
		A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:
		User Login, primary_user jdoe, yes jane.doe@example.com,no
teamName	String	The name of an existing team in Access Control, such as Team1

Table 12-102 (Cont.) Parameters

Example URL and Payload

https://<<BASE-URL>/armARCS/rest/v1/jobs

```
{
  "jobName":"REMOVE_USERS_FROM_TEAM",
  "parameters":{
     "fileName":"users.csv",
     "teamName":"Team1"
  }
}
```

Response

Supported Media Types: application/json

Table 12-103 Parameters

Description		
Application type		
-1 - In Progress		
0 - Success		
1 - Failure		
In case of errors, details are published with the error string		
The status of the job, such as Completed or Error.		
Collection of notification categories		
Detailed information about the link		
Links to the API call		
The HTTP call type		



Table 12-103	(Cont.) Parameters
--------------	--------------------

Name	Description
rel	Possible value: self
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "details": "In Process",
  "links": [
    {
        "rel": "self",
        "href": "https://<BASE-URL>/armARCS/rest/v1/jobs/1000000053010",
        "action": "GET"
    }
  ],
  "status": -1,
  "type": "ARCS",
  "link": null,
  "items": null,
  "error": null
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

Removing Users from a Team for Financial Consolidation and Close and Tax Reporting

Removes Oracle Enterprise Performance Management Cloud users listed in a UTF8 formatted CSV file from an existing team in Access Control. The file must be uploaded to the environment before using this API, and the file should be deleted after the API executes. Use the Upload REST API to upload the file.

A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:

```
User Login, primary_user
jdoe, yes
jane.doe@example.com,no
```

The users are removed only if both these conditions are met:

- User login IDs included in the file exist in the identity domain that services the environment
- The user is assigned to a pre-defined role in the identity domain



The API is asynchronous and returns the Job ID. Use the job status URI to determine whether the process is complete. The presence of status -1 in the response indicates that the update is in progress. Any non-zero status except -1 indicates failure for the update.

Note:

This feature uses a Planning REST API to run a job. Details about Planning REST APIs are described here: Planning REST APIs.

Required Roles

Service Administrators

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/fcmjobs

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/x-www-form-urlencoded

The following table summarizes the request parameters.

Table 12-104 Parameters

Name	Description	Туре	Require d	Default
api_version	The version of the API you are developing with; for the current release, it is $v3$	Path	Yes	None
application	The name of the application, FCCS	Path	Yes	None

Example of Request Body

The following table summarizes the parameters of the JSON request.

Table 12-105 Parameters

Name	Description
jobName	The name of the job, REMOVE_USERS_FROM_TEAM



Table 12-105 (Cont.) Parameters

Name	Description
fileName	The name of the uploaded ANSI or UTF-8 encoded CSV file containing information on the users to be removed, for example, removeUsersFromTeam.csv.
	The file must have been uploaded already using the Upload REST API. The CSV file should not include the account of the user who executes this command.
	A primary user is, by default, designated to perform the tasks that are assigned to the team. The file format is as follows:
	User Login, primary_user jdoe, yes jane.doe@example.com,no
teamName	The name of an existing team in Access Control, such as Team1.

Example URL and Payload

https://<BASE-URL>/HyperionPlanning/rest/v3/applications/FCCS/fcmjobs

```
{
  "jobName":"REMOVE_USERS_FROM_TEAM",
    "parameters":{
    "fileName":"users.csv",
    "teamName":"Team1"
  }
}
```

Response

Supported Media Types: application/json

Table 12-106 Parameters

Name	Description		
jobName	REMOVE_USERS_FROM_TEAM		
jobID	The ID of the job, such as 10000000114040		
status	-1 - In Progress		
	0 - Success		
	1 - Failure		
details	In case of errors, details are published with the error string		
descriptiveStat	The status of the job, such as Completed or Error		
us			
items	Collection of notification categories		
links	Detailed information about the link		
href	Links to the API call		
action	The HTTP call type		
rel	Possible value: self		



Table 12-106 (Cont.) Parameters

Name	Description
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
   "jobName": "REMOVE USERS FROM TEAM",
  "jobId":100000000114040,
  "descriptiveStatus":",
   "detail":"In Progress",
   "status":-1,
   "items":null,
   "links":[
      {
         "rel":"self",
         "href":"https://<EPM-CLOUD-BASE-URL>/HyperionPlanning/rest/v3/
applications/FCCS/fcmjobs/10000000114040",
         "action":"GET"
     }
   ]
}
```

Common Functions

- See Common Helper Functions for Java
- See Common Helper Functions for cURL
- See CSS Common Helper Functions for Groovy

13 Usage Simulation REST APIs

This section describes the REST APIs for simulating user activities for testing purposes.

Table 13-1 Usage Simulation

Task	Request	REST Resource
Simulate Concurrent Usage	POST	/interop/rest/v1/concurrentusage/run

Simulate Concurrent Usage

The Simulate Concurrent Usage REST API executes different concurrent operations on an environment by simulating users. It can be used to validate the performance of the environment to verify that the response time is acceptable when the service is under the load during specific operations run by a specific number of users. For example, it can be used to measure performance when 50 users simultaneously open a form using different POVs. It allows the self-service load testing of environments.

This REST API performs the simulation by executing the specified operations for a given number of users and iterations. It runs multiple iterations to calculate the minimum time, the maximum time and the average time for a particular operation. It supports these operations to perform concurrent usage load testing:

- Open forms
- Save forms
- Run business rules
- Run business rulesets
- Run data rules
- Open ad hoc grids
- Execute report
- Execute book

Note:

This API executes the specified operations on the current environment and may, depending on the operation, update the data in the environment. Run this API on test environments. Running this API on production environments is not advised.

This REST API accepts a ZIP file, that must already have been uploaded to the environment, as input. The ZIP file contains one requirement.csv file, and the input files that support the use cases included in requirement.csv. It can also optionally contain a userVarMemberMapping.csv file to provide user variable member mapping and an options.xml



file to provide Smart View options for some use cases. The REST API then simulates the use cases and creates a report that may be emailed to one or more recipients.

This REST API is version v1.

Required Roles

Service Administrator (Identity Domain Administrator is also required to use testModes 0, 1, and 2.)

REST Resource

POST /interop/rest/v1/concurrentusage/run

Supported Media Types: application/json

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

The following table summarizes the request parameters.

Table 13-2 Paran

Name	Description	Туре	Data Type	Required	Default
InputFile The name of the zip file that contains concurrent usage test cases. The zip file should contain a file named requirement.csv, which contains the details of all the operations to execute for this simulation test, and the input files that contain the details of each operation. It can also optionally contain a userVarMemberMapping.csv file to provide user variable member mapping and an options.xml file to provide Smart View options for some use cases.		Payload	String	Yes	None
	 For information on how to create these files, see Preparing to Run the simulateConcurrentUsage Command in Working with EPM Automate for Oracle Enterprise Performance Management Cloud. Use the Upload REST API to upload the zip file to the environment prior to calling this REST API. 				
numberOfIterations	Number of iterations each use case identified in requirement.csv has to run to measure the response time.	Payload	Integer	No	1

Name	Description	Туре	Data Type	Required	Default
notificationEmails	Email addresses of the recipients to whom the result will be sent at the end of the concurrent usage simulation. The emails must be separated by semi- colons and enclosed in double quotes. For example: "jdoe@example.com;jane.doe@examp le.com".	Payload	String	No	Email of the user who executed the API
lagTime	Number of seconds (5 seconds or more) between the execution of each use case in requirement.csv.	Payload	Integer	No	5
testMode	Mode in which concurrent usages simulation has to run. Possible values are 0, 1, 2 and 3.	Payload	Integer	No	0
	 0 - Default mode: Adds simulated users to the environment and assigns them the Service Administrator role, runs the simulation, and then deletes the simulated users. This mode is useful if you want to run the test only one time. The simulated users have these properties: First Name: testuser1, testuser2, and so on Last Name: testuser1, testuser2, and so on Email Address: testuser1@example.oracle.com , and so on Username: testuser1, testuser2, and so on Username: testuser1, testuser2, and so on To Add Users Only: Adds simulated users to the environment and assigns them the Service Administrator role, but does not run the simulation or delete the simulated users. 2 - Delete Users Only: Deletes simulated users created in a previous concurrent usage simulation run. Does not create users or run the simulation. 3 - Simulation Only: Runs the simulation using already existing simulated users without adding or deleting users. 4 - Use Existing Users: Includes users defined in the users .csv file included in the input ZIP file. In this mode, the simulated users are not created.				

Example URL and Payload

```
{
    "inputFile": "<ZIP_FILE_NAME>",
    "numberOfIterations": 1,
    "testMode": 0,
    "notificationEmails": "<EMAIL_ADDRESS>",
    "lagTime": 5
}
```

https://<BASE URL>/interop/rest/v1/concurrentusage/run

Sample Request

```
{
    "inputFile" : "InputFiles2.zip",
    "numberOfIterations" : 1,
    "testMode" : 0,
    "notificationEmails" : "abc@example.oracle.com",
    "lagTime" : 10
}
```

Response

Supported Media Types: application/json

Name	Description
details	In the case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Possible values: self or Job Status. If the value is set to Job Status, you
	can use the href to get the status
data	null

Table 13-3 Parameters

Example of Response Body

Example 1: Error Case

```
{
   "details": "InputFile is missing in request body",
   "status": 1,
   "items": null,
   "links": [{
        "href": "https://<BASE URL>/interop/rest/v1/concurrentusage/run",
        "action": "POST",
        "rel": "self",
        "data": {
    }
}
```



```
"jobType": "RUN_CONCURRENTUSAGE",
    "numberOfIterations": 2,
    "testMode": 0,
    "lagTime": 5,
    "inputfile": "",
    "notificationEmails": "abc@example.oracle.com"
}
```

Example 2: Success Case

}

```
{
    "details": null,
    "status": -1,
    "items": null,
    "links": [{
        "href": "https://<BASE URL>/interop/rest/v1/concurrentusage/run",
        "action": "POST",
        "rel": "self",
        "data": {
            "jobType": "RUN CONCURRENTUSAGE",
            "numberOfIterations": 2,
            "testMode": 0,
            "lagTime": 5,
            "inputfile": "InputFiles2.zip",
            "notificationEmails": "abc@example.oracle.com"
            }
            },
        {
            "href": "https://<BASE URL>/interop/rest/v1/concurrentusage/jobs/
437838742934700",
            "action": "GET",
            "rel": "Job Status",
            "data": null
        }
    1
}
```

14 Reporting REST APIs

Use the topics in this chapter to run reports with REST APIs for Account Reconciliation, Financial Consolidation and Close, Tax Reporting, and Data Management.

For reports on users with REST APIs, see User Access Report (v1) and User Access Report (v2).

Generate Report for Account Reconciliation

Generates either a single predefined Reconciliation Compliance report, predefined Transaction Matching report or a custom report.

This API is version v1.

Note:

All parameters must be specified for a report.

REST Resource

POST /arm/rest/fcmapi/{api version}/report

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 14-1 REPORT

Name	Description	Path	Required
api_version	Version of the API you are working with. This release is v1	Yes	Yes
groupName	The name of the group the report is associated with.	No	Yes
reportName	The name of the report to be generated.	No	Yes



Name	Description	Path	Required
generatedReportF ileName	The name specified by the user of the report to be generated. If this parameter is not provided, then the report will get generated with the data for reportName parameter in this table.	No	No
parameters	 Each report may have different parameters. Types of parameters: Numerical - should be in BigDecimal format. Text - standard string Date - can be in format yyyy-MM-dd for example 2020-10-01. To use the current date, use the value "CURRENT_DATE". Date/Time - can be in format yyyy-MM-dd HH:mm:ss or yyyy-MM-dd HH:mm:ss for example 2020-10-01 13:01:00, 2020-10-01T13:01:00. To use the current date and time, use the value "CURRENT_DATE_TIME". Boolean Users - user login ID List of choices - case insensitive values 	Νο	No
format	The format of the report (HTML, PDF, XLSX, CSV or CSV2).	No	No (default is PDF)
module	The module within Account Reconciliation: RC (Reconciliation Compliance) or TM (Transaction Matching.	No	No (default is RC)
emails	Comma separated list of email addresses that will receive the report once it's generated.	No	No
runAsync	Generation of report runs asynchronously (true) or synchronously (false). Oracle recommends setting this value to true (async) for larger reports. An example of request body and output is shown.	No	No (default is false)

Table 14-1 (Cont.) REPORT

Note:

If the required parameters, groupName or reportName are not specified, you receive an error.

For details about reportName or parameters, see Working with Predefined Reports in Reconciliation Compliance or Working with Predefined Reports in Transaction Matching in Administering Account Reconciliation.

For details about **Output Format**, see Generating the Report in Administering Account Reconciliation.

For details about retrieving job status while running reports, see Retrieve Job Status for a Report.

Example of request body (to be run synchronously)

```
{
"groupName":"Reconciliation Manager",
"reportName":"Balance by Account Type",
"generatedReportFileName":"myReport.pdf",
"parameters":{"Period":"June 2018","Currency Bucket": "Entered", "Rate
Type": "Accounting"},
"format":"PDF",
"module":"RC",
"emails":"user1@oracle.com,user2@oracle.com",
"runAsync":false
}
```

Example of request body (to be run asynchronously for larger reports)

```
{
"groupName":"Reconciliation Manager",
"reportName":"Balance by Account Type",
"generatedReportFileName":"myReport.pdf",
"parameters":{"Period":"June 2018","Currency Bucket": "Entered", "Rate
Type": "Accounting"},
"format":"PDF",
"module":"RC",
"emails":"user1@oracle.com,user2@oracle.com",
"runAsync":true
}
```

Response

Supported Media Types: application/json

Parameters:



Name	Description	
type	The module within Account Reconciliation: RC (Reconciliation Compliance) or TM (Transaction Matching.	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to the API call	
action	The HTTP call type	
rel	Relationship type (self, Job Status). if set to Job Status, you can use the href to get the status of the operation	
data	Parameters as key value pairs passed in the request	

Table 14-2 Parameters

Examples of Response Body

The following is an example of the response body in JSON format for a Reconciliation Compliance successfully completed report called My Report in pdf format generated synchronously (runAsync=false):

```
{
"type":"RC",
"status":0,
"details": "myReport.pdf",
"links" [{
"action": "POST",
 "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/fcm/rest/fcmapi/v1/report",
  "rel": "self"
 },
       {
            "rel": "report-content",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/interop/rest/v1/
applicationsnapshots/myReport.pdf",
            "action": "GET"
}
]
}
```

The following is an example of the response body in JSON format for a Reconciliation Compliance report generated asynchronously (runAsync=true) where the report is "In Process" and you can use the Job ID generated to retrieve the job status. See Retrieve Job Status for a Report:

```
{
  "links":[
{
  "rel":"self",
  "href": "https://<SERVICE_NAME>-
  <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/report",
  "action": "POST"
```




```
},
{
    "rel":"Job Status",
    "href": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/
    report/job/TM/10000001001009",
    "action": "GET"
}
],
"details":"In Process",
"status":-1,
}
```

Generate Report for Financial Consolidation and Close and Tax Reporting

Generates a report for Financial Consolidation and Close (Task Manager, Supplemental Data, and Enterprise Journal) and Tax Reporting (Task Manager and Supplemental Data).

This API is version v1.



Name Description Path Required Version of the API you are Yes Yes api version working with. This release is v1 The name of the group the Yes groupName No report is associated with. The name of the report to be No Yes reportName generated.



Name	Description	Path	Required
generatedReportF ileName	The user-specified name of the report to be generated. If this parameter is not provided, then the report will get generated with the data for reportName parameter in this table.	No	No
parameters	 Each report may have different parameters. Types of parameters: Numerical - should be in BigDecimal format. Text - standard string Date - can be in format yyyy-MM-dd for example 2020-10-01 Date/Time: can be in format yyyy-MM-dd HH:mm:ss or yyyy-MM-dd 'T' HH:mm:ss for example 2020-10-01 13:01:00, 2020-10-01T13:01:00 Boolean Users - user login ID List of choices - case insensitive values 	No	No
format	The format of the report (HTML, PDF, XLSX, or CSV).	No	No (Default is PDF)
module	Module for which the report is created. For Financial Consolidation and Close, use SDM (Supplemental Data Manager) or Task Manager. For Tax Reporting, use SDM (Supplemental Data Manager) or Task Manager.	No	Νο
emails	Comma separated list of email addresses that will receive the report.	No	No
runAsync	Generation of report runs asynchronously (true) or synchronously (false). Oracle recommends setting this value to true (async) for larger reports. An example of request body and output is shown.	No	No (Default is false)

Table 14-3 (Cont.) Report Parameters

For details about reportName or parameters see Using Task Manager and Supplemental Data Manager Reports.

For details about **Output Format**, see Generating the Report.

For details about retrieving job status while running reports, see Retrieve Job Status for a Report.

Example of request body (to be run synchronously)

```
{
"groupName":"Task Manager",
"reportName":"Late Tasks",
"generatedReportFileName":"myReport.pdf",
"parameters":{"Schedule": "Qtr 2 Close", "Period":"Jun" },
"format":"PDF",
"module":"Task Manager",
"emails":"user1@oracle.com,user2@oracle.com",
"runAsync":false
}
```

Example of request body (to be run asynchronously for larger reports)

```
{
"groupName":"Task Manager",
"reportName":"Late Tasks",
"generatedReportFileName":"myReport.pdf",
"parameters":{"Schedule" : "Qtr 2 Close", "Period":"Jun" },
"format":"PDF",
"module":"Task Manager",
"emails":"user1@oracle.com,user2@oracle.com",
"runAsync":true
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description
type	Type of report: SDM (Supplemental Data Management) or FCCS {Task Manager).
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to the API call
action	The HTTP call type
rel	Relationship type (self, Job Status). If set to Job Status, you can use the href to get the status of the operation.
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following is an example of the response body in JSON format for a Financial Consolidation and Close report called MyReport in pdf format that was run successfully synchronously (runAsync=false):

```
{
     "links": [
         {
             "rel": "self",
             "href":
"https://<BASE-URL>/HyperionPlanning/rest/fcmapi/v1/myReport.pdf",
             "action": "POST"
         },
         {
             "rel": "report-content",
             "href":
"https://<BASE-URL>/HyperionPlanning/rest/fcmapi/v1/myReport.pdf",
             "action": "POST"
 "GET"
         }
     ],
     "details": "MyReport.pdf",
     "type": "FCCS",
     "status": 0,
     "link": null,
     "error": null,
     "items": null
}
```

The following is an example of the response body in JSON format for a Financial Consolidate and Close report generated asynchronously (runAsync=true) where the report is "In Process" and you can use the Job ID generated to retrieve the job status. See Retrieve Job Status for a Report:

```
{
 "links":[
{
"rel":"self",
"href": "https://<SERVICE NAME>-<TENANT NAME>.<dcx>.oraclecloud.com/
HyperionPlanning/rest/fcmapi/v1/report",
"action": "POST"
},
{
"rel":"Job Status",
"href": "https://<SERVICE NAME>-<TENANT NAME>.<dcX>.oraclecloud.com/
HyperionPlanning/rest/fcmapi/v1/report/job/FCCS/100000001001009",
"action": "GET"
}
],
"details":"In Process",
"status":-1,
"type":"FCCS",
"link":null,
"error":null
"items":null
}
```



Generate User Details Report for Account Reconciliation

Generates a User Details report for **Account Reconciliation**. The **User Details** report contains information on the users who have predefined roles in the environment and lists attributes of each user (such as name and email), their status, teams, predefined roles, workflow roles, organizations, groups, and last login timestamps.

You can use the **Download** REST API to download the report after generating it.

REST Resource

POST /arm/rest/fcmapi/{api_version}/rc/export/users

A sample Account Reconciliation Access Control report:

1	A	B	C	D	E	F	G	н	1 I -	J	K	L
1	Name	User Login	Status	Teams	Email	Role	Workflow F	Preparer	Reviewer	Organizations	Power User	Last Login
2	John Doe	jdoe	Available	Admins	john.doe@example.com	Administrator		No	No			
3	Jane Doe	janedoe	Available		jane.doe@example.com	Power User		No	No			
4	App User1	app1	Available	Team A	app.user1@example.com	User		No	No			

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 14-5 REPORT

Name	Description	Path	Required
api_version	Version of the API you are working with. This release is v1	Yes	Yes
fileName	The name of the report to be generated.	No	Yes
format	The format of the report (CSV or XLS).	No	No (default = CSV)

Note:

For details about retrieving job status while running reports, see Retrieve Job Status for a Report.

Examples of request body



Example 1

```
{
   "fileName":"UserDetails.csv",
   "format":"CSV"
}
```

Example 2

```
{
   "fileName":"UserDetails.csv"
}
```

Example 3

```
{
   "fileName":"UserDetails.xls",
   "format":"xls"
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to the API call
action	The HTTP call type
rel	Relationship type can be (self, or Job Status). If set to Job Status, yo can use the href to get the status of the operation

Table 14-6 Parameters

Examples of Response Body

The following is an example of the response body in JSON format for an Account Reconciliation User Details report completed successfully:

Job Response

Job Status Response

}

```
{
    "links": [
        {
            "rel": "self",
            "href": "https:<BASE-URL>/arm/rest/fcmapi/v1/rc/job/42233",
            "action": "GET"
        },
        {
            "rel": "report-content",
            "href": "https:<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/UserDetails.csv/contents",
            "action": "GET"
        }
    ],
    "details": "File UserDetails.csv generated successfully.",
    "status": 0,
    "type": "rc",
    "link": null,
    "error": null,
    "items": null
}
```

Generate User Details Report for Financial Consolidation and Close and Tax Reporting

Generates a User Details report (for Task Manager, Supplemental Data, and Enterprise Journal user assignments) in Financial Consolidation and Close and (for Task Manager and Supplemental Data user assignments) in Tax Reporting. The **User Details** report contains information on the users who have predefined roles in the environment and lists attributes of each user (such as name and email) as well as their status, teams, predefined roles, workflow roles, organizations, groups, and last login timestamps.

You can use the **Download** REST API to download the report after generating it.

This API version is v1.

REST Resource

POST /HyperionPlanning/rest/fcmapi/{api_version}/fcm/export/users

ORACLE

A sample User Details Report:

4	A	В	с	D	E	F	G	н	1	J	к	L	м	N	0
	Name	User Login	Status	Teams	Email	Role	Workflow	Task	Task	Organizati	Last	Form	Form	Form	Groups
								Assignee	Approver		Login	Preparer	Approver	Integrator	
1															
2	John Doe	john.doe@example.com	Available	Admins	john.doe@example.com	Administrator									Service Administrator
3	Jane Doe	jane.doe@example.com	Available		jane.doe@example.com	Power User									Power User
4	user Ats	ats_user	Available		example1@example.com	User									User
5	user2 Ats	ats_user2	Available		example2@example.com	user									User
6	View User	viewUser	Available		view.user@exaple.com	Viewer									Viewer

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 14-7 REPORT

Name	Description	Path	Required
api_version	Version of the API you are working with. This release is v1	Yes	Yes
fileName	The name of the report to be generated.	No	Yes
format	The format of the report (CSV or XLS).	No	No (default = CSV)

Note:

For details about retrieving job status while running reports, see Retrieve Job Status for a Report.

Examples of request body

Example 1

```
{
   "fileName":"UserDetails.csv",
   "format":"CSV"
}
```

Example 2

```
{
   "fileName":"UserDetails.csv"
}
```



Example 3

```
{
   "fileName":"UserDetails.xls",
   "format":"xls"
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to the API call
action	The HTTP call type
rel	Relationship type can be (self, or Job Status). If set to Job Status, you can use the href to get the status of the operation

Example of Response Body

The following is an example of the response body in JSON format for User Details report completed successfully:

Job Response

```
{
    "links": [
        {
            "rel": "self",
            "href": "https:<BASE-URL>/HyperionPlanning/rest/fcmapi/v1/fcm/
export/users",
            "action": "POST"
        },
        {
            "rel": "Job Status",
            "href": "https:<BASE-URL>/HyperionPlanning/rest/fcmapi/v1/fcm/job/
39068",
            "action": "GET"
        }
    ],
    "details": "In Process",
    "status": -1,
    "type": "fcm",
    "link": {},
    "error": null,
    "items": []
}
```



Job Status Response

```
{
    "links": [
        {
            "rel": "self",
            "href": "https:<BASE-URL>/HyperionPlanning/rest/fcmapi/v1/fcm/job/
39068",
            "action": "GET"
        },
        {
            "rel": "report-content",
            "href": "https:<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/userDetail.xls/contents",
            "action": "GET"
        }
    ],
    "details": "File userDetail.xls generated successfully.",
    "status": 0,
    "type": "fcm",
    "link": null,
    "error": null,
    "items": null
}
```

Retrieve Job Status for a Report

Use this REST API to get the processing state for a report job with a specified ID. Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs.

Required Roles

Service Administrator, Power User, User, Viewer

GET /arm/rest/fcmapi/{api version}/job/{module}/{jobIdentifier}

REST Resource

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 14-9 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None

Name	Description	Туре	Required	Default
module	Module for Account Reconciliation Report (valid values are RC or TM) Valid values for Financial Close & Consolidation or Tax Reporting are SDM or FCCS (Task Manager)	Path	Yes	Yes
jobIdentifier	The ID of the job	Path	Yes	None

Parameters

Parameters

The following table summarizes the response parameters.

Name	Description
status	Status of the job: -1 = in process; 0 = completed (success); 1 = error
details	Details about the job status, such as "Big Report 10.csv" for generation of a report in csv format named Big Report 10
jobID	The ID of the job, such as 224
type	The type of report: RC (Reconciliation Compliance); TM (Transaction Matching); FCCS (Task Manager) or SDM (Supplemental Data Manager)

Table 14-10 Parameters

Supported Media Types: application/json

Examples of Response Body

The following shows an example of the response body for a completed (successful) report:

```
{
"links": [
{
        "rel": "self",
        "href": "https:<BASE-URL>/arm/rest/fcmapi/v1/report",
        "action": "POST"
    },
}
            "rel": "report-content",
        "href": "https:<BASE-URL>/interop/rest/11.1.2.3.600/
applicationsnapshots/Big+Report+10.csv/contents",
        "action": "GET"
}
],
    "details": "Big Report 10.csv".
    "status": 0,
    "type": "RC",
    "link": null,
    "error": null,
```



```
"items": null }
```

The following shows an example of the response body for an error occurring during report generation:

```
{
"links": [
{
    "rel": "self",
    "href": "https:<BASE-URL>/arm/rest/fcmapi/v1/report/job/TM/1145",
    "action": "GET"
    },
]

    "details": "Invalid query attached to the report".
    "status": 1,
    "type": "RC",
    "link": null,
    "error": null,
    "items": null
    }
```

The following shows an example of the response body for a report generation that is in process:

```
{
"links": [
{
    "rel": "self",
    "href": "https:<BASE-URL>/arm/rest/fcmapi/v1/report/job/TM/1124",
    "action": "GET"
    },
]

"details": "In Process".
"status": -1,
    "type": "RC",
    "link": null,
    "error": null,
    "items": null
    }
```

Execute Reports for Data Management

The Data Management reporting framework represents a unified solution that incorporates source and target data, templates, and user-defined SQL queries. Templates, created in Oracle Business Intelligence Publisher, consume data in XML format and generate reports dynamically. You can add SQL queries to extract data from tables, or couple them with the report parameters to extend the definition of a standard report. Data Management reports can be generated as PDF, Excel, Word, or HTML output.

Required Roles

Service Administrator, Power User



REST Resource

POST /aif/rest/{api_version}/jobs

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 14-11 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V1	Path	Yes	None
јоbТуре	The job type, REPORT	Path	Yes	None
jobName	The name of the report to be executed, such as Dimension Map For POV (Dimension, Cat, Per)	Path	Yes	None
reportFormatType	The file format of the report, pdf, xlsx, html, or excel	Path	Yes	pdf
parameters	Can vary in count and values based on the report	Path	Yes	None
Location	The location of the report, such as Comma_Vision	Path	Yes	None

Example of Request Body

The following shows an example of the request body in JSON format.

```
{
"jobType":"REPORT",
"jobName":"Dimension Map For POV (Dimension, Cat, Per)",
"reportFormatType":"PDF",
"parameters":{
    "Dimension Name":"ENTITY",
    "Category":"Actual",
    "Period":"Jan15",
    "Location":"Comma_Vision"
    }
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.

Response

The following table summarizes the response parameters.

Table 14-12 Parameters

Name	Description
jobId	The process ID generated in Data Management for the job, such as 1885
status	The job status, such as RUNNING



Name	Description
logFileName	Log file containing entries for this execution, such as outbox\logs\BESSAPP-DB_1885.log
outputFileName	Name of the output file generated; you can use this name to download the report
processType	Type of process executed, EXECUTE_REPORT
executedBy	Login name of the user used to execute the rule, such as admin
details	Returns the exception stack trace in case of an application error, or null

Supported Media Types: application/json

Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"links":
[
0]
"status":"-1",
"details":"null",
"jobId":"1885",
"jobStatus":"RUNNING",
"logFileName":"outbox/logs/1885.log",
"outputFileName":"outbox/reports",
"processType":"EXECUTE_REPORT",
"executedBy":"admin"
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.



15 Data Integration REST APIs

Use the Data Integration REST APIs to run integrations, import and export data mapping, import and export Data Integration APIs, and to execute reports.

Note:

All REST APIs used for Data Integration can be used as REST APIs for Data Management.

URL Structure for Data Integration

URL Structure

Use the following URL structure to access the Data Integration REST resources:

https://<BASE-URL>/aif/rest/{api version}/{path}

Where:

• <BASE-URL>: The first part of your service URL, before the context.

```
For example, if your service URL is https://epm-acme.epm.us-
phoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm-
acme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2-
acme.epm.us6.oraclecloud.com.
```

- api_version: API version you are developing with. The current REST API version for Data Integration is V1.
- *path*: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ internal/" in the URL.

Getting API Versions for Data Integration APIs

You can manage versions using the set of REST resources summarized in the following table.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Get API Versions for Data Integration APIs	GET	/aif/rest/
Get Information about a Specific API Version for Data Integration APIs	GET	<pre>/aif/rest/{apiVersion}</pre>

Table 15-1 Manage Versions of Data Integration APIs

Get API Versions for Data Integration APIs

Returns information about which versions are available and supported. Multiple versions might be supported simultaneously.

Note:

An API version is always supported even when deprecated.

REST Resource

GET /aif/rest/

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 15-2 Parameters

Name	Description
items	Detailed information about the API
version	The version, such as V1
lifecycle	Possible values: active, deprecated
isLatest	Whether this resource is the latest, true or false



Example of Response Body

The following shows an example of the response body in JSON format.

```
"items": [1]
{
"version": "V1"
"isLatest": "true"
"lifecycle": "active"
"links": [3]
{
   "rel": "self"
  "href": "https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/aif/rest/"
   "action": "GET"
   }, {
  "rel": "canonical"
  "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/aif/rest/"
  "action": "GET"
  },{
  "rel": "current"
  "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/aif/rest/V1"
  "action": "GET"
   }
}
}
```

Get Information about a Specific API Version for Data Integration APIs

Returns details for a specific REST API version for Data Integration.

REST Resource

GET /aif/rest/{api version}

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 15-3 Parameters

Name	Description
api_version	Version of the API you are developing with, such as V1



Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 15-4 Parameters

Name	Description
version	The version, such as V1
lifecycle	Lifecycle of the resource, active or deprecated
isLatest	Whether this resource is the latest, true or false

Example of Response Body

The following shows an example of the response body in JSON format.

Lock and Unlock POV

The lock REST API prevents data from being loaded to a selected POV by location or application associated with a current period and category.

When a location or application has been locked, you cannot import, validate, export, or rerun a validation.

You can also get the status of a single location or the status of all locactions for a period and category or a single application.

An unlock RESP API is available so that you can unlock a locked location or application.

Prerequisites:

You must have Service Administrator privileges to execute the lock and unlock REST APIs.

REST Resource

/aif/rest/V1/POV

Required Roles

Service Administrator, Power User

Method:



POST

Lock/Unlock by Location RESP API Request Parameters

The following table summarizes the request parameters for locking by location:

Table 15-5 Parameters

Name	Description	Туре	Required	Default
api_version	V1	Path	Yes	None
category	Specify the predefined Scenario value based on the POV Category from the integration (data rule) definition.	JSON payload	Yes	None
	The categories available are those that are created in the Data Integration set- up, such as "Actual."			
period	Specify the period of the POV from the integration or data load rule defined in Data Integration.	JSON payload	Yes	None
location	Specify the name of the location to lock so that data cannot be loaded to it.	JSON payload	Yes	None
locktype	Specify location for the location lock type.	JSON payload	Yes	None
operation	For a lock operation, specify lock . For an unlock operation, specify unlock .	JSON payload	Yes	None

JSON Request Payload to Lock Location Example:

```
{
"category": "Actual",
"period": "Jan-17",
"location": "FCCSAPP1_LOC1A",
"locktype":"location",
"operation": "lock"
}
```

Response to Locking a Location Example:

```
{
  "details":",
  "status": 0,
  "response": "Location:FCCSAPP1_LOC1A has been locked successfully."
}
```

JSON Request Payload to Unlock Location Example:

```
{
"category": "Actual",
"period": "Jan-17",
"location": "FCCSAPP1_LOC1A",
"locktype":"location",
```



```
"operation":"unlock"
}
```

Response to Unlocking a Location Example:

The following is an example of unlocking a location REST API response.

```
{
"details":",
"status": 0,
"response":"Location:FCCSAPP1_LOC1A has been unlocked successfully."
}
```

Lock/Unlock by Application REST API Request Parameters

Name	Description	Туре	Required	Default
api_version	V1	Path	Yes	None
category	Specify the predefined "Scenario" value based on the POV Category from the integration (data rule) definition.	JSON payload	Yes	None
	The categories available are those that were created in the Data Integration set-up, such as"Actual".			
period	Specify the period of the POV from the integration or data load rule defined in Data Integration.	JSON payload	Yes	None
application	Specify the name of the application to lock so that data cannot be loaded to it.	JSON payload	Yes	None
locktype	Specify application for the application lock type.	JSON payload	Yes	None
unlockbylocation	true/false—Boolean option for whether to unlock by location when an application is locked.	JSON payload	No	false
	If the "unlockbylocation" flag is set to "true" when locking the target application, then the system locks all rules present in the location under target application and not the application level lock.			
	If the "unlockbylocation" flag is set to "false" when locking the target application, then the system locks all rules present in the location under the target application and the application level lock.			
	Rules present for locations in the application cannot be executed when the location is unlocked until the application level lock is removed. Furthermore, when you create a new location under the locked target application, rules can't be executed in the new location until the application level lock is removed.			

Name	Description	Туре	Required	Default
operation	For a lock operation, specify lock . For an unlock operation, specify unlock .	JSON payload	Yes	None

JSON Request Payload to Lock an Application Example:

```
{
"category": "Actual",
"period": "Jan-17",
"application": "FCCSAPP1",
"locktype":"application",
"operation": "lock"
}
```

Response to Locking an Application Example:

The following is an example of locking an application REST API response.

```
{
"details":null,
"status": 0,
"response":"Application: FCCSAPP1 has been locked successfully."
}
```

JSON Request Payload to Unlock a Location for a Locked Application Example:

```
{
"category": "Actual",
"period": "Jan-17",
"application": "FCCSAPP1",
"locktype":"application",
"unlockbylocation":"true",
"operation": "lock"
}
```

Response to Unlocking a Location for a Locked Application Example:

The following is an example of unlocking a location when locking an application REST API response.

```
{
"details":null,
"status": 0,
"response":"Application: FCCSAPP1 has been locked successfully."
}
```

Get Lock Status REST API Request

Get the status of a single location or the status of all locations for a period and category or a single application.

Method:



GET

REST Resource

```
/aif/rest/V1/POV?
location=<locationname>&period=<periodname>&category=<catname>&application=<ap
plicationname>
```

REST Resource Example

/aif/rest/V1/POV?application=FCCSAPP1&period=Jan-17&category=Actual

Response

Supported Media Types: application/json

Example of Response Body

```
"details": null,
"status": 0,
"response": [
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC11"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "AD_ASO_PBCS_To_FCCS"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "AD ASO EPBCS TO FCCS"
},
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
```



```
"location": "ORCL To FCCS"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "SQL To FCCS"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC31"
},
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC23"
},
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC22"
},
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC27"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC26"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1 LOC25"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
```



```
"location": "FCCSAPP1_LOC24"
},
{
"period": "Jan-17",
"category": "Actual",
"status": "Locked",
"application": "FCCSAPP1",
"location": "FCCSAPP1_LOC21"
}
}
```

Running Integrations

Running an integration entails using the INTEGRATION job type for the jobs REST API to execute an integration or data load rule based on how periods are processed and source filters.

The INTEGRATION job type is an enhanced version of DATARULE job type (see Running Data Rules in Data Management). It is recommended that you use the INTEGRATION job type for future integration jobs.

The INTEGRATION jobtype supports running integrations/data load rules based on:

- period names provided to Planning
- Global POVs
- Planning substitution variables
- source filters selected as runtime parameters
- target options selected as runtime parameters
- existing period ranges

It also supports overriding the source filters and target options at runtime without modifying the integration definition.

Prerequisites:

You must have the required privileges to execute a specific data rule/integration.

REST Resource

/aif/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User

Request

Supported Media Types: application/json

Method:

POST



Payload:

{

}

```
"jobType":"INTEGRATION",
"jobName":"GLDATA",
"periodName":"{Mar-20}",
"importMode":"Replace",
"exportMode":"Merge",
"fileName":"inbox/GLBALANCE.txt"
```

REST Payload Description

The following table summarizes the REST payload.

Table 15-6 Parameters

Name	Description	Туре	Required	Default
api_version	V1	Path	Yes	None
јоbТуре	INTEGRATION	JSON payload	Yes	None
jobName	The name of the integration defined in Data Integration. You should enclose the rule or name in quotation marks if it contains a space.	JSON payload	Yes	None



Name	Description	Туре	Required	Default
periodname	Name of the period(s)p enclosed in curly brackets ({}).	JSON payload	Yes	None
	periodname includes:			
	 Single Period—Refers to the Data Integration period name for a single period. The parameter is whatever the period name is defined in Period mapping. Multi-Period—Refers to a multi-period load. The parameter is {Month-Year} {Month-Year}. For example, {Jan-20} {Mar-20} refers to a multi-period load from Jan-20 to Mar-20. 			
	 Planning Period Name—Refers to a Planning period name. The parameter is {Month#Year}, for example, {Jan#FY20}{Mar#FY20}. Using this convention, the client executing the API does not need to know the Data Integration period names. Instead you specify the Planning member names for the Year and Scenario dimensions. 			
	This parameter is supported in the Planning, Tax Reporting, and Financial Consolidation and Close business processes. It is functional for both your service applications and cloud deployments derived from on- premises data sources.			
	 This parameter is useful if triggered from an Oracle Enterprise Performance Management Cloud Groovy script by capturing the Year and Period member names. The application period mapping or global period mapping must exist with the Year and Month in the target values of the period mapping. Planning Substitution Variable—This is an extension of the previous Planning period name parameter whereby a substitution variable can be specified instead of the actual Year/ Month member names. 			
	The convention is {Month#&CurYr} {&FcstMonth#&CurYr}; for example, {Jan#&CurYr}{&FcstMonth#&CurYr}. A combination of both actual member names as well as substitution variables is supported.			
	This parameter is supported in the Planning,Tax Reporting, and Financial Consolidation and Close business processes. It is functional for both			

Name	Description		Туре	Required	Default
	your service app deployments de premises data s				
	 The application global period mathe Data Integra where the API is Year and Month the period mapp and Month refert the substitution execution. GLOBAL POV— 	period mapping or apping must exist in tion of the instance s executed, with the in the target values of bing. In this case, Year to the current value of variable during —Executes the data bal POV period. Use			
		Note: If you use any other period naming parameter other than the parameters described above, you get an "Invalid Input – HTTP 400 " error			



Name	Description	Туре	Required	Default
importMode	Determines how the data is imported into Data Integration. Acceptable values are:	JSON payload	Yes	None
	 Append—Add to the existing POV data in Data Integration. Replace—Delete the POV data and replace it with the data from the file. Map and Validate—Skip importing the data, but re-process the data with updated Mappings and Logic Accounts. No Import—Skip data import into Data Integration staging table. Direct—To use the direct load method to extract data from your on-premises data exercise and the data from your on-premises 			
	data sources and then load the data directly to the EPM Cloud using the EPM Integration Agent, you need to pass an importMode of "Direct." Other modes are not applicable for the direct load.			

Name	Description	Туре	Required	Default
exportMode	Determines how the data is exported into Data Integration. Acceptable values for Planning business	JSON payload	Yes	None
	 processes are: Merge—Merge the data in the Data Integration staging table with the existing Planning data. Replace—Clear the POV data and replace it with data in the Data Integration staging table. The data is cleared for Scenario, Version, Year, Period, and Entity dimensions. Accumulate—Add the data in the Data Integration staging table to Planning. Subtract—Subtract the data in the Data Integration staging table from existing Data Integration data. No Export—Skip data export from Data Integration to Planning. Acceptable values for Financial Consolidation and Close and Tax Reporting are: Merge—Merge the data in the staging 			
	 table with the data in the Financial Consolidation and Close and Tax Reporting application. If data already exists in the application, the system overwrites the existing data with the new data from the load file. If data does not exist, the new data is created. Replace—Delete the POV data and replace it with the data from the file. No Export—Skip the data export from Data Integration to Financial Consolidation and Close or Tax Reporting If you use a regular data load for the Numeric Data Only and Numeric Data and All Data Type load methods, note the export mode requirements based on the load method: 			
	 For a Numeric Data Only load method, Accumulate and Subtract are the applicable export modes. For a Numeric Data and All Data Type load method, Merge, Replace, and No Export are the applicable export modes. If you use the direct data load to extract data from your on-premises data sources and then load the data directly to the EPM Cloud using the EPM Integration Agent, 			

Name	Description	Туре	Required	Default
	note the export mode requirements based on the load method:			
	 For a Numeric Data Only load method, Merge, Accumulate, and Subtract are the applicable export modes. 			
	 For a Numeric Data and All Data Type load method, only Replace is the applicable export mode. 			
	 The No Export mode is not applicable for the Numeric Data Only and Numeric Data and All Data Type load methods. 			
	When running a Quick Mode load, valid export modes are:			
	ReplaceMergeAccumulate			
fileName	The fileName parameter is applicable only for native file-based data loads and ignored if specified for other loads.	JSON payload	No	None
	The file name is optional. If you do not specify a file name, this API imports the data contained in the file name specified in the load data rule. The data file must already reside in the Inbox prior to executing the data load rule, for example, . inbox/GLBALANCES.txt.			
	You can also upload file to folders accessible from the Applications- Inbox/Outbox Explorer using a file name. Reference the files in this folder using this format:: #epminbox/ <filename>.</filename>			

Name	Description	Туре	Required	Default
sourceFilters	A parameter used to update the source filters defined for the data load rule or integration.	JSON payload	No	None
	File-based applications—You cannot use the sourceFilters parameter for file-based applications. If you use this parameter with a file-based application, you get the HTTP 400 error message: "EPMFDM-ERROR: Data Load Rule does not support sourceFilters for File based loads."			
	Data Source based applications— Replaces the pre-defined source filter parameters at the rule level for a data load rule/integration or specifies them at runtime (if not pre-defined at application level when the data source is the type of source application.			
	Each filter name and its value should be sent as a key/value pair in the nested JSON object. The parameter name and value should be the English display names as seen in the user interface. Do not specify internal codes for parameter names and values using LOV validation. LOV validation is done for parameters having a restricted list of parameter values.			
	All filter names are not mandatory. Only filter names specified in the nested JSON object are replaced or set at runtime. The remaining filters are picked from the application/rule definition.			
	Oracle Essbase/Planning/Oracle General Ledger-based applications—Replaces the already defined dimension source filters for a data load rule/integration at runtime when Essbase/Planning/Oracle General Ledger balance type are the source applications.			
	Each dimension name and its value should be sent as a key/value pair in the nested JSON object.			
	Replacing or setting the dimension filters at run time is only supported for dimensions already having a filter defined in the data load rule/integration definition.			
	All filter names are not mandatory. Only dimension names specified in the nested JSON object will be replaced or set in runtime. The remaining filters are picked from data rule/integration definition.			
	Dimension filters are supported for all dimensions including the "Scenario" dimension. The "Year" and "Period" dimensions are not supported as filters			

Name	Description	Туре	Required	Default
	because they are driven by the POV range.			
	All other source applications are not supported.			
targetOptions	A parameter used to update the target options defined for the data load rule or integration.	JSON payload	No	None
	Data Export based applications— Replaces the pre-defined target option parameters at the rule level for a data load rule/integration or specifies them at runtime (if not pre-defined at the rule level) when the Data Export is the type of target application.			
	Each option name and its value should be sent as a key/value pair in the nested JSON object. The parameter name and value should be the English display names as seen in the user interface. Do not specify internal codes for parameter names and values using the LOV validation. LOV validation is done for parameters having a restricted list of parameter values.			
	All option names are not required. Only option names specified in the nested JSON object are replaced or set at runtime. The remaining options are picked from the application/rule definition.			
	Planning target application—Replaces the following options at runtime.			
	 Refresh Database—Yes/No Dimension Name—Specify a dimension name for a custom dimension load rule. In this way the same rule can be used to build multiple dimensions in runtime. Purge Data File—Yes/No 			
	Other target applications are not			

Name	Description	Туре	Required	Default
executionMode	The executionMode parameter is applicable only for Quick Mode integrations.	JSON payload	Yes	None
	Available options:			
	 SYNC—When executionMode is SYNC, then the REST API call submits and waits until the integration has completed (that is, reached either a successful, failed, or warning state) before returning a response. ASYNC—When executionMode is ASYNC, then the REST API call returns a response immediately without waiting for the integration to complete. Usually the integration is in a running state when the REST API response is received. 			
	executionMode is a mandatory			
	parameter and cannot be blank.			

Sample REST Payloads

Below are sample payloads based on the source application type.

File Based Loads

In this example, the source is a text file running an integration through a native File adapter:

```
{
"jobType":"INTEGRATION",
"jobName":"ERPDATA",
"periodName":"{Jan-20}",
"importMode":"REPLACE",
"exportMode":"NONE",
"fileName":"inbox/TestData.txt"
}
```

Planning Applications

In these examples, the source is an Essbase/Planning based application. The supported applications include:

- Planning modules
- Reporting cubes (plan types) of Planning
- Financial Consolidation and Close
- Tax Reporting
- Profitability and Cost Management
- Oracle ERP Cloud Oracle General Ledger Balances Cube



Example of Planning to Financial Consolidation and Close Data Synchronization

```
{
  "jobType":"INTEGRATION",
  "jobName":"PBCStoFCCS",
  "periodName":"{Jan-20}",
  "importMode":"REPLACE",
  "exportMode":"NONE",
  "sourceFilters":{
      "Account":"@RELATIVE(Acc1,0)",
      "Entity":" @CHILDREN(Europe)",
      "Scenario":"Actual"
}
```

Example of Planning to a Data Export to File

```
"jobType":"INTEGRATION",
"jobName":"PBCStoFCCS",
"periodName":"{Jan-20}",
"importMode": "REPLACE",
"exportMode": "NONE",
"sourceFilters":{
    "Account": "@RELATIVE (Acc1, 0) ",
    "Entity":" @CHILDREN(Europe)",
    "Scenario":"Actual"
},
"targetOptions":{
    "Download File Name": "PlanningToFile.csv",
    "Column Delimiter":",",
    "Include Header":"Yes"
}
}
```

Data Source Applications

Example of Incremental File adapter:

```
{
"jobType":"INTEGRATION",
"jobName":"MyIncrementalFileLoad",
"periodName":"{Jan-20}{Mar-20}",
"importMode":"REPLACE",
"exportMode":"NONE",
"sourceFilters":{"Source File":"File1.txt"}
}
```

Example of Netsuite adapter:

```
{
"jobType":"INTEGRATION",
"jobName":"NetsuiteLoad",
"periodName":"{Jan-20}{Mar-20}",
```



```
"importMode":"REPLACE",
"exportMode":"NONE",
"sourceFilters":{
    "Postingperiod":"This Fiscal Quarter",
    "Mainline":"True"
}
```

Example of exporting Oracle NetSuite adapter toPlanning dimensions (metadata rule):

```
{
"jobType":"INTEGRATION",
"jobName":"NetsuiteMetadataLoad",
"periodName":"{Jan-20}{Mar-20}",
"importMode":"REPLACE",
"exportMode":"NONE",
"targetOptions":{
    "Refresh Database":"Yes",
    "Dimension Name":"Product"
}
```

Example of Oracle ERP Cloud (Payables Transactions):

Example of Quick Mode integration:

```
{
{
    "jobType":"INTEGRATION",
    "jobName":"QuickMode_LOC1_DL1",
    "periodName":"{Jan-17}",
    "importMode":"Direct",
    "exportMode":"Merge",
    "executionMode":"ASYNC"
}
```

Response

Supported Media Types: application/json



Running a Pipeline

Executes a Pipeline based on job parameters and variables that you select.

The Pipeline jobtype supports running a Pipeline based on the variable list (depends on how many variables have been defined for the Pipeline in the Data Integration user interface.)

Prerequisites:

- You must have predefined the Pipeline to run it.
- You must have the required privileges to execute a Pipeline.

REST Resource

```
/aif/rest/{api_version}/jobs
```

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Method:

POST

Payload:

REST Payload Description

The following table summarizes the REST payload.

Table 15-7 Parameters

Name	Description	Туре	Required	Default
api_version	V1	Path	Yes	
jobType	PIPELINE	JSON payload	Yes	



Name	Description	Туре	Required	Default
jobName	The Pipeline code defined for the Pipeline in Data Integration.	JSON payload	Yes	
	The code can contain up to 30 alphanumeric characters with a minimum of 3 characters and a maximum of 30 characters. This code cannot be updated after a Pipeline is created.			
variables	Name of the variable(s) used in the Pipeline.	JSON payload	No	
	The list depends on how many variables have been defined in the Pipeline.			
	The default out-of-box variables include:			
	STARTPERIOD			
	ENDPERIOD			
	IMPORTMODEEXPORTMODE			
	ATTACH_LOGS			
	• SEND_MAIL			
	• SEND_TO			
STARTPERIOD	The first period for which data is to be loaded. This period name must be defined in Data Integration Period mapping.		Yes	
	You can also specify a Planning substitution variable whereby a substitution variable can be specified instead of the actual Year/Month member names for the start period.			
	The convention is {Month#&CurYr} {&FcstMonth#&CurYr}; for example, {Jan#&CurYr} {&FcstMonth#&CurYr}.			
	A combination of both actual member names as well as substitution variables is supported.			
	This parameter is supported in the Planning, Tax Reporting, and Financial Consolidation and Close business processes. It is functional for both your service applications and cloud deployments derived from on- premises data sources.			
ENDPERIOD	The last period for which data is to be loaded. This period name must be defined in Data Integration period mapping.	JSON payload	Yes	
	You can also specify a Planning substitution variable whereby a substitution variable can be specified instead of the actual Year/Month member names for the start period.			
	The convention is {Month#&CurYr} {&FcstMonth#&CurYr}; for example, {Jan#&CurYr} {&FcstMonth#&CurYr}.			
	A combination of both actual member names as well as substitution variables is supported.			
	This parameter is supported in the Planning, Tax Reporting, and Financial Consolidation and Close business processes. It is functional for both your service applications and cloud deployments derived from on- premises data sources.			

Table 15-7(Cont.) Parameters



Name	Description	Туре	Required Default
IMPORTMODE	Determines how the data is imported into Data Integration. Acceptable values are: • Append—Add to the existing POV data in Data		Yes
	 Integration. Replace—Delete the POV data and replace it with t data from the file. 	he	
	 Map and Validate—Skip importing the data, but re process the data with updated Mappings and Logic Accounts. 		
	 No Import—Skip data import into Data Integration staging table. 	l	
exportMode	Determines how the data is exported into Data Integration. Acceptable values for Planning business processes are:		Yes
	 Merge—Merge the data in the Data Integration staging table with the existing Planning data. 		
	 Replace—Clear the POV data and replace it with data in the Data Integration staging table. The data cleared for Scenario, Version, Year, Period, and Entity dimensions. 	ı is	
	• Accumulate—Add the data in the Data Integration staging table to Planning.		
	 No Export—Skip data export from Data Integration to Planning. 		
	Acceptable values for Financial Consolidation and Clos and Tax Reporting are:		
	 Merge—Merge the data in the staging table with th data in the Financial Consolidation and Close and Tax Reporting application. 	ie	
	If data already exists in the application, the system overwrites the existing data with the new data from the load file. If data does not exist, the new data is created.		
	• Replace—Delete the POV data and replace it with t data from the file.	he	
	 No Export—Skip the data export from Data Integration to Financial Consolidation and Close or Tax Reporting 	r	
ATTACH_LOGS	• Yes—Logs are zipped and included as an attachme to an email, which can then be download	nt	No
	 No—Logs are not included as an attachment to an email. 		

Table 15-7(Cont.) Parameters

Table 15-7 (Cont.) Parameters

Name	Description	Туре	Required Default
SEND_MAIL	Determines when an email is sent when a Pipeline is run. Options include:		
	Always		
	No—Default value		
	• On Failure		
	On Success		
	For variables, the default value is set in the Pipeline definition. Overriding individual variables is done by passing it in the JSON payload, for example, STARTPERIOD.		
SEND_TO	Determines the recipient email ID for the email notification.		No
	Email IDs are comma separated.		

Import Data Mapping

Member mappings are used to derive the target members for each dimension based on source value. Member mappings are referenced during the data load, enabling Data Integration to determine how to dimensionalize the data that is loaded to the target application. Member mappings define relationships between source members and target dimension members within a single dimension. You must create a member mapping for each target dimension.

You can import member mappings from a selected Excel, .CSV or .TXT file. You can also create new mappings in a text file and import them. Import member mappings support merge or replace modes, along with validate or no validate options for target members.

REST Resource

POST /aif/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 15-8 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V1	Path	Yes	None
jobType	The job type, MAPPINGIMPORT	Path	Yes	None
jobName	The dimension name for a specific dimension to import, such as ACCOUNT, or ALL to import all dimensions	Path	Yes	None



Name	Description	Туре	Required	Default
fileName	The file and path from which to import mappings. The file format can be .CSV, .TXT, .XLS, or .XLSX. The file must be uploaded prior to importing, either to the inbox or to a sub-directory of the inbox. Include the inbox in the file path, for example,inbox/ BESSAPPJan-06.csv	Path	Yes	None
importMode	The import mode: MERGE to add new rules or replace existing rules, or REPLACE to clear prior mapping rules before import	Path	No	MERGE
validationMode	Whether to use validation mode, true or false An entry of true validates the target members against the target application; false loads the mapping file without any validations. Note that the validation process is resource intensive and takes longer than the validation mode of false; the option selected by most customers is false	Path	No	false
locationName	The Data Integration location where the mapping rules should be loaded; mapping rules are specific to a location in Data Integration.	Path	No	None

Table 15-8 (Cont.) Parameters

Example of Request Body

The following shows an example of the request body in JSON format.

```
{
"jobType":"MAPPINGIMPORT",
"jobName":"ACCOUNT"
"fileName":"inbox/BESSAPPJan-06.csv",
"importMode":"MERGE",
"validationMode":"false",
"locationName":"BESSAPP"
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.

Response

The following table summarizes the response parameters.

Table 15-9 Parameters

Name	Description		
jobId	The process ID generated in Data Management for the job, such as 1880		
jobStatus	The job status, such as RUNNING		
logFileName	Log file containing entries for this execution, such as outbox/logs/ BESSAPP-DB_1880.log		
outputFileName	Name of the output file generated, if any, or else null		
processType	Type of process executed, IMPORT_MAPPING		
executedBy	Login name of the user used to execute the rule, such as admin		
details	Returns the exception stack trace in case of an application error, or null		

Supported Media Types: application/json

Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"links":
[
0]
"status":"-1"
"details":"null"
"jobId":"1880"
"jobStatus":"RUNNING",
"logFileName":"nulbox/logs/BESSAPP-DB_1880.log",
"outputFileName":"null",
"processType":"IMPORT_MAPPING",
"executedBy":"admin"
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.

Export Data Mapping

Member mappings are used to derive the target members for each dimension based on source value. Member mappings are referenced during the data load, enabling Data Integration to determine how to dimensionalize the data that is loaded to the target application. Member mappings define relationships between source members and target dimension members within a single dimension. You must create a member mapping for each target dimension.

You can export member mappings to a selected file of format .csv, .txt, .xls, or .xlsx.

REST Resource

```
POST /aif/rest/{api_version}/jobs
```



Required Roles

Service Administrator, Power User

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 15-10 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V1	Path	Yes	None
јоbТуре	The job type, MAPPINGEXPORT	Path	Yes	None
jobName	The dimension name for a specific dimension to import, such as ACCOUNT, or ALL to import all dimensions	Path	Yes	None
fileName	The file and path from which to export mappings. The file format can be .CSV, .TXT, .XLS, or .XLSX. Include the outbox in the file path, for example, outbox/BESSAPPJan-06.csv	Path	Yes	None
locationName	The name of the location, such as BESSAPP	Path	Yes	None

Example of Request Body

The following shows an example of the request body in JSON format.

```
{
"jobType":"MAPPINGEXPORT",
"jobName":"ACCOUNT",
"fileName":"outbox/BESSAPPJan-06.csv",
"locationName":"BESSAPP"
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.

Response

The following table summarizes the response parameters.

Table 15-11 Parameters

Name	Description
jobId	The process ID generated in Data Integration for the job, such as 1881
jobStatus	The job status, such as SUCCESS
logFileName	Log file containing entries for this execution, such as outbox/logs/ BESSAPP-DB_1881.log
outputFileName	Name of the output file generated, such asoutbox/ BESSAPPJan-06.csv
processType	The type of process executed, EXPORT_MAPPING



Table 15-11 (Cont.) Parameters

Name Description	
executedBy	Login name of the user used to execute the rule, such as admin
details	Returns the exception stack trace in case of an application error, or else null

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"links":
[
0]
"status":"0",
"details":"null",
"jobId":"1881",
"jobStatus":"SUCCESS",
"logFileName":"outbox/logs/BESSAPP-DB_1881.log",
"outputFileName":"outbox/BESSAPPJan-06.csv",
"processType":"EXPORT_MAPPING",
"executedBy":"admin"
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.

Export Data Integration

The Export Data Integration API enables you to back up setup and staging data in Data Integration as a snapshot.

REST Resource

/aif/rest/V1/snapshots

Required Roles

Service Administrator, Power User

Method

POST

{

Request

Supported Media Types: application/json

Sample REST API Payload for Export Data Integration

```
"action":"EXPORT",
"snapshotType":"ALL",
```



```
"fileName":"MyBackup.zip",
"overwriteFile":true
```

The following table summarizes the client request.

Table 15-12 Parameters

}

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V1.	Path	Yes	None
action	EXPORT	Payload	Yes	None
snapshottype	 Snapshot type: ALL, ALL_INCREMENTAL, INCREMENTAL, SETUP ALL—Include all setup and staging data. ALL_INCREMENTAL—Include only new or changed staging data based on the POV since the last snapshot was exported and include SETUP and all POVs (old and new) in the output file. INCREMENTAL—Include only new or changed staging data based on the POV since the last snapshot was exported and include only SETUP and new POVs in the output file. SETUP—Include only setup data. 	Payload	Yes	None
fileName	Name of the output file in ZIP format. This file is generated in the outbox as: outbox/ <filename>.zip.</filename>	Payload	Yes	None
	If the file doesn't end with a ZIP extension, Data Management appends the ZIP file extension at the end of the file name.			
overwriteFile	true/false—Boolean option to specify whether or not to replace the output file specified in the filename parameter. This parameter prevents a user from accidentally overwriting the output file if it already exists by throwing a HTTP 400 error.	Payload	No	false

Response

The following table summarizes the response parameters.

Name	Description
action	Always EXPORT
snapshotType	Name of the snapshot type
jobId	The process ID generated in Data Integration for the job, such as 1880
links	Describes links to other resources and actions applicable on the current resource.
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 =cancel pending; 3 = cancelled; 4 = invalid parameter;Integer.MAX_VALUE = unknown

Table 15-13 Parameters

Supported Media Types: application/json

The following shows an example of the response in JSON format.

```
{
    "action": "EXPORT",
    "snapshotType": "SETUP",
    "jobId": 423,
    "links": [
        {
            "rel": "self",
                "href": "https://<BASE-URL>/aif/rest/v1/jobs/jobID",
                "action": "GET"
        }
    ],
    "status": -1
}
```

Import Data Integration

The Import Data Integration API enables you to restore setup and staging data from one environment to another. The system clears the existing data in the target environment and then imports the data from the backup files without merging any operations.

REST Resource

/aif/rest/V1/snapshots

Required Roles

Service Administrator, Power User

Method

POST

Request

Supported Media Types: application/json



Sample REST API Payload for Import Data Integration

```
{
    "action":"IMPORT",
    "fileName":"inbox/MyBackup.zip"
}
```

The following table summarizes the client request.

Table 15-14 Parameters

Name	Description	Туре	Required	Default
action	IMPORT	Payload	Yes	None
filename	File name of the import snapshot (for example: inbox/ <filename>.zip, or inbox/ mybackup/<filename>.zip).</filename></filename>	Payload	Yes	None
	If no path is specified, it is assumed that the file is in the Data Integration root folder. (Files to the Data Integration root folder can only be uploaded from the Data Integration user interface.)			

Response

The following table summarizes the response parameters.

Table 15-15 Parameters

Name	Description
action	Always IMPORT
jobId	The process ID generated in Data Integration for an import Data Integration job is "0."
links	Describes links to other resources and actions applicable on the current resource.
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 =cancel pending; 3 = cancelled; 4 = invalid parameter;Integer.MAX_VALUE = unknown

Supported Media Types: application/json

The following shows an example of the response in JSON format.

```
{
    "action": "IMPORT",
    "jobId": 0,
    "links": [
        {
            "rel": "self",
            "rel": "self",
            "self",
```



```
"href": "https://<BASE-URL>/aif/rest/v1/jobs/jobID",
"action": "GET"
}
],
"status": -1
}
```

Retrieve Job Status

Polls the environment to get the processing state for a job with a specified ID.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. **Required Roles**

Service Administrator, Power User

Rest Resource

```
GET /application/rest/{api_version}/applications/{application}/jobs/
{jobIdentifier}
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 15-16	Parameters
-------------	-------------------

Name	Description
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 = cancel pending; 3 = cancelled; 4 = invalid parameter; Integer.MAX_VALUE = unknown
details	Details about the job status, such as "SUCCESS" when member mappings have been processed successfully.
jobID	The ID of the job, such as 228
jobName	The name of the job, such as BESSAPP
descriptiveStatus	The status of the job, such as Completed or Error

Supported Media Types: application/json

Example of Response Body

The following is an example of the response body in JSON format that shows the job status when member mappings are exported.

```
{
"links":
```



```
[
0]
"status":"0",
"details":"null",
"jobId":"1881",
"jobStatus":"SUCCESS",
"logFileName":"outbox/logs/BESSAPP-DB_1881.log",
"outputFileName":"outbox/BESSAPPJan-06.csv",
"processType":"EXPORT_MAPPING",
"executedBy":"admin"
}
```

16 Data Management REST APIs

Use the Data Management REST APIs to run data rules and batch rules.

Note:

All REST APIs used for Data Integration can be used as REST APIs for Data Management.

URL Structure for Data Management

URL Structure

Use the following URL structure to access the Data Management REST resources:

https://<BASE-URL>/aif/rest/{api version}/{path}

Where:

<BASE-URL>: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- api_version: API version you are developing with. The current REST API version for Data Management is V1.
- *path*: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ <code>internal/"</code> in the URL.

Getting API Versions for Data Management APIs

You can manage versions using the set of REST resources summarized in the following table.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Getting API Versions for Data Management APIs	GET	/aif/rest/
Get Information about a Specific API Version for Data Management APIs	GET	/aif/rest/{apiVersion}

Table 16-1 Manage Versions of Data Management APIs

Get API Versions for Data Management APIs

Returns information about which versions are available and supported. Multiple versions might be supported simultaneously.

Note:

An API version is always supported even when deprecated.

REST Resource

GET /aif/rest/

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 16-2 Parameters

Name Description		
items	Detailed information about the API	
version	The version, such as V1	
lifecycle	Possible values: active, deprecated	
isLatest	Whether this resource is the latest, true or false	



Example of Response Body

The following shows an example of the response body in JSON format.

```
"items": [1]
{
"version": "V1"
"isLatest": "true"
"lifecycle": "active"
"links": [3]
{
   "rel": "self"
   "href": "https://<BASE-URL>/aif/rest/"
  "action": "GET"
  },{
   "rel": "canonical"
   "href": "https://<BASE-URL>/aif/rest/"
  "action": "GET"
   },{
   "rel": "current"
  "href": https://<BASE-URL>/aif/rest/V1"
  "action": "GET"
   }
}
}
```

Get Information about a Specific API Version for Data Management APIs

Returns details for a specific REST API version for Data Management.

REST Resource

```
GET /aif/rest/{api_version}
```

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 16-3 Parameters

Name	Description
api_version	Version of the API you are developing with, such as V1



Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 16-4 Parameters

Name	Description
version	The version, such as V1
lifecycle	Lifecycle of the resource, active or deprecated
isLatest	Whether this resource is the latest, true or false

Example of Response Body

The following shows an example of the response body in JSON format.

Running Data Rules in Data Management

Executes a Data Management data load rule based on the start period and end period, and import or export options that you specify.

Prerequisites

- Data Rules: Data load rules define how Integrations load data from a file. You must have predefined data load rules to load data.
- You must have the required privileges to execute a specific data rule.

REST Resource

POST /aif/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.



Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V1	Path	Yes	None
јоbТуре	should be set to "DATARULE"		Yes	None
jobName	The name of a data load rule defined in Data Management. You should enclose the rule name in quotation marks if it contains a space.		Yes	None
startPeriod	The first period for which data is to be loaded. This period name must be defined in Data Management period mapping.		Yes	None
endPeriod	The last period for which data is to be loaded. This period name must be defined in Data Management period mapping.		Yes	None
importMode	Determines how the data is imported into Data Management. Acceptable values are:		Yes	None
	 APPEND to add to the existing POV data in Data Management REPLACE to delete the POV data and replace it with the data from the file. RECALCULATE to skip importing the data, but re-process the data with updated Mappings and Logic Accounts. NONE to skip data import into Data Management staging table 			

Table 16-5 Parameters

Name	Description	Туре	Required	Default
exportMode	 Determines how the data is exported into Data Management. Acceptable values for Planning Modules and Planning are: STORE_DATA to merge the data in the Data Management staging table with the existing Planning data ADD_DATA to add the data in the Data Management staging table to Planning SUBTRACT_DATA to subtract the data in the Data Management staging table to Planning SUBTRACT_DATA to clear the POV data and replace it with data in the Data Management staging table. The data is cleared for Scenario, Version, Year, Period, and Entity NONE to skip data export from Data Management to Planning Acceptable values for Financial Consolidation and Close and Tax Reporting are: REPLACE to delete the POV data and replace it with the data from the file MERGE: By default, all data load is processed in the Merge mode. If data already existed in the application, the system overwrites the existing data with the new data from the load file. If 	Type	Yes	None
	data does not exist, the new data will be created.			
fileName	• NONE to skip the data export An optional file name. If you do not specify a file name, this API imports the data contained in the file name specified in the load data rule. The data file must already reside in the Inbox prior to data rule execution.		Yes	None
	Import data files from the EPM INBOX accessible from the Applications-Inbox/ Outbox Explorer using a file name. Reference the files in this folder using #epminbox/ <filename>.</filename>			

Table 16-5 (Cont.) Parameters

Example URL

https://<BASE-URL>/aif/rest/V1/jobs
Example of Request Body

```
{"jobType":"DATARULE",
"jobName":"aso to bso dr",
"startPeriod":"Dec-18",
"endPeriod":"Dec-18",
```



```
"importMode":"REPLACE",
"exportMode":"NONE",
"fileName":"#epminbox/TestData.txt"
}
```

Response

Supported Media Types: application/json

Table 16-6 Parameters

Name	Description
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 = cancel pending; 3 = cancelled; 4 = invalid parameter
jobStatus	A text representation of the job status, with one of the following values" RUNNING," "SUCCESS," and "FAILED".
jobId	The process ID generated in Data Management for the job
logFileName	Log File containing entries for this execution.
outputFileName	Name of the output file generated, if any.
processType	Type of the process executed. Will contain "COMM_LOAD_BALANCES" for all Data Rule executions
executedBy	Login name of the user used to execute the rule.
details	Returns the exception stack trace in case of an application error

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "jobStatus": "RUNNING",
    "jobId": 2019,
    "logFileName": "\outbox\logs\Account Reconciliation Manager_2019.log",
    "outputFileName": null,
    "processType": "COMM_LOAD_BALANCES",
    "executedBy": "admin",
    "status": -1,
    "links": [1],
        0:    {
            "rel": "self",
            "href": "https://<BASE-URL>/aif/rest/V1/jobs/2019",
            "action": "GET",
    }
    "details": null
}
```

Running Batch Rules

Executes a batch of jobs that have been defined in Data Management .

Prerequisites



- The batch must be defined in Data Management before it can be executed using the REST API.
- You must have the required privileges to execute a specific batch.

REST Resource

POST /aif/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 16-7 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V1	Path	Yes	None
јоbТуре	should be set to "BATCH"		Yes	None
jobName	The name of a batch defined ir Data Management.	ו	Yes	None

Example URL

https://<BASE-URL>/aif/rest/V1/jobs
Example of Request Body

```
{"jobType":"BATCH",
"jobName":"BatchDataLoad"
}
```

Response

The following table summarizes the response parameters.

Table 16-8 Parameters

Name	Description
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 = cancel pending; 3 = cancelled; 4 = invalid parameter
jobStatus	A text representation of the job status, with one of the following values "RUNNING", "SUCCESS". "FAILED"
jobld	The process Id generated in Data Management for the job
logFileName	Log File containing entries for this execution.
outputFileName	Name of the output file generated, if any.
processType	Type of the process executed. Will contain "COMM_BATCH" for all Data Rule executions
executedBy	Login name of the user used to execute the rule.
details	Returns the exception stack trace in case of an application error

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "jobStatus": "SUCCESS",
"jobId": 2024,
"logFileName": "\outbox\logs\BATCH1 7595.log",
"outputFileName": null,
"processType": "COMM BATCH",
"executedBy": "admin",
"status": -1,
"links": [1],
    0: {
    "rel": "self",
    "href": "https://<BASE-URL>/aif/rest/V1/jobs/2016",
    "action": "GET",
}
"details": null
}
```

For sample code, see the code samples included in Running Data Rules in Data Management.

Retrieve Job Status

Polls the environment to get the processing state for a job with a specified ID.

Using this REST API requires prerequisites, such as understanding how to use jobs. See Prerequisites. Be sure that you understand how to use jobs as described in Managing Jobs. Required Roles

Service Administrator, Power User

REST Resource

```
GET /application/rest/{api_version}/applications/{application}/jobs/
{jobIdentifier}
```

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 16-9 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
applicationName	The name of the application	Path	Yes	None
jobIdentifier	The ID of the job	Path	Yes	None



Response

Parameters

The following table summarizes the response parameters.

Table 16-10 Parameters

Name	Description
status	Status of the job: -1 = in progress; 0 = success; 1 = error; 2 = cancel pending; 3 = cancelled; 4 = invalid parameter; Integer.MAX_VALUE = unknown
details	Details about the job status, such as "SUCCESS" when a batch has processed successfully.
jobID	The ID of the job, such as 226
jobName	The name of the job, such as BATCH1
descriptiveStatus	The status of the job, such as Completed or Error

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body in JSON format when a batch is run.

```
{
"jobStatus": "SUCCESS",
"jobId": 2024,
"logFileName": "\outbox\logs\BATCH1 7595.log",
"outputFileName": null,
"processType": "COMM BATCH",
"executedBy": "admin",
"status": -1,
"links": [1],
   0: {
   "rel": "self",
   "href": "https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/aif/rest/V1/jobs/2024,
   "action": "GET"
}
"details": null
}
```

17 Account Reconciliation APIs

Use the Account Reconciliation REST APIs to get the REST API version, create reconciliations, change period status, import pre-mapped transactions, import profiles, import currency rates, import balances, import pre-mapped balances, monitor reconciliations, and retrieve job status. In Transaction Matching, you can use REST APIs to import pre-mapped transactions, or run auto match.

URL Structure for Account Reconciliation

This topic shows the general URL structure for Account Reconciliation REST APIs..

Use the following URL structure to access the Account Reconciliation REST resources:

https://<BASE-URL>/armARCS/rest/{api version}/{path}

Where:

• <BASE-URL>: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- *api_version*: API version you are developing with. The current REST API version for Account Reconciliation is V1.
- *path*: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ internal/" in the URL.

Getting API Versions for Account Reconciliation REST APIs

You can manage versions using the set of REST resources summarized in the following table.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Task	Request	REST Resource
Get API Versions for Account Reconciliation REST APIs	GET	/armARCS/rest/
Get Information about a Specific API Version for Account Reconciliation REST APIs	GET	<pre>/armARCS/rest/{apiVersion}</pre>

Table 17-1 Manage Versions of Account Reconciliation APIs

Get API Versions for Account Reconciliation REST APIs

Returns information about which versions are available and supported. Multiple versions might be supported simultaneously.



Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

GET /armARCS/rest/

Request

Supported Media Types: application/json

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 17-2 Parameters

details status	In case of errors, details are published with the error string
atatua	
Status	See Migration Status Codes
items	Version of the API you are developing with
version	The version, such as v1
lifecycle	Possible values: active, deprecated
isLatest	Whether this resource is the latest, true or false
links	Detailed information about the link
href	Links to API call



Name	Description
action	The HTTP call type
rel	Can be self or Job Status. If set to Job Status, you can use the href to get the status of the import operation
data	The parameters as key value pairs passed in the request

Table 17-2 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "items": [{
        "isLatest": false,
        "lifecycle": "deprecated",
        "version": "v1",
        "links": [{
             "href": "https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
            "rel": "canonical"
        }, {
            "href": "https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
            "rel": "successor-version"
        }]
    }, {
        "isLatest": true,
        "lifecycle": "active",
        "version": "v1",
        "links": [{
            "href": "https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
            "rel": "canonical"
        }, {
            "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
            "rel": "predecessor-version"
        }]
   }],
    "links": [{
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
        "rel": "canonical"
    }, {
        "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
        "rel": "current"
   }]
}
```



Get Information about a Specific API Version for Account Reconciliation REST APIs

Returns details for a specific REST API version for Account Reconciliation.

REST Resource

GET /armARCS/rest/{api_version}

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 17-3 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, such as V1	Path	Yes	None

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 17-4 Parameters

Name	Description
version	The version, such as v1
lifecycle	Possible values: active, deprecated
isLatest	Whether this resource is the latest, true or false
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	The parameters as key value pairs passed in the request



Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"version": "v1",
"lifecycle": "active",
"isLatest": true,
"links": [{
"rel": "canonical",
"href": "https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
}, {
"rel": "predecessor-version",
"href": "https://<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1",
}]
}
```

Execute a Job in Account Reconciliation

Use this resource to execute a job by providing the job name and type.

The job is expected to be defined in Account Reconciliation with all the required parameters saved with the job definition. For some job types, the parameters can be either provided or overwritten at runtime.

Reconciliation Compliance Supported Job Types:

- CREATE_RECONCILIATIONS
- SET_PERIOD_STATUS
- IMPORT_PREMAPPED_TRANSACTIONS
- IMPORT_PREMAPPED_PROFILES
- IMPORT_RATES
- IMPORT_BALANCES
- MONITOR_RECONCILIATIONS
- IMPORT_PREMAPPED_BALANCES

Transaction Matching Supported Job Types:

- IMPORTTMPREMAPPEDTRANSACTIONS
- RUNAUTOMATCH

This topic describes general information for executing a job. Details for each job type are described in separate topics for individual jobs.

REST Resource

POST /armARCS/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer



Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

This table summarizes the request parameters that are generic to all jobs. The following tables describe parameters specific to individual rules.

Table 17-5 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None

Example URL

https://<BASE-URL>/armARCS/rest/v1/jobs

Response

Supported Media Types: application/json

Parameters

This table summarizes the response parameters that are generic to all jobs. The following tables describe parameters specific to individual rules.

Name		Description
jobName		The name of the job, such as Create Reconciliations
period		The name of period, such as July2016
	Note:	
	For monitor_reconciliation s, the parameter is periodName.	

Table 17-6 Parameters



Name		Description
filter	_	The name of filter, such as MyFilter
	Note:	
	For monitor_reconciliation s, the parameter is filterName.	

Table 17-6 (Cont.) Parameters

Retrieve Periods with a Specific Status

Retrieves a list of periods based on the specified status.

REST Resource

GET /armARCS/rest/periods?status={status}

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this API.

Table 17-7 GET PERIODS

Name	Description	Required	Туре
status	 Status of the periods to be retrieved. The value can be one of the following: OPEN - All open periods CLOSED - All closed periods LOCKED - All locked periods PENDING - All pending periods OPEN_PENDING - All open or pending periods ALL - All periods 	Yes	Query

Example URLs

https://<BASE-URL>oraclecloud.com/armARCS/rest/periods?status=ALL

https://<BASE-URL>/armARCS/rest/periods?status=OPEN PENDING

Response

Supported Media Types: application/json

Parameters:

Name	Description	
details	In case of errors, details are published with the error string	
status	Status of the request. See Migration Status Codes.	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
items	List of periods with the specified status. The format is:	
	<pre>{ "Status": <status code="">, "Id": <internal id="" period="">, "Name": <name of="" period="" the=""> }</name></internal></status></pre>	
	 The status code can be one of the following: 51 - PENDING 52 - OPEN 53 - CLOSED 54 - LOCKED 	

Table 17-8 Parameters

Example of Response Body

The following is an example of the response body, in JSON format.

```
{
  "type": "ARCS",
  "items": [
    {
       "Status": "53",
       "Id": "10000000135004",
       "Name": "January 2022"
    },
    {
       "Status": "53",
       "Id": "10000000135007",
       "Name": "February 2022"
    },
    {
}
```



```
"Status": "53",
      "Id": "10000000135009",
      "Name": "March 2022"
    },
    {
      "Status": "53",
      "Id": "10000000135011",
      "Name": "April 2022"
    }
  ],
  "status": 0,
  "links": [
    {
      "rel": "self",
      "href": "https://<BASE-URL>/armARCS/rest/periods",
      "action": "GET"
    }
  ]
}
```

Change Period Status (Reconciliation Compliance)

Changes the status of a period (open, closed, pending, locked) and returns the success or failure status.

When a period's status is changed to Open, the returned job corresponds to the opening of reconciliations for the specified period. The job's success or failure does not impact the period's status because this change is made immediately. Even if there are failures while reopening reconciliations, the period status still remains Open.

If a period's status is set to Closed or Locked, no job is returned.

REST Resource

POST /armARCS/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.



Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, SET_PERIOD_STATUS	Yes
period	The name of the period, such as July2016	Yes
status	Status to be changed; supported values: pending, open, closed, locked	Yes

Table 17-9 SET PERIOD STATUS

Example of request body

Response

Supported Media Types: application/json

Parameters:

Table 17-	- 10	Parameters
-----------	-------------	------------

Name	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes. When the period's status is changed to Open, the status of the job that opens reconciliations for the specified period is sent as additional information. Use this additional information to check the status of the open reconciliations job.	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "type": "ARCS",
    "status": -1,
    "details": "In Process",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE_NAME>-
```



```
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/2141",
"action": "GET"
}
]
}
```

Create Reconciliation (Reconciliation Compliance)

Copies all selected profiles to a period and returns success or failure status.

REST Resource

```
POST /armARCS/rest/{api version}/jobs
```

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job. For additional parameters that are common to all jobs, see Execute a Job.

Table 17-11	. RULES
-------------	---------

Name	Description	Required	Default
api_version	Version of the API you are working with, such as v1.	Yes	None
jobName	The name of a job, CREATE_RECONCILIATIONS.	Yes	None
period	The name of the period, such as July2016	Yes	None
filter	The name of filter, such as MyFilter	No	None

Example of request body

```
{
  "jobName" : "CREATE_RECONCILIATIONS",
  "parameters": {
         "period":"July2016",
         "filter":"MyFilter"
         }
}
```

Response

Parameters:



Name	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type	
data	Parameters as key value pairs passed in the request	

Table 17-12 Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "type": "ARCS",
  "status": -1,
  "details": "In Process",
  "links": [
    {
        "rel": "self",
        "href": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/2141",
        "action": "GET"
    }
  ]
}
```

Delete Profile

Deletes an Account Reconciliation profile.

REST Resource

POST /armARCS/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User, User

Users with User predefined role may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.



Table 17-13 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with: v1	Path	Yes	None
jobname	The name of the job, DELETE_PROFILE	Payload	Yes	None
accountId	The name of the profile that must be deleted.	Payload	Yes	None

Example of Request Body

```
{
    "jobName": "DELETE_PROFILE",
    "parameters": {
        "accountId": "101-1234-5678",
    }
}
```

Response

Parameters

The following table summarizes the response parameters.

Name	Description
type	The value is "RC".
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 17-14 Parameters

Supported Media Types: application/json

Example of Response Body



]

Import Pre-Mapped Balances (Reconciliation Compliance)

Imports pre-mapped balances and returns the success or failure status.

REST Resource

POST /armARCS/rest/{api version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-15 IMPORT_PREMAPPED_BALANCES

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, IMPORT_PREMAPPED_BALANCES	Yes
period	The name of the period, such as July2016	Yes
balanceType	Supported balance types are SRC for source system balance, and SUB for subsystem balance	Yes
currencyBucket	Currency bucket such as Functional	Yes
file	Name of the import file, such as balances.csv	Yes

Example of request body

{

}

```
"jobName" : "IMPORT_PREMAPPED_BALANCES",
"parameters": {
    "period":"July2016",
    "balanceType":"SRC",
    "file":"balances.csv",
    "currencyBucket":"Functional"
    }
```

ORACLE

Response

Supported Media Types: application/json

Parameters:

Table 17-16 Parameters

Name	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "type": "ARCS",
  "status": -1,
  "details": "In Process",
  "links": [
    {
        "rel": "self",
        "href": "https://<SERVICE_NAME>-
    </texted>
<
```

Import Pre-Mapped Transactions (Reconciliation Compliance)

Imports pre-mapped transactions for a particular period and returns the success or failure status.

REST Resource

POST /armARCS/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.



Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-17 IMPORT_PREMAPPED_TRANSACTIONS

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, IMPORT_PREMAPPED_TRANSACTIONS	Yes
transactionType	 Transaction Type is one of the following: BEX for loading Balance Explanations SRC for loading Source System Adjustments SUB for loading Subsystem Adjustments VEX for loading Variance Explanations 	Yes
file	The file name, such as transactions.csv	
dateFormat	Date Format, such as DD/MM/YYYY, MMM d, yyyy, or All	Yes

Example of request body

```
{
  "jobName" : "IMPORT_PREMAPPED_TRANSACTIONS",
  "parameters": {
            "period":"July2016",
            "transactionType":"SRC",
            "file":"transactions.csv",
            "dateFormat": "MMM d,yyyy"
            }
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type



Table 17-18 (Cont.) Parameters

Name	Description
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "type": "ARCS",
  "status": -1,
  "details": "In Process",
  "links": [
    {
        "rel": "self",
        "href": "https://<SERVICE_NAME>-
    </texted>
        </texted>

        <
```

Import Balances (Reconciliation Compliance)

Imports balances data using Data Management from a previously created Data Load definition, and returns success or failure status.

When using Data Management, if a data load rule fails, the Account Reconciliation log file includes a message such as the following:

```
Dataload process failed for process {JOB_ID}. Check the Data Management log
for more details.
Data Management log file name: {LOG_FILE_NAME}
Detailed error from Data Management process: {DETAILS}
```

Refer to the Data Management log file to understand the reason for the job failure. If multiple data load rules fail, a separate log is created for each data load rule.

REST Resource

POST /armARCS/rest/{api version}/jobs/

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json



Parameters

The following table summarizes the client request.

Table 17-19 IMPORT_BALANCES

Name	Description	Path	Required
api_version	Version of the API you are working with, such as v1	Yes	Yes
jobName	The name of the job, IMPORT_BALANCES	No	Yes
period	The name of the period, such as April 2016	No	Yes
dl_Definition	The name of a previously saved data load using the format DL_name.	No	Yes

Example of request body

```
{
  "jobName" : "IMPORT_BALANCES",
    "parameters": {
        "period":"April 2016",
        "dl_Definition":"DL_test"
        }
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to the API call	
action	The HTTP call type	
rel	Relationship type (self, Job Status). if set to Job Status, you can use the href to get the status of the operation	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
"type": "ARCS",
"status": -1,
"details": "In Process",
```



```
"links": [
{
    "rel": "self",
    "href": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/2141
    "action": "GET"
}
]
```

Import Profiles (Reconciliation Compliance)

Imports profiles and returns the success or failure status.

REST Resource

POST /armARCS/rest/{api version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, IMPORT_PROFILES	Yes
importType	The import type; supported values are Replace and ReplaceAll	Yes
period	The period for which to import, such as July2016	
profileType	The profile type; supported values are Profiles and Children	Yes
fileLocation	The file name, such as profiles.csv	Yes
dateFormat	Date Format, such as DD/MM/YYYY, MMM d, yyyy, or All	Yes

Table 17-21 IMPORT_PROFILES

Example of request body

```
"period":"July2016",
    "importType":"Replace",
    "fileLocation":"profiles.csv",
    "dateFormat": "MMM d,yyyy"
    }
```

}

Response

Supported Media Types: application/json

Parameters:

Table 17-22 Parameters	,
------------------------	---

Name	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type	
data	Parameters as key value pairs passed in the request	

Example of Response Body

The following is an example of the response body in JSON format.

Import Rates (Reconciliation Compliance)

Imports rates for a particular period and rate type, and returns the success or failure status.

REST Resource

POST /armARCS/rest/{api version}/jobs



Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-23 IMPORT_RATES

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, IMPORT_RATES	Yes
period	The name of the period, such as July2016	Yes
rateType	The rate type, such as Accounting	Yes
file	Name of the import file, such as rates.csv	Yes
importType	Supported import types are Replace and ReplaceAll	Yes

Example of request body

```
{
  "jobName" : "IMPORT_RATES",
  "parameters": {
        "period":"July2016",
        "rateType":"Accounting",
        "file":"rates.csv",
        "importType":"ReplaceAll"
        }
}
```

Response

Supported Media Types: application/json

Parameters:

arameters

Name	Description	
details	In case of errors, details are published with the error string	
status	See Migration Status Codes	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	



Table 17-24 (Cont.) Parameters

Name	Description
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "type": "ARCS",
  "status": -1,
  "details": "In Process",
  "links": [
    {
        "rel": "self",
        "href": "https://<SERVICE_NAME>-

</
```

Import Pre-Mapped Transactions (Transaction Matching)

Imports a file of pre-mapped transactions into Transaction Matching, and returns the success or failure status.

REST Resource

POST /arm/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-25 IMPORTTMPREMAPPEDTRANSACTIONS

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes



Name	Description	Required
jobName	The name of a job, IMPORT_PREMAPPED_TRANSACTIONS	Yes
dataSource	Text ID of the data source where the transaction will be imported to	
file	The file name, such as transactions.csv	
reconciliationType	Text ID of the reconciliation type where the transaction file will be imported to	Yes
dateFormat	Date Format is a parameter that includes the format of the date fields in the transactions import file. The default is DD/MM/YYYY. Other supported date formats are MM/dd/yyyy, dd/MM/yyyy, MM-dd-yyyy, d-M-yyyy, and MMM d.yyyy.	Yes

Table 17-25 (Cont.) IMPORTTMPREMAPPEDTRANSACTIONS

Example of request body

```
"jobName" : "importtmpremappedtransactions",
"parameters": {
    "dataSource":"CLEARING",
    "reconciliationType":"CLEARING",
    "file":"clearingTransaction.csv",
    "dateFormat": "MM-DD-YYYY"
    }
```

Response

{

}

Supported Media Types: application/json

Parameters:

Table 17-26 Parameters	s
------------------------	---

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
"type": "TM",
```

```
"status": -1,
"details": "In Process",
"links": [
    {
        "rel": "self",
        "href": "https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/2141",
        "action": "GET"
    }
]
}
```

Import Attribute Values

Imports attribute values into an existing list attribute or group attribute. In Transaction Matching, you can only import group attributes.

REST Resource

POST /armARCS/rest/{api_version}/jobs

Required Roles

Service Administrator, Power User

Users with Power User predefined role may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 17-27 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with: v1	Path	Yes	None
jobname	The name of the job, IMPORT_ATTRIBUTE_VALUES	Payload	Yes	None
importType	The import type. Supported values are Replace, Replace All, and Update.	Payload	No	Replace
fileLocation	The file name containing the values to be imported; example: StoreData.csv	Payload	Yes	None



Table 17-27 (Cont.) Parameters

Name	Description	Туре	Required	Default
dateFormat	Format of date fields in the import file. Supported date formats are as follows: d MMM, yyyy MMM d, yyyy MM/dd/yyyy dd/MM/yyyy dd/MM/yyyy dd-Myyyy dd-MMM-yyy dd-MMM-yyy	Payload	No	dd-MMM-yyyy
attribute	The name of the list attribute or group attribute into which values must be imported.	Payload	Yes	None
module	The name of the module. Supported values are: RC for Reconciliation Compliance and TM for Transaction Matching.	Payload	Yes	None

Example of Request Body

```
{
"jobName" : "IMPORT_ATTRIBUTE_VALUES",
"parameters": {
"attribute":"Store",
"importType":"Replace",
"fileLocation":"StoreData.csv",
"dateFormat": "MMM d,yyyy",
"module": "RC"}
}
```

Response

Parameters

The following table summarizes the response parameters.

Table 17-28 Parameters

Name	Description
type	The application type
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type

Supported Media Types: application/json



Example of Response Body

```
{
"type": "ARCS",
"status": -1,
"details": "In Process",
"links": [
{
    "rel": "self",
    "href": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/oraclecloud.com/arm/rest/
fcmapi/v1/RC/job/2141",
    "action": "GET"
}
]
```

Monitor Reconciliations (Reconciliation Compliance)

Returns the list of reconciliations for a given period name and filter name.

Note:

- If the Reconciliation status for all the Reconciliations in the given Period Name and Filter Name were closed, then the output status would be '0'.
- If the Reconciliations status for any one of the Reconciliations in the given Period Name and Filter Name is open, then the output status would be '-1'.

REST Resource

POST /armARCS/rest/{api version}/jobs/

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.



Name	Description	Path	Required
api_version	Version of the API you are working with, such as v1	Yes	Yes
jobName	The name of the job, MONITOR_RECONCILIATIONS	No	Yes
periodName	The name of the period, such as September 2017	No	Yes
filterName	The name of the filter. For example, Recon status filter.	No	Yes

Table 17-29 MONITOR_RECONCILIATIONS

Example of request body

```
{
  "parameters":
  {"periodName":"September 2017","filterName":"DemoFilter"},
  "jobName":"MONITOR_RECONCILIATIONS"
}
```

Response

Supported Media Types: application/json

Parameters:

Table 17-30 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to the API call
action	The HTTP call type
rel	Relationship type (self, Job Status). if set to Job Status, you can use the href to get the status of the operation
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following is an example of the response body in JSON format when all reconciliations are closed:

```
{
"error":null,
"details":"Account ID : 100-1210, Name : Accounts Receivable, Status :
Closed",
"items":null,
"status":0,
```



```
"link":null,
"links":[{"action":"GET", "rel":"self", "href":"https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/
monitorReconciliations/September%202017/DemoFilter"}],
"type":"ARCS"
}
```

The following is an example of the response body in JSON format when any reconciliation status is open:

```
{
"error":null,
"details":"Account ID : 100-1210, Name : Accounts Receivable, Status : Open",
"items":null,
"status":-1,
"link":null,
"links":[{"action":"GET", "rel":"self", "href":"https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/
monitorReconciliations/September%202017/DemoFilter"}],
"type":"ARCS"
}
```

Import Reconciliation Attributes (Reconciliation Compliance)

Performs flat file loads of attribute values into existing reconciliations.

REST Resource

POST /armARCS/rest/{api version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-31 Import Reconciliation Attributes

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, IMPORT_RECONCILIATION_ATTRIBUTES	Yes
fileName	The name of the upload import file	Yes
period	The name of the period, such as $July2020$	Yes



Name	Description	Required
rules	The rules to run upon completion. Allowed values are: ALL SET ATTR. VAL (Set Attribute Value) 	No
	 SET_ATTR_VAL(Set Attribute Value) CRT_ALT (Create Alert) AUTO_APP(Auto Approve Reconciliation) AUTO_SUB(Auto Submit Reconciliation) You can send multiple values separated by 	
reopen	comma. Default is None.	No
reopen	reconciliations upon completion. Values is either true or false (default).	NO
dateFormat	List of valid date formats, such asDD/MM/ YYYY. You can send multiple values separated by semi-colon.	No

Table 17-31 (Cont.) Import Reconciliation Attributes

Here are some examples of the request body:

Example 1

```
{
    "jobName" : "IMPORT_RECONCILIATION_ATTRIBUTES",
    "parameters":
        {
          "fileName":"import_recon.csv",
          "period":"January 2010",
          "rules":"AUTO_APP,AUTO_SUB",
          "reopen":"true",
          "dateformat":"MM-dd-yyyy;MMM d, yyyy"
        }
}
```

Example 2

```
{
   "jobName" : "IMPORT_RECONCILIATION_ATTRIBUTES",
   "parameters":
    {
        "fileName":"Reconciliations.csv",
        "period":"June 2019",
        "rules":"AUTO_APP,AUTO_SUB",
        "reopen":"true"
    }
}
```

Example 3

{

"jobName" : "IMPORT_RECONCILIATION_ATTRIBUTES",

```
"parameters":
    {
        "fileName":"import_recon.csv",
        "period":"January 2010",
        "rules":"ALL",
        "reopen":"true"
    }
```

Example 4

}

```
{
   "jobName" : "IMPORT_RECONCILIATION_ATTRIBUTES",
   "parameters":
        {
            "fileName":"Reconciliations.csv",
            "period":"June 2019"
        }
}
```

Response

Supported Media Types: application/json

Parameters:

Table 17-32 Parameters

Name	Description	
details	In case of errors, details are published with the error string	
status	 -1 = In Progress 	
	• 0 = Success	
	• 1 = Fail	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type. Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation.	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "type": "ARCS",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/jobs/
10000001155018",
            "action": "GET"
        }
    ],
```

```
"details": "In Process",
"status": -1
```

Run Auto Match (Transaction Matching)

Runs the auto match process in Transaction Matching.

REST Resource

}

POST /arm/rest/{api version}/jobs

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-33 runautomatch

Name	Description	Required
api_version	Version of the API you are working with, such as v1	Yes
jobName	The name of a job, runautomatch	Yes
ReconTypeId	The Text ID of the Reconciliation type to be auto matched	Yes

Example of request body

```
{"jobName":"runautomatch",
"parameters":{"reconTypeId":"INTERCO"}}
```

Response

Supported Media Types: application/json

Parameters:

Table 17-34 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link



Name	Description
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 17-34 (Cont.) Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "type": "TM",
  "status": -1,
  "details": "In Process",
  "links": [
    {
      "rel": "self",
      "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/v1/jobs/2141",
      "action": "GET"
    }
 ],
  "error": null,
 "items": null,
  "link": null
}
```

Purge Transactions (Transaction Matching)

Removes matched transactions for Account Reconciliation using the provided parameters.

You can specify filterOperator and filterValue to further filter the matched transactions. Otherwise, all matched transactions older than or equal to the age from all accounts for the specified matchType are purged.

REST Resource

```
POST /arm/rest/{api version}/jobs
```

Required Roles

Service Administrator, Power User, User, Viewer

Users with Power User, User, and Viewer predefined roles may require additional application roles.

Request

Supported Media Types: application/json

Parameters



The following table summarizes the client request parameters specific to this job.

Name	Description	Туре	Required	Values
api_version	Version of the API you are working with, such as v1	Path	Yes	v1
jobName	The name of a job	Payload	Yes	purgetransactions
ReconTypeId	The identifier (TextID) of the match type from which matched transactions should be deleted	Payload	Yes	Example: CLEARING
matchedStatu s	The status of the transactions to be deleted. The only value currently supported is matched.	Payload	No	Default value: matched
age	Identifies the number of days since the transaction was matched. Matched transactions older than or equal to this value will be deleted.	Payload	Yes	Example: 180
filterOperat or	Optionally, use one of the following filter conditions to identify the accounts containing matched transactions for deletion. This value is combined with the filterValue to identify the accounts from which matched transactions should be purged: • EQUALS • NOT_EQUALS • NOT_EQUALS • STARTS_WITH • ENDS_WITH • CONTAINS • NOT_CONTAINS	Payload	No	Examples: EQUALS Starts_With

Table 17-35 Parameters

Name	Description	Туре	Required	Values
filterValue	Optionally use one or more filter values to identify the transactions to purge. Use a space- separated list to specify multiple values as shown in the examples. If multiple values are specified, transactions from accounts matching any filter operator and filter value combination are selected for purging. EQUALS and NOT_EQUALS support multiple values. STARTS_WITH, ENDS_WITH, CONTAINS, and NOT_CONTAINS only support a single value.	Payload	No	Examples: ["101-1234","102-12 34"] ["102"]
logFileName	Optionally, enter the name of a log file to record information about the API activity.	Payload	No	If a file name is not specified, a log file named PurgeTransactions_J ob_ID is automatically generated. The file is located in the Outbox.

Table 17-35 (Cont.) Parameters

Example of request body

Example of purging matched transactions 120 days or older for CLEARING match type and accounts equal to 101-1234 and 102-1234:

Example of purging matched transactions 120 days or older for CLEARING match type and accounts start with 101:

```
{
    "jobName" : "purgetransactions",
    "parameters":
```

```
{
    "reconTypeId" : "CLEARING",
    "age" : 120,
        "filterOperator":"STARTS_WITH",
                      "filterValue" : ["101"],
                     "logFileName" : "purge-clearing"
}
```

Response

}

Supported Media Types: application/json

Parameters:

Table 17-36 Para	amet	ters
------------------	------	------

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following is an example of the response body in JSON format.

```
{
 "type": "TM",
 "status": -1,
 "details": "In Process",
 "links": [
    {
      "rel": "self",
"href":"https://
<SERVICE_NAME><TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/arm/rest/v1/
jobs/2141",
      "action": "GET"
    }
 ],
 "error": null,
 "items": null,
  "link": null
}
```



Retrieve Job Status (Reconciliation Compliance)

Returns the status of a job for Reconciliation Compliance, indicating if the job is in process, or if it is successfully executed or completed with errors.

REST Resource

GET /armARCS/rest/{api_version}/jobs/{job_id}

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 17-37 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with: v1	Path	Yes	None
jobIdentifier	The ID of the job	Path	Yes	None

Response

Parameters

The following table summarizes the response parameters.

Table 17-38 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Supported Media Types: application/json

Example of Response Body

```
{
  "type": "ARCS",
  "status": 0,
  "details": "Total to copy : 3\nSuccessfully copied : 2\nUnsuccessfully
```



Retrieve Job Status (Transaction Matching)

Returns the status of a job for Transaction Matching, indicating if the job is in process, or if it is successfully executed or completed with errors.

REST Resource

GET /arm/rest/{api_version}/jobs/{job_id}

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 17-39 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with: v1	Path	Yes	None
jobIdentifier	The ID of the job	Path	Yes	None

Response

Parameters

The following table summarizes the response parameters.

Table 17-40 Parameters

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
links	Detailed information about the link



Name	Description
href	Links to API call or status API
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request
log-content	Link to the log file location. This is applicable to Archive Matched Transactions, Purge Archived Transactions, Purge Transactions (Transaction Matching), Import Pre-Mapped Transactions (Transaction Matching), and Unmatch Matched Transaction (Transaction Matching) jobs.
file-content	Link to the location of the archive file, for Archive Matched Transactions jobs.

Table 17-40 (Cont.) Parameters

Supported Media Types: application/json

Example of Response Body

Example 1: Retrieve job status for an Auto Match job

```
{
    "type": "TM",
    "items": [
        0
    ],
    "error": null,
    "link": null,
    "status": 0,
    "details": "Job Completed. Job ID: 10000003918002",
    "links": [
        {
            "rel": "self",
            "href": https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest//v1/jobs/
10000003918002,
            "action": "GET",
            "data": null
        }
    ]
}
```

Example 2: Retrieve job status for Archive Matched Transactions (Transaction Matching) job

```
{
    "type": "TM",
    "items": [
        0
    ],
    "error": null,
    "link": null,
    "status": 0,
    "details": "Job Completed. Job ID: 10000003846005 Log file:
```



```
Archive Transactions Pos2Processor.log\nRe Archive for the Archive Job ID ::
10000003810002\r\nArchive Transactions for Match Type ::
Pos2Processor\nArchive Transactions on or before :: 2022-02-18 23:59:59
UTC\nArchive Transactions age :: 330\nAccount ID : Equals 'XX-XX-
YYYY'\nAccounts considered for Archive : XX-XX-YYYY\n\n Total Number of
Matches present in this archive :: 1479730\nTotal Number of Transactions
Present in this Archive for DataSource - Delivery Partner :: 1490233\nTotal
Number of Transactions Present in this Archive for DataSource - POS ::
1515718\nTotal Number of Adjustments Present in this Archive ::
104709\n\nTotal Number of Transactions Present in this Archive ::
3110660\nTime taken 22 Minute(s) and 02 Second(s) to Archive
Transactions.\r\n",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/v1/jobs/
10000003846005",
            "action": "GET",
            "data": null
        },
        {
            "rel": "log-content",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/rest/applicationsnapshots/
Archive Transactions Pos2Processor.log/contents",
            "action": "GET",
            "data": null
        },
        {
            "rel": "file-content",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/rest/applicationsnapshots/
Archived Transactions Pos2Processor 10000003846005.zip/contents",
            "action": "GET",
            "data": null
        }
    ]
}
```

Example 3: Retrieve job status for Purge Archived Transactions (Transaction Matching) job

```
{
    "type": "TM",
    "items": [
        0
    ],
    "error": null,
    "link": null,
    "status": 0,
    "details": "Job Completed. Job ID: 10000003801002 Log file:
PurgeTransactions_10000003801002.log\nMatch Type: Pos2Processor, Purge for
Archive Job ID: 10000003798009\n\n\nTotal adjustments purged: 0\nTotal
transactions purged from all sources: 0\nTotal matches purged: 0\n\nStatus:
No transactions found for the Archive Transactions job ID. Purge Transactions
```



```
might be already run for this Archive job ID.\n\nTotal time taken: 00
Minute(s) and 00 Second(s) n'',
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest//v1/jobs/
10000003801002",
            "action": "GET",
            "data": null
        },
        {
            "rel": "log-content",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/rest/applicationsnapshots/
PurgeTransactions 10000003801002.log/contents",
            "action": "GET",
            "data": null
        }
    ]
}
```

Export Application Properties

Exports Account Reconciliation application settings (related to Redwood Experience, theme, email notification, and business process name), background image, and logo image to a JSON file so that you can import them into the same or another environment.

This command is useful when you import an application from prod to test environments. If your application settings are different in prod and test environments, you can export them from the test environment before importing the application from the prod environment, and then import the settings in to the test environment to maintain the original settings.

You can download the export file using the Download REST API. This is a synchronous API.

REST Resource

POST /arm/rest/fcmapi/{api version}/rc/export/applicationproperties

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Name	Description	Required	Default
fileName	The name of the JSON file that stores the exported property values.	Yes	None
	Use the Upload API to upload the file to the target environment and then restore these settings in the target environment, as described in Import Application Properties.		
properties	The comma-separated list of properties to be exported.	No	All valid properties are exported.
	Valid values include the following:		
	Theme exports the display theme used in the environment		
	 EmailNotification exports the email notification settings defined in the environment 		
	 DisplayBusinessProcessN ame exports whether to display the business process name on the page in the 		
	environment		
	 RedwoodExperience exports the Redwood Experience setting of the environment 		
	• BackgroundImage exports the backgound image used in the environment		
	LogoImage exports the logo image used in the environment		

Table 17-41 EXPORT APPLICATION PROPERTIES

Examples of request body

Example 1: Exporting all exportable application properties

```
{
  "fileName": "ApplicationProperties.json"
}
```

Example 2: Exporting specific application properties

```
{
   "fileName": "ApplicationProperties.json",
   "properties":["Theme", "EmailNotification", "DisplayBusinessProcessName",
   "RedwoodExperience"]
}
```

Response

Supported Media Types: application/json



Parameters:

Name	Description	
details	In case of errors, details are published with the error string.	
status	Status of the job:	
	 -1 = In Progress 	
	• 0 = Success	
	• 1 = Fail	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type. It can be self or export-content. If the export succeeds, you can use the href to download the exported file.	

Table 17-42 Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "details": "Application properties exported successfully",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/rc/
export/applicationproperties",
            "action": "POST"
        },
        {
            "rel": "export-content",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/
ApplicationProperties.json/contents",
            "action": "GET"
        }
    ],
    "status": 0,
    "type": "RC",
    "link": {},
    "error": null,
    "items": []
}
```

Import Application Properties

Imports Account Reconciliation application settings (related to Redwood Experience, theme, email notification, and business process name), background image, and logo image from an export file into an Account Reconciliation environment.

The export file is available for import after the file is uploaded using the Upload REST API. This a synchronous API.

REST Resource

POST /arm/rest/fcmapi/{api version}/rc/import/applicationproperties

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-43 IMPORT APPLICATION PROPERTIES

Name	Description	Required	Default
api_version	The REST API version for the API. This release is v1.	Yes	v1
fileName	The name of the JSON file that contains exported property values from another environment.	Yes	None
	This file, exported from another environment as described in Export Application Properties, must be available in the environment where you are restoring application settings.		

Example of request body

```
{
   "fileName":"applicationProperties.json"
}
```

Response

Supported Media Types: application/json

Parameters:

Table 17-44	Parameters
-------------	------------

Name	Description
details	In case of errors, details are published with the error string
status	Status of the job:
	 -1 = In Progress
	• 0 = Success
	• 1 = Fail
links	Detailed information about the link
href	Links to API call or status API



Table 17-44 (Cont.) Parameters

Name	Description
action	The HTTP call type
rel	Relationship type. Possible values: self.

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "details": "Application properties imported successfully",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/rc/
import/applicationproperties",
            "action": "POST"
    ],
    "status": 0,
    "type": "RC",
    "link": {},
    "error": null,
    "items": []
}
```

Export Background Image

Exports the background image used in an Account Reconciliation environment to a JPG file so that you can import it into another environment.

You can download the image file using the Download REST API. This is a synchronous API.

REST Resource

POST /arm/rest/fcmapi/{api version}/rc/export/backgroundImage

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.



Name	Description	Required	Default
api_version	The current REST API version for the API. For example, v1 for this API.	Yes	v1
fileName	The name for the background image file in JPG, JPEG, GIF, or PNG format.	Yes	None
	Use the Upload API to upload the background image file to the target environment and then import it into the target environment, as described in Import Background Image.		

Table 17-45 EXPORT BACKGROUND IMAGE

Example of request body

```
{
   "fileName":"backgroundImage.jpg"
}
```

Response

Supported Media Types: application/json

Parameters:

Table 17-46 F	Parameters
---------------	------------

Name	Description	
details	In case of errors, details are published with the error string	
status	Status of the job:	
	 -1 = In Progress 	
	• 0 = Success	
	• 1 = Fail	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type. It can be self or export-content. If the export succeeds, you can use the href to download the exported file.	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
   "details": "Background Image exported successfully",
   "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
```



```
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/rc/
export/backgroundImage",
            "action": "POST"
        },
        {
            "rel": "export-content",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/interop/rest/11.1.2.3.600/
applicationsnapshots/bgImage.jpg/contents",
            "action": "GET"
        }
    ],
    "status": 0,
    "type": "RC",
    "link": {},
    "error": null,
    "items": []
}
```

Import Background Image

Imports the background image from an export file into an Account Reconciliation environment and then sets it as the current background image.

The image will be available for import after you upload the file using the Upload REST API. This is a synchronous API.

REST Resource

POST /arm/rest/fcmapi/{api version}/rc/import/backgroundImage

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-47 IMPORT BACKGROUND IMAGE

Name	Description	Required	Default
api_version	The current REST API version for the API. For example, v1 for this API.	Yes	v1
fileName	The name of the background image file that was exported from another environment. Supported formats include JPG, JPEG, GIF, and PNG.	Yes	None



Example of request body

```
{
   "fileName":"backgroundImage.jpg"
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description	
details	In case of errors, details are published with the error string	
status	Status of the job:	
	 -1 = In Progress 	
	• 0 = Success	
	• 1 = Fail	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type. Possible values: self.	

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "details": "Background image imported successfully.",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/rc/
import/backgroundImage",
            "action": "POST"
        }
    ],
    "status": 0,
    "type": "RC",
    "link": {},
    "error": null,
    "items": []
}
```



Export Logo Image

Exports the corporate logo used in an Account Reconciliation business process to a JPG file so that you can import it into another environment.

The exported file can be download using the Download REST API. This is an asynchronous API.

REST Resource

POST /arm/rest/fcmapi/{api version}/rc/export/logo

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-49 EXPORT LOGO IMAGE

Name	Description	Required	Default
api_version	The current REST API version for the API. For example, v1 for this API.	Yes	v1
fileName	The name of the logo image file in JPG, JPEG, GIF, or PNG format.	Yes	None
	Use the Upload API to upload the background image file to the target environment and then import it into the target environment, as described in Import Logo Image.		

Example of request body

```
{
    "fileName":"logo.jpg"
}
```

Response

Supported Media Types: application/json

Parameters:



Name	Description	
details	In case of errors, details are published with the error string.	
status	Status of the job:	
	 -1 = In Progress 	
	• 0 = Success	
	• 1 = Fail	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type. It can be self or export-content. If the export succeeds, you can use the href to get the status of the import operation.	

Table 17-50Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/RC/
export/logo",
            "action": "POST"
        },
        {
            "rel": "export-content",
            "href": "<SERVICE NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/interop/rest/11.1.2.3.600/
applicationsnapshots/logo.jpg/contents",
            "action": "GET"
        }
    ],
    "details": "Logo image exported successfully.",
    "type": "RC",
    "status": 0,
    "link": {},
    "error": null,
    "items": []
}
```

Import Logo Image

Imports the corporate logo used in an Account Reconciliation environment from an export file into another environment.

The logo is available for import after you upload the image file using the Upload REST API. This is an asynchronous API.



REST Resource

POST /arm/rest/fcmapi/{api version}/rc/import/logo

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 17-51 IMPORT LOG IMAGE

Name	Description	Required	Default
api_version	The current REST API version for the API. For example, v1 for this API.	Yes	v1
fileName	The name of the logo image file that contains the image to be imported. Supported formats include JPG, JPEG, GIF, and PNG.	Yes	None

Example of request body

```
{
    "fileName":"logo.jpg"
}
```

Response

Supported Media Types: application/json

Parameters:

Table 17-52 Parameters

Name	Description	
details	In case of errors, details are published with the error string.	
status	Status of the job:	
	 -1 = In Progress 	
	• 0 = Success	
	• 1 = Fail	
links	Detailed information about the link	
href	Links to API call or status API	
action	The HTTP call type	
rel	Relationship type. Possible values: self.	



Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/fcmapi/v1/RC/
import/logo",
            "action": "POST"
        }
    ],
    "details": "Logo image imported successfully.",
    "type": "RC",
    "status": 0,
    "link": {},
    "error": null,
    "items": []
}
```

Working with Connections in Account Reconciliation

Use these REST APIs to work with connections.

With multiple environments, using REST APIs saves you time and effort by automating the process of logging in and configuring connections. For information about accessing environments, see Accessing EPM Cloud.

Table 17-53	Working with Connections in Account Reconciliation
-------------	----------------------------------------------------

Task	Request	REST Resource
Create a Connection	POST	<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections</pre>
View All Connections	GET	<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections</pre>
Update a Connection	PUT	<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections/{id}</pre>
Delete a Connection	DELETE	<pre>/arm/rest/fcmapi/{api_version}/{module}/ connections/{id}</pre>

Create a Connection

Use this REST API to create a connection that will be saved in an application.

REST Resource

POST /arm/rest/fcmapi/{api version}/{module}/connections

Required Roles

Service Administrator



Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request parameters specific to this job.

Table 17-54Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which to create a connection. For Account Reconciliation, set this value to RC.	Path	Yes	None
url	The URL of the connection, such as https:// < <i>BASE-URL</i> >	Payload	Yes	None
username	A username with the Service Administrator predefined role	Payload	Yes	None
password	The encrypted password for the user For security reasons, only an encrypted password is allowed. Use the EPM Automate encrypt command to generate the encrypted password. See encrypt.	Payload	Yes	None
type	 The type of connection. Valid values include the following: ENTERPRISE_JOURNALS - for Enterprise Journals connections OBJECT_STORAGE - for Object Storage connections 	Payload	Yes	None

Example URL

https://<BASE-URL>/arm/rest/fcmapi/v1/rc/connections

Example of Request Body

```
{
    "url": "https://<BASE-URL>",
    "username": "<NEW_USERNAME>",
    "password": "<NEW_PASSWORD>",
    "type" : "ENTERPRISE_JOURNALS"
}
```

Response

Supported Media Type: application/json

Table 17-55 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.



Example of Response Body

```
{
  "details": "Connection created successfully."
}
```

View All Connections

Use this REST API to view details for all of the connections saved in an application.

Required Roles

Service Administrator

REST Resource

GET /arm/rest/fcmapi/{api version}/{module}/connections

Request

Parameters:

The following table summarizes the client request.

Table 17-56 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which to view connections. For Account Reconciliation, set this value to RC.	Path	Yes	None

Example URL

https://<BASE-URL>/arm/rest/fcmapi/v1/rc/connections

Response

Supported Media Types: application/json

The following table summarizes the parameters.

Table 17-57 Parameters

Parameters	Description
items	Collection of information about the resource
id	Unique identifier for the connection, such as 1c89922d-92ba-46c1-850f- e2a8a416ddf2
type	The type of connection
url	The URL of the connection, such as https:// <base-url></base-url>
links	Detailed information about the link
details	In case of errors, details are published with the error string



Example Response

```
{
    "links": [
        {
            "rel": "self",
            "href": "http://<BASE-URL>/arm/rest/fcmapi/v1/rc/connections",
            "action": "GET"
        }
    ],
    "details": null,
    "items": [
        {
            "username": "ats admin2",
            "password": null,
            "url": "https://<BASE-URL>",
            "id": 10000000558005,
            "type": "ENTERPRISE JOURNALS"
        }
    ]
}
```

Update a Connection

Use this REST API to update a specific connection that is saved in an application.

REST Resource

PUT /arm/rest/fcmapi/{api version}/{module}/connections/{id}

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 17-58 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which to update a connection. For Account Reconciliation, set this parameter to RC.	Path	Yes	None
id	The identifier of the connection that must be updated	Path	Yes	None
url	The URL of the connection, such as https:// < <i>BASE-URL</i> >	Payload	Yes	None



Name	Description	Туре	Required	Default
username	A username with Service Administrator predefined role	Payload	Yes	None
password	The encrypted password for the user	Payload	Yes	None
	For security reasons, only an encrypted password is allowed. Use the EPM Automate encrypt command to generate the encrypted password. See encrypt.			
type	 The type of connection. Valid values include the following: ENTERPRISE_JOURNALS - for Enterprise Journals connections OBJECT_STORAGE - for Object Storage connections 	Payload	Yes	None

Table 17-58 (Cont.) Parameters

Example URL

https://<BASE-URL>/arm/rest/fcmapi/v1/rc/connections/10000000658005

Example of Request Body

```
{
    "url": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcx>.oraclecloud.com",
    "username": "<NEW_USERNAME>",
    "password": "<NEW_PASSWORD>"
}
```

Response

Supported Media Type: application/json

Table 17-59 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.

Example of Response Body

Example 1:

```
{
   "details": "Connection updated successfully."
}
```

Example 2:

```
{
  "details": "Invalid parameters. Test Connection is failed"
}
```



Delete a Connection

Use this REST API to delete a specific connection that is saved in an application.

Required Roles

Service Administrator

REST Resource

DELETE /arm/rest/fcmapi/{api version}/{module}/connections/{id}

Request

Parameters:

The following table summarizes the client request.

Table 17-60 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which to delete a connection. For Account Reconciliation, set this parameter to RC.	Path	Yes	None
id	The identifier of the connection that must be deleted	Path	Yes	None

Example URL

https://<BASE-URL>/arm/rest/fcmapi/v1/rc/connections/10000000552006

Response

Supported Media Type: application/json

Table 17-61 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.

Example of Response Body

```
{
  "details": "Connection deleted successfully."
}
```



Set Application Access Level

Sets the access level for an Account Reconciliation application. You can specify that the application can be accessed only by Service Administrators or by all users.

REST Resource

POST /armARCS/rest/{api_version}/appaccess

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request parameters.

Table 17-62 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
access	 Specify the access level for users. Valid values include the following: ALL_USERS - all users can access the application ADMINISTRATORS - only Service Administrators can access the application 	Payload	Yes	None

Examples of Request Body

Example 1

{
 "access": "ALL_USERS"
}

Example 2

```
{
    "access": "ADMINISTRATORS"
}
```

Response



Table 17-63 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.
status	See Migration Status Codes
links	Detailed information about the link

Example of Response Body

```
{
   "status": 0,
   "details": "Application access updated successfully",
   "links": [
        {
            "rel": "self",
            "href": "http://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/armARCS/rest/v1/appaccess",
            "action": "GET",
            "data": null
        }
   ]
}
```

Retrieve Application Access Level

Returns the access level for an Account Reconciliation application, indicating if all users can access the application or only Service Administrators can access the application.

REST Resource

GET /armARCS/rest/{api_version}/appaccess

Required Roles

Service Administrator

Request

Parameters:

The following table summarizes the client request parameters.

Table 17-64 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None

Example URL

https://<BASE-URL>/armARCS/rest/v1/appacess



Response

Supported Media Type: application/json

Table 17-65	Parameters
-------------	------------

Parameters	Description
links	Detailed information about the link
access	 Indicates the access level for users. ALL_USERS - all users can access the application ADMINISTRATORS - only Service Administrators can access the application

Example of Response Body

```
{
    "items": [
        {
            "access": "ALL_USERS"
        }
    ],
    "links": [
        {
            "rel": "self",
            "href": "https://<BASE-URL>/armARCS/rest/v1/appaccess",
            "action": "GET",
            "data": null
        }
    ]
}
```

View Reconciliation Comments

Returns all the comments, including attachments, for the specified reconciliation.

REST Resource

```
GET /armARCS/rest/{api_version}/period/{period}/reconciliation/
{accountId}/comments
```

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request specific to this job.



Table 17-66 VIEW RECONCILIATION COMMENTS

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v1	Path	Yes	None
period	The name of the reconciliation's period	Path	Yes	None
accountId	The Account ID of the reconciliation for which comments must be retrieved	Path	Yes	None

Example URL

https:// <SERVICE_NAME>-<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/ armARCS/rest/v1/period/Jan 2022/reconciliation/101-BC2-Premapped/comments

Response

Supported Media Types: application/json

Example of Response Body

The following is an example of a reconciliation with one comment and two attachments.

```
[
    {
        "commentId": 10000002580008,
        "parentObjectId": 10000001956143,
        "commentText": "Please investigate the alert on the account. The Risk
Rating has been increased.",
        "postedBy": "admin1",
        "postedDate": "Oct 6, 2022 4:03 PM",
        "carryForward": null,
        "references": [
            {
                "referenceId": 10000002580012,
                "type": "FILE",
                "url": null,
                "name": "adjustment1.pdf",
                "fileDownloadLink": "https://<BASE-URL>/arm/rest/fcmapi/v1/rc/
references/10000002580012/file"
            },
            {
                "referenceId": 10000002580010,
                "type": "URL",
                "url": "https://www.my-example.com",
                "name": "my-example",
                "fileDownloadLink": null
        ]
    }
1
```



Archive Matched Transactions (Transaction Matching)

Archives matched transactions, including support and adjustment details, that are equal to or older than a specified age. The matched transactions are stored in an archive file.

REST Resource

POST /arm/rest/{api_version}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request specific to this job.

Table 17-67 ARCHIVE MATCHED TRANSACTIONS

Name	Description	Туре	Required
api_version	Version of the API you are working with: v1	Path	Yes
jobName	The name of a job, archivetransactions	Payload	Yes
reconTypeId	The TextID of the match type from which matched transactions must be archived	Payload	Yes
age	Matched transactions older than or equal to this value will be archived	Payload	Yes
filterOperator	Filter to identify the accounts	Payload	No
	Valid values are EQUALS, NOT_EQUALS, STARTS_WITH, ENDS_WITH, CONTAINS, NOT_CONTAINS		
filterValue	The Account IDs for the filter operation	Payload	No
logFileName	The name of the log file If a file name is not provided, the log file is named Archive_Transactions_ <recon TypeId>_<job_id>.log.</job_id></recon 	Payload	Νο
fileName	The name of the archive zip file If a file name is not provided, the archive file is named Archive_Transactions_ <recon TypeId>_<job_id>.zip.</job_id></recon 	Payload	No

Example of request body

```
{
  "jobName": "archivetransactions",
  "parameters": {
    "reconTypeId": "Pos2Processor",
    "age": 120,
    "logFileName" : "Archive_Transactions_IC120XXXX.log",
    "fileName" : "Archived_Transactions_IC120XXXX.zip",
    "filterOperator": "EQUALS",
    "filterValue": [
        "201-1234",
        "202-1234"
    ]
  }
}
```

Response

Supported Media Types: application/json

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "type": "TM",
    "items": null,
    "error": null,
    "link": null,
    "status": -1,
    "details": null,
    "links": [
        {
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/arm/rest/v1/jobs/
10000003846005",
            "action": "GET",
            "rel": "self",
            "data": null
        }
    ]
}
```

To get the status of the archive matched transactions job and view its details, see Retrieve Job Status (Transaction Matching).

Purge Archived Transactions (Transaction Matching)

Purges matched transactions that are already archived in Transaction Matching.

REST Resource

POST /arm/rest/{api_version}/jobs



Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request specific to this job.

Table 17-68 PURGE ARCHIVED TRANSACTIONS

Name	Description	Туре	Required	
api_version	Version of the API you are working with: v1	Path	Yes	
jobName	The name of a job, purgearchivetransactions	Payload	Yes	
jobId	Job Id of the Archive job which needs to be purged	Payload	Yes	
logFileName	The name of the log file If a file name is not provided, the log file is named Purge_Transactions_ <reconty peId>_<job_id>.log.</job_id></reconty 	Payload	No	

Example of request body

```
{
  "jobName": "purgearchivetransactions",
  "parameters": {
     "jobId": "100000003801002"
     "logFileName" : "Purge_Archive_Transactions_IC120XXXX.log"
}
```

Response

Supported Media Types: application/json

Example of Response Body

The following is an example of the response body in JSON format.



To get the status of the purge archived transactions job and view its details, see Retrieve Job Status (Transaction Matching).

Unmatch Matched Transactions (Transaction Matching)

Unmatches matched transactions in Transaction Matching. Users must specify the match type and one or more match Ids associated with this match type for which transactions must be unmatched.

For Transaction Matching profiles that are integrated with Reconciliation Compliance, the unmatch operation is skipped if the Accounting Date of one or more transactions that are being unmatched is lower than the Purge Through Date of the reconciliation.

REST Resource

POST /arm/rest/{api version}/jobs

Required Roles

Service Administrator, Power User, Preparer

The user who created a profile can also unmatch transactions associated with that profile.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request specific to this job.

Table 17-69 UNMATCH MATCHED TRANSACTIONS

Name	Description	Туре	Required
api_version	Version of the API you are working with: v1	Path	Yes
jobName	The name of a job, such as unmatchtransactions	Payload	Yes
matchTypeTextId	The ID of the match type to which the matched transactions belong	Payload	Yes



Name	Description	Туре	Required
matchIds	The Match Ids, in a comma separated array Transactions with the following status are considered for unmatching: Confirmed Match, Confirmed Adjust, Suggested Match, Suggested Adjust.	Payload	Yes
forceReopen	 Valid values are: True - Reconciliations will be reopened if the Adjustment Accounting Date is less than the Closed Through Date. False - Matched transactions whose Adjustment Accounting Date is less than the Closed Through Date are skipped. This is the default setting. 		No

Table 17-69 (Cont.) UNMATCH MATCHED TRANSACTIONS

Example of request body

```
{
  "jobName": "unmatchtransactions",
  "parameters": {
    "matchTypeTextId": "IC120",
    "matchIds":[9195754,9219755],
    "forceReopen": false
   }
}
```

Response

Supported Media Types: application/json

Example of Response Body

The following is an example of the response body in JSON format.



}]

To get the status of the unmatch transactions job and view its details, see Retrieve Job Status (Transaction Matching).

Update Unmatched Transactions (Transaction Matching)

Updates one or more editable attributes in an unmatched transaction.

REST Resource

```
POST /arm/rest/{api_version}/dataSources/{dataSource}/transactions/
{transaction}
```

Required Roles

Service Administrator, Power User, Preparer

The user who created a profile can also update transactions associated with that profile.

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request specific to this job.

Table 17-70UPDATE UNMATCHED TRANSACTIONS

Name	Description	Туре	Required
api_version	Version of the API you are working with: v1	Path	Yes
dataSource	Text ID of the data source associated with the unmatched transaction whose attributes must be updated	Path	Yes
transaction	Transaction ID of the unmatched transaction whose attributes must be updated	Path	Yes
reconId	Text Id of the reconciliation associated with the unmatched transaction that must be updated	Payload	Yes
attributeId	Text Id of the attribute within the unmatched transaction that must be updated	Payload	Yes



Name	Description	Туре	Required
calculate	 Set to one of the following values: True - Values of calculated attributes are recalculated False - Values of calculated attributes are left unchanged. The default setting is False. 	Payload	No
forceReopen	 Valid values are: True - Reconciliations will be reopened if the Adjustment Accounting Date is less than the Closed Through Date. False - Matched transactions whose Adjustment Accounting Date is less than the Closed Through Date are skipped. This is the default setting. 		No

Table 17-70 (Cont.) UPDATE UNMATCHED TRANSACTIONS

Example URL

```
https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/arm/rest/v1/
dataSources/POS/transactions/1012
```

Example of request body

```
{
    "reconId": "INTERCO133",
    "attributeId": "POS_AMOUNT",
    "value": "210015.05",
    "calculate": false,
    "forceReopen": false
}
```

Response

Supported Media Types: application/json

Example of Response Body

The following is an example of the response body in JSON format.

```
{
    "type": "TM",
    "items": null,
    "error": null,
    "link": null,
    "status": 0,
```



Financial Consolidation and Close REST APIs

Use the Financial Consolidation and Close REST APIs to get the REST API version, retrieve journals and journal details, submit, approve, post, unpost, and reject journals, and update journal periods. You can also import supplementation data, copy data, clear data, and deploy form templates.

Getting API Versions for Financial Consolidation and Close APIs

You can get information on REST API versions using REST resources. See Getting API Versions for Planning. Financial Consolidation and Close APIs use the same version numbers as Planning.

Get Information about a Specific API Version for Financial Consolidation and Close APIs

Returns details for a specific REST API version for Financial Consolidation and Close.

REST Resource

GET /HyperionPlanning/rest/{api version}

Required Roles

Service Administrator, Power User, User, Viewer

Request

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 18-1 Parameters

Name Description

<code>api_version</code> Version of the API you are developing with, such as V1

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.



Table 18-2 Parameters

Name	Description
version	The version, such as V1

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"version": "v1",
"lifecycle": "active",
"isLatest": true,
"links": [{
    "rel": "canonical",
    "href": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v2"
}, {
    "rel": "predecessor-version",
    "href": "https://<SERVICE_NAME>-
    <TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v1"
}]
}
```

Perform Journal Actions for Financial Consolidation and Close

Performs journal action for the specified journal. Changes the journal status to the new state specified.

Journal actions supported: SUBMIT, APPROVE, POST, UNPOST, REJECT

This API works only for Financial Consolidation and Close.

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
journals/{journalLabel}/actions
```

Required Roles

Role	Available Actions
Service Administrator	All
Power User	Submit/Post/Unpost: Need Write access to all the members in the journal
	Approve/Reject. Need Read access to all the members in the journal
User	Approve/Reject. Need Read access to all the members in the journal and Journal option must have been enabled



Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 18-3 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
journalLabel	Label for the journal	Path	Yes	None
parameters	Parameters for journals, for example:	JSON	Yes	None
	<pre>{"parameters" :{ "scenario": "Actual", "year": "FY17", "period": "Jan", "consolidation": "FCCS_Entity Input", "action": "POST" }</pre>			
	These parameter fields are described in rows below.			
scenario	The scenario for which you are performing the journal action	Query	Yes	None
year	The year for which you are performing the journal action	Query	Yes	None
period	The period for which you are performing the journal action	Query	Yes	None
consolidation	The consolidation for which you are performing the journal action	Query	No	Entity Input
action	The journal action. Supported valid Action values: SUBMIT,REJECT,APPROVE,POST,UNPOS T	Query	Yes	None

Response

Parameters

The following table summarizes the response parameters.

Table 18-4 Parameters

Name	Description
actionDetail	Journal action, such as Posted



Table 18-4	(Cont.)	Parameters
------------	---------	------------

Name	Description	
actionStatus	Action status, such as 0	

Supported Media Types: application/json

Sample JSON Input

{

{

```
"scenario": "Actual",
"year": "FY17",
"period": "Jan",
"action": "POST"
}
```

Example of Response Body

The following shows an example of the response body.

```
"actionDetail": "Posted",
"actionStatus": 0
}
```

Perform Journal Period Updates for Financial Consolidation and Close

Performs journal period update action for the specified period.

Journal period actions supported: OPEN, CLOSE

This API works only for Financial Consolidation and Close.

REST Resource

```
POST /HyperionPlanning/rest/{api_version}/applications/{application}/
journalPeriods/{period}/actions
```

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.



Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
period	The period for which you are performing the journal action	Path	Yes	None
parameters	Parameters for the journal period, for example:	JSON	Yes	None
	{			
	"parameters": {			
	"scenario": "Actual",			
	"year": "FY17",			
	"action": "OPEN"			
	}			
	J			
	These parameters are described in rows below.			
scenario	The scenario for which you are performing the journal action	JSON	Yes	None
year	The year for which you are performing the journal action	JSON	Yes	None
action	The journal period action. Supported valid Action values: OPEN, CLOSE	JSON	Yes	None

Table 18-5 Parameters

Response

Parameters

The following table summarizes the response parameters.

Table 18-6 Parameters

Description
Journal scenario, such as Actual
Journal year, such as FY18
Journal period, such as Jan
Journal period action, such as Open

Supported Media Types: application/json

Sample JSON Input

{

```
"scenario": "Actual",
"year": "FY17",
"period": "Jan",
"action": "OPEN"
```



```
}
```

Example of Response Body

The following shows an example of the response body.

```
{
    "actionDetail": "Open",
    "actionStatus": 0
    }
```

Retrieve Journals for Financial Consolidation and Close

Returns the list of journals for the given scenario, year, period, journal status and other specified filters.

Paging is supported if the optional offset and limit parameters are provided.

This API works only for Financial Consolidation and Close.

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
journals?
q={"scenario":"Actual","year":"FY16","period":"Jan","consolidation":"FCCS_Enti
ty Input","status":
"WORKING","group":"group1","label":"J1","description":"JournalDesc","entity"
:"FCCS_Total Geography"}&offset=0&limit=5
```

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 18-7 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None



Name	Description	Туре	Required	Default
q	Filters for retrieving the journals, for example:	Query	No	5 journals are returned.
	<pre>{"scenario":"Actual","year":"FY1 6","period":"Jan","consolidation ":"FCCS_Entity Input","status": "WORKING","group":"group1" ,"lab el":"J1" ,"description":"Journal Desc","entity":"FCCS_Total Geography"}</pre>			
	Possible values are described in the following rows.			
cenario	Scenario for the journal, for example: "scenario":"Actual"	Query	Yes	None
ear	Year for the journal, for example: "year":"FY16"	Query	Yes	None
eriod	Period for the journal, for example: "period":"Jan"	Query	Yes	None
onsolidation	Consolidation for the journal, for example: "consolidation":"FCCS_Entity Input"	Query	No	Entity Input
tatus	Status for the journal, for example: "status":"WORKING"	Query	Yes	None
	Valid values are "WORKING" , "SUBMITTED", "POSTED", "APPROVED"			
roup	Group for the journal, for example: "group":"group1"	Query	No	None
abel	Label for the journal, for example: "label":"j1"	Query	No	None
lescription	Description for the journal, for example: "description": "adjustment for salary"	Query	No	None
entity	Entity for the journal, for example: "entity":"FCCS_Total Geography"	Query	No	None
offset	Used for pagination of the records. Indicates the actual index from which the records are returned. It is 0 based.	Query	No	0
imit	Used for pagination of the records. Controls how many items to return. Defaults to 5 if not specified.	Query	No	5

Table 18-7 (Cont.) Parameters

Response

The following table summarizes the response parameters.

Table 18-8 Parameters

Name	Description
totalResults	Total number of journals matching the filter criteria
hasMore	True/False, if there are more pages of records



Name	Description
count	Number of journals in this page
limit	Current page size
offset	Current page number
items	List of journals, followed by attributes of journals, such as below:

Table 18-8 (Cont.) Parameters

```
[{
         "scenario": "Actual",
         "currency": "Entity Currency",
         "createdOn": "2018-07-30 06:22:47.516",
         "modifiedBy": "epm default cloud admin",
         "journalType": "Regular",
         "createdBy": "epm default cloud admin",
         "balanceType": "Balanced",
         "postedBy": null,
         "year": "FY17",
         "description": "JournalDesc1",
         "group": "grp1",
         "status": "Working",
         "label": "J4",
         "period": "Jan"]
}]
```

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body.

```
{
       "totalResults": 10
       "hasMore": false,
       "count": 5,
       "limit": 5,
       "offset": 0,
       "items": [{
       "scenario": "Actual",
       "createdOn": "2018-07-30 06:22:47.516",
       "modifiedBy": "epm default cloud admin",
       "journalType": "Regular",
       "createdBy": "epm default cloud admin",
       "balanceType": "Balanced",
       "postedBy": null,
       "year": "FY17",
       "description": "JournalDesc1",
       "group": "grp1",
       "status": "Working",
       "label": "J4",
       "period": "Jan",
```

```
"journalUrl": {,
       "rel": "Journal Item",
       "href": "https://<SERVICE NAME-
<TENANT NAME.<SERVICE TYPE.<dcx>.oraclecloud.com/HyperionPlanning/faces/LogOn?
SO jumpToEfsStructureHome=Y&SO efsJumpToCardId=EPM CA 6",",
       "data": null,
       "action": "GET",
             }
      },
        {
       "scenario": "Actual",
       "currency": "Entity Currency",
       "createdOn": "2018-07-26 10:21:35.634",
       "modifiedBy": "epm default_cloud_admin",
       "journalType": "Regular",
       "createdBy": "epm default cloud admin",
       "balanceType": "Balanced",
       "postedBy": null,
       "year": "FY17",
       "description": "JournalDesc1",
       "group": "grp1",
       "status": "Working",
       "label": "J2",
       "period": "Jan",
       "journalUrl": {,
       "rel": "Journal Item",
       "href": "https://<SERVICE_NAME-
<TENANT NAME.<SERVICE TYPE.<dcx>.oraclecloud.com/HyperionPlanning/faces/LogOn?
SO jumpToEfsStructureHome=Y&SO efsJumpToCardId=EPM CA 6",",
       "data": null,
       "action": "GET",
      },
      }
      ],
      "links": [
      {
      "rel": "Get Journals",
      "href": "https://<SERVICE NAME-
<TENANT NAME.<SERVICE TYPE.<dcx>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/BotApp/journals",
      "action": "GET
      }
      ],
       }
```

Retrieve Journal Details for Financial Consolidation and Close

Returns the journal details for the given scenario, year, period, consolidation, and the journal name.

This API works only for Financial Consolidation and Close.

REST Resource

```
GET /HyperionPlanning/rest/{api_version}/applications/{application}/
journals/{journal label}?
q={"scenario":"Actual","year":"FY16","period":"Jan","consolidation":"Entity
Input"}&"lineItems"="true"
```

Required Roles

Service Administrator

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 18-9 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	The name of the application	Path	Yes	None
journal label	The label of the journal for which to retrieve journal details	Path	Yes	None
ď	Filters to retrieve the journal, for example:	Query	Yes	None
	<pre>q={"scenario":"A ctual","year":"F Y16","period":"J an","consolidati on":"Entity Input"}</pre>			
scenario	Scenario for the journal, for example: "scenario":"Actual"	Query	Yes	None
year	Year for the journal, for example: "Year":"FY16	Query	Yes	None
period	Period for the journal, for example: "period":"Jan"	Query	Yes	None
consolidation	Consolidation for the journal, for example: "consolidation": "Entity Input"	Query	No	Entity Input
lineItems	Line items for the journal. Valid values are true or false.	Query	No	True



Response

Parameters

The following table summarizes the response parameters.

Table 18-10	Parameters
-------------	------------

Name	Description
totalResults	Total number of journals matching the filter criteria
hasMore	True/False, if there are more pages of records
count	Number of journals in this page
limit	Current page size
offset	Current page number
items	List of journals, followed by attributes of journals, such as below:

```
[{
```

```
"scenario": "Actual",
"currency": "Entity Currency",
"createdOn": "2018-07-30 06:22:47.516",
"modifiedBy": "epm_default_cloud_admin",
"journalType": "Regular",
"createdBy": "epm_default_cloud_admin",
"balanceType": "Balanced",
"postedBy": null,
"year": "FY17",
"description": "JournalDesc1",
"group": "grp1",
"status": "Working",
"label": "J4",
"period": "Jan"]
```

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body.

}]

```
{
[
"scenario": "Actual",
"year": "FY18",
"period": "Feb",
"label": "JETest11",
"journalType": "Regular",
"balanceType": "Balanced",
"status": "Posted",
"description": "Journal description",
"group": "IMPORT_Group",
"createdBy": "epm default cloud admin",
```



```
"modifiedBy": "epm default cloud admin",
"postedBy": "epm_default_cloud_admin",
"createdOn": "2023-12-06 18:48:33.503",
"currency": "Entity Currency",
"consolidation": "FCCS Entity Input",
"totCredit": 1300,
"totDebit": 1300,
"journalLineItems":[
{"amountType": "Debit", "amount": 800, "description": "line description",
"entity": "YY E1",...},
{"amountType": "Credit", "amount": 500, "description": "line description",
"entity": "YY E1",...},
{"amountType": "Debit", "amount": 500, "description": "line description",
"entity": "YY E1",...},
{"amountType": "Credit", "amount": 800, "description": "line description",
"entity": "YY E1",...}
1
}
```

Export Consolidation Journals

This REST API is used to execute an Export Consolidation Journals job using the job name. Before executing this job, you should create an Export Consolidation Journals job in Financial Consolidation and Close.

For details on this task, see "Exporting Consolidation Journals" in *Working with Financial Consolidation and Close*.

This REST API returns the job ID after starting the Export Consolidation Journals job.

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Table 18-11 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None



Name	Description	Туре	Required	Default
application	The name of the application	Path	Yes	None
	Get the application name by using the Get Applications API. See Get Applications.			
jobName	Name of the job should be: Export Journal	String	Yes	None
јоbТуре	Type of Job. Supported value: EXPORT_JOURNAL	String	Yes	None
fileName	Name of the file into which the journal entries are to be exported	String	Yes	None

Table 18-11 (Cont.) Parameters

Example of Request Body

```
{
"jobType": "EXPORT_JOURNAL,
"jobName": "Export Journal",
"parameters": {
    "fileName": "JExport1"
  }
}
```

Response Body

Name	Description
status	Status of the job: -1 =In progress; 0 = Success; 1 = Fail
details	In case of errors, details are published with the error string.
descriptiveStatus	The status of the job, such as Completed or Error
items	Collection of Notification categories
links	Detailed information about the link
href	Links to API call
action	The HTTP call type



Table 18-12 (Cont.) Parameters

Name	Description	
rel	Relationship type. Possible values: self	

Example of Response Body:

The following shows an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "http://slc10xth:9000/HyperionPlanning/rest/v3/
applications/FccsRef3/jobs/184",
            "action": "GET"
        },
        {
            "rel": "job-details",
            "href": "http://slc10xth:9000/HyperionPlanning/rest/v3/
applications/FccsRef3/jobs/184/details",
            "action": "GET"
        }
    ],
    "descriptiveStatus": "Processing",
    "status": -1,
    "jobId": 184,
    "jobName": "JExport1",
    "details": null
```

Import Consolidation Journals

This REST API is used to execute an Import Consolidation Journals job using the job name. Before executing this job, you should create an Import Consolidation Journals job in Financial Consolidation and Close.

For details on this task, see "Importing Consolidation Journals" in *Working with Financial Consolidation and Close*.

This REST API returns the job ID, job status and job details after starting the Import Consolidation Journals job.

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/jobs

Required Roles

Service Administrator

Request



Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application	The name of the application Get the application name by using the Get Applications API. See Get Applications.	Path	Yes	None
jobName	Name of the job should be an existing journal import job: <job name></job 	String	Yes	None
јоbТуре	Type of Job. Supported value: IMPORT_JOURNAL	String	Yes	None
fileName	Name of the file from which the journal entries are to be imported	String	No	File specified in the Job
errorFileName	Name of the log file in which messages generated during the import process are to be recorded	String	No	None

Table 18-13 Parameters

Example of Request Body

```
{
   "jobType": "IMPORT_JOURNAL",
   "jobName": "IMPORT1",
   "parameters": {
        "fileName": "TestImport1.jlf",
        "errorFileName": "DHQA_TestImport1_error.log"
   }
}
```

Response Body



Name	Description
type	Application type, for example, FCCS
status	Status of the job: -1 =In progress; 0 = Success; 1 = Fail
details	In case of errors, details are published with the error string.in the job error file and Job Console.
descriptiveStatus	The status of the job, such as Completed or Error
items	Collection of Notification categories
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type. Possible values: self

Table 18-14 Parameters

Example of Response Body:

The following shows an example of the response body in JSON format.

```
{
"links":[
{
"rel": "self",
"href": " https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/FccsRef3/jobs/13",
"action": "GET"
},
"rel": "job-details",
"href": " https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
/applications/FccsRef3/jobs/13/details",
"action": "GET"
}
],
"descriptiveStatus": "Processing",
"status": -1,
"jobId": 13,
"jobName": "JIMPORT1",
"details": null
}
```

Copy Data

This REST API is used to execute a Copy Data job using the profile name. Before executing this job, you should create a Copy Data profile in Financial Consolidation and Close.

For details on this task, see Using Copy Data Profiles.



This REST API returns the job id after starting the Copy Data job.

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Table 18-15 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application	The name of the application	Path	Yes	None
	Get the application name by using the Get Applications API, for example, FCCS or TRCS. See Get Applications.			
jobName	Name of the job should be: EXECUTE PROFILE	String	Yes	None
јоbТуре	Type of Job. Supported value: COPY_DATA	String	Yes	None
ProfileName	Name of the profile to use to copy data	String	Yes	None

Example of Request Body

```
{
   "jobType": "Copy_Data",
   "jobName": "Execute Profile",
   "parameters": {
        "ProfileName": "<ProfileName>",
    }
}
```

Response Body

Name	Description
type	Financial Consolidation and Close Application type, for example, FCCS
status	Status of the job: -1 =In progress; 0 = Success; 1 = Fail
details	In case of errors, details are published with the error string.
descriptiveStatus	The status of the job, such as Completed or Error
items	Collection of Notification categories
links	Detailed information about the link
href	Links to API call



Table 18-16 (Cont.) Parameters

Name	Description
action	The HTTP call type
rel	Relationship type. Possible values: self

Example of Response Body:

The following shows an example of the response body in JSON format.

```
{
  "jobId": 8,
  "descriptiveStatus": "Processing",
  "details": null,
  "jobName": "Copy Data",
  "status": -1,
  "links": [
    {
      "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/<applicationName>/jobs/<JobId>","rel":"self","action":"GET"},
      "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/,
      "rel":"job-details","action":"GET"},
    }
  1
1
```

Clear Data

This REST API is used to execute a Clear Data job using the profile name. Before executing this job, you should create a Clear Data profile in Financial Consolidation and Close.

For details on this task, see Using Clear Data Profiles.

This REST API returns the job id after starting the job.

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.



Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application	The name of the application Get the application name by using the Get Applications API, for example, FCCS or TRCS. See Get Applications.	Path	Yes	None
jobName	Name of the job should be: EXECUTE PROFILE			
јорТуре	Type of Job. Supported value : Clear_Data	String	Yes	None
ProfileName	The name of the profile to use to clear data	String	Yes	None

Table 18-17 Clear Data

Example of request body

Example:

```
{
   "jobType": "Clear_Data",
   "jobName": "Execute Profile",
   "parameters": {
        "ProfileName": "<ClearData_01>",
    }
}
```

Response

Table 18-18 Parameters

Name	Description	
type	Financial Consolidation and Close Application type, for example, FCCS	
status	Status of the job: -1 =In progress; 0 = Success; 1 = Fail	
details	In case of errors, details are published with the error string.	
descriptiveStatus	The status of the job, such as Completed or Error	
items	Collection of Notification categories	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Relationship type. Possible values: self	



Supported Media Types: application/json

Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "jobId": 8,
  "descriptiveStatus": "Processing",
  "details": null,
  "jobName": "Clear Data",
  "status": -1,
  "links": [
    {
      "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/<applicationName>/jobs/<JobId>","rel":"self","action":"GET"},
      "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/,
      "rel":"job-details","action":"GET"},
    }
 1
}
```

Sample

```
{
  "jobId": 8,
  "descriptiveStatus": "Processing",
  "details": null,
  "jobName": "Clear Data",
  "status": -1,
  "links": [
    {
      "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/ Testapp /jobs/8",
      "rel":"self", "action":"GET"},
      "href":"https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/Testapp/jobs/8/details",
      "rel":"job-details","action":"GET"}
                                            }
  1
}
```

Validate Metadata

This REST API is used to automatically run the Validate Metadata process to ensure an errorfree database refresh and consolidation.

For details on this task, see "Validating Metadata" in Administering Financial Consolidation and Close.

Required Roles

Service Administrator

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application_name}/
application/validatemetadata?logFileName={logfile_name}

Request

Supported Media Types: application/json

Table 18-19 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application_name	The name of the application	Path	Yes	None
	Get the application name by using the Get Applications API. See Get Applications.			
logFileName	Name of the log file of exported results	Payload	No	None

Response

Supported Media Types: application/json

Table 18-20 Parameters

Name Description	
numWarnings	Number of metadata warnings
numInfo	Number of metadata information messages
outPutFileName	Ouput file name with the extension of .csv
numErrors	Number of metadata error messages
status	The status of the job, such as Completed or Error

Example of Response Body:

The following shows an example of the response body in JSON format.

```
{
"numWarnings": 0,
"numInfo": 0,
"outPutFileName": "ValidateMetadata.csv,
"numErrors": 20,
"status": "Validate Metadata Completed"
}
```

Generate an Intercompany Matching Report

This REST API is used to execute an Intercompany Matching Report job.

For details on this task, see Managing Intercompany Matching Reports.



This REST API returns the job ID after starting the Intercompany Matching Report job.

Required Roles

Service Administrator, Power User or User

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/jobs

Request

Supported Media Types: application/json

Table 18-21 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application_name	The name of the application	Path	Yes	None
	Get the application name by using the Get Applications API. See Get Applications.			
jobName	The name of the saved Intercompany report definition, for example: IC_Job_01	Payload	Yes	None
јорДуре	Type of Job. Supported value: GENERATE_INTERCOMPANY_REPORT	Payload	Yes	None
parameters	Pass optional parameters to set the report POV	Payload	No	None

Table 18-22Optional Parameters

Name	Description
scenario	The member of the Scenario dimension for the report, for example, Actual
years	The member of the Year dimension for the report, for example, FY22
period	The member of the Period dimension for the report, for example, December
reportFormat	The format for the report, for example, HTML
fileName (optional)	A filename for the report, for example, intercompany_receivables_report

Example of Request Body

```
{
"jobType": "GENERATE_INTERCOMPANY_REPORT",
"jobName": "icp1",
"parameters": {
"scenario":"actual",
"years": "FY22",
"period":"Dec",
"reportFormat":"HTML"
"fileName":"intercompany_receivables_report"
}
```

Response Body

Supported Media Types: application/json



Name	Description
type	Financial Consolidation and Close Application type, for example, FCCS
status	Status of the job: -1 =In progress 0 = Success; 1 = Fail 2 = Cancel Pending 3 = Cancelled 4 = Invalid Parameter >4 = Unknown
details	In case of errors, details are published with the error string.
descriptiveStatus	The status of the job, such as Completed or Error
items	Collection of Notification categories
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type. Possible values: self

Table 18-23Parameters

Example of Response Body:

The following shows an example of the response body in JSON format.

```
{
    "descriptiveStatus": "Processing",
    "jobId": 33,
    "jobName": "icp1",
    "details": null,
    "status": -1,
    "links": [
        {
            "rel": "self",
            "href": "http://slcar262.usdv1.oraclecloud.com:12055/
HyperionPlanning/rest/v3/applications/tst/jobs/33",
            "action": "GET"
        },
        {
            "rel": "job-details",
            "href": "http://slcar262.usdv1.oraclecloud.com:12055/
HyperionPlanning/rest/v3/applications/tst/jobs/33/details",
            "action": "GET"
        }
    ]
}
```

19 Task Manager REST APIs

Use the Task Manager REST APIs to deploy task manager templates, update the task status for event monitoring, and manage Oracle Integration Cloud connections.

Getting API Versions for Task Manager APIs

You can get information on REST API versions using REST resources. See Getting API Versions for Planning. Task Manager REST APIs use the same version numbers as Planning.

Table 19-1 Task Manager REST APIs

API Name	Versions
Deploy Task Manager Templates	v1
Update Task Status for Event Monitoring	v1

Deploy Task Manager Templates

Deploys a Task Manager template to provided year and period to create a new schedule.

This API executes the job based on the job type (TM_DEPLOY_TEMPLATE) provided as a JSON parameter. This is an asynchronous API and responds with a callback API to get the job status.

Parameters

The following table summarizes the client request:

Table 19-2 TM_DEPLOY_TEMPLATES Parameters

Name	Description	Туре	Required	Default
jobType	Type of the Job, value for this Job is TM_DEPLOY_TEM PLATE	String	Yes	None
templateName	The name of the task manager template to be deployed	String	Yes	None
scheduleName	The name of the new schedule that will be created from the template	String	Yes	None
year	The member of the Year dimension where the template will be deployed	String	Yes	None



Name	Description	Туре	Required	Default
period	The member of the Period dimension where the template will be deployed	String	Yes	None
dayZeroDate	The Day Zero date used in creating the Schedule in a valid format	String	Yes	None
dateFormat	The date format for the Day Zero Date	String	No	YYY-MM-DD
orgUnit	The Organization Unit name	String	No	None

Table 19-2 (Cont.) TM_DEPLOY_TEMPLATES Parameters

REST Resource

POST/HyperionPlanning/rest/cmapi/{api version}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 19-3 Parameters

Name	Description	Туре	Required	Default
api_version	It is a path parameter. Version of the API you are developing with for example, v1	String	Yes	None

Examples of Request Body

```
"templateName":"Template1",
```

```
"scheduleName": "scheduleA",
```

```
"year":"2021",
"period":"Jan",
"dayZeroDate":"2021-01-01"
}
```

Example 2:

```
{
```

}

```
"jobType":"TM_DEPLOY_TEMPLATE",
```

```
"parameters":{
```

```
"templateName":"Template1",
```

```
"scheduleName": "scheduleA",
```

```
"year":"2021",
```

```
"period":"Jan",
```

```
"dayZeroDate":"2021-01-01",
```

```
"orgUnit":"JPAC"
```

}

Response

}

Supported Media Types: application/json

Name	Description
jobId	Job ID
descriptiveStatus	Any additional details
details	Message to the end user. In case of errors, details are published.
status	-1 – In Progress; 0 – Success; 1 – Fail
items	Not applicable for this job type
links	Detailed information about the link
rel	Possible values: self
href	Links to API call



Table 19-4 (Cont.) Parameters

Name	Description
action	The HTTP call type

JSON Output

The following is an example of the response body in JSON format.

```
{
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/
cmapi/v1/jobs",
            "action": "POST"
        },
        {
            "rel": "Job Status",
            "href": "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/
cmapi/v1/jobs/14008",
            "action": "GET"
        }
    ],
    "details": "In Process",
    "status": -1,
    "type": "TM",
    "link": {},
    "error": null,
    "items": []
```

}

Update Task Status for Event Monitoring

This API is used to update the task status to "completed" based on an event monitoring integration type. For information on setting up integration type for Event Monitoring, see Creating Custom Event Monitoring Integrations in Administering Financial Consolidation and Close.

REST Resource

POST /HyperionPlanning/rest/cmapi/{api_version}/updateTasksForEventMonitoring

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

Table 19-5 Parameters

Name	Description	Туре	Require d	Default Value
api_version	Version of the API you are developing with	Path	Yes	v1
eventName	Event name as specified in the custom event monitoring integration type.	JSON (String)	Yes	None
integrationName	Integration Code of the custom event monitoring integration type.	JSON (String)	Yes	None
integrationConnectionName	Connection name which the event monitoring integration belongs to.	JSON (String)	Yes	None
parameters	Parameter values as per the custom event monitoring integration type.	JSON	Yes	None
	<pre>The format is: [{"name" :"param1", "value":"value1" , {"name" :"param2",</pre>			
	"value":"value2" }]			
message	A message needs to be added while closing the task. This information is displayed on the task dialog.	JSON (String)	No	None
logLocation	Any location which needs to be added which refers to a log. This information is displayed on the task dialog.	JSON (String)	No	None



Name	Description	Туре	Require d	Default Value
reportLocations	One or more URLs to add while closing the task. The format is: ["Example_URL1", "Example_URL2"]	JSON (List of Strings)	No	None
	This information will be displayed on the Task dialog box.			

Table 19-5 (Cont.) Parameters

Example URL

```
https://<BASE-URL>/HyperionPlanning/rest/cmapi/v1/
updateTasksForEventMonitoring
```

Payload

Example 1

If the custom event monitoring integration has the following properties:

- Integration Connection Name: customAppConn
- Integration Code: customPeriodClose
- Event Name: custom.CloseProcess.period.close
- Parameter Code: periodName and ledgerID

And the task is set up with following parameters:

- periodName: FY18
- ledgerID: 123

The following payload should be sent to close the task:

```
{
    "eventName" : "custom.CloseProcess.period.close",
    "integrationName" : "customPeriodClose",
    "integrationConnectionName" : "customAppConn",
    "parameters": [{
        "name": "periodName",
        "value": "FY18"
    }, {
        "name": "ledgerID",
        "value": "123"
    }]
}
```

Note:

The API expects integration code to be passed for the parameter integrationName.



Example 2

```
{
    "eventName": "custom.CloseProcess.period.close",
    "integrationName": "customPeriodClose",
    "integrationConnectionName": "customAppConn",
    "parameters": [
        {
            "name": "periodName",
            "value": "FY18"
        },
        {
            "name": "ledgerID",
            "value": "123"
        }
    ],
    "message": "Close period",
    "logLocation": "/logs/closeperiod.txt",
    "reportLocations": [
        "http://oracle.com/reportLocation.html"
    1
}
```

Response

Supported Media Types: application/json

Example of a Successful Response

```
Http status code: 200
{
    "type": "RC",
    "items": null,
    "error": null,
    "link": null,
    "status": null,
    "details": "2 task(s) updated.",
    "links": [
        {
            "rel": "self",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/cmapi/v1/
updateTasksForEventMonitoring",
            "action": "POST"
        }
    ]
}
```

Example of an Error Response

Http status: 500

Working with Connections in Task Manager

Use these REST APIs to work with Oracle Integration Cloud connection in Task Manager.



Oracle Integration Cloud is used by custom Process Automation and Event Monitoring Integration tasks.

With multiple environments, using REST APIs saves you time and effort by automating the process of logging in and configuring connections. For information about accessing environments, see Accessing EPM Cloud.

Task	Request	REST Resource
Create a Connection	POST	<pre>/HyperionPlanning/rest/fcmapi/{api_version}/ {module}/connections</pre>
View All Connections	GET	/HyperionPlanning/rest/fcmapi/{api_version}/ {module}/connections
Update a Connection	PUT	/HyperionPlanning/rest/fcmapi/{api_version}/ {module}/connections/{id}
Delete a Connection	DELETE	<pre>/HyperionPlanning/rest/fcmapi/{api_version}/ {module}/connections/{id}</pre>

Table 19-6 Working with Connections in Task Manager

Create a Connection

Use this REST API to create a connection to Oracle Integration Cloud using Task Manager.

REST Resource

POST /HyperionPlanning/rest/fcmapi/{api version}/{module}/connections

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request parameters for Basic authentication and OAuth 2.0 authentication.

Table 19-7 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you're developing with (must be v1)	Path	Yes	None
module	The name of the module for which to create a connection. Set this value to FCM.	Path	Yes	None

Name	Description	Туре	Required	Default
url	The URL of the Integration Cloud environment. Note: The URL must be provided only till the server name, which is oraclecloud.com.	Payload	Yes	None
authType	Type of authentication: Basic OAuth	Payload	Yes	None
	Note: The parameter is applicable only for OAuth 2.0 authentication type.			
oauthProperties	Specify the access token, client ID, and scope of the URL for OAuth 2.0 authentication.	of Payload	Payload	None
	Note: The parameter is applicable only for OAuth 2.0 authentication type.			
username	A username with the Service Administrator predefined role.	Payload	Yes	None
	Note: This parameter is applicable only for basic authentication type.			

Table 19-7 (Cont.) Parameters

Name	Description	Туре	Required	Default
password	The encrypted password for the user.	Payload	Yes	None
	For security reasons, only an encrypted password is allowed. Use the EPM Automate encrypt command to generate the encrypted password. See encrypt.			
	Note: This parameter is applicable only for basic authentication type.			
type	The type of connection. For Oracle Integration Cloud, set this value to ICS.	Payload	Yes	None

Table 19-7 (Cont.) Parameters

```
Example of Request Body- Basic Authentication
```

```
{
    "url": "<URL of Oracle Integration Cloud>",
    "username": "<NEW_USERNAME>",
    "password": "<NEW_PASSWORD>",
    "type" : "ICS"
    "authType": "BASIC"
}
```

Example of Request Body- OAuth 2.0 Authentication

```
{
    "url": "<URL of Oracle Integration Cloud>",
    "type": "ICS",
    "authType": "OAUTH2",
    "oauthProperties": {
        "accessTokenUrl": "<Access token URL>",
        "clientId": "<Client ID>",
        "scope": "<Scope URL>",
        "clientSecret": "<EPMAUTOMATE Encrypted password>"
    }
}
```

Response

Supported Media Type: application/json

Table 19-8 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.

Example of Response Body

```
{
  "details": "Connection created successfully."
}
```

View All Connections

Use this REST API to view all the connections to Oracle Integration Cloud using Task Manager.

Required Roles

Service Administrator

REST Resource

GET /HyperionPlanning/rest/fcmapi/{api_version}/{module}/connections

Request

Parameters:

The following table summarizes the client request.

Table 19-9 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which you want to view the connections. Set this value to FCM.	Path	Yes	None

Response

Supported Media Types: application/json

The following table summarizes the parameters.

Table 19-10 Parameters

Parameters	Description
items	Collection of information about the resource
id	Unique identifier for the connection
type	The type of connection. For Oracle Integration Cloud, set this value to ICS.



Parameters	Description	
url	The URL of the Integration Cloud environment.	
	Note: The URL must be provided only till the server name, which is oraclecloud.com.	
authType	Type of authentication: Basic OAuth 	
oauthProperties	Provides the access token, client ID, and scope of the URL for OAuth 2.0 authentication.	
details	In case of errors, details are published with the error string	

Table 19-10 (Cont.) Parameters

Example Response - Basic Authentication

```
{
    "links": [
        {
            "rel": "self",
            "href": "<URL of Oracle Integration Cloud>",
            "action": "GET"
        }
    ],
    "details": null,
    "items": [
        {
            "username": "ats admin2",
            "password": null,
            "url": "<URL of Oracle Integration Cloud>",
            "id": 10000000558008,
            "type": "ICS"
            "authType": "BASIC"
        }
    ]
}
```

Example Response - OAuth 2.0 Authentication

```
"accessTokenUrl": "<Access token URL>",
    "clientId": "<Client ID>",
    "scope": "<Scope URL>"
    }
    }
    /
    links": [
      {
            "rel": "self",
            "href": "<URL of Oracle Integration Cloud>",
            "action": "GET"
        }
    ]
}
```

Update a Connection

Use this REST API to update a specific connection to Oracle Integration Cloud using Task Manager.

REST Resource

PUT /HyperionPlanning/rest/fcmapi/{api_version}/{module}/connections/{id}

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters:

The following table summarizes the client request.

Table 19-11 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which to update a connection. Set this value to FCM.	Path	Yes	None
id	The identifier of the connection that must be updated	Path	Yes	None
url	The URL of the Integration Cloud environment.		Yes	None
	Note: The URL must be provided only till the server name, which is oraclecloud.com.			






Table 19-11 (Cont.) Parameters

Name	Description	Туре	Required	Default
type	The type of connection. For Oracle Integration Cloud, set this value to ICS.	Payload	Yes	None

Table 19-11 (Cont.) Parameters

Example of Request Body - Basic Authentication

```
{
    "url": "<URL of Oracle Integration Cloud>",
    "username": "<NEW_USERNAME>",
    "password": "<NEW_PASSWORD>"
    "authType": "BASIC"
}
```

Example of Request Body – OAuth 2.0 Authentication

```
{
    "url": "<URL of Oracle Integration Cloud>",
    "type": "ICS",
    "authType": "OAUTH2",
    "oauthProperties": {
        "accessTokenUrl": "<Access token URL>",
        "clientId": "<Client ID>",
        "scope": "<Scope URL>",
        "clientSecret": "<EPMAUTOMATE Encrypted password>"
    }
}
```

Response

Supported Media Type: application/json

Table 19-12 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.

Example of Response Body

Example 1:

```
{
   "details": "Connection updated successfully."
}
```

Example 2:

```
{
  "details": "Invalid parameters. Test Connection is failed"
}
```



Delete a Connection

Use this REST API to delete a specific connection to Oracle Integration Cloud using Task Manager.

Required Roles

Service Administrator

REST Resource

DELETE /HyperionPlanning/rest/fcmapi/{api version}/{module}/connections/{id}

Request

Parameters:

The following table summarizes the client request.

Table 19-13 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with (must be v1)	Path	Yes	None
module	The name of the module for which to delete a connection. Set this value to FCM.	Path	Yes	None
id	The identifier of the connection that must be deleted	Path	Yes	None

Response

Supported Media Type: application/json

Table 19-14 Parameters

Parameters	Description
details	In case of errors, details are published with the error string.

Example of Response Body

```
{
  "details": "Connection deleted successfully."
}
```



20 Supplemental Data Manager REST APIs

Use the Supplemental Data Manager REST APIs to import supplemental collection data for Financial Consolidation and Close and deploy form templates.

Getting API Versions for Supplemental Data Manager APIs

You can get information on REST API versions using REST resources. See Getting API Versions for Planning. Supplemental Data Manager REST APIs use the same version numbers as Planning.

Table 20-1 Supplemental Data Manager REST APIs

API Name	Versions
Import Supplemental Collection Data for Financial Consolidation and Close	v3
Deploy Form Templates	v3

Import Supplemental Collection Data for Financial Consolidation and Close

Imports supplemental data to a collection for the frequency dimensions defined in the collection interval of the collection. Returns the success or failure status.

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/
fcmjobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Parameters

Table 20-2 IMPORT_SUPPLEMENTAL_COLLECTION_DATA

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None



Name	Description	Туре	Required	Default
application	The name of the application Get the application name by using the Get Applications API, for example, FCCS or TRCS. See Get Applications.	Path	Yes	None
jobName	Name of the job	String	No	None
jobType	Type of the Job. Supported value for this Job IMPORT_SUPPLEMENT AL_COLLECTION_DATA	String	Yes	None
fileName	File name to be imported, for example, dataset.csv	String	Yes	None
collection	Collection or sub- collection name	String	Yes	None
year	The year for which the collection is deployed	String	Yes	None
period	Period name for which the collection is deployed	String	Yes	None
parameter	Runtime parameter. This is the frequency dimension used for the Collection.	String	No	None
value	Runtime parameter value. This is the member value for the dimension specified in the parameter.	String	No	None

Table 20-2 (Cont.) IMPORT_SUPPLEMENTAL_COLLECTION_DATA

Table 20-3 Examples of runtime parameters

Parameter	Value	
Product	Oracle EPM	
Consolidation	Entity Input	
Movement	Actual	

Examples of request body

Example 1

```
{
  "jobType" : "IMPORT_SUPPLEMENTAL_COLLECTION_DATA",
  "parameters": {
        "fileName":"import_sdm_data.csv",
        "collection":"Investment Detail Collection",
        "year":"2019",
        "period":"Dec",
```

```
"product:"Oracle EPM",
                             "consolidation":"Entity Input",
                              }
Example 2
 "jobType" : "IMPORT SUPPLEMENTAL COLLECTION DATA",
"parameters": {
                             "fileName":"import sdm data.csv",
                             "collection":"Investment Detail Collection",
                             "year":"2020",
                             "period":"January",
                             "category":"Oracle EPM",
                             "movement":"Actual",
```

```
}
```

}

{

Example 3

```
{
"jobType" : "IMPORT SUPPLEMENTAL COLLECTION DATA",
"parameters": {
                              "fileName":"import sdm data.csv",
                              "collection":"Investment Detail Collection",
                              "year":"2019",
                              "period":"December",
                              "scenario":"Actual",
                              }
}
```

Response

Supported Media Types: application/json

Parameters:

Table 20-4 Parameters

Name	Description	
type	FCCS Application type, for example, FCCS	
status	-1 - In Progress; 0 - Success; 1 - Fail	
details	In case of errors, details are published with the error string	
descriptiveStatus	The status of the job, such as Completed or Error	
items	Collection of Notification categories	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Relationship type. Possible values: self	

Example of Response Body



The following is an example of the response body in JSON format.

```
{
  "jobId":10000000114040,
  "descriptiveStatus":"In Progress",
  "details": "In Progress",
  "status": -1,
  "items": [],
  "links": [
    {
      "rel": "self",
      "href": "https://<SERVICE NAME-
<TENANT NAME.<SERVICE TYPE.<dcx>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/FCCS/fcmjobs/10000000114040"
    }, {",
      "action":"GET"
    }
 ],
ļ
```

Deploy Form Templates

Enables you to deploy form templates that have been created in Financial Consolidation and Close.

For details on Using Deploying a Form Template to a Data Collection Period.

This REST API returns the job id after starting the job.

REST Resource

POST /HyperionPlanning/rest/{api version}/applications/{application}/fcmjobs

Required Roles

Service Administrator, Power User

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request parameters specific to this job.

Table 20-5 Deploy Form Template

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None



Name	Description	Туре	Required	Default
application	The name of the application Get the application name by using the Get Applications API, for example, FCCS. See Get Applications.	Path	Yes	None
jobName	Name of the job that has been defined in Financial Consolidation and Close or no value for the job	String	No	None
јоbТуре	Type of Job. Supported value: DEPLOY_FORM_TEM PLATES	String	Yes	None
CollectionInter valName	The name of the collection interval to which the template should be deployed	String	Yes	None
Parameter for frequency dimension 1	Dimension and member name of interval frequency dimension, to which the template should be deployed.	String	No	None
	This optional key value parameter depends on the number of frequency dimensions in the interval. The key should be dimension name and the value should be member name.			

Table 20-5 (Cont.) Deploy Form Template

Name	Description	Туре	Required	Default
Parameter for frequency dimension 2	Dimension and member name of interval frequency dimension, to which the template should be deployed. This optional key value parameter depends on the number of frequency dimensions in the interval. The key should be dimension name and the value should be member name.	String	Νο	None
Parameter for frequency dimension 3	Dimension and member name of interval frequency dimension, to which the template should be deployed. This optional key value parameter depends on the number of frequency dimensions in the interval. The key should be dimension name and the value should be member name.	String	No	None
Parameter for frequency dimension 4	Dimension and member name of interval frequency dimension, to which the template should be deployed. This optional key value parameter depends on the number of frequency dimensions in the interval. The key should be dimension name and the value should be member name.	String	No	None

Table 20-5 (Cont.) Deploy Form Template

Name	Description	Туре	Required	Default
Template	Names of the form templates to deploy. You can provide multiple parameters with the same key as "TEMPLATE" and this will be converted to a JSON array and passed as a single parameter in the JSON string.	JSON Array	No	None
	This is an optional parameter. However, if nothing is specified for the TEMPLATE key, this parameter is still present as an empty JSON Array in the JSON string, and all templates for the given interval will be deployed. Even if you give only one template name, this should still be passed as a JSON array.			
ResetWorkflows	Either true or false. Optional parameter indicating whether all forms should be reset back to the first stage after redeploying. This parameter is also derived by the system based on changes to the template and collection, so the system-derived value can override	Boolean	No	false

	Table 20-5 ((Cont.)	Deploy	Form	Template
--	--------------	---------	--------	------	----------

Examples of request body

Example 1:

{

```
"jobType" : "DEPLOY_FORM_TEMPLATES",
```

```
"parameters":
    {
        "CollectionIntervalName" : "Journal Collection Interval",
        "Year" : "2020",
        "Period" : "July",
        "Product" : "Oracle EPM",
        "Consolidation" : "Entity Input",
        "Consolidation" : "Entity Input",
        "Template" : [ "Template,1","Template 2" ],
        "ResetWorkflows" : "true"
    }
}
```

Example 2:

```
{
   "jobType" : "DEPLOY_FORM_TEMPLATES",
   "parameters":
        {
            "CollectionIntervalName" : "Loan Collection Interval",
            "Year" : "2020",
            "Period" : "July",
            "Category" : "Oracle EPM",
            "Movement" : "Actual",
            "Template" : ["Template 3"]
        }
}
```

```
Example 3:
```

```
{
    "jobType" : "DEPLOY_FORM_TEMPLATES",
    "parameters":
        {
            "CollectionIntervalName" : "Default",
            "Year" : "2020",
            "Period" : "July",
            "Scenario" : "Actual",
            "Template" : ["Template 5","Template 6"],
            "ResetWorkflows" : "false",
        }
}
```

Example 4:

```
{
    "jobType" : "DEPLOY_FORM_TEMPLATES",
    "parameters":
        {
            "CollectionIntervalName" : "Custom Interval",
            "Year" : "2020",
            "Period" : "July",
            "Template" : ["Template 5","Template 6","Template
7","Template 8"]
```



Response

}

Table 20-6 Parameters

}

Name	Description	
jobId	Financial Consolidation and Close job ID	
descriptiveStatus		
details	Any additional details	
Status	-1 = In progress; 0 = Success; 1 = Fail	
items	Not applicable for this job type	
links	Detailed information about the link	
href	Links to API call	
action	The HTTP call type	
rel	Possible values: self	

Supported Media Types: application/json

JSON Output

The following is an example of the response body in JSON format.

```
{
   "jobId":10000000114040,
  "descriptiveStatus":",
  "detail":"In Progress",
   "status":-1,
   "items":null,
   "links":[
      {
         "rel":"self",
         "href":"https://<SERVICE NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v3/
applications/FCCS/fcmjobs/10000000114040",
         "action":"GET"
     }
  ]
}
```

21 Enterprise Journal REST APIs

Use the Enterprise Journal REST APIs to:

- Monitor Enterprise Journals for Financial Consolidation and Close
- Execute an Enterprise Journal job
- Retrieve Enterprise Journals for Financial Consolidation and Close
- Retrieve Enterprise Journal Content for Financial Consolidation and Close
- Retrieve Enterprise Journal Content by Year and Period for Financial Consolidation and Close
- Update Enterprise Journal Posting Status for Financial Consolidation and Close

Getting API Versions for Enterprise Journal APIs

You can get information on REST API versions using REST resources. See Getting API Versions for Planning. The Enterprise Journal REST APIs use the same version numbers as Planning.

API Name	Versions
Execute an Enterprise Journals Job	v1
Monitor Enterprise Journals for Financial Consolidation and Close	v1
Retrieve Enterprise Journals for Financial Consolidation and Close	v1
Retrieve Enterprise Journal Content for Financial Consolidation and Close	v1
Retrieve Enterprise Journal Content by Year and Period for Financial Consolidation and Close	v1
Update Enterprise Journal Posting Status for Financial Consolidation and Close	v1
Update Validation Status of Enterprise Journals for Financial Consolidation and Close	v1

Table 21-1 Enterprise Journal REST APIs

Monitor Enterprise Journals for Financial Consolidation and Close

Returns the status of Journals for the given parameters.

Note:

- If all journals for given parameters are closed, then the output status would be '0' and detail text specifies that all journals are closed.
- If any journal for the given parameters is in Open status (Pending, Open with Preparer, Open with Approver etc.), then the output status would be '-1'.
- In case of error, a positive number will be returned in status.

REST Resource

```
POST /rest/ej/{api version}/jobs/
```

Required Roles

Service Administrator and Power User

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 21-2 Parameters

Name	Description	Path	Required
api_version	Version of the API you are working with, such as v1.	Yes	Yes
јоbТуре	The name of the job EJ_MONITOR_JOURNALS.	No	Yes
year	The name of the year, such as 2021, 2022 etc.	No	No
period	The name of the period, such as Jan, Feb etc.	No	No
filterName	The name of the filter. For example, Journal status filter.	No	Yes

Note:

Either the combination of Year and Period or the Filter Name must be passed. If Year and Period can be part of filter, then Filter Name is sufficient in the parameters.

Example of request body

```
{
   "jobType": "EJ_MONITOR_JOURNALS",
   "parameters": {
        "year": "2022",
```



```
"period": "Jan",
    "filterName": "Jan22_ERPDirectJournals"
}
```

Response

Supported Media Types: application/json

Parameters:

Name	Description
details	Journal Name and Status. First 100 journals only. Shows Open journals first. In case of errors, details are published with the error string.
status	See Migration Status Codes
links	Detailed information about the link
href	Links to the API call
action	The HTTP call type
rel	Relationship type (self, Job Status). if set to Job Status, you can use the href to get the status of the operation

Examples of Response Body

The following is an example of the response body in JSON format when all journals are closed:

```
{
    "status": 0,
    "details": "All journals for the given filter are closed.",
    "links": [
        {
            "rel": "self",
            "href": "https://<SERVICE_NAME>-<TENANT_NAME>.<SERVICE_TYPE>.<dcX>/
HyperionPlanning/rest/ej/{api_version}/jobs/rest/ej/v1/jobs/monitorJournals?
year=2022&period=Jan&filterName=ERP_Direct",
            "action": "GET"
            }
        ],
        "type": "EPM",
}
```

The following is an example of the response body in JSON format when any journal status is open:

```
{
    "status": -1,
    "details": "Journal_NonDirect1|2022|Jan|1000000001, Status:Open with
Preparer; \n
    Journal_NonDirect1|2022|Jan|100000002, Status:Closed",
```

Execute an Enterprise Journals Job

This API will execute the job based on the job type provided as a JSON parameter. It is an asynchronous API. This API will respond with a callback API to get the Job status.

Job Type	Description
exportEJJournals	This job exports the data of "Ready To Validate" or "Ready to Post" journals based on the operation defined. It creates one CSV file per journal based on the target definition and mappings defined in Enterprise Journals and copies it to an EPM Automate-designated directory. The resulting file follows the naming pattern: <year>_<period>_<journal_id>.csv. After creating the export file, it updates the journal Post status to "Post in Progress" if operation is "posting or updated the validation status to "Validation In Progress" if operation is "validation".</journal_id></period></year>
setEJJournalStatus	This job updates the Post status or Validation status of a journal after importing the journal to the ERP system.
	If operation = posting:
	A CSV file containing the results of the journal posting is provided. The file contains these columns: Year, Period, Journal ID, Posting Status (Posted/Failed), Message, Error Code, Error Message. The Message, Error Code and Error Message columns are optional. Posting status of the journals is updated based on the status provided in the file. Only journals with a Posting status of "Post in Progress" will be updated.
	If operation = validation:
	A CSV file containing the results of the journal validation is provided. The file contains these columns: Year, Period, Journal ID, Validation Statu (Valid/Failed), Message, Error Code, Error Message. The Message, Error Code and Error Message columns are optional. Validation status of the journals is updated based on the status provided in the file. Only journals with a Validation status of "Validation In Progress" will be updated.

Table 21-4 Enterprise Journals Supported Job Types



Job Type	Description
deployEJTemplates	This job is used to deploy finalized journal templates to new journal periods to create journals for year-period combinations, ensuring a consistent and repeatable journal collection process.

Table 21-4 (Cont.) Enterprise Journals Supported Job Types

REST Resource

POST /HyperionPlanning/rest/ej/{api_version}/jobs

Required Roles

Јор Туре	Role	
exportEJJournals	Service Administrator	
setEJJournalStatus	Service Administrator	
deployEJTemplates	Service Administrator, Power User	

Request

Supported Media Types: application/json

Parameters

This table summarizes the request parameters that are generic to all jobs. The following tables describe parameters specific to individual rules.

Table 21-5 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None

Table 21-6exportEJJournalsParameters

Name	Description	Туре	Required	Default
јорТуре	Type of the Job. Value for this job is exportEJJournal s.	String	Yes	None
filename	The name of the zip file to which each individual journal file is added	String	Yes	None
year	The year for which the journal is used for data collection	String	No	None



Name	Description	Туре	Required	Default
period	The period for which the journal is used for data collection	String	No	None
operation	Specifies the operation - posting or validation	String	No	posting

Table 21-6 (Cont.) exportEJJournals Parameters

Table 21-7 setEJJournalStatus Parameters

Name	Description	Туре	Required	Default
јоbТуре	Type of the Job. Value for this job is setEJJournalStatus.	String	Yes	None
filename	 Filename is the file in CSV format that contains the following information regarding the posting process: Year: Year of the Journal posted Period: Period of the Journal posted JournalID: Journal Identifier of Journal posted Posting Status: Valid values are Posted or Failed. (if operation = posting) Validation Status: Valid values are Valid or Failed. (if operation = validation) Failed status has a message and attached error list returned from ERP Message: Optional. Can be used for error messages from ERP in case there is a posting failure Note: Multiple Journal Posting statuses may be included as records in the CSV file. 	String	Yes	None
operation	Specifies the operation. posting or validation	String	No	posting

Table 21-8 deployEJTemplates Parameters

Name	Description	Туре	Required	Default
јоbТуре	Type of the Job. Value for this job is EJ_DEPLOY_TEMPL ATES	String	Yes	None

Name	Description	Туре	Required	Default
year	The year used for the journal	String	Yes	None
period	The period for the journal	String	Yes	None
Template	Names of journal templates that need to be deployed.	JSON Array	No	None
	You can specify multiple parameters with the same key as "TEMPLATE" in the command, and it will be converted into JSON array and passed as a single parameter in JSON string. If you only specify one template name, it is still passed as JSON array. This parameter is optional. If no value is specified in the command for the TEMPLATE key, then this parameter would still be present as an empty JSON array in JSON string, and all templates for the			
	specified year and period will be deployed.			
ResetJournals	Value values: True or False. Optional. Indicates whether or not all journals need to be reset to the first stage after re- deployment.	Boolean	No	False
	This parameter is also derived by the system based on changes to the template. The system-derived value can override the user-specified value.			

Table 21-8	(Cont.)	deployEJ	Templates	Parameters
-------------------	---------	----------	-----------	------------

Examples of Request Body

Example for Job Type: exportEJJournals

```
Example 1:
```

```
{
  "jobType" : "exportEJJournals",
  "parameters": {
        "Filename":"export.zip",
        "Year":"2020"
        "Period":"Jan"
        "Operation":"validation"
        }
}
```

Example 2:

Example for Job Type: setEJJournalStatus

Examples for Job Type: deployEJTemplates

Example 1:

```
"Year":"2020"
"Period":"July"
```



Example 4:

```
{
  "jobType" : "EJ_DEPLOY_TEMPLATES",
  "parameters": {
          "Year":"2020"
          "Period":"July"
          "Template": []
        }
}
```

Response

Supported Media Types: application/json

Name	Description
jobId	Enterprise Journals job identifier
descriptiveStatus	Additional details about the status
details	Message to the user. In cases where there are errors, the error details are published.
status	-1: In Progress0: Success1: Failed
items	Not applicable for this job type
links	Detailed information about the link
rel	Valid value: self
href	Links to API call
action	The HTTP call type

Table 21-9 Parameters



Example of Response Body

The following is an example of the response body in JSON format.

```
{
  "jobId":14013,
  "details": "In Process",
  "status": -1,
  "links": [
      {
            "rel": "self",
            "href": "https://<BASE-URL>/HyperionPlanning/rest/ej/v1/jobs/14013",
            "action": "GET"
        }
    "error": null,
    "items": [ ],
    "type": EPM
}
```

Retrieve Enterprise Journals for Financial Consolidation and Close

Returns the list of journals ready to validate or ready to post based on the parameter sent.

This API works only for Financial Consolidation and Close.

REST Resource

GET /HyperionPlanning/rest/ej/{api version}/ejjournals

Required Roles

Service Administrator

Request URL with Optional Parameters

```
GET /HyperionPlanning/rest/ej/{api_version}/ejjournals?
Year=2018&Period=Jan&PostingStatus=ReadyToPost&ValidationStatus=ReadyToValidat
e
```

Supported Media Types: application/json

Parameters

The following table summarizes the client request.

"Year", "Period", "PostStatus" and "ValidationStatus" are optional. If "Year" and "Period" are not passed, journals from all year and period are listed.

By default, only ReadyToPost journals are listed, however you can provide any valid value for the PostingStatus parameter to get corresponding journals. If a valid value is provided for "ValidationStatus", journals are listed based on the provided value.



Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with: v1	Path	Yes	None
Year	Year for which to list journals, for example, Year=2018. If you do not specify a Year and Period, journals from all Years and Periods are listed.	Query	No	All Years
Period	Period for the journal, for example: Period=Jan. If you do not specify a Year and Period, journals from all Years and Periods are listed. If you specify only Year or only Period, journals from all Years and Periods are listed.	Query	No	All Periods
Postingstatus	Posting status for the journal, for example:	Query	No	ReadyToPost
	PostingStatus=ReadyToPost			
	Valid values are NotPosted, ReadyToPost, PostInProgress, Failed, Posted			
ValidationStatus	Validation status for the journal. Valid Values are NotValidated, ReadyToValidate, ValidationInProgress, Failed, Valid	Query	No	None

Table 21-10 Parameters

Response

Supported Media Types: application/json

Example of Response Body

The following shows an example of the response body.

```
{
 "items": [
   {
  "year": 2020
  "period": "Jan",
 "journalId": "100000001",
 "instanceId": "10000000008821",
  "link": {
     "rel": "content",
     ""https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/
rest/ej/v1/ejjournals/1000000008821",
      "action": "GET"
  }
  }
{
 "year": 2020
  "period": "Jan",
  "journalId": "10000002",
  "instanceId": "10000000008822",
```

```
"link": {
     "rel": "content",
     "https://<SERVICE NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/
rest/ej/v1/ejjournals/1000000008822",
      "action": "GET"
  }
  }
],
  "link": {
     "rel": "self",
      "https://<SERVICE_NAME>-
<TENANT NAME>.<SERVICE TYPE>.<dcx>.oraclecloud.com/HyperionPlanning/
rest/ej/v1/ejjournals",
      "action": "GET"
}
"error": null,{
"type": "EPM"
}
```

Retrieve Enterprise Journal Content for Financial Consolidation and Close

Returns journal content for the instance identifier provided as Path parameter. Each item in the items list represents a line item of the journal.

This API works only for Financial Consolidation and Close.

REST Resource

GET /HyperionPlanning/rest/ej/{api version}/ejjournals/{instanceId}

Required Roles

Service Administrator

Example of Request URL

GET /HyperionPlanning/rest/ej/v1/ejjournals/1000000008821

Supported Media Types: application/json

Table 21-11 Parameters

Name	Description	Туре	Required	Default	
api_version	Version of the API you are developing with	Path	Yes	None	
instanceId	Identifier for the journal for which you want to retrieve journal content	Path	Yes	None	



Example of Response Body

The following shows an example of the response body.

```
{
  "year": 2018
  "period": "Jan",
  "journalId": "100000001",
  "instanceId": "10000000008821",
  "items": [
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "100091",
      "Entered Debit Amount": "19800.00",
      "Entered Credit Amount": "0.00"
},
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "100092",
      "Entered Debit Amount": "0.00",
      "Entered Credit Amount": "19800.00"
},
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "100093",
      "Entered Debit Amount": "34900.00",
      "Entered Credit Amount": "0.00"
},
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "1000943",
      "Entered Debit Amount": "0.00",
      "Entered Credit Amount": "34900.00"
  }
],
  "links": [
{
      "rel": "self",
      "href": "https://<BASE-URL>/HyperionPlanning/rest/ej/v1/ejjournals/
```

```
1000000008821",
     "action": "GET"
},
{
      "rel": "update posting status",
      "href": "https://<BASE-URL>/HyperionPlanning/rest/ej/v1/ejjournals/
1000000008821
/poststatus",
      "action": "POST"
}
{
    "rel": "update_validation_status",
    "href": "https://<BASE-URL>/HyperionPlanning/rest/ej/v1/ejjournals/
1000000008821/validationstatus",
    "action": "POST"
}
],
"error": null,
"type": "EPM"
}
```

Retrieve Enterprise Journal Content by Year and Period for Financial Consolidation and Close

Returns Enterprise journal content for the provided Year, Period, and Journal ID. This API can be used if a user wants to query an Enterprise Journal without knowing the journal identifier.

This API works only for Financial Consolidation and Close.

REST Resource

```
GET /HyperionPlanning/rest/ej/{api_version}/ejjournalcontent?
Year={year}&Period={period}&JournalId={journalId}
```

Required Roles

Service Administrator

Example of Request URL

```
GET /HyperionPlanning/rest/ej/v1/ejjournalcontent?
Year=2018&Period=Jan&JournalId=100000001
```

Supported Media Types: application/json

Table 21-12 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None



Name	Description	Туре	Required	Default
Year	Year for which to list journal, for example, Year=2018	Query	Yes	None
Period	Period for the journal, for example: Period=Jan	Query	Yes	None
JournalId	Identifier for the journal for which you want to retrieve journal content	Query	Yes	None

Table 21-12 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body.

```
{
  "year": 2018
  "period": "Jan",
  "journalId": "100000001",
  "instanceId": "10000000008821",
  "items": [
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "100091",
      "Entered Debit Amount": "19800.00",
      "Entered Credit Amount": "0.00"
},
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "100092",
      "Entered Debit Amount": "0.00",
      "Entered Credit Amount": "19800.00"
},
{
      "Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "100093",
      "Entered Debit Amount": "34900.00",
      "Entered Credit Amount": "0.00"
},
```

{

```
"Status Code": "NEW",
      "Ledger ID": "LNR 12000",
      "Journal Source": "EPM EJ",
      "Journal Category": "Adjustment",
      "Currency Code": "EUR",
      "Segment 1": "1000943",
      "Entered Debit Amount": "0.00",
      "Entered Credit Amount": "34900.00"
  }
],
  "links": [
{
      "rel": "self",
      "https://<BASE-URL>/HyperionPlanning/rest/ej/v1/ejjournals/
1000000008821",
      "action": "GET"
},
{
      "rel": "update posting status",
      ""https://<BASE-URL>/HyperionPlanning/rest/ej/v1/ejjournals/
10000000008821
/poststatus",
      "action": "POST"
}
],
"error": null,
"type": "EPM"
}
```

Update Enterprise Journal Posting Status for Financial Consolidation and Close

Updates the Enterprise Journal Posting status. After journal content has been read and the import to ERP begins, this API must be invoked to update the status to PostInProgress, and after completion of posting, the status should be updated with either Posted or Failed. Error items are read-only if the Posting status is Failed.

This API works only for Financial Consolidation and Close.

REST Resource

```
POST /HyperionPlanning/rest/ej/{api_version}/ejjournals/{instanceId}/
poststatus
```

Required Roles

Service Administrator

Example of Request URL

POST /HyperionPlanning/rest/ej/v1/ejjournals/1000000008821/Posted

Supported Media Types: application/json



Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with: v1	Path	Yes	None
instanceId	The ID of the journal for which you want to update Posting status.	Path	Yes	None
year	Year value of journal period	String	No	None
period	Period of journal	String	No	None
journalId	Journal ID value	String	No	None
status	Journal Post Status	String	Yes	None
	Note: Only "PostInProgres s", "Failed" and "Posted" are supported for status value.			
message	Posting message to be set to the journal	String	No	None
journalBatch	Journal Batch represents the identifier from target ERP system for the current batch of posting.	String	No	None
errorItems	List of errors if any	Array	No	None
errorCode	Identifier for the individual error	String	No	None
errorMessage	Detailed message of the error	String	No	None
entryId	Journal entry identifier, for which error has occurred	String	No	None

Table 21-13 Parameters

Example of Post In Progress:

```
{
"year": "2019",
"period": "Jan",
"journalId": "1000000012",
"status": "PostInProgress"
}
```

Example of an Error:

```
{
    "year": "2019",
    "period": "Jan",
    "journalId": "100000001",
    "status": "Failed",
    "errorItems": [
    {
        "errorCode": "EF04",
        "
```



```
"errorMessage": "The account combination is invalid.",
     "entryId": "Journal Ent 1"
},
{
     "errorCode": "EU07",
     "errorMessage": "Accounting period is not open for the ledger.",
     "entryId": "Journal Ent 2"
]
}
```

Example When Posted:

```
"year": "2021",
"period": "Jan",
"journalId": "1000000003",
"status": "Posted",
"journalBatch": "111720201001-LNR11432"
}
```

Response

}

```
"detail": "Journal 2021 Jan 1000000001 is not in 'Post In Progress' or
'Ready to Post' status.",
"status": 400,
"message": "oracle.apps.epm.sdm.model.common.SDMModelException: Journal 2021
Jan 1000000001 is not in 'Post In Progress' or 'Ready to Post' status.",
"localizedMessage": "oracle.apps.epm.sdm.model.common.SDMModelException:
Journal 2021 Jan 10000000001 is not in 'Post In Progress' or 'Ready to Post'
status.",
"suppressed": []
```

Note:

The maximum character limit of the following fields are:

- journalBatch 255 characters
- errorMessage 255 characters
- errorCode 20 characters
- entryld 500 characters

Update Validation Status of Enterprise Journals for Financial **Consolidation and Close**

Updates the journal validation status. Once journal content has been read, you can invoke this API to update the status to "ValidationInProgress". After completion of validation, the status



must be updated as either "Valid" or "Failed". Error items are read only if validation status is "Failed".

REST Resource

```
POST /HyperionPlanning/rest/ej/{api_version}/ejjournals/{identifier}/
validationstatus
```

Required Roles

Service Administrator

Example of Request URL

```
POST https://<BASE-URL>/HyperionPlanning/rest/ej/v1/ejjournals/
10000000008821/validationstatus
```

Supported Media Types: application/json

Table 21-14 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, for example, v1	Path	Yes	None
instanceId	Identifier for the journal for which you want to update the validation status.	Path	Yes	None
status	Validation status to be updated for the journal	String	Yes	None
	Note: Only "ValidationInProgr ess", "Failed" and "Valid" are supported for status value.			
message	Validation message to be set to the journal	String	No	None
errorItems	List of errors if any	Array	No	None
	Note: Errors are updated only if status is "Failed".			
errorCode	Identifier for the individual error	String	No	None
errorMessage	Detailed message of the error	String	No	None
entryId	Journal entry identifier, for which error has occurred	String	No	None



Example of Validation in Progress:

```
{
   "status": "ValidationInProgress",
   "message":"Validation initiated"
}
```

Example of an Error:

```
{
   "status": "Failed",
    "message":"Validation failed"
    "errorItems": [
        {
            "errorCode": "EF04",
            "errorMessage": "The account combination is invalid.",
            "entryId": "Journal Ent 1"
        },
        {
            "errorCode ": "EU07",
            "errorMessage ": "Accounting period is not open for the ledger.",
            "entryId ": "Journal Ent 2"
        }
   ]
}
```

Example of Response Body:

22 Tax Reporting REST APIs

Use the Tax Reporting REST APIs to get the REST API version, to import supplementation data, copy data, clear data, and deploy form templates.

URL Structure for Tax Reporting

Use the following URL structure to access the Tax Reporting REST resources:

https://<BASE-URL>/HyperionPlanning/rest/{api version}/{path}

Where:

• <BASE-URL>: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- api_version: API version you are developing with. The current REST API version for Tax Reporting is v3.
- path: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ internal/" in the URL.

Getting API Versions for Tax Reporting APIs

You can get information on REST API versions using REST resources. See Getting API Versions for Planning. Tax Reporting APIs use the same version numbers as Planning.

Get Information about a Specific API Version for Tax Reporting

Returns details for a specific REST API version for Tax Reporting.

REST Resource

GET /HyperionPlanning/rest/{api_version}

Required Roles

Service Administrator, Power User, User, Viewer



Request

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 22-1 Parameters

Name	Description
api_version	Version of the API you are developing with, such as V1

Response

Supported Media Types: application/json

Parameters

The following table summarizes the parameters.

Table 22-2 Parameters

Name	Description
version	The version, such as V3

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
"version": "v1",
"lifecycle": "active",
"isLatest": true,
"links": [{
"rel": "canonical",
"href": "https://https://<BASE-URL>/HyperionPlanning/rest/v2"
}, {
"rel": "predecessor-version",
"href": "https://<SERVICE_NAME>-
<TENANT_NAME>.<SERVICE_TYPE>.<dcX>.oraclecloud.com/HyperionPlanning/rest/v1"
}]
}
```

Copy Data

This REST API is used to execute a Copy Data job using the job name. Before executing this job, you should create a Copy Data job in Tax Reporting.

For details on this task, see "Using Copy Data Job" in Administering Tax Reporting

This REST API returns the job ID after starting the Copy Data job.

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json

Table 22-3 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application	The name of the application Get the application name by using the Get Applications API, for example, FCCS or TRCS. See Get Applications.	Path	Yes	None
jobName	Name of the job should be: Execute Profile	Payload	Yes	None
jobType	Type of Job. Supported value: COPY_DATA	Payload	Yes	None
ProfileName	Name of the saved copy data job	Payload	Yes	None

Example of Request Body

```
{
"jobType": "COPY_DATA",
"jobName": "Execute Profile",
"parameters": {
    "ProfileName": "CopyJobTesting"
  }
}
```

Response Body

Supported Media Types: application/json

Name	Description
type	Tax Reporting Application type, for example, TRCS
status	Status of the job: -1 =In progress; 0 = Success; 1 = Fail
details	In case of errors, details are published with the error string.
descriptiveStatus	The status of the job, such as Completed or Error
items	Collection of Notification categories
links	Detailed information about the link

Table 22-4 Parameters



Table 22-4 (Cont.) Parameters

Name	Description
href	Links to API call
action	The HTTP call type
rel	Relationship type. Possible values: self

Example of Response Body:

The following shows an example of the response body in JSON format.

```
{
    "jobId": 45,
    "jobName": "Copy Data",
    "descriptiveStatus": "Processing",
    "details": null,
    "status": -1,
    "links": [
        {
            "href": "https://ttps://<BASE-URL>/HyperionPlanning/rest/v3/
applications/<applicationName>/jobs/<JobId>",
            "rel": "self",
            "action": "GET"
        },
        {
            "href": "https://https://<BASE-URL>/HyperionPlanning/rest/v3/
applications/<applicationName>/jobs/<JobId>/details",
            "rel": "job-details",
            "action": "GET"
        }
    ]
}
```

Clear Data

This REST API is used to execute a Clear Data job using the profile name. Before executing this job, you should create a Clear Data job in Tax Reporting.

For details on this task, see "Using Clear Data Jobs" in Administering Tax Reporting

This REST API returns the job ID after starting the job.

REST Resource

POST /HyperionPlanning/rest/{api_version}/applications/{application}/jobs

Required Roles

Service Administrator

Request

Supported Media Types: application/json



Parameters

The following table summarizes the client request parameters specific to this job.

Table 22-5	Clear Data
------------	------------

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with: v3	Path	Yes	None
application	The name of the application Get the application name by using the Get Applications API, for example, FCCS or TRCS. See Get Applications.	Path	Yes	None
jobName	Name of the job should be: Execute Profile	Payload	Yes	None
јоbТуре	Type of Job. Supported value: CLEAR_DATA	Payload	Yes	None
ProfileName	Name of the saved clear data job	Payload	Yes	None

Example of Request Body

Response Body

Supported Media Types: application/json

Table 22-6 Parameters

Name	Description
type	Tax Reporting Application type, for example, TRCS
status	Status of the job: -1 =In progress; 0 = Success; 1 = Fail
details	In case of errors, details are published with the error string.
descriptiveStatus	The status of the job, such as Completed or Error
items	Collection of Notification categories
links	Detailed information about the link



Name	Description
href	Links to API call
action	The HTTP call type
rel	Relationship type. Possible values: self

Table 22-6 (Cont.) Parameters

Example of Response Body

The following is an example of the response body in JSON format.

```
{
 "jobId": 46,
  "jobName": "Clear Data",
   "descriptiveStatus": "Processing",
   "details": null,
   "status": -1,
    "links": [
        {
            "href": "https://ttps://<BASE-URL>/HyperionPlanning/rest/v3/
applications/<applicationName>/jobs/<JobId>",
            "rel": "self",
            "action": "GET"
        },
        {
            "href":"https://ttps://<BASE-URL>/HyperionPlanning/rest/v3/
applications/<applicationName>/jobs/<JobId>/details",
            "rel": "job-details",
            "action": "GET"
        }
   ]
}
```

Enterprise Profitability and Cost Management REST APIs

Related Topics

- URL Structure for Enterprise Profitability and Cost Management
- Getting API Versions for Enterprise Profitability and Cost Management
- Getting Information About a Specific REST API Version for Enterprise Profitability and Cost Management

Table 23-1 REST APIs

Task	Request	REST Resource
Calculate Model	POST	/HyperionPlanning/rest/v3/applications/{AppName}/jobs/
Clear Data By Point of View	POST	/HyperionPlanning/rest/v3/applications/{AppName}/jobs/
Copy Data by Point of View	POST	/HyperionPlanning/rest/v3/applications/{AppName}/jobs/
Delete Point of View	POST	/HyperionPlanning/rest/v3/applications/{AppName}/jobs/
Generate Model Documentation Report	POST	/HyperionPlanning/rest/v3/applications/{AppName}/jobs/
Validate Model	POST	/HyperionPlanning/rest/v3/applications/{AppName}/jobs/

URL Structure for Enterprise Profitability and Cost Management

Use the following URL structure to access the Enterprise Profitability and Cost Management REST resources:

https://<BASE-URL>/HyperionPlanning/rest/{api version}/{path}

Where:

• *<BASE-URL>*: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- {api_version}: API version you are developing with. The current REST API version for Enterprise Profitability and Cost Management is v3.
- {path}: Identifies the resource.



Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ internal/" in the URL.

Getting API Versions for Enterprise Profitability and Cost Management

You can get information on REST API versions using REST resources.

Important: The version number is case-sensitive. For example, if the version number is listed as v3 with a lowercase v, you cannot enter the version number with a capital V as in this incorrect example, V3, which would result in an error. Instead, you must enter the version number with a lowercase v as in this correct example: v3.

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using REST APIs requires prerequisites. See Prerequisites.

There are two sets of REST APIs relevant for Enterprise Profitability and Cost Management.

- Planning REST APIs (See Getting API Versions for Planning).
- Enterprise Profitability and Cost Management-specific REST APIs. (See Getting Information About a Specific REST API Version for Enterprise Profitability and Cost Management).

Getting Information About a Specific REST API Version for Enterprise Profitability and Cost Management

Returns information about a specific REST API version for Enterprise Profitability and Cost Management.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

GET /HyperionPlanning/rest/{api_version}

Request

Supported Media Types: application/json

Parameters

The following table summarizes the client request.



Table 23-2 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are working with, such as V3	Path	Yes	None

Response Body

Supported Media Types: application/json

The following table summarizes the response parameters.

Table 23-3 Parameters

Attribute	Description
version	v3
lifecycle	Lifecycle of the resource, active or deprecated
isLatest	Whether this resource is the latest, true or false

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "version": "v3",
    "lifecycle": "active",
   "isLatest": true,
    "links": [{
        "rel": "canonical",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v3"
    }, {
        "rel": "predecessor-version",
        "href": "https://<BASE-URL>/HyperionPlanning/rest/v2"
    }]
```

Calculate Model

1

Runs the calculation on a given point of view in a selected cube. This API supports batch calculation with multiple POVs.

This is an asynchronous call, so use the job status URI to determine whether the operation is complete.

This API is version v3.

Required Roles

Service Administrators



REST Resource

POST /HyperionPlanning/rest/v3/applications/{AppName}/jobs/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request parameters specific to this job.

Table 23-4 Parameters

Name	Description	Туре	Required	Default
jobType	Calculation	Payload	Yes	None
jobName	Name of the job Example: "Calculation"	Payload	Yes	None
povDelimiter	<pre>Delimiter used in POV values. The default delimiter is _ (under score). The delimiter must be enclosed in double quotation marks. Only these delimiters are supported: _ (under score) # (hash) & (ampersand) ~ (tilde) % (percentage) ; (semicolon) : (colon) . (dash) Example: "povDelimiter":":" Note: When submitting multiple POVs for calculation, do not use a comma as the delimiter to separate POV members. Comma is reserved for separating POV groups as shown in this example: FY21: Jan:Actual:Working, FY21:Feb:Actual:Working ,FY21:Mar:Actual:Working</pre>	Payload	Yes	:: (Double Colon)
povName	Name of the POV to calculate. You can pass one or more POVs separated by a comma (,). Example: "sourcePOVName":"FY16:May:Actual:Working"	Payload	Yes	None
modelName	Name of the model to calculate Example: "modelName":"10 Actuals Allocation Process"	Payload	Yes	None



Table 23-4	(Cont.) Parameters
------------	--------------------

Name	Description	Туре	Required	Default
executionType	 (ALL_RULES RULESET_SUBSET SINGLE_RULE RUN_FROM_RULE STOP_AFTER_RULE) Identifies the rule execution type If executionType=ALL_RULES, rule related parameters are not required. If executionType=SINGLE_RULE RUN_FROM_RULE STOP AFTER RULE, then provide ruleName only. 	Payload	Yes	None
	 If executionType=RULESET_SUBSET, then provide values for rulesetSeqNumStart and rulesetSeqNumEnd. 			
	Example : "executionType":"ALL_RULES"			
ruleName	Name of the single rule to run Example: "ruleName": "Utlities Expense Adjustment"	Payload	No	None
rulesetSeqNumStart	Sequence number of the first rule in the rule set to run Example : "rulesetSeqNumStart:1"	Payload	No	None
rulesetSeqNumEnd	Sequence number of the last rule in the rule set to run Example : "rulesetSeqNumStart:10"	Payload	No	None
clearCalculatedDat a	(True False) Specifies whether to clear existing calculations	Payload	No	False
	<pre>Example: "clearCalculatedData":"true",</pre>			
executeCalculation s	(True False) Specifies whether to run calculations Example: "executeCalculations":"true"	Payload	No	False
optimizeForReporti ng	(True False) Specifies whether to optimize the calculation process for reporting When running multiple concurrent calculation jobs, set	Payload	No	False
	optimizeReporting=true for all jobs. Only the last job to complete will perform the aggregation, which avoids redundant processing and prevents running jobs from slowing down.			
	Set optimizeReporting=false only when necessary to save processing time; for example, when running a single rule or a sequential series of several POVs.			
	<pre>Example: "optimizeForReporting":"false",</pre>			
captureDebugScript s	(True False) Specifies whether to generate debug scripts	Payload	No	False
	Example : "captureDebugScripts":"false"			
comment	Comment to describe the job	Payload	No	None

Sample Payload

{

```
"jobType":"Calculation",
"jobName":"Calculation",
"parameters":{
"povDelimiter":":",
```

```
"povName":"FY21:Jan:Actual:Working",,
"modelName":"10 Actuals Allocation Process",
"executionType":"ALL_RULES",
"rulesetSeqNumStart":"1",
"rulesetSeqNumEnd":"1",
"clearCalculatedData":"true",
"executeCalculations":"true",
"optimizeForReporting":"true",
"captureDebugScripts":"false"
}
```

Response

}

Supported Media Types: application/json

Table 23-5 Parameters

Name	Description
jobId	ID of the job that is created
jobName	Name of the job
details	In case of errors, details are published with the error string
status	See Migration Status Codes.
links	Detailed information about the link
href	Links to the API call
action	HTTP call type
rel	Can be self and/or Job-details. If set to Job Status, you can use the <code>href</code>
	to get the status of the job.
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "jobId": 26,
    "jobName": "Calculation",
    "status": -1,
    "descriptiveStatus": "Processing",
    "details": null,
    "links": [
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26",
            "action": "GET",
            "rel": "self",
        },
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26/details",
",
```



```
"action": "GET",
"rel": "job-details "
}
]
}
```

Example 2: Job Status with No Errors

```
{
    "jobId": 26,
    "jobName": "Calculation",
    "status": 0,
    "descriptiveStatus": "Success",
    "details": null
    "links": [
        {
            "rel": "self"
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26",
            "action": "GET",
        },
 {
            "rel": "job-details"
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26/details",
            "action": "GET",
        }
    ]
}
```

Clear Data By Point of View

Clears the data for a given point of view in a selected cube.

This is an asynchronous call, so use the job status URI to determine whether the operation is complete.

This API is version v3.

Required Roles

Service Administrators

REST Resource

POST /HyperionPlanning/rest/v3/applications/{AppName}/jobs/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.



Request

Supported Media Types: application/json

The following table summarizes the client request parameters specific to this job.

Table 23-6 Parameters

Name	Description	Туре	Required	Default
јоbТуре	Clear POV	Payload	Yes	None
jobName	Name of the job Example: "Clear POV"	Payload	Yes	None
povDelimiter	<pre>Delimiter used in POV values. The delimiter must be enclosed in double quotation marks. Other than a comma, only these delimiters are supported: • _ (under score) • # (hash) • & (ampersand) • ~ (tilde) • % (percentage) • ; (semicolon) • : (colon) • . (dash) Example: "povDelimiter":":" Note: When submitting multiple POVs for calculation, do not use a comma as the delimiter to separate POV members. Comma is reserved for separating POV groups as shown in this example: FY21: Jan:Actual:Working, FY21: Feb:Actual:Working , FY21: Mar:Actual:Working</pre>	Payload	Yes	:: (Double Colon)
povName	Name of the POV to clear Example: "povName": "to FY21: Jan: Actual: Working"	Payload	Yes	None
cubeName	Name of the cube on which clear operation is to be executed Example: "cubeName": "PCM_CLC"	Payload	Yes	PCM_CLC
clearInput	(True False) Specifies whether to clear input data Example: "clearInput":"true"	Payload	Yes	None
clearAllocatedValu es	(True False) Specifies whether to clear allocated data Example: "clearAllocatedValues":"true"	Payload	Yes	None
clearAdjustmentVal ues	(True False) Specifies whether to clear adjustment data Example : "clearAdjustmentValues":"true"	Payload	Yes	None

Sample Payload

{

```
"jobType":"Clear POV",
"jobName":"Clear POV",
"parameters":{
    "povDelimiter":":",
    "povName":"FY21:Jan:Actual:Working",
```

```
"cubeName":"PCM_CLC",
   "clearInput":"true",
   "clearAllocatedValues":"true",
   "clearAdjustmentValues":"true"
}
```

Response

}

Supported Media Types: application/json

Table 23-7 Parameters

Name	Description
jobId	ID of the job that is created
jobName	Name of the job
details	In case of errors, details are published with the error string
status	See Migration Status Codes.
links	Detailed information about the link
href	Links to the API call
action	HTTP call type
rel	Can be self and/or Job-details. If set to Job Status, you can use the href
	to get the status of the job.
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "jobId": 26,
    "jobName": "Clear POV",
    "status": -1,
    "descriptiveStatus": "Processing",
    "details": null,
    "links": [
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26",
            "action": "GET",
            "rel": "self",
        },
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26/details",
",
            "action": "GET",
            "rel": "job-details "
        }
```



```
]
}
Example 2: Job Status with No Errors
{
    "jobId": 26,
    "jobName": " Copy POV",
    "status": 0,
    "descriptiveStatus": "Success",
    "details": null
    "links": [
        {
            "rel": "self"
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26",
            "action": "GET",
        },
 {
            "rel": "job-details"
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26/details",
            "action": "GET",
        }
```

Copy Data by Point of View

Copies data from a source to a destination point of view in a selected cube.

This is an asynchronous call, so use the job status URI to determine whether the operation is complete.

This API is version v3.

Required Roles

Service Administrators

REST Resource

POST /HyperionPlanning/rest/v3/applications/{AppName}/jobs/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request parameters specific to this job.

Name	Description	Туре	Required	Default
јорТуре	Copy POV	Payload	Yes	None
jobName	Name of the job	Payload	Yes	None
	Example: "Copy POV"			
povDelimiter	<pre>Delimiter used in POV values. The delimiter must be enclosed in double quotation marks. Other than a comma, only these delimiters are supported: _ (under score) # (hash) & (ampersand) ~ (tilde) % (percentage) ; (semicolon) : (colon) - (dash) Example: "povDelimiter":":" Note: When submitting multiple POVs for calculation, do not use a comma as the delimiter to separate POV members. Comma is reserved for separating POV groups as shown in this example: FY21: Jan: Actual: Working, FY21: Feb: Actual: Working , FY21: Mar: Actual: Working</pre>		Yes	:: (Double Colon)
sourcePOVName	Name of the source POV	Payload	Yes	None
Sourcerovname	Example: "sourcePOVName":"FY21:Jan:Actual:Working "	Payloau	165	None
destPOVName	Name of the destination POV Example: "destinationPOVName":"FY21:Feb:Actual:Working"	Payload	Yes	None
соруТуре	(ALL_DATA INPUT) specifies the data to copy from the source Example: "copyType": "ALL_DATA"	Payload	Yes	None
sourceCubeName	Name of the source Oracle Essbase cube Example: "sourceCubeName":"PCM_CLC"	Payload	Yes	None
destCubeName	Name of the destination Essbase cube Example: "destCubeName":"PCM_CLC"	Payload	Yes	None

Table 23-8 Parameters

Sample Payload

{

```
"jobType":"Copy POV",
"jobName":"Copy POV",
"parameters":{
    "povDelimiter":":",
    "sourcePOVName":"FY21:Jan:Actual:Working",
    "destPOVName":"FY21:Feb:Actual:Working",
    "sourceCubeName":"PCM_CLC",
    "destCubeName":"PCM_CLC",
    "createDestPOV":"true",
```

```
"copyType":"ALL_DATA"
}
```

Response

}

Supported Media Types: application/json

Table 23-9 Parameters

Name	Description
jobId	ID of the job that is created
jobName	Name of the job
details	In case of errors, details are published with the error string
status	See Migration Status Codes.
links	Detailed information about the link
href	Links to the API call
action	HTTP call type
rel	Can be self and/or Job-details. If set to Job Status, you can use the href
	to get the status of the job.
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "jobId": 26,
    "jobName": "Copy POV",
    "status": -1,
    "descriptiveStatus": "Processing",
    "details": null,
    "links": [
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26",
            "action": "GET",
            "rel": "self",
        },
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26/details",
",
            "action": "GET",
            "rel": "job-details "
        }
    1
}
```



Example 2: Job Status with No Errors

```
{
    "jobId": 26,
    "jobName": " Copy POV",
    "status": 0,
    "descriptiveStatus": "Success",
    "details": null
    "links": [
        {
            "rel": "self"
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26",
            "action": "GET",
        },
 {
            "rel": "job-details"
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26/details",
            "action": "GET",
        }
```

Delete Point of View

Deletes the data associated with a point of view from the calculation cube.

This is an asynchronous call, so use the job status URI to determine whether the operation is complete.

This API is version v3.

Required Roles

Service Administrators

REST Resource

POST /HyperionPlanning/rest/v3/applications/{AppName}/jobs/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request parameters specific to this job.

Name	Description	Туре	Required	Default
јорТуре	Delete POV	Payload	Yes	None
jobName	Name of the job Example: "Delete POV"	Payload	Yes	None
povDelimiter	<pre>Delimiter used in POV values. The delimiter must be enclosed in double quotation marks. Other than a comma, only these delimiters are supported: _ (under score) # (hash) & (ampersand) ~ (tilde) % (percentage) ; (semicolon) : (colon) - (dash) Example: "povDelimiter":":"</pre>	Payload	Yes	:: (Double Colon)
	Note: When submitting multiple POVs for calculation, do not use a comma as the delimiter to separate POV members. Comma is reserved for separating POV groups as shown in this example:			
	FY21:Jan:Actual:Working,FY21:Feb:Actual:Working ,FY21:Mar:Actual:Working			
povName	Name of the POV to delete Example: "povName":"FY21:Jan:Actual:Working"	Payload	Yes	None

Table 23-10 Parameters

Sample Payload

```
{
  "jobType":"Delete POV",
  "jobName":"Delete POV",
  "parameters":{
        "povDelimiter":":",
        "povName":"FY21:Jan:Actual:Working"
   }
}
```

Response

Supported Media Types: application/json

Table 23-11 Parameters

Name	Description
jobId	ID of the job that is created
jobName	Name of the job
details	In case of errors, details are published with the error string
status	See Migration Status Codes.



Name	Description
links	Detailed information about the link
href	Links to the API call
action	HTTP call type
rel	Can be self and/or Job-details. If set to Job Status, you can use the href to get the status of the job.
data	Parameters as key value pairs passed in the request

Table 23-11 (Cont.) Parameters

Example of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "jobId": 26,
    "jobName": "Delete POV",
    "status": -1,
    "descriptiveStatus": "Processing",
    "details": null,
    "links": [
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26",
            "action": "GET",
            "rel": "self",
        },
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26/details",
",
            "action": "GET",
            "rel": "job-details "
        }
    ]
}
```

Example 2: Job Status with No Errors

```
},
{
    "rel": "job-details"
    "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
jobs/26/details",
    "action": "GET",
    }
]
}
```

Generate Model Documentation Report

Generates an Enterprise Profitability and Cost Management Model Documentation report.

This is an asynchronous call, so use the job status URI to determine whether the operation is complete.

Any validation failures are written to file with file name provided in the parameters, and can be accessed from Inbox/Outbox Explorer.

This API is version v3.

Required Roles

Service Administrators

REST Resource

POST /HyperionPlanning/rest/v3/applications/{AppName}/jobs/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request parameters specific to this job.

Table 23-12 Parameters

Name	Description	Туре	Required	Default
јоbТуре	Generate EPCM Report	Payload	Yes	None
jobName	User-specified name for this job execution	Payload	Yes	None
	Example: "Model Documentation Report for 10			
	Actuals Allocation Process"			
reportName	"MODEL_DOC"	Payload	Yes	None



Name	Description	Туре	Required	Default
outputFileName	Name of the output file to which the report will be generated	Payload	Yes	None
	Example: "My_Model_Doc_Report_Output"			
outputType	(PDF Word Excel HTML XML) Format in which the output will be generated	Payload	Yes	None
	Example: "PDF"			
modelName	Name of model for which the report is generated Example: "10 Actuals Allocation Process"	Payload	Yes	None

Table 23-12 (Cont.) Parameters

Sample Payload

```
{
  "jobType":"Generate EPCM Report",
  "jobName":"Model Documentation Report for 10 Actuals Allocation Process",
  "parameters":{
        "reportName":"MODEL_DOC",
        "outputFileName":"My_Model_Doc_Report_Output",
        "outputType":"PDF",
        "modelName":"10 Actuals Allocation Process"
   }
}
```

Response

Supported Media Types: application/json

Table 23-13 Parameters

Name	Description
jobId	ID of the job that is created
jobName	Name of the job
details	In case of errors, details are published with the error string
status	See Migration Status Codes.
links	Detailed information about the link
href	Links to the API call
action	HTTP call type
rel	Can be self and/or <code>Job-details</code> . If set to <code>Job Status</code> , you can use the <code>href</code>
	to get the status of the job.
data	Parameters as key value pairs passed in the request

Example of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "jobId": 26,
    "jobName": "Generate Report",
    "status": -1,
    "descriptiveStatus": "Processing",
    "details": null,
    "links": [
         {
            "rel": "self",
            "href":http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/6,
            "action": "GET"
         },
         {
            "rel": "job-details",
            "href":http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/6/details,
            "action": "GET"
        }
    ]
}
```

Example 2: Job Status with No Errors

```
{
    "jobId": 26,
    "jobName": "Generate Report",
    "status": 0,
    "descriptiveStatus": "Success",
    "details": null
    "links": [
        {
            "rel": "self",
            "href":http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/6,
            "action": "GET"
        },
        {
            "rel": "job-details",
            "href":http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/6/details,
            "action": "GET"
        }
    ],
}
```

Validate Model

Automates the calculation process for validating a model.

This is an asynchronous call, so use the job status URI to determine whether the operation is complete.

Any validation failures are written to file with file name provided in the parameters, and can be accessed from Inbox/Outbox Explorer.

This API is version v3.

Required Roles

Service Administrators

REST Resource

POST /HyperionPlanning/rest/v3/applications/{AppName}/jobs/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request parameters specific to this job.

Table 23-14 Parameters

Name	Description	Туре	Required	Default
јорТуре	Validate Model	Payload	Yes	None
jobName	Name of the job Example: "Validate Model"	Payload	Yes	None
modelName	Name of the model to validate Example: "modelName":"10 Actuals Allocation Process"	Payload	Yes	None
fileName	Name of the output file to which all the validations (if any) will be written Example : "fileName":"results.txt"	Payload	Yes	None

Sample Payload

```
{
  "jobType":"Validate Model",
  "jobName":"Validate Model",
  "parameters":{
      "modelName":"10 Actuals Allocation Process",
      "fileName":"results.txt"
  }
}
```

Response

Supported Media Types: application/json



Name	Description
jobId	ID of the job that is created
jobName	Name of the job
details	In case of errors, details are published with the error string
status	See Migration Status Codes.
links	Detailed information about the link
href	Links to the API call
action	HTTP call type
rel	Can be self and/or Job-details. If set to Job Status, you can use the href to get the status of the job.
data	Parameters as key value pairs passed in the request

Examples of Response Body

The following examples show the contents of the response body in JSON format:

Example 1: Job is in Progress

```
{
    "jobId": 26,
    "jobName": "Validate Model",
    "status": -1,
    "descriptiveStatus": "Processing",
    "details": null,
    "links": [
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26",
            "action": "GET",
            "rel": "self",
        },
        {
            "href": "http://<BASE-URL>/HyperionPlanning/rest/v3/applications/
BksML40/jobs/26/details",
",
            "action": "GET",
            "rel": "job-details "
        }
    ]
}
```

Example 2: Job Status with No Errors

```
{
    "jobId": 26,
    "jobName": "validate Model",
    "status": 0,
    "descriptiveStatus": "Success",
    "details": null
```



Profitability and Cost Management REST APIs

Related Topics

- URL Structure for Profitability and Cost Management
- Get API Versions for Profitability and Cost Management REST APIs
- Get Information about a Specific API Version for Profitability and Cost Management

Table 24-1 REST APIs

Task	Request	REST Resource
Apply Data Grants	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ applyDataGrants</pre>
Copy ML POV Data	POST	<pre>/epm/rest/{api_version}/applications/{application}/povs/ {srcPOVMemberGroup}/jobs/copyPOVJob/{destPOVMemberGroup}</pre>
Create File-Based Application	POST	<pre>/epm/rest/{api_version}/fileApplications/{application}</pre>
Deploy ML Cube	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ ledgerDeployCubeJob</pre>
Enable File-Based Application	POST	<pre>/epm/rest/{api_version}/fileApplications/{application}/ enableApplication</pre>
Essbase Data Load for Profitability and Cost Management	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ essbaseDataLoadJob</pre>
Export Query Results	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ exportQueryResultsJob</pre>
Export Template for Profitability and Cost Management	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ templateExportJob?fileName={fileName}</pre>
Generate Program Documentation Report	GET	<pre>epm/rest/{api_version}/applications/{application}/povs/ {POV}/programDocumentationReport</pre>
Generate Program Documentation Report - Run as a Job	POST	<pre>/epm/rest/{api_version}/applications/<applicationname>/ povs/<povname>/jobs/programDocReportJob</povname></applicationname></pre>
Import Template for Profitability and Cost Management	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ templateImportJob</pre>
Merge Slices for Profitability and Cost Management	POST	<pre>/epm/rest/{api_version}/applications/{application}/jobs/ mergeSlices</pre>
Optimize ASO Cube	POST	<pre>/epm/rest/v1/applications/{AppName}/jobs/optimizeASOCube</pre>



Task	Request	REST Resource
Retrieve Task Status for Profitability and Cost Management	GET	<pre>/epm/rest/{api_version}/applications/jobs/ ChecktaskStatusJob/{processName}</pre>
Run ML Calculations	POST	<pre>/epm/rest/{api_version}/applications/{application}/povs/ {povGroupMember}/jobs/runLedgerCalculationJob</pre>
Run ML Clear POV	POST	<pre>/epm/rest/{api_version}/applications/{application}/povs/ {povGroupMember}/jobs/clearPOVJob</pre>
Run ML Rule Balancing	GET	<pre>/epm/rest/{api_version}/applications/{application}/povs/ {povGroupMember}/ruleBalance</pre>
Update Dimensions As a Job	POST	<pre>/epm/rest/{api_version}/fileApplications/{application}/ jobs/updateDimension</pre>

Table 24-1 (Cont.) REST APIs

URL Structure for Profitability and Cost Management

Use the following URL structure to access the Profitability and Cost Management REST resources:

https://<BASE-URL>/epm/rest/{api version}/{path}

Where:

• <BASE-URL>: The first part of your service URL, before the context.

For example, if your service URL is https://epm-acme.epm.usphoenix-1.ocs.oraclecloud.com/epmcloud, your <BASE-URL> is https://epmacme.epm.us-phoenix-1.ocs.oraclecloud.com. Similarly, if your service URL is https://
epm2-acme.epm.us6.oraclecloud.com/epmcloud, your <BASE-URL> is https://epm2acme.epm.us6.oraclecloud.com.

- {api_version}: API version you are developing with. The current REST API version for Profitability and Cost Management is V1.
- {*path*}: Identifies the resource.

Note:

Oracle does not authorize or support the use of REST APIs with the path token "/ <code>internal/"</code> in the URL.

Get API Versions for Profitability and Cost Management REST APIs

Returns information about which versions are available and supported. Multiple versions might be supported simultaneously.



Note:

An API version is always supported even when deprecated.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

GET /epm/rest/

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Response

Supported Media Types: application/json

Table 24-2 Par	rameters
----------------	----------

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
items	Version of the API you are developing with
version	The version, such as v1
lifecycle	Possible values: active, deprecated
isLatest	Whether this resource is the latest, true or false

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "items": [{
        "isLatest": false,
        "lifecycle": "deprecated",
        "version": "11.1.2.4.000",
        "links": [{
            "href": "https://<BASE-URL>>/epm/rest/11.1.2.4.000",
            "rel": "canonical"
        }, {
            "href": "https://<BASE-URL>>/epm/rest/v1",
            "rel": "successor-version"
        }]
    }, {
        "isLatest": true,
    }
}
```

```
"lifecycle": "active",
    "version": "v1",
    "links": [{
        "href": "https://<BASE-URL>>/epm/rest/v1",
        "rel": "canonical"
    }, {
        "href": "https://<BASE-URL>>/epm/rest/11.1.2.4.000",
        "rel": "predecessor-version"
    }]
}],
"links": [{
    "href": "https://<BASE-URL>>/epm/rest/11.1.2.4.000",
    "rel": "canonical"
}, {
    "href": "https://<BASE-URL>>/epm/rest/v1",
    "rel": "current"
}]
```

Java Sample - GetRestAPIVersionsInfo.java for Profitability and Cost Management

Prerequisites: json.jar

}

Prerequisites: See Profitability and Cost Management Common Helper Functions for Java

```
public void getRestAPIVersionsInfo() throws Exception {
    String urlString = String.format("%s/epm/rest", serverUrl);
    String response = executeRequest(urlString, "GET", null, "application/
json");
    System.out.println("Response String : " + response);
    JSONObject jsonObj = new JSONObject(response);
    JSONArray itemsArray = jsonObj.getJSONArray("items");
    System.out.println("Details : " + itemsArray.toString());
}
```

cURL Sample - GetRestAPIVersionInfo.sh for Profitability and Cost Management

Common functions: See Profitability and Cost Management Common Helper Functions for cURL

```
funcGetRestAPIVersionInfo()
{
    url=$SERVER URL/epm/rest/$API VERSION
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    status=$?
    echo "status code :$status"
    output='cat response.txt'
    if [ $status == 200 ]; then
        echo "Version $API VERSION details :"
        count='echo $output | jq '.links | length''
        i = 0
        while [ $i -lt $count ]; do
            echo "Service : " 'echo $output | jq '.links['$i'].rel''
            echo "URL :" 'echo $output | jq '.links['$i'].href''
            echo "Action :" 'echo $output | jq '.links['$i'].action''
            echo ""
```

```
i='expr $i + 1'
    done
else
    error='echo $output'
    echo "Error occurred. " $error
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample - GetRestAPIVersionsInfo.groovy for Profitability and Cost Management

```
Prerequisites: json.jar
```

Common functions: See Appendix C: Common Helper Functions for Groovy.

```
def getRestAPIVersionsInfo() {
                 def url;
                 def response;
    try {
                           url = new URL(serverUrl + "/epm/rest");
    } catch (MalformedURLException e) {
             println "Malformed URL. Please pass valid URL"
             System.exit(0);
    }
    response = executeRequest(url, "GET", null, "application/json");
    def object = new JsonSlurper().parseText(response)
                 if(object != null) {
                      def items = object.items
                      println "Rest API Versions Info : " + items
    } else {
                      println "Error occurred while fetching rest api
versions details"
    }
}
```

Get Information about a Specific API Version for Profitability and Cost Management

Returns details for a specific REST API version for Profitability and Cost Management.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

GET /epm/rest/



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the request parameters.

Table 24-3 Parameters

Name	Description	Туре	Require d	Default
api_version	Version of the API you are developing with, such as V1	Path	Yes	None

Response

Supported Media Types: application/json

Table 24-4 Parameters

Name	Description
version	The version, such as v1
lifecycle	Possible values: active, deprecated
isLatest	Whether this resource is the latest, true or false

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
   "items": [{
      "version": "v1",
      "lifecycle": "active",
      "isLatest": true,
      "links": [{
        "rel": "canonical",
        "href": "https://<BASE-URL>>/epm/rest/v1",
      }, {
         "rel": "predecessor-version",
         "href": "https://<BASE-URL>/epm/rest/v1",
     }]
   }],
   "links": [{
     "rel": "current",
      "href": "https://<BASE-URL>/epm/rest/v1"
   }]
}
```



Apply Data Grants

Applies data grants for a given Profitability and Cost Management application.

This API submits a job to remove all existing data grants in Oracle Essbase and recreate them with the latest information from the application. It can also be used to repair data grants if there are any issues.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/jobs/applyDataGrants

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-5 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, such as $\mathtt{v1}$	Path	Yes	None
application	Name of the application to create	Path	Yes	None

Example URL

https://<BASE-URL>/epm/rest/v1/applications/BksML30/jobs/applyDataGrants

Response

Supported Media Types: application/json

Table 24-6 Parameters

Name	Description
details	Task ID, such as BksML12_BksML12_LoadData_D20160118T051020_ba8_1
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability



Name	Description
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-6 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_ApplyDataGrants_D20220511T114653_b85",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_ApplyDataGrants_D20220511T114653_b85",
            "action":"GET",
            "rel":"Job Status"
        }
    ]
}
```

Java Sample - applyDataGrants.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void applyDataGrants() throws Exception {
    String urlString = "%s/epm/rest/%s/applications/%s/jobs/
applyDataGrants";
    executeJob(urlString, "POST", null);
}
```

cURL Sample - ApplyDataGrants.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcApplyDataGrants() {
```

```
url=$SERVER_URL/epm/rest/$API_VERSION/applications/$APP_NAME/jobs/
applyDataGrants
```



```
funcExecuteRequest "POST" $url "application/json"
output=`cat response.txt`
status=`echo $output | jq '.status'`
if [ $status == -1 ]; then
    echo "Started Data Grants successfully"
    funcGetStatus "GET"
else
    error=`echo $output | jq '.details'`
    echo "Error occurred. " $error
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
```

}

Groovy Sample – ApplyDataGrants.groovy for Profitability and Cost Management

```
Prerequisites: json.jar
```

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def applyDataGrants() {
   String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
applications/" + appName +"/jobs/applyDataGrants";
   def url;

try {
    url = new URL(urlString)
      } catch (MalformedURLException e) {
      println "Malformed URL. Please pass valid URL"
      System.exit(0);
      }
    executeJob(url, "POST", null);
}
```

Copy ML POV Data

Copies model artifacts and data from a Source POV combination to a Destination POV combination for any application. Use with Management Ledger applications.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/povs/ {srcPOVMemberGroup}/jobs/copyPOVJob/{destPOVMemberGroup}



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-7 Parameters

Description	Туре	Required	Default
Version of the API you are developing with	Path	Yes	None
Name of the application for which to deploy the cube	Path	Yes	None
Source POV member group, such as 2014_January_Actual	Path	Yes	None
Destination POV member group, such as 2014_March_Actual	Path	Yes	None
Whether to copy the program rule details	Payload	Yes	None
Whether to copy input data	Payload	Yes	None
Note: Do not set the value of this parameter to true if the value of isAllData or isAllInputData is set to true.			
Whether to copy a slice of data from source POV to destination POV	Payload	No	Nothing copied
Whether to copy all input data at the NoRule member, including AdjustmentIn/Out	Form	No	False
Whether to copy all POV data	Form	No	False
Whether to create the destination POV if it does not already exist	Payload	Yes	None
(NET). Valid values are <i>true</i> and <i>false</i> . In some cases, the default nonEmptyTupleEnabled=true does not perform well when copying the Oracle Essbase data. In those cases, use nonEmptyTupleEnabled=false to improve	Payload	No	True
	Povload	Voc	None
	Version of the API you are developing with Name of the application for which to deploy the cube Source POV member group, such as 2014_January_Actual Destination POV member group, such as 2014_March_Actual Whether to copy the program rule details Whether to copy the program rule details Whether to copy input data Note : Do not set the value of this parameter to true if the value of isAllData or isAllInputData is set to true. Whether to copy a slice of data from source POV to destination POV Whether to copy all input data at the NoRule member, including AdjustmentIn/Out Whether to copy all POV data Whether to create the destination POV if it does not already exist Specifies whether to enable the Non Empty Tuple (NET). Valid values are <i>true</i> and <i>false</i> . In some cases, the default nonEmptyTupleEnabled=true does not perform well when copying the Oracle Essbase data. In those cases, use	Version of the API you are developing withPathName of the application for which to deploy the cubePathSource POV member group, such as 2014_January_ActualPathDestination POV member group, such as 2014_March_ActualPathWhether to copy the program rule detailsPayloadWhether to copy input dataPayloadNote: Do not set the value of this parameter to true if the value of isAllData or isAllInputData is set to true.PayloadWhether to copy a slice of data from source POV to destination POVPayloadWhether to copy all input data at the NoRule member, including AdjustmentIn/OutFormWhether to create the destination POV if it does not already existFormSpecifies whether to enable the Non Empty Tuple (NET). Valid values are <i>true</i> and <i>false</i> . In some cases, the default nonEmptyTupleEnabled=true does not perform well when copying the Oracle Essbase data. In those cases, use nonEmptyTupleEnabled=false to improve performance.	Version of the API you are developing with Name of the application for which to deploy the cubePathYesName of the application for which to deploy the cubePathYesSource POV member group, such as 2014_January_ActualPathYesDestination POV member group, such as 2014_March_ActualPathYesWhether to copy the program rule detailsPayloadYesWhether to copy input dataPayloadYesNote: Do not set the value of this parameter to true if the value of isAllData or isAllInputData is set to true.FormNoWhether to copy a slice of data from source POV member, including Adjustmentln/OutFormNoWhether to copy all input data at the NoRule member, including Adjustmentln/OutFormNoWhether to create the destination POV if it does not already existPayloadYesSpecifies whether to enable the Non Empty Tuple cases, the default nonEmptyTupleEnabled=true does not perform well when copying the Oracle Essbase data. In those cases, use nonEmptyTupleEnabled=false to improve performance.No

Example URL and Payload

https://<BASE-URL>/epm/rest/v1/applications/LM1T2/povs/2014_January_Actual/jobs/ copyPOVJob/2014 March Actual

{"isManageRule":"true","isInputData":"true","modelViewName":"Operating
Expenses","createDestPOV":"true","nonEmptyTupleEnabled":"true","stringDelimiter":
"_"}



Response

Supported Media Types: application/json

Name	Description
details	Task ID, such as LM1T2_LM1T2_CopyMLPOV_D20160113T065943_75b_1
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-8 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

Java Sample - CopyPOV.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void copyPOVData() throws Exception {
    JSONObject json = new JSONObject(); String
modelViewName = "Operating Expenses";
    json.put("isManageRule", true);
    json.put("isInputData", true);
    json.put("modelViewName", modelViewName);
    json.put("createDestPOV", true);
    json.put("stringDelimiter", "_");
```



cURL Sample - CopyPOV.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcCopyPOVData() {
    stringDelimiter=" ";
                           modelViewName="Operating Expenses";
    destPovGroupMember="2014 December Actual";
param="{\"isManageRule\":\"true\",\"isInputData\":\"true\",\modelViewName\":\"
$modelViewName\",\"createDestPOV\":\"true\",\"stringDelimiter\":\"$stringDelim
iter\"}"
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/
povs/$POV GROUP MEMBER/jobs/copyPOVJob/$destPovGroupMember
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started Copying POV successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Java Sample - CopyPOV.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void copyPOVData() throws Exception {
    JSONObject json = new JSONObject(); String
modelViewName = "Operating Expenses";
    json.put("isManageRule", true);
    json.put("isInputData", true);
    json.put("modelViewName", modelViewName);
    json.put("createDestPOV", true);
    json.put("stringDelimiter", "_");
```



Create File-Based Application

Creates an application using a flat file using a REST API.

Required Roles

Service Administrator

REST Resource

POST /epm/rest/{api_version}/fileApplications/{application}

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-9 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application to create	Path	Yes	None
description	User comment for this application	Payload	Yes	None
ruleDimensionName	Rule dimension name	Payload	Yes	None
balanceDimensionNa	Balance dimension name	Payload	Yes	None
me				

Example URL and Payload

https://<BASE-URL>/epm/rest/v1/fileApplications/BksML12

```
{"description":
"description","ruleDimensionName":"Rule","balanceDimensionName":"Balance"}
```



Response

Supported Media Types: application/json

Name	Description
details	Task ID, such as BksML12_BksML12_LoadData_D20160118T051020_ba8_1
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-10 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_UpdateDimensions_D20220513T062046_c61",
    "links":[
        {
                "href":"http://<<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_UpdateDimensions_D20220513T062046_c61",
                "action":"GET",
                "rel":"Job Status"
        }
    ]
}
```

Java Sample - CreateFlatFileApplication.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void createFlatFileApplication() throws Exception {
    JSONObject json = new JSONObject();
    json.put("description", "Flat file based application");
    json.put("ruleDimensionName", "Rule");
    json.put("balanceDimensionName", "Balance");
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
```

```
fileApplications/" + "BksML13";
    String response = executeRequest(urlString, "POST", json.toString(),
"application/json");
    JSONObject jsonObj = new JSONObject(response);
    int resStatus = jsonObj.getInt("status");
    if(resStatus == 0) {
        System.out.println("Application created successfully");
    } else {
        System.out.println("Application creation failed");
    }
}
```

cURL Sample - CreateFlatFileApplication.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcCreateFlatFileApplication() {
    description="Flat file based application";
    ruleDimensionName="Rule"
   balanceDimensionName="Balance"
param="{\"description\":\"$description\",\"ruleDimensionName\":\"$ruleDimensio
nName\", \"balanceDimensionName\":\"$balanceDimensionName\"}"
    url=$SERVER URL/epm/rest/$API VERSION/fileApplications/BksML13
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Application created successfully"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Groovy Sample – CreateFlatFileApplication.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def createFlatFileApplication() {
    JSONObject json = new JSONObject();
    json.put("description", "Flat file based application");
    json.put("ruleDimensionName", "Rule");
    json.put("balanceDimensionName", "Balance");
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
fileApplications/" + "BksML13";
```

```
def url;
        try {
                url = new URL(urlString)
        } catch (MalformedURLException e) {
                println "Malformed URL. Please pass valid URL"
                System.exit(0);
        }
        String response = executeRequest(url, "POST", json.toString(),
"application/json")
        JSONObject jsonObj = new JSONObject(response);
        int resStatus = jsonObj.getInt("status");
        if(resStatus == 0) {
            println "Application created successfully"
        } else {
            println "Application creation failed"
        }
}
```

Deploy ML Cube

Deploys or redeploys the calculation cube for a selected Profitability and Cost Management application.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/jobs/ledgerDeployCubeJob

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-11 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None

Table 24-11 (Cont.) Parameters

Name	Description	Туре	Required	Default
application	Name of the application for which to deploy the cube	Path	Yes	None
isKeepData	Specify whether to preserve existing data	Payload	Yes	None
isReplaceCube	Specifies whether to replace existing cube	Payload	Yes	None
	Note: Bo th isKeepData and isReplaceCube cannot be true at the same time.			
isRunNow	Run now or schedule for later. (Schedule for later is not currently supported.)	Payload	Yes	None
comment	Any user comments	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/epm/rest/v1/applications/{applicationName}/jobs/ ledgerDeployCubeJob

{"isKeepData":"true","isRunNow":"true","comment":"Test Ml Deploy"}

Response

Supported Media Types: application/json

Name	Description
details	In case of errors, details are published with the error string
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_DeployCube_D20220511T114550_da1",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_DeployCube_D20220511T114550_da1",
            "action":"GET",
            "rel":"Job Status"
```

] } }

Java Sample - DeployCube.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void deployCube() throws Exception {
    JSONObject json = new JSONObject();
    json.put("isKeepData", true);
    json.put("isReplaceCube", false);
    json.put("isRunNow", true);
    json.put("comment", "Cube deployment");
    String urlString = "%s/epm/rest/%s/applications/%s/jobs/
ledgerDeployCubeJob";
    executeJob(urlString, "POST", json.toString());
}
```

cURL Sample - DeployCube.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcDeployCube() {
    comment="Cube deployment Curl"
param="{\"isKeepData\":\"false\",\"isReplaceCube\":\"true\",\"isRunNow\":\"tru
e\",\"comment\":\"$comment\"}"
   url=$SERVER_URL/epm/rest/$API_VERSION/applications/$APP_NAME/jobs/
ledgerDeployCubeJob
    funcExecuteRequest "POST" $url "$param" "application/json"
   output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ status == -1 ]; then
        echo "Started Deploying Cube successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – DeployCube.groovy for Profitability and Cost Management

Prerequisites: json.jar



Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def deployCube() {
        JSONObject json = new JSONObject();
        json.put("isKeepData", true);
        json.put("isReplaceCube", false);
        json.put("isRunNow", true);
        json.put("comment", "Cube deployment");
        def url;
        def response;
        try {
                 url = new URL(serverUrl + "/epm/rest/" + apiVersion + "/
applications/" + appName + "/jobs/ledgerDeployCubeJob")
        } catch (MalformedURLException e) {
                println "Malformed URL. Please pass valid URL"
                System.exit(0);
       }
        executeJob(url, "POST", json.toString());
```

Enable File-Based Application

Enables an application using a flat file.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/fileApplications/{application}/enableApplication

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-13 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None

Table 24-13 (Cont.) Parameters

Name	Description	Туре	Required	Default
application	Name of the application to enable	Path	Yes	None

Example URL

https://<EPM-CLOUD-BASE-URL>/epm/rest/v1/fileApplications/BksML12/
enableApplication

Response

Supported Media Types: application/json

Table 24-14 Parameters

Name	Description
details	Task ID, such as BksMl12_BksMl12_EnableApplication_D20160113T075011_53c_1
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_EnableApplication_D20220511T114947_65c",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_EnableApplication_D20220511T114947_65c",
            "action":"GET",
            "rel":"Job Status"
        }
    ]
}
```

Java Sample – EnableApplication.java for Profitability and Cost Management

Prerequisites: json.jar



Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void enableApplication() throws Exception {
    String urlString = "%s/epm/rest/%s/fileApplications/%s" +"/
enableApplication";
    executeJob(urlString, "POST", null);
}
```

cURL Sample - EnableApplication.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcEnableApplication() {
    url=$SERVER_URL/epm/rest/$API_VERSION/fileApplications/$APP_NAME/
enableApplication
    funcExecuteRequest "POST" $url "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == -1 ]; then
        echo "Started Enabling Application successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – EnableApplication.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def enableApplication() {
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
fileApplications/"+ appName +"/enableApplication";
    def url;
    try {
        url = new URL(urlString)
    } catch (MalformedURLException e) {
            println "Malformed URL. Please pass valid URL"
            System.exit(0);
    }
    executeJob(url, "POST", null);
}
```



Essbase Data Load for Profitability and Cost Management

Loads input data to an Oracle Essbase application.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/jobs/essbaseDataLoadJob

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-15 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application for which to load the data	Path	Yes	None
clearAllDataFlag	Whether to clear existing data (true) or not (false)	Payload	Yes	None
dataLoadValue	Possible values are ADD_EXISTING_VALUES or OVERWRITE_EXISTING_VALUES	Payload	Yes	None
dataFileName	Name of the data file already present in the inbox folder	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/epm/rest/v1/applications/BksML12/jobs/essbaseDataLoadJob

{"clearAllDataFlag":"true","dataLoadValue":"OVERWRITE_EXISTING_VALUES","dataFileN
ame":"input.txt"}

Response

Supported Media Types: application/json



Name	Description
details	Task ID, such as BksML12_BksML12_LoadData_D20160118T051020_ba8_1
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-16 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_LoadData_D20220511T114654_8bf",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_LoadData_D20220511T114654_8bf",
            "action":"GET",
            "rel":"Job Status"
        }
    ]
}
```

Java Sample - EssbaseDataLoad.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void loadData() throws Exception {
    JSONObject json = new JSONObject();
    json.put("clearAllDataFlag", false);
    json.put("dataLoadValue", "ADD_EXISTING_VALUES");
    json.put("dataFileName", "BksML12C.txt");
    String urlString = "%s/epm/rest/%s/applications/%s/jobs/
essbaseDataLoadJob";
    executeJob(urlString, "POST", json.toString());
```



cURL Sample - EssbaseDataLoad.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcLoadData() {
    dataLoadValue="ADD EXISTING VALUES"
    dataFileName="BksML12C.txt"
param="{\"clearAllDataFlag\":\"false\",\"dataLoadValue\":\"$dataLoadValue\",\"
dataFileName\":\"$dataFileName\"}"
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/jobs/
essbaseDataLoadJob
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started Loading Data successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – EssbaseDataLoad.groovy for Profitability and Cost Management

Prerequisites: json.jar

}

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def loadData() {
        JSONObject json = new JSONObject();
        json.put("clearAllDataFlag", false);
        json.put("dataLoadValue", "ADD EXISTING VALUES");
        json.put("dataFileName", "BksML12C.txt");
        def url;
        def response;
        try {
                 url = new URL(serverUrl + "/epm/rest/" + apiVersion + "/
applications/" + appName + "/jobs/essbaseDataLoadJob")
        } catch (MalformedURLException e) {
                 println "Malformed URL. Please pass valid URL"
                 System.exit(0);
        }
        executeJob(url, "POST", json.toString());
}
```



Export Query Results

Exports query results for a given query or exports all Oracle Essbase data into a file in the Outbox.

When exporting all Essbase data, there is an option for writing the output in columnar format, and columnar-formatted data can be filtered by level-0 dimension members. This API triggers a job that can be monitored in the Job Library.

Required Roles

Service Administrator, Power User, User, Viewer

REST Resource

```
POST /epm/rest/{api_version}/applications/{application}/jobs/
exportQueryResultsJob
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-17	Parameters
-------------	------------

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, such as $\mathtt{v1}$	Path	Yes	None
application	Name of the application	Path	Yes	None
exportOnlyLevelOFl g	Whether to export only Level0 data; values are true or false	Payload	No	false
fileName	Name of the query output file to be exported into the Outbox folder	Payload	Yes	None
fileOutputOptions	 File output options. Available options are: ZIP_ONLY ZIP AND TEXT 	Payload	No	ZIP_ONLY

TEXT_ONLY



Table 24-17 (Cont.) Parameters

Name	Description	Туре	Required	Default
queryName	Query name from the Profitability and Cost Management application When queryName has a value, results for the given query are exported; exportOnlyLevelOFlg is considered if it is included.	Payload	No	None
	When queryName is blank or not included, data for the entire application is exported. In this case, exportOnlyLevelOFlg is ignored.			
roundingPrecision	The rounding precision (decimal places) for exported data. (Note: Applies only if <code>queryName</code> is also used.)	Payload	No	2
dataFormat	Select the output format as native Essbase format, or as columnar format. Values are NATIVE or COLUMNAR. With the COLUMNAR option, all Essbase data is exported, so the queryName parameter is ignored. Data can be filtered using the memberFilters parameter.	Payload	No	NATIVE
The following parameter	rs are only considered when dataFormat=COLUMNAF	۲.		
memberFilters	Accepts a JSON formatted string for dimension and respective level-0 member format. For example: {\"Dim1\":[\"Mem1\"], \"Dim2\": [\"Mem21\", \"Mem22\"]}	Payload	No	None
includeHeader	Adds dimension names as column headers. Values are true or false.	Payload	No	true
delimiter	Character used to separate dimension members in the results file; must be enclosed in double quotes.	Payload	No	Space
keepDuplicateMembe rFormat	When this parameter is set to true, prints member names in Essbase duplicate member format, such as [Account]@[Accoun1]. If set to false, only the member name is printed.	Payload	No	true

Example URL and Payload

https://<BASE-URL>/epm/rest/v1/applications/Ex3F3/jobs/exportQueryResultsJob

```
{"queryName":"Profitability -
Product","fileName":"ProfitabilityProduct_03232016.txt","exportOnlyLevel0Flg":"tr
ue","roundingPrecision":"3"}
```

Response

Supported Media Types: application/json

Table 24-18 Parameters

Name	Description
details	Task ID, such as BksML12_BksML12_ExportQueryResults_D20160323T024820_f73_ 1



Name	Description
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-18 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

Java Sample - ExportQueryResult.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void exportTemplate() throws Exception {
    String fileName = applicationName + "_Template_Export_File";
    JSONObject json = new JSONObject();
    json.put("fileName", fileName);
    String urlString = "%s/epm/rest/%s/applications/%s/jobs/
templateExportJob";
    executeJob(urlString, "POST", json.toString());
}
```



cURL Sample - ExportQueryResult.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcExportQueryResult() {
    queryName="Profitability - Product";
    fileName=$APP NAME+" "+$queryName+" Query Result"
param="{\"queryName\":\"$queryName\",\"fileName\":\"$fileName\",\"exportOnlyLe
velOFlg\":\"false\"}"
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/jobs/
exportQueryResultsJob
    funcExecuteRequest "POST" $url "$param" "application/json"
   output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started Exporting successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – ExportQueryResult.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def exportQueryResult() {
        String queryName = "Profitability - Product";
        String fileName = appName +" "+ queryName + " Query Result";
        JSONObject json = new JSONObject();
        json.put("queryName", queryName);
        json.put("fileName", fileName);
        json.put("exportOnlyLevelOFlg", false);
        String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
applications/" + appName + "/jobs/exportQueryResultsJob";
        def url;
         try {
                 url = new URL(urlString)
         } catch (MalformedURLException e) {
                 println "Malformed URL. Please pass valid URL"
                 System.exit(0);
         }
        executeJob(url, "POST", json.toString());
}
```

Export Template for Profitability and Cost Management

Exports Profitability and Cost Management applications as a template into the Outbox.

Required Roles

Service Administrator, Power User

REST Resource

POST/epm/rest/{api_version}/applications/{application}/jobs/templateExportJob?
fileName={fileName}

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-19 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application	Path	Yes	None
fileName	Name of the template zip file to be exported to the outbox folder	Query	Yes	None

Note:

If the file name is the same as an existing file name, this will override content in existing file.

Example URL and Payload

```
https://<BASE-URL>/epm/rest/v1/applications/BksML30/jobs/
templateExportJob{"fileName":"testFile"}
```

Response

Supported Media Types: application/json



Name	Description
details	Task ID, such as BksML30_ExportTemplate_D20180201T210316_a80
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-20 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_ExportTemplate_D20220511T114738_16e",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_ExportTemplate_D20220511T114738_16e",
            "action":"GET",
            "rel":"Job Status"
        }
    ]
}
```

Java Sample - ExportTemplate.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void exportTemplate() throws Exception {
    String fileName = applicationName + "_Template_Export_File";
    JSONObject json = new JSONObject();
    json.put("fileName", fileName);
    String urlString = "%s/epm/rest/%s/applications/%s/jobs/
templateExportJob";
    executeJob(urlString, "POST", json.toString());
```



cURL Sample - ExportTemplate.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcExportTemplate() {
    fileName=$APP NAME+" Template Export File"
   param="{\"fileName\":\"$fileName\"}"
   url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/jobs/
templateExportJob
   funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ status == -1 ]; then
        echo "Started Exporting successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – ExportTemplate.groovy for Profitability and Cost Management

Prerequisites: json.jar

}

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def exportTemplate() {
    String fileName = appName + "_Template_Export_File";
    JSONObject json = new JSONObject();
    json.put("fileName", fileName);
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
    applications/" + appName + "/jobs/templateExportJob";
    def url;
    try {
        url = new URL(urlString)
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    executeJob(url, "POST", json.toString());
}
```



Generate Program Documentation Report

Generates a Program Documentation report for a given Profitability and Cost Management point of view.

The report is generated in the profitoutbox folder with the name

HPCMMLProgramDocumentationReport_{AppName)_{POV}.pdf. The file can be downloaded using File Explorer.

Required Roles

Service Administrator, Power User, User, or Viewer

REST Resource

GET epm/rest/{api_version}/applications/{application}/povs/{POV}/ programDocumentationReport

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-21 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, such as vl	Path	Yes	None
application	Name of the application for which to create the report	Path	Yes	None
pov	The POV for which to create the report, for example, FY17_JUN_Actual_Working	Path	Yes	None
fileType	The file format to use for the report, PDF, XML, WORD, EXCEL, or HTML	Query	No	PDF
useAlias	Boolean value to specify whether to use aliases in the report, true or falset	Query	No	false

Example URL with fileType set to PDF and useAlias set to true:

https://<BASE-URL>/epm/rest/v1/applications/BksML30/povs/2016_January_Actual/
programDocumentationReport?queryParameter={"fileType":"PDF","useAlias":"true"}

Response

Supported Media Types: application/json



Name	Description
details	Program Documentation report name, such as HPCMMLProgramDocumentationReport_BksML30_2016_January_Ac tual.pdf, and report status
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-22 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":0,
    "statusMessage":"Success",
    "details":"Program Documentation report
HPCMMLProgramDocumentationReport_BksML30_2016_January_Actual.pdf generated
successfully in the Outbox folder."
}
```

Java Sample - GeneratePrgrmDocReport.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void generatePrgrmDocReport() throws Exception {
    JSONObject json = new JSONObject();
    json.put("fileType", "PDF");
    json.put("useAlias", false);
    json.put("stringDelimter", "_");
    String povGroupMember = "2016_January_Actual";
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
    applications/" + applicationName + "/povs/" +
    povGroupMember.trim().replaceAll(" ", "%20") + "/programDocumentationReport";
        urlString = urlString + "?" + "queryParameter=" + json.toString();
        String response = executeRequest(urlString, "GET", null, "application/
json");
```



```
JSONObject jsonObj = new JSONObject(response);
int resStatus = jsonObj.getInt("status");
if(resStatus == 0) {
    System.out.println("Program Documentation Report Generated
Successfully");
    }
    String details = jsonObj.getString("details");
    System.out.println(details);
}
```

cURL Sample - GeneratePrgDocReport.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcGeneratePrgDocReport() {
       url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/
povs/$POV GROUP MEMBER1/programDocumentationReport
       echo $url
       curl -G "$url" --data-urlencode
'queryParameter={"fileType":"PDF","stringDelimter":" ","useAlias":"false"}' -
u "$USERNAME:$PASSWORD" -o "response.txt" -D "respHeader.txt"
       output=`cat response.txt`
       status=`echo $output | jq '.status'`
       echo $status
    if [ $status == 0 ]; then
       echo "Program Documentation Report generated successfully"
       message=`echo $output | jg '.details'`
       echo $message
    else
       error=`echo $output | jq '.details'`
       echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
```

}

Groovy Sample – GeneratePrgrmDocReport.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def generateProgramDocReportJob() {
   JSONObject json = new JSONObject();
   json.put("fileName", "2016JanActual.pdf");
   json.put("fileType", "PDF");
   json.put("useAlias", false);
   json.put("stringDelimter", "_");

String povGroupMember = "2016_January_Actual";
String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/applications/"
+ appName + "/povs/" + povGroupMember.trim().replaceAll(" ", "%20") + "/
```

```
jobs/programDocReportJob";
def url;
try {
    url = new URL(urlString)
} catch (MalformedURLException e) {
    println "Malformed URL. Please pass valid URL"
    System.exit(0);
}
executeJob(url, "POST", json.toString());
}
```

Generate Program Documentation Report - Run as a Job

Submits a job to generate a Program Documentation report for a given Profitability and Cost Management point of view.

The report is generated in the profitoutbox folder with the name as fileName parameter value or HPCMMLProgramDocumentationReport_{AppName)_{POV}.pdf as default. The file can be downloaded using File Explorer or by using the EPM Automate downloadfile command.

Required Roles

Service Administrator, Power User, User, or Viewer

REST Resource

POST

/epm/rest/{api_version}/applications/<applicationName>/povs/<povName>/jobs/
programDocReportJob

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-23 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with, such as $\mathbb{v}\mathbb{1}$	Path	Yes	None
applicationName	Name of the application for which to create the report	Path	Yes	None
povName	The POV for which to create the report, for example, FY17_JUN_Actual_Working	Path	Yes	None



Name	Description	Туре	Required	Default
fileType	The file format to use for the report, PDF, XML, WORD, EXCEL, or HTML	Request Payload	No	PDF
fileName	Name of the output file	Request Payload	No	HPCMMLProgr amDocumenta tionReport_ <appname>_P OV.pdf</appname>
subsetStart	Rule set starting sequence number to specify a range of rule sets to include in the report	Request Payload	No	None
subsetEnd	Rule set ending sequence number to specify a range of rule sets to include in the report	Request Payload	No	None
useAlias	Boolean value to specify whether to use aliases in the report, true or false	Request Payload	No	False
stringDelimiter	POV Dimension members separator	Request Payload	No	" " _

Table 24-23 (Cont.) Parameters

Example URL

https://<BASE-URL>/rest/v1/applications/<applicationName>/povs/<povName>/jobs/
programDocReportJob

Request Payload

```
{
    "fileName":"FY12ActualReport.pdf",
    "fileType": "PDF",
    "subsetStart":"1",
    "subsetEnd":"6",
    "useAlias": false,
    "stringDelimiter":"_"
}
```

Response

Supported Media Types: application/json

Table 24-24 Parameters

Name	Description
details	Program Documentation report name, such as HPCMMLProgramDocumentationReport_BksML30_2016_January_Ac tual.pdf, and report status
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call



Name	Description
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-24 (Cont.) Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

Java Sample - GeneratePrgrmDocReport.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java



cURL Sample - GeneratePrgDocReport.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcProgramDocReportJob() {
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/
povs/$POV GROUP MEMBER1/jobs/programDocReportJob
        stringDelimter=" ";
param="{\"fileName\":\"2016JanActual.pdf\",\"fileType\":\"PDF\",\"subsetStart\
":\"1\",\"subsetEnd\":\"6\",
\"useAlias\":\"false\", \"stringDelimter\":\"$stringDelimiter\"}"
        echo $param
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started program doc report generation"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Groovy Sample – GeneratePrgrmDocReport.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def generateProgramDocReportJob() {
   JSONObject json = new JSONObject();
    json.put("fileName", "2016JanActual");
    json.put("fileType", "PDF");
    json.put("subsetStart", "1");
    json.put("subsetEnd", "6");
    json.put("useAlias", false);
   json.put("stringDelimter", " ");
    String urlString = serverUrl + "/epm/rest/"+ apiVersion +
        "/applications/" + appName + "/povs/" +
        povGroupMember.trim().replaceAll(" ", "%20") +
        "/jobs/programDocReportJob";
    def url;
    try {
          url = new URL(urlString)
    } catch (MalformedURLException e) {
          println "Malformed URL. Please pass valid URL"
          System.exit(0);
    }
```

```
executeJob(url, "POST", json.toString());
```

Import Template for Profitability and Cost Management

Imports a template zip file as an application from the inbox.

Required Roles

}

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/jobs/templateImportJob

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-25 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application	Path	Yes	None
description	User comment for the application	Payload	Yes	None
fileName	Name of the template zip file to be imported from the inbox folder	Payload	Yes	None
isApplicationOverw rite	Whether to override an application if one already exists with same name. Values are <i>true</i> or <i>false</i> .	Payload	Yes	None

Example URL and Payload

https://<BASE-URL>/epm/rest/v1/applications/Ex3F3/jobs/templateImportJob

```
{"description":"description","fileName":"
testFile12345.zip","isApplicationOverwrite":"true"}
```

Response

Supported Media Types: application/json



Name	Description
details	Task ID, such as TD_ae61e427d9ab4d6f99e3b87378fa1c94
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-26 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

Java Sample - ImportTemplate.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void importTemplate() throws Exception {
    JSONObject json = new JSONObject();
    json.put("description", "Import Template");
    json.put("instanceName", "PROFITABILITY_WEB_APP");
    json.put("essApplicationServer", "EssbaseCluster-1");
    json.put("sharedServicesProject", "EssbaseCluster-1");
    json.put("applicationType", "Management Ledger");
    json.put("fileName", "HPCM_BksML12_20160128_200053.zip");
    json.put("isApplicationOverwrite", true);
    String urlString = "%s/epm/rest/%s/applications/%s/jobs/
```

```
templateImportJob";
    executeJob(urlString, "POST", json.toString());
}
```

cURL Sample - ImportTemplate.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcImportTemplate() {
    description="Import Template through Curl Sample"
    instance="PROFITABILITY WEB APP"
    essAppServer="EssbaseCluster-1"
    sharedServicesProject="EssbaseCluster-1"
    applicationType="Management Ledger"
    fileName="PCM BksML12 20160413 042937.zip"
    isApplicationOverwrite="true"
param="{\"description\":\"$description\", \"instanceName\":\"$instance\", \"essA
pplicationServer\":\"$essAppServer\",\"sharedServicesProject\":\"$sharedServic
esProject\",\"applicationType\":\"$applicationType\",\"fileName\":\"$fileName\
", \"isApplicationOverwrite \": \"$isApplicationOverwrite \"}"
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/jobs/
templateImportJob
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started importing successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample - ImportTemplate.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common unctions: See Appendix C: Common Helper Functions for Groovy.

```
def importTemplate() {
    JSONObject json = new JSONObject();
    json.put("description", "Import Template");
    json.put("instanceName", "PROFITABILITY_WEB_APP");
    json.put("essApplicationServer", "EssbaseCluster-1");
    json.put("sharedServicesProject", "EssbaseCluster-1");
    json.put("applicationType", "Management Ledger");
    json.put("fileName", "BksML12_Template.zip");
    json.put("isApplicationOverwrite", true);
```



Merge Slices for Profitability and Cost Management

Merges all incremental data slices into the main database slices.

Optionally, removes the Oracle Essbase cells with zero values to make the cube compact.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api version}/applications/{application}/jobs/mergeSlices

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-27 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the Profitability and Cost Management application	Path	Yes	None
removeZeroCells	If "true", removes cells with zero values	Path	No	"false"

Request URI Example



https://<BASE-URL>/epm/rest/v1/applicaitions/BksML30/jobs/mergeSlices

Request Payload:

```
{
   "removeZeroCells":"true"
)
```

Response

Supported Media Types: application/json

Table 24-28 Parameters

Name	Description
details	In case of errors, details are published with the error string.
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation.
data	Parameters as key value pairs passed in the request

Example of Response Body

Optimize ASO Cube

Optimizes the performance of queries for data extraction by creating aggregate views in ASO cubes for Profitability and Cost Management applications.

This command allows you to perform query optimization operations on ASO cubes in cases where default aggregation is deemed insufficient to meet your data extraction or reporting needs because of large data size. The typical optimization process is as follows:

- Drop default and query-based aggregations.
- Start query tracking.



- Run sample queries from Profitability and Cost Management Query Manager, Oracle Smart View for Office (Windows), or Data Management, and any other MDX queries representative of the type of queries for which optimization is desired to train Oracle Essbase.
- Create aggregation based on optimized or default queries.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/v1/applications/{AppName}/jobs/optimizeASOCube

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-29 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
appName	Name of the application used to run Optimize ASO	Path	Yes	None
type	 Type of operation. Valid values are: clearAggregations removes default and query-based views. 	Form	Yes	None
	 createAggregations creates default Essbase aggregate views. Use this option to perform default aggregation instead of query- based aggregation. 			
	 startQueryTracking starts query tracking. Use this option to allow Essbase to collect optimization information for creating query- based aggregations. 			
	 stopQueryTracking stops query tracking. Use this option to stop Essbase from collecting optimization information. Essbase continues to collect optimization information until you stop query tracking or stop Essbase.) 			
	• createQBOAggregations creates Essbase aggregate views based on the optimized queries that you run after enabling query tracking.			

Response

Supported Media Types: application/json

Name	Description
details	In case of errors, details are published with the error string.
status	See Migration Status Codes
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Can be self and/or Job Status. If set to Job Status, you can use the href to get the status of the import operation.
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_OptimizeASOCube_D20220511T115135_55d",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_OptimizeASOCube_D20220511T115135_55d",
            "action":"GET",
            "rel":"Job Status"
        }
    ]
}
```

Java Sample - OptimizeASOCube.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void optimizeASOCube() throws Exception {
    JSONObject json = new JSONObject();
    json.put("type", "createAggregations");
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
applications/" + applicationName+"/jobs/optimizeASOCube";
    executeJob(urlString, "POST", json.toString());
}
```



cURL Sample - OptimizeASOCube.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcOptimizeASOCube() {
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/jobs/
optimizeASOCube
        param="{\"type\":\"createAggregations\"}"
                echo $param
     funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == -1 ]; then
        echo "Started Optimize ASO Cube successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample – OptimizeASOCube.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def optimizeASOCube() {
    JSONObject json = new JSONObject();
    json.put("type", "createAggregations");
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
    applications/" + appName + "/jobs/optimizeASOCube";
    def url;
    try {
        url = new URL(urlString)
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    executeJob(url, "POST", json.toString());
}
```

Retrieve Task Status for Profitability and Cost Management

Displays the current status of the job process name.

Required Roles

Service Administrator, Power User

REST Resource

GET /epm/rest/{api_version}/applications/jobs/ChecktaskStatusJob/{processName}

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-31 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
applications	Included in the path	Path	Yes	None
processName	The ID of the process or task flow for which to check the task status	Path	Yes	None

Response

Supported Media Types: application/json

The following table summarizes the response parameters.

Table 24-32 Parameters

Name	Description
processName	The Process Name or Taskflowld, such as RBkML1_ExportTemplate_D20160112T025419_836
task	Task name, such as ExportTemplate
status	Task status, such as Success

Example of Response Body

```
{
    "type": "Profitability",
    "links": [{
```



```
"href": "https://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/RBkML1_ExportTemplate_D20160112T025419_836",
    "action": "GET",
    "rel": "self"
    }],
    "status": 0,
    "details":
"ExportTemplate=Success,RBkML1_ExportTemplate_D20160112T025419_836=Done",
    "statusMessage": "Success"
}
```

Run ML Calculations

Runs or clears calculations for a selected application. You can run calculations using rules in a model POV against data in a different data POV without copying rules.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/povs/{povGroupMember}/
jobs/runLedgerCalculationJob

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-33 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application for which to run calculations	Path	Yes	None
povGroupMember	The model POV group member from which the rules will be used for calculations, such as 2016_January_Actual	Path	Yes	None
	If <i>dataPOVName</i> is not passed, <i>povGroupMember</i> is used as both model and data POV.			
dataPOVName	The data POV group member for which to run calculations, such as 2015_January_Actual	Payload	No	None
	exeType=ALL_RULES is the valid combination while using <i>dataPOVName</i> .			



Name	Description	Туре	Required	Default
isClearCalculated	Whether to clear the calculation data, true or false	Payload	No	None
isRunNow	Whether to run now (true) or schedule for later (false); schedule for later is not currently supported	Payload	Yes	true
optimizeReporting	Whether to optimize for reporting (true) or not (false).	Payload	No	true
	When <i>optimizieReporting</i> is used, Profitability and Cost Management runs default aggregations on the Essbase cube when the calculation is complete. You can also run this setting by itself, which improves performance for queries and analytics.			
	If you don't pass this parameter, its setting is assumed to be true ("About Optimizing for Reporting" in <i>Administering Profitability and Cost</i> <i>Management</i>).			
subsetStart	Rule Set Starting Sequence Number	Payload	No	None
subsetEnd	Rule Set Ending Sequence Number	Payload	No	None
ruleName	Rule Name for a SINGLE_RULE option	Payload	No	None
ruleSetName	Rule Set Name for a SINGLE_RULE option	Payload	No	None
ехеТуре	The execution type specifies which rules to run; possible values are ALL_RULES, RULESET_SUBSET, SINGLE_RULE. Other parameters are required based on the exeType value:	Payload	Yes	None
	 exeType = ALL_RULES overrides all other options like subsetStart, subsetEnd, ruleSetName, and ruleName. 			
	 exeType = RULESET_SUBSET considers only subsetStart and subsetEnd. 			
	 exeType = SINGLE_RULE considers only ruleSetName and ruleName. 			
comment	Use comment text, such as "This is run by user1"	Payload	No	None
stringDelimiter	String delimiter for POV group members, such as _	Payload	No	None

Table 24-33 (Cont.) Parameters

Example URL and Payload without Passing Data POV

https://<BASE-URL>/epm/rest/{api_version}/applications/{application}/povs/
{povGroupMember}/jobs /runLedgerCalculationJob

```
{"isClearCalculated":"true","isExecuteCalculations":"true","isRunNow":"true","opt
imizeReporting":"false","comment":"This is run by
user1","exeType":"ALL RULES","stringDelimiter":" "}
```

Example URL and Payload with Data POV Passed

https://<BASE-URL>/epm/rest/{api_version}/applications/{application}/povs/
{povGroupMember}/jobs/runLedgerCalculationJob



{"dataPOVName":"2015_January_Actual","isClearCalculated":"true","isExecuteCalcula tions":"true","isRunNow":"true","optimizeReporting":"false","comment":"This is run by userl","exeType":"ALL RULES","stringDelimiter":" "}

Response

Supported Media Types: application/json

Name	Description
details	Task ID, such as BksML1_BksML1_RunCalcs_D20160113T070358_1da_1
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

```
{
    "type":"Profitability",
    "status":-1,
    "statusMessage":"In Progress",
    "details":"BksML30_RunCalcs_D20220511T114716_a14",
    "links":[
        {
            "href":"http://<BASE-URL>/epm/rest/v1/applications/jobs/
ChecktaskStatusJob/BksML30_RunCalcs_D20220511T114716_a14",
            "action":"GET",
            "rel":"Job Status"
        }
    ]
}
```

Java Sample - RunCalculation.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void runCalculation() throws Exception {
   String subsetStart = null;
   String subsetEnd = null;
   String ruleName = null;
   String ruleSetName = null;
```

```
JSONObject json = new JSONObject();
        json.put("isClearCalculated", true);
        json.put("isExecuteCalculations", true);
        json.put("isRunNow", true);
        json.put("comment", "Run Calculation");
        json.put("subsetStart", subsetStart);
        json.put("subsetEnd", subsetEnd);
        json.put("ruleName", ruleName);
        json.put("ruleSetName", ruleSetName);
        json.put("exeType", "ALL RULES");
        json.put("stringDelimiter", " ");
        String povGroupMember = "2014 January Actual";
        String urlString = "%s/epm/rest/%s/applications/%s/povs/" +
povGroupMember.trim().replaceAll(" ", "%20")
                                       + "/jobs/runLedgerCalculationJob";
        executeJob(urlString, "POST", json.toString());
   }
```

cURL Sample - RunCalculation.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcRunCalculation() {
    subsetStart=""
    subsetEnd=""
   ruleName=""
   ruleSetName=""
    comment="Run Calculation Curl"
    exeType="ALL RULES"
   stringDelimiter=" "
param="{\"isClearCalculated\":\"true\", \"isExecuteCalculations\":\"true\", \"is
RunNow\":\"true\",\"comment\":\"$comment\",\"subsetStart\":\"$subsetStart\",\"
subsetEnd\":\"$subsetEnd\",\"ruleName\":\"$ruleName\",\"ruleSetName\":\"$ruleS
etName\",\"exeType\":\"$exeType\",\"stringDelimiter\":\"$stringDelimiter\"}"
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/
povs/$POV GROUP MEMBER/jobs/runLedgerCalculationJob
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$ status == -1 ]; then
        echo "Started Running Calc successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```



Groovy Sample – RunCalculation.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def runCalculation() {
        String subsetStart = null;
        String subsetEnd = null;
        String ruleName = null;
        String ruleSetName = null;
        JSONObject json = new JSONObject();
        json.put("isClearCalculated", true);
        json.put("isExecuteCalculations", true);
        json.put("isRunNow", true);
        json.put("comment", "Run Calculation");
        json.put("subsetStart", subsetStart);
        json.put("subsetEnd", subsetEnd);
        json.put("ruleName", ruleName);
        json.put("ruleSetName", ruleSetName);
        json.put("exeType", "ALL RULES");
        json.put("stringDelimiter", " ");
        String povGroupMember = "2014 January Actual";
        String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
applications/" + appName + "/povs/"
                                       + povGroupMember.trim().replaceAll("
", "%20") + "/jobs/runLedgerCalculationJob";
        def url;
        try {
                url = new URL(urlString)
        } catch (MalformedURLException e) {
                println "Malformed URL. Please pass valid URL"
                System.exit(0);
        }
        executeJob(url, "POST", json.toString());
    }
```

Run ML Clear POV

Clears model artifacts and data from a POV combination for any application.

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/applications/{application}/povs/{povGroupMember}/
jobs/clearPOVJob



Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-35 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application for which to run calculations	Path	Yes	None
povGroupMembe r	The POV group member for which to clear model artifacts sand data, such as 2015_January_Actual	Path	Yes	None
isManageRule	To clear the program rule details or not; true/false	Payload	No	None
isInputData	To clear input data or not; true/false	Payload	No	None
queryName	A query name already existing within the application; used to clear a region within the given POV	Payload	No	None
isAllocatedVa lues	To clear allocation values or not; true/ false	Payload	No	None
isAdjustmentV alues	To clear adjustment values or not; true/ false	Payload	No	None
stringDelimit er	String delimiter for POV group members	Payload	No	"_" (Undersco re)

Note:

If queryName is used (is not null), then isManageRule, isAllocatedValues, and isAdjustmentValues must be set to false.

If one of these parameters or isInputData is not passed, it is considered as false.

Example URL and payload to clear to a particular region within input data

https://<BASE-URL>/epm/rest/{api_version}/applications/{application}/povs/
{povGroupMember}/jobs/clearPOVJob

{"isInputData":"true", "queryName": "myQueryName", "stringDelimiter":" "}



Response

Supported Media Types: application/json

Name	Description
details	Task ID, such as BksML1_BksML1_ClearMLPOV_D20160113T070358_1da_1
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-36 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

Java Sample - clearPOV.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void clearPOVData() throws Exception {
    JSONObject json = new JSONObject();
    json.put("isManageRule", true);
    json.put("isInputData", true);
    json.put("stringDelimiter", "_");
    String povGroupMember = "2014_January_Actual";
```



cURL Sample - ClearPOV.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
uncClearPOVData() {
   stringDelimiter=" ";
param="{\"isManageRule\":\"true\",\"isInputData\":\"true\",\"stringDelimiter\"
:\"$stringDelimiter\"}"
    url=$SERVER URL/epm/rest/$API VERSION/applications/$APP NAME/
povs/$POV GROUP MEMBER/jobs/clearPOVJob
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started Clearing POV successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```

Groovy Sample - ClearPOV.groovy for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
} catch (MalformedURLException e) {
    println "Malformed URL. Please pass valid URL"
    System.exit(0);
}
executeJob(url, "POST", json.toString());
```

Run ML Rule Balancing

}

Retrieves Rule Balancing data for a particular POV for a given application.

Required Roles

Service Administrator, Power User

REST Resource

```
GET /epm/rest/{api_version}/applications/{application}/povs/{povGroupMember}/
ruleBalance
```

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-37 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application for which to retrieve rule balancing data	Path	Yes	None
povGroupMember	POV name for which to retrieve the results, such as 2015_January_Actual	Path	Yes	None
modelViewName	Model view name to filter the results within the POV area	Query	Yes	None
stringDelimiter	String delimiter for POV group members, such as "_"	Query	No	Underscore, "_"

Example URL and Sample Query Parameter

https://<BASE-URL>/epm/rest/{api_version}/applications/{application}/povs/
{povGroupMembers}/ruleBalance?queryParameter={"modelViewName":"modelViewName"}



Response

Supported Media Types: application/json

Name	Description
details	Rule balancing output for the given POV
status	See Migration Status Codes
statusMessage	Message about the status, such as Success
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Table 24-38 Parameters

Example of Response Body

The following shows an example of the response body in JSON format.

```
"items": [{
     "ruleNumber": "",
      "rules": [],
      "balanceTypeRule": true,
      "scale": 2,
      "sequence": 0,
      "name": "NoRule",
      "description": null,
      "runningBalance": 49357098.03,
      "balance": 49357098.03,
      "allocationIn": null,
      "allocationOut": null,
      "adjustmentIn": null,
      "adjustmentOut": null,
      "input": 49357098.03,
      "runningRemainder": 49357098.03,
      "remainder": 49357098.03,
      "netChange": null,
      "offset": null,
      "inputAsString": "49,357,098.03",
      "adjInAsString": "-",
      "adjOutAsString": "-",
      "allocInAsString": "-",
      "allocOutAsString": "-",
      "balanceAsString": "49,357,098.03",
      "runningBalanceAsString": "49,357,098.03",
      "runningRemainderAsString": "49,357,098.03",
      "remainderAsString": "49,357,098.03",
      "netChangeAsString": "-",
      "offsetAsString": "-"
```



```
},
],
"type": "Profitability",
"status": 0,
"details": "",
"statusMessage": "Success"
}
```

Java Sample - RunRuleBalancing.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

```
public void runRuleBalancing() throws Exception {
        String modelViewName = null;
        JSONObject json = new JSONObject();
        json.put("stringDelimiter", " ");
        json.put("modelViewName", modelViewName);
        String povGroupMember = "2014 January Actual";
        String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
applications/" + applicationName + "/povs/"
                                       + povGroupMember.trim().replaceAll("
", "%20") + "/ruleBalance";
        urlString = urlString + "?" + "queryParameter=" + json.toString();
        String response = executeRequest(urlString, "GET", null, "application/
json");
        JSONObject jsonObj = new JSONObject(response);
        int resStatus = jsonObj.getInt("status");
        if(resStatus == 0) {
            System.out.println("Rule Balancing ran successfully");
            JSONArray itemsArray = jsonObj.getJSONArray("items");
            System.out.println("Details : " + itemsArray.toString());
        } else {
            String details = jsonObj.getString("details");
            System.out.println("Rule Balancing failed. Details : " + details);
        }
    }
```

cURL Sample - RunRuleBalancing.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcRunRuleBalancing() {
    url=$SERVER_URL/epm/rest/$API_VERSION/applications/$APP_NAME/
povs/$POV_GROUP_MEMBER/ruleBalance
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
```

```
list=`cat response.txt | jq 'select(.items != null) | .items[].name'`
if [[ ! -z $list ]]; then
    echo $list
else
    echo "No Items found"
fi
funcRemoveTempFiles "respHeader.txt" "response.txt"
```

Groovy Sample - RunRuleBalancing.groovy for Profitability and Cost Management

Prerequisites: json.jar

}

Common Functions: See Appendix C: Common Helper Functions for Groovy.

```
def runRuleBalancing() {
        String modelViewName = null;
        JSONObject json = new JSONObject();
        json.put("stringDelimiter", " ");
        json.put("modelViewName", modelViewName);
        String povGroupMember = "2014 January Actual";
        def url;
        def response;
        String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
applications/" + appName + "/povs/"
                                       + povGroupMember.trim().replaceAll("
", "%20") + "/ruleBalance";
        urlString = urlString + "?" + "queryParameter=" + json.toString();
        try {
                url = new URL(urlString);
        } catch (MalformedURLException e) {
                println "Malformed URL. Please pass valid URL"
                System.exit(0);
        }
        response = executeRequest(url, "GET", null, "application/json");
        JSONObject jsonObj = new JSONObject(response);
        int resStatus = jsonObj.getInt("status");
        if(resStatus == 0) {
            println "Rule Balancing ran successfully"
            JSONArray itemsArray = jsonObj.getJSONArray("items");
            println "Details : " + itemsArray.toString()
        } else {
            String details = jsonObj.getString("details");
            println "Rule Balancing failed. Details : " + details
        }
    }
```

Update Dimensions As a Job

Updates one or more dimensions from a dimension text/csv file.

Update Dimensions As a Job runs asynchronously; it immediately returns the job ID and the job status (Running or Failed).

Required Roles

Service Administrator, Power User

REST Resource

POST /epm/rest/{api_version}/fileApplications/{application}/jobs/updateDimension

Note:

Before using the REST resources, you must understand how to access the REST resources and other important concepts. See Implementation Best Practices for EPM Cloud REST APIs. Using this REST API requires prerequisites. See Prerequisites.

Request

Supported Media Types: application/json

The following table summarizes the client request.

Table 24-39 Parameters

Name	Description	Туре	Required	Default
api_version	Version of the API you are developing with	Path	Yes	None
application	Name of the application to update	Path	Yes	None
dataFileName	Dimension Metadata flat file name that has already been uploaded to the Inbox folder; multiple file names can be passed separated by comma or other separator character listed in the stringDelimiter parameter	Payload	Yes	None
stringDelimiter	Separator character to use if different from commas	Payload	No	Comma (,)
acceptableDecrease Percentage	Specifies the percentage difference in member count that is allowed for the operation.	Payload	No	None
	If the new member count from the incoming file is less than the existing member count, this represents the percentage decrease that is allowed. If the percentage is exceeded, then the operation will fail.			
	Use this parameter to safeguard against data loss that can happen during a subsequent cube deploy if one or more dimensions did not get fully updated due to missing data in the input file.			



Example URL and Payload

```
https://<BASE-URL>/epm/rest/<api_version>/fileApplications/BksML12/jobs/
updateDimension{"dataFileName":"input.txt","stringDelimiter":",","acceptableDec
reasePercentage":"5"}
```

Response

Supported Media Types: application/json

Name	Description
details	Task ID, such as BksML12_BksML12_ UpdateDimension_D20160118T051020_bb8_1
status	See Migration Status Codes
statusMessage	Message about the status, such as In Progress
type	Profitability
data	Parameters as key value pairs
links	Detailed information about the link
href	Links to API call
action	The HTTP call type
rel	Relationship type
data	Parameters as key value pairs passed in the request

Example of Response Body

The following shows an example of the response body in JSON format.

Java Sample - UpdateDimensionJob.java for Profitability and Cost Management

Prerequisites: json.jar

Common Functions: See Profitability and Cost Management Common Helper Functions for Java

public void updateDimensionJob() throws Exception {



```
JSONObject json = new JSONObject();
json.put("dataFileName", "Accounts.txt,Activity.txt");
String urlString = serverURL + "/epm/rest/" + apiVersion + "/
fileApplications/" + applicationName + "/updateDimensionJob";
exe4cuteJob(urlString, "POST", json.toString(();
}
```

Note:

In the main method, enter the following statement:

```
restSamplesObj.updateDimensionsJob();
```

cURL Sample - UpdateDimensionJob.sh for Profitability and Cost Management

Common Functions: See Profitability and Cost Management Common Helper Functions for cURL.

```
funcUpdateDimensionJob() {
    dataFileName="Accounts.txt,Activity.txt"
    param="{\"dataFileName\":\"$dataFileName\"}"
    url=$SERVER URL/epm/rest/$API VERSION/fileApplications/$APP NAME/
updateDimensionJob
    funcExecuteRequest "POST" $url "$param" "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [status == -1]; then
       echo "Started Update Dimensions Job successfully"
            funcGetStatus "GET"
    else
       error=`echo $output | jq '.details'`
       echo "Error occurred." $error
    fi
             funcRemoveTempFiles "respHeader.txt" response.txt"
```

Note:

At the end, call this statement along with other statements:

funcUpdateDimensionsJob

Groovy Sample – UpdateDimensionJob.groovy for Profitability and Cost Management Prerequisites: json.jar



Common functions: See Appendix C: Common Helper Functions for Groovy.

```
def updateDimensionsJob() {
    JSONObject json = new JSONObject();
    json.put("dataFileName", "Accounts.txt,Activity.txt");
    String urlString = serverUrl + "/epm/rest/"+ apiVersion + "/
fileApplications/"+ appName + "/updateDimensionJob";
    def url;
    try {
        url = new URL(urlString)
    } catch (MalformedURLException e) {
        println "Malformed URL. Please pass valid URL"
        System.exit(0);
    }
    executeJob(url,"POST",json.toString());
}
```

Note:

In the main method, add the following statement:

```
restSamplesObj.updateDimensionJob();
```

25 Narrative Reporting REST APIs

You can use the **REST APIs for Narrative Reporting** to work with Narrative Reporting artifacts, report packages, report snapshots, and reports.

You can use the REST APIs for Narrative Reporting to execute these actions:

- Files
 - Download a file from the temporary repository or to the Library.
 - Upload a temporary file to the Narrative Reporting repository.
- Jobs
 - Start a new Narrative Reporting job for asynchronous execution by the service.
 - Get a Narrative Reporting job's status that provides links to the job results when the job is complete.
- Reports
 - You can get the corresponding Report information
 - You can get the global point of view selections and member suggestions for the Report
 - You can get the required member selection prompts for the Report
- Books
 - You can get the corresponding Book information
 - You can get the global point of view selections and member suggestions for Book
- Bursting Definitions
 - You can view the Bursting Definitions and their content
 - You can execute the Bursting Definition file



26

Enterprise Data Management Cloud REST APIs

Use the REST APIs for Enterprise Data Management Cloud to work with applications, files, jobs, requests, and views.



A Common Helper Functions for Java

This appendix shows the common helper functions for Java for the EPM REST APIs.

Note: The userName variable uses the format <domain>.<username>. See Authentication.

```
/*
    File: PbcsRestSamples.java - Created on Feb 19, 2015
    Copyright (c) 2015 Oracle Corporation. All Rights Reserved.
    This software is the proprietary information of Oracle.
*/
import java.io.BufferedInputStream;
import java.io.BufferedReader;
import java.io.DataOutputStream;
import java.io.File;
import java.io.FileInputStream;
import java.io.FileOutputStream;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStreamWriter;
import java.net.HttpURLConnection;
import java.net.URL;
import java.util.Scanner;
import org.json.JSONArray;
import org.json.JSONObject;
/*
* PBCS Rest Samples.
* The userName variable uses the format <domain>.<username>.
*/
public class PbcsRestSamples{
   private String userName; // PBCS user name
   // IBCS user name
// PBCS user password;
private String serverUrl;
private String apiVersion;
developing/compilier;
// Version of til
                                       // Version of the PBCS API that you
are developing/compiling with.
   private String applicationName; // PBCS application used in this sample
    public static void main(String[] args) {
        try {
            PbcsRestSamples samples = new
PbcsRestSamples("epm default cloud admin", "epm cloud", "https://
<SERVICE NAME>-<TENANT NAME>.<SERVICE TYPE>.<dcX>.oraclecloud.com/",
"11.1.2.3.600", "Vision");
            samples.integrationScenarioImportMetadataIntoApplication();
            samples.integrationScenarioImportDataRunCalcCopyToAso();
samples.integrationScenarioExportMetadataAndDataAndDownloadFiles();
```

```
samples.integrationScenarioRemoveUnnecessaryFiles();
            samples.integrationScenarioExportDataAndDownloadFiles();
            samples.integrationScenarioRefreshTheApplication();
        } catch (Throwable x) {
            System.err.println("Error: " + x.getMessage());
        }
    }
    public PbcsRestSamples (String userName, String password, String
serverUrl, String apiVersion, String applicationName) throws Exception {
        this.userName = userName;
        this.password = password;
        this.serverUrl = serverUrl;
        this.apiVersion = apiVersion;
        this.applicationName = applicationName;
    }
    11
    // BEGIN - Integration scenarios.
    11
   public void integrationScenarioImportMetadataIntoApplication() throws
Exception {
        uploadFile("accounts.zip");
        executeJob("IMPORT_METADATA", "accountMetadata",
"{importZipFileName:accounts.zip}");
        executeJob("CUBE REFRESH", null, null);
    l
   public void integrationScenarioImportDataRunCalcCopyToAso() throws
Exception {
        uploadFile("data.csv");
        executeJob("IMPORT DATA", "loadingqldata",
"{importFileName:data.csv}");
        executeJob("CUBE REFRESH", null, null);
        executeJob("PLAN TYPE MAP", "CampaignToReporting",
"{clearData:false}");
    }
    public void integrationScenarioExportMetadataAndDataAndDownloadFiles()
throws Exception {
        executeJob("EXPORT METADATA", "exportentitymetadata",
"{exportZipFileName:entitydata.zip}");
        executeJob("EXPORT DATA", "Forecastdata",
"{exportFileName:forecastdata.zip}");
        listFiles();
        downloadFile("entitydata.zip");
        downloadFile("forecastdata.zip");
    }
    public void integrationScenarioRemoveUnnecessaryFiles() throws Exception {
        listFiles();
        deleteFile("entitymetadata.csv");
        deleteFile("forecastdata.csv");
    }
    public void integrationScenarioExportDataAndDownloadFiles() throws
```

```
Exception {
        executeJob("EXPORT DATA", "entitydata",
"{exportFileName:entitydata.zip}");
        executeJob("EXPORT DATA", "forecastdata",
"{exportFileName:forecastdata.zip}");
        listFiles();
        downloadFile("entitydata.zip");
        downloadFile("forecastdata.zip");
    }
    public void integrationScenarioRefreshTheApplication() throws Exception {
        uploadFile("accounts.zip");
        executeJob("IMPORT METADATA", "accountMetadata",
"{importZipFileName:accounts.zip}");
        executeJob("CUBE REFRESH", null, null);
    }
    public void integrationScenarioCloneServiceInstance() throws Exception {
        // Part 1 : Change serverUrl, username, password, apiVersion
variables values to match those of first environment
        // Download file from source instance.
        // Comment out all lines below Part 2
        // Uncomment the below line for the first step.
        // downloadFile("Artifact Snapshot");
        // Part 2 : Change serverUrl, username, password, apiVersion to match
those of second environment.
        // Clone the service instance.
        // Comment out code for download file.
        // Uncomment below lines
        recreateService("PBCS");
        deleteFile("Artifact Snapshot");
        uploadFile("Artifact Snapshot.zip");
        importSnapshot("Artifact Snapshot");
    }
    11
    // END - Integration scenarios.
    11
    11
    // BEGIN - Methods that invoke REST API
    11
    11
    // Common Helper Methods
    11
    private String getStringFromInputStream(InputStream is) {
        BufferedReader br = null;
        StringBuilder sb = new StringBuilder();
        String line;
        try {
            br = new BufferedReader(new InputStreamReader(is));
            while ((line = br.readLine()) != null) {
                sb.append(line);
            }
```

```
} catch (IOException e) {
            e.printStackTrace();
        } finally {
            if (br != null) {
                try {
                    br.close();
                } catch (IOException e) {
                    e.printStackTrace();
                }
            }
        }
        return sb.toString();
    }
    private String executeRequest(String urlString, String requestMethod,
String payload, String contentType) throws Exception {
        HttpURLConnection connection = null;
        try {
            URL url = new URL(urlString);
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod(requestMethod);
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization", "Basic " + new
sun.misc.BASE64Encoder().encode((userName + ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", contentType);
            if (payload != null) {
                OutputStreamWriter writer = new
OutputStreamWriter(connection.getOutputStream());
                writer.write(payload);
                writer.flush();
            }
            int status = connection.getResponseCode();
            if (status == 200 || status == 201) {
                return getStringFromInputStream(connection.getInputStream());
            }
            throw new Exception ("Http status code: " + status);
        } finally {
            if (connection != null)
                connection.disconnect();
        }
    }
   private void getJobStatus(String pingUrlString, String methodType) throws
Exception {
        boolean completed = false;
        while (!completed) {
            String pingResponse = executeRequest(pingUrlString, methodType,
null, "application/x-www-form-urlencoded");
            JSONObject json = new JSONObject(pingResponse);
            int status = json.getInt("status");
            if (status == -1) {
                try {
```

```
System.out.println("Please wait...");
                    Thread.sleep(20000);
                } catch (InterruptedException e) {
                    completed = true;
                    throw e;
                ļ
            }
            else {
                if (status > 0) {
                    System.out.println("Error occurred: " +
json.getString("details"));
                }
                else {
                    System.out.println("Completed");
                completed = true;
            }
        }
    }
    private void getMigrationJobStatus(String pingUrlString, String
methodType) throws Exception {
        boolean completed = false;
        while (!completed) {
            String pingResponse = executeRequest(pingUrlString, methodType,
null, "application/x-www-form-urlencoded");
            JSONObject json = new JSONObject(pingResponse);
            int status = json.getInt("status");
            if (status == -1) {
                try {
                    System.out.println("Please wait...");
                    Thread.sleep(20000);
                } catch (InterruptedException e) {
                    completed = true;
                    throw e;
                }
            1
            else {
                if (status == 1) {
                    System.out.println("Error occured");
                    JSONArray itemsArray =
json.getJSONArray("items");
                    JSONObject jObj = null;
                    if(itemsArray.length() <= 0){</pre>
                        System.out.println(json.getString("details"));
                    }else{
                    for (int i=0; i < itemsArray.length(); i++) {</pre>
                        jObj = (JSONObject)itemsArray.get(i);
                        String source = jObj.getString("source");
                        String destination = jObj.getString("destination");
                        String taskURL = null;
                        JSONArray lArray = jObj.getJSONArray("links");
                        for (int j = 0; j < lArray.length(); j++) {
                            JSONObject arr = lArray.getJSONObject(j);
                             if (!JSONObject.NULL.equals(arr) && !
JSONObject.NULL.equals(arr.get("rel")) && arr.get("rel").equals("Job
```

```
Details")) {
                                taskURL = (String) arr.get("href");
                                break;
                            }
                        }
                        System.out.println("Details:");
                        System.out.println("Source: " + source);
                        System.out.println("Destination: "+ destination);
                        boolean errorsCompleted = false;
                        String currentMessageCategory = "";
                        String nextPingURL = taskURL;
                        while(!errorsCompleted) {
                            String nextPingResponse =
executeRequest(nextPingURL, "GET", null, "application/x-www-form-urlencoded");
                            JSONObject jsonObj = new
JSONObject(nextPingResponse);
                            int status1 = jsonObj.getInt("status");
                            if (status1 == 0) {
                                JSONArray artifactArray =
jsonObj.getJSONArray("items");
                                JSONObject jRes = null;
                                 for(int k=0; k < artifactArray.length(); k++) {</pre>
                                     jRes = (JSONObject)artifactArray.get(k);
                                     String artifact =
jRes.getString("artifact").toString();
                                     String msgCategory =
jRes.getString("msgCategory").toString();
                                     String msgText =
jRes.getString("msgText").toString();
                                     if(currentMessageCategory.isEmpty() || !
currentMessageCategory.equals(msgCategory)) {
                                        currentMessageCategory = msgCategory;
System.out.println(currentMessageCategory);
                                     }
                                     System.out.println(artifact +" - " +
msgText);
                                nextPingURL = "";
                                JSONArray nextLinks =
jsonObj.getJSONArray("links");
                                for (int j = 0; j < nextLinks.length(); j++) {
                                     JSONObject nextArray =
nextLinks.getJSONObject(j);
                                     if (!JSONObject.NULL.equals(nextArray)
&& !JSONObject.NULL.equals(nextArray.get("rel")) &&
nextArray.get("rel").equals("next")) {
                                         nextPingURL = (String)
nextArray.get("href");
                                        break;
                                     }
                                 }
                                if(nextPingURL.isEmpty())
                                     errorsCompleted = true;
                             }else if(status1 > 0){
                                System.out.println("Error occured while
```

```
fetching error details: "+ jsonObj.getString("details"));
                                errorsCompleted = true;
                            }
                        }
                    }
                    }
                }else if(status == 0) {
                    System.out.println("Completed");
                completed = true;
            }
        }
    }
   public String fetchPingUrlFromResponse(String response, String retValue)
throws Exception {
        String pingUrlString = null;
        JSONObject jsonObj = new JSONObject(response);
        int resStatus = jsonObj.getInt("status");
        if (resStatus == -1) {
            JSONArray lArray = jsonObj.getJSONArray("links");
            for (int i = 0; i < lArray.length(); i++) {</pre>
                JSONObject arr = lArray.getJSONObject(i);
                if (arr.get("rel").equals(relValue))
                    pingUrlString = (String)
arr.get("href");
        }
        return pingUrlString;
    }
    11
    // END - Common Helper Methods
    11
    11
    // BEGIN - List all the versions in PBCS
    11
    public void getLCMVersions() throws Exception {
        String urlString = String.format("%s/interop/rest", serverUrl);
        String response = executeRequest(urlString, "GET", null,
"application/x-www-form-urlencoded");
        JSONObject json = new JSONObject(response);
        int resStatus = json.getInt("status");
        if (resStatus == 0) {
            JSONArray fileList = json.getJSONArray("items");
            System.out.println("List of files are :");
            JSONObject jObj = null;
            for(int i=0; i<fileList.length(); i++){0) {</pre>
                jObj = (JSONObject)fileList.get(i);
                System.out.println("Version :" + jObj.getString("version"));
                System.out.println("Lifecycle :" +
jObj.getString("lifecycle"));
                System.out.println("Latest :" + jObj.getString("latest"));
                System.out.println("Link :" + ((JSONObject) ((JSONArray)
jObj.getJSONArray("links")).get(0)).getString("href") + "\n");
            }
```

```
}
    }
    //
    // END - List all the versions in PBCS
    11
    11
    // BEGIN - Get application snapshot details
    11
   public void getApplicationSnapshotDetails(String snapshotName) throws
Exception {
        String urlString = String.format("%s/interop/rest/%s/
applicationsnapshots/%s", serverUrl, apiVersion, snapshotName);
        String response = executeRequest(urlString, "GET", null,
"application/x-www-form-urlencoded");
        JSONObject json = new JSONObject(response);
        int resStatus = json.getInt("status");
        if (resStatus == 0) {
            System.out.println("Application details :");
            JSONArray itemsArray = json.getJSONArray("items");
            JSONObject item = (JSONObject) itemsArray.get(0);
            System.out.println("Application snapshot name : " +
item.getString("name"));
            System.out.println("Application snapshot type : " +
item.getString("type"));
            System.out.println("Can be exported flag : " +
item.getString("canExport"));
            System.out.println("Can be imported flag : " +
item.getString("canImport"));
            System.out.println("Can be uploaded flag : " +
item.getString("canUpload"));
            System.out.println("Can be downloaded flag : " +
item.getString("canDownload"));
            JSONArray linksArray = json.getJSONArray("links");
            JSONObject jObj = null;
            System.out.println("Services details :");
            for(int i=0; i < linksArray.length(); i++) {</pre>
                jObj = (JSONObject)linksArray.get(i);
                System.out.println("Service :" + jObj.getString("rel"));
                System.out.println("URL :" + jObj.getString("href"));
                System.out.println("Action :" + jObj.getString("action") +
"\n");
            }
        }
    }
    11
    // END - Get application snapshot details
    11
    11
    // BEGIN - List all the files in PBCS
    //
    public void listFiles() throws Exception {
        String urlString = String.format("%s/interop/rest/%s/
```

```
applicationsnapshots", serverUrl, apiVersion);
        String response = executeRequest(urlString, "GET", null,
"application/x-www-form-urlencoded");
        JSONObject json = new JSONObject(response);
        int resStatus = json.getInt("status");
        if (resStatus == 0) {
            if (json.get("items").equals(JSONObject.NULL))
                System.out.println("No files found");
            else {
                System.out.println("List of files :");
                JSONArray itemsArray = json.getJSONArray("items");
                JSONObject jObj = null;
                for (int i=0; i < itemsArray.length(); i++) {</pre>
                    jObj = (JSONObject)itemsArray.get(i);
                    System.out.println(jObj.getString("name"));
                }
            }
        }
    }
    11
    // END - List all the files in PBCS
    11
    11
    // BEGIN - Delete a file in PBCS
    11
    public void deleteFile(String fileName) throws Exception {
        String urlString = String.format("%s/interop/rest/%s/
applicationsnapshots/%s", serverUrl, apiVersion, fileName);
        String response = executeRequest(urlString, "DELETE", null,
"application/x-www-form-urlencoded");
        JSONObject json = new JSONObject(response);
        int resStatus = json.getInt("status");
        if (resStatus == 0)
            System.out.println("File deleted successfully");
        else
            System.out.println("Error deleting file : " +
json.getString("details"));
   }
    11
    // END - Delete a file in PBCS
    11
    11
    // BEGIN - Download a file from PBCS
    11
    public void downloadFile(String fileName) throws Exception {
        HttpURLConnection connection = null;
        InputStream inputStream = null;
        FileOutputStream outputStream = null;
        try {
            URL url = new URL(String.format("%s/interop/rest/%s/
applicationsnapshots/%s/contents", serverUrl, apiVersion, fileName));
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod("GET");
```

```
connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization", "Basic " + new
sun.misc.BASE64Encoder().encode((userName + ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", "application/x-www-
form-urlencoded");
            int status = connection.getResponseCode();
            if (status == 200) {
                if (connection.getContentType() != null &&
connection.getContentType().equals("application/json")) {
                    JSONObject json = new
JSONObject(getStringFromInputStream(connection.getInputStream()));
                    System.out.println("Error downloading file : " +
json.getString("details"));
                } else {
                    inputStream = connection.getInputStream();
                    outputStream = new FileOutputStream(new File(fileName));
                    int bytesRead = -1;
                    byte[] buffer = new byte[5 * 1024 * 1024];
                    while ((bytesRead = inputStream.read(buffer)) != -1)
                        outputStream.write(buffer, 0, bytesRead);
                    System.out.println("File download completed.");
                }
            } else {
                throw new Exception("Http status code: " + status);
        } finally {
            if (connection != null)
                connection.disconnect();
            if (outputStream != null)
                outputStream.close();
            if (inputStream != null)
                inputStream.close();
        }
    }
    11
    // END - Download a file from PBCS
    11
    11
    // BEGIN - Upload a file to PBCS
    11
    public void uploadFile(String fileName) throws Exception {
        final int DEFAULT CHUNK SIZE = 50 * 1024 * 1024;
        InputStream fis = null;
        byte[] lastChunk = null;
        long totalFileSize = new File(fileName).length(), totalbytesRead = 0;
        boolean isLast = false, status = true;
        Boolean isFirst = true;
        int packetNo = 1, lastPacketNo = (int) (Math.ceil(totalFileSize /
(double) DEFAULT CHUNK SIZE));
        try {
            fis = new BufferedInputStream(new FileInputStream(fileName));
```

```
while (totalbytesRead < totalFileSize && status) {</pre>
                int nextChunkSize = (int) Math.min(DEFAULT CHUNK SIZE,
totalFileSize - totalbytesRead);
                if (lastChunk == null) {
                    lastChunk = new byte[nextChunkSize];
                    totalbytesRead += fis.read(lastChunk);
                    if (packetNo == lastPacketNo)
                        isLast = true;
                    status = sendFileContents(isFirst, isLast, lastChunk,
fileName);
                    isFirst=false;
                    packetNo = packetNo + 1;
                    lastChunk = null;
                }
            System.out.println("Uploaded successfully");
        } finally {
            if (fis != null)
                fis.close();
        }
    }
    private boolean sendFileContents(Boolean isFirst, boolean isLast, byte[]
lastChunk, String fileName) throws Exception {
        HttpURLConnection connection = null;
        try {
            URL url = new URL(String.format("%s/interop/rest/%s/
applicationsnapshots/%s/contents?q={chunkSize:%d,isFirst:%b,isLast:%b}",
                    serverUrl, apiVersion, fileName, lastChunk.length,
isFirst, isLast));
            connection = (HttpURLConnection) url.openConnection();
            connection.setRequestMethod("POST");
            connection.setInstanceFollowRedirects(false);
            connection.setDoOutput(true);
            connection.setUseCaches(false);
            connection.setDoInput(true);
            connection.setRequestProperty("Authorization", "Basic " + new
sun.misc.BASE64Encoder().encode((userName + ":" + password).getBytes()));
            connection.setRequestProperty("Content-Type", "application/octet-
stream");
            DataOutputStream wr = new
DataOutputStream(connection.getOutputStream());
            wr.write(lastChunk);
            wr.flush();
            int statusCode = connection.getResponseCode();
            String status =
getStringFromInputStream(connection.getInputStream());
            if (statusCode == 200 && status != null) {
                int commandStatus = getCommandStatus(status);
                if (commandStatus == 0) {
                    isFirst = false;
                    return true;
                }else if(commandStatus == -1 && isLast){
```

```
getJobStatus(fetchPingUrlFromResponse(status, "Job
Status"), "GET");
                }
            }
            return false;
        } finally {
            if (connection != null)
                connection.disconnect();
        }
    }
    public int getCommandStatus(String response) throws Exception {
        JSONObject json = new JSONObject(response);
        if (!JSONObject.NULL.equals(json.get("status")))
            return json.getInt("status");
        else
            return Integer.MIN VALUE;
    }
    11
    // END - Upload a file to PBCS
    11
    11
    // BEGIN - Import an application snapshot
    11
    public void importSnapshot(String applicationSnapshotName) throws
Exception {
        JSONObject params = new JSONObject();
        params.put("type","import");
        String urlString = String.format("%s/interop/rest/%s/
applicationsnapshots/%s/migration?q=%s", serverUrl, apiVersion,
applicationSnapshotName, params.toString());
        String response = executeRequest(urlString, "POST", null,
"application/x-www-form-urlencoded");
        System.out.println("Import started successfully");
        getMigrationJobStatus(fetchPingUrlFromResponse(response, "Job
Status"),"POST");
   }
    11
    // END - Import an application snapshot
    11
    11
    // BEGIN - Export an application snapshot
    11
   public void exportSnapshot(String applicationSnapshotName) throws
Exception {
        JSONObject params = new JSONObject();
        params.put("type", "export");
        String urlString = String.format("%s/interop/rest/%s/
applicationsnapshots/%s/migration?q=%s", serverUrl, apiVersion,
applicationSnapshotName, params.toString());
        String response = executeRequest(urlString, "POST", null,
"application/x-www-form-urlencoded");
        System.out.println("Export started successfully");
```

```
getMigrationJobStatus(fetchPingUrlFromResponse(response, "Job
Status"), "POST");
   }
   11
    // END - Export an application snapshot
    11
   11
// BEGIN - Provide Feedback
    //
    public void provideFeedback(String description) throws Exception {
        JSONObject params = new JSONObject();
        JSONObject config = new JSONObject();
        config.put("URL", serverUrl);
        params.put("configuration", config);
        params.put("description", description);
        String urlString = String.format("%s/interop/rest/%s/feedback",
serverUrl, apiVersion);
        String response = executeRequest(urlString, "POST",
params.toString(), "application/json");
        JSONObject json = new JSONObject(response);
        int resStatus = json.getInt("status");
        if (resStatus == 0) {
            System.out.println("Feedback successful");
        } else {
            System.out.println("Error occured: " + json.getString("details"));
        }
    }
    11
    // END - Provide Feedback
    11
    11
    // BEGIN - Reset services
   11
    public void hardReset(String comment) throws Exception {
        Scanner in = new Scanner(System.in);
        System.out.println("Are you sure you want to restart the service
instance (yes/no): no ?[Press Enter]");
        String s = in.nextLine();
        if (!s.equals("yes")) {
            System.out.println("User cancelled the recreate command");
            System.exit(0);
        }
        JSONObject params = new JSONObject();
        params.put("comment", java.net.URLEncoder.encode(comment));
        String urlString = String.format("%s/interop/rest/%s/services/PBCS/
resetservice", serverUrl, apiVersion);
        String response = executeRequest(urlString, "POST",
params.toString(), "application/x-www-form-urlencoded");
       waitForCompletion(fetchPingUrlFromResponse(response, "Job Status"));
    }
    //
```

```
// END - Reset services
    11
   11
    // BEGIN - Execute a Job (EXPORT DATA, EXPORT METADATA, IMPORT DATA,
IMPORT METADATA, CUBE REFRESH, ...)
   11
   public void executeJob(String jobType, String jobName, String parameters)
throws Exception {
        String urlString = String.format("%s/HyperionPlanning/rest/%s/
applications/%s/jobs", serverUrl, apiVersion, applicationName);
        JSONObject payload = new JSONObject();
        payload.put("jobName",jobName);
        payload.put("jobType",jobType);
        payload.put("parameters", new JSONObject(parameters));
        String response = executeRequest(urlString, "POST",
payload.toString(), "application/json");
        System.out.println("Job started successfully");
        getJobStatus(fetchPingUrlFromResponse(response, "self"),
"GET");
   }
    11
   // END - Execute a Job (EXPORT DATA, EXPORT METADATA, IMPORT DATA,
IMPORT METADATA, CUBE REFRESH, ...)
   11
}
```

Note:

Note on Proxy Setting: In case of proxies, set the proxy host and port as the system arguments.

B CSS Common Helper Functions for Java

This appendix shows the CSS common helper functions for Java for the EPM REST APIs.

Prerequisites: json.jar

Note on Proxy Setting: In case of proxies, set the proxy host and port as the system arguments.

```
import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStreamWriter;
import java.io.UnsupportedEncodingException;
import java.net.HttpURLConnection;
import java.net.URI;
import java.net.URLEncoder;
import java.nio.charset.Charset;
import java.util.HashMap;
import java.util.Map;
import java.util.Set;
import javax.xml.bind.DatatypeConverter;
import org.json.JSONArray;
import org.json.JSONObject;
public class CSSRESTSamples {
   private static String userName;
   private static String password;
   private String serverUrl;
   private String apiVersion;
    public static void main(String[] args) {
        try {
CSSRESTSamples samples = new CSSRESTSamples("<DOMAINNAME.USERNAME>",
"<PASSWORD>", "<SERVICE URL>", "v1");
           // Call sample APIs.
            // samples.addUsers("AddUser2.csv", "test123$", false);
            // samples.removeUsers("test2.csv");
            // samples.assignRole("test3.csv", "Power User");
            // samples.unassignRole("test4.csv", "Viewer");
            // samples.addUsersToGroup("test5.csv", "TestGroup1");
            // samples.removeUsersFromGroup("test6.csv", "TestGroup2");
            // samples.generateRoleAssignmentReport("JavaSampleReport.csv",
"ServiceUsers");
            // samples.generateUserGroupReport("UserGroupReport.csv");
            // samples.addUserToGroups("Group.csv", "user1");
            // samples.removeUserFromGroups("groups.csv", "joe");
            // samples.addGroups("Group1.csv");
```



```
// samples.removeGroups("DeleteGroup1.csv");
            // samples.generateInvalidLoginReport("2021-06-01",
"2021-06-10", "invalidLoginReport141.csv");
            // samples.generateRoleAssignmentAuditReport("2021-06-01",
"2021-06-10", "roleAssignmentaudit 14778.csv");
            // samples.updateUsers("updateuser.csv");
        } catch (Throwable x) {
            System.err.println("Error: " + x.getMessage());
        }
    }
    public CSSRESTSamples (String userName, String password, String serverUrl,
String apiVersion) throws Exception {
        this.userName = userName;
        this.password = password;
        this.serverUrl = serverUrl;
        this.apiVersion = apiVersion;
    }
    public void addUsers (String fileName, String userPassword, boolean
resetPassword) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("userpassword", userPassword);
            reqParams.put("resetpassword", resetPassword + "");
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeUsers(String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
```

```
Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "DELETE");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
       }
    }
    public void assignRole(String fileName, String roleName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ASSIGN ROLE");
            reqParams.put("rolename", roleName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void unassignRole(String fileName, String roleName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "UNASSIGN ROLE");
            reqParams.put("rolename", roleName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
```

```
System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void addUsersToGroup(String fileName, String groupName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ADD USERS TO GROUP");
            reqParams.put("groupname", groupName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeUsersFromGroup(String fileName, String groupName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "REMOVE USERS FROM GROUP");
            reqParams.put("groupname", groupName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
```



```
public void addUserToGroups(String fileName, String userName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ADD USER TO GROUPS");
            reqParams.put("username", userName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeUserFromGroups(String fileName, String userName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "REMOVE USER FROM GROUPS");
            reqParams.put("username", userName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
       }
    }
   public void generateRoleAssignmentReport(String fileName, String
userType) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/roleassignmentreport";
            Map<String, String> reqHeaders = new HashMap<String, String>();
```

```
reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
                    reqParams.put("usertype", userType);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void generateUserGroupReport(String fileName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/usergroupreport";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void addGroups(String fileName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
```

```
"POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeGroups(String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "DELETE");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void generateInvalidLoginReport(String fromDate, String
toDate,String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/invalidloginreport";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("from date", fromDate);
            regParams.put("to date", toDate);
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
```



```
public void generateRoleAssignmentAuditReport(String fromDate, String
toDate,String fileName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/roleassignmentauditreport";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("from date", fromDate);
            regParams.put("to date", toDate);
            reqParams.put("filename", fileName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void updateUsers(String fileName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "UPDATE USERS");
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    private static class CSSRESTHelper {
       public static final String REST CALL STATUS = "REST CALL STATUS";
       public static final String REST CALL RESPONSE = "REST CALL RESPONSE";
```



}

```
private static Map<String, String> callRestApi (Map context, String
url, Map<String, String> requestHeaders,
                Map<String, String> requestParams, String methodType) {
            HttpURLConnection urlConnection = null;
            Map<String, String> restResult = new HashMap<String, String>();
            restResult.put(REST_CALL_STATUS, "-1");
            boolean isPostMethod = "POST".equalsIgnoreCase(methodType) ||
"PUT".equalsIgnoreCase(methodType);
            try {
                URI baseUri = new URI(url);
                URI uri = null;
                String reqParams = (requestParams != null ?
buildRequestParams(context, requestParams, isPostMethod)
                        : null);
                if (isPostMethod) {
                    uri = new URI(baseUri.getScheme(),
baseUri.getAuthority(), baseUri.getPath(), null, null);
                } else {
                    uri = new URI(baseUri.getScheme(),
baseUri.getAuthority(), baseUri.getPath(), regParams, null);
                }
                urlConnection = (HttpURLConnection)
uri.toURL().openConnection();
                urlConnection.setRequestMethod(methodType);
                if (requestHeaders != null) {
                    Set<String> requestHeaderKeys = requestHeaders.keySet();
                    for (String requestHeaderKey : requestHeaderKeys) {
                        urlConnection.setRequestProperty(requestHeaderKey,
requestHeaders.get(requestHeaderKey));
                    }
                }
                urlConnection.setUseCaches(false);
                urlConnection.setDoOutput(true);
                urlConnection.setDoInput(true);
                if (isPostMethod) {
                    OutputStreamWriter writer = new
OutputStreamWriter(urlConnection.getOutputStream(),
                            Charset.defaultCharset());
                    writer.write(reqParams);
                    writer.flush();
                }
                if (!isPostMethod) {
                    urlConnection.connect();
                }
                int status = urlConnection.getResponseCode();
                restResult.put(REST CALL STATUS, String.valueOf(status));
                String response = readResponse(context,
                        (status >= 400 ? urlConnection.getErrorStream() :
urlConnection.getInputStream()));
                restResult.put(REST CALL RESPONSE, response);
```

```
} catch (Exception e) {
                restResult.put(REST CALL RESPONSE, e.getMessage());
            } finally {
                if (urlConnection != null) {
                    urlConnection.disconnect();
            }
            return restResult;
        }
        private static String buildRequestParams (Map context, Map<String,
String> requestParams, boolean isPostMethod) {
            String reqParams = null;
            try {
                StringBuilder result = new StringBuilder();
                Set<String> reqParamKeys = requestParams.keySet();
                boolean first = true;
                for (String reqParamKey : reqParamKeys) {
                    if (first)
                        first = false;
                    else
                        result.append("&");
                    String regParamValue = requestParams.get(regParamKey);
                    result.append((isPostMethod ?
URLEncoder.encode(reqParamKey, "UTF-8") : reqParamKey));
                    result.append("=");
                    result.append((isPostMethod ?
URLEncoder.encode(reqParamValue, "UTF-8") : reqParamValue));
                }
                reqParams = result.toString();
            } catch (UnsupportedEncodingException e) {
                e.printStackTrace();
            }
            return reqParams;
        }
        private static String readResponse(Map context, InputStream
urlInStream) {
            BufferedReader br = null;
            String response = "";
            try {
                String line;
                br = new BufferedReader(new InputStreamReader(urlInStream,
Charset.defaultCharset()));
                while ((line = br.readLine()) != null) {
                    response += line;
                }
            } catch (Exception e) {
                response += e.getMessage();
            } finally {
                if (br != null) {
                    try {
                        br.close();
                    } catch (IOException e) {
                        e.printStackTrace();
                    }
```

```
}
            return response;
        }
        private static String getCSSRESTJobUrlFromResponse(String response) {
            String jobUrl = "";
            try {
                JSONObject jsonResponse = new JSONObject(response);
                JSONArray links = (JSONArray) jsonResponse.get("links");
                JSONObject jobStatusLink = (JSONObject) links.get(1);
                jobUrl = jobStatusLink.get("href").toString();
            } catch (Exception ex) {
                ex.printStackTrace();
            return jobUrl;
        }
        private static String getCSSRESTJobStatusFromResponse(String
response) {
            String jobStatus = "";
            try {
                JSONObject jsonResponse = new JSONObject(response);
                jobStatus = jsonResponse.get("status").toString();
            } catch (Exception ex) {
                ex.printStackTrace();
            return jobStatus;
        }
        private static String getCSSRESTJobCompletionStatus (Map<String,
String> restResult, Map<String, String> reqHeader) {
            String completionStatus = "";
            try {
                String restStatus =
restResult.get(CSSRESTHelper.REST CALL STATUS);
                if (restStatus.equalsIgnoreCase("200")) {
                    String jobUrl =
getCSSRESTJobUrlFromResponse(restResult.get(CSSRESTHelper.REST CALL RESPONSE))
;
                    String restJobStatus = "-1";
                    Map<String, String> jobStatusResult = null;
                    while (restJobStatus.equalsIgnoreCase("-1")) {
                        jobStatusResult = CSSRESTHelper.callRestApi(new
HashMap(), jobUrl, reqHeader, null, "GET");
                        String jobStatusStatus =
jobStatusResult.get(CSSRESTHelper.REST CALL STATUS);
                        if (jobStatusStatus.equalsIgnoreCase("200")) {
                            restJobStatus = getCSSRESTJobStatusFromResponse(
jobStatusResult.get(CSSRESTHelper.REST CALL RESPONSE));
                        }
                        Thread.sleep(1000);
                    }
                    completionStatus =
jobStatusResult.get(CSSRESTHelper.REST CALL RESPONSE);
```



C Common Helper Functions for cURL

This appendix shows the common helper functions for cURL for the EPM Cloud REST APIs.

Note: the USERNAME variable is < domain>.< username>. See Authentication.

```
#!/bin/sh
SERVER URL="https://<BASE-URL>"
USERNAME = < username >
PASSWORD=<password>
APP NAME="Vision"
API VERSION="11.1.2.3.600"
funcRemoveTempFiles() {
    for var in "$@"
    do
        if [ -f $var ]; then
            rm $var
        fi
    done
}
funcPrintErrorDetails() {
    contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr -d
[:space:]
    if [ ! -z $contentType ] && [[ $contentType = *"application/json"* ]];
then
        output=`cat $1`
        error=`echo $output | jq '.details'`
        echo "Error details: " $error
    fi
}
funcExecuteRequest() {
    if [ ! -z "$4" ]; then
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $4" -d $3 $2`
    else
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $3" $2`
    fi
    if [ $statusCode != 200 ]; then
        echo "Error executing request"
        if [ $statusCode != 000 ]; then
            echo "Response error code : " $statusCode
            funcPrintErrorDetails "response.txt"
            funcRemoveTempFiles "respHeader.txt" "response.txt"
        fi
        exit 0
    fi
```

```
}
funcGetStatus() {
   output=`cat response.txt`
    count=`echo $output | jq '.links | length'`
    i=0
   pingUrl=""
   while [ $i -lt $count ]; do
        rel=`echo $output | jq '.links['$i'].rel'`
        rel=`echo "$rel" | tr -d "\""`
        if [ "$rel" == "Job Status" ]; then
                pingUrl=`echo $output | jq '.links['$i'].href'`
                pingUrl=`echo "$pingUrl" | tr -d "\""`
        fi
        i=`expr $i + 1`
    done
    echo $pingUrl
    completed="false"
    while [ $completed != "true" ]; do
        statusCode2=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD"
-o "pingResponse.txt" -H "Content-Type: application/x-www-form-urlencoded"
"$pingUrl"`
        if [ $statusCode2 == 200 ]; then
            status2=`jq '.status' pingResponse.txt`
            if [ $status2 != -1 ]; then
                completed="true"
                echo "Job completed"
            else
                echo "Please wait..."
                sleep 20
            fi
        else
            echo "Please wait..."
            sleep 20
        fi
        funcRemoveTempFiles "pingResponse.txt"
    done
}
funcGetMigrationStatus() {
    output=`cat response.txt`
    count=`echo $output | jq '.links | length'`
   i=0
   pingUrl=""
    while [ $i -lt $count ]; do
        rel=`echo $output | jq '.links['$i'].rel'`
        rel=`echo "$rel" | tr -d "\""`
        if [ "$rel" == "Job Status" ]; then
                pingUrl=`echo $output | jq '.links['$i'].href'`
                pingUrl=`echo "$pingUrl" | tr -d "\""`
        fi
        i=`expr $i + 1`
    done
    echo $pingUrl
    completed="false"
```

```
while [ $completed != "true" ]; do
        statusCode2=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD"
-o "pingResponse.txt" -H "Content-Type: application/x-www-form-urlencoded"
"$pingUrl"`
        if [ $statusCode2 == 200 ]; then
            status2=`jg '.status' pingResponse.txt`
            if [ $status2 == 0 ]; then
                completed="true"
                echo "Job completed"
            elif [ $status2 == 1 ]; then
                output1=`cat pingResponse.txt`
                echo "Error occurred"
                count=`echo $output1 | jq '.items | length'`
                if [ $count == 0 ]; then
                    echo `echo $output1 | jq '.details'`
                else
                    i=0
                    while [ $i -lt $count ]; do
                        echo "Source : " `echo $output1 | jq
'.items['$i'].source'`
                        echo "Destination :" `echo $output1 | jq
'.items['$i'].destination'`
                        firstPing=`echo $output1 | jq
'.items['$i'].links[0].href'`
                        echo ""
                        taskCompleted="false"
                        while [ $taskCompleted != "true" ]; do
                            statusCode3=`curl -X "GET" -s -w "%{http code}" -
u "$USERNAME:$PASSWORD" -o "taskpingResponse.txt" -H "Content-Type:
application/x-www-form-urlencoded" "$firstPing"`
                            echo $statusCode3
                            output2=`cat taskpingResponse.txt`
                            count1=`echo $output2 | jq '.items | length'`
                            j=0
                            currentMessageCategory=""
                            while [ $j -lt $count1 ]; do
                                msgCategory=`echo $output1 | jq
'.items['$i'].msgCategory'`
                                if [ !-z $currentMessageCategory ] ||
[ $currentMessageCategory != $msgCategory ]; then
                                    currentMessageCategory=msgCategory
                                    echo $currentMessageCategory
                                fi
                                echo `echo $output2 | jq
'.items['$i'].artifact'` " - " `echo $output2 | jq '.items['$i'].msgText'`
                                count2=`echo $output | jq '.links | length'`
                                k=0
                                firstPing=""
                                while [ $k -lt $count ]; do
                                    rel=`echo $output2 | jq
'.links['$i'].rel'`
                                    rel=`echo "$rel" | tr -d "\""`
                                    if [ "$rel" == "next" ]; then
                                            firstPing=`echo $output2 | jq
'.links['$i'].href'`
                                            firstPing=`echo "$firstPing" | tr
```



```
-d "\""`
                                    fi
                                    k=`expr $k + 1`
                                done
                                if [ -z $firstPing ]; then
                                    taskCompleted="true"
                                fi
                                j=`expr $j + 1`
                            done
                        done
                        i=`expr $i + 1`
                    done
                fi
            else
                echo "Please wait..."
                sleep 20
            fi
        else
            echo "Please wait..."
            sleep 20
        fi
        funcRemoveTempFiles "pingResponse.txt" "taskpingResponse.txt"
   done
}
funcGetLCMVersions() {
    url=$SERVER URL/interop/rest
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
   output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "List of versions :"
        count=`echo $output | jq '.items | length'`
        i=0
        while [ $i -lt $count ]; do
            echo "Version : " `echo $output | jq '.items['$i'].version'`
            echo "Lifecycle :" `echo $output | jq '.items['$i'].lifecycle'`
            echo "Latest :" `echo $output | jq '.items['$i'].latest'`
            echo "Link :" `echo $output | jq '.items['$i'].links[0].href'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGetLCMVersionDetails() {
   url=$SERVER_URL/interop/rest/$API_VERSION
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
```

```
output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Version $API VERSION details :"
        count=`echo $output | jq '.links | length'`
        i=0
        while [ $i -lt $count ]; do
            echo "Service : " `echo $output | jq '.links['$i'].rel'`
            echo "URL :" `echo $output | jq '.links['$i'].href'`
            echo "Action :" `echo $output | jq '.links['$i'].action'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGetServices() {
    url=$SERVER URL/interop/rest/$API VERSION/services
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Services list :"
        count=`echo $output | jq '.links | length'`
        i=0
        while [ $i -lt $count ]; do
            rel=`echo $output | jq '.links['$i'].rel'`
            rel=`echo "$rel" | tr -d "\""`
            if [ "$rel" != "self" ]; then
                echo "Service : " `echo $output | jq '.links['$i'].rel'`
                echo "URL :" `echo $output | jq '.links['$i'].href'`
                echo "Action :" `echo $output | jq '.links['$i'].action'`
                echo ""
            fi
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcRecreateService() {
   echo "Are you sure you want to recreate the EPM environment (yes/no): no ?
[Press Enter]"
   read toCreate
    if [ $toCreate != "yes" ]; then
        echo "User cancelled the recreate command"
        exit 0
    fi
```

```
url=$SERVER URL/interop/rest/$API VERSION/services/$1/recreate
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == -1 ]; then
        echo "Started recreating the environment successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGetApplicationSnapshotDetails() {
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Application details :"
        echo "Application snapshot name : " `echo $output | jq
'.items[0].name'
        echo "Application snapshot type : " `echo $output | jq
'.items[0].type'
        echo "Can be exported flag : " `echo $output | jq
'.items[0].canExport'`
        echo "Can be imported flag : " `echo $output | jq
'.items[0].canImport'`
        echo "Can be uploaded flag : " `echo $output | jq
'.items[0].canUpload'`
        echo "Can be downloaded flag : " `echo $output | jq
'.items[0].canDownload'`
        count=`echo $output | jq '.links | length'`
        i=0
        echo "Services details :"
        while [ $i -lt $count ]; do
            echo "Service : " `echo $output | jq '.links['$i'].rel'`
            echo "URL :" `echo $output | jq '.links['$i'].href'`
            echo "Action :" `echo $output | jq '.links['$i'].action'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcListFiles() {
```

```
url=$SERVER URL/interop/rest/$API VERSION/applicationsnapshots
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
   list=`cat response.txt | jq 'select(.items != null) | .items[].name'`
    if [[ ! -z $list ]]; then
        echo $list
    else
        echo "No files found"
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcDeleteFile() {
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName
    funcExecuteRequest "DELETE" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Deleted successfully"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcUploadFile() {
    infile=$1
    if [ ! -f $infile ]; then
        echo "File does not exist"
        exit 0
    fi
    encodedFileName=$(echo $infile | sed -f urlencode.sed)
    url="$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/contents?q="
   filename=$( basename $infile)
    filesize=$( stat -c %s $infile)
   bs=52428800
   noOfPackets=$(($((filesize / bs)) + 1))
   uploadedsize=0
   isFirst=true
    count=1
   isLast="false"
    if [ $noOfPackets = 1 ]; then
     isLast="true"
    fi
    tempFile=/u01/temp/$filename
    if [ ! -d "/u01/temp" ]; then
       mkdir /u01/temp
    fi
```



```
while [ $uploadedsize -ne $filesize ]
    do
        skip=$uploadedsize
        temp=$((filesize - uploadedsize))
        if [ $temp -le $bs ]; then
            length=$temp
        else
            length=$bs
        fi
        echo "Skip : $skip"
        echo "Length : $length"
        (
            dd bs=1 skip=$skip count=0 &> /dev/null
            dd bs=$length count=1 of=$tempFile &> /dev/null
        ) < "$infile"
        param=$(echo "{chunkSize=$length,isFirst=$isFirst,isLast=$isLast}" |
sed -f urlencode.sed)
        urlwithparam="$url$param"
        echo $urlwithparam
        statusCode=`curl -X POST -s -w "%{http code}" -T $tempFile -u
"$USERNAME:$PASSWORD" -o "response.txt" -D "respHeader.txt" -H "Content-Type:
application/octet-stream" "$urlwithparam"`
        funcRemoveTempFiles $tempFile
        if [ $statusCode == 200 ]; then
            output=`cat response.txt`
            status=`echo $output | jq '.status'`
            if [ $status -gt 0 ]; then
                error=`echo $output | jq '.details'`
                echo "Error occurred. " $error
                funcRemoveTempFiles "respHeader.txt" "response.txt"
                exit 0
            else if [ $status == -1 ] || [ $isLast == "true" ]; then
                    funcGetStatus "GET"
                fi
            fi
        else
            echo "Error executing request"
            if [ $statusCode != 000 ]; then
                echo "Response error code : " $statusCode
                funcPrintErrorDetails "response.txt"
                funcRemoveTempFiles "respHeader.txt" "response.txt"
            fi
            exit O
        fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
        uploadedsize=$((uploadedsize + length))
        isFirst="false"
        echo "isFirst : $isFirst"
        count=$((count + 1))
        if [ $count = $noOfPackets ]; then
            isLast="true"
        fi
```

```
echo "Uploaded Size : $uploadedsize"
        echo "isLast : $isLast"
    done
    echo "Uploaded File Successfully"
}
funcDownloadFile() {
   filepath="/u01/$1"
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/contents
    statusCode=`curl -X GET -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o $filepath -H "Content-Type: application/x-www-form-urlencoded" -D
respHeader.txt $url`
    if [ $statusCode == 200 ]; then
        contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr -d
[:space:]`
        if [ ! -z $contentType ] && [[ $contentType = *"application/
json"* ]]; then
            output=`cat $filepath`
            error=`echo $output | jq '.details'`
            echo "Error occurred. " $error
            funcRemoveTempFiles $filepath
        else
            fileExtension=`echo $(grep -r "fileExtension: " respHeader.txt |
awk '{print ($2)}') | tr -d [:space:]`
            if [ ! -z $fileExtension ]; then
                if [[ ! $filepath =~ \.$fileExtension$ ]]; then
                    mv $filepath $filepath.$fileExtension
                fi
            fi
            echo "Downloaded file successfully"
        fi
   else
        echo "Error listing files. "
        if [ $statusCode != 000 ]; then
            echo "Response error code : " $statusCode
            funcPrintErrorDetails $filepath
            funcRemoveTempFiles $filepath
        fi
    fi
    funcRemoveTempFiles "respHeader.txt"
}
funcImportSnapshot() {
   param=$(echo "{type:import}" | sed -f urlencode.sed)
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/migration?q=$param
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
```

```
echo "Started importing successfully"
        funcGetMigrationStatus "POST"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcExportSnapshot() {
    param=$(echo "{type:export}" | sed -f urlencode.sed)
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/migration?q=$param
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started exporting succesfully"
        funcGetMigrationStatus "POST"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcProvideFeedback() {
   url=$SERVER URL/interop/rest/$LCM VERSION/feedback
    description=$(echo $1 | sed -f urlencode.sed)
    param="{\"configuration\":
{\"URL\":\"$SERVER URL\"},\"description\":\"$description\"}"
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Feedback successful"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcHardReset() {
   echo "Are you sure you want to restart the service instance (yes/no): no ?
[Press Enter] "
    read toCreate
    if [ $toCreate != "yes" ]; then
        echo "User cancelled the recreate command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$LCM VERSION/services/PBCS/resetservice
```



```
comment=$(echo $1 | sed -f urlencode.sed)
    param="{\"comment\":\"$comment\"}"
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == -1 ]; then
        echo "Started hard reset succesfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGenerateAuditReport() {
   param=$(echo "{type:userauditreport,fileName:$1,since:$2,until:$3}" | sed
-f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/reports?q=$param
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started generating report successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
   fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGenerateProvisionReport() {
    param=$(echo "{type:provisionreport,fileName:$1}" | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/reports?q=$param
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started generating report successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcExecuteJob() {
    url="$SERVER URL/HyperionPlanning/rest/$API VERSION/
applications/$APP NAME/jobs"
    encodedJobName=$(echo $2 | sed -f urlencode.sed)
```



```
if [ ! -z "$3" ]; then
        param="jobType=$1&jobName=$encodedJobName&parameters=$3"
    else
        param="jobType=$1&jobName=$encodedJobName"
    fi
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started executing job successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcIntegrationScenarioImportMetadataIntoApplication() {
    funcUploadFile "DemoApplication HSS Vision.zip"
    funcExecuteJob "IMPORT METADATA" "accountMetadata"
"{importZipFileName=accounts.zip}"
    funcExecuteJob "CUBE_REFRESH" "cubeRefresh"
}
funcIntegrationScenarioImportDataRunCalcCopyToAso() {
    funcUploadFile "data.csv"
    funcExecuteJob "IMPORT DATA" "loadingqldata" "{importFileName=data.csv}"
    funcExecuteJob "CUBE REFRESH","cubeRefresh"
    funcExecuteJob "PLAN_TYPE_MAP" "CampaignToReporting" "{clearData=false}"
}
funcIntegrationScenarioExportMetadataAndDataAndDownloadFiles() {
    funcExecuteJob "EXPORT METADATA" "exportentitymetadata"
"{exportZipFileName=entitydata.zip}"
    funcExecuteJob "EXPORT DATA" "Forecastdata"
"{exportFileName=forecastdata.zip}"
    funcListFiles
    funcDownloadFile "entitydata.zip"
    funcDownloadFile "forecastdata.zip"
}
funcIntegrationScenarioRemoveUnnecessaryFiles() {
    funcListFiles
    funcDeleteFile "entitymetadata.csv"
    funcDeleteFile "forecastdata.csv"
}
funcIntegrationScenarioExportDataAndDownloadFiles() {
    funcExecuteJob "EXPORT DATA" "entitydata"
"{exportFileName:entitydata.zip}"
    funcExecuteJob "EXPORT DATA" "forecastdata"
"{exportFileName:forecastdata.zip}"
    funcListFiles
    funcDownloadFile "entitydata.zip"
```

```
funcDownloadFile "forecastdata.zip"
}
funcIntegrationScenarioRefreshTheApplication() {
    funcUploadFile "accounts.zip"
    funcExecuteJob "IMPORT METADATA" "accountMetadata"
"{importZipFileName:accounts.zip}"
    funcExecuteJob "CUBE REFRESH" "cubeRefresh"
}
funcIntegrationScenarioCloneServiceInstance() {
    # Part 1 : Change SERVER URL, USERNAME, PASSWORD, API VERSION variables
values to match those of first environment
    # Download file from source instance.
    # Comment out all lines below Part 2
    # Uncomment the below line for the first step.
    # funcDownloadFile "Artifact Snapshot"
    # Part 2 : Change SERVER URL, USERNAME, PASSWORD, API VERSION to match
those of second environment.
    # Clone the service instance.
    # Comment out code for download file.
    # Uncomment below lines
    funcRecreateService "PBCS"
    funcDeleteFile "Artifact Snapshot"
    funcUploadFile "Artifact Snapshot.zip"
    funcImportSnapshot "Artifact Snapshot"
}
funcIntegrationScenarioImportMetadataIntoApplication
funcIntegrationScenarioImportDataRunCalcCopyToAso
funcIntegrationScenarioExportMetadataAndDataAndDownloadFiles
funcIntegrationScenarioRemoveUnnecessaryFiles
funcIntegrationScenarioExportDataAndDownloadFiles
funcIntegrationScenarioRefreshTheApplication#!/bin/sh
SERVER URL="https://<BASE-URL>"
USERNAME="epm default cloud admin"
PASSWORD="epm cloud"
APP NAME="Vision"
API VERSION="11.1.2.3.600"
funcRemoveTempFiles() {
    for var in "$@"
    do
        if [ -f $var ]; then
           rm $var
        fi
    done
}
funcPrintErrorDetails() {
    contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr -d
[:space:]`
    if [ ! -z $contentType ] && [[ $contentType = *"application/json"* ]];
then
```

```
output=`cat $1`
        error=`echo $output | jq '.details'`
        echo "Error details: " $error
   fi
}
funcExecuteRequest() {
    if [ ! -z "$4" ]; then
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $4" -d $3 $2`
    else
        statusCode=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o "response.txt" -D "respHeader.txt" -H "Content-Type: $3" $2`
    fi
    if [ $statusCode != 200 ]; then
        echo "Error executing request"
        if [ $statusCode != 000 ]; then
            echo "Response error code : " $statusCode
            funcPrintErrorDetails "response.txt"
            funcRemoveTempFiles "respHeader.txt" "response.txt"
        fi
        exit 0
   fi
}
funcGetStatus() {
   output=`cat response.txt`
    count=`echo $output | jq '.links | length'`
   i=0
   pingUrl=""
    while [ $i -lt $count ]; do
        rel=`echo $output | jq '.links['$i'].rel'`
        rel=`echo "$rel" | tr -d "\""`
        if [ "$rel" == "Job Status" ]; then
                pingUrl=`echo $output | jq '.links['$i'].href'`
                pingUrl=`echo "$pingUrl" | tr -d "\""`
        fi
        i=`expr $i + 1`
    done
    echo $pingUrl
    completed="false"
    while [ $completed != "true" ]; do
        statusCode2=`curl -X $1 -s -w "%{http code}" -u "$USERNAME:$PASSWORD"
-o "pingResponse.txt" -H "Content-Type: application/x-www-form-urlencoded"
"$pingUrl"`
        if [ $statusCode2 == 200 ]; then
            status2=`jq '.status' pingResponse.txt`
            if [ $status2 != -1 ]; then
                completed="true"
                echo "Job completed"
            else
                echo "Please wait..."
                sleep 20
            fi
        else
```

```
ORACLE
```

```
echo "Please wait..."
            sleep 20
        fi
        funcRemoveTempFiles "pingResponse.txt"
    done
}
funcGetLCMVersions() {
    url=$SERVER URL/interop/rest
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "List of versions :"
        count=`echo $output | jq '.items | length'`
        i=0
        while [ $i -lt $count ]; do
            echo "Version : " `echo $output | jq '.items['$i'].version'`
            echo "Lifecycle :" `echo $output | jq '.items['$i'].lifecycle'`
            echo "Latest :" `echo $output | jq '.items['$i'].latest'`
            echo "Link :" `echo $output | jq '.items['$i'].links[0].href'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGetLCMVersionDetails() {
    url=$SERVER URL/interop/rest/$API VERSION
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
   output=`cat response.txt`
   status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Version $API VERSION details :"
        count=`echo $output | jq '.links | length'`
        i=0
        while [ $i -lt $count ]; do
            echo "Service : " `echo $output | jq '.links['$i'].rel'`
            echo "URL :" `echo $output | jq '.links['$i'].href'`
            echo "Action :" `echo $output | jq '.links['$i'].action'`
            echo ""
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
```



```
funcGetServices() {
    url=$SERVER URL/interop/rest/$API VERSION/services
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Services list :"
        count=`echo $output | jq '.links | length'`
        i=0
        while [ $i -lt $count ]; do
            rel=`echo $output | jq '.links['$i'].rel'`
            rel=`echo "$rel" | tr -d "\""`
            if [ "$rel" != "self" ]; then
                echo "Service : " `echo $output | jq '.links['$i'].rel'`
                echo "URL :" `echo $output | jq '.links['$i'].href'`
                echo "Action :" `echo $output | jq '.links['$i'].action'`
                echo ""
            fi
            i=`expr $i + 1`
        done
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcRecreateService() {
   echo "Are you sure you want to recreate the EPM environment (yes/no): no ?
[Press Enter]"
   read toCreate
    if [ $toCreate != "yes" ]; then
        echo "User cancelled the recreate command"
        exit 0
    fi
    url=$SERVER URL/interop/rest/$API VERSION/services/$1/recreate
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ status == -1 ]; then
        echo "Started recreating the environment successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcGetApplicationSnapshotDetails() {
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName
```

```
funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Application details :"
        echo "Application snapshot name : " `echo $output | jq
'.items[0].name'
        echo "Application snapshot type : " `echo $output | jq
'.items[0].type'
        echo "Can be exported flag : " `echo $output | jq
'.items[0].canExport'`
        echo "Can be imported flag : " `echo $output | jq
'.items[0].canImport'`
        echo "Can be uploaded flag : " `echo $output | jq
'.items[0].canUpload'`
        echo "Can be downloaded flag : " `echo $output | jq
'.items[0].canDownload'`
        count=`echo $output | jq '.links | length'`
        i=0
        echo "Services details :"
        while [ $i -lt $count ]; do
            echo "Service : " `echo $output | jq '.links['$i'].rel'`
            echo "URL :" `echo $output | jq '.links['$i'].href'`
            echo "Action :" `echo $output | jq '.links['$i'].action'`
            echo ""
            i=`expr $i + 1`
        done
   else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcListFiles() {
   url=$SERVER_URL/interop/rest/$API VERSION/applicationsnapshots
    funcExecuteRequest "GET" $url "application/x-www-form-urlencoded"
    list=`cat response.txt | jq 'select(.items != null) | .items[].name'`
    if [[ ! -z $list ]]; then
        echo $list
    else
        echo "No files found"
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcDeleteFile() {
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName
    funcExecuteRequest "DELETE" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
```

```
status=`echo $output | jq '.status'`
    if [ $status == 0 ]; then
        echo "Deleted successfully"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcUploadFile() {
   infile=$1
    if [ ! -f $infile ]; then
        echo "File does not exist"
        exit 0
    fi
    encodedFileName=$(echo $infile | sed -f urlencode.sed)
    url="$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/contents?q="
    filename=$( basename $infile)
    filesize=$( stat -c %s $infile)
   bs=52428800
   noOfPackets=$(($((filesize / bs)) + 1))
    uploadedsize=0
    isFirst=true
   count=1
   isLast="false"
    if [ $noOfPackets = 1 ]; then
     isLast="true"
    fi
    tempFile=/u01/temp/$filename
    if [ ! -d "/u01/temp" ]; then
       mkdir /u01/temp
    fi
    while [ $uploadedsize -ne $filesize ]
    do
        skip=$uploadedsize
        temp=$((filesize - uploadedsize))
        if [ $temp -le $bs ]; then
            length=$temp
        else
            length=$bs
        fi
        echo "Skip : $skip"
        echo "Length : $length"
        (
            dd bs=1 skip=$skip count=0 &> /dev/null
            dd bs=$length count=1 of=$tempFile &> /dev/null
        ) < "$infile"
        param=$(echo "{chunkSize=$length,isFirst=$isFirst,isLast=$isLast}" |
sed -f urlencode.sed)
        urlwithparam="$url$param"
```

```
echo $urlwithparam
       statusCode=`curl -X POST -s -w "%{http code}" -T $tempFile -u
"$USERNAME:$PASSWORD" -o "response.txt" -D "respHeader.txt" -H "Content-Type:
application/octet-stream" "$urlwithparam"`
        funcRemoveTempFiles $tempFile
       if [ $statusCode == 200 ]; then
            output=`cat response.txt`
            status=`echo $output | jq '.status'`
            if [ $status != 0 ]; then
                error=`echo $output | jq '.details'`
                echo "Error occurred. " $error
                funcRemoveTempFiles "respHeader.txt" "response.txt"
                exit 0
            fi
       else
            echo "Error executing request"
            if [ $statusCode != 000 ]; then
                echo "Response error code : " $statusCode
                funcPrintErrorDetails "response.txt"
                funcRemoveTempFiles "respHeader.txt" "response.txt"
            fi
            exit 0
       fi
        funcRemoveTempFiles "respHeader.txt" "response.txt"
       uploadedsize=$((uploadedsize + length))
       isFirst="false"
       echo "isFirst : $isFirst"
       count=$((count + 1))
       if [ $count = $noOfPackets ]; then
            isLast="true"
       fi
       echo "Uploaded Size : $uploadedsize"
       echo "isLast : $isLast"
    done
   echo "Uploaded File Successfully"
}
funcDownloadFile() {
    filepath="/u01/$1"
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/contents
    statusCode=`curl -X GET -s -w "%{http code}" -u "$USERNAME:$PASSWORD" -
o $filepath -H "Content-Type: application/x-www-form-urlencoded" -D
respHeader.txt $url`
    if [ $statusCode == 200 ]; then
       contentType=`echo $(grep 'Content-Type:' respHeader.txt) | tr -d
[:space:]`
       if [ ! -z $contentType ] && [[ $contentType = *"application/
json"* ]]; then
            output=`cat $filepath`
            error=`echo $output | jq '.details'`
```

```
echo "Error occurred. " $error
            funcRemoveTempFiles $filepath
        else
            fileExtension=`echo $(grep -r "fileExtension: " respHeader.txt |
awk '{print ($2)}') | tr -d [:space:]`
            if [ ! -z $fileExtension ]; then
                if [[ ! $filepath =~ \.$fileExtension$ ]]; then
                    mv $filepath $filepath.$fileExtension
                fi
            fi
            echo "Downloaded file successfully"
        fi
    else
        echo "Error listing files. "
        if [ $statusCode != 000 ]; then
            echo "Response error code : " $statusCode
            funcPrintErrorDetails $filepath
            funcRemoveTempFiles $filepath
        fi
    fi
    funcRemoveTempFiles "respHeader.txt"
}
funcImportSnapshot() {
    param=$(echo "{type:import}" | sed -f urlencode.sed)
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/migration?q=$param
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started importing successfully"
        funcGetStatus "POST"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcExportSnapshot() {
    param=$(echo "{type:export}" | sed -f urlencode.sed)
    encodedFileName=$(echo $1 | sed -f urlencode.sed)
    url=$SERVER URL/interop/rest/$API VERSION/
applicationsnapshots/$encodedFileName/migration?q=$param
    funcExecuteRequest "POST" $url "application/x-www-form-urlencoded"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started exporting successfully"
        funcGetStatus "POST"
    else
        error=`echo $output | jq '.details'`
```

```
echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcExecuteJob() {
   url="$SERVER URL/HyperionPlanning/rest/$API VERSION/
applications/$APP NAME/jobs"
    encodedJobName=$(echo $2 | sed -f urlencode.sed)
    if [ ! -z "$3" ]; then
       param="jobType=$1&jobName=$encodedJobName&parameters=$3"
    else
        param="jobType=$1&jobName=$encodedJobName"
    fi
    funcExecuteRequest "POST" $url $param "application/json"
    output=`cat response.txt`
    status=`echo $output | jq '.status'`
    if [ \$status == -1 ]; then
        echo "Started executing job successfully"
        funcGetStatus "GET"
    else
        error=`echo $output | jq '.details'`
        echo "Error occurred. " $error
    fi
    funcRemoveTempFiles "respHeader.txt" "response.txt"
}
funcIntegrationScenarioImportMetadataIntoApplication() {
    funcUploadFile "DemoApplication HSS Vision.zip"
    funcExecuteJob "IMPORT METADATA" "accountMetadata"
"{importZipFileName=accounts.zip}"
    funcExecuteJob "CUBE REFRESH" "cubeRefresh"
}
funcIntegrationScenarioImportDataRunCalcCopyToAso() {
    funcUploadFile "data.csv"
    funcExecuteJob "IMPORT DATA" "loadingqldata" "{importFileName=data.csv}"
    funcExecuteJob "CUBE REFRESH","cubeRefresh"
    funcExecuteJob "PLAN TYPE MAP" "CampaignToReporting" "{clearData=false}"
}
funcIntegrationScenarioExportMetadataAndDataAndDownloadFiles() {
    funcExecuteJob "EXPORT METADATA" "exportentitymetadata"
"{exportZipFileName=entitydata.zip}"
    funcExecuteJob "EXPORT DATA" "Forecastdata"
"{exportFileName=forecastdata.zip}"
    funcListFiles
    funcDownloadFile "entitydata.zip"
    funcDownloadFile "forecastdata.zip"
}
funcIntegrationScenarioRemoveUnnecessaryFiles() {
    funcListFiles
    funcDeleteFile "entitymetadata.csv"
    funcDeleteFile "forecastdata.csv"
```



```
}
funcIntegrationScenarioExportDataAndDownloadFiles() {
   funcExecuteJob "EXPORT DATA" "entitydata"
"{exportFileName:entitydata.zip}"
    funcExecuteJob "EXPORT DATA" "forecastdata"
"{exportFileName:forecastdata.zip}"
    funcListFiles
    funcDownloadFile "entitydata.zip"
    funcDownloadFile "forecastdata.zip"
}
funcIntegrationScenarioRefreshTheApplication() {
    funcUploadFile "accounts.zip"
    funcExecuteJob "IMPORT METADATA" "accountMetadata"
"{importZipFileName:accounts.zip}"
    funcExecuteJob "CUBE REFRESH" "cubeRefresh"
}
funcIntegrationScenarioCloneServiceInstance() {
    # Part 1 : Change SERVER URL, USERNAME, PASSWORD, API VERSION variables
values to match those of first environment
    # Download file from source instance.
    # Comment out all lines below Part 2
    # Uncomment the below line for the first step.
    # funcDownloadFile "Artifact Snapshot"
    # Part 2 : Change SERVER URL, USERNAME, PASSWORD, API VERSION to match
those of second environment.
    # Clone the service instance.
    # Comment out code for download file.
    # Uncomment below lines
    funcRecreateService "PBCS"
    funcDeleteFile "Artifact Snapshot"
    funcUploadFile "Artifact Snapshot.zip"
    funcImportSnapshot "Artifact Snapshot"
}
funcIntegrationScenarioImportMetadataIntoApplication
funcIntegrationScenarioImportDataRunCalcCopyToAso
funcIntegrationScenarioExportMetadataAndDataAndDownloadFiles
funcIntegrationScenarioRemoveUnnecessaryFiles
{\tt funcIntegrationScenarioExportDataAndDownloadFiles}
funcIntegrationScenarioRefreshTheApplication
```

Note on Proxy Setting: In case of proxies, set the proxy host and port as the system arguments.



D CSS Common Helper Functions for cURL

This appendix shows the CSS common helper functions for cURL for the EPM Cloud REST APIs.

Note on Proxy Setting: In case of proxies, set the proxy host and port as the system arguments.

```
#!/bin/sh
#set -x
export PATH=$PATH:<PATH TO JQ BINARY>
SERVER URL="<SERVICE URL>"
USERNAME="<USERNAME>"
PASSWORD="<PASSWORD>"
API VERSION="v1"
# To avoid SSL connection issue in the environment please add -k option for
below curl commands.
funcCallRESTAPI() {
    if [ "$1" == "GET" ] || [ "$1" == "DELETE" ]; then
        if [ "$6" != "" ]; then
            echo `curl -s -u $4:$5 -H "$3" --request $1 -G $2 -d "$6"`
        else
            echo `curl -s -u $4:$5 -H "$3" --request $1 -G $2`
        fi
    else
                if [ "$6" != "" ]; then
                        echo `curl -s -u $4:$5 -H "$3" --request $1 $2 -d
"$6"`
                else
                        echo `curl -s -u $4:$5 -H "$3" --request $1 $2`
                fi
    fi
}
funcCSSRESTHelper() {
        jobOutput=$(funcCallRESTAPI "$1" "$2" "$3" "$4" "$5" "$6")
        jobUrl=`echo $jobOutput | jq '.links[1].href'`
        if [ $jobUrl != null ]; then
                jobUrl="${jobUrl%\"}"
                jobUrl="${jobUrl#\"}"
                jobStatus=-1
                while [ jobStatus == -1 ]; do
                        jobOutput=$(funcCallRESTAPI "GET" "$jobUrl" "$header"
"$USERNAME" "$PASSWORD")
                        jobStatus=`echo $jobOutput | jq '.status'`
                done
                restStatus=`echo $jobOutput | jq '.details'`
                restStatus="${restStatus%\"}"
                restStatus="${restStatus#\"}"
                statusMessage=""
```

```
if [ $jobStatus == 0 ]; then
                        statusMessage="$7 completed successfully."
#"$restStatus"
                else
                        statusMessage=$restStatus
                fi
                   echo "$statusMessage"
        else
                failedMessage=`echo $jobOutput | jq '.details'`
        failedMessage="${failedMessage%\"}"
                failedMessage="${failedMessage#\"}"
                echo $failedMessage
        fi
funcAddUsers() {
    url="$SERVER URL/interop/rest/security/$API VERSION/users"
    params="filename=$1&userpassword=$2&resetpassword=$3"
   header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
    cssRESTAPI="AddUsers"
    statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
funcRemoveUsers() {
        url="$SERVER URL/interop/rest/security/$API VERSION/users"
        params="filename=$1"
        header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
        cssRESTAPI="RemoveUsers"
        statusMessage=$(funcCSSRESTHelper "DELETE" "$url" "$header"
"$USERNAME" "$PASSWORD" "$params" "$cssRESTAPI")
        echo $statusMessage
funcAssignRole() {
        url="$SERVER URL/interop/rest/security/$API VERSION/users"
        params="filename=$1&jobtype=ASSIGN ROLE&rolename=$2"
        header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
        cssRESTAPI="AssignRole"
        statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
        echo $statusMessage
}
funcUnassignRole() {
        url="$SERVER URL/interop/rest/security/$API VERSION/users"
        params="filename=$1&jobtype=UNASSIGN ROLE&rolename=$2"
        header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
        cssRESTAPI="UnassignRole"
        statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
        echo $statusMessage
funcAddUsersToGroup() {
```

```
url="$SERVER URL/interop/rest/security/$API VERSION/groups"
    params="filename=$1&jobtype=ADD_USERS_TO_GROUP&groupname=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="AddUsersToGroup"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
funcRemoveUsersFromGroup() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1&jobtype=REMOVE USERS FROM GROUP&groupname=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="RemoveUsersFromGroup"
       statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcAddUserToGroups() {
    url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
    params="filename=$1&jobtype=ADD USER TO GROUPS&username=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="AddUserToGroups"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
funcRemoveUserFromGroups() {
       url="$SERVER_URL/interop/rest/security/$API_VERSION/groups"
       params="filename=$1&jobtype=REMOVE_USER_FROM_GROUPS&username=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="RemoveUserFromGroups"
        statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcGenerateRoleAssignmentReport() {
       url="$SERVER_URL/interop/rest/security/$API_VERSION/
roleassignmentreport"
       params="filename=$1&usertype=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="generateRoleAssignmentReport"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcGenerateUserGroupReport() {
       url="$SERVER_URL/interop/rest/security/$API_VERSION/usergroupreport"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
        cssRESTAPI="generateUserGroupReport"
        statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
```

```
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcAddGroups() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="addGroups"
        statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcRemoveGroups() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="removeGroups"
        statusMessage=$(funcCSSRESTHelper "DELETE" "$url" "$header"
"$USERNAME" "$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
}
funcGenerateInvalidLoginReport() {
       url="$SERVER URL/interop/rest/security/$API VERSION/
invalidloginreport"
     params="from date=$1&to date=$2&filename=$3"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="generateInvalidLoginReport"
        statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcGenerateRoleAssignmentAuditReport() {
       url="$SERVER URL/interop/rest/security/$API VERSION/
roleassignmentauditreport"
     params="from date=$1&to date=$2&filename=$3"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="generateRoleAssignmentAuditReport"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcUpdateUsers() {
       url="$SERVER_URL/interop/rest/security/$API VERSION/users"
       params="filename=$1&jobtype=UPDATE USERS"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="UpdateUsers"
       statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
}
```



#funcAddUsers test1.csv password false

#funcRemoveUsers test2.csv

#funcAssignRole test3.csv "Power User"

#funcUnAssignRole test4.csv Viewer

#funcAddUsersToGroup test5.csv TestNativeGroup1

#funcRemoveUsersFromGroup test6.csv TestNativeGroup2

#funcGenerateRoleAssignmentReport RoleAssignmentReport.csv ServiceUsers

#funcGenerateUserGroupReport UserGroupReport.csv

#funcAddUserToGroups groups.csv joe

#funcRemoveUserFromGroups groups.csv joe

#funcAddGroups CreateGroup1.csv

#funcRemoveGroups DeleteGroup1.csv

#funcGenerateInvalidLoginReport 2021-06-01 2021-06-10 invalidLoginReport.csv

#funcGenerateRoleAssignmentAuditReport 2021-06-01 2021-06-10

roleAssignmentAuditReport.csv

#funcUpdateUsers updateuser.csv



CSS Common Helper Functions for Groovy

This appendix shows the CSS common helper functions for Groovy for the EPM Cloud REST APIs.

Note:

- Proxy setting: In case of proxies, set the proxy host and port as the system arguments.
- **Username**: The username variable uses the format <*domain*>.<*username*>. Authentication.

```
import java.nio.charset.StandardCharsets
import groovy.json.JsonSlurper
serverUrl="<SERVICE URL>"
username="<DOMAINNAME.USERNAME>"
password="<PASSWORD>"
apiVersion = "v1";
userCredentials = username + ":" + password;
basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
def getResponse(is) {
   BufferedReader br = new BufferedReader(new InputStreamReader(is));
   StringBuilder sb = new StringBuilder();
   String line;
    while ((line = br.readLine()) != null) {
       sb.append(line+"\n");
    }
   br.close();
   return sb.toString();
}
def getUrlFromResponse(scenario, response, relValue) {
    def object = new JsonSlurper().parseText(response)
    def pingUrlStr
    if (object.status == -1) {
        println "Started - " + scenario
        def links = object.links
        links.each{
            if (it.rel.equals(relValue)) {
                pingUrlStr=it.href
            }
        }
    } else {
        println "Error details: " + object.details
        System.exit(0);
    }
    return pingUrlStr
```

```
}
def getJobStatus(pingUrlString, methodType) {
    def pingUrl = new URL(pingUrlString);
    def completed = false;
    while (!completed) {
        pingResponse = executeRequest(pingUrl, methodType, null,
"application/x-www-form-urlencoded");
        status = getJobStatusFromResponse(pingResponse);
        if (status == "Processing") {
            try {
                println "Processing. Please wait..."
                Thread.sleep(5000);
            } catch (InterruptedException e) {
                completed = true
            }
        } else {
            println status
            completed = true
        ł
    }
}
def getJobStatusFromResponse(response) {
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == -1)
        return "Processing"
    else if (status == 0)
        return "Completed"
    else
        return object.details
}
def getJobDetailsFromResponse(response) {
   def object = new JsonSlurper().parseText(response)
    def details = object.details
   if (details != null)
        return object.details
    else
        return null
}
def executeRequest(url, requestType, payload, contentType) {
   HttpURLConnection connection = (HttpURLConnection) url.openConnection();
    connection.setDoOutput(true);
    connection.setInstanceFollowRedirects(false);
    connection.setRequestMethod(requestType);
    connection.setRequestProperty("Content-Type", contentType);
    11
                 connection.setRequestProperty("charset",
StandardCharsets.UTF 8);
    connection.setRequestProperty("Authorization", basicAuth);
   connection.setUseCaches(false);
    if (payload != null) {
```

```
OutputStreamWriter writer = new
OutputStreamWriter(connection.getOutputStream());
        writer.write(payload);
        writer.flush();
    }
    int statusCode
    trv {
        statusCode = connection.responseCode;
    } catch (all) {
        println "Error connecting to the URL"
        System.exit(0);
    }
    def response
    if (statusCode == 200 || statusCode == 201) {
        if (connection.getContentType() != null && !
connection.getContentType().startsWith("application/json")) {
           println "Error occurred in server"
            System.exit(0)
        }
        InputStream is = connection.getInputStream();
        if (is != null)
            response = getResponse(is)
    } else {
        println "Error occurred while executing request"
        println "Response error code : " + statusCode
        InputStream is = connection.getErrorStream();
        if (is != null && connection.getContentType() != null &&
connection.getContentType().startsWith("application/json"))
            println getJobStatusFromResponse(getResponse(is))
        System.exit(0);
    }
    connection.disconnect();
    return response;
}
def addUsersToGroup(fileName, groupName) {
    String scenario = "Adding users in " + fileName + " to group " +
groupName;
    String params = "jobtype=ADD USERS TO GROUP&filename="+ fileName
+"&groupname="+ groupName;
    def url = null;
    def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
```

```
"GET");
  }
}
def removeUsersFromGroup(fileName, groupName) {
    String scenario = "Removing users in " + fileName + " from group " +
groupName;
    String params = "jobtype=REMOVE USERS FROM GROUP&filename="+ fileName
+"&groupname="+ groupName;
    def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def addUserToGroups(fileName, userName) {
    String scenario = "Adding users in " + fileName + " to group " + userName;
    String params = "jobtype=ADD USER TO GROUPS&filename="+ fileName
+"&username="+ userName;
   def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
       println "Please enter a valid URL"
       System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def removeUserFromGroups(fileName, userName) {
   String scenario = "Removing users in " + fileName + " from group " +
userName;
    String params = "jobtype=REMOVE USER FROM GROUPS&filename="+ fileName
+"&username="+ userName;
    def url = null;
```

```
def response = null;
   try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
1
def addUsers(fileName, resetPassword, userPassword) {
    String scenario = "Creating users in " + fileName;
    String params = "jobtype=ADD USERS&filename="+ fileName
+"&resetpassword="+ resetPassword +"&userpassword="+ userPassword;
    def url = null;
   def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def addUsers(fileName) {
    addUsers(fileName, null, null);
}
def deleteUsers(fileName) {
    String scenario = "Deleting users in " + fileName;
    String params = null;
   def url = null;
   def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users?filename=" + fileName);
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "DELETE", null, "application/x-www-form-
```

```
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def assignUsersRoles(fileName, roleName) {
    String scenario = "Assigning users in " + fileName + " with role " +
roleName;
    String params = "jobtype=ASSIGN ROLE&filename="+ fileName +"&rolename="+
roleName;
   def url = null;
   def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
       System.exit(0);
    }
   response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def unassignUsersRoles(fileName, roleName) {
    String scenario = "Un-assigning users in " + fileName + " with role " +
roleName;
    String params = "jobtype=UNASSIGN ROLE&filename="+ fileName
+"&rolename="+ roleName;
   def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
       println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def generateRoleAssignmentReport(fileName, userType) {
    String scenario = "Generating Role assignment report in " + fileName + "
```

```
with usertype as " + userType;
    String params = "jobtype=GENERATE_ROLE_ASSIGNMENT_REPORT&filename="+
fileName + "&usertype=" + userType;
   def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
roleassignmentreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def generateUserGroupReport(fileName) {
    String scenario = "Generating User Group Report in " + fileName;
    String params = "jobtype=GENERATE USER GROUP REPORT&filename="+ fileName;
    def url = null;
   def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
usergroupreport");
   } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def addGroups(fileName) {
   println "addgroups"
   String scenario = "Creating Groups in " + fileName;
   String params = "filename="+ fileName;
   def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
```



```
if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
def removeGroups(fileName) {
    String scenario = "Deleting Groups in " + fileName;
    String params = null;
    def url = null;
   def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups?filename=" + fileName);
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "DELETE", null, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
def generateRoleAssignmentAuditReport(from date, to date, fileName) {
    String scenario = "Generating Role assignment audit report in " +
fileName;
   String params =
"jobtype=GENERATE ROLE ASSIGNMENT AUDIT REPORT&from date="+from date+"&to date
="+to date+"&filename="+ fileName;
    def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
roleassignmentauditreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
   response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
def generateInvalidLoginReport(from date, to date, fileName) {
    String scenario = "Generating Invalid Login report in " + fileName;
    String params =
"jobtype=GENERATE INVALID LOGIN REPORT&from date="+from date+"&to date="+to da
```

```
te+"&filename="+ fileName;
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
invalidloginreport");
   } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def updateUsers(fileName) {
    String scenario = "Updating users from " + fileName ;
   String params = "jobtype=UPDATE USERS&filename="+ fileName;
   def url = null;
   def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
   } catch (MalformedURLException e) {
       println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
//Execute commands here
//addUsersToGroup("Users.csv",
"G1");
                   //PUT
//removeUsersFromGroup("Users.csv",
"G1");
    //PUT
//addUsers("AddUsers123.csv", "false",
"newPassword");
                                                        //POST
11
addUsers("AddUsers456.csv");
//POST
11
deleteUsers("RemoveUsers.csv");
                                                               //DELETE
//assignUsersRoles("Users.csv", "Service
```



```
Administrator");
                                            //PUT
//assignUsersRoles("users.csv",
"viewer");
                                                                      //PUT
//unassignUsersRoles("Users.csv", "Drill
Through");
                                                              //PUT
//
generateRoleAssignmentReport("GroovySampleReport3.csv,"ServiceUsers");
                        // POST
//
generateUserGroupReport("UserGroupReportGroovy.csv");
           // POST
//addUserToGroups("Group.csv",
"user1");
                                                         //PUT
//removeUserFromGroups("groups.csv",
"joe");
                                                  //PUT
//
addGroups("CreateGroup1.csv");
// POST
11
removeGroups("DeleteGroup1.csv");
   // DELETE
//generateInvalidLoginReport("2020-06-01", "2021-06-10",
"report12345.csv"); //POST
//updateUsers("updateuser.csv");
                                                                  // PUT
```

REST API Examples with Postman

This appendix provides examples of how to run selected REST APIs using a web client called Postman.

- Example: Using REST APIs to Upload with Postman
- Example: Using REST APIs to Upload to an External Directory with Postman
- Example: Using REST APIs to Upload a Snapshot with Postman

Example: Using REST APIs to Upload with Postman

In this example, we upload a file named users.csv to our environment, https://<BASE-URL>.

For an example of coding parameters, scroll down to the end of this topic.

Notes:

- This example uses the 11.1.2.3.600 Upload API, which is a simpler non-chunked version.
- The name of the file is passed in the URL itself, for example, https://<BASE-URL>/ interop/rest/11.1.2.3.600/applicationsnapshots/users.csv/contents
- If the filename contains special characters or has whitespace, it should be encoded using any online resource, such as urlencode.org.
- 1. Example of Upload parameters.



2. Example of Upload authorization.



Untitled Request			📮 Co		
POST v /interop/rest/11.1.2.	3.600/applicationsnapshots/users.csv/contents	Send	▼ Sa	ave *	
Params Authorization Headers (1) Body Pre-reques	st Script Tests Settings		Cool	kies Code	•
TYPE Basic Auth The authorization header will be automatically generated when you send the request. Learn more about authorization Preview Request	Heads up! These parameters hold sensitive data. To keep Username Password	this data secure while working in a collaborative environment, we recommend using variables. Learn more about epm_default_cloud_admin 	rariables	×	
Response					


3. Example of Upload headers.

PO	T v /interop/rest/11.1.2.3.600/applicationsnap	pshots/users.cov/contents		Send Save
	ms Authorization • Headers (1) Body • Pre-request Script Tests	Settings		Cookies Code
*	leaders (1)			
	KEY	VALUE	DESCRIPTION	🚥 Bulk Edit - Presets 💌
~	Content-Type	application/octet-stream		
	Key	Value	Description	
Resp	onse			

4. Example of Upload body.

POST	Ŧ	Interop/rest/11.1.2.3.600/epplicationsnapshots/users.csu/contents	Send 🔹	Save	Ŧ
Params	Authoriz	ation Headers (1) Body Pre-request Script Tests Settings		Cookies	Code
none	• form	data 🔍 x-www-form-urlencoded 🔍 raw 🐞 binary 🔍 GraphQL BETA			
A users.csv	×				
Response					

5. Example of Upload response on success.





Example: Using REST APIs to Upload to an External Directory with Postman

In this example, we upload a file named data.txt to the inbox directory in our environment, https://<BASE-URL>.

Notes:

- This example uses the 11.1.2.3.600 Upload API, which is a simpler non-chunked version.
- The name of the file is passed in the URL itself, for example, https://<BASE-URL>/ interop/rest/11.1.2.3.600/applicationsnapshots/data.txt/contents? extDirPath=inbox
- If the filename contains special characters or has white space, it must be encoded using any online resource, such as urlencode.org. (See an example at the bottom of this topic: Example: Using REST APIs to Upload with Postman.)
- 1. Example of parameters for Upload to external directory.

POST *	/interop/rest/11.1.2.3.600/applicationsn	apshots/data.txt/contents?extDirPath=inbox		Send • Sav	ve 🔻
Params Authorization Headers (1)	Body Pre-request Script Tests	Settings		Cookie	ies Code
Query Params					
KEY		VALUE	DESCRIPTION	8	Bulk Edit
✓ extDirPath		Inbox			
Key		Value	Description		
Response					

2. Example of authorization for Upload to external directory.

POST v	1.3.600/applicationsnapshots/data.txt/contents?extDirPath=inbox	Send •	Save	v
Params Authorization Headers (1) Body Pre-reque	st Script Tests Settings		Cookies	Code
TYPE Basic Auth	Heads up! These parameters hold sensitive data. To keep	this data secure while working in a collaborative environment, we recommend using variables. Learn more about variable	5	×
The authorization header will be automatically generated when you send the request. Learn more about authorization	Username Password	,admin		
Preview Request		Show Password		
Response				

3. Example of Upload to external directory headers.

POS	T • /interop/rest/11.1.2.3.600/applicatio	rsnapshots/data.txt/contents?extDirPath=inbox		Send T Save T
Paran	ms Authorization Headers (1) Body Pre-request Script Tes	s Settings		Cookies Code
₹ H	leaders (1)			
	KEY	VALUE	DESCRIPTION	🚥 🛛 Bulk Edit 🔹 Presets 💌
	Content-Type	application/octet-stream		
	Key	Value	Description	
Respo				

4. Example of Upload to external directory body.



POST *	/interop/rest/11.1.2.3.600/applicationsnapshots/data.tst/contents?lextDirPath=inbox	Send v Save v
Params Authorization Head	ers (1) Body Pre-request Script Tests Settings	Cookies Code
none form-data x-www-f	orm-urlencoded 🛛 💿 raw 🕘 binary 🔘 GraphQL BETA	
data.txt ×		
Response		

5. Example of Upload to external directory response on success.

POST	Send	- Save -
Params Authorization Headers (10) Body Pre-request Script Tests Settings		Cookies Cod
none form-data xwww-form-uriencoded raw shinary GraphQL BETA		
data.tut X		
Body Coolsies (1) Headers (8) Test Results	Status: 200 OK Time: 1324ms Size: 631 B	Save Response 👻
Pretty Raw Preview Visualize BETA JSON ¥ 📅		n Q
1 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1		

Example: Using REST APIs to Upload a Snapshot with Postman

In this example, we upload a snapshot named Artifact Snapshot.zip to our environment, https://<BASE-URL>.

Notes:

- We are using the 11.1.2.3.600 Upload API, which is a simpler non-chunked version.
- The name of the file is passed in the URL itself, for example, https://<BASE-URL>/ interop/rest/11.1.2.3.600/applicationsnapshots/Artifact%20Snapshot.zip/ contents
- If the filename contains special characters or has white space, it must be encoded using any online resource, such as urlencode.org
- 1. Example of Upload snapshot parameters.

POS	iT v		/interop	p/rest/11.1.2.3.600/app	licationsna	pshots/Artifact%20Snapshot.zip/contents		Send 🔹	Save 🔻
Parar	ns Authorizat	on Headers (1)	Body 鱼	Pre-request Script	Tests	Settings			Cookies Code
Quer	y Params								
	KEY					VALUE	DESCRIPTION		Bulk Edit
	Key					Value	Description		
Resp	onse								

2. Example of Upload Snapshot authorization.



POST v /interop/rest/11.1.2	.3.600/applicationsnapshots/Artifact%205napshot.zip/contents	Send 💌	Save	¥
Params Authorization • Headers (1) Body • Pre-reque	st Script Tests Settings		Cookies	Code
TYPE Basic Auch The authorization header will be automatically generated when you send the request. Learn more about authorization	Heads up! These parameters hold sensitive data. To keep Username Password	this data secure while working in a collaborative environment, we recommend using variables. Learn more about variables	1	×
Preview Request Response		Show Password		

3. Example of Upload Snapshot headers.

PO	ST v /interop/rest/11.1.2.3.600/applicationsna	apshots/Artifect%20Snapshot.zip/contents		Send 🔫	Save 🔻
Para	ms Authorization • Headers (1) Body • Pre-request Script Tests	Settings			Cookies Code
* 1	Headers (1)				
	KEY	VALUE	DESCRIPTION	+++ Bulk Edit	Presets 🔻
\checkmark	Content-Type	application/octet-stream			
	Key	Value	Description		
Resp	onse				

4. Example of Upload Snapshot body.

Params Authorization Headers (1) Body Pre-request Script Tests Settings	Cookies Code
🖲 none 🔍 form-data 🔍 x-www-form-urlencoded 🔍 raw 🐞 binary 🔘 GraphQL 🕅	
🛦 [Artifact Snapshot.zip X]	
Response	

5. Example of Upload Snapshot response on success.

POST v	/interop	p/rest/11.1.2.3.600/applicationsnapshots/Artifact%20Snapshot.zip/contents	Send	▼ Save
Params Authorization	Headers (10) Body •	Pre-request Script Tests Settings		Cookies C
none 🛛 form-data	• x-www-form-urlencoded	raw 🖲 binary 🔘 GraphQL BETA		
Artifact Snapshot.zip X				
dy Cookies (1) Headers	s (8) Test Results		Status: 200 OK Time: 6m 8.49s Size: 809 B	Save Response
Pretty Raw Preview	w Visualize BETA JSON	- 5		
6 "data" 7 "actic 8), 9 9 { 10 "href" 11 "rel": 12 "data"	: "self", ": null, on": "POST"	<pre>/interop/rest/11.1.2.3.400/applicationsnapshots/ArtifactW285napshot.zip/contents*, /interop/rest/11.1.2.3.400/applicationsnapshots/ArtifactW13285napshot.zip/contents/status*,</pre>		

6. Example of checking status for Upload Snapshot .



GET	GET						•
Params Authorization Headers (B) Body Pre-request Script Tests Settings							Code
Query Pa	rams						
KEY		VALUE	DESCRIPTION			Bi	ilk Edit
Key		Value	Description				
Body Co	okies (1) Headers (7) Test Results	Stat	us: 200 OK Time: 9.98a	Size: 504 B	Save Respo	nse 👻	
Pretty	Raw Preview Visualize BETA JSON -				ų.	I Q	
1 2 3 4 5 6 7 8 9 10 11 12 13	<pre>ilass": {</pre>	.1.2.3.600/applicationsnapshots/Artifact%205napshot.zip/contents/statug*,					

G

Profitability and Cost Management Common Helper Functions

Use the Profitability and Cost Management common helper functions as you work with Profitability and Cost Management REST APIs..

Profitability and Cost Management Common Helper Functions for Java

Common Helper Functions for Java

```
import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;
import java.io.OutputStreamWriter;
import java.io.UnsupportedEncodingException;
import java.net.HttpURLConnection;
import java.net.URI;
import java.net.URLEncoder;
import java.nio.charset.Charset;
import java.util.HashMap;
import java.util.Map;
import java.util.Set;
import javax.xml.bind.DatatypeConverter;
import org.json.JSONArray;
import org.json.JSONObject;
public class CSSRESTSamples {
   private static String userName;
   private static String password;
   private String serverUrl;
   private String apiVersion;
    public static void main(String[] args) {
        try {
CSSRESTSamples samples = new CSSRESTSamples("<DOMAINNAME.USERNAME>",
"<PASSWORD>", "<SERVICE URL>", "v1");
           // Call sample APIs.
            // samples.addUsers("AddUser2.csv", "test123$", false);
            // samples.removeUsers("test2.csv");
            // samples.assignRole("test3.csv", "Power User");
            // samples.unassignRole("test4.csv", "Viewer");
            // samples.addUsersToGroup("test5.csv", "TestGroup1");
            // samples.removeUsersFromGroup("test6.csv", "TestGroup2");
```

```
// samples.generateRoleAssignmentReport("JavaSampleReport.csv");
            // samples.generateUserGroupReport("UserGroupReport.csv");
            // samples.addUserToGroups("Group.csv", "user1");
            // samples.removeUserFromGroups("groups.csv", "joe");
            // samples.addGroups("Group1.csv");
            // samples.removeGroups("DeleteGroup1.csv");
            // samples.generateInvalidLoginReport("2021-06-01",
"2021-06-10", "invalidLoginReport141.csv");
            // samples.generateRoleAssignmentAuditReport("2021-06-01",
"2021-06-10", "roleAssignmentaudit 14778.csv");
        } catch (Throwable x) {
            System.err.println("Error: " + x.getMessage());
        }
    }
    public CSSRESTSamples(String userName, String password, String serverUrl,
String apiVersion) throws Exception {
        this.userName = userName;
        this.password = password;
        this.serverUrl = serverUrl;
        this.apiVersion = apiVersion;
    }
    public void addUsers (String fileName, String userPassword, boolean
resetPassword) {
        trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            regParams.put("filename", fileName);
            reqParams.put("userpassword", userPassword);
            reqParams.put("resetpassword", resetPassword + "");
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeUsers(String fileName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
```

```
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "DELETE");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
   public void assignRole(String fileName, String roleName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ASSIGN ROLE");
            reqParams.put("rolename", roleName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void unassignRole(String fileName, String roleName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/users";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "UNASSIGN ROLE");
            reqParams.put("rolename", roleName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
```

```
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void addUsersToGroup(String fileName, String groupName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ADD USERS TO GROUP");
            reqParams.put("groupname", groupName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeUsersFromGroup(String fileName, String groupName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "REMOVE USERS FROM GROUP");
            reqParams.put("groupname", groupName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
```

```
e.printStackTrace();
       }
    }
    public void addUserToGroups(String fileName, String userName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            reqParams.put("jobtype", "ADD USER TO GROUPS");
            reqParams.put("username", userName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeUserFromGroups(String fileName, String userName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            regParams.put("filename", fileName);
            reqParams.put("jobtype", "REMOVE USER FROM GROUPS");
            reqParams.put("username", userName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "PUT");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void generateRoleAssignmentReport(String fileName) {
       try {
```

```
String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/roleassignmentreport";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void generateUserGroupReport(String fileName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/usergroupreport";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
   public void addGroups(String fileName) {
       trv {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
            Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
```

```
Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void removeGroups(String fileName) {
        try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/groups";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "DELETE");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    public void generateInvalidLoginReport(String fromDate, String
toDate,String fileName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/invalidloginreport";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("from date", fromDate);
            regParams.put("to date", toDate);
            reqParams.put("filename", fileName);
           Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
```

```
e.printStackTrace();
       }
    }
    public void generateRoleAssignmentAuditReport(String fromDate, String
toDate,String fileName) {
       try {
            String url = this.serverUrl + "/interop/rest/security/" +
apiVersion + "/roleassignmentauditreport";
           Map<String, String> reqHeaders = new HashMap<String, String>();
            reqHeaders.put("Authorization", "Basic " + DatatypeConverter
                    .printBase64Binary((this.userName + ":" +
this.password).getBytes(Charset.defaultCharset())));
            Map<String, String> reqParams = new HashMap<String, String>();
            reqParams.put("from date", fromDate);
            regParams.put("to date", toDate);
            regParams.put("filename", fileName);
            Map<String, String> restResult = CSSRESTHelper.callRestApi(new
HashMap(), url, reqHeaders, reqParams,
                    "POST");
            String jobStatus =
CSSRESTHelper.getCSSRESTJobCompletionStatus(restResult, reqHeaders);
            System.out.println(jobStatus);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
    private static class CSSRESTHelper {
       public static final String REST CALL STATUS = "REST CALL STATUS";
       public static final String REST CALL RESPONSE = "REST CALL RESPONSE";
       private static Map<String, String> callRestApi (Map context, String
url, Map<String, String> requestHeaders,
                Map<String, String> requestParams, String methodType) {
            HttpURLConnection urlConnection = null;
            Map<String, String> restResult = new HashMap<String, String>();
            restResult.put(REST_CALL_STATUS, "-1");
            boolean isPostMethod = "POST".equalsIgnoreCase(methodType) ||
"PUT".equalsIgnoreCase(methodType);
            try {
                URI baseUri = new URI(url);
                URI uri = null;
                String reqParams = (requestParams != null ?
buildRequestParams(context, requestParams, isPostMethod)
                        : null);
                if (isPostMethod) {
                    uri = new URI(baseUri.getScheme(),
baseUri.getAuthority(), baseUri.getPath(), null, null);
                } else {
                    uri = new URI(baseUri.getScheme(),
baseUri.getAuthority(), baseUri.getPath(), regParams, null);
                }
                urlConnection = (HttpURLConnection)
```

```
uri.toURL().openConnection();
                urlConnection.setRequestMethod(methodType);
                if (requestHeaders != null) {
                    Set<String> requestHeaderKeys = requestHeaders.keySet();
                    for (String requestHeaderKey : requestHeaderKeys) {
                        urlConnection.setRequestProperty(requestHeaderKey,
requestHeaders.get(requestHeaderKey));
                    }
                }
                urlConnection.setUseCaches(false);
                urlConnection.setDoOutput(true);
                urlConnection.setDoInput(true);
                if (isPostMethod) {
                    OutputStreamWriter writer = new
OutputStreamWriter(urlConnection.getOutputStream(),
                            Charset.defaultCharset());
                    writer.write(reqParams);
                    writer.flush();
                }
                if (!isPostMethod) {
                    urlConnection.connect();
                }
                int status = urlConnection.getResponseCode();
                restResult.put(REST CALL STATUS, String.valueOf(status));
                String response = readResponse(context,
                        (status >= 400 ? urlConnection.getErrorStream() :
urlConnection.getInputStream()));
                restResult.put(REST CALL RESPONSE, response);
            } catch (Exception e) {
                restResult.put(REST CALL RESPONSE, e.getMessage());
            } finally {
                if (urlConnection != null) {
                    urlConnection.disconnect();
                }
            }
            return restResult;
        ł
        private static String buildRequestParams (Map context, Map<String,
String> requestParams, boolean isPostMethod) {
            String reqParams = null;
            try {
                StringBuilder result = new StringBuilder();
                Set<String> reqParamKeys = requestParams.keySet();
                boolean first = true;
                for (String reqParamKey : reqParamKeys) {
                    if (first)
                        first = false;
                    else
                        result.append("&");
                    String regParamValue = requestParams.get(regParamKey);
```

```
result.append((isPostMethod ?
URLEncoder.encode(reqParamKey, "UTF-8") : reqParamKey));
                    result.append("=");
                    result.append((isPostMethod ?
URLEncoder.encode(reqParamValue, "UTF-8") : reqParamValue));
                }
                reqParams = result.toString();
            } catch (UnsupportedEncodingException e) {
                e.printStackTrace();
            }
            return reqParams;
        }
        private static String readResponse (Map context, InputStream
urlInStream) {
            BufferedReader br = null;
            String response = "";
            try {
                String line;
                br = new BufferedReader(new InputStreamReader(urlInStream,
Charset.defaultCharset()));
                while ((line = br.readLine()) != null) {
                    response += line;
                }
            } catch (Exception e) {
                response += e.getMessage();
            } finally {
                if (br != null) {
                    try {
                        br.close();
                    } catch (IOException e) {
                        e.printStackTrace();
                    }
                }
            }
            return response;
        }
        private static String getCSSRESTJobUrlFromResponse(String response) {
            String jobUrl = "";
            try {
                JSONObject jsonResponse = new JSONObject(response);
                JSONArray links = (JSONArray) jsonResponse.get("links");
                JSONObject jobStatusLink = (JSONObject) links.get(1);
                jobUrl = jobStatusLink.get("href").toString();
            } catch (Exception ex) {
                ex.printStackTrace();
            return jobUrl;
        }
        private static String getCSSRESTJobStatusFromResponse(String
response) {
            String jobStatus = "";
            try {
                JSONObject jsonResponse = new JSONObject(response);
```

```
jobStatus = jsonResponse.get("status").toString();
            } catch (Exception ex) {
                ex.printStackTrace();
            return jobStatus;
        }
        private static String getCSSRESTJobCompletionStatus (Map<String,
String> restResult, Map<String, String> reqHeader) {
            String completionStatus = "";
            try {
                String restStatus =
restResult.get(CSSRESTHelper.REST_CALL_STATUS);
                if (restStatus.equalsIgnoreCase("200")) {
                    String jobUrl =
getCSSRESTJobUrlFromResponse(restResult.get(CSSRESTHelper.REST CALL RESPONSE))
;
                    String restJobStatus = "-1";
                    Map<String, String> jobStatusResult = null;
                    while (restJobStatus.equalsIgnoreCase("-1")) {
                        jobStatusResult = CSSRESTHelper.callRestApi(new
HashMap(), jobUrl, reqHeader, null, "GET");
                        String jobStatusStatus =
jobStatusResult.get(CSSRESTHelper.REST CALL STATUS);
                        if (jobStatusStatus.equalsIgnoreCase("200")) {
                            restJobStatus = getCSSRESTJobStatusFromResponse(
jobStatusResult.get(CSSRESTHelper.REST CALL RESPONSE));
                        }
                        Thread.sleep(1000);
                    }
                    completionStatus =
jobStatusResult.get(CSSRESTHelper.REST CALL RESPONSE);
                }
            } catch (Exception ex) {
                ex.printStackTrace();
            1
            return completionStatus;
        }
    };
}
```

Profitability and Cost Management Common Helper Functions for cURL

Common Helper Functions for cURL

```
#!/bin/sh
#set -x
export PATH=$PATH:<PATH_TO_JQ_BINARY>
SERVER_URL="<SERVICE_URL>"
USERNAME="<USERNAME>"
PASSWORD="<PASSWORD>"
API VERSION="v1"
```



```
# To avoid SSL connection issue in the environment please add -k option for
below curl commands.
funcCallRESTAPI() {
    if [ "$1" == "GET" ] || [ "$1" == "DELETE" ]; then
        if [ "$6" != "" ]; then
            echo `curl -s -u $4:$5 -H "$3" --request $1 -G $2 -d "$6"`
        else
            echo `curl -s -u $4:$5 -H "$3" --request $1 -G $2`
        fi
    else
                if [ "$6" != "" ]; then
                        echo `curl -s -u $4:$5 -H "$3" --request $1 $2 -d
"$6"`
                else
                        echo `curl -s -u $4:$5 -H "$3" --request $1 $2`
                fi
    fi
}
funcCSSRESTHelper() {
        jobOutput=$(funcCallRESTAPI "$1" "$2" "$3" "$4" "$5" "$6")
        jobUrl=`echo $jobOutput | jq '.links[1].href'
        if [ $jobUrl != null ]; then
                jobUrl="${jobUrl%\"}"
                jobUrl="${jobUrl#\"}"
                jobStatus=-1
                while [ $jobStatus == -1 ]; do
                        jobOutput=$(funcCallRESTAPI "GET" "$jobUrl" "$header"
"$USERNAME" "$PASSWORD")
                        jobStatus=`echo $jobOutput | jq '.status'`
                done
                restStatus=`echo $jobOutput | jq '.details'`
                restStatus="${restStatus%\"}"
                restStatus="${restStatus#\"}"
                statusMessage=""
                if [ $jobStatus == 0 ]; then
                        statusMessage="$7 completed successfully."
#"$restStatus"
                else
                        statusMessage=$restStatus
                fi
                   echo "$statusMessage"
        else
                failedMessage=`echo $jobOutput | jq '.details'`
        failedMessage="${failedMessage%\"}"
                failedMessage="${failedMessage#\"}"
                echo $failedMessage
        fi
}
funcAddUsers() {
    url="$SERVER URL/interop/rest/security/$API VERSION/users"
    params="filename=$1&userpassword=$2&resetpassword=$3"
    header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
    cssRESTAPI="AddUsers"
```

```
statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
   echo $statusMessage
}
funcRemoveUsers() {
       url="$SERVER URL/interop/rest/security/$API VERSION/users"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="RemoveUsers"
       statusMessage=$(funcCSSRESTHelper "DELETE" "$url" "$header"
"$USERNAME" "$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcAssignRole() {
       url="$SERVER URL/interop/rest/security/$API VERSION/users"
       params="filename=$1&jobtype=ASSIGN ROLE&rolename=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="AssignRole"
        statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcUnassignRole() {
       url="$SERVER URL/interop/rest/security/$API VERSION/users"
       params="filename=$1&jobtype=UNASSIGN ROLE&rolename=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="UnassignRole"
       statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcAddUsersToGroup() {
    url="$SERVER URL/interop/rest/security/$API VERSION/groups"
    params="filename=$1&jobtype=ADD USERS TO GROUP&groupname=$2"
    header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
    cssRESTAPI="AddUsersToGroup"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
}
funcRemoveUsersFromGroup() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1&jobtype=REMOVE USERS FROM GROUP&groupname=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="RemoveUsersFromGroup"
       statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcAddUserToGroups() {
```

```
url="$SERVER URL/interop/rest/security/$API VERSION/groups"
    params="filename=$1&jobtype=ADD USER TO GROUPS&username=$2"
    header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
    cssRESTAPI="AddUserToGroups"
    statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
    echo $statusMessage
funcRemoveUserFromGroups() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1&jobtype=REMOVE USER FROM GROUPS&username=$2"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="RemoveUserFromGroups"
       statusMessage=$(funcCSSRESTHelper "PUT" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcGenerateRoleAssignmentReport() {
       url="$SERVER URL/interop/rest/security/$API VERSION/
roleassignmentreport"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="generateRoleAssignmentReport"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcGenerateUserGroupReport() {
       url="$SERVER URL/interop/rest/security/$API VERSION/usergroupreport"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded;charset=UTF-8"
       cssRESTAPI="generateUserGroupReport"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcAddGroups() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="addGroups"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcRemoveGroups() {
       url="$SERVER URL/interop/rest/security/$API VERSION/groups"
       params="filename=$1"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
        cssRESTAPI="removeGroups"
        statusMessage=$(funcCSSRESTHelper "DELETE" "$url" "$header"
```

```
"$USERNAME" "$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
funcGenerateInvalidLoginReport() {
       url="$SERVER URL/interop/rest/security/$API VERSION/
invalidloginreport"
    params="from date=$1&to date=$2&filename=$3"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="generateInvalidLoginReport"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
}
funcGenerateRoleAssignmentAuditReport() {
       url="$SERVER URL/interop/rest/security/$API VERSION/
roleassignmentauditreport"
     params="from date=$1&to date=$2&filename=$3"
       header="Content-Type: application/x-www-form-urlencoded; charset=UTF-8"
       cssRESTAPI="generateRoleAssignmentAuditReport"
       statusMessage=$(funcCSSRESTHelper "POST" "$url" "$header" "$USERNAME"
"$PASSWORD" "$params" "$cssRESTAPI")
       echo $statusMessage
}
#funcAddUsers test1.csv password false
#funcRemoveUsers test2.csv
#funcAssignRole test3.csv "Power User"
#funcUnAssignRole test4.csv Viewer
#funcAddUsersToGroup test5.csv TestNativeGroup1
#funcRemoveUsersFromGroup test6.csv TestNativeGroup2
#funcGenerateRoleAssignmentReport RoleAssignmentReport.csv
#funcGenerateUserGroupReport UserGroupReport.csv
#funcAddUserToGroups groups.csv joe
#funcRemoveUserFromGroups groups.csv joe
#funcAddGroups CreateGroup1.csv
#funcRemoveGroups DeleteGroup1.csv
#funcGenerateInvalidLoginReport 2021-06-01 2021-06-10 invalidLoginReport.csv
#funcGenerateRoleAssignmentAuditReport 2021-06-01 2021-06-10
roleAssignmentAuditReport.csv
```

Profitability and Cost Management Common Helper Functions for Groovy

Common Helper Functions for Groovy

import java.nio.charset.StandardCharsets
import groovy.json.JsonSlurper
serverUrl="<SERVICE_URL>"

```
username="<DOMAINNAME.USERNAME>"
password="<PASSWORD>"
```



```
apiVersion = "v1";
userCredentials = username + ":" + password;
basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
def getResponse(is) {
   BufferedReader br = new BufferedReader(new InputStreamReader(is));
    StringBuilder sb = new StringBuilder();
    String line;
    while ((line = br.readLine()) != null) {
        sb.append(line+"\n");
    }
   br.close();
    return sb.toString();
}
def getUrlFromResponse(scenario, response, relValue) {
   def object = new JsonSlurper().parseText(response)
    def pingUrlStr
    if (object.status == -1) {
        println "Started - " + scenario
        def links = object.links
        links.each{
            if (it.rel.equals(relValue)) {
                pingUrlStr=it.href
        }
    } else {
        println "Error details: " + object.details
        System.exit(0);
    }
    return pingUrlStr
}
def getJobStatus(pingUrlString, methodType) {
    def pingUrl = new URL(pingUrlString);
    def completed = false;
    while (!completed) {
        pingResponse = executeRequest(pingUrl, methodType, null,
"application/x-www-form-urlencoded");
        status = getJobStatusFromResponse(pingResponse);
        if (status == "Processing") {
            try {
                println "Processing. Please wait..."
                Thread.sleep(5000);
            } catch (InterruptedException e) {
                completed = true
        } else {
            println status
            completed = true
        }
    }
}
```

```
def getJobStatusFromResponse(response) {
    def object = new JsonSlurper().parseText(response)
    def status = object.status
    if (status == -1)
        return "Processing"
    else if (status == 0)
        return "Completed"
    else
        return object.details
}
def getJobDetailsFromResponse(response) {
    def object = new JsonSlurper().parseText(response)
    def details = object.details
    if (details != null)
        return object.details
    else
       return null
}
def executeRequest(url, requestType, payload, contentType) {
   HttpURLConnection connection = (HttpURLConnection) url.openConnection();
    connection.setDoOutput(true);
    connection.setInstanceFollowRedirects(false);
    connection.setRequestMethod(requestType);
    connection.setRequestProperty("Content-Type", contentType);
    11
                 connection.setRequestProperty("charset",
StandardCharsets.UTF 8);
    connection.setRequestProperty("Authorization", basicAuth);
    connection.setUseCaches(false);
    if (payload != null) {
        OutputStreamWriter writer = new
OutputStreamWriter(connection.getOutputStream());
        writer.write(payload);
        writer.flush();
    }
    int statusCode
    try {
        statusCode = connection.responseCode;
    } catch (all) {
        println "Error connecting to the URL"
        System.exit(0);
    }
   def response
    if (statusCode == 200 || statusCode == 201) {
        if (connection.getContentType() != null && !
connection.getContentType().startsWith("application/json")) {
            println "Error occurred in server"
            System.exit(0)
        ł
        InputStream is = connection.getInputStream();
        if (is != null)
```

```
response = getResponse(is)
    } else {
        println "Error occurred while executing request"
        println "Response error code : " + statusCode
        InputStream is = connection.getErrorStream();
        if (is != null && connection.getContentType() != null &&
connection.getContentType().startsWith("application/json"))
           println getJobStatusFromResponse(getResponse(is))
        System.exit(0);
    }
    connection.disconnect();
    return response;
}
def addUsersToGroup(fileName, groupName) {
    String scenario = "Adding users in " + fileName + " to group " +
groupName;
    String params = "jobtype=ADD USERS TO GROUP&filename="+ fileName
+"&groupname="+ groupName;
    def url = null;
    def response = null;
   try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
def removeUsersFromGroup(fileName, groupName) {
    String scenario = "Removing users in " + fileName + " from group " +
groupName;
    String params = "jobtype=REMOVE USERS FROM GROUP&filename="+ fileName
+"&groupname="+ groupName;
    def url = null;
    def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
       System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
```

```
"GET");
  }
}
def addUserToGroups(fileName, userName) {
    String scenario = "Adding users in " + fileName + " to group " + userName;
    String params = "jobtype=ADD USER TO GROUPS&filename="+ fileName
+"&username="+ userName;
    def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def removeUserFromGroups(fileName, userName) {
    String scenario = "Removing users in " + fileName + " from group " +
userName;
    String params = "jobtype=REMOVE USER FROM GROUPS&filename="+ fileName
+"&username="+ userName;
   def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
       println "Please enter a valid URL"
       System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def addUsers(fileName, resetPassword, userPassword) {
    String scenario = "Creating users in " + fileName;
    String params = "jobtype=ADD USERS&filename="+ fileName
+"&resetpassword="+ resetPassword +"&userpassword="+ userPassword;
    def url = null;
    def response = null;
```



```
try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
def addUsers(fileName) {
    addUsers(fileName, null, null);
}
def deleteUsers(fileName) {
    String scenario = "Deleting users in " + fileName;
   String params = null;
   def url = null;
   def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users?filename=" + fileName);
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "DELETE", null, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def assignUsersRoles(fileName, roleName) {
    String scenario = "Assigning users in " + fileName + " with role " +
roleName;
    String params = "jobtype=ASSIGN ROLE&filename="+ fileName +"&rolename="+
roleName;
   def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
       System.exit(0);
    }
    response = executeRequest(url, "PUT", params, "application/x-www-form-
```

```
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def unassignUsersRoles(fileName, roleName) {
    String scenario = "Un-assigning users in " + fileName + " with role " +
roleName;
    String params = "jobtype=UNASSIGN ROLE&filename="+ fileName
+"&rolename="+ roleName;
    def url = null;
    def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
users");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
       System.exit(0);
    }
   response = executeRequest(url, "PUT", params, "application/x-www-form-
urlencoded");
   if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
}
def generateRoleAssignmentReport(fileName) {
    String scenario = "Generating Role assignment report in " + fileName;
    String params = "jobtype=GENERATE ROLE ASSIGNMENT REPORT&filename="+
fileName;
   def url = null;
   def response = null;
    try {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
roleassignmentreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
       getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def generateUserGroupReport(fileName) {
    String scenario = "Generating User Group Report in " + fileName;
    String params = "jobtype=GENERATE USER GROUP REPORT&filename="+ fileName;
```

```
def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
usergroupreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def addGroups(fileName) {
   println "addgroups"
    String scenario = "Creating Groups in " + fileName;
   String params = "filename="+ fileName;
   def url = null;
   def response = null;
    trv {
       url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
    }
1
def removeGroups(fileName) {
    String scenario = "Deleting Groups in " + fileName;
   String params = null;
   def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
groups?filename=" + fileName);
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "DELETE", null, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
```

```
}
}
def generateRoleAssignmentAuditReport(from date,to date,fileName) {
    String scenario = "Generating Role assignment audit report in " +
fileName;
   String params =
"jobtype=GENERATE ROLE ASSIGNMENT AUDIT REPORT&from date="+from date+"&to date
="+to date+"&filename="+ fileName;
   def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
roleassignmentauditreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
    response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
def generateInvalidLoginReport(from date, to date, fileName) {
    String scenario = "Generating Invalid Login report in " + fileName;
    String params =
"jobtype=GENERATE INVALID LOGIN REPORT&from date="+from date+"&to date="+to da
te+"&filename="+ fileName;
    def url = null;
    def response = null;
    try {
        url = new URL(serverUrl + "/interop/rest/security/" + apiVersion + "/
invalidloginreport");
    } catch (MalformedURLException e) {
        println "Please enter a valid URL"
        System.exit(0);
    }
   response = executeRequest(url, "POST", params, "application/x-www-form-
urlencoded");
    if (response != null) {
        getJobStatus(getUrlFromResponse(scenario, response, "Job Status"),
"GET");
   }
}
//Execute commands here
//addUsersToGroup("Users.csv",
"G1");
                   //PUT
//removeUsersFromGroup("Users.csv",
"G1");
```

```
//PUT
//addUsers("AddUsers123.csv", "false",
"newPassword");
                                                        //POST
11
addUsers("AddUsers456.csv");
//POST
11
deleteUsers("RemoveUsers.csv");
                                                                //DELETE
//assignUsersRoles("Users.csv", "Service
Administrator");
                                            //PUT
//assignUsersRoles("users.csv",
"viewer");
                                                                      //PUT
//unassignUsersRoles("Users.csv", "Drill
Through");
                                                               //PUT
//
generateRoleAssignmentReport("GroovySampleReport3.csv");
          // POST
11
generateUserGroupReport("UserGroupReportGroovy.csv");
           // POST
//addUserToGroups("Group.csv",
                                                         //PUT
"user1");
//removeUserFromGroups("groups.csv",
"joe");
                                                  //PUT
//
addGroups("CreateGroup1.csv");
// POST
11
removeGroups("DeleteGroup1.csv");
   // DELETE
//generateInvalidLoginReport("2020-06-01", "2021-06-10",
"report12345.csv"); //POST
```

Н

Sample Starter Kit for Consultants - Integration with Business Intelligence Cloud Service

This topic describes a sample starter kit that can be used by infrastructure consultants to plan integration for Planning with Business Intelligence Cloud Service.

Prerequisites

- You have accounts for Business Intelligence Cloud Service, Planning, and Oracle Application Express.
- You have considerable technical and functional expertise with Business Intelligence Cloud Service, Planning, Oracle Application Express, REST, Groovy, and scripting.

These are the basic tasks for the sample starter kit for consultants:

- Export data and metadata from Planning using the Planning REST API.
- Download data and metadata to an on-premise server using the Planning REST API.
- Use the metadata to create schema/tables in Business Intelligence Cloud Service using the Business Intelligence Cloud Service REST API.
- Populate the tables in Business Intelligence Cloud Service using the data imported from Planning by using the Business Intelligence Cloud Service REST API.

Note:

If you are using DBaaS, the target reporting database can optionally be accessed by

standard tools like SQL Developer and Toad.

Note:

The DataSync tool (available from OTN) can also be used to create tables and load and update data in the tables. Data uploads can be scheduled using the DataSync jobs and native scheduler. This approach will work for Database Schema Service and DBaaS used as reporting database for BICS.

These are the basic steps for the sample starter kit for consultants:

- **1.** Install the scripting engine and deploy demo scripts.
- 2. Use the SQL APEX REST API client to call a client sample that calls a SQL query with a bind variable passed on the URL.
- Use the Business Intelligence REST API client to provide methods as necessary for your use case.
- 4. Use the Planning REST API client to provide methods as necessary for your use case.



- 5. Incorporate helper functions.
- 6. Integrate Planning with Business Intelligence Cloud Service using a demo script.

Planning, Business Intelligence Cloud Service, and SQL Web REST services expose functions available in EPM Automate, DataSync, and for direct database SQL/PLSQL calls. The REST APIs can be scripted using any language. This appendix describes a sample starter kit to show how this can be implemented using Groovy for demonstration purposes. For information on REST APIs for Business Intelligence Cloud Service and Application Express, see:

- Business Intelligence REST APIs
- Application Express REST APIs

Installing the Scripting Engine and Deploying Demo Scripts

For reference, demo scripts are described here: Integration of Planning to Business Intelligence Cloud Service.

1. Install the Groovy engine, http://www.groovy-lang.org/install.html

Select the binary release (https://bintray.com/artifact/download/groovy/maven/apache-groovy-binary-2.4.5.zip).

2. Create the files as shown in Integration of Planning to Business Intelligence Cloud Service, and put them in a folder structure similar to the following:

```
pbcsbics
   PBCSBICSAutomation.properties
   com
      oracle
      ceal
      <groovy files>
```

3. Open a shell:

```
cd <yourrootfolder>\pbcsbics
```

On a single line, type:

```
<yourrootfolder>\apache-groovy-binary-2.4.5\groovy-2.4.5\bin\groovy -
classpath
<yourrootfolder>\pbcsbics
<yourrootfolder>\pbcsbics\com\oracle\ceal\PBCSBICSIntegration.groovy
```

SQL Application Express REST API client

The Application Express REST API client sample demonstrates calling an SQL query with a bind variable passed on the URL.

Client creation using com.oracle.ceal.ApexRestClient

```
apexClient=new ApexRestClient(apexRestUrl, proxy Host, proxy Port,cloud
identityDomain, cloud username, cloud password,
ignoreSSLCertificationPathErrors)
```



- Apex REST URL in the format: https://server

Example: https://<SERVER>.oraclecloud.com/apex

- proxy host:
 - * Leave empty if not using a proxy
 - * If using a tool like Fiddler for HTTP captures, specify localhost.
 - If you need to go through a proxy to connect to Oracle cloud services, specify the proxy host.
- proxy port:
 - * Leave empty if not using a proxy
 - * If using Fiddler, use 8888.
 - * Otherwise, enter your proxy port.
- Cloud identity domain: this is provided with your cloud login. You can also find this in the APEX URL.
- ignoreSSLCertificationPathErrors (true or false): Set this to true if connecting through a proxy like Fiddler.
- Calling an SQL Query defined in APEX / SQL Workshop / RESTful web services

The REST web service must be created first. For more information, read this Oracle By Example: http://www.oracle.com/webfolder/technetwork/tutorials/obe/cloud/13_2/dbservice/ restfulws/restfulws.html

```
apexClient.launchSQLQueryUsingGETAndVariableOnUrl("<module name>/<uri>",
"<bind variable>")
```

Example:

apexClient.launchSQLQueryUsingGETAndVariableOnUrl("bics/test", "7839")

This example uses the following definition of the REST service in APEX:

RESTful Service Module: bics/ URI Template: test/{ID} Method: GET Source Type: Query Format: JSON Requires Secure Access: YES Source: Select EMPNO, ENAME, JOB, MGR, HIREDATE, SAL, COMM, DEPTNO from EMP where EMPNO = :ID

The URL call will be in the following format:

https://<SERVER>.oraclecloudapps.com/apex/bics/test/7839

The response will be in the following format:

```
Response Content-Type:application/json
```

```
{"next":{"$ref":"https://<SERVER>.oraclecloudapps.com/apex/bics/test/7839?
page=1"},"items":
[{"empno":7839,"ename":"KING","job":"PRESIDENT","hiredate":"1981-11-17T00:0
0:002","sal":5000,"deptno":10}]}
```

Calling a PL/SQL defined in APEX / SQL Workshop / RESTful web services

A method is available, but all the configuration work must be done in APEX.

```
apexClient.launchProcUsingGET("<module name>/<uri>")
```



The definition of the REST service in APEX is for this example:

RESTful Service Module: bics/ URI Template: plsql/ Method: GET Source Type: PL/SQL Requires Secure Access: YES Source:

```
DECLARE
       prevdeptno
                    number;
       deptloc
                    varchar2(30);
       deptname
                    varchar2(30);
       CURSOR getemps IS select * from emp
               where ((select job from emp where ename = :empname) IN
('PRESIDENT', 'MANAGER'))
                        or deptno = (select deptno from emp where ename
= :empname)
                        order by deptno, ename;
       BEGIN
           sys.htp.htmlopen;
           sys.htp.headopen;
           sys.htp.title('Departments');
           sys.htp.headclose;
           sys.htp.bodyopen;
            for emprecs in getemps
           loop
           if emprecs.deptno != prevdeptno or prevdeptno is null then
                           select dname, loc into deptname, deptloc
                               from dept where deptno = (select deptno
from emp where ename = emprecs.ename);
                     if prevdeptno is not null then
                            sys.htp.print('');
         end if;
                     sys.htp.print('Department ' || deptname || ' located
in ' || deptloc || '');
                     sys.htp.print('');
         end if;
           sys.htp.print('' || emprecs.ename || ', ' || emprecs.job
|| ', ' || emprecs.sal || '');
           prevdeptno := emprecs.deptno;
           end loop;
           sys.htp.print('');
           sys.htp.bodyclose;
            sys.htp.htmlclose;
       END;
       URL call will be in the form: https://<SERVER>.oraclecloudapps.com/
apex/bics/plsql/
       Response will be in following format for this specific plsql
example
                Response Content-Type:text/html; charset=UTF-8
                <HTML>
                <HEAD>
                <TITLE>Departments</TITLE>
                </HEAD>
                <BODY>
                </BODY>
                    </HTML>
```

Business Intelligence REST API Client

The Business Intelligence REST API client provides the following methods:

Client creation using com.oracle.ceal.BicsRestClient

```
(BicsClientRestClient.groovy)bicsClient=new BicsRestClient(bics Rest Url, proxy Host, proxy Port,cloud identityDomain, cloud username, cloud password, ignoreSSLCertificationPathErrors)
```

- Business Intelligence REST URL in the format: https://servername

Example: https://<SERVER>.oraclecloud.com

- proxy host:
 - * Leave empty if not using a proxy
 - * If using a tool like Fiddler for HTTP captures, specify localhost.
 - * If you need to go through a proxy to connect to Oracle cloud services, specify the proxy host.
- proxy port:
 - Leave empty if not using a proxy
 - * If using Fiddler, use 8888.
 - * Otherwise, enter your proxy port.
- Cloud identity domain: this is provided with your cloud login. You can also find this in the BI URL.
- ignoreSSLCertificationPathErrors (true or false): Set this to true if connecting through a proxy like Fiddler.
- About bics

```
bicsClient.aboutBics()
```

List all tables

bicsClient.listAllTables()

Get table info

bicsClient.getTableInfo(table name)

Delete table

```
bicsClient.deleteTable(table name)
```

Create a table with X columns and a specific column name prefix

bicsClient.createTableToLoadCSV(table name, number of columns , column prefix)
Example:

```
bicsClient.createTableToLoadCSV("ceal 4", 3 ,"MYCOL")
```

This creates a table called CEAL_4 with three columns named: MYCOL1, MYCOL2, MYCOL3



By default the columns have the following properties:

```
"dataType":"VARCHAR" // creates a VARCHAR2 column in database
    "length":300,
    "precision":0,
    "nullable":true,
    "defaultValue":null,
```

These values can be modified in BicsRestClient.groovy in the createTableToLoadCSV method

Delete data from table

bicsClient.deleteDataFromTable(table name)

Load data in table

```
loadDataInTableUsingCSV(tableName, localCsvFilePath, localCsvFileName,
delimiterInCsv,numberOfColumnsInCsv,numberOfLinesToSkip,columnPrefixInTable,is
Zipped)
```

Example:

```
bicsClient.loadDataInTableUsingCSV("ceal_4","d:\
\temp","export.csv",",",3,0,"MYCOL",false)
```

Create a table with a specific column name

bicsClient.createTableToLoadCSVWithHeaderNames("ceal 8", listHeaders)

Load data in table using mappings to specific column names

```
loadDataInTableUsingCSVAndHeader(tableName, localCsvFilePath,
localCsvFileName, delimiterInCsv,numberOfLinesToSkip,listHeaders,isZipped)
```

Example:

```
bicsClient.loadDataInTableUsingCSVAndHeader("ceal_8","d:\
\temp",fileNameInZip,",",1,listHeaders,false)
```

Planning REST API Client

The Planning REST API client provides the following methods:

 Client creation using com.oracle.ceal.PbcsRestClient (PbcsClientRestClient.groovy)

```
PbcsRestClient pbcsClient=new
PbcsRestClient(pbcsParams.planningRestUrl,pbcsParams.interopRestUrl,pbcsPar
ams.proxyHost,pbcsParams.proxyPort,pbcsParams.identityDomain,pbcsParams.use
rname, pbcsParams.password, pbcsParams.ignoreSSLCertificationPathErrors)
```

List all files

```
pbcsClient.listFiles()
```

Delete a file

pbcsClient.deleteFile(fileName)

Export data



response=pbcsClient.exportData(appName, Job name for export, export filename
on server)

Get job status

pbcsClient.getJobStatus(appName,jobId)

Download file

pbcsClient.downloadFile(server file name, local destination folder)

Export metadata

pbcsClient.exportMetaData(appName,job name for metadata export, Export filename on server)

Execute LCM Export

pbcsClient.executeLCMExport(snapshot name)

Run business rule

pbcsClient.runBusinessRule(appname, business rule, runtime prompts)

Example:

pbcsClient.runBusinessRule("Vision", "AggOliv", "{Period:Q1, Entity:USA}")

Cube refresh

pbcsClient.cubeRefresh(appname,jobname)

Example:

pbcsClient.cubeRefresh("Vision", "RefreshOliv")

Run plantype map

pbcsClient.runPlanTypeMap(appname, jobname, cleardata true/false)

Example:

pbcsClient.cubeRefresh("Vision","RefreshOliv")pbcsClient.runPlanTypeMap("Visio n","MapOliv","false")

Run Ruleset

pbcsClient.runRuleSet(appname, ruleset)

Import data

pbcsClient.importData(appname, jobname, export filename)

Last parameter (export filename) defaults to jobname if no server import filename is specified

Import metadata

pbcsClient.importMetaData(appname, jobname, export metadata filename)

Last parameter defaults to jobname if no server import filename is specified

Example:

pbcsClient.importMetaData("Vision", "ImportMetaOliv", "ExportMetadataOliv.zip")

Execute LCM import

pbcsClient.executeLCMImport(snapshot name)

Upload file



pbcsClient.uploadFile(Local folder containing file to upload to server,file to upload)

Example:

```
//local folder, and filename as parameters
pbcsClient.uploadFile("d:\\temp","ExportOliv.zip")
```

Helper Functions

The properties file containing connection parameters can also be accessed using this class:

com.oracle.ceal.BICSAutomationParameters Or com.oracle.ceal.PBCSAutomationParameters Or

com.oracle.ceal.APEXAutomationParameters

The Properties file must contain for BICS:

```
proxyHost=
proxyPort=
ignoreSSLCertificationPathErrors=true or false
bicsRestUrl=https://biserverurl
bicsIdentityDomain=
bicsUsername=
bicsPassword=
```

// this loads a file named PBCSBICSAutomation.properties
PbcsRestClient pbcsClient

```
PBCSAutomationParameters pbcsParams=new
PBCSAutomationParameters('PBCSBICSAutomation.properties')
```

```
pbcsClient=new
```

PbcsRestClient(pbcsParams.planningRestUrl,pbcsParams.interopRestUrl,pbcsPar ams.proxyHost,pbcsParams.proxyPort,pbcsParams.identityDomain,pbcsParams.use rname, pbcsParams.password, pbcsParams.ignoreSSLCertificationPathErrors)

Properties file must contain for Planning:

```
pbcsPlanningRestUrl=https://<SERVER>/rest/11.1.2.3.600
pbcsInteropRestUrl=https://<SERVER>/interop/rest/11.1.2.3.600
pbcsIdentityDomain=
pbcsUsername=
pbcsPassword=
proxyHost=
proxyHost=
ignoreSSLCertificationPathErrors=true or false
// this loads a file named PBCSBICSAutomation.properties
ApexRestClient apexClient
APEXAutomationParameters apexParams=new
```

APEXAutomationParameters ('PBCSBICSAutomation.properties')



```
apexClient=new
ApexRestClient(apexParams.apexRestUrl,apexParams.proxyHost,apexParams.proxy
Port,apexParams.identityDomain,apexParams.username, apexParams.password,
apexParams.ignoreSSLCertificationPathErrors)
```

The properties file must contain for Planning:

```
apexRestUrl=https://apexserver/apex
apexIdentityDomain=
apexUsername=
apexPassword=
proxyHost=
proxyPort=
ignoreSSLCertificationPathErrors=true or false
```

- The Planning REST client also contains helper functions for dealing with CSV files:
 - Finding the number of columns in a .csv file

Example:

```
nbColsInCsv=pbcsClient.findNbOfColsInCSV("d:\\temp\\", "export.csv", ",")
```

Finding header names in a .csv file (first line):

```
listHeaders=pbcsClient.getHeadersInCSVAsList(folder containing csv file,
csv filename, delimiter)
```

Example:

listHeaders=pbcsClient.getHeadersInCSVAsList("d:\\temp\\", fileName, ",")

The Planning REST client also contains helpers functions for dealing with asynchronous calls:

```
Class WaitForCode
```

Method retry(sleep time, nb of retries) { code to run }

Example:

}

The Business Intelligence Cloud Service REST client also contains helpers functions for trimming lists:

```
def truncateList(listName, truncateLength)
```



Example to truncate headers for columns to 30 characters:

Integration of Planning to Business Intelligence Cloud Service

The demo scripts in the following topics show Groovy examples of integration for Planning and Business Intelligence Cloud Service. Review these topics to see Groovy examples.

Groovy Sample – PBCSBICSIntegration.groovy

```
package com.oracle.ceal
class PBCSBICSIntegration {
    static main(args) {
        def pbcsExportfiles
        PbcsRestClient pbcsClient
        BicsRestClient bicsClient
        ApexRestClient apexClient
        PBCSAutomationParameters pbcsParams=new
PBCSAutomationParameters ('PBCSBICSAutomation.properties')
        if (pbcsParams.isConfigValid() == true) {
            pbcsClient=new
PbcsRestClient(pbcsParams.planningRestUrl,pbcsParams.interopRestUrl,pbcsParams
.proxyHost,pbcsParams.proxyPort,pbcsParams.identityDomain,pbcsParams.username,
 pbcsParams.password, pbcsParams.ignoreSSLCertificationPathErrors)
            pbcsClient.listFiles()
            pbcsClient.deleteFile("ExportOliv.zip")
            pbcsClient.deleteFile("ExportMetadataOliv.zip")
            def response
            //last parameter is server filename for export. If not set, this
defaults to jobname as filename
response=pbcsClient.exportData("Vision", "JobOliv", "ExportOliv.zip")
            String jobId = "";
            jobId=pbcsClient.getJobIdFromJSONResponse(response)
            if (jobId!="") println "Export running with jobid:"+jobId
            // Looping to get jobId status while it s being processed on
server
            // In this example waiting 6 secs each time, and trying 100 times
to get a valid status (not processing)
            WaitForCode.retry(6000,100) {
                // second parameter is jobid (is obtained from json response
from server)
```



```
def responseJobStatus
                responseJobStatus=pbcsClient.getJobStatus("Vision",jobId)
                if (responseJobStatus.contains("Processing")) throw new
Exception ("Job not finished"
            }
            //download server file name to local folder
            pbcsClient.downloadFile("ExportOliv.zip", "d:\\temp")
            //last parameter is server filename for export. If not set, this
defaults to jobname as filename
pbcsClient.exportMetaData("Vision", "JobOlivMeta", "ExportMetadataOliv.zip")
            pbcsClient.downloadFile("ExportMetadataOliv.zip","d:\\temp")
            pbcsExportfiles=pbcsClient.unZip("d:\\temp\\ExportOliv.zip","d:\
\temp/\")
            pbcsExportfiles.each { fileNameInZip ->
                println "-->"+fileNameInZip
                println "Nb of cols in csv:"+pbcsClient.findNbOfColsInCSV("d:\
\temp\\", fileNameInZip, ",")
                def headers
                headers=pbcsClient.getHeadersInCSVAsList("d:\\temp\\",
fileNameInZip, ",")
                headers.each { header ->
                    println "header -- "+header+"--"
                }
                println "<--"
            }
        } else {
            println "Configuration for PBCS is invalid. Please check
PBCSBICSAutomation.properties"
        }
        BICSAutomationParameters bicsParams=new
BICSAutomationParameters ('PBCSBICSAutomation.properties')
        if (bicsParams.isConfigValid() == true) {
            // load to bics
            bicsClient=new
BicsRestClient (bicsParams.bicsRestUrl, bicsParams.proxyHost, bicsParams.proxyPor
t, bicsParams.identityDomain, bicsParams.username, bicsParams.password,
bicsParams.ignoreSSLCertificationPathErrors)
            bicsClient.aboutBics()
            bicsClient.listAllTables()
            bicsClient.getTableInfo("ceal 4")
            bicsClient.deleteTable("ceal 4")
            // this creates a table with x columns MYCOL1 MYCOL2 MYCOL3
            bicsClient.createTableToLoadCSV("ceal 4", 3 ,"MYCOL")
            bicsClient.deleteDataFromTable("ceal 4")
            //loadDataInTableUsingCSV(tableName, localCsvFilePath,
localCsvFileName,
delimiterInCsv,numberOfColumnsInCsv,numberOfLinesToSkip,columnPrefixInTable,is
```

```
Zipped)
            bicsClient.loadDataInTableUsingCSV("ceal 4", "d:\
\temp", "export.csv", ", ", 3, 0, "MYCOL", false)
            println "**Uploading each file from zip**"
            pbcsExportfiles.each { fileNameInZip ->
                println "-->"+fileNameInZip
                def nbColsInCsv
                nbColsInCsv=pbcsClient.findNbOfColsInCSV("d:\\temp\\",
fileNameInZip, ",")
                println "Nb of cols in csv:"+nbColsInCsv
                def listHeaders
                listHeaders=pbcsClient.getHeadersInCSVAsList("d:\\temp\\",
fileNameInZip, ",")
                listHeaders=bicsClient.truncateList(listHeaders, 30)
                bicsClient.deleteTable("ceal 8")
                bicsClient.createTableToLoadCSVWithHeaderNames("ceal 8",
listHeaders )
                //loadDataInTableUsingCSVAndHeader(tableName,
localCsvFilePath, localCsvFileName,
delimiterInCsv,numberOfLinesToSkip,listHeaders,isZipped)
                bicsClient.loadDataInTableUsingCSVAndHeader("ceal 8", "d:\
\temp",fileNameInZip,",",1,listHeaders,false)
                println "<--"
            l
            println "****"
        } else {
            println "Configuration for BICS is invalid. Please check
PBCSBICSAutomation.properties"
        }
        APEXAutomationParameters apexParams=new
APEXAutomationParameters ('PBCSBICSAutomation.properties')
        if (apexParams.isConfigValid() == true) {
            // load to bics
            apexClient=new
ApexRestClient(apexParams.apexRestUrl,apexParams.proxyHost,apexParams.proxyPor
t,apexParams.identityDomain,apexParams.username, apexParams.password,
apexParams.ignoreSSLCertificationPathErrors)
            // see ApexRestClient.groovy method def
launchProcUsingGETAndParameterOnUrl(apexUri, parameter) for info on the rest
configuration on server
            apexClient.launchSQLQueryUsingGETAndVariableOnUrl("bics/test",
"7839")
            apexClient.launchProcUsingGET("bics/plsql/")
        } else {
            println "Configuration for Apex is invalid. Please check
PBCSBICSAutomation.properties"
        }
```



```
}
}
With PBCSBICSAutomation.properties like the following:
pbcsPlanningRestUrl=https://<SERVER>/HyperionPlanning/rest/11.1.2.3.600
pbcsInteropRestUrl=https://<SERVER>/interop/rest/11.1.2.3.600
pbcsIdentityDomain=
pbcsUsername=
pbcsPassword=
proxyHost=
proxyPort=
ignoreSSLCertificationPathErrors=false
bicsRestUrl=https://bicsserver
bicsIdentityDomain=
bicsUsername=
bicsPassword=
apexRestUrl=https://dbserver/apex
apexIdentityDomain=
apexUsername=
apexPassword=
```

Groovy Sample – PbcsRestClient.groovy

```
package com.oracle.ceal
import javax.net.ssl.HostnameVerifier
import javax.net.ssl.HttpsURLConnection
import javax.net.ssl.SSLContext
import javax.net.ssl.SSLSession
import javax.net.ssl.TrustManager
import javax.net.ssl.X509TrustManager
import java.net.HttpURLConnection
import java.util.regex.Pattern
import java.util.regex.Matcher
import java.util.zip.ZipEntry
import java.util.zip.ZipFile
class PbcsRestClient {
   private HttpURLConnection connection
   private def planningUrl
   private def interopUrl
   private def proxyHost
   private def proxyPort
   private def user
   private def pwd
   private def domain
   private def ignoreSSLCertsErrors
   public PbcsRestClient(planningServerUrl, interopServerUrl, httpProxyHost,
```

```
httpProxyPort, identityDomain,username, password,
ignoreSSLCertificationPathErrors) {
```

```
planningUrl=planningServerUrl
        interopUrl=interopServerUrl
        proxyHost=httpProxyHost
        proxyPort=httpProxyPort
        domain=identityDomain
        user=username
        pwd=password
        ignoreSSLCertsErrors=ignoreSSLCertificationPathErrors
    }
    def setProxyParams() {
        Properties systemProperties = System.getProperties()
        systemProperties.setProperty("http.proxyHost",proxyHost)
        systemProperties.setProperty("http.proxyPort",proxyPort)
        systemProperties.setProperty("https.proxyHost",proxyHost)
        systemProperties.setProperty("https.proxyPort",proxyPort)
    }
    def setSSLParams() {
        if (ignoreSSLCertsErrors !=null &&
ignoreSSLCertsErrors.toUpperCase() == "TRUE") {
            println "Ignoring SSL certification path errors"
            // Disable SSL cert validation
            def hostnameVerifier = [
                verify: { hostname, session -> true }
            1
            def trustManager = [
                    checkServerTrusted: { chain, authType -> },
                    checkClientTrusted: { chain, authType -> },
                    getAcceptedIssuers: { null }
            1
            HttpsURLConnection.setDefaultHostnameVerifier(hostnameVerifier as
HostnameVerifier)
HttpsURLConnection.setDefaultSSLSocketFactory(context.getSocketFactory())
            SSLContext context = SSLContext.getInstance("SSL")
            context.init(null, [trustManager as X509TrustManager] as
TrustManager[], null)
        }
    }
    def openConnection(restUrl,method,localFileNameWithPathForStorage) {
        println "Opening connection to $restUrl with method:$method"
        int statusCode
        setProxyParams()
        setSSLParams()
        URL newUrl
        newUrl=new URL(restUrl)
```

```
connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        if (method=="")
            connection.setRequestMethod("GET")
        else
            connection.setRequestMethod(method)
        connection.setRequestProperty("Content-Type", "application/x-www-form-
urlencoded")
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        String response=""
        try {
            statusCode = connection.responseCode
            println "Connection status code: $statusCode "
            if (statusCode==401) {
                println "Not authorized"
            }
            if (statusCode==200) {
                println "Authentication succeeded"
                println "Server response:"
                println "-----"
response=displayServerResponse(connection,localFileNameWithPathForStorage)
                println "----"
            1
            if (statusCode==400) {
                println "Bad request"
                println "Server response:"
                println "-----"
                response=displayServerResponse(connection,"")
                println "----"
            ł
        } catch (Exception e) {
            println "Error connecting to the URL"
            println e.getMessage()
        } finally {
            if (connection != null) {
                connection.disconnect();
            1
        }
        return response
    }
    def displayServerResponse(connection,localFileNameWithPathForStorage) {
        InputStream is;
        if (connection.getResponseCode()==200) {
```

```
is=connection.getInputStream();
    } else {
        is=connection.getErrorStream();
    }
   println "Response Content-Type:"+connection.getContentType()
   if (connection.getContentType().contains("application/json")) {
        BufferedReader br = new BufferedReader(new InputStreamReader(is));
        StringBuilder sb = new StringBuilder();
        String line;
        while ((line = br.readLine()) != null) {
            sb.append(line+"\n");
        }
        br.close();
        println sb
        return sb.toString()
    } else {
   if (connection.getResponseCode()==200) {
    //storing content
        final int BUFFER SIZE = 5 * 1024 * 1024;
        def fileExt = connection.getHeaderField("fileExtension");
        println "Downloading file with fileExtension header:"+fileExt
        if (fileExt!=null) {
            def saveFilePath = localFileNameWithPathForStorage;
            File f = new File(saveFilePath);
            is = connection.getInputStream();
            FileOutputStream outputStream = new FileOutputStream(f);
            int bytesRead = -1;
            byte[] buffer = new byte[BUFFER SIZE];
            while ((bytesRead = is.read(buffer)) != -1) {
                outputStream.write(buffer, 0, bytesRead);
            }
            println "Downloaded file to $localFileNameWithPathForStorage"
            return localFileNameWithPathForStorage
        } else {
            println "Could not find fileExtension header"
        }
    }
   return ""
}
def listFiles() {
   println "**Listing files**"
   def restUrl=interopUrl+"/applicationsnapshots"
   def response
   response=openConnection(restUrl,"GET","")
   println "****"
}
def deleteFile(serverFileName) {
   println "**deleting file**"
   def restUrl=interopUrl+"/applicationsnapshots/"+serverFileName
   def response
```

```
response=openConnection(restUrl, "DELETE", "")
        println "****"
    }
    def getJobStatus(appName, jobId) {
        println "**get Job status**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs/" + jobId
        def response
        response=openConnection(restUrl, "GET", "")
        println "****"
        return response
    }
    def exportData(appName, jobName, exportServerFileName) {
        println "**Exporting data**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=EXPORT DATA"
        if (exportServerFileName!="") {
            def exportFileJSON="{exportFileName:$exportServerFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
        return response
    }
    def getJobIdFromJSONResponse(response) {
        def jobId=""
        try {
            Pattern regex = Pattern.compile("\"jobId\":\\d+");
            Matcher matcher = regex.matcher(response);
            while (matcher.find()) {
                jobId = matcher.group(0).replace("\"jobId\":","");
            }
        } catch (Exception e) {
            println "No jobId found in server response"
        ł
        return jobId
    }
    def downloadFile(serverFileName,localFolderForStorage) {
        println "**Downloading file**"
        def restUrl=interopUrl+"/applicationsnapshots/"+serverFileName+ "/
contents"
        def response
response=openConnection(restUrl,"GET",localFolderForStorage+"/"+serverFileName
)
        println "****"
    }
```



```
def exportMetaData(appName, jobName, exportServerFileName) {
        println "**Exporting metadata**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=EXPORT METADATA"
        if (exportServerFileName!="") {
            def exportFileJSON="{exportZipFileName:$exportServerFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def executeLCMExport(snapshotName) {
        println "**Exporting snapshot**"
        def typeExport="{type:export}"
        def restUrl=interopUrl+"/applicationsnapshots/"+snapshotName+ "/
migration?q="+typeExport
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def executeLCMImport(snapshotName) {
        println "**Importing snapshot**"
        def typeImport="{type:import}"
        def restUrl=interopUrl+"/applicationsnapshots/"+snapshotName+ "/
migration?q="+typeImport
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def runBusinessRule(appName, jobName, JSONRuntimePrompt) {
        println "**Running business rule**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=RULES"
        if (JSONRuntimePrompt!="") {
            // Example for JSONRuntimePrompt {Period:Q1,Entity:USA}
            restUrl=restUrl+"&parameters=" + JSONRuntimePrompt
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def runRuleSet(appName, jobName) {
        println "**Running rule set**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=RULESET"
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
```

```
def cubeRefresh(appName, jobName) {
        println "**Refreshing cube**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=CUBE REFRESH"
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def runPlanTypeMap(appName, jobName, clearData) {
        println "**Running map (job of type plan_type_map) **"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=PLAN TYPE MAP"
        if (clearData!=null && clearData.toUpperCase()=="FALSE") {
            restUrl=restUrl+"&parameters={clearData:false}"
        } else {
            println "Clear data is set to true (default)"
        }
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def importData(appName, jobName, importFileName) {
        println "**Importing data**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=IMPORT DATA"
        if (importFileName!="") {
            def exportFileJSON="{importFileName:$importFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def importMetaData(appName, jobName, importZipFileName) {
        println "**Importing metadata**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=IMPORT METADATA"
        if (importZipFileName!="") {
            def exportFileJSON="{importZipFileName:$importZipFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def uploadFile(localPath,fileName) {
        println "**Uploading file**"
```

```
def restUrl=interopUrl+"/applicationsnapshots/"+fileName
        final int DEFAULT CHUNK SIZE = 50 * 1024 * 1024;
        int packetNo = 1;
        boolean status = true;
        byte[] lastChunk = null;
        File f = new File(localPath+"/"+fileName);
        InputStream fis = null;
        long totalFileSize = f.length();
        boolean isLast = false;
        Boolean isFirst = true;
        boolean firstRetry = true;
        int lastPacketNo = (int) (Math.ceil(totalFileSize/ (double))
DEFAULT CHUNK SIZE));
        long totalbytesRead = 0;
        try {
            fis = new BufferedInputStream(new
FileInputStream(localPath+"/"+fileName));
            while (totalbytesRead < totalFileSize && status) {</pre>
                int nextChunkSize = (int) Math.min(DEFAULT CHUNK SIZE,
totalFileSize - totalbytesRead);
                if (lastChunk == null) {
                    lastChunk = new byte[nextChunkSize];
                    int bytesRead = fis.read(lastChunk);
                    totalbytesRead += bytesRead;
                    if (packetNo == lastPacketNo) {
                        isLast = true;
                    }
                    status = sendRequestToRestForUpload(restUrl, isFirst,
isLast,lastChunk);
                    isFirst=false;
                    if (status) {
                        println "\r" + ((100 * totalbytesRead)/
totalFileSize) + "% completed";
                    } else {
                break;
                }
                    packetNo = packetNo + 1;
                    lastChunk = null;
            }
        } catch (Exception e) {
            println "Exception occurred while uploading file";
            println e.getMessage()
        } finally {
            if (null != fis) {
            }
        }
        println "****"
    }
    def sendRequestToRestForUpload(restUrl,isFirst, isLast,lastChunk) {
        def url=restUrl+"/contents?
q={isLast:$isLast,chunkSize:"+lastChunk.length+",isFirst:$isLast}"
        println "Opening connection for upload to $url"
```

```
int statusCode
        setProxyParams()
        setSSLParams()
        URL newUrl
        newUrl=new URL(url)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        connection.setRequestMethod("POST")
        connection.setRequestProperty("Content-Type", "application/octet-
stream")
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        DataOutputStream wr = new
DataOutputStream(connection.getOutputStream());
        wr.write(lastChunk);
        wr.flush();
        boolean status = false
        int execStatus
        try {
            execStatus = connection.getResponseCode();
            InputStream is = connection.getInputStream();
            BufferedReader br = new BufferedReader(new InputStreamReader(is));
            StringBuilder sb = new StringBuilder();
            String line;
            while ((line = br.readLine()) != null) {
                sb.append(line+"\n");
            }
            br.close();
            String stat = sb.toString();
            if (null == stat || stat.isEmpty()) {
                return status;
            } else {
                if (200 == execStatus) {
                    println stat
                }
            }
        } catch (Exception e) {
            println "Exception occurred while uploading file";
            println e.getMessage()
        } finally {
            if (connection != null) {
                connection.disconnect();
            }
        }
```

```
// Helper functions
    def unZip(fileName, destinationFolder) {
        // code from http://www.oracle.com/technetwork/articles/java/
compress-1565076.html
         println ("**Unzipping "+fileName+"**")
         def fileList=[]
        int BUFFER = 2048;
        try {
            BufferedOutputStream dest = null;
            BufferedInputStream is = null;
            ZipEntry entry;
            ZipFile zipfile = new ZipFile(fileName);
            Enumeration e = zipfile.entries();
            while(e.hasMoreElements()) {
               entry = (ZipEntry) e.nextElement();
               //println("Extracting: " +entry);
               is = new BufferedInputStream(zipfile.getInputStream(entry));
               int count;
               byte[] data;
               data = new byte[BUFFER];
               FileOutputStream fos = new
FileOutputStream(destinationFolder+"/"+entry.getName());
               fileList.push(entry.getName())
               dest = new BufferedOutputStream(fos, BUFFER);
               while ((count = is.read(data, 0, BUFFER)) != -1) {
                  dest.write(data, 0, count);
               }
               dest.flush();
               dest.close();
               is.close();
            1
         } catch (FileNotFoundException fnfe) {
             println "Make sure there is not folder in the zip . Zip not
processed"
             //fnfe.printStackTrace();
         } catch(Exception e) {
             println "An error occurred while unzipping."
             println e.getMessage()
         }
         return fileList
         println "****"
    }
     def findNbOfColsInCSV(filePath, fileName, delimiter) {
        File csvFile=new File (filePath+"/"+fileName);
        Scanner scanner = new Scanner(csvFile);
        scanner.useDelimiter(delimiter);
        def nbCols
        nbCols=0
        if (scanner.hasNextLine()) {
```

}

```
String[] vals = scanner.nextLine().split(delimiter);
            nbCols=vals.size()
        }
        scanner.close();
        return nbCols
        }
     def getHeadersInCSVAsList(filePath, fileName, delimiter) {
         String[] headers =[]
         BufferedReader br = new BufferedReader(new
FileReader(filePath+"/"+fileName));
         String firstLine = br .readLine();
         println "First line is : " + firstLine
         println "Removing all non ascii chars from line"
         firstLine = firstLine.replaceAll("[^ -~]", "");
         firstLine = firstLine.replaceAll(" ", "");
        // firstLine = firstLine.replaceAll("\"", "");
         headers = firstLine.split(delimiter);
         def headersList = headers as List
         headersList = headersList.collect { it.trim() }
         return headersList
         }
}
class WaitForCode {
static retry( sleepTime, nbOfRetries, Closure logicToRun) {
 Throwable catched = null
  for(int i=0; i<nb0fRetries; i++) {</pre>
      try {
          return logicToRun.call()
      } catch(Throwable t){
          catched = t
          println ("Retrying...")
          Thread.sleep(sleepTime)
      }
  }
 println ("Retry count limit exceeded. Stopping check.")
 throw catched
}
}
```

Groovy Sample – PbcsRestClient.groovy

```
package com.oracle.ceal
import javax.net.ssl.HostnameVerifier
import javax.net.ssl.HttpsURLConnection
import javax.net.ssl.SSLContext
```

```
import javax.net.ssl.SSLSession
import javax.net.ssl.TrustManager
import javax.net.ssl.X509TrustManager
import java.net.HttpURLConnection
import java.util.regex.Pattern
import java.util.regex.Matcher
import java.util.zip.ZipEntry
import java.util.zip.ZipFile
class PbcsRestClient {
   private HttpURLConnection connection
   private def planningUrl
   private def interopUrl
   private def proxyHost
   private def proxyPort
   private def user
   private def pwd
   private def domain
   private def ignoreSSLCertsErrors
    public PbcsRestClient(planningServerUrl, interopServerUrl, httpProxyHost,
httpProxyPort, identityDomain, username, password,
ignoreSSLCertificationPathErrors) {
        planningUrl=planningServerUrl
        interopUrl=interopServerUrl
        proxyHost=httpProxyHost
        proxyPort=httpProxyPort
        domain=identityDomain
        user=username
        pwd=password
        ignoreSSLCertsErrors=ignoreSSLCertificationPathErrors
    }
    def setProxyParams() {
        Properties systemProperties = System.getProperties()
        systemProperties.setProperty("http.proxyHost",proxyHost)
        systemProperties.setProperty("http.proxyPort", proxyPort)
        systemProperties.setProperty("https.proxyHost",proxyHost)
        systemProperties.setProperty("https.proxyPort",proxyPort)
    }
    def setSSLParams() {
        if (ignoreSSLCertsErrors !=null &&
ignoreSSLCertsErrors.toUpperCase() == "TRUE") {
            println "Ignoring SSL certification path errors"
            // Disable SSL cert validation
            def hostnameVerifier = [
                verify: { hostname, session -> true }
            ]
            def trustManager = [
                    checkServerTrusted: { chain, authType -> },
```

```
checkClientTrusted: { chain, authType -> },
                    getAcceptedIssuers: { null }
            ]
            HttpsURLConnection.setDefaultHostnameVerifier(hostnameVerifier as
HostnameVerifier)
HttpsURLConnection.setDefaultSSLSocketFactory(context.getSocketFactory())
            SSLContext context = SSLContext.getInstance("SSL")
            context.init(null, [trustManager as X509TrustManager] as
TrustManager[], null)
        }
    }
    def openConnection(restUrl,method,localFileNameWithPathForStorage) {
        println "Opening connection to $restUrl with method: $method"
        int statusCode
        setProxyParams()
        setSSLParams()
        URL newUrl
        newUrl=new URL(restUrl)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        if (method=="")
            connection.setRequestMethod("GET")
        else
            connection.setRequestMethod(method)
        connection.setRequestProperty("Content-Type","application/x-www-form-
urlencoded")
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        String response=""
        try {
            statusCode = connection.responseCode
            println "Connection status code: $statusCode "
            if (statusCode==401) {
                println "Not authorized"
            }
            if (statusCode==200) {
                println "Authentication succeeded"
                println "Server response:"
                println "-----"
```

```
response=displayServerResponse(connection,localFileNameWithPathForStorage)
                println "----"
            }
            if (statusCode==400) {
                println "Bad request"
                println "Server response:"
                println "-----"
                response=displayServerResponse(connection,"")
                println "-----"
            1
        } catch (Exception e) {
            println "Error connecting to the URL"
            println e.getMessage()
        } finally {
            if (connection != null) {
                connection.disconnect();
            }
        }
        return response
    }
    def displayServerResponse(connection,localFileNameWithPathForStorage) {
        InputStream is;
        if (connection.getResponseCode()==200) {
            is=connection.getInputStream();
        } else {
            is=connection.getErrorStream();
        println "Response Content-Type:"+connection.getContentType()
        if (connection.getContentType().contains("application/json")) {
            BufferedReader br = new BufferedReader(new InputStreamReader(is));
            StringBuilder sb = new StringBuilder();
            String line;
            while ((line = br.readLine()) != null) {
                sb.append(line+"\n");
            }
            br.close();
            println sb
            return sb.toString()
        } else {
        if (connection.getResponseCode()==200) {
        //storing content
            final int BUFFER SIZE = 5 * 1024 * 1024;
            def fileExt = connection.getHeaderField("fileExtension");
            println "Downloading file with fileExtension header:"+fileExt
            if (fileExt!=null) {
                def saveFilePath = localFileNameWithPathForStorage;
                File f = new File(saveFilePath);
                is = connection.getInputStream();
                FileOutputStream outputStream = new FileOutputStream(f);
                int bytesRead = -1;
                byte[] buffer = new byte[BUFFER SIZE];
                while ((bytesRead = is.read(buffer)) != -1) {
                    outputStream.write(buffer, 0, bytesRead);
                }
```

```
println "Downloaded file to $localFileNameWithPathForStorage"
                return localFileNameWithPathForStorage
            } else {
                println "Could not find fileExtension header"
            }
        }
        }
        return ""
    }
    def listFiles() {
        println "**Listing files**"
        def restUrl=interopUrl+"/applicationsnapshots"
        def response
        response=openConnection(restUrl, "GET", "")
        println "****"
    }
    def deleteFile(serverFileName) {
        println "**deleting file**"
        def restUrl=interopUrl+"/applicationsnapshots/"+serverFileName
        def response
        response=openConnection(restUrl,"DELETE","")
        println "****"
    }
    def getJobStatus(appName, jobId) {
        println "**get Job status**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs/" + jobId
        def response
        response=openConnection(restUrl,"GET","")
        println "****"
        return response
    }
    def exportData(appName, jobName, exportServerFileName) {
        println "**Exporting data**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=EXPORT DATA"
        if (exportServerFileName!="") {
            def exportFileJSON="{exportFileName:$exportServerFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
        return response
    }
    def getJobIdFromJSONResponse(response) {
```

```
def jobId=""
        try {
            Pattern regex = Pattern.compile("\"jobId\":\\d+");
            Matcher matcher = regex.matcher(response);
            while (matcher.find()) {
                jobId = matcher.group(0).replace("\"jobId\":","");
            }
        } catch (Exception e) {
            println "No jobId found in server response"
        }
        return jobId
    }
    def downloadFile(serverFileName,localFolderForStorage) {
        println "**Downloading file**"
        def restUrl=interopUrl+"/applicationsnapshots/"+serverFileName+ "/
contents"
        def response
response=openConnection(restUrl,"GET",localFolderForStorage+"/"+serverFileName
)
        println "****"
    }
    def exportMetaData(appName, jobName, exportServerFileName) {
        println "**Exporting metadata**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=EXPORT METADATA"
        if (exportServerFileName!="") {
            def exportFileJSON="{exportZipFileName:$exportServerFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def executeLCMExport(snapshotName) {
        println "**Exporting snapshot**"
        def typeExport="{type:export}"
        def restUrl=interopUrl+"/applicationsnapshots/"+snapshotName+ "/
migration?q="+typeExport
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def executeLCMImport(snapshotName) {
        println "**Importing snapshot**"
        def typeImport="{type:import}"
        def restUrl=interopUrl+"/applicationsnapshots/"+snapshotName+ "/
migration?q="+typeImport
        def response
        response=openConnection(restUrl, "POST", "")
```

```
println "****"
    }
    def runBusinessRule(appName, jobName, JSONRuntimePrompt) {
        println "**Running business rule**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=RULES"
        if (JSONRuntimePrompt!="") {
            // Example for JSONRuntimePrompt {Period:Q1,Entity:USA}
            restUrl=restUrl+"&parameters=" + JSONRuntimePrompt
        }
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def runRuleSet(appName, jobName) {
        println "**Running rule set**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=RULESET"
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def cubeRefresh(appName,jobName) {
        println "**Refreshing cube**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=CUBE_REFRESH"
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def runPlanTypeMap(appName, jobName, clearData) {
        println "**Running map (job of type plan type map)**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=PLAN TYPE MAP"
        if (clearData!=null && clearData.toUpperCase()=="FALSE") {
            restUrl=restUrl+"&parameters={clearData:false}"
        } else {
            println "Clear data is set to true (default)"
        def response
        response=openConnection(restUrl,"POST","")
        println "****"
    }
    def importData(appName, jobName, importFileName) {
        println "**Importing data**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=IMPORT DATA"
        if (importFileName!="") {
```

```
def exportFileJSON="{importFileName:$importFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def importMetaData(appName, jobName, importZipFileName) {
        println "**Importing metadata**"
        def restUrl=planningUrl+"/applications/"+appName+"/jobs?jobName=" +
jobName + "&jobType=IMPORT METADATA"
        if (importZipFileName!="") {
            def exportFileJSON="{importZipFileName:$importZipFileName}"
            restUrl=restUrl+"&parameters=" + exportFileJSON
        }
        def response
        response=openConnection(restUrl, "POST", "")
        println "****"
    }
    def uploadFile(localPath,fileName) {
        println "**Uploading file**"
        def restUrl=interopUrl+"/applicationsnapshots/"+fileName
        final int DEFAULT CHUNK SIZE = 50 * 1024 * 1024;
        int packetNo = 1;
        boolean status = true;
        byte[] lastChunk = null;
        File f = new File(localPath+"/"+fileName);
        InputStream fis = null;
        long totalFileSize = f.length();
        boolean isLast = false;
        Boolean isFirst = true;
        boolean firstRetry = true;
        int lastPacketNo = (int) (Math.ceil(totalFileSize/ (double)
DEFAULT CHUNK SIZE));
        long totalbytesRead = 0;
        try {
            fis = new BufferedInputStream(new
FileInputStream(localPath+"/"+fileName));
            while (totalbytesRead < totalFileSize && status) {</pre>
                int nextChunkSize = (int) Math.min(DEFAULT CHUNK SIZE,
totalFileSize - totalbytesRead);
                if (lastChunk == null) {
                    lastChunk = new byte[nextChunkSize];
                    int bytesRead = fis.read(lastChunk);
                    totalbytesRead += bytesRead;
                    if (packetNo == lastPacketNo) {
                        isLast = true;
                    }
                    status = sendRequestToRestForUpload(restUrl,isFirst,
isLast,lastChunk);
                    isFirst=false;
```

```
if (status) {
                        println "\r" + ((100 * totalbytesRead)/
totalFileSize) + "% completed";
                    } else {
                break;
                }
                    packetNo = packetNo + 1;
                    lastChunk = null;
            }
        } catch (Exception e) {
            println "Exception occurred while uploading file";
            println e.getMessage()
        } finally {
            if (null != fis) {
        println "****"
    }
    def sendRequestToRestForUpload(restUrl,isFirst, isLast,lastChunk) {
        def url=restUrl+"/contents?
q={isLast:$isLast,chunkSize:"+lastChunk.length+",isFirst:$isLast}"
        println "Opening connection for upload to $url"
        int statusCode
        setProxyParams()
        setSSLParams()
        URL newUrl
        newUrl=new URL(url)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        connection.setRequestMethod("POST")
        connection.setRequestProperty("Content-Type", "application/octet-
stream")
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        DataOutputStream wr = new
DataOutputStream(connection.getOutputStream());
        wr.write(lastChunk);
        wr.flush();
        boolean status = false
        int execStatus
        try {
            execStatus = connection.getResponseCode();
```

```
InputStream is = connection.getInputStream();
            BufferedReader br = new BufferedReader(new InputStreamReader(is));
            StringBuilder sb = new StringBuilder();
            String line;
            while ((line = br.readLine()) != null) {
                sb.append(line+"\n");
            }
            br.close();
            String stat = sb.toString();
            if (null == stat || stat.isEmpty()) {
                return status;
            } else {
                if (200 == execStatus) {
                    println stat
                }
            }
        } catch (Exception e) {
            println "Exception occurred while uploading file";
            println e.getMessage()
        } finally {
            if (connection != null) {
                connection.disconnect();
            }
        }
    }
    // Helper functions
    def unZip(fileName, destinationFolder) {
        // code from http://www.oracle.com/technetwork/articles/java/
compress-1565076.html
         println ("**Unzipping "+fileName+"**")
         def fileList=[]
        int BUFFER = 2048;
        try {
            BufferedOutputStream dest = null;
            BufferedInputStream is = null;
            ZipEntry entry;
            ZipFile zipfile = new ZipFile(fileName);
            Enumeration e = zipfile.entries();
            while(e.hasMoreElements()) {
               entry = (ZipEntry) e.nextElement();
               //println("Extracting: " +entry);
               is = new BufferedInputStream(zipfile.getInputStream(entry));
               int count;
               byte[] data;
               data = new byte[BUFFER];
               FileOutputStream fos = new
FileOutputStream(destinationFolder+"/"+entry.getName());
               fileList.push(entry.getName())
               dest = new BufferedOutputStream(fos, BUFFER);
               while ((count = is.read(data, 0, BUFFER)) != -1) {
                  dest.write(data, 0, count);
               }
               dest.flush();
```

```
dest.close();
               is.close();
            }
         } catch (FileNotFoundException fnfe) {
             println "Make sure there is not folder in the zip . Zip not
processed"
             //fnfe.printStackTrace();
         } catch(Exception e) {
             println "An error occurred while unzipping."
             println e.getMessage()
         }
         return fileList
         println "****"
    }
    def findNbOfColsInCSV(filePath, fileName, delimiter) {
        File csvFile=new File (filePath+"/"+fileName);
        Scanner scanner = new Scanner(csvFile);
        scanner.useDelimiter(delimiter);
        def nbCols
        nbCols=0
        if (scanner.hasNextLine()) {
            String[] vals = scanner.nextLine().split(delimiter);
            nbCols=vals.size()
        }
        scanner.close();
        return nbCols
        }
     def getHeadersInCSVAsList(filePath, fileName, delimiter) {
         String[] headers =[]
         BufferedReader br = new BufferedReader(new
FileReader(filePath+"/"+fileName));
         String firstLine = br .readLine();
         println "First line is : " + firstLine
         println "Removing all non ascii chars from line"
         firstLine = firstLine.replaceAll("[^ -~]", "");
        firstLine = firstLine.replaceAll(" ", "");
        // firstLine = firstLine.replaceAll("\"", "");
        headers = firstLine.split(delimiter);
         def headersList = headers as List
         headersList = headersList.collect { it.trim() }
         return headersList
         }
}
class WaitForCode {
```

```
static retry( sleepTime, nbOfRetries, Closure logicToRun){
  Throwable catched = null
  for(int i=0; i<nbOfRetries; i++){
     try {
        return logicToRun.call()
     } catch(Throwable t){
        catched = t
        println ("Retrying...")
        Thread.sleep(sleepTime)
     }
   }
  println ("Retry count limit exceeded. Stopping check.")
   throw catched
}
</pre>
```

Groovy Sample – BicsRestClient.groovy

```
package com.oracle.ceal
import java.net.HttpURLConnection;
import javax.net.ssl.HostnameVerifier
import javax.net.ssl.HttpsURLConnection
import javax.net.ssl.SSLContext
import javax.net.ssl.SSLSession
import javax.net.ssl.TrustManager
import javax.net.ssl.X509TrustManager
class BicsRestClient {
   private HttpURLConnection connection
   private bicsUrl
   private def proxyHost
   private def proxyPort
   private def user
   private def pwd
   private def domain
   private def ignoreSSLCertsErrors
    public BicsRestClient(bicsServerUrl,httpProxyHost, httpProxyPort,
identityDomain,username, password, ignoreSSLCertificationPathErrors) {
        bicsUrl=bicsServerUrl
        proxyHost=httpProxyHost
        proxyPort=httpProxyPort
        domain=identityDomain
        user=username
        pwd=password
        ignoreSSLCertsErrors=ignoreSSLCertificationPathErrors
    }
    def setProxyParams() {
        Properties systemProperties = System.getProperties()
        systemProperties.setProperty("http.proxyHost",proxyHost)
        systemProperties.setProperty("http.proxyPort",proxyPort)
```

```
systemProperties.setProperty("https.proxyHost",proxyHost)
        systemProperties.setProperty("https.proxyPort", proxyPort)
    }
    def setSSLParams() {
        if (ignoreSSLCertsErrors !=null &&
ignoreSSLCertsErrors.toUpperCase() == "TRUE") {
            println "Ignoring SSL certification path errors"
            // Disable SSL cert validation
            def hostnameVerifier = [
                verify: { hostname, session -> true }
            ]
            def trustManager = [
                    checkServerTrusted: { chain, authType -> },
                    checkClientTrusted: { chain, authType -> },
                    getAcceptedIssuers: { null }
            1
            HttpsURLConnection.setDefaultHostnameVerifier(hostnameVerifier as
HostnameVerifier)
HttpsURLConnection.setDefaultSSLSocketFactory(context.getSocketFactory())
            SSLContext context = SSLContext.getInstance("SSL")
            context.init(null, [trustManager as X509TrustManager] as
TrustManager[], null)
        }
    }
    def openConnection(restUrl,method,contentType, body) {
        println "Opening connection to bics $restUrl with method:$method"
        int statusCode
        setProxyParams()
        setSSLParams()
        URL newUrl
        newUrl=new URL(restUrl)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        if (method=="")
            connection.setRequestMethod("GET")
        else
```

```
connection.setRequestMethod(method)
```



```
//adding X-ID-TENANT-NAME <identity domain>
        //connection.setRequestProperty("X-ID-TENANT-NAME", domain)
        if (contentType.toUpperCase() == "FORM") {
            connection.setRequestProperty("Content-Type","application/x-www-
form-urlencoded")
        }
        if (contentType.toUpperCase() == "JSON") {
            connection.setRequestProperty("Content-Type","application/json")
        }
        if (contentType.toUpperCase() == "") {
            // add no content type
        }
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        if (body!=null && body!="") {
            DataOutputStream wr = new DataOutputStream
(connection.getOutputStream ());
           wr.writeBytes (body);
            wr.flush ();
            wr.close ();
        }
        String response=""
        try {
            statusCode = connection.responseCode
            println "Connection status code: $statusCode "
            if (statusCode==401 || statusCode==403) {
                println "Not authorized"
            if (statusCode==200) {
               println "Authentication succeeded"
                println "Server response:"
                println "-----"
                response=displayServerResponse(connection)
               println "----"
            if (statusCode==400 || statusCode==500) {
               println "Bad request"
               println "Server response:"
                println "----"
                response=displayServerResponse(connection)
               println "----"
            1
        } catch (Exception e) {
            println "Error connecting to the URL"
           println e.getMessage()
        } finally {
            if (connection != null) {
                connection.disconnect();
            }
```

```
}
        return response
    }
    def displayServerResponse(connection) {
        InputStream is;
        if (connection.getResponseCode()==200) {
            is=connection.getInputStream();
        } else {
            is=connection.getErrorStream();
        }
        println "Response Content-Type:"+connection.getContentType()
        BufferedReader br = new BufferedReader(new InputStreamReader(is));
        StringBuilder sb = new StringBuilder();
        String line;
        while ((line = br.readLine()) != null) {
            sb.append(line+"\n");
        }
        br.close();
        println sb
        return sb.toString()
    }
    def aboutBics() {
        println "**About bics**"
        def restUrl=bicsUrl+"/dataload/v1/about"
        def response
        response=openConnection(restUrl, "GET", "FORM", "")
        println "****"
    }
    def listAllTables() {
        //<URL>/dataload/v1/tables
        println "**List tables**"
        def restUrl=bicsUrl+"/dataload/v1/tables"
        def response
        response=openConnection(restUrl, "GET", "FORM", "")
        println "****"
    }
    def getTableInfo(tableName) {
        println "**Get table info**"
        def restUrl=bicsUrl+"/dataload/v1/tables?
name="+tableName.toUpperCase()
        def response
        response=openConnection(restUrl, "GET", "", "")
        println "****"
    }
```



```
def createTableToLoadCSV(tableName, numberOfVarCharCols, columnPrefix ) {
        println "**Create table**"
        // create json manually for X columns
        /*
         {
        "columnName":"COL 1",
        "dataType":"VARCHAR",
        "length":300,
        "precision":0,
        "nullable":true,
        "defaultValue":null,
        },
         * */
        def restUrl=bicsUrl+"/dataload/v1/tables/"+tableName.toUpperCase()
        def JSONColumns
        JSONColumns="["
        def i
        for (i = 1; i <=numberOfVarCharCols; i++) {</pre>
            if (i==numberOfVarCharCols) {
JSONColumns=JSONColumns+"{\"columnName\":\""+columnPrefix.toUpperCase()
+""+i+"\", \"dataType\": \"VARCHAR\", \"length\":300, \"precision\":0, \"nullable\"
:true,\"defaultValue\":null}"
            } else {
JSONColumns=JSONColumns+"{\"columnName\":\""+columnPrefix.toUpperCase()
+""+i+"\",\"dataType\":\"VARCHAR\",\"length\":300,\"precision\":0,\"nullable\"
:true, \"defaultValue\":null},"
            }
         }
        JSONColumns=JSONColumns+"]"
        println "JSON columns:"+JSONColumns
        def response
        response=openConnection(restUrl, "PUT", "JSON", JSONColumns)
        println "****"
    }
    def createTableToLoadCSVWithHeaderNames(tableName, listHeaders ) {
        println "**Create table**"
        // create json manually for X columns with headers in list
        /*
         {
        "columnName":"COL 1",
        "dataType":"VARCHAR",
        "length":300,
        "precision":0,
        "nullable":true,
        "defaultValue":null,
        },
```

```
* */
        def restUrl=bicsUrl+"/dataload/v1/tables/"+tableName.toUpperCase()
        def JSONColumns
        JSONColumns="["
        listHeaders.each { headerName ->
            if(headerName == listHeaders.last()) {
JSONColumns=JSONColumns+"{\"columnName\":\""+headerName.toUpperCase()
+"\",\"dataType\":\"VARCHAR\",\"length\":300,\"precision\":0,\"nullable\":true
, \"defaultValue\":null}"
            } else {
JSONColumns=JSONColumns+"{\"columnName\":\""+headerName.toUpperCase()
+"\",\"dataType\":\"VARCHAR\",\"length\":300,\"precision\":0,\"nullable\":true
, \"defaultValue\":null},"
            }
        }
        JSONColumns=JSONColumns+"]"
        println "JSON columns:"+JSONColumns
        def response
        response=openConnection(restUrl,"PUT","JSON", JSONColumns)
        println "****"
    }
    def loadDataInTableUsingCSV(tableName, localCsvFilePath,
localCsvFileName,
delimiterInCsv,numberOfColumnsInCsv,numberOfLinesToSkip,columnPrefixInTable,is
Zipped) {
        println "**Load csv file in table**"
        println "Processing:"+localCsvFilePath+"/"+localCsvFileName
        if (isZipped==true) println "Upload of zip not supported at this
time. Ignoring isZipped parameter"
        File localCsv=new File(localCsvFilePath+"/"+localCsvFileName)
        if(!localCsv.exists() || localCsv.isDirectory()) {
            println "File does not exist"
            println "****"
            return
        ł
        def restUrl=bicsUrl+"/dataload/v1/tables/"+tableName.toUpperCase()+"/
data"
        setProxyParams()
        setSSLParams()
        URL newUrl
```

```
newUrl=new URL(restUrl)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        connection.setRequestMethod("PUT")
        //connection.setRequestProperty("X-ID-TENANT-NAME",domain)
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        /*
         * The first part is a JSON descriptor (Content-Type: application/
json)
         * of the data load. The second part is an input stream
         * (Content-Type: application/octet-stream).
         * Data in the stream can be text data read
         * from comma-separated values (CSV)
         * */
        def boundary = System.currentTimeMillis() ;
        connection.setRequestProperty("Content-Type", "multipart/mixed;
boundary=" + boundary);
        OutputStream outputStream = connection.getOutputStream();
        PrintWriter writer = new PrintWriter(new
OutputStreamWriter(outputStream, "UTF-8"),true);
        // JSON
        /*
         * {
        "columnMaps":[
                {
                    "column":{
                        "name":"NAME",
                        "optionalJavaSqlType":null,
                        "partOfUniqueKey":true,
                    },
                    "position":1,
                },
                {...
                }
        ],
        "optionalMaximumErrors":null,
        "removeDuplicates":true
        "optionalWriteMode":"Insert all",
        "delimiter":","
        "timestampFormat":"yyyy-MM-dd",
        "numberOfLinesToSkip":0
        },
         *
         */
        def i
```

```
def JSONDataLoad
        JSONDataLoad="{\"columnMaps\":["
        for (i =1; i <=numberOfColumnsInCsv; i++) {</pre>
            if (i==numberOfColumnsInCsv) {
                JSONDataLoad=JSONDataLoad+"{\"column\":
{\"name\":\""+columnPrefixInTable.toUpperCase()
+""+i+"\","+"\"optionalJavaSqlType\":null,\"partOfUniqueKey\":false},"+"\"posi
tion\":"+i+"}"
            } else {
                JSONDataLoad=JSONDataLoad+"{\"column\":
{\"name\":\""+columnPrefixInTable.toUpperCase()
+""+i+"\","+"\"optionalJavaSqlType\":null,\"partOfUniqueKey\":false},"+"\"posi
tion\":"+i+"},"
            }
         }
        JSONDataLoad=JSONDataLoad+'''],
        "optionalMaximumErrors":null,
        "removeDuplicates":false,
        "optionalWriteMode":"Insert all",
        "delimiter":"'''+delimiterInCsv+"\","+'''
        "timestampFormat":"",
        "numberOfLinesToSkip":''' + numberOfLinesToSkip +'''}
        ...
        writer.append("--" + boundary).append("\r\n");
        writer.append("Content-Type: application/json").append("\r\n");
        writer.append("\r\n");
        writer.flush();
        writer.append(JSONDataLoad)
        writer.append("\r\n");
        writer.flush();
        writer.append("\r\n").flush();
        //writer.append("--" + boundary ).append("\r\n");
        // CSV or ZIP file content
        writer.append("--" + boundary).append("\r\n");
        writer.append("Content-Type: application/octet-
stream").append("\r\n");
        writer.append("\r\n");
        writer.flush();
        FileInputStream inputStream = new FileInputStream(new
File(localCsvFilePath+"/"+localCsvFileName));
        byte[] buffer = new byte[4096];
        int bytesRead = -1;
        while ((bytesRead = inputStream.read(buffer)) != -1) {
            outputStream.write(buffer, 0, bytesRead);
        }
        outputStream.flush();
        inputStream.close();
        writer.append("\r\n");
        writer.flush();
        writer.append("\r\n").flush();
        writer.append("--" + boundary + "--").append("\r\n");
```

```
writer.close();
        String response=""
        def statusCode
        try {
            statusCode = connection.responseCode
            println "Connection status code: $statusCode "
            if (statusCode==401 || statusCode==403) {
                println "Not authorized"
            1
            if (statusCode==200) {
                println "Authentication succeeded"
                println "Server response:"
                println "-----"
                response=displayServerResponse(connection)
                println "-----"
            if (statusCode==400 || statusCode==500) {
               println "Bad request"
                println "Server response:"
                println "-----"
                response=displayServerResponse(connection)
                println "-----"
            }
        } catch (Exception e) {
            println "Error connecting to the URL"
            println e.getMessage()
        } finally {
            if (connection != null) {
                connection.disconnect();
            }
        }
        println "****"
    }
    def loadDataInTableUsingCSVAndHeader(tableName, localCsvFilePath,
localCsvFileName, delimiterInCsv,numberOfLinesToSkip,listHeaders,isZipped) {
        println "**Load csv file in table using headers**"
        println "Processing:"+localCsvFilePath+"/"+localCsvFileName
        if (isZipped==true) println "Upload of zip not supported at this
time. Ignoring isZipped parameter"
        File localCsv=new File(localCsvFilePath+"/"+localCsvFileName)
        if(!localCsv.exists() || localCsv.isDirectory()) {
            println "File does not exist"
            println "****"
            return
        }
        def restUrl=bicsUrl+"/dataload/v1/tables/"+tableName.toUpperCase()+"/
data"
        setProxyParams()
        setSSLParams()
```

```
URL newUrl
        newUrl=new URL(restUrl)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
        connection.setRequestMethod("PUT")
        //connection.setRequestProperty("X-ID-TENANT-NAME", domain)
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        /*
         * The first part is a JSON descriptor (Content-Type: application/
json)
         * of the data load. The second part is an input stream
         * (Content-Type: application/octet-stream).
         * Data in the stream can be text data read
         * from comma-separated values (CSV)
         * */
        def boundary = System.currentTimeMillis() ;
        connection.setRequestProperty("Content-Type","multipart/mixed;
boundary=" + boundary);
        OutputStream outputStream = connection.getOutputStream();
        PrintWriter writer = new PrintWriter(new
OutputStreamWriter(outputStream, "UTF-8"),true);
        // JSON
        /*
         * {
        "columnMaps":[
                {
                    "column":{
                        "name":"NAME",
                        "optionalJavaSqlType":null,
                        "partOfUniqueKey":true,
                    },
                    "position":1,
                },
                {...
                }
        ],
        "optionalMaximumErrors":null,
        "removeDuplicates":true
        "optionalWriteMode":"Insert all",
        "delimiter":","
        "timestampFormat":"yyyy-MM-dd",
        "numberOfLinesToSkip":0
        },
```

```
*/
        int i
        i=1
        def JSONDataLoad
        JSONDataLoad="{\"columnMaps\":["
        listHeaders.each { headerName ->
            if(headerName == listHeaders.last()) {
                    JSONDataLoad=JSONDataLoad+"{\"column\":
{\"name\":\""+headerName.toUpperCase()
+"\","+"\"optionalJavaSqlType\":null,\"partOfUniqueKey\":false},"+"\"position\
":"+i+"}"
            } else {
                    JSONDataLoad=JSONDataLoad+"{\"column\":
{\"name\":\""+headerName.toUpperCase()
+"\","+"\"optionalJavaSqlType\":null,\"partOfUniqueKey\":false},"+"\"position\
":"+i+"},"
            i=i+1
        }
        JSONDataLoad=JSONDataLoad+'''],
        "optionalMaximumErrors":null,
        "removeDuplicates":false,
        "optionalWriteMode":"Insert all",
        "delimiter":"'''+delimiterInCsv+"\","+'''
        "timestampFormat":"",
        "numberOfLinesToSkip":''' + numberOfLinesToSkip +'''}
        ...
        writer.append("--" + boundary).append("\r\n");
        writer.append("Content-Type: application/json").append("\r\n");
        writer.append("\r\n");
        writer.flush();
        writer.append(JSONDataLoad)
        writer.append("\r\n");
        writer.flush();
        writer.append("\r\n").flush();
        //writer.append("--" + boundary ).append("\r\n");
        // CSV or ZIP file content
        writer.append("--" + boundary).append("\r\n");
        writer.append("Content-Type: application/octet-
stream").append("\r\n");
        writer.append("\r\n");
        writer.flush();
        FileInputStream inputStream = new FileInputStream(new
File(localCsvFilePath+"/"+localCsvFileName));
        byte[] buffer = new byte[4096];
        int bytesRead = -1;
        while ((bytesRead = inputStream.read(buffer)) != -1) {
            outputStream.write(buffer, 0, bytesRead);
```

```
outputStream.flush();
   inputStream.close();
   writer.append("\r\n");
   writer.flush();
   writer.append("\r\n").flush();
   writer.append("--" + boundary + "--").append("\r\n");
   writer.close();
   String response=""
   def statusCode
   try {
        statusCode = connection.responseCode
        println "Connection status code: $statusCode "
        if (statusCode==401 || statusCode==403) {
           println "Not authorized"
        }
        if (statusCode==200) {
           println "Authentication succeeded"
           println "Server response:"
           println "-----"
           response=displayServerResponse(connection)
           println "-----"
        1
        if (statusCode==400 || statusCode==500) {
           println "Bad request"
           println "Server response:"
           println "-----"
            response=displayServerResponse(connection)
           println "-----"
        ł
    } catch (Exception e) {
        println "Error connecting to the URL"
        println e.getMessage()
    } finally {
        if (connection != null) {
           connection.disconnect();
        }
    }
   println "****"
}
def deleteTable(tableName) {
   println "**Delete table**"
   def restUrl=bicsUrl+"/dataload/v1/tables/"+tableName.toUpperCase()
   def response
   response=openConnection(restUrl,"DELETE","","")
   println "****"
}
def deleteDataFromTable(tableName) {
   println "**Delete all data from table**"
```

```
def restUrl=bicsUrl+"/dataload/v1/tables/"+tableName.toUpperCase()+"/
data"
        def response
        response=openConnection(restUrl,"DELETE","","")
        println "****"
    }
    def truncateList(listName, truncateLength) {
        println "**Truncating list**"
        def trimmedList
        listName=listName*.trim()
        trimmedList=listName*.take(truncateLength)
        println ("New list:"+trimmedList)
        println "****"
        return trimmedList
    }
}
```

Groovy Sample – ApexRestClient.groovy

```
package com.oracle.ceal
import java.net.HttpURLConnection;
import javax.net.ssl.HostnameVerifier
import javax.net.ssl.HttpsURLConnection
import javax.net.ssl.SSLContext
import javax.net.ssl.SSLSession
import javax.net.ssl.TrustManager
import javax.net.ssl.X509TrustManager
class ApexRestClient {
   private HttpURLConnection connection
   private apexUrl
   private def proxyHost
   private def proxyPort
   private def user
   private def pwd
   private def domain
   private def ignoreSSLCertsErrors
    public ApexRestClient(apexServerUrl,httpProxyHost, httpProxyPort,
identityDomain,username, password, ignoreSSLCertificationPathErrors) {
        apexUrl=apexServerUrl
        proxyHost=httpProxyHost
        proxyPort=httpProxyPort
        domain=identityDomain
        user=username
        pwd=password
        ignoreSSLCertsErrors=ignoreSSLCertificationPathErrors
    }
```



```
def setProxyParams() {
        Properties systemProperties = System.getProperties()
        systemProperties.setProperty("http.proxyHost",proxyHost)
        systemProperties.setProperty("http.proxyPort",proxyPort)
        systemProperties.setProperty("https.proxyHost",proxyHost)
        systemProperties.setProperty("https.proxyPort",proxyPort)
    }
    def setSSLParams() {
        if (ignoreSSLCertsErrors !=null &&
ignoreSSLCertsErrors.toUpperCase() == "TRUE") {
            println "Ignoring SSL certification path errors"
            // Disable SSL cert validation
            def hostnameVerifier = [
                verify: { hostname, session -> true }
            1
            def trustManager = [
                    checkServerTrusted: { chain, authType -> },
                    checkClientTrusted: { chain, authType -> },
                    getAcceptedIssuers: { null }
            1
            HttpsURLConnection.setDefaultHostnameVerifier(hostnameVerifier as
HostnameVerifier)
HttpsURLConnection.setDefaultSSLSocketFactory(context.getSocketFactory())
```

```
SSLContext context = SSLContext.getInstance("SSL")
            context.init(null, [trustManager as X509TrustManager] as
TrustManager[], null)
        }
    ł
    def openConnection(restUrl,method,contentType, body) {
        println "Opening connection to apex $restUrl with method:$method"
        int statusCode
        setProxyParams()
        setSSLParams()
        URL newUrl
        newUrl=new URL(restUrl)
        connection = (HttpURLConnection) newUrl.openConnection()
        connection.setDoOutput(true)
        connection.setDoInput(true)
        connection.setUseCaches(false)
```

```
if (method=="")
```



```
connection.setRequestMethod("GET")
        else
            connection.setRequestMethod(method)
        if (contentType.toUpperCase() == "FORM") {
            connection.setRequestProperty("Content-Type", "application/x-www-
form-urlencoded")
        }
        if (contentType.toUpperCase() == "JSON") {
            connection.setRequestProperty("Content-Type", "application/json")
        }
        if (contentType.toUpperCase() == "") {
            // add no content type
        }
        String userCredentials = domain +"."+user + ":" + pwd
        String basicAuth = "Basic " +
javax.xml.bind.DatatypeConverter.printBase64Binary(userCredentials.getBytes())
        connection.setRequestProperty("Authorization", basicAuth)
        if (body!=null && body!="") {
            DataOutputStream wr = new DataOutputStream
(connection.getOutputStream ());
            wr.writeBytes (body);
            wr.flush ();
            wr.close ();
        }
        String response=""
        try {
            statusCode = connection.responseCode
            println "Connection status code: $statusCode "
            if (statusCode==401 || statusCode==403) {
                println "Not authorized"
            ł
            if (statusCode==200) {
                println "Authentication succeeded"
                println "Server response:"
                println "----"
                response=displayServerResponse(connection)
                println "-----"
            }
            if (statusCode==400 || statusCode==500) {
                println "Bad request"
                println "Server response:"
                println "-----"
                response=displayServerResponse(connection)
                println "-----"
            }
        } catch (Exception e) {
            println "Error connecting to the URL"
            println e.getMessage()
        } finally {
            if (connection != null) {
```

```
connection.disconnect();
            }
        }
        return response
    }
    def displayServerResponse(connection) {
        InputStream is;
        if (connection.getResponseCode()==200) {
            is=connection.getInputStream();
        } else {
            is=connection.getErrorStream();
        }
        println "Response Content-Type:"+connection.getContentType()
        BufferedReader br = new BufferedReader(new InputStreamReader(is));
        StringBuilder sb = new StringBuilder();
        String line;
        while ((line = br.readLine()) != null) {
            sb.append(line+"\n");
        }
        br.close();
        println sb
        return sb.toString()
    }
    def launchProcUsingGET(apexUri) {
        println "**Launching PL/SQL in apex**"
        def restUrl=apexUrl+"/"+apexUri
        /*
         * Procedure in apex is defined this way
         * RESTful Service Module: bics/
           URI Template: plsql/
           Method: GET
            Source Type: PL/SQL
            Requires Secure Access: YES
            Source:
                DECLARE
                    prevdeptno number;
                    deptloc
                                varchar2(30);
                    deptname
                                 varchar2(30);
                    CURSOR getemps IS select * from emp
                                        where ((select job from emp where
ename = :empname) IN ('PRESIDENT', 'MANAGER'))
                                        or deptno = (select deptno from emp
where ename = :empname)
                                         order by deptno, ename;
                BEGIN
                    sys.htp.htmlopen;
                    sys.htp.headopen;
                    sys.htp.title('Departments');
                    sys.htp.headclose;
                    sys.htp.bodyopen;
```

```
for emprecs in getemps
                   loop
                        if emprecs.deptno != prevdeptno or prevdeptno is null
then
                              select dname, loc into deptname, deptloc
                            from dept where deptno = (select deptno from emp
where ename = emprecs.ename);
                          if prevdeptno is not null then
                             sys.htp.print('');
                         end if;
                          sys.htp.print('Department ' || deptname || '
located in ' || deptloc || '');
                         sys.htp.print('');
           end if;
           sys.htp.print('');
           prevdeptno := emprecs.deptno;
           end loop;
            sys.htp.print('');
           sys.htp.bodyclose;
           sys.htp.htmlclose;
       END;
           URL call will be in the form: https://
<SERVER>.oraclecloudapps.com/apex/bics/plsql/
           Response will be in following format for this specific plsql
example
           Response Content-Type:text/html; charset=UTF-8
           <HTML>
            <HEAD>
            <TITLE>Departments</TITLE>
           </HEAD>
           <BODY>
            </BODY>
            </HTML>
        */
       def response
       response=openConnection(restUrl, "GET", "FORM", "")
       println "****"
       println "****"
    }
    def launchSQLQueryUsingGETAndVariableOnUrl(apexUri, parameter) {
       println "**Launching Sql query in apex**"
        /*
         * Procedure in apex is defined this way
         * RESTful Service Module: bics/
           URI Template: test/{ID}
           Method: GET
           Source Type: Query
           Format: JSON
           Requires Secure Access: YES
```

```
Source: select
EMPNO, ENAME, JOB, MGR, HIREDATE, SAL, COMM, DEPTNO
                         from EMP where EMPNO = :ID
            URL call will be in the form: https://
<SERVER>.oraclecloudapps.com/apex/bics/test/7839
            Response will be in following format:
            Response Content-Type:application/json
                 {"next":{"$ref":"https://<SERVER>.oraclecloudapps.com/apex/
bics/test/7839?page=1"},"items":
[{"empno":7839,"ename":"KING","job":"PRESIDENT","hiredate":"1981-11-17T00:00:0
OZ", "sal":5000, "deptno":10}] 
         *
         */
        def restUrl=apexUrl+"/"+apexUri+"/"+parameter
        def response
        response=openConnection(restUrl, "GET", "FORM", "")
        println "****"
    }
}
```

Groovy Sample — APEXAutomationParameters.groovy

```
package com.oracle.ceal
import java.io.File;
import java.util.Properties;
class APEXAutomationParameters {
   private Properties props = new Properties()
   def apexRestUrl
   def APEX REST URL='apexRestUrl'
    def identityDomain
    def APEX IDENTITY DOMAIN='apexIdentityDomain'
   def username
    def APEX USERNAME='apexUsername'
    def password
    def APEX PASSWORD='apexPassword'
   def proxyHost
    def PROXY HOST='proxyHost'
    def proxyPort
    def PROXY PORT='proxyPort'
    def ignoreSSLCertificationPathErrors
    def IGNORE CERT PATH ERRORS='ignoreSSLCertificationPathErrors'
    public APEXAutomationParameters(propertiesFile) {
        def propsFileName=propertiesFile
        File propsFile = new File(propsFileName)
        try {
            props.load(propsFile.newDataInputStream())
        } catch ( FileNotFoundException fnfe) {
```

```
println "$propsFileName APEX properties file not found in the
current directory. Exiting."
           System.exit(1);
        }
        apexRestUrl=props.getProperty(APEX REST URL)
        identityDomain=props.getProperty(APEX IDENTITY DOMAIN)
        username=props.getProperty(APEX USERNAME)
        password=props.getProperty(APEX PASSWORD)
        proxyHost=props.getProperty(PROXY HOST)
        proxyPort=props.getProperty(PROXY PORT)
ignoreSSLCertificationPathErrors=props.getProperty(IGNORE CERT PATH ERRORS)
    }
    def isConfigValid() {
        try {
            // Required parameters check
            assert apexRestUrl != '' : "$APEX REST URL is empty"
            assert identityDomain != '' : "$APEX IDENTITY DOMAIN is empty"
            assert username != '' : "$APEX USERNAME is empty"
            assert password != '' : "$APEX PASSWORD is empty"
            // validate url is correct
            URL apexUrl=new URL(apexRestUrl)
            // connection test
            // ssl check
            println "$APEX REST URL = $apexRestUrl"
            println "$APEX IDENTITY DOMAIN = $identityDomain"
            println "$APEX USERNAME = $username"
           println "$APEX PASSWORD = *****"
        } catch(AssertionError e) {
           println e.getMessage()
            return false
        } catch (MalformedURLException e) {
           println "APEX Rest url is incorrect. Current value: $apexRestUrl ,
expected format http|https://"
            println e.getMessage()
           return false
        }
       return true
    }
}
```

Groovy Sample — BICSAutomationParameters.groovy

```
package com.oracle.ceal
import java.io.File;
import java.util.Properties;
```

```
class BICSAutomationParameters {
   private Properties props = new Properties()
    def bicsRestUrl
    def BICS REST URL='bicsRestUrl'
    def identityDomain
    def BICS IDENTITY DOMAIN='bicsIdentityDomain'
    def username
    def BICS USERNAME='bicsUsername'
    def password
    def BICS PASSWORD='bicsPassword'
    def proxyHost
    def PROXY HOST='proxyHost'
    def proxyPort
    def PROXY PORT='proxyPort'
    def ignoreSSLCertificationPathErrors
    def IGNORE CERT PATH ERRORS='ignoreSSLCertificationPathErrors'
    public BICSAutomationParameters(propertiesFile) {
        def propsFileName=propertiesFile
        File propsFile = new File(propsFileName)
        trv {
           props.load(propsFile.newDataInputStream())
        } catch ( FileNotFoundException fnfe) {
            println "$propsFileName BICS properties file not found in the
current directory. Exiting."
           System.exit(1);
        }
        bicsRestUrl=props.getProperty(BICS REST URL)
        identityDomain=props.getProperty(BICS IDENTITY DOMAIN)
        username=props.getProperty(BICS USERNAME)
        password=props.getProperty(BICS PASSWORD)
        proxyHost=props.getProperty(PROXY HOST)
        proxyPort=props.getProperty(PROXY PORT)
ignoreSSLCertificationPathErrors=props.getProperty(IGNORE CERT PATH ERRORS)
    }
    def isConfigValid() {
        try {
            // Required parameters check
            assert bicsRestUrl != '' : "$BICS_REST_URL is empty"
            assert identityDomain != '' : "$BICS IDENTITY DOMAIN is empty"
            assert username != '' : "$BICS USERNAME is empty"
            assert password != '' : "$BICS PASSWORD is empty"
            // validate url is correct
            URL bicsUrl=new URL(bicsRestUrl)
            // connection test
```

// ssl check



```
println "$BICS_REST_URL = $bicsRestUrl"
println "$BICS_IDENTITY_DOMAIN = $identityDomain"
println "$BICS_USERNAME = $username"
println "$BICS_PASSWORD = *****"
} catch(AssertionError e) {
    println e.getMessage()
    return false
} catch (MalformedURLException e) {
    println "BICS Rest url is incorrect. Current value:$bicsRestUrl ,
expected format http|https://"
    println e.getMessage()
    return false
}
return true
}
```

}

Groovy Sample — PBCSAutomationParameters.groovy

```
package com.oracle.ceal
class PBCSAutomationParameters {
   private Properties props = new Properties()
   def planningRestUrl
    def PBCS PLANNING REST URL='pbcsPlanningRestUrl'
    def interopRestUrl
    def PBCS INTEROP REST URL='pbcsInteropRestUrl'
    def identityDomain
    def PBCS IDENTITY DOMAIN='pbcsIdentityDomain'
    def username
    def PBCS USERNAME='pbcsUsername'
   def password
   def PBCS PASSWORD='pbcsPassword'
    def proxyHost
    def PROXY HOST='proxyHost'
    def proxyPort
    def PROXY PORT='proxyPort'
    def ignoreSSLCertificationPathErrors
    def IGNORE CERT PATH ERRORS='ignoreSSLCertificationPathErrors'
    public PBCSAutomationParameters(propertiesFile) {
        def propsFileName=propertiesFile
        File propsFile = new File(propsFileName)
        try {
            props.load(propsFile.newDataInputStream())
        } catch ( FileNotFoundException fnfe) {
            println "$propsFileName PBCS properties file not found in the
current directory. Exiting."
           System.exit(1);
        }
```

```
planningRestUrl=props.getProperty(PBCS PLANNING REST URL)
        interopRestUrl=props.getProperty(PBCS INTEROP REST URL)
        identityDomain=props.getProperty(PBCS IDENTITY DOMAIN)
       username=props.getProperty(PBCS USERNAME)
       password=props.getProperty(PBCS PASSWORD)
       proxyHost=props.getProperty(PROXY HOST)
       proxyPort=props.getProperty(PROXY PORT)
ignoreSSLCertificationPathErrors=props.getProperty(IGNORE CERT PATH ERRORS)
    }
    def isConfigValid() {
       try {
            // Required parameters check
            assert planningRestUrl != '' : "$PBCS_PLANNING_REST_URL is empty"
            assert interopRestUrl != '' : "$PBCS INTEROP REST URL is empty"
            assert identityDomain != '' : "$PBCS IDENTITY DOMAIN is empty"
            assert username != '' : "$PBCS USERNAME is empty"
            assert password != '' : "$PBCS PASSWORD is empty"
            // validate url is correct
            URL planningUrl=new URL(planningRestUrl)
            URL interopUrl=new URL(interopRestUrl)
            // connection test
            // ssl check
            println "$PBCS PLANNING REST URL = $planningRestUrl"
            println "$PBCS INTEROP REST URL = $interopRestUrl"
            println "$PBCS IDENTITY DOMAIN = $identityDomain"
            println "$PBCS USERNAME = $username"
            println "$PBCS PASSWORD = *****"
        } catch(AssertionError e) {
           println e.getMessage()
            return false
        } catch (MalformedURLException e) {
            println "PBCS Rest urls are incorrect. Current
value: $planningRestUrl and $interopRestUrl, expected format http/https://
<SERVER>/HyperionPlanning/rest/11.1.2.3.xyz http|https://<SERVER>/interop/
rest/11.1.2.3.xyz"
           println e.getMessage()
            return false
        }
       return true
    }
}
```

Troubleshooting the Integration

Use an HTTP proxy such as Fiddler to trace HTTP calls

- In this case, set proxyHost / proxyPort to localhost 8888 in your properties file defining the configuration
- Also set ignoreSSLCertificationPathErrors=true

