

AperTO - Archivio Istituzionale Open Access dell'Università di Torino

## Energy and economic evaluation of a poplar plantation for woodchips production in Italy

### **This is the author's manuscript**

*Original Citation:*

*Availability:*

This version is available <http://hdl.handle.net/2318/1616696> since 2016-11-25T14:54:24Z

*Published version:*

DOI:10.1016/j.biombioe.2013.11.012

*Terms of use:*

Open Access

Anyone can freely access the full text of works made available as "Open Access". Works made available under a Creative Commons license can be used according to the terms and conditions of said license. Use of all other works requires consent of the right holder (author or publisher) if not exempted from copyright protection by the applicable law.

(Article begins on next page)



## 27 **Introduction**

28 The cultivation of crops for biomass production on good, arable soils allows to increase the  
29 energy production, with many advantages from the environmental point of view. This solution  
30 increases the farmers' revenues and leads to advantages for the environment [1,2,3,4,5].

31 In the last 10 years, the cultivation of crops for biomass production has been inserted in the  
32 cultural plans of several farms, particularly in Northern Italy; farmers take advantage of their  
33 low input requirement and the added possibility of exploiting set-aside areas [6]. In Italy,  
34 there are two different methods of cultivation: very Short Rotation Coppice (vSRC), with very  
35 high density, from 5,500 to 14,000 plants ha<sup>-1</sup> and harvested with a rotation period of 1-4  
36 years and Short Rotation Coppice (SRC) with a high density from 1,000 to 2,000 plants ha<sup>-1</sup>  
37 and harvested with a rotation of 5-7 years [7,8]. In Europe, the farmers prefer the vSRC  
38 cultivation model [9,10,11,12,13], while in Italy, recently, the farmers prefer the previously  
39 described SRC method, because the most recent poplar hybrids have enhanced productivity  
40 and improved the biomass quality (high calorific value), as a result of a better wood/bark ratio  
41 [14,15,16,17]. Furthermore, it is also preferred, because in the rural development plans of the  
42 main Regions of northern Italy, the establishment of this cultural model is financed.

43 Most of the studies carried out until now in Italy have focused only on the vSRC method, as  
44 they are more spread throughout the territory; little has been yet experienced on the SRC  
45 method [18,19].

46 In order to evaluate from the energy and economic point of view a poplar SRC in the river Po  
47 Valley an *ad hoc* study was made and a specific model has been developed.

48

## 49 **Materials and methods**

50 A series of data were collected, both in the nursery and in the poplar SRC plantation, nearby  
51 the experimental farm "MEZZI" of CRA-PLF, close to Casale Monferrato (AL), during 2006-  
52 2012 period. All the cultural operations for poplar plantation were analysed: the working time

53 and both machines and manpower requirements were recorded on the field, in compliance  
54 with CIOSTA (Comité International d'Organisation Scientifique du Travail en Agriculture)  
55 methodology, on at least 5.000 m<sup>2</sup> surface areas and for periods not shorter than 2 hours [20].  
56 The developed model allowed the determination of manpower and energy requirements, as  
57 well as the costs analysis considering different crop density and biomass production. The  
58 model considers a continuous poplar SRC plantation: the whole acreage is divided into  
59 different “modules”, each corresponding to 1 year of the crop cycle, allowing to refer all costs  
60 to annuity. Regarding the economic and energetic evaluation, a 6 years rotation, with  
61 harvesting carried out at the end of the cycle and with a starting poplar plants density of 1100  
62 for hectare was considered, with a 3.00 × 3.00 m spacing and a mean production of 15 Mg ha<sup>-1</sup>  
63 <sup>1</sup>D.M. year<sup>-1</sup> [21,22]. For all post-emergency treatment, it was supposed to use traditional  
64 tractors with 4 RM, with a maximum width of 2.2 m. In detail, for the nursery and the poplar  
65 SRC plantation it was assumed to prepare the soil with ploughing at 40 cm depth after seed  
66 bed fertilization – 500 kg ha<sup>-1</sup> of 8.24.24 (N,P,K).  
67 Secondary tillage was carried out by two harrowing interventions, while for the plantations of  
68 rods (1.20-2.00 m in length), an Allasia V1 planter was considered [23]. The cultural  
69 operations assumed for the SRC cultivation and nursery were fertilization and weed control,  
70 both necessary to allow a high production of biomass [24,25]. Finally, it was assumed to use a  
71 heavy cultivator for stumps removal (table 1-2).  
72 For biomass harvesting, a chipper prototype Gandini Bio-harvester (purchase cost € 60,000)  
73 was used, with a tractor of 190 kW Case Magnum 260 EP (purchase cost € 170,000). The  
74 working capacity of the Gandini Bio-harvester is about 60 t h<sup>-1</sup> (about 120 plants h<sup>-1</sup>)[26]. For  
75 the transport of the biomass in the farm (about 400 meters distant), two tractors with trailers  
76 were used. The average cost of the Gandini Bio-harvester was determined considering  
77 contractors costs.

78

79 The manpower requirement was determined considering the number of operators and the  
80 working time to carry out every cultural operation.

81

82 The energy consumption were determined considering both direct costs – fuel and lubricant  
83 consumption - and primary energy – machine, equipment and mineral fertilizer energy  
84 contents (table 3) [27]. Machine fuel consumption was determined by refilling the machine  
85 tank at the end of each working phase. The tank was refilled using a 2000 cm<sup>3</sup> glass pipe with  
86 20 cm<sup>3</sup> graduations, corresponding to the accuracy of our measurements.

87 The lubricant consumption was determined in function of the fuel consumption using a  
88 specific algorithm setup by Piccarolo [28].

89 The human work was expressed in manpower hour requirement, for every cultural operation,  
90 but it was not considered from the energy point of view.

91

92 The economic evaluation was determined for every cultural operation considering both the  
93 machine cost and that of the production factors (fertilizers, plant protection products)  
94 (table 4).

95 The hourly cost rate of each machine was evaluated using the method proposed by Miyata  
96 [29], with prices updated to 2013. An annual utilization of at least 500 hours (tractor used also  
97 for other operations) was assumed for tractors, and the power requirement was calculated by  
98 taking into consideration the data recorded during experimentation and the drawbar pull and  
99 power requirement, in the different operating conditions. Labor cost was set to 18.5 € hour<sup>1</sup>.  
100 Fuel cost was assumed to be 0.9 € kg (subsidized fuel for agricultural use). Also the tractor  
101 hourly cost was determined with the methodology proposed by Miyata [29].

102 For the evaluation of economic sustainability it was determined the Net Present Value (NPV)  
103 that indicates the difference between the total income and the total costs determined

104 considering a biomass value of 100 € Mg<sup>-1</sup>D.M. This determination was done for different  
105 costs of land and water use [30].

106

## 107 **Results**

108 Near 27 hours per year<sup>-1</sup> of manpower were required for the cultivation of one SRC hectare.  
109 The biomass harvesting required less than 45% of the total time, while the pesticides  
110 application required more than 9% (Fig. 1).

111

112 The energy consumption for the cultivation and management of 100 ha of poplar irrigated  
113 SRF is of 15.2 GJ ha<sup>-1</sup> per year and represents about the 5% of the biomass energy production  
114 (about 270 GJ ha<sup>-1</sup> for year). The input/output ratio is close to 18. The largest part of energetic  
115 input (44%) is linked to cultural operations, in particular at the top dressing (36% of the total  
116 energy requirement). Harvesting and biomass transport to the farm storage represents about  
117 25% of the total energy requirements; the flood irrigation does not require any energy input  
118 (Fig. 2).

119 In conclusion, for arable surfaces between 50 and 200 ha, the total energy cost resulted  
120 between 4.9 and 5.2% of the energy produced.

121 In the total balance, the direct energy cost results to be 1.9% and the indirect energy cost the  
122 3.0%, for a 50 ha SRC cultivation and 3.2% for a 200 ha SRC cultivation.

123

124 The production cost of the SRC with 6 year cycle resulted closely connected to both the  
125 cultivated surfaces and to the production level. Considering a biomass production of  
126 90 Mg ha<sup>-1</sup> D.M. per cycle, equivalent to about 180 Mg ha<sup>-1</sup> W.B., the production cost is close  
127 to 122 € Mg<sup>-1</sup> D.M. for SRC surfaces of 100 ha (Fig. 3), a value higher than the market price  
128 of wood chips (95 € Mg<sup>-1</sup> D.M.) .

129 The cultural operations that have the higher weight on the total production costs are the “crop  
130 management operations” (near 26,9%) (Fig. 4). The most expensive are the interrow  
131 cultivations (weed control) for post-emergence treatment and the irrigation intervention; but  
132 these operations are indispensable to get a high biomass production. Besides, land use costs  
133 showed also a high incidence on the total costs. For example, considering a 100 ha SRF  
134 surface, with  $15 \text{ ha}^{-1}\text{year}^{-1}$  D.M. biomass production, for every cycle and zero cost for  
135 irrigation, the biomass cost production is  $113 \text{ € Mg}^{-1}$  D.M., with land use cost of  $200 \text{ € ha}^{-1}\text{year}^{-1}$ .  
136 In the case of a land use cost of  $400 \text{ € ha}^{-1}\text{year}^{-1}$  the biomass production cost is of  
137  $126 \text{ € Mg}^{-1}$  D.M. The land rent cost weights upon total production cost for the 11 and 21%  
138 respectively. Considering zero the cost rate of land, the biomass production cost fluctuates  
139 from  $103 \text{ € Mg}^{-1}$  D.M. to  $119 \text{ € Mg}^{-1}$  D.M. with 50 and  $300 \text{ € ha}^{-1}$  irrigation costs respectively  
140 (Fig 5-6).

141 Nevertheless, it has to be considered the influence of the transport and storage costs in terms  
142 of biomass losses on the total biomass production cost. The transport cost weights upon total  
143 cost for the 2 and 15% for distances of 5 and 50 km respectively (Fig. 7).

144

## 145 **Discussion**

146 The poplar SRC plantation, in the considered condition, - 6 years rotations, with harvesting  
147 carried out at the end of the cycle and a production of  $15 \text{ Mg ha}^{-1}\text{D.M. year}^{-1}$ , - is very  
148 interesting under the energy point of view, since the output/input ratio results to be higher  
149 than 18.

150 This value is 5 points higher than that calculated for a vSRC by Manzone et al [17]. The better  
151 results are to be attributed at the minor energy consumption for SRC planting, because the  
152 rods preparation is less expensive compared to cuttings production and the SRC starting  
153 investment ( $1,700 \text{ plants ha}^{-1}$ ) is minor to vSRC plantation ( $6,700 \text{ plants ha}^{-1}$ ).

154 Furthermore, the use of rods in SRC planting reduces also the energy consumption for the  
155 weed control, because the shoots are placed at a height (50 – 120 cm) greater than that of the  
156 cuttings and they can better compete with the weeds.

157  
158 The largest part of energy input (44%) is linked to cultural operations, in particular at the top  
159 dressing (36.8% of the total energy requirement) necessary to have a high biomass production  
160 ( $15 \text{ Mg ha}^{-1} \text{ D.M. year}^{-1}$ ) [31] as well as to choose the most appropriate clone for the site [11].

161  
162 In the total balance, the energy input per unit biomass produced is 4.1% of the energy output.  
163 This value is similar to that found in another analysis made in Sweden on willow SRC [32].

164  
165 The SRC economic evaluation, differently from energy point of view, is negative because the  
166 market price of the woodchip is low respect to value of production. In fact, in order to get  
167 economic SRC sustainability, the biomass price shall be at least  $115 \text{ € Mg}^{-1} \text{ D.M.}$  ( $\text{€ } 15$  more  
168 than to currently market price).

169 But with this model, in 6 years trees with a diameter at breast height of 150-200 mm are  
170 grown. So the basal part of the trunk, up to 4-6 m, can be used to produce industrial wood  
171 (OSB panel, packaging) with a value higher than the one of wood chips for energy. In this  
172 case the economic balance become positive [33].

173 Since the tree have not a small diameter ( $> 150 \text{ mm}$ ), this biomass plantations  
174 offer woodchips of high quality, with high fibres content (85–90%) and favourable particle-  
175 size distribution. On the contrary, vSRC presented a high bark content ( $>20\%$ ) and  
176 occasionally a mediocre particle-size distribution, being often too rich in fines ( $>10\%$ ). These  
177 problems were especially serious with fuel derived from 1-year old vSRC sprouts [18].

178 A material with high bark content have a low market price because showed a low lower  
179 heating value and a high ash content [34,35,36]



180

181 Besides, it is to highlight that the rods planting is a difficult operation management due to the  
182 reduced available time (march and april) and because the planters used have a low working  
183 rate and required a high manpower [23].

184

## 185 **Conclusions**

186 A large SRF plantation diffusion will be possible only with an increase of the biomass market  
187 value or with economic support for the production.

188 At present, Italian farmer prefer the SRC cultivation model respect to that vSRC cultivation  
189 model because from tree with 6 years of age is possible to obtain wood assortment of high  
190 economic value to sell to sawmills (packaging) or for OSB panel production.

191 It is to underline that SRC cultivation can contribute to solve the problem of the exceeding  
192 traditional cultivations and that it is able to improve the relations between agriculture and  
193 environment. It's getting more important to find low environmental impact cultural solutions  
194 able to maximize the biomass yield by using the poplar auxometric curve.

195

## 196 **References**

197 [1] Bonari E, Villari R. Le biomasse agricole e forestali nello scenario energetico nazionale.

198 Convegno di studio, progetto fuoco 2004, 18-19 marzo – Verona, Italy

199 [2] Bruzzi I, Petrini C, Malagoli C. Colture agricole alternative per la produzione di elettricità.

200 L'informatore Agrario 1996; 2: 39-45.

201 [3] Paine LK, Peterson TL, Undersander DJ, Rineer KC, Bartelt GA, Temple SA Sample

202 DW, Klemme RM. Some ecological and socio-economic considerations for biomass  
203 energy crop production. Biomass BIOENERG 1996; 10: 231-242

204 [4] Pinazzi P. L'utilizzo energetico del pioppo e del legno in generale. Convegno: la

205 pioppicoltura nella filiera legno-prospettive e azioni di rilancio, 2005; 23 giugno – Casale

206 Monferrato (AL).

207 [5] Rosch C, Kaltschmitt M. Energy from biomass – do non-technical barrier prevent an  
208 increased use? *Biomass BIOENERG* 1999; 16: 347-356.

209 [6] Di Muzio Pasta V, Negri M, Facciotto G, Bergante S, Maggiore TM. Growth dynamic and  
210 biomass production of 12 poplar and two willow clones in a short rotation coppice in  
211 northern Italy. In: 15° European biomass conference & exhibition, from research to  
212 market deployment. Proceedings of the international conference held in Berlin, Germany;  
213 2007. P. 749-754

214 [7] Bergante S, Facciotto G. Impianti annuali, biennali, quinquennali. *SHERWOOD – Foreste  
215 ed Alberi Oggi* 2006; 128 (11): 25-36

216 [8] Facciotto G., Nervo G., Vietto L. Biomass production with fast growing woody plants for  
217 energy purposes in Italy. ASO Funded Project Workshop 'Increased biomass production  
218 with fast-growing tree species in short rotation forestry: impact of species and clone  
219 selection and socio-economic impacts'. Bulgaria, 17-21 November 2008. pp 10

220 [9] Armstrong A, Johns C, Tubby I. Effect of spacing and cutting cycle on the yield of poplar  
221 grown as an energy crop. *Biomass BIOENERG* 1999; 17 (4): 305-314

222 [10] Kauter D, Lewandowski I, Claupein W. Quantity and quality of harvestable biomass  
223 from *Populus* short rotation coppice for solid fuel use a review on the physiological basis  
224 and management influences. *Biomass BIOENERG* 2003; 24 (6): 411-427

225 [11] Laureysens I, Deraedt W, Inderherberge T, Ceulemans R. Population dynamics in a six-  
226 year old coppice culture of poplar. I. Clonal differences in stool mortality, shoot  
227 dynamics and shoot diameter distribution in relation biomass production. *Biomass  
228 BIOENERG* 2003; 24 (2): 81-95

229 [12] Mitchell CP, Stevens EA, Watters MP. Short Rotation Forestry operations, productivity  
230 and cost based on experience gained in the UK. *Forest ecology and management* 1999;  
231 121 (1-2): 123-136

- 232 [13] Proe MF, Griffiths JH, Craig J. Effects of spacing, species and copping on leaf area, light  
233 interception and photosynthesis in short rotation forestry. Biomass BIOENERG 2002; 23  
234 (5): 315-326
- 235 [14] Paris p, Facciotto G, Nervo G, Minotta G, Sabatti M, Scaravonati A, et al. Short rotation  
236 forestry of poplars in Italy: current situation and prospective. In: Book of abstract of fifth  
237 international poplar symposium, poplars and willow: from research models to  
238 multipurpose trees for a bio-based society held in Orvieto, Italy; 2010. P. 105-6
- 239 [15] Benomar L, Des Rocher A, Larocque Gr. The effect of spacing on growth, morphology  
240 and biomass production and allocation in two hybrid poplar clones growing in the boreal  
241 region of Canada. Trees: Struct Funct 2012; 26 (3): 939-49
- 242 [16] Phelps JE, Isebrands JG, Jowett D. Raw material quality of short rotation intensively  
243 cultured Populus clones. I. A comparison of stem and branch properties at three spacing.  
244 IAWA Bulletin n.s; 1982. P.193-200.
- 245 [17] Manzone M, Airoidi G, Balsari P. Energetic and economic evaluation of a poplar  
246 cultivation for the biomass production in Italy. Biomass BIOENERG 2009; 33:1258-64
- 247 [18] Spinelli R, Nati C, Sozzi L, Magagnotti N, Picchi G. Physical characterization of  
248 commercial woodchips on the Italian energy market. Fuel 2011; 90 (6): 2198-2202
- 249 [19] Spinelli R., Schweier J., De Francesco F. 2012 Harvesting techniques for non-industrial  
250 biomass plantations. Biosystems Engineering 113: 319-324.
- 251 [20] Bolli P, Scotton M. Lineamenti di tecnica della meccanizzazione agricola, Edizioni  
252 Agricole: Bologna, Italy; 1987.
- 253 [21] Facciotto G, Bergante S, Lioia C, Mughini G, Rosso L, Nervo G. Come scegliere e  
254 coltivare le colture da biomassa, Supplemento Forlener L'informatore Agrario 2005;  
255 34:27-30
- 256 [22] Rosso L, Facciotto G, Bergante S, Vietto L, Nervo G. Selection and testing of *populus*  
257 *alba* and *Salix spp.* as bioenergy feedstock: preliminary results. Applied Energy 2013;

258 102:87-92

259 [23] Balsari P, Facciotto G, Manzone M. - Trapiantatrici a confronto per cedui a breve  
260 rotazione. Supplemento a Informatore Agrario 2007; 33:11-15

261 [24] Buhler DD, Netzer DA, Riemenschneider DE, Hartzler RG. Weed management in short  
262 rotation poplar and herbaceous perennial crops grown for biofuel production. Biomass  
263 BIOENERG 1998;14: 385-394

264 [25] Friedrich E. Produktionbedingungen fuer die bewirtschaftung schnellwachsender  
265 baumarten im stockausschlagtrieb in kurzen umtriebszeiten auf landwirtschaftlichen  
266 flaechen, statusseminar schnellwachsende baumarten-tagungsband 23-24 oktober 1995  
267 Kassel Fachagentur Nachwachsende Rohstoffe e.V. Guelzow: 101

268 [26] Manzone M. The mechanization of Short Rotation Forestry for biomass production to  
269 energy use. Phd thesis., University of Torino, 2009; 335 pp.

270 [27] Jarach M. Sui valori di equivalenza per l'analisi ed il bilancio energetico in agricoltura.  
271 Riv. di Ing. Agraria, 1985; 2: 02-114.

272 [28] Piccarolo P. Criteri di scelta e di gestione delle macchine agricole. Macchine e Motori  
273 Agricoli 1989; 12: 37-57.

274 [29] Miyata E.S. 1980. Determining fixed and operating costs of logging equipment. General  
275 Technical Report NC-55. Forest Service North Central Forest Experiment Station, St.  
276 Paul, MN. 14 pp.

277 [30] Povellato A. Prospettive incerte per il mercato degli affitti. L'informatore Agrario 1997;  
278 44: 27.30

279 [31] Dimitriou I, Rosenqvist H. Sewage sludge and wastewater fertilisation od short Rotation  
280 Coppice (SRC) for increased bioenergy production – Biological and economic potential.  
281 Biomass BIOENERG 2011; 35: 835-842

- 282 [32] Borjesson PII. Energy analysis of biomass production and transportation. *Biomass &*  
283 *Bioenergy* 1996; 11 (4): 305-318
- 284 [33] Coaloa D, Nervo G., Scotti A. Multi-purpose poplar plantations in Italy. In: *Improving*  
285 *Lives with Poplars and Willows. Abstracts of submitted papers. 24th Session of the*  
286 *International Poplar Commission, Dehradun, India, 30 October-2 November 2012.*  
287 *Working Paper IPC/11 FAO, Rome, Italy. p. 74*
- 288 [34] Klasnja B, Kopitovic S, Orlovic S. Wood and bark of some poplar and willow clones as  
289 fuelwood. *Biomass BIOENERG* 2002; 23 (6): 427–432
- 290 [35] García R, Pizarro C, Lavín AG, Bueno JL. Characterization of Spanish biomass wastes  
291 for energy use *Bioresource Technology* 2012; 103: 249–258
- 292 [36] Guidi W, Piccioni E, Ginanni M, Bonari E. Bark content estimation in poplar (*populus*  
293 *deltoides* L.) short rotation coppice in Central Italy. *Biomass BIOENERG* 2008; 32: 518-  
294 524